

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250285649

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Panchaksharaiah; Vishwas Sharadanagar

METHODS AND SYSTEMS FOR ENHANCING USER-GENERATED CONTENT

Abstract

User-generated content is received from multiple user devices, including first content recorded by a first user device during a first time interval and second content recorded by a second user device during a second time interval. If the second time interval immediately precedes, or immediately follows, the first time interval, then at least a portion of the second content may be appended to the first content. For example, if a user ends recording of the first content before an interesting event occurs, then a portion of the second content may be appended to the first content so that the user has a recording including the missed event. The second content may be selected based on a location, and/or a field of view of the second user device during the second time interval being similar to that of the first user device during the first time interval.

Inventors: Panchaksharaiah; Vishwas Sharadanagar (Tiptur, IN)

Applicant: Adeia Guides Inc. (San Jose, CA)

Family ID: 1000008620998

Appl. No.: 19/215712

Filed: May 22, 2025

Related U.S. Application Data

parent US continuation 18389405 20231114 parent-grant-document US 12334112 child US 19215712

parent US continuation 17534683 20211124 parent-grant-document US 11854580 child US 18389405

Publication Classification

Int. Cl.: **G11B27/036** (20060101); **G06F3/04842** (20220101); **G06V20/30** (20220101); **G06V20/40** (20220101); **G06V40/16** (20220101); **G10L25/57** (20130101); **G11B27/02** (20060101); **G11B27/10** (20060101); **H04N5/265** (20060101)

U.S. Cl.:

CPC **G11B27/036** (20130101); **G06V20/30** (20220101); **G06V20/42** (20220101); **G06V20/44** (20220101); **G06V40/161** (20220101); **G10L25/57** (20130101); **G11B27/02** (20130101); **G11B27/10** (20130101); **H04N5/265** (20130101); **G06F3/04842** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This is a continuation application of U.S. patent application Ser. No. 18/389,405, filed Nov. 14, 2023, which is a continuation of U.S. patent application Ser. No. 17/534,683, filed Nov. 24, 2021, now U.S. Pat. No. 11,854,580, the disclosure of which are hereby incorporated by reference herein in their entireties.

FIELD

[0002] The present disclosure is directed to methods and systems that can enhance user-generated content. In particular, the present disclosure includes methods and systems for augmenting content generated using a first user device using additional content generated using another user device.

BACKGROUND

[0003] It has become commonplace for portable user devices to be used for capturing audio and/or video of events and sights. For example, a user may use their smartphone to record a video of their surroundings, to replay in the future and/or make available to others. However, when capturing real-life, unscripted events, a user will not be aware of an imminent event of interest, and might stop a recording in progress just before the event occurs. For example, a user attending a football game in a stadium might record a portion of the game. An event immediately following the recorded portion of the game would not be included in the user's recording. For instance, if the user were to record a portion of the game where the ball is in play close to their location in the stadium, and stop recording as the play moves away from that location, then the user might miss recording a touchdown that occurs shortly after the recording has stopped. In another example, the user might stop recording the game while waiting for play to restart after a touchdown is scored and miss an event such as an entertaining celebration of the touchdown by the scoring team, or a player waving to them from the field during the break in play.

[0004] In a similar manner, the user might be prompted to start recording a portion of the game in response to an occurrence, or start, of an event of interest. Such a recording would necessarily miss at least a part of the event that prompted the user to start recording.

SUMMARY

[0005] According to an aspect, there is provided a method comprising: receiving content recorded by a plurality of user devices, the content including first content recorded by a first one of the user devices during a first time interval and second content recorded by a second one of the user devices during a second time interval; determining a first time point, wherein the first time point is a start time of the first time interval or an end time of the first time interval; determining a location of the first user device during at least a portion of the first time interval; determining that the second time interval includes the first time point; determining a location of the second user device during the second time interval; selecting the second content from the content recorded by the plurality of user devices, based on the determination that the second time interval includes the first time point, and based on the determined location of the second user device; and modifying the first content to

include at least a portion of the second content.

[0006] In this manner, user-generated content from the first user device can be augmented with user-generated content from the second user device immediately preceding, or immediately following the first time interval. Such augmentation effectively extends the first time interval covered by the first content and thus provides a user that has recorded the first content with an enhanced recording.

[0007] For example, a plurality of users may use their smartphones, or other user devices, to capture video at locations such as a stadium, arena, or tourist sightseeing spot. The above method allows a video captured by a first user to be augmented by appending at least a portion of a video captured by a second user to the beginning or end of the first user's video, for example, to provide video of an event that was missed by the first user.

[0008] Alternatively, or additionally, a portion of the first content may be replaced with at least a portion of the second content. For example, an event during the first time interval might not be captured if the event was not visible in a field of view of the first user device. For example, the first user's view of the event might have been obscured by a person or object in a line of sight between the first user and a location of the event. The method may include replacing, or adding, at least a portion of second content captured by a second user, where the second content includes an unobstructed view of the event.

[0009] In some embodiments, the method further comprises detecting an occurrence of an event at a second time point that is not included in the first time interval, and determining that the second content includes a recording of the event. The determination may be based on the second time point, a start time of the second interval, and an end time of the second interval. The determination may be further based on an audio component of the second content and/or a video component of the second content. The detection of the occurrence of the event may include one or more of analyzing an audio component of recorded content including the event, analyzing a video component of recorded content including the event, analyzing keywords in an audio commentary relating to the event, analyzing keywords in social media posts relating to the event, or analyzing keywords in information accessed from a website.

[0010] Optionally, selecting the second content may be further based on a location of the second user device during at least a portion of the second time interval, and/or a field of view of the second user device during at least a portion of the second time interval. The field of view of the second user device may be determined based on one or more of: an orientation of the second user device during at least a portion of the second time interval; an angle of the second user device during at least a portion of the second time interval; an elevation of the second user device during at least a portion of the second time interval; or any permutation of these parameters.

[0011] In some embodiments, the method may include detecting one or more faces in the second content, wherein modifying, using the control circuitry, a video component of said at least a portion of the second content to obscure the detected one or more faces. Such modifications may be used to preserve privacy of people shown in the second content.

[0012] In some embodiments, the second content is selected automatically, based on one or more parameters as discussed above. In other embodiments, the first device may be provided with information associated with recorded content from the plurality of user devices that is determined to include the event, to allow a user of the first device to select the second content. For example, the first device may be provided with images from content recorded by multiple other user devices, to allow the first user to select content recorded by one of the other user devices based, for example, on a viewpoint provided by that content. The second content may then be selected based on input indicating a selection of that content by the first user.

[0013] The method may further comprise determining, based on a video component of the second content, that the event is visible in the second content. For example, object recognition may be performed to determine whether a particular event can be seen in the second content, in order to

avoid selecting second content in which the event is obscured. Optionally, the determination of whether the event is visible in the second content may take into account both the information determined based on the video component and information indicating a field of view of the second user device. The field of view of the second user device may be determined based on one or more of an orientation, angle, or elevation of the second user device during the second time interval. [0014] In some embodiments, receiving the content recorded by the plurality of user devices comprises identifying, from user-generated content uploaded to a cloud service or social networking platform, content recorded at a geographical location corresponding to the event during a predetermined time period. The content recorded at the geographical location during the predetermined time period may then be obtained from the cloud service or social networking platform.

[0015] According to another aspect, there is provided an apparatus configured to perform any of the methods set out in the above aspect. An example of such an apparatus comprises control circuitry, or other means, configured to: receive content recorded by a plurality of user devices, the content including first content recorded by a first one of the user devices during a first time interval and second content recorded by a second one of the user devices during a second time interval; determine a first time point, wherein the first time point is a start time of the first time interval or an end time of the first time interval; determine a location of the first user device during at least a portion of the first time interval; determine that the second time interval includes the first time point; determine a location of the second user device during the second time interval; select the second content from the content recorded by the plurality of user devices, based on the determination that the second time interval includes the first time point, and based on the determined location of the second user device; and modify the first content to include at least a portion of the second content.

[0016] The apparatus may further include a cloud server configured to receive uploads of the recorded content from at least some of the plurality of user devices. Such a cloud server may make such recorded content available for inclusion in the first content. For instance, the at least a portion of the second content may be selected from the uploaded content for inclusion in the modified first content.

[0017] According to yet another aspect, there is provided a computer program that, when executed by control circuitry, causes the control circuitry to perform any of the methods discussed above. For example, there may be provided a non-transitory computer-readable medium, in which is stored computer-readable instructions including: instructions to receive content recorded by a plurality of user devices, the content including first content recorded by a first one of the user devices during a first time interval and second content recorded by a second one of the user devices during a second time interval; instructions to determine a first time point, wherein the first time point is a start time of the first time interval or an end time of the first time interval; instructions to determine a location of the first user device during at least a portion of the first time interval; instructions to determine that the second time interval includes the first time point; instructions to determine a location of the second user device during the second time interval; instructions to select the second content from the content recorded by the plurality of user devices, based on the determination that the second time interval includes the first time point, and based on the determined location of the second user device; and instructions to modify the first content to include at least a portion of the second content.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] The below and other objects and advantages of the disclosure will be apparent upon

consideration of the following detailed description, taken in conjunction with the accompanying drawings, in which like reference characters refer to like parts throughout, and in which:

[0019] FIGS. **1A** and **1B** depict a scenario in which a user device creates content according to an embodiment;

[0020] FIGS. **2A** and **2B** depict the creation of content by other user devices in the scenario shown in FIGS. **1A** and **1B**;

[0021] FIGS. **3A-3D** depict examples of modification of the content created by a user device in accordance with various embodiments;

[0022] FIG. **4** depicts a system according to an embodiment;

[0023] FIG. **5** depicts a server according to an embodiment;

[0024] FIG. **6** depicts a user device that may be included in the system of FIG. **4**;

[0025] FIG. **7** is a flowchart of a method of collecting user-generated content that may be performed by the server of FIG. **5** in accordance with an embodiment;

[0026] FIG. **8** is a flowchart of a method to augment user-generated content performed by the server of FIG. **5** in accordance with an embodiment;

[0027] FIG. **9** depicts a display screen that may be displayed by a user device during performance of the method of FIG. **8**; and

[0028] FIG. **10** is a flowchart of a method that may be included in the method of FIG. **8**.

DETAILED DESCRIPTION

[0029] Methods and systems according to the present disclosure allow content generated using a first user device to be augmented using content generated using a second user device. In the exemplary embodiments set out below, video captured by a first user device is augmented using video captured by a second user device. In other embodiments, such methods and systems may be used to augment content other than captured video, such as audio content or other multimedia content generated or captured by the first user device.

[0030] FIGS. **1A** and **1B** depict a scenario in which a first user **100** is generating content by capturing video using a first user device **102**. In this particular example, the first user device **102** is a smartphone, and the first user **100** is making a video recording **108** of a cricket match from their location **104** within a sports stadium **106**. The recording **108** covers a field of view **110** during a particular time interval **112** between a start time T_s and a finish time T_f , shown in FIG. **1B**. For example, the recording **108** may capture action in the match between T_s and T_f and/or images of other attendees in the stadium **106**, such as friends and family members of the first user **100**, but will not capture events occurring outside the time interval **112**, such as an event occurring at time T_{e1} or T_{e2} .

[0031] At a site such as sports stadium **106**, it is almost inevitable that video will be captured by other attendees. For example, the sports stadium **106** may have a capacity of 50,000 people and is full. If each attendee captures an average of 2 videos each, then 100,000 videos may be captured over the course of the soccer game, so it is likely that another user will have captured video of the event missed by the first user at time T_{e1} or T_{e2} , albeit with different fields of view when compared with the recording **108**, due to differences in the locations of the first user **100** and other users and, potentially, differences in orientation and elevation of the first user device **102** compared with user devices of the other users.

[0032] FIGS. **2A** and **2B** depict examples of other users **200**, **202**, **204** capturing video using respective user devices **206**, **208**, **210**, with respective fields of view **212**, **214**, **216** from locations **218**, **220**, **222** in the vicinity of the location **104** of the first user **100**. Their captured videos may include respective second recordings **224**, **226**, **228** during time intervals **230**, **232**, **234** that at least partially overlap, or even encompass, time interval **112**, as shown in FIG. **2B**. By appending at least a portion of one of the second recordings **224**, **226**, **228** to the first recording **108**, the first user **100** can be provided with an augmented recording that includes one or more of the missed events.

[0033] FIGS. **3A-3D** depict examples of how the first recording **108** can be augmented by

appending some or all of the second recordings **224**, **226**, **228** to the first recording **108**. In the example shown in FIG. 3A, at least a portion **224'** of second recording **224** is prepended to the first recording **108** to provide a modified recording **300** that includes video of the event occurring at time **Te1** captured by the second user device **206**.

[0034] In the example shown in FIG. 3B, at least a portion **226'** of the second recording **226** is appended to the first recording **108** to provide a modified first recording **302** that includes video of the event occurring at time **Te2** captured by the second user device **208**.

[0035] In the example shown in FIG. 3C, a portion **224'** of second recording **224** is prepended to the first recording **108**, and a portion **226'** of the second recording **228** is appended to the first recording **108** to provide a modified first recording **304** that includes the events occurring at times **Te1** and **Te2**.

[0036] In another example, shown in FIG. 3D, a modified first recording **306** that includes both of the events is obtained by prepending and appending portions **228'**, **228''** of the same recording, such as second recording **228** captured by the other second user device **210**, which covers a time interval **234** encompassing the first time interval **112**.

[0037] In some embodiments, a portion of the first recording may even be replaced with at least a portion of a second recording. For example, the modified first recording **306** of FIG. 3D may also include a portion **228'''** of the second recording **228** that was recorded during the first time interval **112**. A portion of the first recording **108** during the first time interval **112** may be replaced by such a portion **228'''** if, for example, the first recording **108** covered a time **Te3** at which an event occurred but did not show a clear view of the event. If the field of view **110** of the first user device **102** was partially obscured during the time **Te3** of the event, then the modified first recording **306** may include the portion **228'''** of a second recording **228** that provides a better, or even an unobscured, view of the event at time **Te3**, in place of the corresponding portion of the first recording **108**.

[0038] FIG. 4 depicts a system **400** for augmenting user-generated content according to an embodiment. The system comprises a server **402**, which can communicate with the user devices **102**, **206**, **208**, **210** via a communication network **404**. Optionally, the server **402** may also communicate with a cloud storage server **406**, such as Google Photos™ or Apple iCloud™ and/or a social media platform server **408**, via the communication network **404**. Google Photos™ is a trademark owned by Google LLC. iCloud™ is a trademark owned by Apple Inc.

[0039] Although only one communication network **404** is shown in the example of FIG., in other embodiments, the first and second user devices **102**, **206**, **208**, **210** may communicate with the server **402**, cloud storage server **406**, and/or social media platform **408** via one or more first communication networks **404**. For example, the user devices **102**, **206**, **208**, **210** may transmit recordings **108**, **224**, **226**, **228** to one or more of the server **402**, cloud storage server **406**, or social media platform **408** via a communication network **404**, such as the Internet or the “Internet of Things,” which may be accessed via a cellphone network or local area network, not shown.

[0040] For example, the communication network **404** may be a local area network, such as a local Wi-Fi network. The server **402** may be a server that is provided in association with the site, such as a server **402** associated with the stadium **106**, that allows the users **100**, **200**, **202**, **204** to upload videos over the local area network. In this manner, a video augmentation service may be provided by the promotor, team or owner of the stadium **106** as a service to spectators at the game, using the uploaded videos. The service may be accessed via a webpage inviting a user **100**, **200**, **202**, **204** to upload videos, for example, in exchange for the opportunity to have their own videos augmented by other users' content. Alternatively, or additionally, another user incentive, such as a voucher, gift, or monetary compensation, may be offered to encourage the users **100**, **200**, **202**, **204** to make their recordings **108**, **224**, **226**, **228** available to the augmentation service.

[0041] Alternatively, or additionally, the server **402** may source videos **108**, **224**, **226**, **228** uploaded by the users **100**, **200**, **202**, **204** from the cloud storage server **406**, and/or posts by those users **100**,

200, 202, 204 on the social media platform **408**.

[0042] FIG. 5 is a block diagram of the server **402**. The server **402** is configured to transmit and receive content and data via I/O path **500**. In particular, the I/O path **500** may receive recordings **108, 224, 226, 228** from one or more of the user devices **100, 206, 208, 210**, the cloud storage server **406**, and the social media platform **408**, and may provide a modified video **300, 302, 304, 306** to the first user device **102** via the communication network **404**, shown in FIG. 4.

[0043] The server **402** includes control circuitry **502**. The control circuitry **402** includes processing circuitry **504**, and memory **506** (e.g., RAM, ROM, hard disk, removable disk, etc.). The control circuitry **502** may be used to send and receive requests, and other data, using I/O path **500**.

[0044] The control circuitry **502** may include any suitable processing circuitry **504**, such as circuitry based on one or more microprocessors, microcontrollers, digital signal processors, programmable logic devices, FPGAs, ASICs, etc., and may include a multi-core processor (e.g., dual-core, quad-core, hexa-core, or any suitable number of cores) or supercomputer. In some embodiments, processing circuitry may be distributed across multiple separate processors or processing units, for example, multiple of the same type of processing units (e.g., two Intel Core i7 processors) or multiple different processors (e.g., an Intel Core i5 processor and an Intel Core i7 processor). The control circuitry **502** executes instructions for an application stored in the memory **506**. Specifically, the control circuitry **502** may be instructed by applications to perform functions to prepend or append at least a portion **224', 226', 228', 228''** of a selected recording **224, 226, 228** to the first recording **108**.

[0045] The control circuitry **502** includes communications circuitry suitable for communicating with the communication network **404**, cloud storage server **406** and social media platform **408**. The communications circuitry may include a cable modem, an integrated services digital network (ISDN) modem, a digital subscriber line (DSL) modem, a telephone modem, Ethernet card, or a wireless modem for communications with other equipment, or any other suitable communications circuitry via the communication network **404**.

[0046] Additional storage **508** may be included, for example, for storing recordings **108, 224, 226, 228** uploaded by the users **100, 200, 202, 204**, and/or data relating to those recordings **108, 224, 226, 228**. As referred to herein, the phrase “storage” should be understood to mean any device for storing electronic data, computer software, or firmware, such as random-access memory, read-only memory, hard drives, optical drives, or any other suitable fixed or removable storage devices, and/or any combination of the same.

[0047] FIG. 6 depicts an exemplary user device **600** that may be used as the first user device **102**, and/or one or more of the second user devices **206, 208, 210**. As discussed above, in this example, the user device **600** is a smartphone. In other embodiments, the user device **600** may be another type of portable user device capable of recording content, such as a tablet, or a wearable device.

[0048] The user device **600** is configured to receive content and data via second input/output (I/O) path **602**. Second I/O path **602** may provide content (e.g., one or more of broadcast programming, on-demand programming, Internet content, content available over a local area network (LAN) or wide area network (WAN), and/or other content) and data to the second control circuitry **604**, which includes second processing circuitry **606** and second storage **608**. The second control circuitry **604** may be used to send and receive commands, requests, and other suitable data using the second I/O path **602**. The second I/O path **602** may connect the second control circuitry **604**, and, specifically, the second processing circuitry **606**, to one or more communication networks, such as the communication network **404** shown in FIG. 4. I/O functions may be provided via one or more of these communication paths, but are shown as a single path in FIG. 6 to avoid overcomplicating the drawing.

[0049] The second control circuitry **604** may include any suitable processing circuitry **606**, such as the examples discussed above in relation to the processing circuitry **504** of the server **402**. The second control circuitry **604** executes instructions for an application stored in the second storage

608. For example, applications may provide instructions to the second control circuitry **604** to generate displays. In some implementations, any action performed by the second control circuitry **604** may be based on instructions received from the applications.

[0050] The second control circuitry **604** includes second communications circuitry suitable for communicating with an application server, networks or servers. In a client-server arrangement, the instructions for carrying out the above-mentioned functionality may be stored on an application server. The communications circuitry may include a cable modem, an integrated services digital network (ISDN) modem, a digital subscriber line (DSL) modem, a telephone modem, Ethernet card, or a wireless modem for communications with other equipment, or any other suitable communications circuitry via one or more communication networks. In addition, the second communications circuitry may include circuitry that enables peer-to-peer communication with other user devices.

[0051] The second control circuitry **604** may include video generating circuitry, one or more MPEG-2 decoders or other digital decoding circuitry, or any other suitable video circuits or combinations of such circuits. Encoding circuitry (e.g., for converting analog, or digital signals to MPEG signals for storage) may also be provided. The second control circuitry **604** may also include scaler circuitry for upconverting and downconverting content into the preferred output format of the user device **600**. The circuitry described herein, including for example, the video generating, encoding, decoding, encrypting, decrypting, scaler, and analog/digital circuitry, may be implemented using software running on one or more general purpose or specialized processors.

[0052] A user may send instructions to the second control circuitry **604** using a user input interface **610**. The user input interface **610** may be any suitable user interface, such as a remote control, mouse, trackball, keypad, keyboard, touch-screen, touchpad, stylus input, joystick, voice recognition interface, or other user input interfaces. In this particular example, a display **612** is integrated with other elements of the user device **600** and may be a touch-screen or touch-sensitive display. In such circumstances, the user input interface **610** is integrated with or combined with the display **612**. Display **612** may any suitable display, such as a liquid crystal display (LCD), electronic ink display, light-emitting diode display, organic light-emitting diode display, or any other suitable equipment for displaying visual images. In some embodiments, the display **612** may be HDTV-capable. In some embodiments, display **612** may be a 3D display, and the interactive application and any suitable content may be displayed in 3D. A video card or graphics card may generate the output to the display **612**. The video card may offer various functions such as accelerated rendering of 3D scenes and 2D graphics, MPEG-2/MPEG-4 decoding, TV output, or the ability to connect multiple monitors. The video card may be any processing circuitry described above in relation to the second control circuitry **604**. The video card may be integrated with the second control circuitry **604**. Speakers **614** may be provided as integrated with other elements of the user equipment device **600**. The audio component of videos and other content displayed on display **612** may be output through the speakers **614**.

[0053] The applications may be stand-alone applications implemented on the user devices **600**. For example, the application may be implemented as software or a set of executable instructions which may be stored in the second storage **608** and executed by the second control circuitry **604**.

[0054] In some embodiments, the applications may be client-server applications where a client application resides on the user equipment device, and a server application resides on a remote server. For example, applications may be implemented partially as a client application on the second control circuitry **604** and partially on a remote server as a server application running on the control circuitry **502** of the server **402**. When executed by the control circuitry **502** of the server **402**, the application may instruct the control circuitry **502** to generate application displays and transmit the generated displays to the user equipment device **600**. The server application may instruct the control circuitry **502** to transmit data for storage on the user device **600**. The client application may instruct the second control circuitry **604** of the user equipment **600** to generate the

application displays.

[0055] The user device **600** also includes a camera **616** for capturing still images and video and a microphone **618** for capturing audio input.

[0056] In addition, the user device **600** includes additional sensors **620**, including one or more of a compass, an accelerometer, and a Global Positioning Service (GPS) sensor. The output from the sensors **620** is used, by the second control circuitry **604**, to determine data such as one or more of a location of the user device **600**, an orientation of the user device **600**, or an elevation of the user device **600**. That data may then be linked to a recording made by the user device **600**, such as the recordings **108, 224, 226, 228** made by user devices **102, 206, 208, 210**, for example, as metadata included in, or otherwise associated with the recordings **108, 224, 226, 228**, or otherwise transmitted to the server **402** in conjunction with the recordings **108, 224, 226, 228**.

[0057] FIG. 7 is a flowchart of a method of collecting user-generated content for use in augmenting user-generated content that may be performed by the server **402**, in accordance with an embodiment. Starting at **700**, the control circuitry **502** begins monitoring for events (step **702**). In the specific example shown in FIG. 1, events within the soccer game may be detected, for instance through manual input, detection of score changes, analysis of audio or video captured within the stadium, or analysis of audio or textual commentary. Examples of events may include goals, penalty kicks, a player being sent off, a player being substituted, etc. The monitoring may begin at the start of the game. Alternatively, the monitoring may begin prior to the start of the game, for example, to detect pre-game events such as incidents during player warm-up sessions, pre-game entertainment, and so on, and/or may continue after the game has finished to detect post-game events such as a trophy presentation.

[0058] If an event is detected (step **704**), then the control circuitry **502** determines information about the event (step **706**). The information includes a time at which the event occurred. Optionally, the information may further include a location within the stadium, and/or a type of the event. The determination may be based on one or more of a manual input, time of detection of a score change, captured audio, captured video, audio or textual commentary.

[0059] The control circuitry **502** then stores a log entry indicating the event, for example, in the storage **508** (step **708**). For each event, the log entry indicates a time of the event and, optionally, a location within the stadium and/or type of event. In this manner, a timeline of events in the soccer game may be compiled by the server **402**.

[0060] The server **402** then determines whether one or more recordings **108, 224, 226, 228** of at least part of the game are obtainable (step **710**). In this particular example, the recordings **108, 224, 226, 228** are videos uploaded by the user devices **102, 206, 208, 210** to the server **402** and stored in the storage **508** while the game is in progress. In other examples, the recordings may be videos uploaded to the server **402**, to the cloud storage server **406**, or to the social media platform **408** during the game and/or, optionally, after, the game.

[0061] The server **402** then stores data associated with the recordings **108, 224, 226, 228** (step **712**) to indicate the time interval **112, 230, 232, 234** covered by the recording **108, 224, 226, 228**, such as the start and end times T_s , T_f of the recording **108, 224, 226, 228**. The data may, optionally, also include one or more of an angle, direction, in-stadium location **104, 218, 220, 222**, and elevation of the respective user device **102, 206, 208, 210** that captured the recording **108, 224, 226, 228**, as indicated by data provided by that user device **102, 206, 208, 210**. Multiple instances of an angle, direction, location **104, 218, 220, 222**, and elevation may be stored for a particular recording **108, 224, 226, 228** to reflect any changes in the position of the respective user device **102, 206, 208, 210** and/or its field of view during the time interval **112, 230, 232, 234** covered by the recording **108, 224, 226, 228**. In this manner, a database of recordings **108, 224, 226, 228** may be compiled by the server **402**, with information that can be used to determine whether the recordings **108, 224, 226, 228** potentially include one or more of the detected events.

[0062] These processes of monitoring and logging events (steps **702-708**) and compiling the

database of recordings (steps **710-712**) continue until it is determined that they are complete (steps **714, 716**). The process of monitoring and logging events (steps **702-708**) may continue until the game has finished, or until post-game activity on the pitch has been completed (step **714**). The process of compiling the database of recordings (steps **710-712**) may be deemed complete at the same time that the monitoring finishes (step **716**) or, optionally, may continue until a later time. For example, the database may continue to be compiled for a set number of hours, days, or weeks, to allow for users uploading recordings after the end of the game. The process then ends at **718**.

[0063] FIG. **8** is a flowchart of a process to augment user-generated content performed by the server **402** of FIG. **5**, in accordance with an embodiment. This process may be performed in parallel with the process of FIG. **7**, for example, in conjunction with determining that a recording **108** from the first user device **102** has been uploaded (step **710**) and storing the data associated with the recording (step **712**). Alternatively, or additionally, this process may be performed if the recording **108** is uploaded after the process of FIG. **7** has been completed.

[0064] Starting at **800**, the control circuitry **502** of the server **402** receives, or otherwise obtains, the first recording **108** (step **802**). For example, the first user device **102** may have uploaded the first recording **108** to the server **402**. This step may coincide with the determination at step **710** in FIG. **7**.

[0065] The control circuitry **502** then determines a first time point associated with the first recording **108** (step **804**). For example, the first time point may be the start time T_s or the end time T_f of the time interval **112** covered by the first recording **108**. This determination may be based on the data associated with the first recording **108**, as discussed above in relation to step **712** of FIG. **7**.

[0066] The control circuitry **502** also determines a location associated with the first recording **108** (step **806**). This determination may be based on the data associated with the first recording **108**, as discussed above in relation to step **712** of FIG. **7**, such as GPS data. Step **806** may, optionally, further include determining the field of view **110** of the first user device **102** during the first time interval **112**. The field of view **110** may be determined based on one or more of an orientation, elevation, or angle of the first user device **102** during the first time interval **112**.

[0067] The control circuitry **502** then selects at least a portion of a second recording **224, 226, 228** to prepend or append to the first recording **108** (step **808**). The selection will depend on the second time interval **230, 232, 234** covered by the second recording **224, 226, 228** including the first time point. For example, if the first recording **108** is to be augmented by adding video of the event that occurred at time T_{e1} , prior to the start time T_s of the first recording **108**, then a portion of a second recording **224, 226, 228** may be selected that includes a time point corresponding to the start time T_s and a second time point corresponding to time T_{e1} . Similarly, if the first recording **108** is to be augmented by adding video of the event at time T_{e2} , after the finish time T_f of the first recording **108**, then a portion of a second recording **224, 226, 228** may be selected that includes a time point corresponding to the end time T_f of the first recording **108** and a time point corresponding to the time T_{e2} .

[0068] The selection of the portion of the second recording **224, 226, 228** at step **808** may also be based on a location of the respective second user device **206, 208, 210** during the second time interval **230, 232, 234**, as indicated in the data stored at step **712** of FIG. **7**. For example, the control circuitry **502** may select a portion **228'** from the second recording **228** made by the second user device **210** instead of a portion **224'** from the second recording **224** made by the second user device **206**, based on the location **222** of the second user device **210** during the second time interval **234** being closer to the location **104** of the first user device **102**, when compared with the location **218** of the second user device **206** during the respective second time interval **230**, as shown in FIG. **2A**.

[0069] The selection of the portion of the second recording **224, 226, 228** at step **808** may optionally take into account the respective fields of view **212, 214, 216** of the second user devices **206, 208, 210**. This data may be used to exclude a second recording **224, 226, 228** that does not

include the event. For example, a second user located close to the first user **100** may have uploaded video recorded during the time **Te1**, **Te2** the event occurred but might have been capturing video of their friends or family, instead of capturing video of the event on the field. Elevation, orientation, and/or angle data for the second user devices **206**, **208**, **210** may be utilized in order to select the second recording **224**, **226**, **228** for which the field of view **212**, **214**, **216** provides the closest match to the field of view **110** of the first user device **102**. These determinations may be based on the data stored in step **712** of FIG. 7 for the recordings **108**, **224**, **226**, **228**.

[0070] Optionally, the selection of the portion of the second recording at step **808** may also include performing object recognition on at least a portion of one or more candidate second recordings **224**, **226**, **228**, or analyzing object recognition data obtained previously, to determine whether or not the event is visible in the second recordings **224**, **226**, **228**. In the example shown in FIGS. **1A** and **2A**, at least part of the field of view **110** of the first user device **102** is obscured from the view **216** of one of the second user devices **210** due to people **230** standing between the respective second user **204** and the part of the pitch. The obscuration of the event may be detected by the absence of an associated object, such as a soccer ball associated with a goal event. In this example, even though, of the second user locations **218**, **220**, **222**, the location **222** of the second user **204** might be the closest to the location **104** of the first user **100**, the control circuitry **502** may instead select a portion **226'** of the recording **226** made by another of the second users **202** because it provides an unobscured view of the event.

[0071] The control circuitry **502** then modifies the first recording **108**, by prepending or appending the selected portion **224'**, **226'**, **228'**, **228''** to the first recording **108** as appropriate (step **810**). In some embodiments, the entirety of a selected second recording may be added to the first recording **108**.

[0072] Optionally, the modification at step **810** may include producing or obtaining an edited version of the selected portion for addition to the first recording **108**. In particular, the selected portion **224'**, **226'**, **228'**, **228''** may be edited to blur or mask faces in the selected portion in order to preserve the privacy of people shown in the relevant second recording **224**, **226**, **228**.

[0073] The control circuitry **502** then provides the modified first recording **300**, **302**, **304** to the first user device **102** (step **812**). For example, the control circuitry **502** may transmit the modified first recording **300**, **302**, **304** to the first user device **100** via the communication network **404**. In another example, the control circuitry **502** may send to the first user **100** a link, such as a Uniform Resource Locator (URL) address that may be used to access the modified first recording **300**, **302**, **304**. Such an address or link may be sent to the first user **102** in an e-mail, chat message, text message or other message. The process then ends at **814**.

[0074] While the process of FIG. **8** has been described in conjunction with the process of FIG. **7**, in another embodiment, the process of FIG. **8** may be performed independently of the process of FIG. **7**. For example, the process of FIG. **8** may be performed in response to receipt of a request from the first user **100** to augment the first recording **108** by adding video before and/or after the first time interval **112** that is not related to a detected event in the game. For instance, if the first user **100** stopped capturing video just before a player in the game waved at them, then the first user **100** might wish to append, to the first recording **108**, video of the player waving, and may request such video from the server **402**, regardless of whether or not event monitoring, as described in relation to step **702** of FIG. **7**, has been performed.

[0075] In either of the methods described above with reference to FIG. **8**, the selection of the portion at step **808** may be based on a selection received from the first user device **102**. A method for such a selection will now be described with reference to FIGS. **9** and **10**.

[0076] FIG. **9** depicts an example display screen **900** in which such images from candidate second recordings **224**, **226**, **228** are presented on the display of the first user device **102** to allow the first user **100** to make such a selection.

[0077] Referring now to FIG. **10**, starting at **1000**, the control circuitry **502** of the server identifies

candidate recordings **224, 226, 228** for providing a portion to augment the first recording **108** (step **1002**). The control circuitry **502** may identify the candidate second recordings **224, 226, 228** by filtering the second recordings **224, 226, 228** based on respective time interval information and respective location information, such as the data stored at step **712** in the method of FIG. 7. The respective time intervals **230, 232, 234** may be compared with a desired time interval or time point that is based on a request received from the first user device **102** or on the start and/or end times T_s , T_f of the first interval **112**.

[0078] At step **1004**, the control circuitry **502** provides still or video images from the candidate second recordings **224, 226, 228** to the first user device **102**. The provided images may be presented on the display of the first user device **102**, for example, in the display screen **900** shown in FIG. 9. The first user **100** can select one of the second recordings **224, 226, 228**, via a user input interface. For example, the first user may position a highlight region **902** over a corresponding image and confirm selection of that image using touchscreen and/or cursor input. An indication of that user selection is then transmitted by the first user device **102** to the server **402**.

[0079] The control circuitry **502** then receives the indication of the user selection at step **1006**, completing the selection of the portion at **1008**. The control circuitry **502** then proceeds to modify the first recording **108**, as described above in relation to step **810** of FIG. 8.

[0080] Basing the selection of the portion, at least in part, on such a user selection can provide greater reliability in the selection of a suitable portion **224', 226', 228', 228''** of a second recording **224, 226, 228**. For instance, the first user **100** wishes to add video that might not correspond to an event in the soccer game. In the example discussed above, where a player waved to the first user **100**, the player's wave is unlikely to have been detected and logged as an event by the server **402** and, therefore, allowing the user **100** to select a portion **224', 226', 228', 228''** of a second recording **224, 226, 228** that meets their requirements can result in greater reliability.

[0081] Similarly, a process involving such a user selection may avoid the selection of a portion in which an event is obscured, for example, by the people **230** shown in the second recording **228**, without needing to perform, or rely on, an object recognition process as described above in relation to step **808** of FIG. 8.

[0082] The above disclosure is meant to be exemplary and not limiting. As discussed above, the disclosure is not limited to augmenting captured video. The disclosed methods and systems may, instead, be used to augment other types of content, including audio content, or multimedia content other than live video recordings. Only the claims that follow are meant to set bounds as to what the present invention includes.

[0083] For example, although embodiments have been described with reference to a particular type of location, namely a sports stadium, the methods and systems may be applied to content relating to other types of locations, such as other types of area, sites such as tourist sights, safari locations, and so on.

[0084] While the above example related to a sports event, in which recordings were uploaded to a server associated with a stadium during a game, the methods and systems may be used to provide a content augmentation service at a later time. For example, users may be permitted to upload videos to a content augmentation server via the Internet at any time after an event.

[0085] The above-described embodiments related to a system in which a server **402** determines whether to prepend or append video to a first recording **108**. In other embodiments, the user devices **102, 206, 208, 210** may be arranged to share recordings **108, 224, 226, 228**. In such an embodiment, the first user device **102** may be configured to determine whether to augment the recording **108** using a portion of a shared recording **224, 226, 228** and/or to prepend or append such a portion to the first recording **108**. Optionally, such a determination may be based on information regarding detected events received from a server **402**.

[0086] In many of the above-described embodiments, a first recording **108** is augmented by prepending or appending at least a portion of a second recording **224, 226, 228**. In other

embodiments, a portion of the first recording **108** may be replaced by at least a portion of a second recording **224, 226, 228**. For example, it may be determined that one of the second recordings **224, 226, 228** includes a better view of an event that occurred during the first time interval. As discussed above, one user's view of an event may be obstructed by people or objects between that user and the event. An object recognition process, such as that described above in relation to step **808** of FIG. **8** may be used to determine whether the first recording **108** includes an obstructed view of an event. In response to a determination that the first recording **108** includes such an obstructed view, a portion of the first recording **108** including a time at which the event occurred may be replaced with a portion of a second recording **224, 226, 228** that provides an unobstructed view, or a less obstructed view, of that event.

[0087] Furthermore, it should be noted that the features and limitations described in any one embodiment may be applied to any other embodiment herein, and flowcharts or examples relating to one embodiment may be combined with any other embodiment in a suitable manner, done in different orders, or done in parallel. In addition, the systems and methods described herein may be performed in real time. It should also be noted that the systems and/or methods described above may be applied to, or used in accordance with, other systems and/or methods.

Claims

1. A method comprising: receiving a first recording of an event, the first recording being an initial portion of the event and not including the event in its entirety; receiving a second recording, the second recording having an overlap with the first recording and including a remaining portion of the event that captures the event in its entirety and an initial portion of a second event; receiving a third recording having an overlap with the second recording and including a remaining portion of the second event that captures the second event in its entirety; determining a relationship between the first, second, and third recordings; and generating an augmented recording by combining portions of the first, second, and third recordings based on the determined relationships to more complete the first and second event.
2. The method of claim 1, wherein the more complete first and second event includes a recording of the first and second event in its entirety.
3. The method of claim 1, wherein the more complete first event includes an additional portion of the first event that was not included in the first recording prior to the first recording being combined with the second recording.
4. The method of claim 1, further comprising: determining that a portion of the first recording of the event during a first time interval includes a partially obscured view of the event; identifying a fourth recording that includes a non-obscured view of the event for the same portion of the event that is partially obscured in the first recording; and replacing the partially obscured portion of the first recording with the non-obscured portion from the fourth recording.
5. The method of claim 1, wherein combining portions of the first, second, and third recordings includes appending or prepending the second recording to the first recording and the third recording to the second recording.
6. The method of claim 1, further comprising: in response to determining that the first recording does not include the event in its entirety: monitoring uploads of recordings from other users related to the event; and identifying an upload of a new recording based on the monitoring; and combining a portion of the new recording with the first recording if the new recording overlaps at least a portion of the first recording and is related to the event.
7. The method of claim 6, wherein the monitoring is performed until completion of the event.
8. The method of claim 6, wherein the monitoring is performed even after completion of the event.
9. The method of claim 1, further comprising: determining a location of a first device during at least a portion of the first device generating the first recording of the event; determining a location

of a second device during at least a portion of the second device generating the second recording of the event; and selecting the second recording for combining with the first recording in response to determining that the location of the second device, during at least the portion of the second device generating the second recording of the event, was within a predetermined distance of the first device during at least the portion of the first device generating the first recording of the event.

10. The method of claim 1, further comprising, storing in a database a log entry for the first event, wherein the log entry for the first event comprises at least one of: a time of the event, a location of a user within a stadium, and a type of event.

11. A system comprising: a memory configured to store a first recording of an event received from a first device; and a control circuitry configured to: receive the first recording of the event from the first device, the first recording being an initial portion of the event and not including the event in its entirety; receive a second recording, the second recording having an overlap with the first recording and including a remaining portion of the event that captures the event in its entirety and an initial portion of a second event; receive a third recording having an overlap with the second recording and including a remaining portion of the second event that captures the second event in its entirety; determine a relationship between the first, second, and third recordings; and generate an augmented recording by combining portions of the first, second, and third recordings based on the determined relationships to more complete the first and second event.

12. The system of claim 11, wherein the more complete first and second event includes a recording of the first and second event in its entirety.

13. The system of claim 11, wherein the more complete first event includes an additional portion of the first event that was not included in the first recording prior to the first recording being combined with the second recording.

14. The system of claim 11, further comprising, control circuitry configured to: determine that a portion of the first recording of the event during a first time interval includes a partially obscured view of the event; identify a fourth recording that includes a non-obscured view of the event for the same portion of the event that is partially obscured in the first recording; and replace the partially obscured portion of the first recording with the non-obscured portion from the fourth recording.

15. The system of claim 11, wherein combining portions of the first, second, and third recordings includes the control circuitry configured to append or prepend the second recording to the first recording and the third recording to the second recording.

16. The system of claim 11, further comprising, control circuitry configured to: in response to determining that the first recording does not including the event in its entirety: monitor uploads of recordings from other users related to the event; and identify an upload of a new recording based on the monitoring; and combine a portion of the new recording with the first recording if the new recording overlaps at least a portion of the first recording and is related to the event.

17. The system of claim 16, wherein the monitoring is performed by the control circuitry until completion of the event.

18. The system of claim 16, wherein the monitoring is performed by the control circuitry even after completion of the event.

19. The system of claim 11, further comprising, control circuitry configured to: determine a location of the first device during at least a portion of the first device generating the first recording of the event; determine a location of a second device during at least a portion of the second device generating the second recording of the event; and select the second recording for combining with the first recording in response to determining that the location of the second device, during at least the portion of the second device generating the second recording of the event, was within a predetermined distance of the first device during at least the portion of the first device generating the first recording of the event.

20. The system of claim 11, further comprising, control circuitry configured to store in a database a

log entry for the first event, wherein the log entry for the first event comprises at least one of: a time of the event, a location of a user within a stadium, and a type of event.
