

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286948

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Ko; Heena et al.

Devices and Methods for Adjusting the Provision of Notifications

Abstract

An electronic device receives a communication. In response to receiving the communication, when a first mode is active on the electronic device and the communication meets respective criteria for the first mode, the device outputs a notification that corresponds to the communication in a first manner. When the first mode is active and the communication does not meet the respective criteria for the first mode, the device forgoes outputting the notification in the first manner. When a second mode is active on the electronic device and the communication meets respective criteria for the second mode, the device outputs the notification in the first manner. When the second mode is active and the communication does not meet the respective criteria for the second mode, the device forgoes outputting the notification in the first manner.

Inventors: Ko; Heena (London, GB), Dascola; Jonathan R. (San Francisco, CA), Foss; Christopher P. (San Francisco, CA), Wang; Corey K. (Palo Alto, CA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 1000008621045

Appl. No.: 19/215990

Filed: May 22, 2025

Related U.S. Application Data

parent US continuation 17084579 20201029 PENDING child US 19215990

parent US continuation 16142599 20180926 parent-grant-document US 10904379 child US 17084579

us-provisional-application US 62668168 20180507

us-provisional-application US 62679946 20180603

Publication Classification

Int. Cl.: H04M1/72472 (20210101); G06F3/048 (20130101); G06F3/0482 (20130101); G06F3/0484 (20220101); G06F3/04847 (20220101); G06F9/54 (20060101); H04M1/7243 (20210101); H04M1/72451 (20210101); H04M1/72454 (20210101); H04M1/72457 (20210101)

U.S. Cl.:

CPC H04M1/72472 (20210101); G06F9/542 (20130101); H04M1/7243 (20210101); H04M1/72451 (20210101); H04M1/72454 (20210101); H04M1/72457 (20210101); G06F3/048 (20130101); G06F3/0482 (20130101); G06F3/0484 (20130101); G06F3/04847 (20130101)

Background/Summary

RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 17/084,579, filed Oct. 29, 2000, which is a continuation of U.S. patent application Ser. No. 16/142,599, filed Sep. 26, 2018, now U.S. Pat. No. 10,904,379, which claims priority to U.S. Provisional Application Ser. No. 62/679,946, filed Jun. 3, 2018, and U.S. Provisional Application Ser. No. 62/668,168, filed May 7, 2018, all of which are incorporated by reference herein in their entireties.

TECHNICAL FIELD

[0002] This relates generally to electronic devices with touch-sensitive surfaces, including but not limited to electronic devices with touch-sensitive surfaces that provide notifications, and more particularly, to devices and methods that adjust the provision of notifications.

BACKGROUND

[0003] The use of portable electronic devices has increased significantly in recent years, with many applications typically residing in the memory of such devices. Example applications include communications applications (e.g., messaging and telephone), calendar applications, news applications, media playback applications (e.g., podcast, music, and video), payment applications, reminder applications, social media applications, and service delivery applications. These applications generate events, which contain information of varying degrees of importance to users. Notifications that correspond to the generated events may be displayed. Example notifications include digital images, video, text, icons, control elements (such as buttons) and/or other graphics to notify users of events. Example applications that generate notifications include messaging applications (e.g., iMessage or Messages from Apple Inc. of Cupertino, California), calendar applications (e.g., iCal or Calendar from Apple Inc. of Cupertino, California), news applications (e.g., Apple News from Apple Inc. of Cupertino, California), media playback applications (e.g., Podcasts, Apple Music and iTunes from Apple Inc. of Cupertino, California), payment applications (e.g., Apple Pay from Apple Inc. of Cupertino, California), reminder applications (e.g., Reminders from Apple Inc. of Cupertino, California), social media applications, and service delivery applications.

[0004] The types of notifications that a user wants to receive while working, playing, or sleeping may be quite different. But current user interfaces for adjusting when alerts and other notifications are provided (and which notifications are provided) are cumbersome and inefficient. For example, to change alert settings, some devices require the user to navigate to obscure, hard-to-find settings user interfaces of the devices' operating systems. At present, there is no simple way for a user to easily adjust the provision of notifications in different contexts. Existing methods take longer than necessary, thereby wasting energy. This latter consideration is particularly important in battery-

operated devices.

SUMMARY

[0005] Accordingly, there is a need for electronic devices with faster, more efficient methods and interfaces for adjusting the provision of notifications. Such methods and interfaces optionally complement or replace conventional methods for adjusting the provision of notifications. Such methods and interfaces reduce the number, extent, and/or nature of the inputs from a user and produce a more efficient human-machine interface. For battery-operated devices, such methods and interfaces conserve power and increase the time between battery charges.

[0006] The above deficiencies and other problems associated with interfaces that adjust the provision of notifications are reduced or eliminated by the disclosed electronic devices. In some embodiments, the device includes a desktop computer. In some embodiments, the device is portable (e.g., a notebook computer, tablet computer, or handheld device). In some embodiments, the device includes a personal electronic device (e.g., a wearable electronic device, such as a watch). In some embodiments, the device has (and/or is in communication with) a display generation component and one or more input devices. In some embodiments, the device has (and/or is in communication with) a touchpad. In some embodiments, the device has (and/or is in communication with) a touch-sensitive display (also known as a “touch screen” or “touch screen display”). In some embodiments, the device has a graphical user interface (GUI), one or more processors, memory and one or more modules, programs or sets of instructions stored in the memory for performing multiple functions. In some embodiments, the user interacts with the GUI in part through stylus and/or finger contacts and gestures on the touch-sensitive surface. In some embodiments, the functions optionally include game playing, image editing, drawing, presenting, word processing, spreadsheet making, telephoning, video conferencing, e-mailing, instant messaging, workout support, digital photographing, digital videoing, web browsing, digital music playing, note taking, and/or digital video playing. Executable instructions for performing these functions are, optionally, included in a non-transitory computer readable storage medium or other computer program product configured for execution by one or more processors.

[0007] In accordance with some embodiments, a method is performed at an electronic device with a display, a touch-sensitive surface, and one or more sensors to detect intensities of contacts with the touch-sensitive surface. The method includes, while the electronic device is in a display-off state, detecting a first input. The method includes, in response to detecting the first input: activating the display of the device, and displaying, on the display, a first user interface that corresponds to a display-on state of the device. The first user interface is an initial user interface that is displayed when the device switches from the display-off state to the display-on state in response to detecting the first input. The first user interface includes a control affordance for controlling generation of alerts by the device. The first user interface is distinct from a home screen user interface that includes a plurality of application launch icons corresponding to a plurality of applications. The method includes, while displaying the first user interface that includes the control affordance, detecting a second input that includes a contact at a location on the touch-sensitive surface that corresponds to the control affordance. The method includes, in response to detecting the second input: in accordance with a determination that the second input meets activation criteria for the control affordance, wherein the activation criteria include a requirement that the second input includes an increase in a characteristic intensity of the contact that exceeds an intensity threshold while the contact is at the location on the touch-sensitive surface that corresponds to the control affordance in order for the activation criteria to be met, initiating a process for adjusting alert settings of the device; and, in accordance with a determination that the second input does not meet the activation criteria for the control affordance, forgoing initiating the process for adjusting alert settings of the device.

[0008] In accordance with some embodiments, a method is performed at an electronic device with a display. The method includes receiving a communication. The method includes, in response to

receiving the communication: in accordance with a determination that a first mode is active on the electronic device: in accordance with a determination that the communication meets whitelisting criteria for the first mode, outputting, at the device, a notification that corresponds to the communication in a first manner; and, in accordance with a determination that the communication does not meet the whitelisting criteria for the first mode, forgoing outputting the notification that corresponds to the communication in the first manner. The method includes, in response to receiving the communication, in accordance with a determination that a second mode is active on the electronic device: in accordance with a determination that the communication meets whitelisting criteria for the second mode, wherein the whitelisting criteria for the second mode are different from the whitelisting criteria for the first mode, outputting, at the device, the notification that corresponds to the communication in the first manner; and, in accordance with a determination that the communication does not meet the whitelisting criteria for the second mode, forgoing outputting the notification that corresponds to the communication in the first manner.

[0009] In accordance with some embodiments, a method is performed at an electronic device with a display. The method includes detecting a plurality of manual activations of a first mode on the electronic device. The first mode, while active, prevents output of notifications when communications of a first type are received. The method includes, after detecting the plurality of manual activations of the first mode: automatically determining, based on the plurality of manual activations of the first mode, a set of conditions that correspond to manual activations of the first mode and outputting, at the device, a suggestion for activation of the first mode at the electronic device. The method includes, after outputting the suggestion, receiving a response that accepts the suggestion for activation of the first mode. The method includes, in response to receiving the response that accepts the suggestion, changing settings at the device that are associated with the first mode.

[0010] In accordance with some embodiments, a method is performed at an electronic device with a display. The method includes, while the electronic device is in a reduced notification mode, receiving one or more communications. The method includes, after receiving the one or more communications, detecting an alert condition for the reduced notification mode. The method includes, in response to detecting the alert condition for the reduced notification mode, displaying a first user interface that includes a first affordance which, when activated, causes deactivation of the reduced notification mode of the electronic device. The method includes, while displaying the first user interface, detecting a first input that activates the first affordance. The method includes, in response to detecting the first input that activates the first affordance: deactivating the reduced notification mode, and displaying, on the display, a second user interface, wherein the second user interface does not display, on the display, content from any one of the one or more communications. The method includes, while the second user interface is displayed, detecting a second input and in response to detecting the second input, displaying notifications that include content for at least some of the one or more communications received while the electronic device was in the reduced notification mode.

[0011] In accordance with some embodiments, an electronic device includes a display, an optional touch-sensitive surface, one or more optional sensors to detect intensities of contacts with the touch-sensitive surface, one or more processors, memory, and one or more programs. The one or more programs are stored in the memory and configured to be executed by the one or more processors. The one or more programs include instructions for performing the operations of any of the methods described herein. In accordance with some embodiments, a computer readable storage medium has stored therein instructions which when executed by an electronic device with a display, an optional touch-sensitive surface, and one or more optional sensors to detect intensities of contacts with the touch-sensitive surface, cause the device to perform the operations of any of the methods described herein. In accordance with some embodiments, a graphical user interface on an electronic device that includes memory and one or more processors to execute one or more

programs stored in the memory includes one or more of the elements displayed in any of the methods described herein, which are updated in response to inputs, as described in any of the methods described herein. In accordance with some embodiments, an electronic device includes a display, an optional touch-sensitive surface, one or more optional sensors to detect intensities of contacts with the touch-sensitive surface, and means for performing the operations of any of the methods described herein. In accordance with some embodiments, an information processing apparatus, for use in an electronic device that includes a display, an optional touch-sensitive surface, and one or more optional sensors to detect intensities of contacts with the touch-sensitive surface, includes means for performing the operations of any of the methods described herein. [0012] Thus, electronic devices are provided with faster, more efficient methods and interfaces for adjusting the provision of notifications, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace conventional methods for adjusting the provision of notifications.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] For a better understanding of the various described embodiments, reference should be made to the Description of Embodiments below, in conjunction with the following drawings in which like reference numerals refer to corresponding parts throughout the figures.

[0014] FIG. 1A is a block diagram illustrating a portable multifunction device with a touch-sensitive display in accordance with some embodiments.

[0015] FIG. 1B is a block diagram illustrating example components for event handling in accordance with some embodiments.

[0016] FIG. 2 illustrates a portable multifunction device having a touch screen in accordance with some embodiments.

[0017] FIG. 3 is a block diagram of an example multifunction device with a display and a touch-sensitive surface in accordance with some embodiments.

[0018] FIG. 4A illustrates an example user interface for a menu of applications on a portable multifunction device in accordance with some embodiments.

[0019] FIG. 4B illustrates an example user interface for a multifunction device with a touch-sensitive surface that is separate from the display in accordance with some embodiments.

[0020] FIGS. 4C-4E illustrate examples of dynamic intensity thresholds in accordance with some embodiments.

[0021] FIGS. 5A-5BM illustrate example user interfaces for providing notifications and adjusting settings for providing notifications, in accordance with some embodiments.

[0022] FIGS. 6A-6E are flow diagrams illustrating a method of adjusting alert settings on an electronic device, in accordance with some embodiments.

[0023] FIGS. 7A-7C are flow diagrams illustrating a method of providing alerts (e.g., notifications) on an electronic device, in accordance with some embodiments.

[0024] FIGS. 8A-8E are flow diagrams illustrating a method of activating a reduced notification mode (e.g., a “do-not-disturb” mode) of an electronic device, in accordance with some embodiments.

[0025] FIGS. 9A-9D are flow diagrams illustrating a method of providing notifications when a reduced notification mode of an electronic device is deactivated, in accordance with some embodiments.

DESCRIPTION OF EMBODIMENTS

[0026] The methods, devices, and GUIs described herein improve user interface interactions that adjust the provision of notifications in multiple ways.

[0027] Some embodiments described below provide devices and methods for adjusting settings for controlling generation of alerts (e.g., notifications) by a device. More specifically, in some embodiments, a device displays of a virtual button (e.g., a control affordance on a touch-sensitive display) for controlling generation of alerts by the device (e.g., for controlling a reduced notification mode of the device, such as a “do-not-disturb” mode). The virtual button is displayed in an initial user interface that appears when the device wakes up from a display-off state (e.g., the virtual button is displayed on a wake screen). After an intensity of a contact at the virtual button exceeds an intensity threshold, the device initiates a process for adjusting alert settings of the device (e.g., the device displays a menu with user-selectable auto-expiration options for the reduced notification mode, or displays a menu with user-selectable options for switching to a different reduced notification mode). In some embodiments, the virtual button toggles the reduced notification mode in response to a light press (e.g., a contact with a characteristic intensity above a first intensity threshold, such as IT.sub.L, but below a second intensity threshold, such as IT.sub.D) and initiates the process for adjusting the alert settings in response to a deep press (e.g., a contact with a characteristic intensity above a second intensity threshold, such as IT.sub.D). In some embodiments, the virtual button is unresponsive to contacts with an intensity below the first intensity threshold, which reduces the risk of accidental activation of the button.

[0028] Some embodiments described below provide devices and methods with different reduced notification modes (e.g., different “do-not-disturb” modes) for different contexts (e.g., a productivity mode, a social mode, a sleep mode, and an exercise mode). The different reduced notification modes have different whitelists (e.g., lists of applications from which notifications are allowed to “break through” the reduced notification mode). An active reduced notification mode causes the device to at least partially block notifications that are not whitelisted for that particular reduced notification mode. For example, a notification that is whitelisted for an active reduced notification mode will be displayed and the user will be notified of its arrival by a sound and/or a haptic alert. In contrast, a notification that is not whitelisted for the active reduced notification mode will be displayed without a sound or haptic alert (or will not be provided at all while the particular reduced notification mode is active). Thus, a user can, for example, set the device to a productivity mode at work and not be distracted by social media, then can go home and set the device to a social mode to avoid being bothered by work emails.

[0029] Some embodiments described below provide devices and methods for automatically suggesting activation of a reduced notification mode based on a plurality of prior manual activations of the reduced notification mode. In some embodiments, a device associates a set of conditions with individual manual activations of a reduced notification mode. For example, a device will detect that the user has often manually activated a productivity mode around the time when the user arrives at work around 9 AM. Based on the plurality of prior manual activations, the device outputs an activation suggestion for the reduced notification mode. In some embodiments, the activation suggestion is a suggestion, provided upon a respective manual activation of the reduced notification mode, to automatically activate the reduced notification mode whenever the device detects a similar set of conditions (e.g., “Would you like to automatically activate productivity mode whenever you arrive at work in the morning?”). In some embodiments, the activation suggestion is a suggestion, provided when the device detects a similar set of conditions, to activate the reduced notification mode at that time (e.g., “You’ve arrived at work! Would you like to activate productivity mode?”)

[0030] Some embodiments described below include devices and methods for provision of notifications when a reduced notification mode is deactivated (e.g., a reduced notification mode such as a sleep mode, that is associated with a wake-up alarm). These methods and devices provide a gradual “wake-up” that avoids overwhelming the user with notifications immediately upon waking up and turning off their alarm. To that end, when a user turns off their alarm (which also disables the reduced notification mode), a user interface forgoes displaying content from

communications received by the device while the device was in the reduced notification mode. Instead, the user interface displays a small amount of information, such as the weather and/or a “Good Morning” message. The user can then navigate to his/her notifications when he/she is ready. [0031] Below, FIGS. 1A-1B, 2, and 3 provide a description of example devices. FIGS. 5A-5BM illustrate example user interfaces for providing alerts (e.g., notifications) and adjusting alert settings on a device. FIGS. 6A-6E are flow diagrams illustrating a method of adjusting alert settings on an electronic device. FIGS. 7A-7C are flow diagrams illustrating a method of providing alerts (e.g., notifications) on an electronic device. FIGS. 8A-8E are flow diagrams illustrating a method of activating a reduced notification mode (e.g., a “do-not-disturb” mode) of an electronic device. FIGS. 9A-9D are flow diagrams illustrating a method of deactivating a first mode. The user interfaces in FIGS. 5A-5BM are used to illustrate the processes in FIGS. 6A-6E, 7A-7C, 8A-8E, and 9A-9D.

Example Devices

[0032] Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the various described embodiments.

However, it will be apparent to one of ordinary skill in the art that the various described embodiments may be practiced without these specific details. In other instances, well-known methods, procedures, components, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the embodiments.

[0033] It will also be understood that, although the terms first, second, etc. are, in some instances, used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first contact could be termed a second contact, and, similarly, a second contact could be termed a first contact, without departing from the scope of the various described embodiments. The first contact and the second contact are both contacts, but they are not the same contact, unless the context clearly indicates otherwise.

[0034] The terminology used in the description of the various described embodiments herein is for the purpose of describing particular embodiments only and is not intended to be limiting. As used in the description of the various described embodiments and the appended claims, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0035] As used herein, the term “if” is, optionally, construed to mean “when” or “upon” or “in response to determining” or “in response to detecting,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” is, optionally, construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event],” depending on the context.

[0036] Embodiments of electronic devices, user interfaces for such devices, and associated processes for using such devices are described. In some embodiments, the device is a portable communications device, such as a mobile telephone, that also contains other functions, such as PDA and/or music player functions. Example embodiments of portable multifunction devices include, without limitation, the iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, California. Other portable electronic devices, such as laptops or tablet computers with touch-sensitive surfaces (e.g., touch screen displays and/or touchpads), are, optionally, used. It

should also be understood that, in some embodiments, the device is not a portable communications device, but is a desktop computer with a touch-sensitive surface (e.g., a touch screen display and/or a touchpad).

[0037] In the discussion that follows, an electronic device that includes a display and a touch-sensitive surface is described. It should be understood, however, that the electronic device optionally includes one or more other physical user-interface devices, such as a physical keyboard, a mouse and/or a joystick.

[0038] The device typically supports a variety of applications, such as one or more of the following: a note taking application, a drawing application, a presentation application, a word processing application, a website creation application, a disk authoring application, a spreadsheet application, a gaming application, a telephone application, a video conferencing application, an e-mail application, an instant messaging application, a workout support application, a photo management application, a digital camera application, a digital video camera application, a web browsing application, a digital music player application, and/or a digital video player application.

[0039] The various applications that are executed on the device optionally use at least one common physical user-interface device, such as the touch-sensitive surface. One or more functions of the touch-sensitive surface as well as corresponding information displayed on the device are, optionally, adjusted and/or varied from one application to the next and/or within a respective application. In this way, a common physical architecture (such as the touch-sensitive surface) of the device optionally supports the variety of applications with user interfaces that are intuitive and transparent to the user.

[0040] Attention is now directed toward embodiments of portable devices with touch-sensitive displays. FIG. 1A is a block diagram illustrating portable multifunction device **100** with touch-sensitive display system **112** in accordance with some embodiments. Touch-sensitive display system **112** is sometimes called a “touch screen” for convenience, and is sometimes simply called a touch-sensitive display. Device **100** includes memory **102** (which optionally includes one or more computer readable storage mediums), memory controller **122**, one or more processing units (CPUs) **120**, peripherals interface **118**, RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, input/output (I/O) subsystem **106**, other input or control devices **116**, and external port **124**. Device **100** optionally includes one or more optical sensors **164**. Device **100** optionally includes one or more intensity sensors **165** for detecting intensities of contacts on device **100** (e.g., a touch-sensitive surface such as touch-sensitive display system **112** of device **100**). Device **100** optionally includes one or more tactile output generators **167** for generating tactile outputs on device **100** (e.g., generating tactile outputs on a touch-sensitive surface such as touch-sensitive display system **112** of device **100** or touchpad **355** of device **300**). These components optionally communicate over one or more communication buses or signal lines **103**.

[0041] It should be appreciated that device **100** is only one example of a portable multifunction device, and that device **100** optionally has more or fewer components than shown, optionally combines two or more components, or optionally has a different configuration or arrangement of the components. The various components shown in FIG. 1A are implemented in hardware, software, firmware, or a combination thereof, including one or more signal processing and/or application specific integrated circuits.

[0042] Memory **102** optionally includes high-speed random access memory and optionally also includes non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Access to memory **102** by other components of device **100**, such as CPU(s) **120** and the peripherals interface **118**, is, optionally, controlled by memory controller **122**.

[0043] Peripherals interface **118** can be used to couple input and output peripherals of the device to CPU(s) **120** and memory **102**. The one or more processors **120** run or execute various software programs and/or sets of instructions stored in memory **102** to perform various functions for device

100 and to process data.

[0044] In some embodiments, peripherals interface **118**, CPU(s) **120**, and memory controller **122** are, optionally, implemented on a single chip, such as chip **104**. In some other embodiments, they are, optionally, implemented on separate chips.

[0045] RF (radio frequency) circuitry **108** receives and sends RF signals, also called electromagnetic signals. RF circuitry **108** converts electrical signals to/from electromagnetic signals and communicates with communications networks and other communications devices via the electromagnetic signals. RF circuitry **108** optionally includes well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth. RF circuitry **108** optionally communicates with networks, such as the Internet, also referred to as the World Wide Web (WWW), an intranet and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN) and/or a metropolitan area network (MAN), and other devices by wireless communication. The wireless communication optionally uses any of a plurality of communications standards, protocols and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), high-speed uplink packet access (HSUPA), Evolution, Data-Only (EV-DO), HSPA, HSPA+, Dual-Cell HSPA (DC-HSPA), long term evolution (LTE), near field communication (NFC), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g and/or IEEE 802.11n), voice over Internet Protocol (VOIP), Wi-MAX, a protocol for e-mail (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

[0046] Audio circuitry **110**, speaker **111**, and microphone **113** provide an audio interface between a user and device **100**. Audio circuitry **110** receives audio data from peripherals interface **118**, converts the audio data to an electrical signal, and transmits the electrical signal to speaker **111**. Speaker **111** converts the electrical signal to human-audible sound waves. Audio circuitry **110** also receives electrical signals converted by microphone **113** from sound waves. Audio circuitry **110** converts the electrical signal to audio data and transmits the audio data to peripherals interface **118** for processing. Audio data is, optionally, retrieved from and/or transmitted to memory **102** and/or RF circuitry **108** by peripherals interface **118**. In some embodiments, audio circuitry **110** also includes a headset jack (e.g., **212**, FIG. 2). The headset jack provides an interface between audio circuitry **110** and removable audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

[0047] I/O subsystem **106** couples input/output peripherals on device **100**, such as touch-sensitive display system **112** and other input or control devices **116**, with peripherals interface **118**. I/O subsystem **106** optionally includes display controller **156**, optical sensor controller **158**, intensity sensor controller **159**, haptic feedback controller **161**, and one or more input controllers **160** for other input or control devices. The one or more input controllers **160** receive/send electrical signals from/to other input or control devices **116**. The other input or control devices **116** optionally include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, joysticks, click wheels, and so forth. In some alternate embodiments, input controller(s) **160** are, optionally, coupled with any (or none) of the following: a keyboard, infrared port, USB port, stylus, and/or a pointer device such as a mouse. The one or more buttons (e.g., **208**, FIG. 2) optionally include an

up/down button for volume control of speaker **111** and/or microphone **113**. The one or more buttons optionally include a push button (e.g., **206**, FIG. 2).

[0048] Touch-sensitive display system **112** provides an input interface and an output interface between the device and a user. Display controller **156** receives and/or sends electrical signals from/to touch-sensitive display system **112**. Touch-sensitive display system **112** displays visual output to the user. The visual output optionally includes graphics, text, icons, video, and any combination thereof (collectively termed “graphics”). In some embodiments, some or all of the visual output corresponds to user interface objects. As used herein, the term “affordance” refers to a user-interactive graphical user interface object (e.g., a graphical user interface object that is configured to respond to inputs directed toward the graphical user interface object). Examples of user-interactive graphical user interface objects include, without limitation, a button, slider, icon, selectable menu item, switch, hyperlink, or other user interface control.

[0049] Touch-sensitive display system **112** has a touch-sensitive surface, sensor or set of sensors that accepts input from the user based on haptic and/or tactile contact. Touch-sensitive display system **112** and display controller **156** (along with any associated modules and/or sets of instructions in memory **102**) detect contact (and any movement or breaking of the contact) on touch-sensitive display system **112** and converts the detected contact into interaction with user-interface objects (e.g., one or more soft keys, icons, web pages or images) that are displayed on touch-sensitive display system **112**. In some embodiments, a point of contact between touch-sensitive display system **112** and the user corresponds to a finger of the user or a stylus.

[0050] Touch-sensitive display system **112** optionally uses LCD (liquid crystal display) technology, LPD (light emitting polymer display) technology, or LED (light emitting diode) technology, although other display technologies are used in other embodiments. Touch-sensitive display system **112** and display controller **156** optionally detect contact and any movement or breaking thereof using any of a plurality of touch sensing technologies now known or later developed, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with touch-sensitive display system **112**. In some embodiments, projected mutual capacitance sensing technology is used, such as that found in the iPhone®, iPod Touch®, and iPad® from Apple Inc. of Cupertino, California.

[0051] Touch-sensitive display system **112** optionally has a video resolution in excess of 100 dpi. In some embodiments, the touch screen video resolution is in excess of 400 dpi (e.g., 500 dpi, 800 dpi, or greater). The user optionally makes contact with touch-sensitive display system **112** using any suitable object or appendage, such as a stylus, a finger, and so forth. In some embodiments, the user interface is designed to work with finger-based contacts and gestures, which can be less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions desired by the user.

[0052] In some embodiments, in addition to the touch screen, device **100** optionally includes a touchpad for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad is, optionally, a touch-sensitive surface that is separate from touch-sensitive display system **112** or an extension of the touch-sensitive surface formed by the touch screen.

[0053] Device **100** also includes power system **162** for powering the various components. Power system **162** optionally includes a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

[0054] Device **100** optionally also includes one or more optical sensors **164**. FIG. 1A shows an

optical sensor coupled with optical sensor controller **158** in I/O subsystem **106**. Optical sensor(s) **164** optionally include charge-coupled device (CCD) or complementary metal-oxide semiconductor (CMOS) phototransistors. Optical sensor(s) **164** receive light from the environment, projected through one or more lens, and converts the light to data representing an image. In conjunction with imaging module **143** (also called a camera module), optical sensor(s) **164** optionally capture still images and/or video. In some embodiments, an optical sensor is located on the back of device **100**, opposite touch-sensitive display system **112** on the front of the device, so that the touch screen is enabled for use as a viewfinder for still and/or video image acquisition. In some embodiments, another optical sensor is located on the front of the device so that the user's image is obtained (e.g., for selfies, for videoconferencing while the user views the other video conference participants on the touch screen, etc.).

[0055] Device **100** optionally also includes one or more contact intensity sensors **165**. FIG. **1A** shows a contact intensity sensor coupled with intensity sensor controller **159** in I/O subsystem **106**. Contact intensity sensor(s) **165** optionally include one or more piezoresistive strain gauges, capacitive force sensors, electric force sensors, piezoelectric force sensors, optical force sensors, capacitive touch-sensitive surfaces, or other intensity sensors (e.g., sensors used to measure the force (or pressure) of a contact on a touch-sensitive surface). Contact intensity sensor(s) **165** receive contact intensity information (e.g., pressure information or a proxy for pressure information) from the environment. In some embodiments, at least one contact intensity sensor is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **112**). In some embodiments, at least one contact intensity sensor is located on the back of device **100**, opposite touch screen display system **112** which is located on the front of device **100**.

[0056] Device **100** optionally also includes one or more proximity sensors **166**. FIG. **1A** shows proximity sensor **166** coupled with peripherals interface **118**. Alternately, proximity sensor **166** is coupled with input controller **160** in I/O subsystem **106**. In some embodiments, the proximity sensor turns off and disables touch-sensitive display system **112** when the multifunction device is placed near the user's ear (e.g., when the user is making a phone call).

[0057] Device **100** optionally also includes one or more tactile output generators **167**. FIG. **1A** shows a tactile output generator coupled with haptic feedback controller **161** in I/O subsystem **106**. In some embodiments, tactile output generator(s) **167** include one or more electroacoustic devices such as speakers or other audio components and/or electromechanical devices that convert energy into linear motion such as a motor, solenoid, electroactive polymer, piezoelectric actuator, electrostatic actuator, or other tactile output generating component (e.g., a component that converts electrical signals into tactile outputs on the device). Tactile output generator(s) **167** receive tactile feedback generation instructions from haptic feedback module **133** and generates tactile outputs on device **100** that are capable of being sensed by a user of device **100**. In some embodiments, at least one tactile output generator is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **112**) and, optionally, generates a tactile output by moving the touch-sensitive surface vertically (e.g., in/out of a surface of device **100**) or laterally (e.g., back and forth in the same plane as a surface of device **100**). In some embodiments, at least one tactile output generator sensor is located on the back of device **100**, opposite touch-sensitive display system **112**, which is located on the front of device **100**.

[0058] Device **100** optionally also includes one or more accelerometers **168**. FIG. **1A** shows accelerometer **168** coupled with peripherals interface **118**. Alternately, accelerometer **168** is, optionally, coupled with an input controller **160** in I/O subsystem **106**. In some embodiments, information is displayed on the touch screen display in a portrait view or a landscape view based on an analysis of data received from the one or more accelerometers. Device **100** optionally includes, in addition to accelerometer(s) **168**, a magnetometer and a GPS (or GLONASS or other global navigation system) receiver for obtaining information concerning the location and orientation (e.g., portrait or landscape) of device **100**.

[0059] In some embodiments, the software components stored in memory **102** include operating system **126**, communication module (or set of instructions) **128**, contact/motion module (or set of instructions) **130**, graphics module (or set of instructions) **132**, haptic feedback module (or set of instructions) **133**, text input module (or set of instructions) **134**, Global Positioning System (GPS) module (or set of instructions) **135**, and applications (or sets of instructions) **136**. Furthermore, in some embodiments, memory **102** stores device/global internal state **157**, as shown in FIGS. **1A** and **3**. Device/global internal state **157** includes one or more of: active application state, indicating which applications, if any, are currently active; display state, indicating what applications, views or other information occupy various regions of touch-sensitive display system **112**; sensor state, including information obtained from the device's various sensors and other input or control devices **116**; and location and/or positional information concerning the device's location and/or attitude.

[0060] Operating system **126** (e.g., iOS, Darwin, RTXC, LINUX, UNIX, OS X, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

[0061] Communication module **128** facilitates communication with other devices over one or more external ports **124** and also includes various software components for handling data received by RF circuitry **108** and/or external port **124**. External port **124** (e.g., Universal Serial Bus (USB), FIREWIRE, etc.) is adapted for coupling directly to other devices or indirectly over a network (e.g., the Internet, wireless LAN, etc.). In some embodiments, the external port is a multi-pin (e.g., 30-pin) connector that is the same as, or similar to and/or compatible with the 30-pin connector used in some iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, California. In some embodiments, the external port is a Lightning connector that is the same as, or similar to and/or compatible with the Lightning connector used in some iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, California.

[0062] Contact/motion module **130** optionally detects contact with touch-sensitive display system **112** (in conjunction with display controller **156**) and other touch-sensitive devices (e.g., a touchpad or physical click wheel). Contact/motion module **130** includes various software components for performing various operations related to detection of contact (e.g., by a finger or by a stylus), such as determining if contact has occurred (e.g., detecting a finger-down event), determining an intensity of the contact (e.g., the force or pressure of the contact or a substitute for the force or pressure of the contact), determining if there is movement of the contact and tracking the movement across the touch-sensitive surface (e.g., detecting one or more finger-dragging events), and determining if the contact has ceased (e.g., detecting a finger-up event or a break in contact). Contact/motion module **130** receives contact data from the touch-sensitive surface. Determining movement of the point of contact, which is represented by a series of contact data, optionally includes determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change in magnitude and/or direction) of the point of contact. These operations are, optionally, applied to single contacts (e.g., one finger contacts or stylus contacts) or to multiple simultaneous contacts (e.g., "multitouch"/multiple finger contacts). In some embodiments, contact/motion module **130** and display controller **156** detect contact on a touchpad.

[0063] Contact/motion module **130** optionally detects a gesture input by a user. Different gestures on the touch-sensitive surface have different contact patterns (e.g., different motions, timings, and/or intensities of detected contacts). Thus, a gesture is, optionally, detected by detecting a particular contact pattern. For example, detecting a finger tap gesture includes detecting a finger-down event followed by detecting a finger-up (lift off) event at the same position (or substantially the same position) as the finger-down event (e.g., at the position of an icon). As another example, detecting a finger swipe gesture on the touch-sensitive surface includes detecting a finger-down event followed by detecting one or more finger-dragging events, and subsequently followed by

detecting a finger-up (lift off) event. Similarly, tap, swipe, drag, and other gestures are optionally detected for a stylus by detecting a particular contact pattern for the stylus.

[0064] In some embodiments, detecting a finger tap gesture depends on the length of time between detecting the finger-down event and the finger-up event, but is independent of the intensity of the finger contact between detecting the finger-down event and the finger-up event. In some embodiments, a tap gesture is detected in accordance with a determination that the length of time between the finger-down event and the finger-up event is less than a predetermined value (e.g., less than 0.1, 0.2, 0.3, 0.4 or 0.5 seconds), independent of whether the intensity of the finger contact during the tap meets a given intensity threshold (greater than a nominal contact-detection intensity threshold), such as a light press or deep press intensity threshold. Thus, a finger tap gesture can satisfy particular input criteria that do not require that the characteristic intensity of a contact satisfy a given intensity threshold in order for the particular input criteria to be met. For clarity, the finger contact in a tap gesture typically needs to satisfy a nominal contact-detection intensity threshold, below which the contact is not detected, in order for the finger-down event to be detected. A similar analysis applies to detecting a tap gesture by a stylus or other contact. In cases where the device is capable of detecting a finger or stylus contact hovering over a touch sensitive surface, the nominal contact-detection intensity threshold optionally does not correspond to physical contact between the finger or stylus and the touch sensitive surface.

[0065] The same concepts apply in an analogous manner to other types of gestures. For example, a swipe gesture, a pinch gesture, a depinch gesture, and/or a long press gesture are optionally detected based on the satisfaction of criteria that are either independent of intensities of contacts included in the gesture, or do not require that contact(s) that perform the gesture reach intensity thresholds in order to be recognized. For example, a swipe gesture is detected based on an amount of movement of one or more contacts; a pinch gesture is detected based on movement of two or more contacts towards each other; a depinch gesture is detected based on movement of two or more contacts away from each other; and a long press gesture is detected based on a duration of the contact on the touch-sensitive surface with less than a threshold amount of movement. As such, the statement that particular gesture recognition criteria do not require that the intensity of the contact(s) meet a respective intensity threshold in order for the particular gesture recognition criteria to be met means that the particular gesture recognition criteria are capable of being satisfied if the contact(s) in the gesture do not reach the respective intensity threshold, and are also capable of being satisfied in circumstances where one or more of the contacts in the gesture do reach or exceed the respective intensity threshold. In some embodiments, a tap gesture is detected based on a determination that the finger-down and finger-up event are detected within a predefined time period, without regard to whether the contact is above or below the respective intensity threshold during the predefined time period, and a swipe gesture is detected based on a determination that the contact movement is greater than a predefined magnitude, even if the contact is above the respective intensity threshold at the end of the contact movement. Even in implementations where detection of a gesture is influenced by the intensity of contacts performing the gesture (e.g., the device detects a long press more quickly when the intensity of the contact is above an intensity threshold or delays detection of a tap input when the intensity of the contact is higher), the detection of those gestures does not require that the contacts reach a particular intensity threshold so long as the criteria for recognizing the gesture can be met in circumstances where the contact does not reach the particular intensity threshold (e.g., even if the amount of time that it takes to recognize the gesture changes).

[0066] Contact intensity thresholds, duration thresholds, and movement thresholds are, in some circumstances, combined in a variety of different combinations in order to create heuristics for distinguishing two or more different gestures directed to the same input element or region so that multiple different interactions with the same input element are enabled to provide a richer set of user interactions and responses. The statement that a particular set of gesture recognition criteria do

not require that the intensity of the contact(s) meet a respective intensity threshold in order for the particular gesture recognition criteria to be met does not preclude the concurrent evaluation of other intensity-dependent gesture recognition criteria to identify other gestures that do have criteria that are met when a gesture includes a contact with an intensity above the respective intensity threshold. For example, in some circumstances, first gesture recognition criteria for a first gesture—which do not require that the intensity of the contact(s) meet a respective intensity threshold in order for the first gesture recognition criteria to be met—are in competition with second gesture recognition criteria for a second gesture—which are dependent on the contact(s) reaching the respective intensity threshold. In such competitions, the gesture is, optionally, not recognized as meeting the first gesture recognition criteria for the first gesture if the second gesture recognition criteria for the second gesture are met first. For example, if a contact reaches the respective intensity threshold before the contact moves by a predefined amount of movement, a deep press gesture is detected rather than a swipe gesture. Conversely, if the contact moves by the predefined amount of movement before the contact reaches the respective intensity threshold, a swipe gesture is detected rather than a deep press gesture. Even in such circumstances, the first gesture recognition criteria for the first gesture still do not require that the intensity of the contact(s) meet a respective intensity threshold in order for the first gesture recognition criteria to be met because if the contact stayed below the respective intensity threshold until an end of the gesture (e.g., a swipe gesture with a contact that does not increase to an intensity above the respective intensity threshold), the gesture would have been recognized by the first gesture recognition criteria as a swipe gesture. As such, particular gesture recognition criteria that do not require that the intensity of the contact(s) meet a respective intensity threshold in order for the particular gesture recognition criteria to be met will (A) in some circumstances ignore the intensity of the contact with respect to the intensity threshold (e.g. for a tap gesture) and/or (B) in some circumstances still be dependent on the intensity of the contact with respect to the intensity threshold in the sense that the particular gesture recognition criteria (e.g., for a long press gesture) will fail if a competing set of intensity-dependent gesture recognition criteria (e.g., for a deep press gesture) recognize an input as corresponding to an intensity-dependent gesture before the particular gesture recognition criteria recognize a gesture corresponding to the input (e.g., for a long press gesture that is competing with a deep press gesture for recognition).

[0067] Graphics module **132** includes various known software components for rendering and displaying graphics on touch-sensitive display system **112** or other display, including components for changing the visual impact (e.g., brightness, transparency, saturation, contrast or other visual property) of graphics that are displayed. As used herein, the term “graphics” includes any object that can be displayed to a user, including without limitation text, web pages, icons (such as user-interface objects including soft keys), digital images, videos, animations and the like.

[0068] In some embodiments, graphics module **132** stores data representing graphics to be used. Each graphic is, optionally, assigned a corresponding code. Graphics module **132** receives, from applications etc., one or more codes specifying graphics to be displayed along with, if necessary, coordinate data and other graphic property data, and then generates screen image data to output to display controller **156**.

[0069] Haptic feedback module **133** includes various software components for generating instructions (e.g., instructions used by haptic feedback controller **161**) to produce tactile outputs using tactile output generator(s) **167** at one or more locations on device **100** in response to user interactions with device **100**.

[0070] Text input module **134**, which is, optionally, a component of graphics module **132**, provides soft keyboards for entering text in various applications (e.g., contacts module **137**, e-mail client module **140**, IM module **141**, browser module **147**, and any other application that needs text input).

[0071] GPS module **135** determines the location of the device and provides this information for use in various applications (e.g., to telephone module **138** for use in location-based dialing, to camera

module **143** as picture/video metadata, and to applications that provide location-based services such as weather widgets, local yellow page widgets, and map/navigation widgets).

[0072] Applications **136** optionally include the following modules (or sets of instructions), or a subset or superset thereof: [0073] contacts module **137** (sometimes called an address book or contact list); [0074] telephone module **138**; [0075] video conferencing module **139**; [0076] e-mail client module **140**; [0077] instant messaging (IM) module **141**; [0078] workout support module **142**; [0079] camera module **143** for still and/or video images; [0080] image management module **144**; [0081] browser module **147**; [0082] calendar module **148**; [0083] widget modules **149**, which optionally include one or more of: weather widget **149-1**, stocks widget **149-2**, calculator widget **149-3**, alarm clock widget **149-4**, dictionary widget **149-5**, and other widgets obtained by the user, as well as user-created widgets **149-6**; [0084] widget creator module **150** for making user-created widgets **149-6**; [0085] search module **151**; [0086] video and music player module **152**, which is, optionally, made up of a video player module and a music player module; [0087] notes module **153**; [0088] map module **154**; and/or [0089] online video module **155**.

[0090] Examples of other applications **136** that are, optionally, stored in memory **102** include other word processing applications, other image editing applications, drawing applications, presentation applications, JAVA-enabled applications, encryption, digital rights management, voice recognition, and voice replication.

[0091] In conjunction with touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, contacts module **137** includes executable instructions to manage an address book or contact list (e.g., stored in application internal state **192** of contacts module **137** in memory **102** or memory **370**), including: adding name(s) to the address book; deleting name(s) from the address book; associating telephone number(s), e-mail address(es), physical address(es) or other information with a name; associating an image with a name; categorizing and sorting names; providing telephone numbers and/or e-mail addresses to initiate and/or facilitate communications by telephone module **138**, video conference module **139**, e-mail client module **140**, or IM module **141**; and so forth.

[0092] In conjunction with RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, telephone module **138** includes executable instructions to enter a sequence of characters corresponding to a telephone number, access one or more telephone numbers in address book **137**, modify a telephone number that has been entered, dial a respective telephone number, conduct a conversation and disconnect or hang up when the conversation is completed. As noted above, the wireless communication optionally uses any of a plurality of communications standards, protocols and technologies.

[0093] In conjunction with RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, touch-sensitive display system **112**, display controller **156**, optical sensor(s) **164**, optical sensor controller **158**, contact module **130**, graphics module **132**, text input module **134**, contact list **137**, and telephone module **138**, videoconferencing module **139** includes executable instructions to initiate, conduct, and terminate a video conference between a user and one or more other participants in accordance with user instructions.

[0094] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, e-mail client module **140** includes executable instructions to create, send, receive, and manage e-mail in response to user instructions. In conjunction with image management module **144**, e-mail client module **140** makes it very easy to create and send e-mails with still or video images taken with camera module **143**.

[0095] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, the instant messaging module **141** includes executable instructions to enter a sequence of characters corresponding to an instant message, to modify previously entered characters, to transmit a respective instant message

(for example, using a Short Message Service (SMS) or Multimedia Message Service (MMS) protocol for telephony-based instant messages or using XMPP, SIMPLE, Apple Push Notification Service (APNs) or IMPS for Internet-based instant messages), to receive instant messages, and to view received instant messages. In some embodiments, transmitted and/or received instant messages optionally include graphics, photos, audio files, video files and/or other attachments as are supported in a MMS and/or an Enhanced Messaging Service (EMS). As used herein, “instant messaging” refers to both telephony-based messages (e.g., messages sent using SMS or MMS) and Internet-based messages (e.g., messages sent using XMPP, SIMPLE, APNs, or IMPS).

[0096] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, text input module **134**, GPS module **135**, map module **154**, and video and music player module **152**, workout support module **142** includes executable instructions to create workouts (e.g., with time, distance, and/or calorie burning goals); communicate with workout sensors (in sports devices and smart watches); receive workout sensor data; calibrate sensors used to monitor a workout; select and play music for a workout; and display, store and transmit workout data.

[0097] In conjunction with touch-sensitive display system **112**, display controller **156**, optical sensor(s) **164**, optical sensor controller **158**, contact module **130**, graphics module **132**, and image management module **144**, camera module **143** includes executable instructions to capture still images or video (including a video stream) and store them into memory **102**, modify characteristics of a still image or video, and/or delete a still image or video from memory **102**.

[0098] In conjunction with touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, text input module **134**, and camera module **143**, image management module **144** includes executable instructions to arrange, modify (e.g., edit), or otherwise manipulate, label, delete, present (e.g., in a digital slide show or album), and store still and/or video images.

[0099] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, and text input module **134**, browser module **147** includes executable instructions to browse the Internet in accordance with user instructions, including searching, linking to, receiving, and displaying web pages or portions thereof, as well as attachments and other files linked to web pages.

[0100] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, text input module **134**, e-mail client module **140**, and browser module **147**, calendar module **148** includes executable instructions to create, display, modify, and store calendars and data associated with calendars (e.g., calendar entries, to do lists, etc.) in accordance with user instructions.

[0101] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, text input module **134**, and browser module **147**, widget modules **149** are mini-applications that are, optionally, downloaded and used by a user (e.g., weather widget **149-1**, stocks widget **149-2**, calculator widget **149-3**, alarm clock widget **149-4**, and dictionary widget **149-5**) or created by the user (e.g., user-created widget **149-6**). In some embodiments, a widget includes an HTML (Hypertext Markup Language) file, a CSS (Cascading Style Sheets) file, and a JavaScript file. In some embodiments, a widget includes an XML (Extensible Markup Language) file and a JavaScript file (e.g., Yahoo! Widgets).

[0102] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, text input module **134**, and browser module **147**, the widget creator module **150** includes executable instructions to create widgets (e.g., turning a user-specified portion of a web page into a widget).

[0103] In conjunction with touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, and text input module **134**, search module **151** includes executable instructions to search for text, music, sound, image, video, and/or other files in memory

102 that match one or more search criteria (e.g., one or more user-specified search terms) in accordance with user instructions.

[0104] In conjunction with touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, audio circuitry **110**, speaker **111**, RF circuitry **108**, and browser module **147**, video and music player module **152** includes executable instructions that allow the user to download and play back recorded music and other sound files stored in one or more file formats, such as MP3 or AAC files, and executable instructions to display, present or otherwise play back videos (e.g., on touch-sensitive display system **112**, or on an external display connected wirelessly or via external port **124**). In some embodiments, device **100** optionally includes the functionality of an MP3 player, such as an iPod (trademark of Apple Inc.).

[0105] In conjunction with touch-sensitive display system **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, notes module **153** includes executable instructions to create and manage notes, to do lists, and the like in accordance with user instructions.

[0106] In conjunction with RF circuitry **108**, touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, text input module **134**, GPS module **135**, and browser module **147**, map module **154** includes executable instructions to receive, display, modify, and store maps and data associated with maps (e.g., driving directions; data on stores and other points of interest at or near a particular location; and other location-based data) in accordance with user instructions.

[0107] In conjunction with touch-sensitive display system **112**, display system controller **156**, contact module **130**, graphics module **132**, audio circuitry **110**, speaker **111**, RF circuitry **108**, text input module **134**, e-mail client module **140**, and browser module **147**, online video module **155** includes executable instructions that allow the user to access, browse, receive (e.g., by streaming and/or download), play back (e.g., on the touch screen **112**, or on an external display connected wirelessly or via external port **124**), send an e-mail with a link to a particular online video, and otherwise manage online videos in one or more file formats, such as H.264. In some embodiments, instant messaging module **141**, rather than e-mail client module **140**, is used to send a link to a particular online video.

[0108] Each of the above identified modules and applications correspond to a set of executable instructions for performing one or more functions described above and the methods described in this application (e.g., the computer-implemented methods and other information processing methods described herein). These modules (i.e., sets of instructions) need not be implemented as separate software programs, procedures or modules, and thus various subsets of these modules are, optionally, combined or otherwise re-arranged in various embodiments. In some embodiments, memory **102** optionally stores a subset of the modules and data structures identified above. Furthermore, memory **102** optionally stores additional modules and data structures not described above.

[0109] In some embodiments, device **100** is a device where operation of a predefined set of functions on the device is performed exclusively through a touch screen and/or a touchpad. By using a touch screen and/or a touchpad as the primary input control device for operation of device **100**, the number of physical input control devices (such as push buttons, dials, and the like) on device **100** is, optionally, reduced.

[0110] The predefined set of functions that are performed exclusively through a touch screen and/or a touchpad optionally include navigation between user interfaces. In some embodiments, the touchpad, when touched by the user, navigates device **100** to a main, home, or root menu from any user interface that is displayed on device **100**. In such embodiments, a “menu button” is implemented using a touchpad. In some other embodiments, the menu button is a physical push button or other physical input control device instead of a touchpad.

[0111] FIG. **1B** is a block diagram illustrating example components for event handling in

accordance with some embodiments. In some embodiments, memory **102** (in FIG. 1A) or **370** (FIG. 3) includes event sorter **170** (e.g., in operating system **126**) and a respective application **136-1** (e.g., any of the aforementioned applications **136**, **137-155**, **380-390**).

[0112] Event sorter **170** receives event information and determines the application **136-1** and application view **191** of application **136-1** to which to deliver the event information. Event sorter **170** includes event monitor **171** and event dispatcher module **174**. In some embodiments, application **136-1** includes application internal state **192**, which indicates the current application view(s) displayed on touch-sensitive display system **112** when the application is active or executing. In some embodiments, device/global internal state **157** is used by event sorter **170** to determine which application(s) is (are) currently active, and application internal state **192** is used by event sorter **170** to determine application views **191** to which to deliver event information.

[0113] In some embodiments, application internal state **192** includes additional information, such as one or more of: resume information to be used when application **136-1** resumes execution, user interface state information that indicates information being displayed or that is ready for display by application **136-1**, a state queue for enabling the user to go back to a prior state or view of application **136-1**, and a redo/undo queue of previous actions taken by the user.

[0114] Event monitor **171** receives event information from peripherals interface **118**. Event information includes information about a sub-event (e.g., a user touch on touch-sensitive display system **112**, as part of a multi-touch gesture). Peripherals interface **118** transmits information it receives from I/O subsystem **106** or a sensor, such as proximity sensor **166**, accelerometer(s) **168**, and/or microphone **113** (through audio circuitry **110**). Information that peripherals interface **118** receives from I/O subsystem **106** includes information from touch-sensitive display system **112** or a touch-sensitive surface.

[0115] In some embodiments, event monitor **171** sends requests to the peripherals interface **118** at predetermined intervals. In response, peripherals interface **118** transmits event information. In other embodiments, peripheral interface **118** transmits event information only when there is a significant event (e.g., receiving an input above a predetermined noise threshold and/or for more than a predetermined duration).

[0116] In some embodiments, event sorter **170** also includes a hit view determination module **172** and/or an active event recognizer determination module **173**.

[0117] Hit view determination module **172** provides software procedures for determining where a sub-event has taken place within one or more views, when touch-sensitive display system **112** displays more than one view. Views are made up of controls and other elements that a user can see on the display.

[0118] Another aspect of the user interface associated with an application is a set of views, sometimes herein called application views or user interface windows, in which information is displayed and touch-based gestures occur. The application views (of a respective application) in which a touch is detected optionally correspond to programmatic levels within a programmatic or view hierarchy of the application. For example, the lowest level view in which a touch is detected is, optionally, called the hit view, and the set of events that are recognized as proper inputs are, optionally, determined based, at least in part, on the hit view of the initial touch that begins a touch-based gesture.

[0119] Hit view determination module **172** receives information related to sub-events of a touch-based gesture. When an application has multiple views organized in a hierarchy, hit view determination module **172** identifies a hit view as the lowest view in the hierarchy which should handle the sub-event. In most circumstances, the hit view is the lowest level view in which an initiating sub-event occurs (i.e., the first sub-event in the sequence of sub-events that form an event or potential event). Once the hit view is identified by the hit view determination module, the hit view typically receives all sub-events related to the same touch or input source for which it was identified as the hit view.

[0120] Active event recognizer determination module **173** determines which view or views within a view hierarchy should receive a particular sequence of sub-events. In some embodiments, active event recognizer determination module **173** determines that only the hit view should receive a particular sequence of sub-events. In other embodiments, active event recognizer determination module **173** determines that all views that include the physical location of a sub-event are actively involved views, and therefore determines that all actively involved views should receive a particular sequence of sub-events. In other embodiments, even if touch sub-events were entirely confined to the area associated with one particular view, views higher in the hierarchy would still remain as actively involved views.

[0121] Event dispatcher module **174** dispatches the event information to an event recognizer (e.g., event recognizer **180**). In embodiments including active event recognizer determination module **173**, event dispatcher module **174** delivers the event information to an event recognizer determined by active event recognizer determination module **173**. In some embodiments, event dispatcher module **174** stores in an event queue the event information, which is retrieved by a respective event receiver module **182**.

[0122] In some embodiments, operating system **126** includes event sorter **170**. Alternatively, application **136-1** includes event sorter **170**. In yet other embodiments, event sorter **170** is a stand-alone module, or a part of another module stored in memory **102**, such as contact/motion module **130**.

[0123] In some embodiments, application **136-1** includes a plurality of event handlers **190** and one or more application views **191**, each of which includes instructions for handling touch events that occur within a respective view of the application's user interface. Each application view **191** of the application **136-1** includes one or more event recognizers **180**. Typically, a respective application view **191** includes a plurality of event recognizers **180**. In other embodiments, one or more of event recognizers **180** are part of a separate module, such as a user interface kit or a higher level object from which application **136-1** inherits methods and other properties. In some embodiments, a respective event handler **190** includes one or more of: data updater **176**, object updater **177**, GUI updater **178**, and/or event data **179** received from event sorter **170**. Event handler **190** optionally utilizes or calls data updater **176**, object updater **177** or GUI updater **178** to update the application internal state **192**. Alternatively, one or more of the application views **191** includes one or more respective event handlers **190**. Also, in some embodiments, one or more of data updater **176**, object updater **177**, and GUI updater **178** are included in a respective application view **191**.

[0124] A respective event recognizer **180** receives event information (e.g., event data **179**) from event sorter **170**, and identifies an event from the event information. Event recognizer **180** includes event receiver **182** and event comparator **184**. In some embodiments, event recognizer **180** also includes at least a subset of: metadata **183**, and event delivery instructions **188** (which optionally include sub-event delivery instructions).

[0125] Event receiver **182** receives event information from event sorter **170**. The event information includes information about a sub-event, for example, a touch or a touch movement. Depending on the sub-event, the event information also includes additional information, such as location of the sub-event. When the sub-event concerns motion of a touch, the event information optionally also includes speed and direction of the sub-event. In some embodiments, events include rotation of the device from one orientation to another (e.g., from a portrait orientation to a landscape orientation, or vice versa), and the event information includes corresponding information about the current orientation (also called device attitude) of the device.

[0126] Event comparator **184** compares the event information to predefined event or sub-event definitions and, based on the comparison, determines an event or sub-event, or determines or updates the state of an event or sub-event. In some embodiments, event comparator **184** includes event definitions **186**. Event definitions **186** contain definitions of events (e.g., predefined sequences of sub-events), for example, event 1 (**187-1**), event 2 (**187-2**), and others. In some

embodiments, sub-events in an event **187** include, for example, touch begin, touch end, touch movement, touch cancellation, and multiple touching. In one example, the definition for event 1 (**187-1**) is a double tap on a displayed object. The double tap, for example, comprises a first touch (touch begin) on the displayed object for a predetermined phase, a first lift-off (touch end) for a predetermined phase, a second touch (touch begin) on the displayed object for a predetermined phase, and a second lift-off (touch end) for a predetermined phase. In another example, the definition for event 2 (**187-2**) is a dragging on a displayed object. The dragging, for example, comprises a touch (or contact) on the displayed object for a predetermined phase, a movement of the touch across touch-sensitive display system **112**, and lift-off of the touch (touch end). In some embodiments, the event also includes information for one or more associated event handlers **190**.

[0127] In some embodiments, event definition **187** includes a definition of an event for a respective user-interface object. In some embodiments, event comparator **184** performs a hit test to determine which user-interface object is associated with a sub-event. For example, in an application view in which three user-interface objects are displayed on touch-sensitive display system **112**, when a touch is detected on touch-sensitive display system **112**, event comparator **184** performs a hit test to determine which of the three user-interface objects is associated with the touch (sub-event). If each displayed object is associated with a respective event handler **190**, the event comparator uses the result of the hit test to determine which event handler **190** should be activated. For example, event comparator **184** selects an event handler associated with the sub-event and the object triggering the hit test.

[0128] In some embodiments, the definition for a respective event **187** also includes delayed actions that delay delivery of the event information until after it has been determined whether the sequence of sub-events does or does not correspond to the event recognizer's event type.

[0129] When a respective event recognizer **180** determines that the series of sub-events do not match any of the events in event definitions **186**, the respective event recognizer **180** enters an event impossible, event failed, or event ended state, after which it disregards subsequent sub-events of the touch-based gesture. In this situation, other event recognizers, if any, that remain active for the hit view continue to track and process sub-events of an ongoing touch-based gesture.

[0130] In some embodiments, a respective event recognizer **180** includes metadata **183** with configurable properties, flags, and/or lists that indicate how the event delivery system should perform sub-event delivery to actively involved event recognizers. In some embodiments, metadata **183** includes configurable properties, flags, and/or lists that indicate how event recognizers interact, or are enabled to interact, with one another. In some embodiments, metadata **183** includes configurable properties, flags, and/or lists that indicate whether sub-events are delivered to varying levels in the view or grammatic hierarchy.

[0131] In some embodiments, a respective event recognizer **180** activates event handler **190** associated with an event when one or more particular sub-events of an event are recognized. In some embodiments, a respective event recognizer **180** delivers event information associated with the event to event handler **190**. Activating an event handler **190** is distinct from sending (and deferred sending) sub-events to a respective hit view. In some embodiments, event recognizer **180** throws a flag associated with the recognized event, and event handler **190** associated with the flag catches the flag and performs a predefined process.

[0132] In some embodiments, event delivery instructions **188** include sub-event delivery instructions that deliver event information about a sub-event without activating an event handler. Instead, the sub-event delivery instructions deliver event information to event handlers associated with the series of sub-events or to actively involved views. Event handlers associated with the series of sub-events or with actively involved views receive the event information and perform a predetermined process.

[0133] In some embodiments, data updater **176** creates and updates data used in application **136-1**. For example, data updater **176** updates the telephone number used in contacts module **137**, or

stores a video file used in video and music player module **152**. In some embodiments, object updater **177** creates and updates objects used in application **136-1**. For example, object updater **177** creates a new user-interface object or updates the position of a user-interface object. GUI updater **178** updates the GUI. For example, GUI updater **178** prepares display information and sends it to graphics module **132** for display on a touch-sensitive display.

[0134] In some embodiments, event handler(s) **190** includes or has access to data updater **176**, object updater **177**, and GUI updater **178**. In some embodiments, data updater **176**, object updater **177**, and GUI updater **178** are included in a single module of a respective application **136-1** or application view **191**. In other embodiments, they are included in two or more software modules.

[0135] It shall be understood that the foregoing discussion regarding event handling of user touches on touch-sensitive displays also applies to other forms of user inputs to operate multifunction devices **100** with input-devices, not all of which are initiated on touch screens. For example, mouse movement and mouse button presses, optionally coordinated with single or multiple keyboard presses or holds; contact movements such as taps, drags, scrolls, etc., on touch-pads; pen stylus inputs; movement of the device; oral instructions; detected eye movements; biometric inputs; and/or any combination thereof are optionally utilized as inputs corresponding to sub-events which define an event to be recognized.

[0136] FIG. **2** illustrates a portable multifunction device **100** having a touch screen (e.g., touch-sensitive display system **112**, FIG. **1A**) in accordance with some embodiments. The touch screen optionally displays one or more graphics within user interface (UI) **200**. In these embodiments, as well as others described below, a user is enabled to select one or more of the graphics by making a gesture on the graphics, for example, with one or more fingers **202** (not drawn to scale in the figure) or one or more styluses **203** (not drawn to scale in the figure). In some embodiments, selection of one or more graphics occurs when the user breaks contact with the one or more graphics. In some embodiments, the gesture optionally includes one or more taps, one or more swipes (from left to right, right to left, upward and/or downward) and/or a rolling of a finger (from right to left, left to right, upward and/or downward) that has made contact with device **100**. In some implementations or circumstances, inadvertent contact with a graphic does not select the graphic. For example, a swipe gesture that sweeps over an application icon optionally does not select the corresponding application when the gesture corresponding to selection is a tap.

[0137] Device **100** optionally also includes one or more physical buttons, such as “home” or menu button **204**. As described previously, menu button **204** is, optionally, used to navigate to any application **136** in a set of applications that are, optionally executed on device **100**. Alternatively, in some embodiments, the menu button is implemented as a soft key in a GUI displayed on the touch screen display.

[0138] In some embodiments, device **100** includes the touch screen display, menu button **204** (sometimes called home button **204**), push button **206** for powering the device on/off and locking the device, volume adjustment button(s) **208**, Subscriber Identity Module (SIM) card slot **210**, head set jack **212**, and docking/charging external port **124**. Push button **206** is, optionally, used to turn the power on/off on the device by depressing the button and holding the button in the depressed state for a predefined time interval; to lock the device by depressing the button and releasing the button before the predefined time interval has elapsed; and/or to unlock the device or initiate an unlock process. In some embodiments, device **100** also accepts verbal input for activation or deactivation of some functions through microphone **113**. Device **100** also, optionally, includes one or more contact intensity sensors **165** for detecting intensities of contacts on touch-sensitive display system **112** and/or one or more tactile output generators **167** for generating tactile outputs for a user of device **100**.

[0139] FIG. **3** is a block diagram of an example multifunction device with a display and a touch-sensitive surface in accordance with some embodiments. Device **300** need not be portable. In some embodiments, device **300** is a laptop computer, a desktop computer, a tablet computer, a

multimedia player device, a navigation device, an educational device (such as a child's learning toy), a gaming system, or a control device (e.g., a home or industrial controller). Device **300** typically includes one or more processing units (CPU's) **310**, one or more network or other communications interfaces **360**, memory **370**, and one or more communication buses **320** for interconnecting these components. Communication buses **320** optionally include circuitry (sometimes called a chipset) that interconnects and controls communications between system components. Device **300** includes input/output (I/O) interface **330** comprising display **340**, which is typically a touch screen display. I/O interface **330** also optionally includes a keyboard and/or mouse (or other pointing device) **350** and touchpad **355**, tactile output generator **357** for generating tactile outputs on device **300** (e.g., similar to tactile output generator(s) **167** described above with reference to FIG. **1A**), sensors **359** (e.g., optical, acceleration, proximity, touch-sensitive, and/or contact intensity sensors similar to contact intensity sensor(s) **165** described above with reference to FIG. **1A**). Memory **370** includes high-speed random access memory, such as DRAM, SRAM, DDR RAM or other random access solid state memory devices; and optionally includes non-volatile memory, such as one or more magnetic disk storage devices, optical disk storage devices, flash memory devices, or other non-volatile solid state storage devices. Memory **370** optionally includes one or more storage devices remotely located from CPU(s) **310**. In some embodiments, memory **370** stores programs, modules, and data structures analogous to the programs, modules, and data structures stored in memory **102** of portable multifunction device **100** (FIG. **1A**), or a subset thereof. Furthermore, memory **370** optionally stores additional programs, modules, and data structures not present in memory **102** of portable multifunction device **100**. For example, memory **370** of device **300** optionally stores drawing module **380**, presentation module **382**, word processing module **384**, website creation module **386**, disk authoring module **388**, and/or spreadsheet module **390**, while memory **102** of portable multifunction device **100** (FIG. **1A**) optionally does not store these modules.

[0140] Each of the above identified elements in FIG. **3** are, optionally, stored in one or more of the previously mentioned memory devices. Each of the above identified modules corresponds to a set of instructions for performing a function described above. The above identified modules or programs (i.e., sets of instructions) need not be implemented as separate software programs, procedures or modules, and thus various subsets of these modules are, optionally, combined or otherwise re-arranged in various embodiments. In some embodiments, memory **370** optionally stores a subset of the modules and data structures identified above. Furthermore, memory **370** optionally stores additional modules and data structures not described above.

[0141] Attention is now directed towards embodiments of user interfaces ("UI") that are, optionally, implemented on portable multifunction device **100**.

[0142] FIG. **4A** illustrates an example user interface **400** for a menu of applications on portable multifunction device **100** in accordance with some embodiments. Similar user interfaces are, optionally, implemented on device **300**. In some embodiments, user interface **400** includes the following elements, or a subset or superset thereof: [0143] Signal strength indicator(s) for wireless communication(s), such as cellular and Wi-Fi signals; [0144] Time; [0145] a Bluetooth indicator; [0146] a Battery status indicator; [0147] Tray **408** with icons for frequently used applications, such as: [0148] Icon **416** for telephone module **138**, labeled "Phone," which optionally includes an indicator **414** of the number of missed calls or voicemail messages; [0149] Icon **418** for e-mail client module **140**, labeled "Mail," which optionally includes an indicator **410** of the number of unread e-mails; [0150] Icon **420** for browser module **147**, labeled "Browser;" and [0151] Icon **422** for video and music player module **152**, labeled "Music;" and [0152] Icons for other applications, such as: [0153] Icon **424** for IM module **141**, labeled "Messages;" [0154] Icon **426** for calendar module **148**, labeled "Calendar;" [0155] Icon **428** for image management module **144**, labeled "Photos;" [0156] Icon **430** for camera module **143**, labeled "Camera;" [0157] Icon **432** for online video module **155**, labeled "Online Video;" [0158] Icon **434** for stocks widget **149-2**, labeled

“Stocks;” [0159] Icon **436** for map module **154**, labeled “Maps;” [0160] Icon **438** for weather widget **149-1**, labeled “Weather;” [0161] Icon **440** for alarm clock widget **149-4**, labeled “Clock;” [0162] Icon **442** for workout support module **142**, labeled “Workout Support;” [0163] Icon **444** for notes module **153**, labeled “Notes;” and [0164] Icon **446** for a settings application or module, which provides access to settings for device **100** and its various applications **136**.

[0165] It should be noted that the icon labels illustrated in FIG. **4A** are merely examples. For example, other labels are, optionally, used for various application icons. In some embodiments, a label for a respective application icon includes a name of an application corresponding to the respective application icon. In some embodiments, a label for a particular application icon is distinct from a name of an application corresponding to the particular application icon.

[0166] FIG. **4B** illustrates an example user interface on a device (e.g., device **300**, FIG. **3**) with a touch-sensitive surface **451** (e.g., a tablet or touchpad **355**, FIG. **3**) that is separate from the display **450**. Although many of the examples that follow will be given with reference to inputs on touch screen display **112** (where the touch sensitive surface and the display are combined), in some embodiments, the device detects inputs on a touch-sensitive surface that is separate from the display, as shown in FIG. **4B**. In some embodiments, the touch-sensitive surface (e.g., **451** in FIG. **4B**) has a primary axis (e.g., **452** in FIG. **4B**) that corresponds to a primary axis (e.g., **453** in FIG. **4B**) on the display (e.g., **450**). In accordance with these embodiments, the device detects contacts (e.g., **460** and **462** in FIG. **4B**) with the touch-sensitive surface **451** at locations that correspond to respective locations on the display (e.g., in FIG. **4B**, contact **460** corresponds to **468** and contact **462** corresponds to **470**). In this way, user inputs (e.g., contacts **460** and **462**, and movements thereof) detected by the device on the touch-sensitive surface (e.g., **451** in FIG. **4B**) are used by the device to manipulate the user interface on the display (e.g., **450** in FIG. **4B**) of the multifunction device when the touch-sensitive surface is separate from the display. It should be understood that similar methods are, optionally, used for other user interfaces described herein.

[0167] Additionally, while the following examples are given primarily with reference to finger inputs (e.g., finger contacts, finger tap gestures, finger swipe gestures, etc.), it should be understood that, in some embodiments, one or more of the finger inputs are replaced with input from another input device (e.g., a mouse based input or a stylus input). For example, a swipe gesture is, optionally, replaced with a mouse click (e.g., instead of a contact) followed by movement of the cursor along the path of the swipe (e.g., instead of movement of the contact). As another example, a tap gesture is, optionally, replaced with a mouse click while the cursor is located over the location of the tap gesture (e.g., instead of detection of the contact followed by ceasing to detect the contact). Similarly, when multiple user inputs are simultaneously detected, it should be understood that multiple computer mice are, optionally, used simultaneously, or a mouse and finger contacts are, optionally, used simultaneously.

[0168] As used herein, the term “focus selector” refers to an input element that indicates a current part of a user interface with which a user is interacting. In some implementations that include a cursor or other location marker, the cursor acts as a “focus selector,” so that when an input (e.g., a press input) is detected on a touch-sensitive surface (e.g., touchpad **355** in FIG. **3** or touch-sensitive surface **451** in FIG. **4B**) while the cursor is over a particular user interface element (e.g., a button, window, slider or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations that include a touch screen display (e.g., touch-sensitive display system **112** in FIG. **1A** or the touch screen in FIG. **4A**) that enables direct interaction with user interface elements on the touch screen display, a detected contact on the touch screen acts as a “focus selector,” so that when an input (e.g., a press input by the contact) is detected on the touch screen display at a location of a particular user interface element (e.g., a button, window, slider or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations, focus is moved from one region of a user interface to another region of the user interface without corresponding movement

of a cursor or movement of a contact on a touch screen display (e.g., by using a tab key or arrow keys to move focus from one button to another button); in these implementations, the focus selector moves in accordance with movement of focus between different regions of the user interface. Without regard to the specific form taken by the focus selector, the focus selector is generally the user interface element (or contact on a touch screen display) that is controlled by the user so as to communicate the user's intended interaction with the user interface (e.g., by indicating, to the device, the element of the user interface with which the user is intending to interact). For example, the location of a focus selector (e.g., a cursor, a contact, or a selection box) over a respective button while a press input is detected on the touch-sensitive surface (e.g., a touchpad or touch screen) will indicate that the user is intending to activate the respective button (as opposed to other user interface elements shown on a display of the device).

[0169] As used in the specification and claims, the term “intensity” of a contact on a touch-sensitive surface refers to the force or pressure (force per unit area) of a contact (e.g., a finger contact or a stylus contact) on the touch-sensitive surface, or to a substitute (proxy) for the force or pressure of a contact on the touch-sensitive surface. The intensity of a contact has a range of values that includes at least four distinct values and more typically includes hundreds of distinct values (e.g., at least 256). Intensity of a contact is, optionally, determined (or measured) using various approaches and various sensors or combinations of sensors. For example, one or more force sensors underneath or adjacent to the touch-sensitive surface are, optionally, used to measure force at various points on the touch-sensitive surface. In some implementations, force measurements from multiple force sensors are combined (e.g., a weighted average or a sum) to determine an estimated force of a contact. Similarly, a pressure-sensitive tip of a stylus is, optionally, used to determine a pressure of the stylus on the touch-sensitive surface. Alternatively, the size of the contact area detected on the touch-sensitive surface and/or changes thereto, the capacitance of the touch-sensitive surface proximate to the contact and/or changes thereto, and/or the resistance of the touch-sensitive surface proximate to the contact and/or changes thereto are, optionally, used as a substitute for the force or pressure of the contact on the touch-sensitive surface. In some implementations, the substitute measurements for contact force or pressure are used directly to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is described in units corresponding to the substitute measurements). In some implementations, the substitute measurements for contact force or pressure are converted to an estimated force or pressure and the estimated force or pressure is used to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is a pressure threshold measured in units of pressure). Using the intensity of a contact as an attribute of a user input allows for user access to additional device functionality that may otherwise not be readily accessible by the user on a reduced-size device with limited real estate for displaying affordances (e.g., on a touch-sensitive display) and/or receiving user input (e.g., via a touch-sensitive display, a touch-sensitive surface, or a physical/mechanical control such as a knob or a button).

[0170] In some embodiments, contact/motion module **130** uses a set of one or more intensity thresholds to determine whether an operation has been performed by a user (e.g., to determine whether a user has “clicked” on an icon). In some embodiments, at least a subset of the intensity thresholds is determined in accordance with software parameters (e.g., the intensity thresholds are not determined by the activation thresholds of particular physical actuators and can be adjusted without changing the physical hardware of device **100**). For example, a mouse “click” threshold of a trackpad or touch screen display can be set to any of a large range of predefined thresholds values without changing the trackpad or touch screen display hardware. Additionally, in some implementations a user of the device is provided with software settings for adjusting one or more of the set of intensity thresholds (e.g., by adjusting individual intensity thresholds and/or by adjusting a plurality of intensity thresholds at once with a system-level click “intensity” parameter).

[0171] As used in the specification and claims, the term “characteristic intensity” of a contact refers

to a characteristic of the contact based on one or more intensities of the contact. In some embodiments, the characteristic intensity is based on multiple intensity samples. The characteristic intensity is, optionally, based on a predefined number of intensity samples, or a set of intensity samples collected during a predetermined time period (e.g., 0.05, 0.1, 0.2, 0.5, 1, 2, 5, 10 seconds) relative to a predefined event (e.g., after detecting the contact, prior to detecting liftoff of the contact, before or after detecting a start of movement of the contact, prior to detecting an end of the contact, before or after detecting an increase in intensity of the contact, and/or before or after detecting a decrease in intensity of the contact). A characteristic intensity of a contact is, optionally based on one or more of: a maximum value of the intensities of the contact, a mean value of the intensities of the contact, an average value of the intensities of the contact, a top 10 percentile value of the intensities of the contact, a value at the half maximum of the intensities of the contact, a value at the 90 percent maximum of the intensities of the contact, a value produced by low-pass filtering the intensity of the contact over a predefined period or starting at a predefined time, or the like. In some embodiments, the duration of the contact is used in determining the characteristic intensity (e.g., when the characteristic intensity is an average of the intensity of the contact over time). In some embodiments, the characteristic intensity is compared to a set of one or more intensity thresholds to determine whether an operation has been performed by a user. For example, the set of one or more intensity thresholds includes a first intensity threshold and a second intensity threshold. In this example, a contact with a characteristic intensity that does not exceed the first intensity threshold results in a first operation, a contact with a characteristic intensity that exceeds the first intensity threshold and does not exceed the second intensity threshold results in a second operation, and a contact with a characteristic intensity that exceeds the second intensity threshold results in a third operation. In some embodiments, a comparison between the characteristic intensity and one or more intensity thresholds is used to determine whether or not to perform one or more operations (e.g., whether to perform a respective option or forgo performing the respective operation) rather than being used to determine whether to perform a first operation or a second operation.

[0172] In some embodiments, a portion of a gesture is identified for purposes of determining a characteristic intensity. For example, a touch-sensitive surface receives a continuous swipe contact transitioning from a start location and reaching an end location (e.g., a drag gesture), at which point the intensity of the contact increases. In this example, the characteristic intensity of the contact at the end location is based on only a portion of the continuous swipe contact, and not the entire swipe contact (e.g., only the portion of the swipe contact at the end location). In some embodiments, a smoothing algorithm is applied to the intensities of the swipe contact prior to determining the characteristic intensity of the contact. For example, the smoothing algorithm optionally includes one or more of: an unweighted sliding-average smoothing algorithm, a triangular smoothing algorithm, a median filter smoothing algorithm, and/or an exponential smoothing algorithm. In some circumstances, these smoothing algorithms eliminate narrow spikes or dips in the intensities of the swipe contact for purposes of determining a characteristic intensity.

[0173] The user interface figures described herein optionally include various intensity diagrams that show the current intensity of the contact on the touch-sensitive surface relative to one or more intensity thresholds (e.g., a contact detection intensity threshold IT.sub.0, a light press intensity threshold IT.sub.L, a deep press intensity threshold IT.sub.D (e.g., that is at least initially higher than IT.sub.L), and/or one or more other intensity thresholds (e.g., an intensity threshold IT.sub.H that is lower than IT.sub.L)). This intensity diagram is typically not part of the displayed user interface, but is provided to aid in the interpretation of the figures. In some embodiments, the light press intensity threshold corresponds to an intensity at which the device will perform operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, the deep press intensity threshold corresponds to an intensity at which the device will perform operations that are different from operations typically associated with clicking a

button of a physical mouse or a trackpad. In some embodiments, when a contact is detected with a characteristic intensity below the light press intensity threshold (e.g., and above a nominal contact-detection intensity threshold $IT_{sub.0}$ below which the contact is no longer detected), the device will move a focus selector in accordance with movement of the contact on the touch-sensitive surface without performing an operation associated with the light press intensity threshold or the deep press intensity threshold. Generally, unless otherwise stated, these intensity thresholds are consistent between different sets of user interface figures.

[0174] In some embodiments, the response of the device to inputs detected by the device depends on criteria based on the contact intensity during the input. For example, for some “light press” inputs, the intensity of a contact exceeding a first intensity threshold during the input triggers a first response. In some embodiments, the response of the device to inputs detected by the device depends on criteria that include both the contact intensity during the input and time-based criteria. For example, for some “deep press” inputs, the intensity of a contact exceeding a second intensity threshold during the input, greater than the first intensity threshold for a light press, triggers a second response only if a delay time has elapsed between meeting the first intensity threshold and meeting the second intensity threshold. This delay time is typically less than 200 ms (milliseconds) in duration (e.g., 40, 100, or 120 ms, depending on the magnitude of the second intensity threshold, with the delay time increasing as the second intensity threshold increases). This delay time helps to avoid accidental recognition of deep press inputs. As another example, for some “deep press” inputs, there is a reduced-sensitivity time period that occurs after the time at which the first intensity threshold is met. During the reduced-sensitivity time period, the second intensity threshold is increased. This temporary increase in the second intensity threshold also helps to avoid accidental deep press inputs. For other deep press inputs, the response to detection of a deep press input does not depend on time-based criteria.

[0175] In some embodiments, one or more of the input intensity thresholds and/or the corresponding outputs vary based on one or more factors, such as user settings, contact motion, input timing, application running, rate at which the intensity is applied, number of concurrent inputs, user history, environmental factors (e.g., ambient noise), focus selector position, and the like. Example factors are described in U.S. patent application Ser. Nos. 14/399,606 and 14/624,296, which are incorporated by reference herein in their entireties.

[0176] For example, FIG. 4C illustrates a dynamic intensity threshold **480** that changes over time based in part on the intensity of touch input **476** over time. Dynamic intensity threshold **480** is a sum of two components, first component **474** that decays over time after a predefined delay time $p1$ from when touch input **476** is initially detected, and second component **478** that trails the intensity of touch input **476** over time. The initial high intensity threshold of first component **474** reduces accidental triggering of a “deep press” response, while still allowing an immediate “deep press” response if touch input **476** provides sufficient intensity. Second component **478** reduces unintentional triggering of a “deep press” response by gradual intensity fluctuations of in a touch input. In some embodiments, when touch input **476** satisfies dynamic intensity threshold **480** (e.g., at point **481** in FIG. 4C), the “deep press” response is triggered.

[0177] FIG. 4D illustrates another dynamic intensity threshold **486** (e.g., intensity threshold $I_{sub.D}$). FIG. 4D also illustrates two other intensity thresholds: a first intensity threshold $I_{sub.H}$ and a second intensity threshold $I_{sub.L}$. In FIG. 4D, although touch input **484** satisfies the first intensity threshold $I_{sub.H}$ and the second intensity threshold $I_{sub.L}$ prior to time $p2$, no response is provided until delay time $p2$ has elapsed at time **482**. Also in FIG. 4D, dynamic intensity threshold **486** decays over time, with the decay starting at time **488** after a predefined delay time $p1$ has elapsed from time **482** (when the response associated with the second intensity threshold $I_{sub.L}$ was triggered). This type of dynamic intensity threshold reduces accidental triggering of a response associated with the dynamic intensity threshold $I_{sub.D}$ immediately after, or concurrently with, triggering a response associated with a lower intensity threshold, such as the first intensity

threshold I.sub.H or the second intensity threshold I.sub.L.

[0178] FIG. 4E illustrate yet another dynamic intensity threshold 492 (e.g., intensity threshold I.sub.D). In FIG. 4E, a response associated with the intensity threshold I.sub.L is triggered after the delay time p2 has elapsed from when touch input 490 is initially detected. Concurrently, dynamic intensity threshold 492 decays after the predefined delay time p1 has elapsed from when touch input 490 is initially detected. So a decrease in intensity of touch input 490 after triggering the response associated with the intensity threshold I.sub.L, followed by an increase in the intensity of touch input 490, without releasing touch input 490, can trigger a response associated with the intensity threshold Ip (e.g., at time 494) even when the intensity of touch input 490 is below another intensity threshold, for example, the intensity threshold I.sub.L.

[0179] An increase of characteristic intensity of the contact from an intensity below the light press intensity threshold IT.sub.L to an intensity between the light press intensity threshold IT.sub.L and the deep press intensity threshold IT.sub.D is sometimes referred to as a “light press” input. An increase of characteristic intensity of the contact from an intensity below the deep press intensity threshold IT.sub.D to an intensity above the deep press intensity threshold IT.sub.D is sometimes referred to as a “deep press” input. An increase of characteristic intensity of the contact from an intensity below the contact-detection intensity threshold IT.sub.0 to an intensity between the contact-detection intensity threshold IT.sub.0 and the light press intensity threshold IT.sub.L is sometimes referred to as detecting the contact on the touch-surface. A decrease of characteristic intensity of the contact from an intensity above the contact-detection intensity threshold IT.sub.0 to an intensity below the contact-detection intensity threshold IT.sub.0 is sometimes referred to as detecting liftoff of the contact from the touch-surface. In some embodiments IT.sub.0 is zero. In some embodiments, IT.sub.0 is greater than zero. In some illustrations a shaded circle or oval is used to represent intensity of a contact on the touch-sensitive surface. In some illustrations, a circle or oval without shading is used represent a respective contact on the touch-sensitive surface without specifying the intensity of the respective contact.

[0180] In some embodiments, described herein, one or more operations are performed in response to detecting a gesture that includes a respective press input or in response to detecting the respective press input performed with a respective contact (or a plurality of contacts), where the respective press input is detected based at least in part on detecting an increase in intensity of the contact (or plurality of contacts) above a press-input intensity threshold. In some embodiments, the respective operation is performed in response to detecting the increase in intensity of the respective contact above the press-input intensity threshold (e.g., the respective operation is performed on a “down stroke” of the respective press input). In some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the press-input threshold (e.g., the respective operation is performed on an “up stroke” of the respective press input).

[0181] In some embodiments, the device employs intensity hysteresis to avoid accidental inputs sometimes termed “jitter,” where the device defines or selects a hysteresis intensity threshold with a predefined relationship to the press-input intensity threshold (e.g., the hysteresis intensity threshold is X intensity units lower than the press-input intensity threshold or the hysteresis intensity threshold is 75%, 90%, or some reasonable proportion of the press-input intensity threshold). Thus, in some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the hysteresis intensity threshold that corresponds to the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the hysteresis intensity threshold (e.g., the respective operation is performed on an “up stroke” of the respective press input). Similarly, in

some embodiments, the press input is detected only when the device detects an increase in intensity of the contact from an intensity at or below the hysteresis intensity threshold to an intensity at or above the press-input intensity threshold and, optionally, a subsequent decrease in intensity of the contact to an intensity at or below the hysteresis intensity, and the respective operation is performed in response to detecting the press input (e.g., the increase in intensity of the contact or the decrease in intensity of the contact, depending on the circumstances).

[0182] For ease of explanation, the description of operations performed in response to a press input associated with a press-input intensity threshold or in response to a gesture including the press input are, optionally, triggered in response to detecting: an increase in intensity of a contact above the press-input intensity threshold, an increase in intensity of a contact from an intensity below the hysteresis intensity threshold to an intensity above the press-input intensity threshold, a decrease in intensity of the contact below the press-input intensity threshold, or a decrease in intensity of the contact below the hysteresis intensity threshold corresponding to the press-input intensity threshold. Additionally, in examples where an operation is described as being performed in response to detecting a decrease in intensity of a contact below the press-input intensity threshold, the operation is, optionally, performed in response to detecting a decrease in intensity of the contact below a hysteresis intensity threshold corresponding to, and lower than, the press-input intensity threshold. As described above, in some embodiments, the triggering of these responses also depends on time-based criteria being met (e.g., a delay time has elapsed between a first intensity threshold being met and a second intensity threshold being met).

[0183] As used in the specification and claims, the term “tactile output” refers to physical displacement of a device relative to a previous position of the device, physical displacement of a component (e.g., a touch-sensitive surface) of a device relative to another component (e.g., housing) of the device, or displacement of the component relative to a center of mass of the device that will be detected by a user with the user's sense of touch. For example, in situations where the device or the component of the device is in contact with a surface of a user that is sensitive to touch (e.g., a finger, palm, or other part of a user's hand), the tactile output generated by the physical displacement will be interpreted by the user as a tactile sensation corresponding to a perceived change in physical characteristics of the device or the component of the device. For example, movement of a touch-sensitive surface (e.g., a touch-sensitive display or trackpad) is, optionally, interpreted by the user as a “down click” or “up click” of a physical actuator button. In some cases, a user will feel a tactile sensation such as an “down click” or “up click” even when there is no movement of a physical actuator button associated with the touch-sensitive surface that is physically pressed (e.g., displaced) by the user's movements. As another example, movement of the touch-sensitive surface is, optionally, interpreted or sensed by the user as “roughness” of the touch-sensitive surface, even when there is no change in smoothness of the touch-sensitive surface. While such interpretations of touch by a user will be subject to the individualized sensory perceptions of the user, there are many sensory perceptions of touch that are common to a large majority of users. Thus, when a tactile output is described as corresponding to a particular sensory perception of a user (e.g., an “up click,” a “down click,” “roughness”), unless otherwise stated, the generated tactile output corresponds to physical displacement of the device or a component thereof that will generate the described sensory perception for a typical (or average) user. Using tactile outputs to provide haptic feedback to a user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

[0184] In some embodiments, a tactile output pattern specifies characteristics of a tactile output, such as the amplitude of the tactile output, the shape of a movement waveform of the tactile output, the frequency of the tactile output, and/or the duration of the tactile output.

[0185] When tactile outputs with different tactile output patterns are generated by a device (e.g., via one or more tactile output generators that move a moveable mass to generate tactile outputs), the tactile outputs may invoke different haptic sensations in a user holding or touching the device. While the sensation of the user is based on the user's perception of the tactile output, most users will be able to identify changes in waveform, frequency, and amplitude of tactile outputs generated by the device. Thus, the waveform, frequency and amplitude can be adjusted to indicate to the user that different operations have been performed. As such, tactile outputs with tactile output patterns that are designed, selected, and/or engineered to simulate characteristics (e.g., size, material, weight, stiffness, smoothness, etc.); behaviors (e.g., oscillation, displacement, acceleration, rotation, expansion, etc.); and/or interactions (e.g., collision, adhesion, repulsion, attraction, friction, etc.) of objects in a given environment (e.g., a user interface that includes graphical features and objects, a simulated physical environment with virtual boundaries and virtual objects, a real physical environment with physical boundaries and physical objects, and/or a combination of any of the above) will, in some circumstances, provide helpful feedback to users that reduces input errors and increases the efficiency of the user's operation of the device. Additionally, tactile outputs are, optionally, generated to correspond to feedback that is unrelated to a simulated physical characteristic, such as an input threshold or a selection of an object. Such tactile outputs will, in some circumstances, provide helpful feedback to users that reduces input errors and increases the efficiency of the user's operation of the device.

[0186] In some embodiments, a tactile output with a suitable tactile output pattern serves as a cue for the occurrence of an event of interest in a user interface or behind the scenes in a device. Examples of the events of interest include activation of an affordance (e.g., a real or virtual button, or toggle switch) provided on the device or in a user interface, success or failure of a requested operation, reaching or crossing a boundary in a user interface, entry into a new state, switching of input focus between objects, activation of a new mode, reaching or crossing an input threshold, detection or recognition of a type of input or gesture, etc. In some embodiments, tactile outputs are provided to serve as a warning or an alert for an impending event or outcome that would occur unless a redirection or interruption input is timely detected. Tactile outputs are also used in other contexts to enrich the user experience, improve the accessibility of the device to users with visual or motor difficulties or other accessibility needs, and/or improve efficiency and functionality of the user interface and/or the device. Tactile outputs are optionally accompanied with audio outputs and/or visible user interface changes, which further enhance a user's experience when the user interacts with a user interface and/or the device, and facilitate better conveyance of information regarding the state of the user interface and/or the device, and which reduce input errors and increase the efficiency of the user's operation of the device.

User Interfaces and Associated Processes

[0187] Attention is now directed towards embodiments of user interfaces (“UI”) and associated processes that are implemented on an electronic device, such as portable multifunction device **100** or device **300**, with a display, a touch-sensitive surface, (optionally) one or more tactile output generators for generating tactile outputs, and (optionally) one or more sensors to detect intensities of contacts with the touch-sensitive surface.

[0188] FIGS. 5A-5AY illustrate example user interfaces for providing alerts (e.g., notifications) and adjusting alert settings on a device, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. 6A-6E, 7A-7C, and 8A-8E. For convenience of explanation, some of the embodiments will be discussed with reference to operations performed on a device with a touch-sensitive display system **112**. In such embodiments, the focus selector is, optionally: a respective finger or stylus contact, a representative point corresponding to a finger or stylus contact (e.g., a centroid of a respective contact or a point associated with a respective contact), or a centroid of two or more contacts detected on the touch-sensitive display system **112**. However, analogous operations are, optionally,

performed on a device with a display **450** and a separate touch-sensitive surface **451** in response to detecting the contacts on the touch-sensitive surface **451** while displaying the user interfaces shown in the figures on the display **450**, along with a focus selector.

[0189] FIGS. 5A-5R illustrate example user interfaces for adjusting alert settings of a device (e.g., referred to as device **100** for simplicity), in accordance with some embodiments. More specifically, FIGS. 5A-5R illustrate the operation of a virtual button (e.g., a control affordance on a touch-sensitive display) for controlling generation of alerts by the device (e.g., for controlling a reduced notification mode of the device). The virtual button is displayed on an initial user interface that appears after the device wakes up from a display-off state (e.g., the virtual button is displayed on a wake screen). After an intensity of a contact at the virtual button exceeds an intensity threshold, the device initiates a process for adjusting alert settings of the device (e.g., the device displays a menu with user-selectable auto-expiration options for the reduced notification mode, or displays a menu with user-selectable options for switching to a different reduced notification mode). In some embodiments, the virtual button toggles the reduced notification mode in response to a light press (e.g., a contact with a characteristic intensity above a first intensity threshold, such as IT.sub.L, but below a second intensity threshold, such as IT.sub.D) and initiates the process for adjusting the alert settings in response to a deep press (e.g., a contact with a characteristic intensity above a second intensity threshold, such as IT.sub.D). In the examples described below, IT.sub.L is used as a button toggle threshold and IT.sub.D is used as a settings activation threshold. In some embodiments, the virtual button is unresponsive to contacts with an intensity below IT.sub.L, reducing the risk that the user accidentally activates the button.

[0190] FIG. 5A illustrates device **100** in a display-off state. For example, in the display-off state, device **100** is still on, but touchscreen **112** is not illuminated or activated. In some embodiments, device **100** enters the display-off state when a user presses a lock button (e.g., a physical button on device **100**) or device **100** remains idle for a predefined amount of time (e.g., 30 seconds or a minute without device **100** detecting an input that prevents device **100** from entering the display-off state, such as a user input to perform operations on device **100** or a wake input, as described below).

[0191] FIG. 5B illustrates an initial user interface **502** (e.g., a wake screen) displayed in response to an input for waking up device **100**. Note that the initial user interface **502** is distinct from a home screen user interface that includes a plurality of application launch icons corresponding to a plurality of applications (e.g., as shown in FIG. 4A). In some embodiments, the input for waking up device **100** is a user input. For example, device **100** detects movement of the device (e.g., device **100** detects vertical movement or shaking of the device using one or more accelerometers), detects actuation of any physical button on the device, or detects a voice command asking the device to wake up). In some embodiments, the device wakes up in response to an event that occurs within the device (e.g., an alarm going off, a communication being received).

[0192] The initial user interface **502** includes a virtual button (e.g., a control affordance) **504-a** for accessing a flashlight on the device **100**, a virtual button **504-b** for controlling provision of alerts by device **100**, and a virtual button **504-c** for accessing a camera on the device **100**. In FIG. 5B, the virtual button **504-b** is shaded, providing a visual indication that a reduced notification mode of the device is activated.

[0193] In some embodiments, device **100** includes a plurality of reduced notification modes (e.g., “do-not-disturb” modes) including a productivity mode, a social mode, an exercise mode, and a sleep mode. The initial user interface **502** includes a visual indication **506** (e.g., displayed text) informing the user of which reduced notification mode is active (e.g., the productivity mode) and an optional auto-expiration condition for the active reduced notification mode (e.g., “Until 5 PM”).

[0194] The initial user interface **502** also includes a date and time indicator **508** of the current date and time as well as a lock indicator **510** showing whether the device is in a locked state (e.g., in FIG. 5B, device **100** is in the locked state, so the lock icon is shown as locked).

[0195] FIG. 5C illustrates the initial user interface **502** after receiving an input to unlock device **100**. To that end, FIG. 5C is the same as FIG. 5B, except the lock indicator **510** is unlocked in FIG. 5C. In some embodiments, the input to unlock the device is a contact on a fingerprint sensor on home button **204** and successful recognition of a known-user's fingerprint. In some embodiments, the input to unlock the device is successful recognition of a known-user's face (e.g., without the user taking any action besides holding touchscreen **112** towards his or her face).

[0196] FIG. 5D is analogous to FIG. 5C except that in FIG. 5D a contact **514** is detected on the virtual button **504-b** for controlling generation of alerts by device **100**.

[0197] In some embodiments, an increase of the intensity of contact **514** above IT.sub.D (or some other intensity threshold) is required to enable the device to display options for adjusting alert settings of the device. In some embodiments, the display of the options for adjusting the alert settings of the device is triggered (e.g., initiated) upon detecting a subsequent decrease in intensity of contact **514** (e.g., either detecting lift-off or detecting a decrease in intensity of contact **514** below a predefined threshold). To that end, FIG. 5D and some subsequent figures include intensity diagrams **512** (corresponding to the intensity of contact **514**) that have intensity thresholds IT.sub.H, IT.sub.L, and IT.sub.D. FIGS. 5D-5F, which are in chronological order, illustrate the intensity of contact **514** increasing above IT.sub.L (FIG. 5D), then increasing above IT.sub.D (FIG. 5E), and then dropping below IT.sub.H (FIG. 5F).

[0198] FIG. 5F illustrates display of a menu of modification options **516** for adjusting the alert settings of the device. FIG. 5G illustrates that, in some embodiments, the modification options **516** remain displayed after the contact **514** ends.

[0199] In this example, the modification options **516** are auto-expiration options for changing an auto-expiration condition for a currently active reduced notification mode (e.g., productivity mode). Modification option **516-b**, which when active automatically de-activates productivity mode at a user-settable time (e.g., 5 PM), is currently active and, for that reason, visually distinguished (e.g., highlighted) from the other modification options **516**. The displayed modification options **516** also include: a modification option **516-a** which, when active, automatically de-activates productivity mode after a user-settable duration; modification option **516-c** which, when active, automatically de-activates productivity mode when the device leaves a user-settable geo-fenced location; modification option **516-d** which, when active, automatically de-activates productivity mode when the device enters a user-settable geo-fenced location; and modification option **516-e** which, when active, automatically de-activates productivity mode when a calendar meeting ends.

[0200] FIG. 5H illustrates a contact **518** selecting modification option **516-c**. In some embodiments, contact **518** is a separate and distinct contact from contact **514**, which triggered display of the modification options **516**. In some embodiments, contact **518** is a continuation of contact **514** (e.g., contact **514/518** is continuously detected on touchscreen **112**)

[0201] FIG. 5I illustrates the device **100** responding by updating the visual indication **506** to show that device **100** will remain in productivity mode until device **100** leaves the geographical location "1 Inf. Loop" (e.g., leaves a geo-fenced area corresponding to 1 Inf. Loop).

[0202] FIG. 5J illustrates a contact **520** over virtual button **504-b**. Contact **520** has a characteristic intensity above IT.sub.L. For the purposes of this example, it is assumed that contact **520** does not experience an increase in intensity above IT.sub.D, which would enable display of modification options **516**, as discussed previously. Instead, for example, FIG. 5J illustrates the maximum intensity of contact **520**. As illustrated in this example, in some embodiments, a contact over virtual button **504-b** having a characteristic intensity (e.g., maximum intensity) between IT.sub.L and IT.sub.D toggles the reduced notification mode on and off.

[0203] To that end, FIG. 5K illustrates the result of contact **520**. The reduced notification mode is disabled (as indicated by the fact that virtual button **504-b** is no longer shaded). In addition, in response to de-activating the reduced notification mode, device **100** provides notifications **522**

(e.g., messages) that were received while the device was in the reduced notification mode. For example, message **522-a** was received by the device at 2:05 PM but not provided to the user until 3:26 PM, the time at which the reduced notification mode was de-activated. Likewise, message **522-b** was received by the device at 1:39 PM but not provided to the user until 3:26 PM.

[0204] FIGS. 5L-5O illustrate a manner in which a user can cancel an input (e.g., a contact) that would otherwise trigger display of modification options **516**, described above. To that end, FIG. 5L returns to an example starting with the reduced notification mode (e.g., productivity mode) activated (e.g., as indicated by the shaded virtual button **504-b**). A contact **524** over virtual button **504-b** is detected in FIG. 5L, and experiences an increase in intensity above IT.sub.D as shown in FIG. 5M. However, as shown in FIG. 5M, contact **524** moves to a location away from (e.g., not over) virtual button **504-b**, and, as shown in FIG. 5N, the intensity of contact **524** decreases below IT.sub.H (e.g., or lifts off) while at the location away from virtual button **504-b**. As shown in FIG. 5O, device **100** does not perform an operation (e.g., does not display modification options **516**) in response to contact **524**, because the input to display the modification options **516** is considered by the device to be canceled. Thus, in some embodiments, even though a user input (e.g., a contact) enables display of modification options **516**, modification options **516** are not displayed unless a triggering condition (e.g., a decrease in contact intensity) is detected while the input is over the virtual button **504-b**.

[0205] FIGS. 5P-5Q illustrate that, in some embodiments, virtual button is unresponsive to contacts having an intensity below a predetermined threshold (e.g., below button toggle threshold IT.sub.L). To that end, device detects a contact **526**. The maximum intensity of contact **526** is shown in FIG. 5P. That is, the maximum intensity of contact **526** is above a minimum detection threshold IT.sub.0 (at which device **100** detects the presence of contact **526**) but below IT.sub.H (or IT.sub.L). As shown in FIG. 5Q, device **100** does not perform an operation (e.g., does not display modification options **516** and does not toggle virtual button **504-b**) in response to contact **526**. Requiring that contact **526** have a characteristic intensity above a predefined threshold prevents accidental toggling of the reduced notification mode on and off or changing alert settings (e.g., while device **100** is in the user's pocket).

[0206] FIG. 5R illustrates an example in which the visual indication **506** of the active reduced notification mode (and, optionally, an active auto-expiration condition) is itself a control affordance. Thus, in some embodiments, device **100** performs any of the operations described with reference to FIGS. 5A-5Q, but with respect to a contact over visual indication/virtual button **506** instead of virtual button **504-b**.

[0207] FIGS. 5S-5AI illustrate example user interfaces for devices that provide different reduced notification modes (e.g., different “do-not-disturb” modes) for different contexts. For example, the devices shown in FIGS. 5S-5AI provide a productivity mode, a social mode, a sleep mode, and an exercise mode. The different reduced notification modes have different whitelists (e.g., lists of applications from which notifications are allowed to “breakthrough” the reduced notification mode). An active reduced notification mode causes the device to at least partially block notifications that are not whitelisted for that particular reduced notification mode. For example, a notification that is whitelisted for an active reduced notification mode will be displayed and the user will be notified of its arrival by a sound and/or a haptic alert. In contrast, a notification that is not whitelisted for the active reduced notification mode will be displayed without a sound or haptic alert (or not provided at all while the particular reduced notification mode is active). Thus, a user can, for example, set the device to a productivity mode at work and not be distracted by social media, then can go home and set the device to a social mode to avoid being bothered by work emails.

[0208] As an example, FIGS. 5S-5T illustrate provision of notifications from initial user interface **502** (e.g., the wake screen) while device **100** is in a productivity mode. In some embodiments, the productivity mode is initialized with a default whitelist of applications. The whitelist for the

productivity mode can include, for example, applications that are tagged by their developers, by users in an application store as relating to productivity, or by any group of keywords relating to productivity. As described later, in some embodiments, a user can modify the default whitelist. In this example, it is assumed that the calendar application is whitelisted in the productivity mode and that a messages (e.g., “text messaging”) application is not whitelisted.

[0209] As shown in FIGS. 5S, device **100** receives a calendar invitation (e.g., a communication) while in the productivity mode. In response to receiving the calendar invitation, device **100** determines that the communication is received from a whitelisted application for the productivity mode and provides a corresponding notification that includes a displayed notification **530-a** and a sound alert **532**.

[0210] FIG. 5T illustrates a notifications user interface **534**. In some embodiments, a user can access the notifications user interface **534** by swiping length-wise (e.g., vertically) on touchscreen **112** from the wake screen **502** when device **100** is unlocked. For the purposes of this example, notification user interface **534** in FIG. 5T shows notifications corresponding to all of the communications received while device **100** has been in the productivity mode. In particular, in addition to displayed notification **530-a**, notification user interface **534** shows a displayed notification **530-b** corresponding to a message received from a user Alice and a displayed notification **530-c** corresponding to a message received from a user Bob. Displayed notifications **530-b** and **530-c** were not whitelisted in the productivity mode and thus not provided on the wake screen **502** while device **100** was in the productivity mode. In addition, in some embodiments, no sound or haptic alert was provided when the communications corresponding to displayed notifications **530-b** and **530-c** were received.

[0211] FIG. 5U illustrates that, in some embodiments, when the user returns from the notifications user interface **534** (FIG. 5T) to the wake screen **502** (e.g., by swiping down on the notifications user interface **534**), the whitelisted notifications are once again the only notifications provided.

[0212] FIGS. 5V-5Y illustrate user interfaces for changing from one reduced notification mode (e.g., productivity mode) to a different reduced notification mode (e.g., social mode). To that end, in FIG. 5V, productivity mode is active. Device **100** detects a contact **536** that meets criteria for adjusting alert settings of the device (e.g., as described with reference to FIGS. 5A-5R and method **600**, FIGS. 6A-6E).

[0213] In contrast to FIGS. 5A-5R, which illustrate adjusting auto-expiration settings of an active reduced notification mode, FIG. 5W illustrates an example in which contact **536** (FIG. 5V) initiates display of modification options **538-a** through **538-d** for selecting a different reduced notification mode (e.g., in a settings menu **540**). In FIG. 5X, a contact **542** is detected that selects a “social” reduced notification mode (herein referred to as a social mode) by selecting modification option **538-b**. In response, as shown in FIG. 5Y, the visual indication **506** shows that the social mode is active rather than the productivity mode (as shown in FIG. 5S).

[0214] As an example, FIGS. 5Z-5AA illustrate provision of notifications from initial user interface **502** (e.g., the wake screen) while device **100** is in the social mode. In some embodiments, the social mode is initialized with a default whitelist of applications. The whitelist for the social mode can include, for example, applications that are tagged by their developers or by users in an application store as relating to rest, relaxation, social media, entertainment, and the like. As described later, in some embodiments, a user can modify the default whitelist for the social mode. In this example, it is assumed that the calendar application is not whitelisted in the productivity mode and that the messages (e.g., “text messaging”) application is whitelisted.

[0215] As shown in FIG. 5Z, the device receives a message from Bob (e.g., a communication) while in the social mode. In response to receiving the message from the messaging application, device **100** determines that the communication is received from a whitelisted application for the social mode and provides a corresponding notification that includes a displayed notification **530-d** and a sound alert **544**.

[0216] FIG. 5AA illustrates notifications user interface 534. For the purposes of this example, notification user interface 534 in FIG. 5AA shows notifications corresponding to all of the communications received while device 100 has been in the social mode. In particular, in addition to displayed notification 530-d, notification user interface 534 shows a displayed notification 530-e corresponding to a calendar invitation received while device 100 was in the social mode. Displayed notification 530-e was not whitelisted and thus not provided on the wake screen 502 while device was in the social mode. In addition, in some embodiments, no sound or haptic alert was provided when the communications corresponding to displayed notifications 530-e was received.

[0217] Thus, as seen by comparing FIGS. 5S-5T with FIGS. 5Z-5AA, device 100 provides functionality that mirrors the user's life through different reduced notification modes for different contexts. For example, as with the user's life, the social mode and the productivity mode are, in some senses, complementary (e.g., the productivity mode includes at least one application on its whitelist that is not on the whitelist for the social mode, and vice versa).

[0218] FIGS. 5AB-5AD illustrate user interfaces for adjusting settings (e.g., including a whitelist of applications) of a social reduced notification mode.

[0219] FIG. 5AB illustrates a “Do Not Disturb” settings user interface 546 (e.g., a settings interface for reduced notification modes, which are sometimes colloquially referred to herein as “Do Not Disturb” modes). The setting user interface 546 includes virtual buttons 548 corresponding to each of the plurality of reduced notification modes (e.g., virtual buttons 548-a through 548-d). As shown in FIG. 5AB, device 100 detects a contact 550 on the virtual button 548-b corresponding to the social mode.

[0220] In response, as shown in FIG. 5AC, device 100 displays a social mode settings user interface 552. The social mode settings user interface, for example, allows the user to toggle the social mode on/off, provides geographical auto-activation conditions (e.g., the social mode is set to auto-activate when device 100 is near the user's home, which for the sake of this example is assumed to be stored in device 100's memory), provides geographical auto-deactivation conditions (e.g., the social mode is set to auto-de-activate when device 100 is near the user's work, which for the sake of this example is assumed to be stored in the device 100's memory), and allows the user to schedule set times when the social mode is active (e.g., the user has set the social mode to be active from 5 PM to 8 AM, which the user can modify by selecting the options with, e.g., a touch input).

[0221] FIG. 5AC continues the example by illustrating user selection of the application whitelist in the social mode settings user interface 552 (e.g., via a tap gesture by contact 554).

[0222] In response, as shown in FIG. 5AD, device 100 displays a social mode application whitelist user interface 556. The application whitelist shown in the social mode application whitelist user interface 556 (e.g., those applications toggled to “on” in user interface 556) is an initial default whitelist for the social mode (e.g., comprising the device 100's “best guess” as to which applications should be whitelisted in the social mode, based on, for example, attributes tagged by the developers of the applications or other users of the applications). For example, to name a few, the application whitelist for the social mode includes a social media application, a television (TV) application, a game center, etc. A mail application, professional networking application, and calendar application are not whitelisted in the initial default list of whitelisted applications for the social mode because such applications are more likely to be relevant to the user's work life. The user can add or remove applications from the social mode whitelist by toggling the “off/on” toggle for each application in the social mode application whitelist user interface 556.

[0223] FIGS. 5AE-5AG illustrate user interfaces for adjusting settings (e.g., including a whitelist of applications) of a productivity reduced notification mode.

[0224] FIG. 5AE illustrates the “Do Not Disturb” settings user interface 546 and is analogous to FIG. 5AB except that, in FIG. 5AE, the user selects (e.g., via a tap gesture by contact 558) the virtual button 548-a corresponding to the productivity mode, instead of virtual button 548-b

corresponding to the social mode (FIG. 5AB).

[0225] In response, as shown in FIG. 5AF, device **100** displays a productivity mode settings user interface **560**, which is analogous to social mode settings user interface **546** except that the user interface **560** is for the productivity reduced notification mode rather than the social reduced notification mode.

[0226] FIG. 5AF continues the example by illustrating user selection of the application whitelist in the productivity mode settings user interface **560** (e.g., via a tap gesture by contact **562**).

[0227] In response, as shown in FIG. 5AG, device **100** displays a productivity mode application whitelist user interface **564**. The application whitelist shown in the productivity mode application whitelist user interface **564** (e.g., those applications toggled to “on” in user interface **564**) is an initial default whitelist for the productivity mode (e.g., comprising the device **100**'s “best guess” as to which applications should be whitelisted in the productivity mode, based on, for example, attributes tagged by the developers of the applications or other users of the applications). For example, to name a few, the application whitelist for the productivity mode includes the calendar application, a professional networking application, and the mail application. The social media application, game center application, and TV application are not whitelisted in the initial default list of whitelisted applications for the productivity mode because such applications are not likely to be relevant to the user's work. The user can add or remove applications from the whitelist of applications for the productivity mode by toggling the “off/on” toggle for each application in the productivity mode application whitelist user interface **564**.

[0228] In some embodiments, different reduced notification modes have different automatic activation conditions (e.g., as shown in FIGS. 5AC and 5AF, the user can configure distinct automatic activation conditions for different reduced notification modes). As another example, FIGS. 5AH-5AI illustrate embodiments in which a particular reduced notification mode is automatically activated when a related application in a predefined set of applications is running in a foreground of the device. In particular, FIGS. 5AH-5AI illustrate an example in which a user input activating an exercise application (e.g., a tap gesture by a contact **566** on an exercise application icon in a home screen, FIG. 5AH) causes the exercise application **570** to run in the foreground of the device. In response to detecting that the exercise application **570** is running in the foreground of the device, the device automatically activates an exercise reduced notification mode and notifies the user (e.g., via notification **568**, FIG. 5AI).

[0229] FIGS. 5AJ-5AY illustrate example user interfaces for devices that automatically suggest activation of a reduced notification mode based on a plurality of manual activations of the reduced notification mode. In some embodiments, a device associates a set of conditions with individual manual activations of a reduced notification mode. For example, a device detects that the user has manually activated a productivity mode five times around 9 AM when the user arrives at work. After the plurality of manual activations, the device outputs an activation suggestion for the productivity reduced notification mode. In some embodiments, the activation suggestion is a suggestion, provided upon a manual activation of the reduced notification mode, to automatically activate the reduced notification mode whenever the device detects a similar set of conditions (e.g., “Would you like to automatically activate the productivity mode whenever you arrive at work in the morning?”). In some embodiments, the activation suggestion is a suggestion, provided when the device detects a similar set of conditions, to activate the reduced notification mode (e.g., “You've arrived at work! Would you like to activate productivity mode?”)

[0230] FIG. 5AJ illustrates wake screen **502** having virtual buttons **504**, as described with reference to FIG. 5B, including virtual button **504-b** corresponding to a reduced notification mode. In FIG. 5AJ, the reduced notification mode is not active (e.g., as indicated by the fact that virtual button **504-b** is not shaded). However, in FIG. 5AJ, device **100** detects contact **572** that meets toggle criteria for the virtual button **504-b**. Thus, in FIG. 5AK, which follows FIG. 5AJ, the reduced notification mode is active (as indicated by the shading of virtual button **504-b**).

[0231] For the sake of this example, the manual activation of the reduced notification mode shown in FIGS. 5AJ-5AK is assumed to be one of a plurality of manual activations of the reduced notification mode, the rest of which occurred at other times in similar circumstances (e.g., similar times of day, days of the week, locations, etc.). For example, the user, in the past week, activated the reduced notification mode at the following times on respective nights while at home: 9:44 PM, 10:23 PM, 10:01 PM, and 10:07 PM (as shown in FIGS. 5AJ-5AK). From those manual activations, device **100** determines a set of conditions: the user activates the reduced notification mode (1) while at home and (2) around 10 PM (e.g., determined by taking the mean of the manual activation times and rounding to the nearest quarter of an hour).

[0232] FIGS. 5AL-5AM follow FIGS. 5AJ-5AK and illustrate an example in which device **100** outputs a suggestion, based on the plurality of manual activations of the reduced notification mode, to activate the reduced notification mode, in accordance with some embodiments. For example, FIG. 5AL illustrates that the next night, when the user is at home, the reduced notification mode is not active at 9:59 PM. As shown in 5 AM, when the clock strikes 10 PM, because of the previous plurality of manual activations of the reduced notification mode, device **100** outputs an activation suggestion **574** to activate sleep mode (e.g., device **100** detects the set of conditions corresponding to the previous manual activations of the sleep mode and, upon detecting the set of conditions, outputs a suggestion to activate the sleep mode).

[0233] FIGS. 5AN-5AQ illustrate an example in which device **100** outputs a suggestion, based on the plurality of manual activations of the reduced notification mode, to automatically activate the reduced notification mode when the set of conditions corresponding to the manual activation is detected, in accordance with some embodiments. That is, FIGS. 5AN-5AQ follow FIG. 5AJ and illustrate an alternative response of device **100** as compared with FIGS. 5AL-5AM.

[0234] FIG. 5AN illustrates that upon detecting the manual activation (via contact **572**, FIG. 5AJ), device **100** outputs a suggestion **576** to automatically activate the reduced notification mode the next time the set of conditions is detected (e.g., and upon subsequent detections of the set of conditions). In some embodiments, the suggestion **576** to activate the reduced notification mode the next time the set of conditions is detected is a suggestion to set-up automatic conditions for the reduced notification mode (including automatic activation and de-activation conditions). In some embodiments, the suggestion **576** includes affordances for modifying activation/expiration options **578** corresponding to automatic activation and/or expiration conditions (e.g., modification option **578-a** is a location expiration option that corresponds to a condition that the reduced notification mode should automatically turn off, notwithstanding the schedule, if the user is not home; modification option **578-b** is a scheduled begin activation option that corresponds to a condition that the reduced notification mode should automatically turn on at a set time; modification option **578-c** is a scheduled end expiration option that corresponds to a condition that the reduced notification mode should automatically turn off at a set time; modification option **578-d** corresponds to a condition that the schedule should apply on certain days of the week). In some embodiments, the values (e.g., conditions) for the modification options **578** can be changed or de-activated (when appropriate) by the user (e.g., by selecting an option with a touch input, such as a tap gesture).

[0235] In this example, modification options whose conditions (e.g., values) are automatically determined by the device based on manual activations/de-activations are visually distinguished from those which are not. For example, the “home” condition for modification option **578-a**, the “10 PM” scheduled begin condition for modification option **578-b**, and the days for which the schedule applies (modification option **578-d**) are assumed, for the sake of this example, to have been determined automatically by the device as a set of conditions corresponding to manual activations of the reduced notification mode, and thus are visually distinguished.

[0236] As shown in FIG. 5AN, device **100** detects a contact **580** which accepts the set of conditions (e.g., including automatic activation and de-activation conditions).

[0237] FIG. 5AO follows FIG. 5AN (e.g., shows the device the next night, with the set of automatic activation conditions active after the user has accepted the suggestion 576). In particular, 5AO illustrates that, at 9:59 PM the next night, the reduced notification mode is not active. FIG. 5AP follows FIG. 5AO and illustrates that, when the clock strikes 10 PM, the device automatically activates the reduced notification mode without user intervention (in FIGS. 5AO-5AP the device is assumed to be located at the user's home so that all of the automatic activation conditions are met). Device 100 also displays a visual indication 582 of an automatic expiration condition (e.g., that the reduced notification mode (e.g., sleep mode) will remain active until 6 AM). The automatic expiration condition is based on the user's acceptance of suggestion 576 (FIG. 5AN).

[0238] Note that, in some embodiments, the automatic activation of the reduced notification mode includes a geographical/location based criterion (e.g., the reduced notification mode automatically activates and remains active, according to the schedule, if the user is at home). As shown in FIG. 5AQ, in some embodiments, device 100 automatically de-activates the reduced notification mode (e.g., sleep mode) if the device 100 detects that its location does not meet the geographical/location based criteria (e.g., the device is no longer at home). For example, in FIG. 5AQ, the user left home early to go to the airport. As a result, device 100 automatically, without user intervention, de-activates the reduced notification mode and displays a notification 584 notifying the user.

[0239] FIGS. 5AR-5AW illustrates wake screen 502 having virtual buttons 504, as described with reference to FIG. 5B, including virtual button 504-b corresponding to a reduced notification mode. In FIG. 5AR, the reduced notification mode is active (e.g., as indicated by the fact that virtual button 504-b is shaded). However, in FIG. 5AR, device 100 detects a gesture by contact 586 that meets toggle criteria for the virtual button 504-b.

[0240] For the sake of this example, the manual de-activation of the reduced notification mode shown in FIG. 5AR is assumed to be one of a plurality of manual de-activations of the reduced notification mode, the rest of which occurred at other times in similar circumstances (e.g., similar times of day, days of the week, locations, etc.). For example, the user, in the past week, de-activated the reduced notification mode at the following times on respective afternoons: 5:08 PM, 5:15 PM, 4:59 PM, and 4:46 PM (as shown in FIG. 5AR). From those manual de-activations, device 100 determines a set of conditions: the user de-activates the reduced notification mode around 5 PM (e.g., determined by taking the mean of the manual de-activation times and rounding to the nearest quarter of an hour).

[0241] FIGS. 5AS-5AT follow FIG. 5AR and illustrate an example in which device 100 outputs a suggestion, based on the plurality of manual de-activations of the reduced notification mode, to de-activate the reduced notification mode, in accordance with some embodiments. In FIG. 5AS, the next afternoon (as compared to FIG. 5AR) the reduced notification mode is active (as indicated by the shading of virtual button 504-b. As shown in 5AT, when the clock strikes 5 PM, because of the previous plurality of manual de-activations of the reduced notification mode, the device outputs a de-activation suggestion 588 to de-activate productivity mode (e.g., the device detects the set of conditions corresponding to the previous manual de-activations of the productivity mode and, upon detecting the set of conditions, outputs a suggestion to de-activate the sleep mode).

[0242] FIGS. 5AU-5AW illustrate an example in which device 100 outputs a suggestion, based on the plurality of manual de-activations of the reduced notification mode, to automatically de-activate the reduced notification mode when the set of conditions corresponding to the manual de-activation is detected, in accordance with some embodiments. That is, FIGS. 5AU-5AW follow FIG. 5AR and illustrate an alternative response of the device as compared with FIGS. 5AS-5AT.

[0243] FIG. 5AU illustrates that upon detecting the manual de-activation (via contact 586, FIG. 5AR), device 100 outputs a suggestion 590 to automatically de-activate the reduced notification mode the next time the set of conditions is detected (e.g., and upon subsequent detections of the set of conditions). In some embodiments, the suggestion 590 to de-activate the reduced notification mode the next time the set of conditions is detected is a suggestion to set-up automatic conditions

for the reduced notification mode (including automatic activation and de-activation conditions). In some embodiments, the suggestion **590** includes affordances for modifying activation/expiration options **592** corresponding to automatic activation and/or expiration conditions (e.g., modification option **592-a** is a location expiration option that corresponds to a condition that the reduced notification mode should automatically turn off, notwithstanding the schedule, if the user is not home; modification option **592-b** is a scheduled begin activation option that corresponds to a condition that the reduced notification mode should automatically turn on at a set time; modification option **592-c** is a scheduled end expiration option that corresponds to a condition that the reduced notification mode should automatically turn off at a set time; modification option **592-d** corresponds to a condition that the schedule should apply on certain days of the week). In some embodiments, the values (e.g., conditions) for the modification options **592** can be changed or deactivated (when appropriate) by the user (e.g., by selecting an option with a touch input).

[0244] In this example, modification options whose conditions (e.g., values) are automatically determined by device **100** based on manual activations/de-activations are visually distinguished from those who are not. For example, the “work” condition for modification option **592-a**, the “5 PM” scheduled begin condition for modification option **592-b**, and the days for which the schedule applies (modification option **592-d**) are assumed, for the sake of this example, to have been determined automatically by the device as a set of conditions corresponding to prior manual activations of the reduced notification mode, and are thus visually distinguished.

[0245] As shown in FIG. 5AU, device **100** detects a contact **594** which accepts the set of conditions (e.g., including automatic activation and de-activation conditions).

[0246] FIG. 5AV follows FIG. 5AU (e.g., shows the device the next afternoon, with the set of automatic activation conditions active after the user has accepted the suggestion **590**). In particular, 5AV illustrates that, at 4:59 PM the next afternoon, the reduced notification mode is active. Device **100** also displays a visual indication **596** of an automatic expiration condition (e.g., that the reduced notification mode (e.g., productivity mode) will remain active until 5 PM). The automatic expiration condition is based on the user's acceptance of suggestion **590** (FIG. 5AU).

[0247] FIG. 5AW follows FIG. 5AV and illustrates that, when the clock strikes 5 PM, the device automatically de-activates the reduced notification mode without user intervention.

[0248] FIGS. 5AX-5AY illustrate an example in which the device **100** outputs an activation suggestion for a reduced notification mode in response to one or more (e.g., a plurality of) manual activations of the reduced notification mode with a corresponding calendar condition. For example, in FIG. 5AX, device **100** outputs a notification **598** reminding the user of a calendar appointment. The notification offers the user the option to activate the reduced notification mode, which the user accepts via a tap gesture by contact **5100** (thus manually activating the reduced notification mode). FIG. 5AY illustrates that, in response to and upon the receiving the gesture by contact **5100** accepting the suggestion to activate the reduced notification mode, device **100** outputs an activation suggestion **5102** that the device enter the reduced notification mode whenever the user's calendar indicates that the user is busy. If the user accepts the suggestion (e.g., by pressing “ok”) the device **100** automatically enters the reduced notification (e.g., productivity) mode automatically, without user intervention, whenever the user's calendar indicates that the user is busy.

[0249] FIGS. 5AZ-5BM illustrate example user interfaces for providing notifications when a reduced notification mode (e.g., a sleep mode) is deactivated.

[0250] FIG. 5AZ illustrates an initial user interface **502** (e.g., a wake screen). As described with reference to FIG. 5B, the initial user interface **502** includes virtual buttons **504-a**, **504-b**, and **504-c**. The initial user interface **502** further includes a displayed notification **5104** (e.g., a reminder to go to bed) that indicates that the reduced notification mode will be activated at a user-defined future time. For example, FIG. 5AZ shows a notification **5104** at 9:45 PM that alerts the user that it will be “time for bed” at 10 PM (e.g., at which point the reduced notification mode will automatically activate). In some embodiments, the notification **5104** is accompanied by an audio output and/or a

tactile output (e.g., a sound and/or vibration).

[0251] In some embodiments, the reduced notification mode (e.g., a “do-not-disturb” mode) corresponds to a bedtime mode (e.g., sleep mode). For example, in some circumstances, the reduced notification automatically activates at a user-defined bed time (e.g., “time for bed”) and deactivates at a user-defined wake-up time (e.g., the alarm time). For example, the user sets “time for bed” to be 10 PM, sets the notification **5104** to be displayed 15 minutes before it is “time for bed,” and sets her alarm to go off at 6:15 AM. Alternatively, in some circumstances, a default setting is used to set the “time for bed” and the alarm time. In the following example, sleep mode is set to begin at 10 PM on Saturday, and the alarm is set to go off at 6:15 AM on Sunday. In various circumstances, the user stops the alarm (e.g., by pressing a stop button) or snoozes the alarm (e.g., by pressing a snooze button). In the case of snoozing the alarm, sleep mode remains active until the snooze period is over and a second alarm goes off, at which point the user may press snooze again (e.g., for an additional 10 minutes) or stop the alarm to deactivate sleep mode.

[0252] FIG. 5BA illustrates the initial user interface **502** before the reduced notification mode is activated. Continuing with the example in FIG. 5AZ, the reduced notification mode (e.g., corresponding to “time for bed”) is set to activate at 10 PM. At 9:59 PM, the initial user interface **502** is shown at a predefined brightness corresponding to the device not being in the reduced notification mode. FIG. 5BB illustrates the automatic activation of the reduced notification mode. In some embodiments, the reduced notification mode limits the notifications (e.g., alerts) the device displays while the reduced notification mode is active. In some embodiments, the reduced notification mode also reduces the brightness of the display while the reduced notification mode is active. In some embodiments, reducing the brightness of the display includes reducing a background of a displayed user interface and maintaining the brightness of one or more foreground user interface objects.

[0253] In this example, at 10 PM, the device forgoes displaying incoming notifications to the user and the brightness of the initial user interface **502** is reduced in accordance with the activation of the reduced notification mode. As noted above, this reduction of brightness corresponds to the “sleep mode” such that the screen remains at the reduced brightness. during the predefined time that sleep mode is active (e.g., 10 PM to 6:15 AM) even when the user is using the device (e.g., in some embodiments, the display turns off after a predefined amount of time when the user is not using the device).

[0254] In some embodiments, objects in the foreground of the user interface **502** maintain their respective brightness while the reduced notification mode is active. In some embodiments, only the brightness of the background of the user interface **502** is reduced. For example, in some embodiments, the time and date displayed in the user interface **502** are considered objects in the foreground. Thus, in some embodiments, the time and date are maintained at the same brightness when the reduced notification mode is active as compared to when the reduced notification mode is not active. In some embodiments, the virtual buttons **504-a**, **504-b** and **504-c** are considered objects in the foreground. In some embodiments, the virtual buttons **504-a**, **504-b** and **504-c** are not considered objects in the foreground (e.g., are part of the background) and thus the brightness of the virtual buttons **504** is reduced in accordance with activation of the reduced notification mode.

[0255] In some embodiments, objects in the foreground of the user interface **502** reduce their respective brightness while the reduced notification mode is active, but the reduction in brightness of the objects in the foreground is less than the reduction in brightness of the background. Thus, in some embodiments, the time and date are reduced in brightness when the reduced notification mode is active as compared to when the reduced notification mode is not active, but the time and date do not become as dim as the background.

[0256] FIG. 5BC illustrates device **100** with display **112** in a display off state. In some embodiments, the display **112** remains in the display off state until device **100** detects an input for waking up device **100**. For example, while the reduced notification mode is active, if the user

provides an input for waking the device (e.g., by movement of the device **100** or by actuation of any physical button on the device **100**), the display **112** displays user interface **502** (e.g., or another user interface) at the reduced brightness. If the user uses device **100** during “sleep mode” (e.g., if the user wakes up in the middle of the night), the display **100** activates at the reduced brightness. Thus, in some embodiments, the device remains in “sleep mode” even if the user provides inputs to the device at any point during the time “sleep mode” is active (e.g., 10 PM to 6:15 AM).

[0257] In some embodiments, detecting an input to wake-up the device includes detecting movement of the device **100** (e.g., device **100** detects vertical movement or shaking of the device using one or more accelerometers), detecting actuation of any physical button on the device, or detecting a voice command asking the device to wake-up. In some embodiments, the device **100** wakes up in response to an internal event (e.g., an alarm going off, a communication being received). In some embodiments, if no user input is received, the display **112** remains in the display off state until the device detects an alert condition for the reduced notification mode (e.g., the device detects that it is time for the sleep mode alarm to go off).

[0258] FIG. 5BD shows the response of device **100** to the sleep mode alarm going off. In some embodiments, in response to the sleep mode alarm going off (e.g., when it is 6:15 AM), a user interface **502-a** is displayed. User interface **502-a** includes an “alarm” alert **5106**, a “snooze” affordance **5108** (e.g., virtual button) and/or a “stop” affordance **5110**. The virtual buttons **504-a**, **504-b**, and **504-c** shown in FIG. 5BD are optionally displayed on the user interface **502-a**.

[0259] In some embodiments, user interface **502-a** is an updated user interface from user interface **502**. For example, in some embodiments, the user interface background and/or one or more of the user interface objects displayed in user interface **502-a** (e.g., virtual buttons **504**) are the same as those in user interface **502**. In some embodiments, user interface **502-a** is updated to include additional elements, such as affordances, or other overlays. Alternatively, in some embodiments, user interface **502-a** is a distinct user interface from user interface **502**.

[0260] In addition to displaying the “alarm” alert **5106**, and affordances **5108** and **5110**, in some circumstances, device **100** outputs audio output and/or a tactile output (e.g., sound alert **532**). Thus, in some embodiments, the device **100** outputs a sound in addition to displaying the first user interface **502-a**.

[0261] In some embodiments, the user interface **502-a** is presented at a reduced brightness (e.g., to appear dimmed, in an analogous fashion to user interface **502** in FIG. 5BB). In some embodiments, the user interface **502-a** is displayed with different color tones (e.g., warmer tones corresponding to less blue light) as compared with the color tones of the user interface **502**. For example, device **100** displays the user interface **502-a** at the reduced brightness corresponding to the reduced notification mode. Note that depending on which elements are considered in the foreground and the background, affordances and icons displayed in user interface **502-a** also appear at the reduced brightness, or appear at a brightness corresponding to a brightness of the device when the device is not in the reduced notification mode.

[0262] In some embodiments, the user can select either affordance **5108** to snooze the alarm or affordance **5110** to turn off the alarm. FIGS. 5BE-5BG illustrate a first example in which device **100** delays deactivation of (e.g., snoozes) the reduced notification mode after displaying a first user interface in response to detecting an alert condition for the reduced notification mode.

[0263] For example, as shown in FIG. 5BE, the user provides an input **5112** on the “snooze” affordance **5108**. In some embodiments, in response to activation of the “snooze” affordance, the device **100** remains in the reduced notification mode. In some embodiments, in response to activation of the “snooze” affordance, the device no longer displays user interface **502-a**, and instead displays user interface **502** (e.g., at the reduced brightness). In some embodiments, as shown in FIG. 5BF, the device **100** further displays an indication **5114** indicating that the deactivation of the reduced notification mode is delayed (e.g., shows the alarm is snoozing for another 7 minutes and 13 seconds). Also note an indication displayed on the initial user interface

that states “Sleep Mode Until 6:25 AM,” is displayed to indicate delay of deactivation of the reduced notification mode. In some embodiments, the indication **5114** is an object in the foreground and thus, even during reduced notification mode, maintains a brightness that corresponds to a brightness of the display when not in the reduced notification mode. Alternatively, in some embodiments, the indication **5114** is considered as part of the background of the initial user interface and is displayed at a reduced brightness while in the reduced notification mode. In some embodiments, activation of the “snooze” affordance delays the deactivation of the reduced notification mode by a predefined amount of time.

[0264] FIG. **5BG** illustrates expiration of the delay caused by activating the “snooze” affordance. As shown, at expiration of the “snooze” status (e.g., which expires 10 minutes after the first display of the first user interface), the device displays the user interface **502-a**.

[0265] As explained above, in some embodiments, the user interface **502-a** is presented at a reduced brightness (e.g., to appear dimmed) corresponding to the reduced notification mode or is presented at a brightness corresponding to a brightness of the device when the device is not in the reduced notification mode.

[0266] FIGS. **5BH-5BM** illustrate a second example in which device **100** deactivates the reduced notification mode in response to detecting a first input on a first affordance (e.g., “stop” button **5110**). That is, FIGS. **5BH-5BM** follow FIG. **5BD** and illustrate an alternative response of device **100** as compared with FIGS. **5BE-5BG**.

[0267] FIG. **5BH** illustrates an input **5116** on “stop” affordance **5110**. In response to detecting the input **5116** that activates the affordance **5110**, the device **100** deactivates the reduced notification mode. As shown in FIG. **5BI**, in response to the activation of affordance **5110**, the device also displays a user interface **502-b**. In some embodiments, the user interface **502-b** is an updated user interface **502**. For example, in some embodiments, background elements and/or icons from user interface **502** are displayed in user interface **502-b**. Alternatively, in some embodiments, the user interface **502-b** is a distinct user interface from user interface **502**.

[0268] The device also ceases the audio output and/or tactile output (e.g., turns the alarm sounds and/or vibrations off) in response to activation of “stop” affordance **5110**. The user interface **502-b** optionally includes location-based information **5118** (e.g., local weather). In some embodiments, the user interface **502-b** includes a “notifications” affordance **5120**. Note that second user interface **502-b** does not display content from notifications received while the device was in sleep mode. For example, if a call or a message was received by device **100** while device **100** was in sleep mode, the information related to the call or the message is not displayed on the user interface **502-b**. In this way, a user is able to deactivate the reduced notification mode (e.g., sleep mode) by turning off the alarm (e.g., selecting the “stop” affordance), and is optionally presented with some information (e.g., local weather) without overloading the user with notifications that may have been missed during the reduced notification mode.

[0269] FIG. **5BJ** illustrates an input **5122** that activates the “notifications” affordance **5120**. As shown in FIG. **5BK**, in response to the input **5122**, the device displays notifications for the user on a user interface **502-c** (e.g., notifications that include content from communications that were received while the device **100** was in the reduced notification mode, as well as notifications from earlier). For example, as shown in FIGS. **5BK-5BL**, notifications are displayed, including a message **5124-a** from Bob that was received at 12:04 AM the same day (e.g., while the reduced notification mode was active), a message **5124-b** from Alice that was received at 11:22 PM the previous day (e.g., while the reduced notification mode was active) and a calendar invitation **5124-c** that was received at 5:15 PM the previous day. In some embodiments, the notifications that were received while the reduced notification mode was active (e.g., “during sleep mode”) are displayed on a portion of the user interface that is separate from the notifications that were received before sleep mode (e.g., “from yesterday”). In some embodiments, the notifications are displayed in a time order (e.g., with the most recent notifications displayed toward the top). For example, the messages

from Bob and Alice are displayed in a top portion of the user interface under the heading “during sleep mode” because they were received while the reduced notification mode was active, while the calendar invitation is displayed separately under the heading “from yesterday” because it was received before the reduced notification mode was active. In some embodiments, the notifications are selectable by a user. For example, user selection of a notification results in the device providing more information (e.g., detail) regarding the selected notification.

[0270] For example, FIG. 5BL shows an input **5126** that selects message notification **5124-a** from Bob. In various circumstances, the input **5126** is a swipe gesture, a touch input, a voice command, or any other user input performed by a user of the device. As shown in FIG. 5BM, in response to selection of the message notification, the device displays a user interface **5128**. In some embodiments, the user interface **5128** corresponds to the notification that was selected. For example, a messaging application user interface that displays messages with Bob is displayed in response to the user selecting the message notification **5124-a** from Bob.

[0271] FIGS. 6A-6E are flow diagrams depicting a method **600** of adjusting alert settings on an electronic device, in accordance with some embodiments. Although some of the examples which follow will be given with reference to inputs on a touch-sensitive display in which a touch-sensitive surface and a display are combined, in some embodiments, the device detects inputs on a touch-sensitive surface **451** that is separate from the display **450**, as shown in FIG. 4B.

[0272] In some embodiments, method **600** is performed by an electronic device (e.g., portable multifunction device **100**, FIG. 1A) and/or one or more components of the electronic device (e.g., I/O subsystem **106**, operating system **126**, etc.). In some embodiments, method **600** is governed by instructions that are stored in a non-transitory computer-readable storage medium and that are executed by one or more processors of a device, such as the one or more processors **122** of device **100** (FIG. 1A). For ease of explanation, the following describes method **600** as performed by device **100**. In some embodiments, with reference to FIG. 1A, the operations of method **600** are performed by or use, at least in part, operating system **126**, communication module **128**, and/or graphics module **132**, as well as a touch-sensitive display (e.g., touch screen **112**). Some operations in method **600** are, optionally, combined and/or the order of some operations is, optionally, changed.

[0273] As described below, method **600** (and associated interfaces) provides an intuitive way to adjust alert settings on an electronic device, accessible from an initial user interface that is displayed when the device switches from a display-off state to a display-on state (e.g., a wake screen). Providing device-alert setting controls from a wake screen makes it easy to adjust these alert settings, such as reduced-notification settings. By triggering the device-alert setting controls using intensity-based activation criteria, method **600** reduces the risk that a user will accidentally change a setting. The method reduces the number, extent, and/or nature of the inputs from a user when adjusting alert settings, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, enabling a user to adjust alert settings faster and more efficiently conserves power and increases the time between battery charges.

[0274] While an electronic device is in a display-off state, device **100** detects (**602**) a first input (e.g., an input to wake the device from a display-off state). In some embodiments, detecting the first input includes detecting movement of the device (e.g., an inertial input). In some embodiments, detecting the first input includes detecting movement of the device along a predefined axis (e.g., an axis of the device or an axis measured with respect to gravity). For example, the first input includes vertical movement of the device (e.g., lifting the device). In some embodiments, detecting the first input includes detecting pressing of a physical button on the device (e.g., pressing any button on the device wakes the device from the display-off state). FIG. 5A illustrates an example of the electronic device in the display-off state.

[0275] In response to detecting the first input (**604**), device **100** activates (**606**) a display of device **100** (e.g., wakes the device from the display-off state) and displays (**608**) a first user interface that

corresponds to a display-on state of the device (e.g., wake screen **502**, FIG. 5B). The first user interface is an initial user interface that is displayed when the device switches from the display-off state to the display-on state in response to detecting the first input (e.g., a wake screen). In some embodiments, the first user interface displays a visual indicator that changes when the electronic device changes from a locked mode to an unlocked mode. For example, in FIGS. 5B-5C, in response to a valid authentication input (such as a passcode, fingerprint, and/or facial recognition input), a lock indicator **510** changes from indicating that the device is locked (FIG. 5B) to indicating that the device is unlocked (FIG. 5C).

[0276] The first user interface includes a control affordance for controlling generation of alerts by the device. For example, in FIGS. 5B-5C, the user interface includes a reduced notification control affordance **504-b**. For example, in FIG. 5R, visual indication **506** is a control affordance that also displays information indicating which of a plurality of reduced notification modes is active and what auto-expiration conditions are active. In some embodiments, the control affordance is displayed in the first user interface when the device is in a reduced notification state (e.g., a reduced notification mode is active), but the control affordance is not shown if the device is not in a reduced notification state (e.g., no reduced notification mode is active).

[0277] The first user interface (e.g., the wake screen) is distinct from a home screen user interface that includes a plurality of application launch icons corresponding to a plurality of applications (e.g., wake screen **502** is distinct from the home screen user interface shown in FIG. 4A). For example, when the device is in an unlocked state, the user optionally navigates from the first user interface to the home screen by pressing a home button (e.g., home button **204**, FIGS. 5A-5BM).

[0278] While displaying the first user interface that includes the control affordance, device **100** detects (**610**) a second input that includes a contact at a location on the touch-sensitive surface that corresponds to the control affordance. For example, the display is a touch-sensitive display that includes the touch-sensitive surface (e.g., the display is a touchscreen) and the contact is over the control affordance on the touch-sensitive display (e.g., contact **514**, FIG. 5D). As another example, the display is separate from the touch-sensitive surface and a contact is detected on the touch-sensitive surface while a cursor is over the control affordance.

[0279] In response to detecting the second input (**612**), in accordance with a determination that the second input meets activation criteria (e.g., reduced notification activation criteria) for the control affordance, device initiates (**614**) a process for adjusting alert settings of the device (e.g., by displaying settings for controlling generation of alerts). The activation criteria (e.g., control activation criteria) include a requirement that the second input includes an increase in a characteristic intensity of the contact that exceeds an intensity threshold (e.g., an intensity threshold greater than a nominal contact detection threshold, such as intensity threshold IT.sub.D or intensity threshold IT.sub.L) while the contact is at the location on the touch-sensitive surface that corresponds to the control affordance in order for the activation criteria to be met (e.g., in FIG. 5E, contact **514** has increased in intensity, exceeding IT.sub.D, while over virtual button **504-b**). In some embodiments, a user input that meets the activation criteria triggers additional functionality beyond toggling the control affordance, whereas the device toggles the reduced notification mode on or off when toggle criteria are met (described below). In some embodiments, device **100** determines whether the second input meets the activation criteria.

[0280] In some embodiments, the process for adjusting the alert settings of the device is (**616**) initiated upon detecting a decrease in the characteristic intensity of the contact (e.g., crossing below an intensity threshold, such as IT.sub.D or a lower intensity threshold) while the contact is at the location on the touch-sensitive surface that corresponds to the control affordance (e.g., the display is a touch-sensitive display that includes the touch-sensitive surface and the contact is over the control affordance on the touch-sensitive display when the decrease in intensity is detected). In some embodiments, the process for adjusting the alert settings of the device is initiated upon detecting the increase in the characteristic intensity of the contact above the intensity threshold

(e.g., IT.sub.D) while the contact is over the control affordance. In some embodiments, the process for adjusting the alert settings of the device is initiated upon detecting lift-off of the contact while the contact is at the location on the touch-sensitive surface that corresponds to the control affordance.

[0281] Initiating the process for adjusting the alert settings of the device upon detecting a decrease in the characteristic intensity of the contact allows additional intensity-based thresholds to be used (e.g., toggle criteria, as discussed with reference to FIGS. 5J-5K) and allows for an unintended input to be canceled (e.g., as discussed with reference to FIGS. 5L-5N). Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0282] In some embodiments, initiating the process for adjusting the alert settings of device **100** includes (**618**) displaying one or more activateable modification options for adjusting the alert settings of device **100** (e.g., displaying a reduced notification settings menu that includes the one or more activation modification options for a reduced notification mode). For example, as described with reference to FIGS. 5E-5H, in some embodiments, the one or more activateable modification options include one or more auto-expiration options corresponding to auto-expiration conditions. When the device is in a reduced notification mode and an active auto-expiration condition occurs (e.g., a time, location, or calendar condition), the device automatically, without user intervention, de-activates the reduced notification mode.

[0283] Providing activateable modification options for adjusting the alert settings of the device, accessible from the wake screen, makes it easy to adjust the corresponding options for the alert settings. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0284] In some embodiments, the process for adjusting the alert settings of the device is (**620**) a process for adjusting an active reduced notification mode of device **100**. The active reduced notification mode of the device is a first reduced notification mode of a plurality of reduced notification modes of the device (e.g., each option corresponds to a respective reduced notification mode, as shown in FIGS. 5W-5X). The control affordance includes a visual indication identifying the first reduced notification mode. The visual indication identifying the first reduced notification mode is distinct from visual indicia for other reduced notification modes of the plurality of reduced notification modes of the device. For example, FIG. 5R illustrates an example in which the visual indication/virtual button **506** includes the text “Productivity Mode,” whereas virtual button **506** would say, e.g., “Social Mode” if a social reduced notification mode were active instead of the productivity reduced notification mode.

[0285] Providing a visual indication identifying which reduced notification mode is active allows a user to know which types of alerts will be provided. Providing improved visual feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0286] In some embodiments, the process for adjusting the alert settings of the device is (**622**) a process for adjusting an active reduced notification mode of the device. The control affordance includes a visual indication of an auto-expiration condition for the active reduced notification mode. In some embodiments, the auto-expiration condition is an end time after which the reduced notification mode will no longer be active (e.g., visual indication/virtual button **506**, FIG. 5R, includes the text “Until 5 PM” which indicates that the active productivity mode will automatically be de-activated at 5 PM). In some embodiments, the auto-expiration condition is a different end condition which, when met, causes the device to de-activate the reduced notification mode (e.g., a location-based end condition). In some embodiments, the auto-expiration condition is a remaining

duration for the reduced notification mode (e.g., a countdown timer for the reduced notification mode stating, e.g., “Productivity Mode for another 2:37”). In some embodiments, rather than the control affordance including the visual indication of the auto-expiration condition for the reduced notification mode, the visual indication of the auto-expiration condition is displayed separately from (e.g., adjacent to) the control affordance in the first user interface (e.g., the visual indication is displayed in the first user interface but is not activateable for initiating the process for adjusting the alert settings of the device, as shown in FIG. 5B, which shows non-activateable text that says “Productivity Mode Until 5 PM”). In some embodiments, the visual indication of the auto-expiration condition is displayed in a control bar (e.g., the set of virtual buttons **504**, FIG. 5B, is a control bar).

[0287] Providing a visual indication of an auto-expiration condition for the active reduced notification mode allows a user to know the current auto-expiration condition (e.g., without having to navigate to a settings user interface). Providing improved visual feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0288] In response to detecting the second input (**612**), in accordance with a determination that the second input does not meet the activation criteria for the control affordance, device forgoes (**624**) initiating the process for adjusting alert settings of the device. In some embodiments, forgoing initiating the process for adjusting the alert settings of the device includes maintaining display of the first user interface that includes the control affordance for the reduced notification mode.

[0289] In some embodiments, after detecting the increase in the characteristic intensity of the contact that exceeds the intensity threshold while the contact is at the location on the touch-sensitive surface that corresponds to the control affordance: device **100** detects (**626**) movement of the contact to a location on the touch-sensitive surface that does not correspond to the control affordance (e.g., movement of contact **524**, FIGS. 5L-5N). While the contact is at the location on the touch-sensitive surface that does not correspond to the control affordance, device **100** detects lift-off of the contact (e.g., the intensity of the contact drops below a minimum detection threshold). In response to detecting lift-off of the contact while the contact is at the location on the touch-sensitive surface that does not correspond to the control affordance, device **100** forgoes initiating the process for adjusting the alert settings of the device (e.g., does not initiate or cancels initiating the process for adjusting the alert settings of the device).

[0290] As another example, in some embodiments, after detecting the increase in the characteristic intensity of the contact that exceeds the intensity threshold while the contact is at the location on the touch-sensitive surface that corresponds to the control affordance: device **100** detects (**628**) movement of the contact to a location on the touch-sensitive surface that does not correspond to the control affordance (e.g., movement of contact **524**, FIGS. 5L-5N). While the contact is at the location on the touch-sensitive surface that does not correspond to the control affordance, device **100** detects a decrease in the characteristic intensity of the contact (e.g., below the intensity threshold or a lower intensity threshold that is distinct from and higher than the minimum detection threshold for detecting a contact). In response to detecting the decrease in the characteristic intensity of the contact while the contact is at the location on the touch-sensitive surface that does not correspond to the control affordance, device **100** forgoes initiating the process for adjusting the alert settings of device **100** (e.g., does not initiate or cancels initiating the process for adjusting the alert settings of the device).

[0291] Providing ways to forgo initiating the process for adjusting the alert settings of the device allows the user to cancel an unintended input that would have otherwise resulted in initiating the process for adjusting the alert settings of the device. This helps users avoid accidental or unintended adjusting of the alert settings, reducing the number of inputs needed to undo such actions. Providing additional control options without cluttering the user interface enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the

user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0292] In some embodiments, while displaying the first user interface that includes the control affordance, device **100** detects (**630**) a third input that includes detecting a respective contact at a location on the touch-sensitive surface that corresponds to the control affordance. In response to detecting the third input, in accordance with a determination that the third input meets toggle criteria for the control affordance, device **100** toggles the alert settings of the device. The toggle criteria do not include a requirement that the third input has an increase in a characteristic intensity of the respective contact that exceeds the intensity threshold (e.g., IT.sub.D) while the respective contact is at the location on the touch-sensitive surface that corresponds to the control affordance in order for the toggle criteria to be met. For example, for a device with a touch-sensitive display, in response to a tap gesture on the control affordance, a previously selected reduced notification mode of the device is toggled from on to off, or from off to on.

[0293] In some embodiments, the toggle criteria include a requirement that a respective input includes an increase in a characteristic intensity of a contact above a first intensity threshold (e.g., IT.sub.L) (higher than a minimum detection threshold) while the contact is at the location on the touch-sensitive surface that corresponds to the control affordance in order for the toggle criteria to be met (as described with reference to FIGS. 5J-5K). The activation criteria include a requirement that the respective input includes an increase in the characteristic intensity of the contact above a second intensity threshold (e.g., IT.sub.D) (e.g., higher than the first intensity threshold) while the contact is at the location on the touch-sensitive surface that corresponds to the control affordance in order for the activation criteria to be met (e.g., as described with reference to FIGS. 5D-5F).

[0294] Disambiguating between an input directed to the control affordance that meets toggle criteria and an input directed to the control affordance that meets activation criteria for adjusting alert settings of the device increases the operability of the control affordance (e.g., allows the user to choose between a toggle switch versus a more fine-grained control based on the characteristics of a single input (such as an intensity of a single contact) on the control affordance). Providing additional control options without cluttering the user interface enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0295] In some embodiments, the control affordance is (**632**) a first control affordance of a plurality of control affordances in the first user interface (e.g., virtual buttons **504**, FIG. 5B). For each control affordance of the plurality of control affordances, a respective control affordance is activated when corresponding activation criteria are met. The corresponding activation criteria include a requirement that an input directed to the respective control affordance includes an increase in characteristic intensity of a respective contact that exceeds an intensity threshold while the respective contact is at a location on the touch-sensitive surface that corresponds to the respective control affordance in order for the corresponding activation criteria to be met. In some embodiments, the plurality of control affordances is displayed in a predefined control area, such as a control bar. In some embodiments, the plurality of control affordances includes a camera affordance for activating a camera and a flashlight affordance for activating a flashlight.

[0296] Providing the plurality of control affordances on the wake screen increases the operability of the wake screen (e.g., provides greater functionality from an initial screen displayed after the display turns on). Providing additional control options enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0297] It should be understood that the particular order in which the operations in FIGS. 6A-6E have been described is merely one example and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. In some embodiments, one or

more operations of method **600** are combined, supplemented, or replaced with one or more operations of other methods described herein (e.g., method **700** and/or method **800** and/or method **900**).

[0298] FIGS. 7A-7C are flow diagrams depicting a method **700** of providing alerts (e.g., notifications) on an electronic device, in accordance with some embodiments. Although some of the examples which follow will be given with reference to inputs on a touch-sensitive display in which a touch-sensitive surface and a display are combined, in some embodiments, the device detects inputs on a touch-sensitive surface **451** that is separate from the display **450**, as shown in FIG. 4B.

[0299] In some embodiments, method **700** is performed by an electronic device (e.g., portable multifunction device **100**, FIG. 1A) and/or one or more components of the electronic device (e.g., I/O subsystem **106**, operating system **126**, etc.). In some embodiments, method **700** is governed by instructions that are stored in a non-transitory computer-readable storage medium and that are executed by one or more processors of a device, such as the one or more processors **122** of device **100** (FIG. 1A). For ease of explanation, the following describes method **700** as performed by device **100**. In some embodiments, with reference to FIG. 1A, the operations of method **700** are performed by or use, at least in part, operating system **126**, communication module **128**, and/or graphics module **132**, as well as a touch-sensitive display (e.g., touch screen **112**). Some operations in method **700** are, optionally, combined and/or the order of some operations is, optionally, changed.

[0300] As described below, method **700** (and associated interfaces) provides different reduced notification modes (e.g., with different whitelists) for different contexts (e.g., a productivity mode for work, and a social mode for rest and relaxation), which increases the operability of the device. Providing different reduced notification modes for different contexts makes the device more useful because a user can continue to use the device for needed (or wanted) tasks without being distracted by unwanted notifications, which may otherwise cause the user to turn all alerts off. Thus, for a given context, method **700** reduces the risk that a user will accidentally miss needed (or wanted) notifications in that context, while also preventing unwanted alerts in that context. The method reduces the number, extent, and/or nature of the inputs from a user by obviating the need for the user to frequently adjust settings for controlling generation of alerts by the device, thereby creating a more efficient human-machine interface. For battery-operated electronic devices, reducing the need for frequent settings adjustments conserves power and increases the time between battery charges.

[0301] Device **100** receives (**702**) a communication at an electronic device. In some embodiments, the communication is received from a source remote from the electronic device (e.g., a server, a cell phone tower, another electronic device). For example, the communication is a text or multimedia message received from another user's device. Alternatively, the communication is a phone call. Alternatively, the communication is a news item received from a news outlet. In some embodiments, the communication is received from an application running on the device. For example, the communication may correspond to an alarm or a reminder set by the user of the electronic device.

[0302] In response to receiving the communication (**704**), device **100** performs operations **706** through **720**.

[0303] In accordance with a determination that a first mode (e.g., a first reduced notification mode) is active on the electronic device (**706**), and in accordance with a determination that the communication meets whitelisting criteria for the first mode, device **100** outputs (**708**), at the device, a notification that corresponds to the communication in a first manner (e.g., the notification is provided in the first manner upon receiving the communication). In some embodiments, device **100** determines whether the communication meets the whitelisting criteria for the first mode in response to receiving the communication. In some embodiments, the first manner includes, upon

receiving the communication, displaying a notification corresponding to the communication on the display. In some embodiments, the first manner includes, upon receiving the communication, providing a sound or haptic alert corresponding to the communication. For example, in FIG. 5S, notification **530-a** is displayed and a sound is provided because the calendar application is whitelisted for the active productivity mode.

[0304] In some embodiments, the first notification is (**710**) received for (e.g., from) a first application and the whitelisting criteria for the first mode include a criterion that is met when the first application is in a predefined list of applications for the first mode (e.g., notification **530-a**, FIG. 5S, is received from a calendar application which is included in a whitelist of applications for the productivity mode, as shown in FIG. 5AG).

[0305] Providing a whitelist of applications for the first mode obviates the need for users to frequently navigate to a settings user interface to change individual notification settings or to check needed applications for recent notifications. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0306] In accordance with a determination that a first mode is active on the electronic device (**706**), and in accordance with a determination that the communication does not meet the whitelisting criteria for the first mode, device **100** forgoes (**712**) outputting the notification that corresponds to the communication in the first manner. In some embodiments, in accordance with a determination that a first mode is active on the electronic device, and in accordance with a determination that the communication does not meet the whitelisting criteria for the first mode, device **100** outputs the notification that corresponds to the communication in a second manner, different from the first manner. For example, in some embodiments, the second manner includes, upon receiving the communication, displaying a notification but without providing a sound or haptic alert. In some embodiments, when device **100** forgoes outputting the notification in the first manner, device **100** does not provide the notification at all upon receiving the communication (e.g., the user has to provide one or more inputs to see the notification, such as a swipe up on interface **502**, FIG. 5S to reach notifications interface **534** in FIG. 5T).

[0307] In accordance with a determination that a second mode (e.g., a second reduced notification mode) is active on the electronic device (**714**), and in accordance with a determination that the communication meets whitelisting criteria for the second mode, different from the whitelisting criteria for the first mode, device **100** outputs (**716**), at the device, the notification that corresponds to the communication in the first manner (e.g., or in a third manner different from the first manner and the second manner). In some embodiments, the electronic device determines whether the communication meets the whitelisting criteria for the second mode in response to receiving the communication.

[0308] In some embodiments, the whitelisting criteria for the second mode include (**718**) a criterion that is met when the first application is in a predefined list of applications for the second mode. The predefined list of applications for the second mode includes one or more applications that are not in the predefined list of applications for the first mode. In some embodiments, the predefined list of applications for the first mode includes one or more applications that are not in the predefined list of applications for the second mode (e.g., the first mode and the second mode are complementary reduced notification modes). For example, as shown in FIG. 5Z, the device outputs a message **530-d** in the social mode (e.g., the messaging application is whitelisted for the social mode) that would not have been output in the same manner in the productivity mode (e.g., the messaging application is not whitelisted in the productivity mode).

[0309] In some embodiments, the predefined list of applications for the second mode includes a plurality of applications that are not in the predefined list of applications for the first mode and vice versa. In some embodiments, none of the applications in the predefined list of applications for the

first mode are in the predefined list of applications for the second mode, and none of the applications in the predefined list of applications for the second mode are in the predefined list of applications for the first mode.

[0310] In some embodiments, the first reduced notification mode and the second reduced notification mode are respective modes of a plurality of reduced notification modes (e.g., more than two reduced notification modes, such as a productivity mode, a sleep mode, a social mode, and an exercise mode). Each respective reduced notification mode has a corresponding predefined list of applications. In some embodiments, each reduced notification mode has its own whitelist of applications. In some embodiments, the predefined list of applications for a given mode is distinct from the predefined list of applications for other modes.

[0311] Providing different whitelists of applications for different modes helps customize each mode to its context, obviating the need for users to frequently navigate to a settings user interface to change individual notification settings or to check needed applications for recent notifications. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0312] In accordance with a determination that a second mode is active on the electronic device (714), and in accordance with a determination that the communication does not meet the whitelisting criteria for the second mode, device 100 forgoes (720) outputting the notification that corresponds to the communication in the first manner (e.g., outputs the notification that corresponds to the communication in the second manner or a fourth manner different from the first, second, and third manners).

[0313] In some embodiments, while the first mode is active on the electronic device, device 100 detects (722) de-activation of the first mode. In response to detecting de-activation of the first mode, device outputs (724) (e.g., by displaying), at the device, notifications that correspond to communications received while the device was in the first mode that were not presented while the device was in the first mode (e.g., or not presented in the first manner). For example, the device provides blocked notifications (e.g., notifications which were blocked while in the first mode) on a wake screen after the first mode ends (e.g., as shown in FIGS. 5J-5K). In some embodiments, the device receives a plurality of communications while in a particular reduced notification mode, and, in response to detecting de-activation of the particular reduced notification mode, presents notifications corresponding to each (or at least some) of the communications received while the device was in the particular reduced notification mode.

[0314] Providing notifications after a reduced notification mode has been de-activated, which were not presented while in the reduced notification mode, obviates the need for the user to manually look for notifications that were not provided while the reduced notification mode was active. Automatically providing such notifications upon de-activation of the reduced notification mode also reduces the risk that a user will miss an important notification. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0315] In some embodiments, the first mode is (726) a productivity mode, and the second mode is a social mode, distinct from the productivity mode (e.g., having different application whitelists). Device 100 initiates (728) the predefined list of applications for the productivity mode to include applications relating to productivity and initiates (730) the predefined list of applications for the social mode to include social media applications. In some embodiments, initiating the predefined list of applications for a given mode includes displaying an initial list of applications in a user interface that allows a user to edit the initial list of applications for the mode (e.g., user interfaces 556 and 564 in FIGS. 5AD and 5AG, respectively). For example, when the user first sets up the

productivity mode, the device displays an initial list of applications by automatically populating the list with suggested applications that relate to productivity (e.g., an email application, a calendar application). In some embodiments, the predefined list of applications for the productivity mode is a default list of applications. In some embodiments, the default list of applications includes applications that are tagged with one or more predefined attributes (e.g., category attributes, e.g., tagged by the developer of the application). In some embodiments, the default list of applications includes applications in a respective sub-directory on the device (e.g., within a productivity folder). In some embodiments, the default list of applications includes one or more applications automatically installed on the device (e.g., an email application, a calendar application).

[0316] Initiating different whitelists of applications for different reduced notification modes simplifies the process of setting up each of the modes. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0317] In some embodiments, device **100** receives (**732**) an input to add (or remove) a respective application to the predefined list of applications for the first mode (or the second mode). In response to receiving the input, device **100** adds (or removes) (**734**) the respective application to the predefined list of applications for the first mode. In some embodiments, the device displays a user interface for editing the whitelist of applications for each reduced notification mode (e.g., the user interfaces shown in FIG. 5AD and FIG. 5AG). In some embodiments, the input is a voice command to the device (e.g., the user can state, to a personal assistant running on the device, “Please give me my email notifications” or, in response to receiving an unwanted notification, can state, “Please hide those notifications from me”).

[0318] Providing a way for the user to modify whitelists for different reduced notification modes makes the various reduced notification modes more effective for a user. Providing additional control options enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0319] In some embodiments, the first mode is (**736**) associated with a first set of activation conditions (e.g., activation conditions for the first mode). In some embodiments, the activation conditions are automatic activation conditions to automatically activate the first mode when the electronic device detects the set of conditions. For example, in response to detecting the first set of activation conditions, the device automatically, without user intervention, activates the first mode (e.g., as described with reference to FIG. 5AJ and FIGS. 5AN-5AP). In some embodiments, the activation conditions are conditions which, when met, cause the device to provide a suggestion (e.g., a displayed suggestion or an audially output suggestion) to activate the first mode (e.g., additional user intervention is required to accept the suggestion and activate the first mode, as described with reference to FIGS. 5AJ-5AM).

[0320] In some embodiments, the second mode is associated with a second set of activation conditions (e.g., automatic activation conditions for the second mode), different from the first set of activation conditions. In response to detecting the second set of activation conditions, the device automatically, without user intervention, activates the second mode. In some embodiments, the activation conditions are conditions which, when met, cause the device to provide a suggestion (e.g., a displayed suggestion or an audially output suggestion) to activate the second mode (e.g., additional user intervention is required to accept the suggestion and activate the second mode).

[0321] In some embodiments, each activation condition in the first (or second) set of activation conditions must be met for the first (or second) set of activation conditions to be met. In some embodiments, the first set of activation conditions and the second set of activation conditions are mutually exclusive (e.g., both sets of activation conditions cannot simultaneously be met). For example, the first set of activation conditions includes an activation condition that is met when the

device detects its physical location within a first geo-fenced area (e.g., the first mode is a social mode/relaxation mode and the first geo-fenced area is an area surrounding the user's home) and the second set of activation conditions is met when the device detects its physical location within a second geo-fenced area that does not geographically overlap with the first geo-fenced area (e.g., the second mode is a productivity/work mode and the second geo-fenced area is an area surrounding the user's place of work). As another example, the first set of activation conditions includes an activation condition that is met during a first set of hours (e.g., daytime hours or work hours) and the second set of activation conditions includes an activation condition that is met during a second set of hours (e.g., nighttime hours), where the first set of hours and the second set of hours are non-overlapping.

[0322] Providing different activation conditions for different reduced notification modes obviates the need for the user to manually activate an appropriate reduced notification mode. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0323] In some embodiments, the first set of activation conditions for the first mode includes (738) a condition that is met when a respective application in a predefined set of applications is running in a foreground of the device. For example, a fitness application running in the foreground automatically triggers an “exercise” reduced notification mode on the electronic device (e.g., as described with reference to FIGS. 5AH-5AI). In some embodiments, the activation conditions are met when any application in the predefined set of applications is running in the foreground of the device (e.g., when the first mode is an exercise mode, any exercise application running in the foreground is sufficient to activate the first mode or cause output of a suggestion to activate the first mode). In some embodiments, the predefined set of applications includes a group (e.g., a plurality) of applications (e.g., a group of health or fitness applications). In some embodiments, the predefined set of applications are grouped by attribute (e.g., the applications are tagged as health or fitness applications by the developer or user). In some embodiments, the predefined set of applications comprises applications in a respective sub-directory of the device (e.g., within a health or fitness folder on an application springboard).

[0324] Automatically activating a reduced notification mode when a predefined application is “foregrounding” obviates the need for the user to manually activate the appropriate reduced notification mode. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0325] In some embodiments, the first mode is (740) associated with a first set of expiration conditions (e.g., automatic expiration conditions for the first mode, such as the auto-expiration condition “Until 5 PM” for the productivity mode shown in FIG. 5E). In response to detecting the first set of expiration conditions, the device automatically, without user intervention, de-activates the first mode. In some embodiments, the second mode is associated with a second set of expiration conditions (e.g., automatic expiration conditions for the second mode, such as Near Work” for the social mode) different from the first set of expiration conditions. In response to detecting the second set of expiration conditions, the device automatically, without user intervention, de-activates the second mode.

[0326] Providing different auto-expiration conditions for the different reduced notification modes obviates the need for the user to manually de-activate an activated reduced notification mode). Automatically de-activating a reduced notification mode also reduces the risk that a user will forget to de-activate the reduced notification mode and will miss an important notification. Performing an operation when a set of conditions has been met without requiring further user input enhances the

operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0327] It should be understood that the particular order in which the operations in FIGS. 7A-7C have been described is merely one example and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. In some embodiments, one or more operations of method **700** are combined, supplemented, or replaced with one or more operations of other methods described herein (e.g., method **600** and/or method **800** and/or method **900**).

[0328] FIGS. 8A-8E are flow diagrams depicting a method **800** of activating a reduced notification mode (e.g., a “do-not-disturb” mode) of an electronic device, in accordance with some embodiments. Although some of the examples which follow will be given with reference to inputs on a touch-sensitive display in which a touch-sensitive surface and a display are combined, in some embodiments, the device detects inputs on a touch-sensitive surface **451** that is separate from the display **450**, as shown in FIG. 4B.

[0329] In some embodiments, method **800** is performed by an electronic device (e.g., portable multifunction device **100**, FIG. 1A) and/or one or more components of the electronic device (e.g., I/O subsystem **106**, operating system **126**, etc.). In some embodiments, method **800** is governed by instructions that are stored in a non-transitory computer-readable storage medium and that are executed by one or more processors of a device, such as the one or more processors **122** of device **100** (FIG. 1A). For ease of explanation, the following describes method **800** as performed by device **100**. In some embodiments, with reference to FIG. 1A, the operations of method **800** are performed by or use, at least in part, operating system **126**, communication module **128**, and/or graphics module **132**, as well as a touch-sensitive display (e.g., touch screen **112**). Some operations in method **800** are, optionally, combined and/or the order of some operations is, optionally, changed.

[0330] As described below, method **800** (and associated interfaces) provides a suggestion to a user for activation of a reduced notification mode when a set of conditions are met after the user has repeatedly and manually activated a particular reduced notification mode under the same or similar conditions. For example, based on a plurality of manual activations, a device will output a suggestion to activate a reduced notification mode or provide a suggestion to setup an auto-activation of the reduced notification mode. Providing such suggestions reduces the number, extent, and/or nature of the inputs from a user (e.g., by obviating the need for the user to manually create or activate a reduced notification mode under the same or similar conditions), thereby creating a more efficient human-machine interface.

[0331] Device **100** detects (**802**) a plurality of manual activations of a first mode (e.g., a reduced notification mode, sometimes called a do-not-disturb mode) on an electronic device (e.g., by toggling virtual button **504-b**). The first mode, while active, prevents (or reduces) output of notifications when communications of a first type are received (e.g., non-whitelisted notifications). In some embodiments, the device detects and stores/logs the time and/or device location (e.g., geographical location) when a given manual activation of the reduced notification mode occurs.

[0332] After detecting the plurality of manual activations of the first mode (**804**): device **100** automatically determines, based on the plurality of manual activations of the first mode, a set of conditions that correspond to manual activations of the first mode, and outputs, at the device, a suggestion for activation of the first mode at the electronic device.

[0333] In some embodiments, the set of conditions includes (**806**) a time-of-day condition. For example, the device detects that the user has repeatedly turned on a reduced notification mode during “nighttime” or “daytime” and suggests a reduced notification period of appropriate length (e.g., 8, 10, 12 hours). In some embodiments, the set of conditions includes a location condition. In

some embodiments, the set of conditions includes a calendar condition. For example, when the device detects a predetermined number of manual activations (e.g., five) of the reduced notification mode over a predetermined period of time (e.g., two weeks), and the manual activations meet grouping criteria (e.g., the manual activations were within an hour of the same time each night), the device determines a time condition (e.g., a mean of the manual activation times rounded to the nearest quarter of an hour) and, optionally, associates a location condition with the manual activations (e.g., a modal location of the device during the manual activations).

[0334] Providing automatic reduced notification activation conditions, as described below, based on time-of-day, location, and/or a user's calendar increases the flexibility of the automatic reduced notification functionality (e.g., the functionality is useful in a broader array of contexts). Providing automatic reduced notification activation conditions based on time-of-day, location, and/or a user's calendar also obviates the need for the user to manually activate the reduced notification mode in a broader array of contexts. Performing an operation when a set of conditions has been met without requiring further user input and reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0335] After outputting the suggestion, device **100** receives (**808**) a response that accepts the suggestion for activation of the first mode (e.g., a gesture on an “accept” or “ok” affordance or a voice command) (e.g., an input on the “Ok” affordance, FIG. 5AM, or by contact **580**, FIG. 5AN).

[0336] In response to receiving the response that accepts the suggestion (e.g., after receiving the response that accepts the suggestion), device **100** changes (**809**) settings at the device that are associated with the first mode.

[0337] In some embodiments, the suggestion for activation of the first mode at the electronic device is a suggestion to activate the first mode that is provided in response to detecting the set of conditions (e.g., as shown in FIG. 5AM). In some embodiments, the suggestion is output upon detecting the set of conditions. In some embodiments, changing the settings at the device that are associated with the first mode includes activating the first mode (e.g., upon acceptance of the suggestion). In some embodiments, the electronic device automatically suggests the reduced notification mode whenever the electronic device subsequently detects the automatic reduced notification mode conditions.

[0338] Providing a suggestion to activate a reduced notification mode when a set of conditions are met (e.g., after the user has repeatedly and manually activated a particular reduced notification mode under the same or similar conditions) obviates the need for the user to manually schedule a reduced notification mode for the same or similar conditions. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by reducing user mistakes when operating/interacting with the device).

[0339] In some embodiments, the set of conditions are automatic reduced notification mode conditions. In some embodiments, the suggestion for activation of the first mode is (**810**) a suggestion to automatically activate the first mode, without user intervention, when the electronic device detects the set of conditions (e.g., as described with reference to FIGS. 5AJ and 5AN-5AP). In some embodiments, the suggestion is provided upon detecting a respective manual activation of the reduced notification mode. In some embodiments, changing the settings at the device that are associated with the first mode includes setting the device to automatically activate the first mode when the electronic device detects the set of conditions that correspond to the manual activations of the first mode. In some embodiments, after receiving the response that accepts the suggestion and while the device is not in the first mode, device **100** detects (**812**) the set of conditions. In some embodiments, in response to detecting the set of conditions, device **100** automatically, without user intervention, activates (**814**) the first mode (e.g., as described with reference to FIGS. 5AN-5AP).

[0340] In some embodiments, after receiving the response that accepts the suggestion, the electronic device automatically activates the reduced notification mode whenever the electronic device subsequently detects the automatic reduced notification mode conditions (e.g., until the user disables the automatic activation of the do-not-disturb mode).

[0341] Automatically activating a reduced notification mode when a set of conditions are met (e.g., after the user has repeatedly and manually activated a particular reduced notification mode under the same or similar conditions) obviates the need for the user to manually create a reduced notification mode under the same or similar conditions. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by reducing user mistakes when operating/interacting with the device).

[0342] In some embodiments, after detecting the set of conditions and while the device is in the first mode (e.g., after receiving the response that accepts the suggestion), device **100** detects (**816**) that the set of conditions is no longer met. In response to detecting that the set of conditions is no longer met, device **100** automatically, without user intervention, de-activates (**818**) the first mode (e.g., as described with reference to FIG. 5AQ).

[0343] Automatically deactivating the reduced notification mode when the set of conditions is no longer met obviates the need for the user to manually de-activate the reduced notification mode. Automatically deactivating the reduced notification mode also reduces the risk that a user will miss an important notification. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0344] In some embodiments, after receiving the response that accepts the suggestion for activation of the first mode, device **100** outputs (**820**) expiration options that correspond to expiration conditions for automatically de-activating the first mode (e.g., automatic expiration conditions for the first mode). In some embodiments, the set of expiration conditions includes a single expiration condition (e.g., “turn reduced notification mode off in 1 hour”, “turn reduced notification mode off when I leave this location”, or “turn reduced notification mode off at the end of this calendar appointment”). In some embodiments, the set of expiration conditions includes a plurality of user-selectable expiration conditions (e.g., each expiration condition has a corresponding user-selectable displayed affordance). In some embodiments, the expiration options are output in response to receiving the response that accepts the suggestion to automatically activate the first mode when the electronic device detects the set of conditions.

[0345] In some embodiments, the expiration options output in operation **820** include at least one expiration option having an expiration condition determined from a plurality of manual de-activations of the first mode (e.g., activation/expiration options **578-a**, **578-b**, and **578-d**, FIG. 5AN). For example, device **100** detects (**822**) a plurality of manual de-activations of the first mode on the electronic device. Device **100** automatically determines, based on the plurality of manual de-activations of the first mode, a condition that corresponds to manual de-activations of the first mode. The expiration options include an option corresponding to the condition.

[0346] Automatically determining and suggesting a deactivation condition for the reduced notification mode simplifies the setup of the suggested reduced notification mode once the suggested mode is accepted. Performing an operation when a set of conditions has been met without requiring further user input and reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0347] In some embodiments, outputting the expiration options includes (**824**) displaying the expiration options in a user interface for modifying expiration options for the first mode. And the

option that is based on manual de-activations of the first mode is visually distinguished from other expiration options for the first mode displayed in the user interface for modifying expiration options for the first mode (e.g., activation/expiration options **578-a**, **578-b**, and **578-d**, FIG. 5AN, are shown in bold and underlined).

[0348] Visually distinguishing expirations options that are based on the plurality of manual de-activations of the reduced notification mode aides a user's selection of an appropriate auto-expiration condition for the suggested mode. Providing improved feedback enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0349] In some embodiments, outputting the expiration options includes **(826)** displaying the expiration options in a user interface for modifying expiration options for the first mode (e.g., a user interface for setting up the automatic reduced notification mode, including auto-activate and auto-de-activate options, as shown and discussed with reference to FIG. 5AN). And the option based on manual de-activations of the first mode is automatically set to the condition that corresponds to manual de-activations of the first mode in the user interface for modifying the expiration options for the first mode (e.g., expiration options **578-a**, **578-b**, and **578-d**, FIG. 5AN, are initially set to the automatically determined conditions, where the automatically determined conditions are determined based on the plurality of manual activations/de-activations).

[0350] Auto-setting the expiration options that are based on the plurality of manual de-activations of the reduced notification mode aides a user's selection of an appropriate auto-expiration condition. Performing an operation when a set of conditions has been met without requiring further user input and reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0351] In some embodiments, after outputting the expiration options, device **100** receives **(828)** a response (e.g., a gesture on an “accept” or “ok” affordance or a voice command) that accepts a first expiration option corresponding to an expiration condition for automatically de-activating the first mode. After receiving the response that accepts the first expiration option, device **100** detects **(830)** that the corresponding first expiration condition is met. In response to detecting that the first expiration condition is met, device **100** automatically, without user intervention, de-activates **(832)** the first mode (e.g., as described with reference to FIGS. 5AU-5AW).

[0352] With reference to operations **820-832**, automatically displaying de-activation conditions for the reduced notification mode simplifies the setup of the suggested reduced notification mode once the suggested mode is accepted. Performing an operation when a set of conditions has been met without requiring further user input and reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0353] In some embodiments, device **100** detects **(834)** a plurality of manual activations of a second mode on the electronic device. The second mode, while active, prevents (or reduces) output of notifications when communications of a second type are received. In some embodiments, the first mode is a first reduced notification mode that has a first set of whitelisting criteria for allowing output of notifications when communications are received (e.g., communications not of the first type) and the second mode is a second reduced notification mode, different from the first, that has a second set of whitelisting criteria for allowing output of notifications when communications are received (e.g., communications not of the second type).

[0354] In some embodiments, after detecting the plurality of manual activations of the second mode: device **100** automatically determines **(836)**, based on the plurality of manual activations of

the second mode, a second set of conditions that correspond to manual activations of the second mode; and, outputs, at the device, a second suggestion for activation of the second mode at the electronic device. For example, different reduced notification modes (e.g., social mode and productivity mode) can have different auto-activation/auto-deactivation conditions, or different activation/de-activation suggestion conditions, as described with reference to FIGS. 5AJ-5AQ (“sleep mode” conditions) and FIGS. 5AR-5AY (“productivity mode” conditions).

[0355] In some embodiments, after outputting the second suggestion, device **100** receives (**838**) a response that accepts the second suggestion for activation of the second mode. Subsequently, in response to detecting the second set of conditions, device **100** changes (**840**) settings at the device that are associated with the second mode (e.g., activates the second mode upon receiving the response or sets the device to automatically activate the second mode upon detecting the set of conditions).

[0356] Providing a suggestion to a user to configure the device to automatically activate a particular reduced notification mode when a particular set of conditions are met (e.g., after the user has repeatedly and manually activated a particular reduced notification mode under the same or similar conditions) obviates the need for the user to manually activate a particular reduced notification mode under the same or similar conditions. Performing an operation when a set of conditions has been met without requiring further user input and reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0357] In some embodiments, device **100** detects (**842**) a plurality of manual de-activations of the first mode on the electronic device (e.g., by toggling virtual button **504-b**, as described with reference to FIGS. 5J-5K).

[0358] In some embodiments, after detecting the plurality of manual de-activations of the first mode: device **100** automatically determines (**844**) based on the plurality of manual de-activations of the first mode, a third set of conditions that correspond to the manual de-activations of the first mode; and, outputs, at the device, a third suggestion for de-activation of the first mode. In some embodiments, after outputting the third suggestion, device **100** receives (**846**) a response that accepts the third suggestion for de-activation of the first mode. Subsequently, in response to detecting the third set of conditions, device **100** automatically, changes (**848**) settings at the device associated with de-activating the first mode (e.g., as described with reference to FIGS. 5AR-5AW).

[0359] Automatically determining and suggesting a set of automatic deactivation conditions for the reduced notification mode obviates the need for the user to manually de-activate the reduced notification mode. Performing an operation when a set of conditions has been met without requiring further user input and reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

[0360] It should be understood that the particular order in which the operations in FIGS. **8A-8E** have been described is merely one example and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. In some embodiments, one or more operations of method **8A-8E** are combined, supplemented, or replaced with one or more operations of other methods described herein (e.g., method **600** and/or method **700** and/or method **900**).

[0361] FIGS. **9A-9D** are flow diagrams illustrating a method **900** of providing notifications when a reduced notification mode of an electronic device is deactivated, in accordance with some embodiments. Although some of the examples which follow will be given with reference to inputs

on a touch-sensitive display in which a touch-sensitive surface and a display are combined, in some embodiments, the device detects inputs on a touch-sensitive surface **451** that is separate from the display **450**, as shown in FIG. **4B**.

[0362] In some embodiments, method **900** is performed by an electronic device (e.g., portable multifunction device **100**, FIG. **1A**) and/or one or more components of the electronic device (e.g., I/O subsystem **106**, operating system **126**, etc.). In some embodiments, method **900** is governed by instructions that are stored in a non-transitory computer-readable storage medium and that are executed by one or more processors of a device, such as the one or more processors **122** of device **100** (FIG. **1A**). For ease of explanation, the following describes method **900** as performed by device **100**. In some embodiments, with reference to FIG. **1A**, the operations of method **900** are performed by or use, at least in part, operating system **126**, communication module **128**, and/or graphics module **132**, as well as a touch-sensitive display (e.g., touch screen **112**). Some operations in method **900** are, optionally, combined and/or the order of some operations is, optionally, changed.

[0363] As described below, method **900** provides a more efficient, less intrusive way to provide notifications to users after they have been sleeping. Providing content from individual notifications (e.g., the identity of the sender and/or text from the corresponding communications) to waking users only after displaying an initial wake screen without content from individual notifications enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes—such as misreading, overlooking, or otherwise mishandling notifications about communications received while sleeping—when operating/interacting with the device upon waking). For battery-operated electronic devices, enabling a user to handle notifications more efficiently upon waking conserves power and increases the time between battery charges.

[0364] In some embodiments, prior to the electronic device being in a reduced notification mode (e.g., a sleep mode), device **100** displays (**902**) a third user interface, such as user interface **502** shown in FIG. **5AZ-5BA**, that includes: a background and one or more user interface objects displayed in a foreground of the third user interface. While displaying the third user interface, device **100** detects activation of the reduced notification mode. For example, the device **100** automatically (e.g., without user input) activates a sleep mode in accordance with detection of an activation condition that was previously set for the sleep mode. Before detecting the activation of the reduced notification mode, the background of the third user interface is displayed (**904**) at a predefined brightness that corresponds to the device not being in the reduced notification mode. Automatically reducing the brightness of the user interface in the reduced notification mode conserves power and increases the time between battery charges.

[0365] In some embodiments, in response to detecting the activation of the reduced notification mode, device **100** reduces (**906**) a brightness of the background of the third user interface, as shown in FIG. **5BB** (which illustrates the background of user interface **502** with shading to indicate a reduced brightness). In some embodiments, before detecting activation of the reduced notification mode, the background of the third user interface is displayed with a first brightness (e.g., user interface **502** in FIGS. **5AZ** and **5BA** are displayed at the first brightness). After detecting activation of the reduced notification mode, the background of the third interface is displayed at a second brightness that is less bright than the first brightness (e.g., user interface **502** in FIG. **5BB** upon activation of “Sleep Mode” at 10:00 PM is displayed at the second brightness).

[0366] In some embodiments, in response to detecting the activation of the reduced notification mode, device **100** maintains (**908**) a brightness of the one or more user interface objects displayed in the foreground of the third user interface. In some embodiments, before detecting activation of the reduced notification mode, the foreground of the third user interface is displayed with the first brightness. After detecting activation of the reduced notification mode, the foreground of the third user interface (e.g., user interface **502**) is maintained at the first brightness. In some embodiments,

the foreground of user interface **502** includes a time and/or date indication, and/or virtual buttons **504-a** to **504-c**. Maintaining the brightness of other of foreground objects allows the device to be used while the background brightness is reduced, which conserves power and increases the time between battery charges.

[0367] In some embodiments, the reduced notification mode is set up automatically by setting an alarm (e.g., the time of the set alarm corresponds to an alert condition for the reduced notification mode). In some embodiments, the device allows the user to set a sleep time and a wake time for one or more days of the week. For example, between the sleep time (e.g., 10 PM in FIG. 5BB) and the wake time (e.g., 6:15 AM in FIG. 5BD), the reduced notification mode is automatically (or by default) activated.

[0368] While the electronic device (e.g., device **100**) is in the reduced notification mode, device **100** receives (**910**) one or more communications. In some embodiments, the one or more communications are received prior to detecting the alert condition for the reduced notification mode.

[0369] In some embodiments, in response to receiving the one or more communications while the device is in the reduced notification mode, device **100** stores (**912**) the one or more communications without displaying, on the display, notifications with content from any one of the one or more communications. Storing the one or more communications, without providing notifications, enhances the operability of the device by facilitating a less intrusive way to provide notifications to users after they have been sleeping. This makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes—such as misreading, overlooking, or otherwise mishandling notifications—when operating/interacting with the device upon waking).

[0370] For example, in some embodiments, the content includes the identity of the sender (e.g., or contact information of the sender) and/or text/audio messages from the corresponding communications. For example, as described with reference to FIGS. 5AZ-5BM, the device **100** received messages from Bob (at 11:22 PM on Saturday) and Alice (at 12:04 AM on Sunday) while the device is in the reduced notification mode (from 10 PM on Saturday until 6:15 AM on Sunday), and thus stores the one or more communications (e.g., messages) without displaying notifications with content while the device is in the reduced notification mode.

[0371] After receiving the one or more communications (e.g., messages from Bob and Alice), device **100** detects (**914**) an alert condition for the reduced notification mode. For example, the device **100** detects a wake time (e.g., an alarm time) that was previously set for the sleep mode.

[0372] In some embodiments, when communications of a first type are received while the electronic device is in the reduced notification mode, device **100** prevents (**916**) output of notifications that correspond to the communications of the first type. Forgoing display of notifications received while the reduced notification mode is active avoids disturbing the user at times when the user does not want to be disturbed. Providing notifications at appropriate times enhances the operability of the device by making the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes—such as misreading, overlooking, or otherwise mishandling notifications about communications received at inopportune times).

[0373] In some embodiments, communications of the first type are communications that are not whitelisted in the reduced notification mode. In some embodiments, when communications of a second type are received while the electronic device is in the reduced notification mode, the electronic device outputs notifications corresponding to the communications of the second type (e.g., upon receiving the communications of the second type). As an example of the second type of communication, in some embodiments, certain applications are whitelisted for various reduced notification modes. As another example of the second type of communication, the user of the electronic device may set the device to provide notifications of calls and/or messages from specific

user contacts (e.g., “Favorites”) even while the reduced notification is active. For example, the user sets the device to allow calls and/or messages from his or her family, or allow calls and/or messages when a single contact calls multiple times within a predefined time window (e.g., in response to a non-favorite friend calling 3 times within 3 minutes, the device provides a notification).

[0374] In response to detecting the alert condition for the reduced notification mode, device **100** displays (**918**) a first user interface that includes a first affordance which, when activated, causes the deactivation of the reduced notification mode of the electronic device. For example, device **100** displays an alarm screen (e.g., user interface **502-a**) that includes a “stop” button (e.g., affordance **5110**).

[0375] In some embodiments, the first user interface (e.g., user interface **502-a**) does not display (**920**), on the display, content from any one of the one or more communications received while in the reduced notification mode. Providing content from individual notifications (e.g., the identity of the sender and/or text from the corresponding communications) to waking users after displaying an alarm screen without content from individual notifications enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes-such as misreading, overlooking, or otherwise mishandling notifications-when operating/interacting with the device upon waking).

[0376] In some embodiments, the first user interface displays an indicia of the number of communications received while in the reduced notification mode, without displaying content (e.g., the identity of the sender and/or text/audio from the corresponding communications) from any one of the one or more communications. For example, the user interface **502-a** (e.g., an “alarm” user interface) provides an indication that there are “2 notifications available” (e.g., a message from Bob and Alice received during the reduced notification mode). In some embodiments, the indicia of the number of communications further includes outstanding notifications that were received prior to the device being in the reduced notification mode. For example, the user interface **502-a** indicates that there are “3 notifications available,” including the two missed notifications (from Bob and Alice) during the reduced notification mode, and the outstanding (e.g., not yet dismissed) notification from the previous day (e.g., a calendar invitation).

[0377] In some embodiments, the first user interface includes (**922**) a second affordance (e.g., “snooze” affordance **5108**) which, when activated, causes delay of the deactivation of the reduced notification mode.

[0378] In some embodiments, in response to detecting the alert condition for the reduced notification mode, device **100** provides (**924**) an audio output and/or a tactile output that indicates that the alert condition has been met.

[0379] While displaying the first user interface, device **100** detects (**926**) a first input that activates the first affordance. For example, device **100** detects a tap gesture (e.g., input **5116**) on the “stop” icon on the alarm screen, as shown in FIG. 5BH.

[0380] In some embodiments, in response to detecting the first input that activates the first affordance (**928**): in accordance with a determination that location-services are active on the electronic device, device **100** provides location-based information (e.g., local weather information **5118** as shown in FIG. 5BI) in a second user interface (e.g., user interface **502-b**) and in accordance with a determination that location services are not active on the electronic device, device **100** forgoes providing location-based information in the second user interface. Automatically providing weather or other location-based information to the user in the morning, when available, without user input as soon as the user wakes up provides the user with relevant information for their day without requiring navigation to a specific application. The device performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0381] In some embodiments, in response to detecting the activation of the reduced notification mode, device **100** reduces (**930**) a brightness of the display (e.g., as explained above with reference to FIG. 5BB). For example, the brightness is reduced from a first brightness level to a second brightness level, where the second brightness level is less bright than the first brightness level. After detecting the alert condition for the reduced notification mode (e.g., after the set time for the alarm is detected at 6:15 AM), device **100** maintains a reduced brightness of the display (e.g., the user interface **502-a** (alarm screen), shown in FIGS. 5BD, 5BE, 5BG and 5BH, remains at the reduced brightness). For example, after detecting the alert condition for the reduced notification mode, while displaying the first user interface **502-a**, and before detecting the first input that activates the first affordance, the first user interface is displayed at the second brightness level. [0382] While displaying the first user interface (e.g., user interface **502-a**) that includes the first affordance (e.g., “stop” affordance **5110**) and the second affordance (e.g., “snooze” affordance **5108**), device **100** detects a third input (e.g., input **5112**, FIG. 5BE) that activates the second affordance (e.g., activates the “snooze” affordance). In response to detecting the third input, device **100** delays the deactivation of the reduced notification mode, while maintaining the reduced brightness of the display (e.g., at the second brightness level), as shown in FIG. 5BF. In response to detecting the first input (e.g., input **5116**, FIG. 5BH) that activates the first affordance (e.g., activates “stop” affordance **5110**), device **100** increases the brightness of the display (e.g., from the second brightness level to the first brightness level that is greater than the second brightness level). For example, after activation of the “stop” affordance, the reduced notification mode is deactivated and the brightness of the display is increased to the first brightness level (e.g., the first brightness level of the display in FIGS. 5AZ and 5BA).

[0383] In some embodiments, after (e.g., in response to) detecting the alert condition for the reduced notification mode, device **100** displays (**932**) the first user interface (e.g., user interface **502-a**) at a first brightness level. In some embodiments, the first brightness level is selected by the user or is set to a default first brightness level. While displaying the first user interface that includes the first affordance (e.g., “stop” affordance **5110**) and the second affordance (e.g., “snooze” affordance **5108**) at the first brightness level, device **100** detects a third input (e.g., input **5112**, FIG. 5BE) that activates the second affordance. In response to detecting the third input, device **100** reduces the brightness of the first user interface to a second brightness level that is less than the first brightness level. Upon expiration of a predefined delay time (e.g., 10 minutes), device **100** increases the brightness of the first user interface to the first brightness level. For example, the second brightness level is represented by shading in FIG. 5BF, and at the expiration of the predefined time (e.g., at 6:25 AM) shown in FIG. 5BG, the brightness of the display is no longer shaded, representing an increase in brightness from the display in FIG. 5BF. Maintaining the reduced brightness while the deactivation of the reduced notification mode is delayed conserves power and increases the time between battery charges.

[0384] In response to detecting the first user input (e.g., input **5116**, FIG. 5BH) that activates the first affordance (**934**), device **100** deactivates the reduced notification mode, and displays, on the display, a second user interface (e.g., user interface **502-b**), wherein the second user interface does not display content from any of the one or more communications. In some embodiments, the second user interface displays an indicia of the number of communications received while in the reduced notification mode (e.g., displayed as text “2 notifications” on user interface **502-b** or as part of the “notifications” icon **5120** in FIG. 5BI), without displaying content (e.g., the identity of the sender and/or text) from any one of the one or more communications.

[0385] In some embodiments, the second user interface includes (**936**) a second affordance (e.g., “notifications” affordance **5120**, FIG. 5BI) which, when activated, causes display of notifications (e.g., as shown in FIG. 5BK) for at least some of the one or more communications received while in the reduced notification mode.

[0386] While the second user interface (e.g., user interface **502-b**) is displayed, device **100** detects

(938) a second input (e.g., input **5122**, FIG. 5BJ). In some embodiments, the second input activates (940) the second affordance (e.g., the “Notifications” affordance **5120**). For example, a tap gesture on the “notifications” icon in FIG. 5BJ would activate the “notifications” affordance. Alternatively, in some embodiments, the second input is a vertical swipe gesture, such as a vertically upward swipe gesture from the bottom of the display (e.g., the gesture does not start on an affordance). Providing an affordance which causes display of notifications from an initial screen that does not include content from notifications reduces the cognitive burden on the user while providing easy access to notifications. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device).

[0387] In response to detecting the second input, device **100** displays (942) notifications (e.g., notifications **5124-a** through **5124-c**) that include content (e.g., identity of the sender and/or text) for at least some of the one or more communications received while the electronic device was in the reduced notification mode. For example, device **100** displays notifications in user interface **502-c**. As described above, in some embodiments, user interface **502-c** is an updated version of user interface **502** (e.g., updated with overlays including the notifications), or is a distinct user interface.

[0388] In some embodiments, before activation of the reduced notification mode, device **100** receives (944) a first plurality of communications (e.g., including calendar invitation notification **5124-c** received Saturday at 5:15 PM, before activation of the reduced notification mode on Saturday at 10:00 PM). While the reduced notification mode is active (e.g., between 10:00 PM and 6:15 AM), device **100** receives a second plurality of communications (e.g., messages from Bob and Alice). After (e.g., in response to) receiving the second input (e.g., input **5122** or the vertical swipe gesture), device **100** displays (e.g., in user interface **502-c**) notifications that correspond to the first plurality of communications separately from displaying notifications that correspond to the second plurality of communications.

[0389] In some embodiments, device **100** displays (946), in a first portion of the second user interface (e.g., the “From yesterday” portion shown in FIG. 5BK), notifications corresponding to the first plurality of communications (e.g., calendar notification **5124-c**). In some embodiments, device **100** displays, in a second portion of the second user interface (e.g., the “During sleep mode” portion shown in FIG. 5BK), visually distinct from the first portion of the second user interface, notifications corresponding to the second plurality of communications (e.g., notifications **5124-a** and **5124-b**).

[0390] Displaying notifications that were received at different times allows a user to easily navigate between notifications that were missed while in the reduced notification mode and notifications that they may have seen previously before the device was in reduced notification mode. Separately displaying individual notifications to waking users enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes-such as misreading, overlooking, or otherwise mishandling notifications-when operating/interacting with the device upon waking).

[0391] In some embodiments, before activation of the reduced notification mode, device **100** displays (948) the notifications corresponding to the first plurality of communications. For example, the device **100** displays notification **5124-c** (from FIG. 5BK) on user interface **502** in FIG. 5AZ, before activation of the reduced notification mode. In response to activation of the reduced notification mode, device **100** removes from the display the notifications corresponding to the first plurality of communications. For example, device **100** ceases display of notification **5124-c** in FIG. 5BB, after (e.g., in response to) activation of the reduced notification mode.

[0392] It should be understood that the particular order in which the operations in FIGS. 9A-9D have been described is merely one example and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would

recognize various ways to reorder the operations described herein. In some embodiments, one or more operations of method **9A-9D** are combined, supplemented, or replaced with one or more operations of other methods described herein (e.g., methods **600**, **700** and/or **800**).

[0393] The operations described above with reference to FIGS. **6A-6E**, **7A-7C**, **8A-8E** and **9A-9D** are, optionally, implemented by components depicted in FIGS. **1A-1B**. For example, detecting operation **602** and/or detecting operation **610** are, optionally, implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136-1**. A respective event recognizer **180** of application **136-1** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface (or whether rotation of the device) corresponds to a predefined event or sub-event, such as selection of an object on a user interface, or rotation of the device from one orientation to another. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** optionally uses or calls data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1A-1B**.

[0394] The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, to thereby enable others skilled in the art to best use the invention and various described embodiments with various modifications as are suited to the particular use contemplated.

Claims

1. A method, comprising: at an electronic device with a display: receiving a communication; and, in response to receiving the communication: in accordance with a determination that a first mode is active on the electronic device: in accordance with a determination that the communication meets respective criteria for the first mode wherein the respective criteria for the first mode include a first list of applications for the first mode, outputting, at the electronic device, a notification that corresponds to the communication in a first manner; and, in accordance with a determination that the communication does not meet the respective criteria for the first mode, forgoing outputting the notification that corresponds to the communication in the first manner; and, in accordance with a determination that a second mode is active on the electronic device: in accordance with a determination that the communication meets respective criteria for the second mode, wherein the respective criteria for the second mode are different from the respective criteria for the first mode, the respective criteria for the second mode include a second list of applications for the second mode, wherein the second list of applications is different from the first list of applications, outputting, at the electronic device, the notification that corresponds to the communication in the first manner; and, in accordance with a determination that the communication does not meet the respective criteria for the second mode, forgoing outputting the notification that corresponds to the communication in the first manner.

2. The method of claim 1, wherein: the respective criteria for the first mode include a criterion that is met when the first application is in the first list of applications for the first mode.

3. The method of claim 2, wherein: the respective criteria for the second mode include a criterion that is met when the first application is in the second list of applications for the second mode; and

the second list of applications for the second mode includes one or more applications that are not in the first list of applications for the first mode.

4. The method of claim 2, wherein: the first mode is a productivity mode; the second mode is a social mode, distinct from the productivity mode; and the method includes: initializing the first list of applications for the productivity mode to include applications relating to productivity; and initializing the second list of applications for the social mode to include social media applications.

5. The method of claim 2, including: receiving an input to add a respective application to the first list of applications for the first mode; in response to receiving the input: adding the respective application to the first list of applications for the first mode.

6. The method of claim 1, wherein: the first mode is associated with a first set of activation conditions, wherein in response to detecting the first set of activation conditions, the electronic device automatically, without user intervention, activates the first mode; and the second mode is associated with a second set of activation conditions, different from the first set of activation conditions, wherein in response to detecting the second set of activation conditions, the electronic device automatically, without user intervention, activates the second mode.

7. The method of claim 6, wherein the first set of activation conditions for the first mode includes a condition that is met when a respective application in a predefined set of applications is running in a foreground of the electronic device.

8. The method of claim 1, wherein: the first mode is associated with a first set of expiration conditions, wherein in response to detecting the first set of expiration conditions, the electronic device automatically, without user intervention, de-activates the first mode; and the second mode is associated with a second set of expiration conditions different from the first set of expiration conditions, wherein in response to detecting the second set of expiration conditions, the electronic device automatically, without user intervention, de-activates the second mode.

9. The method of claim 1, including: while the first mode is active on the electronic device, detecting de-activation of the first mode; and, in response to detecting de-activation of the first mode, outputting, at the electronic device, notifications that correspond to communications received while in the first mode that were not presented while in the first mode.

10. An electronic device, comprising: a display; one or more processors; memory; and one or more programs, wherein the one or more programs are stored in the memory and configured to be executed by the one or more processors, the one or more programs including instructions for: receiving a communication; and, in response to receiving the communication: in accordance with a determination that a first mode is active on the electronic device: in accordance with a determination that the communication meets respective criteria for the first mode wherein the respective criteria for the first mode include a first list of applications for the first mode, outputting, at the electronic device, a notification that corresponds to the communication in a first manner; and, in accordance with a determination that the communication does not meet the respective criteria for the first mode, forgoing outputting the notification that corresponds to the communication in the first manner; and, in accordance with a determination that a second mode is active on the electronic device: in accordance with a determination that the communication meets respective criteria for the second mode, wherein the respective criteria for the second mode are different from the respective criteria for the first mode, the respective criteria for the second mode include a second list of applications for the second mode, wherein the second list of applications is different from the first list of applications, outputting, at the electronic device, the notification that corresponds to the communication in the first manner; and, in accordance with a determination that the communication does not meet the respective criteria for the second mode, forgoing outputting the notification that corresponds to the communication in the first manner.

11. The electronic device of claim 10, wherein: the respective criteria for the first mode include a criterion that is met when the first application is in the first list of applications for the first mode.

12. The electronic device of claim 11, wherein: the respective criteria for the second mode include

a criterion that is met when the first application is in the second list of applications for the second mode; and the second list of applications for the second mode includes one or more applications that are not in the first list of applications for the first mode.

13. A computer-readable storage medium storing one or more programs, the one or more programs comprising instructions which, when executed by an electronic device with a display, cause the electronic device to: receive a communication; and, in response to receiving the communication: in accordance with a determination that a first mode is active on the electronic device: in accordance with a determination that the communication meets respective criteria for the first mode wherein the respective criteria for the first mode include a first list of applications in the first mode, output, at the electronic device, a notification that corresponds to the communication in a first manner; and, in accordance with a determination that the communication does not meet the respective criteria for the first mode, forgo outputting the notification that corresponds to the communication in the first manner; and, in accordance with a determination that a second mode is active on the electronic device: in accordance with a determination that the communication meets respective criteria for the second mode, wherein the respective criteria for the second mode are different from the respective criteria for the first mode, the respective criteria for the second mode include a second list of applications for the second mode, wherein the second list of applications is different from the first list of applications, output, at the electronic device, the notification that corresponds to the communication in the first manner; and, in accordance with a determination that the communication does not meet the respective criteria for the second mode, forgo outputting the notification that corresponds to the communication in the first manner.

14. The computer readable storage medium of claim 12, wherein: the respective criteria for the first mode include a criterion that is met when the first application is in the first list of applications for the first mode.

15. The computer readable storage medium of claim 14, wherein: the respective criteria for the second mode include a criterion that is met when the first application is in the second list of applications for the second mode; and the second list of applications for the second mode includes one or more applications that are not in the first list of applications for the first mode.
