

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250287180

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Koga; Jeffrey et al.

ACTIVE TRUCK TRACKING AND ALERTS FOR RESIDENTIAL REFUSE CAN COLLECTION

Abstract

A system for tracking refuse collection vehicles includes one or more memory devices having instructions stored thereon that, when executed by one or more processors, cause the one or more processors to perform operations including receiving, from a user device, a first user input indicating one or more parameters of a geofence, the geofence defining a virtual perimeter around a geographical location, determining whether the refuse collection vehicle is within the virtual perimeter of the geofence based on a current location of the refuse collection vehicle, and transmitting, to the user device, a first notification based on a determination that the refuse collection vehicle is within the geofence, the first notification indicating to a user of the user device that the refuse collection vehicle is within the geofence.

Inventors: Koga; Jeffrey (Oshkosh, WI), Davis; Emily (Rochester, MN), Kappers; Jerrod (Oshkosh, WI), Schad; Vince (Oshkosh, WI), Messina; Robert S. (Oshkosh, WI), Yakes; Christopher K. (Oshkosh, WI), Rocholl; Joshua D. (Rochester, MN), Hoover; Vincent (Byron, MN), Weckwerth; Clinton T. (Pine Island, MN), Klein; Zachary L. (Rochester, MN), Beck; John (Oshkosh, WI), Chan; Brendan (Oshkosh, WI), Wachter; Skylar A. (Dodge Center, MN), Matsumoto; Dale (Oshkosh, WI), Datema; Bryan S. (Rochester, MN), Clifton; Cody D. (Oshkosh, WI), Wei; Zhenyi (Oshkosh, WI), Dunn; Kevin (Oshkosh, WI)

Applicant: OSHKOSH CORPORATION (Oshkosh, WI)

Family ID: 78286929

Assignee: OSHKOSH CORPORATION (Oshkosh, WI)

Appl. No.: 19/216595

Filed: May 22, 2025

Related U.S. Application Data

Publication Classification

Int. Cl.: **H04W4/021** (20180101); **G06Q50/26** (20240101); **H04W4/029** (20180101); **H04W4/12** (20090101)

U.S. Cl.:

CPC **H04W4/021** (20130101); **G06Q50/26** (20130101); **H04W4/029** (20180201); **H04W4/12** (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS [0001] This application is a continuation of U.S. application Ser. No. 17/232,855, filed Apr. 16, 2021, which claims the benefit of U.S. Provisional Patent Application No. 63/011,586, filed Apr. 17, 2020, which is incorporated herein by reference in its entirety.

BACKGROUND

[0002] Refuse vehicles collect a wide variety of waste, trash, and other material from residences and businesses. Operators of the refuse vehicles transport the material from various waste receptacles within a municipality to a storage or processing facility (e.g., a landfill, an incineration facility, a recycling facility, etc.).

SUMMARY

[0003] One implementation of the present disclosure is a system for tracking refuse collection vehicles. The system includes one or more memory devices having instructions stored thereon that, when executed by one or more processors, cause the one or more processors to perform operations including receiving, from a user device, a first user input indicating one or more parameters of a geofence, the geofence defining a virtual perimeter around a geographical location, determining whether the refuse collection vehicle is within the virtual perimeter of the geofence based on a current location of the refuse collection vehicle, and transmitting, to the user device, a first notification based on a determination that the refuse collection vehicle is within the geofence, the first notification indicating to a user of the user device that the refuse collection vehicle is within the geofence.

[0004] Another implementation of the present disclosure is a method for tracking a refuse collection vehicle. The method includes receiving, by a server and from a user device, a first user input indicating one or more parameters of a geofence, the geofence defining a virtual perimeter around a geographical location, determining, by the server, whether the refuse collection vehicle is within the virtual perimeter of the geofence based on a current location of the refuse collection vehicle, and transmitting, by the server to the user device, a first notification based on a determination that the refuse collection vehicle is within the geofence, the first notification indicating to a user of the user device that the refuse collection vehicle is within the geofence.

[0005] Yet another implementation of the present disclosure is a device including a user interface, one or more processors, and one or more memory devices having instructions stored thereon that, when executed by the one or more processors, cause the one or more processors to receive, via the user interface, a first user input indicating one or more boundaries of a geofence, the geofence

defining a virtual perimeter around a geographical location, transmit the first user input to a remote server, receive a first notification based on a determination that a refuse collection vehicle is within the geofence, the first notification indicating a distance of the refuse collection vehicle from a central point of the geofence, and receive a second notification based on a determination that the refuse collection vehicle has left the geofence.

[0006] Another implementation of the present disclosure is a concrete mixer vehicle. The concrete mixer vehicle includes a mixer drum having an inner volume configured to hold a mixture for transportation and placement. The concrete mixer vehicle also includes a chute configured to receive mixture exiting the mixer drum and direct the mixture. The concrete mixer vehicle also includes a controller configured to transition the concrete mixer vehicle between a first autonomous mode and a second autonomous mode. The controller is configured to operate the mixer drum and the chute to perform a first autonomous action in the first autonomous mode, and operate the mixer drum and the chute to perform a second autonomous action in the second autonomous mode.

[0007] Another implementation of the present disclosure is a method for autonomously operating a concrete mixer vehicle. The method includes detecting a condition indicating that the concrete mixer vehicle is at a concrete plant. The method also includes transitioning the concrete mixer vehicle into an autonomous plant mode in response to detecting the condition that the concrete mixer vehicle is at the concrete plant. The method also includes operating the concrete mixer vehicle according to the autonomous plant mode for an autonomous plant operation. The method also includes detecting a condition indicating that the concrete mixer vehicle is at a jobsite. The method also includes transitioning the concrete mixer vehicle into an autonomous jobsite mode in response to detecting the condition that indicates that the concrete mixer vehicle is at the jobsite. The method also includes operating the concrete mixer vehicle according to the autonomous jobsite mode for an autonomous jobsite operation.

[0008] Another implementation of the present disclosure is a method for autonomously operating a concrete mixer vehicle. The method includes obtaining sensor data from a sensor of the concrete mixer vehicle, the sensor data indicating a jobsite area and one or more structures positioned at the jobsite area. The method also includes identifying boundaries of the one or more structures positioned at the jobsite area based on the sensor data. The method also includes receiving a user input comprising a desired pour area. The method also includes operating the chute and the mixer drum of the concrete mixer vehicle to pour a material according to the user input.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The disclosure will become more fully understood from the following detailed description, taken in conjunction with the accompanying figures, wherein like reference numerals refer to like elements, in which:

[0010] FIGS. 1A and 1B are perspective views of a refuse vehicle, according to some embodiments.

[0011] FIGS. 2A-2C are examples configurations of the refuse vehicle of FIGS. 1A and 1B, according to some embodiments.

[0012] FIG. 3 is a block diagram of a tracking and alert system for residential refuse can collection, according to an exemplary embodiment.

[0013] FIG. 4 is an example diagram of a geofence, according to an exemplary embodiment.

[0014] FIG. 5 is a process for tracking a refuse vehicle and alerting a user for residential refuse can collection, according to an exemplary embodiment.

[0015] FIG. 6 is a side view of a concrete mixer truck with a drum assembly and a control system, according to an exemplary embodiment.

[0016] FIG. 7 is a detailed side view of the drum assembly of the concrete mixer truck of FIG. 6, according to an exemplary embodiment.

[0017] FIG. 8 is a schematic diagram of a drum drive system of the concrete mixer truck of FIG. 1, according to an exemplary embodiment.

[0018] FIG. 9 is a power flow diagram for the concrete mixer truck of FIG. 6 having a drum drive system that is selectively coupled to a transmission with a clutch, according to an exemplary embodiment.

[0019] FIG. 10 is a schematic diagram of a drum drive system of the concrete mixer truck of FIG. 1, according to another exemplary embodiment.

[0020] FIG. 11 is a graphical user interface provided by an interface of the concrete mixer truck of FIG. 6, according to an exemplary embodiment.

[0021] FIG. 12 is a block diagram of a system for selectably transitioning the concrete mixer truck of FIG. 1 between various predefined modes of operation, shown to include a mode controller, according to an exemplary embodiment.

[0022] FIG. 13 is a block diagram of the mode controller of FIG. 12, according to an exemplary embodiment.

[0023] FIG. 14 is an interior view of a cab of the concrete mixer truck of FIG. 6, shown to include a display device, according to an exemplary embodiment.

[0024] FIG. 15 is a method for selectably transitioning a concrete mixer truck between various predefined modes of operation, according to an exemplary embodiment.

[0025] FIG. 16 is a block diagram of the mode controller of FIG. 13 including one or more autonomous modes, according to an exemplary embodiment.

[0026] FIG. 17 is a diagram showing a concrete mixer truck transporting between a plant area and a jobsite while communicating with a geolocation system, according to an exemplary embodiment.

[0027] FIG. 18 is a flow diagram for operating a concrete mixer truck according to different autonomous modes, according to an exemplary embodiment.

[0028] FIG. 19 is a side view of a concrete mixer truck including an electronic control system for autonomous operation of a chute of the concrete mixer truck to pour a slurry material to a jobsite, according to an exemplary embodiment.

[0029] FIG. 20 is a perspective view of a form or structure that can be positioned at the jobsite of FIG. 19, according to an exemplary embodiment.

[0030] FIG. 21 is a perspective view of another form or structure that can be positioned at the jobsite of FIG. 19, according to an exemplary embodiment.

[0031] FIG. 22 is a block diagram of the electronic control system of FIG. 19, according to an exemplary embodiment.

[0032] FIG. 23 is a depiction of a user input device of the electronic control system of FIGS. 19 and 22, according to an exemplary embodiment.

[0033] FIG. 24 is a flow diagram of a process for autonomously operating a chute and mixer drum of a concrete mixer truck to pour a slurry material, according to an exemplary embodiment.

DETAILED DESCRIPTION

[0034] Before turning to the figures, which illustrate certain exemplary embodiments in detail, it should be understood that the present disclosure is not limited to the details or methodology set forth in the description or illustrated in the figures. It should also be understood that the terminology used herein is for the purpose of description only and should not be regarded as limiting.

[0035] According to an exemplary embodiment, a system and methods for tracking a refuse vehicle and alerting a user to the refuse vehicle's location to aid in residential refuse can collection are disclosed herein. The refuse vehicle may be a garbage truck, a waste collection truck, a sanitation truck, etc., configured for side loading, front loading, or rear loading. The refuse vehicle may include a positioning system that includes components such as a global positioning system (GPS)

transceiver, a cellular transceiver, inertia sensors, etc., to determine a location of the refuse vehicle. A server system may determine, based on the location of the refuse vehicle, whether the refuse vehicle is within a geofence established by a customer. When the refuse vehicle enters or exits an area defined by the geofence, an alert may be sent to a device of the customer.

Overview

[0036] Referring first to FIGS. **1A** and **1B**, a refuse vehicle **10** is shown, according to some embodiments. Refuse vehicle **10** may be a garbage truck, a waste collection truck, a sanitation truck, etc., and may be configured as a side-loading refuse vehicle (e.g., as shown in FIG. **1A**), front loading refuse vehicle (e.g., as shown in FIG. **1B**), or a rear-loading refuse vehicle. In other embodiments, refuse vehicle **10** is another type of vehicle (e.g., a skid-loader, a telehandler, a plow truck, a boom lift, etc.). As shown, refuse vehicle **10** includes a chassis, shown as frame **12**; a body assembly, shown as body **14**, coupled to the frame **12** (e.g., at a rear end thereof, etc.); and a cab, shown as cab **16**, coupled to the frame **12** (e.g., at a front end thereof, etc.). The cab **16** may include various components to facilitate operation of the refuse vehicle **10** by an operator, such as a seat, a steering wheel, hydraulic controls, a graphical user interface (e.g., a touchscreen user interface), switches, buttons, dials, etc.

[0037] As shown, refuse vehicle **10** includes a prime mover, shown as engine **18**, coupled to the frame **12** at a position beneath the cab **16**. Engine **18** is configured to provide power to a series of tractive elements, shown as wheels **19**, and/or to other systems of refuse vehicle **10** (e.g., a pneumatic system, a hydraulic system, etc.). Engine **18** may be configured to utilize one or more of a variety of fuels (e.g., gasoline, diesel, bio-diesel, ethanol, natural gas, etc.), according to various exemplary embodiments. According to an alternative embodiment, engine **18** additionally or alternatively includes one or more electric motors coupled to frame **12** (e.g., a hybrid refuse vehicle, an electric refuse vehicle, etc.). The electric motors may consume electrical power from an on-board storage device (e.g., batteries, ultracapacitors, etc.), from an on-board generator (e.g., an internal combustion engine, etc.), and/or from an external power source (e.g., overhead power lines, etc.) and provide power to the systems of refuse vehicle **10**.

[0038] In some embodiments, refuse vehicle **10** is configured to transport refuse from various waste receptacles within a municipality to a storage and/or processing facility (e.g., a landfill, an incineration facility, a recycling facility, etc.). As shown, the body **14** includes a plurality of panels, shown as panels **32**, a tailgate **34**, and a cover **36**. In some embodiments, as shown in FIG. **1B**, body **14** further includes a door, shown as top door **38**, which is movably coupled along cover **36** to seal the opening thereby preventing refuse from escaping the refuse compartment **30** (e.g., due to wind, bumps in the road, etc.). Panels **32**, tailgate **34**, cover **36**, and/or door **38** define a collection chamber (e.g., hopper, etc.), shown as refuse compartment **30**. Loose refuse may be placed into refuse compartment **30** where it may thereafter be compacted. Refuse compartment **30** may provide temporary storage for refuse during transport to a waste disposal site and/or a recycling facility. In some embodiments, at least a portion of body **14** and refuse compartment **30** extend in front of cab **16**. In some embodiments, body **14** and refuse compartment **30** are positioned behind cab **16**.

[0039] In some embodiments, refuse compartment **30** includes a hopper volume and a storage volume. Refuse may be initially loaded into the hopper volume and thereafter compacted into the storage volume. According to an exemplary embodiment, the hopper volume is positioned between the storage volume and cab **16** (i.e., refuse is loaded into a position of refuse compartment **30** behind cab **16** and stored in a position further toward the rear of refuse compartment **30**). In other embodiments, the storage volume is positioned between the hopper volume and cab **16** (e.g., a rear-loading refuse vehicle, etc.).

[0040] As shown in FIG. **1A**, refuse vehicle **10**, when configured as a side-loading refuse vehicle, may include a side-loading lift mechanism/system (i.e., a side-loading lift assembly), shown as lift assembly **100**. Lift assembly **100** includes a grabber assembly, shown as grabber assembly **42**, slidably coupled to a guide, shown as track **20**, and configured to move along an entire length of

the track **20**. Track **20** is shown to extend along substantially an entire height of the body **14** and is configured to cause the grabber assembly **42** to tilt or rotate near an upper height of the body **14**. In other embodiments, the track **20** extends along substantially an entire height of the body **14** on a rear side of the body **14**.

[0041] Grabber assembly **42** is shown to include a pair of actuators, shown as actuators **44**. Actuators **44** are configured to releasably secure a refuse can to grabber assembly **42**, according to an exemplary embodiment. Actuators **44** are selectively repositionable (e.g., individually, simultaneously, etc.) between an engaged position or state and a disengaged position or state. In the engaged position, actuators **44** are rotated towards one other such that the refuse can may be grasped therebetween. In the disengaged position, actuators **44** rotate outwards (e.g., as shown in FIG. 2A) such that the refuse can is not grasped by actuators **44**. By transitioning between the engaged position and the disengaged position, actuators **44** releasably couple the refuse can to grabber assembly **42**.

[0042] In operation, the refuse vehicle **10** may pull up alongside the refuse can, such that the refuse can is positioned to be grasped by the grabber assembly **42** therein. The grabber assembly **42** may then transition into an engaged state to grasp the refuse can. After the refuse can has been securely grasped, the grabber assembly **42** may be transported along the track **20** (e.g., by an actuator) with the refuse can. When the grabber assembly **42** reaches the end of track **20**, grabber assembly **42** may tilt and empty the contents of the refuse can into the refuse compartment **30**. The tilting is facilitated by the path of track **20**. When the contents of the refuse can have been emptied into refuse compartment **30**, the grabber assembly **42** may descend along track **20** and return the refuse can to the ground. Once the refuse can has been placed on the ground, the grabber assembly **42** may transition into the disengaged state, releasing the refuse can.

[0043] As shown in FIG. 1B, refuse vehicle **10**, when configured as a front loading refuse vehicle, may include a front loading lift mechanism/system (i.e., a front loading lift assembly), shown as lift assembly **200**. Lift assembly **200** includes a pair of arms, shown as lift arms **52**, coupled to the frame **12** and/or the body **14** on either side of the refuse vehicle **10** such that the lift arms **52** extend forward of the cab **16** (e.g., a front loading refuse vehicle, etc.). In other embodiments, the lift assembly **200** extends rearward of the body **14** (e.g., a rear-loading refuse vehicle, etc.). In still other embodiments, the lift assembly **200** extends from a side of the body **14** (e.g., a side-loading refuse vehicle, etc.). The lift arms **52** may be rotatably coupled to frame **12** with a pivot (e.g., a lug, a shaft, etc.). As shown, the lift assembly **200** includes first actuators, shown as lift arm actuators **54** (e.g., hydraulic cylinders, etc.), coupled to the frame **12** and the lift arms **52**. The lift arm actuators **54** are positioned such that extension and retraction thereof rotates the lift arms **52** about an axis extending through the pivot, according to an exemplary embodiment.

[0044] An attachment assembly **210** may be coupled to the lift arms **52** of the lift assembly **200**. As shown, the attachment assembly **210** is configured to engage with a first attachment, shown as container attachment **220**, to selectively and releasably secure the container attachment **220** to the lift assembly **200**. In some embodiments, attachment assembly **210** may be configured to engage with a second attachment, such as a fork attachment, to selectively and releasably secure second attachment to the lift assembly **200**. In various embodiments, attachment assembly **210** may be configured to engage with another type of attachment (e.g., a street sweeper attachment, a snow plow attachment, a snowblower attachment, a towing attachment, a wood chipper attachment, a bucket attachment, a cart tipper attachment, a grabber attachment, etc.).

[0045] As shown in FIG. 1B, the lift arms **52** are rotated by the lift arm actuators **54** to lift the container attachment **220** or other attachment over the cab **16**. Lift assembly **200** includes second actuators, shown as articulation actuators **56** (e.g., hydraulic cylinders, etc.). In some embodiments, the articulation actuators **56** are positioned to articulate the attachment assembly **210**. Such articulation may assist in tipping refuse out of the container attachment **220** and/or a refuse can (e.g., coupled to the lift assembly **200** by a fork attachment, etc.) and into the hopper volume of the

refuse compartment **30** through an opening in the cover **36**. The lift arm actuators **54** may thereafter rotate the lift arms **52** to return the empty container attachment **220** to the ground. In some embodiments, top door **38** is movably coupled along the cover **36** to seal the opening thereby preventing refuse from escaping the refuse compartment **30** (e.g., due to wind, bumps in the road, etc.).

[0046] In some embodiments, refuse truck **10** includes a positioning system configured to determine a location of refuse truck **10** during operations. The positioning system may include, for example, a global positioning system (GPS) transceiver, a radio transceiver for a cellular network, inertial sensors, etc. In one example, refuse truck **10** includes at least a GPS transceiver for determining a location of refuse truck **10** as it operates (e.g., traverses a refuse can collection route). In another example, the location of refuse truck **10** may be triangulated based on signals from or more cellular radio transceivers, or by any combination of data from one or more components of a positioning system.

[0047] Referring now to FIGS. 2A-2C, example configurations of refuse vehicle **10** are shown, according to some embodiments. FIGS. 2A-2C may illustrate examples of potential configurations of refuse vehicle **10** in addition to the configurations described above with respect to FIGS. 1A-1B. Specifically, FIG. 2A illustrates a front loading configuration of refuse vehicle **10** with an intermediate storage container. FIG. 2B illustrates another front loading configuration of refuse vehicle **10** with an intermediate storage container that includes an actuator assembly (e.g., similar to container attachment **220**). FIG. 2C illustrates a side-loading configuration of refuse vehicle **10** (e.g., an auto side-loader) with a grabber-tipper assembly configured to engage an industrial or commercial refuse can. It will be appreciated that the configurations shown in FIGS. 2A-2C illustrate example configurations of refuse vehicle **10** and are not intended to be limiting. As described above, refuse vehicle **10** may be configured in any number of front, side, and/or rear-loading configurations, with any type of lift and/or grabber assembly for engaging a commercial or residential refuse can.

Tracking and Alert System

[0048] Referring now to FIG. 3, a tracking and alert system **300** for residential refuse can collection is shown, according to some embodiments. System **300** may track (i.e., determine) a location of refuse vehicle **10** as it operates, such as while refuse vehicle **10** traverses a refuse can collection route. System **300** may alert a customer (e.g., having a refuse can) to the location of refuse vehicle **10** when refuse vehicle **10** enters an area defined by a geofence set by the customer. In this manner, the customer may be alerted when refuse vehicle **10** is within a certain proximity of a location set by the customer (e.g., the customer's location or a location of the customer's refuse can(s)). Accordingly, the customer may place the refuse can to be retrieved and/or emptied by refuse truck **10** in an appropriate position once the customer receives the alert.

[0049] System **300** is shown to include a network **302**. Network **302** may be any type of network (e.g., a VPN, WAN, LAN, etc.) that allows the components of system **300** to communicate remotely. In communication with network **302** is a server **304**, a user device **306**, and refuse vehicle **10**. Each of server **304**, user device **306**, and refuse vehicle **10** may include a wired or wireless network interface (e.g., an antenna, a transmitter, a transceiver, etc.) for conducting data communications with network **302**. In some embodiments, the network interfaces of each of user device **306** and/or refuse vehicle **10** may include a cellular device configured to provide Internet access by connecting to a cellular tower via a 2G network, a 3G network, an LTE network, etc. In some embodiments, network interfaces may include other types of wireless interfaces such as Bluetooth, WiFi, Zigbee, etc. As an example, server **304** may include a wired network interface to communicate with network **302** and user device **306** may include a cellular and/or WiFi network interface. It will be appreciated that each of server **304**, user device **306**, and refuse vehicle **10** may include a different type of network interface.

[0050] Server **304** may be any remote computing system (i.e., a computer, a cloud server, etc.)

having at least a processor **308** and a memory **310**. Processor **308** may be coupled to memory **310**. Processor **308** may be a general purpose or specific purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a group of processing components, or other suitable processing components. Processor **308** is configured to execute computer code or instructions stored in memory **310** or received from other computer readable media (e.g., CDRom, network storage, a remote server, etc.).

[0051] Memory **310** may include one or more devices (e.g., memory units, memory devices, storage devices, etc.) for storing data and/or computer code for completing and/or facilitating the various processes described in the present disclosure. Memory **310** may include random access memory (RAM), read-only memory (ROM), hard drive storage, temporary storage, non-volatile memory, flash memory, optical memory, or any other suitable memory for storing software objects and/or computer instructions. Memory **310** may include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present disclosure. Memory **310** may be communicably connected to processor **308** and may include computer code for executing (e.g., by processor **308**) one or more of the processes described herein.

[0052] In some embodiments, server **304** may include (i.e., host) one or more application programming interfaces (API) for processing geofence data inputted by a user, tracking refuse vehicle **10**, and/or transmitting alerts to user device **306**. For example, server **304** may host at least a geofencing API and an API configured to generate and transmit alerts to user device **306**.

[0053] User device **306** may be any electronic device that allows a user to transmit and/or receive information or other data via network **302**. Examples of user devices include, but are not limited to, mobile phones, electronic tablets, laptops, desktop computers, workstations, and other types of electronic devices. Generally, user device **306** may include at least a display for presenting information to a user and a user input device for receiving user inputs. The user input components of user device **306** may include, for example, a keyboard, buttons, a touchscreen, etc. In one example, user device **306** is a smart phone having a touchscreen display configured to present an application or other user interface for establishing a geofence.

[0054] In some embodiments, a user of user device **306** (e.g., a customer of a refuse collection company having a refuse can) may input one or more parameters to define a geofence around a particular location. A geofence is a virtual boundary that defines a perimeter around a physical (i.e., geographical) location. In other words, the geofence data inputted by the user defines a virtual boundary around an area or location specified by the user. For example, the user may input a perimeter around the user's home address to define the geofence. The user may input geofence data (i.e., geofence parameters) via a user interface of user device **306**, for example. In one example, the user may establish a geofence around a location where a refuse can is stored (e.g., the home address of the user). In some embodiments, the user may input a geofence and/or geofence data via an application on a computer or smart phone, via a website, or by any other appropriate means.

[0055] In some embodiments, the user of user device **306** may be presented with a map of an area around a particular location, and the user may draw or otherwise indicate a perimeter (i.e., boundary) of a geofence. In other embodiments, the user may enter a distance (e.g., time, miles, number of stops, etc.) from the particular location. In yet other embodiments, any other known or appropriate means for establishing a geofence may be used. The geofence data may be transmitted from user device **306** to server **304**. Subsequently, server **304** may store the geofence data in memory **310** and/or process the geofence data via processor **308**. Processing the geofence data may include generating a geofence from received geofence data (i.e., parameters) and/or storing a generated geofence or geofence data in memory **310**.

[0056] While in operation, the location of refuse vehicle **10** may be tracked by server **304**. Generally, the location of refuse vehicle **10** may be tracked by server **304** by any suitable or known method. As an example, a GPS transceiver and/or controller of refuse vehicle **10** may determine the

location of refuse vehicle **10**, and the location may be transmitted (e.g., via a cellular network) from refuse truck **10** to server **304**. Based on the location of refuse vehicle **10**, server **304** may determine whether refuse vehicle **10** is within the geofence (e.g., has crossed a boundary of the geofence) established by the user.

[0057] In the event that server **304** determines that refuse vehicle **10** is within the geofence, server **304** may generate and transmit a notification (i.e., an alert) to user device **306**. In this regard, the notification may indicate to the user that a refuse collection vehicle is within a specified proximity of the user's location (e.g., within a given distance of the user's refuse container). In one example, the user may receive (e.g., via user device **306**) a push notification or a text message that notifies the user that the refuse vehicle is in their area. In another example, the notification may indicate how close the refuse vehicle is to the user (e.g., in miles, in number of stops, etc.).

[0058] In some embodiments, when refuse vehicle **10** leaves the geofenced area (e.g., when refuse vehicle **10** crosses a boundary of the geofence a second time), server **304** may generate and transmit a second notification to user device **306**. The second notification may indicate to the user that refuse truck **10** has left the geofence area, thereby notifying the user that they may retrieve their refuse can from a curb, a street side, or other location where the refuse can is placed for pickup.

[0059] In some embodiments, server **304** can also communicate with remote systems **312**, which may include any system or device related to the tracking of refuse collections vehicles, as described herein. For example, remote systems **312** may include computing devices such as laptop or desktop computers, mobile phones, additional servers, etc. In some embodiments, remote systems **312** can include an access control system configured to control access to a location, such as a building, a parking lot, a storage area, etc. In some such embodiments, the access control system may be configured to control a gate, door, etc., that secures a refuse can containment area. A refuse can containment area may be a secure area for containing (i.e., housing) one or more refuse cans. For example, the refuse can containment area may be a garage or an open lot containing one or more refuse cans.

[0060] In some embodiments, server **304** may transmit commands to the access control system to cause an access control device (e.g., an electronic lock, a motor, an actuator, etc.) to actuate, thereby allowing access to the refuse can containment area. For example, the command may cause access control system to actuate an electronic lock to allow access to the refuse can containment area. In another example, the command may cause access control system to actuate a motor to open a gate, thereby allowing access to the refuse can containment area. In some embodiments, a user (e.g., of user device **306**) can define a distance from a particular location (e.g., a location of the refuse can containment area) at which the server **304** transmits commands to the access control system. Thus, in some such embodiments, the user may establish a second geofence for allowing access to the refuse can containment, which may be similar in area to a first geofence for notifying the user that a refuse collection vehicle (e.g., refuse vehicle **10**) is nearby. In other such embodiments, the second geofence may be smaller and/or may be contained within the first geofence. For example, the user may be notified when refuse vehicle **10** crosses a boundary of the first geofence (e.g., a few miles from a target location), and an operator of refuse vehicle **10** may be granted access to the refuse can containment area when crossing a boundary of the second geofence (e.g., a few hundred from a target location). In this manner, the refuse can containment area may remain secured until refuse vehicle **10** is nearby.

[0061] Referring now to FIG. **4**, an example of a geofence **400** is shown, according to some embodiments. Geofence **400** is shown as a substantially circular geofence that surrounds a location **402** set by a user (e.g., a user's home address), shown on a map of an area around location **402**. In this example interface, geofence **400** may have been generated based on geofence data input by the user by specifying a distance from location **402** (e.g., 2-miles), where the boundary of geofence **400** is a radius from location **402**. As shown in FIG. **4**, refuse truck **10** may be tracked as it travels

along a roadway or other path. When refuse truck **10** crosses the boundary of geofence **400** (e.g., enters the geofenced area), a notification may be sent to a device of the user (e.g., by server **304**). Similarly, a notification may be sent to a device of the user when refuse truck **10** leaves the geofenced area or crosses the boarder of geofence **400** a second time.

[0062] While a circular geofence defining a radius of a particular distance from location **402** is shown in FIG. **4**, it will be appreciated that the geofence may be defined by any number of parameters. For example, a user may specify a distance from a location based on typical driving times or distances via known roadways (e.g., rather than a straight-line distance). Accordingly, the geofence may not necessarily be substantially circular, as shown in FIG. **4**, but may take any shape (e.g., any polygonal shape). For example, the geofence may be defined by one or more straight lines such as roadways or other boundaries. In another example, a user may establish a geofence based on a number of stops refuse vehicle **10** is from the user's location. In such embodiments, the geofence may not necessarily be presented as an overlay to a map.

[0063] Referring now to FIG. **5**, a process **500** for tracking a refuse vehicle and alerting a user for residential refuse can collection is shown, according to some embodiments. Process **500** may be implemented by system **300**, for example. Process **500** may alert a user when a tracked refuse vehicle (e.g., refuse vehicle **10**) is within a particular distance or proximity of a location specified by the user to facilitate the placement and/or retrieval of a refuse can by the user. It will be appreciated that the steps of process **500** are not intended to be limiting, such that process **500** may include more or few steps than those shown and that the steps of process **500** may be completed in any order.

[0064] At step **502**, geofence data is received from a user device. As described above with respect to FIG. **3**, for example, the geofence data may be received by server **304** or another computer system from user device **306** (e.g., via network **302**). In some embodiments, the user may input geofence data via an application on a computer or smart phone, via a website, etc. As described above, for example, the user may be presented with a map of an area around a particular location or a central point, and the user may draw or otherwise indicate a boundary that defines a geofence. To continue this example, the user may enter an address (e.g., a home address) and a user interface may be presented with a map of the area around the address. The user may then enter a distance (e.g., miles, time, etc.) such as by entering a number, moving a slide or other graphical element, drawing a boundary, or by any other appropriate means.

[0065] In some embodiments, the user may not be presented with a map of the area but may be able to enter a distance or other data that defines a distance or proximity from the particular location. For example, the user may selectively turn on a setting of an application that alerts the user when a refuse vehicle is within a predefined distance of the user's location. Subsequent to receiving the geofence data, the geofence data may be processed by the server or computer system (e.g., server **304** of system **300**). Processing the geofence data may include generating a geofence from parameters received from the user device, for example. The geofence may then be stored by the server. In some embodiments, a user may define multiple geofences or may access a previously stored or entered geofence to modify parameters of the geofence. For example, the user may change a distance (e.g., a radius) of the geofence or may change a location (e.g., an address) that the geofence is centered on.

[0066] At step **504**, a location of a refuse vehicle (e.g., refuse vehicle **10**) is determined. In some embodiments, the location of the refuse vehicle is tracked by a server (e.g., server **304**) or computer system of a tracking and alert system, such as system **300**. It will be appreciated that any number of known method may be used to determine the location of the refuse vehicle. In some embodiments, the location of the refuse vehicle may be determined based on GPS data received from the refuse vehicle by the tracking and alert system. In this regard, a GPS transceiver of the refuse vehicle may determine a location of the refuse vehicle and transmit the location to the tracking and alert system via a network connection (e.g., a cellular connection). In some embodiments, GPS data may be

used in combination with other data (e.g., inertial data indicating movement of the refuse vehicle) to determine a location and/or trajectory of the refuse vehicle.

[0067] At step **506**, the determined location of the refuse vehicle may be compared with the geofence stored by the tracking and alert system and/or received from the user device to determine whether the refuse vehicle is within the geofenced area (e.g., whether the refuse vehicle has crossed a boundary of the geofence or the perimeter established by the geofence). In the event that the refuse vehicle has not crossed the geofence boundary or entered the geofenced area, the location of the refuse vehicle may continue to be tracked. Once the refuse vehicle crosses the geofence boundary or enters the area defined by the geofence, process **500** may continue to step **508**.

[0068] At step **508**, based on a determination that the refuse vehicle is within the geofenced area, a first alert (i.e., a notification) is transmitted to the user device. As described above, the first alert may be transmitted to user device **306** from server **304**, in some embodiments. The first alert may inform the user that the refuse vehicle is within the geofenced area and/or indicate that the refuse vehicle is within a user-specified distance of a particular location set by the user (e.g., the user's home address). In one example, the first alert may simply indicate that the refuse vehicle is nearby. Accordingly, the user may place the refuse can in a pickup location (e.g., at a curb, at a side of a roadway, etc.) in response to receiving the first alert. In another example, the first alert may indicate the distance that the refuse truck is from the user's location, such as in miles, time (e.g., minutes), number of stops, etc. In various embodiments, the first alert may be sent as a text message, an email, a push notification, an automated voice call, or by any other suitable method.

[0069] In some embodiments, at step **508**, a command may also be transmitted to an access control system for a refuse can containment area. The command may cause an actuator (e.g., a door actuator, a gate actuator, a motor, an electronic lock, etc.) to facilitate access to a refuse can containment area. For example, the command may cause an electronic lock to be disengaged, allowing access to the refuse can containment area to retrieve a refuse can. As another example, the command may cause a motor coupled to a gate to be activate, opening the gate and allowing access to the refuse can containment area to retrieve the refuse can.

[0070] At step **510**, a location of a refuse vehicle (e.g., refuse vehicle **10**) is once again determined, as described above with respect to step **504**. At step **512**, the newly determined location of the refuse vehicle may be compared with the geofence stored by the tracking and alert system and/or received from the user device to determine whether the refuse vehicle has left the geofenced area. For example, after determining that the refuse vehicle entered the geofence at step **506**, subsequently determined locations of the refuse vehicle may be compared to the geofence to determine whether the refuse vehicle has crossed a boundary of the geofence or the perimeter established by the geofence a second time. In the event that the refuse vehicle has not left the geofenced area, the location of the refuse vehicle may continue to be tracked. Once the refuse vehicle crosses the geofence boundary and/or leaves the area defined by the geofence, process **500** may continue to step **514**.

[0071] At step **514**, responsive to a determination that the refuse vehicle has left the geofenced area, a second alert (i.e., a notification) is transmitted to the user device. The second alert may inform the user that the refuse vehicle has left the geofenced area, thereby indicating to the user that the user may retrieve a refuse can from a pickup location (e.g., a curb, a sidewalk, etc.) In one example, the second alert may indicate that the refuse vehicle has left the geofenced area and/or that the user's refuse can has been emptied. The second alert may be transmitted in a similar manner to the first alert and may be sent as a text message, an email, a push notification, an automated voice call, or by any other suitable method.

Concrete Mixer Vehicle Modes

[0072] Referring to the FIGS. **6-15**, a system and a controller for a concrete mixer truck or a concrete placement vehicle are shown, according to an exemplary embodiment. The system and/or the controller facilitate selection and transition between various predefined modes of operation of

one or more controllable elements. In some embodiments, the various predefined modes of operation include an add water mode, a spreader mode, an admixture mode, a smooth mode, a wet load mode, and an aggressive mode. The various modes may be for different concrete placement and concrete transit environments setup to minimize operator interaction while enhancing the experience for a specific instant, according to some embodiments. Based on load, location, environment, job, etc., operators of concrete mixing trucks need to hold various skill sets to manually control the concrete mixer truck to accomplish various functions in different situations, according to some embodiments. The system and the controller facilitate simple transitioning of the concrete mixer truck between various predefined modes of operation to automate many of the operations which the operator may have to do manually in other systems, according to some embodiments. The predefined modes of operation and the automated operations therein increase repeatability, and help remove human errors which may occur due to distractions at a plant, while in transit and on the jobsite.

[0073] According to the exemplary embodiment shown in FIGS. **6-10**, a vehicle, shown as concrete mixer truck **600**, includes a drum assembly, shown as drum assembly **700**, and a control system, shown as drum control system **750**. According to an exemplary embodiment, the concrete mixer truck **600** is configured as a rear-discharge concrete mixer truck. In other embodiments, the concrete mixer truck **600** is configured as a front-discharge concrete mixer truck. As shown in FIG. **6**, the concrete mixer truck **600** includes a chassis, shown as frame **612**, and a cab, shown as cab **614**, coupled to the frame **612** (e.g., at a front end thereof, etc.). The drum assembly **700** is coupled to the frame **612** and disposed behind the cab **614** (e.g., at a rear end thereof, etc.), according to the exemplary embodiment shown in FIG. **6**. In other embodiments, at least a portion of the drum assembly **700** extends in front of the cab **614**. The cab **614** may include various components to facilitate operation of the concrete mixer truck **600** by an operator (e.g., a seat, a steering wheel, hydraulic controls, a user interface, switches, buttons, dials, etc.).

[0074] As shown in FIGS. **6, 8, and 9**, the concrete mixer truck **600** includes a prime mover, shown as engine **616**. As shown in FIG. **6**, the engine **616** is coupled to the frame **612** at a position beneath the cab **614**. The engine **616** may be configured to utilize one or more of a variety of fuels (e.g., gasoline, diesel, bio-diesel, ethanol, natural gas, etc.), according to various exemplary embodiments. According to an alternative embodiment, as shown in FIG. **10** and described in more detail herein, the prime mover additionally or alternatively includes one or more electric motors and/or generators, which may be coupled to the frame **612** (e.g., a hybrid vehicle, an electric vehicle, etc.). The electric motors may consume electrical power from an on-board storage device (e.g., batteries, ultra-capacitors, etc.), from an on-board generator (e.g., an internal combustion engine, a genset, etc.), and/or from an external power source (e.g., overhead power lines, etc.) and provide power to systems of the concrete mixer truck **600**.

[0075] As shown in FIGS. **6 and 9**, the concrete mixer truck **600** includes a power transfer device, shown as transmission **618**. In one embodiment, the engine **616** produces mechanical power (e.g., due to a combustion reaction, etc.) that flows into the transmission **618**. As shown in FIGS. **6 and 9**, the concrete mixer truck **600** includes a first drive system, shown as vehicle drive system **620**, that is coupled to the transmission **618**. The vehicle drive system **620** may include drive shafts, differentials, and other components coupling the transmission **618** with a ground surface to move the concrete mixer truck **600**. As shown in FIG. **6**, the concrete mixer truck **600** includes a plurality of tractive elements, shown as wheels **622**, that engage a ground surface to move the concrete mixer truck **600**. In one embodiment, at least a portion of the mechanical power produced by the engine **616** flows through the transmission **618** and into the vehicle drive system **620** to power at least a portion of the wheels **622** (e.g., front wheels, rear wheels, etc.). In one embodiment, energy (e.g., mechanical energy, etc.) flows along a first power path defined from the engine **616**, through the transmission **618**, and to the vehicle drive system **620**.

[0076] As shown in FIGS. **6-8 and 10**, the drum assembly **700** of the concrete mixer truck **600**

includes a drum, shown as mixer drum **702**. The mixer drum **702** is coupled to the frame **612** and disposed behind the cab **614** (e.g., at a rear and/or middle of the frame **612**, etc.). As shown in FIGS. **6-10**, the drum assembly **700** includes a second drive system, shown as drum drive system **720**, that is coupled to the frame **612**. As shown in FIGS. **6** and **7**, the concrete mixer truck **600** includes a first support, shown as front pedestal **706**, and a second support, shown as rear pedestal **708**. According to an exemplary embodiment, the front pedestal **706** and the rear pedestal **708** cooperatively couple (e.g., attach, secure, etc.) the mixer drum **702** to the frame **612** and facilitate rotation of the mixer drum **702** relative to the frame **612**. In an alternative embodiment, the drum assembly **700** is configured as a stand-alone mixer drum that is not coupled (e.g., fixed, attached, etc.) to a vehicle. In such an embodiment, the drum assembly **700** may be mounted to a stand-alone frame. The stand-alone frame may be a chassis including wheels that assist with the positioning of the stand-alone mixer drum on a worksite. Such a stand-alone mixer drum may also be detachably coupled to and/or capable of being loaded onto a vehicle such that the stand-alone mixer drum may be transported by the vehicle.

[0077] As shown in FIGS. **6** and **7**, the mixer drum **702** defines a central, longitudinal axis, shown as axis **704**. According to an exemplary embodiment, the drum drive system **720** is configured to selectively rotate the mixer drum **702** about the axis **704**. As shown in FIGS. **6** and **7**, the axis **704** is angled relative to the frame **612** such that the axis **704** intersects with the frame **612**. According to an exemplary embodiment, the axis **704** is elevated from the frame **612** at an angle in the range of five degrees to twenty degrees. In other embodiments, the axis **704** is elevated by less than five degrees (e.g., four degrees, three degrees, etc.) or greater than twenty degrees (e.g., twenty-five degrees, thirty degrees, etc.). In an alternative embodiment, the concrete mixer truck **600** includes an actuator positioned to facilitate selectively adjusting the axis **704** to a desired or target angle (e.g., manually in response to an operator input/command, automatically according to a control scheme, etc.).

[0078] As shown in FIGS. **6** and **7**, the mixer drum **702** of the drum assembly **700** includes an inlet, shown as hopper **710**, and an outlet, shown as chute **712**. According to an exemplary embodiment, the mixer drum **702** is configured to receive a mixture, such as a concrete mixture (e.g., cementitious material, aggregate, sand, etc.), with the hopper **710**. The mixer drum **702** may include a mixing element (e.g., fins, etc.) positioned within the interior thereof. The mixing element may be configured to (i) agitate the contents of mixture within the mixer drum **702** when the mixer drum **702** is rotated by the drum drive system **720** in a first direction (e.g., counterclockwise, clockwise, etc.) and (ii) drive the mixture within the mixer drum **702** out through the chute **712** when the mixer drum **702** is rotated by the drum drive system **720** in an opposing second direction (e.g., clockwise, counterclockwise, etc.).

[0079] According to the exemplary embodiment shown in FIGS. **7-9**, the drum drive system is a hydraulic drum drive system. As shown in FIGS. **7-9**, the drum drive system **720** includes a pump, shown as pump **722**; a reservoir, shown as fluid reservoir **724**, fluidly coupled to the pump **722**; and an actuator, shown as drum motor **726**. As shown in FIGS. **8** and **9**, the pump **722** and the drum motor **726** are fluidly coupled. According to an exemplary embodiment, the drum motor **726** is a hydraulic motor, the fluid reservoir **724** is a hydraulic fluid reservoir, and the pump **722** is a hydraulic pump. The pump **722** may be configured to pump fluid (e.g., hydraulic fluid, etc.) stored within the fluid reservoir **724** to drive the drum motor **726**.

[0080] According to an exemplary embodiment, the pump **722** is a variable displacement hydraulic pump (e.g., an axial piston pump, etc.) and has a pump stroke that is variable. The pump **722** may be configured to provide hydraulic fluid at a flow rate that varies based on the pump stroke (e.g., the greater the pump stroke, the greater the flow rate provided to the drum motor **726**, etc.). The pressure of the hydraulic fluid provided by the pump **722** may also increase in response to an increase in pump stroke (e.g., where pressure may be directly related to work load, higher flow may result in higher pressure, etc.). The pressure of the hydraulic fluid provided by the pump **722** may

alternatively not increase in response to an increase in pump stroke (e.g., in instances where there is little or no work load, etc.). The pump 722 may include a throttling element (e.g., a swash plate, etc.). The pump stroke of the pump 722 may vary based on the orientation of the throttling element. In one embodiment, the pump stroke of the pump 722 varies based on an angle of the throttling element (e.g., relative to an axis along which the pistons move within the axial piston pump, etc.). By way of example, the pump stroke may be zero where the angle of the throttling element is equal to zero. The pump stroke may increase as the angle of the throttling element increases. According to an exemplary embodiment, the variable pump stroke of the pump 722 provides a variable speed range of up to about 10:1. In other embodiments, the pump 722 is configured to provide a different speed range (e.g., greater than 10:1, less than 10:1, etc.).

[0081] In one embodiment, the throttling element of the pump 722 is movable between a stroked position (e.g., a maximum stroke position, a partially stroked position, etc.) and a destroked position (e.g., a minimum stroke position, a partially destroked position, etc.). According to an exemplary embodiment, an actuator is coupled to the throttling element of the pump 722. The actuator may be positioned to move the throttling element between the stroked position and the destroked position. In some embodiments, the pump 722 is configured to provide no flow, with the throttling element in a non-stroked position, in a default condition (e.g., in response to not receiving a stroke command, etc.). The throttling element may be biased into the non-stroked position. In some embodiments, the drum control system 750 is configured to provide a first command signal. In response to receiving the first command signal, the pump 722 (e.g., the throttling element by the actuator thereof, etc.) may be selectively reconfigured into a first stroke position (e.g., stroke in one direction, a destroked position, etc.). In some embodiments, the drum control system 750 is configured to additionally or alternatively provide a second command signal. In response to receiving the second command signal, the pump 722 (e.g., the throttling element by the actuator thereof, etc.) may be selectively reconfigured into a second stroke position (e.g., stroke in an opposing second direction, a stroked position, etc.). The pump stroke may be related to the position of the throttling element and/or the actuator.

[0082] According to another exemplary embodiment, a valve is positioned to facilitate movement of the throttling element between the stroked position and the destroked position. In one embodiment, the valve includes a resilient member (e.g., a spring, etc.) configured to bias the throttling element in the destroked position (e.g., by biasing movable elements of the valve into positions where a hydraulic circuit actuates the throttling element into the destroked positions, etc.). Pressure from fluid flowing through the pump 722 may overcome the resilient member to actuate the throttling element into the stroked position (e.g., by actuating movable elements of the valve into positions where a hydraulic circuit actuates the throttling element into the stroked position, etc.).

[0083] As shown in FIG. 9, the concrete mixer truck 600 includes a power takeoff unit, shown as power takeoff unit 632, that is coupled to the transmission 618. In another embodiment, the power takeoff unit 632 is coupled directly to the engine 616. In one embodiment, the transmission 618 and the power takeoff unit 632 include mating gears that are in meshing engagement. A portion of the energy provided to the transmission 618 flows through the mating gears and into the power takeoff unit 632, according to an exemplary embodiment. In one embodiment, the mating gears have the same effective diameter. In other embodiments, at least one of the mating gears has a larger diameter, thereby providing a gear reduction or a torque multiplication and increasing or decreasing the gear speed.

[0084] As shown in FIG. 9, the power takeoff unit 632 is selectively coupled to the pump 722 with a clutch 634. In other embodiments, the power takeoff unit 632 is directly coupled to the pump 722 (e.g., without clutch 634, etc.). In some embodiments, the concrete mixer truck 600 does not include the clutch 634. By way of example, the power takeoff unit 632 may be directly coupled to the pump 722 (e.g., a direct configuration, a non-clutched configuration, etc.). According to an

alternative embodiment, the power takeoff unit **632** includes the clutch **634** (e.g., a hot shift PTO, etc.). In one embodiment, the clutch **634** includes a plurality of clutch discs. When the clutch **634** is engaged, an actuator forces the plurality of clutch discs into contact with one another, which couples an output of the transmission **618** with the pump **722**. In one embodiment, the actuator includes a solenoid that is electronically actuated according to a clutch control strategy. When the clutch **634** is disengaged, the pump **722** is not coupled to (i.e., is isolated from) the output of the transmission **618**. Relative movement between the clutch discs or movement between the clutch discs and another component of the power takeoff unit **632** may be used to decouple the pump **722** from the transmission **618**.

[0085] In one embodiment, energy flows along a second power path defined from the engine **616**, through the transmission **618** and the power takeoff unit **632**, and into the pump **722** when the clutch **634** is engaged. When the clutch **634** is disengaged, energy flows from the engine **616**, through the transmission **618**, and into the power takeoff unit **632**. The clutch **634** selectively couples the pump **722** to the engine **616**, according to an exemplary embodiment. In one embodiment, energy along the first flow path is used to drive the wheels **622** of the concrete mixer truck **600**, and energy along the second flow path is used to operate the drum drive system **720** (e.g., power the pump **722**, etc.). By way of example, the clutch **634** may be engaged such that energy flows along the second flow path when the pump **722** is used to provide hydraulic fluid to the drum motor **726**. When the pump **722** is not used to drive the mixer drum **702** (e.g., when the mixer drum **702** is empty, etc.), the clutch **634** may be selectively disengaged, thereby conserving energy. In embodiments without clutch **634**, the mixer drum **702** may continue turning (e.g., at low speed) when empty.

[0086] The drum motor **726** is positioned to drive the rotation of the mixer drum **702**. In some embodiments, the drum motor **726** is a fixed displacement motor. In some embodiments, the drum motor **726** is a variable displacement motor. In one embodiment, the drum motor **726** operates within a variable speed range up to about 3:1 or 4:1. In other embodiments, the drum motor **726** is configured to provide a different speed range (e.g., greater than 4:1, less than 3:1, etc.). According to an exemplary embodiment, the speed range of the drum drive system **720** is the product of the speed range of the pump **722** and the speed range of the drum motor **726**. The drum drive system **720** having a variable pump **722** and a variable drum motor **726** may thereby have a speed range that reaches up to 30:1 or 40:1 (e.g., without having to operate the engine **616** at a high idle condition, etc.). According to an exemplary embodiment, increased speed range of the drum drive system **720** having a variable displacement motor and a variable displacement pump relative to a drum drive system having a fixed displacement motor frees up boundary limits for the engine **616**, the pump **722**, and the drum motor **726**. Advantageously, with the increased capacity of the drum drive system **720**, the engine **616** does not have to run at either high idle or low idle during the various operating modes of the drum assembly **700** (e.g., mixing mode, discharging mode, filling mode, etc.), but rather the engine **616** may be operated at a speed that provides the most fuel efficiency and most stable torque. Also, the pump **722** and the drum motor **726** may not have to be operated at displacement extremes to meet the speed requirements for the mixer drum **702** during various applications, but can rather be modulated to the most efficient working conditions (e.g., by the drum control system **750**, etc.).

[0087] As shown in FIG. 7, the drum drive system **720** includes a drive mechanism, shown as drum drive wheel **728**, coupled to the mixer drum **702**. The drum drive wheel **728** may be welded, bolted, or otherwise secured to the head of the mixer drum **702**. The center of the drum drive wheel **728** may be positioned along the axis **704** such that the drum drive wheel **728** rotates about the axis **704**. According to an exemplary embodiment, the drum motor **726** is coupled to the drum drive wheel **728** (e.g., with a belt, a chain, a gearing arrangement, etc.) to facilitate driving the drum drive wheel **728** and thereby rotate the mixer drum **702**. The drum drive wheel **728** may be or include a sprocket, a cogged wheel, a grooved wheel, a smooth-sided wheel, a sheave, a pulley, or

still another member. In other embodiments, the drum drive system **720** does not include the drum drive wheel **728**. By way of example, the drum drive system **720** may include a gearbox that couples the drum motor **726** to the mixer drum **702**. By way of another example, the drum motor **726** (e.g., an output thereof, etc.) may be directly coupled to the mixer drum **702** (e.g., along the axis **704**, etc.) to rotate the mixer drum **702**.

[0088] According to the exemplary embodiment shown in FIG. **10**, the drum drive system **720** of the drum assembly **700** is configured to be an electric drum drive system. As shown in FIG. **10**, the drum drive system **720** includes the drum motor **726**, which is electrically powered to drive the mixer drum **702**. By way of example, in an embodiment where the concrete mixer truck **600** has a hybrid powertrain, the engine **616** may drive a generator (e.g., with the power takeoff unit **632**, etc.), shown as generator **730**, to generate electrical power that is (i) stored for future use by the drum motor **726** in storage (e.g., battery cells, etc.), shown as energy storage source **732**, and/or (ii) provided directly to drum motor **726** to drive the mixer drum **702**. The energy storage source **732** may additionally be chargeable using a mains power connection (e.g., through a charging station, etc.). By way of another example, in an embodiment where the concrete mixer truck **600** has an electric powertrain, the engine **616** may be replaced with a main motor, shown as primary motor **626**, that drives the wheels **622**. The primary motor **626** and the drum motor **726** may be powered by the energy storage source **732** and/or the generator **730** (e.g., a regenerative braking system, etc.).

[0089] According to the exemplary embodiments shown in FIGS. **8** and **10**, the drum control system **750** for the drum assembly **700** of the concrete mixer truck **600** includes a controller, shown as drum assembly controller **752**. In one embodiment, the drum assembly controller **752** is configured to selectively engage, selectively disengage, control, and/or otherwise communicate with components of the drum assembly **700** and/or the concrete mixer truck **600** (e.g., actively control the components thereof, etc.). As shown in FIGS. **8** and **10**, the drum assembly controller **752** is coupled to the engine **616**, the primary motor **626**, the pump **722**, the drum motor **726**, the generator **730**, the energy storage source **732**, a pressure sensor **754**, a temperature sensor **756**, a speed sensor **758**, a motor sensor **760**, an input/output (“I/O”) device **770**, and/or a remote server **780**. In other embodiments, the drum assembly controller **752** is coupled to more or fewer components. By way of example, the drum assembly controller **752** may send and/or receive signals with the engine **616**, the primary motor **626**, the pump **722**, the drum motor **726**, the generator **730**, the energy storage source **732**, the pressure sensor **754**, the temperature sensor **756**, the speed sensor **758**, the motor sensor **760**, the I/O device **770**, and/or the remote server **780**.

[0090] The drum assembly controller **752** may be implemented as hydraulic controls, a general-purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a digital-signal-processor (DSP), circuits containing one or more processing components, circuitry for supporting a microprocessor, a group of processing components, or other suitable electronic processing components. According to an exemplary embodiment, the drum assembly controller **752** includes a processing circuit having a processor and a memory. The processing circuit may include an ASIC, one or more FPGAs, a DSP, circuits containing one or more processing components, circuitry for supporting a microprocessor, a group of processing components, or other suitable electronic processing components. In some embodiments, the processor is configured to execute computer code stored in the memory to facilitate the activities described herein. The memory may be any volatile or non-volatile computer-readable storage medium capable of storing data or computer code relating to the activities described herein. According to an exemplary embodiment, the memory includes computer code modules (e.g., executable code, object code, source code, script code, machine code, etc.) configured for execution by the processor.

[0091] According to an exemplary embodiment, the drum assembly controller **752** is configured to facilitate detecting the buildup of concrete within the mixer drum **702**. By way of example, over

time after various concrete discharge cycles, concrete may begin to build up and harden within the mixer drum **702**. Such buildup is disadvantageous because of the increased weight of the concrete mixer truck **600** and decreased charge capacity of the mixer drum **702**. Such factors may reduce the efficiency of concrete delivery. Therefore, the concrete that has built up must be cleaned from the interior of the mixer drum **702** (i.e., using a chipping process). Typically, the buildup is monitored either (i) manually by the operator of the concrete mixer truck **600** (e.g., by inspecting the interior of the mixer drum **702**, etc.) or (ii) using expensive load cells to detect a change in mass of the mixer drum **702** when empty. According to an exemplary embodiment, the drum assembly controller **752** is configured to automatically detect concrete buildup within the mixer drum **702** using sensor measurements from more cost effective sensors and processes.

[0092] FIG. **11** shows a graphical user interface (GUI) **1100** which may be displayed to a vehicle operator (e.g., via user interface device **1202** as shown in FIG. **12**), according to an exemplary embodiment. GUI **1100** is shown to include graphical displays indicating a drum speed **1102**, a slump **1104** of mixture, a pressure **1118**, etc. GUI **1100** is configured to display various operational properties of mixer drum **702**, concrete mixer truck **600**, and the mixture (e.g., concrete) within mixer drum **702**, according to some embodiments. GUI **1100** is configured to receive various user inputs to selectably transition mixer drum **702** and/or concrete mixer truck **600** between various predetermined drum modes **1101**, according to some embodiments. According to some embodiments, GUI **1100** includes a smooth drum mode **1106**, a spreader drum mode **1108**, a wet load drum mode **1110**, an admixture drum mode **1112**, an add water drum mode **1114**, and an aggressive drum mode **1116**. GUI **1100** is configured to receive user inputs (e.g., through a touchscreen, buttons, levers, selecting devices, etc.) to select any of smooth drum mode **1106**, spreader drum mode **1108**, wet load drum mode **1110**, admixture drum mode **1112**, add water drum mode **1114**, and aggressive drum mode **1116**, according to some embodiments. In some embodiments, GUI **1100** is configured to receive one or more input parameters for the selected mode in addition to the selected mode. In some embodiments, GUI **1100** prompts an operator to input one or more input parameters in response to a selection of one of drum modes **1101**.

[0093] GUI **1100** may be implemented in a display device (e.g., a user interface, a human machine interface, user interface device **1202**, etc.) positioned within cab **614**, according to an exemplary embodiment. Drum modes **1101** cause mixer drum **702** and/or chute **712** to operate according to various predefined modes for different concrete placement and concrete transit environments or to achieve desired characteristics of concrete or mixture within mixer drum **702**. Advantageously, drum modes **1101** may remove the need for an operator to manually adjust operations of mixer drum **702** and facilitates automated operation of the concrete mixer truck **600**. Drum modes **1101** facilitate a simpler operation of mixer drum **702**, and facilitate a more repeatable operation of mixer drum **702**, according to some embodiments.

[0094] As disclosed above, each of drum modes **1101** cause mixer drum **702** and/or concrete mixer truck **600** to operate according to a predefined mode. Smooth drum mode **1106** causes mixer drum **702** to operate according to a standard drum mode, according to an exemplary embodiment. In an exemplary embodiment, smooth drum mode **1106** is a default operating mode of mixer drum **702**. For example, mixer drum **702** may automatically transition or be transitioned into smooth drum mode **1106** in response to a key cycle (e.g., an ignition of engine **616**). In some embodiments, smooth drum mode **1106** includes ramps and smoothing features to smoothly reduce drum momentum when a drum stop is engaged or when switching between charge and discharge.

[0095] Spreader drum mode **1108** causes mixer drum **702** to operate for the purposes of spreading a cement slurry or the mixture contained in mixer drum **702**, according to an exemplary embodiment. When spreader drum mode **1108** is selected, mixer drum **702** and chute **712** are operated for the purpose of spreading the cement slurry, according to some embodiments. When in spreader drum mode **1108**, mixer drum **702** and chute **712** are operated based on speed of concrete mixer truck **600**, and an angle of concrete mixer truck **600**, according to some embodiments.

[0096] Wet load drum mode **1110** keeps mixer drum **702** spinning faster when concrete mixer truck **600** is moving at a slower speed, according to an exemplary embodiment. This facilitates keeping mixture or concrete in mixer drum **702** farther forwards in mixer drum **702**. Wet load drum mode **1110** may be activated when concrete mixer truck **600** has a full load with a high slump (e.g., immediately after loading at a plant). Wet load drum mode **1110** may use information such as the speed of concrete mixer truck **600** and current mixer drum speed to control speed of mixer drum **702**. In some embodiments, wet load drum mode **1110** uses an acceleration, pitch, roll, etc., of concrete mixer truck **600** to control speed of mixer drum **702** to prevent concrete/mixture spillage. In some systems, the operator must manually adjust speed of mixer drum **702** based on vehicle speed, acceleration, fullness, and road grade while driving concrete mixer truck **600**. If the operator does not manually adjust speed of mixer drum **702** while driving concrete mixer truck **600**, spillage of concrete contained within mixer drum **702** may occur. Advantageously, wet load drum mode **1110** removes the need for the operator to manually adjust the mixer drum speed while driving and reduces the skillset needed to operate concrete mixer truck **600**.

[0097] Admixture drum mode **1112** causes mixer drum **702** to operate such that a mixture is properly mixed after it is added to mixer drum **702**, according to an exemplary embodiment. Admixture drum mode **1112** may cause mixer drum **702** to spin at a mixing drum speed for a settable or predetermined number of revolutions. In response to completing the selected or predetermined number of revolutions, mixer drum **702** may be transitioned into a constant speed mode (where mixer drum **702** rotates at a constant speed) or into smooth drum mode **1106**. Advantageously, admixture drum mode **1112** reduces fuel usage by preventing mixer drum **702** from excessive/unneeded revolutions, increases drum life, and reduces the likelihood of over/under mixing the concrete in mixer drum **702**. Additionally, admixture drum mode **1112** advantageously removes the need for the operator to manually monitor the number of revolutions of mixer drum **702**.

[0098] Aggressive drum mode **1116** causes mixer drum **702** to operate without any ramping or smoothing features to smoothly reduce mixer drum momentum when a drum stop is engaged or when switching between charge and discharge, according to an exemplary embodiment. Aggressive drum mode **1116** can be used to rock mixer drum **702** in the case of materials/concrete mixture stuck within mixer drum **702**. Advantageously, this can be used to clear clogs, clumps, etc., to clear mixer drum **702**. For example, when in aggressive drum mode **1116**, mixer drum **702** may be driven to rotate in a first direction for a predetermined amount of time or a predetermined angular distance, then suddenly stopped, then driven to rotate in an opposite direction.

[0099] In some embodiments, drum modes **1101** includes an empty load drum mode and a dry load drum mode. In some embodiments, both empty load drum mode and dry load drum mode cause mixer drum **702** to spin at a low speed (e.g., less than 2 rpm). In some embodiments, empty load drum mode keeps mixer drum **702** spinning at a low speed to keep rollers of mixer drum **702** from flat spotting. In some embodiments, empty load drum mode causes mixer drum **702** to spin at an angular speed of less than 1 rpm. In some embodiments, empty load drum mode can be transitioned into after mixture has exited mixer drum **702** and mixer drum **702** is completely empty or nearly empty. In some embodiments, dry load drum mode causes mixer drum **702** to rotate at angular speed less than wet load drum mode **1110**. In some embodiments, dry load drum mode causes mixer drum **702** to rotate at an angular speed of approximately 1-1.5 rpm. In some embodiments, dry load drum mode causes mixer drum **702** to rotate just fast enough to keep material in mixer drum **702** and keep rollers of mixer drum **702** from flat spotting. In some embodiments, dry load drum mode can be transitioned into before water has been added to the mixture or if the mixture of mixer drum **702** is relatively dry.

[0100] As shown in FIG. **12**, a mode controller **1204** of a system **1200** for the mixer truck **600** is configured to perform switching between various predetermined modes of operation, according to an exemplary embodiment. System **1200** illustrates the information which mode controller **1204**

may receive and output to mixer drum **702** and chute **712** of concrete mixer truck **600** or to generate control signals (e.g., direction and/or speed) for mixer drum **702** and/or chute **712** of concrete mixer truck **600** to operate mixer truck **600** and/or chute **712** according to a selected mode. Mode controller **1204** can receive mode selection commands from user interface device **1202**. User interface device **1202** may include one or more display devices, buttons, switches, touchscreens, etc., configured to display a currently selected mode and configured to receive a user input to cause mixer drum **702** and/or chute **712** to operate according to one of drum modes **1101** or to transition concrete mixer truck **600** between the various drum modes **1101**. In some embodiments, user interface device **1202** includes (e.g., displays) GUI **1100**, facilitating selection of drum modes **1101** and displaying various information (e.g., slump **1104**, pressure **1118**, drum speed **1102**, a currently selected drum mode, etc.). Mode controller **1204** can be positioned locally on the mixer truck **600**.

[0101] Mode controller **1204** may adjust an operation of mixer drum **702** and/or chute **712** to operate according to the selected drum mode, or may cause drum assembly controller **752** to operate according to the selected drum mode. In some embodiments, mode controller **1204** is drum assembly controller **752** and/or incorporates some or all of the functionality of drum assembly controller **752** to adjust an operation of mixer drum **702** and/or chute **712**. For example mode controller **1204** may provide drum assembly controller **752** with setpoints (e.g., a drum speed setpoint), control signals, etc., and drum assembly controller **752** may use these setpoints and/or control signals to cause mixer drum **702** and/or chute **712** to operate according to the selected predefined mode of operation.

[0102] Mode controller **1204** is shown receiving vehicle speed **708** (v), mixer drum speed **1210** (ω), mixer drum revolutions **1212** (#rev), vehicle angle **1214** (θ), and mode selection. Mode controller **1204** may receive any of this information from one or more sensors, systems, devices, etc., present on concrete mixer truck **600**. For example, mode controller **1204** may receive any of this information from a McNeilus FLEX Controls™ system present on concrete mixer truck **600**. In another example, mode controller **1204** receives mixer drum speed **1210** from a speed sensor configured to measure an angular velocity of mixer drum **702**. Similarly, mode controller **1204** may directly receive any of vehicle speed **708**, mixer drum speed **1210**, mixer drum revolutions **1212**, vehicle angle **1214**, etc., directly from sensors.

[0103] Vehicle speed **708** is a value of a present velocity of concrete mixer truck **600**, according to some embodiments. For example, vehicle speed **708** may have units of miles per hour, meters per second, feet per second, etc. Mixer drum speed **1210** is a value of a present angular velocity of mixer drum **702**, according to some embodiments. Mixer drum revolutions **1212** is a value of a number of revolutions completed over a time period, according to some embodiments. Vehicle angle **1214** is a value of an orientation of concrete mixer truck **600** relative to a reference orientation, according to some embodiments. For example, vehicle angle **1214** may indicate a current pitch of concrete mixer truck **600** (e.g., if concrete mixer truck **600** is positioned on a hill or an inclined surface). In some embodiments, vehicle angle **1214** is received from an orientation sensor (e.g., a gyroscope) which indicates an orientation of concrete mixer truck **600**. In some embodiments, vehicle angle **1214** is an angle of turn of concrete mixer truck **600**. In some embodiments, vehicle angle **1214** is an angle of concrete mixer truck **600** relative to a spreading zone (e.g., a zone to be filled with mixture present in mixer drum **702**).

[0104] Mode controller **1204** uses the vehicle speed **708**, mixer drum speed **1210**, mixer drum revolutions **1212**, and vehicle angle **1214** in addition to the selected mode to determine at least one of direction and speed of mixer drum **702** and/or at least one of direction and speed of chute **712** to cause mixer drum **702** and/or chute **712** to operate according to the selected mode. In some embodiments, mode controller **1204** stores a set of equations, relationships, rules, instructions, functions, programs, etc., associated with each of the drum modes **1101** and based on the selected mode, operates to produce direction/speed of mixer drum **702** and/or direction/speed of chute **712**

according to the selected mode. Mode controller **1204** is described in greater detail below with reference to FIG. **13**.

[0105] Referring now to FIG. **13**, mode controller **1204** is shown in greater detail, according to an exemplary embodiment. Mode controller **1204** is configured to receive mode selection inputs from user interface device **1202**, sensor/system inputs from sensors/systems **1330**, and transition mixer drum **702** and/or chute **712** between various predefined modes of operation, according to some embodiments. In some embodiments, sensors/systems **1330** include any sensors present on concrete mixer truck **600** and any systems (e.g., control systems, measurement systems, monitoring systems, vehicle electronic systems, etc.). For example, sensor/systems **1330** may include one or more sensors and/or systems configured to measure and/or monitor mixer drum revolutions **1212**, mixer drum speed **1210**, vehicle angle **1214**, vehicle speed **708**, a position of mixer drum **702**, a position and speed of chute **712**, a weight of mixer drum **702**, etc. In some embodiments, sensor/systems **1330** includes a McNeilus FLEX Controls™ system. In some embodiments, sensors/systems **1330** are configured to communicably connect with user interface device **1202** to display various information determined, measured, monitored, detected, etc., by sensors/systems **1330**. In some embodiments, sensors/systems **1330** include sensors and/or systems configured to determine an event. In some embodiments, user interface device **1202** is a component of sensors/systems **1330**. Mode controller **1204** may receive any sensory information, sensor signals, mode selections (e.g., from user interface device **1202**, from sensors/systems **1330**, etc.) and determine commands for drum assembly controller **752** and/or control signals to directly control mixer drum **702** and/or chute **712** to operate according to the selected predefined mode of operation. In some embodiments, sensors/systems **1330** is configured to monitor, measure, sense, detect, etc., any of vehicle speed **708**, mixer drum speed **1210**, mixer drum revolutions **1212**, and vehicle speed **708**, or any other information required for mode manager **1308** to determine commands/control signals to operate mixer drum **702** and/or chute **712** according to a predefined mode.

[0106] In some embodiments, mode controller **1204** uses commands received from user interface device **1202** to transition mixer drum **702** and/or chute **712** between the various predefined modes of operation. In some embodiments, the command to transition between the various predefined modes of operation is an input at user interface device **1202** including but not limited to any of actuating a button, actuating a switch, touching a touchscreen, etc. In some embodiments, user interface device **1202** is configured to receive sensor/system information from sensors/systems **1330** and either display information regarding various sensory inputs and/or information determined by one or more systems. In some embodiments, user interface device **1202** or mode controller **1204** is configured to analyze any of the sensor/system information received from sensors/systems **1330** to determine if an event has occurred (e.g., a high slump event). In some embodiments, sensors/systems **1330** are configured to provide mode controller with information regarding an event. In some embodiments, sensors/systems **1330** are configured to analyze various sensor/system information to determine if an event has occurred which should be responded to with changing an operation of mixer drum **702** and/or chute **712** (e.g., transition into a different predefined mode of operation, transition between drum modes **1101** in response to the event, etc.). In some embodiments, if an event occurs which should be responded to with a transition between drum modes **1101**, sensors/systems **1330** provide mode controller **1204** with at least one of the event which occurred and a determination of what drum mode **601** to transition into.

[0107] Referring still to FIG. **13**, mode controller **1204** includes a communications interface **828** and a processing circuit **1302**, according to some embodiments. Communications interface **828** may include wired or wireless interfaces (e.g., jacks, antennas, transmitters, receivers, transceivers, wire terminals, etc.) for conducting data communications with various systems, devices, sensors, or networks. For example, communications interface **828** may include an Ethernet card and port for sending and receiving data via an Ethernet-based communications network and/or a Wi-Fi

transceiver for communicating via a wireless communications network. Communications interface **828** may be configured to communicate via local area networks or wide area networks (e.g., the Internet, a building WAN, etc.) and may use a variety of communications protocols (e.g., BACnet, IP, LON, etc.). In some embodiments, communications interface **828** is a universal serial bus interface and is configured to communicate serially with one or more various systems, devices, sensors, or networks. In some embodiments, communications interface **828** is any other serial communications interface.

[0108] Communications interface **828** may be a network interface configured to facilitate electronic data communications between mode controller **1204** and various external systems or devices (e.g., user interface device **1202**, drum assembly controller **752**, mixer drum **702**, chute **712**, sensors/systems **1330**, remote server **780**, motor **726**, motor **626**, drum drive system **720**, etc.). For example, mode controller **1204** may receive mode selection and sensor/system inputs from user interface device **1202** and/or sensors/systems **1330** and output commands and/or control signals to drum assembly controller **752**, mixer drum **702**, chute **712**, motor **726**, engine **616**, motor **626**, etc. via communications interface **828**.

[0109] Still referring to FIG. **13**, processing circuit **1302** is shown to include a processor **1304** and memory **1306**, according to some embodiments. Processor **1304** may be a general purpose or specific purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a group of processing components, or other suitable processing components. Processor **1304** may be configured to execute computer code or instructions stored in memory **1306** or received from other computer readable media (e.g., CDROM, network storage, a remote server, etc.).

[0110] Memory **1306** may include one or more devices (e.g., memory units, memory devices, storage devices, etc.) for storing data and/or computer code for completing and/or facilitating the various processes described in the present disclosure. Memory **1306** may include random access memory (RAM), read-only memory (ROM), hard drive storage, temporary storage, non-volatile memory, flash memory, optical memory, or any other suitable memory for storing software objects and/or computer instructions. Memory **1306** may include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present disclosure. Memory **1306** may be communicably connected to processor **1304** via processing circuit **1302** and may include computer code for executing (e.g., by processor **1304**) one or more processes described herein.

[0111] Referring still to FIG. **13**, memory **1306** is shown to include mode manager **1308**, communications manager **1326**, display device manager **1324**, and control signal command generator **1322**, according to some embodiments. Communications manager **1326** receives any of a mode selection, sensor/system inputs, and event inputs and determines if mode manager **1308** should transition between drum modes **1101** based on the received mode selection, sensor/system inputs, and event inputs, according to some embodiments. In some embodiments, communications manager **1326** is configured to receive and analyze sensor/system information and determine if an event has occurred (e.g., slump has exceeded a predetermined threshold value, indicating an added water event) and cause mode manager **1308** to transition into an appropriate mode (e.g., wet load mode **1318** or add water mode **1310**). In some embodiments, communications manager **1326** receives a command from user interface device **1202** and causes mode manager **1308** to transition between a first mode to a second mode (e.g., from add water mode **1310** to smooth mode **1316**) based on the received command.

[0112] In some embodiments, communications manager **1326** is configured to receive sensor/system inputs and convert the sensor/system inputs to a data form which mode manager **1308** can use to determine data outputs. For example, in some embodiments, communications manager **1326** receives a signal from an rpm sensor via communications interface **828**, and determines an rpm value (ω) based on the signal received from the rpm sensor. In some

embodiments, communications manager **1326** is configured to receive or determine an event and provide display device manager **1324** with information regarding the type of event and any other relevant event information. In some embodiments, display device manager **1324** uses the received event and relevant event information to provide a notification (e.g., an alert) regarding the event and the relevant event information. In some embodiments, communications manager **1326** is configured to provide mode manager **1308** with a command to transition from a first mode to a second mode (e.g., smooth mode **1316** to spreader mode **1312**) and provides display device manager **1324** with an indication regarding the mode transition. In some embodiments, display device manager **1324** uses the indication to cause user interface device **1202** to display an alert and/or notification regarding the mode transition. In some embodiments, communications manager **1326** is configured to provide mode manager **1308** with any of vehicle speed **708**, mixer drum speed **1210**, mixer drum revolutions **1212**, and vehicle angle **1214** as received from sensors/systems **1330** via communications interface **828**.

[0113] Referring still to FIG. **13**, memory **1306** includes mode manager **1308**, according to some embodiments. In some embodiments, mode manager **1308** is configured to adjust an operation of at least mixer drum **702** and chute **712** to operate according to a predefined mode of operation. In some embodiments, mode manager **1308** includes add water mode **1310**, spreader mode **1312**, admixture mode **1314**, smooth mode **1316**, wet load mode **1318**, aggressive mode **1320**, empty mode **832**, and dry mode **834**. In some embodiments, mode manager **1308** includes a set of instructions (e.g., equations, functions, scripts, relationships, rules, data, etc.) for determining operational values (e.g., direction of rotation, speed of rotation) of mixer drum **702** and chute **712** such that mixer drum **702** and/or chute **712** operate according to one of modes 810-820 and 832-834. In some embodiments, mode manager **1308** receives a command from communications manager **1326** to transition into a predefined mode of operation (e.g., aggressive mode **1320**) and required informational inputs (e.g., at least one of vehicle speed **708**, mixer drum speed **1210**, mixer drum revolutions **1212**, vehicle angle **1214**, etc.) to determine operational properties of mixer drum **702** and/or chute **712** such that mixer drum **702** and/or chute **712** operate according to the predefined mode. In some embodiments, any of the outputs of mode manager **1308** may be referred to as control variables.

[0114] Referring still to FIG. **13**, mode manager **1308** is shown to include add water mode **1310**, according to some embodiments. In some embodiments, add water mode **1310** is add water drum mode **1114** as shown and described in greater detail above with reference to FIG. **11**. In some embodiments, add water mode **1310** can be implemented immediately after water is added to mixer drum **702** to sufficient mix the concrete/mixture present in mixer drum **702**. When add water mode **1310** is selected, mode manager **1308** determines a speed at which mixer drum **702** should rotate and a number of revolutions mixer drum **702** complete, according to some embodiments. In some embodiments, add water mode **1310** sets mixer drum speed **1210** to a predetermined add water speed. In some embodiments, the predetermined add water speed of mixer drum **702** is greater than 7 rpm. In some embodiments, when in add water mode **1310**, mode manager **1308** monitors a total number of revolutions completed, and continues causing mixer drum to operate at the predetermined add water speed until the total number of revolutions meets a predetermined number of revolutions. In some embodiments, the predetermined number of revolutions is a value based on an ASTM C94 standard and is 30 revolutions. In some embodiments, after the predetermined number of revolutions at the predetermined add water speed has been completed, mode manager **1308** automatically transitions into a constant speed mode or smooth mode **1316**. In some embodiments, add water mode **1310** causes mixer drum **702** to operate according to the following conditions:

[00001]

If: $rev_{total} < rev_{threshold}$ Then: = AWM If: $rev_{total} \geq rev_{threshold}$ Then: TransitionMode

where $rev_{sub.total}$ is a total number of revolutions completed since add water mode **1310** was first

implemented, ω is an angular speed of mixer drum **702**, rev.sub.threshold is a predetermined number of revolutions for add water mode **1310** (e.g., 30 revolutions as set by ASTM C94), and $\omega.\text{sub.AWM}$ is a predetermined add water speed (e.g., >7 rpm).

[0115] In some embodiments, rev.sub.threshold is a predefined value, while in other embodiments, rev.sub.threshold is a value set by a user before add water mode **1310** is implemented. In some embodiments, $\omega.\text{sub.AWM}$ is also settable by a user before add water mode **1310** is implemented. In some embodiments, once the total number of completed revolutions satisfies/meets the total number of revolutions for add water mode **1310**, mode manager **1308** transitions into another mode. For example, mode manager **1308** may transition into smooth mode **1316** after add water mode **1310** has been completed (e.g., $\text{rev.sub.total} \geq \text{rev.sub.threshold}$).

[0116] Advantageously, add water mode **1310** facilitates proper mixing after water addition without the need for an operator/user to manually watch a drum counter, according to some embodiments. This may save fuel, increase life of mixer drum **702**, and reduce the occurrence of under/over mixing concrete.

[0117] Referring still to FIG. **13**, mode manager **1308** includes admixture mode **1314**, according to some embodiments. In some embodiments, admixture mode **1314** is admixture drum mode **1112** as shown and described in greater detail above with reference to FIG. **11**. In some embodiments, admixture mode **1314** can be implemented immediately after an admixture is added to mixer drum **702** to sufficient mix the concrete/mixture present in mixer drum **702**. In some embodiments, admixture mode **1314** causes mixer drum **702** to operate similarly to add water mode **1310**. For example, admixture mode **1314** may cause mixer drum **702** to rotate for a predefined number of revolutions at a predetermined mixer drum speed. However, in some embodiments, admixture mode **1314** causes mixer drum **702** to rotate at an admixture mode speed, $\omega.\text{sub.admixture}$, for a predetermined number of revolutions, $\text{rev.sub.threshold,admixture}$. In some embodiments, the admixture mode drum speed $\omega.\text{sub.admixture}$ is the same as $\omega.\text{sub.AWM}$ (e.g., greater than 7 rpm). In some embodiments, the predetermined number of revolutions $\text{rev.sub.threshold,admixture}$ for admixture mode **1314** is different than rev.sub.threshold . In some embodiments, the predetermined number of revolutions for admixture mode **1314** is 70 revolutions as set by ASTM C94. Admixture mode **1314** facilitates the same advantages of add water mode **1310** by reducing the need for an operator to manually watch a drum counter and saving fuel, increasing life of mixer drum **702**, and reducing the occurrence of over/under mixing concrete/mixture present in mixer drum **702**, according to some embodiments.

[0118] Referring still to FIG. **13**, mode manager **1308** includes smooth mode **1316**, according to some embodiments. In some embodiments, smooth mode **1316** is smooth drum mode **1106** as shown and described in greater detail above with reference to FIG. **11**. In some embodiments, smooth mode **1316** is a standard mode of operation, and unless mode manager **1308** transitions into one of the other modes, mode manager **1308** defaults to causing mixer drum **702** to operate according to smooth mode **1316**. In some embodiments, smooth mode **1316** causes mixer drum **702** to rotate at a predetermined smooth mode speed $\omega.\text{sub.smooth}$ indefinitely. In some embodiments, $\omega.\text{sub.smooth}$ is less than $\omega.\text{sub.admixture}$ and $\omega.\text{sub.AWM}$. In some embodiments, mode manager **1308** returns to smooth mode **1316** in response to a key cycle (e.g., ignition).

[0119] Referring still to FIG. **13**, mode manager **1308** includes wet load mode **1318**, according to some embodiments. In some embodiments, wet load mode **1318** is wet load drum mode **1110** as shown and described in greater detail above with reference to FIG. **11**. In some embodiments, when mode manager **1308** is in wet load mode **1318**, mixer drum **702** is kept rotating faster when concrete mixer truck **600** is moving at a slower speed. Advantageously, this keeps material/concrete/cement present in mixer drum **702** further forwards (e.g., towards cab **614**). Advantageously, this may prevent wet loads from spilling out of mixer drum **702**. In some embodiments, wet load mode **1318** causes mixer drum **702** to rotate at a wet load speed $\omega.\text{sub.wet}$. In some embodiments, $\omega.\text{sub.wet}$ is inversely proportional to a speed of concrete mixer truck **600**,

$v: \omega_{\text{sub.wet}} \propto 1/v$ In some embodiments, wet load mode **1318** determines $\omega_{\text{sub.wet}}$ based on speed v of concrete mixer truck **600** and a current speed of mixer drum **702**. This relationship is shown as:

$$\omega_{\text{sub.wet}} = f_{\text{sub.wet}}(v, \omega_{\text{sub.current}})$$

where $\omega_{\text{sub.current}}$ is a current speed of mixer drum **702**, and $f_{\text{sub.wet}}$ is a function (e.g., linear, non-linear, etc.) relating $\omega_{\text{sub.wet}}$ to the speed v of concrete mixer truck **600** and the current speed $\omega_{\text{sub.current}}$ of mixer drum **702**, according to some embodiments. In some embodiments, wet load mode **1318** determines an amount to increase or decrease the current speed of mixer drum **702** based on the current speed of mixer drum **702** and the speed v of concrete mixer truck **600**. In some embodiments, the increase or decrease is determined by:

$$\Delta\omega_{\text{sub.current}} = f_{\text{sub}}(\Delta(v, \omega_{\text{sub.current}}))$$

where $\Delta\omega_{\text{sub.current}}$ is an amount to increase or decrease $\omega_{\text{sub.current}}$ to achieve $\omega_{\text{sub.wet}}$, and $f_{\text{sub}}(\Delta)$ is a function relating $\Delta\omega_{\text{sub.current}}$ to v and $\omega_{\text{sub.current}}$.

[0120] Wet load mode **1318** may be activated by an operator when a full load with a high slump is present in mixer drum **702** (usually before leaving the plant). Advantageously, wet load mode **1318** removes the need for the operator to manually control the speed of mixer drum **702** while driving. In some embodiments, wet load mode **1318** includes rotating or driving mixer drum **702** at a specific speed for a full load with a high slump.

[0121] Referring still to FIG. **13**, mode manager **1308** includes spreader mode **1312**, according to some embodiments. In some embodiments, spreader mode **1312** is spreader drum mode **1108** as shown and described in greater detail above with reference to FIG. **11**. In some embodiments, spreader drum mode **1108** is activated by an operator for spreading a cement slurry contained in mixer drum **702**. In some embodiments, when mode manager **1308** is in spreader mode **1312**, mode manager **1308** controls an operation of mixer drum **702** and chute **712** to deliver and spread the cement slurry mixture. In some embodiments, spreader mode **1312** includes determining at least one of when to start rotating mixer drum **702**, when to stop rotating mixer drum **702**, speed of mixer drum **702**, pivoting speed of chute **712**, a direction which chute **712** should pivot, a distance (e.g., an angle) that chute **712** should pivot in each direction to spread the slurry mixture, an amount of time that chute **712** should pivot in each direction to spread the slurry mixture, etc., based on vehicle speed **708** and vehicle angle **1214**. In some embodiments, spreader mode **1312** determines a discharge speed, $v_{\text{sub.discharge}}$, and a drum speed, $\omega_{\text{sub.discharge,drum}}$ to provide the cement of mixer drum **702** to a receiving site/area at a constant volumetric flow rate. In some embodiments, spreader mode **1312** determines a speed at which to pivot chute **712** in each direction such that a certain amount of mixture (e.g., concrete, cement, etc.) is delivered to the receiving site/area.

[0122] In some embodiments, mode manager **808**, when operating in spreader mode **1312**, receives an input from user interface device **1202** regarding a desired depth of concrete, $d_{\text{sub.concrete}}$, for the receiving area, an angular displacement of chute **712** in a first direction (e.g., counterclockwise), $\theta_{\text{sub.1}}$, and an angular displacement of chute **712** in a second direction (e.g., clockwise), $\theta_{\text{sub.2}}$. In some embodiments, $\theta_{\text{sub.1}}$ and $\theta_{\text{sub.2}}$ indicate a width of the receiving site/area which the mixture is to be delivered to.

[0123] In some embodiments, $d_{\text{sub.concrete}}$, $\theta_{\text{sub.1}}$, and $\theta_{\text{sub.2}}$ are used to in addition to vehicle speed **708** (v) and vehicle angle **1214** (θ) to determine operations of mixer drum **702** and chute **712** to provide material/mixture from mixer drum **702** to the receiving area at a constant rate. For example, as concrete mixer truck **600** drives forwards, at least one of $\omega_{\text{sub.discharge,drum}}$ and a pivoting speed of chute **712** ($\omega_{\text{sub.chute}}$) increases such that material/mixture is provided to the receiving area, regardless of vehicle speed **708**. In some embodiments, $\omega_{\text{sub.chute}}$ and $\omega_{\text{sub.discharge,drum}}$ are limited to maximum speed, and therefore the operator must not operate

concrete mixer truck **600** such that vehicle speed **708** exceeds a predetermined threshold value. In some embodiments, vehicle speed **708** is limited to a maximum value, $v_{sub.vehicle,max}$. In some embodiments, as long as vehicle speed **708** remains below the maximum value $v_{sub.vehicle,max}$, the concrete/mixture is evenly distributed throughout the receiving area.

[0124] In some embodiments, $\omega_{sub.discharge,drum}$ and $\omega_{sub.chute}$ are determined based on time-values. For example, in some embodiments, a first amount of time $t_{sub.1}$ for chute **712** to rotate/move in a first direction, and a second amount of time $t_{sub.2}$ for chute **712** to rotate in a second direction, opposite the first direction, are input through user interface device **1202**. In some embodiments, the first amount of time and the second amount of time are determined based on $\theta_{sub.1}$ and $\theta_{sub.2}$. In some embodiments, a current position of chute **712** is determined by receiving information from a sensor configured to detect a position of chute **712**. In some embodiments, the sensor is a proximity sensor, configured to sense if chute **712** is centered. In some embodiments, spreader mode **1312** centered chute **712** before implementing automatic control of mixer drum **702** and chute **712**.

[0125] In some embodiments, spreader mode **1312** causes user interface device **1202** to prompt an operator of concrete mixer truck **600** to input required parameters. In some embodiments, the required parameters include at least one of $\theta_{sub.1}$, $\theta_{sub.2}$, $t_{sub.1}$, $t_{sub.2}$, and $d_{sub.concrete}$. Spreader mode **1312** uses the input parameters in addition to vehicle speed v and vehicle angle θ to determine $\omega_{sub.discharge,drum}$ and $\omega_{sub.chute}$ to facilitate delivery of the mixture/concrete/cement to the receiving area at the desired thickness $d_{sub.concrete}$, according to some embodiments.

[0126] Advantageously, automatically determining $\omega_{sub.discharge,drum}$ and $\omega_{sub.chute}$ facilitates easy spreading/discharge of mixture (e.g., concrete, cement, etc.) present in mixer drum **702** to a receiving site, according to some embodiments. An operator can position concrete mixer truck **600** near the receiving area such that chute **712** is above the receiving area and can implement spreader mode **1312** through user interface device **1202**. The operator may be prompted to input required parameters (e.g., $d_{sub.concrete}$, $\theta_{sub.1}$, $\theta_{sub.2}$, etc.). After the operator has input the required parameters and spreader mode **1312** is engaged, the operator can pull concrete mixer truck **600** forwards (or backwards depending on which end of concrete mixer truck **600** chute **712** is positioned at), and spreader mode **1312** automatically determines operations of mixer drum **702** and chute **712** (e.g., $\omega_{sub.discharge,drum}$, $\omega_{sub.chute}$) to provide the mixture to the receiving site across the range specified by the operator (e.g., from $\theta_{sub.1}$ to $\theta_{sub.2}$) at the required rate/with the required thickness/depth ($d_{sub.concrete}$). Advantageously, this removes the need for manually moving or controlling chute **712** and mixer drum **702** to deliver the mixture to the receiving area, according to some embodiments. In some embodiments, the operator can manually input (e.g., at user interface device **1202**) any of the parameters/values which spreader mode **1312** determines automatically or uses to determine the operational values of mixer drum **702** and/or chute **712** (e.g., $\omega_{sub.discharge,drum}$, $\omega_{sub.chute}$, $t_{sub.1}$, $t_{sub.2}$, $v_{sub.discharge}$, volumetric discharge rate, etc.).

[0127] Referring still to FIG. **13**, mode manager **1308** includes aggressive mode **1320**, according to some embodiments. In some embodiments, aggressive mode **1320** is aggressive drum mode **1116** as shown and described in greater detail above with reference to FIG. **11**. In some embodiments, aggressive mode **1320** causes mixer drum **702** to operate to clear clogged or built up mixture present within mixer drum **702**. For example, if during spreader mode **1312**, mixer drum **702** and/or any components between mixer drum **702** and chute **712** to facilitate egress of the mixture from mixer drum **702** to chute **712** become clogged, mode manager **1308** can transition mixer drum **702** into aggressive mode **1320**. In some embodiments, mode manager **1308** automatically transitions into spreader mode **1312** in response to a received event (e.g., a blockage/clog/build up event). In some embodiments, mode manager **1308** transitions into spreader mode **1312** in response to a manual command received from user interface device **1202**. For example, if an operator sees

that mixer drum **702** is clogged, the operator may manually transition mixer drum **702** into aggressive mode **1320** by inputting a command at user interface device **1202**.

[0128] Aggressive mode **1320** may cause mixer drum **702** to actuatably start and stop rotating. In some embodiments, aggressive mode **1320** does not incorporate any ramping or smoothed stopping functions. For example, McNeilus FLEX Controls™ includes a Smooth Drum Stop technology which smoothly reduces drum momentum when a drum stop is engaged. In some embodiments, aggressive mode **1320** implements a drum stop but does not use the Smooth Drum Stop technology.

[0129] In some embodiments, aggressive mode **1320** includes rocking mixer drum **702** back and forth to clear any blockages or clogging. In some embodiments, aggressive mode **1320** causes mixer drum **702** to rotate a certain amount or for a certain amount of time in a first direction at a first angular speed (e.g., $\omega_{sub.1}$), then rapidly decelerates mixer drum **702**, bringing mixer drum **702** to a complete stop. In some embodiments, this is repeated a predetermined number of times. In some embodiments, this is repeated until a clogging or a buildup is mitigated. In some embodiments, after causing mixer drum **702** to rotate the certain amount or for the certain amount of time in the first direction at the first angular speed, mixer drum **702** is caused to rotate in an opposite direction for a second amount of time or for a second certain amount. In this way, mixer drum **702** is rocked back and forth (e.g., clockwise, then counter clockwise) and the inertial forces and momentum of mixer drum **702** cause any blockages or clogging or buildups of material within mixer drum **702** to be cleared.

[0130] Advantageously, aggressive mode **1320** facilitates easy un-clogging of mixer drum **702** and/or any other components which concrete/mixture/material may build up on, according to some embodiments. This removes the need for an operator to manually unclog mixer drum **702**. In some embodiments, the rocking of mixer drum **702** is performed such that excessive inertial/momentum forces are not introduced to mixer drum **702** or components which mount mixer drum **702** to concrete mixer truck **600**. In some embodiments, aggressive mode **1320** can only be activated/transitioned into if concrete mixer truck **600** is stationary, or if vehicle speed **708** is less than a maximum threshold value (e.g., 10 mph).

[0131] Referring still to FIG. **13**, memory **1306** includes empty mode **832** and dry mode **834**, according to some embodiments. In some embodiments, empty mode **832** is empty load drum mode and dry mode **834** is dry load drum mode as described above with reference to FIG. **11**. In some embodiments, both empty mode **832** and dry mode **834** cause mixer drum **702** to spin at a low speed (e.g., less than 2 rpm). In some embodiments, empty mode **832** keeps mixer drum **702** spinning at a low speed to keep rollers of mixer drum **702** from flat spotting. In some embodiments, empty mode **832** causes mixer drum **702** to spin at an angular speed of less than 1 rpm. In some embodiments, empty mode **832** can be transitioned into after mixture has exited mixer drum **702** and mixer drum **702** is completely empty or nearly empty (e.g., in response to mode controller **1204** determining that mixer drum **702** is empty). In some embodiments, dry mode **834** causes mixer drum **702** to rotate at angular speed less than wet load mode **1318**. In some embodiments, dry mode **834** causes mixer drum **702** to rotate at an angular speed of approximately 1-1.5 rpm. In some embodiments, dry mode **834** causes mixer drum **702** to rotate fast enough to keep material in mixer drum **702** and prevent rollers of mixer drum **702** from flat spotting. In some embodiments, dry mode **834** can be transitioned into before water has been added to the mixture or if the mixture of mixer drum **702** is relatively dry.

[0132] In some embodiments, mode controller **1204** automatically transitions into either dry mode **834** or empty mode **832** in response to determining that mixer drum **702** is empty, or in response to a command from user interface device **1202**. For example, if mode controller **1204** receives an indication that the mixture within mixer drum **702** is dry, mode controller **1204** can automatically transition into dry mode **834**. Likewise, if mode controller **1204** receives an indication that there is no material/mixture within mixer drum **702**, or there is a negligible amount of material/mixture within mixer drum **702**, mode controller **1204** can transition into empty mode **832**.

[0133] Referring still to FIG. 13, memory 1306 includes control signal/command generator 1322 and display device manager 1324, according to some embodiments. In some embodiments, mode manager 1308 is configured to output data regarding operational settings of mixer drum 702 and/or chute 712 to cause mixer drum 702 and/or chute 712 to operate according to the selected mode. In some embodiments, control signal/command generator 1322 is configured to determine/generate control signals and provide the control signals to mixer drum 702 and/or chute 712 to cause mixer drum 702 and/or chute 712 to operate according to the output data from mode manager 1308. For example, if mode manager 1308 outputs a drum speed of 10 rpm, control signal/command generator 1322 may generate control signals to cause mixer drum 702 to rotate at the drum speed of 10 rpm. In some embodiments, control signal/command generator 1322 outputs the control signals to an element (e.g., a mover) configured to control a desired operation of mixer drum 702 and/or chute 712. For example, control signal/command generator 1322 may output control signals to one or more motors, actuators, engines, etc., to cause mixer drum 702 and/or chute 712 to operate according to the operation/data as determined by mode manager 1308.

[0134] In some embodiments, control signal/command generator 1322 is configured to output a command to a controller (e.g., drum assembly controller 752) to cause mixer drum 702 and/or chute 712 to function according to the determined operation (e.g., as determined by mode manager 1308). In some embodiments, control signal/command generator 1322 is configured to output a command to a system, controller, device, etc., which is configured to generate control signals for mixer drum 702 and/or chute 712 to adjust an operation of mixer drum 702 and/or chute 712. In some embodiments, control signal/command generator 1322 outputs any of the command and the control signal via communications interface 828. In some embodiments, the command and/or the control signal(s) are transmitted wirelessly to a controller or device (e.g., drum assembly controller 752 and motor 726). In some embodiments, the command(s) and/or the control signal(s) are transmitted via a wired connection between communications interface 828 and one or more controllers, motors, systems, etc., configured to adjust an operation of mixer drum 702 and/or chute 712.

[0135] In some embodiments, display device manager 1324 is configured to cause user interface device 1202 to display information regarding a selected mode. In some embodiments, display device manager 1324 receives the data outputs/determined operational values of mixer drum 702 and/or chute 712 from mode manager 1308 and causes user interface device 1202 to display the data outputs/determined operational values of mixer drum 702 and/or chute 712. For example, if mode manager 1308 outputs $\omega_{\text{sub.discharge,drum}} = -7$ rpm, display device manager 1324 may cause user interface device 1202 to display a notification that indicates the present value (i.e., -7 rpm) of $\omega_{\text{sub.discharge,drum}}$.

[0136] Referring now to FIG. 14, display system 1400 includes user interface device 1202 positioned within cab 614 of concrete mixer truck 600, according to some embodiments. In some embodiments, user interface device 1202 is configured to display GUI 1100 to provide notifications, messages, alerts, etc., to an operator of concrete mixer truck 600. In some embodiments, user interface device 1202 is a touchscreen device, configured to receive an input from the operator to transition mixer drum 702 and/or chute 712 between various predefined modes of operation, as described in greater detail above with reference to FIGS. 6 and 8. In some embodiments, user interface device 1202 is mounted to a dashboard 1402 of cab 614.

[0137] Referring now to FIG. 15, a process 1500 for transitioning a concrete mixer truck between various predefined modes of operation is shown, according to some embodiments. In some embodiments, process 1500 may be performed by mode controller 1204, user interface device 1202, and drum assembly controller 752, or any other device, system, controller, etc., configured to control an operation of mixer drum 702 and/or chute 712.

[0138] Process 1500 includes receiving a selection of a mode of operation of a mixer drum (e.g., mixer drum 702) and a chute (e.g., chute 712) from various predefined modes of operation (step

1502), according to some embodiments. In some embodiments, step **1502** includes receiving the selection from a user interface device. In some embodiments, the received selection is an event. In some embodiments, the event indicates a transition from one predefined mode to another predefined mode of operation of the mixer drum and the chute. In some embodiments, the selection and/or the event are received by mode controller **1204** (or more specifically, communications manager **1326**) via communications interface **828**. In some embodiments, the various predefined modes of operation include but are not limited to an add water mode, a spreader mode, an admixture mode, a smooth mode, a wet load mode, and an aggressive mode.

[0139] Process **1500** includes transitioning the mixer drum and the chute into the selected predefined mode of operation (step **1504**), according to some embodiments. In some embodiments, step **1504** is performed by mode controller **1204** or, more particularly, mode manager **1308**. In some embodiments, the mixer drum and the chute are selected into the predefined mode of operation in response to at least one of an event, a selected input, etc.

[0140] Process **1500** includes determining one or more control variables of at least one of the mixer drum and the chute based on the selected predefined mode of operation (step **1506**), according to some embodiments. In some embodiments, the one or more control variables are determined by mode controller **1204** or more specifically mode manager **1308** of mode controller **1204**. In some embodiments, the one or more control variables are determined using at least one of an equation, a set of equations, a set of rules, a function, a lookup table, etc., corresponding the selected predefined mode of operation. In some embodiments, each of the various predefined modes of operation includes a corresponding equation, set of equations, set of rules, function, or lookup table, etc., used to determine one or more control variables for the mixer drum (e.g., mixer drum **702**) and the chute (e.g., chute **712**) for the selected predefined mode of operation. In some embodiments, the one or more control variables are used to determine control signals for controllable elements (e.g., mixer drum **702**, chute **712**) to adjust an operation of the controllable elements. In some embodiments, mode controller **1204** is configured to use the one or more control variables to determine control signals for the controllable elements. In some embodiments, mode controller **1204** is configured to provide the one or more control variables to another controller, system, device, etc., configured to use the one or more control variables to generate control signals for the controllable elements to implement the selected predefined mode of operation.

[0141] Process **1500** includes adjusting an operation of the mixer drum (e.g., mixer drum **702**) and/or the chute (e.g., chute **712**) based on the selected predefined mode of operation (step **1508**), according to some embodiments. In some embodiments, the operation of the mixer drum and/or the chute are adjusted based on the one or more control variables determined in step **1506**. In some embodiments, the operation of the mixer drum and/or the chute are adjusted based on the control variables determined in step **1506** and one or more operational values of the concrete mixer truck, or the mixer drum, or the chute (e.g., v of the truck, ω of the mixer drum, etc.). In some embodiments, step **1508** is performed by mode controller **1204**. In some embodiments, step **1508** is performed by another controller configured to communicably connect with mode controller **1204**, receive the one or more control variables, and generate control signals to adjust an operation of the mixer drum and/or the chute.

[0142] Process **1500** includes displaying information regarding the selected predefined mode of operation and one or more operating values of the mixer drum and/or the chute (step **1510**), according to some embodiments. In some embodiments, step **1510** is performed by mode controller **1204** and/or user interface device **1202**. In some embodiments, user interface device **1202** displays information regarding the selected predefined mode of operation to a user (e.g., an operator of the concrete mixer truck). In some embodiments, the one or more operation values of the mixer drum and the chute are live-values, indicating a present operational status of the mixer drum and/or the chute.

Concrete Mixer Vehicle with Autonomous Modes

[0143] Referring particularly to FIGS. **16-18**, the concrete mixer truck **600** is transitionable between different autonomous modes, according to an exemplary embodiment. For example, the concrete mixer truck **600** may be transitionable between a first autonomous mode when geographically located at a plant, and a second autonomous mode when geographically located at a jobsite. The concrete mixer truck **600** can be automatically or manually transitioned between the first and the second autonomous mode. The concrete mixer truck **600** can implement any of the functionality of tracking and alert system **300** to facilitate operation of the concrete mixer truck **600** while in any of the autonomous modes (e.g., operation of systems, transportation, implements, etc., thereof) or to facilitate automatic transitioning between the autonomous modes. In some embodiments, any of the autonomous modes described herein are also configured to perform any of the functionality of the add water mode **1310**, the spreader mode **1312**, the admixture mode **1314**, the smooth mode **1316**, the wet load mode **1318**, the aggressive mode **1320**, or the dry mode **1334**.

[0144] Referring particularly to FIG. **16**, a diagram of the system **1200** according to another embodiment is shown. The mode controller **1204** includes the mode manager **1308** and is configured to generate control signals or commands for the drum assembly controller **752**, the mixer drum **702**, the chute **712**, a washout system **714** of the concrete mixer truck **600**, or the vehicle drive system **620** of the concrete mixer truck **600**. The washout system **714** of the concrete mixer truck **600** is a system that is configured to clear various tubular members (e.g., by providing pressurized air, water, etc., therethrough). The tubular members can be configured to fluidly couple with an additive source, and the washout system **714** may clear or clean the tubular members.

[0145] Referring still to FIG. **16**, the mode manager **1308** includes autonomous modes **1336**. Specifically, the autonomous modes **1336** include a plant mode **1338** and a site mode **1340**. The mode manager **1308** can transition the concrete mixer truck **600** between the plant mode **1338** and the site mode **1340** in response to a user input received from the user interface device **1202** (e.g., a button), a chassis input (e.g., a sensor or system signal, an identified behavior, an identified function, etc.) received from a chassis sensor **1342** of frame **612**, a geolocation received from a geosystem **1344** (e.g., a GPS sensor, the tracking and alert system **300**, a satellite, a network system, etc.), sensor data received from a sensor **1330** of the concrete mixer truck **600** (e.g., any of the sensors described herein, a weight sensor, a revolution sensor, etc.), or a command from a cloud computing system **1346**.

[0146] When the mode manager **1308** transitions the concrete mixer truck **600** into the plant mode **1338**, the mode manager **1308** can generate control signals for the concrete mixer truck **600** (e.g., for the drum assembly controller **752**, the mixer drum **702**, and the vehicle drive system **620**) to facilitate automatic loading or filling of the mixer drum **702** without requiring driver interaction. For example, when the concrete mixer truck **600** is in the plant mode **1338**, the mode controller **1204** can generate control signals to autonomously control the speed of the mixer drum **702**, and detect when filling of the mixer drum **702** is completed. The mode controller **1204** can detect or sense when the mixer drum **702** is being loaded based on the sensor data received from the sensor(s) **1330** (e.g., hydraulic sensor information, weight information, etc.), or based on the geolocation received from the geosystem **1344** (e.g., indicating that the concrete mixer truck **600** is positioned beneath a filling or concrete plant). The mode controller **1204** can also monitor sensor data indicating a fill level of the mixer drum **702** and can integrate or communicate with a plant-local system (e.g., wirelessly) to facilitate loading or filling of the mixer drum **702** with appropriate slurry material, ingredients, additives, concrete, etc. The mode controller **1204** can also automatically operate the vehicle drive system **620** to align the mixer drum **702** for filling at the concrete plant (e.g., using the geolocation as feedback). For example, if the geolocation indicates that the concrete mixer truck **600** is within a geofence at a concrete plant, the mode controller **1204** may transition the concrete mixer truck **600** into the plant mode **1338** to facilitate autonomous filling of the mixer drum **702**.

[0147] The mode controller **1204** also facilitates or controls the concrete mixer truck **600** to mix the

materials within the mixer drum **702** after the mixer drum **702** has been filled. In some embodiments, the mode controller **1204** operates the drum assembly controller **752** or the mixer drum **702** (or motor, engine, or motive element thereof) to drive the mixer drum **702** to rotate to mix the material. For example, when the mode controller **1204** detects that the mixer drum **702** has been sufficiently filled with material, the mode controller **1204** may then implement an autonomous mixing function. The plant mode **1338** can implement any of the functionality of the add water mode **1310**, the smooth mode **1316**, the aggressive mode **1320**, the dry mode **1334**, etc., to facilitate autonomous mixing of the material within the mixer drum **702**. The mode controller **1204** may commence mixing when it detects that a specific number of revolutions of the mixer drum **702** have been completed, or when a sensor signal from a material sensor in the mixer drum **702** indicating that the material has been sufficiently mixed, or in response to a signal from another source indicating a completion of the mixing (e.g., an input or cell signal received from the cloud computing system **1346** indicating that the concrete is mixed). The mode controller **1204** may also initiate a washout sequence to be performed by the washout system **714** based on data or information indicating a completion of loading, mixing, and/or the geolocation of the concrete mixer truck **600**.

[0148] Referring still to FIG. **16**, the mode controller **1204** can also be configured to transition the concrete mixer truck **600** into the site mode **1340**. The concrete mixer truck **600** can automatically transition into the site mode **1340** when the geolocation of the concrete mixer truck **600** indicates that the concrete mixer truck **600** is at a jobsite. In some embodiments, the concrete mixer truck **600** is transitioned into the site mode **1340** automatically in response to the chassis input. In some embodiments, the concrete mixer truck **600** is transitioned into the site mode **1340** in response to receiving a user input from the user interface device **1202**.

[0149] When the concrete mixer truck **600** is in the site mode **1340**, the mode controller **1204** may generate commands or control signals for the drum assembly controller **752**, the mixer drum **702**, the chute **712**, and/or the vehicle drive system **620** to facilitate a fully-autonomous or semi-autonomous discharge or pouring of the concrete to a jobsite, or a specific area. For example, the concrete mixer truck **600** can operate to control speed of the mixer drum **702**, direction of rotation of the mixer drum **702**, rotation angle of the chute **712**, lift angle of the chute **712**, whether or not one or more chutes are extended or unfolded (e.g., by operation of a hydraulic, pneumatic, or electric system) for autonomous pouring of the concrete.

[0150] In some embodiments, the mode controller **1204** is configured to receive information regarding the jobsite (e.g., from a user input, from the cloud computing system **1346**, when at the concrete plant, etc.) and use the information to autonomously pour concrete. In some embodiments, the information regarding the jobsite includes one or more geofences, geozones, or areas where concrete should be poured, a depth of concrete to be poured, a type of concrete to be poured, etc.). Based on the information, the mode controller **1204** can adjust speed of the mixer drum **702**, operation of the chute **712**, etc., to pour concrete at the jobsite into the correct location or across the one or more areas. For example, feedback from a position or angle sensor of the chute **712** may be used by the mode controller **1204** to direct the chute **712** to pour concrete at a consistent depth across a patio, zone, area, slab, etc. In some embodiments, the mode controller **1204** also controls the vehicle drive system **620** to automatically cause the concrete mixer truck **600** to stop, drive forwards, drive in reverse, turn, etc., to facilitate proper dispensing or pouring of the concrete for the one or more areas of the jobsite (e.g., to reposition the concrete mixer truck **600**).

[0151] In some embodiments, the mode controller **1204** receives the one or more areas where concrete should be poured at a jobsite as a geofence on a map (e.g., drawn on a map by an individual). The mode controller **1204** can autonomously facilitate transportation of the concrete mixer truck **600** to the one or more areas using the map and the geolocation provided by the geosystem **1344**. The mode controller **1204** can also use information for the one or more areas indicating required depth of concrete to autonomously operate the concrete mixer truck **600** to pour

the concrete at the required depth. In some embodiments, the mode controller **1204** is configured to determine where to pour the concrete based on data received from a visual sensor, camera, etc. The mode controller **1204** can identify a visual indicator at the jobsite (e.g., shapes of forms) and may operate the concrete mixer truck **600** to pour the concrete until the forms are full. In some embodiments, the mode controller **1204** is configured to determine where to pour concrete based on a signal from an operator (e.g., an individual at the jobsite holding a symbol or signal generator that the mode controller **1204** identifies). For example, the symbol or signal generator can be an orange circle which can be identified by the mode controller **1204** using a camera. The operator may move the visual indicator (e.g., the orange circle) and the mode controller **1204** or concrete mixer truck **600** can track and follow the visual indicator to facilitate pouring the concrete. The visual indicator may be moved to direct flow of pouring of the concrete or to indicate an extent of the area that requires concrete.

[0152] Referring particularly to FIG. **17**, a diagram **1700** depicts the functionality of the autonomous modes **1336**. Diagram **1700** illustrates a plant area **1702** and a jobsite **1704** that are at different geographic locations. The concrete mixer truck **600** or controllers thereof may wirelessly communicate with a geolocation system **1710** (e.g., a cloud computing system, a satellite, a GPS system, etc.). The geolocation system **1710** can implement any of the functionality of system **300**, or may be geosystem **1344** (or vice versa). When the concrete mixer truck **600** is geographically located at the plant area **1702**, the concrete mixer truck **600** can be transitioned into the plant mode **1338** (e.g., automatically). The concrete mixer truck **600** may automatically transport itself beneath a filling station **1712** and communicate with local controllers at the filling station **1712** to facilitate autonomous filling and mixing of the mixer drum **702** of the concrete mixer truck **600**.

[0153] The concrete mixer truck **600** can then transport along a route **1708** to the jobsite **1704**. In some embodiments, the concrete mixer truck **600** is configured to be driven by an operator along the route **1708** and can be tracked by the geolocation system **1710** as it transports along the route **1708**. In some embodiments, the mode controller **1204** is configured to autonomously transport the concrete mixer truck **600** along the route **1708** to the jobsite **1704**.

[0154] When the concrete mixer truck **600** arrives at the jobsite **1704**, the mode controller **1204** can transition the concrete mixer truck **600** into the site mode **1340**. The jobsite **1704** includes one or more pour areas, shown as area **1706a** and area **1706b**. The concrete mixer truck **600** operates in the site mode **1340** to autonomously pour the concrete at the area **1706a** and the area **1706b**. In some embodiments, the concrete mixer truck **600** operates in the site mode **1340** to automatically pour the concrete at the areas **1706** and to transport between the area **1706a** and the area **1706b**.

[0155] Referring particularly to FIG. **18**, a process **1800** for operating a concrete mixer truck according to various autonomous modes is shown, according to some embodiments. Process **1800** includes steps **1802-1816** and can be performed by the concrete mixer truck **600** and the mode controller **1204**. In some embodiments, process **1800** facilitates autonomous filling, mixing, and pouring of a concrete material.

[0156] Process **1800** includes providing a concrete mixer truck that is transitionable between at least a first autonomous mode and a second autonomous mode (step **1802**), according to some embodiments. In some embodiments, the concrete mixer truck is the concrete mixer truck **600**. In some embodiments, the first autonomous mode is the plant mode **1338** to facilitate autonomous operations at a concrete plant. In some embodiments, the second autonomous mode is the site mode **1340** to facilitate the performance of autonomous operations at a site (e.g., automatic pouring).

[0157] Process **1800** includes detecting one or more conditions indicating that the concrete mixer is at a concrete plant (step **1804**), according to some embodiments. In some embodiments, step **1804** includes detecting one or more conditions that indicate that the concrete mixer truck should be transitioned into the first autonomous mode. The one or more conditions can be sensor data indicating a relative position of the concrete mixer truck, a geotracking data indicating a geographic location of the concrete mixer, a chassis signal, a user input, communications with a

plant controller or system, near field communications, wireless communications, proximity data (e.g., relative location between the concrete mixer truck and a fill location), etc. Step **1804** can be performed by the mode controller **1204**.

[0158] Process **1800** includes transitioning the concrete mixer truck into the first autonomous mode (step **1806**) in response to detecting the one or more conditions, according to some embodiments. In some embodiments, step **1806** is performed by the mode controller **1204**. Step **1806** can be performed for subsequent autonomous actions in the first autonomous mode to facilitate automatic filling, mixing, etc., of a mixer drum of the concrete mixer truck.

[0159] Process **1800** includes operating the concrete mixer truck in the first autonomous mode to automatically fill a mixer drum of the truck and mix a slurry material (step **1808**), according to some embodiments. Step **1808** can be performed by the mode controller **1204**, the drum assembly controller **752**, the mixer drum **702**, the chute **712**, the washout system **714**, and/or the vehicle drive system **620**. Step **1808** can include positioning the concrete mixer truck beneath a fill station, and initiating mixing once sensor data or a command indicates that the mixer drum has been filled. Once the mixer drum has been filled, the mode controller **1204** may operate the mixer drum to rotate to mix the slurry material. Step **1808** can also include operating a washout system after the slurry material has been sufficiently mixed.

[0160] Process **1800** includes transporting the concrete mixer truck to a jobsite (step **1810**), according to some embodiments. In some embodiments, step **1810** is performed manually by a driver (e.g., driving the concrete mixer truck to the jobsite). In some embodiments, step **1810** is performed autonomously by an autonomous drive system of the concrete mixer truck which may communicate with a geolocation system.

[0161] Process **1800** includes detecting one or more conditions that indicate that the concrete mixer truck is at the jobsite or is at a pour area of the jobsite (step **1812**), according to some embodiments. In some embodiments, the one or more conditions include sensor data (e.g., camera data) indicating that the concrete mixer truck is at the jobsite, a user input that the concrete mixer truck is at the jobsite, geolocation data indicating that the concrete mixer truck is at the jobsite, etc. Step **1812** can be performed by the mode controller **1204**.

[0162] Process **1800** includes transitioning the concrete mixer truck into the second autonomous mode (step **1814**), according to some embodiments. In some embodiments, step **1814** is performed in response to step **1812**. In some embodiments, step **1814** is performed by the mode controller **1204**. Step **1814** can include re-configuring the mode controller **1204** for controlling the concrete mixer truck to autonomously perform various pouring operations.

[0163] Process **1800** includes operating the concrete mixer truck in the second autonomous mode to automatically pour the slurry material (step **1816**), according to some embodiments. In some embodiments, step **1816** is performed by mode controller **1204**. Step **1816** can include operating a mixer drum (or a drum drive system) and various motors, engines, etc., thereof, in combination a chute to pour the slurry material (e.g., discharge from the mixer drum) to or across the pour area of the jobsite. In some embodiments, step **1816** is performed to fully or semi-autonomously pour the slurry material or concrete to different pour areas or jobsites.

Automatic Chute Control and Concrete Placement

[0164] Referring particularly to FIGS. **19-22**, the concrete mixer truck **600** can be configured to implement the techniques described herein to automatically control the chute to pour the concrete or discharge the slurry material from the mixer drum **702**. The concrete mixer truck **600** can include a system to operate positioning and angle based on real-time sensor data indicating a relative position of a form into which the concrete or slurry material is to be formed.

[0165] Referring particularly to FIGS. **19** and **22**, the concrete mixer truck **600** includes an electronic control system **1900**, according to an exemplary embodiment. The electronic control system **1900** can be a part of the drum control system **750** or may integrate with the drum control system **750**. In some embodiments, the electronic control system **1900** includes the chute **712**. The

electronic control system **1900** is configured to operate the chute **712** to rotate upwards or downwards (e.g., in direction **1904**) and/or about an axis **1906**. In some embodiments, any of the functionality of the electronic control system **1900** as described herein is implemented by mode controller **1204**.

[0166] The electronic control system **1900** also includes one or more sensors **1908** that are configured to obtain sensor data, image data, etc., of a pour site **1910**. The pour site **1910** may be a jobsite or an area where concrete or slurry material is to be discharged. The pour site **1910** can include a form **2000** into which the concrete or slurry material is to be poured. The sensor **1908** can be or include a radar sensor, a camera, an ultrasonic sensor, a lidar sensor, a GPS sensor, etc., and may be configured to detect, measure, obtain, etc., geometry, relative distance, topology, etc., of the pour site **1910**. In some embodiments, the sensor **1908** is configured to detect relative location and geometry of the form **2000**.

[0167] The electronic control system **1900** also includes one or more actuators **1902**. The one or more actuators **1902** can be configured to change the position, extension, rotation, angle, etc., of the chute **712** to adjust a discharge direction or destination of the slurry material or concrete in the mixer drum **702** (e.g., as the concrete mixer truck **600** operates to discharge the slurry material). In some embodiments, the one or more actuators **1902** include a hydraulic actuator, an electric actuator, an electric motor, an engine, a pneumatic actuator, etc., configured to drive the chute **712** (e.g., upwards and downwards in direction **1904** and/or about axis **1906** in either direction). The electronic control system **1900** also includes a controller **2200** that is configured to obtain sensor data from the one or more sensors **1908** and operate the chute **712** (e.g., orientation, position, extension, angle, rotation, movement, etc.) based on the sensor data. The controller **2200** can be the same as or similar to the mode controller **1204**. In some embodiments, the controller **2200** is configured to integrate or communicate with the mode controller **1204** to receive commands from the mode controller **1204** for operation of the chute **712**. In some embodiments, operation of the chute **712** (e.g., by the controller **2200** or through operation of the actuators **1902**) is tied with operation of the mixer drum **702**, so that the chute **712** and the mixer drum **702** operate cooperatively to discharge the slurry material to the pour site **1910**.

[0168] Advantageously, the sensor(s) **1908** can be configured to detect the pour site **1910** (e.g., a work area) and its environment. The electronic control system **1900** (e.g., a chute, discharge, or pouring control system) can be configured to automatically or autonomously operate discharge of the slurry material (e.g., operation of the chute **712**) based on the detection of the pour site **1910** and its environment. In some embodiments, the techniques or functionality described herein with regards to the electronic control system **1900** can be implemented by mode controller **1204** when the concrete mixer truck is in the site mode **1340**. The electronic control system **1900** can also be configured to control or operate speed of the mixer drum **702**, and/or direction of rotation of the mixer drum **702**. In some embodiments, the electronic control system **1900** (e.g., the controller **2200**) is configured to determine an amount of concrete or slurry material to be dispensed or discharged (e.g., based on the sensor data obtained from the sensors **1908**). In some embodiments, the sensor data obtained from the sensors **1908** can include detection of individuals or people at the pour site **1810** and/or ground level and/or terrain (e.g., surface topology) of the pour site **1910**. Advantageously, the electronic control system **1900** facilitates automatic or autonomous discharge and pouring of concrete/slurry material, provides improved safety (e.g., by detecting if people are present at the pour site **1910** or proximate the chute **712** and implementing one or more safety features), reduces a required skill level for the driver/operator, and reduces a need for an operator to be at the chute **712** or proximate the pour site **1910** during concrete pouring.

[0169] The controller **2200** can be configured to receive the sensor data (e.g., worksite sensor data) from the sensors **1908**, and desired pour area data from a user device **2300**. The desired pour area data may be a user input received from the user device **2300** indicating an area and depth where concrete or slurry material should be discharged. The controller **2200** is configured to generate

control signals for any of the actuators **1902**, the vehicle drive system **620** (e.g., to pull the vehicle forwards as the concrete or slurry material is discharged), or the drum assembly controller **752**. The controller **2200** may be implemented as a general-purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a digital-signal-processor (DSP), circuits containing one or more processing components, circuitry for supporting a microprocessor, a group of processing components, or other suitable electronic processing components. According to an exemplary embodiment, the controller **2200** includes processing circuitry **2202** having a processor **2204** and memory **2206**. The processing circuitry **2202** may include an ASIC, one or more FPGAs, a DSP, circuits containing one or more processing components, circuitry for supporting a microprocessor, a group of processing components, or other suitable electronic processing components. In some embodiments, the processor **2204** is configured to execute computer code stored in the memory **2206** to facilitate the activities described herein. The memory **2206** may be any volatile or non-volatile computer-readable storage medium capable of storing data or computer code relating to the activities described herein. According to an exemplary embodiment, the memory **2206** includes computer code modules (e.g., executable code, object code, source code, script code, machine code, etc.) configured for execution by the processor **2204**.

[0170] Referring particularly to FIG. **20**, the form **2000** is shown, according to an exemplary embodiment. The form **2000** includes sidewalls **2002** which may rest upon a ground surface at the pour site **1910**. The sidewalls **2002** can define a space, area, volume, etc., shown as volume **2004** into which concrete or slurry material is to be poured. In some embodiments, the sensor(s) **1908** are configured to obtain data indicating the different positions, height, geometry, etc., of the sidewalls **2002**, or more generally, the form **2000**. In some embodiments, a top surface **2006** of the form **2000** includes a reflective material, a color coating, a reflective tape, etc. Advantageously, the top surface **2006** can be identified by the controller **2200** based on the sensor data obtained from sensors **1908** to identify boundaries or peripheries of the form **2000**. In some embodiments, the controller **2200** is configured to perform an image analysis or image processing technique to identify the top surfaces **2006**, edges, etc., and boundaries of the form **2000**, or the sidewalls **2102** of the form **2000**. The form **2000** can generally be a structure that stands upright from the ground surface to form a path, area, space, etc., where the concrete or slurry material can be poured. The form **2000** can have any shape (e.g., rectangular, irregular, etc.). The reflective tape on the top surface **2006** may be optional and, if used, can improve accuracy of the determination of the boundaries of the form **2000**.

[0171] Referring particularly to FIGS. **21** and **23**, the form **2000** can be provided as form **2100**. Form **2100** is shown as rectangular area including reinforcement **2106** (e.g., metal bars). Form **2100** includes sidewalls **2102** that define an inner volume or pour area therebetween. The controller **2200** can be configured to generate control signals for the actuators **1902**, the vehicle drive system **620**, and the drum assembly controller **752** to cause the chute **712** to follow a path **2108** while dispensing slurry material or concrete (e.g., into the form **2100**). The controller **2200** can also use user inputs obtained from the user device **2300** (e.g., a personal computer device, a tablet, etc.) to determine the path **2108** and to determine a rate at which the concrete or slurry material should be discharged.

[0172] Referring particularly to FIG. **23**, the user device **2300** can include a display screen **2302** (e.g., a touchscreen) for displaying the sensor data obtained from the sensor **1908**, or a graphical representation of the pour site **1910**. In some embodiments, the user or operator can provide different inputs (e.g., width, length, and depth) to define a pour volume of slurry material or concrete to be poured into the form **2100** or **2000**. For example, the user can provide a length **2308**, a width **2306**, and a depth **2304**. The length **2308**, width **2306**, and depth **2304** can be provided to the controller **2200** and can be used to determine the path **2108** for the chute **712**, and a rate at which the slurry material or concrete should be discharged as the chute **712** is operated to travel along the path **2108**. In some embodiments, the user device **2300** is configured to display a total

volume **2310** of slurry material to be dispensed or poured based on the length **2308**, the width **2306**, and the depth **2304** as provided by the user. In some embodiments, the user device **2300** is configured to display an estimated weight **2312** of the slurry material or concrete to be dispensed. In some embodiments, the user device **2300** is configured to display an available weight **2314** of slurry material or concrete present in the mixer drum **702**. If there is sufficient weight or amount of slurry material or concrete present in the mixer drum **702**, the user may select a start button **2316** to initiate a fully-autonomous or semi-autonomous pouring process. The user device **2300** may be locally positioned at the concrete mixer truck **600** (e.g., in a cab) or may be positioned remotely. For example, the user inputs received at the user device **2300** can be remotely provided to the controller **2200**.

[0173] Referring again to FIG. **22**, the controller **2200** may determine control signals for the actuators **1902**, the vehicle drive system **620**, and the drum assembly controller **752** to pour the slurry material based on the sensor data obtained from the sensors **1908**, and the user inputs received from the user device **2300**, while accounting for any of slump of the slurry material (e.g., based on a slump sensor), discharge speed of the slurry material, an amount of concrete in the mixer drum **702**, an amount of time that the concrete takes to transport along the chute **712**, an amount of time for the concrete to travel from the mixer drum **702** to a bottom of the chute **712**, an outdoor temperature, a temperature of the concrete or slurry material, or a truck angle. The controller **2200** can control the actuators **1902**, the vehicle drive system **620**, or the drum assembly controller **752** using sensor data that indicates speed of the mixer drum **702** and direction of rotation of the mixer drum **702**. In some embodiments, the controller **2200** is configured to generate control signals for the vehicle drive system **620** to cause the concrete mixer truck **600** to drive forwards or backwards as required. In some embodiments, the controller **2200** prompts a driver to pull forwards or backwards (e.g., by providing driver prompts to the driver via a human machine interface positioned in a cab of the concrete mixer truck **600**, the user device **2300**, or the vehicle drive system **620**) to achieve concrete pouring in a semi-autonomous manner. The controller **2200** can also provide feedback to the driver (e.g., real-time sensor data obtained from the sensor **1908**) as the concrete is poured. The controller **2200** can also prompt the driver or an operator to provide the user inputs shown in FIG. **23** (e.g., a spatial area, a length, width, depth for the spatial area, etc.).

[0174] Referring particularly to FIG. **24**, a process **2400** for automatically pouring concrete from a concrete mixer truck is shown, according to an exemplary embodiment. Process **2400** includes steps **2402-2410** and can be performed by the concrete mixer truck **600**, or electronic control system **1900** as described in greater detail above. In some embodiments, process **2400** is performed as step **1816** of process **1800**.

[0175] Process **2400** includes providing a concrete mixer truck including a sensor, a mixer drum, and a chute for dispensing slurry material (step **2402**), according to some embodiments. In some embodiments, the concrete mixer truck is the concrete mixer truck **600**. In some embodiments, the sensor is or includes the sensors **1908**. In some embodiments, the sensor is configured to obtain data of a jobsite, work area, pour area, zone, etc., proximate a discharge portion of the concrete mixer truck (e.g., where the slurry material will be dispensed from). In some embodiments, the sensor is a camera, a radar system, a LIDAR system, a scanning system, etc., configured to obtain sensor data indicating an environment, surface topology, etc., of the jobsite where the slurry material is to be dispensed. In some embodiments, the sensor data also indicates boundaries of one or more forms, structure, etc., positioned at the jobsite, into which the slurry material is to be poured.

[0176] Process **2400** includes obtaining sensor data from the sensor indicating the jobsite area and one or more forms at the jobsite area (step **2404**), according to some embodiments. In some embodiments, step **2404** is performed by the sensors **1908** and the controller **2200**. In some embodiments, the sensor data is image or camera data (e.g., obtained from a real-time video camera

that is directed towards the jobsite area).

[0177] Process **2400** includes identifying boundaries of the one or more forms based on the sensor data (step **2406**), according to some embodiments. In some embodiments, the one or more forms include a reflective material (e.g., a reflective tape) positioned along a top edge or surface of the one or more forms to facilitate identifying the boundaries of the one or more forms. In some embodiments, step **2406** is performed by the controller **2200**. In some embodiments, step **2406** includes performing an image analysis technique, or otherwise analyzing the sensor data (e.g., depending on a type of sensor that the sensor data originates from) to identify the boundaries of the one or more forms. In some embodiments, step **2406** includes presenting the identified boundaries to a user or operator (e.g., on the user device **2300**) and prompting or requesting a confirmation from the user. Step **2406** can also include allowing the user or operator to adjust the boundaries and provide a user input indicating that the automatically identified boundaries and/or manually updated boundaries are correct.

[0178] Process **2400** includes receiving a user input indicating a desired pour area including width, length, and depth (step **2408**), according to some embodiments. In some embodiments, the user input is received from an operator, technician, user, etc., at a user device (e.g., a tablet having a display screen) such as user device **2300**. In some embodiments, the user input includes a specific area of the one or more forms across which the slurry material should be poured. The user input can include the width, length, and depth of the specific area. In some embodiments, step **2408** is optional and process **2400** can be performed to deposit or pour the slurry material into an area within the boundaries identified in step **2406**.

[0179] Process **2400** includes operating the chute and the mixer drum of the concrete mixer truck to autonomously pour the slurry material according to the user input (step **2410**), according to some embodiments. In some embodiments, step **2410** includes operating or controlling the chute and the mixer drum of the concrete mixer truck to pour the slurry material across the specific area at the depth as indicated in the user input. In some embodiments, step **2410** is performed by the controller **2200** by providing control signals to any of the actuators **1902**, the vehicle drive system **620**, or the drum assembly controller **752**. In some embodiments, step **2410** can include adjusting an angle of the chute of the concrete mixer truck to follow a path across the specific area. The chute can be controlled through operation of one or more electric motors, actuators, engines, etc., to rotate the chute (e.g., the chute **712**) side to side and/or up and down. In some embodiments, step **2410** also includes operating a drive system of the concrete mixer truck to control the concrete mixer truck to pull forwards or backwards (e.g., to facilitate dispensing or pouring the slurry material along the path). In some embodiments, step **2410** includes prompting a driver to pull the concrete mixer truck forwards or rearwards (e.g., in a semi-autonomous implementation). In some embodiments, step **2410** includes controlling rotational speed of the mixer drum to pour the slurry material to the jobsite according to the depth specified in step **2408**.

[0180] The present disclosure contemplates methods, systems, and program products on any machine-readable media for accomplishing various operations. The embodiments of the present disclosure may be implemented using existing computer processors, or by a special purpose computer processor for an appropriate system, incorporated for this or another purpose, or by a hardwired system. Embodiments within the scope of the present disclosure include program products comprising machine-readable media for carrying or having machine-executable instructions or data structures stored thereon. Such machine-readable media can be any available media that can be accessed by a general purpose or special purpose computer or other machine with a processor. By way of example, such machine-readable media can comprise RAM, ROM, EPROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code in the form of machine-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer or other machine with a processor. When

information is transferred or provided over a network or another communications connection (either hardwired, wireless, or a combination of hardwired or wireless) to a machine, the machine properly views the connection as a machine-readable medium. Thus, any such connection is properly termed a machine-readable medium. Combinations of the above are also included within the scope of machine-readable media. Machine-executable instructions include, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or group of functions.

[0181] As utilized herein, the terms “approximately,” “about,” “substantially,” and similar terms are intended to have a broad meaning in harmony with the common and accepted usage by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described and claimed without restricting the scope of these features to the precise numerical ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of the subject matter described and claimed are considered to be within the scope of the invention as recited in the appended claims.

[0182] It should be noted that the terms “exemplary” and “example” as used herein to describe various embodiments is intended to indicate that such embodiments are possible examples, representations, and/or illustrations of possible embodiments (and such term is not intended to connote that such embodiments are necessarily extraordinary or superlative examples).

[0183] The terms “coupled,” “connected,” and the like, as used herein, mean the joining of two members directly or indirectly to one another. Such joining may be stationary (e.g., permanent, etc.) or moveable (e.g., removable, releasable, etc.). Such joining may be achieved with the two members or the two members and any additional intermediate members being integrally formed as a single unitary body with one another or with the two members or the two members and any additional intermediate members being attached to one another.

[0184] References herein to the positions of elements (e.g., “top,” “bottom,” “above,” “below,” “between,” etc.) are merely used to describe the orientation of various elements in the figures. It should be noted that the orientation of various elements may differ according to other exemplary embodiments, and that such variations are intended to be encompassed by the present disclosure.

[0185] Also, the term “or” is used in its inclusive sense (and not in its exclusive sense) so that when used, for example, to connect a list of elements, the term “or” means one, some, or all of the elements in the list. Conjunctive language such as the phrase “at least one of X, Y, and Z,” unless specifically stated otherwise, is otherwise understood with the context as used in general to convey that an item, term, etc. may be either X, Y, Z, X and Y, X and Z, Y and Z, or X, Y, and Z (i.e., any combination of X, Y, and Z). Thus, such conjunctive language is not generally intended to imply that certain embodiments require at least one of X, at least one of Y, and at least one of Z to each be present, unless otherwise indicated.

[0186] It is important to note that the construction and arrangement of the systems as shown in the exemplary embodiments is illustrative only. Although only a few embodiments of the present disclosure have been described in detail, those skilled in the art who review this disclosure will readily appreciate that many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.) without materially departing from the novel teachings and advantages of the subject matter recited. For example, elements shown as integrally formed may be constructed of multiple parts or elements. It should be noted that the elements and/or assemblies of the components described herein may be constructed from any of a wide variety of materials that provide sufficient strength or durability, in any of a wide variety of colors, textures, and combinations. Accordingly, all such modifications are intended to be included within the scope of the present inventions. Other substitutions, modifications, changes, and

omissions may be made in the design, operating conditions, and arrangement of the preferred and other exemplary embodiments without departing from scope of the present disclosure or from the spirit of the appended claims.

Claims

1. A system for tracking refuse collection vehicles, the system comprising: one or more memory devices having instructions stored thereon that, when executed by one or more processors, cause the one or more processors to perform operations comprising: receiving, from a user device operated by a customer of a refuse collection company, a user input indicating one or more parameters of a geofence; determining whether a refuse collection vehicle is within a virtual perimeter of the geofence based on cellular communications obtained via a cellular network from the refuse collection vehicle; and in response to the refuse collection vehicle transporting into the virtual perimeter of the geofence, transmitting a command to an access control system of the customer, the command initiating operation of an actuator of the access control system to open a door or gate to allow access to an area in which a waste receptacle is positioned.
2. The system of claim 1, wherein the operations further comprise: providing a notification to the customer in response to the refuse collection vehicle being within the geofence, the notification being provided as at least one of a text message, a push notification, an automated phone call, or an email.
3. The system of claim 2, wherein the notification further indicates a distance of the refuse collection vehicle from a central point of the geofence.
4. The system of claim 1, wherein the one or more parameters of the geofence comprise a central location for the geofence and a radius of the geofence.
5. The system of claim 1, the operations further comprising: presenting, via the user device, a map of the area of the waste receptacle; and receiving, via the user device, the user input defining one or more boundaries of the geofence within the map.
6. The system of claim 1, wherein the refuse collection vehicle comprises a global positioning system (GPS) transceiver, wherein a current location of the refuse collection vehicle is determined based on GPS data received by the one or more processors from the refuse collection vehicle.
7. The system of claim 1, wherein the refuse collection vehicle comprises a cellular network transceiver, wherein a current location of the refuse collection vehicle is triangulated based on signals from one or more cellular towers.
8. A method for tracking a refuse collection vehicle, the method comprising: receiving, from a user device operated by a customer of a refuse collection company, a user input indicating one or more parameters of a geofence; determining whether a refuse collection vehicle is within a virtual perimeter of the geofence based on cellular communications obtained via a cellular network from the refuse collection vehicle; and in response to the refuse collection vehicle transporting into the virtual perimeter of the geofence, transmitting a command to an access control system of the customer, the command initiating operation of an actuator of the access control system to open a door or gate to allow access to an area in which a waste receptacle is positioned.
9. The method of claim 8, further comprising: providing a notification to the customer in response to the refuse collection vehicle being within the geofence, the notification being provided as at least one of a text message, a push notification, an automated phone call, or an email.
10. The method of claim 9, wherein the notification further indicates a distance of the refuse collection vehicle from a central point of the geofence.
11. The method of claim 8, wherein the one or more parameters of the geofence comprise a central location for the geofence and a radius of the geofence.
12. The method of claim 8, further comprising: presenting, via the user device, a map of the area of the waste receptacle; and receiving, via the user device, the user input defining one or more

boundaries of the geofence within the map.

13. A device, comprising: a user interface; one or more processors; and one or more memory devices having instructions stored thereon that, when executed by the one or more processors, cause the one or more processors to: receive, from the user interface operated by a customer of a refuse collection company, a user input indicating one or more parameters of a geofence, the one or more parameters of the geofence configured to define a virtual perimeter around a geographical location, the virtual perimeter to trigger a notification responsive to a refuse collection vehicle crossing the virtual perimeter; transmit the user input to a remote server; receive, from the remote server, a notification that the refuse collection vehicle has crossed the virtual perimeter; and operate the user interface to notify the customer that the refuse collection vehicle has crossed the virtual perimeter.

14. The device of claim 13, wherein the notification comprises at least one of a text message, a push notification, an automated phonecall, or an email.

15. The device of claim 13, wherein the instructions further cause the one or more processors to: present, via the user interface, a map of an area based on a current location of the device; and receive, via the user interface, the user input defining the virtual perimeter of the geofence within the map.

16. The device of claim 13, wherein the one or more parameters of the geofence comprise a central location for the geofence and a radius of the geofence.

17. The device of claim 13, wherein the one or more parameters of the geofence comprise a central location for the geofence and a radius of the geofence.

18. The device of claim 13, wherein the notification further indicates a distance of the refuse collection vehicle from a central point of the geofence.

19. The device of claim 13, wherein notification is a first notification, wherein the instructions cause the one or more processors to: receive a second notification, the second notification indicating that the refuse collection vehicle has left the geofence; and operate the user interface to notify the customer that the refuse collection vehicle has left the geofence.

20. The device of claim 19, wherein the second notification comprises at least one of a text message, a push notification, an automated phonecall, or an email.
