

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411987
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Narayanswamy; Raman et al.

Systems, methods, and non-transitory computer-readable media for secure individual identification

Abstract

A privacy-enhancing system, method, and non-transitory computer-readable medium for securely identifying an individual over time without retaining sensitive biometric data. In one embodiment, the system includes a local identity server including an electronic processor, a communication interface, and a memory. The electronic processor is configured to initiate a personalization of a partner-specific identification vehicle that identifies the individual based at least in part on an individual global unique identifier associated with the individual, receive a request for a service from the individual via the communication interface, receive consent and registration information from the individual via the communication interface, generate an identity confirmation that confirms an identity of the individual, and output the identity confirmation via the communication interface. The individual global unique identifier is generated from information derived from the registration information and the individual global unique identifier is not indicative of personally identifiable information (PII) of the individual.

Inventors: Narayanswamy; Raman (Pelham, NH), Praszczalek; Przemek (Irvington, NY)

Applicant: MASTERCARD INTERNATIONAL INCORPORATED (Purchase, NY)

Family ID: 71071644

Assignee: MASTERCARD INTERNATIONAL INCORPORATED (Purchase, NY)

Appl. No.: 18/411919

Filed: January 12, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250148127 A1	May. 08, 2025

Related U.S. Application Data

continuation parent-doc US 18167822 20230210 US 11907404 child-doc US 18411919
continuation parent-doc US 17565653 20211230 US 11803662 20231031 child-doc US 18167822
continuation parent-doc US 16710665 20191211 US 11250161 20220215 child-doc US 17565653
us-provisional-application US 62779874 20181214

Publication Classification

Int. Cl.: **G06F21/62** (20130101); **G06F21/32** (20130101)

U.S. Cl.:

CPC **G06F21/6254** (20130101); **G06F21/32** (20130101);

Field of Classification Search

CPC: G06F (21/6254); G06F (21/32)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9536065	12/2016	Bouse et al.	N/A	N/A
10142333	12/2017	Griffin et al.	N/A	N/A
10257161	12/2018	Balaji et al.	N/A	N/A
10489737	12/2018	Racz	N/A	G06Q 90/20
10497014	12/2018	Karuvath et al.	N/A	N/A
10552176	12/2019	Putney et al.	N/A	N/A
10623451	12/2019	Rathod	N/A	H04L 51/04
10673617	12/2019	Antoniou et al.	N/A	N/A
10673847	12/2019	Lidsky	N/A	N/A
10694035	12/2019	Knuth et al.	N/A	N/A
10778842	12/2019	Knuth et al.	N/A	N/A
10897536	12/2020	Knuth	N/A	H04L 65/1069
11019204	12/2020	Knuth et al.	N/A	N/A
11115203	12/2020	Herder, III et al.	N/A	N/A
11196860	12/2020	Knuth	N/A	H04M 3/4365
11227060	12/2021	John et al.	N/A	N/A
11256791	12/2021	Douglas et al.	N/A	N/A
11308311	12/2021	Sandhan et al.	N/A	N/A
11329980	12/2021	Callahan et al.	N/A	N/A
11456865	12/2021	Wentz et al.	N/A	N/A
11570301	12/2022	Knuth	N/A	H04M 3/4365
11700249	12/2022	Lidsky	713/186	G06Q 20/3829
11756412	12/2022	Hatambeiki	N/A	N/A
11758041	12/2022	Murphy et al.	N/A	N/A
11800011	12/2022	Knuth et al.	N/A	N/A

11863698	12/2023	Aroxa	N/A	H04M 3/42059
12069203	12/2023	Murphy	N/A	H04M 3/42059
12149514	12/2023	Kravitz	N/A	G06Q 10/063
12256045	12/2024	Knuth	N/A	H04M 3/42068
12282457	12/2024	Williams	N/A	G06F 16/122
2015/0033305	12/2014	Shear et al.	N/A	N/A
2015/0059003	12/2014	Bouse	N/A	N/A
2017/0141920	12/2016	Herder, III et al.	N/A	N/A
2017/0142102	12/2016	Toyoshima et al.	N/A	N/A
2018/0007060	12/2017	Leblang et al.	N/A	N/A
2018/0218069	12/2017	Rege	N/A	G06F 16/24573
2018/0246983	12/2017	Rathod	N/A	G06F 16/972
2018/0309801	12/2017	Rathod	N/A	H04M 3/5175
2019/0005440	12/2018	Racz	N/A	G06Q 10/08
2019/0036917	12/2018	Sun	N/A	N/A
2019/0058581	12/2018	Wood	N/A	H04L 9/3239
2019/0089539	12/2018	Dupont	N/A	N/A
2019/0205889	12/2018	Cantrell et al.	N/A	N/A
2019/0220583	12/2018	Douglas et al.	N/A	N/A
2019/0238391	12/2018	Kakeno et al.	N/A	N/A
2019/0362129	12/2018	Sandhan et al.	N/A	N/A
2019/0363889	12/2018	Wang	N/A	N/A
2019/0377963	12/2018	Hamid et al.	N/A	N/A
2020/0019644	12/2019	Mazouchi et al.	N/A	N/A
2020/0028677	12/2019	Herder, III et al.	N/A	N/A
2020/0036707	12/2019	Callahan et al.	N/A	N/A
2020/0074059	12/2019	Beckett, Jr.	N/A	N/A
2020/0076798	12/2019	Lidsky	N/A	N/A
2020/0092102	12/2019	Wang	N/A	N/A
2020/0127826	12/2019	Ebrahimi et al.	N/A	N/A
2020/0145219	12/2019	Sebastian et al.	N/A	N/A
2020/0153960	12/2019	Knuth et al.	N/A	N/A
2020/0177598	12/2019	Storr	N/A	N/A
2020/0228321	12/2019	Krishnamacharya et al.	N/A	N/A
2020/0259955	12/2019	Knuth	N/A	H04L 65/1069
2020/0296091	12/2019	Lidsky	N/A	H04L 63/0861
2020/0382306	12/2019	Wang	N/A	N/A
2021/0144243	12/2020	Aroxa et al.	N/A	N/A
2021/0144246	12/2020	Murphy et al.	N/A	N/A
2021/0144521	12/2020	Saiffee et al.	N/A	N/A
2021/0184857	12/2020	Chen et al.	N/A	N/A
2021/0334570	12/2020	Hamid et al.	N/A	N/A
2021/0365539	12/2020	Fiske	N/A	N/A

2021/0406398	12/2020	Brannon et al.	N/A	N/A
2022/0058329	12/2021	Ricci	N/A	N/A
2022/0086274	12/2021	Knuth et al.	N/A	N/A
2022/0094790	12/2021	Knuth et al.	N/A	N/A
2022/0172603	12/2021	Hatambeiki	N/A	N/A
2022/0277064	12/2021	Streit	N/A	N/A
2023/0132554	12/2022	Kravitz et al.	N/A	N/A
2023/0353672	12/2022	Murphy	N/A	H03M 3/436
2023/0368653	12/2022	Hatambeiki	N/A	H04N 21/43615
2024/0281410	12/2023	Williams	N/A	G06F 16/164
2025/0063028	12/2024	Kravitz	N/A	H04L 63/0464

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
20170107409	12/2016	KR	N/A
2018001831	12/2017	WO	N/A
2018222211	12/2017	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion for Application No. PCT/US2019/064125 dated Mar. 25, 2020 (11 pages). cited by applicant
Intellectual Property India First Examination Report for application 202117026180, dated Dec. 29, 2022 (8 pages). cited by applicant

Primary Examiner: Gundry; Stephen T

Attorney, Agent or Firm: Michael Best & Friedrich LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. Non-Provisional application Ser. No. 18/167,822, filed Feb. 10, 2023, which is a continuation of U.S. Non-Provisional application Ser. No. 17/565,653, filed on Dec. 30, 2021, now U.S. Pat. No. 11,803,662, which is a continuation of U.S. Non-Provisional application Ser. No. 16/710,665, filed on Dec. 11, 2019, now U.S. Pat. No. 11,250,161, which claims the benefit of U.S. Provisional Application No. 62/779,874, filed on Dec. 14, 2018, the entire contents of which are hereby incorporated by reference.

FIELD OF THE INVENTION

(1) The present disclosure relates generally to secure identification. More specifically, the present disclosure relates privacy-enhancing systems, methods, and non-transitory computer-readable media.

BACKGROUND

(2) A partner-specific identification vehicle (or other form factor) issued to an individual by a partner uniquely identifies the individual to that partner. For example, the partner-specific identification vehicle may contain personally identifiable information (also referred to as “PII”) or the partner-specific identification vehicle may access the PII of the individual on the partner's

server. In particular, the partner-specific identification vehicle may store an individual's biometric data (one form of PII) or other detailed information that personally identifies the individual.

(3) However, with the increasing number of cyber-attacks on various entities, the risk of exposing the individual's PII is increasing. Once an individual's PII is obtained by a nefarious actor, the risk of an identity theft or fraud on the individual is high because the nefarious actor may use the individual's PII to pretend to be the individual.

SUMMARY

(4) The present disclosure relates to privacy-enhancing systems, methods, and non-transitory computer-readable media that provide for a partner-specific identification vehicle and identifies an individual without compromising or retaining any of the individual's PII. By not comprising any of the individual's PII, the systems, methods, and non-transitory computer-readable media of the present disclosure improve computer security because a nefarious actor cannot commit identity theft or fraud on the individual even after gaining access to information on the individual's partner-specific identification vehicle.

(5) One embodiment of the present disclosure includes a system for securely identifying an individual. The system includes a local identity server including a first electronic processor, a first communication interface, and a first memory. The first electronic processor is configured to initiate a personalization of a partner-specific identification vehicle that identifies the individual based at least in part on an individual global unique identifier associated with the individual, receive a request for a service from the individual via the first communication interface, receive consent and registration information from the individual via the first communication interface, generate an identity confirmation that confirms an identity of the individual, and output the identity confirmation via the first communication interface, wherein the individual global unique identifier is generated from information derived from the registration information, and wherein the individual global unique identifier is not indicative of personally identifiable information (PII) of the individual.

(6) Another embodiment of the present disclosure includes a method for securely identifying an individual. The method includes initiating, with a local identity server, a personalization of a partner-specific identification vehicle that identifies the individual based at least in part on an individual global unique identifier associated with the individual. The method includes receiving, with the local identity server, a request for a service from the individual via a network. The method includes receiving, with the local identity server, consent and registration information from the individual via the network. The method includes generating, with the local identity server, an identity confirmation that confirms an identity of the individual. The method also includes outputting, with the local identity server, the identity confirmation to the network. In this embodiment, the individual global unique identifier is generated from information derived from the registration information, and the individual global unique identifier is not indicative of personally identifiable information of the individual.

(7) Yet another embodiment of the present disclosure includes a non-transitory computer-readable medium comprising instructions that, when executed by an electronic processor, causes the electronic processor to perform a set of operations. The set of operations includes initiating a personalization of a partner-specific identification vehicle that identifies an individual based at least in part on an individual global unique identifier associated with the individual. The set of operations includes receiving a request for a service from the individual via a network. The set of operations includes receiving consent and registration information from the individual via the network. The set of operations includes generating an identity confirmation that confirms an identity of the individual. The set of operations also includes outputting the identity confirmation to the network. In this embodiment, the individual global unique identifier is generated from information derived from the registration information, and the individual global unique identifier is not indicative of personally identifiable information of the individual.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) FIG. 1 illustrates an example system for securely identifying an individual.
- (2) FIG. 2 illustrates a secure identity lifecycle with biometrics.
- (3) FIG. 3 illustrates a registration phase of the secure identity lifecycle with biometrics.
- (4) FIG. 4 illustrates an issuance phase of the secure identity lifecycle with biometrics.
- (5) FIG. 5 illustrates an identity authentication phase of the secure identity lifecycle with biometrics.
- (6) FIG. 6 illustrates a first identity management phase of the secure identity lifecycle with biometrics.
- (7) FIG. 7 illustrates a second identity management phase of the secure identity lifecycle with biometrics.
- (8) FIG. 8 illustrates a secure identity lifecycle without biometrics.
- (9) FIG. 9 illustrates a registration phase of the secure identity lifecycle without biometrics.
- (10) FIG. 10 illustrates an issuance phase of the secure identity lifecycle without biometrics.
- (11) FIG. 11 illustrates a token issuance process of the example system of FIG. 1.
- (12) FIG. 12 illustrates a successful token matching process of the example system of FIG. 1.
- (13) FIG. 13 illustrates an unsuccessful token matching process of the example system of FIG. 1.
- (14) FIG. 14 illustrates a second example system for securely identifying an individual.
- (15) FIG. 15 illustrates one example implementation of the identity network/switch of FIG. 14.
- (16) FIG. 16 illustrates another example implementation of the identity network/switch of FIG. 14.
- (17) FIG. 17 is a flowchart illustrating one example method for securely identifying an individual with the example system of FIG. 1.

DETAILED DESCRIPTION OF THE EMBODIMENTS

- (18) The following description is composed of five different sections. The first section (FIG. 1) highlights an example system for securely identifying an individual. The second section (FIGS. 2-7) highlights the issuance of an identity vehicle using biometrics with no PII revealed by identity vehicle or otherwise collected using the example system of FIG. 1. The third section (FIGS. 8-10) highlights where the issuance of an identity vehicle happens in an environment where there are no biometrics or no biometrics yet, so detailed information is collected instead of using the biometrics of the example system of FIG. 1. The fourth section (FIGS. 11-13) highlights a process for token issuance and matching as part of the process that uses biometrics and the example system of FIG. 1. The fifth section (FIGS. 14-16) highlights an identity network/switch in the second example system of FIG. 14. The last section (FIG. 17) highlights a method for securely identifying an individual with the example system of FIG. 1.
- (19) FIG. 1 illustrates an example system **100** for securely identifying an individual. In the example of FIG. 1, the system **100** includes a local identity server **104**, a global identity server **118**, a local partner server **130**, a partner computer **135**, an individual **140**, and a network **160**.
- (20) The local identity server **104** and the global identity server **118** may be owned by, or operated by or on behalf of, an administrator. The global identity server **118** may also be implemented by one or more networked computer servers.
- (21) The local identity server **104** includes an electronic processor **106**, a communication interface **108**, and a memory **110**. The electronic processor **106** is communicatively coupled to the communication interface **108** and the memory **110**. The electronic processor **106** is a microprocessor or another suitable processing device. The communication interface **108** may be implemented as one or both of a wired network interface and a wireless network interface. The memory **110** is one or more of volatile memory (e.g., RAM) and non-volatile memory (e.g., ROM, FLASH, magnetic media, optical media, et cetera). In some examples, the memory **110** is also a

non-transitory computer-readable medium. Although shown within the local identity server **104**, memory **110** may be, at least in part, implemented as network storage that is external to the local identity server **104** and accessed via the communication interface **108**. For example, all or part of memory **110** may be housed on the “cloud.”

(22) The global identity server **118** includes an electronic processor **120**, a communication interface **122**, and a memory **124**. The electronic processor **120** is communicatively coupled to the communication interface **122** and the memory **124**. The electronic processor **120** is a microprocessor or another suitable processing device. The communication interface **122** may be implemented as one or both of a wired network interface and a wireless network interface. The memory **124** is one or more of volatile memory (e.g., RAM) and non-volatile memory (e.g., ROM, FLASH, magnetic media, optical media, et cetera). In some examples, the memory **124** is also a non-transitory computer-readable medium. The memory **124** may be, at least in part, implemented as network storage that is external to the global identity server **118** and accessed via the communication interface **122**. For example, all or part of memory **124** may be housed on the “cloud.”

(23) The identity lifecycle engine **112** may be stored within a transitory or non-transitory portion of the memory **110**. The identity lifecycle engine **112** includes machine readable instructions that are executed by processor **106** to perform the functionality of the local identity server **104** as described below with respect to FIGS. 2-13.

(24) The memory **110** may include a database **114** for storing information about individuals. The database **114** may be an RDF database, i.e., employ the Resource Description Framework. Alternatively, the database **114** may be another suitable database with features similar to the features of the Resource Description Framework. The database **114** may include a plurality of records. Each record may be associated with and contain personal information about one individual. For example, in the illustrated embodiment, record **116** may be associated with the individual **1440**, and other N records may be respectively associated with one of N other individuals (not expressly shown in FIG. 1).

(25) The local partner server **130** is in data communication with the partner computer **135**. The partner computer **135** may be web-compatible mobile computer, such as an Apple laptop, an Android tablet, a Google smart phone, etc. Alternately, or in addition, the partner computer **135** may be a desktop computer. The partner computer **135** includes an electronic processor in communication with memory. In an embodiment, the electronic processor of the computer **135** is also in communication with a biometric scanner and a communication interface. The electronic processor is a microprocessor or another suitable processing device, the memory is one or more of volatile memory and non-volatile memory, and the biometric scanner is one or more biometric scanning devices (e.g., a device that scans fingerprints, facial features, irises, handwriting, et cetera) now known or subsequently developed. The communication interface may be a wireless or wired network interface.

(26) An application, which contains software instructions implemented by the electronic processor of the partner computer **135** to perform the functions of the partner computer **135** as described herein, is stored within a transitory or a non-transitory portion of the memory. The application may have a graphical user interface that facilitates interaction between the individual **140** and the local partner server **130**.

(27) The partner computer **135** may include or be in communication with a point of sale system (POS), e.g., a mobile POS system (such as a mobile card reader). As discussed herein, the partner computer **135** may use the mobile POS system to, among other things, read a partner-specific identification asset (not shown and considered to be part of the block “individual **140**”) associated with the individual **140** to verify the identity of the individual **140**.

(28) The partner computer **135** may communicate with the local partner server **130** over network **160**. The network **160** is preferably (but not necessarily) a wireless network, such as a wireless

personal area network, local area network, or other suitable network. The local partner server **130** may include an Application Programming Interface (API) that allows the individual **140** to communicate with the local partner server **130** via the partner computer **135**. The local partner server **130** may directly communicate with the local identity server **104** or indirectly communicate over network **160**.

(29) The local partner server **130** has an electronic processor in communication with memory. The electronic processor is a microprocessor or another suitable processing device, and the memory is one or more of volatile memory and non-volatile memory (including memory remote from the partner computer **135** and accessible thereby over a network).

(30) In an embodiment, the memory may include a database and software. The database of the local partner server **130** may include information about individual **140** and other individuals, as set forth herein. The software of the local partner server **130** may facilitate interaction between the local partner server **130** and individuals (e.g., the individual **140**) and allow for the local partner server **130** to track the interactions as described in greater detail below.

(31) The local identity server **104** may likewise communicate with partner servers other than the local partner server **130**. The term “partner”, as used herein, encompasses any other organizations engaging with individuals, including but not limited to non-governmental organizations and other charitable institutions (including governmental organizations). The term “individual”, as used herein, encompasses a person (or household) that seeks to interact with an organization or entity, including but not limited to seeking assistance (e.g., a refugee in a refugee camp, a person who receives aid, etc.). The workings of the local identity server **104** and the local partner server **130** will now be described in additional detail with FIGS. 2-13.

(32) With respect to FIGS. 2-7, the system **100** enrolls the individual **140** using biometrics, issues a partner-specific identification asset, and identifies the individual **140** with the partner-specific identification asset and without exposing or compromising any PII regarding the individual **140**. With respect to FIGS. 8-10, the system **100** enrolls the individual **140** using detailed information instead of biometrics, issues a partner-specific identification asset, and identifies the individual **140** with the partner-specific identification asset and without exposing or compromising any PII regarding the individual **140**. Lastly, with respect to FIGS. 11-13, the system **100** issues a token, verifies that the individual **140** is the cardholder with an on-card biometric verification, and confirms a relationship between the individual **140** and a partner based at least in part on the token and without exposing or compromising any PII regarding the individual **140**.

(33) FIG. 2 illustrates a secure identity lifecycle **200** with biometrics. In the example of FIG. 2, the individual **140** requests enrollment in a program or service offered by a partner via the local partner server **130**. For example, the individual **140** may visit the partner to access the partner computer **135** and enroll.

(34) The local partner server **130** captures the registration of the individual **140** and outputs the registration information to the local identity server **104**. The individual **140** also indicates consent to the local partner server **130** and/or the local identity server **104**.

(35) As part of registering, the individual **140** provides biometric data associated with the individual **140**. For example, the individual undergoes a facial scan, a fingerprint scan, an iris scan, or other suitable biometric scan. The biometric data associated with the individual **140** is included in the registration information that is output by the local partner server **130** to the local identity server **104**.

(36) The local identity server **104** captures the biometric data (including images) and generates a biometric template based on the biometric data. After generating the biometric template, the local identity server **104** generates a biometrically-derived hash that includes no biometric data (hereinafter referred to as “biometric hash”) and clears the biometric image, the biometric template, and any biometric data associated with the individual **140** from temporary memory. That is, once the biometric template is generated, the biometric template temporarily persists in the short-

term/cache memory until a successful creation of a hash, which triggers a memory flush. For example, the local identity server **104** may use the Trust Stamp™ technology to generate the biometric hash from the biometric template.

(37) Although not shown in FIG. 2, if the biometric hash is unable to be generated from the biometric template, the local identity server **104** either clears the biometric template from temporary memory and attempts to generate another biometric template from the biometric data or clears both the biometric template and the biometric data from the temporary memory and requests additional biometric data from the individual **140**.

(38) After successfully generating the biometric hash, the local identity server **104** performs de-duplication using predictive matching to determine whether the biometric hash matches any existing biometric hashes stored in the database **114**. For example, the local identity server **104** may use the Trust Stamp™ technology to perform predictive matching to determine whether the biometric hash matches any existing biometric hashes stored in the database **114**. After checking against existing biometric hashes in the database **114**, the local identity server **104** either generates a new global unique identifier (GUID) associated with the individual **140** and stores the GUID and the biometric hash in the database **114** or simply stores the biometric hash to an existing GUID associated with the individual **140**.

(39) After storing the biometric hash, the local identity server **104** generates a token based on the GUID of the individual **140** and the GUID of the partner associated with the local partner server **130**. Upon generating the token, the local identity server **104** stores the identification status of the individual **140**, the consent of the individual **140**, the token associated with the individual **140**, and the GUID associated with the individual **140** in the database **114**. The local identity server **104** also shares some of the identity elements with the partner.

(40) After storing all of the information associated with the individual **140** in the database **114**, the local identity server **104** generates a personalization packet (e.g., the biometric hash, the GUID, and/or the token) of the individual **140** and initiates the personalization of an identification asset (e.g., an near field communication (NFC) identification card) as well as the delivery of the identification asset to the partner. The above-described enrollment between the individual **140**, the local partner server **130**, and the local identity server **104** is an offline enrollment.

(41) FIG. 3 illustrates a registration phase **300** of the secure identity lifecycle **200** with biometrics of FIG. 2. In the example of FIG. 3, the individual **140** requests enrollment in a program (e.g., a livelihoods program) or service offered by a partner via the local partner server **130**. For example, the individual **140** may visit the partner to access the partner computer **135** and enroll.

(42) The local partner server **130** captures the registration of the individual **140** and outputs the registration information to the local identity server **104**. The individual **140** also indicates consent to the local partner server **130** and/or the local identity server **104**.

(43) As part of registering, the individual **140** provides biometric data associated with the individual **140**. For example, the individual undergoes a facial scan, a fingerprint scan, an iris scan, or other suitable biometric scan. The biometric data associated with the individual **140** is included in the registration information that is output by the local partner server **130** to the local identity server **104**.

(44) The local identity server **104** captures the biometric data (including images) and generates a biometric template based on the biometric data. After generating the biometric template, the local identity server **104** generates a biometric hash and clears the biometric template, the biometric image, and any biometric data associated with the individual **140** from temporary memory. Although not shown in FIG. 2, if the biometric hash is unable to be generated from the biometric template, the local identity server **104** either clears the biometric template from temporary memory and attempts to generate another biometric template from the biometric data or clears both the biometric template and the biometric data from the temporary memory and requests additional biometric data from the individual **140**.

(45) After successfully generating the biometric hash, the local identity server **104** performs de-duplication using predictive matching to determine whether the biometric hash matches any existing biometric hash records stored in the database **114**. Upon determining that the biometric hash matches an existing record, the local identity server **104** appends the generated biometric hash to the record and outputs a confirmation of a successful biometric capture to the individual **140** via the local partner server **130**.

(46) Additionally, the identification status of the individual **140**, the consent of the individual **140** are stored in the database **114**. The local identity server **104** also shares some of the identity elements with the partner.

(47) FIG. 4 illustrates an issuance phase **400** of the secure identity lifecycle **200** with biometrics of FIG. 2. In the example of FIG. 4, after successfully generating the biometric hash, the local identity server **104** performs local de-duplication using predictive matching to determine whether the biometric hash matches any existing biometric hashes stored in the database **114**. After checking against existing biometric hashes in the database **114**, the local identity server **104** either generates a new global unique identifier (GUID) associated with the individual **140** and stores the GUID and the biometric hash in the database **114** or simply stores the biometric hash to an existing GUID associated with the individual **140**.

(48) After storing the biometric hash, the local identity server **104** generates a token based on the GUID of the individual **140** and the GUID of the partner associated with the local partner server **130**. Upon generating the token, the local identity server **104** stores the identification status of the individual **140**, the consent of the individual **140**, the token associated with the individual **140**, and the GUID associated with the individual **140** in the database **114**.

(49) After storing all of the information associated with the individual **140** in the database **114**, the local identity server **104** may transmit the biometric hash to the global identity server **118** via the network **160**. In other words, when “online,” the local identity server **104** send biometric hashes to the global identity server **118**.

(50) After receiving the biometric hash from the local identity server **104**, the global identity server **118** performs global de-duplication using predictive matching to determine whether the biometric hash matches any existing biometric hashes stored in the global database **126**. After checking against existing biometric hashes in the global database **126**, the global identity server **118** stores the biometric hash associated with the individual **140**.

(51) After storing all of the information associated with the individual **140** in the database **114**, the local identity server **104** generates a personalization packet (e.g., the biometric has, the GUID, and/or the token) of the individual **140** and initiates the personalization of an identification asset (e.g., an near field communication (NFC) identification card) as well as the delivery of the identification asset to the partner.

(52) FIG. 5 illustrates an identity authentication phase of the secure identity lifecycle with biometrics of FIG. 2. In the example of FIG. 5, the individual **140** uses the identification asset and ID profile that was created with the personalization packet described above in FIG. 4 at the partner's premise. The individual **140** also submits new biometric data using a previous biometric modality. The local partner server **130** passes the information of the individual **140** through to the local identity server **104**.

(53) After receiving the ID profile containing a first biometric hash and the new biometric data, the local identity server **104** looks up any records corresponding to the individual **140**. The local identity server **104** also generates a biometric template from the new biometric data and generates a second biometric hash from the biometric template. The local identity server **104** authenticates the identity of the individual **140** by performing de-duplication between the first biometric hash and the second biometric hash.

(54) If a match between the first biometric hash and the second biometric hash is at or above a threshold level (e.g., 90% similarity), the hashes are considered to match. If a match between the

first biometric hash and the second biometric hash is below a threshold level (e.g., 90% similarity), the hashes are considered to not match. The threshold is not a static level, but rather a dynamic level. For example, the age of the individual **140** may be considered when applying the threshold level to compensate for any growth that has occurred since the first biometric hash was generated. (55) After determining there is a match between the first biometric hash and the second biometric hash, the local identity server **104** authenticates the session with the individual **140**. The local server **104** also stores the successful authentication in the record **116** associated with the individual **140** and outputs the successful authentication to the local partner server **130**. The local partner server **130** may store the successful authentication in its own database.

(56) FIG. **6** illustrates a first identity management phase **600** of the secure identity lifecycle with biometrics of FIG. **2**. In the example of FIG. **6**, the individual **140** uses the identification asset and ID profile that was created with the personalization packet described above in FIG. **4** at the partner. The individual **140** submits new biometric data using a new biometric modality (e.g., an iris scan) as well as providing new consent to the new biometric data.

(57) The local identity server **104** generates a biometric template from the new biometric data and generates a second biometric hash (e.g., an iris-based hash) from the biometric template. Additionally, after receiving the ID profile containing a first biometric hash (e.g., a fingerprints-based hash) and the new biometric data, the local identity server **104** looks up any records corresponding to the individual **140**. For example, the local identity server **104** looks up whether the individual **140** has any existing biometric hashes. Upon determining there are existing biometric hashes, the local identity server **104** determines the types of the existing biometric hashes. The local identity server **104** maintains the identity of the individual **140** by performing de-duplication between the first biometric hash and the second biometric hash to detect the new biometric hash modality.

(58) FIG. **7** illustrates a second identity management phase **700** of the secure identity lifecycle with biometrics of FIG. **2**. In the example of FIG. **7**, the local identity server **104** receives information regarding the use of the identification asset and ID profile that was created with the personalization packet described above in FIG. **4** at the partner. The local identity server **104** also receives new biometric data using a new biometric modality (e.g., an iris scan).

(59) The local identity server **104** generates a biometric template from the new biometric data and generates a second biometric hash (e.g., an iris-based hash) from the biometric template. Additionally, after receiving the ID profile containing a first biometric hash (e.g., a fingerprints-based hash) and the new biometric data, the local identity server **104** looks up any records corresponding to the individual **140**. For example, the local identity server **104** looks up whether the individual **140** has any existing biometric hashes (e.g., biometric hashes associated with other partners). Upon determining there are existing biometric hashes, the local identity server **104** determines the types of the existing biometric hashes. The local identity server **104** maintains the identity of the individual **140** by performing de-duplication between the first biometric hash and the second biometric hash to detect the new biometric hash modality. After detecting there is a new biometric hash modality, the local identity server **104** stores the second biometric hash in the record **116** associated with the individual **140** and updates the identification asset to include the second biometric hash.

(60) FIG. **8** illustrates a secure identity lifecycle **800** without biometrics. In the example of FIG. **8**, the individual **140** requests enrollment in a program or service offered by a partner via the local partner server **130**. For example, the individual **140** may visit the partner to access the partner computer **135** and enroll.

(61) The local partner server **130** captures the registration of the individual **140** and outputs the registration information to the local identity server **104**. The individual **140** also indicates consent to the local partner server **130** and/or the local identity server **104**.

(62) As part of registering, the individual **140** provides detailed information associated with the

individual **140**. The detailed information associated with the individual **140** is included in the registration information that is output by the local partner server **130** to the local identity server **104**.

(63) The local identity server **104** performs de-duplication on data fields and generates an individual global unique identifier (GUID) associated with the individual **140**. The local identity server **104** also generates a unique identifier (e.g., a web ID including the public individual GUID) that is public. After generating the unique identifier, the local identity server **104** generates a personal identification number (PIN) and username and establishes a user data store associated with the individual **140** in the database **114**.

(64) After establishing the user data store, the local identity server **104** generates a token based on the GUID of the individual **140** and the GUID of the partner associated with the local partner server **130**. Upon generating the token, the local identity server **104** stores the unique identifier of the individual **140**, the identification status of the individual **140**, the consent of the individual **140**, the token associated with the individual **140**, and the GUID associated with the individual **140** in the database **114**. The local identity server **104** also shares some of the identity elements with the local partner server **130**.

(65) After storing all of the information associated with the individual **140** in the database **114**, the local identity server **104** generates a personalization packet (e.g., the biometric hash, the GUID, and/or the token) of the individual **140** and initiates the personalization of an identification asset (e.g., an near field communication (NFC) identification card) as well as the delivery of the identification asset to the partner. The above-described enrollment between the individual **140**, the local partner server **130**, and the local identity server **104** is an offline enrollment.

(66) FIG. **9** illustrates a registration phase **900** of the secure identity lifecycle **800** without biometrics. In the example of FIG. **9**, the individual **140** requests enrollment in a program or service offered by a partner via the local partner server **130**. For example, the individual **140** may visit the partner to access the partner computer **135** and enroll.

(67) The local partner server **130** captures the registration of the individual **140** and outputs the registration information to the local identity server **104**. The individual **140** also indicates consent to the local partner server **130** and/or the local identity server **104**.

(68) As part of registering, the individual **140** provides detailed information associated with the individual **140**. The detailed information associated with the individual **140** is included in the registration information that is output by the local partner server **130** to the local identity server **104**.

(69) The local identity server **104** performs de-duplication on data fields to determine whether the individual is already enrolled. Upon determining that the individual is not enrolled, the local identity server **104** generates a user global unique identifier (GUID) associated with the individual **140**. The local identity server **104** also generates a unique identity profile (e.g., a web ID) that is public. After generating the unique identity profile, the local identity server **104** confirms the successful creation of the ID profile. Upon determining that the individual is enrolled, the local identity server **104** updates or appends data elements in an existing ID profile that is associated with the individual **140**. After updating the ID profile, the local identity server **104** confirms the successful update of the ID profile.

(70) FIG. **10** illustrates an issuance phase **1000** of the secure identity lifecycle **800** without biometrics. In the example of FIG. **10**, the local identity server **104** performs de-duplication on data fields and generates two user global unique identifier (GUID) associated with the individual **140**. One of the two individual GUIDs is public and the other of the two individual GUIDs is private.

(71) The local identity server **104** also generates a unique identifier (e.g., a Web ID, including the public individual GUID) that is public. After generating the unique identifier, the local identity server **104** generates a personal identification number (PIN) and username and establishes a user data store associated with the individual **140** in the database **114**.

(72) After establishing the user data store, the local identity server **104** generates a token based on the private GUID of the individual **140** and the GUID of the partner associated with the local partner server **130**. Upon generating the token, the local identity server **104** stores the unique identifier of the individual **140**, the identification status of the individual **140**, the consent of the individual **140**, the token associated with the individual **140**, and the private GUID associated with the individual **140** in the database **114**. The local identity server **104** also shares some of the identity elements with the local partner server **130**.

(73) After storing all of the information associated with the individual **140** in the database **114**, the local identity server **104** generates a personalization packet (e.g., the unique identifier, the GUID, and/or the token) of the individual **140** and initiates the personalization of an identification asset (e.g., an near field communication (NFC) identification card) as well as the delivery of the identification asset to the partner.

(74) FIG. **11** illustrates a token issuance process **1100** of the example system of FIG. **1**. In the example of FIG. **11**, the local identity server **104** performs local de-duplication of information from the individual **140** and generates a global unique identifier (GUID) or “G” that is private (i.e., based on detailed information provided by the individual **140**) or biometrically derived (i.e., based on biometric data provided by the individual **140**).

(75) The local identity server **104** generates a token “T” by combining the GUID “G” with the partner global unique identifier “P” that is private. The local identity server **104** stores the identification status, the token “T”, the GUID “G”, and the partner GUID “P” in the database **114**. The local identity server **104** may also share some of the ID data elements with the local partner server **130** (e.g., the partner GUID “P” and the token “T”).

(76) After storing all of the information associated with the individual **140** in the database **114**, the local identity server **104** generates a personalization packet (e.g., the GUID and/or the token) of the individual **140** and initiates the personalization of an identification asset (e.g., an near field communication (NFC) identification card) as well as the delivery of the identification asset to the partner and/or the individual.

(77) FIG. **12** illustrates a successful token matching process **1200** of the example system of FIG. **1**. In the example of FIG. **12**, the individual **140** brings the identification asset (e.g., the NFC smartcard) to the partner and the partner computer. The local identity server **104** confirms an authentication of the biometric hash on the card based an on-card biometric match (e.g., the authentication phase **500** of FIG. **5**).

(78) After confirming an on-card biometric match, the local identity server **104** retrieves the ID profile and the biometric hash stored on the identification asset via the local partner server **130** and the partner computer **135**. Specifically, the local identity server **104** retrieves the individual GUID stored on the identification asset.

(79) Additionally, after confirming the on-card biometric match, the local identity server **104** retrieves the token associated with the individual **140** and the partner GUID from the local partner server **130**. The local identity server **104** uses the individual GUID “G” and the partner GUID “P” to generate a new context token. The local identity server **104** then uses a matching technique to compare the new content token to the token retrieved from the local partner server **130**.

(80) Upon determining the new context token matches the token retrieved from the local partner server **130**, the local identity server **104** captures the successful relationship match and captures the identification asset interaction. The local identity server **104** also authenticates the session and outputs confirmation of the authenticated session to the local partner sever **130**. Upon receiving confirmation, the local partner server **130** clears the individual **140** to proceed.

(81) FIG. **13** illustrates an unsuccessful token matching process **1300** of the example system of FIG. **1**. In the example of FIG. **13**, the individual **140** brings the identification asset (e.g., the NFC smartcard) to the partner and the partner computer. The local identity server **104** confirms an authentication of the biometric hash on the card based an on-card biometric match (e.g., the

authentication phase **500** of FIG. 5).

(82) After confirming an on-card biometric match, the local identity server **104** retrieves the ID profile and the biometric hash stored on the identification asset via the local partner server **130** and the partner computer **135**. Specifically, the local identity server **104** retrieves the individual GUID stored on the identification asset.

(83) Additionally, after confirming the on-card biometric match, the local identity server **104** retrieves the token associated with the individual **140** and the partner GUID from the local partner server **130**. The local identity server **104** uses the individual GUID “G” and the partner GUID “P” to generate a new context token. The local identity server **104** then uses predictive matching to compare the new content token to the token retrieved from the local partner server **130**.

(84) Upon determining the new context token does not match the token retrieved from the local partner server **130**, the local identity server **104** captures the unsuccessful relationship match and the unauthorized relationship attempt (whether friendly or unfriendly). The local identity server **104** also rejects the session and outputs an indication that the user-partner unique relation is not confirmed to the local partner sever **130**. Upon receiving the indication, the local partner server **130** does not clear the individual **140** to proceed. A number of possible exceptions processing actions may be designed and initiated at that stage to guide a response to this event. For example, the exceptions processing actions may include one or more of rejecting the authentication attempt, creating a record of a potential fraud attempt, sending the unmatched token to the global data store for “matching” and flagging profile of individual associated with the unmatched token, performing an alternate method of authentication, or other suitable exceptions processing action.

(85) As illustrated in FIG. 13, in some examples, the local identity server **104** searches the database **114** to find a token that matches the new context token. Upon determining a match between a token in the database **114** and the new context token, the local identity server **104** determines an individual that is linked to the new context token and flags that relationship for possible review.

(86) Thus, as has been described, the system **100** may, among other things, allow the individual **140** to be securely identified without compromising the PII of the individual **140**.

(87) FIG. 14 illustrates a second example system **1400** for securely identifying an individual. In the example of FIG. 14, the system **1400** includes an identity (ID) network/switch **1402** as part of a local identity server **1404**, a plurality of local partner servers **1406A-1406N**, legacy servers **1408**, a global identity server **1418**, and an individual **1440**.

(88) In the example of FIG. 14, the identity (ID) network/switch **1402** interconnects the biometric services of the local identity server **1404**, the legacy servers **1408**, and the global identity server **1418**. In some examples, the local identity server **1404** is the same or similar to the local identity server **104**; each local partner server of the plurality of local partner servers **1406A-1406N** is the same or similar to the local partner server **130**; and the global identity server **1418** is the same or similar to the global identity server **118**, respectively, as described above in FIGS. 1-13.

Consequently, the redundant description of the local identity server **1404**, the plurality of local partner servers **1406A-1406N**, and the global identity server **1418** is not repeated herein.

(89) As illustrated in FIG. 14, each of the plurality of local partner servers **1406A-1406N** includes an agency application with an identity software development kit (ID SDK). The ID SDK is a program that differentiates between standardized biometric templates associated with the local identity server **1404** and/or the global identity server **1418**, and proprietary biometric templates associated with one or more of the legacy servers **1408**. For example, when the individual **1440** requests a service from the local partner server **1406A** and provides a standardized biometric template from an individual resource (e.g., an identification vehicle), the local partner server **1406A** routes the standardized biometric template to the global identity server **1418** via the local identity server **1404**.

(90) However, when the individual **1440** requests a service from the local partner server **1406A** and provides a proprietary biometric template from the individual resource, the local partner server

1406A routes the proprietary biometric template to one or more of the legacy servers **1408** via the local identity server **1404**. Additionally, in some examples, when the individual **1440** requests a service from the local partner server **1406A** and provides a proprietary biometric template from the individual resource, the local partner server **1406A** may also route the proprietary biometric template to one or more of the legacy servers **1408** and the global identity server **1418** via the local identity server **1404**. In other words, the identity network/switch **1402** is a network that interconnects various databases to receive identity information from the individual **1440** and one or more databases are targeted based on the type of identity information that is received from the individual **1440**.

(91) In the example of FIG. **14**, the identity information from the individual **1440** may be provided to the global identity server **1418**, one or more of the legacy servers **1408**, or both without exposing any personally identifiable information (PII). Consequently, the ID network/switch **1402** allows the legacy servers **1408** to interoperate with the local identity server **1404**, the global identity server **1418**, and the plurality of local partner servers **1406A-1406N** without needing to expose any PII that may exist in the legacy servers **1408**. In some examples, the legacy servers **1408** may include existing government databases (e.g., a national identity database), financial databases, telecommunication databases, or other suitable legacy databases that include personally identifiable information (PII).

(92) Additionally, as illustrated in FIG. **14**, the global identity server **1418** includes a biometric hash translation service. However, in other examples, the local identity server **1404** may include the biometric hash translation service. The biometric hash translation service translates the proprietary biometric template from either the individual **1440** via the ID network/switch **1402** or the legacy servers **1408** to a biometric hash. The biometric hash may then be stored in the database **126** of the global identity server **1418**. Similarly, the biometric hash may also be stored in the database **114** of the local identity server **1404**. In other words, the biometric hash translation service in combination with the ID network/switch **1402** increases the number of biometric hashes that are associated with the individual **1440** by converting the proprietary biometric templates that are sent to and associated with the legacy servers **1408** to biometric hashes. The biometric hashes that are converted from the proprietary biometric templates may then be stored locally and/or globally.

(93) FIG. **15** illustrates one example implementation of the identity network/switch **1402** of FIG. **14**. In the example of FIG. **15**, the individual **1440** requests enrollment in a program or service offered by a partner via the local partner server **1406A**. For example, the individual **1440** may visit the partner to access the partner computer **135A** and enroll.

(94) The local partner server **1406A** captures the registration of the individual **1440** from the partner computer **135A** and outputs the registration information to the local identity server **1404A**. The individual **1440** also indicates consent to the local partner server **1406A** and/or the local identity server **1404A**.

(95) As part of registering, the individual **1440** provides biometric data associated with the individual **1440**. For example, the individual undergoes a facial scan, a fingerprint scan, an iris scan, or other suitable biometric scan. The biometric data associated with the individual **1440** is transformed by the local partner server **1406A** into a standardized biometric template, which is then associated with the local partner server **1406A**. The standardized biometric template and the registration information is output by the local partner server **1406A** to the local identity server **1404A**.

(96) The local identity server **1404A** captures the standardized biometric template and the registration information. The local identity server **1404A** generates a biometric hash based on the standardized biometric template and clears both the standardized biometric template and any biometric data associated with the individual **1440** from temporary memory. For example, the local identity server **1404A** may use the Trust Stamp™ technology to generate the biometric hash from the standardized biometric template created by the local partner server **1406A**.

(97) Although not shown in FIG. 15, if the biometric hash is unable to be generated from the standardized biometric template, the local identity server **1404A** clears the standardized biometric template from temporary memory and requests another standardized biometric template from the individual **1440** via the local partner server **1406A**.

(98) After successfully generating the biometric hash, the local identity server **1404A** performs de-duplication using predictive matching to determine whether the biometric hash matches any existing biometric hashes stored in the database **114**. For example, the local identity server **1404A** may use the Trust Stamp™ technology to perform predictive matching to determine whether the biometric hash matches any existing biometric hashes stored in the database **114**. After checking against existing biometric hashes in the database **114**, the local identity server **1404A** either generates a new global unique identifier (GUID) associated with the individual **1440** and stores the GUID and the biometric hash in the database **114** or simply stores the biometric hash to an existing GUID associated with the individual **1440**.

(99) After storing all of the information associated with the individual **1440** in the database **114**, the local identity server **1404A** may transmit the biometric hash to the global identity server **1418** via the network **160**. In other words, when “online,” the local identity server **1404A** sends biometric hashes to the global identity server **1418**.

(100) After receiving the biometric hash from the local identity server **1404A**, the global identity server **1418** performs global de-duplication using predictive matching to determine whether the biometric hash matches any existing biometric hashes stored in the global database **126**. After checking against existing biometric hashes in the global database **126**, the global identity server **1418** stores the biometric hash associated with the individual **1440**.

(101) Additionally, in the example of FIG. 15, the individual **1440** requests enrollment in a program or service offered by a second partner via the local partner server **1406B**. For example, the individual **1440** may visit the second partner to access the partner computer **135B** and enroll.

(102) The local partner server **1406B** captures the registration of the individual **1440** and outputs the registration information to the local identity server **1404B**. The individual **1440** also indicates consent to the local partner server **1406B** and/or the local identity server **1404B**.

(103) As part of registering, the individual **1440** provides biometric data associated with the individual **1440**. For example, the individual **1440** undergoes a facial scan, a fingerprint scan, an iris scan, or other suitable biometric scan. Additionally, in some examples, the individual **1440** may provide an existing standardized biometric template to the local partner server **1406B**. The biometric data associated with the individual **1440** is transformed into a standardized biometric template that is associated with the local partner server **1406B**. The standardized biometric template, the registration information, and the existing standardized biometric template are output by the local partner server **1406B** to the local identity server **1404B**.

(104) The local identity server **1404B** captures the standardized biometric template, the registration information, and the existing standardized biometric template. The local identity server **1404B** performs a hash translation between the standardized biometric template and the existing standardized biometric template and generates a biometric hash based on the hash translation and clears the standardized biometric template, the existing standardized biometric template, and any biometric data associated with the individual **1440** from the temporary memory. For example, the local identity server **1404B** may use the Trust Stamp™ technology to generate the biometric hash from the standardized biometric template created by the local partner server **1406B** and the existing standardized template created by the local partner server **1406A**.

(105) Although not shown in FIG. 15, if the biometric hash is unable to be generated from the hash translation, the local identity server **1404B** may clear the standardized biometric template from temporary memory and request another standardized biometric template from the individual **1440** via the local partner server **1406B**.

(106) After successfully generating the biometric hash, the local identity server **1404B** performs a

record query (i.e., a 1:1 record query for 1:n predictive match) of the individual because the biometric hash is based at least in part on an existing standardized biometric template. The global identity server **1418** outputs any similar biometric hashes to the local identity server **1404B**.

(107) The local identity server **1404B** performs de-duplication using predictive matching to determine whether the biometric hash matches any existing biometric hashes stored in the database **114** and the biometric hashes received from the global identity server **1418**. For example, the local identity server **1404B** may use the Trust Stamp™ technology to perform predictive matching to determine whether the biometric hash matches any existing biometric hashes stored in the database **114** and the biometric hashes received from the global identity server **1418**.

(108) In one example, after checking against existing biometric hashes in the database **114** and the biometric hashes received from the global identity server **1418**, the local identity server **1404B** finds no match and generates a new global unique identifier (GUID) associated with the individual **1440** and stores the GUID and the biometric hash in the database **114**. In another example, after checking against existing biometric hashes in the database **114** and the biometric hashes received from the global identity server **1418**, the local identity server **1404B** finds a match and stores the biometric hash, the existing hashes, and an existing GUID associated with the individual **1440** in the database **114**.

(109) After storing all of the information associated with the individual **1440** in the database **114**, the local identity server **1404B** may transmit the biometric hash to the global identity server **1418** via the network **160**. In other words, when “online,” the local identity server **1404B** sends “matched” biometric hashes to the global identity server **1418**.

(110) After receiving the biometric hash from the local identity server **1404B**, the global identity server **1418** may simply store the biometric hash associated with the individual **1440**. In other examples, after receiving the biometric hash from the local identity server **1404B**, the global identity server **1418** may perform a global de-duplication using predictive matching to determine whether the biometric hash matches any existing biometric hashes stored in the global database **126**. After performing the global de-duplication, the global identity server **1418** stores the biometric hash associated with the individual **1440**.

(111) In the example of FIG. 15, the identity network/switch **1402** of FIG. 14 is the interconnection between the local partner servers **1406A** and **1406B**, the local identity servers **1404A** and **1404B**, and the global identity server **1418**. With the above-noted interconnection, the local identity servers **1404A** and **1404B** continuously update their respective database **114** when the individual **1440** requests a service. Likewise, the global identity server **1418** continuously updates the database **126** when the individual **1440** requests a service. These continuous updates of biometric hashes ensure that the local identity servers **1404A** and **1404B** and the global identity server **1418** may accurately identify the individual **1440** even as the biometric data of the individual **1440** changes over time. For example, these continuous updates may account for the aging of the individual **1440** over time.

(112) FIG. 16 illustrates another example implementation of the identity network/switch **1402** of FIG. 14. In the example of FIG. 16, the individual **1440** has previously enrolled in a program or service offered by a partner via the local partner server **1406A**. For example, the individual **1440** has previously visited the partner to access the partner computer **135A** and enroll in a service.

(113) The local partner server **1406A** captured the registration of the individual **1440** and output the registration information to the local legacy server **1602** (e.g., one of the legacy servers **1408** as described above in FIG. 14). The individual **1440** also indicated consent to the local partner server **1406A** and/or the local legacy server **1602**.

(114) As part of registering, the individual **1440** provided biometric data associated with the individual **1440**. For example, the individual **1440** underwent a facial scan, a fingerprint scan, an iris scan, or other suitable biometric scan. The biometric data associated with the individual **1440** is transformed into a proprietary biometric template at the local partner server **1406A** based on the proprietary form issued by the local legacy server **1602**. The proprietary biometric template, the

biometric data, and the registration information is output by the local partner server **1406A** to the local legacy server **1602**.

(115) The local legacy server **1602** captured the proprietary biometric template, the biometric data, and the registration information. The local legacy server **1602** performed de-duplication using predictive matching of personally identifiable information (PII) to determine whether the proprietary biometric template matches any existing proprietary biometric templates stored in the local legacy server **1602**. After checking against existing proprietary biometric templates in the database of the local legacy server **1602**, the local legacy server **1602** outputs the proprietary biometric template to the global legacy server **1604**.

(116) In the example of FIG. 15, after storing the proprietary biometric template, the global legacy server **1604** outputs the proprietary biometric template to the local identity server **1404**. The local identity server **1404** uses a hash translation service (as described above in FIG. 14) to translate the proprietary biometric template into a biometric hash. In some examples, the local identity server **1404** transmits the biometric hash to the global identity server **1418**, and the global identity server **1418** stores the biometric hash in the database **126**.

(117) However, in some examples, to translate the proprietary biometric template into a biometric hash, the local identity server **1404** adjusts the proprietary biometric template into a standards-based and “hash-friendly” template that allows for transformation into a biometric hash. In other words, the proprietary aspect of the proprietary biometric template may need to be removed by the local identity server **1404** to create a “hash-friendly” biometric template that may be hashed by the local identity server **1404**. Although the hash translation service is described with respect to the local identity server **1404**, the hash translation service may be implemented by any of the servers that store or use the proprietary biometric template.

(118) Additionally, in the example of FIG. 15, the individual **1440** requests enrollment in a program or service offered by a second partner via the local partner server **1406B**. For example, the individual **1440** may visit the second partner to access the partner computer **135B** and enroll.

(119) The local partner server **1406B** captures the registration of the individual **1440** and outputs the registration information to the local identity server **1404**. The individual **1440** also indicates consent to the local partner server **1406B** and/or the local identity server **1404**.

(120) As part of registering, the individual **1440** provides biometric data associated with the individual **1440**. For example, the individual **1440** undergoes a facial scan, a fingerprint scan, an iris scan, or other suitable biometric scan. Additionally, in some examples, the individual **1440** may provide an existing proprietary biometric template to the local partner server **1406B** via a pre-existing individual resource (e.g., an identity card). The biometric data associated with the individual **1440** is transformed into a standardized biometric template. The standardized biometric template, the registration information, and the existing proprietary biometric template are output by the local partner server **1406B** to the local identity server **1404**. The local identity server **1404** captures the standardized biometric template, the registration information, and the existing proprietary biometric template. The local identity server **1404** generates a biometric hash based on the standardized biometric template and clears the standardized biometric template and any biometric data associated with the individual **1440** from temporary memory. For example, the local identity server **1404** may use the Trust Stamp™ technology to generate the biometric hash from the standardized biometric template created by the local partner server **1406B**.

(121) After successfully generating the biometric hash and in response to receiving the existing proprietary biometric template, the local identity server **1404** performs a record query (i.e., a 1:1 record query for 1:n predictive match) regarding the individual **1440**. The global identity server **1418** outputs any similar biometric hashes to the local identity server **1404**. Additionally, in some examples, the local identity server **1404** may use the hash translation service to translate the existing proprietary biometric template into a biometric hash as described above.

(122) The local identity server **1404** performs de-duplication using predictive matching to

determine whether the biometric hash (or biometric hashes) matches any existing biometric hashes stored in the database **114** and the biometric hashes received from the global identity server **1418**. For example, the local identity server **1404** may use the Trust Stamp™ technology to perform predictive matching to determine whether the biometric hash (or biometric hashes) matches any existing biometric hashes stored in the database **114** and the biometric hashes received from the global identity server **1418**.

(123) In one example, after checking against existing biometric hashes in the database **114** and the biometric hashes received from the global identity server **1418**, the local identity server **1404** finds no match and generates a new global unique identifier (GUID) associated with the individual **1440** and stores the GUID and the biometric hash in the database **114**. In another example, after checking against existing biometric hashes in the database **114** and the biometric hashes received from the global identity server **1418**, the local identity server **1404** finds a match and stores the biometric hash, the existing hashes match, and the existing GUID associated with the individual **1440** in the database **114**.

(124) After storing all of the information associated with the individual **1440** in the database **114**, the local identity server **1404** may transmit the biometric hash to the global identity server **1418** via the network **160**. In other words, when “online,” the local identity server **1404** sends “matched” biometric hashes to the global identity server **1418**.

(125) After receiving the biometric hash from the local identity server **1404**, the global identity server **1418** may simply store the biometric hash associated with the individual **1440**. In other examples, after receiving the biometric hash from the local identity server **1404**, the global identity server **1418** may perform a global de-duplication using predictive matching to determine whether the biometric hash matches any existing biometric hashes stored in the global database **126**. After performing the global de-duplication and finding a match, the global identity server **1418** stores the biometric hash associated with the individual **1440**.

(126) In the example of FIG. **16**, the identity network/switch **1402** of FIG. **14** is the interconnection between the local partner servers **1406A** and **1406B**, the local identity server **1404**, the local legacy server **1602**, the global legacy server **1604**, and the global identity server **1418**. With the above-noted interconnection, the local identity server **1404** continuously updates the database **114** when the individual **1440** requests a service from the first partner or the second partner. Additionally, in some examples, the global identity server **1418** also continuously updates the database **126** when the individual **1440** requests a service from the first partner or the second partner. By continually updating the database **126** and the database **114**, the local identity server **1404** and the global identity server **1418** may continue to accurately identify the individual **1440** even as the biometric data of the individual **1440** changes over time. For example, the local identity server **1404** and the global identity server **1418** may accurately identify the individual **1440** even as the individual **1440** ages over time.

(127) FIG. **17** is a flowchart illustrating one example method **1700** for securely identifying an individual with the local identity server **104** in the example system **100** of FIG. **1**. FIG. **17** is described with respect to FIG. **1**.

(128) The method **1700** includes initiating, with the local identity server **104**, a personalization of a partner-specific identification vehicle that identifies the individual **140** based at least in part on an individual global unique identifier associated with the individual **140** (at block **1702**). The method **1700** includes receiving, with the local identity server **104**, a request for a service from the individual **140** via the network **160** (at block **1704**). The method **1700** includes receiving, with the local identity server **104**, consent and registration information from the individual **140** via the network **160** (at block **1706**). The method **1700** includes generating, with the local identity server **104**, an identity confirmation that confirms an identity of the individual **140** (at block **1708**). The method **1700** also includes outputting, with the local identity server **104**, the identity confirmation to the network **160** (at block **1710**). In this example of the method **1700**, the individual global

unique identifier is generated from information derived from the registration information, and the individual global unique identifier is not indicative of personally identifiable information of the individual.

(129) Many different arrangements of the various components depicted, as well as components not shown, are possible without departing from the spirit and scope of the present disclosure. Embodiments of the present disclosure have been described with the intent to be illustrative rather than restrictive. Alternative embodiments will become apparent to those skilled in the art that do not depart from its scope. A skilled artisan may develop alternative means of implementing the aforementioned improvements without departing from the scope of the present disclosure. It should thus be noted that the matter contained in the above description or shown in the accompanying drawings is to be interpreted as illustrative and not in a limiting sense.

Claims

1. A system for securely identifying an individual, the system comprising: a first local identity server including a first electronic processor, a first communication interface, and a first memory, the first electronic processor is configured to initiate a personalization of a partner-specific identification vehicle that identifies the individual based at least in part on an individual global unique identifier associated with the individual, receive a first request for a first service from the individual via the first communication interface, receive consent and registration information from the individual via the first communication interface, generate a first identity confirmation that confirms an identity of the individual, and output the first identity confirmation via the first communication interface, wherein the individual global unique identifier is generated from information derived from the registration information, and wherein the partner-specific identification vehicle is not indicative of personally identifiable information of the individual; and a second local identity server including a second electronic processor, a second communication interface, and a second memory, the second electronic processor is configured to receive a second request for a second service from the individual via the second communication interface, receive second consent and second registration information from the individual via the second communication interface, generate a second identity confirmation that confirms an identity of the individual, determine whether the second identity confirmation is a match to any other identity confirmations by querying a global identity server with the second identity confirmation via the second communication interface, receive an identity match acknowledgement and one or more identity confirmations from the global identity server, wherein the one or more identity confirmations includes the first identity confirmation, and store the second identity confirmation and the one or more identity confirmations in the second memory.
2. The system of claim 1, further comprising: a first local partner server including a third electronic processor, a third communication interface, and a third memory that are communicatively connected to each other, the third electronic processor is configured to receive the request for the service from the individual, output the first consent and the first registration information from the individual via the third communication interface, receive the first identity confirmation via the third communication interface, and approve the first request for the first service from the individual based on the first identity confirmation, wherein the first communication interface and the third communication interface communicate with each other over a network; and a second local partner server including a fourth electronic processor, a fourth communication interface, and a fourth memory that are communicatively connected to each other, the fourth electronic processor is configured to receive the second request for the second service from the individual, output the second consent and the second registration information from the individual via the fourth communication interface, receive the second identity confirmation via the fourth communication interface, and approve the second request for the second service from the individual based on the

second identity confirmation, wherein the first communication interface and the fourth communication interface communicate with each other over a network.

3. The system of claim 2, further comprising: one or more legacy servers, each of the one or more legacy servers including a fifth electronic processor, a fifth communication interface, and a legacy database that are communicatively connected to each other, wherein the third electronic processor is further configured to receive a first biometric template of the individual from the partner-specific identification vehicle that is assigned to the individual, generate a second biometric template of the individual based on the registration information, output the first biometric template of the individual and the second biometric template of the individual via the third communication interface, wherein the first electronic processor is further configured to receive the first biometric template and the second biometric template via the first communication interface, determine whether the first biometric template is associated with one of the one or more legacy servers, and output the first biometric template to the one of the one or more legacy servers via the first communication interface in response to determining that the first biometric template is associated with the one of the one or more legacy servers, and wherein the first communication interface, the third communication interface, the fifth communication interface communicate with each other over the network.

4. The system of claim 3, further comprising: a global identity server including a sixth electronic processor, a sixth communication interface, and a sixth memory that are communicatively connected to each other, wherein the first electronic processor is further configured to output the first biometric template via the first communication interface, and wherein the sixth electronic processor is configured to receive the first biometric template via the sixth communication interface, translate the first biometric template into a biometric hash, perform de-duplication to determine whether the biometric hash matches any other biometric hashes, associate the biometric hash with the individual global unique identifier that is assigned to the individual in response to determining that the biometric hash matches a different biometric hash that is already associated with the individual, store the biometric hash in the sixth memory in response to associating the biometric hash with the individual global unique identifier, and output the first identity confirmation via the sixth communication interface in response to associating the biometric hash with the individual global unique identifier.

5. The system of claim 3, wherein the first electronic processor is configured to translate the first biometric template into a biometric hash, perform de-duplication to determine whether the biometric hash matches any other biometric hashes, associate the biometric hash with the individual global unique identifier that is assigned to the individual in response to determining that the biometric hash matches a different biometric hash that is already associated with the individual, store the biometric hash in the first memory in response to associating the biometric hash with the individual global unique identifier, and output the first identity confirmation via the first communication interface in response to associating the biometric hash with the individual global unique identifier.

6. The system of claim 2, further comprising: a global identity server including a fifth electronic processor, a fifth communication interface, and a fifth memory that are communicatively connected to each other, wherein the third electronic processor is further configured to receive a first biometric template of the individual from the partner-specific identification vehicle that is assigned to the individual, generate a second biometric template of the individual based on the registration information, output the first biometric template of the individual and the second biometric template of the individual via the third communication interface, wherein the first electronic processor is further configured to generate a biometric hash based on the second biometric template, and output the first biometric template and the biometric hash via the first communication interface, and wherein the fifth electronic processor is configured to receive the first biometric template and the biometric hash via the fifth communication interface, translate the first biometric template into a

second biometric hash, perform de-duplication to determine whether the biometric hash and the second biometric hash match any other biometric hashes, associate the biometric hash and the second biometric hash with the individual global unique identifier that is assigned to the individual in response to determining that the biometric hash and the second biometric hash match a different biometric hash that is already associated with the individual, store the biometric hash and the second biometric hash in the fifth memory in response to associating the biometric hash and the second biometric hash with the individual global unique identifier, and output the first identity confirmation via the fifth communication interface in response to associating the biometric hash and the second biometric hash with the individual.

7. The system of claim 2, wherein the third electronic processor is further configured to receive a first biometric template of the individual from the partner-specific identification vehicle that is assigned to the individual, generate a second biometric template of the individual based on the registration information, output the first biometric template of the individual and the second biometric template of the individual via the third communication interface, and wherein the first electronic processor is configured to generate a biometric hash based on the second biometric template, translate the first biometric template into a second biometric hash, perform de-duplication to determine whether the biometric hash and the second biometric hash match any other biometric hashes, associate the biometric hash and the second biometric hash with the individual global unique identifier that is assigned to the individual in response to determining that the biometric hash and the second biometric hash match a different biometric hash that is already associated with the individual, store the biometric hash and the second biometric hash in the third memory in response to associating the biometric hash and the second biometric hash with the individual global unique identifier, and output the first identity confirmation to the first local partner server via the third communication interface in response to associating the biometric hash and the second biometric hash with the individual global unique identifier.

8. The system of claim 2, wherein the third electronic processor is further configured to generate a biometric template of the individual based on the registration information, and output the biometric template of the individual via the third communication interface.

9. The system of claim 8, wherein the first electronic processor is configured to receive the biometric template via the first communication interface, generate a biometric hash based on the biometric template, perform de-duplication to determine whether the biometric hash matches any other biometric hashes, associate the biometric hash with the individual global unique identifier that is assigned to the individual in response to determining that the biometric hash matches a different biometric hash that is already associated with the individual, store the biometric hash in the third memory in response to associating the biometric hash with the individual global unique identifier, and output the first identity confirmation via the first communication interface in response to associating the biometric hash with the individual global unique identifier.

10. The system of claim 8, further comprising: a global identity server including a fifth electronic processor, a fifth communication interface, and a fifth memory that are communicatively connected to each other, wherein the first electronic processor is further configured to receive the biometric template via the first communication interface, generate a biometric hash based on the biometric template, and output the biometric hash via the first communication interface, wherein the fifth electronic processor is configured to receive the biometric hash via the fifth communication interface, perform de-duplication to determine whether the biometric hash matches any other biometric hashes, associate the biometric hash with the individual global unique identifier that is assigned to the individual in response to determining that the biometric hash matches a different biometric hash that is already associated with the individual, store the biometric hash in the fifth memory in response to associating the biometric hash with the individual global unique identifier, and output the first identity confirmation to the first local partner server via the fifth communication interface in response to associating the biometric hash with the individual global

unique identifier, and wherein the first communication interface, the third communication interface, the fifth communication interface communicate with each other over the network.

11. A method for securely identifying an individual, the method comprising: initiating, with a first local identity server, a personalization of a partner-specific identification vehicle that identifies the individual based at least in part on an individual global unique identifier associated with the individual; receiving, with the first local identity server, a request for a service from the individual via a network; receiving, with the first local identity server, consent and registration information from the individual via the network; generating, with the first local identity server, a first identity confirmation that confirms an identity of the individual, wherein the individual global unique identifier is generated from information derived from the registration information, and wherein the partner-specific identification vehicle is not indicative of personally identifiable information of the individual; outputting, with the first local identity server, the first identity confirmation to the network; receiving, with a second local identity server, a second request for a second service from the individual via a second network; receiving, with the second local identity server, second consent and second registration information from the individual via the second network; generating, with the second local identity server, a second identity confirmation that confirms an identity of the individual; determining, with the second local identity server, whether the second identity confirmation is a match to any other identity confirmations by querying a global identity server with the second identity confirmation via a third network; receiving, with the second local identity server, an identity match acknowledgement and one or more identity confirmations from the global identity server via the third network, wherein the one or more identity confirmations includes the first identity confirmation; and storing, with the second local identity server, the second identity confirmation and the one or more identity confirmations in a local memory.

12. The method of claim 11, further comprising: receiving, with a first local partner server, the request for the service from the individual; outputting, with the first local partner server, the consent and the registration information from the individual to the network; receiving, with the first local partner server, the first identity confirmation via the network; and approving, with the first local partner server, the request for the service from the individual based on the first identity confirmation, wherein the first local identity server and the first local partner server communicate with each other over the network.

13. The method of claim 12, further comprising: receiving, with a second local partner server, the second request for the second service from the individual, outputting, with the second local partner server, the second consent and the second registration information from the individual to the second network, receiving, with the second local partner server, the second identity confirmation via the second network, and approving, with the second local partner server, the second request for the second service from the individual based on the second identity confirmation, wherein the first local identity server and the second local partner server communicate with each other over the second network.

14. The method of claim 12, further comprising: receiving, with the first local partner server, a first biometric template of the individual from the partner-specific identification vehicle that is assigned to the individual; generating, with the first local partner server, a second biometric template of the individual based on the registration information; outputting, with the first local partner server, the first biometric template of the individual and the second biometric template of the individual to the network; receiving, with the first local identity server, the first biometric template and the second biometric template via the network; determining, with the first local identity server, whether the first biometric template is associated with one of one or more legacy servers; and outputting, with the first local identity server, the first biometric template to the one of the one or more legacy servers via the network in response to determining that the first biometric template is associated with the one of the one or more legacy servers; wherein the first local identity server, the first local partner server, and one or more legacy servers communicate with each other via the network, and

wherein each of the one or more legacy servers includes a legacy database.

15. The method of claim 14, further comprising: outputting, with the first local identity server, the first biometric template to the network; receiving, with a global identity server, the first biometric template via the network; translating, with the global identity server, the first biometric template into a biometric hash; performing, with the global identity server, de-duplication to determine whether the biometric hash matches any other biometric hashes; associating, with the global identity server, the biometric hash with the individual global unique identifier that is assigned to the individual in response to determining that the biometric hash matches a different biometric hash that is already associated with the individual; storing, with the global identity server, the biometric hash in a memory in response to associating the biometric hash with the individual global unique identifier; and outputting, with the global identity server, the first identity confirmation to the network in response to associating the biometric hash with the individual global unique identifier.

16. The method of claim 14, further comprising: translating, with the first local identity server, the first biometric template into a biometric hash; performing, with the first local identity server, de-duplication to determine whether the biometric hash matches any other biometric hashes; associating, with the first local identity server, the biometric hash with the individual global unique identifier that is assigned to the individual in response to determining that the biometric hash matches a different biometric hash that is already associated with the individual; storing, with the first local identity server, the biometric hash in a memory in response to associating the biometric hash with the individual global unique identifier; and outputting, with the first local identity server, the first identity confirmation to the network in response to associating the biometric hash with the individual global unique identifier.

17. The method of claim 12, further comprising: receiving, with the first local partner server, a first biometric template of the individual from the partner-specific identification vehicle that is assigned to the individual; generating, with the first local partner server, a second biometric template of the individual based on the registration information; outputting, with the first local partner server, the first biometric template of the individual and the second biometric template of the individual to the network; generating, with the first local identity server, a biometric hash based on the second biometric template; outputting, with the first local identity server, the first biometric template and the biometric hash to the network; receiving, with a global identity server, the first biometric template and the biometric hash via the network; translating, with the global identity server, the first biometric template into a second biometric hash; performing, with the global identity server, de-duplication to determine whether the biometric hash and the second biometric hash match any other biometric hashes; associating, with the global identity server, the biometric hash and the second biometric hash with the individual global unique identifier that is assigned to the individual in response to determining that the biometric hash and the second biometric hash match a different biometric hash that is already associated with the individual; storing, with the global identity server, the biometric hash and the second biometric hash in a memory in response to associating the biometric hash and the second biometric hash with the individual global unique identifier; and outputting, with the global identity server, the first identity confirmation to the network in response to associating the biometric hash and the second biometric hash with the individual.

18. The method of claim 12, further comprising: receiving, with the first local partner server, a first biometric template of the individual from the partner-specific identification vehicle that is assigned to the individual; generating, with the first local partner server, a second biometric template of the individual based on the registration information; outputting, with the first local partner server, the first biometric template of the individual and the second biometric template of the individual to the network; generating, with the first local identity server, a biometric hash based on the second biometric template; translating, with the first local identity server, the first biometric template into a second biometric hash; performing, with the first local identity server, de-duplication to determine whether the biometric hash and the second biometric hash match any other biometric hashes;

associating, with the first local identity server, the biometric hash and the second biometric hash with the individual global unique identifier that is assigned to the individual in response to determining that the biometric hash and the second biometric hash match a different biometric hash that is already associated with the individual; storing, with the first local identity server, the biometric hash and the second biometric hash in a memory in response to associating the biometric hash and the second biometric hash with the individual global unique identifier; and outputting, with the first local identity server, the first identity confirmation to the first local partner server to the network in response to associating the biometric hash and the second biometric hash with the individual global unique identifier.

19. The method of claim 12, further comprising: generating, with the first local partner server, a biometric template of the individual based on the registration information; and outputting, with the first local partner server, the biometric template of the individual to the network.

20. The method of claim 19, further comprising: receiving, with the first local identity server, the biometric template via the network; generating, with the first local identity server, a biometric hash based on the biometric template; performing, with the first local identity server, de-duplication to determine whether the biometric hash matches any other biometric hashes; associating, with the first local identity server, the biometric hash with the individual global unique identifier that is assigned to the individual in response to determining that the biometric hash matches a different biometric hash that is already associated with the individual; storing, with the first local identity server, the biometric hash in a memory in response to associating the biometric hash with the individual global unique identifier; and outputting, with the first local identity server, the first identity confirmation to the network in response to associating the biometric hash with the individual global unique identifier.
