

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250277634

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

MICHIWA; Kazuyoshi et al.

HEAT STORAGE DEVICE

Abstract

A heat storage device includes a ceramic part, and a latent heat storage part provided inside the ceramic part. The ceramic part includes a first surface, a second surface opposite to the first surface, a third surface connecting the first surface and the second surface, and a first groove provided in the third surface and connected to the first surface and the second surface.

Inventors: MICHIWA; Kazuyoshi (Nagano, JP), NAGAI; Koji (Nagano, JP), WATANABE; Takuya (Nagano, JP)

Applicant: SHINKO ELECTRIC INDUSTRIES CO., LTD. (Nagano, JP)

Family ID: 94687983

Appl. No.: 19/051640

Filed: February 12, 2025

Foreign Application Priority Data

JP	2024-031450	Mar. 01, 2024
----	-------------	---------------

Publication Classification

Int. Cl.: F28D20/02 (20060101); F28D20/00 (20060101); F28F21/04 (20060101)

U.S. Cl.:

CPC F28D20/021 (20130101); F28F21/04 (20130101); F28D2020/0078 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is based upon and claims priority to Japanese Patent Application No. 2024-031450, filed on Mar. 1, 2024, the entire contents of which are incorporated herein by reference.

FIELD

[0002] Certain aspects of the embodiments discussed herein are related to heat storage devices.

BACKGROUND

[0003] Heat storage devices using latent heat storages have been proposed. An example of the heat storage device is proposed in Japanese Laid-Open Patent Publication No. 2015-048393, for example.

[0004] Recently, there are increased demands to improve a thermal storage efficiency.

SUMMARY

[0005] Accordingly, it is an object in one aspect of the embodiments to provide a heat storage device which can improve the thermal storage efficiency.

[0006] According to one aspect of the embodiments, a heat storage device includes a ceramic part; and a latent heat storage part provided inside the ceramic part, wherein the ceramic part includes a first surface, a second surface opposite to the first surface, a third surface connecting the first surface and the second surface, and a first groove provided in the third surface and connected to the first surface and the second surface.

[0007] The object and advantages of the embodiments will be realized and attained by means of the elements and combinations particularly pointed out in the claims.

[0008] It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and not restrictive of the invention, as claimed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1A, FIG. 1B, and FIG. 1C are diagrams illustrating an example of a heat storage device according to a first embodiment;

[0010] FIG. 2 is a cross sectional view illustrating an example of a multi-heat storage device including a plurality of heat storage devices according to the first embodiment;

[0011] FIG. 3 is a perspective view illustrating an example of the heat storage device according to a second embodiment;

[0012] FIG. 4 is a perspective view illustrating an example of the heat storage device according to a third embodiment;

[0013] FIG. 5 is a cross sectional view illustrating an example of the multi-heat storage device including a plurality of heat storage devices according to the third embodiment;

[0014] FIG. 6 is a perspective view illustrating an example of the heat storage device according to a fourth embodiment;

[0015] FIG. 7A, FIG. 7B, and FIG. 7C are diagrams illustrating an example of the heat storage device according to a fifth embodiment; and

[0016] FIG. 8A and FIG. 8B are diagrams illustrating an example of the heat storage device according to a sixth embodiment.

DESCRIPTION OF EMBODIMENTS

[0017] Preferred embodiments of the present invention will be described with reference to the accompanying drawings. In the drawings, those parts that are substantially the same are designated by the same reference numerals, and a repeated description thereof may be omitted.

First Embodiment

[0018] First, a first embodiment will be described. The first embodiment relates to a heat storage device. FIG. 1A, FIG. 1B, and FIG. 1C are diagrams illustrating an example of a heat storage

device according to a first embodiment. FIG. 1A is a perspective view of the heat storage device, FIG. 1B is a top view of the heat storage device, and FIG. 1C is a cross sectional view of the heat storage device. FIG. 1C corresponds to a cross sectional view taken along a line Ic-Ic in FIG. 1B. [0019] As illustrated in FIG. 1A through FIG. 1C, a heat storage device 1 according to the first embodiment includes a ceramic part 10, a latent heat storage part 21, and heating element 41. A plurality of closed spaces 18 are formed in the ceramic part 10. The ceramic part 10 is integrally formed, for example. For example, the ceramic part 10 does not have a joint connected to the closed space 18. The latent heat storage part 21 is provided inside the closed space 18. In other words, the latent heat storage part 21 is sealed inside the ceramic part 10. That is, the latent heat storage part 21 is airtightly covered with the ceramic part 10 which is a continuous body. The ceramic part 10 has a function of preventing a leakage of melted latent heat storage part 21. The latent heat storage part 21 has a columnar shape, such as a circular columnar shape or the like, for example. The latent heat storage part 21 is provided inside each of the closed spaces 18. That is, a plurality of latent heat storage parts 21 are provided inside the ceramic part 10. The latent heat storage parts 21 are arranged with long axes thereof parallel to one another. As illustrated in FIG. 1B, the plurality of latent heat storage parts 21 are densely arranged in a regular triangle lattice, for example.

[0020] The latent heat storage part 21 is formed of a metal, for example. The latent heat storage part 21 includes aluminum (Al), copper (Cu), silicon (Si), or boron (B), or an arbitrary combination of two or more of such elements, for example.

[0021] A main component of the latent heat storage part 21 may be aluminum. The latent heat storage part 21 may include aluminum at a ratio of 99 mass % or greater. That is, the latent heat storage part 21 may be composed of aluminum having a purity of 99 mass % or greater.

[0022] The main component of the latent heat storage part 21 may be copper. The latent heat storage part 21 may include copper at a ratio of 99 mass % or greater. That is, the latent heat storage part 21 may be composed of copper having a purity of 99 mass % or greater.

[0023] The main component of the latent heat storage part 21 may be silicon. The latent heat storage part 21 may include silicon at a ratio of 50 mass % or greater. The latent heat storage part 21 may be composed of silicon having a purity of 50 mass % or greater. Preferably, the latent heat storage part 21 includes silicon at a ratio of 99 mass % or greater, and is composed of silicon having a purity of 99 mass % or greater. The latent heat storage part 21 may include boron (B), aluminum (Al), bismuth (Bi), antimony (Sb), gallium (Ga), copper (Cu), iron (Fe), titanium (Ti), yttrium (Y), indium (In), zinc (Zn), tin (Sn), or an arbitrary combination of two or more of such elements at a ratio of less than 50 mass % in total.

[0024] The main component of the latent heat storage part 21 may be boron. The latent heat storage part 21 may include boron at a ratio of 50 mass % or greater. The latent heat storage part 21 may be composed of boron having a purity of 50 mass % or greater. Preferably, the latent heat storage part 21 includes 80 mass % or greater of boron, and is composed of boron having a purity of 80 mass % or greater. More preferably, the latent heat storage part 21 includes boron at a ratio of 99 mass % or greater, and is composed of boron having a purity of 99 mass % or greater. The latent heat storage part 21 may include silicon (Si), aluminum (Al), iron (Fe), copper (Cu), cobalt (Co), or any combination of two or more such elements at a ratio of less than 20 mass % in total.

[0025] In the case where the main component of the latent heat storage part 21 is aluminum, the ceramic part 10 includes aluminum oxide (Al_2O_3) at a ratio of 96 mass % or greater, for example. That is, the ceramic part 10 may be composed of aluminum oxide having a purity of 96 mass % or greater.

[0026] In the case where the main component of the latent heat storage part 21 is copper, the ceramic part 10 includes aluminum oxide at a ratio of 90 mass % or greater, or mullite ($3\text{Al}_2\text{O}_3 \cdot 2\text{SiO}_2$) at a ratio of 90 mass % or greater, or aluminum nitride (AlN) at a ratio of 95 mass % or greater, or a mixture of aluminum nitride and boron nitride (BN) at a

ratio of 95 mass % or greater. The ceramic part **10** may further include a sintering aid (or a sintering additive) or the like. Examples of the sintering aid include silicon, magnesium, calcium, or the like. Ceramic grains included in the ceramic part **10** preferably have a grain diameter (or a grain size) of approximately 1 μm or less, and more preferably approximately 0.3 μm or less.

[0027] In the case where the main component of the latent heat storage part **21** is silicon, the ceramic part **10** includes mullite, aluminum oxide (Al_2O_3), cordierite ($2\text{MgO} \cdot \text{Al}_2\text{O}_3 \cdot 5\text{SiO}_2$), anorthite ($\text{CaAl}_2\text{Si}_2\text{O}_8$), sillimanite (Al_2SiO_5), silica nitride (Si_3N_4), boron nitride, aluminum nitride, a composite material (or composite ceramic) of aluminum nitride and boron nitride, silica carbide (SiC), tungsten carbide (WC), boron carbide (B_4C), molybdenum disilicide (MoSi_2), tungsten disilicide (WSi_2), or an arbitrary combination of two or more of such materials. The ceramic part **10** may be composed of mullite, aluminum oxide, cordierite, anorthite, sillimanite, silicon nitride, boron nitride, aluminum nitride, a composite material of aluminum nitride and boron nitride, silicon carbide, tungsten carbide, boron carbide, molybdenum disilicide, tungsten disilicide, or an arbitrary combination of two or more of such materials.

[0028] In the case where the main component of the latent heat storage part **21** is boron, the ceramic part **10** may be composed of boron nitride (BN), boron carbide (B_4C), aluminum nitride (AlN), a composite material of aluminum nitride and boron nitride, silicon nitride (Si_3N_4), silicon carbide (SiC), or an arbitrary combination of two or more of such materials. The ceramic part **10** may be composed of boron nitride, boron carbide, aluminum nitride, a composite material (or composite ceramic) of aluminum nitride and boron nitride, silicon nitride, silicon carbide, or an arbitrary combination of two or more of such materials.

[0029] In the case where the main component of the latent heat storage part **21** is boron, the ceramic part **10** may include a boride. The ceramic part **10** may be composed of a boride. The boride is titanium boride (TiB_2), zirconium boride (ZrB_2), hafnium boride (HfB_2), vanadium boride (VB_2), niobium boride (NbB_2), tantalum boride (TaB_2), lanthanum boride (LaB_6), or any combination of two or more of such materials.

[0030] The heating element **41** is provided inside the ceramic part **10**. The heating element **41** is provided between a surface of the ceramic part **10** and a surface of the latent heat storage part **21**. The heating element **41** generates Joule heat when energized. The heating element **41** has a substantially cylindrical shape around each latent heat storage part **21**. The heating element **41** can heat the latent heat storage part **21**. In order to reduce heat loss, a distance between the heating element **41** and the latent heat storage part **21** is preferably small. The heating element **41** includes tungsten, or molybdenum, or both of tungsten and molybdenum, for example. The heating element **41** may include a mixture of tungsten and aluminum oxide, or a mixture of molybdenum and aluminum oxide. In this case, the heating element **41** may further include one or more materials selected from silicon oxide, magnesium oxide, calcium carbonate, or the like. The heat storage device **1** may include a plurality of heating elements **41**.

[0031] The ceramic part **10** has a substantially hexahedral shape having surfaces **11**, **12**, **13**, **14**, **15** and **16** in the top view (or a plan view) illustrated in FIG. 1B. The surfaces **11** and **12** are parallel to each other, the surfaces **13** and **14** are parallel to each other, and the surfaces **15** and **16** are parallel to each other. That is, the surface **12** is a surface opposite to the surface **11**, the surface **14** is a surface opposite to the surface **13**, and the surface **16** is a surface opposite to the surface **15**. The surfaces **13**, **14**, **15**, and **16** connect (or join) the surface **11** and the surface **12**. The ceramic part **10** may have a rectangular parallelepiped shape or a cubic shape in the top view. For example, the long axis of the latent heat storage part **21** is perpendicular to the surfaces **11** and **12**. The surfaces **11**, **12**, **13**, **14**, **15**, and **16** are examples of a first surface, a second surface, a third surface, a fourth surface, a fifth surface, and a sixth surface, respectively.

[0032] A groove **31** is formed in the surface **13**. A plurality of grooves **31** may be formed in the surface **13**. The groove **31** is connected to the surfaces **11** and **12**, and the surfaces **11** and **12** have

recesses associated with the groove **31**. The groove **31** may be formed in a linear shape. The groove **31** is an example of a first groove.

[0033] Two terminals of the heating element **41** are provided on the surface **12**. A pin having a lead wire is connected thereto is attached to each terminal, and electric power is supplied to the heating element **41** from the outside via the lead wires.

[0034] In a case where heat is to be stored in the heat storage device **1**, a heat medium (or a heat transfer medium), such as air or the like, is supplied toward the heat storage device **1** substantially perpendicularly to the surfaces **11** and **12**. As a result, the heat medium makes contact not only with the surface **11** or **12** but also with the surfaces **13**, **14**, **15**, and **16**, and the heat of the heat medium is transferred to the latent heat storage part **21** via the ceramic part **10**. When the latent heat storage part **21** is heated to a temperature higher than a solid-liquid phase transition temperature, latent heat associated with the phase transition is stored in the latent heat storage part **21**. In the present embodiment, because one or a plurality of grooves **31** are formed in the surface **13**, an area of the ceramic part **10** in contact with the heat medium is larger than that of a case where the groove **31** is not formed. For this reason, a heat storage efficiency can be improved.

[0035] Further, it is possible to use not only the heating medium, but also the electric power. In this case, the pins are attached to the terminals of the heating element **41**, and the electric power is supplied to the heating element **41** from the lead wires to cause the heating element **41** to generate heat. The heat generated by the heating element **41** is stored in the latent heat storage part **21**. Accordingly, the electric power applied from the outside can be converted into heat and stored in the latent heat storage part **21**. For example, by generating heat from the heating element **41** by surplus electric power, the surplus electric power can be stored as heat. An energy stored in the latent heat storage part **21** can be supplied to a factory, an office, a commercial building, or the like as energy of heat, steam (pressure), or electric power (turbine power generation using steam pressure, or the like).

[0036] One or a plurality of grooves **31** may also be formed in one, two, or three (or all) of the surfaces **14**, **15**, and **16**.

[0037] A plurality of heat storage devices **1** may be arranged in a vertical direction and a horizontal direction, that is, in a matrix. FIG. 2 is a cross sectional view illustrating an example of a multi-heat storage device having a plurality of heat storage devices according to the first embodiment. FIG. 2 illustrates a cross section of the heat storage device **1** taken along a line II-II in FIG. 1B.

[0038] A multi-heat storage device **61** illustrated in FIG. 2 includes a plurality of heat storage devices **1**. The plurality of heat storage devices **1** are arranged so that one surface **13** and another surface **14** of two adjacent heat storage devices **1** in the vertical direction in FIG. 2 oppose each other, respectively. The plurality of heat storage devices **1** are also arranged so that one surface **11** and another surface **12** of two adjacent heat storage devices **1** in the horizontal direction in FIG. 2 oppose each other, respectively. In addition, the plurality of heat storage devices **1** may be arranged so that one surface **15** and another surface **16** of two adjacent heat storage devices **1** in a direction perpendicular to both the vertical direction and the horizontal direction in FIG. 2 oppose each other, respectively. Moreover, the grooves **31** are connected between the two adjacent heat storage devices **1** in the vertical direction in FIG. 2 having the surfaces **11** and **12** thereof opposing each other, respectively.

[0039] In the multi-heat storage device **61**, when the heat medium is supplied toward the heat storage devices **1** substantially perpendicularly to the surfaces **11** and **12**, the heat medium can flow inside the grooves **31** and make contact with the plurality of heat storage devices **1**. Accordingly, even in a case where the heat included in the heat medium cannot be transferred to one heat storage device **1**, the heat can be transferred to other heat storage devices **1**.

Second Embodiment

[0040] A second embodiment will be described. The second embodiment differs from the first embodiment mainly in the arrangement of the grooves. FIG. 3 is a perspective view illustrating an

example of the heat storage device according to the second embodiment.

[0041] As illustrated in FIG. 3, in a heat storage device 2 according to the second embodiment, a groove 32 is formed in the surface 11. A plurality of grooves 32 may be formed in the surface 11. The groove 32 is connected to the surfaces 15 and 16, and the surfaces 15 and 16 have recesses associated with the groove 32. The groove 32 may be formed in a linear shape. The groove 32 is an example of a second groove.

[0042] Otherwise, the configuration of the second embodiment is the same as the configuration of the first embodiment.

[0043] The second embodiment can also obtain advantageous features or effects that are the same as those obtainable by the first embodiment. Further, because one or a plurality of grooves 32 are formed in the surface 11, even in the case where the heat medium is supplied toward the heat storage device 1 substantially perpendicularly to the surfaces 15 and 16, the area of the ceramic part 10 in contact with the heat medium can be increased.

[0044] One or a plurality of grooves 32 may also be formed in the surface 12.

[0045] Similar to the heat storage device 1, a plurality of heat storage devices 2 may be arranged in the vertical direction and the horizontal direction, that is, in a matrix. In this case, the grooves 31 are connected between the two adjacent heat storage devices 2 having the surfaces 11 and 12 thereof opposing each other, respectively. Moreover, the grooves 32 are connected between the two adjacent heat storage devices 2 having the surfaces 15 and 16 thereof opposing each other, respectively.

Third Embodiment

[0046] A third embodiment will be described. The third embodiment differs from the second embodiment mainly in the arrangement of the grooves. FIG. 4 is a perspective view illustrating an example of the heat storage device according to the third embodiment.

[0047] As illustrated in FIG. 4, in a heat storage device 3 according to the third embodiment, a groove 33 is formed in the surface 11. A plurality of grooves 33 may be formed in the surface 11. The groove 33 is connected to the surfaces 13 and 14, and the surfaces 13 and 14 have recesses associated with the groove 33. The groove 33 may be formed in a linear shape. The groove 31 and the groove 33 may be connected to each other. The groove 33 is an example of a second groove.

[0048] Otherwise, the configuration of the third embodiment is the same as the configuration of the second embodiment.

[0049] The third embodiment can also obtain advantageous features or effects that are the same as those obtainable by the second embodiment.

[0050] One or a plurality of grooves 33 may also be formed in the surface 12.

[0051] Similar to the heat storage device 1, a plurality of heat storage devices 3 may be arranged in the vertical direction and the horizontal direction, that is, in a matrix. FIG. 5 is a cross sectional view illustrating an example of the multi-heat storage device having a plurality of heat storage devices according to the third embodiment.

[0052] A multi-heat storage device 63 illustrated in FIG. 5 includes a plurality of heat storage devices 3. The plurality of heat storage devices 3 are arranged so that one surface 13 and another surface 14 of two adjacent heat storage devices 3 in the vertical direction in FIG. 5 oppose each other, respectively. The plurality of heat storage devices 3 are also arranged so that one surface 11 and another surface 12 of two adjacent heat storage devices 3 in the horizontal direction in FIG. 5 oppose each other, respectively. In addition, the plurality of heat storage devices 3 may be arranged so that one surface 15 and another surface 16 of two adjacent heat storage devices 3 in a direction perpendicular to both the vertical direction and the horizontal direction in FIG. 5 oppose each other, respectively. Moreover, the grooves 31 are connected between the two adjacent heat storage devices 3 in the vertical direction in FIG. 5 having the surfaces 11 and 12 thereof opposing each other, respectively. Further, the grooves 33 are connected between the two adjacent heat storage devices 3 in the horizontal direction in FIG. 5 having the surfaces 13 and 14 thereof opposing each

other, respectively.

[0053] In the multi-heat storage device **63**, when the heat medium is supplied toward the heat storage device **1** substantially perpendicularly to the surfaces **11** and **12**, the heat medium can flow inside the grooves **31** and make contact with the plurality of heat storage devices **3**, similar to the multi-heat storage device **61**. In addition, when the heat medium is supplied toward the heat storage device **1** substantially perpendicularly to the surfaces **13** and **14**, the heat medium can flow inside the grooves **33** and make contact with the plurality of heat storage devices **3**. Accordingly, even in a case where the heat included in the heat medium cannot be transferred to one heat storage device **3**, the heat can be transferred to other heat storage devices **3**.

Fourth Embodiment

[0054] A fourth embodiment will be described. The fourth embodiment differs from the second embodiment mainly in the arrangement of the grooves. FIG. **6** is a perspective view illustrating an example of the heat storage device according to the fourth embodiment.

[0055] As illustrated in FIG. **6**, in a heat storage device **4** according to the fourth embodiment, grooves **32** and **33** are formed in the surface **11**. A plurality of grooves **32** and a plurality of grooves **33** may be formed in the surface **11**. On the other hand, the groove **31** is not formed in the surface **13**. In the present embodiment, the groove **32** is an example of a first groove, the groove **33** is an example of a third groove, the surface **15** is an example of a first surface, the surface **16** is an example of a second surface, the surface **11** is an example of a third surface, the surface **13** is an example of a fifth surface, and the surface **14** is an example of a sixth surface. From another viewpoint, the groove **33** is an example of a first groove, the groove **32** is an example of a third groove, the surface **13** is an example of a first surface, the surface **14** is an example of a second surface, the surface **11** is an example of a third surface, the surface **15** is an example of a fifth surface, and the surface **16** is an example of a sixth surface.

[0056] Otherwise, the configuration of the fourth embodiment is the same as the configuration of the second embodiment.

[0057] When heat is to be stored in the heat storage device **4**, the heat medium is supplied toward the heat storage device **4** substantially perpendicularly to the surfaces **13** and **14** or substantially perpendicularly to the surfaces **15** and **16**. As a result, the heat medium makes contact not only with the surface **13**, or **14**, or **15**, or **16**, but also with at least the surfaces **11** and **12**, and the heat of the heat medium is transferred to the latent heat storage part **21** via the ceramic part **10**. In the present embodiment, because one or a plurality of grooves **32** and **33** are formed in the surface **11**, the area of the ceramic part **10** in contact with the heat medium is larger than that of a case where the groove **32** or **33** is not formed. For this reason, the heat storage efficiency can be improved.

Fifth Embodiment

[0058] A fifth embodiment will be described. The fifth embodiment differs from the first embodiment mainly in that a metal layer is provided. FIG. **7A**, FIG. **7B**, and FIG. **7C** are diagrams illustrating an example of the heat storage device according to a fifth embodiment. FIG. **7A** is a perspective view of the heat storage device, FIG. **7B** is a top view of the heat storage device, and FIG. **7C** is a cross sectional view of the heat storage device. FIG. **7C** corresponds to a cross sectional view taken along a line VIIc-VIIc in FIG. **7B**.

[0059] As illustrated in FIG. **7A** through FIG. **7C**, a heat storage device **5** according to the fifth embodiment includes a metal layer **51**. A plurality of grooves **31** are provided in the surface **13**, and the metal layer **51** is provided inside each of the grooves **31**. The metal layer **51** is a copper (Cu) layer, for example. The metal layer **51** may cover other portions of the surface **13**, as long as the metal layer **51** is provided inside each groove **31**.

[0060] One metal layer **51** is electrically connected to one end of the heating element **41**, and another metal layer **51** is electrically connected to another end of the heating element **41**, as illustrated in FIG. **7B**.

[0061] Otherwise, the configuration of the fifth embodiment is the same as the configuration of the

first embodiment.

[0062] The fifth embodiment can also obtain advantageous features or effects that are the same as those obtainable by the first embodiment. In addition, because the metal layer **51** is provided in the groove **31**, a thermal resistance between the heat medium and the ceramic part **10** can be reduced, and it is possible to further improve the heat storage efficiency.

[0063] Moreover, the heating element **41** can be supplied with electric power from the outside through the metal layer **51**. For example, by causing a power supply terminal connected to an external power source to make contact with the metal layer **51**, electric power can be supplied to the heating element **41**. Because the metal layer **51** is less likely to be affected by a thermal expansion and a thermal contraction of the heat storage device compared to the terminal provided on the surface **12** of the heat storage device **1**, the heat storage device **5** can achieve a better long-term stability than the heat storage device **1**.

[0064] The heating element **41** does not need to be connected to the metal layer **51**, and the terminals of the heating element **41** may be provided on the surface **12**, similar to the first embodiment.

Sixth Embodiment

[0065] A sixth embodiment will be described. The sixth embodiment differs from the first embodiment mainly in the shapes and the arrangements of the latent heat storage part and the heating element. FIG. **8A** and FIG. **8B** are diagrams illustrating an example of the heat storage device according to the sixth embodiment. FIG. **8A** is a top view of the heat storage device, and FIG. **8B** is a cross sectional view of the heat storage device. FIG. **8B** corresponds to a cross sectional view taken along a line VIIIb-VIIIb in FIG. **8A**.

[0066] As illustrated in FIG. **8A** and FIG. **8B**, a heat storage device **6** according to the sixth embodiment includes a latent heat storage part **22** in place of the latent heat storage part **21**, and includes electric heating elements **42** and **43** in place of the heating element **41**.

[0067] The latent heat storage part **22** has a plate shape with two principal surfaces **22A** and **22B**, for example. The principal surfaces **22A** and **22B** are parallel to the surfaces **11** and **12**. The principal surface **22A** is located on a side closer to the surface **11** than to the surface **12**, and the principal surface **22B** is located on a side closer to the surface **12** than to the surface **11**. That is, a distance between the principal surface **22A** and the surface **11** is shorter than a distance between the principal surface **22B** and the surface **11**. The latent heat storage part **22** has a substantially rectangular shape in the top view.

[0068] The heating element **42** is provided between the principal surface **22A** and the surface **11**, and the heating element **43** is provided between the principal surface **22B** and the surface **12**. For example, the heating elements **42** and **43** are arranged in a meander shape in the top view on a plane parallel to the principal surfaces **22A** and **22B**. Hence, the latent heat storage part **22** is located between the heating element **42** and the heating element **43**. The heating element **42** is an example of a first heating element, and the heating element **43** is an example of a second heating element.

[0069] Otherwise, the configuration of the sixth embodiment is the same as the configuration of the first embodiment.

[0070] The sixth embodiment can also obtain advantageous features or effects that are the same as those obtainable by the first embodiment. Further, when the ceramic parts **10** have the same size, a volume of the latent heat storage part **22** can easily be made larger than a total volume of the latent heat storage part **21**, and a heat storage capacity can be increased.

[0071] In the sixth embodiment, the metal layer **51** may be provided inside the groove **31**, similar to the fifth embodiment, and the heating elements **42** and **43** may be electrically connected to the metal layer **51**.

[0072] Moreover, a plurality of latent heat storage parts **22** may be arranged inside the ceramic part **10** so that the principal surface **22A** and the principal surface **22B** oppose each other between

adjacent latent heat storage parts 22, and a heating element similar to the heating elements 42 and 43 may be provided between adjacent latent heat storage parts 22.

[0073] Accordingly to each of the embodiments described above, it is possible to improve the thermal storage efficiency.

[0074] Although the embodiments are numbered with, for example, “first,” “second,” “third,” “fourth,” “fifth,” or “sixth,” the ordinal numbers do not imply priorities of the embodiments. Many other variations and modifications will be apparent to those skilled in the art.

[0075] All examples and conditional language recited herein are intended for pedagogical purposes to aid the reader in understanding the invention and the concepts contributed by the inventor to furthering the art, and are to be construed as being without limitation to such specifically recited examples and conditions, nor does the organization of such examples in the specification relate to a showing of the superiority and inferiority of the invention. Although the embodiments of the present invention have been described in detail, it should be understood that the various changes, substitutions, and alterations could be made hereto without departing from the spirit and scope of the invention.

Claims

1. A heat storage device comprising: a ceramic part; and a latent heat storage part provided inside the ceramic part, wherein: the ceramic part includes: a first surface; a second surface opposite to the first surface; a third surface connecting the first surface and the second surface; and a first groove provided in the third surface and connected to the first surface and the second surface.
2. The heat storage device as claimed in claim 1, further comprising: a metal layer provided inside the first groove.
3. The heat storage device as claimed in claim 2, further comprising: a heating element provided inside the ceramic part and configured to heat the latent heat storage part, wherein the metal layer is electrically connected to the heating element.
4. The heat storage device as claimed in claim 1, wherein the ceramic part includes: a fourth surface opposite to the third surface, and connecting the first surface and the second surface; and a second groove provided in the first surface and connected to the third surface and the fourth surface.
5. The heat storage device as claimed in claim 4, wherein the first groove and the second groove are connected.
6. The heat storage device as claimed in claim 1, wherein the ceramic part includes: a fifth surface connected to the third surface, and connecting the first surface and the second surface; a sixth surface opposite to the fifth surface, connected to the third surface, and connecting the first surface and the second surface; and a third groove provided in the third surface and connected to the fifth surface and the sixth surface.
7. The heat storage device as claimed in claim 1, further comprising: a first heating element and a second heating element, provided inside the ceramic part, and configured to heat the latent heat storage part, wherein the latent heat storage part is located between the first heating element and the second heating element.
8. The heat storage device as claimed in claim 7, wherein: the latent heat storage part has a plate shape having two principal surfaces, and the first heating element and the second heating element are arranged on a plane parallel to the two principal surfaces.
9. A multi-heat storage device comprising: a plurality of heat storage devices according to claim 1, wherein: the ceramic part includes a fourth surface opposite to the third surface, and connecting the first surface and the second surface, and the plurality of heat storage devices are arranged so that the third surface and the fourth surface of two adjacent heat storage devices in a first direction oppose each other, respectively, and the first surface and the second surface of two adjacent heat

storage devices in a second direction perpendicular to the first direction oppose each other, respectively.
