

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12383915
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Turbeville; Vance

Portable fluid spraying system

Abstract

A portable fluid spraying system for spraying a fluid includes a housing. A pump, a hose, and a tank for containing a fluid are coupled to and positioned in the housing. The pump is activatable to urge the fluid from the tank through the hose. The hose is wound on a reel which is biased to rotate such that the hose winds onto the reel.

Inventors:	Turbeville; Vance (Kimberly, ID)
Applicant:	Turbeville; Vance (Kimberly, ID)
Family ID:	92120713
Appl. No.:	18/104878
Filed:	February 02, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240261809 A1	Aug. 08, 2024

Publication Classification

Int. Cl.: **B05B9/00** (20060101); **B05B9/04** (20060101); **B05B12/08** (20060101); **B05B15/656** (20180101); **H01R13/66** (20060101)

U.S. Cl.:

CPC **B05B9/007** (20130101); **B05B9/0403** (20130101); **B05B12/081** (20130101); **B05B15/656** (20180201); **H01R13/6675** (20130101);

Field of Classification Search

CPC: B05B (9/007); B05B (9/0403); B05B (15/656); B05B (12/081); B60S (3/044); B60S (3/04); B60S (3/06); H01R (13/6675)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3454042	12/1968	Phillips	N/A	N/A
5029758	12/1990	Chayer	239/588	B60S 3/044
5351640	12/1993	Attaway	N/A	N/A
6152707	12/1999	Alberg	417/423.3	E03B 11/06
6189811	12/2000	Rudy	239/525	F04B 17/006
7017603	12/2005	Rosine	242/395.1	B65H 75/403
10087066	12/2017	Hall	N/A	B62B 3/02
2010/0243086	12/2009	Gilpatrick	137/565.01	B08B 3/026
2011/0014066	12/2010	Gilpatrick	417/313	F04B 17/06
2011/0132413	12/2010	Gans	N/A	N/A
2011/0162570	12/2010	Moser	N/A	N/A
2012/0080062	12/2011	Parker	134/198	B44D 3/006
2014/0339803	12/2013	Hammer	280/830	E03B 1/041
2017/0012448	12/2016	Miller	N/A	H02J 7/0029

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO2017143942	12/2016	WO	N/A

Primary Examiner: Pham; Tuongminh N

Background/Summary

(g) BACKGROUND OF THE INVENTION

(1) Field of the Invention

(1) The disclosure relates to portable spraying devices and more particularly pertains to a new portable spraying device for spraying a fluid.

(2) Description of Related Art Including Information Disclosed Under 37 CFR 1.97 and 1.98

(2) The prior art relates to devices which are utilized for supplying pressurized fluids in a portable manner.

(h) BRIEF SUMMARY OF THE INVENTION

(3) An embodiment of the disclosure meets the needs presented above by generally comprising a housing with a base wall and a perimeter wall. The perimeter wall is attached to and extends upwardly from the base wall. The base wall and the perimeter wall bound an interior space. The perimeter wall includes a front wall, a rear wall, a first lateral wall, and a second lateral wall. A tank for containing a fluid is coupled to the housing and is positioned within the interior space. A pump is fluidly coupled to the tank and is positioned in the interior space. The pump includes a motor for driving the pump. A supply hose is fluidly coupled to the pump, and the pump is activatable to urge the fluid from the tank through the supply hose. The supply hose extends through the perimeter wall of the housing. A control circuit is electrically coupled to the pump. A

reel is rotatably coupled to the housing and is positioned within the interior space. The supply hose is wound onto the reel. The reel includes a torsion spring biased to rotate the reel in a first direction to wind the supply hose onto the reel.

(4) There has thus been outlined, rather broadly, the more important features of the disclosure in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the disclosure that will be described hereinafter and which will form the subject matter of the claims appended hereto.

(5) The objects of the disclosure, along with the various features of novelty which characterize the disclosure, are pointed out with particularity in the claims annexed to and forming a part of this disclosure.

(i) BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWING(S)

(6) The disclosure will be better understood and objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:

Description

(1) FIG. 1 is a top front side perspective view of a portable fluid spraying system according to an embodiment of the disclosure.

(2) FIG. 2 is a front view of an embodiment of the disclosure.

(3) FIG. 3 is a rear view of an embodiment of the disclosure.

(4) FIG. 4 is a side view of an embodiment of the disclosure.

(5) FIG. 5 is a top view of an embodiment of the disclosure with a lid of the system removed from a housing of the system.

(6) FIG. 6 is a cross-sectional view of an embodiment of the disclosure taken from Arrows 6-6 in FIG. 2.

(7) FIG. 7 is a cross-sectional view of an embodiment of the disclosure taken from Arrows 7-7 in FIG. 6.

(8) FIG. 8 is an in-use view of an embodiment of the disclosure.

(9) FIG. 9 is a block diagram of an embodiment of the disclosure.

(j) DETAILED DESCRIPTION OF THE INVENTION

(10) With reference now to the drawings, and in particular to FIGS. 1 through 9 thereof, a new portable spraying device embodying the principles and concepts of an embodiment of the disclosure and generally designated by the reference numeral 10 will be described.

(11) As best illustrated in FIGS. 1 through 6, the portable fluid spraying system 10 generally comprises a housing 12 with a base wall 14 and a perimeter wall 16. The perimeter wall 16 is attached to and extends upwardly from the base wall 14. The base wall 14 and the perimeter wall 16 bound an interior space 18. The perimeter wall 16 includes a front wall 20, a rear wall 22, a first lateral wall 24, and a second lateral wall 26. A tank 28 for containing a fluid 30 is coupled to the housing 12 and is positioned within the interior space 18. A pump 32 is fluidly coupled to the tank 28 and is positioned in the interior space 18. The pump 32 includes a motor for driving the pump 32. A supply hose 34 is fluidly coupled to the pump 32, and the pump 32 is activatable to urge the fluid 30 from the tank 28 through the supply hose 34. The supply hose 34 extends through the perimeter wall 16 of the housing 12. A control circuit 36 is electrically coupled to the pump 32 and is positioned in the interior space 18. A reel 38 is rotatably coupled to the housing 12 and is positioned within the interior space 18. The supply hose 34 is wound onto the reel 38. The reel 38 includes a torsion spring 40 biased to rotate the reel 38 in a first direction to wind the supply hose 34 onto the reel 38.

(12) A first carrying handle **42** is coupled to the first lateral wall **24**, and a second carrying handle **44** is coupled to the second lateral wall **26**. Each of a first wheel **46** and a second wheel **48** is rotatably coupled to the housing **12**. The first wheel **46** is positioned on the first lateral wall **24** of the housing **12** adjacent to the rear wall **22**, and the second wheel **48** is positioned on the second lateral wall **26** of the housing **12** adjacent to the rear wall **22**. The first wheel **46** and the second wheel **48** have a common rotational axis. An extendable handle **50** is slidably coupled to the rear wall **22** of the housing **12** such that the extendable handle **50** is extendable upwardly from the housing **12**.

(13) A nozzle **52** is fluidly coupled to a distal end **54** of the supply hose **34** with respect to the pump **32** for dispensing the fluid **30** from the nozzle **52**. A fluid level gauge **56** is in fluid communication with the tank **28** to indicate a level of the fluid **30** within the tank **28**. The fluid level gauge **56** is mounted on the housing **12** and includes an indicator dial **58** facing outwardly away from the housing **12**. The fluid level gauge **56** is electrically coupled to the control circuit **36** such that the control circuit **36** deactivates the pump **32** when the fluid level gauge **56** indicates that the tank **28** is empty. The fluid level gauge **56** may include a float **60** which is buoyant in the fluid **30** such that it remains near a top surface of the fluid **30** in the tank **28**. In such an embodiment, the float **60** is operatively coupled to the indicator dial **58** to indicate a level of fluid **30** contained in the tank **28** and operatively coupled to the control circuit **36** to deactivate the pump **32** when the tank **28** is empty of the fluid **30**.

(14) A lid **64** is removably positioned on the housing **12** to cover the interior space **18**. A top handle **66** is coupled to and extends upwardly from the lid **64**. An inlet tube **68** is fluidly coupled to the tank **28** and is positioned on a top side **70** of the tank **28** such that the tank **28** is fillable via the inlet tube **68**. An inlet cap **72** is removably coupled to the inlet tube **68** to selectively close the inlet tube **68**. An outlet tube **74** for draining the tank **28** through the outlet tube **74** is fluidly coupled to the tank **28** and is positioned on a rear side **76** of the tank **28** adjacent to a bottom side **78** of the tank **28**. The outlet tube **74** extends through the perimeter wall **16** of the housing **12**. The outlet tube **74** is externally threaded and is shaped such that the outlet tube **74** may fluidly couple to a garden hose. An outlet cap **80** is removably coupled to the outlet tube **74** to selectively close the outlet tube **74**.

(15) A light emitter **82** is coupled to the housing **12** and is positioned on the perimeter wall **16**. The light emitter **82** is electrically coupled to the control circuit **36** and is directed to emit light away from the housing **12**. A power supply **84** is electrically coupled to the control circuit **36** and is positioned within the interior space **18**. The power supply **84** comprises a battery **86**. A plurality of electrical outlets **88** is electrically coupled to the control circuit **36** and is positioned on the perimeter wall **16** of the housing **12**. A power inverter **90** is electrically coupled to the control circuit **36** for converting direct current electrical power supplied by the power supply **84** into an alternating current electrical power supplied to each electrical outlet **88** of the plurality of electrical outlets **88**. The power inverter **90** is also positioned within the interior space **18**.

(16) An input **92** is electrically coupled to the control circuit **36** and is positioned on the perimeter wall **16** of the housing **12**. The input **92** includes a power switch **94** for selectively supplying electrical power to the plurality of electrical outlets **88**, a pump switch **96** for selectively activating the pump **32**, and a light switch **98** for selectively activating the light emitter **82**. A charging cord **100** for charging the battery **86** is electrically coupled to the control circuit **36** and is coupled to the perimeter wall **16**. The charging cord **100** is configured for electrically coupling to an alternating current power source. A cord mount **102** is coupled to the perimeter wall **16** of the housing **12** which comprises a plurality of radially positioned hooks **104** upon which the charging cord **100** is wound. A charging port **106** is electrically coupled to the control circuit **36** and is coupled to the perimeter wall **16**. The charging port **106** is configured for receiving electrical power from a direct current power source. A direct current cord **108** is stored in the interior space **18** and is couplable to the charging port **106**.

(17) In use, the tank **28** is filled with the fluid **30**. The system **10** may be moved to a location where a user **110** desires to spray the fluid **30** by carrying the system **10** with the first and second carrying handles **42** and **44**, rolling the system **10** on a surface via the first and second wheels **46** and **48** while grasping the extendable handle **50**, or a combination thereof. The supply hose **34** may be unwound from the reel **38** to reach areas the user **110** desires to spray. The pump **32** is activated and the user **110** directs the supply hose **34** toward the desired areas. The fluid **30** may be water, a washing fluid **30** containing soap, a solvent, a surfactant, or the like, or any fluid **30** the user **110** desires to spray. The system **10** may be used, for example, to water plants, wash a car **112** or boat, and the like.

(18) With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of an embodiment enabled by the disclosure, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by an embodiment of the disclosure.

(19) Therefore, the foregoing is considered as illustrative only of the principles of the disclosure. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the disclosure to the exact construction and operation shown and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the disclosure. In this patent document, the word “comprising” is used in its non-limiting sense to mean that items following the word are included, but items not specifically mentioned are not excluded. A reference to an element by the indefinite article “a” does not exclude the possibility that more than one of the element is present, unless the context clearly requires that there be only one of the elements.

Claims

1. A portable fluid spraying system comprising: a housing having a base wall and a perimeter wall, the perimeter wall being attached to and extending upwardly from the base wall, the base wall and the perimeter wall bounding an interior space, the perimeter wall including a front wall, a rear wall, a first lateral wall, and a second lateral wall; a tank for containing a fluid being coupled to the housing and being positioned within the interior space; a pump being fluidly coupled to the tank and being positioned in the interior space, the pump including a motor for driving the pump; a supply hose being fluidly coupled to the pump, the pump being activatable to urge the fluid from the tank through the supply hose, the supply hose extending through the perimeter wall of the housing; a control circuit being electrically coupled to the pump; a reel being rotatably coupled to the housing and being positioned within the interior space, the supply hose being wound onto the reel, the reel including a torsion spring biased to rotate the reel in a first direction to wind the supply hose onto the reel; a first wheel and a second wheel each being rotatably coupled to the housing, the first wheel being positioned on the first lateral wall of the housing adjacent to the rear wall, the second wheel being positioned on the second lateral wall of the housing adjacent to the rear wall, the first wheel and the second wheel having a common rotational axis; a fluid level gauge being in fluid communication with the tank to indicate a level of the fluid within the tank, the fluid level gauge being mounted on the housing and includes an indicator dial facing outwardly away from the housing, the fluid level gauge being electrically coupled to the control circuit such that the control circuit deactivates the pump when the fluid level gauge indicates that the tank is empty; a lid being removably positioned on the housing to cover the interior space; and a top handle being coupled to and extending upwardly from the lid; an inlet tube being fluidly coupled to the tank and being positioned on a top side of the tank, wherein the tank is fillable via the inlet tube; and an inlet cap being removably coupled to the inlet tube to selectively close the inlet tube; an outlet tube for

draining the tank through the outlet tube being fluidly coupled to the tank and being positioned on a rear side of the tank adjacent to a bottom side of the tank, the outlet tube extending through the perimeter wall of the housing, the outlet tube being externally threaded and being shaped such that the outlet tube is configured for coupling to a garden hose; an outlet cap being removably coupled to the outlet tube to selectively close the outlet tube; a light emitter being coupled to the housing and being positioned on the perimeter wall, the light emitter being directed to emit light away from the housing, the light emitter being electrically coupled to the control circuit; and a power supply being electrically coupled to the control circuit, the power supply being positioned within the interior space.

2. The system of claim 1, further comprising a first carrying handle and a second carrying handle, the first carrying handle being coupled to the first lateral wall, the second carrying handle being coupled to the second lateral wall.

3. The system of claim 1, further comprising an extendable handle being slidably coupled to the rear wall of the housing, the extendable handle being extendable upwardly from the housing.

4. The system of claim 1, further comprising a nozzle being fluidly coupled to a distal end of the supply hose with respect to the pump for dispensing the fluid from the nozzle.

5. The system of claim 1, wherein the power supply comprises a battery.

6. The system of claim 1, further comprising: a plurality of electrical outlets being electrically coupled to the control circuit and being positioned on the perimeter wall of the housing; and a power inverter being electrically coupled to the control circuit for converting direct current electrical power supplied by the power supply into an alternating current electrical power supplied to each electrical outlet of the plurality of electrical outlets, the power inverter being positioned within the interior space.

7. The system of claim 6, further comprising an input being electrically coupled to the control circuit and being positioned on the perimeter wall of the housing, the input including a power switch for selectively supplying electrical power to the plurality of electrical outlets.

8. The system of claim 1, further comprising an input being electrically coupled to the control circuit and being positioned on the perimeter wall of the housing, the input including a pump switch for selectively activating the pump.

9. The system of claim 1, further comprising an input being electrically coupled to the control circuit and being positioned on the perimeter wall of the housing, the input including a light switch for selectively activating the light emitter.

10. The system of claim 5, further comprising a charging cord for charging the battery, being electrically coupled to the control circuit and being coupled to the perimeter wall, the charging cord being configured for electrically coupling to an alternating current power source.

11. The system of claim 10, further comprising: a cord mount being coupled to the perimeter wall of the housing, the cord mount comprising a plurality of radially positioned hooks, the charging cord being wound onto the cord mount; a charging port being electrically coupled to the control circuit and being coupled to the perimeter wall, the charging port being configured for receiving electrical power from a direct current power source; and a direct current cord being stored in the interior space, the direct current cord being couplable to the charging port.

12. A portable fluid spraying system comprising: a housing having a base wall and a perimeter wall, the perimeter wall being attached to and extending upwardly from the base wall, the base wall and the perimeter wall bounding an interior space, the perimeter wall including a front wall, a rear wall, a first lateral wall, and a second lateral wall; a tank for containing a fluid being coupled to the housing and being positioned within the interior space; a pump being fluidly coupled to the tank and being positioned in the interior space, the pump including a motor for driving the pump; a supply hose being fluidly coupled to the pump, the pump being activatable to urge the fluid from the tank through the supply hose, the supply hose extending through the perimeter wall of the housing; a control circuit being electrically coupled to the pump, the control circuit being

positioned in the interior space; a reel being rotatably coupled to the housing and being positioned within the interior space, the supply hose being wound onto the reel, the reel including a torsion spring biased to rotate the reel in a first direction to wind the supply hose onto the reel; a first carrying handle and a second carrying handle, the first carrying handle being coupled to the first lateral wall, the second carrying handle being coupled to the second lateral wall; a first wheel and a second wheel each being rotatably coupled to the housing, the first wheel being positioned on the first lateral wall of the housing adjacent to the rear wall, the second wheel being positioned on the second lateral wall of the housing adjacent to the rear wall, the first wheel and the second wheel having a common rotational axis; an extendable handle being slidably coupled to the rear wall of the housing, the extendable handle being extendable upwardly from the housing; a nozzle being fluidly coupled to a distal end of the supply hose with respect to the pump for dispensing the fluid from the nozzle; a fluid level gauge being in fluid communication with the tank to indicate a level of the fluid within the tank, the fluid level gauge being mounted on the housing and including an indicator dial facing outwardly away from the housing, the fluid level gauge being electrically coupled to the control circuit such that the control circuit deactivates the pump when the fluid level gauge indicates that the tank is empty; a lid being removably positioned on the housing to cover the interior space; a top handle being coupled to and extending upwardly from the lid; an inlet tube being fluidly coupled to the tank and being positioned on a top side of the tank, wherein the tank is fillable via the inlet tube; an inlet cap being removably coupled to the inlet tube to selectively close the inlet tube; an outlet tube for draining the tank through the outlet tube being fluidly coupled to the tank and being positioned on a rear side of the tank adjacent to a bottom side of the tank, the outlet tube extending through the perimeter wall of the housing, the outlet tube being externally threaded and being shaped such that the outlet tube is configured for coupling to a garden hose; an outlet cap being removably coupled to the outlet tube to selectively close the outlet tube; a light emitter being coupled to the housing and being positioned on the perimeter wall, the light emitter being directed to emit light away from the housing, the light emitter being electrically coupled to the control circuit; a power supply being electrically coupled to the control circuit, the power supply being positioned within the interior space, the power supply comprising a battery; a plurality of electrical outlets being electrically coupled to the control circuit and being positioned on the perimeter wall of the housing; a power inverter being electrically coupled to the control circuit for converting direct current electrical power supplied by the power supply into an alternating current electrical power supplied to each electrical outlet of the plurality of electrical outlets, the power inverter being positioned within the interior space; an input being electrically coupled to the control circuit and being positioned on the perimeter wall of the housing, the input including: a power switch for selectively supplying electrical power to the plurality of electrical outlets; a pump switch for selectively activating the pump; and a light switch for selectively activating the light emitter; a charging cord for charging the battery being electrically coupled to the control circuit and being coupled to the perimeter wall, the charging cord being configured for electrically coupling to an alternating current power source; a cord mount being coupled to the perimeter wall of the housing, the cord mount comprising a plurality of radially positioned hooks, the charging cord being wound onto the cord mount; a charging port being electrically coupled to the control circuit and being coupled to the perimeter wall, the charging port being configured for receiving electrical power from a direct current power source; and a direct current cord being stored in the interior space, the direct current cord being couplable to the charging port.
