

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12387624
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Yang; Tung-Po

Label and beverage container with label attached

Abstract

A label member is configured to be partially removably attached to a bottle of a beverage container. The label member includes a double-sided tape and a flexible drip prevention film. The double-sided tape has a first adhesive surface and a second adhesive surface that are located opposite to each other, and the first adhesive surface is configured to be attached to the bottle. The flexible drip prevention film is removably attached to the second adhesive surface of the double-sided tape, and the flexible drip prevention film is configured to be rollable into a cylindrical tube to be inserted into a mouth of the beverage container after being removed from the double-sided tape. In addition, at least a part of the flexible drip prevention film extends beyond an edge of the second adhesive surface of the double-sided tape.

Inventors:	Yang; Tung-Po (Los Gatos, CA)
Applicant:	STUDIO EIGHT LLC (Los Gatos, CA)
Family ID:	92635842
Assignee:	STUDIO EIGHT LLC (Los Gatos, CA)
Appl. No.:	18/118882
Filed:	March 08, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240304112 A1	Sep. 12, 2024

Publication Classification

Int. Cl.: G09F3/02 (20060101); B65D23/06 (20060101); B65D23/14 (20060101); G09F3/00 (20060101)

U.S. Cl.:

CPC **G09F3/0288** (20130101); **B65D23/065** (20130101); **B65D23/14** (20130101);
G09F3/0292 (20130101); B65D2203/02 (20130101); G09F2003/0222 (20130101);
G09F2003/0226 (20130101); G09F2003/0241 (20130101); G09F2003/0257 (20130101);
G09F2003/0273 (20130101)

Field of Classification Search

CPC: G09F (3/0288); G09F (3/0292); G09F (2003/0222); G09F (2003/0226); G09F
(2003/0241); G09F (2003/0257); G09F (2003/0273); G09F (3/10); B65D (23/065); B65D
(23/14); B65D (2203/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5651481	12/1996	Jensen	222/569	B65D 23/065
6073816	12/1999	Granberg	222/571	B01L 99/00
9227760	12/2015	Pieriboni	N/A	B65D 47/40
9302833	12/2015	Faye et al.	N/A	N/A
2005/0023308	12/2004	Burato	222/569	B65D 23/065
2010/0116854	12/2009	Gumpold	222/566	B65D 23/065
2011/0290822	12/2010	Bouwer	222/108	B65D 23/065
2012/0244623	12/2011	Patel	374/102	G09F 3/0292
2013/0291417	12/2012	Erenguc	40/638	G09F 3/0288
2022/0277670	12/2021	Young	N/A	G09F 3/02

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10208427	12/2002	DE	G09F 3/0291
2952441	12/2014	EP	B65D 23/065
2773535	12/1998	FR	B65D 23/065
2252292	12/1991	GB	B65D 25/20
WO-9529474	12/1994	WO	G09F 3/0292
WO-0188483	12/2000	WO	G01K 11/165
WO-2006048673	12/2005	WO	B65D 23/065
WO-2009065157	12/2008	WO	B65D 23/065
WO-2012038557	12/2011	WO	B65D 23/065
WO-2019073327	12/2018	WO	B01F 13/0022

OTHER PUBLICATIONS

Machine translation of DE 10208427 A1. (Year: 2003). cited by examiner

Machine translation of FR 2773535 A1. (Year: 1999). cited by examiner

Machine translation of WO 2009065157 A1. (Year: 2009). cited by examiner

Machine translation of WO 2012038557 A1. (Year: 2012). cited by examiner

Primary Examiner: Nordmeyer; Patricia L.

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates generally to labels and beverage containers with label attached, and more specifically, removable labels with drip prevention design and beverage containers with label attached.

BACKGROUND

(2) Generally, the thickness of the mouth of a container, such as a bottle, is thicker than the neck to allow a cap or a cork to be attached. As a result, the beverage may drip and/or flow down the bottle body when pouring. This phenomenon wastes beverage, and requires cleaning to avoid further contamination. In order to prevent the problem, there are accessories for fluid guidance and drip prevention (e.g., bottle pouring film and drip prevention film) available on the market.

(3) However, beverage products do not include such accessories, inconveniently, consumers are required to buy these accessories separately.

SUMMARY

(4) The present disclosure relates to labels and beverage containers with label attached which address the inconvenience to buy accessories separately in order for fluid guidance or drip prevention.

(5) According to one or more embodiments of this disclosure, a label member is configured to be partially removable after attached to a beverage container. The label member includes a double-sided tape and a flexible drip prevention film. The double-sided tape has a first adhesive surface and a second adhesive surface that are located opposite to each other, and the first adhesive surface is configured to be attached to the bottle. The flexible drip prevention film is removably attached to the second adhesive surface of the double-sided tape, and the flexible drip prevention film is configured to be rollable into a cylindrical tube to be inserted into a mouth of the beverage container after being removed from the double-sided tape. In addition, at least a part of the flexible drip prevention film extends beyond an edge of the second adhesive surface of the double-sided tape.

(6) According to one or more embodiments of this disclosure, a beverage container includes a bottle and a label member. The label member includes a double-sided tape and a flexible drip prevention film. The double-sided tape has a first adhesive surface and a second adhesive surface that are located opposite to each other, and the first adhesive surface is attached to the bottle. The flexible drip prevention film is removably attached to the second adhesive surface of the double-sided tape, and the flexible drip prevention film is configured to be rollable into a cylindrical tube to be inserted into a mouth of the beverage container after being removed from the double-sided tape. In addition, at least a part of the flexible drip prevention film extends beyond an edge of the second adhesive surface of the double-sided tape.

(7) In view of the above description, the flexible drip prevention film of the label member is removable from the double-sided tape and rollable into a cylindrical tube to be inserted into the mouth of the beverage container after being removed from the double-sided tape for fluid guidance and drip prevention. Therefore, when a consumer pours fluid from the bottle of the beverage container, the flexible drip prevention film can guide the fluid and prevent the fluid from dripping or flowing down along the bottle from the mouth. In addition, at least a part of the flexible drip prevention film extends beyond the edge of the second adhesive surface of the double-sided tape, such that the consumer can easily grip the part of the flexible drip prevention film extending beyond the double-sided tape to pull and remove the flexible drip prevention film from the double-

sided tape. Consumer can also easily adhere the flexible drip prevention film back to the second adhesive surface without exposing adhesive.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The embodiments are illustrated by way of example and not by way of limitation in the figures of the accompanying drawings.
- (2) FIG. 1 is a perspective view of a beverage container in accordance with the first embodiment of the present disclosure;
- (3) FIG. 2 is an exploded view of the beverage container in FIG. 1;
- (4) FIG. 3 is a perspective view of the beverage container in FIG. 1 when a flexible drip prevention film of a label member is rolled into a cylindrical tube and inserted into a mouth of the beverage container;
- (5) FIG. 4 is an exploded view of a label member in accordance with the second embodiment of the present disclosure;
- (6) FIG. 5 is an exploded view of a label member in accordance with the third embodiment of the present disclosure;
- (7) FIG. 6 is an exploded view of a label member in accordance with the fourth embodiment of the present disclosure;
- (8) FIG. 7 is an exploded view of a label member in accordance with the fifth embodiment of the present disclosure;
- (9) FIG. 8 is an exploded view of a label member in accordance with the sixth embodiment of the present disclosure;
- (10) FIG. 9 is a perspective view of a label member in accordance with the seventh embodiment of the present disclosure; and
- (11) FIG. 10 is an exploded view of the label member in FIG. 9.

DETAILED DESCRIPTION

(12) In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding. For purposes of explanation, one or more specific embodiments are given to provide a thorough understanding of the invention, and which are described in sufficient detail to enable one skilled in the art to practice the described embodiments. It should be noted the following descriptions are not intended to limit the embodiments to one specific embodiment. On the contrary, it is intended to cover alternatives, modifications, and equivalents as can be included within the spirit and scope of the described embodiments as defined by the appended claims.

(13) Please refer to FIG. 1 to FIG. 3, where FIG. 1 is a perspective view of a beverage container in accordance with the first embodiment of the present disclosure, FIG. 2 is an exploded view of the beverage container in FIG. 1, and FIG. 3 is a perspective view of the beverage container in FIG. 1 when a flexible drip prevention film of a label member is rolled into a cylindrical tube and inserted into a mouth of the beverage container.

(14) In this embodiment, a beverage container 9 is provided. The beverage container 9 includes a bottle 8 and a label member 1, and the label member 1 includes a double-sided tape 11 and a flexible drip prevention film 12.

(15) The double-sided tape 11 includes a first adhesive layer, a second adhesive layer and an intermediate layer located between the first adhesive layer and the second adhesive layer. The double-sided tape 11 has a first adhesive surface GS1 at the first adhesive layer thereof facing towards the bottle 8, and the double-sided tape 11 has a second adhesive surface GS2 at the second adhesive layer thereof facing away from the bottle 8. The first adhesive surface GS1 of the double-

sided tape **11** is attached to the bottle **8**, and the flexible drip prevention film **12** is removably attached to the second adhesive surface GS2 of the double-sided tape **11**. In this embodiment, the double-sided tape **11** is transparent, the first adhesive layer and the second adhesive layer of the double-sided tape **11** are, for example, polyethylene terephthalate (PET) based adhesive layers, and the intermediate layer is, for example, a polyester film, but the present disclosure is not limited thereto.

(16) A label pattern (e.g., Studio eight) is printed on the flexible drip prevention film **12**, showing product information, such as brand or contents. It is noted that the words of the label pattern shown in the figures is only exemplary, and the present disclosure is not limited thereto. In other embodiments, the label pattern may be any desired words or patterns according to actual design requirements. Moreover, the label pattern may be optional, and the present disclosure is not limited thereto.

(17) As shown in FIG. 3, the flexible drip prevention film **12** is removable from the double-sided tape **11**, and the flexible drip prevention film **12** can be rolled into a cylindrical tube to be inserted into a mouth **7** of the beverage container **9** after being removed from the double-sided tape **11** for fluid guidance and drip prevention. Therefore, when a consumer pours wine or beverage from the bottle **8** of the beverage container **9**, the flexible drip prevention film **12** can guide the wine or other beverages to prevent the beverage from dripping or flowing down along the bottle **8** from the mouth **7**. In this or other embodiments, the flexible drip prevention film **12** may have engagement structurers at opposite sides thereof, such that when the flexible drip prevention film **12** is rolled into a cylindrical tube, the engagement structures can be engaged with each other to maintain the shape of the flexible drip prevention film **12**, but the present disclosure is not limited thereto.

(18) In this embodiment, the stickiness of the first adhesive layer of the double-sided tape **11** is greater than that of the second adhesive layer of the double-sided tape **11**. Therefore, when the consumer pulls to remove the flexible drip prevention film **12** from the double-sided tape **11**, the double-sided tape **11** will not be unexpectedly removed from the bottle **8**. Moreover, the second adhesive layer enables the flexible drip prevention film **12** to be removed from and attached back to the second adhesive surface GS2 of the double-sided tape **11** repeatedly, such that the consumer may remove the flexible drip prevention film **12** from the mouth **7** and temporarily attach the flexible drip prevention film **12** back onto the double-sided tape **11** on the bottle **8**. Therefore, it is convenient for the consumer to reuse the flexible drip prevention film **12** without losing or getting the flexible drip prevention film **12** dirty unexpectedly.

(19) At least a part of the flexible drip prevention film **12** extends beyond an edge of the second adhesive surface GS2 of the double-sided tape **11**, such that the consumer can easily grip the part of the flexible drip prevention film **12** extending beyond the double-sided tape **11** to pull and remove the flexible drip prevention film **12** from the double-sided tape **11**. In this embodiment, the area of the surface of the flexible drip prevention film **12** facing the double-sided tape **11** is larger than the area of the second adhesive surface GS2 of the double-sided tape **11**, such that the periphery of the flexible drip prevention film **12** extends beyond the edge of the double-sided tape **11**. Therefore, the consumer can easily grip the periphery of the flexible drip prevention film **12** to remove the flexible drip prevention film **12** from the double-sided tape **11**. In addition, consumer can also easily adhere the flexible drip prevention film **12** back to the second adhesive surface GS2 without exposing adhesive. For example, the periphery of the flexible drip prevention film **12** may extend beyond the edge of the double-sided tape **11** by about 2 mm, but the present disclosure is not limited thereto.

(20) In this embodiment, the whole periphery of the flexible drip prevention film **12** extends beyond the edge of the second adhesive surface GS2 of the double-sided tape **11**, but the present disclosure is not limited thereto. In some embodiments, only a part of the periphery of the flexible drip prevention film may extend beyond the edge of the second adhesive surface of the double-sided tape. Furthermore, in this and some other embodiments, when the beverage container **9** is

placed upright, the label member **1** is configured such that at least the lateral sides of the flexible drip prevention film **12** extend beyond the edge of the second adhesive surface GS2. In specific, as shown in FIG. **1**, a reference curved line RC is defined to be located at the surface of the flexible drip prevention film **12** and pass through the center of the flexible drip prevention film **12**, the reference curved line RC is parallel to the circumferential direction of the bottle **8**, and the reference curved line RC passes through the part of the flexible drip prevention film **12** extending beyond the edge of the second adhesive surface. Therefore, since the flexible drip prevention film is curved when attached to the bottle, it is easier for the consumer to grip the lateral sides of the flexible drip prevention film when the consumer removes the flexible drip prevention film from the double-sided tape compared to the top side (i.e., the side closest to the mouth of the bottle) or the bottom side (i.e., the side closest to the bottom of the bottle) of the flexible drip prevention film, and it is also easier to attach the flexible drip prevention film back onto the double-sided tape.

(21) The flexible drip prevention film **12** may be made of a material including polyethylene terephthalate, and thus, the flexible drip prevention film **12** has a relatively low surface tension to prevent beverage drip when it is used to pour beverage. Furthermore, the flexible drip prevention film **12** being a PET film is favorable for the flexible drip prevention film **12** to be easily rolled into a cylindrical tube to be inserted into the mouth **7** of the beverage container **9**. In addition, the flexible drip prevention film **12** may have high tearing resistance and alcohol/chemical resistance, so that the flexible drip prevention film **12** may not deteriorate or be damaged when it is in contact with alcohol or juice. Moreover, the flexible drip prevention film **12** can be cleaned/rinsed for sanitary and reuse purposes. In this embodiment, the flexible drip prevention film **12** is translucent, but the present disclosure is not limited thereto. In other embodiments, the flexible drip prevention film may be transparent or opaque.

(22) The ink material of the label pattern may be a synthetic ink specially formulated for polyethylene terephthalate material, so that the label pattern may have high alcohol/chemical resistance and may have good scratch resistance to ensure that the label pattern does not easily peel off from the flexible drip prevention film **12**. In this embodiment, the label pattern is, for example, halogen-free and meets U.S. Food and Drug Administration (FDA) requirements.

(23) In this embodiment, the label member **1** is in an elliptical shape, but the present disclosure is not limited thereto. In other embodiments, the label member may be in other shapes, such as circular or rectangular shapes, according to actual design requirements.

(24) The present disclosure is not limited to the position where the label member **1** is attached to the bottle **8** in the first embodiment. In other embodiments, the label member may be attached to the neck or bottom of the bottle according to actual design requirements.

(25) Please refer to FIG. **4**, which is an exploded view of a label member in accordance with the second embodiment of the present disclosure.

(26) In this embodiment, a label member **1b** is provided. The label member **1b** includes a double-sided tape **11b**, a flexible drip prevention film **12b** and a release liner **13b**. The structures and corresponding effects of the double-sided tape **11b** and the flexible drip prevention film **12b** are substantially the same or similar to those of the double-sided tape **11** and the flexible drip prevention film **12** as described in the first embodiment, and thus, an explanation in this regard will not be provided again.

(27) The release liner **13b** is, for example, a glassine release paper, and the release liner **13b** is removably attached to a first adhesive surface GS1 of the double-sided tape **11b**. Before the label member **1b** is attached to a beverage container, the first adhesive surface GS1 of the double-sided tape **11b** should be covered by the release liner **13b** to prevent the first adhesive surface GS1 from accidentally adhering to alien objects during manufacturing processes or shipping of the label member **1b**. Moreover, before the attachment of the label member **1b** to the bottle of the beverage container, the release liner **13b** should be removed from the first adhesive surface GS1 of the double-sided tape **11b** in advance, so that the first adhesive surface GS1 can be attached to the

bottle.

(28) Please refer to FIG. 5, which is an exploded view of a label member in accordance with the third embodiment of the present disclosure.

(29) In this embodiment, a label member **1c** is provided. The label member **1c** includes a double-sided tape **11c**, a flexible drip prevention film **12c**, a release liner **13c** and a temperature authentication pattern **14c**. The structures and corresponding effects of the double-sided tape **11c**, the flexible drip prevention film **12c** and the release liner **13c** are substantially the same or similar to those of the double-sided tape **11** and the flexible drip prevention film **12** as described in the first embodiment and those of the release liner **13b** as described in the second embodiment, and thus, an explanation in this regard will not be provided again.

(30) In this embodiment, the double-sided tape **11c** and the flexible drip prevention film **12c** are transparent or translucent, the temperature authentication pattern **14c** is formed on the first adhesive surface GS1 of the double-sided tape **11c** by, for example, printing, and the temperature authentication pattern **14c** may change to a marked state permanently from an unmarked state once the temperature of the temperature authentication pattern **14c** is equal to or higher than a predetermined temperature. Therefore, when the label member **1c** is attached to a bottle of a beverage container after the release liner **13c** had been removed from the label member **1c**, consumers and store salesmen can identify whether the beverage is exposed to the environment of a predetermined temperature or higher temperature or not during shipping or in storage, thereby preventing spoiled products from being purchased by the consumers. Moreover, the temperature authentication pattern **14c** in the marked state may appear any desired words or patterns, and the present disclosure is not limited thereto. Said the temperature authentication pattern **14c** changing to a marked state from an unmarked state may become visible from transparent as an example.

(31) Please refer to FIG. 6, which is an exploded view of a label member in accordance with the fourth embodiment of the present disclosure.

(32) In this embodiment, a label member **1d** is provided. The label member **1d** includes a double-sided tape **11d**, a flexible drip prevention film **12d**, a release liner **13d** and a tamper-proof layer **15d**. The structures and corresponding effects of the double-sided tape **11d**, the flexible drip prevention film **12d** and the release liner **13d** are substantially the same or similar to those of the double-sided tape **11** and the flexible drip prevention film **12** as described in the first embodiment and those of the release liner **13b** as described in the second embodiment, and thus, an explanation in this regard will not be provided again.

(33) In this embodiment, the tamper-proof layer **15d** is, for example, an acrylic adhesive and disposed on the first adhesive surface GS1 of the double-sided tape **11d**, and the tamper-proof layer **15d** is configured to be at least partially irremovably fixed to a bottle of a beverage container. Therefore, when the label member **1d** is attached to the bottle of the beverage container after the release liner **13d** had been removed from the label member **1d**, the tamper-proof layer **15d** is at least partially irremovably fixed to the bottle, such that when a consumer removes the label member **1d** from the bottle, the tamper-proof layer **15d** leaves indications on the bottle. Therefore, the label member **1d** or the beverage container can be prevented from being tampered or reused inappropriately. Said indications left on the bottle by the tamper-proof layer **15d** may be any patterns or words, and the present disclosure is not limited thereto.

(34) Please refer to FIG. 7, which is an exploded view of a label member in accordance with the fifth embodiment of the present disclosure.

(35) In this embodiment, a label member **1e** is provided. The label member **1e** includes a double-sided tape **11e**, a flexible drip prevention film **12e**, a temperature authentication pattern **14e**, a tamper-proof layer **15e** and a release liner **13e**. The structures and corresponding effects of the components are substantially the same or similar to those of the corresponding components as described in the above embodiments, and thus, an explanation in this regard will not be provided again.

(36) Please refer to FIG. 8, which is an exploded view of a label member in accordance with the sixth embodiment of the present disclosure.

(37) In this embodiment, a label member 1f is provided. The label member 1f includes a double-sided tape 11f, a flexible drip prevention film 12f, a temperature authentication film 16f, a tamper-proof layer 15f and a release liner 13f. The structures and corresponding effects of the double-sided tape 11f, the flexible drip prevention film 12f, and the release liner 13f are substantially the same or similar to those of the corresponding components as described in the above embodiments, and thus, an explanation in this regard will not be provided again.

(38) In this embodiment, the tamper-proof layer 15f has a through hole 150f. The shape and size of the temperature authentication film 16f are substantially the same as those of the through hole 150f, and the thickness of the tamper-proof layer 15f may be equal to that of the temperature authentication film 16f. The temperature authentication film 16f is located in the through hole 150f and attached to the first adhesive surface GS1 of the double-sided tape 11f. The double-sided tape 11f and the flexible drip prevention film 12f are transparent or translucent. A temperature authentication pattern 14f is formed on the temperature authentication film 16f by, for example, printing, and the temperature authentication pattern 14f is visible through the double-sided tape 11f and the flexible drip prevention film 12f. The temperature authentication pattern 14f is configured to change to a marked state permanently from an unmarked state once the temperature of the temperature authentication pattern 14f is equal to or higher than a predetermined temperature. Moreover, the temperature authentication pattern 14f may be any words or patterns, and the present disclosure is not limited thereto. Said the temperature authentication pattern 14f changing to a marked state from an unmarked state may become visible from transparent as an example.

(39) In this embodiment, the temperature authentication film 16f and the tamper-proof layer 15f of the label member 1f are formed in the same layer, such that the whole label member 1f has a relatively even thickness so as to ensure the flatness of the label member 1f.

(40) In this embodiment, the temperature authentication film 16f and the tamper-proof layer 15f are formed in the same layer, but the present disclosure is not limited thereto. In other embodiments, a through hole may be formed on the double-sided tape, and the temperature authentication film may be located in the through hole of the double-sided tape and attached to the tamper-proof layer, such that the temperature authentication film and the double-sided tape are formed in the same layer.

(41) Please refer to FIG. 9 and FIG. 10, where FIG. 9 is a perspective view of a label member in accordance with the seventh embodiment of the present disclosure, and FIG. 10 is an exploded view of the label member in FIG. 9.

(42) In this embodiment, a label member 1g is provided. The label member 1g includes a composite tape CT, a flexible drip prevention film 12g and a release liner 13g. The composite tape CT includes a double-sided adhesive area and a single-sided adhesive area. The double-sided adhesive area may be a double-sided tape 11g, and the single-sided adhesive area may be a single-sided tape 17g. Moreover, the structures and corresponding effects of the double-sided tape 11g, the flexible drip prevention film 12g and the release liner 13g are substantially the same or similar to those of the double-sided tape 11 and the flexible drip prevention film 12 as described in the first embodiment and the release liner 13b as described in the second embodiment, and thus, an explanation in this regard will not be provided again.

(43) The single-sided tape 17g is connected at least a part of a periphery of the double-sided tape 11g. The single-sided tape 17g has a single side adhesive surface GS3 configured to be attached to a bottle.

(44) The release liner 13g is removably attached to the first adhesive surface GS1 of the double-sided tape 11g and the single side adhesive surface GS3 of the single-sided tape 17g. Before the label member 1g is attached to a beverage container, the first adhesive surface GS1 of the double-sided tape 11g and the single side adhesive surface GS3 of the single-sided tape 17g should be covered by the release liner 13g to prevent the first adhesive surface GS1 and the single side

adhesive surface GS3 from accidentally adhering to alien objects during manufacturing processes or shipping of the label member **1g**. Moreover, before the attachment of the label member **1g** to the bottle of the beverage container, the release liner **13g** should be removed from the first adhesive surface GS1 of the double-sided tape **11g** and the single side adhesive surface GS3 of the single-sided tape **17g** in advance, so that the first adhesive surface GS1 and the single side adhesive surface GS3 can be attached to the bottle.

(45) The flexible drip prevention film **12g** is removably attached to the second adhesive surface GS2 of the double-sided adhesive area (i.e., the double-sided tape **11g**) of the composite tape CT, and at least a part of the flexible drip prevention film **12g** extends beyond the edge of the second adhesive surface GS2.

(46) In this embodiment, the edge of the flexible drip prevention film **12g** may be flush with the edge of the composite tape CT, and thus does not extend beyond the edge of the composite tape CT. However, at least a part of the flexible drip prevention film **12g** extends beyond the edge of the second adhesive surface GS2 of the double-sided tape **11g**, such that a part of the flexible drip prevention film **12g** overlapping the single-sided tape **17g** is not adhered to the composite tape CT. Therefore, it is easier for the consumer to grip the flexible drip prevention film **12g** to remove the flexible drip prevention film **12g** from the composite tape CT. However, the present disclosure is not limited thereto. For example, in other embodiments, there may be a part of the flexible drip prevention film extending beyond the edge of the composite tape, or the whole periphery of the flexible drip prevention film may extend beyond the edge of the composite tape.

(47) In this embodiment, the single-sided tape **17g** is connected to a part of the periphery of the double-sided tape **11g** and located on one side of the double-sided tape **11g**, but the present disclosure is not limited thereto. In other embodiments, the single-sided tape may surround the periphery of the double-sided tape.

(48) In view of the above description, the flexible drip prevention film of the label member is removable from the double-sided tape, and the flexible drip prevention film after being removed from the double-sided tape can be rolled into a cylindrical tube to be inserted into the mouth of the beverage container for fluid guidance and drip prevention. Therefore, when a consumer pours fluid from the bottle of the beverage container, the flexible drip prevention film can guide the fluid and prevent the fluid from dripping or flowing down along the bottle from the mouth. In addition, at least a part of the flexible drip prevention film extends beyond the edge of the second adhesive surface of the double-sided tape, such that the consumer can easily grip the part of the flexible drip prevention film extending beyond the double-sided tape to pull and remove the flexible drip prevention film from the double-sided tape. Consumer can also easily adhere the flexible drip prevention film back to the second adhesive surface without exposing adhesive.

(49) In some configurations, a label pattern is printed on the flexible drip prevention film for showing product information, such as brand or contents.

(50) In some configurations, the stickiness of the first adhesive layer of the double-sided tape is greater than that of the second adhesive layer of the double-sided tape. Therefore, when the consumer pulls the flexible drip prevention film to remove the flexible drip prevention film, the double-sided tape will not unexpectedly remove from the bottle as well. Moreover, the second adhesive layer enables the flexible drip prevention film to be removed from and attached back to the second adhesive surface of the double-sided tape repeatedly, such that the consumer may remove the flexible drip prevention film from the mouth and attach the flexible drip prevention film back onto the double-sided tape on the bottle. Therefore, it is convenient for the consumer to reuse the flexible drip prevention film without losing or getting the flexible drip prevention film dirty unexpectedly.

(51) The embodiments were chosen and described in order to best explain the principles of the disclosure and its practical applications, to thereby enable others skilled in the art to best utilize the disclosure and various embodiments with various modifications as are suited to the particular use

contemplated. It is intended that the scope of the disclosure be defined by the following claims and their equivalents.

Claims

1. A label member configured to be partially removably attached to a bottle of a beverage container, and the label member comprising: a double-sided tape having a first adhesive surface and a second adhesive surface that are located opposite to each other, and the first adhesive surface configured to be attached to the bottle; and a flexible drip prevention film removably attached to the second adhesive surface of the double-sided tape, and the flexible drip prevention film configured to be rollable into a cylindrical tube to be inserted into a mouth of the beverage container after being removed from the double-sided tape; wherein at least a part of the flexible drip prevention film extends beyond an edge of the second adhesive surface of the double-sided tape, and a surface of the flexible drip prevention film facing the double-sided tape only partially contacts the double-sided tape; wherein the label member further comprises a single-sided tape connected to at least a part of a periphery of the double-sided tape, and the single-sided tape has a single side adhesive surface configured to be attached to the bottle.
2. A beverage container comprising: a bottle; and the label member according to claim 1.
3. A label member configured to be partially removably attached to a bottle of a beverage container, and the label member comprising: a double-sided tape having a first adhesive surface and a second adhesive surface that are located opposite to each other, and the first adhesive surface configured to be attached to the bottle; and a flexible drip prevention film removably attached to the second adhesive surface of the double-sided tape, and the flexible drip prevention film configured to be rollable into a cylindrical tube to be inserted into a mouth of the beverage container after being removed from the double-sided tape; wherein at least a part of the flexible drip prevention film extends beyond an edge of the second adhesive surface of the double-sided tape, and a surface of the flexible drip prevention film facing the double-sided tape only partially contacts the double-sided tape; wherein the double-sided tape comprises a first adhesive layer, a second adhesive layer, and an intermediate layer located between the first adhesive layer and the second adhesive layer, the first adhesive layer and the second adhesive layer are PET-based adhesive layers, the intermediate layer is a polyester film, the first adhesive surface is located at the first adhesive layer, the second adhesive surface is located at the second adhesive layer, and a stickiness of the first adhesive layer is greater than a stickiness of the second adhesive layer.
4. The label member according to claim 3, further comprising a release liner removably attached to the first adhesive surface.
5. The label member according to claim 3, wherein a label pattern is printed on the flexible drip prevention film.
6. The label member according to claim 5, wherein the label pattern is made of a material comprising polyethylene terephthalate (PET).
7. The label member according to claim 3, wherein the flexible drip prevention film is made of a material comprising polyethylene terephthalate.
8. The label member according to claim 3, further comprising a temperature authentication pattern, wherein the double-sided tape and the flexible drip prevention film are transparent or translucent, the temperature authentication pattern is formed on the first adhesive surface of the double-sided tape, and the temperature authentication pattern is configured to change to a marked state from an unmarked state once a temperature of the temperature authentication pattern is equal to or higher than a predetermined temperature.
9. The label member according to claim 3, further comprising a tamper-proof layer disposed on the first adhesive surface of the double-sided tape, wherein the tamper-proof layer is configured to be at least partially irremovably fixed to the bottle.

10. The label member according to claim 9, wherein the tamper-proof layer is an acrylic adhesive.
11. The label member according to claim 9, further comprising a temperature authentication film, wherein the tamper-proof layer has a through hole, the temperature authentication film is located in the through hole and attached to the first adhesive surface of the double-sided tape, the double-sided tape and the flexible drip prevention film are transparent or translucent, a temperature authentication pattern is formed on the temperature authentication film, the temperature authentication pattern is visible through the double-sided tape and the flexible drip prevention film, and the temperature authentication pattern is configured to change to a marked state from an unmarked state once a temperature of the temperature authentication pattern is equal to or higher than a predetermined temperature.
12. A beverage container comprising: a bottle; and a label member comprising: a double-sided tape having a first adhesive surface and a second adhesive surface that are located opposite to each other, and the first adhesive surface attached to the bottle; and a flexible drip prevention film removably attached to the second adhesive surface of the double-sided tape, and the flexible drip prevention film configured to be rollable into a cylindrical tube to be inserted into a mouth of the beverage container after being removed from the double-sided tape; wherein at least a part of the flexible drip prevention film extends beyond an edge of the second adhesive surface of the double-sided tape, and a surface of the flexible drip prevention film facing the double-sided tape only partially contacts the double-sided tape; wherein the double-sided tape comprises a first adhesive layer, a second adhesive layer, and an intermediate layer located between the first adhesive layer and the second adhesive layer, the first adhesive layer and the second adhesive layer are PET-based adhesive layers, the intermediate layer is a polyester film, the first adhesive surface is located at the first adhesive layer, the second adhesive surface is located at the second adhesive layer, and a stickiness of the first adhesive layer is greater than a stickiness of the second adhesive layer.
13. The beverage container according to claim 12, wherein a label pattern is printed on the flexible drip prevention film.
14. The beverage container according to claim 13, wherein the label pattern is made of a material comprising polyethylene terephthalate.
15. The beverage container according to claim 12, wherein the flexible drip prevention film is made of a material comprising polyethylene terephthalate.
16. The beverage container according to claim 12, wherein the label member further comprises a temperature authentication pattern, the double-sided tape and the flexible drip prevention film are transparent or translucent, the temperature authentication pattern is formed on the first adhesive surface of the double-sided tape, and the temperature authentication pattern is configured to change to a marked state from an unmarked state once a temperature of the temperature authentication pattern is equal to or higher than a predetermined temperature.
17. The beverage container according to claim 12, wherein the label member further comprises a tamper-proof layer disposed on the first adhesive surface of the double-sided tape, and the tamper-proof layer is configured to be at least partially irremovably fixed to the bottle.
18. The beverage container according to claim 17, wherein the tamper-proof layer is an acrylic adhesive.
19. The beverage container according to claim 17, wherein the label member further comprises a temperature authentication film, the tamper-proof layer has a through hole, the temperature authentication film is located in the through hole and attached to the first adhesive surface of the double-sided tape, the double-sided tape and the flexible drip prevention film are transparent or translucent, a temperature authentication pattern is formed on the temperature authentication film, the temperature authentication pattern is visible through the double-sided tape and the flexible drip prevention film, and the temperature authentication pattern is configured to change to a marked state from an unmarked state once a temperature of the temperature authentication pattern is equal to or higher than a predetermined temperature.

20. The beverage container according to claim 12, wherein a reference curved line is defined to be located at a surface of the flexible drip prevention film and pass through a center of the flexible drip prevention film, the reference curved line is parallel to a circumferential direction of the bottle, and the reference curved line passes through the at least a part of the flexible drip prevention film extending beyond the edge of the second adhesive surface.
