

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396709
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Thiagarajan; Naveenan et al.

Ultrasound probe and method of making the same

Abstract

An ultrasound probe is presented. The ultrasound probe includes an ultrasound probe handle. Moreover, the ultrasound probe also includes a phase change chamber monolithic with respect to a portion of the ultrasound probe handle, where the phase change chamber includes hermetic chamber walls extending around and defining an enclosed chamber and a material disposed within the hermetic chamber walls, where the material is configured to change phase in response to heat from a component of the ultrasound probe.

Inventors: Thiagarajan; Naveenan (Niskayuna, NY), Lee; Warren (Niskayuna, NY), Rush; Brian Magann (Niskayuna, NY)

Applicant: General Electric Company (Schenectady, NY)

Family ID: 1000008782289

Assignee: GENERAL ELECTRIC COMPANY (Schenectady, NY)

Appl. No.: 16/212863

Filed: December 07, 2018

Prior Publication Data

Document Identifier	Publication Date
US 20200178941 A1	Jun. 11, 2020

Publication Classification

Int. Cl.: A61B8/00 (20060101); B33Y10/00 (20150101); G01N29/22 (20060101); G01N29/32 (20060101)

U.S. Cl.:

CPC **A61B8/546** (20130101); **A61B8/4455** (20130101); **A61B8/4483** (20130101); **A61B8/56** (20130101); **B33Y10/00** (20141201); **G01N29/226** (20130101); **G01N29/326** (20130101);

Field of Classification Search

CPC: A61B (8/4444); A61B (8/4455); A61B (8/4483); A61B (8/546); A61B (8/56); B33Y (10/00); G01N (29/226); G01N (29/326)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5213103	12/1992	Martin et al.	N/A	N/A
5545942	12/1995	Jaster	310/341	G10K 11/004
5560362	12/1995	Sliwa, Jr.	600/459	G10K 11/004
5721463	12/1997	Snyder	N/A	N/A
5961465	12/1998	Kelly, Jr.	600/459	A61B 8/546
7105986	12/2005	Wildes et al.	N/A	N/A
7314447	12/2007	Park et al.	N/A	N/A
2006/0191344	12/2005	Hashimoto	73/632	A61B 8/546
2011/0018395	12/2010	Ruffa	310/334	B06B 1/0618
2011/0301508	12/2010	Sethuraman	601/2	A61N 7/022
2012/0060610	12/2011	Oaks	73/632	A61B 8/4444
2013/0303918	12/2012	Miyajima	600/459	A61B 8/4444
2015/0289413	12/2014	Rush et al.	N/A	N/A
2016/0077059	12/2015	Chung	73/620	G01N 29/2406
2017/0020490	12/2016	Ryu	N/A	A61B 8/4427
2017/0043189	12/2016	Stoddard	N/A	G10K 11/24
2017/0065259	12/2016	Pinch	N/A	A61B 8/546
2017/0164926	12/2016	Spicci et al.	N/A	N/A
2018/0125461	12/2017	Clark et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1707122	12/2009	EP	N/A
2017027654	12/2016	WO	N/A

OTHER PUBLICATIONS

PCT application PCT/US2019/064822 filed Dec. 6, 2019; International Search Report/Written Opinion issued Mar. 27, 2020, 10 pages. cited by applicant

Saunders et al., “Ultrasound transducer self heating: development of 3-D finite-element models”, Journal of Physics Conference Series, pp. 72-77, Aug. 2004. cited by applicant

Chabok et al., “Ultrasound Transducer Array Fabrication Based on Additive Manufacturing of Piezocomposites”, ASME/ISCIE 2012 International Symposium on Flexible Automation, pp. 433-444, Jun. 2012. cited by applicant

Patankar et al., “A time-stepping analytical model for 3D transient vapor chamber transport”, 2017 16th IEEE Intersociety Conference on Thermal and Thermomechanical Phenomena in Electronic Systems (ITherm), pp. 1075-1087, Orlando, Jun. 2017. cited by applicant

Primary Examiner: Buran; Ashley K

Assistant Examiner: Talty; Maria Christina

Attorney, Agent or Firm: McCoy Russell LLP

Background/Summary

BACKGROUND

(1) Embodiments of the present specification generally relate to ultrasound imaging and more specifically to an ultrasound probe having a thermal management assembly and a method of making the same.

(2) Ultrasound imaging provides a relatively inexpensive method of imaging. During the process of ultrasound scanning, a clinician attempts to capture a view of a certain anatomy which confirms or negates a particular medical condition. Once the clinician is satisfied with the quality of a view or a scan plane, the image is frozen to proceed to a measurement phase.

(3) Recent developments in ultrasound imaging have led to current state of the art ultrasound devices that boast of relatively high image resolutions and ease of use. These developments have in turn led to increased use of ultrasound for clinical research as well as day to day point of care practice. Consequently, the use of ultrasound imaging has been steadily increasing over the years. Moreover, the improved ultrasound technology has led to higher frequency ultrasound probes that are well-suited for imaging relatively shallow anatomical structures, as is generally the case for musculoskeletal imaging.

(4) Notwithstanding the various advantages of ultrasound, an important factor that restricts the use of ultrasound has been the fact that performing ultrasound scanning requires extended operation of an ultrasound probe at high power to render higher image resolution, while maintaining the surface and key component temperatures under their respective limits. Many of the currently available advanced probes are limited thermally owing to the limited surface area available for convection and numerous interfaces in the conductive heat transfer path from the heat dissipating internal components of the probe to the surface of the probe.

(5) Some conventional approaches to ultrasound probe design to improve conductive heat transfer internal to the probe entail use of heat pipes along a heat spreader bonded to a plastic housing. This design of the probe disadvantageously leads to multiple parts and interfaces. Certain other currently available probes include conventional heat pipes that are incorporated with the probes. However, these probes can offer only incremental gains in thermal performance at a cost of significantly increased complexity and part count.

BRIEF DESCRIPTION

(6) In accordance with aspects of the present specification, an ultrasound probe is presented. The ultrasound probe includes an ultrasound probe handle. Moreover, the ultrasound probe also includes a phase change chamber monolithic with respect to a portion of the ultrasound probe handle, where the phase change chamber includes hermetic chamber walls extending around and defining an enclosed chamber and a material disposed within the hermetic chamber walls, where the material is configured to change phase in response to heat from a component of the ultrasound probe.

(7) In accordance with another aspect of the present specification, an imaging system is presented. The imaging system includes an acquisition subsystem configured to acquire image data corresponding to a subject, where the acquisition subsystem includes an ultrasound probe including an ultrasound probe handle and a phase change chamber monolithic with respect to a portion of the

ultrasound probe handle, where the phase change chamber includes hermetic chamber walls extending around and defining an enclosed chamber and a material disposed within the hermetic chamber walls, where the material is configured to change phase in response to heat from a component of the ultrasound probe. In addition, the imaging system includes a processing subsystem in operative association with the acquisition subsystem and configured to process the image data to generate one or more images corresponding to the subject.

(8) In accordance with yet another aspect of the present specification, a method is presented. The method includes additively fabricating first and second segments of an ultrasound probe handle, where at least one of the first and second segments includes a phase change chamber monolithic with respect to the respective segment and including hermetic chamber walls extending around and defining an enclosed chamber, and a material disposed within the hermetic chamber walls, and where the material is configured to change phase in response to heat from one or more components of the ultrasound probe. Furthermore, the method includes operatively coupling the first and second segments.

Description

DRAWINGS

(1) These and other features, aspects, and advantages of the present disclosure will become better understood when the following detailed description is read with reference to the accompanying drawings in which like characters represent like parts throughout the drawings, wherein:

(2) FIG. 1 is a diagrammatical illustration of a system for ultrasound imaging, in accordance with aspects of the present specification;

(3) FIGS. 2-5 are diagrammatical illustrations of different embodiments of an ultrasound probe having various configurations of a thermal management assembly in the form of a phase change chamber, where the ultrasound probe is configured for use in the system of FIG. 1, in accordance with aspects of the present specification;

(4) FIGS. 6-9 are cross-sectional views of different embodiments of an ultrasound probe having various configurations of a thermal management assembly in the form of a phase change chamber, where the ultrasound probe is configured for use in the system of FIG. 1, in accordance with aspects of the present specification;

(5) FIG. 10 is a diagrammatical illustration of an ultrasound imaging system for use in the system of FIG. 1; and

(6) FIG. 11 is a flow chart depicting a method for manufacturing an ultrasound probe having an exemplary phase change chamber, in accordance with aspects of the present specification.

DETAILED DESCRIPTION

(7) Ultrasound imaging is being increasingly used to image anatomical regions of interest in a patient. As will be appreciated, an important factor that restricts the use of ultrasound at high power to render higher image resolution is the requirement to maintain the surface and key component temperatures under their respective limits. Systems and methods of the present application present an exemplary design of a three-dimensional (3D) phase change chamber that is configured to provide a thermal management structure for an ultrasound probe. The phase change chamber may be in the form of a 3D vapor chamber (VC), a thermal energy storage chamber, or a combination thereof. Also, the phase change chamber provides enhanced heat transport from internal heat generating components of the ultrasound probe to an outer surface of the phase change chamber for cooling by the ambient environment and/or to phase change material volumes for thermal energy absorption and storage. Additionally, the phase change chamber may also be configured to provide a mechanical support structure for the ultrasound probe.

(8) It may be noted that although the various systems and methods are described in the context of a

medical imaging system, these systems and methods may also be used in the imaging of non-living objects such as but not limited to pipes, tubes, luggage, packages, and the like.

(9) FIG. 1 is a block diagram of an exemplary system **100** for use in diagnostic imaging, in accordance with aspects of the present specification. More particularly, the system **100** is configured to aid a clinician in imaging a patient **102** to deliver consistent clinical outcomes.

(10) During imaging, the clinician typically positions an image acquisition device on or about a region of interest in a patient **102** being imaged. In one example, the patient **102** may be positioned in a supine position on a patient support **106**. Furthermore, an image acquisition device **104** that is operatively coupled to a medical imaging system **108** may be used to acquire image data corresponding to an object or a region of interest in the patient **102**. In one embodiment, the image acquisition device **104** may be a probe configured to acquire image data corresponding to one or more anatomical regions of interest in the patient **102**.

(11) In a presently contemplated configuration, the system **100** may be configured to acquire image data representative of the patient **102** via the image acquisition device **104**. Also, in one embodiment, the probe **104** may include an invasive probe or a non-invasive or external probe, such as an external ultrasound probe, that is configured to aid in the acquisition of image data. In one example, the image acquisition device **104** may include a two-dimensional (2D) or a three-dimensional (3D) ultrasound probe. Additionally, the probe **104** may be a wired probe or a wireless probe. Also, in certain other embodiments, image data may be acquired via one or more sensors (not shown) that may be disposed on the patient **102**. By way of example, the sensors may include physiological sensors (not shown) such as positional sensors. In some embodiments, the positional sensors may include electromagnetic field sensors or inertial sensors. These sensors may be operatively coupled to a data acquisition device, such as an imaging system, via leads (not shown), for example.

(12) It may also be noted that although the embodiments illustrated herein are described in the context of an ultrasound probe, other types of probes such as endoscopes, laparoscopes, surgical probes, probes adapted for interventional procedures, or combinations thereof are also contemplated in conjunction with the present specification. An external probe may also be employed in situations where a user such as a sonographer guiding an imaging procedure is located at a remote location and therefore unable to see the probe or the patient **102**.

(13) Furthermore, in one example, the acquired image data may include a two-dimensional (2D)) B-mode ultrasound image. Also, in certain embodiments, the image data may include pre-scan-converted or radio frequency (RF) ultrasound data. Additionally, the 2D images may include static 2D images or cine loops that include a series of 2D images or image frames acquired over time. It may be noted that the acquired image data may include 2D ultrasound images, 3D ultrasound images, four-dimensional (4D) ultrasound images, or combinations thereof. Other modes of ultrasound imaging such as Doppler modes of ultrasound imaging may also be used to acquired image data. Some non-limiting examples of the Doppler modes of ultrasound imaging include color, pulsed wave, continuous wave, power doppler, and the like.

(14) Additionally, in one example, the medical imaging system **108** is an ultrasound imaging system. The ultrasound imaging system **108** is in operative association with the image acquisition device **104** and is configured to receive ultrasound image data corresponding to the patient **102** and process the ultrasound image data to generate one or more images corresponding to the patient **102**.

(15) It should be noted that although the exemplary embodiments illustrated hereinafter are described in the context of a medical imaging system, other imaging systems and applications such as industrial imaging systems and non-destructive evaluation and inspection systems, such as pipeline inspection systems, liquid reactor inspection systems, are also contemplated. Additionally, the exemplary embodiments illustrated and described hereinafter may find application in multi-modality imaging systems that employ ultrasound imaging in conjunction with other imaging modalities, position-tracking systems or other sensor systems. In one example, the multi-modality

imaging system may include a positron emission tomography (PET) imaging system-ultrasound imaging system. Furthermore, in other non-limiting examples of the multi-modality imaging systems, the ultrasound imaging system may be used in conjunction with other imaging systems, such as, but not limited to, a computed tomography (CT) imaging system, a contrast enhanced ultrasound imaging system, an X-ray imaging system, an optical imaging system, a magnetic resonance (MR) imaging system, an optical imaging system, virtual/augmented reality imaging systems, and other imaging systems, in accordance with aspects of the present specification.

(16) As noted hereinabove, in a presently contemplated configuration, the medical imaging system **108** is an ultrasound imaging system. Further, the medical imaging system **108** may include an acquisition subsystem **110** and a processing subsystem **112**, in one embodiment. Moreover, the acquisition subsystem **110** of the medical imaging system **108** is configured to receive image data representative of the patient **102** from the image acquisition device **104**, in one embodiment. For example, the acquired image data may include a plurality of 2D ultrasound images or slices. In other embodiments, 3D images or 4D images may be acquired. It may be noted that the terms images and image frames may be used interchangeably.

(17) In addition, the acquisition subsystem **110** may also be configured to acquire images stored in the optical data storage article. It may be noted that the optical data storage article may be an optical storage medium, such as a compact disc (CD), a digital versatile disc (DVD), multi-layer structures, such as DVD-5 or DVD-9, multi-sided structures, such as DVD-10 or DVD-18, a high definition digital versatile disc (HD-DVD), a Blu-ray disc, a near field optical storage disc, a holographic storage medium, or another like volumetric optical storage medium, such as, for example, two-photon or multi-photon absorption storage format. Further, the 2D images so acquired by the acquisition subsystem **110** may be stored locally on the medical imaging system **108** in a data repository **116**, for example.

(18) Moreover, the image data acquired from the patient **102** may then be processed by the processing subsystem **112**. The processing subsystem **112**, for example, may include one or more application-specific processors, graphical processing units, digital signal processors, microcomputers, microcontrollers, Application Specific Integrated Circuits (ASICs), Field Programmable Gate Arrays (FPGAs), Programmable Logic Arrays (PLAs), and/or other suitable processing devices. Alternatively, the processing subsystem **112** may be configured to store the acquired image data and/or the user input in the data repository **116** for later use. In one embodiment, the data repository **116**, for example, may include a hard disk drive, a floppy disk drive, a compact disk-read/write (CD-R/W) drive, a Digital Versatile Disc (DVD) drive, a flash drive, and/or a solid-state storage device.

(19) The image data acquired and/or processed by the medical imaging system **108** may be employed to generate an ultrasound image that is used to aid a clinician in making measurements and/or providing a diagnosis based on the generated image. In certain embodiments, the processing subsystem **112** may be further coupled to a storage system, such as the data repository **116**, where the data repository **116** is configured to store the generated image(s). In certain embodiments, the data repository **116** may include a local database.

(20) Moreover, as illustrated in FIG. **1**, the medical imaging system **108** may include a display **118** and a user interface **120**. In certain embodiments, such as in a touch screen, the display **118** and the user interface **120** may overlap. Also, in some embodiments, the display **118** and the user interface **120** may include a common area. In accordance with aspects of the present specification, the display **118** of the medical imaging system **108** may be configured to display an image generated by the medical imaging system **108** based on the acquired image data.

(21) In addition, the user interface **120** of the medical imaging system **108** may include a human interface device (not shown) configured to aid the clinician in manipulating image data displayed on the display **118**. The human interface device may include a mouse-type device, a trackball, a joystick, a stylus, or a touch screen configured to facilitate the clinician to identify the one or more

regions of interest in the images. However, as will be appreciated, other human interface devices, such as, but not limited to, a touch screen, may also be employed. Furthermore, in accordance with aspects of the present specification, the user interface **120** may be configured to aid the clinician in navigating through the images acquired by the medical imaging system **108**. Additionally, the user interface **120** may also be configured to aid in manipulating and/or organizing the displayed images and/or generated indicators displayed on the display **118**.

(22) As noted hereinabove, an important factor that restricts the use of ultrasound has been the fact that performing ultrasound scanning requires extended operation of an ultrasound probe at high power to render higher image resolution, while maintaining the surface and key component temperatures under their respective limits. FIG. **2** presents an exemplary design of a structure configured for use in an ultrasound probe such as the ultrasound probe **104** of FIG. **1** that circumvents the shortcomings of the presently available ultrasound probes. More particularly, an exemplary design of a 3D thermal management assembly or structure in the form of a phase change chamber that is configured to provide enhanced thermal management for an ultrasound probe is presented. The exemplary phase change chamber may also be configured to simultaneously provide mechanical support to the various components of the ultrasound probe **104**.

(23) Referring now to FIG. **2**, a diagrammatical illustration **200** of one embodiment of an ultrasound probe for use in the system **100** of FIG. **1** is depicted. FIG. **2** is described in conjunction with the components of FIG. **1**.

(24) The ultrasound probe **200** includes an ultrasound probe handle **202**. In one embodiment, the ultrasound probe handle **202** may include two or more segments that are operatively coupled to one another. In the example depicted in FIG. **2**, the ultrasound probe handle **202** is depicted as having a first segment **204** and a second segment **206**. Also, in FIG. **2**, each segment **204**, **206** is representative of one half of the ultrasound probe handle **202**. It may be noted that in accordance with further aspects of the present specification, use of a single segment or other number of segments for the ultrasound probe handle **202** is also envisaged.

(25) Further, the ultrasound probe **200** includes a thermal management assembly in the form of a phase change chamber **208** that is configured to provide enhanced thermal management for the ultrasound probe **200**. The reference number **208** shown in FIG. **2** refers to the interior of the chamber. In particular, the phase change chamber **208** is monolithic with respect to a portion of the ultrasound probe handle **202**. The phase change chamber **208** is a monolithic structure configured to thermally interface with one or more heat generating components in the ultrasound probe **200** to dissipate the heat generated by the components of the ultrasound probe **200**. In one embodiment, the phase change chamber **208** is thermally coupled to one or more components of the ultrasound probe **200** to facilitate dissipation of heat from the heat generating components of the ultrasound probe **200**. Moreover, in certain embodiments, the phase change chamber **208** may include two or more phase change chambers. Further, in certain embodiments, the phase change chamber **208** extends along at least a portion of a wall of the ultrasound probe handle **202**. In other embodiments, the phase change chamber **208** forms at least a portion of a wall of the ultrasound probe handle **202**.

(26) In one embodiment, the phase change chamber is a three-dimensional (3D) vapor chamber **208**. Additionally, the 3D vapor chamber **208** extends along at least two orthogonal directions. Furthermore, the embodiment illustrated in FIG. **2** depicts the phase change chamber **208** as including two 3D vapor chambers. Each 3D vapor chamber **208** corresponds to a segment **204**, **206** of the ultrasound probe handle **202**. As will be appreciated, the 3D vapor chamber **208** is a heat transfer device that is vacuum sealed. Further, the 3D vapor chamber **208** typically includes an evaporator end and a condenser end. In addition, as depicted in the embodiment of FIG. **2**, each of the 3D vapor chambers **208** is designed in the shape of a corresponding segment **204**, **206** of the ultrasound probe handle **202**.

(27) Moreover, the 3D vapor chamber **208** has hermetic chamber walls that extend around and

define an enclosed chamber. Additionally, a material is disposed within the hermetic chamber walls. This material is configured to change phase in response to heat received from a component of the ultrasound probe **200**. In the example of FIG. 2, the material is a working fluid that is configured to transition between a liquid phase and a vapor phase. It may be noted that in certain embodiments, the hermetic chamber walls may include openings or ports. In one example, these openings or ports may be used to fill the working fluid within the chamber walls.

(28) Reference numeral **210** is used to represent an expanded view of a cross-section of one embodiment of the enclosed chamber of the 3D vapor chamber **208**. In certain embodiments, the 3D vapor chamber **208** includes an external wall **212** and an internal wall **214**. Moreover, each of the external wall **212** and the internal wall **214** includes an interior surface and an exterior surface. Also, a cavity is formed between the external wall **212** and the internal wall **214**.

(29) Additionally, the 3D vapor chamber **208** includes a porous wick structure **216** configured to facilitate transport of the working fluid in the 3D vapor chamber **208**. In particular, the porous wick structure **216** is disposed such that the porous wick structure **216** lines one or more interior surfaces of the external wall **212** and/or the internal wall **214** of the 3D vapor chamber **208**. In some embodiments, the porous wick structure **216** may be formed on interior surfaces of the external and internal walls **212**, **214**. The porous wick structure **216** includes pores that are configured to hold the working fluid in the liquid phase. More particularly, the pores in the porous wick structure **216** are configured to hold the working fluid in the liquid phase in the 3D vapor chamber **204** until heat received from a heat generating component of the ultrasound probe **200** vaporizes the working fluid into a vapor phase in the enclosed 3D vapor chamber **208**. Also, the porous wick structure **216** aids in returning the working fluid from the condenser end to the evaporator end of the 3D vapor chamber **208**.

(30) Also, the 3D vapor chamber **208** includes a vapor transport column or vapor space **218**. The vapor transport column **218** is configured to aid in the transport of the working fluid in a vapor phase within the 3D vapor chamber **208**.

(31) Moreover, in some embodiments, the 3D vapor chamber **208** may include one or more support columns (not shown in FIG. 2) that extend between the external and internal walls **212**, **214**. These columns are employed to prevent the external and internal walls **212**, **214** from moving toward each other or to reduce the distance by which the external and internal walls **212**, **214** move toward each other.

(32) Furthermore, the working fluid such as water is used in the 3D vapor chamber **208** to aid in the transfer of heat from the heat generating components of the ultrasound probe **200**. It may be noted that the working fluid is in a liquid phase and housed in the pores of the porous wick structure **216**. Once the 3D vapor chamber **208** is placed in contact with a heat source such as a heat generating component in the ultrasound probe **200**, the heat from the heat source is absorbed by the working fluid at the evaporator end of the 3D vapor chamber **208**. The absorbed heat results in the working fluid being transformed from a liquid phase to a vapor phase. The working fluid in the vapor phase travels from the evaporator end toward the condenser end via the vapor transport column **218** of the 3D vapor chamber **208**. Subsequently, the working fluid in the vapor phase is cooled at the condenser end by releasing the latent heat. In some embodiments, the latent heat is transferred to an outer surface of the 3D vapor chamber **208** and the heat is then dissipated into the surrounding environment. The condensed working fluid is then returned to the evaporator end of the 3D vapor chamber **208** via the porous wick structure **216**.

(33) As previously noted, one or more components of the ultrasound probe **200** generate heat during operation of the ultrasound probe **200**. Some examples of the heat generating components in the ultrasound probe **200** include a transducer assembly, ASICs, processors, batteries, sensors (not shown in FIG. 2), and the like. Reference numeral **220** is used to depict the transducer assembly in the ultrasound probe **200**. It is desirable to efficiently dissipate the heat generated by the internal components of the ultrasound probe **200** such as the transducer assembly **220** to ensure safe and

continuous operation of the ultrasound probe **200** to image the patient **102**.

(34) In accordance with aspects of the present specification, the 3D vapor chamber **208** is configured to provide enhanced thermal management of the ultrasound probe **200**. In particular, the 3D vapor chamber **208** is configured to facilitate enhanced heat transfer from the heat generating components of the ultrasound probe **200** by thermally contacting one or more surfaces of the heat generating components of the ultrasound probe **200**. Accordingly, the 3D vapor chamber **208** is in thermal communication with the heat generating components of the ultrasound probe **200**. In the example of FIG. 2, the transducer assembly **220** is thermally coupled to the 3D vapor chamber **208** of the ultrasound probe **200**. More specifically, in one example, the internal wall **214** is configured to be in thermal communication with the heat generating components such as the transducer assembly **220** of the ultrasound probe **200**. Reference numeral **222** is representative of a portion of the internal wall **214** of the 3D vapor chamber **208** that is in direct thermal communication with the transducer assembly **220**. In some embodiments, the 3D vapor chamber **208** may be directly thermally coupled to the heat generating components via use of a thermal interface material. Some non-limiting examples of the thermal interface material include thermal pads, grease, adhesive, and the like. By way of a non-limiting example, an adhesive material may be employed to effect a thin adhesive joint between the 3D vapor chamber **208** and the heat generating components of the ultrasound probe **200**. Some non-limiting examples of the adhesive material include thermally non-conductive epoxy, thermally conductive epoxy, filled epoxy, and the like.

(35) Moreover, the 3D vapor chamber **208** is configured to provide enhanced thermal management in the ultrasound probe **200** by absorbing the heat/thermal energy generated by the heat generating components of the ultrasound probe **200**. The heat absorbed by the 3D vapor chamber **208** is in turn transferred to the working fluid in the 3D vapor chamber **208**. As the working fluid absorbs the heat, the working fluid in the liquid phase is transformed to a gas/vapor phase. The working fluid in the vapor/gas phase then travels down in the vapor transport column **218** toward the condenser end of the 3D vapor chamber **208** where the working fluid in the vapor phase is cooled, releasing its latent heat. In particular, the heat is transferred from the working fluid to an outer surface of the 3D vapor chamber **208** and is dissipated to the surrounding environment. Subsequent to the cooling, the working fluid is transformed from the vapor phase to the liquid phase. The porous wick structure **216** and capillary action aid in recirculating the working fluid in the liquid phase to the evaporator end, where the working fluid once again absorbs thermal energy from the external and/or internal walls **212**, **214** of the 3D vapor chamber **208**.

(36) Further, to facilitate rapid and efficient removal/dissipation of heat or thermal energy from internal components of the ultrasound probe **200**, the 3D vapor chamber **208** is formed using a material with a high thermal conductivity. By way of example, the 3D vapor chamber **208** may be formed using materials such as, but not limited to, titanium, aluminum, copper, and the like.

(37) It may be noted that for ease of illustration and description, the 3D vapor chamber **208** is depicted as including two 3D vapor chamber portions. These portions may be sealed to form the 3D vapor chamber **208**. Accordingly, in one embodiment, the 3D vapor chamber **208** is a continuous structure.

(38) The ultrasound probe **200** including the ultrasound probe handle **202** and the 3D vapor chamber **208** may be formed using additive manufacturing, such as by being formed using three-dimensional (3D) printing, rapid prototyping (RP), direct digital manufacturing (DDM), selective laser melting (SLM), electron beam melting (EBM), direct metal laser melting (DMLM), and the like. Some other exemplary methods of additive fabricating usable with the present specification may include processes, such as, but not limited to, direct writing, electron beam deposition, laser deposition, stereo-lithography, and the like. Alternatively, the ultrasound probe **200** may be formed in any another manner.

(39) Additionally, the porous wick structure **216** may also be formed using additive manufacturing and may be formed from sintered powder. Alternatively, the porous wick structure **216** may be

formed using other techniques and/or from other materials. It may be noted that in certain embodiments, the porous wick structure **216** may line the entire interior surface of the hermetic external and internal chamber walls **212**, **214** of the 3D vapor chamber **208** and is configured to hold the working fluid in the liquid phase.

(40) Additively manufacturing the 3D vapor chamber **204** as described hereinabove results in a 3D vapor chamber **208** that is a single, monolithic structure and configured to interface with one or more heat sources in the ultrasound probe **200** to facilitate the enhanced dissipation of heat generated by the internal components of the ultrasound probe **200**. In particular, the 3D vapor chamber **208** is configured to facilitate transfer of thermal energy from the heat generating components of the ultrasound probe **200** such as the transducer assembly **220** and internal electronics of the ultrasound probe **200** to the outer surface of the 3D vapor chamber **208** for cooling by the ambient environment.

(41) In accordance with aspects of the present specification, in some embodiments, at least a portion of the 3D vapor chamber **208** is configured to conform to a shape of the ultrasound probe handle **202** of the ultrasound probe **200**. Accordingly, in this example, the 3D vapor chamber **208** conforms to the shape of the ultrasound probe handle **202**. In other embodiments, an outer coating such as an outer electrically insulating cover may be disposed on an outer/exterior surface of the 3D vapor chamber **208**. In this example, the 3D vapor chamber **208** having the outer coating forms the ultrasound probe handle **202** of the ultrasound probe **200**.

(42) In yet another embodiment, the 3D vapor chamber **208** is configured to conform to the shape of one or more components of the ultrasound probe **200**. In this example, the 3D vapor chamber **208** may conform to one or more aspects of the shape of the component. By way of example, if the component has a shape of a cube, then the 3D vapor chamber **208** may be configured to conform to one or more faces of the cube. Moreover, in this example, the 3D vapor chamber **208** is an internal structure that conforms to the shape of the internal components of the ultrasound probe **200**. Furthermore, in one embodiment, an outer shell that encompasses the 3D vapor chamber **208** may be disposed around the 3D vapor chamber **208**. Accordingly, in this example, the outer shell functions as the ultrasound probe handle **200** of the ultrasound probe **200**. Moreover, the 3D vapor chamber **208** forms an ergonomic exterior shape of the ultrasound probe handle **202** of the ultrasound probe **200**.

(43) Accordingly, the design of the ultrasound probe **200** having the 3D vapor chamber **208** provides enhanced thermal management in the ultrasound probe **200** via the 3D vapor chamber **208**. As will be appreciated, the currently available techniques rely on the thermal conductivity of the material such as copper and titanium to transport the heat. However, the exemplary 3D vapor chamber **208** uses evaporation and condensation of the working fluid to transport the heat in the 3D vapor chamber **208**. Consequently, use of the 3D vapor chamber **208** provides up to a 20× improvement over that provided via use of copper for heat transportation.

(44) In accordance with further aspects of the present specification, in addition to facilitating enhanced thermal management in the ultrasound probe **200**, the 3D vapor chamber **208** may also be configured to provide mechanical support to the internal components of the ultrasound probe **200**. This aspect will be described in greater detail with reference to FIGS. 6-9.

(45) Turning now to FIG. 3, a diagrammatical illustration **300** of another embodiment of an ultrasound probe for use in the system **100** of FIG. 1 is depicted. FIG. 3 is described in conjunction with the components of FIGS. 1-2.

(46) The ultrasound probe **300** includes an ultrasound probe handle **302**. As previously described with reference to FIG. 2, in certain embodiments, the ultrasound probe handle **302** may include two or more segments that are operatively coupled to one another. FIG. 3 depicts the ultrasound probe handle **302** as having a first segment **304** and a second segment **306**. Each segment **304**, **306** is representative of one half of the ultrasound probe handle **302**. In accordance with further aspects of the present specification, use of a single segment or other number of segments for the ultrasound

probe handle **302** is envisioned.

(47) In addition, the ultrasound probe **300** includes a thermal management assembly in the form of a phase change chamber **308** that is configured to provide enhanced thermal management for the ultrasound probe **300**. The reference number **308** shown in FIG. **3** refers to the interior of the chamber. As previously noted, that the phase change chamber **308** is monolithic with respect to a portion of the ultrasound probe handle **302** and is configured to thermally interface with one or more heat generating components in the ultrasound probe **300** to dissipate the heat generated by the components of the ultrasound probe **300**. Further, in certain embodiments, the phase change chamber **308** may include two or more phase change chambers.

(48) In the example illustrated in FIG. **3**, the phase change chamber is a thermal energy storage chamber **308**. The embodiment illustrated in FIG. **3** depicts the phase change chamber **308** as including two thermal energy storage chambers. Each thermal energy storage chamber **308** corresponds to each segment **304**, **306** of the ultrasound probe handle **302**. Additionally, as depicted in the embodiment of FIG. **3**, each of the thermal energy storage chambers **308** is designed in the shape of a corresponding segment **304**, **306** of the ultrasound probe handle **302**.

(49) Furthermore, the thermal energy storage chamber **308** has hermetic chamber walls that extend around and define an enclosed chamber and a material is disposed within the hermetic chamber walls. This material is configured to change phase in response to heat received from a component of the ultrasound probe **300**. In the example of FIG. **3**, the material is a phase change material that is configured to transition between a solid phase and a liquid phase. Further, the phase change material is configured to transition from a first state to a second state to absorb and/or release heat. In some embodiments, the first and second states may be the same, while in some other embodiments, the first and second states may be different. By way of example, the phase change material may transition from a solid state to a liquid state upon receiving a determined level of heat from the component of the ultrasound probe **300**. Other non-limiting examples of the transition of the phase change material include a solid-to-solid phase transition, a liquid-to-solid phase transition, or a liquid-to-liquid phase transition. In yet another embodiment, the phase change material may undergo chemical reactions to absorb and/or release heat. Additionally, one or more phase change materials may have the same or different phase transition temperatures. It may be noted that in certain embodiments, the hermetic chamber walls may include openings or ports. In one example, these openings or ports may be used to fill the phase change material within the chamber walls.

(50) Reference numeral **310** is used to represent an expanded view of a cross-section of one embodiment of the enclosed chamber of the thermal energy storage chamber **308**. In one embodiment, the thermal energy storage chamber **308** includes an external wall **312** and an internal wall **314**. Each of the external wall **312** and the internal wall **314** includes an interior surface and an exterior surface. Also, the external wall **312** and the internal wall **314** form a cavity or space **316**.

(51) In the example of FIG. **3**, the material that is disposed within the thermal energy storage chamber **308** is a phase change material **318**. More particularly, the phase change material **318** is disposed in a cavity **316** between the external and internal walls **312**, **314** of the thermal storage energy chamber **308**. The phase change material **318** has a solid phase, a liquid phase, or a combination thereof. Also, the phase change material **318** may include materials such as, but not limited to, organic materials, inorganic materials, metallic alloys, eutectic alloys, or combinations thereof. Also, in certain embodiments, the phase change material **318** may also include thermally conductive fillers such as, but not limited to, particles, spheres, and ribbons of materials such as graphite, copper, aluminum, and the like to improve heat transfer. In yet another embodiment, the phase change material **318** may be an encapsulated phase change material where the phase change material is contained within a polymeric shell. Further, the phase change material **318** may be configured to facilitate the bidirectional transfer of heat between the heat generating components of the ultrasound probe **300** and the phase change material **318** in the thermal energy storage chamber

308.

(52) Moreover, in certain embodiments, the thermal energy storage chamber **308** may include one or more support columns (not shown in FIG. **3**) that extend between the external and internal walls **312**, **314**. These columns are employed to prevent the external and internal walls **312**, **314** from moving toward each other or to reduce the distance by which the external and internal walls **312**, **314** move toward each other.

(53) As previously noted, one or more components of the ultrasound probe **300** generate heat during operation of the ultrasound probe **300**. Some examples of the heat generating components in the ultrasound probe **300** include a transducer assembly, ASICs, processors, batteries, sensors (not shown in FIG. **3**), and the like. Reference numeral **320** is used to depict the transducer assembly in the ultrasound probe **300**. It is desirable to efficiently dissipate the heat generated by the components of the ultrasound probe **300** to ensure safe and continuous operation of the ultrasound probe **300** to image the patient **102**.

(54) In accordance with aspects of the present specification, the thermal energy storage chamber **308** is configured to facilitate enhanced thermal management of the ultrasound probe **300**. In particular, the thermal energy storage chamber **308** is configured to provide enhanced heat transfer from the heat generating components of the ultrasound probe **300** by directly thermally contacting one or more surfaces of the heat generating components of the ultrasound probe **300**. By way of example, in FIG. **3**, the transducer assembly **320** is thermally coupled to the thermal energy storage chamber **308** of the ultrasound probe **300**. More specifically, the internal wall **314** is configured to be in thermal communication with the heat generating components such as the transducer assembly **320** of the ultrasound probe **300**. Reference numeral **322** is used to represent a portion of the internal wall **314** of the thermal energy storage chamber **308** that is in direct thermal communication with the transducer assembly **320**. In some embodiments, the thermal energy storage chamber **308** may be directly thermally coupled to the heat generating components via use of a thermal interface material such as, but not limited to, thermal pads, grease, adhesive, and the like. By way of a non-limiting example, an adhesive material such as, but not limited to, thermally non-conductive epoxy, thermally conductive epoxy, filled epoxy, and the like, may be employed to effect a thin adhesive joint between the thermal energy storage chamber **308** and the heat generating components of the ultrasound probe **300**.

(55) Moreover, the thermal energy storage chamber **308** is configured to absorb the heat/thermal energy generated by the heat generating components of the ultrasound probe **300**. The heat absorbed by the thermal energy storage chamber **308** is in turn transferred to the phase change material **318** for storage in the thermal energy storage chamber **308**. As the phase change material **318** absorbs the heat, the phase change material in the solid phase is transformed to a liquid phase. By way of example, the phase change material **318** may absorb the heat from the heat generating component when the heat generating component exceeds the melting point of phase change material **318**, thereby lowering the temperature rise of heat generating component. Accordingly, the absorbed heat is stored in the thermal energy storage chamber **308**. In certain embodiments, the heat may be transferred to an outer surface of the thermal energy storage chamber **308** and is dissipated to the surrounding environment. It may be noted that in certain embodiments the thermal energy storage chamber **308** is designed such that the phase change material **318** does not impede the heat transfer from the heat generating component through the chamber walls to the surrounding ambient.

(56) In certain embodiments, it may be desirable to dissipate the stored heat to the ambient. Accordingly, in this example, the thermal energy stored in the phase change material **318** in the thermal energy storage chamber **308** may be dissipated to the surrounding environment. Consequent to this dissipation of the stored heat, the phase change material **318** is cooled, thereby transitioning the phase change material **318** from the liquid phase to the solid phase.

(57) In yet another embodiment, it may be desirable to transfer heat to a component of the

ultrasound probe **300**. In this example, the thermal energy stored in the phase change material **318** in the thermal energy storage chamber **308** may be conveyed to the component to be heated. Consequent to this transfer of heat, the phase change material **318** is cooled, thereby transitioning the phase change material **318** from the liquid phase to the solid phase. Moreover, in other embodiments, the ultrasound probe may include multiple thermal energy storage chambers. In this example, the heat may be transferred from one thermal energy storage chamber to another thermal energy storage chamber.

(58) It may be noted that to facilitate rapid and efficient removal/dissipation of heat or thermal energy from internal components of the ultrasound probe **300**, the thermal energy storage chamber **308** is formed using a material with a high thermal conductivity. By way of example, the thermal energy storage chamber **308** may be formed using materials such as, but not limited to, titanium, aluminum, copper, and the like. In some embodiments, the internal walls such as the internal wall **314** may also be retrofitted with heat conducting elements such as heat pipes, copper, graphite sheets, rods, and the like.

(59) Further, for case of illustration and description, the thermal energy storage chamber **308** is depicted as including two phase change chamber portions. These portions may be sealed to form the thermal energy storage chamber **308**. Accordingly, in one embodiment, the thermal energy storage chamber **308** is a continuous structure.

(60) It may also be noted that in some embodiments, the cavity **316** may also include fins (not shown in FIG. 3) extending from the inner surfaces of the external wall **312** and/or the internal wall **314** to aid in heat transport to the phase change material **318**. In this example, the fins may be in the form of studs or may extend in an annular fashion around the radius of the ultrasound probe **300**. It may be noted that the annular fins may have openings or ports to facilitate filling and/or transport of the phase change material **318**. Moreover, it may also be noted that the fins in the cavity **316** of the thermal energy storage chamber **308** are internal fins.

(61) Additionally, in certain embodiments, multiple such fins may be dispersed along the length of the thermal energy storage chamber **308**. The fins or studs serve to increase the surface area of the thermal energy storage chamber **308**, which in turn improves heat transfer. In certain embodiments, the fins and/or studs may be formed using the same material as the external wall **312** and the internal wall **314** of the thermal energy storage chamber **308**. Moreover, as previously noted, the phase change material **318** may also include thermally conductive fillers such as particles, spheres, and/or ribbons of graphite, copper, aluminum, and the like to improve heat transfer.

(62) The ultrasound probe **300** including the ultrasound probe handle **302** and the thermal energy storage chamber **308** may be formed using additive manufacturing, such as by being formed using three-dimensional (3D) printing, rapid prototyping (RP), direct digital manufacturing (DDM), selective laser melting (SLM), electron beam melting (EBM), direct metal laser melting (DMLM), and the like. Some other exemplary methods of additive fabricating usable with the present specification may include processes, such as, but not limited to, direct writing, electron beam deposition, laser deposition, stereo-lithography, and the like. Alternatively, the ultrasound probe **300** may be formed in any another manner such as, but not limited to, casting, welding, machining, and the like. Additively manufacturing the thermal energy storage chamber **308** as described hereinabove results in a thermal energy storage chamber **308** that is a single, monolithic structure and configured to interface with one or more heat sources in the ultrasound probe **300** to facilitate the enhanced dissipation of heat generated by the internal components of the ultrasound probe **300**.

(63) In accordance with further aspects of the present specification, the ultrasound probe **300** may include two or more thermal energy storage chambers **308**. These thermal energy storage chambers **308** may be distributed within an inner volume of the ultrasound probe **300**. Additionally, each of the two or more thermal energy storage chambers may include a corresponding phase change material disposed within a corresponding thermal energy storage chamber. Moreover, each phase change material may have a different melting point, thereby facilitating maintaining different

components of the ultrasound probe **300** at different temperatures. In certain other embodiments, the thermal energy storage chambers **308** may be distributed within the volume of phase change chamber due to space constraints.

(64) As previously described with respect to FIG. 2, at least a portion of the thermal energy storage chamber **308** may be configured to conform to a shape of the ultrasound probe handle **302** of the ultrasound probe **300**. Furthermore, in some other embodiments, an outer coating such as an outer electrically insulating cover may be disposed on an outer/exterior surface of the thermal energy storage chamber **308**. Moreover, the thermal energy storage chamber **308** may form an ergonomic exterior shape of the ultrasound probe handle **302** of the ultrasound probe **300**.

(65) Accordingly, the design of the ultrasound probe **300** having the thermal energy storage chamber **308** provides enhanced thermal management in the ultrasound probe **300**. As will be appreciated, the currently available techniques rely on the thermal conductivity of the material such as copper and titanium to transport the heat. However, the exemplary 3D vapor chamber **208** uses evaporation and condensation of the working fluid to transport the heat in the 3D vapor chamber **208**. Consequently, use of the 3D vapor chamber **208** provides up to a 20× improvement over that provided via use of copper for heat transportation.

(66) Furthermore, in accordance with further aspects of the present specification, in addition to facilitating enhanced thermal management in the ultrasound probe **300**, the thermal energy storage chamber **308** may also be configured to provide mechanical support to the internal components of the ultrasound probe **300**. This aspect will be described in greater detail with reference to FIGS. 6-9.

(67) FIG. 4 is a diagrammatical illustration **400** of yet another embodiment of an ultrasound probe for use in the system **100** of FIG. 1 is depicted. FIG. 4 is described in conjunction with the components of FIGS. 1-3. In accordance with aspects of the present specification, in the embodiment **400** of FIG. 4, a phase change chamber of the ultrasound probe **400** is a nested configuration of the 3D vapor chamber **208** of FIG. 2 and the thermal energy storage chamber **308** of FIG. 3.

(68) The ultrasound probe **400** includes an ultrasound probe handle **402**. In one embodiment, the ultrasound probe handle **402** may include two or more segments that are operatively coupled to one another. In FIG. 4, the ultrasound probe handle **402** is depicted as having a first segment **404** and a second segment **406**, where each segment **404**, **406** is representative of one half of the ultrasound probe handle **402**.

(69) Moreover, the ultrasound probe **400** includes a thermal management assembly in the form of a phase change chamber **408** that is configured to provide enhanced thermal management for the ultrasound probe **400**. The reference number **408** shown in FIG. 4 refers to the interior of the chamber. The phase change chamber **408** is monolithic with respect to a portion of the ultrasound probe handle **402** and is configured to thermally interface with one or more heat generating components in the ultrasound probe **400** to dissipate the heat generated by the components of the ultrasound probe **400**. In one embodiment, the phase change chamber **408** is directly/thermally coupled to one or more components of the ultrasound probe **400** to facilitate dissipation of heat from the heat generating components of the ultrasound probe. Also, in certain embodiments, the phase change chamber **408** may include two or more phase change chambers.

(70) In a presently contemplated configuration, the phase change chamber **408** has a nested configuration. More particularly, the phase change chamber **408** includes a 3D vapor chamber **410** such as the 3D vapor chamber **208** of FIG. 2 and a thermal energy storage chamber **412** such as the thermal energy storage chamber **308** of FIG. 3. Reference numeral **414** is used to represent an expanded view of a cross-section of one embodiment of the phase change chamber **408**.

(71) The phase change chamber **408** has hermetic chamber walls that extend around and define an enclosed chamber. In certain embodiments, the 3D vapor chamber **410** includes an external wall **416**. Further, the phase change chamber **408** includes a common wall **418** that is shared by the 3D

vapor chamber **410** and the thermal energy storage chamber **412**. In one example, the external wall **416** and the common wall **418** form a cavity. Additionally, the 3D vapor chamber **410** includes a working fluid that is disposed within the cavity. Further, the 3D vapor chamber **410** includes a porous wick structure **420** configured to facilitate transport of the working fluid in the 3D vapor chamber **410**. In particular, the porous wick structure **420** is disposed such that the porous wick structure **420** lines one or more interior surfaces of the external wall **416** of the 3D vapor chamber **410** and/or the common wall **418**. Also, the porous wick structure **420** includes pores that are configured to hold the working fluid in a liquid phase in the 3D vapor chamber **410** until heat received from a heat generating component of the ultrasound probe **400** vaporizes the working fluid into a vapor phase in the enclosed 3D vapor chamber **410**. Moreover, the porous wick structure **420** aids in returning the working fluid from the condenser end to the evaporator end of the 3D vapor chamber **410**. In addition, the 3D vapor chamber **410** includes a vapor transport column or vapor space **422**. The vapor transport column **422** is configured to aid in the transport of the working fluid in a vapor phase within the 3D vapor chamber **410**.

(72) In accordance with further aspects of the present specification, the phase change chamber **408** also includes the thermal energy storage chamber **412**. Furthermore, the thermal energy storage chamber **412** has a hermetic chamber wall such as an internal wall **424**. Also, a cavity **426** is formed between the common wall **418** and the internal wall **424**. A phase change material **428** such as wax is housed in this cavity **426** and the phase change material **428** is configured to change phase in response to heat received from a component of the ultrasound probe **400**. In particular, the phase change material **428** is configured to transition between a solid phase and a liquid phase.

(73) It may also be noted that in some embodiments, the cavity **426** may also include fins (not shown in FIG. 4) extending from the common wall **418** and/or the internal wall **424** into the phase change material **428** to aid in heat transport to the phase change material **428**. As noted hereinabove, the fins in the cavity **426** are internal fins. In this example, the fins may be in the form of studs or may extend in an annular fashion around the radius of the ultrasound probe **400**. It may be noted that the annular fins may have openings or ports to facilitate filling and/or transport of the phase change material **428**. Also, the fins may have a structure that is similar to the structure of the 3D vapor chamber **410** and/or the thermal energy storage chamber **412**. Also, as previously noted, the phase change material **428** may also include thermally conductive fillers such as particles, spheres, and/or ribbons of graphite, copper, aluminum, and the like to improve heat transfer.

(74) Moreover, in certain embodiments, multiple such fins may be dispersed along the length of the 3D vapor chamber **410**. It may be noted the fins used in the 3D vapor chamber **410** are external fins. The fins or studs serve to increase the surface area of the 3D vapor change chamber **410**, which in turn improves heat transfer. In certain embodiments, the fins and/or studs may be formed using the same material as the common wall **418**, the external wall **416**, and/or the internal wall **424** of the phase change chamber **408**.

(75) Furthermore, the phase change material **428** such as wax is used in the thermal energy storage chamber **412** to aid in the absorption of heat from the heat generating components of the ultrasound probe **400**. The phase change material **428** is in a solid phase and housed in the cavity **426**. Once the thermal energy storage chamber **412** is placed in contact with a heat source such as a heat generating component in the ultrasound probe **400**, the heat from the heat source is absorbed by the phase change material **428** in the thermal energy storage chamber **412**. It may be noted that in certain embodiments, the heat source may also be the heat from the 3D vapor chamber **410**. The absorbed heat results in the phase change material **428** being transformed from a solid phase to a liquid phase. As previously noted, transitions between other phases and/or chemical reactions may also occur during the transportation of the heat. In some embodiments, the absorbed heat may be stored in the thermal energy storage chamber **412**. However, in other embodiments, the latent heat may be transferred to an outer surface of the phase change chamber **408** and the heat is dissipated into the surrounding environment.

(76) In accordance with farther aspects of the present specification, in some embodiments, the 3D vapor chamber **410** may be placed in direct contact with the heat dissipating component(s) in the ultrasound probe **400** (see FIG. 5) since the 3D vapor chamber **410** effectively has a very high thermal conductivity. Accordingly, the 3D vapor chamber **410** is configured to absorb the heat generated by the heat dissipating component(s) in the ultrasound probe **400**. Further, in this example, the 3D vapor chamber **410** is configured to carry the absorbed heat to another part of the ultrasound probe **400** having the nested configuration of the 3D vapor chamber **410** and the thermal energy storage chamber **412**, and the heat is stored in the thermal energy storage chamber **412**.

(77) As previously noted, one or more components of the ultrasound probe **400** generate heat during operation of the ultrasound probe **400**. Reference numeral **430** is used to depict a heat generating component of the ultrasound probe **400** such as a transducer assembly. It is desirable to efficiently dissipate the heat generated by the transducer assembly to ensure safe and continuous operation of the ultrasound probe **400** to image the patient **102**.

(78) In accordance with aspects of the present specification, the 3D vapor chamber **410** and the thermal energy storage chamber **412** are configured to facilitate enhanced thermal management of the ultrasound probe **400**. In particular, the 3D vapor chamber **410** and/or the thermal energy storage chamber **412** are configured to provide enhanced heat transfer from the heat generating components of the ultrasound probe **400** by directly thermally contacting one or more surfaces of the heat generating components of the ultrasound probe **400**. In the example of FIG. 4, the transducer assembly **430** is thermally coupled to the 3D vapor chamber **410** and/or the thermal energy storage chamber **412** of the ultrasound probe **400**. In one example, the transducer assembly **430** is directly thermally coupled to a portion **432** of an interior surface of the phase change chamber **408**. In some embodiments, the phase change chamber **408** may be directly thermally coupled to the heat generating components via use of a thermal interface material such as thermal pads, grease, adhesive, and the like.

(79) It may be noted that to facilitate rapid and efficient removal/dissipation of heat or thermal energy from internal components of the ultrasound probe **400**, the phase change chamber **408** is formed using a material with a high thermal conductivity. By way of example, the phase change chamber **408** may be formed using materials such as, but not limited to, titanium, aluminum, copper, and the like.

(80) Further, for ease of illustration and description, the phase change chamber **408** is depicted as including two phase change chamber portions. These portions may be sealed to form the phase change chamber **408**. Accordingly, in one embodiment, the phase change chamber **408** is a continuous structure.

(81) The ultrasound probe **400** including the ultrasound probe handle **402**, the 3D vapor chamber **410** and thermal energy storage chamber **208** may be formed using additive manufacturing, such as by being formed using three-dimensional (3D) printing, rapid prototyping (RP), direct digital manufacturing (DDM), selective laser melting (SLM), electron beam melting (EBM), direct metal laser melting (DMLM), and the like. Some other exemplary methods of additive fabricating usable with the present specification may include processes, such as, but not limited to, direct writing, electron beam deposition, laser deposition, stereo-lithography, and the like. Alternatively, the ultrasound probe **400** may be formed in any another manner.

(82) Additively manufacturing the phase change chamber **408** as described hereinabove results in a phase change chamber **408** that is a single, monolithic structure and configured to interface with one or more heat sources in the ultrasound probe **400** to facilitate the enhanced dissipation of heat generated by the internal components of the ultrasound probe **400**. In particular, the phase change chamber **408** is configured to facilitate transfer of thermal energy from the heat generating components of the ultrasound probe **400** such as the transducer assembly **430** and internal electronics of the ultrasound probe **400** for dissipation, storage, or both. By way of example, the 3D vapor chamber **410** is used to absorb the heat generated by the ultrasound components and transfer

the absorbed heat to an outer surface of the phase change chamber **408** for cooling by the ambient environment. Additionally, the thermal energy storage chamber **412** is used to absorb the heat generated by the ultrasound components and stored the absorbed heat in the phase change material **428**.

(83) Accordingly, the design of the ultrasound probe **400** having the 3D vapor chamber **410** and the thermal energy storage chamber **412** provides enhanced thermal management in the ultrasound probe **400**. As previously noted, the currently available techniques rely on the thermal conductivity of the material such as copper and titanium to transport the heat. Also, typically, phase change materials have a poor thermal conductivity and hence need thick conducting walls or fillers within the phase change material to transport heat into the phase change material. Using the exemplary 3D vapor chamber **410** high heat transport capabilities in conjunction with the thermal energy storage chamber **412** aids in enhanced heat spreading along the phase change material **428**, thereby facilitating uniform melting of the phase change material **428**. Consequently, this design of the ultrasound probe **400** having the 3D vapor chamber **410** and the thermal energy storage chamber **412** results in higher heat absorption and hence longer duration of temperature control of the heat generating component.

(84) Referring now to FIG. 5, a diagrammatical illustration **500** of yet another embodiment of an ultrasound probe for use in the system **100** of FIG. 1 is depicted. FIG. 5 is described in conjunction with the components of FIGS. 1-4. In a presently contemplated configuration of FIG. 5, a phase change chamber of the ultrasound probe **500** is a nested configuration of the 3D vapor chamber **410** and the thermal energy storage chamber **412** of FIG. 4. Additionally, the 3D vapor chamber in the nested configuration includes a projection that is configured to be in thermal contact with a heat generating component of the ultrasound probe **500**.

(85) The ultrasound probe **500** includes an ultrasound probe handle **502**. Also, the ultrasound probe handle **502** may include two or more segments such as a first segment **504** and a second segment **506** that are operatively coupled to one another.

(86) In accordance with aspects of the present specification, the ultrasound probe **500** includes a thermal management assembly in the form of a phase change chamber **508** that is configured to provide enhanced thermal management for the ultrasound probe **500**. The phase change chamber **508** is monolithic with respect to a portion of the ultrasound probe handle **502** and is configured to thermally interface with one or more heat generating components in the ultrasound probe **500** to dissipate the heat generated by the components of the ultrasound probe **500**. As depicted in FIG. 5, the phase change chamber **508** has a nested configuration such as the nested configuration **400** of FIG. 4. More particularly, the phase change chamber **508** includes a 3D vapor chamber **510** such as the 3D vapor chamber **410** and a thermal energy storage chamber **512** such as the thermal energy storage chamber **412** of FIG. 4. An expanded view of a cross-section of one embodiment of the phase change chamber **508** is generally referenced by reference numeral **514**.

(87) Moreover, as previously noted with reference to FIG. 4, the 3D vapor chamber **510** has hermetic chamber walls that extend around and define an enclosed chamber. The 3D vapor chamber **510** includes an external wall **516**. Also, the phase change chamber **508** includes a common wall **518** that is shared by the 3D vapor chamber **510** and the thermal energy storage chamber **512**. Additionally, the 3D vapor chamber **510** includes a working fluid that is disposed within a cavity between the external wall **516** and the common wall **518**. The working fluid is configured to change phase in response to heat received from a component of the ultrasound probe **500**. Moreover, the 3D vapor chamber **510** includes a porous wick structure **520** configured to facilitate transport of the working fluid in the 3D vapor chamber **510**. The porous wick structure **520** includes pores that are configured to hold the working fluid in a liquid phase in the 3D vapor chamber **510**. Also, the porous wick structure **520** aids in returning the working fluid from the condenser end to the evaporator end of the 3D vapor chamber **410**. Further, the 3D vapor change chamber **510** includes a vapor transport column or vapor space configured to aid in the transport of

the working fluid in a vapor phase within the 3D vapor chamber **510**.

(88) In a presently contemplated configuration, one or more portions of the 3D vapor chamber **510** may extend inward from at least one of the hermetic chamber walls and at least partially towards an inner section of the ultrasound probe handle **502**. This extension may be generally referred to as a projection **524**. It may be noted that for ease of illustration the configuration of the 3D vapor chamber **510** of FIG. 5 is depicted as including one projection **524**. However, the 3D vapor chamber **510** may include more than one projection **524**. In this embodiment, the projection **524** of the 3D vapor chamber **510** is disposed in direct thermal contact with one or more components **526** of the ultrasound probe **500** and configured to facilitate dissipation of heat generated by the components **526** of the ultrasound probe **500**. In certain embodiments, the ultrasound probe **500** may also include a heat dissipating component **528**. The heat dissipating component **528** is configured to thermally couple the 3D phase change chamber **510** to one or more heat generating components of the ultrasound probe **500**. Accordingly, in this example, the heat dissipating component **528** is positioned in direct thermal contact with one or more heat generating components **526** of the ultrasound probe **500** and the projection **524** is thermally coupled to the heat dissipating component **528**. Hence, the heat generated by the components **526** of the ultrasound probe **500** is transferred to the projection **524** in the 3D vapor chamber **510** via the heat dissipating component **528**.

(89) Additionally, the phase change chamber **508** also includes the thermal energy storage chamber **512**. The thermal energy storage chamber **512** has a hermetic chamber wall such as an internal wall **530**. Also, a phase change material **534** such as wax is housed in a cavity **532** that is formed between the common wall **518** and the internal wall **530**. Moreover, this phase change material **534** is configured to change phase in response to heat received from a component **526** of the ultrasound probe **500**. The phase change material **534** that is configured to transition between a solid phase and a liquid phase.

(90) Further, for ease of illustration and description, the phase change chamber **508** is depicted as including two phase change chamber portions. These portions may be sealed to form the phase change chamber **508**. Accordingly, in one embodiment, the phase change chamber **508** is a continuous structure.

(91) The ultrasound probe **500** including the ultrasound probe handle **502**, the 3D vapor chamber **510** and thermal energy storage chamber **512** may be formed using additive manufacturing, such as by being formed using three-dimensional (3D) printing, rapid prototyping (RP), direct digital manufacturing (DDM), selective laser melting (SLM), electron beam melting (EBM), direct metal laser melting (DMLM), and the like. Some other exemplary methods of additive fabricating usable with the present specification may include processes, such as, but not limited to, direct writing, electron beam deposition, laser deposition, stereo-lithography, and the like.

(92) As will be appreciated, it is desirable to have an ultrasound probe that is an ergonomically sound structure and a light weight structure capable of dissipating heat generated in the ultrasound probe by transferring and/or storing the generated heat to an outer surface of the ultrasound probe, and subsequently to the ambient environment. FIGS. 6-9 represent further embodiments of an ultrasound probe having a thermal management assembly in the form of an exemplary phase change chamber that is configured to provide enhanced thermal management for the ultrasound probe by facilitating enhanced dissipation and/or storage of heat generated by internal components of the ultrasound probe. It may be noted that phase change chambers depicted in FIGS. 6-9 may be created using additive manufacturing, such as by being formed using three-dimensional (3D) printing, rapid prototyping (RP), direct digital manufacturing (DDM), selective laser melting (SLM), electron beam melting (EBM), direct metal laser melting (DMLM), or the like. Alternatively, the phase change chambers can be formed in another manner.

(93) Turning now to FIG. 6, a diagrammatical illustration **600** of a cross-section of one embodiment of an ultrasound probe for use in the system **100** of FIG. 1, in accordance with aspects

of the present specification, is depicted. FIG. 6 is described in conjunction with the components of FIGS. 1-5.

(94) In the example of FIG. 6, a cross-sectional view of a wireless ultrasound probe **600** is depicted. As will be appreciated, a wireless ultrasound probe **600** includes additional components such as batteries, wireless transmitters, wireless receivers, and corresponding electronics to support operation of the wireless ultrasound probe **600**. Moreover, these additional components are distributed across the wireless ultrasound probe **600** serve as additional heat sources. Further, due to the additional components such as the batteries and/or wireless transmitters/receivers, the heat generated in the ultrasound probe **600** is distributed and higher in magnitude.

(95) In the embodiment depicted in FIG. 6, the ultrasound probe **600** is depicted as including an ultrasound probe handle **602** and a thermal management assembly in the form of a phase change chamber **604** within the ultrasound probe handle walls and configured to provide enhanced thermal management for the ultrasound probe **600**. In the example of FIG. 6, the phase change chamber **604** is a 3D vapor chamber configured to facilitate enhanced thermal management of the ultrasound probe **600** having the additional heat sources. As previously noted, the 3D vapor chamber **604** is monolithic with respect to at least a portion of the ultrasound probe handle **602**. Additionally, the 3D vapor chamber **604** is configured to be a thermally conductive structure. In certain embodiments, the 3D vapor chamber **604** may also be configured to provide mechanical or structural support to internal components of the ultrasound probe **600**.

(96) The ultrasound probe **600** includes a transducer assembly **606**, one or more processors, ASICs, batteries, sensors and the like. Components such as processors, ASICs, batteries, sensors, and the like are generally represented by reference numeral **608**. Also, these components **608** may be mounted on a mother board **610**. As noted hereinabove, the components **606**, **608** are additional heat sources in the ultrasound probe **600** and are distributed in the volume of the ultrasound probe **600**.

(97) In the embodiment depicted in FIG. 6, the 3D vapor chamber **604** is configured to interface with the various heat sources **606**, **608** within the 3D vapor chamber **604** to facilitate dissipation of heat generated by the heat sources **606**, **608**. To that end, the vapor chamber **604** includes one or more projections **612** configured to facilitate the enhanced transfer of heat from the heat generating internal components **606**, **608** of the ultrasound probe **600**. These projections **612** may be similar to the projection **524** of FIG. 5 and are depicted in greater detail in FIG. 6. In one embodiment, the projections **612** may include finger-like protrusions. Additionally, in the example depicted in FIG. 6, the projections **612** are disposed on an interior surface of the 3D vapor chamber **604** such that each projection **612** contacts at least one heat source **608**. In particular, each projection **612** is thermally coupled to at least one heat source **608**.

(98) Moreover, as previously noted, the 3D vapor chamber **604** and the 3D vapor chamber projections **612** may be created using additive manufacturing, such as by being formed using three-dimensional (3D) printing, rapid prototyping (RP), direct digital manufacturing (DDM), selective laser melting (SLM), electron beam melting (EBM), direct metal laser melting (DMLM), or the like. Alternatively, the 3D vapor chamber **604** can be formed in another manner.

(99) The design of the ultrasound probe **600** having the 3D vapor chamber **604**, which in turn has the projections **612** provides a single monolithic structure configured to access multiple heat sources **608** and dissipate the heat generated by the heat sources **608**. Moreover, the 3D vapor chamber **604** having the projections **612** is formed using a material having a high thermal conductivity. Consequently, the heat generated by the components **608** is efficiently transported to an outer surface of the ultrasound probe handle **602** via the projections **612** in the 3D vapor chamber **604** for dissipation into the surrounding environment.

(100) It may be noted that the exemplary design of the 3D vapor chamber **604** aids in replacing a spine, heat spreaders, heat pipes, thermal pads, plastic PCB holders that are used in conventional ultrasound probes. Additionally, the 3D vapor chamber **604** may be used as a handle of an

ultrasound probe. Moreover, the design of FIG. 6 provides the ultrasound probe **600** having the ultrasound probe handle **602** that has a lower weight, less complexity, higher thermal performance, and faster installation time compared to the conventional ultrasound probes. It may be noted that a cross-section of one embodiment of a shell **614** of the 3D vapor chamber **604** may have a structure that is substantially similar to the cross-section **214** of the 3D vapor chamber **208** of FIG. 2.

(101) Additionally, in certain embodiments, the ultrasound probe **600** and the 3D vapor chamber **604** in particular may include a thermal mounting platform **616**. In this example, the 3D vapor chamber **604** extends along the length of the ultrasound probe handle walls to the area of the thermal mounting platform **616**. Further, the thermal mounting platform **616** is directly coupled to the transducer assembly **606** and configured to transfer heat generated by the transducer assembly **606** to the 3D vapor chamber **604** for dissipation to the surrounding environment. As will be appreciated, the transducer assembly **606** typically includes a stack of components such as a transducer array of one or more transducer elements, processing electronics in the form of application specific integrated circuits (ASICs), a thermal-acoustic backing, and the like (not shown in FIG. 6). The thermal-acoustic backing of the transducer assembly **606** may be mounted on and directly coupled to the thermal mounting platform **616**.

(102) The heat generated by the transducer assembly **606** is transferred from the transducer assembly **606** via the thermal-acoustic backing to the thermal mounting platform **616**. The thermal mounting platform **616** in turn transfers this heat to the enclosure or shell **614** of the 3D vapor chamber **604**. The enclosure **614** provides an expansive surface area for the dissipation of the heat generated by the transducer assembly **606** for cooling by the ambient environment. Also, the thermal mounting platform **616** may be formed using a strong and light weight material such as titanium. Some non-limiting examples of the material used to form the thermal mounting platform **616** include titanium, copper, aluminum, and the like. However, other materials may also be used to form the thermal mounting platform **616**.

(103) In accordance with further aspects of the present specification, in addition to facilitating enhanced thermal management in the ultrasound probe **600**, the 3D vapor chamber **604** may also be configured to provide mechanical support to the internal components of the ultrasound probe **600**. By way of example, the thermal mounting platform **616** in addition to facilitating dissipation of heat from the transducer assembly **606** may also be configured to provide mechanical support to the transducer assembly **606** in the ultrasound probe **600**. As noted hereinabove, the thermal-acoustic backing of the transducer assembly **606** may be mounted on and directly coupled to the thermal mounting platform **616**.

(104) FIGS. 7-9 represent different embodiments of an ultrasound probe. In particular, embodiments of the ultrasound probe depicted in FIGS. 7-9 illustrate alternative configurations of the ultrasound probe **600** depicted in FIG. 6. In addition, a cross-section of one embodiment of the phase change chambers of the embodiments depicted in FIGS. 7-9 may have a structure that is substantially similar to the cross-sections **210**, **310**, **414**, **514** of the phase change chambers of FIGS. 2-5.

(105) FIG. 7 is a diagrammatical illustration **700** of a cross-section of another embodiment of an ultrasound probe, in accordance with aspects of the present specification. Also, FIG. 7 is described in conjunction with the components of FIGS. 1-6.

(106) As previously described with reference to FIG. 6, a digital wireless probe includes additional heat sources and hence experiences a higher internal heat load. Accordingly, it is desirable that a surface area of the ultrasound probe be large enough to maintain temperatures of the ultrasound probe to a value below about 43° C.

(107) In the embodiment depicted in FIG. 7, the ultrasound probe **700** is depicted as including ultrasound probe handle **702** and a thermal management assembly in the form of a phase change chamber **704** within walls of the ultrasound probe handle **702** and configured to provide enhanced thermal management for the ultrasound probe **700**. In a presently contemplated configuration, the

phase change chamber **704** includes a 3D vapor chamber **706** and a thermal energy storage chamber **708** configured to facilitate enhanced thermal management of the ultrasound probe **700** having the additional heat sources.

(108) The ultrasound probe **700** includes a transducer assembly **710**, one or more processors, ASICs, batteries, sensors, and the like. Components such as processors, ASICs, batteries, sensors and the like are generally represented by reference numeral **712**. These components **712** may be mounted on a mother board **714**. As noted hereinabove, the components **712** are additional heat sources in the ultrasound probe **700** and are distributed in the volume of the ultrasound probe **700**.

(109) The 3D vapor chamber **706** is configured to interface with the various heat sources **712** of the ultrasound probe **700** to facilitate dissipation of heat generated by the heat sources **712**.

Accordingly, the 3D vapor chamber **706** includes one or more projections **716** configured to facilitate the enhanced transfer of heat from the heat generating internal components **712** of the ultrasound probe **700**. In one embodiment, the projections **716** may include finger-like protrusions. Additionally, in the example depicted in FIG. 7, the projections **716** are disposed on an interior surface of the 3D vapor chamber **706** such that each projection **716** contacts at least one heat source **712**. In particular, each projection **716** is thermally coupled to at least one heat source **712**.

(110) The design of the ultrasound probe **700** having the 3D vapor chamber **706**, which in turn has the projections **716** provides a single monolithic structure configured to access multiple heat sources **712** and dissipate generated by these heat sources **712**. Moreover, the 3D vapor chamber **706** having the projections **716** are formed using a material having a high thermal conductivity. Consequently, the heat generated by the components **712** is efficiently transported to an outer surface of the ultrasound probe handle **702** via the projections **716** in the 3D vapor chamber **706** for dissipation into the surrounding environment.

(111) In the example of FIG. 7, the ultrasound probe **700** and more particularly the phase change chamber **704** additionally includes the thermal energy storage chamber **708** that is configured to house a phase change material (PCM) **720**. As will be appreciated, a phase change material is a material that melts and solidifies at a determined temperature and is capable of storing and releasing large amounts of energy. By way of example, heat is absorbed by the phase change material **720** when the phase change material **720** changes from a solid phase to a liquid phase at a corresponding melting temperature. Also, the stored energy is released when the phase change material **720** cools down to a corresponding freezing point to change phase from a liquid to a solid. It may be noted that in certain embodiments, the freezing point and the melting point of the phase change material **720** may be the same or different. Moreover, the phase change material **720** may include materials such as, but not limited to, organic materials, inorganic materials, metallic alloys, eutectic alloys, paraffin wax, or combinations thereof. Furthermore, in certain embodiments, the phase change material **720** may be injected into or otherwise disposed in the thermal energy storage chamber **708**. In some embodiments, the phase change material(s) **720** may also be encapsulated within one or more polymeric shells. Accordingly, in this example, the phase change material(s) **720** may be referred to as encapsulated phase change material(s). Also, in one example, the one or more polymeric shells may have a size of less than or about 5 mm.

(112) In this embodiment of the ultrasound probe **700**, a portion of heat generated by the internal components **712** of the ultrasound probe **700** may be dissipated through an outer surface of the phase change chamber **704**. The remaining heat is absorbed by the phase change material **720** and stored in the thermal energy storage chamber **708** as the phase change material is transitioned from a solid phase to a liquid phase.

(113) Furthermore, in certain embodiments, the ultrasound probe **700** and the phase change chamber **704** in particular may include a thermal mounting platform **718**. In this example, the thermal mounting platform **718** is directly coupled to the transducer assembly **710** and configured to transfer heat generated by the transducer assembly **710** to the 3D vapor chamber **706** for dissipation to the surrounding environment. Moreover, the thermal mounting platform **718** may

also be configured to transfer heat generated by the transducer assembly **710** to the phase change material **720** for storage in the thermal energy storage chamber **708**. It may be noted that in addition to facilitating enhanced thermal management in the ultrasound probe **700**, the 3D vapor chamber **706** and the thermal mounting platform **718** in particular may also be configured to provide mechanical support to the internal components of the ultrasound probe **700**.

(114) Additionally, the 3D vapor chamber **706** may also include one or more fins (not shown in FIG. 7). As previously noted, the fins in the 3D vapor chamber **706** may be external fins. In this embodiment, the fins aid in dissipating the heat generated in the ultrasound probe **700**. In one embodiment, the fins may be integral with an enclosure or shell **724** of the 3D vapor chamber **706**. By way of a non-limiting example, the fins may be integrated with the enclosure **724** of the 3D vapor chamber **706** as a plain metal or as an extension of the 3D vapor chamber **706**, similar to the projection **524** of FIG. 5. More particularly, the fins **722** are in thermal communication with the 3D vapor chamber **706** to facilitate the dissipation of heat from the heat generating components **710**, **712** of the ultrasound probe **700**.

(115) Furthermore, by way of a non-limiting example, the fins may have a rectangular cross-section or a circular cross-section. Also, the fins may extend annularly along the radius of the ultrasound probe handle **702**. In certain embodiments, the annular fins may have openings or ports to facilitate filling and/or transport of the phase change material **722**.

(116) In addition, the fins may also be in the form of pins and/or studs of various cross-sectional shapes that extend from the enclosure or shell **724** of the 3D vapor chamber **706** into the thermal energy storage chamber **708** such that the fins are in thermal contact with the phase change material **720**. The fins may also be aligned along the length of the shell **724**. In other embodiments, the fins having varying shapes and/or forms may be dispersed in a random fashion along the shell **724**. These fins may be similar to the projection **524** depicted in FIG. 5.

(117) Furthermore, in certain embodiments, the thermal energy storage chamber **708** may also include one or more of the fins **722**. As previously noted, the fins **722** in the thermal energy storage chamber **708** are internal fins. In this example, the fins **722** may be optimally spaced within a volume of phase change material **720** in the thermal energy storage chamber **708** and configured to aid in dissipating heat from the phase change material **720**. Also, in one embodiment, the fins **722** may be spaced uniformly within the volume of the phase change material **720** in the thermal energy storage chamber **708**. However, in another embodiment, the fins **722** may be disposed with variable spacing within the volume of phase change material **720** in the thermal energy storage chamber **708**. These fins **722** are configured to lower the heat conduction resistance from the 3D vapor chamber **706** to the phase change material **720** in the thermal energy storage chamber **708** and also promote uniform change in the state/phase of the phase change material **720**. Moreover, the fins **722** are also in thermal communication with the phase change material **720** to facilitate the efficient bidirectional transfer of heat between the heat generating components **710**, **712** of the ultrasound probe **700** and the phase change material **720**. In one example, the fins **722** may aid in transferring heat from the heat generating components **710**, **712** of the ultrasound probe **700** to the phase change material **720** for storage in the thermal energy storage chamber **708**. In another example, the fins **722** may aid in transferring the heat stored in the phase change material **720** in the thermal energy storage chamber **708** to the components **710**, **712** of the ultrasound probe **700** and/or the environment surrounding the ultrasound probe **700**.

(118) Use of the phase change material **720** in the thermal energy storage chamber **708** results in a lower surface area requirement of the ultrasound probe **700**, thereby allowing the ultrasound probe **700** to be smaller in size than a corresponding size of an ultrasound probe without the phase change material **720**. Moreover, a choice of the phase change material **720** may be customized based on the heat generating sources in the ultrasound probe **700**. By way of non-limiting example, a phase change material **720** that is configured to melt at 35° C. may be selected. Moreover, use of the phase change material **720** advantageously provides a uniformity in temperature as the phase

change processes take place over a constant temperature. Accordingly, all the components of the ultrasound probe **700** that are in contact with the phase change material **720** may be maintained at a constant temperature for a determined period of time. Hence, the ultrasound probe **700** may be maintained at near isothermal device temperatures until all the phase change material **720** has melted by transitioning from the solid phase to the liquid phase. Accordingly, in the embodiment of FIG. 7, heat generated by the transducer assembly **710** and/or the components **712** of the ultrasound probe **700** may be transferred to the 3D vapor chamber **706** for dissipation and/or to the thermal energy storage chamber **708** for storage in the phase change material **720**.

(119) Moreover, as previously noted, the phase change chamber **704** having the 3D vapor chamber **706** and the thermal energy storage chamber **708** may be created using additive manufacturing, such as by being formed using three-dimensional (3D) printing, rapid prototyping (RP), direct digital manufacturing (DDM), selective laser melting (SLM), electron beam melting (EBM), direct metal laser melting (DMLM), or the like.

(120) Turning now to FIG. 8, a diagrammatical illustration **800** of a cross-section of yet another embodiment of an ultrasound probe, in accordance with aspects of the present specification, is depicted. FIG. 8 is described in conjunction with the components of FIGS. 1-7.

(121) In FIG. 7, the phase change material **720** was housed in one thermal energy storage chamber **708** disposed at one end of the ultrasound probe **700**. However, in accordance with further aspects of the present specification, the phase change material may also be distributed within an internal volume/surface of an ultrasound probe in one or more smaller volumes. Accordingly, in the embodiment of FIG. 8, the ultrasound probe **800** includes two or more thermal energy storage chambers disposed at different locations along the inner surface of an enclosure of a phase change chamber.

(122) In the embodiment depicted in FIG. 8, the ultrasound probe **800** is depicted as including an ultrasound probe handle **802** and a thermal management assembly in the form of a phase change chamber **804** within the ultrasound probe handle walls and configured to provide enhanced thermal management for the ultrasound probe **800**. In a presently contemplated configuration, the phase change chamber **804** includes a 3D vapor chamber **806** and two or more thermal energy storage chambers **808** configured to facilitate enhanced thermal management of the ultrasound probe **800** having the additional heat sources.

(123) As depicted in FIG. 8, the ultrasound probe **800** includes a transducer assembly **810**, one or more processors, ASICs, batteries, sensors and the like. Reference numeral **812** is used to represent components such as processors, ASICs, batteries, sensors, and the like. The components **812** are additional heat sources in the ultrasound probe **800** and are distributed in the volume of the ultrasound probe **800**. Also, these components **812** may be mounted on a mother board **814**.

(124) The 3D vapor chamber **806** is configured to interface with the various heat sources **812** of the ultrasound probe **800** to facilitate dissipation of heat generated by the heat sources **812**. In one embodiment, the 3D vapor chamber **806** includes one or more projections **816** such as finger-like protrusions configured to facilitate the enhanced transfer of heat from the heat generating internal components **812** of the ultrasound probe **800**. Additionally, each projection **816** is configured to be thermally coupled to at least one heat source **812**.

(125) Moreover, in certain embodiments, the ultrasound probe **800** and the 3D vapor chamber **806** in particular may include a thermal mounting platform **818** that is directly coupled to the transducer assembly **810** and configured to transfer heat generated by the transducer assembly **810** to the 3D vapor chamber **806** for dissipation to the surrounding environment.

(126) Furthermore, in the example of FIG. 8, the ultrasound probe **800** and more particularly the phase change chamber **804** additionally includes a thermal energy storage chamber **808** that is configured to house a phase change material (PCM) **820**. Heat is absorbed by the phase change material **820** when the phase change material **820** changes from a solid phase to a liquid phase. Also, the stored energy is released when the phase change material **820** changes from a liquid

phase to a solid phase. Moreover, the phase change material **820** may include materials such as, but not limited to, organic materials, inorganic materials, metallic alloys, eutectic alloys, paraffin wax, or combinations thereof. Furthermore, in certain embodiments, the phase change material **820** may be injected into or otherwise disposed in the thermal energy storage unit **808**.

(127) As previously noted, the heat generating components **812** are distributed within the volume of the ultrasound probe **800**. Accordingly, in the example of FIG. **8**, the ultrasound probe **800** additionally includes two or more thermal energy storage chambers **808** to facilitate enhanced heat dissipation from the heat generating components **812** in the ultrasound probe **800**. In accordance with aspects of the present specification, the thermal energy storage chambers **808** may be distributed within the volume of the ultrasound probe handle **802**.

(128) Each of the thermal storage chambers **808** is configured to house a corresponding phase change material **820**. Furthermore, each phase change material **820** may have a different phase transition temperature and may be of different types. Use of this configuration allows the added flexibility of having phase changing materials (PCMs) **820** with different melting points in each of the thermal energy storage chambers **808**. By way of example, a phase change material **820** having a desired melting temperature may be selected based on a desired maximum temperature of the heat generating component **812**. Consequently, the heat generating components **812** may be capped at different desirable peak temperatures by using phase change materials **820** of varying melting temperatures.

(129) In the embodiment **800** of FIG. **8**, a portion of heat generated by the internal components **812** of the ultrasound probe **800** may be dissipated through an outer surface of the 3D vapor chamber **806**. The remaining heat may be absorbed by the phase change materials **820** corresponding to the different thermal energy storage chambers **808** and stored in the respective thermal energy storage chambers **808** as the phase change materials **820** are transitioned from a solid phase to a liquid phase at respective phase transition temperatures.

(130) Moreover, in some embodiments, the phase change chamber **804** may also include one or more fins (not shown in FIG. **8**) configured to aid in dissipating heat generated in the ultrasound probe **800**. In one embodiment, these fins may be integral with the enclosure **824** of the 3D vapor chamber **806**. Also, these fins may be external fins.

(131) Also, in certain embodiments, each thermal energy storage chamber **808** may also include a corresponding set of fins **822**. These fins **822** may be internal fins. Also, as previously noted, each set of fins **822** may be uniformly spaced or disposed with variable spacing within a volume of the corresponding phase change material **820** in the thermal energy storage chamber **808** and configured to aid in dissipating heat from the phase change materials **820**. In particular, the phase change materials **820** are in thermal communication with the corresponding set of fins **822** to facilitate dissipation of heat stored within the phase change materials **820**.

(132) As will be appreciated, phase change materials are typically poor heat conductors and hence disadvantageously need internal heat spreading structures such as thermally conductive fins and foams. Advantageously, the thermal energy storage chambers **808** having the respective phase change materials **820** and the 3D vapor chamber **806** provide an ultrasound probe **800** having an enhanced heat dissipating ability. Moreover, the fins **822** provide the enhanced heat dissipating capability, thereby allowing effective storage of the heat in the phase change materials **820**.

Furthermore, the phase change materials **820** typically pose a containment risk as the phase change materials **820** expand while melting. However, integrating the thermal energy storage chambers **808** having the phase change materials **820** with the monolithic structure of the phase change chamber **804** alleviates any risk of leakage of the phase change materials **820**, thereby obviating the need for additional components such as O-rings, fasteners, and thicker shells.

(133) Use of the phase change material **820** in the thermal energy storage chamber **808** results in a lower surface area requirement of the ultrasound probe **800**, thereby allowing the ultrasound probe **800** to be smaller in size than a corresponding size of an ultrasound probe without the phase change

material **820**. Moreover, a choice of the phase change material **820** may be customized based on the heat generating sources in the ultrasound probe **800**. By way of non-limiting example, a phase change material **820** that is configured to melt at a desirable temperature may be selected. Also, in the embodiment of FIG. **8**, heat generated by the transducer assembly **810** and/or the components **812** of the ultrasound probe **800** may be transferred to the 3D vapor chamber **806** for dissipation and/or to the thermal energy storage chambers **808** for storage.

(134) Moreover, as previously noted, the phase change chamber **804** having the 3D vapor chamber **806** and the thermal energy storage chamber **808** may be created using additive manufacturing, such as by being formed using three-dimensional (3D) printing, rapid prototyping (RP), direct digital manufacturing (DDM), selective laser melting (SLM), electron beam melting (EBM), direct metal laser melting (DMLM), or the like.

(135) FIG. **9** is a diagrammatical illustration **900** of a cross-section of yet another embodiment of an ultrasound probe for use in the system **100** of FIG. **1**, in accordance with aspects of the present specification. Also, FIG. **9** is described in conjunction with the components of FIGS. **1-8**.

(136) According to further aspects of the present specification, the ultrasound probe **900** having an ultrasound probe handle **902** and a thermal management assembly in the form of a phase change chamber **904** that is configured to provide enhanced thermal management for the ultrasound probe **900** is depicted in FIG. **9**. In the example of FIG. **9**, the phase change chamber **904** is a 3D vapor chamber. Further, the 3D vapor chamber **904** includes projections finger-like protrusions **906** that are integral to an interior surface of an enclosure **908** of the 3D vapor chamber **904**. Also, the ultrasound probe **900** includes a transducer assembly **910**. In addition, the ultrasound probe **900** includes components **912** such as processors, ASICs, batteries, sensors and the like that may be mounted on a mother board **914**. Moreover, the 3D vapor chamber **904** may include a thermal mounting platform **916** configured to facilitate dissipation of heat generated by the transducer assembly **910**.

(137) In the embodiment depicted in FIG. **9**, the ultrasound probe **900** includes an outer protective shell **918** that is disposed such that the outer protective shell **918** encompasses the enclosure **908** the 3D vapor chamber **904**. Additionally, the ultrasound probe **900** may also include one or more extended surfaces such as fins and/or studs **920** that are disposed at least on an outer surface of the enclosure **908** of the 3D vapor chamber **904**. The fins **920** are external fins. Also, these fins and/or studs **920** aid in enhancing a contact surface area of the enclosure **908** of the 3D vapor chamber **904** with the outer protective shell **918**. It may be noted that the studs and/or fins **920** may be integrated with the enclosure **908** of the 3D vapor chamber **904**.

(138) Additionally, in some embodiments, the outer protective shell **918** may be a thin plastic shell. However, in another embodiment, the outer protective shell **918** may be fabricated by dip coating the 3D vapor chamber **904** in a plastic coating. It may be noted that the outer protective shell **918** is formed such that the outer protective shell **918** conforms to a shape of the 3D vapor chamber **904** and the studs and/or fins **920** disposed thereon. Moreover, the outer protective shell **918** is configured to shield the ultrasound probe **900** from electric contact. Also, the outer protective shell **918** is configured to act as a sealing element, thereby providing hygiene benefits to the ultrasound probe **900**. In addition, the material of the protective shell/coating **918** may be chosen to have anti-scratch, anti-bacterial, and/or anti-fungal properties.

(139) As previously noted with reference to FIG. **1**, the medical imaging system **108** may include an ultrasound imaging system. FIG. **10** is a block diagram **1000** of an embodiment of an ultrasound imaging system depicted in FIG. **1**. The ultrasound system **1100** includes an acquisition subsystem, such as the acquisition subsystem **110** of FIG. **1** and a processing subsystem, such as the processing subsystem **112** of FIG. **1**. The acquisition subsystem **110** may include a transducer assembly **1006**. In addition, the acquisition subsystem **110** includes transmit/receive switching circuitry **1008**, a transmitter **1010**, a receiver **1012**, and a beamformer **1014**. It may be noted that in certain embodiments, the transducer assembly **1006** is disposed in the probe **104** (see FIG. **1**). Also, in

certain embodiments, the transducer assembly **1006** may include a plurality of transducer elements (not shown) arranged in a spaced relationship to form a transducer array, such as a one-dimensional or two-dimensional transducer array, for example. Additionally, the transducer assembly **1006** may include an interconnect structure (not shown) configured to facilitate operatively coupling the transducer array to an external device (not shown), such as, but not limited to, a cable assembly or associated electronics. In the illustrated embodiment, the interconnect structure may be configured to couple the transducer array to the T/R switching circuitry **1008**.

(140) The processing subsystem **112** includes a control processor **1016**, a demodulator **1018**, an imaging mode processor **1020**, a scan converter **1022**, and a display processor **1024**. The display processor **1024** is further coupled to a display monitor **1036**, such as the display **118** (see FIG. 1), for displaying images. User interface **1038**, such as the user interface area **120** (see FIG. 1), interacts with the control processor **1016** and the display monitor **1036**. The control processor **1016** may also be coupled to a remote connectivity subsystem **1026** including a remote connectivity interface **1028** and a web server **1030**. The processing subsystem **112** may be further coupled to a data repository **1032**, such as the data repository **116** of FIG. 1, configured to receive and/or store ultrasound image data. The data repository **1032** interacts with an imaging workstation **1034**.

(141) The aforementioned components may be dedicated hardware elements such as circuit boards with digital signal processors or may be software running on a general-purpose computer or processor such as a commercial, off-the-shelf personal computer (PC). The various components may be combined or separated according to various embodiments of the invention. Thus, those skilled in the art will appreciate that the present ultrasound imaging system **1000** is provided by way of example, and the present specifications are in no way limited by the specific system configuration.

(142) In the acquisition subsystem **110**, the transducer assembly **1006** is in contact with the patient **102**. The transducer assembly **1006** is coupled to the transmit/receive (T/R) switching circuitry **1008**. Also, the T/R switching circuitry **1008** is in operative association with an output of transmitter **1010** and an input of the receiver **1012**. The output of the receiver **1012** is an input to the beamformer **1014**. In addition, the beamformer **1014** is further coupled to the input of the transmitter **1010** and to the input of the demodulator **1018**. The beamformer **1014** is also operatively coupled to the control processor **1016** as shown in FIG. 10.

(143) In the processing subsystem **112**, the output of demodulator **1018** is in operative association with an input of the imaging mode processor **1020**. Additionally, the control processor **1016** interfaces with the imaging mode processor **1020**, the scan converter **1022**, and the display processor **1024**. An output of imaging mode processor **1020** is coupled to an input of scan converter **1022**. Also, an output of the scan converter **1022** is operatively coupled to an input of the display processor **1024**. The output of display processor **1024** is coupled to the monitor **1036**.

(144) The ultrasound system **1000** transmits ultrasound energy into the subject such as the patient **102** and receives and processes backscattered ultrasound signals from the subject **102** to create and display an image. To generate a transmitted beam of ultrasound energy, the control processor **1016** sends command data to the beamformer **1014** to generate transmit parameters to create a beam of a desired shape originating from a certain point at the surface of the transducer assembly **1006** at a desired steering angle. The transmit parameters are sent from the beamformer **1014** to the transmitter **1010**. The transmitter **1010** uses the transmit parameters to properly encode transmit signals to be sent to the transducer assembly **1006** through the T/R switching circuitry **1008**. The transmit signals are set at certain levels and phases with respect to each other and are provided to individual transducer elements such as the source elements of the transducer assembly **1006**. The transmit signals excite the transducer elements to emit irradiating energy or waves with the same phase and level relationships. As a result, a transmitted beam of irradiating energy is formed in the patient **102** within a scan plane along a scan line when the transducer assembly **1006** is acoustically coupled to the patient **102** by using, for example, ultrasound gel. The process is known as

electronic scanning.

(145) The transducer assembly **1006** may be a two-way transducer. When the irradiating energy is transmitted into the patient **102**, the tissue being imaged may absorb at least a portion of the delivered irradiating energy. The absorbed energy may result in a thermoelastic expansion of the tissue, which in turn results in the generation of acoustic or ultrasound waves. The acoustic or ultrasound waves may be detected by the detector elements in the transducer assembly **1006**. The transducer assembly **1006** and more particularly, the detector elements in the transducer assembly **1006** may be configured to receive the acoustic waves at different times, depending on the distance into the tissue they return from and the angle with respect to the surface of the transducer assembly **1006** at which they return. The detector elements may be configured to convert the ultrasound energy from the acoustic waves into electrical signals.

(146) The electrical signals are then routed through the T/R switching circuitry **1008** to the receiver **1012**. The receiver **1012** amplifies and digitizes the received signals and provides other functions such as gain compensation. The digitized received signals corresponding to the backscattered waves received by each transducer element at various times preserve the amplitude and phase information of the backscattered waves.

(147) The digitized signals are sent to the beamformer **1014**. The control processor **1016** sends command data to beamformer **1014**. The beamformer **1014** uses the command data to form a receive beam originating from a point on the surface of the transducer assembly **1006** at a steering angle typically corresponding to the point and steering angle of the previous irradiating energy transmitted along a scan line. The beamformer **1014** operates on the appropriate received signals by performing time delaying and focusing, according to the instructions of the command data from the control processor **1016**, to create received beam signals corresponding to sample volumes along a scan line in the scan plane within the patient **102**. The phase, amplitude, and timing information of the received signals from the various transducer elements may be used to create the received beam signals.

(148) The received beam signals may be communicated to the processing subsystem **112**. The demodulator **1018** demodulates the received beam signals to create pairs of I and Q demodulated data values corresponding to sample volumes within the scan plane. Demodulation is accomplished by comparing the phase and amplitude of the received beam signals to a reference frequency. The I and Q demodulated data values preserve the phase and amplitude information of the received signals.

(149) The demodulated data is transferred to the imaging mode processor **1020**. The imaging mode processor **1020** uses parameter estimation techniques to generate imaging parameter values from the demodulated data in scan sequence format. The imaging parameters may include parameters corresponding to various possible imaging modes such as B-mode, color velocity mode, spectral Doppler mode, and tissue velocity imaging mode, for example. The imaging parameter values are passed to the scan converter **1022**. The scan converter **1022** processes the parameter data by performing a translation from scan sequence format to display format. The translation includes performing interpolation operations on the parameter data to create display pixel data in the display format.

(150) The scan converted pixel data is sent to the display processor **1024** to perform any final spatial or temporal filtering of the scan converted pixel data, to apply grayscale or color to the scan converted pixel data, and to convert the digital pixel data to analog data for display on the monitor **1036**. The user interface **1038** is coupled to the control processor **1016** to allow a user to interface with the ultrasound system **1000** based on the data displayed on the monitor **1036**.

(151) FIG. **11** is an example flow chart **1100** of a method of additive fabrication of an ultrasound probe having an ultrasound probe handle and a thermal management assembly in the form of a phase change chamber that is configured to provide enhanced thermal management for the ultrasound probe, in accordance with aspects of the present specification.

(152) At step **1102**, the method commences by additively fabricating first and second segments of an ultrasound probe handle. It may be noted that at least one segment of the first and second segments of the ultrasound probe handle includes a phase change chamber. The phase change chamber is monolithic with respect to the corresponding segment. Moreover, the phase change chamber includes hermetic chamber walls that extend around and define an enclosed chamber. In certain embodiments, the phase change chamber may be a 3D vapor chamber, a thermal energy storage chamber, or a combination thereof.

(153) Furthermore, a material is disposed within the hermetic chamber walls. The material is configured to change phase in response to heat received from a component of the ultrasound probe. Also, the material may include a working fluid and/or a phase change material. Various embodiments of the phase change chamber have been described with reference to FIGS. 2-9. If the phase change chamber is a 3D vapor change chamber, the material is a working fluid that is filled in the 3D vapor chamber. The working fluid has a liquid phase and a vapor phase and is configured to facilitate the dissipation of heat from the heat generating components of the ultrasound probe. Also, if the phase change chamber includes one or more thermal energy storage chambers, the material is a phase change material that may be filled in each of the thermal energy storage chambers. The phase change materials are configured to absorb and store at least a portion of the heat generated in the ultrasound probe and facilitate storage of the absorbed heat.

(154) Additionally, the phase change chamber having the 3D vapor chamber and/or the thermal energy storage chamber may be created using additive manufacturing, such as by being formed using three-dimensional (3D) printing, rapid prototyping (RP), direct digital manufacturing (DDM), selective laser melting (SLM), electron beam melting (EBM), direct metal laser melting (DMLM), or the like. In one embodiment, a single three-dimensional model of the ultrasound probe handle and/or the phase change chamber to be formed may be obtained. Further, the ultrasound probe handle may be additively fabricated based on the 3D model.

(155) Further, as previously noted, the phase change chamber is configured to facilitate enhanced transfer of heat from the heat generating components of the ultrasound probe. Accordingly, at step **1104**, one or more components of the ultrasound probe may be positioned in thermal communication with the phase change chamber. Some non-limiting examples of the components of the ultrasound probe include a transducer assembly, ASICs, processors, batteries, sensors, and the like. Also, in some embodiments, the processor, the battery, the sensor, and/or the ASIC may be mounted on a support platform such as a mother board.

(156) In particular, the phase change chamber is thermally coupled to one or more heat generating components of the ultrasound probe. In some embodiments, the phase change chamber may be directly thermally coupled to the heat generating components via use of a thermal interface material. Some non-limiting examples of the thermal interface material include thermal pads, grease, adhesive, and the like. For example, an adhesive material may be employed to form a thin adhesive joint between the phase change chamber and the heat generating components of the ultrasound probe. The adhesive material includes non-conductive epoxy, conductive epoxy, filled epoxy, and the like. Moreover, at step **1106**, the first and second segments of the ultrasound probe handle may be operatively coupled to form the ultrasound probe handle of the ultrasound probe.

(157) Also, in certain other embodiments, the method further includes additively fabricating one or more fins on the inner surface and/or the outer surface of the phase change chamber. These fins aid in further enhancing the heat dissipation capability of the vapor chamber. Moreover, the method may also include providing an outer protective shell such that the outer protective shell encompasses the enclosure of the vapor chamber.

(158) Furthermore, the foregoing examples, demonstrations, and process steps such as those that may be performed by the system may be implemented by suitable code on a processor-based system, such as a general-purpose or special-purpose computer. It should also be noted that different implementations of the present specification may perform some or all of the steps

described herein in different orders or substantially concurrently, that is, in parallel. Additionally, the functions may be implemented in a variety of programming languages, including but not limited to Ruby, Hypertext Preprocessor (PHP), Perl, Delphi, Python, C, C++, or Java. Such code may be stored or adapted for storage on one or more tangible, machine-readable media, such as on data repository chips, local or remote hard disks, optical disks (that is, CDs or DVDs), solid-state drives, or other media, which may be accessed by the processor-based system to execute the stored code. Note that the tangible media may include paper or another suitable medium upon which the instructions are printed. For instance, the instructions may be electronically captured via optical scanning of the paper or other medium, then compiled, interpreted or otherwise processed in a suitable manner if necessary, and then stored in the data repository or memory.

(159) It may be noted that the foregoing examples, demonstrations, and process steps that may be performed by certain components of the present systems, for example by the processing subsystem 112 may be implemented by suitable code on a processor-based system. The processor-based system, for example, may include a general-purpose or a special-purpose computer. It may also be noted that different implementations of the present specification may perform some or all of the steps described herein in different orders or substantially concurrently.

(160) Systems and methods of the present application present an exemplary design of a 3D thermal management system in the form of a 3D phase change chamber that is configured to provide a thermal management assembly/structure for an ultrasound probe. As will be appreciated, an important factor that restricts the use of ultrasound has been the fact that performing ultrasound scanning requires extended operation of an ultrasound probe at high power to render higher image resolution, while maintaining the surface and key component temperatures under their respective limits. The exemplary design of the phase change chamber provides enhanced heat transport from internal components of the ultrasound probe to an exterior/outer surface of the phase change chamber for cooling by the ambient environment and/or to phase change material volumes for thermal energy absorption/storage. Additionally, the phase change chamber forms an ergonomic exterior shape of a handle of the ultrasound probe and replaces multiple components such as heat spreaders, heat pipes, spine, PCB holder, and the associated interfaces that are used in traditional ultrasound probes. The phase change chamber provides a simplified structure of an ultrasound probe that results in reduced installation time and can accommodate additional heat loads. Additionally, the phase change chamber may also be configured to provide a mechanical support structure for the ultrasound probe.

(161) Although specific features of embodiments of the present specification may be shown in and/or described with respect to some drawings and not in others, this is for convenience only. It is to be understood that the described features, structures, and/or characteristics, illustrated in the figures and described herein, may be combined and/or used interchangeably in any suitable manner in the various embodiments, for example, to construct additional assemblies and methods for use in diagnostic imaging.

(162) While only certain features of the present specification have been illustrated and described herein, many modifications and changes will occur to those skilled in the art. It is, therefore, to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit of the invention.

Claims

1. An ultrasound probe, comprising: a transducer assembly including one or more individual transducer elements; an inner wall and an outer wall defining an enclosed phase change chamber between the inner wall and the outer wall, wherein the inner wall is in thermal communication with the transducer assembly, wherein the outer wall functions as an ultrasound probe handle, wherein the inner wall and the outer wall defining the phase change chamber are formed from a metal with

thermal conductivity, wherein the inner wall extends along an entirety of a length of the outer wall from a first side of the ultrasound probe to an opposite, second side of the ultrasound probe, and wherein the inner wall and the outer wall are hermetic walls; and a material disposed within the phase change chamber, wherein the material is configured to change phase in response to heat from a component of the ultrasound probe.

2. The ultrasound probe of claim 1, wherein the inner wall is coupled to the outer wall at the first side and the second side of the ultrasound probe, and wherein the phase change chamber extends along the entirety of the length of the outer wall.
3. The ultrasound probe of claim 2, wherein the ultrasound probe handle comprises a first segment and a second segment coupled together, and wherein the phase change chamber is collectively defined by the first segment and the second segment coupled together.
4. The ultrasound probe of claim 2, wherein the inner wall is in direct thermal communication with the transducer assembly and the phase change chamber is between the inner wall and the outer wall, wherein the transducer assembly is positioned at the first side of the ultrasound probe, wherein the outer wall includes a third side and a fourth side each extending along an entirety of the length of the outer wall, and wherein the inner wall is coupled to the outer wall along the third side and the fourth side.
5. The ultrasound probe of claim 1, wherein the phase change chamber comprises a vapor chamber extending along at least two orthogonal dimensions, wherein the material comprises a working fluid disposed in the vapor chamber, wherein the working fluid can be in a liquid phase or a gas phase, and wherein the working fluid is configured to transition between the liquid phase and the gas phase in response to heat.
6. The ultrasound probe of claim 5, wherein the vapor chamber further comprises a porous wick structure disposed inside and lining one or more interior surfaces of the inner and outer walls, and wherein the porous wick structure comprises pores configured to hold the liquid phase of the working fluid inside the vapor chamber.
7. The ultrasound probe of claim 1, wherein the phase change chamber is configured to store thermal energy.
8. The ultrasound probe of claim 1, further comprising a plurality of fins in thermal communication with the phase change chamber and configured to transfer heat between one or more components of the ultrasound probe and the phase change chamber, wherein the plurality of fins extend into the phase change chamber from an inner surface of the outer wall and/or an inner surface of the inner wall, and wherein the plurality of fins is distributed along a length of the phase change chamber.
9. The ultrasound probe of claim 1, wherein the phase change chamber includes a 3D vapor chamber and a thermal energy storage chamber separated by a common wall, and wherein the material disposed within the phase change chamber includes a first material disposed within the 3D vapor chamber and a second, different material disposed within the energy storage chamber.
10. The ultrasound probe of claim 1, wherein the phase change chamber is vacuum sealed.
11. The ultrasound probe of claim 1, wherein the component comprises the transducer assembly, a processor, a battery, a sensor, an application specific integrated circuit, or combinations thereof, and wherein the phase change chamber has a shape that corresponds to a shape of the outer wall.
12. The ultrasound probe of claim 11, further comprising a thermal mounting platform coupled to the phase change chamber, wherein the thermal mounting platform is directly coupled to the transducer assembly and configured to transfer heat generated by the transducer assembly to the phase change chamber.
13. The ultrasound probe of claim 1, wherein the phase change chamber comprises an additively manufactured structure such that each of the inner wall and outer wall is monolithic.
14. The ultrasound probe of claim 1, wherein the inner wall and the outer wall together form a shell, an outer surface of the shell being the outer wall, the phase change chamber being a space between the inner wall and the outer wall and entirely within the shell.

15. The ultrasound probe of claim 1, wherein the phase change chamber further includes a projection in direct thermal contact with the component, and wherein the projection comprises a portion of the phase change chamber that extends inward at least partially towards an inner section of the ultrasound probe.
 16. The ultrasound probe of claim 1, further comprising a heat dissipating component, wherein the heat dissipating component is in direct contact with both the phase change chamber and the component.
 17. The ultrasound probe of claim 1, wherein the metal is one of titanium, aluminum, or copper.
 18. The ultrasound probe of claim 1, wherein the phase change chamber is a three-dimensional (3D) vapor chamber.
-