

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397920
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Czapla; Lionel et al.

Device for coupling a propulsion system to an engine pylon of an aircraft, and corresponding aircraft

Abstract

A device for coupling a propulsion system to an engine pylon of an aircraft, the device comprising a baseplate comprising first and second parts of the baseplate placed against each other so as to form a base suitable for being fastened to the propulsion system, and a first wall extending substantially perpendicularly to the base. The first wall of the baseplate interacts with a sleeve, a pair of flanges and fasteners to the engine pylon.

Inventors: Czapla; Lionel (Toulouse, FR), Fukasaku; Kotaro (Toulouse, FR), Amargier; Rémi (Toulouse, FR)

Applicant: Airbus Operations SAS (Toulouse, FR)

Family ID: 1000008782214

Assignee: Airbus Operations SAS (Toulouse, FR)

Appl. No.: 18/742442

Filed: June 13, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240417090 A1	Dec. 19, 2024

Foreign Application Priority Data

FR	2306195	Jun. 16, 2023
----	---------	---------------

Publication Classification

Int. Cl.: B64D27/40 (20240101)

U.S. Cl.:

CPC **B64D27/402** (20240101);

Field of Classification Search

CPC: B64D (27/40); B64D (27/402); B64D (27/404); B64D (27/406); F02C (7/20)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4717094	12/1987	Chee	N/A	N/A
4943013	12/1989	Kapala et al.	N/A	N/A
5927644	12/1998	Ellis et al.	N/A	N/A
6581874	12/2002	Lemire	60/797	B64D 41/00
2009/0108127	12/2008	Cazals	244/54	B64D 27/40
2011/0266389	12/2010	Combes et al.	N/A	N/A
2014/0084129	12/2013	Sandy	248/554	B64D 27/40
2022/0355946	12/2021	Berjot	N/A	B64D 27/404

OTHER PUBLICATIONS

French Search Report for corresponding French Patent Application No. 2306195 dated Dec. 5, 2023. cited by applicant

Primary Examiner: Michener; Joshua J
Assistant Examiner: Zohoor; Colin
Attorney, Agent or Firm: Greer, Burns & Crain, Ltd.

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS

(1) This application claims the benefit of French Patent Application Number 2306195 filed on Jun. 16, 2023, the entire disclosure of which is incorporated herein by way of reference.

FIELD OF THE INVENTION

(2) The present invention relates to a device for coupling a propulsion system to the wing of an aircraft. More specifically, the invention relates to a device for coupling a propulsion system to the engine pylon of the aircraft, and to an aircraft comprising a propulsion system and at least one such device for coupling the propulsion system to the engine pylon.

BACKGROUND OF THE INVENTION

(3) Usually, for an aircraft, a propulsion unit comprises for example a turbojet engine that is fastened to a wing of the aircraft using an engine pylon. The engine pylon generally consists of a structure comprising a plurality of tubes fastened to ribs.
(4) The turbojet engine is fastened to the ribs of the engine pylon by means of engine mounts that conventionally comprise a plurality of front engine mounts at the front, and a plurality of rear engine mounts at the rear. Generally, the turbojet engine is fastened by its gearbox at the front, and

by the body of the turbojet engine at the rear.

(5) FIG. 2 illustrates an example of a prior art mount **9** for coupling a turbojet engine T to the engine pylon M of an aircraft. The mount **9** comprises a baseplate **90** in the shape of an inverted T, comprising a base **900** from which a wall **902** extends substantially (i.e., $\pm 10\%$) perpendicularly. The base **900** has a generally quadrilateral shape and is suitable for being in contact with the turbojet engine T and fastened to the turbojet engine T, for example using threaded elements (on the gearbox for the front mount and on the body of the turbojet engine for the rear mount, for example).

(6) The wall **902** comprises a bore in which a sleeve (not shown) is housed, which itself has a bore through which is threaded a fastening pin **91** that is fastened to the engine pylon M, for example by screwing. The mount **9** further comprises shock absorbing pads **92** implemented on either side of the wall **902** of the baseplate **90** and held by a set of flanges **93** in order to partially absorb the forces generated by the turbojet engine. A mount **9** implementing pads **92** is also referred to as a flexible mount. A spacer **94** can also be implemented, around part of the sleeve, between the mount **9** and the engine pylon M.

(7) Although the current installations are satisfactory in terms of fastening the turbojet engine to the engine pylon, the implementation of these installations requires a plurality of these installations in order to guard against the potential failure of the mount, particularly in the event that the base **900** breaks or cracks. Having a plurality of these installations leads to excess weight and therefore increased fuel consumption, which is unsatisfactory.

(8) There is therefore a need to provide a solution ensuring optimum and more secure fastening of a turbojet engine to the wing of an aircraft.

SUMMARY OF THE INVENTION

(9) An object of the present invention is to propose a device for coupling a propulsion system to the engine pylon of an aircraft, this device providing a more secure solution for fastening a propulsion system in the event of the failure of the mount.

(10) To this end, a device is proposed for coupling a propulsion system to an engine pylon of an aircraft, said device comprising: a baseplate substantially in the shape of an inverted T, said baseplate comprising a base suitable for being fastened to said propulsion system and a first wall extending substantially perpendicularly to said base, said first wall comprising a first bore extending along a longitudinal axis; a substantially tubular sleeve comprising a first portion at least partially received in said first bore of said baseplate and a second portion, a first end of which extends in the continuation of said first portion towards said engine pylon, a second end of said second portion being suitable for interacting with said engine pylon, said sleeve comprising a central bore coaxial with said longitudinal axis; fastening means comprising a first nut suitable for being rigidly connected to said engine pylon and a first fastening screw, said first fastening screw comprising a first fastening head from which extends perpendicularly a first threaded shank, said first threaded shank being fitted through said central bore of said sleeve; a second front flange and a second rear flange, said second flanges being arranged respectively on either side of said first wall of said baseplate, said second flanges each comprising a fourth bore coaxial with said longitudinal axis; a spacer suitable for being arranged between said second rear flange and said engine pylon, said spacer comprising a fifth bore coaxial with said longitudinal axis so that said spacer is fitted onto said second portion of said sleeve.

(11) Said first portion of said sleeve is fitted through said fourth bores of said second flanges. Said first fastening head bears against said second front flange and said first threaded shank is fitted through said central bore of said sleeve, said first threaded shank being screwed to said first nut rigidly connected to said engine pylon.

(12) According the invention, said baseplate comprises a first part and a second part of the baseplate, each of said first and second parts being L-shaped, wherein said first part comprises a first base wall from which extends perpendicularly a second wall comprising a sixth bore, and said

second part comprises a second base wall from which extends perpendicularly a third wall comprising a seventh bore.

(13) Said first and second parts of the baseplate are placed against each other so that said second wall and said third wall together form said first wall of said baseplate, said first and second base walls together form said base of said baseplate, and said sixth and seventh bores together form said first bore.

(14) As a result, if one of the first or second parts of the baseplate fails, the other part of the baseplate ensures that the propulsion system continues to be coupled to the engine pylon. The risk of the complete loss of the device for coupling the propulsion system to the engine pylon is therefore reduced.

(15) Advantageously, the device comprises means for centering said first and second parts of the baseplate relative to each other along said longitudinal axis.

(16) According to one particular aspect, said centering means comprise at least one male cylinder coaxial with the longitudinal axis, protruding from a first contact face of said second wall, or of said third wall respectively, and at least one cylindrical recess coaxial with the longitudinal axis, for receiving said at least one male cylinder, said at least one cylindrical recess being made in a second contact face of said third wall, or of said second wall respectively, said first and second contact faces being arranged facing each other when said first and second parts of the baseplate are assembled.

(17) According to another particular aspect, the fastening means comprise a second nut positioned bearing against a free end of said first threaded shank at the opposite end from said first fastening head, the second fastening means also comprising a second fastening screw comprising a second fastening head from which extends perpendicularly a second threaded shank. Said second fastening head bears against said first fastening head and said second threaded shank is fitted through an eighth bore extending coaxially with said longitudinal axis, passing through said first fastening screw, and said second threaded shank is screwed into said second nut.

(18) According to another particular aspect, the device also comprises: a pair of first flanges, said first flanges being fastened respectively on either side of said first wall of said baseplate, said first flanges each comprising a second bore coaxial with said longitudinal axis; and a pair of pads, said pads being arranged respectively against one of said first flanges, said pads each comprising a third bore coaxial with said longitudinal axis; wherein said pads are each clamped between a second flange and a first flange; and wherein each first portion of said sleeve is threaded through said second bores of said first flanges and through said third bores of said pads.

(19) The invention also proposes an aircraft comprising a propulsion system, an engine pylon and at least one device as described above, said propulsion system being coupled to the engine pylon by said at least one device, wherein said baseplate is fastened to said propulsion system and said first nut is fastened to said engine pylon.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The aforementioned features of the invention, along with others, will become more apparent on reading the following description of an embodiment and its variants, said description being given with reference to the appended drawings, in which:

(2) FIG. 1 is a side view of an aircraft according to the invention;

(3) FIG. 2 is a perspective view of a mount according to a prior art solution;

(4) FIG. 3 is a perspective view of a coupling device according to one exemplary embodiment of the invention;

(5) FIG. 4 is a cross-sectional side view along the plane A of the device in FIG. 3;

(6) FIG. 5 is a cross-sectional side view along the plane A of a first variant of the device in FIG. 3;
(7) FIG. 6 is a cross-sectional side view along the plane A of a second variant of the device in FIG. 3; and

(8) FIG. 7 is a cross-sectional side view along the plane A of a third variant of the device in FIG. 3.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(9) FIG. 1 shows an aircraft **10** that comprises a propulsion system **102**, for example a turbojet engine or turboprop engine. The propulsion system **102** is connected to a wing **104** of the aircraft **10** by means of an engine pylon **106**.

(10) In the following description, terms relating to a position are given with reference to an aircraft in the normal flight position, that is, as shown in FIG. 1, and the positions “front” and “rear” are given relative to the front and rear of the propulsion system **102** and relative to the direction of travel **F** of the aircraft **10** when the propulsion system **102** is operating.

(11) In the following description, and by convention, the X direction is the longitudinal direction of the propulsion system, which is horizontal when the aircraft is on the ground, the Y direction is the transverse direction, which is horizontal when the aircraft is on the ground, and the Z direction is the vertical direction, which is vertical when the aircraft is on the ground, these three directions X, Y and Z being mutually orthogonal.

(12) The engine pylon **106** and the propulsion system **102** have a vertical mid-plane XZ and the propulsion system **102** is in this case a turboprop engine with a propeller **102a**, but it could be a turbofan engine with a nacelle.

(13) FIGS. 3 and 4 show a device **2** for coupling a propulsion system **102** to the engine pylon **106** of the aircraft **10** according to a main embodiment of the invention. Here, the device **2** is illustrated horizontally so that the elements can be described in relation to the orthonormal coordinate system X, Y, Z described above. It will clearly be understood that the device **2** can be arranged and oriented differently in order to adapt to the propulsion system **102** and engine pylon **106** to which the device is fastened. FIG. 4 illustrates a cross-sectional side view along the section plane A. The section plane A is a plane parallel to the vertical plane XZ passing through the axis of the first fastening screw described in greater detail hereinafter. The section plane A is the same for FIGS. 5 to 7.

(14) In this example, the device **2** comprises a baseplate **20** substantially in the shape of an inverted T. This baseplate **20** comprises a substantially flat base **200**, which in this illustration extends in a plane parallel to the plane XY. The base **200** is suitable for being fastened to the propulsion system **102** by fastening means such as threaded elements. To this end, the base **200** has, in this example, holes **205** made at least in each corner of the base **200**. The holes **205** are each suitable for receiving a fastening screw to allow a screw fastening. Other techniques for fastening the baseplate to the propulsion system can be envisaged, such as riveting or welding in particular.

(15) The baseplate **20** comprises a first wall **201** that extends perpendicularly to the base **200**, that is, in a plane parallel to the plane YZ. The first wall **201** further comprises a first bore **202** situated substantially in the center of the first wall **201** and that extends along a longitudinal axis **5**, which is shown here substantially parallel to the horizontal axis X.

(16) The baseplate **20** can also comprise lateral reinforcing walls **203** extending between the base **200** and the first wall **201**, on the lateral edges of the baseplate **20**, so as to absorb the mechanical forces. In this example, the lateral walls **203** are triangular.

(17) The device **2** also comprises a generally tubular sleeve **50** extending coaxially with the longitudinal axis **5**. The sleeve **50** comprises a first portion **502** at least part of which is received in the first bore **202** of the baseplate **20**, and a second portion **504** a first end of which extends from and in the continuation of the first portion **502** towards the engine pylon **106**.

(18) As illustrated in FIG. 4, the free end of the second portion **504** is suitable for interacting with the engine pylon **106**. More specifically, the free end of the second portion **504** is fitted into a recess **107** made in the engine pylon **106**.

(19) In this example, the first and second portions **502**, **504** are separated by a shoulder **508** making it possible to optimize the positioning of the sleeve **50**, as described in greater detail hereinafter.

(20) The sleeve **50** further comprises a central bore **506** extending coaxially with the first bore **202** of the baseplate **20**. This central bore **506** is suitable for receiving a first fastening screw **221**, described below.

(21) The device **2** comprises fastening means **22** that make it possible to fasten the device **2** to the engine pylon **106**. To this end, the fastening means **22** comprise a first nut **220** rigidly connected to the engine pylon **106** and a first fastening screw **221**. In this example, the first nut **220** rigidly connected to the engine pylon **106** is captive, but any other type of nut that can be rigidly connected to the engine pylon can be implemented. An axial assembly clearance **J1** (visible in FIG. **4**) can be provided between the free end of the second portion **504** of the sleeve **50** and the first nut **220** so as to allow the deformation of the pads described hereinafter on the tightening of the first fastening screw **221**. The axial clearance **J1** also allows the compression of the spacer **30** between the engine pylon **106** and a second rear flange **282b** described hereinafter.

(22) The first fastening screw **221** comprises a first fastening head **222** arranged at the opposite end from the engine pylon **106** and that bears against a second front flange **282a** (described below). A first threaded shank **223** extends perpendicularly from the first fastening head **222**, along the longitudinal axis **5**, and is fitted through the central bore **506** of the sleeve **50**. The first threaded shank **223** has a length greater than the length of the sleeve **50** so that it can be screwed into the nut **220** rigidly connected to the engine pylon **106**. The sleeve **50**, via the fastening means **22**, makes it possible to transfer the shear forces generated by the propulsion system **102** to the engine pylon **106**.

(23) The device **2** further comprises a pair of first flanges comprising a first front flange **242a** and a first rear flange **242b**. The first front and rear flanges **242a**, **242b** are respectively fastened on either side of the first wall **201** of the baseplate **20**. In this example, the first front and rear flanges **242a**, **242b** are fastened to the first wall **201** using fastening screws situated in the vicinity of the lateral edges of the first wall **201**. However, it will be understood that other fastening means can be envisaged without departing from the scope of the invention.

(24) The first front and rear flanges **242a**, **242b** each comprise a second bore, **244a**, **244b** respectively, extending coaxially with the longitudinal axis **5**. The dimensions of the second bores **244a**, **244b** are configured so that they can receive the first portion **502** of the sleeve **50**. In this example, a radial assembly clearance is provided between the second bores **244a**, **244b** and the first portion **502** of the sleeve **50** in order to allow the deformation of the pads (described below) up to a predetermined load level.

(25) The device **2** comprises at least one pair of pads that allow the predetermined deformation of the device **2** in order to at least partially absorb the forces generated by the propulsion system **102**. Implementing these pads makes it possible to obtain a “flexible mount”.

(26) In this example, the device **2** comprises two pads, namely a front pad **262a** and a rear pad **262b**. The front and rear pads **262a**, **262b** are arranged respectively bearing against the first front flange **242a** and the first rear flange **242b**.

(27) The front and rear pads **262a**, **262b** each comprise a third bore, **264a**, **264b** respectively, extending coaxially with the longitudinal axis **5**. The dimensions of the third bores **264a**, **264b** are configured so that they can receive the first portion **502** of the sleeve **50**. In this example, a radial assembly clearance is provided between the third bores **264a**, **264b** and the first portion **502** of the sleeve **50** in order to allow the deformation of the pads **262a**, **262b** up to a predetermined load level. In this example, the pads **262a**, **262b** are made from an elastomer the elasticity of which can be selected as a function of the maximum deformation desired, for example.

(28) The device **2** further comprises a pair of second flanges comprising a second front flange **282a** and a second rear flange **282b**. The second front and rear flanges **282a**, **282b** are respectively arranged on either side of the first wall **201** of the baseplate **20**. More specifically, the second front

and rear flanges **282a**, **282b** respectively bear against the front and rear pads **262a**, **262b** so that the front pad **262a** is clamped between the first front flange **242a** and the second front flange **282a**, and the rear pad **262b** is clamped between the first rear flange **242b** and the second rear flange **282b**.

(29) The second front and rear flanges **282a**, **282b** each comprise a fourth bore, **284a**, **284b** respectively, extending coaxially with the longitudinal axis **5**. In this example, no radial assembly clearance is provided between the fourth bores **284a**, **284b** and the first portion **502** of the sleeve **50** in order to allow conjoint radial movement between the sleeves **50** and the second front and rear flanges **282a**, **282b**. In particular, the first and second parts **21**, **22** of the baseplate move relative to the sleeve **50** and relative to the second front and rear flanges **282a**, **282b** due to the deformation of the pads **262a**, **262b**.

(30) The sleeve **50** drives the second front and rear flanges **282a**, **282b**, which in turn cause the deformation of the pads **262a**, **262b**.

(31) The second front and rear flanges **282a**, **282b** each comprise, on their faces **287a**, **287b** that are facing each other when the device **2** is assembled, that is their faces in contact with the pad, first and second cavities **288a**, **288b**. More specifically, the first cavity **288a** made on the face **287a** of the second front flange **282a** makes it possible to receive the free end of the first portion **502** of the sleeve **50**. In this example, an axial assembly clearance **J2** (visible in FIG. **4**) is provided between the cavity **288a** and the first portion **502** of the sleeve **50**, in order to allow the deformation of the pads **262a**, **262b** on the tightening of the first fastening screw **221**. The second cavity **288b** made on the face **287b** of the second rear flange **282b** makes it possible to receive the shoulder **508** separating the first and second portions **502**, **504** of the sleeve **50**.

(32) The device **2** also comprises a spacer **30** suitable for being arranged between the second rear flange **282b** and the engine pylon **106**, and for bearing against the second rear flange **282b** and the engine pylon **106** when the device **2** is assembled. When the first fastening screw **221** is tightened, the spacer **30** is therefore compressed between the second rear flange **282b** and the engine pylon **106**.

(33) The spacer **30** comprises a fifth bore **32** extending coaxially with the longitudinal axis **5**. The dimensions of the fifth bore **32** are configured so that they can receive the second portion **504** of the sleeve **50**. More specifically, the spacer **30** is fitted onto the second portion **504** of the sleeve **50** and therefore extends around the second portion **504** of said sleeve **50**.

(34) The first portion **502** of the sleeve **50** is therefore fitted through the second bores **244a**, **244b** of the first flanges **242a**, **242b**, through the third bores **264a**, **264b** of the pads **262a**, **262b** and through the fourth bores **284a**, **284b** of the second flanges **282a**, **282b**, while the spacer **30** is fitted onto the second portion **504** of the sleeve **50**. In addition, the first fastening head **222** bears against the second front flange **282a** and the first threaded shank **223** is fitted through the central bore **506** of the sleeve **50** in order to be screwed to the first nut **220** rigidly connected to the engine pylon **106**. Implementing the spacer **30** and the second flanges **282a**, **282b** therefore makes it possible, on the tightening of the first fastening screw **221**, to clamp the elements of the device **2** together.

(35) Optionally, the device **2** can implement a protective cylinder **60** that is fitted onto at least part of the first portion **502** of the sleeve **50**. The cylinder **60** makes it possible to protect the sleeve **50** from any contact and friction between it and the baseplate **20** on the deformation of the pads **262a**, **262b**.

(36) According to the invention, and in order to provide a solution in the event the failure of the baseplate **20** (such as a crack in the base **200**, for example), the baseplate **20** is divided so that it comprises a first part **21** and a second part **23** of the baseplate **20**. As a result, if one of the first or second parts **21**, **22** of the baseplate **20** fails, the other part of the baseplate ensures that the propulsion system **102** continues to be coupled to the engine pylon **106**. The risk of the complete loss of the device **2** for coupling the propulsion system **102** to the engine pylon **106** is therefore reduced. In addition, this solution makes it possible to provide multiple paths (via the first and second parts of the baseplate) for transferring the forces generated by the propulsion system **1002**

to the engine pylon **106**.

(37) More specifically, each of the first and second parts **21**, **23** is in the shape of an L the vertical portions of which are placed against each other on assembly of the device **2**. The first part **21** comprises a first base wall **210** extending in a plane parallel to the horizontal plane XY from which extends perpendicularly a second wall **212**, which therefore extends in a plane parallel to the vertical plane YZ. The second wall **212** comprises a sixth bore **214** extending coaxially with the longitudinal axis **5**.

(38) The second part **23** of the baseplate **20** comprises a second base wall **230** extending in a plane parallel to the horizontal plane XY and from which extends perpendicularly a third wall **232**, which therefore extends in a plane parallel to the vertical plane YZ. The third wall **232** comprises a seventh bore **234** extending coaxially with the longitudinal axis **5**. In this example, each of the first and second parts **21**, **23** of the baseplate **20** comprises lateral reinforcing walls **203**.

(39) The first and second parts **21**, **23** of the baseplate **20** are arranged bearing against each other so that the second wall **212** and the third wall **232** are placed against each other and together form the first wall **201** of the baseplate **20**, the first base wall **210** and the second base wall **230** together form the base **200** of the baseplate **20**, and the sixth and seventh bores **214**, **234** together form the first bore **202** of the baseplate **20**.

(40) In the example illustrated in FIGS. **3** and **4**, each of the first and second base walls **210**, **230** comprises four holes **205** made substantially in each corner of the first and second base walls **210**, **230**. The holes **205** are each suitable for receiving a fastening screw that makes it possible to fasten the first and second parts **21**, **23** of the baseplate **20** to the propulsion system **102**.

(41) In a first variant of the main exemplary embodiment, and as illustrated in FIG. **5**, the device **2** further comprises means **40** for centering the first and second parts **21**, **23** of the baseplate **20** relative to each other relative to the direction X, and more specifically relative to the longitudinal axis **5** of the first fastening screw **221**. These centering means **40** make it possible to facilitate the positioning of the first and second parts **21**, **23** of the baseplate **20** relative to each other and the assembly of the different elements of the device **2**. The centering means **40** also make it possible to improve the holding of the first and second parts **21**, **23** of the baseplate **20** relative to each other, for example on the failure of one of the first and second parts **21**, **23** of the baseplate **20**.

(42) In this example, the centering means **40** comprise at least one male cylinder **402**, coaxial with the longitudinal axis **5**, borne by and protruding from a first contact face **211**, **231** of the part **21** or the part **22** of the baseplate **20**. The at least one male cylinder **402** interacts with a corresponding female cylindrical recess **404** for receiving the male cylinder **402**. The cylindrical recess **404** extends coaxially with the longitudinal axis **5** and is made in a second contact face **211**, **231** of the other of the parts **21**, **23**. The first and second contact faces are arranged facing each other when the first and second parts **21**, **23** of the baseplate **20** are assembled.

(43) More particularly, in the example illustrated in FIG. **5**, the first wall **201** of the first part **21** of the baseplate **20** comprises a cylindrical recess **404** on its second contact face **211**, oriented towards the second part **23** of the baseplate **20**. The second wall **230** of the second part **23** of the baseplate **20** comprises a male cylinder **402** protruding from the first contact face **231** oriented towards the first part **21** of the baseplate **20**. The male cylinder **402** and the cylindrical recess **404** have corresponding dimensions and positions so that the male cylinder **402** of the second part **23** of the baseplate **20** is received in the cylindrical recess **404** of the first part **21** of the baseplate **20**.

(44) It will be clearly understood that the male cylinder could be borne by the first part of the baseplate and the cylindrical recess could be made in the second part of the baseplate without departing from the scope of the invention.

(45) In a second variant of the main exemplary embodiment, and as illustrated in FIG. **6**, the device **2** comprises a solution in the event of the failure of the first fastening screw **221**. In this second variant, the fastening means **22** of the device **2** comprise a second nut **224**, referred to as a lock nut, and a second fastening screw **225**. The second nut **224** is arranged within the engine pylon **106** and

bears against the free end of the first threaded shank 223 of the first fastening screw 221, that is at the opposite end from the first fastening head 222 of the first fastening screw 221. More specifically, the second nut 224 is housed in the engine pylon 106 and is a through nut. The second fastening screw 225 comprises a second fastening head 226 bearing against the first fastening head 221 from which extends perpendicularly a second threaded shank 227, along the longitudinal axis 5. The second threaded shank 227 is fitted through an eighth bore 228 passing through the first fastening screw 221 and extending along the longitudinal axis 5. The length of the second threaded shank 227 is selected so that the second threaded shank 227 extends beyond the free end of the first threaded shank 223 and the second threaded shank 227 can be screwed into the second nut 224.

(46) As a result, in the event of the failure of the first fastening screw 221 (the breaking of the threaded shank, for example), the second fastening screw 225 takes over so as to ensure that the propulsion system 102 continues to be coupled to the engine pylon 106. In other words, the second fastening screw 225 is a “backup”, in that it is not directly engaged with the elements of the device 2, unlike the first fastening screw 221. The second fastening screw 225 is only engaged in the event of the failure of the first fastening screw 221.

(47) In a third variant illustrated in FIG. 7, the device 2 comprises both the centering means 40 described with reference to FIG. 5 and the second fastening screw 225 described with reference to FIG. 6. As the implementation of the centering means 40 and the second fastening screw is identical, it is not described again. Such a device 2 therefore proposes a solution in the event of the failure of the baseplate 20 and/or the first fastening screw 221.

(48) While at least one exemplary embodiment of the present invention(s) is disclosed herein, it should be understood that modifications, substitutions and alternatives may be apparent to one of ordinary skill in the art and can be made without departing from the scope of this disclosure. This disclosure is intended to cover any adaptations or variations of the exemplary embodiment(s). In addition, in this disclosure, the terms “comprise” or “comprising” do not exclude other elements or steps, the terms “a” or “one” do not exclude a plural number, and the term “or” means either or both. Furthermore, characteristics or steps which have been described may also be used in combination with other characteristics or steps and in any order unless the disclosure or context suggests otherwise. This disclosure hereby incorporates by reference the complete disclosure of any patent or application from which it claims benefit or priority.

Claims

1. A device for coupling a propulsion system to an engine pylon of an aircraft, said device comprising: a baseplate in a shape of an inverted T, said baseplate comprising a base configured to be fastened to said propulsion system and a first wall extending substantially perpendicularly to said base, said first wall comprising a first bore extending along a longitudinal axis; a tubular sleeve comprising a first portion at least partially received in said first bore of said baseplate, and a second portion a first end of which extends in a continuation of said first portion towards said engine pylon, a second end of said second portion being configured to interact with said engine pylon, said sleeve comprising a central bore coaxial with said longitudinal axis; fastening means comprising a first nut configured to be rigidly connected to said engine pylon and a first fastening screw, said first fastening screw comprising a first fastening head from which extends perpendicularly a first threaded shank, said first threaded shank being fitted through said central bore of said sleeve; a second front flange and a second rear flange, said second front and rear flanges being arranged respectively on either side of said first wall of said baseplate, said second flanges each comprising a fourth bore coaxial with said longitudinal axis; a spacer configured to be arranged between said second rear flange and said engine pylon, said spacer comprising a fifth bore coaxial with said longitudinal axis so that said spacer is fitted onto said second portion of said sleeve; wherein said first portion of said sleeve is fitted through said fourth bores of said second

flanges; wherein said first fastening head bears against said second front flange, and said first threaded shank is fitted through said central bore of said sleeve, said first threaded shank being screwed to said first nut rigidly connected to said engine pylon; wherein said baseplate comprises a first part and a second part of the baseplate, each of said first and second parts being L-shaped, wherein said first part comprises a first base wall from which extends perpendicularly a second wall comprising a sixth bore, and said second part comprises a second base wall from which extends perpendicularly a third wall comprising a seventh bore, said first and second parts of the baseplate being placed against each other so that said second wall and said third wall together form said first wall of said baseplate, said first and second base walls together form said base of said baseplate, and said sixth and seventh bores together form said first bore.

2. The device according to claim 1, further comprising: means for centering said first and second parts of the baseplate relative to each other along said longitudinal axis.

3. The device according to claim 2, wherein said means for centering comprise at least one male cylinder coaxial with the longitudinal axis, protruding from a first contact face of said second wall, or of said third wall respectively, and at least one cylindrical recess coaxial with the longitudinal axis, for receiving said at least one male cylinder, said at least one cylindrical recess being made in a second contact face of said third wall, or of said second wall respectively, said first and second contact faces being arranged facing each other when said first and second parts of the baseplate are assembled.

4. The device according to claim 1, wherein said fastening means comprise a second fastening means having a second nut positioned bearing against a free end of said first threaded shank at an opposite end from said first fastening head, the second fastening means also comprising a second fastening screw comprising a second fastening head from which extends perpendicularly a second threaded shank, wherein said second fastening head bears against said first fastening head, and said second threaded shank is fitted through an eighth bore extending coaxially with said longitudinal axis, passing through said first fastening screw, and said second threaded shank is screwed into said second nut.

5. The device according to claim 1, further comprising: a pair of first flanges, said first flanges being fastened respectively on either side of said first wall of said baseplate, said first flanges each comprising a second bore coaxial with said longitudinal axis; and a pair of pads, said pads being arranged respectively against one of said first flanges, said pads each comprising a third bore coaxial with said longitudinal axis; wherein said pads are each clamped between a second flange and a first flange; and wherein said first portion of said sleeve is fitted through said second bores of said first flanges and through said third bores of said pads.

6. An aircraft comprising: a propulsion system, an engine pylon, and the device according to claim 1, said propulsion system being coupled to the engine pylon by said device, wherein said baseplate is fastened to said propulsion system, and said first nut is fastened to said engine pylon.
