

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400448
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Nooshabadi; Saeid et al.

Systems and methods for a step and scan detection network for hitchball location estimation

Abstract

Systems and methods for estimation of vehicle hitchball location are disclosed. A plurality of image frames may be received from a rear-facing camera of a vehicle. The rear-facing camera may be directed at a front of a trailer that is coupled to the vehicle at a hitchball. An approximate lateral location of the hitchball coupled to the vehicle may be determined by obtaining a plurality of cropped images along a hitch drawbar coupled to the vehicle by stepping along the vertical direction, and performing a stepwise lateral scan, centered at the hitch drawbar.

Inventors: Nooshabadi; Saeid (Gilroy, CA), Qian; Yongbo (San Jose, CA), Nagasamy; Vijay (Fremont, CA), Singh; Gurjeet (Castro Valley, CA), Patel; Manan Sanjay (Canton, MI), Mustafa; Ali (Dearborn, MI)

Applicant: Ford Global Technologies, LLC (Dearborn, MI)

Family ID: 1000008782350

Appl. No.: 17/649747

Filed: February 02, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230245453 A1	Aug. 03, 2023

Publication Classification

Int. Cl.: G06V20/40 (20220101); B60R1/00 (20220101); B60R1/26 (20220101); B60R11/04 (20060101); G06V10/25 (20220101); G06V10/82 (20220101); G06V20/56 (20220101)

U.S. Cl.:

CPC **G06V20/46** (20220101); **B60R1/003** (20130101); **B60R1/26** (20220101); **B60R11/04** (20130101); **G06V10/25** (20220101); **G06V10/82** (20220101); **G06V20/56** (20220101); **B60R2300/806** (20130101)

Field of Classification Search

CPC: B60R (1/003); B60R (1/26); B60R (11/04); B60R (2300/80); B60R (2300/06); B60R (1/23); B60R (2300/304); B60D (1/248); B60D (1/00); B60D (1/01); B60D (1/06); B62D (25/209); G06V (20/56); G06V (10/25); G06V (10/255); G06V (10/82); G06V (20/46); G06V (20/70); G06V (20/41); G06N (3/09)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9499018	12/2015	Gehrke	N/A	B60R 1/003
9696723	12/2016	Zeng et al.	N/A	N/A
9731568	12/2016	Wuergler et al.	N/A	N/A
10155478	12/2017	Hu	N/A	G06T 7/74
10987984	12/2020	Carpenter	N/A	N/A
11050933	12/2020	Chen	N/A	B60D 1/36
11676300	12/2022	Ramirez Llanos	382/103	G06V 20/56
2018/0081370	12/2017	Miller	N/A	B60W 10/04
2019/0086927	12/2018	Skvarce	N/A	N/A
2020/0079165	12/2019	Niewiadomski	N/A	G05D 1/0246
2020/0097021	12/2019	Carpenter et al.	N/A	N/A
2020/0130582	12/2019	Wong	N/A	B62D 13/06
2020/0282910	12/2019	Nagasamy	N/A	B60D 1/62
2020/0324593	12/2019	Niewiadomski	N/A	B62D 15/027
2021/0034903	12/2020	Daga	N/A	G06V 10/7747
2022/0024391	12/2021	Gali	N/A	G06T 7/73
2022/0084212	12/2021	Dahal	N/A	G06N 3/08

OTHER PUBLICATIONS

Rosebrock. "Turning any CNN image classifier into an object detector with Keras, TensorFlow, and OpenCV," pyimagesearch [retrieved Jun. 22, 2020]. Retrieved from Internet <URL: <https://pyimagesearch.com/2020/06/22/turning-any-cnn-image-classifier-into-an-object-detector-with-keras-tensorflow-and-opencv/>> (Year: 2020). cited by examiner

Atoum et al., "Monocular Video-Based Trailer Coupler Detection Using Multiplexer Convolutional Neural Network," 2017 IEEE International Conference on Computer Vision (ICCV), Venice, Italy, 2017, pp. 5478-5486, doi: 10.1109/ICCV.2017.584. (Year: 2017). cited by examiner

Ashok Dahal et al., DEEPTRAILERASSIST: Deep Learning Based Trailer Detection, Tracking and Articulation Angle Estimation on Automotive Rear-View Camera, IEEE/CFV International Conference on Computer Vision Workshop, 2019. cited by applicant

Yousef Atoum et al., Monocular Video-Based Trailer Coupler Detection Using Multiplexer Convolutional Neural Network, Michigan State University and General Motors. cited by applicant

Background/Summary

BACKGROUND

(1) Despite significant developmental efforts in automation, driver assisted features for maneuvering with a trailer call for accurate estimations of the location of a hitchball. The location of the hitchball is important for trailer angle detection (TAD) and other driver assist features for maneuvering a vehicle with a trailer, such as backup assistance.

(2) It is desirable to provide solutions that provide hitchball position information and associated hitch angle information after a vehicle is hitched to a trailer.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) A detailed description is set forth below with reference to the accompanying drawings. The use of the same reference numerals may indicate similar or identical items. Various embodiments may utilize elements and/or components other than those illustrated in the drawings, and some elements and/or components may not be present in various embodiments. Elements and/or components in the figures are not necessarily drawn to scale. Throughout this disclosure, depending on the context, singular and plural terminology may be used interchangeably.

(2) FIG. 1 illustrates an example system that includes a vehicle configured with a trailer hitch and camera in accordance with an embodiment of the disclosure.

(3) FIG. 2 illustrates some example functional blocks that may be included in a system for a vehicle in accordance with an embodiment of the disclosure.

(4) FIG. 3. illustrates an image from a rear facing camera of a tow vehicle with a lateral stepwise scan overlaying the image in accordance with an embodiment of the disclosure.

(5) FIG. 4 illustrates a flow diagram of a method in accordance with an embodiment of the disclosure.

DETAILED DESCRIPTION

(6) Overview

(7) In terms of a general overview, this disclosure is generally directed to systems and methods for estimation of vehicle hitchball location. In one example embodiment, a plurality of image frames may be received from a rear-facing camera of a vehicle. The rear-facing camera may be directed at a front of a trailer that is coupled to the vehicle at a hitchball. An approximate lateral location of the hitchball coupled to the vehicle may be determined by obtaining a plurality of cropped images along a hitch drawbar coupled to the vehicle by stepping along the vertical direction, and performing a stepwise lateral scan, centered at the hitch drawbar. At each vertical step, during the stepwise lateral scan, the plurality of cropped images may be fed into a neural network to process each cropped image to detect the hitchball therein. The lateral scan may be repeated for several vertical steps, until a predetermined percentage of the processed cropped images in the lateral scan detect the hitchball therein. The predetermined percentage of cropped images may be optimized by repeating the procedure multiple times to enable a vote by the neural network.

(8) Illustrative Embodiments

(9) The disclosure will be described more fully hereinafter with reference to the accompanying drawings, in which example embodiments of the disclosure are shown. This disclosure may,

however, be embodied in many different forms and should not be construed as limited to the example embodiments set forth herein. It will be apparent to persons skilled in the relevant art that various changes in form and detail can be made to various embodiments without departing from the spirit and scope of the present disclosure. Thus, the breadth and scope of the present disclosure should not be limited by any of the above-described example embodiments but should be defined only in accordance with the following claims and their equivalents. The description below has been presented for the purposes of illustration and is not intended to be exhaustive or to be limited to the precise form disclosed. It should be understood that alternative implementations may be used in any combination desired to form additional hybrid implementations of the present disclosure. For example, any of the functionality described with respect to a particular device or component may be performed by another device or component. Furthermore, while specific device characteristics have been described, embodiments of the disclosure may relate to numerous other device characteristics. Further, although embodiments have been described in language specific to structural features and/or methodological acts, it is to be understood that the disclosure is not necessarily limited to the specific features or acts described. Rather, the specific features and acts are disclosed as illustrative forms of implementing the embodiments.

(10) It should also be understood that the word “example” as used herein is intended to be non-exclusionary and non-limiting in nature. Furthermore, certain words and phrases that are used herein should be interpreted as referring to various objects and actions that are generally understood in various forms and equivalencies by persons of ordinary skill in the art. For example, the word “application” or the phrase “software application” as used herein with respect to a mobile device such as a smartphone, refers to code (software code, typically) that is installed in the mobile device. The code may be launched and operated via a human machine interface (HMI) such as a touchscreen. The word “action” may be used interchangeably with words such as “operation” and “maneuver” in the disclosure. The word “maneuvering” may be used interchangeably with the word “controlling” in some instances. The word “vehicle” as used in this disclosure can pertain to any one of various types of vehicles such as cars, vans, sports utility vehicles, trucks, electric vehicles, gasoline vehicles, hybrid vehicles, and autonomous vehicles. Phrases such as “automated vehicle,” “autonomous vehicle,” and “partially-autonomous vehicle” as used in this disclosure generally refer to a vehicle that can perform at least some operations without a driver being seated in the vehicle.

(11) FIG. 1 illustrates an example system **100** that includes a trailer **101** hitched to a vehicle **102** in accordance with an embodiment of the disclosure. Trailer **101** may be coupled to vehicle **102** via a hitchball. The vehicle **102** may be one of various types of vehicles with a chassis and may be a gasoline powered vehicle, an electric vehicle, a hybrid electric vehicle, or an autonomous vehicle, all of which may be configured as an automated or semi-automated vehicle. The system **100** may be implemented in a variety of ways and can include various types of devices. For example, the example system **100** can include some components that are a part of the vehicle **102**. The components that can be a part of the vehicle **102** can include a vehicle on-board computer **110**, and a sensor system **112** coupled to cameras, such as backup camera or rear-facing camera **150** coupled to the vehicle **102**. Thus, on-board computer **110** may be coupled to vehicle **102** chassis, the on-board computer including at least a memory and a processor, such as memory **122** and processor **104** coupled to the memory, wherein the processor **104** is configured to determine where a hitchball is coupled to a trailer connected vehicle **102**.

(12) The vehicle on-board computer **110** may perform various functions such as controlling engine operations (fuel injection, speed control, emissions control, braking, etc.), managing climate controls (air conditioning, heating etc.), activating airbags, and issuing warnings (check engine light, bulb failure, low tire pressure, vehicle in a blind spot, etc.), among other functions.

(13) The vehicle computer on-board **110**, in one or more embodiments, may be used to support features such as passive keyless operations, remotely-controlled vehicle maneuvering operations,

and remote vehicle monitoring operations. Vehicle on-board computer **110** may further control some maneuvers performed by the vehicle **102** during the self-parking operation (referred to in the industry as a Remote Park Assist (RePA) operation) as well as other operations such as a trailer-hitch assist operation (referred to in the industry as a Remote Trailer Hitch Assist (ReTHA) operation) and a trailer maneuvering assist operation (referred to in the industry as a Remote Trailer Maneuver Assist (ReTMA) operation). Some of the features available regarding hitch assist and maneuvering assist call for knowledge of the location of the hitchball **109** after the hitchball **109** is attached to a hitch and no longer visible. For example, if a driver manually attaches a trailer to the hitchball **109** and then uses trailer maneuvering assistance operations, the location of the hitchball is needed. In such cases, vehicle on-board computer **110** may execute certain operations associated with locating the hitchball **109** where a hitchball couples to a trailer, such as trailer **101**.

(14) The vehicle on-board computer **110** may perform various functions such as controlling engine operations (fuel injection, speed control, emissions control, braking, etc.), managing climate controls (air conditioning, heating etc.), activating airbags, and issuing warnings (check engine light, bulb failure, low tire pressure, vehicle in a blind spot, etc.). In one or more embodiments, vehicle on-board computer **110** may enable a self-driving car or provide driver assistance. Thus, vehicle on-board computer **110** may further include an Advanced Driver-Assistance System (“ADAS”) enhancement system **125**, which is shown to further include, as one embodiment, the various components of the vehicle **102** that may be controlled, activated, and/or operated by the vehicle by the ADAS enhancement system **125**. In one implementation, the ADAS enhancement system **125** can be an independent device (enclosed in an enclosure, for example). In another implementation, some or all components of the ADAS enhancement system **125** can be housed, merged, or can share functionality, with vehicle on-board computer **110**. For example, an integrated unit that combines the functionality of the ADAS enhancement system **125** can be operated by a single processor and a single memory device. In the illustrated example configuration, the ADAS enhancement system **125** includes the processor **104**, an input/output interface **127**, and memory **122**, ADAS Enhancement System Module **177**, database **175** and operating system **180**. The input/output interface **127** is configured to provide communications between the ADAS enhancement system **125** and other components such as the sensors **150**, the vehicle control components **126** and any infotainment system **160**, if present. The memory **122**, which is one example of a non-transitory computer-readable medium, may be used to store an operating system (OS) **180**, a database **175**, and various code modules such as an ADAS enhancement system module **177**. The modules, including ADAS enhancement system module **177**, may be provided in the form of computer-executable instructions that can be executed by processor **104** for performing various operations in accordance with the disclosure.

(15) In one or more embodiments, communications network **140** includes a cellular or Wi-Fi communication link enabling vehicle **102** to communicate with network **140**, which may include a cloud-based network or source for transferring data in accordance with this disclosure.

(16) Vehicle **102** rear-facing camera **150** may further include a set of nodes and/or sensors such as radars mounted upon vehicle **102** in a manner that allows the vehicle on-board computer **110** to communicate with devices and collect data for locating a hitchball and hitch drawbar **105**.

Examples of may include sensors, radars and/or emitters capable of detecting objects, distances such as ultrasonic radar, LiDAR, cameras, including back-up cameras and the like. In one or more embodiments, sensors/cameras may further include one or more of Bluetooth®-enabled sensors, or Bluetooth® low energy (BLE)-enabled sensors. In one embodiment, a single node and/or sensor and/or backup camera **150** may be mounted at the rear of the vehicle **102** as a back-up camera or radar. Other sensors may also be present in vehicle **102** including wheel speed sensors, accelerometers, rate sensors, GPS sensors, and steering wheel sensors.

(17) Vehicle on-board computer **110** includes hitchball location module **130** to perform hitchball location by collecting data from rear-facing camera **150** on vehicle **102** or other sensors directed at

the hitchball location **109**. Vehicle on-board computer **110** further may control vehicle **102** using some maneuvers performed by the vehicle **102** during the self-parking operation (referred to in the industry as a Remote Park Assist (RePA) operation) as well as other operations such as a trailer-hitch assist operation (referred to in the industry as a Remote Trailer Hitch Assist (ReTHA) operation) and a trailer maneuvering assist operation (referred to in the industry as a Remote Trailer Maneuver Assist (ReTMA) operation).

(18) Referring to FIG. 2, vehicle on-board computer **110** is shown configured to execute various operations associated with estimating the location of a hitchball via hitchball location module **130** in accordance with one or more embodiments.

(19) As shown, in one embodiment, on-board computer **110** includes components such as processor **202** and memory **204**, which is one example of a non-transitory computer-readable medium, may be used to store the operating system (OS) **240**, database **230**, and various modules, such as hitchball module **130**. One or more modules in the form of computer-executable instructions may be executed by the processor **210** for performing various operations in accordance with the disclosure. More particularly, hitchball location module **130** may be executed by the processor **202** in accordance with the disclosure for determining the location of hitchball **109** which identifies the location of a hitchball for connecting vehicle **102** to a trailer.

(20) Referring back to FIG. 1, trailer **101** and vehicle **102** are shown in a hitched position. According to an embodiment, hitchball location is determined while trailer **101** is connected, and either stationary or moving. More specifically, according to embodiments, a neural network receives a plurality of images or videos from at least a rear-facing camera on vehicle **102** and determines the hitchball location.

(21) As shown on FIG. 1, sensors coupled to vehicle **102** include rear-facing camera(s) **150**. In one or more embodiments, the data received by rear-facing camera **150** may be provided to hitchball location module **130** to determine a hitchball location after vehicle **102** and trailer **101** are coupled, stationary or moving.

(22) Referring now to FIG. 3, an image **300** from rear-facing camera **150** is shown with an overlay **310** of six lateral scans, over a predetermined location of drawbar **105** coupled to a hitch **320** covering a hitchball. As shown, each of the lateral scans from left to right are identified with a zero “0” where no recognizable hitchball indication is found at a predetermined number of crops. On the other hand, the top lateral scan **330** is identified with a one “1” as an indication of a hitchball is found, at a predetermined number of crops.

(23) As shown, at a vertical step, each lateral scan proceeds along a strip identified by the width of the scans. For each image **300** an analysis is performed along two dimensions in a stepwise manner to create a plurality of cropped images. At each vertical step, each lateral scan shows multiple steps with cropped images **340**. In one embodiment, overlay **310** is a 64 by 64 pixel template with the number of vertical and lateral steps and image crops being determined according to system requirements.

(24) In one or more embodiments, image **300** is exemplary of multiple images or videos received at hitchball location module **130**. For example, a lateral scan of the 64 by 64 pixel template, or any other size, can represent a region of interest in an area in which hitchball **109** is known to exist. Thus, location module **130** may perform neural network processing including performing a lateral scan with a stepwise probability calculation of the region of interest.

(25) In one or more embodiments, the location module **130** may perform artificial intelligence algorithms or the like as will be appreciated by one of ordinary skill in the art with the benefit of this disclosure. Thus, the stepwise probability calculation applies artificial intelligence of a known shape of the hitchball to recognize one or more cropped images that include the hitchball. The stepwise probability calculation includes data of a known shape of the hitchball to recognize one or more cropped images that include the hitchball. The known shape may include information stored, and the hitchball location information may include partial information stored from vehicle

manufacturing information. Due to the inconsistencies in manufacturing, however, stored manufacturing partial information may not be accurate, and there is a need for verification. The stored manufacturing partial information, however, only apply to the lateral location of the hitchball which is expected to be fixed. The longitudinal location of the hitchball depends on the particular hitch assembly employed and needs to be discovered in the field.

(26) In one or more embodiments, the stepwise probability calculation includes reviewing each cropped image in each lateral scan at a fixed step size, and scanning at each step to determine likelihood of the presence of the hitchball. This lateral scanning and stepwise probability calculation may be repeated at multiple vertical locations until a predetermined percentage of cropped images including the hitchball are detected. The number of repeats can be determined according to the type of vehicle involved and the type of camera being used. For example, if a high definition camera or video camera **150** is used, fewer repetitions may be needed.

(27) In one or more embodiments, performing the lateral scan may include scanning or collecting pairs of cropped images such that each pair includes a positive cropped image including the hitchball and a negative cropped image situated below or/and above the positive cropped image with no visible hitchball. Such image pairs may be used to train a neural network. For example, a neural network may be trained offline or over a network **140**. Such training could include deep-learning based object detection and/or computer-vision based detection. For example, the 64 by 64 pixel template, or any other size, **310** applied to each image frame **300** may be used for training a neural network using the image pairs and step and scan location techniques described herein.

(28) Referring now to FIG. 4, a flow diagram **400** illustrates a method in accordance with an embodiment. As shown block **410** provides for receiving a plurality of image frames from a camera directed at a front of a trailer coupled to a vehicle at a hitchball. For example, network **140** or computer **110** may receive image frames from camera **150** located on vehicle **102** coupled to trailer **101**. As shown in FIG. 3, image **300** may represent one of the image frames received from camera **150**.

(29) Block **420** provides for determining an approximate lateral location of the hitchball coupled to the vehicle. For example, determining an approximate lateral location may include receiving data identifying the location of drawbar **105** coupled to vehicle **102** and use the location of the drawbar **105** holding a hitchball **109** as the approximate lateral location.

(30) Block **430** provides for obtaining a plurality of cropped images, at stepwise vertical location, along a hitch drawbar coupled to the vehicle, along a lateral strip centered at the hitch drawbar by performing a stepwise lateral scan. For example, using camera **150**, images or video along the located hitch drawbar **105** may be analyzed to provide a plurality of cropped images to enable input to a neural network.

(31) Block **440** provides that during the stepwise lateral scan, feeding the plurality of cropped images into a neural network to detect each cropped image that includes the hitchball. For example, the 64 by 64 template or any other size, **310** may be used to perform the lateral scan and feed into a neural network using hitchball location module **130**.

(32) Block **450** provides for repeating the lateral scanning until a predetermined percentage of the cropped images that include the hitchball are detected. For example, if a higher percentage of cropped images contains the hitchball, further repetition at a different vertical location, may not be necessary. In one or more embodiments, the repeating can be until a confidence level or artificial intelligence determines that the hitchball is located sufficiently to enable other vehicle maneuvers or enable further driver assistance modules within a towing vehicle.

(33) Block **460** provides for optimizing the predetermined percentage of cropped images to enable a voting by the neural network. For example, in one or more embodiments, a neural network involves voting to determine whether a hitchball is properly located. That is, the neural network may combine the outputs of a set of neural network classifiers to reach a combined decision. The methods may range from the requirement of a complete agreement to schemes based on the

distribution of votes collected. Any number of voting schemes may be used by the neural network.

(34) In the above disclosure, reference has been made to the accompanying drawings, which form a part hereof, which illustrate specific implementations in which the present disclosure may be practiced. It is understood that other implementations may be utilized, and structural changes may be made without departing from the scope of the present disclosure. References in the specification to “one embodiment,” “an embodiment,” “an example embodiment,” “an example embodiment,” “example implementation,” etc., indicate that the embodiment or implementation described may include a particular feature, structure, or characteristic, but every embodiment or implementation may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment or implementation. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment or implementation, one skilled in the art will recognize such feature, structure, or characteristic in connection with other embodiments or implementations whether or not explicitly described. For example, various features, aspects, and actions described above with respect to an autonomous parking maneuver are applicable to various other autonomous maneuvers and must be interpreted accordingly.

(35) Implementations of the systems, apparatuses, devices, and methods disclosed herein may comprise or utilize one or more devices that include hardware, such as, for example, one or more processors and system memory, as discussed herein. An implementation of the devices, systems, and methods disclosed herein may communicate over a computer network. A “network” is defined as one or more data links that enable the transport of electronic data between computer systems and/or modules and/or other electronic devices. When information is transferred or provided over a network or another communications connection (either hardwired, wireless, or any combination of hardwired or wireless) to a computer, the computer properly views the connection as a transmission medium. Transmission media can include a network and/or data links, which can be used to carry desired program code means in the form of computer-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer. Combinations of the above should also be included within the scope of non-transitory computer-readable media.

(36) Computer-executable instructions comprise, for example, instructions and data which, when executed at a processor, cause the processor to perform a certain function or group of functions. The computer-executable instructions may be, for example, binaries, intermediate format instructions such as assembly language, or even source code. Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the described features or acts described above. Rather, the described features and acts are disclosed as example forms of implementing the claims.

(37) A memory device can include any one memory element or a combination of volatile memory elements (e.g., random access memory (RAM, such as DRAM, SRAM, SDRAM, etc.)) and non-volatile memory elements (e.g., ROM, hard drive, tape, CDROM, etc.). Moreover, the memory device may incorporate electronic, magnetic, optical, and/or other types of storage media. In the context of this document, a “non-transitory computer-readable medium” can be, for example but not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, or device. More specific examples (a non-exhaustive list) of the computer-readable medium would include the following: a portable computer diskette (magnetic), a random-access memory (RAM) (electronic), a read-only memory (ROM) (electronic), an erasable programmable read-only memory (EPROM, EEPROM, or Flash memory) (electronic), and a portable compact disc read-only memory (CD ROM) (optical). Note that the computer-readable medium could even be paper or another suitable medium upon which the program is printed, since the program can be electronically captured, for instance, via optical scanning of the paper or other medium, then compiled, interpreted or otherwise processed in a suitable manner if necessary, and then stored in a

computer memory.

(38) Those skilled in the art will appreciate that the present disclosure may be practiced in network computing environments with many types of computer system configurations, including in-dash vehicle computers, personal computers, desktop computers, laptop computers, message processors, mobile devices, multi-processor systems, microprocessor-based or programmable consumer electronics, network PCs, minicomputers, mainframe computers, mobile telephones, PDAs, tablets, pagers, routers, switches, various storage devices, and the like. The disclosure may also be practiced in distributed system environments where local and remote computer systems, which are linked (either by hardwired data links, wireless data links, or by any combination of hardwired and wireless data links) through a network, both perform tasks. In a distributed system environment, program modules may be located in both the local and remote memory storage devices.

(39) Further, where appropriate, the functions described herein can be performed in one or more of hardware, software, firmware, digital components, or analog components. For example, one or more application specific integrated circuits (ASICs) can be programmed to carry out one or more of the systems and procedures described herein. Certain terms are used throughout the description, and claims refer to particular system components. As one skilled in the art will appreciate, components may be referred to by different names. This document does not intend to distinguish between components that differ in name, but not function.

(40) At least some embodiments of the present disclosure have been directed to computer program products comprising such logic (e.g., in the form of software) stored on any computer-usable medium. Such software, when executed in one or more data processing devices, causes a device to operate as described herein.

(41) While various embodiments of the present disclosure have been described above, it should be understood that they have been presented by way of example only, and not limitation. It will be apparent to persons skilled in the relevant art that various changes in form and detail can be made therein without departing from the spirit and scope of the present disclosure. Thus, the breadth and scope of the present disclosure should not be limited by any of the above-described example embodiments but should be defined only in accordance with the following claims and their equivalents. The foregoing description has been presented for the purposes of illustration and description. It is not intended to be exhaustive or to limit the present disclosure to the precise form disclosed. Many modifications and variations are possible in light of the above teaching. Further, it should be noted that any or all of the aforementioned alternate implementations may be used in any combination desired to form additional hybrid implementations of the present disclosure. For example, any of the functionality described with respect to a particular device or component may be performed by another device or component. Further, while specific device characteristics have been described, embodiments of the disclosure may relate to numerous other device characteristics. Further, although embodiments have been described in language specific to structural features and/or methodological acts, it is to be understood that the disclosure is not necessarily limited to the specific features or acts described. Rather, the specific features and acts are disclosed as illustrative forms of implementing the embodiments. Conditional language, such as, among others, “can,” “could,” “might,” or “may,” unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments could include, while other embodiments may not include, certain features, elements, and/or steps. Thus, such conditional language is not generally intended to imply that features, elements, and/or steps are in any way required for one or more embodiments.

Claims

1. A method, comprising: receiving a plurality of image frames from a camera directed at a front of a trailer coupled to a vehicle at a hitchball, wherein the hitchball is attached to the trailer covered

by a hitch of the trailer; receiving data indicating a location of a hitch drawbar coupled to the vehicle and data indicating a lateral location of the hitchball from vehicle manufacturing information, wherein the vehicle manufacturing information is used only for the lateral location of the hitchball; determining a lateral location of the hitchball coupled to the vehicle based on the data indicating the location of the hitch drawbar; performing a stepwise lateral scan of only a region of interest based on a template centered at the lateral location of the hitchball from the vehicle manufacturing information, the stepwise lateral scan comprising obtaining a plurality of cropped images in a longitudinal direction along the hitch drawbar at a vertical step; during the stepwise lateral scan, feeding the plurality of cropped images into a neural network to detect each cropped image in the plurality of cropped images that includes the hitchball; repeating the stepwise lateral scan until a predetermined percentage of the cropped images in the plurality of cropped images that include the hitchball are detected; optimizing the predetermined percentage of the cropped images in the plurality of cropped images that include the hitchball to enable a voting by the neural network; and automatically performing, by the vehicle, a self-parking operation using the voting by the neural network indicating a location of the hitchball.

2. The method of claim 1, wherein the neural network includes a deep-learning based object detection and computer-vision based detection within the template on each of the plurality of image frames received from the camera directed at the front of the trailer.

3. The method of claim 1, wherein the stepwise lateral scan includes a stepwise probability calculation of the region of interest.

4. The method of claim 3, wherein the stepwise probability calculation includes recognizing one or more of the cropped images in the plurality of cropped images that include the hitchball by applying artificial intelligence of a known shape of the hitchball.

5. The method of claim 3, wherein the stepwise probability calculation includes recognizing one or more of the cropped images in the plurality of cropped images that include the hitchball by including data of a known shape of the hitchball.

6. The method of claim 3, wherein the stepwise probability calculation is a fixed step of any size over the stepwise lateral scan.

7. The method of claim 1, wherein the repeating the stepwise lateral scan until the predetermined percentage of the cropped images in the plurality of cropped images that include the hitchball are detected includes lateral scanning of the plurality of image frames received from the camera directed at the front of the trailer.

8. The method of claim 1, wherein, in multiple vertical steps, the performing the stepwise lateral scan of each of the plurality of cropped images along the hitch drawbar further includes: collecting pairs of cropped images, each pair including a positive cropped image including the hitchball which is also shifted laterally stepwise to increase a number of positive cropped images including the hitchball, and at least one negative cropped image beneath and/or above the positive cropped image with no visible hitchball within a region of interest of any size.

9. The method of claim 8, wherein the pairs of cropped images are used to train the neural network offline.

10. A system for a vehicle, comprising: a memory that stores computer-executable instructions; a processor configured to access the memory and execute the computer-executable instructions to: receive a plurality of image frames from a camera directed at a front of a trailer coupled to a vehicle at a hitchball, wherein the hitchball is attached to the trailer and is no longer visible; receive data indicating a location of a hitch drawbar coupled to the vehicle and data indicating a lateral location of the hitchball from vehicle manufacturing information, wherein the vehicle manufacturing information is used only for the lateral location of the hitchball; determine a lateral location of the hitchball coupled to the vehicle based on the data indicating the location of the hitch drawbar; perform a stepwise lateral scan of only a region of interest based on a template centered at the lateral location of the hitchball from the vehicle manufacturing information, the stepwise lateral

scan comprising obtaining a plurality of cropped images in a longitudinal direction along the hitch drawbar at a vertical step; during the stepwise lateral scan, feed the plurality of cropped images into a neural network to detect each cropped image in the plurality of cropped images that includes the hitchball; repeat the stepwise lateral scan until a predetermined percentage of the cropped images in the plurality of cropped images that include the hitchball are detected; optimize the predetermined percentage of the cropped images in the plurality of cropped images that include the hitchball to enable a voting by the neural network; and automatically performing, by the vehicle, a self-parking operation using the voting by the neural network indicating a location of the hitchball.

11. The system of claim 10, wherein the stepwise lateral scan includes a stepwise probability calculation of the region of interest.

12. The system of claim 11, wherein the stepwise probability calculation includes recognizing the cropped images in the plurality of cropped images that include the hitchball by applying artificial intelligence of a known shape of the hitchball.

13. A vehicle, comprising: a chassis; a rear-facing camera directed at a front of a trailer coupled to the vehicle at a hitchball; a memory and a processor coupled to the memory, the processor configured to access the memory and execute the computer-executable instructions to: receive a plurality of image frames from a camera directed at a front of a trailer coupled to a vehicle at a hitchball, wherein the hitchball is attached to the trailer and is no longer visible; receive data indicating a location of a hitch drawbar coupled to the vehicle and data indicating a lateral location of the hitchball from vehicle manufacturing information, wherein the vehicle manufacturing information is used only for the lateral location of the hitchball; determine a lateral location of the hitchball coupled to the vehicle based on the data indicating the location of the hitch drawbar; perform a stepwise lateral scan of only a region of interest based on a template centered at the lateral location of the hitchball from the vehicle manufacturing information, the stepwise lateral scan comprising obtaining a plurality of cropped images in a longitudinal direction along the hitch drawbar; during the stepwise lateral scan, feed the plurality of cropped images into a neural network to detect each cropped image in the plurality of cropped images that includes the hitchball; repeat the stepwise lateral scan until a predetermined percentage of the cropped images in the plurality of cropped images that include the hitchball are detected; optimize the predetermined percentage of the cropped images in the plurality of cropped images that include the hitchball to enable a voting by the neural network; and automatically performing, by the vehicle, a self-parking operation using the voting by the neural network indicating a location of the hitchball.

14. The vehicle of claim 13, wherein the stepwise probability calculation includes recognizing the cropped images in the plurality of cropped images that include the hitchball by applying artificial intelligence of a known shape of the hitchball.

15. The vehicle of claim 13, wherein the processor is configured to execute instructions to perform the stepwise lateral scan of each of the plurality of cropped images along vertical steps including collecting pairs of cropped images, each pair including a positive cropped image that can be increased to any desired number by shifting a crop laterally stepwise including the hitchball and negative cropped images beneath and/or above the positive cropped image with no visible hitchball within a region of interest of any size, wherein the pairs of cropped images are used for training the neural network offline.
