



US 20250281702A1

(19) **United States**

(12) **Patent Application Publication**
Demurjian et al.

(10) **Pub. No.: US 2025/0281702 A1**

(43) **Pub. Date: Sep. 11, 2025**

(54) **HANDHELD ORAL MEDICATION
DISPENSING DEVICE WITH ACTIVATOR
MECHANISM**

(21) Appl. No.: **18/600,402**

(22) Filed: **Mar. 8, 2024**

Publication Classification

(51) **Int. Cl.**
A61M 11/00 (2006.01)

(52) **U.S. Cl.**
CPC **A61M 11/007** (2014.02); **A61M 2205/103**
(2013.01); **A61M 2205/123** (2013.01); **A61M**
2205/6009 (2013.01); **A61M 2205/8206**
(2013.01); **A61M 2210/0625** (2013.01)


(71) Applicant: **Aspargo Laboratories, Inc.**, New
York, NY (US)

(72) Inventors: **Adam Demurjian**, Red Bank, NJ (US);
Ravi Sawhney, Malibu, CA (US);
Lance Hussey, Simi Valley, CA (US);
Michael Kulick, Simi Valley, CA (US);
Brian Weingarth, Woodland Hills, CA
(US); **Josh Probst**, Culver City, CA
(US); **Rajvir Logani**, Calabasas, CA
(US); **Cary Chow**, Santa Monica, CA
(US); **Christianna Bethel**, Glendale,
CA (US); **Craig Steel**, El Segundo, CA
(US); **Michael Schuffert**, Chatsworth,
CA (US); **John Vernon**, Malibu, CA
(US)

(73) Assignee: **Aspargo Laboratories, Inc.**, New
York, NY (US)

(57) **ABSTRACT**

The present disclosure provides a handheld medication dispensing device. The device includes a housing containing a cartridge carrier, designed with a specific connector to align with a medication cartridge. The device also includes an authentication mechanism that works in conjunction with an activator mechanism. When operated, the activator mechanism causes the cartridge carrier to move the medication cartridge between a stored position and a dispensing position, where it can be compressed to safely and efficiently dispense medication to a user.






FIG. 1




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C





FIG. 6

102






FIG. 7G
(Prior Art)

102




FIG. 7H




FIG. 8A




FIG. 8B





FIG. 9






FIG. 11A




FIG. 11C






FIG. 11B



HANDHELD ORAL MEDICATION DISPENSING DEVICE WITH ACTIVATOR MECHANISM

BACKGROUND OF THE INVENTION

(1) Field of Invention

[0001] The present invention relates to a medication dispensing device and, more particularly, to a keyed and handheld oral medication dispensing device with a unique activator mechanism.

(2) Description of Related Art

[0002] The field of medication treatment has grown increasingly complex in recent years, with patients frequently needing to manage and administer multiple types of medication. Under such circumstances, it is vital to provide reliable, accessible, and simple methodologies to patients for dispensing their medications. Many existing dispensing devices, however, tend to be cumbersome, confusing, or inefficient. Often, they rely on patients having to manually change their medication reminders or products, which can involve complicated steps or create potential for mistakes, like grabbing the wrong medication or dispensing an incorrect dosage. Furthermore, mistakes may potentially have serious health implications. Hence, it's vital to design an easy-to-use and fail-safe medication dispensing device.

[0003] Further, existing oral medications are typically taken as tablets or syrups. Such medication delivery items may be functional, but often take time for efficacy due to digestive and other body related functions. Additionally, such medication delivery techniques are inconvenient to carry on ones person or inconspicuously use. Thus, a need exist for a unique oral medication dispensing device that provides an alternative to tablet and syrup-type medications.

[0004] One embodiment disclosed herein pertains to a handheld oral medication dispensing device with an automatic cartridge activator mechanism. The purpose of this design is not only to make medication administration simpler and more efficient but also to mitigate potential errors associated with manual cartridge switching. The device provides user authentication and employs a simple yet effective actuation mechanism to operate, further enhancing safety measures. The innovative design of the keyed connector and the configuration of the cartridges can significantly aid patients manage and administer their medication effectively and safely.

SUMMARY OF INVENTION

[0005] The present disclosure provides a handheld oral medication dispensing device with an automatic cartridge activator mechanism. The purpose of this design is not only to make medication administration simpler and more efficient but also to mitigate potential errors associated with manual cartridge switching. The device provides user authentication and employs a simple yet effective actuation mechanism to operate, further enhancing safety measures. The innovative design of the keyed connector and the configuration of the cartridges can significantly aid patients manage and administer their medication effectively and safely.

[0006] In one aspect, the medication dispensing device has a housing with a cartridge carrier therein, the cartridge

carrier having a keyed connector that is keyed to a medication cartridge to allow for insertion and alignment of the medication cartridge within the cartridge carrier. Further, in another aspect, an activator mechanism is positioned within the housing, the activator mechanism operably connected with the cartridge carrier to cause the cartridge carrier to actuate, whereby upon actuation of the cartridge carrier, the cartridge carrier selectively moves an inserted medication cartridge between a stored position and a dispensing position.

[0007] In yet another aspect, the cartridge carrier is rotatable within the housing.

[0008] In another aspect, the cartridge carrier includes a proximal end and a distal end, the proximal end being open for receiving the medication cartridge therein, while the distal end includes a gear wheel operably connected to the activator mechanism.

[0009] In yet another aspect, the activator mechanism includes at least a battery, a motor, and one or more gears that are operably connected to the gear wheel, such that activation of the activator mechanism causes the motor to turn the one or more gears and, in doing so, turn the gear wheel and rotate the cartridge carrier.

[0010] In yet another aspect, the keyed connector includes one or more alignment features that protrude into the cartridge carrier.

[0011] In yet another aspect, activation of the activator mechanism causes a rotation of the cartridge carrier, thereby causing the pair of opposing protrusions to travel through the pair of opposing slots and the pair of opposing channels from the first junction to the second junction and, in doing so, lift the medication cartridge from the cartridge carrier from the stored position to the dispensing position.

[0012] In yet another aspect, the dispensing device further comprises an authentication mechanism operably connected with the activator mechanism, the authentication mechanism operable for authenticating a user and, when authenticated, activating the activator mechanism to cause the cartridge carrier to actuate and move the inserted medication cartridge from the stored position to the dispensing position.

[0013] Finally, as can be appreciated by one in the art, the present invention also comprises a method for forming and using the invention as described herein.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The objects, features and advantages of the present invention will be apparent from the following detailed descriptions of the various aspects of the invention in conjunction with reference to the following drawings, where:

[0015] FIG. 1 shows an exemplary illustration a handheld medication dispensing device and medication cartridge according to various embodiments of the present invention;

[0016] FIG. 2A shows an interior-view of the medication dispensing device, depicting a cartridge carrier;

[0017] FIG. 2B shows an interior-view of the medication dispensing device, depicting the medication cartridge inserted into the cartridge carrier;

[0018] FIG. 3 is an interior-view illustration of the medication dispensing device, depicting an activator mechanism as operably connected with the cartridge carrier;

[0019] FIG. 4 shows an exemplary illustration of the cartridge carrier and medication cartridge;

[0020] FIG. 5A shows a side-view illustration of the medication cartridge;

[0021] FIG. 5B shows a top-view illustration of the medication cartridge;

[0022] FIG. 5C is a cross-sectional, side-view illustration of the medication cartridge, taken from line A-A of FIG. 5B;

[0023] FIG. 6 shows an exploded-view illustration of the medication cartridge;

[0024] FIG. 7A shows a front-view illustration of the medication cartridge;

[0025] FIG. 7B shows a right, side-view illustration of the medication cartridge;

[0026] FIG. 7C shows a left, side-view illustration of the medication cartridge;

[0027] FIG. 7D shows a rear-view illustration of the medication cartridge;

[0028] FIG. 7E shows a top-view illustration of the medication cartridge;

[0029] FIG. 7F is a cross-sectional, side-view illustration of the medication cartridge, taken from line A-A of FIG. 7C;

[0030] FIG. 7G is an illustration of a lotion pump assembly of the prior art;

[0031] FIG. 7H is an illustration of an example pump assembly as applied to the medication cartridge in accordance with various embodiments of the present invention;

[0032] FIG. 8A shows an exemplary illustration of the cartridge carrier and medication cartridge;

[0033] FIG. 8B shows an exemplary illustration of the cartridge carrier and medication cartridge, depicting the medication cartridge as being inserted into the cartridge carrier;

[0034] FIG. 9 shows an exemplary illustration of the medication cartridge inserted into the cartridge carrier;

[0035] FIG. 10A shows an exemplary illustration of the medication cartridge inserted into the cartridge carrier, depicting the medication cartridge in a stored position;

[0036] FIG. 10B shows an exemplary illustration of the medication cartridge inserted into the cartridge carrier, depicting the cartridge carrier rotating to move the medication cartridge up and toward the dispensing position;

[0037] FIG. 10C shows an exemplary illustration of the medication cartridge inserted into the cartridge carrier, depicting the cartridge carrier as rotated to move the medication cartridge up and into the dispensing position;

[0038] FIG. 11A shows an exemplary illustration of the medication cartridge, depicting the vial sliding within the shell;

[0039] FIG. 11B shows close-up view of Detail A, taken from FIG. 11A;

[0040] FIG. 11C shows an exemplary illustration of the medication cartridge, depicting the vial within the shell;

[0041] FIG. 12A shows an exemplary illustration of the medication cartridge within the cartridge carrier, depicting the medication cartridge in the dispensing position and being pressed downward to activate the pump assembly and dispense medication from the medication cartridge; and

[0042] FIG. 12B shows an exemplary illustration of the medication cartridge within the cartridge carrier, depicting the medication cartridge in the dispensing position and being pressed downward to activate the pump assembly and dispense medication from the medication cartridge.

DETAILED DESCRIPTION

[0043] The present invention relates to a medication dispensing device and, more particularly, to a keyed and handheld medication dispensing device with a unique activator mechanism. The following description is presented to enable one of ordinary skill in the art to make and use the invention and to incorporate it in the context of particular applications. Various modifications, as well as a variety of uses in different applications will be readily apparent to those skilled in the art, and the general principles defined herein may be applied to a wide range of embodiments. Thus, the present invention is not intended to be limited to the embodiments presented, but is to be accorded the widest scope consistent with the principles and novel features disclosed herein.

[0044] In the following detailed description, numerous specific details are set forth in order to provide a more thorough understanding of the present invention. However, it will be apparent to one skilled in the art that the present invention may be practiced without necessarily being limited to these specific details. In other instances, well-known structures and devices are shown in block diagram form, rather than in detail, in order to avoid obscuring the present invention.

[0045] The reader's attention is directed to all papers and documents which are filed concurrently with this specification and which are open to public inspection with this specification, and the contents of all such papers and documents are incorporated herein by reference. All the features disclosed in this specification, (including any accompanying claims, abstract, and drawings) may be replaced by alternative features serving the same, equivalent or similar purpose, unless expressly stated otherwise. Thus, unless expressly stated otherwise, each feature disclosed is only one example of a generic series of equivalent or similar features.

[0046] Furthermore, any element in a claim that does not explicitly state "means for" performing a specified function, or "step for" performing a specific function, is not to be interpreted as a "means" or "step" clause as specified in 35 U.S.C. Section 112, Paragraph 6. In particular, the use of "step of" or "act of" in the claims herein is not intended to invoke the provisions of 35 U.S.C. 112, Paragraph 6.

[0047] Please note, if used, the labels left, right, front, back, top, bottom, forward, reverse, clockwise and counter clockwise have been used for convenience purposes only and are not intended to imply any particular fixed direction. Instead, they are used to reflect relative locations and/or directions between various portions of an object.

(1) Description

[0048] As noted above, the present invention relates to a medication dispensing device and, more particularly, to a keyed and handheld medication dispensing device with a unique activator mechanism. As shown in FIG. 1, the handheld medication dispensing device 100 is designed primarily to securely store and dispense medication from a medication cartridge 102. The device 100 comprises a housing 104, principally structured to protect the critical internal components while offering ergonomic suitability for handheld operation. The housing 104 exterior is designed with both convenience and comfort in mind, allowing a user to hold the device 100 and access the medication with ease. In an exemplary embodiment, the housing 104 may be

configured in a variety of shapes, sizes, and materials to accommodate different user preferences and medication types.

[0049] In one embodiment, the device **100** includes an authentication mechanism **106** that is designed to authenticate a user's identification in various manners. The authentication mechanism **106** is any suitable mechanism, device, system, etc., that allows for user authentication, non-limiting examples of which include biometrics (such as fingerprint reader or facial recognition via a camera and app, etc.), a password or passcode system, a security token, or any other known authentication method or device. The authentication mechanism **106** is set up to permit the authenticated or designated user access to the operation of the said device **100**, thereby ensuring a highly secure and personal way of dispensing medication. In one embodiment and as illustrated, the authentication mechanism **106** includes a fingerprint reader and all associated components as necessary to allow for authentication with such a reader, including an integrated circuit, power (battery), etc. For example, in a first use, the authentication mechanism **106** can be configured to recognize the user and thereafter only allow access to the recognized user. Such a setup can be configured in any suitable manner as understood by those skilled in the art. As non-limiting example, a first use may require that a user place a finger on the authentication mechanism **106** which turns on the device **100** and provides indicia (e.g., via a light, digital screen, etc.) to notify the user to place their finger on the fingerprint reader. The fingerprint reader then reads and stores the fingerprint of the designated user. Thereafter, the activator mechanism can only be activated by the designated user upon placement of the finger on the fingerprint reader. In another example, software or a phone application can be used to wirelessly communicate (e.g., via Wi-Fi, Bluetooth, etc.) with the device **100** to program the device to only recognize the designated user via the authentication mechanism. In this aspect, the device **100** includes all necessary components to allow it to wirelessly communicate with an external device, non-limiting examples of which include Wi-Fi transceivers/components, Bluetooth components/gear, etc. In an alternative embodiment, the device **100** can simply be turned off and on (without an authentication mechanism), and includes a button or other similar feature to cause the device **100** to operate and actuate the activation mechanism as described in further detail below.

[0050] In one aspect, the authentication mechanism **106** is a biometric fingerprint reader linked to a mobile app, which can be used to prevent unauthorized medication dispensing, requiring user authorization via the app for initialization, and connecting to caregivers and personal networks to ensure medication adherence. The design of the device **100**, accessories, and app is centered around the need for an easier and better way to receive the right dose, at the right time, in the right way and frequency. In one aspect, controlled via the app, the handheld device **100** can alert users to their medication schedule, while also notifying caregivers and family members about adherence. For restricted medications, the device **100** and associated app can restrict dosing until authorized by the prescribing physician. Tampering with the medication cartridge **102** triggers alerts to caregivers, pharmacists, and physicians, ensuring safe usage, especially for restricted medications by alerting through the app that the medication has not been taken as prescribed. In another aspect, the device **100** and medication

cartridge **102** are formed to include any necessary components that allow the device **100** to recognize a specific medication cartridge **102**. As a non-limiting example, each medication cartridge **102** can be formed to include a Radio Frequency Identification (RFID) tag, while the device **100** includes an RFID reader (or other similar technology).

[0051] As shown in the interior views of FIGS. 2A and 2B, integrated within the housing **104** is a cartridge carrier **200**. The cartridge carrier **200** functions as a receptacle for the medication cartridge **102**. The cartridge carrier **200** includes a keyed connector, most importantly, innovatively designed to align with a specified type of medication cartridge **102**. This keyed connector serves as an interlocking structure that carefully guides the positioning and orientation of the cartridge **102**, allowing only for the insertion of a compatible medication cartridge **102**. The keyed connector along with the cartridge carrier **200** ensure the correct placement and alignment of the medication cartridge **102**, which can help eliminate potential misuse or cartridge damage, and fostering a smooth transition between stored and dispensing positions (as described in further detail below).

[0052] As shown in the interior view of FIG. 3, an activator mechanism **300** forms part of the configuration and is integrated within the housing **104**. The activator mechanism **300**, when engaged, prompts the cartridge carrier **200** to actuate. The involvement of the activator mechanism **300** ensures a controlled movement of the inserted medication cartridge **102** between two positions—a stored position and a dispensing position. Note that FIG. 2A depicts the medication cartridge in a stored position, while FIG. 3 depicts the medication cartridge in a dispensing position.

[0053] In the stored position, as shown in FIG. 2A, the medication is kept secure within the device **100**. The position ensures safety by preventing unintentional discharge of medication when not in use. When the activator mechanism **300** is activated, the cartridge carrier **200** rotates to lift up the medication cartridge **102** into the dispensing position. When this dispensing position is selected, the medication cartridge **102** is correctly oriented to dispense the medication through a dispensing aperture (described in further detail below) integrated into the medication cartridge **102**.

[0054] The link between the activator mechanism **300** and the cartridge carrier **200** allows for reliable and essential movement control. This means the user can confidently operate the device **100** knowing the medication is dispensed accurately and safely.

[0055] The cartridge carrier **200** is formed in any suitable manner to allow for activation by the activator mechanism **300**, which results in transitioning the medication cartridge **102** between the stored and dispensing positions. In an embodiment and as shown in FIG. 3, the cartridge carrier **200** is rotatable within the housing **104**. The cartridge carrier **200** may be formed of materials that possess strength and durability such as, but not limited to, metals, polymers, and/or composites. The size, shape, and dimensions of the cartridge carrier may vary as per the application requirements.

[0056] The housing **104** may be constructed to accommodate the rotatable cartridge carrier **200**. The construction of the housing **104** can also encompass different types of materials that provide the necessary strength and durability inclusive of, but not limited to metals, polymers, composites, among others. The interior of the housing **104** is ideally

designed to allow the cartridge carrier **200** to rotate through actuation of the activator mechanism **300**.

[0057] The activator mechanism **300**, ensuring the cartridge carrier's **200** rotation within the housing **104**, can be implemented through a variety of means, such as mechanical gears, electric motors, a battery, manually operated mechanisms, integrated circuits, or any combination thereof. This activator mechanism **300** administration permits the user to precisely position the cartridge carrier **200** within the housing **104** between a first position (in which the medication cartridge **102** is inserted into the cartridge carrier **200** and is stored in a stored position) and a second position (in which the medication cartridge **102** is lifted from the housing **104** to a dispensing position). The activator mechanism **300** can then be activated to rotate the cartridge carrier **200** in an opposite direction to return the medication cartridge **102** to the stored position.

[0058] In one aspect, the dispensing device **100** includes a locking mechanism that is configured to selectively lock/unlock the medication cartridge **102** within the cartridge carrier **200**. The locking mechanism may involve an interlocking system, a magnetic attachment, or any other secure attachment mechanism. As a non-limiting example, the locking mechanism may be a spring-loaded detent style 'click-in' and 'click-out' mechanism formed at the bottom of the medication cartridge **102** and cartridge carrier **200**. In another aspect, the locking mechanism can be an electronically actuated lock (e.g., mechanized tab, etc.) that locks the medication cartridge **102** into the cartridge carrier **200**. For example, the exterior surface of the medication cartridge can include a slot that is formed to accommodate a tab that is electronically moved (e.g., turned/slid, etc.) into the slot when locking and, in the alternative, pulled from the slot when released. As yet another non-limiting example, the locking mechanism can include programming such that after the cartridge **102** is inserted into the cartridge carrier **202**, the cartridge carrier **200** is rotate partially until alignment features (described in further detail below and depicted as element **406**) are positioned in the middle of the second slot (described in further detail below and depicted as element **710**), with the cartridge carrier **200** then stopped until it is desired to rotate further to position the medication cartridge **102** in the dispensing position. With the alignment features in the middle of the second slot, the cartridge **102** is effectively locked within the cartridge carrier **200**. Thus, as can be appreciated by those skilled in the art, there are several mechanisms that can be employed to selectively lock the medication cartridge **102** into the cartridge carrier **200**.

[0059] In another aspect, the inclusion of the locking mechanism may also be included to secure the cartridge carrier **200** at any desired rotational position, thus preventing unintentional and unwanted movement when the cartridge carrier **200** is set in a particular position. This locking mechanism can be integrated into the cartridge carrier **200**, the housing **104**, the activator mechanism **300**, or combinations of these components. This rotatable cartridge carrier **200** system installed within a housing **104** assembly may have wide ranging applications, such as, for instance, accommodating various cartridges for providing users with quick and easy access to different medications and dosages, multiple configurations, interchangeability of components, and more. Thus, the present one embodiment discloses a rotatable cartridge carrier **200** system, promoting ease of use, enhancing performance, providing efficient operation,

flexibility, improved control and precision, leading to a more efficient and user-friendly functionality.

[0060] In one embodiment and as shown in FIG. 4, the cartridge carrier **200** includes both a proximal end **400** and a distal end **402**. The proximal end **400** of this unit is open, and it is specifically structured to receive the medication cartridge **102**. This can be any kind of medication cartridge **102**, and the open design simplifies the process of interchanging cartridges of differing medications, volumes, or other specifications, thus making it broadly applicable and versatile.

[0061] The distal end **402** of the cartridge carrier **200** includes a key component of this one embodiment—a gear wheel **404**. This gear wheel **404** is not a mere inclusion but is operably connected to the activator mechanism **300**. The gear wheel **404** and activator mechanism **300** are conceptually designed to work in harmony. In operation, when the user deploys the activator mechanism **300**, the included gear wheel **404** is rotated, thereby rotating the cartridge carrier **200**.

[0062] The gear wheel **404** is a significant element in the functioning of this device **100** mainly due to its interaction with the activator mechanism **300**. The gear wheel **404**, upon the interaction with activator mechanism **300**, contributes to the precision with which the cartridge carrier **200** is rotated to position the medication cartridge **102** between the stored and dispensing positions. Its size, teeth count, and interaction with other gears if connected, contribute to its function.

[0063] Moreover, the position of the gear wheel **404** at the distal end **402** of the cartridge carrier **200** may also assist in a user-friendly, ergonomic design. The gear wheel's **404** location ensures a seamless connection between the mechanical parts of the activator mechanism **300** and the carrier cartridge **200**, augmenting the device's **100** overall performance.

[0064] As noted above and referring again to FIG. 3, the device **100** includes an activator mechanism **300** to selectively turn the gear wheel **404** and, by extension, rotate the cartridge carrier **200**. The activator mechanism **300** includes any components as necessary to rotate the gear wheel **404**. In one embodiment, the activator mechanism **300** comprises of at least a battery **304**, a motor **302**, and one or more gears **306** that are operably connected to the gear wheel **404**. The battery in the device **100** forms the power source, capable of providing a stable and reliable supply of power to the other components. The size, capacity, and type of the battery **304** may be customized according to design preferences, device requirements, or various other factors, while being compliant with standard safety and operation guidelines. In some aspects, the battery **304** is encased within the device **100** and intended for device **100** replacement upon depletion of the battery **304**, while in other aspects, it is replaceable. In yet other aspects, the battery **304** is rechargeable using a charging port **308** or any other charging means as known to those skilled in the art.

[0065] The motor **302** functions as the primary mechanical component that is responsible for movement or force in the device **100**. Upon activation, the motor **302** draws power from the battery and begins to turn to rotate any of the one or more gears and the operably connected gear wheel **404**. The type, size, and characteristics of the motor **302** can be adjusted based on the requirements of the device, anticipated load, desired performance factors among other parameters.

[0066] The one or more gears represent a transmission mechanism, operably connected to the motor 302 and the gear wheel 404. Upon the activation of the device 100, the rotational force produced by the motor 302 is transferred to these gears. The gears enable the transfer of power from the motor 302 to the gear wheel 404. Upon receiving the force from the one or more gears of the activator mechanism 300, the gear wheel 404 begins to turn. This turning of the gear wheel 404 then contributes to the rotation of a cartridge carrier 200.

[0067] Referring again to FIG. 4, one embodiment pertains to an enhanced cartridge carrier 200 system, specifically designed with one or more alignment features 406 that protrude into the cartridge carrier 200 for a keyed connection and accurate cartridge 102 positioning, thereby improving the overall functionality of the cartridge 102 and the cartridge carrier 200 system.

[0068] The alignment features 406 of one embodiment are distinguishable protrusions present on the inner surface of the cartridge carrier 200. These alignment features 406 serve to guide the cartridge 102 into the correct position within the cartridge carrier 200 when installing a cartridge 102 into the system.

[0069] These protruding alignment features 406 also help to prevent misalignment and displacement of the cartridge 102 while it is installed and during operation. Notably and as described below in further detail, the alignment features 406 are critical in transitioning an inserted cartridge 102 between the stored and dispensing position.

[0070] The alignment features 406 are strategically located within the cartridge carrier 200 in a manner to engage with corresponding features or portions on the cartridge 102. When the cartridge 102 is inserted into the carrier 200, the protruding alignment features 406 guide it into the correct position as the features 406 fit into compatible sections (i.e., alignment channels 408) of the cartridge 102. This results in a snug and correct fit of the cartridge 102 within the cartridge carrier 200.

[0071] Furthermore, these alignment features 406 may come in various shapes and sizes and can be constructed using various materials that are suitable for the system and the intended application. They can be rigid to withstand the pressure exerted by the cartridge 102 as it is inserted into the cartridge carrier 200, or flexible to allow for slight variations in cartridge 102 size and shape.

[0072] For further understanding, FIGS. 5A through 5C depict side, top, and cross-sectional views, respectively, of the cartridge carrier 200 and alignment features 406. These features 406, protruding into the interior of the cartridge carrier 200, support the accurate placement of cartridges 102 within the device. Thus, the functionality and efficiency of the overall dispensing device 100 are significantly improved along with consistent cartridge 102 performance ensured by these alignment features 406. This inventive cartridge carrier 200 system design genuinely adds value to applications where precise alignment of cartridges 102 in their carrier systems is crucial. This one embodiment indeed ensures an innovative update for improving the efficiency of cartridge insertion and alignment in cartridge carrier systems, potentially paving the way for advancements in devices utilizing such systems.

[0073] As noted above and referring again to FIG. 4, the present disclosure also provides a unique medication cartridge 102 that can be inserted within a cartridge carrier, thus

providing a novel means to carry, store and administer medication. The essence of this one embodiment lies in the exclusive design of the medication cartridge 102 and the cartridge carrier that is not only easy to operate but also provides secure storage and effortless administration of the medication.

[0074] The medication cartridge 102 is an integral part of the inventive concept and is designed to contain distinct types of medications, be it in liquid, gel, or cream, or other dispensable forms of medication. The cartridge 102 can be made up of pharmaceutically safe materials ensuring no chemical reactions occur when in contact with the medication. The cartridge 102, itself can showcase cylindrical or other geometrical shapes as required by shape of the cartridge carrier 200. The medication cartridge 102 and cartridge carrier 200 partnership provides an ideal solution in various medical environments, such as hospitals, pharmacies, nursing homes, or even domestic settings. It proves to be beneficial where multiple medications should be stored and administered safely and hygienically. It combines innovation with convenience, improving medication storage, and administration methodologies.

[0075] As noted above and as shown in FIG. 6, the cartridge 102 itself is also designed to provide a marked improvement over other medication containers. It is envisioned to include markings or identification systems for easily recognizing the type of medication stored within each cartridge 102. The real innovation lies in the incorporation of one or more channels 408 and aligned slots 606 within the cartridge 102. These are constructed meticulously within the cartridge 102 and serve a distinct function of aligning and receiving one or more alignment features 406. As will be evident below, these channels 408 and slots 606 engage with the aforementioned alignment features 406 to allow for controlled operation of the device 100.

[0076] Further and as shown throughout FIGS. 6 through 7F, the present disclosure provides an improved configuration for a medication cartridge 102, particularly advantageous for medications that require enhanced storage for securely maintaining their efficacy and quality. The innovative design of the medication cartridge 102 includes a robust shell 600 that has a dispensing aperture 604 designed for the release of the medication stored within a medication vial 602.

[0077] The shell 600, formed from long-lasting and reliable material (e.g., plastic, metal, etc.), is shaped to house the vial 602 securely and efficiently. This shell 600 acts as a protective layer for the vial 602 placed inside, while maintaining the required conditions for the preservation of the medication. The dispensing aperture 604 deployed on the shell 600 is engineered in a way to align with the outlet 702 of the vial 602, ensuring precise and mess-free dispensation of the medication.

[0078] Inside the shell 600 is a medication vial 602, which is shaped and positioned in a manner that it can slide without difficulty within the shell 600. This ability of the vial 602 to slide enables convenient load and unload of the medication. The vial 602 includes a pump assembly 700 that is equipped with an outlet 702. The design and positioning of this outlet 702 are such that it aligns perfectly with the dispensing aperture 604 on the shell.

[0079] The pump assembly 700 is any suitable assembly that can be affixed with a container (i.e., the vial 602) to allow for pumping or otherwise dispensing a medication or

fluid therefrom, a non-limiting example of which includes a compression or spring-loaded pump, similar to the pump mechanism as used in a standard lotion bottle. For reference, FIG. 7G provides an illustration of an example pump assembly as provided for in the prior art, while FIG. 7H provides a non-limiting example of the pump assembly as modified and applied to the present invention. The pump assembly of the prior art (as shown in FIG. 7G) includes a clamp 1, press head 2, press lever 3, coat 4, screw cap 5, connect cap 6, gasket 7, piston 8, piston seat 9, spring 10, spring seat 11, valve 12, housing 13, and a straw 14. As applied to the present invention (as depicted in FIGS. 7F and 7H), the pump assembly 700 is connected to the vial 602, while the shell 600 serves as the press head that is used to press down the piston 8 to force the fluid through the straw 14 and out of the dispensing aperture 604. In some instances the pump assembly 700 can be screwed onto the vial 602; however, it should be understood that the invention is not intended to be limited thereto as the pump assembly 700 can be attached in any suitable manner between the vial 602 and shell 600 to allow for dispensing fluid from the vial 602 and out of the dispensing aperture 604. Further, it should be understood that the specific pump assembly 700 as depicted in FIG. 7H is provided as a non-limiting example of a suitable pump assembly and that the invention is not intended to be limited thereto as other mechanisms or assemblies can be used to dispense the fluid upon actuation. For example, the pump assembly can be formed as an airless pump, a peristaltic pump, a diaphragm pump, a pressurized canister style pump, or any other configuration in which activation of the assembly causes the fluid to dispense.

[0080] For illustrative purposes in comparison to a lotion bottle, the vial 602 would serve as the container to hold the fluid, while the shell 600 serves as the pump head that can be depressed to pump the fluid, with the various components of the pump assembly 700 positioned therebetween. In operation and when the medication cartridge 102 is moved to the dispensing position, the alignment features 406 operate to hold the vial 602 in place (due to their locking position in the channel terminal as described in further detail below), while a user can selective press the shell 600 downward around the vial 602 to activate the pump assembly 700 and force fluid from the vial 602.

[0081] For example, the vial 602 includes a reservoir 720 in which the medication is stored. The medication can be in a gas or fluid form; however, desirably and in one aspect, the medication is fluid and can be squirted from the medication cartridge 102 (and vial 602) via actuation of the pump assembly 700. As apparent from the description further below, the pump assembly 700 can be easily operated to cause the medication to be dispensed from the vial 602 through its outlet 702. When a force is applied on the pump assembly 700, it triggers the release of the medication inside of the vial 602, causing the medication to travel from the vial 602, passing through the aligned outlet 702 and dispensing aperture 604, where it is released to the user.

[0082] As noted above, the pump assembly 700 is any suitable assembly, mechanism, or device that can be affixed with the vial 602 to allow for selective dispensing therefrom. As can be appreciated by those skilled in the art, a non-limiting example of such a pump assembly 700 is a spring-loaded system utilizing a stacked one-way valve system to temporarily create a vacuum, allowing fluid to be aspirated

from the reservoir 720 and dispensed through the outlet 702 and dispensing aperture 604 upon depression of the shell 600 around the vial 602.

[0083] As noted above, the medication cartridge 102 is generally formed of two components, a shell 600 and a medication vial 602. The vial 602 is sized to be secured within and slide within the shell 600. As shown, the medication cartridge 102 includes a top end 704 and a bottom end 706. Although the shell 600 in FIG. 6 is illustrated as having a cap component 608 at the top end 704, the invention is not intended to be limited thereto as the shell 600 can be formed such that the cap component 608 is integrally formed with the shell 600 as a single unit. In such an aspect, a hole (e.g., sealable hole) can be formed at the bottom end 706 (or top end 704) of the shell 600 to allow for insertion of the vial 602 into the shell 600.

[0084] Notably and of particular importance, the vial 602 includes channels 408 that are aligned with the slots 606 on the shell 600. These channels 408 and slots 606 are built in a manner to accurately align with the alignment features 406 of the cartridge carrier 200. The number and size of these channels 408 and slots 606 can vary depending on the number of alignment features 406 intended to be placed therein. These channels are purposefully built to receive these alignment features, allowing secure and precise positioning. This design ensures that the alignment features do not shift their placement, further guaranteeing the stabilization of the medication within the cartridge.

[0085] For example, one example embodiment includes a structure involving a pair of opposing channels 408 are formed on opposite sides of the vial 602. These channels 408 are typically parallel to each other, though variations can occur. In one aspect, each of the pair of opposing channels 408 originates from the lowermost end or bottom end 706 of the vial 602. The pair of opposing channels 408 rise upward from this point, extending towards the top end 704 of the vial 602. This ascension continues until they reach a point known as the first junction 714. It must be clarified that this first junction 714 is not an arbitrary point but is a strategically designed and located structural feature within the device to precisely position the cartridge 102 between stored and dispensing positions.

[0086] Once these channels 408 have reached the first junction 714, the trajectory shifts. At this point, the channels 408 do not continue with the upward gradient. Instead, they commence a downward traversal toward the bottom end 706. They proceed downwards, but not vertically downwards. This descent is carried out on an angle around the vial 602, intended to enhance function and performance.

[0087] These angled downward channels 408 continue to move in the said direction until they reach an area deemed as the second junction 716. It is at this point that these channels 408 cease to continue. They terminate at this juncture, each channel 408 ending in what is referred to as a channel terminal 718. As will be apparent below, this distinctive configuration of the channels 708 enables them to perform their intended purpose more efficiently. It is important to consider the precise and specific architectural design of these channels 408, including their starting point at the bottom end 706 of the vial 602, their rise towards the first junction 714, their angled descent towards the second junction 716, which with respect to the channels, is the final termination at the channel terminal 718. These particular design elements reveal a thoughtful consideration of their

role within the device and contribute both independently and collectively to the overall functionality and performance of the device or system in question.

[0088] The present disclosure also provides an embodiment which is characterized by a pair of opposing slots **606** in the shell **600** that align with the pair of opposing channels **408**. More specifically, one embodiment is the configuration and interaction of these parts, enabling the pair of opposing protrusions **406** to pass through the pair of opposing slots **606** and into the pair of opposing channels **408** to allow for moving the cartridge **102** between the stored and dispensing positioned and, ultimately, sliding the vial **602** within the shell **600** for dispensation of the medication.

[0089] The pair of opposing slots **606** are formed through the surface of the shell **600** to allow access to the channels **408** therein. These slots **606** are designed with precise measurements to fit and accommodate corresponding elements, namely, a distinct pair of opposing protrusions **406**. The opposing slots **606** are carved or formed into the shell **600** and aligned in such a way that they maintain a clear, unobstructed path for the protrusions **406** to pass through them with ease. The unique arrangement allows for the insertion of the pair of opposing protrusions **406**, which are another critical characteristic of this one embodiment. These protrusions **406**, with their matching dimensions to the slots **606**, are designed to glide smoothly through the opposing slots **606** and into the aligned opposing channels **408**. The path provided by the slots **606** guides and directs the protrusions **406** into the appropriate channels **408**. Consequently, this ensures a specific interaction between the three parts: the opposing protrusions **406** smoothly pass through the opposing slots **606**, and they are then guided into the opposing channels **408**, maintaining a suitable and secure connection.

[0090] Further, the medication cartridge **102** presents an innovative design with respect to the pair of opposing slots **606**. Each of the pair of opposing slots **606** is formed of a first slot **708**, a second slot **710**, and a third slot **712**. These slots are strategically positioned and oriented for the optimal functioning of the device. The first slot **708** in each pair begins at the bottom end **706** of the shell **600** and extends upward toward the top end **704**. It is arranged in such a way that it mandates a route which ascends from the base to a designated position along the length of the cartridge **102**, otherwise referred to as the first junction **714**.

[0091] Subsequent to the first junction **714**, the structure of the shell **600** features a second slot **710** for each pair. Instead of following the upward trajectory of its predecessor, this second slot **710** takes on a unique characteristic of its own by providing an angled path that descends from the first junction **714**. This downward movement proceeds until it reaches a designated point along the body of the shell **600**, referred to herein as the second junction **716**. Moreover, the slot design of the shell **600** reverts back to an upward direction in the subsequent and final arrangement of each pair-the third slot **712**. Commencing from the second junction **716**, this slot ascends once again (e.g., vertically) towards the top end **704** of the cartridge. The distinct positions and paths of the slots **708**, **710**, and **712** provide a sophisticated layout that enhances the fundamental operations of this medication cartridge **102**. Notably, while the channel **408** terminates at the second junction **716** or channel terminal **718**, the third slot **712** proceeds upwards from the second junction **716**. This differentiation allows for the

selective dispensing of the medication therein. This innovative structure enhances the controlled dispensing of medication, making this cartridge **102** particularly advantageous in the administration of drugs. The angles and special slot layout improves the overall efficiency and operational effectiveness of the delivery system, which in turn can broaden its potential applications in the medical and pharmaceutical fields. The precise orientation of the slots from bottom to top and their alternating directions contribute to creating a balanced and smooth transition of the medication within the cartridge **102**. The level of control provided by this inventive structure is a significant evolution in medication delivery system designs.

[0092] For further understanding, FIGS. **8A** and **8B** depict a medication cartridge **102** as being installed or otherwise inserted into the cartridge carrier **200**. As shown, the alignment features **406** (i.e., opposing protrusions) provided a keyed connection and alignment by passing through the channels **408** and slots **606** to allow the cartridge **102** to be contained within the carrier **200**. As shown in FIG. **9**, the alignment feature **406** has travelled through the first slot **708** and channel **408** to rest at the first junction **714**. In this position, the medication cartridge **102** is held within the dispensing device in a stored position. Since the alignment feature **406** is at a fixed location within the cartridge carrier **200**, and because the second slot **710** and channel **408** descend downwards at an angle from the first junction **714**, rotation of the cartridge carrier **200** necessarily forces the medication cartridge **102** upwards within the cartridge carrier **200**. These aspects are further depicted in FIGS. **10A** through **10C**.

[0093] FIG. **10A** depicts the medication cartridge in a stored position. As shown, the alignment feature **416** rests within the first junction **714**. As shown in FIG. **10B**, rotation **1000** (via the gear wheel **404**) of the cartridge carrier **200** forces the alignment feature **416** to traverse through the second slot **710** and channel **408** away from the first junction **714**. In doing so and as shown, the medication cartridge **102** is lifted upwards within the cartridge carrier **200**. Further rotation **1000** of the cartridge carrier **200**, as shown in FIG. **10C**, results in the alignment feature **416** to traverse until it rests within the second junction **716** and the channel **408** terminates at the channel terminal **718**. Notably, when the alignment feature **416** is at the second junction **716**, the medication cartridge **102** is lifted from the dispensing device **100** into the dispensing position. Thus, the journey of the protrusions commences from the first junction **714**, progressing towards the second junction **716**. As a consequence of this carefully guided pathway, the medication cartridge **102** experiences an upward shift. This movement is instrumental in the transition of the medication cartridge **102** from what is denoted as the 'stored position' to its final location, the 'dispensing position'.

[0094] While the cartridge **102** is in the dispensing position, the vial **602** therein is in the expanded state and ready to be compressed to dispense medication. As shown in FIGS. **11A** through **11C**, although the channel **408** in the vial **602** has terminated, the slot in the shell **600** continues upwards as the third slot **712**. Thus, when the medication cartridge **102** is in the dispensing position, a user can selectively press down on the medication cartridge **102** to cause the vial **602** to slide within the shell **600**. As shown in FIG. **11C**, due to the stepped inner wall **1100** and end of the channel **408**, the vial **602** is held in place by the alignment

features 406 and only the outer shell 600 can travel downward when pressed down, causing the shell 600 to slide downward over the vial 602 and allowing the pump assembly to be actuated and spray/dispense the medication. This feature is further illustrated in FIGS. 12A and 12B. As shown, pressing downward 1200 on the medication cartridge 102 causes the alignment features 406 to travel upwards through the third slot 712, thereby forcing the shell 600 downward while holding the vial 602 in place. While the shell 600 is forced downward, it compresses the vial 602 from the expanded to compressed state. The transition from the expanded to compressed state activates the pump assembly to force medication 1202 from the vial 602 and through the dispensing aperture 604, similar to a squirt of medication. The pump assembly can be configured as a spring-loaded pump mechanism that lifts the shell 600 after being compressed, thereby returning the alignment features 406 to the second junction 716. Once dispensed, the dispensing device 100 and associated activator mechanism 300 can be activated to turn the gear wheel 404 in an opposite direction as previously rotated. Such a rotation lowers the medication cartridge 102 back to the stored position as the alignment features 406 are forced back to the first junction 714 (shown in FIG. 10A).

[0095] In one aspect, the device 100 is formed to sense once a predetermined number of squirts (e.g., one, etc., as prescribed) have been initiated so that it automatically activates the activator mechanism 300 to return the medication cartridge 102 back to the stored position, thereby retracting the medication cartridge 102 and inaccessibility after user. For example, magnetic sensors, a trigger, electrical sensors, light sensors, or any other means for determining if medication has been dispensed from the vial 602 can be included within the device 100. As a non-limiting example, a magnet can be positioned at the bottom of the shell 600 while a magnetic reed switch is similarly positioned at the bottom of the cartridge carrier 200. Pressing the medication cartridge 102 and its shell 600 downward within the cartridge carrier 200 brings the magnet into close proximity of the magnetic reed switch to notify the associated electronics (integrated circuit, etc.) that a single squirt has been dispensed. After the predetermined number of squirts, the activator mechanism is activated to rotate the cartridge carrier 200 and return the medication cartridge 102 to the stored position to prevent further and unauthorized use. In another aspect, the device 100 can include any necessary components (integrated circuit, etc.) to allow for a timed configuration in which the medication cartridge 102 is held in the dispensing position. For example, the device 100 can be programmed such that after authentication and movement of the medication cartridge 102 in the dispensing position, it is returned to the stored position after a predetermined or preprogrammed amount of time (e.g. 2 seconds, etc.).

[0096] As noted above, a unique design feature allows for the vial 602 to exist in two distinct states; namely an expanded state and a compressed state. The transition between these two stages is critical to the functionality of the device. When it moves from the expanded state towards the compressed state, the incorporated pump assembly 700 is triggered into action. This incorporation of a pump assembly 700 and its associated operation indicates an upbeat sophistication of the one embodiment, going beyond traditional static medical dispensing devices. The purpose of this actuation is specifically to ensure the controlled release of the

medicine within the vial 602. On the actuation of the pump assembly 700, the medicine 1202 is pushed out of the vial's 602 outlet. This outflow proceeds under the controlling and moderating role of the pump assembly 700, guaranteeing a controlled and managed release of the medicine.

[0097] In summary, the present disclosure provides an innovative medication dispensing device 100. The core of this medication dispensing device 100 revolves around a unique cartridge carrier 200 design, integrated with a pair of opposing protrusions 406 and a uniquely designed medication cartridge that is functionally designed to operate based on the positioning of the protrusions 406 after user authentication. As noted above, in one aspect, the device 100 includes an authentication mechanism 106. Upon successful authentication, the authentication mechanism 106 triggers the activator mechanism 300. In this context, the activation entails the initiation of moving the medication cartridge 102. When activated, it can efficaciously induce the cartridge carrier 200 mechanism to actuate, progressing the inserted medication cartridge 102 from a stored position to a dispensing position. Maximal effectiveness is ensured as the activator mechanism 106 is engendered only after a successful user authentication process, thereby verifying that the medication is dispensed to the appropriate user. This sequence not only ensures secure and controlled dispensing of the medication but also minimizes errors and the potential for unlawful access. In one aspect, the interconnectedness between the authentication mechanism 106 and the activator mechanism 300 forms the crux of this system, thereby augmenting the overall safety and operation of the dispensing device 100. Moreover, this intricate mechanism, in coordination with the user and the cartridge carrier 200, ensures that the process of moving the medication cartridge 102 from a stored position to a dispensing position is not only smooth but also efficient and secure.

[0098] Thus, in one aspect, a purpose of this inventive operation is to modify the positioning of the medication cartridge 102 from a state of storage to a dispensing state, thereby facilitating the delivery of medication in a controlled, efficient, and timely manner. The operational process involved in use of the dispensing device 100 advances through several stages, starting with the activation of the activator mechanism 300. The initiation of this mechanism 300 leads to a rotational motion in the cartridge carrier 200, a critical movement that fosters the maneuvering of the pair of opposing protrusions 406 (i.e., alignment features). This rotation is precisely designed to stimulate this movement, making the entire process efficient and seamless. The pair of opposing protrusions 406 are guided in their motion by a pair of opposing slots 606 in conjunction with a pair of opposing channels 408. These channels 408 and slots 606 function in harmony, not only providing a safe passage but also controlling the direction of the movement of these protrusions 406 while guiding the medication cartridge 102 between a stored position and a raised dispensing position. The unique features of the slots 606 and channels 408 also allow a user to compress the vial 602 within the medication cartridge 102 to dispense medication 1202.

[0099] Finally, while this invention has been described in terms of several embodiments, one of ordinary skill in the art will readily recognize that the invention may have other applications in other environments. It should be noted that many embodiments and implementations are possible. Further, the following claims are in no way intended to limit the

scope of the present invention to the specific embodiments described above. In addition, any recitation of “means for” is intended to evoke a means-plus-function reading of an element and a claim, whereas, any elements that do not specifically use the recitation “means for”, are not intended to be read as means-plus-function elements, even if the claim otherwise includes the word “means”. Further, while particular method steps have been recited in a particular order, the method steps may occur in any desired order and fall within the scope of the present invention.

What is claimed is:

1. (canceled)

2. A handheld medication dispensing device, comprising: a housing having a cartridge carrier therein, the cartridge carrier having a keyed connector that is keyed to a medication cartridge to allow for insertion and alignment of the medication cartridge within the cartridge carrier;

an activator mechanism positioned within the housing, the activator mechanism operably connected with the cartridge carrier to cause the cartridge carrier to actuate, whereby upon actuation, the cartridge carrier moves an inserted medication cartridge between a stored position and a dispensing position; and

wherein the cartridge carrier is rotatable within the housing, such that upon rotation, an inserted medication cartridge, when inserted therein, is raised upward from the housing from the stored position to the dispensing position.

3. The handheld medication dispensing device as set forth in claim 2, wherein the cartridge carrier includes a proximal end and a distal end, the proximal end being open for receiving the medication cartridge therein, while the distal end includes a gear wheel operably connected to the activator mechanism.

4. The handheld medication dispensing device as set forth in claim 3, wherein the activator mechanism includes at least a battery, a motor, and one or more gears that are operably connected to the gear wheel, such that activation of the activator mechanism causes the motor to turn the one or more gears and, in doing so, turn the gear wheel and rotate the cartridge carrier.

5. The handheld medication dispensing device as set forth in claim 4, wherein the keyed connector includes one or more alignment features that protrude into the cartridge carrier.

6. (canceled)

7. The handheld medication dispensing device as set forth in claim 5, further comprising an authentication mechanism operably connected with the activator mechanism, the authentication mechanism operable for authenticating a user and, when authenticated, activating the activator mechanism to cause the cartridge carrier to actuate and move an inserted medication cartridge from the stored position to the dispensing position.

8. (canceled)

9. (canceled)

10. (canceled)

* * * * *