

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250269795

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

MASUTANI; Nami et al.

VEHICULAR VIEWING DEVICE AND METHOD OF ASSEMBLING VEHICULAR VIEWING DEVICE

Abstract

In a door mirror device, a base is attached to a vehicle body side, and the base supports a mirror and is covered by an inner cover. Here, the inner cover is rotated in a state in which an insertion tube of the base is inserted into an insertion hole in the inner cover, whereby the inner cover is locked in the axial direction and the circumferential direction of the insertion hole to the base. For this reason, the inner cover can be stably rotated, and the inner cover can be easily assembled to the base.

Inventors: MASUTANI; Nami (Aichi, JP), NAKAYAMA; Yuto (Aichi, JP)

Applicant: KABUSHIKI KAISHA TOKAI-RIKA-DENKI-SEISAKUSHO (Niwa-gun, JP)

Family ID: 1000008492994

Appl. No.: 19/061314

Filed: February 24, 2025

Foreign Application Priority Data

JP 2024-027811

Feb. 27, 2024

Publication Classification

Int. Cl.: B60R1/076 (20060101)

U.S. Cl.:

CPC B60R1/076 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application is based on and claims priority under 35 USC 119 from Japanese Patent Application No. 2024-27811 filed on Feb. 27, 2024, the disclosure of which is incorporated by reference herein.

BACKGROUND

Technical Field

[0002] The present invention relates to a vehicular viewing device where a cover body covers a support body that supports a viewing mechanism and to a method of assembling the vehicular viewing device.

Related Art

[0003] Japanese Utility Model Application Laid-open (JP-U) No. S63-6953 discloses a door mirror structure where a core portion is attached to a vehicle body side, and the core portion supports a mirror and is covered by a cover portion.

[0004] Here, in this door mirror structure, a plate-shaped part of the core portion is inserted into a holding portion of the cover portion while the cover portion is rotated, and a projection on the plate-shaped part is mated with a recess in the holding portion, whereby the cover portion is locked in the holding portion axial direction and the holding portion circumferential direction to the core portion.

SUMMARY

[0005] In consideration of the circumstances described above, it is an object of the present invention to obtain a vehicular viewing device with which a cover body can be easily assembled to a support body and a method of assembling the vehicular viewing device.

[0006] A vehicular viewing device of a first aspect of the invention includes: a viewing mechanism that assists viewing by an occupant; a support body that is attached to a vehicle body side and that supports the viewing mechanism; and a cover body that is provided with an insertion hole, that is rotated in an insertion hole circumferential direction in a state in which the support body is inserted into the insertion hole whereby the cover body is locked in an insertion hole axial direction and the insertion hole circumferential direction to the support body, and that covers the support body.

[0007] In the vehicular viewing device of the first aspect of the invention, the viewing mechanism assists viewing by the occupant. Furthermore, the support body is attached to the vehicle body side, and the support body supports the viewing mechanism and is covered by the cover body.

[0008] Here, the cover body is rotated in the insertion hole circumferential direction in a state in which the support body is inserted into the insertion hole in the cover body, whereby the cover body is locked in the insertion hole axial direction and the insertion hole circumferential direction to the support body. For this reason, the cover body can be stably rotated, and the cover body can be easily assembled to the support body.

[0009] A vehicular viewing device of a second aspect of the invention is the vehicular viewing device of the first aspect of the invention, further including a raised portion that is provided at one of the support body or the cover body, and a recessed portion that is provided at another of the support body or the cover body and into which the raised portion is inserted whereby the cover body is locked in the insertion hole axial direction and the insertion hole circumferential direction to the support body.

[0010] In the vehicular viewing device of the second aspect of the invention, the raised portion on one of the support body or the cover body is inserted into the recessed portion in the other of the support body or the cover body, whereby the cover body is locked in the insertion hole axial direction and the insertion hole circumferential direction to the support body. For this reason, the cover body can be easily locked in the insertion hole axial direction and the insertion hole circumferential direction to the support body.

[0011] A vehicular viewing device of a third aspect of the invention is the vehicular viewing device

of the second aspect of the invention, wherein the raised portion is inserted into the recessed portion whereby the cover body is locked in an insertion hole radial direction to the support body. [0012] In the vehicular viewing device of the third aspect of the invention, the raised portion is inserted into the recessed portion, whereby the cover body is locked in the insertion hole radial direction to the support body. For this reason, the cover body can be locked in the insertion hole radial direction to the support body with a simple configuration.

[0013] A vehicular viewing device of a fourth aspect of the invention is the vehicular viewing device of any of the first aspect to the third aspect of the invention, further including an engagement portion that is provided at the cover body and that is engaged with the support body whereby rotation of the cover body in a direction in which the locking of the cover body in the insertion hole axial direction and the insertion hole circumferential direction to the support body is canceled, is locked.

[0014] In the vehicular viewing device of the fourth aspect of the invention, the engagement portion of the cover body is engaged with the support body, whereby rotation of the cover body in a direction in which the locking of the cover body in the insertion hole axial direction and the insertion hole circumferential direction to the support body is canceled, is locked. For this reason, the locking of the cover body in the insertion hole axial direction and the insertion hole circumferential direction to the support body can be limited from being canceled.

[0015] A vehicular viewing device of a fifth aspect of the invention is the vehicular viewing device of any of the first aspect to the fourth aspect of the invention, wherein the support body supports the cover body in the insertion hole axial direction and guides the rotation of the cover body in the insertion hole circumferential direction.

[0016] In the vehicular viewing device of the fifth aspect of the invention, the support body supports the cover body in the insertion hole axial direction and guides the rotation of the cover body in the insertion hole circumferential direction. For this reason, the cover body can be even more stably rotated in the insertion hole circumferential direction.

[0017] A method of assembling a vehicular viewing device of a sixth aspect of the invention is a method of assembling a vehicular viewing device including a viewing mechanism that assists viewing by an occupant, a support body that is attached to a vehicle body side and that supports the viewing mechanism, and a cover body that is provided with an insertion hole and that covers the support body, wherein the cover body is rotated in an insertion hole circumferential direction in a state in which the support body is inserted into the insertion hole whereby the cover body is locked in an insertion hole axial direction and the insertion hole circumferential direction to the support body.

[0018] In the vehicular viewing device at the sixth aspect of the invention, the viewing mechanism assists viewing by the occupant. Furthermore, the support body is attached to the vehicle body side, and the support body supports the viewing mechanism and is covered by the cover body.

[0019] Here, in the method of assembling the vehicular viewing device of the sixth aspect of the invention, the cover body is rotated in the insertion hole circumferential direction in a state in which the support body is inserted into the insertion hole in the cover body, whereby the cover body is locked in the insertion hole axial direction and the insertion hole circumferential direction to the support body. For this reason, the cover body can be stably rotated, and the cover body can be easily assembled to the support body.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] An exemplary embodiment of the present invention will be described in detail based on the following figures, wherein:

[0021] FIG. 1A is a back view showing a door mirror device pertaining to the embodiment of the invention as viewed from the front side of a vehicle;

[0022] FIG. 1B is a perspective view showing the door mirror device pertaining to the embodiment of the invention as viewed from the rear side of the vehicle and inward in the vehicle width direction;

[0023] FIG. 2A is a perspective view showing main portions of the door mirror device pertaining to the embodiment of the invention as viewed from the rear side of the vehicle and outward in the vehicle width direction;

[0024] FIG. 2B is a perspective view showing main portions of the door mirror device pertaining to the embodiment of the invention as viewed from the front side of the vehicle and outward in the vehicle width direction;

[0025] FIG. 3A is a side view showing a base of the door mirror device pertaining to the embodiment of the invention as viewed from outward in the vehicle width direction;

[0026] FIG. 3B is a side view showing the base of the door mirror device pertaining to the embodiment of the invention as viewed from inward in the vehicle width direction;

[0027] FIG. 4A is a front elevation view showing the base of the door mirror device pertaining to the embodiment of the invention as viewed from the front side of the vehicle;

[0028] FIG. 4B is a top view showing the base of the door mirror device pertaining to the embodiment of the invention as viewed from above;

[0029] FIG. 5A is a perspective view showing an inner cover of the door mirror device pertaining to the embodiment of the invention as viewed from the rear side of the vehicle and inward in the vehicle width direction;

[0030] FIG. 5B is a perspective view showing the inner cover of the door mirror device pertaining to the embodiment of the invention as viewed from the front side of the vehicle and outward in the vehicle width direction;

[0031] FIG. 6A is a perspective view showing the inner cover of the door mirror device pertaining to the embodiment of the invention as viewed from the rear side of the vehicle and outward in the vehicle width direction;

[0032] FIG. 6B is a perspective view showing the inner cover of the door mirror device pertaining to the embodiment of the invention as viewed from below;

[0033] FIG. 7A is a top view showing the inner cover being assembled to the base in the door mirror device pertaining to the embodiment of the invention as viewed from above; and

[0034] FIG. 7B is a cross-sectional view (a cross-sectional view taken along line 7B-7B of FIG. 7A) showing the inner cover being assembled to the base in the door mirror device pertaining to the embodiment of the invention as viewed from the front side of the vehicle.

DETAILED DESCRIPTION

[0035] In FIG. 1A, a door mirror device **10** serving as a vehicular viewing device pertaining to an embodiment of the invention is shown in a back view as viewed from the front side of a vehicle, and in FIG. 1B, the door mirror device **10** is shown in a perspective view as viewed from the rear side of the vehicle and inward in the vehicle width direction. Moreover, in FIG. 2A, main portions of the door mirror device **10** are shown in a perspective view as viewed from the rear side of the vehicle and outward in the vehicle width direction, and in FIG. 2B, main portions of the door mirror device **10** are shown in a perspective view as viewed from the front side of the vehicle and outward in the vehicle width direction. It will be noted that in the drawings arrow FR indicates the vehicle forward direction, arrow OUT indicates the outward direction (vehicle leftward direction) in the vehicle width direction, and arrow UP indicates the upward direction.

[0036] The door mirror device **10** pertaining to the present embodiment is installed on the vehicle front end portion of the up and down direction middle portion of a side door (front side door; not shown in the drawings) serving as a vehicle body side of a vehicle (automobile) and is disposed on the vehicle outer side of the side door.

[0037] As shown in FIG. 1A, FIG. 1B, FIG. 2A, and FIG. 2B, the door mirror device **10** is provided with a substantially columnar base **12** (see FIG. 3A, FIG. 3B, FIG. 4A, and FIG. 4B) serving as a support body, and the lower portion of the base **12** runs through an outer panel of the side door and is attached to an inner panel of the side door, whereby the door mirror device **10** is installed on the side door.

[0038] The upper portion of the base **12** is provided with a substantially round tube-shaped insertion tube **14**. The insertion tube **14** projects outward in the vehicle width direction, and its axial direction is substantially aligned with the up and down direction. On the lower portion of the inside of the insertion tube **14**, a substantially annular plate-shaped anchor plate **16** is integrally provided, and the anchor plate **16** is disposed coaxially with the insertion tube **14**. On the lower portion of the outer periphery of the insertion tube **14**, a predetermined number (in the present embodiment, three) of substantially rectangular plate-shaped raised portions **18** are integrally provided, and the predetermined number of raised portions **18** are arranged substantially equidistantly in the circumferential direction of the insertion tube **14**. The raised portions **18** are disposed orthogonally to the axial direction of the insertion tube **14**, and the positions of the predetermined number of raised portions **18** in the axial direction of the insertion tube **14** coincide with each other. On the lower end portion of the outer periphery of the insertion tube **14**, a substantially rectangular plate-shaped engagement plate **20** serving as an engaged portion is integrally provided, and the engagement plate **20** is disposed orthogonally to the axial direction of the insertion tube **14**.

[0039] The base **12** is covered, on the upper side of the outer panel of the side door, by a substantially round tube-shaped base cover **22** that is made of resin and serves as a cover member, and the upper end portion of the base cover **22** is configured by a projecting portion **22A** and projects outward in the vehicle width direction. The base cover **22** is configured by assembling to each other an inner cover **24** serving as a cover body located on the vehicle width direction inner side (see FIG. 5A, FIG. 5B, FIG. 6A, and FIG. 6B) and an outer cover **26** located on the vehicle width direction outer side. The inner cover **24** configures the upper part (including the vehicle width direction inner part) of the projecting portion **22A**, and the outer cover **26** configures the lower part (excluding the vehicle width direction inner part) of the projecting portion **22A**.

[0040] On the inner cover **24** (the base cover **22**), a substantially annular plate-shaped upper wall is integrally provided. The upper wall of the inner cover **24** is disposed substantially orthogonally to the up and down direction, and its lower surface is configured to be planar. The inner peripheral edge of the upper wall of the inner cover **24** is configured substantially in the shape of a round tube and projects upward, and the inside of the upper wall of the inner cover **24** is configured as an insertion hole **28**. On the lower portion of the peripheral surface of the insertion hole **28**, a predetermined number (in the present embodiment, four) of rectangular planar locking surfaces **30** serving as locking portions are formed. The predetermined number of locking surfaces **30** are arranged equidistantly in the circumferential direction of the insertion hole **28** and are disposed orthogonally to the radial direction of the insertion hole **28**. The insertion tube **14** of the base **12** is coaxially inserted into the insertion hole **28** from below, and the locking surfaces **30** are abutted against the insertion tube **14**. For this reason, the peripheral surface of the insertion hole **28** is locked to the insertion tube **14** in the radial direction, and the inner cover **24** is locked in the radial direction of the insertion hole **28** to the base **12**.

[0041] On the lower surface of the upper wall of the inner cover **24**, a predetermined number (in the present embodiment, three) of cross-sectionally L-shaped plate-shaped locking pieces **32** are integrally provided, and the predetermined number of locking pieces **32** are arranged substantially equidistantly in the circumferential direction of the insertion hole **28**. The insides of the locking pieces **32** are configured as recessed portions **32A** and are open in the direction of arrow A (one side in the circumferential direction of the insertion hole **28**) and on their insertion hole **28** sides. The sides opposite from the insertion hole **28** of the insides of the locking pieces **32** located on the

vehicle width direction inner side are closed off by the peripheral wall of the inner cover **24**, and the side opposite from the insertion hole **28** of the inside of the locking piece **32** located on the vehicle width direction outer side is closed off by a closure wall **32B**.

[0042] The raised portions **18** of the base **12** (the insertion tube **14**) are inserted into the locking pieces **32** (the recessed portions **32A**). The proximal end walls (upper walls) of the locking pieces **32** are abutted against the raised portions **18**, whereby rotation of the locking pieces **32** in the direction of arrow A is locked by the raised portions **18**, and the inner cover **24** is locked in the direction of arrow A to the base **12**. The distal end walls (lower walls) of the locking pieces **32** and the upper wall of the inside cover **24** are abutted against the raised portions **18**, whereby the locking pieces **32** are locked to the raised portions **18** on both sides in the up and down direction, and the inner cover **24** is locked on both sides in the up and down direction to the base **12**.

[0043] On the upper portion of the inner surface of the peripheral wall of the inner cover **24**, an engagement claw **34** serving as an engagement portion is integrally provided, and the engagement claw **34** extends on the side of the direction of arrow A on the lower side of the locking pieces **32**. On the distal end portion of the engagement claw **34**, a claw portion **34A** that is substantially trapezoidal in cross-section is integrally provided, and the claw portion **34A** projects downward. The claw portion **34A** is engaged with the engagement plate **20** of the base **12** (the insertion tube **14**) from above, whereby rotation of the engagement claw **34** in the direction of arrow B (the other side in the circumferential direction of the insertion hole **28**) is locked by the engagement plate **20**, and the inner cover **24** is locked in the direction of arrow B to the base **12**.

[0044] On the upper side of the base **12** is disposed a storage mechanism (not shown in the drawings) serving as a support mechanism. The lower portion of the storage mechanism is inserted into the insertion tube **14** of the base **12** from above. When, in a state in which a predetermined number (in the present embodiment, three) of screws (not shown in the drawings) have been passed through the anchor plate **16** inside the insertion tube **14** from below, the lower portion of the storage mechanism is fastened by the screws to the anchor plate **16**, the storage mechanism (not shown in the drawings) is anchored to and supported by the upper side of the base **12**.

[0045] The upper part of the storage mechanism above the lower portion is inserted into the vehicle width direction inner portion of a substantially cuboidal box-shaped visor **36** serving as a surrounding body, and the visor **36** is anchored to and supported by the storage mechanism. The vehicle rear surface of the visor **36** is configured as a substantially rectangular opening **38**, and the opening **38** opens the inside of the visor **36** in the vehicle rearward direction.

[0046] Inside the visor **36**, a substantially rectangular plate-shaped mirror **40** serving as a viewing mechanism is supported, and the mirror **40** is disposed in the opening **38** of the visor **36**. The obverse side of the mirror **40** is exposed in the vehicle rearward direction through the opening **38** of the visor **36**, and viewing in the vehicle rearward direction by an occupant of the vehicle is assisted by the occupant viewing light reflected by the mirror **40**.

[0047] It will be noted that when the storage mechanism is activated in one direction, the visor **36** and the mirror **40** are pivoted in the vehicle rearward direction and inward in the vehicle width direction about the insertion tube **14** and stored. Moreover, when the storage mechanism is activated in the other direction, the visor **36** and the mirror **40** are pivoted in the vehicle forward direction and outward in the vehicle width direction about the insertion tube **14** and erected (restored).

[0048] Next, the action of the present embodiment will be described.

[0049] When assembling the door mirror device **10** having the above configuration, in a state in which the insertion tube **14** of the base **12** has been inserted into the insertion hole **28** of the inner cover **24** of the base cover **22** from below, the inner cover **24** is rotated in the direction of arrow A and the raised portions **18** of the base **12** are inserted into the locking pieces **32** (the recessed portions **32A**) of the inner cover **24** (see FIG. 7A and FIG. 7B). Moreover, the engagement claw **34** of the inner cover **24** is temporarily elastically deformed upward by the engagement plate **20** of the

base **12**, and the claw portion **34A** of the engagement claw **34** becomes engaged with the engagement plate **20**.

[0050] Then, the lower portion of the storage mechanism inside the visor **36** is inserted into the insertion tube **14** of the base **12** from above, and the lower portion of the storage mechanism is fastened by the predetermined number of screws to the anchor plate **16** inside the insertion tube **14** from below, whereby the visor **36** (including the storage mechanism and the mirror **40**) is supported by the upper side of the base **12**.

[0051] Thereafter, when the outer cover **26** is assembled to the inner cover **24**, the base cover **22** is configured and the part of the base **12** between the side door (the outer panel) and the visor **36** is covered by the base cover **22**.

[0052] Here, in the state in which the insertion tube **14** of the base **12** is inserted into the insertion hole **28** of the inner cover **24**, the inner cover **24** is rotated in the direction of arrow A (the one side in the circumferential direction of the insertion hole **28**) and the raised portions **18** of the base **12** are inserted into the locking pieces **32** (the recessed portions **32A**) of the inner cover **24**, whereby the distal end portions and the proximal end portions of the locking pieces **32** are abutted against the raised portions **18**, and the inner cover **24** is locked in the upward direction (one side in the axial direction of the insertion hole **28**) and the direction of arrow A to the base **12**. For this reason, the inner cover **24** can be stably rotated in the direction of arrow A by the insertion of the insertion tube **14** into the insertion hole **28**, and the inner cover **24** can be easily assembled to the base **12**. Moreover, in contrast to a case where an elastic claw extending downward from the upper wall of the inner cover **24** is locked to the base **12** and the inner cover **24** is locked to the base **12** in the upward direction, the up and down direction dimension of the projecting portion **22A** of the base cover **22** can be limited from becoming larger because of the elastic claw, design freedom for the base cover **22** can be raised, and the strength of the locking of the inner cover **24** to the base **12** in the upward direction can be limited from becoming lower because of the elastic claw.

[0053] Moreover, as described above, the raised portions **18** of the base **12** are inserted into the locking pieces **32** of the inner cover **24**, and the inner cover **24** is locked in the upward direction and the direction of arrow A to the base **12**. For this reason, the inner cover **24** can be easily locked in the upward direction and the direction of arrow A to the base **12**.

[0054] Moreover, the upper wall of the inner cover **24** is locked in the downward direction (the other side in the axial direction of the insertion hole **28**) to the raised portions **18** of the base **12**. For this reason, the inner cover **24** can be locked in the downward direction to the base **12**.

[0055] Furthermore, the insertion tube **14** of the base **12** is inserted into the insertion hole **28** of the inner cover **24**, and the locking surfaces **30** on the peripheral surface of the insertion hole **28** are abutted against the insertion tube **14**, whereby the peripheral surface of the insertion hole **28** is locked to the insertion tube **14** in the radial direction, and the inner cover **24** is locked in the radial direction of the insertion hole **28** to the base **12**. For this reason, the inner cover **24** can be locked in the radial direction of the insertion hole **28** to the base **12**.

[0056] Moreover, the claw portion **34A** of the engagement claw **34** of the inner cover **24** is engaged with the engagement plate **20** of the base **12**, whereby rotation of the inner cover **24** in the direction of arrow B (the other side in the circumferential direction of the insertion hole **28**, the direction in which the locking of the inner cover **24** in the upward direction and the direction of arrow A to the base **12** is canceled) is locked. For this reason, the locking of the inner cover **24** in the upward direction and the direction of arrow A to the base **12** can be limited from being canceled.

[0057] Furthermore, when the inner cover **24** is rotated in the direction of arrow A, the raised portions **18** of the base **12** support the upper wall of the inner cover **24** from below (the other side in the axial direction of the insertion hole **28**) and guide the rotation of the inner cover **24** in the direction of arrow A. For this reason, the inner cover **24** can be rotated even more stably in the direction of arrow A.

[0058] It will be noted that in the present embodiment the inner cover **24** is locked in the radial

direction of the insertion hole **28** to the base **12** as a result of the locking surfaces **30** on the peripheral surface of the insertion hole **28** of the inner cover **24** being abutted against the insertion tube **14** of the base **12**. However, the inner cover **24** may also be locked in the radial direction of the insertion hole **28** to the base **12** as a result of the raised portions **18** of the base **12** being inserted into the locking pieces **32** of the inner cover **24** and the closure portions (the peripheral wall of the inner cover **24** or the closure wall **32B**) on the sides of the locking pieces **32** opposite from the insertion hole **28** being abutted against the raised portions **18**. Because of this, the inner cover **24** can be locked in the radial direction of the insertion hole **28** to the base **12** with a simple configuration that uses the locking pieces **32** and the raised portions **18**.

[0059] Furthermore, in the present embodiment, the raised portions **18** are provided on the base **12** and the recessed portions **32A** are provided in the inner cover **24**. However, the recessed portions **32A** may be provided in the base **12** and the raised portions **18** may be provided on the inner cover **24**.

[0060] Moreover, in the present embodiment, three each of the raised portions **18** and the recessed portions **32A** are provided. However, one, two, or four or more each of the raised portions **18** and the recessed portions **32A** may be provided.

[0061] Furthermore, in the present embodiment, the viewing mechanism is configured by the mirror **40**. However, the viewing mechanism may also be configured by a camera, and in this case, viewing by the occupant is assisted by images captured by the camera.

Claims

1. A vehicular viewing device comprising: a viewing mechanism that assists viewing by an occupant; a support body that is attached to a vehicle body side and that supports the viewing mechanism; and a cover body that is provided with an insertion hole, that is rotated in an insertion hole circumferential direction in a state in which the support body is inserted into the insertion hole whereby the cover body is locked in an insertion hole axial direction and the insertion hole circumferential direction to the support body, and that covers the support body.
2. The vehicular viewing device of claim 1, further comprising a raised portion that is provided at one of the support body or the cover body, and a recessed portion that is provided at another of the support body or the cover body and into which the raised portion is inserted whereby the cover body is locked in the insertion hole axial direction and the insertion hole circumferential direction to the support body.
3. The vehicular viewing device of claim 2, wherein the raised portion is inserted into the recessed portion whereby the cover body is locked in an insertion hole radial direction to the support body.
4. The vehicular viewing device of claim 1, further comprising a locking surface that is provided at a peripheral surface of the insertion hole and that is abutted against the support body whereby the cover body is locked in an insertion hole radial direction to the support body.
5. The vehicular viewing device of claim 1, wherein a peripheral wall of the cover body is abutted against the support body whereby the cover body is locked in an insertion hole radial direction to the support body.
6. The vehicular viewing device of claim 1, further comprising an engagement portion that is provided at the cover body and that is engaged with the support body whereby rotation of the cover body in a direction in which the locking of the cover body in the insertion hole axial direction and the insertion hole circumferential direction to the support body is canceled, is locked.
7. The vehicular viewing device of claim 6, wherein the engagement portion extends on an insertion hole circumferential direction side.
8. The vehicular viewing device of claim 6, wherein the engagement portion is elastic.
9. The vehicular viewing device of claim 1, wherein the support body supports the cover body in the insertion hole axial direction and guides the rotation of the cover body in the insertion hole

circumferential direction.

10. A method of assembling a vehicular viewing device including a viewing mechanism that assists viewing by an occupant, a support body that is attached to a vehicle body side and that supports the viewing mechanism, and a cover body that is provided with an insertion hole and that covers the support body, wherein the cover body is rotated in an insertion hole circumferential direction in a state in which the support body is inserted into the insertion hole whereby the cover body is locked in an insertion hole axial direction and the insertion hole circumferential direction to the support body.
