

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250269807

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

INOUE; Shigeyuki et al.

VEHICLE LOWER STRUCTURE

Abstract

A vehicle lower structure includes a floor carpet, an intermediate member disposed below the floor carpet, a power storage device disposed below the intermediate member, and a seat disposed above the floor carpet, wherein the intermediate member includes a first member underlying the seat in an up/down direction, and a second member having an underlying portion underlying the seat in the up/down direction and a non-underlying portion not underlying the seat in the up/down direction, and flame retardancy of the first member is higher than flame retardancy of the second member.

Inventors: INOUE; Shigeyuki (Toyota-shi, JP), KAWAMOTO; Naoya (Nisshin-shi, JP), SAKURABA; Takahito (Seto-shi, JP), KAKISHITA; Kenichi (Nagoya-shi, JP), TAKASE; Kohei (Susono-shi, JP), MIYAMURA; Kai (Toyota-shi, Aichi-ken, JP), KUMAZAWA; Kazuya (Nagoya-shi, Aichi-ken, JP)

Applicant: TOYOTA JIDOSHA KABUSHIKI KAISHA (Aichi-ken, JP)

Family ID: 1000008494569

Appl. No.: 19/064693

Filed: February 27, 2025

Foreign Application Priority Data

JP	2024-028875	Feb. 28, 2024
----	-------------	---------------

Publication Classification

Int. Cl.: B60R13/08 (20060101); B60H1/24 (20060101); B60L50/60 (20190101); B60N3/04 (20060101); B62D21/03 (20060101); B62D25/20 (20060101)

U.S. Cl.:

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This nonprovisional application is based on Japanese Patent Application No. 2024-028875 filed on Feb. 28, 2024, with the Japan Patent Office, the entire contents of which are hereby incorporated by reference.

BACKGROUND

Field

[0002] The present disclosure relates to a vehicle lower structure.

Description of the Background Art

[0003] As disclosed in Japanese Patent Laying-Open No. **2023-139898**, a vehicle lower structure including a power storage device is known.

SUMMARY

[0004] Although it is preferable for a vehicle lower structure including a power storage device to have a higher flame retardancy, a member having flame retardancy is often not inexpensive. An object of the present disclosure is to provide a vehicle lower structure that can achieve flame retardancy at a lower cost.

[0005] A vehicle lower structure in the present disclosure includes a floor carpet forming a portion of a vehicle compartment, an intermediate member disposed below the floor carpet, a power storage device disposed below the intermediate member, and a sea disposed above the floor carpet, wherein the intermediate member includes a first member underlying the seat in an up/down direction, and a second member having an underlying portion underlying the seat in the up/down direction and a non-underlying portion not underlying the seat in the up/down direction, and flame retardancy of the first member is higher than flame retardancy of the second member.

[0006] According to the above configuration, by ensuring a high flame retardancy at the portion underlying the seat in the up/down direction, and reducing the used amount of an expensive resin having flame retardancy at the portion not underlying the seat in the up/down direction, it is possible to provide a vehicle lower structure that can achieve flame retardancy at a lower cost.

[0007] In the above disclosure, the vehicle lower structure may include a lower frame including a pair of side members, a front member connecting front portions of the pair of side members, a rear member connecting rear portions of the pair of side members, and a cross member connecting intermediate portions of the pair of side members in a vehicle front/rear direction, wherein the intermediate member may be disposed to fill a space formed by a plurality of members among the pair of side members, the front member, the cross member, and the rear member, inside the plurality of members.

[0008] According to the above configuration, the intermediate member can be disposed without any gap in the space formed by the plurality of members among the pair of side members, the front member, the cross member, and the rear member, inside the plurality of members.

[0009] In the above disclosure, heat conductivity of the second member may be lower than heat conductivity of the first member.

[0010] According to the above configuration, for the second member having the non-underlying portion not underlying the seat in the up/down direction, of the intermediate member, heat from the power storage device is likely to be transferred to an occupant sitting in the seat. Therefore, by lowering heat conductivity of this portion, the heat from the power storage device can be suppressed from being transferred to the feet of the occupant sitting in the seat.

[0011] The vehicle lower structure in the above disclosure may further include a metal sheet disposed between the floor carpet and each of the first member and the second member.

[0012] According to the above configuration, heat generated in the power storage device and directed upward, for example, can be dispersed in a horizontal direction at a height position of the metal sheet.

[0013] In the above disclosure, the metal sheet may be disposed to contact the cross member.

[0014] According to the above configuration, the heat generated in the power storage device and directed upward, for example, can be dispersed in the horizontal direction at the height position of the metal sheet and transferred to the cross member.

[0015] In the above disclosure, the metal sheet may be disposed to entirely cover the first member, the second member, and the cross member from above.

[0016] According to the above configuration, it is possible to prevent air or the like from flowing from above the metal sheet toward the intermediate member below the metal sheet, and to obtain a higher flame retardant effect below the metal sheet.

[0017] The vehicle lower structure in the above disclosure may further include an expansion member disposed between the cross member and the power storage device and expanding at least in the up/down direction by being heated.

[0018] According to the above configuration, the expansion member expands by heating, and can increase the distance between the intermediate member and the power storage device by expanding and increasing its volume.

[0019] The vehicle lower structure in the above disclosure may include a duct through which an airflow generated by an air conditioning system for adjusting temperature in the vehicle compartment flows, wherein the duct may have an outlet, and the outlet may be provided to provide the airflow at a position between the first member or the second member and the power storage device.

[0020] According to the above configuration, the intermediate member can be cooled by the airflow from the air conditioning system, and the heat from the power storage device can be suppressed from being transferred to the occupant.

[0021] The foregoing and other objects, features, aspects and advantages of the present disclosure will become more apparent from the following detailed description of the present disclosure when taken in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] FIG. 1 is a side view showing a vehicle 1 including a vehicle lower structure 10 in a first embodiment.

[0023] FIG. 2 is a plan view showing a vehicle compartment 13 of vehicle 1 in the first embodiment.

[0024] FIG. 3 is a cross sectional view of vehicle lower structure 10 in the first embodiment as viewed from a front side of vehicle 1, which corresponds to a cross sectional view taken along a line III-III in FIG. 4 and viewed in a direction indicated by arrows.

[0025] FIG. 4 is a cross sectional view of vehicle lower structure 10 in the first embodiment as viewed from a left side of vehicle 1, which corresponds to a cross sectional view taken along a line IV-IV in FIG. 3 and viewed in a direction indicated by arrows.

[0026] FIG. 5 is an enlarged view of a portion in FIG. 4.

[0027] FIG. 6 is an exploded cross sectional view of vehicle lower structure 10 in the first embodiment, which corresponds to FIG. 4.

[0028] FIG. 7 is an exploded perspective view of vehicle lower structure 10 in the first

embodiment.

[0029] FIG. **8** is a cross sectional view showing a vehicle lower structure **10A** in a second embodiment, which corresponds to FIG. **5** in the first embodiment.

[0030] FIG. **9** is a cross sectional view showing a vehicle lower structure **10B** in a third embodiment, which corresponds to FIG. **5** in the first embodiment.

[0031] FIG. **10** is a cross sectional view showing a vehicle lower structure **10C** in a fourth embodiment, which corresponds to FIG. **5** in the first embodiment.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0032] Hereinafter, embodiments of the present disclosure will be described. When the number, amount, or the like is mentioned in the embodiments described below, the scope of the present disclosure is not necessarily limited to that number, amount, or the like unless otherwise specified. Each component is not necessarily essential to the present disclosure unless otherwise specified. The same parts and corresponding parts will be designated by the same reference numerals, and the same description may not be repeated.

[0033] Arrows F, B, U, D, L, and R in the drawings used in the following description indicate directions with respect to a vehicle, and arrow F indicates a “forward direction”, arrow B indicates a “backward direction”, arrow U indicates an “upward direction”, arrow D indicates a “downward direction”, arrow L indicates a “left direction”, and arrow R indicates a “right direction”.

First Embodiment

(Vehicle **1**)

[0034] Referring to FIGS. **1** to **7**, a vehicle **1** including a vehicle lower structure **10** in a first embodiment will be described. FIG. **1** is a side view showing vehicle **1**, and FIG. **2** is a plan view showing a vehicle compartment **13** of vehicle **1**.

[0035] Vehicle **1** is, for example, an electrically powered vehicle such as an electric vehicle or a hybrid vehicle that can be driven by a motor. Vehicle **1** includes vehicle compartment **13**, seats **11** and **12** in which occupants can sit, and vehicle lower structure **10** (FIG. **1**).

(Vehicle Lower Structure **10**)

[0036] FIG. **3** is a cross sectional view of vehicle lower structure **10** as viewed from a front side of vehicle **1**, which corresponds to a cross sectional view taken along a line III-III in FIG. **4** and viewed in a direction indicated by arrows. FIG. **4** is a cross sectional view of vehicle lower structure **10** as viewed from a left side of vehicle **1**, which corresponds to a cross sectional view taken along a line IV-IV in FIG. **3** and viewed in a direction indicated by arrows. FIG. **5** is an enlarged view of a portion in FIG. **4**. FIG. **6** is an exploded cross sectional view of vehicle lower structure **10**, which corresponds to FIG. **4**. FIG. **7** is an exploded perspective view of vehicle lower structure **10**.

[0037] As shown in FIGS. **3** to **7** (in particular, FIGS. **6** and **7**), vehicle lower structure **10** includes a floor carpet **14**, an intermediate member **20**, a lower frame **15**, and a power storage device **40**.

(Lower Frame **15**)

[0038] Lower frame **15** supports power storage device **40**, for example. Here, lower frame **15** (FIG. **7**) includes a pair of side members **16L** and **16R**, a front member **16F**, a rear member **16B**, and cross members **17** and **18**. Front member **16F** extends in a vehicle width direction and connects front portions of the pair of side members **16L** and **16R**. Rear member **16B** extends in the vehicle width direction and connects rear portions of the pair of side members **16L** and **16R**. Each of cross members **17** and **18** also extends in the vehicle width direction and connects intermediate portions of the pair of side members **16L** and **16R** in a vehicle front/rear direction.

[0039] Spaces (spaces SP1, SP2, and SP3) are each formed by a plurality of members among the pair of side members **16L** and **16R**, front member **16F**, cross members **17** and **18**, and rear member **16B**, inside the plurality of members. In the present embodiment, the pair of side members **16L** and **16R**, front member **16F**, and cross member **17** are disposed in a rectangular frame shape, and space SP1 (FIGS. **6** and **7**) is formed inside these members. Similarly, the pair of side members **16L** and

16R and cross members **17** and **18** are disposed in a rectangular frame shape, and space **SP2** is formed inside these members.

[0040] The pair of side members **16L** and **16R**, cross member **18**, and rear member **16B** are disposed in a rectangular frame shape, and space **SP3** is formed inside these members. Vehicle lower structure **10** is not provided with a member generally called a floor panel or the like, which is constituted by a metal steel plate or the like. Vehicle lower structure **10** penetrates through spaces **SP1**, **SP2**, and **SP3** in an up/down direction at portions where spaces **SP1**, **SP2**, and **SP3** are provided.

(Intermediate Member **20**)

[0041] Intermediate member **20** is disposed below floor carpet **14**. Here, intermediate member **20** is disposed to fill at least one of spaces **SP1**, **SP2**, and **SP3** described above. Intermediate member **20** includes first members **21A** and **21B** and second members **22A** and **22B**. First members **21A** and **21B** and second members **22A** and **22B** are constituted by members including a foamed resin, for example, and each have a block-like shape. First members **21A** and **21B** and second members **22A** and **22B** can be constituted by members that are lighter than metal and softer than metal.

[0042] First member **21A** and second member **22A** are disposed to be adjacent to each other in a horizontal direction, for example. First member **21A** and second member **22A** integrated with each other have substantially the same size and shape as those of space **SP1**. First member **21A** and second member **22A** are disposed to fill space **SP1** (FIGS. **6** and **7**).

[0043] Second member **22B** has substantially the same size and shape as those of space **SP2**, and second member **22B** is disposed to fill space **SP2**. First member **21B** has substantially the same size and shape as those of space **SP3**, and first member **21B** is disposed to fill space **SP3**.

[0044] Referring to FIG. **5**, as will be described in detail later, first member **21A** is disposed to underlie seat **11** in the up/down direction. On the other hand, second member **22A** includes an underlying portion **24** underlying seat **11** in the up/down direction and a non-underlying portion **23** not underlying seat **11** in the up/down direction.

(Floor Carpet **14** and Seats **11**, **12**)

[0045] Floor carpet **14** is a member forming a portion of vehicle compartment **13** above floor carpet **14**. Seats **11** and **12** are disposed above floor carpet **14**. As shown in FIGS. **1** and **2**, a pair of seats **11** are disposed to be arranged in a right/left direction at positions above floor carpet **14** inside vehicle compartment **13**, and seat **12** is disposed behind the seats.

[0046] As shown in FIG. **6**, floor carpet **14** is disposed above intermediate member **20** (first members **21A** and **21B** and second members **22A** and **22B**). Floor carpet **14** may be disposed to directly contact upper surfaces of first members **21A** and **21B** and second members **22A** and **22B**. Between floor carpet **14** and each of first members **21A** and **21B** and second members **22A** and **22B**, a fixture for preventing movement of floor carpet **14**, a structure for preventing slippage (a hook-and-loop fastener), or the like may be provided as appropriate. Although floor carpet **14** is constituted by one member in vehicle **1** in the present embodiment, floor carpet **14** may be constituted by a plurality of members.

(Power Storage Device **40**)

[0047] As shown in FIGS. **3** to **6**, power storage device **40** is disposed below intermediate member **20** (first members **21A** and **21B** and second members **22A** and **22B**). Power storage device **40** (FIG. **3**) includes a power storage module **41** and a case **42**. Power storage module **41** includes a plurality of power storage cells **41C** accommodated by case **42** and arranged in the horizontal direction. Power storage cell **41C** is configured to include a battery that stores electric power to be supplied to the motor. The plurality of power storage cells **41C** may be stacked in the vehicle width direction, or may be stacked in the vehicle front/rear direction.

[0048] Case **42** (FIG. **3**) has a top plate **43**, an adhesive **44**, side walls **45**, inner walls **46**, a support member **47**, and a bottom plate **48**. Top plate **43**, a pair of side walls **45**, and bottom plate **48** are made of FRP, for example, these members constitute an outer structure of case **42**, and adhesive **44**,

inner walls **46** and support member **47**, and power storage module **41** are disposed in this structure. [0049] Power storage module **41** (each of the plurality of power storage cells **41C**) is bonded to top plate **43** with adhesive **44**. Inner walls **46** are disposed on both outer sides of power storage module **41** (the plurality of power storage cells **41C**) in a stacking direction. Support member **47** has a plate-like shape, and is disposed between power storage module **41** and bottom plate **48**. Each inner wall **46** is integrated with top plate **43** by a fixture **61**, and is integrated with bottom plate **48** by a fixture **62**.

[0050] Power storage device **40** configured as described above is fastened to, for example, side members **16L** and **16R** of lower frame **15**, by a plurality of fasteners **63** (FIG. 3). Thereby, power storage device **40** is supported by lower frame **15**. Seals **51** and **52** (FIGS. 4 and 6) may be disposed between power storage device **40** (top plate **43**) and lower frame **15** (front member **16F**, side member **16R**).

[0051] As shown in FIG. 6, power storage device **40** is disposed below intermediate member **20** (first members **21A** and **21B** and second members **22A** and **22B**). Power storage device **40** (top plate **43**) may be disposed to directly contact lower surfaces of first members **21A** and **21B** and second members **22A** and **22B** (see also FIG. 3).

(Intermediate Member **20** and Flame Retardancy)

[0052] As described above, intermediate member **20** includes first members **21A** and **21B** and second members **22A** and **22B**. First members **21A** and **21B** are disposed to underlie seats **11** and **12** in the up/down direction. On the other hand, second members **22A** and **22B** have underlying portions underlying seats **11** and **12** in the up/down direction (underlying portion **24** underlying seat **11** in the case of second member **22A**) and non-underlying portions not underlying seats **11** and **12** in the up/down direction (non-underlying portion **23** not underlying seat **11** in the case of second member **22A**).

[0053] As shown in FIG. 5, for example, a reference line **11M** passing through a front end portion **11T** of seat **11** (here, a seat cushion) and extending downward in a vertical direction is defined, and a reference line **11N** passing through a rear end portion **11V** of seat **11** (here, the seat cushion) and extending downward in the vertical direction is defined. In the present embodiment, first member **21A** is located between reference line **11M** and reference line **11N** in the vehicle front/rear direction (see also FIG. 2). Entire first member **21A** is configured to underlie seat **11**.

[0054] As shown in FIG. 5, for example, reference line **11M** passing through front end portion **11T** of seat **11** and extending downward in the vertical direction is defined. In the present embodiment, non-underlying portion **23** of second member **22A** is disposed on a front side relative to reference line **11M**, and underlying portion **24** of second member **22A** is disposed on a rear side relative to reference line **11M**.

[0055] Second member **22B** (see FIG. 4) is configured such that a portion of second member **22B** close to its rear end portion underlies seat **12** in the up/down direction, and most of second member **22B** is disposed not to underlie seats **11** and **12** in the up/down direction.

[0056] Here, flame retardancy of first members **21A** and **21B** is configured to be higher than flame retardancy of second members **22A** and **22B**. For example, first members **21A** and **21B** are made of a resin material having flame retardancy higher than flame retardancy of the members constituting second members **22A** and **22B**.

[0057] The flame retardancy can be evaluated, for example, based on the UL (Underwriter's Laboratories) Standards (standards for UL Test No. 94) or the like. As a member for improving the flame retardancy, for example, a glass cloth, a carbon cloth made of carbon fibers, a fluorine fiber cloth made of fluorine fibers, a fluorine resin film, or the like can be utilized. For example, a member obtained by adding a halogen compound, antimony oxide, glass fibers, or the like to a resin material such as polybutylene terephthalate (PBT) serving as a base material may be used. (Functions and Effects)

[0058] As described above, in the present embodiment, floor carpet **14** is disposed above

intermediate member **20** (first members **21A** and **21B** and second members **22A** and **22B**), and power storage device **40** is disposed below intermediate member **20** (first members **21A** and **21B** and second members **22A** and **22B**). Vehicle lower structure **10** is not provided with a member generally called a floor panel or the like, which is constituted by a metal steel plate or the like. When power storage device **40** is provided directly below the floor panel, the floor panel can exhibit flame retardancy.

[0059] In vehicle lower structure **10**, first members **21A** and **21B** of intermediate member **20** underlie seats **11** and **12** in the up/down direction, and first members **21A** and **21B** of intermediate member **20** ensure a high flame retardancy. On the other hand, second members **22A** and **22B** of intermediate member **20** have the non-underlying portions not underlying seats **11** and **12** in the up/down direction, and the flame retardancy of second members **22A** and **22B** is lower than the flame retardancy of first members **21A** and **21B**.

[0060] By ensuring a high flame retardancy at the portions underlying seats **11** and **12** in the up/down direction, and reducing the used amount of an expensive resin having flame retardancy at the portions not underlying seats **11** and **12** in the up/down direction, it is possible to provide a vehicle lower structure that can achieve flame retardancy at a lower cost.

Modification of the First Embodiment

[0061] As a modification of the first embodiment described above, heat conductivity of second members **22A** and **22B** may be configured to be lower than heat conductivity of first members **21A** and **21B**.

[0062] When a heat transfer path is considered for the portions of intermediate member **20** underlying seats **11** and **12** in the up/down direction (first members **21A** and **21B**), heat from power storage device **40** is transferred to the occupants sitting in seats **11** and **12** via intermediate member **20**, floor carpet **14**, and seats **11** and **12**.

[0063] On the other hand, for the portions of intermediate member **20** not underlying seats **11** and **12** in the up/down direction (second members **22A** and **22B**), the heat from power storage device **40** is transferred to the feet of the occupants sitting in seats **11** and **12** without passing through seats **11** and **12**.

[0064] That is, for the portions of intermediate member **20** not underlying seats **11** and **12** in the up/down direction (the non-underlying portions of second members **22A** and **22B**), the heat from power storage device **40** is likely to be transferred to the occupants sitting in seats **11** and **12**. Therefore, by lowering heat conductivity of these portions (for example, the non-underlying portions of second members **22A** and **22B**), the heat from power storage device **40** can be suppressed from being transferred to the feet of the occupants sitting in seats **11** and **12**.

Second Embodiment

[0065] FIG. **8** is a cross sectional view showing a vehicle lower structure **10A** in a second embodiment, which corresponds to FIG. **5** in the first embodiment. Vehicle lower structure **10A** further includes a metal sheet **30** disposed between floor carpet **14** and each of first members **21A** and **21B** and second members **22A** and **22B**.

[0066] In the present embodiment, metal sheet **30** is disposed to contact two first members **21A** and **21B** and two second members **22A** and **22B**. Metal sheet **30** is satisfactory when it is disposed to contact at least one first member and at least one second member. Metal sheet **30** can be formed of aluminum foil or the like, for example. According to such a configuration, heat generated in power storage device **40** and directed upward, for example, can be dispersed in the horizontal direction at a height position of metal sheet **30**.

[0067] Further, metal sheet **30** may be disposed to contact cross members **17** and **18**. According to such a configuration, the heat generated in power storage device **40** and directed upward, for example, can be dispersed in the horizontal direction at the height position of metal sheet **30** and transferred to cross members **17** and **18**.

[0068] Further, metal sheet **30** may be disposed to entirely cover first members **21A** and **21B**,

second members **22A** and **22B**, and cross members **17** and **18** from above. According to such a configuration, it is possible to prevent air or the like from flowing from above metal sheet **30** toward intermediate member **20** below metal sheet **30**, and to obtain a higher flame retardant effect below metal sheet **30**.

Third Embodiment

[0069] FIG. **9** is a cross sectional view showing a vehicle lower structure **10B** in a third embodiment, which corresponds to FIG. **5** in the first embodiment. As shown in FIG. **9**, vehicle lower structure **10B** further includes an expansion member **32** disposed between cross members **17**, **18** and power storage device **40** and expanding at least in the up/down direction by being heated.

[0070] Expansion member **32** expands by heating, and can increase the distance between intermediate member **20** and power storage device **40** by expanding and increasing its volume. Expansion member **32** may be constituted by a member including expanded graphite and a thermoplastic elastomer, for example. Expansion member **32** may also be constituted by a urethane-based resin or a silicone-based resin (such as a silicone sheet or a silicone rubber sheet). Expansion member **32** is not limited to having a sheet-like shape, and may be applied to a lower surface of intermediate member **20** or an upper surface of power storage device **40**.

Fourth Embodiment

[0071] FIG. **10** is a cross sectional view showing a vehicle lower structure **10C** in a fourth embodiment, which corresponds to FIG. **5** in the first embodiment. As shown in FIG. **10**, a vehicle in the fourth embodiment includes ducts **71**, **72**, and **73** through which airflows generated by an air conditioning system for adjusting temperature in the vehicle compartment flow. Ducts **71**, **72**, and **73** have outlets **71H**, **72H**, and **73H**, respectively, and outlets **71H**, **72H**, and **73H** are provided to provide the airflows at positions between first members **21A**, **21B** or second members **22A**, **22B** and power storage device **40**.

[0072] According to the above configuration, intermediate member **20** can be cooled by the airflows from the air conditioning system, and the heat from power storage device **40** can be suppressed from being transferred to the occupants.

[0073] Although the embodiments of the present disclosure have been described, it should be understood that the embodiments disclosed herein are illustrative and non-restrictive in every respect. The scope of the present disclosure is defined by the scope of the claims, and is intended to include any modifications within the scope and meaning equivalent to the scope of the claims.

Claims

1. A vehicle lower structure comprising: a floor carpet forming a portion of a vehicle compartment; an intermediate member disposed below the floor carpet; a power storage device disposed below the intermediate member; and a seat disposed above the floor carpet, wherein the intermediate member includes a first member underlying the seat in an up/down direction, and a second member having an underlying portion underlying the seat in the up/down direction and a non-underlying portion not underlying the seat in the up/down direction, and flame retardancy of the first member is higher than flame retardancy of the second member.
2. The vehicle lower structure according to claim 1, comprising a lower frame including a pair of side members, a front member connecting front portions of the pair of side members, a rear member connecting rear portions of the pair of side members, and a cross member connecting intermediate portions of the pair of side members in a vehicle front/rear direction, wherein the intermediate member is disposed to fill a space formed by a plurality of members among the pair of side members, the front member, the cross member, and the rear member, inside the plurality of members.
3. The vehicle lower structure according to claim 1, wherein heat conductivity of the second member is lower than heat conductivity of the first member.

4. The vehicle lower structure according to claim 2, further comprising a metal sheet disposed between the floor carpet and each of the first member and the second member.
 5. The vehicle lower structure according to claim 4, wherein the metal sheet is disposed to contact the cross member.
 6. The vehicle lower structure according to claim 4, wherein the metal sheet is disposed to entirely cover the first member, the second member, and the cross member from above.
 7. The vehicle lower structure according to claim 2, further comprising an expansion member disposed between the cross member and the power storage device and expanding at least in the up/down direction by being heated.
 8. The vehicle lower structure according to claim 1, comprising a duct through which an airflow generated by an air conditioning system for adjusting temperature in the vehicle compartment flows, wherein the duct has an outlet, and the outlet is provided to provide the airflow at a position between the first member or the second member and the power storage device.
-