

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250270455

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

DANNER; Travis et al.

HYDROCARBON PURIFICATION

Abstract

Embodiments of the present disclosure generally relate to methods and systems for purifying hydrocarbons, such as feedstock hydrocarbons containing one or more contaminants. In one or more embodiments, a method of purifying a hydrocarbon is provided and includes flowing a feedstock hydrocarbon stream through a heating unit, then combining the hydrocarbon stream and a primary solvent in a laminar flow reactor to produce a hydrocarbon-solvent stream, flowing the hydrocarbon-solvent stream through a cooling unit, and introducing the hydrocarbon-solvent stream into a separation unit to produce a scrubbed hydrocarbon stream and a solvent stream. The scrubbed hydrocarbon stream has a final contaminant concentration which is less than the initial contaminant concentration. The methods and systems for purifying hydrocarbons may be used to prepare a purified hydrocarbon product having the contaminant reduced by 10 times, about 40 times, about 100 times, or greater compared to the feedstock hydrocarbons.

Inventors: DANNER; Travis (Chattanooga, TN), MAUSS; Mark (Dubuque, IA)

Applicant: LUTROS, LLC (Chattanooga, TN)

Family ID: 1000008493758

Appl. No.: 19/060519

Filed: February 21, 2025

Related U.S. Application Data

us-provisional-application US 63660970 20240617

us-provisional-application US 63557009 20240223

Publication Classification

Int. Cl.: C10G49/24 (20060101); C10G49/22 (20060101); C10G49/26 (20060101)

U.S. Cl.:

CPC **C10G49/24** (20130101); **C10G49/22** (20130101); **C10G49/26** (20130101);
C10G2300/202 (20130101); C10G2300/4012 (20130101); C10G2300/44 (20130101);
C10G2300/807 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application claims benefit to U.S. Prov. Appl. No. 63/557,009, filed on Feb. 23, 2024, and claims benefit to U.S. Prov. Appl. No. 63/660,970, filed on Jun. 17, 2024, which are both herein incorporated by reference in their entirety.

BACKGROUND

Field

[0002] Embodiments of the present disclosure generally relate to methods and systems for processing hydrocarbons, and more specifically, methods and systems for purifying hydrocarbons including oils, fats, and/or greases.

Description of the Related Art

[0003] Purification of hydrocarbons, e.g., fats, oils, and/or greases occurs for a variety of industries, e.g., food, cosmetics, waxes, biofuels, and other oleochemical products. Typically, hydrocarbons are purified using one or more steps to solubilize contaminants in an aqueous stream through the use of water washing and separation techniques, such as centrifuging. Remaining contaminants are then further adsorbed and/or filtered out by using adsorbent filtrations, such as “bleaching clays”—such as silica, diatomaceous earth, and/or carbon black. Unfortunately, each of these processes is costly, where each subsequent process increases the capital and operating expenses along with waste disposal and important product loss. Attempts to reduce waste disposal and product loss have implemented high shear mixing, cavitation, filtration powers, chelating agents, and enzymes. While these efforts have increased efficiency and yield, the capital and operating expenses remained the same.

[0004] Therefore, there is a need for improved methods and systems for purifying hydrocarbons, especially methods for purifying oils, fats, and/or greases from vegetable and/or animal sources.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] So that the manner in which the recited features of the present disclosure may be understood in detail, a more particular description of the disclosure, briefly summarized, may be had by reference to embodiments, some of which are illustrated in the appended drawings. It is to be noted, however, that the appended drawings illustrate only exemplary embodiments and are therefore not to be considered limiting of its scope, may admit to other equally effective embodiments.

[0006] FIG. 1 is a flowchart depicting a method for purifying a feedstock hydrocarbon, according to one or more embodiments described and discussed herein.

[0007] FIG. 2 depicts a system for purifying a feedstock hydrocarbon, according to one or more embodiments described and discussed herein.

[0008] FIG. 3 depicts another system for purifying a feedstock hydrocarbon, according to one or more embodiments described and discussed herein.

[0009] FIG. 4 depicts a system containing a liquid-filled laminar flow reactor, the system is

configured to purify a feedstock hydrocarbon, according to one or more embodiments described and discussed herein.

[0010] FIG. 5 depicts a system containing a vapor-infused laminar flow reactor, the system is configured to purify a feedstock hydrocarbon, according to one or more embodiments described and discussed herein.

[0011] FIG. 6 depicts a system for purifying a feedstock hydrocarbon and recycling process water, according to one or more embodiments described and discussed herein.

[0012] FIG. 7 depicts a system for purifying and recycling process water, according to one or more embodiments described and discussed herein.

[0013] To facilitate understanding, identical reference numerals have been used, where possible, to designate identical elements that are common to the Figures. It is contemplated that elements and features of one or more embodiments may be beneficially incorporated in other embodiments.

SUMMARY

[0014] Embodiments of the present disclosure generally relate to methods and systems for purifying hydrocarbons, such as feedstock hydrocarbons containing one or more contaminants. In some examples, the feedstock hydrocarbons may be or include oils, fats, and/or greases derived from one or more vegetable and/or animal sources. The contaminant may be or include one or more inorganics. The methods and systems for purifying hydrocarbons may be used to prepare a purified hydrocarbon product having the contaminant reduced by 10 times, about 40 times, about 100 times, or greater compared to the feedstock hydrocarbons. In some examples, the contaminant is not detectable in the purified hydrocarbon product.

[0015] In one or more embodiments, a method of purifying a hydrocarbon is provided and includes flowing a feedstock hydrocarbon stream through a heating unit to produce a heated hydrocarbon stream, where the feedstock hydrocarbon stream has an initial concentration of a contaminant and contains one or more of an oil, a fat, a grease, or any combination thereof. The method also includes combining the heated hydrocarbon stream and a primary solvent in a laminar flow reactor to further heat and produce a hydrocarbon-solvent stream, flowing the hydrocarbon-solvent stream through a cooling unit to produce a cooled hydrocarbon-solvent stream, and introducing the cooled hydrocarbon-solvent stream into a separation unit to produce a scrubbed hydrocarbon stream and a solvent stream. The scrubbed hydrocarbon stream has a final concentration of the contaminant, and the final concentration of the contaminant is less than the initial concentration of the contaminant.

[0016] In other embodiments, a method of purifying a hydrocarbon is provided and includes flowing a feedstock hydrocarbon stream through a heating unit to produce a heated hydrocarbon stream, where the feedstock hydrocarbon stream has an initial concentration of a contaminant and contains one or more of an oil, a fat, a grease, or any combination thereof, and then combining the heated hydrocarbon stream and a primary solvent in a laminar flow reactor to further heat and produce a hydrocarbon-solvent stream. The hydrocarbon-solvent stream may be produced by introducing a flow of the heated hydrocarbon stream into a headspace in an upper portion of the laminar flow reactor. The flow of the heated hydrocarbon stream is completely or substantially free of turbulence, and the heated hydrocarbon stream is at a first temperature. The hydrocarbon-solvent stream may further be produced by introducing a flow of the primary solvent into the headspace in the upper portion of the laminar flow reactor, the flow of the primary solvent is completely or substantially free of turbulence, and the primary solvent is at a second temperature greater than the first temperature. The hydrocarbon-solvent stream may be produced by condensing the primary solvent into the heated hydrocarbon stream to produce an intermediate stream, and flowing the intermediate stream through a reaction zone disposed in a lower portion of the laminar flow reactor to produce the hydrocarbon-solvent stream. The method further includes introducing the hydrocarbon-solvent stream into a separation unit to produce a scrubbed hydrocarbon stream and a solvent stream, where the solvent stream contains the contaminant, and flowing the scrubbed hydrocarbon stream through a first finishing unit to produce a purified hydrocarbon stream. The

purified hydrocarbon stream has a final concentration of the contaminant, and the final concentration of the contaminant is less than the initial concentration of the contaminant.

[0017] In some embodiments, a method of purifying a hydrocarbon is provided and includes flowing a feedstock hydrocarbon stream through a deaerator to degas the feedstock hydrocarbon stream, where the feedstock hydrocarbon stream has an initial concentration of a contaminant and contains soybean oil, corn oil, canola oil, camelina oil, yellow grease, choice white grease, beef tallow, poultry fat, used cooking oil, tall oil, pyrolysis oil, or any combination thereof. The method also includes flowing the degassed feedstock hydrocarbon stream through a heating unit to produce a heated hydrocarbon stream, combining the heated hydrocarbon stream and steam in a laminar flow reactor to produce an aqueous hydrocarbon stream, and flowing the aqueous hydrocarbon stream through a cooling unit to produce a cooled aqueous hydrocarbon stream. The method further includes introducing the cooled aqueous hydrocarbon stream into a vertical extraction column to produce a scrubbed hydrocarbon stream and an aqueous stream by a countercurrent liquid-liquid extraction, where the aqueous stream contains the contaminant, and flowing the scrubbed hydrocarbon stream through a first finishing unit to produce a purified hydrocarbon stream. The purified hydrocarbon stream has a final concentration of the contaminant, and the initial concentration of the contaminant is about 40 times or greater than the final concentration of the contaminant.

[0018] In one or more embodiments, a system for purifying a hydrocarbon is provided and contains a deaerator fluidly coupled to and downstream of a feedstock hydrocarbon source, and a heating portion of a recuperator fluidly coupled to and downstream of the deaerator. The feedstock hydrocarbon source is configured to contain a feedstock hydrocarbon having an initial concentration of a contaminant and containing one or more of an oil, a fat, a grease, or any combination thereof. The system also contains an additive source fluidly coupled to and downstream of the deaerator. The additive source is configured to contain an additive containing a hydrolyzing agent, an acid, a base, a salt, a chelating agent, a polar solvent, a non-polar solvent, or any combination thereof. The system also contains a laminar flow reactor containing an upper portion opposite a lower portion, where the upper portion of the laminar flow reactor is fluidly coupled to and downstream of the heating portion of the recuperator. The system also contains a primary solvent source fluidly coupled to and upstream of the upper portion of the laminar flow reactor, a cooling portion of the recuperator fluidly coupled to and downstream of the lower portion of the laminar flow reactor, and a pressure reduction device fluidly coupled to and downstream of the cooling portion of the recuperator. The system further contains a separation unit fluidly coupled to and downstream of the pressure reduction device, where the separation unit contains a scrubbed hydrocarbon stream outlet and a solvent stream outlet. The system may also contain a first finishing unit fluidly coupled to and downstream of the scrubbed hydrocarbon stream outlet, wherein the first finishing unit contains a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof. The first finishing unit contains a purified hydrocarbon stream outlet configured to provide a purified hydrocarbon having a final concentration of the contaminant of at least 10 times, about 40 times, or about 100 times less than the initial concentration of the contaminant. The system may further contain a second finishing unit fluidly coupled to and downstream of the solvent stream outlet, wherein the second finishing unit contains a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof.

DETAILED DESCRIPTION

[0019] Embodiments of the present disclosure generally relate to methods and systems for purifying hydrocarbons, such as feedstock hydrocarbons containing one or more contaminants. In some examples, the feedstock hydrocarbons may be or include one or more oils, fats, greases, or any combination thereof. The feedstock hydrocarbons may be derived from one or more vegetable and/or animal sources. The contaminant may be or include one or more of a halide, phosphorous,

one or more phosphorus containing compounds, sulfur, one or more sulfur containing compounds, nitrogen, one or more nitrogen containing compounds, a gum or lecithin, an alkali metal, an alkali earth metal, a transition metal, a metalloid, a heavy metal, or any combination thereof. The methods and systems for purifying hydrocarbons may be used to prepare a purified hydrocarbon product having a contaminant reduced by 10 times, about 40 times, about 100 times, or greater compared to the feedstock hydrocarbons. In some examples, the contaminant is not detectable in the purified hydrocarbon product.

[0020] FIG. 1 is a flowchart depicting a process or method **100** for purifying a feedstock hydrocarbon, according to one or more embodiments described and discussed herein. The method **100** includes operations **105-170**, as further described and discussed below. The feedstock hydrocarbon stream has an initial contaminant concentration which is reduced and/or removed during operations performed or otherwise conducted throughout the method **100**. FIG. 2 depicts a hydrocarbon purification system **200** for processing or otherwise purifying a feedstock hydrocarbon, according to one or more embodiments described and discussed herein. In one or more embodiments, the method **100** may be performed or otherwise conducted with the hydrocarbon purification system **200**.

[0021] In some embodiments, the method **100** may include optionally combining one or more additives into a feedstock hydrocarbon stream (at operation **105**) and optionally flowing the feedstock hydrocarbon stream through a deaerator to degas the feedstock hydrocarbon stream (at operation **110**). The method **100** further includes optionally combining one or more additives into the feedstock hydrocarbon stream (at operation **115**), flowing the feedstock hydrocarbon stream through one or more heating units to heat the feedstock hydrocarbon stream (at operation **120**), and optionally combining one or more additives into the feedstock hydrocarbon stream (at operation **125**). The one or more additives may be added into feedstock hydrocarbon stream at any of operations **105**, **115**, and/or **125**. The method **100** further includes combining the feedstock hydrocarbon stream and a primary solvent (e.g., steam, water, and/or one or more organic solvents) in laminar flow reactor to produce a hydrocarbon-solvent stream (at operation **130**), and then flowing the hydrocarbon-solvent stream through one or more cooling units to cool the hydrocarbon-solvent stream (at operation **140**). The method **100** also includes optionally flowing the hydrocarbon-solvent stream through pressure reduction device to reduce the pressure of the hydrocarbon-solvent stream (at operation **145**). Thereafter, the method **100** further includes introducing the hydrocarbon-solvent stream into one or more separation units to produce a scrubbed hydrocarbon stream and a primary or first solvent stream (at operation **150**). The method **100** further includes flowing the scrubbed hydrocarbon stream through a first finishing unit to produce a purified hydrocarbon stream having final contaminant concentration of less than the initial contaminant concentration (at operation **160**) and flowing the primary or first solvent stream from the separation unit through a second finishing unit to produce a secondary hydrocarbon stream and a secondary solvent stream (at operation **170**).

[0022] In one or more embodiments, the hydrocarbon purification system **200** for purifying a hydrocarbon is provided and contains a feedstock hydrocarbon source **205**. The feedstock hydrocarbon source **205** may contain a feedstock hydrocarbon containing one or more of an oil, a fat, a grease, or any combination thereof, as well as other type of feedstock hydrocarbon discussed further below. The feedstock hydrocarbon has an initial concentration of a contaminant which is reduced and/or removed with method **100**.

[0023] The hydrocarbon purification system **200** contains a feedstock hydrocarbon source **205** that contains one or more feedstock hydrocarbons and provides the feedstock hydrocarbon stream. In one or more embodiments, the feedstock hydrocarbon may be or contain a non-polar fluid, e.g., petroleum-based feedstocks, such as petroleum crude oil, shale oil, petroleum refinery intermediate streams (such as vacuum tower bottoms (VTB)), pyrolysis oils, recycled plastics, coal liquids, used motor oil, and mixtures thereof. Alternatively, the feedstock hydrocarbon may be or contain a

renewable feedstock, such as plant oil. Suitable plant oils include oils of camelina, canola, Carinata, castor, coconut, Jatropha, palm, peanut, Pongamia, soy bean, tung, and/or corn (such as derived from distiller grains), soap stock, waste vegetable oil, yellow grease (from cooking oil), brown grease (from grease traps and wastewater treatment), highly acidic oils (also referred to as acidic oils), animal tallow, algal oil, microbial oil, terpenes and other pine-related byproducts from tall oils, pine oils, or other biosynthetic oils and/or pyrolysis oils (such as derived from pyrolysis, esterification, oligomerization, or polymerization) and mixtures thereof. In some embodiments, the feedstock hydrocarbon may be plant based, animal based, insect based, microbial based, or any combination thereof. In one or more embodiments, the feedstock hydrocarbon may be or contain a food oil which may include one or more plant oils, one or more plant based oils, one or more animal based oils, or any combination thereof. In some embodiments, the feedstock hydrocarbon may be or contain one food oils, purified and/or non-purified food oils, other oils, greases, fats, and/or other substances (e.g., vegetable oils, animal fats, fatty acids, fatty alcohols, and mineral oils), according to one or more embodiments described and discussed herein. In one or more embodiments, the feedstock hydrocarbon may be or contain soybean oil, coconut oil, palm oil, canola oil, corn oil, peanut oil, sunflower oil, cottonseed oil, olive oil, beef fat or lard, pork fat or lard, poultry fat, fish oil, tall oil, pyrolysis oil, or any combination thereof. In one or more examples, the feedstock hydrocarbon may be or contain soybean oil, corn oil, canola oil, camelina oil, yellow grease, choice white grease, beef tallow, poultry fat, used cooking oil, pyrolysis oil, or any combination thereof. In other examples, the feedstock hydrocarbon may be or contain one or more polymeric materials, one or more plastic materials, one or more oligomers, or any combination thereof. Exemplary polymeric materials and/or plastic materials may be or contain one or more of polyethylene terephthalate (PETE), high density polyethylene (HDPE), polyvinyl chloride (PVC), low density polyethylene (LDPE), polypropylene (PP), polystyrene (PS), derivatives thereof, or any combination thereof.

[0024] The feedstock hydrocarbon may contain one or more contaminants which are reduced and/or removed by the methods described and discussed herein. Exemplary contaminants contained in the feedstock hydrocarbon may be or contain one or more of a halide (e.g., Cl, F, Br, I), phosphorous, sulfur, nitrogen, a gum or lecithin, a transition metal, an alkali metal, a rare earth metal, other metals, a metalloid, a heavy metal, an inorganic, or any combination thereof. In some examples, the contaminant of total metals may be or contain sodium, potassium, magnesium, calcium, iron, or any combination thereof.

[0025] The hydrocarbon purification system **200** may contain a deaerator **210** fluidly coupled to and downstream of the feedstock hydrocarbon source **205**. The deaerator **210** may be used to remove or reduce gas dissolved in the feedstock hydrocarbon or other hydrocarbon stream. The feedstock hydrocarbon or other hydrocarbon stream is degassed upon flowing through the deaerator **210**. The feedstock hydrocarbon or other hydrocarbon stream may be degassed at any stage of the method **100**. In some examples, the feedstock hydrocarbon or other hydrocarbon stream may be degassed at operation **110** of the method **100**.

[0026] The hydrocarbon purification system **200** contains one or more heating units **220** fluidly coupled to and downstream of the deaerator **210**. The heating units **220** may include one or more primary heating units **220** and one or more supplemental heating units **220** fluidly coupled to and downstream of the deaerator **210** and/or fluidly coupled to and upstream of the laminar flow reactor **230**. Each of the heating units **220** may be or contain a heating portion of a recuperator, a steam heater, an electric heater, a fuel combustion heater, other heating sources, or any combination thereof. The feedstock hydrocarbon or other hydrocarbon stream may be heated at any stage of the method **100**. In some examples, the feedstock hydrocarbon or other hydrocarbon stream may be heated at operation **120** of the method **100**.

[0027] The hydrocarbon purification system **200** also contains an additive source **215** fluidly coupled to and downstream of the deaerator **210**. One or more additives may be added to the

feedstock hydrocarbon or other hydrocarbon stream at any portion of the method **100**. In some examples, the additives may be added to the feedstock hydrocarbon or other hydrocarbon stream at operation **105**, **115**, and/or **125** during the method **100**. The additive source **215** is configured to contain one or more additives. Exemplary additives may be or contain one or more hydrolyzing agents, one or more acids, one or more bases, one or more salts, one or more chelating agents, one or more polar solvents, one or more non-polar solvents, or any combination thereof. In one or more examples, the additive may be or contain one or more hydrolyzing agents. The hydrolyzing agent may be or contain any chemical capable of hydrolyzing a hydrocarbon, e.g., fat, oil, or grease. For example, the hydrolyzing agent may be or contain acetic acid, ascorbic acid, citric acid, hydrochloric acid, fumaric acid, glucaric acid, gluconic acid, glutamic acid, hydrochloric acid, lactic acid, malic acid, oxalic acid, phosphoric acid, propionic acid, sulfuric acid, tartaric acid, salts thereof, or any combination thereof. As a further example, the hydrolyzing agent may be or contain nitrilotriacetic acid (NTA), ethylenediaminetetraacetic acid (EDTA), sodium hydroxide, potassium hydroxide, lithium hydroxide, ammonium hydroxide, or any combination thereof. Without being bound by theory the additive may react with a triglyceride to separate a fatty acid of the triglyceride from the glycerin backbone, allowing for the purification of the fatty acids in the triglyceride. Additionally, and without being bound by theory, the additive may hydrolyze phospholipids and other contaminants more readily than fatty acids, allowing for selective hydrolyzing of phospholipids at lower temperatures and with shorter residence times than those required for fatty acid splitting of triglycerides, reducing free fatty acid formation in the hydrocarbon purification system **200** including the laminar flow reactor **230**. Additionally, and without being bound by theory, the additive may increase a density and/or molecular weight of the aqueous phase, thereby promoting faster separation of the organic phase and the aqueous phase. In one or more embodiments, the feedstock hydrocarbon may include about 50 parts per million (ppm) to about 20,000 ppm of one or more additives, e.g., about 50 ppm to about 1,000 ppm, about 1,000 ppm to about 4,000 ppm, about 4,000 ppm to about 6,000 ppm, about 6,000 ppm to about 8,000 ppm, about 8,000 ppm to about 10,000 ppm, or about 10,000 ppm to about 20,000 ppm.

[0028] The hydrocarbon purification system **200** also contains a laminar flow reactor **230** containing an upper portion opposite a lower portion. The upper portion of the laminar flow reactor **230** is fluidly coupled to and downstream of the heating unit **220**. In one or more examples, the laminar flow reactor **230** may be or contain a liquid-filled laminar flow reactor and may contain an inflow distributor assembly, an outflow header assembly, a packing assembly, or any combination thereof. For example, the laminar flow reactor **230** may contain an inflow distributor assembly in the upper portion and an outflow header assembly in the lower portion. In other examples, the laminar flow reactor **230** may be or contain a vapor-infused laminar flow reactor and may contain an inflow distributor assembly, a packing assembly, or any combination thereof.

[0029] In one or more embodiments, each of a liquid phase within the laminar flow reactor **230** and/or an intermediate stream within the laminar flow reactor **230** and/or a hydrocarbon-solvent stream within the laminar flow reactor **230** may independently persist in laminar flow and a Reynolds number of 2,300 or less. In one or more embodiments, each of a liquid phase within the laminar flow reactor **230** and/or an intermediate stream within the laminar flow reactor **230** and/or a hydrocarbon-solvent stream within the laminar flow reactor **230** may independently have a Reynolds number of about 0, about 10, about 50, about 100, about 200, about 300, about 500, about 600, about 800, about 1,000, about 1,200, about 1,500, about 1,600, about 1,800, less than or about 2,000, less than or about 2,000, less than or about 2,100, less than or about 2,200, less than or about 2,250, less than or about 2,290, or 2,300. For example, each of a liquid phase within the laminar flow reactor **230** and/or an intermediate stream within the laminar flow reactor **230** and/or a hydrocarbon-solvent stream within the laminar flow reactor **230** may independently have a Reynolds number in a range from about 0 to 2,300, about 0 to about 2,290, about 0 to about 2,250, about 0 to about 2,200, about 0 to about 2,150, about 0 to about 2,100, about 0 to about 2,050,

about 0 to about 2,000, about 0 to less than 2,000, about 0 to about 1,800, about 0 to about 1,600, about 0 to about 1,500, about 0 to about 1,200, about 0 to about 1,000, about 0 to about 800, about 0 to about 600, about 0 to about 500, about 0 to about 200, about 0 to about 100, about 500 to 2,300, about 500 to about 2,290, about 500 to about 2,250, about 500 to about 2,200, about 500 to about 2,150, about 500 to about 2,100, about 500 to about 2,050, about 500 to about 2,000, about 500 to less than 2,000, about 500 to about 1,800, about 500 to about 1,600, about 500 to about 1,500, about 500 to about 1,200, about 500 to about 1,000, about 500 to about 800, about 500 to about 600, about 1,000 to 2,300, about 1,000 to about 2,290, about 1,000 to about 2,250, about 1,000 to about 2,200, about 1,000 to about 2,150, about 1,000 to about 2,100, about 1,000 to about 2,050, about 1,000 to about 2,000, about 1,000 to less than 2,000, about 1,000 to about 1,800, about 1,000 to about 1,600, about 1,000 to about 1,500, or about 1,000 to about 1,200. Not to be bound by theory, it is believed that a liquid with a Reynolds number of greater 2,300 has a turbulent flow instead of a laminar flow.

[0030] The hydrocarbon purification system **200** also contains one, two, or more primary solvent source **225a**, **225b** fluidly coupled to and upstream of the upper portion of the laminar flow reactor **230**. In one or more examples, each of the primary solvent source **225a**, **225b** may independently be or contain a water and/or steam source configured to store and/or disperse water and/or steam. In other examples, each of the primary solvent source **225a**, **225b** may independently be or contain a solvent source and be configured to store and/or disperse one or more vapor solvents and/or liquid solvents. The solvent may be or contain one or more of a polar protic solvent, a polar aprotic solvent, a nonpolar hydrocarbon solvent, a nonpolar ether solvent, a nonpolar chlorocarbon solvent, or any combination thereof. For example, the solvent may be or include one or more alcohols, one or more ketones, one or more aromatics, one or more alky sulfoxides, one or more furans, or any combination thereof. Exemplary solvents may be water, methanol, ethanol, propanol, butanol, glycerol, acetone, methyl ethyl ketone, benzene, toluene, xylene, dimethyl sulfoxide (DMSO), tetrahydrofuran, supercritical carbon dioxide, or any combination thereof. In one or more examples, the feedstock hydrocarbon stream and a primary solvent (e.g., water, steam, and/or one or more organic solvents) may be combined in laminar flow reactor to produce a hydrocarbon-solvent stream at operation **130** of the method **100**.

[0031] The hydrocarbon purification system **200** contains a cooling unit **235** fluidly coupled to and downstream of the lower portion of the laminar flow reactor **230**. The cooling unit **235** may be or contain a cooling portion of the recuperator, a coolant circulation system, a refrigeration system, or other cooling system. In one or more examples, the hydrocarbon-solvent stream may be introduced and flowed through one or more cooling units to cool the hydrocarbon-solvent stream at operation **140** of the method **100**.

[0032] The hydrocarbon purification system **200** may also contain one or more pressure reduction devices **240** fluidly coupled to and downstream of the cooling unit **235**. The pressure reduction device **240** may be or contain a low-shear pressure reduction device, a cyclonic pressure reduction device, a multi-stage pressure reduction device, or any combination thereof. In one or more examples, the pressure reduction device **240** is a cyclonic pressure reduction device, such as the Typhoon® Valve System, commercially available from the Mokveld Company. In one or more examples, the hydrocarbon-solvent stream or the cooled hydrocarbon-solvent stream may be introduced and flowed through one or more pressure reduction device to reduce the pressure of the hydrocarbon-solvent stream or the cooled hydrocarbon-solvent stream at operation **145** of the method **100**.

[0033] In one or more examples, the cooled hydrocarbon-solvent stream may be flowed through the pressure reduction device **240** such that the cooled hydrocarbon-solvent stream enters the pressure reduction device **240** at a first pressure and exits the pressure reduction device **240** at a second pressure less than the first pressure. For example, the cooled hydrocarbon-solvent stream may be at a first pressure entering the pressure reduction device **240** and at a second pressure when

exiting the pressure reduction device **240**. In some examples, the first pressure may be at least 10 times about 20 times, about 50 times, about 100 times, or greater than the second pressure. In other examples, the second pressure is at least one half of the value of the first pressure.

[0034] The first pressure may be in a range from about 500 pounds per square inch (psi), greater than 500 psi, about 550 psi, about 600 psi, or about 800 psi to about 1,000 psi, about 1,200 psi, about 1,500 psi, about 1,800 psi, about 2,000 psi, or greater. For example, the first pressure may be in a range from about 500 psi to about 2,000 psi, about 500 psi to about 1,800 psi, about 500 psi to about 1,500 psi, about 500 psi to about 1,200 psi, about 500 psi to about 1,000 psi, about 500 psi to about 800 psi, about 500 psi to about 600 psi, about 800 psi to about 2,000 psi, about 800 psi to about 1,800 psi, about 800 psi to about 1,500 psi, about 800 psi to about 1,200 psi, about 800 psi to about 1,000 psi, about 1,000 psi to about 2,000 psi, about 1,000 psi to about 1,800 psi, about 1,000 psi to about 1,500 psi, or about 1,000 psi to about 1,200 psi.

[0035] The second pressure may be in a range from about 1 psi, about 5 psi, about 10 psi, about 20 psi, about 50 psi, or about 100 psi to about 150 psi, about 200 psi, about 250 psi, about 300 psi, about 350 psi, about 400 psi, about 450 psi, less than 500 psi, about 500 psi. For example, the second pressure may be in a range from about 1 psi to less than or about 500 psi, about 1 psi to about 400 psi, about 1 psi to about 350 psi, about 1 psi to about 300 psi, about 1 psi to about 250 psi, about 1 psi to about 200 psi, about 1 psi to about 150 psi, about 1 psi to about 100 psi, about 1 psi to about 80 psi, about 1 psi to about 50 psi, about 1 psi to about 10 psi, about 50 psi to less than or about 500 psi, about 50 psi to about 400 psi, about 50 psi to about 350 psi, about 50 psi to about 300 psi, about 50 psi to about 250 psi, about 50 psi to about 200 psi, about 50 psi to about 150 psi, about 50 psi to about 100 psi, about 50 psi to about 80 psi, about 50 psi to about 60 psi, about 100 psi to less than or about 500 psi, about 100 psi to about 400 psi, about 100 psi to about 350 psi, about 100 psi to about 300 psi, about 100 psi to about 250 psi, about 100 psi to about 200 psi, about 100 psi to about 150 psi, or about 100 psi to about 120 psi.

[0036] In one or more examples, the first pressure may be in a range about 500 psi to about 1,500 psi, and the second pressure may be in a range from about 1 psi to about 500 psi. In other examples, the first pressure may be in a range greater than 500 psi to about 1,500 psi, and the second pressure may be in a range from about 1 psi to about 500 psi. In some examples, the first pressure may be in a range about 500 psi to about 1,500 psi, and the second pressure may be in a range from about 1 psi to less than 500 psi.

[0037] The hydrocarbon purification system **200** contains a separation unit **245** fluidly coupled to and downstream of the pressure reduction device **240**. The separation unit **245** may be or contain one or more extraction columns, one or more centrifuges, one or more cross-flow filtration units, one or more coalescers, one or more decanters, one or more electrostatic separators, one or more membrane purifiers, or any combination thereof. In one or more embodiments, the separation unit **245** may be any of the extraction columns and/or other units and systems described and discussed in U.S. Pub. No. 2024/0150660, which is herein incorporated by reference in its entirety.

[0038] In one or more examples, the separation unit **245** contains a vertical extraction column. One or more solvent or water sources **250** may be fluidly coupled to and upstream of the separation unit **245**. The solvent or water source **250** may supply and otherwise introduce one or more solvents or water into the separation unit **245**. The separation unit **245** contains a scrubbed hydrocarbon stream outlet and a solvent stream outlet. In one or more examples, a scrubbed hydrocarbon stream flowing from the scrubbed hydrocarbon stream outlet of the separation unit **245** contains a final concentration of the contaminant of at least 10 times, about 40 times, or about 100 times less than the initial concentration of the contaminant.

[0039] In one or more examples, the separation unit **245** is a vertical extraction column containing an upper portion opposite a lower portion, an upper inlet in the upper portion configured to receive a water or solvent stream, and a lower inlet in the lower portion coupled to and downstream of the pressure reduction device **240**. The lower inlet may be configured to receive a cooled hydrocarbon-

solvent stream. A central region of the vertical extraction column is disposed between the upper and lower portions and configured to perform a countercurrent liquid-liquid extraction by flowing the cooled hydrocarbon-solvent stream toward the upper portion of the vertical extraction column and flowing the solvent or water stream toward the lower portion of the vertical extraction column. The scrubbed hydrocarbon stream outlet may be disposed in the upper portion of the vertical extraction column and a solvent stream outlet may be disposed in the lower portion of the vertical extraction column. In some examples, the central region of the vertical extraction column contains one or more packing assemblies. In one or more examples, the hydrocarbon-solvent stream may be introduced and flowed into one or more separation units to produce a scrubbed hydrocarbon stream and a primary or first solvent stream at operation **150** of the method **100**.

[0040] In one or more embodiments, the solvent stream is an aqueous stream and is diverted or otherwise flowed from the separation unit **245** to a mixer (not shown). The solvent stream or aqueous stream is concentrated and/or dried and then blended with a product in the mixer. The product may be or contain one or more of a processed grain, vegetable meal, fruit meal, protein meal, meat, stover, hay, forage, or any combination thereof. The mixer may be or contain one or more of a tumbler mixer, paddle mixer, cone mixer, screw mixer, or any combination thereof.

[0041] The hydrocarbon purification system **200** may also contain one, two, or more finishing units, such as finishing units **255**, **270**. For example, the first finishing unit **255** may be fluidly coupled to and downstream of the scrubbed hydrocarbon stream outlet of the separation unit **245**. The first finishing unit **255** may be or contain a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof.

[0042] The first finishing unit **255** contains a purified hydrocarbon stream outlet configured to provide a purified hydrocarbon stream **265** having a final concentration of the contaminant of at least 10 times, about 40 times, or about 100 times less than the initial concentration of the contaminant. The first finishing unit **255** also contains a water-solvent waste stream **260**. In one or more examples, the scrubbed hydrocarbon stream may be flowed through a first finishing unit to produce a purified hydrocarbon stream having final contaminant concentration having a value less than the initial contaminant concentration at operation **160** of the method **100**.

[0043] In one or more embodiments, the initial concentration of the contaminant in the feedstock hydrocarbon is about 10 times, about 20 times, about 40 times, about 50 times, about 100 times, about 120 times, about 150 times, about 200 times, about 300 times, about 500 times, about 1,000 times, or greater than the final concentration of the contaminant of the purified or scrubbed hydrocarbon stream. In some examples, the initial contaminant concentration of the feedstock hydrocarbon is about 40 ppm, about 100 ppm, about 200 ppm, about 300 ppm, about 500 ppm, about 1,000 ppm, or greater, and the final concentration of the total metals is less than 20 ppm, less than 10 ppm, less than 5 ppm, less than 2 ppm, or less than 1 ppm in the purified or scrubbed hydrocarbon stream. In one or more embodiments, the initial concentration of the total metals is 40 ppm or greater, and the final concentration of the total metals in the feedstock hydrocarbon is less than 5 ppm, less than 2 ppm, or less than 1 ppm in the purified or scrubbed hydrocarbon stream. In other examples, the contaminant is phosphorus, the initial concentration of the phosphorous is 100 ppm or greater in the feedstock hydrocarbon, and the final concentration of the phosphorus is less than 5 ppm, such as less than 2 ppm, or less than 1 ppm in the purified or scrubbed hydrocarbon stream.

[0044] In one or more examples, the contaminant may be or include phosphorous, sulfur, nitrogen, total metals, or a combination thereof within the purified or scrubbed hydrocarbon stream. The final concentration of the contaminant may be less than 100 ppm, less than 50 ppm, less than 20 ppm, less than 10 ppm, less than 5 ppm, less than 1 ppm, or less than 0.1 ppm, or lower within the purified or scrubbed hydrocarbon stream. For example, the final concentration of the any of the contaminant may be non-detectable (ND) within the purified or scrubbed hydrocarbon stream. A non-detectable amount is based on the sensitivity of the instrument used to detect the concentration,

and in some examples, the instrument may have a sensitivity of about 0.1 ppm.

[0045] The second finishing unit **270** may be fluidly coupled to and downstream of the solvent stream outlet. The second finishing unit **270** contains a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof. The second finishing unit **270** contains a water-solvent waste stream **275** and a hydrocarbon stream **280**. The water-solvent waste stream **275** may be further processed in a water-solvent purification system. The hydrocarbon stream **280** may be recycled back into the hydrocarbon purification system **200**, such as being transferred to the feedstock hydrocarbon source **205**, the deaerator **210**, or components of the hydrocarbon purification system **200**. In one or more examples, the primary or first solvent stream may be flowed from the separation unit through a second finishing unit to produce a secondary hydrocarbon stream and a secondary solvent stream at operation **170** of the method **100**.

[0046] FIG. **3** depicts a hydrocarbon purification system **300** for purifying a feedstock hydrocarbon, according to one or more embodiments described and discussed herein. In one or more embodiments, the hydrocarbon purification system **300** for purifying a hydrocarbon is provided and contains a feedstock hydrocarbon source **310**. The feedstock hydrocarbon source **310** contains a feedstock hydrocarbon containing one or more of an oil, a fat, a grease, or any combination thereof, as well as other type of feedstock hydrocarbon discussed further below. The feedstock hydrocarbon has an initial concentration of a contaminant which is reduced and/or removed by the method **100** and/or with the processes and methods described and discussed herein.

[0047] In one or more embodiments, the feedstock hydrocarbon may be or contain a non-polar fluid, e.g., petroleum-based feedstocks, such as petroleum crude oil, shale oil, petroleum refinery intermediate streams (such as vacuum tower bottoms (VTB)), pyrolysis oils, recycled plastics, coal liquids, used motor oil, and mixtures thereof. Alternatively, the feedstock hydrocarbon may be or contain a renewable feedstock, such as plant oil. Suitable plant oils include oils of camelina, canola, Carinata, castor, coconut, Jatropha, palm, peanut, Pongamia, soy bean, tung, and/or corn (such as derived from distiller grains), soap stock, waste vegetable oil, yellow grease (from cooking oil), brown grease (from grease traps and wastewater treatment), highly acidic oils (also referred to as acidic oils), animal tallow, algal oil, microbial oil, terpenes and other pine-related byproducts from tall oils, pine oils, or other biosynthetic oils and/or pyrolysis oils (such as derived from pyrolysis, esterification, oligomerization, or polymerization) and mixtures thereof. In some embodiments, the feedstock hydrocarbon may be plant based, animal based, insect based, microbial based, or any combination thereof. In one or more embodiments, the feedstock hydrocarbon may be or contain a food oil which may include one or more plant oils, one or more plant based oils, one or more animal based oils, or any combination thereof. In some embodiments, the feedstock hydrocarbon may be or contain one food oils, purified and/or non-purified food oils, other oils, greases, fats, and/or other substances (e.g., vegetable oils, animal fats, fatty acids, fatty alcohols, and mineral oils), according to one or more embodiments described and discussed herein. In one or more embodiments, the feedstock hydrocarbon may be or contain soybean oil, coconut oil, palm oil, canola oil, corn oil, peanut oil, sunflower oil, cottonseed oil, olive oil, beef fat or lard, pork fat or lard, poultry fat, fish oil, tall oil, pyrolysis oil, or any combination thereof. In one or more examples, the feedstock hydrocarbon may be or contain soybean oil, corn oil, canola oil, camelina oil, yellow grease, choice white grease, beef tallow, poultry fat, used cooking oil, pyrolysis oil, or any combination thereof. In other examples, the feedstock hydrocarbon may be or contain one or more polymeric materials, one or more plastic materials, one or more oligomers, or any combination thereof. Exemplary polymeric materials and/or plastic materials may be or contain one or more of polyethylene terephthalate (PETE), high density polyethylene (HDPE), polyvinyl chloride (PVC), low density polyethylene (LDPE), polypropylene (PP), polystyrene (PS), derivatives thereof, or any combination thereof.

[0048] The feedstock hydrocarbon may contain one or more contaminants which are reduced

and/or removed by the methods described and discussed herein. Exemplary contaminants contained in the feedstock hydrocarbon may be or contain one or more of a halide (e.g., Cl, F, Br, I), phosphorous, sulfur, nitrogen, a gum or lecithin, a transition metal, an alkali metal, a rare earth metal, other metals, a metalloid, a heavy metal, an inorganic, or any combination thereof. In some examples, the contaminant of total metals may be or contain sodium, potassium, magnesium, calcium, iron, or any combination thereof.

[0049] The feedstock hydrocarbon is transferred by line **312** to a deaerator **314** fluidly coupled to and downstream of the feedstock hydrocarbon source **310**. The deaerator **314** may be used to degas the feedstock hydrocarbon. A pump **318** may be used to transfer or flow the feedstock hydrocarbon through the hydrocarbon purification system **300**. The feedstock hydrocarbon is transferred via line **316** to a connection point **326** where the feedstock hydrocarbon may be combined with one or more additives. The additive is delivered from an additive source **320** which is fluidly coupled to and upstream of the connection point **326** via line **322**. A pump **324** may be used to transfer or flow the additive via line **322**. The additive source **320** contains one or more additives may be or contain one or more hydrolyzing agents, one or more acids, one or more bases, one or more salts, one or more chelating agents, one or more polar solvents, one or more non-polar solvents, or any combination thereof.

[0050] The feedstock hydrocarbon containing the additive is transferred from the connection point **326** via line **328** to one or more heating units.

[0051] The hydrocarbon purification system **300** contains one or more heating units fluidly coupled to and downstream of the feedstock hydrocarbon source **310**, the additive source **320**, and/or the deaerator **314**. The heating units may include one or more primary heating units and one or more supplemental heating units fluidly coupled to and downstream of the deaerator **314** and/or fluidly coupled to and upstream of a laminar flow reactor **350**. A heating unit may be or contain a heating portion of a recuperator **330** which extends between inlet **332** and outlet **334**. The feedstock hydrocarbon containing the additive is transferred via line **328**, into inlet **332** and out of the outlet **334**, while flowing through and being heated in the heating portion of the recuperator **330**. The heated feedstock hydrocarbon may flow via line **340** through a secondary heater, such as a steam heater **342**. Each of the heating portion of a recuperator **330** and/or the steam heater **342** may be substituted with other types of heating units including an electric heater, a fuel combustion heater, other heating sources, or any combination thereof.

[0052] The heated feedstock hydrocarbon may be flowed via line **341** to the laminar flow reactor **350** containing an upper portion **352** opposite a lower portion **354**. The feedstock hydrocarbon may be introduced into the upper portion by line **341**. A primary solvent source **344** via line **346** may be fluidly coupled to line **341** and configured to introduce one or more solvents (e.g., water, steam, organic solvent, organic vapor) into the heated feedstock hydrocarbon in line **341** prior to entering into the laminar flow reactor **350**. In some examples, primary solvent source **344** via line **348** may be fluidly coupled to line **307** and configured to introduce one or more solvents (e.g., water, steam, organic solvent, organic vapor) into a recycled water or solvent in line **307** prior to entering into the laminar flow reactor **350**.

[0053] In one or more embodiments, the primary solvent (e.g., steam or vaporized solvent) from the primary solvent source **344** may be introduced into the laminar flow reactor **350** through one or more injection devices disposed at line **346** and/or line **348**. For example, each of line **346** and line **348** may independently be or contain one or more injection devices in fluid communication with the laminar flow reactor **350**. The injection device may be or contain one or more distributors, valves, nozzles, other injecting devices, or any combination thereof. The primary solvent may independently have a pressure drop across each of the injection device at line **346** and/or the injection device at line **348** in a range from about 0.0001 psi, about 0.005 psi, about 0.001 psi, about 0.05 psi, about 0.01 psi, about 0.5 psi, or about 0.1 psi to about 1 psi, about 5 psi, about 10 psi, about 20 psi, about 30 psi, about 40 psi, about 50 psi, about 60 psi, about 70 psi, about 80 psi,

or greater. For example, the primary solvent may independently have a pressure drop across the injection device at line **346** and/or the injection device at line **348** in a range from about 0.0001 psi to about 80 psi, about 0.0001 psi to about 60 psi, about 0.0001 psi to about 40 psi, about 0.0001 psi to about 20 psi, about 0.0001 psi to about 10 psi, about 0.0001 psi to about 5 psi, about 0.0001 psi to about 1 psi, about 0.0001 psi to about 0.1 psi, about 0.0001 psi to about 0.01 psi, about 0.0001 psi to about 0.001 psi, about 0.0001 psi to about 0.0005 psi, about 0.001 psi to about 80 psi, about 0.001 psi to about 60 psi, about 0.001 psi to about 40 psi, about 0.001 psi to about 20 psi, about 0.001 psi to about 10 psi, about 0.001 psi to about 5 psi, about 0.001 psi to about 1 psi, about 0.001 psi to about 0.1 psi, about 0.001 psi to about 0.01 psi, about 0.01 psi to about 80 psi, about 0.01 psi to about 60 psi, about 0.01 psi to about 40 psi, about 0.01 psi to about 20 psi, about 0.01 psi to about 10 psi, about 0.01 psi to about 5 psi, about 0.01 psi to about 1 psi, or about 0.01 psi to about 0.1 psi.

[0054] In one or more examples, the laminar flow reactor **350** may be or contain a liquid-filled laminar flow reactor and may contain an inflow distributor assembly, an outflow header assembly, a packing assembly, or any combination thereof. For example, the laminar flow reactor **350** may contain an inflow distributor assembly in the upper portion and an outflow header assembly in the lower portion. In other examples, the laminar flow reactor **350** may be or contain a vapor-infused laminar flow reactor and may contain an inflow distributor assembly, a packing assembly, or any combination thereof.

[0055] A primary solvent source **356** via line **358** may be fluidly coupled to the laminar flow reactor **350** and configured to introduce one or more solvents (e.g., water, steam, organic solvent, organic vapor) into the feedstock hydrocarbon in the laminar flow reactor **350** to produce a hydrocarbon-solvent stream. In some examples, the primary solvent source **356** via line **358** may be fluidly coupled to the laminar flow reactor **350** at or by a middle portion disposed between the upper portion **352** and the lower portion **354**, as depicted in FIG. 3. In other examples, the primary solvent source **356** via line **358** may be fluidly coupled to the laminar flow reactor **350** at the upper portion **352** and/or at the lower portion **354** (not shown).

[0056] In one or more examples, the primary solvent source **356** may be or contain a steam source configured to store and/or disperse water and/or steam. In other examples, the primary solvent source **356** may be or contain a solvent source and be configured to store and/or disperse one or more solvents. The solvent may be or contain one or more of a polar protic solvent, a polar aprotic solvent, a nonpolar hydrocarbon solvent, a nonpolar ether solvent, a nonpolar chlorocarbon solvent, or any combination thereof. For example, the solvent may be or include one or more alcohols, one or more ketones, one or more aromatics, one or more alkyl sulfoxides, one or more furans, or any combination thereof. Exemplary solvents may be water, methanol, ethanol, propanol, butanol, glycerol, acetone, methyl ethyl ketone, benzene, toluene, xylene, dimethyl sulfoxide (DMSO), tetrahydrofuran, supercritical carbon dioxide, or any combination thereof.

[0057] In one or more embodiments, each of a liquid phase within the laminar flow reactor **350** and/or an intermediate stream within the laminar flow reactor **350** and/or a hydrocarbon-solvent stream within the laminar flow reactor **350** may independently persist in laminar flow and a Reynolds number of 2,300 or less. In one or more embodiments, each of a liquid phase within the laminar flow reactor **350** and/or an intermediate stream within the laminar flow reactor **350** and/or a hydrocarbon-solvent stream within the laminar flow reactor **350** may independently have a Reynolds number of about 0, about 10, about 50, about 100, about 200, about 300, about 500, about 600, about 800, about 1,000, about 1,200, about 1,500, about 1,600, about 1,800, less than or about 2,000, less than or about 2,000, less than or about 2,100, less than or about 2,200, less than or about 2,250, less than or about 2,290, or 2,300. For example, each of a liquid phase within the laminar flow reactor **350** and/or an intermediate stream within the laminar flow reactor **350** and/or a hydrocarbon-solvent stream within the laminar flow reactor **350** may independently have a Reynolds number in a range from about 0 to 2,300, about 0 to about 2,290, about 0 to about 2,250,

about 0 to about 2,200, about 0 to about 2,150, about 0 to about 2,100, about 0 to about 2,050, about 0 to about 2,000, about 0 to less than 2,000, about 0 to about 1,800, about 0 to about 1,600, about 0 to about 1,500, about 0 to about 1,200, about 0 to about 1,000, about 0 to about 800, about 0 to about 600, about 0 to about 500, about 0 to about 200, about 0 to about 100, about 500 to 2,300, about 500 to about 2,290, about 500 to about 2,250, about 500 to about 2,200, about 500 to about 2,150, about 500 to about 2,100, about 500 to about 2,050, about 500 to about 2,000, about 500 to less than 2,000, about 500 to about 1,800, about 500 to about 1,600, about 500 to about 1,500, about 500 to about 1,200, about 500 to about 1,000, about 500 to about 800, about 500 to about 600, about 1,000 to 2,300, about 1,000 to about 2,290, about 1,000 to about 2,250, about 1,000 to about 2,200, about 1,000 to about 2,150, about 1,000 to about 2,100, about 1,000 to about 2,050, about 1,000 to about 2,000, about 1,000 to less than 2,000, about 1,000 to about 1,800, about 1,000 to about 1,600, about 1,000 to about 1,500, or about 1,000 to about 1,200. Not to be bound by theory, it is believed that a liquid with a Reynolds number of greater 2,300 has a turbulent flow instead of a laminar flow.

[0058] The hydrocarbon-solvent stream via line **360** may be flowed from the laminar flow reactor **350** and through one or more cooling units. The cooling unit is fluidly coupled to and downstream of the lower portion **354** of the laminar flow reactor **350**. The hydrocarbon-solvent stream via line **360** may be flowed into a cooling portion of the recuperator **330** which extends between inlet **336** and outlet **338**. The hydrocarbon-solvent stream is transferred via line **360**, into inlet **336** and out of the outlet **338**, while flowing through and being cooled in the cooling portion of the recuperator **330**. The cooling unit may be substituted with other types of cooling units including air cooled and/or a circulation cooling systems.

[0059] The cooled hydrocarbon-solvent stream may be flowed via line **362** into and through one or more pressure reduction devices **364**. The pressure reduction device **364** is fluidly coupled to and downstream of the cooling unit **235** via line **362** and fluidly coupled to and upstream of a separation unit **370** via line **366**. The pressure reduction device **364** may be or contain a low-shear pressure reduction device, a cyclonic pressure reduction device, a multi-stage pressure reduction device, or any combination thereof. The pressure reduction device **364** may decrease the pressure of the hydrocarbon-solvent stream by about 10 times, about 20 times, about 50 times, about 100 times, or greater between line **362** and line **366**. The first pressure of the hydrocarbon-solvent stream at line **362** may be in a range from about 500 psi to about 1,500 psi, and the second pressure of the hydrocarbon-solvent stream at line **366** is in a range from about 1 psi to about 500 psi, where the second pressure is at least one half of the value of the first pressure. In one or more examples, the pressure reduction device **364** is a cyclonic pressure reduction device, such as the Typhoon® Valve System, commercially available from the Mokveld Company.

[0060] In one or more examples, the cooled hydrocarbon-solvent stream may be flowed through the pressure reduction device **364** such that the cooled hydrocarbon-solvent stream enters the pressure reduction device **364** at a first pressure and exits the pressure reduction device **364** at a second pressure less than the first pressure. For example, the cooled hydrocarbon-solvent stream may be at a first pressure entering the pressure reduction device **364** and at a second pressure when exiting the pressure reduction device **364**. In some examples, the first pressure may be at least 10 times, about 20 times, or greater than the second pressure. In other examples, the second pressure is at least one half of the value of the first pressure.

[0061] The first pressure may be in a range from about 500 psi, greater than 500 psi, about 550 psi, about 600 psi, or about 800 psi to about 1,000 psi, about 1,200 psi, about 1,500 psi, about 1,800 psi, about 2,000 psi, or greater. For example, the first pressure may be in a range from about 500 psi to about 2,000 psi, about 500 psi to about 1,800 psi, about 500 psi to about 1,500 psi, about 500 psi to about 1,200 psi, about 500 psi to about 1,000 psi, about 500 psi to about 800 psi, about 500 psi to about 600 psi, about 800 psi to about 2,000 psi, about 800 psi to about 1,800 psi, about 800 psi to about 1,500 psi, about 800 psi to about 1,200 psi, about 800 psi to about 1,000 psi, about

1,000 psi to about 2,000 psi, about 1,000 psi to about 1,800 psi, about 1,000 psi to about 1,500 psi, or about 1,000 psi to about 1,200 psi.

[0062] The second pressure may be in a range from about 1 psi, about 5 psi, about 10 psi, about 20 psi, about 50 psi, or about 100 psi to about 150 psi, about 200 psi, about 250 psi, about 300 psi, about 350 psi, about 400 psi, about 450 psi, less than 500 psi, about 500 psi. For example, the second pressure may be in a range from about 1 psi to less than or about 500 psi, about 1 psi to about 400 psi, about 1 psi to about 350 psi, about 1 psi to about 300 psi, about 1 psi to about 250 psi, about 1 psi to about 200 psi, about 1 psi to about 150 psi, about 1 psi to about 100 psi, about 1 psi to about 80 psi, about 1 psi to about 50 psi, about 1 psi to about 10 psi, about 50 psi to less than or about 500 psi, about 50 psi to about 400 psi, about 50 psi to about 350 psi, about 50 psi to about 300 psi, about 50 psi to about 250 psi, about 50 psi to about 200 psi, about 50 psi to about 150 psi, about 50 psi to about 100 psi, about 50 psi to about 80 psi, about 50 psi to about 60 psi, about 100 psi to less than or about 500 psi, about 100 psi to about 400 psi, about 100 psi to about 350 psi, about 100 psi to about 300 psi, about 100 psi to about 250 psi, about 100 psi to about 200 psi, about 100 psi to about 150 psi, or about 100 psi to about 120 psi.

[0063] In one or more examples, the first pressure may be in a range about 500 psi to about 1,500 psi, and the second pressure may be in a range from about 1 psi to about 500 psi. In other examples, the first pressure may be in a range greater than 500 psi to about 1,500 psi, and the second pressure may be in a range from about 1 psi to about 500 psi. In some examples, the first pressure may be in a range about 500 psi to about 1,500 psi, and the second pressure may be in a range from about 1 psi to less than 500 psi.

[0064] The separation unit **370** is fluidly coupled to and downstream of the pressure reduction device **364** via line **366**. The separation unit **370**, as depicted in FIG. **3**, is a vertical extraction column. In other embodiments, the separation unit **370** may be a horizontal extraction column, a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof. In one or more embodiments, the separation unit **370** may be any of the extraction columns and/or other units and systems described and discussed in U.S. Pub. No. 2024/0150660, which is herein incorporated by reference in its entirety.

[0065] One or more solvent or water sources **378** via line **380** may be fluidly coupled to and upstream of the separation unit **370**. The solvent or water source **378** may supply and otherwise introduce one or more solvents or water into the separation unit **370**. The separation unit **370** contains a scrubbed hydrocarbon stream outlet via line **386** and a solvent stream outlet via line **398**. In one or more examples, a scrubbed hydrocarbon stream flowing from the scrubbed hydrocarbon stream outlet via line **380** of the separation unit **370** contains a final concentration of the contaminant of at least 10 times, about 40 times, or about 100 times less than the initial concentration of the contaminant.

[0066] In one or more embodiments, the initial concentration of the contaminant in the feedstock hydrocarbon is about 10 times, about 20 times, about 40 times, about 50 times, about 100 times, about 120 times, about 150 times, about 300 times, about 500 times, about 1,000 times, or greater than the final concentration of the contaminant of the purified or scrubbed hydrocarbon stream. In some examples, the initial contaminant concentration of the feedstock hydrocarbon is about 40 ppm, about 100 ppm, about 200 ppm, about 300 ppm, about 500 ppm, about 1,000 ppm, or greater, and the final concentration of the total metals is less than 20 ppm, less than 10 ppm, less than 5 ppm, less than 2 ppm, or less than 1 ppm in the purified or scrubbed hydrocarbon stream. In one or more embodiments, the initial concentration of the total metals is 40 ppm or greater, and the final concentration of the total metals in the feedstock hydrocarbon is less than 5 ppm, less than 2 ppm, or less than 1 ppm in the purified or scrubbed hydrocarbon stream. In other examples, the contaminant is phosphorus, the initial concentration of the phosphorous is 100 ppm or greater in the feedstock hydrocarbon, and the final concentration of the phosphorus is less than 5 ppm, such as less than 2 ppm, or less than 1 ppm in the purified or scrubbed hydrocarbon stream.

[0067] In one or more examples, the contaminant may be or include phosphorous, sulfur, nitrogen, total metals, or a combination thereof within the purified or scrubbed hydrocarbon stream. The final concentration of the contaminant may be less than 100 ppm, less than 50 ppm, less than 20 ppm, less than 10 ppm, less than 5 ppm, less than 1 ppm, or less than 0.1 ppm, or lower within the purified or scrubbed hydrocarbon stream. For example, the final concentration of the any of the contaminant may be non-detectable (ND) within the purified or scrubbed hydrocarbon stream. A non-detectable amount is based on the sensitivity of the instrument used to detect the concentration, and in some examples, the instrument may have a sensitivity of about 0.1 ppm.

[0068] In one or more examples, the separation unit **370** is a vertical extraction column containing an upper portion **372b** opposite a lower portion **374b**, an upper inlet via line **380** in the upper portion **372a** configured to receive a solvent or water stream, and a lower inlet via line **366** in the lower portion **374a** coupled to and downstream of the pressure reduction device **364**. The lower inlet via line **366** may be configured to receive a cooled hydrocarbon-solvent stream. A central region of the vertical extraction column **370** is disposed between the upper and lower portions **372b**, **374b** and configured to perform a countercurrent liquid-liquid extraction by flowing the cooled hydrocarbon-solvent stream toward the upper portion **372a** of the vertical extraction column **370** and flowing the solvent or water stream toward the lower portion **374b** of the vertical extraction column **370**. The scrubbed hydrocarbon stream outlet via line **386** may be disposed in the upper portion **372b** of the vertical extraction column **370**. A solvent stream outlet via line **398** may be disposed in the lower portion **472b** of the vertical extraction column **370**. The solvent stream outlet via line **398** may transport a water-solvent waste stream away from the vertical extraction column **370**. In some examples, the central region of the vertical extraction column **370** contains one or more packing assemblies **376**. In some examples, a rag discharge unit **384** via line **382** is fluidly coupled to and downstream of a lower portion of the central region of the vertical extraction column **370**. The rag discharge unit **384** is configured to receive a rag composition containing a mixture of oil, water, solids, and interfacially active components.

[0069] One or more solvent or water sources **378** via line **380** may be fluidly coupled to and upstream of the separation unit **370**. The solvent or water source **378** may supply and otherwise introduce one or more solvents or water into the separation unit **370**. The separation unit **370** contains a scrubbed hydrocarbon stream outlet via line **386** and a solvent stream outlet via line **398**. In one or more examples, a scrubbed hydrocarbon stream flowing from the scrubbed hydrocarbon stream outlet via line **386** of the separation unit **370** contains a final concentration of the contaminant of at least 10 times, about 40 times, or about 100 times less than the initial concentration of the contaminant.

[0070] In one or more embodiments, the solvent stream is an aqueous stream and is diverted or otherwise flowed from the separation unit **370** to a mixer (not shown). The solvent stream or aqueous stream is concentrated and/or dried and then blended with a product in the mixer. The product may be or contain one or more of a processed grain, vegetable meal, fruit meal, protein meal, meat, stover, hay, forage, or any combination thereof. The mixer may be or contain one or more of a tumbler mixer, paddle mixer, cone mixer, screw mixer, or any combination thereof.

[0071] A finishing unit **388** may be fluidly coupled to and downstream of the scrubbed hydrocarbon stream outlet via line **386** of the separation unit **370**. The finishing unit **388** may be or contain a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof. The scrubbed hydrocarbon stream outlet via line **386** may be flowed to and introduce into a finishing unit **388** that contains a purified hydrocarbon stream outlet or line **390** for providing a purified hydrocarbon stream **392**. The finishing unit **388** also contains a water-solvent waste outlet or line **394** for providing a water-solvent waste stream **396**. The purified hydrocarbon stream **392** has a final concentration of the contaminant of at least 10 times, about 20 times, about 100 times less than the initial concentration of the contaminant.

[0072] A finishing unit **302** may be fluidly coupled to and downstream of the solvent stream outlet

via line **398** of the separation unit **370**. The finishing unit **302** may be or contain a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof. The finishing unit **302** contains a water-solvent waste stream via line **306** and a hydrocarbon stream via line **302**. The water-solvent waste stream via line **306** may be further processed in a water-solvent purification system **303** via line **301** and a pump **308**. Alternatively, the water-solvent waste stream via line **306** may be recycled via line **305** and/or line **307** and a pump **308** into any component of the system downstream of the deaerator unit **314**. The water-solvent purification system **303** may be used to transport and introduce one or more solvents, including water and/or steam, into any component in the system which uses solvent, solvent vapor, water, and/or steam. The hydrocarbon stream via line **304** may be recycled back into the hydrocarbon purification system **300**, such as being transferred to the feedstock hydrocarbon source **310**, the deaerator **314**, or components of the hydrocarbon purification system **300**.

[0073] In one or more embodiments, the streams throughout the hydrocarbon purification system **300** have different amounts of solvent (e.g., water) within the various portions of the hydrocarbon purification system **300**. In one or more examples, each of the streams at line **305** and/or line **307** may independently contain a concentration of water or other solvent in a range from about 0 wt % to about 50 wt %, about 2 wt % to about 30 wt %, or about 5 wt % to about 20 wt % relative to the mass percentage of hydrocarbon within and contained at the respective line. In other examples, each of the streams at line **346** and/or line **348** and/or line **356** may independently contain a concentration of water or other solvent in a range from about 0 wt % to about 20 wt %, about 2 wt % to about 15 wt %, or about 5 wt % to about 10 wt % relative to the mass percentage of hydrocarbon within and contained at the respective line. In some examples, the stream at line **380** may contain a concentration of water or other solvent in a range from about 5 wt % to about 50 wt %, about 5 wt % to about 35 wt %, or about 5 wt % to about 20 wt % relative to the mass percentage of hydrocarbon within and contained at line **380**.

[0074] FIG. 4 depicts a flow reactor system **400** containing a liquid-filled laminar flow reactor **430**, according to one or more embodiments described and discussed herein. The flow reactor system **400** and the liquid-filled laminar flow reactor **430** are configured to purify a feedstock hydrocarbon. Each of the flow reactor system **400** and the liquid-filled laminar flow reactor **430** may independently be incorporated into the hydrocarbon purification systems **200**, **300**. In one or more embodiments, the liquid-filled laminar flow reactor **430** is used as the laminar flow reactor **230** in the hydrocarbon purification system **200**. In other embodiments, the liquid-filled laminar flow reactor **430** is used as the laminar flow reactor **350** in the hydrocarbon purification system **300**.

[0075] In one or more embodiments, the hydrocarbon purification system **400** for purifying a hydrocarbon is provided and contains a feedstock hydrocarbon source **406**. The feedstock hydrocarbon source **406** contains a feedstock hydrocarbon containing one or more of an oil, a fat, a grease, or any combination thereof, as well as other type of feedstock hydrocarbon discussed further below. The feedstock hydrocarbon has an initial concentration of a contaminant which is reduced and/or removed by the method **100** and/or with the processes and methods described and discussed herein.

[0076] In one or more embodiments, the feedstock hydrocarbon may be or contain a non-polar fluid, e.g., petroleum-based feedstocks, such as petroleum crude oil, shale oil, petroleum refinery intermediate streams (such as vacuum tower bottoms (VTB)), pyrolysis oils, recycled plastics, coal liquids, used motor oil, and mixtures thereof. Alternatively, the feedstock hydrocarbon may be or contain a renewable feedstock, such as plant oil. Suitable plant oils include oils of camelina, canola, Carinata, castor, coconut, Jatropha, palm, peanut, Pongamia, soy bean, tung, and/or corn (such as derived from distiller grains), soap stock, waste vegetable oil, yellow grease (from cooking oil), brown grease (from grease traps and wastewater treatment), highly acidic oils (also referred to as acidic oils), animal tallow, algal oil, microbial oil, terpenes and other pine-related byproducts

from tall oils, pine oils, or other biosynthetic oils and/or pyrolysis oils (such as derived from pyrolysis, esterification, oligomerization, or polymerization) and mixtures thereof. In some embodiments, the feedstock hydrocarbon may be plant based, animal based, insect based, microbial based, or any combination thereof. In one or more embodiments, the feedstock hydrocarbon may be or contain a food oil which may include one or more plant oils, one or more plant based oils, one or more animal based oils, or any combination thereof. In some embodiments, the feedstock hydrocarbon may be or contain one food oils, purified and/or non-purified food oils, other oils, greases, fats, and/or other substances (e.g., vegetable oils, animal fats, fatty acids, fatty alcohols, and mineral oils), according to one or more embodiments described and discussed herein. In one or more embodiments, the feedstock hydrocarbon may be or contain soybean oil, coconut oil, palm oil, canola oil, corn oil, peanut oil, sunflower oil, cottonseed oil, olive oil, beef fat or lard, pork fat or lard, poultry fat, fish oil, tall oil, pyrolysis oil, or any combination thereof. In one or more examples, the feedstock hydrocarbon may be or contain soybean oil, corn oil, canola oil, camelina oil, yellow grease, choice white grease, beef tallow, poultry fat, used cooking oil, pyrolysis oil, or any combination thereof. In other examples, the feedstock hydrocarbon may be or contain one or more polymeric materials, one or more plastic materials, one or more oligomers, or any combination thereof. Exemplary polymeric materials and/or plastic materials may be or contain one or more of polyethylene terephthalate (PETE), high density polyethylene (HDPE), polyvinyl chloride (PVC), low density polyethylene (LDPE), polypropylene (PP), polystyrene (PS), derivatives thereof, or any combination thereof.

[0077] The feedstock hydrocarbon may contain one or more contaminants which are reduced and/or removed by the methods described and discussed herein. Exemplary contaminants contained in the feedstock hydrocarbon may be or contain one or more of a halide (e.g., Cl, F, Br, I), phosphorous, sulfur, nitrogen, a gum or lecithin, a transition metal, an alkali metal, a rare earth metal, other metals, a metalloid, a heavy metal, an inorganic, or any combination thereof. In some examples, the contaminant of total metals may be or contain sodium, potassium, magnesium, calcium, iron, or any combination thereof.

[0078] A solvent source **402** and an additive source **404** via one or more lines **405** are fluidly coupled to and upstream of the feedstock hydrocarbon source **406**. One or more solvents including water may be transferred from the solvent source **402** and one or more additives may be transferred from the additive source **404** via line **405** and introduced and combined into the feedstock hydrocarbon within the feedstock hydrocarbon source **406**.

[0079] The solvent in the solvent source **402** may contain one or more of a polar protic solvent, a polar aprotic solvent, a nonpolar hydrocarbon solvent, a nonpolar ether solvent, a nonpolar chlorocarbon solvent, or any combination thereof. For example, the solvent may be or include one or more alcohols, one or more ketones, one or more aromatics, one or more alky sulfoxides, one or more furans, or any combination thereof. Exemplary solvents may be water, methanol, ethanol, propanol, butanol, glycerol, acetone, methyl ethyl ketone, benzene, toluene, xylene, dimethyl sulfoxide (DMSO), tetrahydrofuran, supercritical carbon dioxide, or any combination thereof. The additive source **404** contains one or more additives may be or contain one or more hydrolyzing agents, one or more acids, one or more bases, one or more salts, one or more chelating agents, one or more polar solvents, one or more non-polar solvents, or any combination thereof.

[0080] The additive source **404** may contain one or more additives. Exemplary additives may be or contain one or more of a hydrolyzing agent, an acid, a base, a salt, a chelating agent, a polar solvent, a non-polar solvent, or any combination thereof. In one or more examples, the additive may be or contain one or more hydrolyzing agents. The hydrolyzing agent may be or contain any chemical capable of hydrolyzing a hydrocarbon, e.g., fat, oil, or grease. For example, the hydrolyzing agent may be or contain acetic acid, ascorbic acid, citric acid, hydrochloric acid, fumaric acid, glucaric acid, gluconic acid, glutamic acid, hydrochloric acid, lactic acid, malic acid, oxalic acid, phosphoric acid, propionic acid, sulfuric acid, tartaric acid, salts thereof, or any

combination thereof. As a further example, the hydrolyzing agent may be or contain nitrilotriacetic acid (NTA), ethylenediaminetetraacetic acid (EDTA), sodium hydroxide, potassium hydroxide, lithium hydroxide, ammonium hydroxide, or any combination thereof. Without being bound by theory the additive may react with a triglyceride to separate a fatty acid of the triglyceride from the glycerin backbone, allowing for the purification of the fatty acids in the triglyceride. Additionally, and without being bound by theory, the additive may hydrolyze phospholipids and other contaminants more readily than fatty acids, allowing for selective hydrolyzing of phospholipids at lower temperatures and with shorter residence times than those required for fatty acid splitting of triglycerides, reducing free fatty acid formation in the hydrocarbon purification system **400** including the liquid-filled laminar flow reactor **430**. Additionally, and without being bound by theory, the additive may increase a density and/or molecular weight of the aqueous phase, thereby promoting faster separation of the organic phase and the aqueous phase. In one or more embodiments, the feedstock hydrocarbon via line **405** may include about 50 parts per million (ppm) to about 20,000 ppm of one or more additives, e.g., about 50 ppm to about 1,000 ppm, about 1,000 ppm to about 4,000 ppm, about 4,000 ppm to about 6,000 ppm, about 6,000 ppm to about 8,000 ppm, about 8,000 ppm to about 10,000 ppm, or about 10,000 ppm to about 20,000 ppm.

[0081] The feedstock hydrocarbon containing the additive is transferred via line **408** to one or more heating units fluidly coupled to and downstream of the feedstock hydrocarbon source **406**. The heating units may include one or more primary heating units and one or more supplemental heating units fluidly coupled to and downstream of the hydrocarbon source **406** and/or fluidly coupled to and upstream of a liquid-filled laminar flow reactor **430**. A heating unit may be or contain a heating portion of a recuperator **410** which extends between inlet **412** and outlet **414**. The feedstock hydrocarbon containing the additive is transferred via line **408**, into inlet **412** and out of the outlet **414**, while flowing through and being heated in the heating portion of the recuperator **410**. The heated feedstock hydrocarbon may flow via line **420** through a secondary heater, such as a heater **422**. Each of the heating portion of a recuperator **410** and/or the heater **422** may be substituted with other types of heating units including an electric heater, a fuel combustion heater, a steam heater, other heating sources, or any combination thereof.

[0082] The heated feedstock hydrocarbon may be flowed via line **424** to the liquid-filled laminar flow reactor **430** containing an upper portion **432b** opposite a lower portion **434b**. A primary solvent source **426** via line **427** may be fluidly coupled to line **424** and configured to introduce one or more solvents (e.g., water, steam, organic solvent, organic vapor) into the heated feedstock hydrocarbon in line **424** to produce a hydrocarbon-solvent stream prior to introducing the hydrocarbon-solvent stream into the liquid-filled laminar flow reactor **430**. As such, the feedstock hydrocarbon and/or the hydrocarbon-solvent stream may be introduced into an upper reactor segment **432a** by line **424**.

[0083] In one or more embodiments, the primary solvent (e.g., steam or vaporized solvent) from the primary solvent source **426** may be introduced prior to the liquid-filled laminar flow reactor **430** into line **424** through one or more injection devices disposed at line **427**. For example, line **427** may be or contain one or more injection devices in fluid communication with the liquid-filled laminar flow reactor **430**. The injection device may be or contain one or more distributors, valves, nozzles, other injecting devices, or any combination thereof. The primary solvent may have a pressure drop across the injection device at line **427** in a range from about 0.0001 psi, about 0.005 psi, about 0.001 psi, about 0.05 psi, about 0.01 psi, about 0.5 psi, or about 0.1 psi to about 1 psi, about 5 psi, about 10 psi, about 20 psi, about 30 psi, about 40 psi, about 50 psi, about 60 psi, about 70 psi, about 80 psi, or greater. For example, the primary solvent may independently have a pressure drop across the injection device at line **427** in a range from about 0.0001 psi to about 80 psi, about 0.0001 psi to about 60 psi, about 0.0001 psi to about 40 psi, about 0.0001 psi to about 20 psi, about 0.0001 psi to about 10 psi, about 0.0001 psi to about 5 psi, about 0.0001 psi to about 1 psi, about 0.0001 psi to about 0.1 psi, about 0.0001 psi to about 0.01 psi, about 0.0001 psi to about

0.001 psi, about 0.0001 psi to about 0.0005 psi, about 0.001 psi to about 80 psi, about 0.001 psi to about 60 psi, about 0.001 psi to about 40 psi, about 0.001 psi to about 20 psi, about 0.001 psi to about 10 psi, about 0.001 psi to about 5 psi, about 0.001 psi to about 1 psi, about 0.001 psi to about 0.1 psi, about 0.001 psi to about 0.01 psi, about 0.01 psi to about 80 psi, about 0.01 psi to about 60 psi, about 0.01 psi to about 40 psi, about 0.01 psi to about 20 psi, about 0.01 psi to about 10 psi, about 0.01 psi to about 5 psi, about 0.01 psi to about 1 psi, or about 0.01 psi to about 0.1 psi.

[0084] The solvent in the solvent source **426** may contain one or more of a polar protic solvent, a polar aprotic solvent, a nonpolar hydrocarbon solvent, a nonpolar ether solvent, a nonpolar chlorocarbon solvent, or any combination thereof. For example, the solvent may be or include one or more alcohols, one or more ketones, one or more aromatics, one or more alky sulfoxides, one or more furans, or any combination thereof. Exemplary solvents may be water, methanol, ethanol, propanol, butanol, glycerol, acetone, methyl ethyl ketone, benzene, toluene, xylene, dimethyl sulfoxide (DMSO), tetrahydrofuran, supercritical carbon dioxide, or any combination thereof.

[0085] In one or more embodiments, the liquid-filled laminar flow reactor **430** contains one or more inflow distributor assemblies **438** in the upper reactor segment **432a**, one or more outflow header assemblies **440** in a lower reactor segment **434a**, one or more packing assemblies **436**, or any combination thereof. In some examples, the liquid-filled laminar flow reactor **430** contains one or more packing assemblies **436** disposed between the inflow distributor assembly **438** and the outflow header assembly **440**. In one or more embodiments, the liquid-filled laminar flow reactor **430** contains one inflow distributor assembly **438** in the upper reactor segment **432a**, two outflow header assemblies **440** in the lower reactor segment **434a**, and one packing assembly **436** between the inflow distributor assembly **438** and the outflow header assemblies **440**. In other embodiments, the liquid-filled laminar flow reactor **430** contains one inflow distributor assembly **438** in the upper reactor segment **432a** and one or two outflow header assemblies **440** in the lower reactor segment **434a**, but lacking the packing assembly **436**.

[0086] The inflow distributor assembly **438** is fluidly coupled to line **424** and configured to receive the hydrocarbon-solvent stream. The inflow distributor assembly **438** sprays or otherwise distributes the hydrocarbon-solvent stream across the diameter of the liquid-filled laminar flow reactor **430**. The outflow header assemblies **440** may be distributed in the lower reactor segment **434a** so that residence time of the hydrocarbon-solvent stream may be varied as desired through the liquid-filled laminar flow reactor **430**.

[0087] The packing assembly **436** may be used to restrict one or more flows of the hydrocarbon-solvent stream. The packing assembly **436** may be or contain one or more packing materials, such as a random packing material, a structured packing material, one or more sieve trays, or a combination thereof. For example, the packing assembly **436** may be or contain a polymeric material, a ceramic material, a metallic material, a glass material, or any combination thereof. In one or more examples, the packing assembly **436** contains one or more packing materials disposed within the liquid-filled laminar flow reactor **430**. While only one packing assembly **436** is depicted in FIG. 4, any number of the packing assemblies **436** may be placed in the liquid-filled laminar flow reactor **430**. For example, there may be 1, 2, 3, 4, 5 or more packing assemblies **436** disposed in the packing assemblies **436**. Without being bound by theory the packing assembly **436** may be disposed in the liquid-filled laminar flow reactor **430** on one or more of a void fraction, surface area, unit volume, random packing arrangement, structure packing arrangement, tray, continuous phase, dispersed phase, viscosity, and/or surface tension.

[0088] The hydrocarbon-solvent stream exits the liquid-filled laminar flow reactor **430** via lines **442**. The hydrocarbon-solvent stream may flow through the outflow header assemblies **440** and then lines **442** which are fluidly coupled to and downstream of the outflow header assemblies **440**. The hydrocarbon-solvent stream may flow through the **434b** and then line **443** to exit the liquid-filled laminar flow reactor **430**. The hydrocarbon-solvent streams via line **442** may merge and combine with the hydrocarbon-solvent streams via line **443**.

[0089] The hydrocarbon-solvent stream via line **443** may be flowed from the liquid-filled laminar flow reactor **430** and through one or more cooling units. The cooling unit is fluidly coupled to and downstream of the lower portion **434b** of the liquid-filled laminar flow reactor **430**. The hydrocarbon-solvent stream via line **443** may be flowed into a cooling portion of the recuperator **410** which extends between inlet **416** and outlet **418**. The hydrocarbon-solvent stream is transferred via line **443**, into inlet **416** and out of the outlet **418**, while flowing through and being cooled in the cooling portion of the recuperator **410**. The cooling unit may be substituted with other types of cooling units including air cooled and/or a circulation cooling systems.

[0090] The cooled hydrocarbon-solvent stream may be flowed via line **444** into and through one or more other units and/or systems **450**. The units and/or systems **450** may be or include any one or more components in the systems **200**, **300**. The units and/or systems **450** may be any of the portions of systems **200**, **300** downstream from the laminar flow reactor **230** and/or the laminar flow reactor **350**, respectively. In one or more embodiments, the cooled hydrocarbon-solvent stream via line **444** may enter the hydrocarbon purification system **200** at the pressure reduction device **240**, the separation unit **245**, and/or any other segment or portion of the hydrocarbon purification system **200**. In other embodiments, the cooled hydrocarbon-solvent stream via line **444** may enter the hydrocarbon purification system **300** at the pressure reduction device **364**, the separation unit **370**, and/or any other segment or portion of the hydrocarbon purification system **300**.

[0091] FIG. 5 depicts a flow reactor system **500** containing a vapor-infused laminar flow reactor **530**, according to one or more embodiments described and discussed herein. The flow reactor system **500** and the vapor-infused laminar flow reactor **530** are configured to purify a feedstock hydrocarbon. Each of the flow reactor system **400** and the vapor-infused laminar flow reactor **530** may independently be incorporated into the hydrocarbon purification systems **200**, **300**. In one or more embodiments, the vapor-infused laminar flow reactor **530** is used as the laminar flow reactor **230** in the hydrocarbon purification system **200**. In other embodiments, the vapor-infused laminar flow reactor **530** is used as the laminar flow reactor **350** in the hydrocarbon purification system **300**.

[0092] In one or more embodiments, the hydrocarbon purification system **500** for purifying a hydrocarbon is provided and contains a feedstock hydrocarbon source **506**. The feedstock hydrocarbon source **506** contains a feedstock hydrocarbon containing one or more of an oil, a fat, a grease, or any combination thereof, as well as other type of feedstock hydrocarbon discussed further below. The feedstock hydrocarbon has an initial concentration of a contaminant which is reduced and/or removed by the method **100** and/or with the processes and methods described and discussed herein.

[0093] In one or more embodiments, the feedstock hydrocarbon may be or contain a non-polar fluid, e.g., petroleum-based feedstocks, such as petroleum crude oil, shale oil, petroleum refinery intermediate streams (such as vacuum tower bottoms (VTB)), pyrolysis oils, recycled plastics, coal liquids, used motor oil, and mixtures thereof. Alternatively, the feedstock hydrocarbon may be or contain a renewable feedstock, such as plant oil. Suitable plant oils include oils of camelina, canola, Carinata, castor, coconut, Jatropha, palm, peanut, Pongamia, soy bean, tung, and/or corn (such as derived from distiller grains), soap stock, waste vegetable oil, yellow grease (from cooking oil), brown grease (from grease traps and wastewater treatment), highly acidic oils (also referred to as acidic oils), animal tallow, algal oil, microbial oil, terpenes and other pine-related byproducts from tall oils, pine oils, or other biosynthetic oils and/or pyrolysis oils (such as derived from pyrolysis, esterification, oligomerization, or polymerization) and mixtures thereof. In some embodiments, the feedstock hydrocarbon may be plant based, animal based, insect based, microbial based, or any combination thereof. In one or more embodiments, the feedstock hydrocarbon may be or contain a food oil which may include one or more plant oils, one or more plant based oils, one or more animal based oils, or any combination thereof. In some embodiments, the feedstock

hydrocarbon may be or contain one food oils, purified and/or non-purified food oils, other oils, greases, fats, and/or other substances (e.g., vegetable oils, animal fats, fatty acids, fatty alcohols, and mineral oils), according to one or more embodiments described and discussed herein. In one or more embodiments, the feedstock hydrocarbon may be or contain soybean oil, coconut oil, palm oil, canola oil, corn oil, peanut oil, sunflower oil, cottonseed oil, olive oil, beef fat or lard, pork fat or lard, poultry fat, fish oil, tall oil, pyrolysis oil, or any combination thereof. In one or more examples, the feedstock hydrocarbon may be or contain soybean oil, corn oil, canola oil, camelina oil, yellow grease, choice white grease, beef tallow, poultry fat, used cooking oil, pyrolysis oil, or any combination thereof. In other examples, the feedstock hydrocarbon may be or contain one or more polymeric materials, one or more plastic materials, one or more oligomers, or any combination thereof. Exemplary polymeric materials and/or plastic materials may be or contain one or more of polyethylene terephthalate (PETE), high density polyethylene (HDPE), polyvinyl chloride (PVC), low density polyethylene (LDPE), polypropylene (PP), polystyrene (PS), derivatives thereof, or any combination thereof.

[0094] The feedstock hydrocarbon may contain one or more contaminants which are reduced and/or removed by the methods described and discussed herein. Exemplary contaminants contained in the feedstock hydrocarbon may be or contain one or more of a halide (e.g., Cl, F, Br, I), phosphorous, sulfur, nitrogen, a gum or lecithin, a transition metal, an alkali metal, a rare earth metal, other metals, a metalloid, a heavy metal, an inorganic, or any combination thereof. In some examples, the contaminant of total metals may be or contain sodium, potassium, magnesium, calcium, iron, or any combination thereof.

[0095] A solvent source **502** and an additive source **504** via one or more lines **505** are fluidly coupled to and upstream of the feedstock hydrocarbon source **506**. One or more solvents including water may be transferred from the solvent source **502** and one or more additives may be transferred from the additive source **504** via line **505** and introduced and combined into the feedstock hydrocarbon within the feedstock hydrocarbon source **506**.

[0096] The solvent in the solvent source **502** may contain one or more of a polar protic solvent, a polar aprotic solvent, a nonpolar hydrocarbon solvent, a nonpolar ether solvent, a nonpolar chlorocarbon solvent, or any combination thereof. For example, the solvent may be or include one or more alcohols, one or more ketones, one or more aromatics, one or more alky sulfoxides, one or more furans, or any combination thereof. Exemplary solvents may be water, methanol, ethanol, propanol, butanol, glycerol, acetone, methyl ethyl ketone, benzene, toluene, xylene, dimethyl sulfoxide (DMSO), tetrahydrofuran, supercritical carbon dioxide, or any combination thereof. The additive source **504** contains one or more additives may be or contain one or more hydrolyzing agents, one or more acids, one or more bases, one or more salts, one or more chelating agents, one or more polar solvents, one or more non-polar solvents, or any combination thereof.

[0097] The additive source **504** may contain one or more additives. Exemplary additives may be or contain one or more of a hydrolyzing agent, an acid, a base, a salt, a chelating agent, a polar solvent, a non-polar solvent, or any combination thereof. In one or more examples, the additive may be or contain one or more hydrolyzing agents. The hydrolyzing agent may be or contain any chemical capable of hydrolyzing a hydrocarbon, e.g., fat, oil, or grease. For example, the hydrolyzing agent may be or contain acetic acid, ascorbic acid, citric acid, hydrochloric acid, fumaric acid, glucaric acid, gluconic acid, glutamic acid, hydrochloric acid, lactic acid, malic acid, oxalic acid, phosphoric acid, propionic acid, sulfuric acid, tartaric acid, salts thereof, or any combination thereof. As a further example, the hydrolyzing agent may be or contain nitrilotriacetic acid (NTA), ethylenediaminetetraacetic acid (EDTA), sodium hydroxide, potassium hydroxide, lithium hydroxide, ammonium hydroxide, or any combination thereof. Without being bound by theory the additive may react with a triglyceride to separate a fatty acid of the triglyceride from the glycerin backbone, allowing for the purification of the fatty acids in the triglyceride. Additionally, and without being bound by theory, the additive may hydrolyze phospholipids and other

contaminants more readily than fatty acids, allowing for selective hydrolyzing of phospholipids at lower temperatures and with shorter residence times than those required for fatty acid splitting of triglycerides, reducing free fatty acid formation in the hydrocarbon purification system **500** including the vapor-infused laminar flow reactor **530**. Additionally, and without being bound by theory, the additive may increase a density and/or molecular weight of the aqueous phase, thereby promoting faster separation of the organic phase and the aqueous phase. In one or more embodiments, the feedstock hydrocarbon via line **505** may include about 50 parts per million (ppm) to about 20,000 ppm of one or more additives, e.g., about 50 ppm to about 1,000 ppm, about 1,000 ppm to about 4,000 ppm, about 4,000 ppm to about 6,000 ppm, about 6,000 ppm to about 8,000 ppm, about 8,000 ppm to about 10,000 ppm, or about 10,000 ppm to about 20,000 ppm.

[0098] The feedstock hydrocarbon containing the additive is transferred via line **508** to one or more heating units fluidly coupled to and downstream of the feedstock hydrocarbon source **506**. The heating units may include one or more primary heating units and one or more supplemental heating units fluidly coupled to and downstream of the hydrocarbon source **506** and/or fluidly coupled to and upstream of a vapor-infused laminar flow reactor **530**. A heating unit may be or contain a heating portion of a recuperator **510** which extends between inlet **512** and outlet **514**. The feedstock hydrocarbon containing the additive is transferred via line **508**, into inlet **512** and out of the outlet **514**, while flowing through and being heated in the heating portion of the recuperator **510**. The heated feedstock hydrocarbon may flow via line **524** through a secondary heater, not shown. Each of the heating portion of a recuperator **510** and/or the secondary heater may be substituted with other types of heating units including an electric heater, a fuel combustion heater, a steam heater, other heating sources, or any combination thereof.

[0099] The heated feedstock hydrocarbon may be flowed via line **524** to the vapor-infused laminar flow reactor **530** containing an upper portion **532b** opposite a lower portion **534b**. In one or more embodiments, the vapor-infused laminar flow reactor **530** contains one or more solvent distributors **528** in an upper reactor segment **532a**, one or more inflow distributor assemblies **538** in the upper reactor segment **532a**, one or more packing assemblies **536**, or any combination thereof. In some examples, the vapor-infused laminar flow reactor **530** contains one solvent distributor **528** disposed above one inflow distributor assembly **538**, and one or more packing assemblies **536** disposed below the solvent distributor **528** and the inflow distributor assembly **538**. A reaction zone **533** is disposed in a lower reactor segment **534a** below the packing assembly **536**.

[0100] A primary solvent source **526** via line **527** may be fluidly coupled to the one or more solvent distributors **528** disposed inside the upper reactor segment **532a** of the vapor-infused laminar flow reactor **530**. The solvent distributor **528** is configured to introduce one or more solvents (e.g., water, steam, organic solvent, organic vapor) into the upper reactor segment **532a**. The heated feedstock hydrocarbon via line **424** may be fluidly coupled to the one or more inflow distributor assemblies **538** in the upper reactor segment **532a**. The solvent and the heated feedstock hydrocarbon are combined to produce a hydrocarbon-solvent stream in the vapor-infused laminar flow reactor **530**. The solvent in the solvent source **526** may contain one or more of a polar protic solvent, a polar aprotic solvent, a nonpolar hydrocarbon solvent, a nonpolar ether solvent, a nonpolar chlorocarbon solvent, or any combination thereof. For example, the solvent may be or include one or more alcohols, one or more ketones, one or more aromatics, one or more alkyl sulfoxides, one or more furans, or any combination thereof. Exemplary solvents may be water, methanol, ethanol, propanol, butanol, glycerol, acetone, methyl ethyl ketone, benzene, toluene, xylene, dimethyl sulfoxide (DMSO), tetrahydrofuran, supercritical carbon dioxide, or any combination thereof.

[0101] In one or more embodiments, the solvent distributor **528** is fluidly coupled to line **527** and configured to receive the one or more primary solvents (e.g., water, steam, organic solvent, organic vapor). The solvent distributor **528** sprays or otherwise distributes the solvent across the diameter of the vapor-infused laminar flow reactor **530**. The inflow distributor assembly **538** is fluidly

coupled to line **524** and configured to receive the heated feedstock hydrocarbon. The inflow distributor assembly **538** sprays or otherwise distributes the heated feedstock hydrocarbon across the diameter of the vapor-infused laminar flow reactor **530**. The solvent and the heated feedstock hydrocarbon are combined and mixed to produce a hydrocarbon-solvent stream.

[0102] The packing assembly **536** may be used to restrict one or more flows of the hydrocarbon-solvent stream. The packing assembly **536** may be or contain one or more packing materials, such as a random packing material, structured packing material, one or more sieve trays, or a combination thereof. For example, the packing assembly **536** may be or contain a polymeric material, a ceramic material, a metallic material, a glass material, or any combination thereof. In one or more examples, the packing assembly **536** contains one or more packing materials disposed within the vapor-infused laminar flow reactor **530**. While only one packing assembly **536** is depicted in FIG. 5, any number of the packing assemblies **536** may be placed in the vapor-infused laminar flow reactor **530**. For example, there may be 1, 2, 3, 4, 5 or more packing assemblies **536** disposed in the packing assemblies **536**. Without being bound by theory the packing assembly **536** may be disposed in the vapor-infused laminar flow reactor **530** on one or more of a void fraction, surface area, unit volume, random packing arrangement, structure packing arrangement, tray, continuous phase, dispersed phase, viscosity, and/or surface tension.

[0103] In one or more embodiments, the hydrocarbon-solvent stream may be introduced a flow of the heated hydrocarbon stream into a headspace in an upper portion of the laminar flow reactor. The flow of the heated hydrocarbon stream via line **524** is completely or substantially free of turbulence, and the heated hydrocarbon stream is at a first temperature within the headspace or the upper reactor segment **532a**. The hydrocarbon-solvent stream may further be produced by introducing a flow of the primary solvent via line **527** into the headspace or the upper reactor segment **532a**, the flow of the primary solvent via line **524** is completely or substantially free of turbulence, and the primary solvent is at a second temperature greater than the first temperature. The hydrocarbon-solvent stream may be produced by condensing the primary solvent into the heated hydrocarbon stream to produce an intermediate stream, and flowing the intermediate stream through the reaction zone **533** disposed in the lower reactor segment **534a** to produce the hydrocarbon-solvent stream. The hydrocarbon-solvent stream exits the vapor-infused laminar flow reactor **530** via line **542**. The hydrocarbon-solvent stream may flow through line **542** which is fluidly coupled to and downstream of the reaction zone **533**.

[0104] In one or more embodiments, the primary solvent may be introduced into the headspace through an injection device. The injection device may be or contain one or more distributors, valves, nozzles, other injecting devices, or any combination thereof. The primary solvent may have a pressure drop across the injection device in a range from about 0.0001 psi, about 0.005 psi, about 0.001 psi, about 0.05 psi, about 0.01 psi, about 0.5 psi, or about 0.1 psi to about 1 psi, about 5 psi, about 10 psi, about 20 psi, about 30 psi, about 40 psi, about 50 psi, about 60 psi, about 70 psi, about 80 psi, or greater. For example, the primary solvent may have a pressure drop across the injection device in a range from about 0.0001 psi to about 80 psi, about 0.0001 psi to about 60 psi, about 0.0001 psi to about 40 psi, about 0.0001 psi to about 20 psi, about 0.0001 psi to about 10 psi, about 0.0001 psi to about 5 psi, about 0.0001 psi to about 1 psi, about 0.0001 psi to about 0.1 psi, about 0.0001 psi to about 0.01 psi, about 0.0001 psi to about 0.001 psi, about 0.0001 psi to about 0.0005 psi, about 0.001 psi to about 80 psi, about 0.001 psi to about 60 psi, about 0.001 psi to about 40 psi, about 0.001 psi to about 20 psi, about 0.001 psi to about 10 psi, about 0.001 psi to about 5 psi, about 0.001 psi to about 1 psi, about 0.001 psi to about 0.1 psi, about 0.001 psi to about 0.01 psi, about 0.01 psi to about 80 psi, about 0.01 psi to about 60 psi, about 0.01 psi to about 40 psi, about 0.01 psi to about 20 psi, about 0.01 psi to about 10 psi, about 0.01 psi to about 5 psi, about 0.01 psi to about 1 psi, or about 0.01 psi to about 0.1 psi.

[0105] In some embodiments, the vapor-infused laminar flow reactor **530** may be maintained at a pressure in a range from about 1 psi to about 50 psi of a saturation pressure of the primary solvent

at a target reaction temperature. In some examples a reaction temperature in the laminar flow reactor is in a range from about 50° C. to about 400° C., and a temperature in the vapor-infused laminar flow reactor **530** may be in a range from about 150° C. to about 300° C., such as about 200° C. to about 275° C.

[0106] In one or more examples, the primary solvent comprises, contains, consists of, or consist essential of water and/or steam. In some examples, the primary solvent may be introduced as a superheated vapor, a saturated vapor, or a subcooled vapor.

[0107] In one or more embodiments, each of a liquid phase within the headspace of the vapor-infused laminar flow reactor **530** and/or an intermediate stream within the vapor-infused laminar flow reactor **530** and/or a hydrocarbon-solvent stream within the vapor-infused laminar flow reactor **530** may independently persist in laminar flow and have a Reynolds number of 2,300 or less. In one or more embodiments, each of a liquid phase within the headspace of the vapor-infused laminar flow reactor **530** and/or an intermediate stream within the vapor-infused laminar flow reactor **530** and/or a hydrocarbon-solvent stream within the vapor-infused laminar flow reactor **530** may independently have a Reynolds number of about 0, about 10, about 50, about 100, about 200, about 300, about 500, about 600, about 800, about 1,000, about 1,200, about 1,500, about 1,600, about 1,800, less than or about 2,000, less than or about 2,000, less than or about 2,100, less than or about 2,200, less than or about 2250, less than or about 2,290, or 2,300. For example, each of a liquid phase within the headspace of the vapor-infused laminar flow reactor **530** and/or an intermediate stream within the vapor-infused laminar flow reactor **530** and/or a hydrocarbon-solvent stream within the vapor-infused laminar flow reactor **530** may independently have a Reynolds number in a range from about 0 to 2,300, about 0 to about 2,290, about 0 to about 2,250, about 0 to about 2,200, about 0 to about 2,150, about 0 to about 2,100, about 0 to about 2,050, about 0 to about 2,000, about 0 to less than 2,000, about 0 to about 1,800, about 0 to about 1,600, about 0 to about 1,500, about 0 to about 1,200, about 0 to about 1,000, about 0 to about 800, about 0 to about 600, about 0 to about 500, about 0 to about 200, about 0 to about 100, about 500 to 2,300, about 500 to about 2,290, about 500 to about 2,250, about 500 to about 2,200, about 500 to about 2,150, about 500 to about 2,100, about 500 to about 2,050, about 500 to about 2,000, about 500 to less than 2,000, about 500 to about 1,800, about 500 to about 1,600, about 500 to about 1,500, about 500 to about 1,200, about 500 to about 1,000, about 500 to about 800, about 500 to about 600, about 1,000 to 2,300, about 1,000 to about 2,290, about 1,000 to about 2,250, about 1,000 to about 2,200, about 1,000 to about 2,150, about 1,000 to about 2,100, about 1,000 to about 2,050, about 1,000 to about 2,000, about 1,000 to less than 2,000, about 1,000 to about 1,800, about 1,000 to about 1,600, about 1,000 to about 1,500, or about 1,000 to about 1,200. Not to be bound by theory, it is believed that a liquid with a Reynolds number of greater 2,300 has a turbulent flow instead of a laminar flow.

[0108] The hydrocarbon-solvent stream via line **542** may be flowed from the vapor-infused laminar flow reactor **530** and through one or more cooling units. The cooling unit is fluidly coupled to and downstream of the lower portion **534b** of the vapor-infused laminar flow reactor **530**. The hydrocarbon-solvent stream via line **542** may be flowed into a cooling portion of the recuperator **510** which extends between inlet **516** and outlet **518**. The hydrocarbon-solvent stream is transferred via line **542**, into inlet **516** and out of the outlet **518**, while flowing through and being cooled in the cooling portion of the recuperator **510**. The cooling unit may be substituted with other types of cooling units including air cooled and/or a circulation cooling systems.

[0109] The cooled hydrocarbon-solvent stream may be flowed via line **544** into and through one or more other units and/or systems **550**. The units and/or systems **550** may be or include any one or more components in the systems **200**, **300**. The units and/or systems **550** may be any of the portions of systems **200**, **300** downstream from the laminar flow reactor **230** and/or the laminar flow reactor **350**, respectively. In one or more embodiments, the cooled hydrocarbon-solvent stream via line **544** may enter the hydrocarbon purification system **200** at the pressure reduction

device **240**, the separation unit **245**, and/or any other segment or portion of the hydrocarbon purification system **200**. In other embodiments, the cooled hydrocarbon-solvent stream via line **544** may enter the hydrocarbon purification system **300** at the pressure reduction device **364**, the separation unit **370**, and/or any other segment or portion of the hydrocarbon purification system **300**.

[0110] FIG. **6** depicts a system **600** for purifying a feedstock hydrocarbon and recycling process water or other solvents, according to one or more embodiments described and discussed herein. In one or more embodiments, the system **600** is used in conjunction with the hydrocarbon purification systems **200**, **300**. The system **600** is an efficient system that recycles most, if not all, of the water or other solvents when purifying the feedstock hydrocarbon. The system **600** has an efficiency of greater than 95 wt %, greater than 96 wt %, greater than 97 wt %, such as about 97.5 wt %, about 98 wt %, about 98.5 wt %, about 99 wt % or greater relative to a total solvent concentration within the system **600**.

[0111] A hydrocarbon source **602** via line **604** may be fluidly coupled to and upstream of a laminar flow reactor **610**. The hydrocarbon source **602** contains one or more feedstock hydrocarbon streams. The feedstock hydrocarbon stream may be formed in the hydrocarbon purification systems **200**, **300**, as described and discussed herein. The feedstock hydrocarbon stream contains one or more feedstock hydrocarbons, one or more additives, and one or more solvents. In one or more examples, the solvent is or contains water and/or steam.

[0112] The feedstock hydrocarbon stream via line **604** may contain the solvent in a range from about 1%, about 5%, about 10%, about 15 wt %, about 18 wt %, about 20 wt %, about 22 wt %, or about 24 wt % to about 25 wt %, about 28 wt %, about 30 wt %, about 32 wt %, about 35 wt %, or greater relative to a total solvent concentration within the system **600**. For example, the feedstock hydrocarbon stream via line **604** may contain the solvent in a range from about 1% to about 5%, about 1% to about 10%, about 1% to about 15%, about 1% to about 25%, about 15 wt % to about 35 wt %, about 15 wt % to about 30 wt %, about 15 wt % to about 25 wt %, about 15 wt % to about 20 wt %, about 20 wt % to about 35 wt %, about 20 wt % to about 30 wt %, about 20 wt % to about 25 wt %, about 25 wt % to about 30 wt %, about 22 wt % to about 28 wt %, about 23 wt % to about 27 wt %, or about 24 wt % to about 26 wt %, relative to a total solvent concentration within the system **600**.

[0113] A primary solvent source **606** via line **608** may be fluidly coupled to the laminar flow reactor **610** and configured to introduce one or more solvents (e.g., water, steam, organic solvent, organic vapor) into the feedstock hydrocarbon stream in the laminar flow reactor **610** to produce a hydrocarbon-solvent stream. In some examples, the primary solvent source **606** via line **608** may be fluidly coupled to the laminar flow reactor **610** at or by an upper portion or a middle portion of the laminar flow reactor **610**.

[0114] In one or more examples, the primary solvent source **606** may be or contain a steam source configured to store and/or disperse water and/or steam. In other examples, the primary solvent source **606** may be or contain a solvent source and be configured to store and/or disperse one or more solvents. The solvent may be or contain one or more of a polar protic solvent, a polar aprotic solvent, a nonpolar hydrocarbon solvent, a nonpolar ether solvent, a nonpolar chlorocarbon solvent, or any combination thereof. For example, the solvent may be or include one or more alcohols, one or more ketones, one or more aromatics, one or more alkyl sulfoxides, one or more furans, or any combination thereof. Exemplary solvents may be water, methanol, ethanol, propanol, butanol, glycerol, acetone, methyl ethyl ketone, benzene, toluene, xylene, dimethyl sulfoxide (DMSO), tetrahydrofuran, supercritical carbon dioxide, or any combination thereof.

[0115] The primary solvent via line **608** may contain the solvent (e.g., water, steam, organic solvent, organic vapor) in a range from about 15 wt %, about 18 wt %, about 20 wt %, about 22 wt %, or about 24 wt % to about 25 wt %, about 28 wt %, about 30 wt %, about 32 wt %, about 35 wt %, or greater relative to a total solvent concentration within the system **600**. For example, the

primary solvent via line **608** may contain the solvent in a range from about 15 wt % to about 35 wt %, about 15 wt % to about 30 wt %, about 15 wt % to about 25 wt %, about 15 wt % to about 20 wt %, about 20 wt % to about 35 wt %, about 20 wt % to about 30 wt %, about 20 wt % to about 25 wt %, about 25 wt % to about 30 wt %, about 22 wt % to about 28 wt %, about 23 wt % to about 27 wt %, or about 24 wt % to about 26 wt %, relative to a total solvent concentration within the system **600**.

[0116] The hydrocarbon-solvent stream via line **612** may be flowed from the laminar flow reactor **610** and through one or more cooling units to produce a cooled hydrocarbon-solvent stream via line **616**. The cooling unit is fluidly coupled to and downstream of the lower portion of the laminar flow reactor **610**. The hydrocarbon-solvent stream via line **612** may be flowed into a cooling portion of the recuperator, a coolant circulation system, a refrigeration system, or other type of cooling units.

[0117] The hydrocarbon-solvent stream via lines **612**, **616** may contain the solvent (e.g., water, steam, organic solvent, organic vapor) in a range from about 30 wt %, about 35 wt %, about 40 wt %, or about 45 wt % to about 50 wt %, about 55 wt %, about 60 wt %, about 65 wt %, about 70 wt %, or greater relative to a total solvent concentration within the system **600**. For example, the hydrocarbon-solvent stream via lines **612**, **616** may contain the solvent (e.g., water, steam, organic solvent, organic vapor) in a range from about 30 wt % to about 60 wt %, about 30 wt % to about 55 wt %, about 30 wt % to about 50 wt %, about 30 wt % to about 45 wt %, about 30 wt % to about 40 wt %, about 40 wt % to about 60 wt %, about 40 wt % to about 55 wt %, about 40 wt % to about 50 wt %, about 40 wt % to about 45 wt %, about 45 wt % to about 60 wt %, about 45 wt % to about 55 wt %, about 45 wt % to about 50 wt %, or about 45 wt % to about 48 wt %, relative to a total solvent concentration within the system **600**.

[0118] The cooled hydrocarbon-solvent stream may be flowed via line **616** into and through one or more pressure reduction devices **618**. The pressure reduction device **618** is fluidly coupled to and downstream of the cooling unit **614** via line **616** and fluidly coupled to and upstream of a separation unit **622** via line **620**. The pressure reduction device **618** may be or contain a low-shear pressure reduction device, a cyclonic pressure reduction device, a multi-stage pressure reduction device, or any combination thereof. The pressure reduction device **618** may decrease the pressure of the hydrocarbon-solvent stream by about 10 times, about 20 times, about 50 times, about 100 times, or greater between line **362** and line **620**. In some examples, the second pressure of the hydrocarbon-solvent stream at line **620** is at least one half of the value of the first pressure of the hydrocarbon-solvent stream at line **616**. In one or more examples, the pressure reduction device **618** is a cyclonic pressure reduction device, such as the Typhoon® Valve System, commercially available from the Mokveld Company.

[0119] The first pressure of the hydrocarbon-solvent stream at line **616** may be in a range from about 500 psi, greater than 500 psi, about 550 psi, about 600 psi, or about 800 psi to about 1,000 psi, about 1,200 psi, about 1,500 psi, about 1,800 psi, about 2,000 psi, or greater. For example, the first pressure of the hydrocarbon-solvent stream at line **616** may be in a range from about 500 psi to about 2,000 psi, about 500 psi to about 1,800 psi, about 500 psi to about 1,500 psi, about 500 psi to about 1,200 psi, about 500 psi to about 1,000 psi, about 500 psi to about 800 psi, about 500 psi to about 600 psi, about 800 psi to about 2,000 psi, about 800 psi to about 1,800 psi, about 800 psi to about 1,500 psi, about 800 psi to about 1,200 psi, about 800 psi to about 1,000 psi, about 1,000 psi to about 2,000 psi, about 1,000 psi to about 1,800 psi, about 1,000 psi to about 1,500 psi, or about 1,000 psi to about 1,200 psi.

[0120] The second pressure of the hydrocarbon-solvent stream at line **620** may be in a range from about 1 psi, about 5 psi, about 10 psi, about 20 psi, about 50 psi, or about 100 psi to about 150 psi, about 200 psi, about 250 psi, about 300 psi, about 350 psi, about 400 psi, about 450 psi, less than 500 psi, about 500 psi. For example, the second pressure of the hydrocarbon-solvent stream at line **620** may be in a range from about 1 psi to less than or about 500 psi, about 1 psi to about 400 psi, about 1 psi to about 350 psi, about 1 psi to about 300 psi, about 1 psi to about 250 psi, about 1 psi

to about 200 psi, about 1 psi to about 150 psi, about 1 psi to about 100 psi, about 1 psi to about 80 psi, about 1 psi to about 50 psi, about 1 psi to about 10 psi, about 50 psi to less than or about 500 psi, about 50 psi to about 400 psi, about 50 psi to about 350 psi, about 50 psi to about 300 psi, about 50 psi to about 250 psi, about 50 psi to about 200 psi, about 50 psi to about 150 psi, about 50 psi to about 100 psi, about 50 psi to about 80 psi, about 50 psi to about 60 psi, about 100 psi to less than or about 500 psi, about 100 psi to about 400 psi, about 100 psi to about 350 psi, about 100 psi to about 300 psi, about 100 psi to about 250 psi, about 100 psi to about 200 psi, about 100 psi to about 150 psi, or about 100 psi to about 120 psi.

[0121] In one or more examples, the first pressure may be in a range about 500 psi to about 1,500 psi, and the second pressure may be in a range from about 1 psi to about 500 psi. In other examples, the first pressure may be in a range greater than 500 psi to about 1,500 psi, and the second pressure may be in a range from about 1 psi to about 500 psi. In some examples, the first pressure may be in a range about 500 psi to about 1,500 psi, and the second pressure may be in a range from about 1 psi to less than 500 psi.

[0122] The separation unit **622** is fluidly coupled to and downstream of the pressure reduction device **618** via line **620**. The separation unit **622**, as depicted in FIG. **6**, is a vertical extraction column. In other embodiments, the separation unit **622** may be a horizontal extraction column, a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof.

[0123] One or more solvent or water sources **624** via line **626** may be fluidly coupled to and upstream of the separation unit **622**. The solvent or water source **624** may supply and otherwise introduce one or more solvents or water via line **626** into the separation unit **622**. The separation unit **622** contains a scrubbed hydrocarbon stream outlet via line **632** and a solvent stream outlet via line **644**. In one or more examples, a scrubbed hydrocarbon stream flowing from the scrubbed hydrocarbon stream outlet via line **626** of the separation unit **622** contains a final concentration of the contaminant of at least 10 times, about 40 times, or about 100 times less than the initial concentration of the contaminant. In some examples, a rag discharge unit **630** via line **628** is fluidly coupled to and downstream of a lower portion of the central region of the vertical extraction column **622**. The rag discharge unit **630** is configured to receive a rag composition containing a mixture of oil, water, solids, and interfacially active components.

[0124] One or more solvent or water sources **624** via line **626** may be fluidly coupled to and upstream of the separation unit **622**. The solvent or water source **624** may supply and otherwise introduce one or more solvents or water into the separation unit **622**. The separation unit **622** contains a scrubbed hydrocarbon stream outlet via line **632** and a solvent stream outlet via line **644**. In one or more examples, a scrubbed hydrocarbon stream flowing from the scrubbed hydrocarbon stream outlet via line **632** of the separation unit **622** contains a final concentration of the contaminant of at least 10 times, about 40 times, or about 100 times less than the initial concentration of the contaminant.

[0125] The solvent stream via line **626** may contain the solvent (e.g., water, steam, organic solvent, organic vapor) in a range from about 30 wt %, about 35 wt %, about 40 wt %, or about 45 wt % to about 50 wt %, about 55 wt %, about 60 wt %, about 65 wt %, about 70 wt %, or greater relative to a total solvent concentration within the system **600**. For example, the solvent stream via line **626** may contain the solvent (e.g., water, steam, organic solvent, organic vapor) in a range from about 30 wt % to about 60 wt %, about 30 wt % to about 55 wt %, about 30 wt % to about 50 wt %, about 30 wt % to about 45 wt %, about 30 wt % to about 40 wt %, about 40 wt % to about 60 wt %, about 40 wt % to about 55 wt %, about 40 wt % to about 50 wt %, about 40 wt % to about 45 wt %, about 45 wt % to about 60 wt %, about 45 wt % to about 55 wt %, about 45 wt % to about 50 wt %, or about 45 wt % to about 48 wt %, relative to a total solvent concentration within the system **600**.

[0126] A finishing unit **634** may be fluidly coupled to and downstream of the scrubbed hydrocarbon stream outlet via line **632** of the separation unit **622**. The finishing unit **634** may be or

contain a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof. The scrubbed hydrocarbon stream outlet via line **632** may be flowed to and introduce into a finishing unit **634** that contains a purified hydrocarbon stream outlet or line **636** for providing a purified hydrocarbon stream **638**. The finishing unit **634** also contains a water-solvent waste outlet or line **640** for providing a water-solvent waste stream **642**. The purified hydrocarbon stream **638** has a final concentration of the contaminant of at least 10 times, about 20 times, about 100 times less than the initial concentration of the contaminant.

[0127] The water-solvent waste stream **642** contains a low amount or portion of water or other solvent relative to total solvent concentration within the system **600**. The water-solvent waste stream **642** may contain the solvent (e.g., water, steam, organic solvent, organic vapor) in a range from about 0.1 wt %, about 0.2 wt %, about 0.5 wt %, about 0.8 wt %, or about 1 wt %, about 1.2 wt % to about 1.5 wt %, about 1.8 wt %, about 2 wt %, about 2.2 wt %, about 2.5 wt %, about 2.8 wt %, about 3 wt %, about 3.5 wt %, about 4 wt %, about 5 wt %, or greater relative to a total solvent concentration within the system **600**. For example, the water-solvent waste stream **642** may contain the solvent (e.g., water, steam, organic solvent, organic vapor) in a range from about 0.1 wt % to about 5 wt %, about 0.1 wt % to about 4 wt %, about 0.1 wt % to about 3 wt %, about 0.1 wt % to about 2.5 wt %, about 0.1 wt % to about 2.2 wt %, about 0.1 wt % to about 2 wt %, about 0.1 wt % to about 1.8 wt %, about 0.1 wt % to about 1.5 wt %, about 0.1 wt % to about 1.2 wt %, about 0.1 wt % to about 1 wt %, about 0.1 wt % to about 0.8 wt %, about 0.1 wt % to about 0.5 wt %, about 1 wt % to about 5 wt %, about 1 wt % to about 4 wt %, about 1 wt % to about 3 wt %, about 1 wt % to about 2.5 wt %, about 1 wt % to about 2.2 wt %, about 1 wt % to about 2 wt %, about 1 wt % to about 1.8 wt %, about 1 wt % to about 1.5 wt %, about 1 wt % to about 1.2 wt %, about 1.5 wt % to about 5 wt %, about 1.5 wt % to about 4 wt %, about 1.5 wt % to about 3 wt %, about 1.5 wt % to about 2.5 wt %, about 1.5 wt % to about 2.2 wt %, about 1.5 wt % to about 2 wt %, or about 1.5 wt % to about 1.8 wt %, relative to a total solvent concentration within the system **600**.

[0128] A finishing unit **646** may be fluidly coupled to and downstream of the solvent stream outlet via line **644** of the separation unit **622**. The finishing unit **646** may be or contain a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof. The finishing unit **646** contains a water-solvent waste stream via line **648** and a hydrocarbon stream via line (not shown). The water-solvent waste stream via line **648** may be further processed in a water-solvent purification system **650**. The water-solvent purification system **650** may be used to transport and introduce one or more solvents, including water and/or steam, into any component in the system which uses solvent, solvent vapor, water, and/or steam. The hydrocarbon stream via line **640** may be recycled back into the system **600**, such as being transferred to the feedstock hydrocarbon source **605**, the deaerator, or components of the system **600**.

[0129] The water-solvent waste stream via line **648** contains a large amount or portion of water or other solvent relative to total solvent concentration within the system **600**. The water-solvent waste stream via line **648** may contain the solvent (e.g., water, steam, organic solvent, organic vapor) in a range from about 90 wt %, about 92 wt %, about 95 wt %, about 96 wt %, or about 97 wt % to about 97.5 wt %, about 98 wt %, about 98.2 wt %, about 98.5 wt %, about 98.8 wt %, about 99 wt %, about 99.2 wt %, about 99.5 wt %, about 99.8 wt %, about 99.9, or greater relative to a total solvent concentration within the system **600**. For example, the water-solvent waste stream via line **648** may contain the solvent (e.g., water, steam, organic solvent, organic vapor) in a range from about 90 wt % to about 99.9 wt %, about 90 wt % to about 99.5 wt %, about 90 wt % to about 99.2 wt %, about 90 wt % to about 99 wt %, about 90 wt % to about 98.8 wt %, about 90 wt % to about 98.5 wt %, about 90 wt % to about 98.2 wt %, about 90 wt % to about 98 wt %, about 90 wt % to about 97.5 wt %, about 90 wt % to about 97 wt %, about 90 wt % to about 96 wt %, about 90 wt % to about 95 wt %, about 90 wt % to about 92 wt %, about 95 wt % to about 99.9 wt %, about 95 wt % to about 99.5 wt %, about 95 wt % to about 99.2 wt %, about 95 wt % to about 99 wt %, about

95 wt % to about 98.8 wt %, about 95 wt % to about 98.5 wt %, about 95 wt % to about 98.2 wt %, about 95 wt % to about 98 wt %, about 95 wt % to about 97.5 wt %, about 95 wt % to about 97 wt %, about 95 wt % to about 96 wt %, about 95 wt % to about 95.5 wt %, about 97 wt % to about 99.9 wt %, about 97 wt % to about 99.5 wt %, about 97 wt % to about 99.2 wt %, about 97 wt % to about 99 wt %, about 97 wt % to about 98.8 wt %, about 97 wt % to about 98.5 wt %, about 97 wt % to about 98.2 wt %, about 97 wt % to about 98 wt %, or about 97 wt % to about 97.5 wt %, relative to a total solvent concentration within the system **600**.

[0130] FIG. 7 depicts a solvent recycling system **700** for purifying and recycling process water, according to one or more embodiments described and discussed herein. In one or more embodiments, the solvent recycling system **700** is used in conjunction with the hydrocarbon purification systems **200**, **300** and/or the system **600**, as described and discussed herein. In one or more examples, the solvent recycling system **700** is used in conjunction with the water-solvent waste stream **275** of the hydrocarbon purification system **200**, the water-solvent purification system **303** of the hydrocarbon purification system **300**, and the water-solvent waste stream via line **648** and/or the water-solvent purification system **650** of the system **600**. The solvent recycling system **700** is an efficient system that recycles most, if not all, of the water or other solvents when purifying the feedstock hydrocarbon.

[0131] The solvent recycling system **700** contains a water-solvent waste stream source **702**. The water-solvent waste stream source **702** contains the water-solvent waste stream which may be direct from the water-solvent waste stream **275** of the hydrocarbon purification system **200**, the water-solvent purification system **303** of the hydrocarbon purification system **300**, and the water-solvent waste stream via line **648** and/or the water-solvent purification system **650** of the system **600**, as described and discussed herein. In some embodiments, the water-solvent waste stream may be flowed via line **704** from the water-solvent waste stream source **702** to a source **706**. The source **706** may store and/or transport the water-solvent waste stream to further reuse in several portions of the hydrocarbon purification systems **200**, **300** and/or the system **600**, such as in the reactors.

[0132] The water-solvent waste stream in source **706** may have a purity of about 95 wt % to 99 wt %. For example, the water-solvent waste stream in source **706** may have a purity of about 95 wt %, about 95.5 wt %, about 96 wt %, about 96.5 wt %, or about 97 wt % to about 97.5 wt %, about 98 wt %, about 98.5 wt %, about 98.8 wt %, or 99 wt %. In some examples, the water-solvent waste stream in source **706** may have a purity in a range from about 95 wt % to 99 wt %, about 96 wt % to 99 wt %, about 97 wt % to 99 wt %, about 97.5 wt % to 99 wt %, about 98 wt % to 99 wt %, about 98.5 wt % to 99 wt %, about 95 wt % to about 98 wt %, about 96 wt % to about 98 wt %, about 97 wt % to about 98 wt %, about 97.5 wt % to about 98 wt %, about 95 wt % to about 97 wt %, or about 96 wt % to about 97 wt %.

[0133] In one or more examples, the source **706** may be one or more of the liquid solvent sources introduced upstream of the laminar flow reactor via lines **305** and/or **307**.

[0134] In other examples, the source **706** may be the recycled water-solvent in line **307** fluidly coupled to the laminar flow reactor **350** and configured to introduce one or more solvents in the hydrocarbon purification system **300**.

[0135] In one or more examples, the source **706** may be the water-solvent purification system **650** and/or is configured to supply solvent to the hydrocarbon source **602** which is fluidly coupled to the laminar flow reactor **610** via line **604** and configured to introduce one or more solvents in the hydrocarbon purification system **600**.

[0136] The water-solvent waste stream in the water-solvent waste stream source **702** may be transported via line **708** to a filtration unit **710** to produce a concentrate via line **716** and a permeate via line **714**. The filtration unit **710** may be or contain one or more of a cross-filtration unit, a leaf filter, filter press, or any combination thereof. The permeate of the water-solvent waste stream via line **714** may be directed to and combined into with the water-solvent waste stream in line **704** and further transported to the source **706**. In other examples, the permeate of the water-solvent waste

stream via line **714** may be introduced to and treated in a reverse osmosis unit **718** to produce a concentrate via line **732** and a permeate via line **720**.

[0137] In some examples, the permeate via line **720** may be transferred to and introduced into a filter unit **724** to produce a purified solvent via line **726**. The filter unit may be of contain one or more activated carbon absorption filters, one or more deionized filters, or any combination thereof. The purified solvent via line **726** may be introduced and stored in the source **728** as a purified solvent. The purified solvent in a source **728** may have a purity of greater than 99.99 wt %. For example, the purified solvent in a source **728** may have a purity of greater than 99.99 wt %, about 99.995 wt %, about 99.999 wt %, about 99.9995 wt %, about 99.9999 wt %, about 99.99995 wt %, about 99.9999 wt %, or greater. In one or more examples, the purified solvent in a source **728** may have a purity in a range from greater than 99.99 wt % to about 99.9999 wt %, greater than 99.99 wt % to about 99.9995 wt %, greater than 99.99 wt % to about 99.999 wt %, greater than 99.99 wt % to about 99.995 wt %, about 99.995 wt % to about 99.9999 wt %, about 99.995 wt % to about 99.9995 wt %, about 99.995 wt % to about 99.999 wt %, about 99.999 wt % to about 99.9999 wt %, or about 99.999 wt % to about 99.9995 wt %.

[0138] In one or more embodiments, the purified solvent stored in the source **728** is the highest purity solvent within the system **700**. The source **728** may store and/or transport the purified solvent to further reuse in any portion or component of the hydrocarbon purification systems **200**, **300** and/or the system **600**, such as in the extraction columns, the reactors, any of the solvent sources.

[0139] In other examples, the permeate via line **720** may be transferred to and introduced into a source **746** as a purified solvent via lines **722**, **744**. The purified solvent in a source **746** may have a purity of greater than 99 wt % to 99.99 wt %. For example, the purified solvent in a source **746** may have a purity of greater than 99 wt %, about 99.1 wt %, about 99.2 wt %, about 99.3 wt %, about 99.4 wt %, about 99.5 wt %, about 99.6 wt %, about 99.7 wt %, about 99.8 wt %, about 99.9 wt %, about 99.95 wt %, or 99.99 wt %. In one or more examples, the purified solvent in a source **746** may have a purity of greater than 99 wt % to 99.99 wt %, about 99.2 wt % to 99.99 wt %, about 99.4 wt % to 99.99 wt %, about 99.5 wt % to 99.99 wt %, about 99.6 wt % to 99.99 wt %, about 99.8 wt % to 99.99 wt %, about 99.9 wt % to 99.99 wt %, or about 99.95 wt % to 99.99 wt %.

[0140] In one or more embodiments, the purified solvent stored in the source **746** has an intermediate purity within the system **700**. The purified solvent stored in the source **746** has a purity greater than the water-solvent waste stream in source **706** and less than the purified solvent stored in the source **728**. The source **746** may store and/or transport the purified solvent to further reuse in several portions of the hydrocarbon purification systems **200**, **300** and/or the system **600**, such as in the extraction columns and the reactors.

[0141] In one or more examples, the source **728** may be one or more of the primary solvent source **225a**, **225b** fluidly coupled to and upstream of the upper portion of the laminar flow reactor **230** in the hydrocarbon purification system **200**. The primary solvent source **225a**, **225b** may supply and introduce the purified solvent into the laminar flow reactor **230**. In some examples, the source **728** may introduce the purified solvent into the separation unit **245** in the hydrocarbon purification system **200**.

[0142] In other examples, the source **728** may be the primary solvent source **356** via line **358** fluidly coupled to the laminar flow reactor **350** and configured to introduce one or more solvents in the hydrocarbon purification system **300**. In some examples, the source **728** may be the recycled feedstock hydrocarbon in line **307** fluidly coupled to the laminar flow reactor **350** and configured to introduce one or more solvents in the hydrocarbon purification system **300**. In other examples, the source **728** may introduce the purified solvent into the laminar flow reactor **350** in the hydrocarbon purification system **300**.

[0143] In one or more examples, the source **728** may be the water-solvent purification system **650**

and/or is configured to supply solvent to the hydrocarbon source **602** which is fluidly coupled to the laminar flow reactor **610** via line **604** and configured to introduce one or more solvents in the hydrocarbon purification system **600**. In some examples, the source **728** may be the water-solvent purification system **650** and/or is configured to supply solvent to the primary solvent source **606** which is fluidly coupled to the laminar flow reactor **610** via line **608** and configured to introduce one or more solvents in the hydrocarbon purification system **600**. In other examples, the source **728** may introduce the purified solvent into the separation unit **622** in the hydrocarbon purification system **600**.

[0144] In one or more examples, the source **746** may introduce the purified solvent into the separation unit **245** in the hydrocarbon purification system **200**.

[0145] In other examples, the source **746** may be the recycled feedstock hydrocarbon in line **307** fluidly coupled to the laminar flow reactor **350** and configured to introduce one or more solvents in the hydrocarbon purification system **300**. In other examples, the source **746** may introduce the purified solvent into the laminar flow reactor **350** in the hydrocarbon purification system **300**.

[0146] In one or more examples, the source **746** may be the water-solvent purification system **650** and/or is configured to supply solvent to the hydrocarbon source **602** which is fluidly coupled to the laminar flow reactor **610** via line **604** and configured to introduce one or more solvents in the hydrocarbon purification system **600**. In some examples, the source **746** may introduce the purified solvent into the separation unit **622** in the hydrocarbon purification system **600**.

[0147] The concentrate of the water-solvent waste stream via line **716** may be transferred to and introduced into a dryer unit **734**. Also, the concentrate via line **732** may be transferred to and introduced into the dryer unit **734**. The concentrates via line **716** and/or via line **732** may independently be dried or may be combined and then dried by the dryer unit **734** to produce a distilled solvent stream via line **736** and a byproducts stream via line **740**. The distilled solvent stream via line **736** is transferred to and stored in the source **738**, and then transferred to the source **746**. The byproducts stream via line **740** is transferred to a byproducts source **742**. The byproducts stream may be a solid and/or have a desired moisture concentration. In one or more examples, one or more byproducts from the byproducts stream via line **740** is combined and mixed with one or more products within a mixer or other device. The product may be or contain one or more of a processed grain, vegetable meal, fruit meal, protein meal, meat, stover, hay, forage, or any combination thereof. The mixer may be or contain one or more of a tumbler mixer, paddle mixer, cone mixer, screw mixer, or any combination thereof.

Example

[0148] In one or more examples, the hydrocarbon purification systems described and discussed herein, including the hydrocarbon purification systems **200**, **300**) and the processes and methods described and discussed herein, including the method **100**, have been used to achieved the fat and oil purification (pretreatment) results provided as in Table 1. Most notable is purifying fat and oil to the level of non-detectable (ND) concentrations and/or very low concentrations for phosphorus, total metals, and chloride.

TABLE-US-00001 TABLE 1 Purified Hydrocarbons Hydrocarbon Source P Total Cl N (ppm) Metals (ppm) (ppm) Start (S), Final (F) S F S F S F S F S F 300 ppm P SBO 357 <1 315 <1 1 ND 150 50 500 ppm P SBO 589 <1 542 ND 1 1 180 74 1000 ppm P SBO 1100 <2 1095 <1 <2 <2 343 125 DCO 4 <0.5 26 ND 3 1 27 27 Low-Grade DCO 397 2 687 4 12 ND 270 135 SBO Blend w/Tallow & YG 87 <1 NA <1 NA <2 NA 43 Beef Tallow 104 ND 132 <4 70 <2 155 155 Poultry Fat 320 <1.5 156 <8 10 <2 680 580 Canola Oil 58 <1.5 28 ND <1 <1 35 26 Camelina Oil 27 ND 45 4 ND ND 12 9 Used Cooking Oil 7.5 <1.5 11 <2 33 <15 121 100 NOTES: SBO = soybean oil DCO = ethanol distiller's corn oil YG = yellow grease NA = not available ND = not detected Total Metals include Na, K, Mg, Ca, Fe

Exemplary Embodiments

[0149] The present disclosure provides, among others, the following embodiments, each of which

may be considered as optionally including any alternate embodiments per one or more of the following Clauses 1-64:

[0150] Clause 1. A method of purifying a hydrocarbon, comprising: flowing a feedstock hydrocarbon stream through a heating unit to produce a heated hydrocarbon stream, wherein the feedstock hydrocarbon stream has an initial concentration of a contaminant and comprises one or more of an oil, a fat, a grease, or any combination thereof; combining the heated hydrocarbon stream and a primary solvent in a laminar flow reactor to produce a hydrocarbon-solvent stream; flowing the hydrocarbon-solvent stream through a cooling unit to produce a cooled hydrocarbon-solvent stream; and introducing the cooled hydrocarbon-solvent stream into a separation unit to produce a scrubbed hydrocarbon stream and a solvent stream, wherein the scrubbed hydrocarbon stream has a final concentration of the contaminant, and wherein the final concentration of the contaminant is less than the initial concentration of the contaminant.

[0151] Clause 2. A method of purifying a hydrocarbon, comprising: flowing a feedstock hydrocarbon stream through a deaerator to degas the feedstock hydrocarbon stream, wherein the feedstock hydrocarbon stream has an initial concentration of a contaminant and comprises soybean oil, corn oil, canola oil, camelina oil, yellow grease, choice white grease, beef tallow, poultry fat, used cooking oil, tall oil, pyrolysis oil, or any combination thereof; flowing the degassed feedstock hydrocarbon stream through a heating unit to produce a heated hydrocarbon stream; combining the heated hydrocarbon stream and steam in a laminar flow reactor to produce an aqueous hydrocarbon stream; flowing the aqueous hydrocarbon stream through a cooling unit to produce a cooled aqueous hydrocarbon stream; introducing the cooled aqueous hydrocarbon stream into a vertical extraction column to produce a scrubbed hydrocarbon stream and an aqueous stream by a countercurrent liquid-liquid extraction, wherein the aqueous stream comprises the contaminant; and flowing the scrubbed hydrocarbon stream through a first finishing unit to produce a purified hydrocarbon stream, wherein the purified hydrocarbon stream has a final concentration of the contaminant, and wherein the initial concentration of the contaminant is about 40 times or greater than the final concentration of the contaminant.

[0152] Clause 3. A method of purifying a hydrocarbon, comprising: flowing a feedstock hydrocarbon stream through a heating unit to produce a heated hydrocarbon stream, wherein the feedstock hydrocarbon stream has an initial concentration of a contaminant and comprises one or more of an oil, a fat, a grease, or any combination thereof; combining the heated hydrocarbon stream and a primary solvent in a laminar flow reactor to produce a hydrocarbon-solvent stream, wherein producing the hydrocarbon-solvent stream further comprises: introducing a flow of the heated hydrocarbon stream into a headspace in an upper portion of the laminar flow reactor, wherein the flow of the heated hydrocarbon stream is completely or substantially free of turbulence, and wherein the heated hydrocarbon stream is at a first temperature; introducing a flow of the primary solvent into the headspace in the upper portion of the laminar flow reactor, wherein the flow of the primary solvent is completely or substantially free of turbulence, and wherein the primary solvent is at a second temperature greater than the first temperature; and condensing the primary solvent into the heated hydrocarbon stream to produce an intermediate stream; and flowing the intermediate stream through a reaction zone disposed in a lower portion of the laminar flow reactor to produce the hydrocarbon-solvent stream; introducing the hydrocarbon-solvent stream into a separation unit to produce a scrubbed hydrocarbon stream and a solvent stream, wherein the solvent stream comprises the contaminant; and flowing the scrubbed hydrocarbon stream through a first finishing unit to produce a purified hydrocarbon stream, wherein the purified hydrocarbon stream has a final concentration of the contaminant, and wherein the final concentration of the contaminant is less than the initial concentration of the contaminant.

[0153] Clause 4. A system for purifying a hydrocarbon, comprising: a deaerator fluidly coupled to and downstream of a feedstock hydrocarbon source, wherein the feedstock hydrocarbon source is configured to contain a feedstock hydrocarbon having an initial concentration of a contaminant and

comprising one or more of an oil, a fat, a grease, or any combination thereof; a heating portion of a recuperator fluidly coupled to and downstream of the deaerator; an additive source fluidly coupled to and downstream of the deaerator, wherein the additive source is configured to contain an additive comprising a hydrolyzing agent, an acid, a base, a salt, a chelating agent, a polar solvent, a non-polar solvent, or any combination thereof; a laminar flow reactor comprising an upper portion opposite a lower portion, and wherein the upper portion of the laminar flow reactor is fluidly coupled to and downstream of the heating portion of the recuperator; a primary solvent source fluidly coupled to and upstream of the upper portion of the laminar flow reactor; a cooling portion of the recuperator fluidly coupled to and downstream of the lower portion of the laminar flow reactor; a pressure reduction device fluidly coupled to and downstream of the cooling portion of the recuperator; a separation unit fluidly coupled to and downstream of the pressure reduction device, wherein the separation unit comprises a scrubbed hydrocarbon stream outlet and a solvent stream outlet; a first finishing unit fluidly coupled to and downstream of the scrubbed hydrocarbon stream outlet, wherein the first finishing unit comprises a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof, and wherein the first finishing unit comprises a purified hydrocarbon stream outlet configured to provide a purified hydrocarbon having a final concentration of the contaminant of at least 10 times less than the initial concentration of the contaminant; and a second finishing unit fluidly coupled to and downstream of the solvent stream outlet, wherein the second finishing unit comprises a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof.

[0154] Clause 5. The method or the system according to any one of Clauses 1-4, wherein the primary solvent comprises a polar protic solvent, a polar aprotic solvent, a nonpolar hydrocarbon solvent, a nonpolar ether solvent, a nonpolar chlorocarbon solvent, or any combination thereof.

[0155] Clause 6. The method or the system according to any one of Clauses 1-5, wherein the primary solvent comprises water, steam, or a combination thereof.

[0156] Clause 7. The method or the system according to any one of Clauses 1-6, wherein the feedstock hydrocarbon stream comprises soybean oil, corn oil, canola oil, camelina oil, yellow grease, choice white grease, beef tallow, poultry fat, used cooking oil, tall oil, pyrolysis oil, or any combination thereof.

[0157] Clause 8. The method or the system according to any one of Clauses 1-7, wherein the feedstock hydrocarbon stream further comprises a polymeric material, a plastic material, or any combination thereof.

[0158] Clause 9. The method or the system according to any one of Clauses 1-8, wherein the contaminant comprises one or more of a halide (e.g., Cl, F, Br, I), phosphorous, sulfur, nitrogen, a gum or lecithin, an alkali metal, a metalloid, a heavy metal, or any combination thereof.

[0159] Clause 10. The method or the system according to any one of Clauses 1-9, prior to flowing the feedstock hydrocarbon stream through the heating unit, further comprising flowing the feedstock hydrocarbon stream through a deaerator to degas the feedstock hydrocarbon stream.

[00160] 11. The method or the system according to any one of Clauses 1-10, further comprising combining an additive into the feedstock hydrocarbon stream, the heated hydrocarbon stream, or both the feedstock hydrocarbon stream and the heated hydrocarbon stream, wherein the additive comprises a hydrolyzing agent, an acid, a base, a salt, a chelating agent, a polar solvent, a non-polar solvent, or any combination thereof.

[0160] Clause 12. The method or the system according to any one of Clauses 1-11, wherein the additive comprises one or more of acetic acid, ascorbic acid, citric acid, hydrochloric acid, fumaric acid, glucaric acid, gluconic acid, glutamic acid, hydrochloric acid, lactic acid, malic acid, oxalic acid, phosphoric acid, propionic acid, sulfuric acid, tartaric acid, salts thereof, or any combination thereof.

[0161] Clause 13. The method or the system according to any one of Clauses 1-12, further

comprising introducing and combining the heated hydrocarbon stream, an additive, and the primary solvent in the laminar flow reactor to produce the hydrocarbon-solvent stream.

[0162] Clause 14. The method or the system according to any one of Clauses 1-13, wherein the heating unit comprises a recuperator, a steam heater, an electric heater, a fuel combustion heater, or any combination thereof.

[0163] Clause 15. The method or the system according to any one of Clauses 1-14, wherein the heated hydrocarbon stream is produced by flowing the feedstock hydrocarbon stream through a heating portion of a recuperator, and then at least one of a steam heater, an electric heater, a fuel combustion heater, or any combination thereof.

[0164] Clause 16. The method or the system according to any one of Clauses 1-15, wherein the heated hydrocarbon stream is flowed into a primary solvent pocket within an upper portion of the laminar flow reactor, and wherein the primary solvent pocket comprises the primary solvent; and/or optionally, wherein the primary solvent is combined with the heated hydrocarbon stream prior to being introduced into the laminar flow reactor.

[0165] Clause 17. The method or the system according to any one of Clauses 1-16, wherein the primary solvent is introduced into the laminar flow reactor through an injection device, and wherein the primary solvent has a pressure drop across the injection device in a range from about 0.0001 psi to about 40 psi.

[0166] Clause 18. The method or the system according to any one of Clauses 1-17, wherein the primary solvent comprises steam, wherein a first source of the steam is combined with the heated hydrocarbon stream prior to being introduced into the laminar flow reactor, a combination of the first source of the steam and the heated hydrocarbon stream is flowed into a steam pocket within an upper portion of the laminar flow reactor, and wherein the steam pocket comprises a second source of the steam.

[0167] Clause 19. The method or the system according to any one of Clauses 1-18, wherein the laminar flow reactor is a liquid-filled laminar flow reactor comprising an inflow distributor assembly, an outflow header assembly, a packing assembly, or any combination thereof.

[0168] Clause 20. The method or the system according to any one of Clauses 1-19, wherein the laminar flow reactor is a vapor-infused laminar flow reactor comprising an inflow distributor assembly, a packing assembly, or any combination thereof, and optionally wherein the vapor-infused laminar flow contains steam and/or one or more organic solvents.

[0169] Clause 21. The method or the system according to any one of Clauses 1-20, wherein the cooled hydrocarbon-solvent stream is produced by flowing the hydrocarbon-solvent stream a recuperator, a coolant circulation system, a refrigeration system, or a combination thereof.

[0170] Clause 22. The method or the system according to any one of Clauses 1-21, wherein the cooled hydrocarbon-solvent stream is produced by flowing the hydrocarbon-solvent stream through a cooling portion of a recuperator, and wherein the heated hydrocarbon stream is produced by flowing the feedstock hydrocarbon stream through a heating portion of the recuperator.

[0171] Clause 23. The method or the system according to any one of Clauses 1-22, further comprising flowing the cooled hydrocarbon-solvent stream through a pressure reduction device, wherein the cooled hydrocarbon-solvent stream is at a first pressure entering the pressure reduction device and at a second pressure exiting the pressure reduction device, and wherein the first pressure is at least 10 times greater than the second pressure.

[0172] Clause 24. The method or the system according to any one of Clauses 1-23, wherein the first pressure is in a range from about 500 psi to about 1,500 psi, and the second pressure is in a range from about 1 psi to about 500 psi, and wherein the second pressure is at least one half of the value of the first pressure.

[0173] Clause 25. The method or the system according to any one of Clauses 1-24, wherein the pressure reduction device is a low-shear pressure reduction device, a cyclonic pressure reduction device, a multi-stage pressure reduction device, or any combination thereof.

[0174] Clause 26. The method or the system according to any one of Clauses 1-25, wherein the separation unit comprises an extraction column, a vertical extraction column, a horizontal extraction column, a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof.

[0175] Clause 27. The method or the system according to any one of Clauses 1-26, wherein the separation unit comprises a vertical extraction column.

[0176] Clause 28. The method or the system according to any one of Clauses 1-27, further comprising: introducing the cooled hydrocarbon-solvent stream into a lower portion of the vertical extraction column; introducing a solvent or water stream into an upper portion of the vertical extraction column; performing a countercurrent liquid-liquid extraction by flowing the cooled hydrocarbon-solvent stream toward the upper portion of the vertical extraction column and flowing the solvent or water stream toward the lower portion of the vertical extraction column; and flowing the scrubbed hydrocarbon stream from the upper portion of the vertical extraction column, and flowing the solvent stream from the lower portion of the vertical extraction column.

[0177] Clause 29. The method or the system according to any one of Clauses 1-28, wherein the vertical extraction column comprises a packing assembly.

[0178] Clause 30. The method or the system according to any one of Clauses 1-29, wherein producing the hydrocarbon-solvent stream further comprises: introducing a flow of the heated hydrocarbon stream into a headspace in an upper portion of the laminar flow reactor, wherein the flow of the heated hydrocarbon stream is completely or substantially free of turbulence, and wherein the heated hydrocarbon stream is at a first temperature; introducing a flow of the primary solvent into the headspace in the upper portion of the laminar flow reactor, wherein the flow of the primary solvent is completely or substantially free of turbulence, and wherein the primary solvent is at a second temperature greater than the first temperature; and condensing the primary solvent into the heated hydrocarbon stream to produce an intermediate stream; and flowing the intermediate stream through a reaction zone disposed in a lower portion of the laminar flow reactor to produce the hydrocarbon-solvent stream.

[0179] Clause 31. The method or the system according to any one of Clauses 1-30, wherein the primary solvent comprises a polar protic solvent, a polar aprotic solvent, a nonpolar hydrocarbon solvent, a nonpolar ether solvent, a nonpolar chlorocarbon solvent, or any combination thereof; and/or wherein the primary solvent comprises water.

[0180] Clause 32. The method or the system according to any one of Clauses 1-31, wherein a liquid phase within the headspace of the laminar flow reactor has a Reynolds number in a range from about 0 to 2,300, or wherein each of the intermediate stream and/or the hydrocarbon-solvent stream independently has a Reynolds number in a range from about 0 to 2,300.

[0181] Clause 33. The method or the system according to any one of Clauses 1-32, further comprising flowing the scrubbed hydrocarbon stream through a first finishing unit to produce a purified hydrocarbon stream, wherein the purified hydrocarbon stream has the final concentration of the contaminant or a further reduced concentration of the contaminant.

[0182] Clause 34. The method or the system according to any one of Clauses 1-33, wherein the first finishing unit comprises a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof.

[0183] Clause 35. The method or the system according to any one of Clauses 1-34, further comprising flowing an aqueous waste stream from the first finishing unit to a water purification system, wherein the aqueous waste stream comprises at least a portion of the contaminant.

[0184] Clause 36. The method or the system according to any one of Clauses 1-35, wherein the initial concentration of the contaminant is about 40 times, about 100 times, or greater than the final concentration of the contaminant.

[0185] Clause 37. The method or the system according to any one of Clauses 1-36, wherein the contaminant comprises phosphorus, the initial concentration of the phosphorous is 100 ppm or

greater, and the final concentration of the phosphorus is less than 5 ppm, such as less than 2 ppm, or less than 1 ppm.

[0186] Clause 38. The method or the system according to any one of Clauses 1-37, wherein the contaminant comprises total metals, the initial concentration of the total metals is 40 ppm or greater, and the final concentration of the total metals is less than 5 ppm, less than 2 ppm, or less than 1 ppm, and optionally wherein the total metals contains sodium, potassium, magnesium, calcium, iron, or any combination thereof.

[0187] Clause 39. The method or the system according to any one of Clauses 1-38, further comprising flowing the solvent stream from the separation unit through a second finishing unit to produce a secondary hydrocarbon stream and a secondary solvent stream, wherein each of the solvent stream and the secondary solvent stream independently comprises water.

[0188] Clause 40. The method or the system according to any one of Clauses 1-39, wherein the second finishing unit comprises a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof.

[0189] Clause 41. The method or the system according to any one of Clauses 1-40, wherein the secondary hydrocarbon stream is combined into the feedstock hydrocarbon stream, the feedstock hydrocarbon stream, or a combination thereof.

[0190] Clause 42. The method or the system according to any one of Clauses 1-41, wherein the secondary solvent stream is flowed to a water purification system, the laminar flow reactor, the separation unit, or a combination thereof.

[0191] Clause 43. The method or the system according to any one of Clauses 1-42, wherein each of the secondary solvent stream and/or the solvent stream is an aqueous stream, and wherein the aqueous stream is concentrated and/or dried and then blended with a product in a mixer, and wherein the product comprises a processed grain, vegetable meal, fruit meal, protein meal, meat, stover, hay, forage, or any combination thereof, and optionally wherein the mixer is or contains a tumbler mixer, paddle mixer, cone mixer, screw mixer, or any combination thereof.

[0192] Clause 44. The method or the system according to any one of Clauses 1-43, wherein the feedstock hydrocarbon stream contains a plastic or polymeric material and pyrolysis oils.

[0193] Clause 45. The method or the system according to any one of Clauses 1-44, wherein the primary solvent comprises a polar protic solvent, a polar aprotic solvent, a nonpolar hydrocarbon solvent, a nonpolar ether solvent, a nonpolar chlorocarbon solvent, or any combination thereof.

[0194] Clause 46. The method or the system according to any one of Clauses 1-45, wherein the primary solvent comprises water.

[0195] Clause 47. The method or the system according to any one of Clauses 1-46, wherein the primary solvent is introduced into the headspace through an injection device, and wherein the primary solvent has a pressure drop across the injection device in a range from about 0.0001 psi to about 80 psi, or about 0.0001 psi to about 60 psi, or about 0.0001 psi to about 40 psi, or about 0.0001 psi to about 20 psi, or about 0.0001 psi to about 10 psi, or about 0.0001 psi to about 5 psi, or about 0.0001 psi to about 1 psi, or about 0.0001 psi to about 0.1 psi.

[0196] Clause 48. The method or the system according to any one of Clauses 1-47, wherein the laminar flow reactor is maintained at a pressure in a range from about 1 psi to about 50 psi of a saturation pressure of the primary solvent at a target reaction temperature.

[0197] Clause 49. The method or the system according to any one of Clauses 1-48, wherein a reaction temperature in the laminar flow reactor is in a range from about 50° C. to about 400° C.

[0198] Clause 50. The method or the system according to any one of Clauses 1-49, wherein a second temperature in the laminar flow reactor is in a range from about 150° C. to about 300° C., or about 200° C. to about 275° C.

[0199] Clause 51. The method or the system according to any one of Clauses 1-50, wherein the primary solvent is introduced as a superheated vapor, a saturated vapor, or a subcooled vapor.

[0200] Clause 52. The method or the system according to any one of Clauses 1-51, wherein each of

a liquid phase within the headspace of the laminar flow reactor and/or the intermediate stream and/or the hydrocarbon-solvent stream independently has a Reynolds number in a range from about 0 to 2,300.

[0201] Clause 53. The method or the system according to any one of Clauses 1-52, wherein each of a liquid phase within the headspace of the laminar flow reactor and/or the intermediate stream and/or the hydrocarbon-solvent stream independently has a Reynolds number in a range from about 0 to less than 2,000.

[0202] Clause 54. The method or the system according to any one of Clauses 1-53, wherein the primary solvent source is a steam source configured to store and disperse steam.

[0203] Clause 55. The method or the system according to any one of Clauses 1-54, wherein the laminar flow reactor is a liquid-filled laminar flow reactor comprising an inflow distributor assembly, an outflow header assembly, a packing assembly, or any combination thereof.

[0204] Clause 56. The method or the system according to any one of Clauses 1-55, wherein the laminar flow reactor comprises an inflow distributor assembly in the upper portion and an outflow header assembly in the lower portion.

[0205] Clause 57. The method or the system according to any one of Clauses 1-56, wherein the laminar flow reactor is a vapor-infused laminar flow reactor comprising an inflow distributor assembly, a packing assembly, or any combination thereof.

[0206] Clause 58. The method or the system according to any one of Clauses 1-57, wherein the pressure reduction device is a low-shear pressure reduction device, a cyclonic pressure reduction device, a multi-stage pressure reduction device, or any combination thereof.

[0207] Clause 59. The method or the system according to any one of Clauses 1-58, wherein the separation unit comprises an extraction column, a vertical extraction column, a horizontal extraction column, a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof.

[0208] Clause 60. The method or the system according to any one of Clauses 1-59, wherein the separation unit comprises a vertical extraction column.

[0209] Clause 61. The method or the system according to any one of Clauses 1-60, wherein the vertical extraction column comprises: an upper portion opposite a lower portion; an upper inlet in the upper portion configured to receive a solvent or water stream; a lower inlet in the lower portion coupled to and downstream of the pressure reduction device, and wherein the lower inlet configured to receive a cooled hydrocarbon-solvent stream; a central region disposed between the upper and lower portions and configured to perform a countercurrent liquid-liquid extraction by flowing the cooled hydrocarbon-solvent stream toward the upper portion of the vertical extraction column and flowing the solvent or water stream toward the lower portion of the vertical extraction column; a scrubbed hydrocarbon stream outlet disposed in the upper portion of the vertical extraction column; and a solvent stream outlet disposed in the lower portion of the vertical extraction column.

[0210] Clause 62. The method or the system according to any one of Clauses 1-61, wherein the central region comprises a packing assembly.

[0211] Clause 63. The method or the system according to any one of Clauses 1-62, further comprising a supplemental heating unit fluidly coupled to and downstream of the deaerator and fluidly coupled to and upstream of the laminar flow reactor.

[0212] Clause 64. The method or the system according to any one of Clauses 1-63, wherein the supplemental heating unit comprises a second recuperator, a steam heater, an electric heater, a fuel combustion heater, or any combination thereof.

[0213] While the foregoing is directed to embodiments of the disclosure, other and further embodiments may be devised without departing from the basic scope thereof, and the scope thereof is determined by the claims that follow. All documents described herein are incorporated by reference herein, including any priority documents and/or testing procedures to the extent they are

not inconsistent with this text. As is apparent from the foregoing general description and the specific embodiments, while forms of the present disclosure have been illustrated and described, various modifications may be made without departing from the spirit and scope of the present disclosure. Accordingly, it is not intended that the present disclosure be limited thereby. Likewise, the term “comprising” is considered synonymous with the term “including” for purposes of United States law. Likewise, whenever a composition, an element, or a group of elements is preceded with the transitional phrase “comprising”, it is understood that the same composition or group of elements with transitional phrases “consisting essentially of”, “consisting of”, “selected from the group of consisting of”, or “is” preceding the recitation of the composition, element, or elements and vice versa, are contemplated. As used herein, the term “about” refers to a $\pm 10\%$ variation from the nominal value. It is to be understood that such a variation may be included in any value provided herein.

[0214] Certain embodiments and features have been described using a set of numerical upper limits and a set of numerical lower limits. It should be appreciated that ranges including the combination of any two values, e.g., the combination of any lower value with any upper value, the combination of any two lower values, and/or the combination of any two upper values are contemplated unless otherwise indicated. Certain lower limits, upper limits and ranges appear in one or more claims below.

Claims

1. A method of purifying a hydrocarbon, comprising: flowing a feedstock hydrocarbon stream through a heating unit to produce a heated hydrocarbon stream, wherein the feedstock hydrocarbon stream has an initial concentration of a contaminant and comprises one or more of an oil, a fat, a grease, or any combination thereof; combining the heated hydrocarbon stream and a primary solvent in a laminar flow reactor to produce a hydrocarbon-solvent stream; flowing the hydrocarbon-solvent stream through a cooling unit to produce a cooled hydrocarbon-solvent stream; and introducing the cooled hydrocarbon-solvent stream into a separation unit to produce a scrubbed hydrocarbon stream and a solvent stream, wherein the scrubbed hydrocarbon stream has a final concentration of the contaminant, and wherein the final concentration of the contaminant is less than the initial concentration of the contaminant.
2. The method of claim 1, wherein the primary solvent comprises water, steam, or a combination thereof.
3. The method of claim 1, wherein the feedstock hydrocarbon stream comprises soybean oil, corn oil, canola oil, camelina oil, yellow grease, choice white grease, beef tallow, poultry fat, used cooking oil, tall oil, pyrolysis oil, or any combination thereof.
4. The method of claim 1, wherein the feedstock hydrocarbon stream further comprises a polymeric material, a plastic material, or any combination thereof.
5. The method of claim 1, wherein the contaminant comprises one or more of a halide, phosphorous, sulfur, nitrogen, a gum or lecithin, an alkali metal, a metalloid, a heavy metal, or any combination thereof.
6. The method of claim 1, prior to flowing the feedstock hydrocarbon stream through the heating unit, further comprising flowing the feedstock hydrocarbon stream through a deaerator to degas the feedstock hydrocarbon stream.
7. The method of claim 1, further comprising combining an additive into the feedstock hydrocarbon stream, the heated hydrocarbon stream, or both the feedstock hydrocarbon stream and the heated hydrocarbon stream, wherein the additive comprises a hydrolyzing agent, an acid, a base, a salt, a chelating agent, a polar solvent, a non-polar solvent, or any combination thereof.
8. The method of claim 7, wherein the additive comprises one or more of acetic acid, ascorbic acid, citric acid, hydrochloric acid, fumaric acid, glucaric acid, gluconic acid, glutamic acid,

hydrochloric acid, lactic acid, malic acid, oxalic acid, phosphoric acid, propionic acid, sulfuric acid, tartaric acid, salts thereof, or any combination thereof.

9. The method of claim 1, further comprising introducing and combining the heated hydrocarbon stream, an additive, and the primary solvent in the laminar flow reactor to produce the hydrocarbon-solvent stream.

10. The method of claim 1, wherein the heated hydrocarbon stream is flowed into a primary solvent pocket within an upper portion of the laminar flow reactor, and wherein the primary solvent pocket comprises the primary solvent.

11. The method of claim 1, wherein the primary solvent is combined with the heated hydrocarbon stream prior to being introduced into the laminar flow reactor.

12. The method of claim 1, wherein the primary solvent comprises steam, wherein a first source of the steam is combined with the heated hydrocarbon stream prior to being introduced into the laminar flow reactor, a combination of the first source of the steam and the heated hydrocarbon stream is flowed into a steam pocket within an upper portion of the laminar flow reactor, and wherein the steam pocket comprises a second source of the steam.

13. The method of claim 1, wherein the laminar flow reactor is a liquid-filled laminar flow reactor comprising an inflow distributor assembly, an outflow header assembly, a packing assembly, or any combination thereof.

14. The method of claim 1, wherein the laminar flow reactor is a vapor-infused laminar flow reactor comprising an inflow distributor assembly, a packing assembly, or any combination thereof.

15. The method of claim 1, further comprising flowing the cooled hydrocarbon-solvent stream through a pressure reduction device, wherein the cooled hydrocarbon-solvent stream is at a first pressure entering the pressure reduction device and at a second pressure exiting the pressure reduction device, and wherein the first pressure is in a range from about 500 psi to about 1,500 psi, and the second pressure is in a range from about 1 psi to about 500 psi, and wherein the second pressure is at least one half of the value of the first pressure.

16. The method of claim 1, wherein the separation unit comprises an extraction column, a vertical extraction column, a horizontal extraction column, a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof.

17. The method of claim 1, wherein the separation unit comprises a vertical extraction column.

18. The method of claim 17, further comprising: introducing the cooled hydrocarbon-solvent stream into a lower portion of the vertical extraction column; introducing a solvent or water stream into an upper portion of the vertical extraction column; performing a countercurrent liquid-liquid extraction by flowing the cooled hydrocarbon-solvent stream toward the upper portion of the vertical extraction column and flowing the solvent or water stream toward the lower portion of the vertical extraction column; and flowing the scrubbed hydrocarbon stream from the upper portion of the vertical extraction column, and flowing the solvent stream from the lower portion of the vertical extraction column.

19. The method of claim 17, wherein the vertical extraction column comprises a packing assembly.

20. The method of claim 1, wherein producing the hydrocarbon-solvent stream further comprises: introducing a flow of the heated hydrocarbon stream into a headspace in an upper portion of the laminar flow reactor, wherein the flow of the heated hydrocarbon stream is completely or substantially free of turbulence, and wherein the heated hydrocarbon stream is at a first temperature; introducing a flow of the primary solvent into the headspace in the upper portion of the laminar flow reactor, wherein the flow of the primary solvent is completely or substantially free of turbulence, and wherein the primary solvent is at a second temperature greater than the first temperature; and condensing the primary solvent into the heated hydrocarbon stream to produce an intermediate stream; and flowing the intermediate stream through a reaction zone disposed in a lower portion of the laminar flow reactor to produce the hydrocarbon-solvent stream.

21. The method of claim 20, wherein each of a liquid phase within the headspace of the laminar

flow reactor and/or the intermediate stream and/or the hydrocarbon-solvent stream independently has a Reynolds number in a range from about 0 to 2,300.

22. The method of claim 1, further comprising flowing the scrubbed hydrocarbon stream through a first finishing unit to produce a purified hydrocarbon stream, wherein the purified hydrocarbon stream has the final concentration of the contaminant or a further reduced concentration of the contaminant.

23. The method of claim 1, wherein the initial concentration of the contaminant is about 40 times or greater than the final concentration of the contaminant.

24. The method of claim 1, wherein the contaminant comprises phosphorus, the initial concentration of the phosphorous is 100 ppm or greater, and the final concentration of the phosphorus is less than 5 ppm, and/or wherein the contaminant comprises total metals, the initial concentration of the total metals is 40 ppm or greater, and the final concentration of the total metals is less than 5 ppm.

25. The method of claim 1, wherein the solvent stream is an aqueous stream, and wherein the aqueous stream is concentrated and/or dried and then blended with a product in a mixer, and wherein the product comprises a processed grain, vegetable meal, fruit meal, protein meal, meat, stover, hay, forage, or any combination thereof.

26. The method of claim 1, further comprising flowing the solvent stream from the separation unit through a second finishing unit to produce a secondary hydrocarbon stream and a secondary solvent stream, wherein each of the solvent stream and the secondary solvent stream independently comprises water.

27. The method of claim 26, wherein the secondary hydrocarbon stream is combined into the feedstock hydrocarbon stream, the feedstock hydrocarbon stream, or a combination thereof.

28. The method of claim 26, wherein the secondary solvent stream is flowed to a water purification system, the laminar flow reactor, the separation unit, or a combination thereof.

29. The method of claim 26, wherein the secondary solvent stream is an aqueous stream, and wherein the aqueous stream is concentrated and/or dried and then blended with a product in a mixer, and wherein the product comprises a processed grain, vegetable meal, fruit meal, protein meal, meat, stover, hay, forage, or any combination thereof.

30. A method of purifying a hydrocarbon, comprising: flowing a feedstock hydrocarbon stream through a deaerator to degas the feedstock hydrocarbon stream, wherein the feedstock hydrocarbon stream has an initial concentration of a contaminant and comprises soybean oil, corn oil, canola oil, camelina oil, yellow grease, choice white grease, beef tallow, poultry fat, used cooking oil, tall oil, pyrolysis oil, or any combination thereof; flowing the degassed feedstock hydrocarbon stream through a heating unit to produce a heated hydrocarbon stream; combining the heated hydrocarbon stream and steam in a laminar flow reactor to produce an aqueous hydrocarbon stream; flowing the aqueous hydrocarbon stream through a cooling unit to produce a cooled aqueous hydrocarbon stream; introducing the cooled aqueous hydrocarbon stream into a vertical extraction column to produce a scrubbed hydrocarbon stream and an aqueous stream by a countercurrent liquid-liquid extraction, wherein the aqueous stream comprises the contaminant; and flowing the scrubbed hydrocarbon stream through a first finishing unit to produce a purified hydrocarbon stream, wherein the purified hydrocarbon stream has a final concentration of the contaminant, and wherein the initial concentration of the contaminant is about 40 times or greater than the final concentration of the contaminant.

31. A method of purifying a hydrocarbon, comprising: flowing a feedstock hydrocarbon stream through a heating unit to produce a heated hydrocarbon stream, wherein the feedstock hydrocarbon stream has an initial concentration of a contaminant and comprises one or more of an oil, a fat, a grease, or any combination thereof; combining the heated hydrocarbon stream and a primary solvent in a laminar flow reactor to produce a hydrocarbon-solvent stream, wherein producing the hydrocarbon-solvent stream further comprises: introducing a flow of the heated hydrocarbon

stream into a headspace in an upper portion of the laminar flow reactor, wherein the flow of the heated hydrocarbon stream is completely or substantially free of turbulence, and wherein the heated hydrocarbon stream is at a first temperature; introducing a flow of the primary solvent into the headspace in the upper portion of the laminar flow reactor, wherein the flow of the primary solvent is completely or substantially free of turbulence, and wherein the primary solvent is at a second temperature greater than the first temperature; and condensing the primary solvent into the heated hydrocarbon stream to produce an intermediate stream; and flowing the intermediate stream through a reaction zone disposed in a lower portion of the laminar flow reactor to produce the hydrocarbon-solvent stream; introducing the hydrocarbon-solvent stream into a separation unit to produce a scrubbed hydrocarbon stream and a solvent stream, wherein the solvent stream comprises the contaminant; and flowing the scrubbed hydrocarbon stream through a first finishing unit to produce a purified hydrocarbon stream, wherein the purified hydrocarbon stream has a final concentration of the contaminant, and wherein the final concentration of the contaminant is less than the initial concentration of the contaminant.

32. The method of claim 31, wherein the primary solvent comprises water or steam.

33. The method of claim 31, wherein the solvent stream is an aqueous stream, and wherein the aqueous stream is concentrated and/or dried and then blended with a product in a mixer, and wherein the product comprises a processed grain, vegetable meal, fruit meal, protein meal, meat, stover, hay, forage, or any combination thereof.

34. The method of claim 31, wherein the primary solvent is introduced into the headspace through an injection device, and wherein the primary solvent has a pressure drop across the injection device in a range from about 0.0001 psi to about 40 psi.

35. The method of claim 31, wherein the laminar flow reactor is maintained at a pressure in a range from about 1 psi to about 50 psi of a saturation pressure of the primary solvent at a target reaction temperature.

36. The method of claim 31, wherein each of a liquid phase within the headspace of the laminar flow reactor and/or the intermediate stream and/or the hydrocarbon-solvent stream independently has a Reynolds number in a range from about 0 to 2,300.

37. A system for purifying a hydrocarbon, comprising: a deaerator fluidly coupled to and downstream of a feedstock hydrocarbon source, wherein the feedstock hydrocarbon source is configured to contain a feedstock hydrocarbon having an initial concentration of a contaminant and comprising one or more of an oil, a fat, a grease, or any combination thereof; a heating portion of a recuperator fluidly coupled to and downstream of the deaerator; an additive source fluidly coupled to and downstream of the deaerator, wherein the additive source is configured to contain an additive comprising a hydrolyzing agent, an acid, a base, a salt, a chelating agent, a polar solvent, a non-polar solvent, or any combination thereof; a laminar flow reactor comprising an upper portion opposite a lower portion, and wherein the upper portion of the laminar flow reactor is fluidly coupled to and downstream of the heating portion of the recuperator; a primary solvent source fluidly coupled to and upstream of the upper portion of the laminar flow reactor; a cooling portion of the recuperator fluidly coupled to and downstream of the lower portion of the laminar flow reactor; a pressure reduction device fluidly coupled to and downstream of the cooling portion of the recuperator; a separation unit fluidly coupled to and downstream of the pressure reduction device, wherein the separation unit comprises a scrubbed hydrocarbon stream outlet and a solvent stream outlet; a first finishing unit fluidly coupled to and downstream of the scrubbed hydrocarbon stream outlet, wherein the first finishing unit comprises a centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof, and wherein the first finishing unit comprises a purified hydrocarbon stream outlet configured to provide a purified hydrocarbon having a final concentration of the contaminant of at least 10 times less than the initial concentration of the contaminant; and a second finishing unit fluidly coupled to and downstream of the solvent stream outlet, wherein the second finishing unit comprises a

centrifuge, a cross-flow filtration unit, a coalescer, a decanter, an electrostatic separator, a membrane purifier, or any combination thereof.
