

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384405
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Tamura; Takao et al.

Vehicle control device, vehicle control method, and storage medium

Abstract

A device recognizes road lane markings and outputs first left road lane markings and first right road lane markings, recognizes the road lane markings based on map information and outputs second left road lane markings and second right road lane markings, determines deviations between first left road lane markings and second left road lane markings and deviations between first right road lane markings and second right road lane markings, determines that deviations are present only in one of the first left road lane markings and the second left road lane markings and the first right road lane markings and the second right road lane markings, sets a position at which a predetermined width is offset as a center of a travel path on which the vehicle is to travel in the future, and generates the travel path based on the center of the travel path.

Inventors:	Tamura; Takao (Wako, JP), Tamura; Sho (Wako, JP)
Applicant:	HONDA MOTOR CO., LTD. (Tokyo, JP)
Family ID:	82900388
Assignee:	HONDA MOTOR CO., LTD. (Tokyo, JP)
Appl. No.:	17/676868
Filed:	February 22, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220266857 A1	Aug. 25, 2022

Foreign Application Priority Data

JP	2021-028473	Feb. 25, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: B60W60/00 (20200101); **G01C21/30** (20060101); **G05D1/00** (20240101); **G06V20/56** (20220101)

U.S. Cl.:

CPC **B60W60/001** (20200201); **B60W60/005** (20200201); **G01C21/30** (20130101); **G05D1/0214** (20130101); **G05D1/0234** (20130101); **G05D1/0274** (20130101); **G06V20/588** (20220101); B60W2420/403 (20130101); B60W2420/408 (20240101); B60W2552/53 (20200201); B60W2554/4041 (20200201)

Field of Classification Search

CPC: B60W (60/001); B60W (60/005); B60W (2420/42); B60W (2420/52); B60W (2552/53); B60W (2554/4041); B60W (30/12); B60W (40/06); G01C (21/30); G01C (21/32); G01C (21/3407); G01C (21/3602); G05D (1/0214); G05D (1/0234); G05D (1/0274); G06V (20/588); G06V (10/764)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10984551	12/2020	Shikimachi	N/A	G06T 7/74
11167758	12/2020	Fukushige	N/A	G06V 20/588
2014/0050362	12/2013	Park et al.	N/A	N/A
2015/0367778	12/2014	Vladimerou et al.	N/A	N/A
2019/0035110	12/2018	Shikimachi	N/A	N/A
2020/0026297	12/2019	Kato	N/A	B60W 60/001
2020/0051436	12/2019	Ochida et al.	N/A	N/A
2020/0094837	12/2019	Kato	N/A	B60W 30/12
2021/0009127	12/2020	Horiba	N/A	B60W 50/0097
2021/0031804	12/2020	Oyama	N/A	N/A
2021/0224556	12/2020	Xu	N/A	G06V 20/41
2022/0161794	12/2021	Kakeda	N/A	B60W 60/0059
2024/0199010	12/2023	Shimizu	N/A	B60W 30/12
2024/0428448	12/2023	Lin	N/A	G06T 7/74
2025/0076070	12/2024	Lin	N/A	G01C 21/3658

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110494903	12/2018	CN	N/A
112319502	12/2020	CN	N/A
112017001175	12/2017	DE	G01C 21/28
2008-049918	12/2007	JP	N/A
2013-097714	12/2012	JP	N/A

2017-520056	12/2016	JP	N/A
2017-165309	12/2016	JP	N/A
2019-040390	12/2018	JP	N/A
2019-048570	12/2018	JP	N/A
2019-053596	12/2018	JP	N/A
2020-163870	12/2019	JP	N/A
2021-026693	12/2020	JP	N/A

OTHER PUBLICATIONS

Machine Translation DE-112017001175-T5 (Year: 2018). cited by examiner

Japanese Office Action for Japanese Patent Application No. 2021-028473 dated Dec. 6, 2022. cited by applicant

Chinese Office Action for Chinese Patent Application No. 202210159253.8 mailed Nov. 29, 2024. cited by applicant

Primary Examiner: Cass; Jean Paul

Attorney, Agent or Firm: Amin, Turocy & Watson, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application is based upon and claims the benefit of priority from Japanese Patent Application No. 2021-028473, filed Feb. 25, 2021, the entire contents of which is incorporated herein by reference.

BACKGROUND

Field of the Invention

(2) The present invention relates to a vehicle control device, a vehicle control method, and a storage medium.

Description of Related Art

(3) Research is underway on the control of automated driving in a case where lane markings of a lane in which a vehicle is traveling cannot be detected. For example, Japanese Unexamined Patent Application, First Publication No. 2019-53596 discloses a technique in which vehicle travel control is performed on the basis of a smaller width out of a width of a road specified on the basis of surroundings information acquired by a first acquirer and a width of the road indicated by information regarding the road acquired by a second acquirer.

SUMMARY

(4) In the technique of the related art, a smaller road width is always selected regardless of the correctness of the acquired information. As a result, in a case where the selected information is incorrect, inappropriate vehicle travel control may be performed.

(5) The present invention has been made in consideration of such circumstances, and one object thereof is to provide a vehicle control device, a vehicle control method, and a storage medium capable of more appropriately performing vehicle travel control.

(6) A vehicle control device, a vehicle control method, and a storage medium according to the present invention have the following configurations.

(7) (1): According to an aspect of the present invention, there is provided a vehicle control device including a storage device that stores a program; and a hardware processor, in which the hardware processor executes the program stored in the storage device to recognize a pair of left and right

road lane markings that divides a lane in which a vehicle is located on the basis of an output from a detection device that detects a surrounding situation of the vehicle, and output the left and right road lane markings as a first left road lane marking and a first right road lane marking, respectively, recognize a pair of left and right road lane markings that divides the lane in which the vehicle is located on the basis of map information, and output the left and right road lane markings as a second left road lane marking and a second right road lane marking, respectively, determine whether or not there is a deviation between the first left road lane marking and the second left road lane marking, and determine whether or not there is a deviation between the first right road lane marking and the second right road lane marking, in a case where it is determined that a deviation is present only in one of a pair of the first left road lane marking and the second left road lane marking and a pair of the first right road lane marking and the second right road lane marking, set a position at which a predetermined width is offset from the other of the pair of the first left road lane marking and the second left road lane marking and the pair of the first right road lane marking and the second right road lane marking to the one pair, as a center of a travel path on which the vehicle is to travel in the future, generate the travel path on the basis of the center of the travel path, and set the predetermined width on the basis of a smaller width out of a width between the first left road lane marking and the first right road lane marking and a width between the second left road lane marking and the second right road lane marking.

(8) (2): In the above aspect (1), the hardware processor determines whether or not a deviation is present on the basis of a deviation amount between the first left road lane marking and the second left road lane marking, the hardware processor determines whether or not a deviation is present on the basis of a deviation amount between the first right road lane marking and the second right road lane marking, and the deviation amount is an amount related to a lateral distance between the first left road lane marking and the second left road lane marking, an angle between the first left road lane marking and the second left road lane marking, a lateral distance between the first right road lane marking and the second right road lane marking, or an angle between the first right road lane marking and the second right road lane marking.

(9) (3): In the above aspect (2), the hardware processor determines that a deviation is present in a case where the deviation amount is equal to or more than the threshold value, and the hardware processor sets the threshold value on the basis of an amount of change in curvature of the first left road lane marking or the first right road lane marking.

(10) (4): In the above aspect (1), the hardware processor controls steering and acceleration/deceleration of the vehicle regardless of an operation of a driver of the vehicle, a driving mode of the vehicle is determined to be one of a plurality of driving modes including a first driving mode and a second driving mode, the second driving mode being a driving mode in which a task imposed on the driver is light compared with the first driving mode, some of the plurality of driving modes including at least the second driving mode being controlled by the hardware processor, and, in a case where a task related to the determined driving mode is not being executed by the driver, the driving mode of the vehicle being changed to a driving mode in which the task is heavier, and the hardware processor continues the second driving mode in a case where the driving mode of the vehicle is the second driving mode and the hardware processor generates the travel path.

(11) (5): In the above aspect (4), the hardware processor recognizes a traveling trajectory of a preceding vehicle, and, in a case where the recognized traveling trajectory intersects the first left road lane marking or the first right road lane marking, the hardware processor changes the driving mode of the vehicle from the second driving mode to the first driving mode.

(12) (6): According to another aspect of the present invention, there is provided a vehicle control method of causing a computer mounted in a vehicle to recognize a pair of left and right road lane markings that divides a lane in which the vehicle is located on the basis of an output from a detection device that detects a surrounding situation of the vehicle, and output the left and right

road lane markings as a first left road lane marking and a first right road lane marking, respectively; recognize a pair of left and right road lane markings that divides the lane in which the vehicle is located on the basis of map information, and output the left and right road lane markings as a second left road lane marking and a second right road lane marking, respectively; determine whether or not there is a deviation between the first left road lane marking and the second left road lane marking, and determine whether or not there is a deviation between the first right road lane marking and the second right road lane marking; in a case where it is determined that a deviation is present only in one of a pair of the first left road lane marking and the second left road lane marking and a pair of the first right road lane marking and the second right road lane marking, set a position at which a predetermined width is offset from the other of the pair of the first left road lane marking and the second left road lane marking and the pair of the first right road lane marking and the second right road lane marking to the one pair, as a center of a travel path on which the vehicle is to travel in the future; generate the travel path on the basis of the center of the travel path; and set the predetermined width on the basis of a smaller width out of a width between the first left road lane marking and the first right road lane marking and a width between the second left road lane marking and the second right road lane marking.

(13) (7): According to still another aspect of the present invention, there is provided a non-transitory computer readable medium storing a program causing a computer mounted in a vehicle to recognize a pair of left and right road lane markings that divides a lane in which the vehicle is located on the basis of an output from a detection device that detects a surrounding situation of the vehicle, and output the left and right road lane markings as a first left road lane marking and a first right road lane marking, respectively; recognize a pair of left and right road lane markings that divides the lane in which the vehicle is located on the basis of map information, and output the left and right road lane markings as a second left road lane marking and a second right road lane marking, respectively; determine whether or not there is a deviation between the first left road lane marking and the second left road lane marking, and determine whether or not there is a deviation between the first right road lane marking and the second right road lane marking; in a case where it is determined that a deviation is present only in one of a pair of the first left road lane marking and the second left road lane marking and a pair of the first right road lane marking and the second right road lane marking, set a position at which a predetermined width is offset from the other of the pair of the first left road lane marking and the second left road lane marking and the pair of the first right road lane marking and the second right road lane marking to the one pair, as a center of a travel path on which the vehicle is to travel in the future; generate the travel path on the basis of the center of the travel path; and set the predetermined width on the basis of a smaller width out of a width between the first left road lane marking and the first right road lane marking and a width between the second left road lane marking and the second right road lane marking.

(14) According to the aspects (1) to (7), vehicle travel control can be performed more appropriately.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a configuration diagram of a vehicle system using a vehicle control device according to an embodiment.
- (2) FIG. 2 is a functional configuration diagram of a first controller and a second controller.
- (3) FIG. 3 is a diagram showing an example of a correspondence relationship between a driving mode, a control state of an own vehicle M, and a task.
- (4) FIG. 4 is a diagram for describing an outline of an operation of the vehicle control device of the present embodiment.
- (5) FIG. 5 is a diagram showing an example of a deviation amount measured for determination of a

deviation determiner.

(6) FIG. 6 is a diagram showing an example of a threshold value used for determination of the deviation determiner.

(7) FIG. 7 is a diagram for describing an outline of an exception process by the vehicle control device of the present embodiment.

(8) FIG. 8 is a flowchart showing an example of a flow of an operation of the vehicle control device of the present embodiment.

DESCRIPTION OF EMBODIMENTS

(9) Hereinafter, embodiments of a vehicle control device, vehicle control method, and storage medium of the present invention will be described with reference to the drawings.

(10) Overall Configuration

(11) FIG. 1 is a configuration diagram of a vehicle system **1** using a vehicle control device according to an embodiment. A vehicle having the vehicle system **1** mounted therein is, for example, a two-wheeled, three-wheeled, or four-wheeled vehicle, and a drive source thereof is an internal combustion engine such as a diesel engine or a gasoline engine, a motor, or a combination thereof. The motor is operated by using power generated by a generator connected to the internal combustion engine or power released from a secondary battery or a fuel cell.

(12) The vehicle system **1** includes, for example, a camera **10**, a radar device **12**, light detection and ranging (LIDAR) **14**, an object recognition device **16**, a communication device **20**, a human machine interface (HMI) **30**, a vehicle sensor **40**, a navigation device **50**, a map positioning unit (MPU) **60**, a driving operator **80**, an automated driving control device **100**, a traveling drive force output device **200**, a brake device **210**, and a steering device **220**. The devices and the apparatuses are connected to each other via a multiplex communication line such as a Controller Area Network (CAN) communication line, a serial communication line, or a wireless communication network. The configuration shown in FIG. 1 is only an example, and some of the constituents may be omitted, and other constituents may be added.

(13) The camera **10** is a digital camera using a solid-state imaging element such as a charge coupled device (CCD) or a complementary metal oxide semiconductor (CMOS). The camera **10** is attached at any location in a vehicle (hereinafter, an own vehicle M) in which the vehicle system **1** is mounted. For example, in a case of imaging the front in the own vehicle M, the camera **10** is attached to the upper part of a front windshield, the back surface of a rearview mirror, or the like. The camera **10** periodically and repeatedly captures images of the surroundings of the own vehicle M. The camera **10** may be a stereo camera.

(14) The radar device **12** radiates electric waves such as millimeter waves in the surroundings of the own vehicle M, detects electric waves (reflected waves) reflected by an object, and thus detects at least a position of (a distance to and an azimuth of) the object. The radar device **12** is attached at any location in the own vehicle M. The radar device **12** may detect a position and a speed of an object according to a frequency modulated continuous wave (FM-CW) method.

(15) The LIDAR **14** applies light (or an electromagnetic wave with a wavelength close to that of the light) in the surroundings of the own vehicle M, and measures scattered light. The LIDAR **14** detects a distance to a target on the basis of a time from light emission to light reception. The applied light is, for example, pulsed laser light. The LIDAR **14** is attached at any location in the own vehicle M.

(16) The object recognition device **16** performs a sensor fusion process on detection results from some or all of the camera **10**, the radar device **12**, and the LIDAR **14**, and thus recognizes a position, the type, a speed, and the like of an object. The object recognition device **16** outputs a recognition result to the automated driving control device **100**. The object recognition device **16** may output detection results from the camera **10**, the radar device **12**, and the LIDAR **14** to the automated driving control device **100** without change. The object recognition device **16** may be omitted from the vehicle system **1**.

(17) The communication device **20** performs communication with another vehicle present in the surroundings of the own vehicle **M**, or performs communication with various server apparatuses via a wireless base station by using, for example, a cellular network, a Wi-Fi network, Bluetooth (registered trademark), or dedicated short range communication (DSRC).

(18) The HMI **30** presents various types of information to an occupant of the own vehicle **M**, and also receives an input operation from the occupant. The HMI **30** includes various display devices, speakers, buzzers, touch panels, switches, keys, and the like.

(19) The vehicle sensor **40** includes a vehicle speed sensor that detects a speed of the own vehicle **M**, an acceleration sensor that detects acceleration, a gyro sensor that detects angular velocity, an azimuth sensor that detects an orientation of the own vehicle **M**, and the like.

(20) The navigation device **50** includes, for example, a global navigation satellite system (GNSS) receiver **51**, a navigation HMI **52**, and a route determiner **53**. The navigation device **50** stores first map information **54** in a storage device such as a hard disk drive (HDD) or a flash memory. The GNSS receiver **51** specifies a position of the own vehicle **M** on the basis of a signal received from the GNSS satellite. A position of the own vehicle **M** may be specified or complemented by an inertial navigation system (INS) using an output from the vehicle sensor **40**. The navigation HMI **52** includes a display device, a speaker, a touch panel, keys, and the like. The navigation HMI **52** may be partially or entirely integrated into the HMI **30** described above. The route determiner **53** determines, for example, a route (hereinafter, a route on a map) from a position of the own vehicle **M** specified by the GNSS receiver **51** (or any entered position) to a destination that is entered by an occupant by using the navigation HMI **52** on the basis of the first map information **54**. The first map information **54** is, for example, information in which a road shape is expressed by a link indicating a road and nodes connected to each other via the link. The first map information **54** may include a curvature of a road, point of interest (POI) information, and the like. The route on the map is output to MPU **60**. The navigation device **50** may perform route guidance using the navigation HMI **52** on the basis of the route on the map. The navigation device **50** may be implemented, for example, by a function of a terminal apparatus such as a smartphone or a tablet terminal carried by the occupant. The navigation device **50** may transmit the current position and the destination to a navigation server via the communication device **20**, and may acquire a route equivalent to the route on the map from the navigation server.

(21) The MPU **60** includes, for example, a recommended lane determiner **61**, and stores second map information **62** in a storage device such as an HDD or a flash memory. The recommended lane determiner **61** divides the route on the map provided from the navigation device **50** into a plurality of blocks (for example, divides the route on the map every 100 m in a vehicle advancing direction), and determines a recommended lane for each block by referring to the second map information **62**. The recommended lane determiner **61** determines in which lane from the left the own vehicle will travel. In a case where there is a branch location on the route on the map, the recommended lane determiner **61** determines a recommended lane such that the own vehicle **M** can travel on a reasonable route to advance to a branch destination.

(22) The second map information **62** is map information with higher accuracy than the first map information **54**. The second map information **62** includes, for example, information regarding the center of a lane or information regarding a boundary of the lane. The second map information **62** may include road information, traffic regulation information, address information (address/postal code), facility information, telephone number information, information regarding prohibited sections in which a mode A or a mode B that will be described later is prohibited. The second map information **62** may be updated at any time by the communication device **20** performing communication with other devices.

(23) The driving operator **80** includes, for example, an accelerator pedal, a brake pedal, a shift lever, a steering wheel, an odd-shaped steering wheel, a joystick, and other operators. A sensor that detects an amount of operation or the presence or absence of operation is attached to the driving

operator **80**, and a detection result from the sensor is output to the automated driving control device **100**, or is output to some or all of the traveling drive force output device **200**, the brake device **210**, and the steering device **220**.

(24) The automated driving control device **100** includes, for example, a first controller **120** and a second controller **160**. Each of the first controller **120** and the second controller **160** is realized, for example, by a hardware processor such as a central processing unit (CPU) executing a program (software). One or both of these constituents may be realized by hardware (a circuit portion; including circuitry) such as a large scale integration (LSI), an application specific integrated circuit (ASIC), a field-programmable gate array (FPGA), or a graphics processing unit (GPU), and may be realized by software and hardware in cooperation. The program may be stored in advance in a storage device (a storage device provided with a non-transitory storage medium) of the automated driving control device **100**, and may be stored in an attachable and detachable storage medium such as a DVD or a CD-ROM and may be installed in an HDD or a flash memory of the automated driving control device **100** when the storage medium (non-transitory storage medium) is attached to a drive device. The automated driving control device **100** is an example of a “vehicle control device”, and a combination of the action plan generator **140** and the second controller **160** is an example of a “driving controller”.

(25) FIG. 2 is a functional configuration diagram of the first controller **120** and the second controller **160**. The first controller **120** includes, for example, a recognizer **130**, an action plan generator **140**, and a mode determiner **150**. The first controller **120** is realized by combining, for example, a function of artificial intelligence (AI) with a function of a model provided in advance. For example, a function of “recognizing an intersection” may be realized by executing recognition of the intersection using deep learning and recognition based on conditions (for example, there are a signal that can be matched with a pattern, and a road marking) given in advance in parallel, and scoring and comprehensively evaluating both of recognition results. Consequently, the reliability of automated driving is ensured.

(26) The recognizer **130** includes, for example, an object recognizer **132**, a road lane marking recognizer **134**, a map matcher **136**, and a preceding vehicle trajectory recognizer **138**. The road lane marking recognizer **134** is an example of a “first recognizer”, the map matcher **136** is an example of a “second recognizer”, and the preceding vehicle trajectory recognizer **138** is an example of a “third recognizer”.

(27) The object recognizer **132** recognizes states such as a position, a speed, and an acceleration of an object present in the surroundings of the own vehicle M on the basis of information input from the camera **10**, the radar device **12**, and the LIDAR **14** via the object recognition device **16**. The position of the object is recognized as, for example, a position on absolute coordinates with a representative point (for example, the centroid or the drive axis center) of the own vehicle M as the origin, and is used for control. The position of the object may be represented by a representative point such as the centroid or a corner of the object, and may be represented by a region. The “states” of the object may include an acceleration, a jerk, or an “action state” of the object (for example, whether or not the object is changing lanes or trying to change lanes).

(28) The road lane marking recognizer **134** extracts edge points having a large luminance difference from adjacent pixels in an image output by the camera **10**, and recognizes a pair of left and right road lane markings in the image by connecting the edge points. In this case, the road lane marking recognizer **134** recognizes the left and right road lane markings as coordinates in a vehicle coordinate system in which a representative point of the own vehicle is set to the origin, a vehicle center axis is set to an X axis, and an axis orthogonal to the vehicle center axis is set to a Y axis.

(29) The map matcher **136** collates a position of the own vehicle M specified by the navigation device **50**, an image captured by the camera **10**, an output from an azimuth sensor included in the vehicle sensor **40**, and the like with the second map information **62**, and recognizes on which road and in which lane the own vehicle M is traveling on the map. The map matcher **136** further

recognizes a pair of left and right road lane markings that divides a lane in which the own vehicle M is located on the basis of the second map information **62**. In this case, the map matcher **136** recognizes the a pair of left and right road lane markings as coordinates in the vehicle coordinate system, similarly to the road lane marking recognizer **134**. The map matcher **136** integrates the a pair of left and right road lane markings recognized by the road lane marking recognizer **134** with the a pair of left and right road lane markings recognized by itself in the vehicle coordinate system. Details of these four road lane markings will be described later with reference to FIG. **4**.

(30) The preceding vehicle trajectory recognizer **138** determines whether or not there is a preceding vehicle of the own vehicle M on the basis of an image output by the camera **10**, and in a case where it is determined that there is the preceding vehicle of the own vehicle M, acquires a traveling trajectory of the preceding vehicle as coordinate points in the vehicle coordinate system.

(31) The action plan generator **140** generates target trajectories in which the own vehicle M automatically (regardless of an operation of a driver) travels in the future such that the own vehicle can travel in a recommended lane determined by the recommended lane determiner **61** in principle and can also cope with a surrounding situation of the own vehicle M. The target trajectory includes, for example, a speed element. For example, the target trajectory is expressed by sequentially arranging locations (trajectory points) to be reached by the own vehicle M. The trajectory points are locations to be reached by the own vehicle M every predetermined traveling distance (for example, about several [m]) in terms of a distance along a road, and, separately therefrom, a target speed and a target acceleration for each predetermined sampling time (for example, any of about 0.1 to 0.9 seconds) are generated as parts of the target trajectory. A trajectory point may be a position to be reached by the own vehicle M at a sampling time point every predetermined sampling time. In this case, the information of the target velocity and the target acceleration is expressed by the interval of the trajectory points. The action plan generator **140** includes a deviation determiner **142** and a travel path center setter **144**, and these functions will be described later.

(32) The mode determiner **150** determines a driving mode of the own vehicle M to be one of a plurality of driving modes in which tasks imposed on a driver are different. The mode determiner **150** includes, for example, a driver state determiner **152** and a mode change processor **154**. These individual functions will be described later.

(33) FIG. **3** is a diagram showing an example of a correspondence relationship between a driving mode, a control state of the own vehicle M, and a task. Driving modes of the own vehicle M include, for example, five modes from a mode A to a mode E. A control state, that is, the degree of automation of driving control for the own vehicle M is highest in the mode A, then becomes lower in the order of the mode B, the mode C, and the mode D, and is lowest in the mode E. In contrast, a task imposed on a driver is lightest in the mode A, then becomes heavier in the order of the mode B, the mode C, and the mode D, and is heaviest in the mode E. In the modes D and E, the vehicle is in a control state that is not automated driving, and thus the automated driving control device **100** is responsible for finishing control related to automated driving and transitioning to driving assistance or manual driving. Hereinafter, details of each driving mode will be exemplified.

(34) In the mode A, the vehicle is in an automated driving state, and neither front monitoring nor gripping of the steering wheel **82** (steering gripping in the figure) is imposed on the driver. However, even in the mode A, the driver is required to be in a posture to quickly transition to manual driving in response to a request from the system centered on the automated driving control device **100**. The term “automated driving” referred to here means that both steering and acceleration/deceleration are controlled without depending on the driver's operation. The term “front” means a space in an advancing direction of the own vehicle M that is visually recognized through the front windshield. The mode A is a driving mode that is executable in a case of satisfying a condition that the own vehicle M is traveling at a predetermined speed (for example, about 50 [km/h]) or less on a motorway such as an expressway and there is a preceding vehicle that

is a following target, and may be referred to as traffic jam pilot (TJP). In a case where this condition is no longer satisfied, the mode determiner **150** changes a driving mode of the own vehicle M to the mode B.

(35) In the mode B, the vehicle is in a driving assistance state, and the task of monitoring the front in the own vehicle M (hereinafter, front monitoring) is imposed on the driver, but the task of gripping the steering wheel **82** is not imposed on the driver. In the mode C, the vehicle is in a driving assistance state, and the task of front monitoring and the task of gripping the steering wheel **82** are imposed on the driver. The mode D is a driving mode that requires a certain degree of driving operation by the driver with respect to at least one of steering and acceleration/deceleration of the own vehicle M. For example, in the mode D, driving assistance such as adaptive cruise control (ACC) or lane keeping assist system (LKAS) is provided. In the mode E, the vehicle is in a manual driving state in which both steering and acceleration/deceleration require driving operations by the driver. In both the mode D and the mode E, the task of monitoring the front in the own vehicle M is naturally imposed on the driver.

(36) The mode determiner **150** changes a driving mode of the own vehicle M to a driving mode in which the task is heavier in a case where the task related to the determined driving mode (hereinafter, the current driving mode) is not executed by the driver.

(37) For example, in the mode A, in a case where the driver is in a posture where the driver cannot transition to manual driving in response to a request from the system (for example, in a case where the driver continues to look outside a permissible area or a sign that driving becomes difficult is detected), the mode determiner **150** uses the HMI **30** to prompt the driver to transition to manual driving, and if the driver does not respond, the mode determiner **150** performs control of gradually bringing the own vehicle M to a road shoulder and stopping the own vehicle M to stop the automated driving. After the automated driving is stopped, the own vehicle is in the mode D or E, and the own vehicle M can be started by a manual operation of the driver. Hereinafter, the same applies to “stop automated driving”. In a case where the driver is not monitoring the front in the mode B, the mode determiner **150** uses the HMI **30** to prompt the driver to monitor the front, and if the driver does not respond, the mode determiner **150** performs control of gradually bringing the own vehicle M to a road shoulder and stopping the own vehicle M to stop the automated driving. In the mode C, in a case where the driver is not monitoring the front or is not gripping the steering wheel **82**, the mode determiner **150** uses the HMI **30** to prompt the driver to monitor the front and/or grip the steering wheel **82**, and if the driver does not respond, the mode determiner **150** performs control of gradually bringing the own vehicle M to a road shoulder and stopping the own vehicle M to stop the automated driving.

(38) The driver state determiner **152** monitors a state of the driver in order to perform the above mode change, and determines whether or not the state of the driver is a state corresponding to a task. For example, the driver state determiner **152** analyzes an image captured by a driver monitor camera **70** to estimate a posture of the driver, and determines whether or not the driver is in a posture to be unable to transition to manual driving in response to a request from the system. The driver state determiner **152** analyzes the image captured by the driver monitor camera **70** and performs a line-of-sight estimation process, and thus determines whether or not the driver is monitoring the front.

(39) The mode change processor **154** performs various processes for a mode change. For example, the mode change processor **154** instructs the action plan generator **140** to generate a target trajectory for stopping at a road shoulder, gives an operation instruction to a driving assistance device (not shown), or controls the HMI **30** in order to prompt the driver to perform an action.

(40) The second controller **160** controls the traveling drive force output device **200**, the brake device **210**, and the steering device **220** such that the own vehicle M can pass along the target trajectory generated by the action plan generator **140** as scheduled.

(41) Referring to FIG. 2 again, the second controller **160** includes, for example, an acquirer **162**, a

speed controller **164**, and a steering controller **166**. The acquirer **162** acquires information regarding the target trajectory (trajectory points) generated by the action plan generator **140**, and stores the information in a memory (not shown). The speed controller **164** controls the traveling drive force output device **200** or the brake device **210** on the basis of a speed element included in the target trajectory stored in the memory. The steering controller **166** controls the steering device **220** according to a curved state of the target trajectory stored in the memory. Processes in the speed controller **164** and the steering controller **166** are realized by a combination of, for example, feedforward control and feedback control. As an example, the steering controller **166** executes a combination of feedforward control based on a curvature of a road in front of the own vehicle **M** and feedback control based on deviation from the target trajectory.

(42) The traveling drive force output device **200** outputs traveling drive force (torque) for traveling of the vehicle to drive wheels. The traveling drive force output device **200** includes, for example, a combination of an internal combustion engine, a motor, and a transmission, and an electronic control unit (ECU) controlling the constituents. The ECU controls the constituents according to information that is input from the second controller **160** or information that is input from the driving operator **80**.

(43) The brake device **210** includes, for example, a brake caliper, a cylinder that transmits hydraulic pressure to the brake caliper, an electric motor that generates the hydraulic pressure in the cylinder, and a brake ECU. The brake ECU controls the electric motor on the basis of information being input from the second controller **160** or information being input from the driving operator **80**, so that brake torque corresponding to a braking operation is output to each vehicle wheel. The brake device **210** may include, as a backup, a mechanism transmitting hydraulic pressure generated by operating the brake pedal included in the driving operator **80**, to the cylinder via a master cylinder. The brake device **210** is not limited to the above configuration and may be an electronic control type hydraulic brake device that controls an actuator according to information being input from the second controller **160** and thus transmits hydraulic pressure in a master cylinder to the cylinder.

(44) The steering device **220** includes, for example, a steering ECU and an electric motor. The electric motor changes an orientation of a turning wheel by applying force to, for example, a rack-and-pinion mechanism. The steering ECU drives the electric motor on the basis of information being input from the second controller **160** or information being input from the driving operator **80**, so that an orientation of the turning wheel is changed.

(45) Operation

(46) Hereinafter, an operation of the vehicle control device of the present embodiment will be described with reference to FIG. **4**. In the present embodiment, it is assumed that the own vehicle **M** is traveling in the mode **B** as a driving mode. FIG. **4** is a diagram for describing an outline of the operation of the vehicle control device of the present embodiment. In FIG. **4**, **L1** indicates a lane in which the own vehicle **M** is traveling, a dotted line **Lcl** indicates a position of a left road lane marking (hereinafter, referred to as a “first left road lane marking”) with respect to the own vehicle **M** recognized on the basis of an image captured by the camera **10** in the vehicle coordinate system, a dotted line **Lcr** indicates a position of a right road lane marking (hereinafter, referred to as a “first right road lane marking”) with respect to the own vehicle **M** recognized on the basis of the image captured by the camera **10** in the vehicle coordinate system, a thick solid line **Lml** indicates a position of a left road lane marking (hereinafter, referred to as a “second left road lane marking”) with respect to the own vehicle **M** indicated by the second map information **62** in the vehicle coordinate system, and a thick solid line **Lmr** indicates a position of a right road lane marking (hereinafter, referred to as a “second right road lane marking”) with respect to the own vehicle **M** indicated by the second map information **62** in the vehicle coordinate system. Hereinafter, in a case where the left side and the right side are not differentiated, a road lane marking of the own vehicle **M** indicated by the camera **10** may be expressed as **Lc**, and a road lane marking of the own vehicle **M** indicated by the second map information **62** may be expressed as **Lm**.

(47) The deviation determiner **142** determines whether or not there is a deviation between the first left road lane marking Lcl and the second left road lane marking Lml, and also determines whether or not there is a deviation between the first right road lane marking Lcr and the second right road lane marking Lmr. Specifically, the deviation determiner **142** determines whether or not a deviation amount of a lateral distance $\Delta Y1$ between the first left road lane marking Lcl and the second left road lane marking Lml, an angle $\Delta\theta1$ between the first left road lane marking Lcl and the second left road lane marking Lml, a lateral distance ΔYr between the first right road lane marking Lcr and the second right road lane marking Lmr, or an angle $\Delta\theta r$ between the first right road lane marking Lcr and the second right road lane marking Lmr is equal to or more than a threshold value, and in a case where it is determined that the lateral distance $\Delta Y1$, the angle $\Delta\theta1$, the lateral distance ΔYr , or the angle $\Delta\theta r$ is equal to or more than the threshold value, determines that there is a deviation. Hereinafter, in a case where the left side and the right side are not differentiated, the angle $\Delta\theta1$ or the angle $\Delta\theta r$ may be expressed as an angle $\Delta\theta$, and the lateral distance $\Delta Y1$ or the lateral distance ΔYr may be expressed as a lateral distance ΔY .

(48) In a case where the deviation determiner **142** determines that there is a deviation with respect to only one of a pair of the first left road lane marking Lcl and the second left road lane marking Lml and a pair of the first right road lane marking Lcr and the second right road lane marking Lmr, the travel path center setter **144** sets a position at which a predetermined width W_o is offset to the one pair from the other of the pair of the first left road lane marking Lcl and the second left road lane marking Lml and the pair of the first right road lane marking Lcr and the second right road lane marking Lmr as the center CP of a travel path on which the own vehicle M is to travel in the future. In this case, the travel path center setter **144** sets the predetermined width W_o on the basis of a smaller width out of a width W_c between the first left road lane marking Lcl and the first right road lane marking Lcr, and a width W_m between the second left road lane marking Lml and the second right road lane marking Lmr. Specifically, the travel path center setter **144** sets the predetermined width W_o to $\frac{1}{2}$ of the smaller width out of the width W_c and the width W_m . That is, $W_o = \frac{1}{2} \times \min(W_c, W_m)$ is established. Therefore, the action plan generator **140** generates a target trajectory such that the center of the own vehicle M passes through the center CP of the set travel path. Consequently, even in a case where a deviation occurs in the recognition of the road lane markings for one of the left and right pairs, automated driving in the mode B can be continued on the basis of the other pair in which a deviation does not occur in the recognition of the road lane markings.

(49) On the other hand, in a case where it is determined that there is a deviation in both the pair of the first left road lane marking Lcl and the second left road lane marking Lml and the pair of the first right road lane marking Lcr and the second right road lane marking Lmr, the deviation determiner **142** causes the mode determiner **150** to change the driving mode from the mode B to the mode C (or a driving mode in which a task is heavier) without causing the travel path center setter **144** to set the center CP of a travel path. Consequently, in a case where a deviation occurs in the recognition of the road lane markings for both the left and right pairs, safety can be ensured by changing the driving mode to a driving mode in which a task is heavier.

(50) In a case where it is determined that there is no deviation for the pair of the first left road lane marking Lcl and the second left road lane marking Lml and the pair of the first right road lane marking Lcr and the second right road lane marking Lmr, since the road lane markings are recognized normally, the mode determiner **150** continues the driving mode of the mode B.

(51) FIG. 5 is a diagram showing an example of a deviation amount measured for determination by the deviation determiner **142**. As shown in FIG. 5, the deviation determiner **142** calculates the lateral distance ΔY between the road lane marking Lc and the road lane marking Lm on the basis of the road lane marking Lc and the road lane marking Lm recognized by the recognizer **130**, and also calculates the angle $\Delta\theta$ between the road lane marking Lc and the road lane marking Lm recognized by the recognizer **130**. Here, the road lane marking Lc and the road lane marking Lm

that are calculation targets of the lateral distance $\Delta\theta$ and the angle $\Delta\theta$ are the road lane marking Lc and the road lane marking Lm within a predetermined distance (for example, 30 m) from the own vehicle M. In a case where the road lane marking Lc and the road lane marking Lm recognized by the recognizer **130** are curves instead of straight lines, the deviation determiner **142** may approximate the curves to straight lines and then calculate the lateral distance ΔY and the angle $\Delta\theta$. (52) The deviation determiner **142** compares the calculated lateral distance ΔY and angle $\Delta\theta$ with threshold values, respectively. FIG. 6 is a diagram showing an example of a threshold value used for determination by the deviation determiner **142**. As shown in FIG. 6, the deviation determiner **142** determines whether or not the lateral distance ΔY is a first threshold value $\Delta Y1$ or more and a second threshold value $\Delta Y2$ or less, and the angle $\Delta\theta$ is a third threshold value $\Delta\theta1$ or more and a fourth threshold value $\Delta\theta2$ or less.

(53) When a combination of the lateral distance ΔY and the angle $\Delta\theta$ is within a range of a region R1 in which the lateral distance ΔY is the first threshold value $\Delta\theta1$ or more and the second threshold value $\Delta Y2$ or less, and the angle $\Delta\theta$ is 0 or more and the third threshold value $\Delta\theta1$ or less, or is within a range of a region R2 in which the lateral distance ΔY is 0 or more and the first threshold value $\Delta Y1$ or less and the angle $\Delta\theta$ is the third threshold value $\Delta\theta1$ or more and the fourth threshold value $\Delta\theta2$ or less, the deviation determiner **142** determines that there is a deviation, and causes the travel path center setter **144** to set the center CP of a travel path.

(54) Since a region R0 in which the lateral distance ΔY is 0 or more and the first threshold value $\Delta\theta1$ or less and the angle $\Delta\theta$ is 0 or more and the third threshold value $\Delta\theta1$ or less is a normal region, the deviation determiner **142** determines that there is no deviation when the combination of the lateral distance ΔY and the angle $\Delta\theta$ is within the range of the region R0. When the combination of the lateral distance ΔY and the angle $\Delta\theta$ is outside the range of the region R0, the region R1, and the region R2, the deviation determiner **142** determines that a deviation is present, but changes the driving mode from the mode B to the mode C (or a driving mode in which a task is heavier) instead of causing the travel path center setter **144** to set the center CP of a travel path. Consequently, even in a case where a deviation occurs in the recognition of the road lane markings for one of the left and right pairs, automated driving in the mode B can be continued on the basis of the other pair for which a deviation does not occur in the recognition of the road lane markings, and when an occurring deviation is excessive (that is, the lateral distance ΔY is more than the second threshold value $\Delta Y2$, or the angle $\Delta\theta$ is more than the fourth threshold value $\Delta\theta2$), the driving mode is changed to a driving mode in which a task is heavier. Therefore, safety can be ensured.

(55) In the above description, the first threshold value $\Delta Y1$, the second threshold value $\Delta Y2$, the third threshold value $\Delta\theta1$, and the fourth threshold value $\Delta\theta2$ are described as constants, but in the present embodiment, the deviation determiner **142** sets these threshold values on the basis of an amount of change in curvature of the first left road lane marking Lcl or the first right road lane marking Lcr. Here, an amount of change in curvature means a rate of change over time in the curvature R in front X [m] of the road lane marking Lc indicated by the camera **10**, and may be calculated, for example, by representing a position in front X [m] from the own vehicle M on the road lane marking Lc as a polynomial, differentiating the polynomial twice with respect to X, and then further differentiating with respect to time t. As described above, by setting the threshold value according to the amount of change in curvature of the road lane marking detected by the camera **10**, it is possible to more flexibly determine a deviation in recognition of the road lane marking.

(56) Next, with reference to FIG. 7, an exception process by the vehicle control device of the present embodiment will be described. FIG. 7 is a diagram for describing an outline of an exception process by the vehicle control device of the present embodiment. In FIG. 7, M1 indicates a preceding vehicle of the own vehicle M, and MT indicates a traveling trajectory of the preceding vehicle M1. The deviation determiner **142** determines whether or not the traveling trajectory MT recognized by the recognizer **130** intersects the first left road lane marking Lcl or the first right road lane marking Lcr, and, in a case where it is determined that the traveling trajectory MT

recognized by the recognizer **130** intersects the first left road lane marking Lcl or the first right road lane marking Lcr, the mode determiner **150** changes a driving mode from the mode B to the mode C (or a driving mode in which a task is heavier) regardless of a deviation determination result by the deviation determiner **142**. This is so that, in a case where the traveling trajectory MT intersects the first left road lane marking Lcl or the first right road lane marking Lcr, the recognition accuracy of the camera **10** may be significantly low, and thus an occupant of the own vehicle M is alerted by changing the driving mode to a driving mode in which a task is heavier. In FIG. 7, since the traveling trajectory MT intersects the first right road lane marking Lcr, the mode determiner **150** changes the driving mode from the mode B to the mode C (or a driving mode in which a task is heavier) regardless of a determination result by the deviation determiner **142**.

(57) Next, with reference to FIG. 8, a flow of an operation of the vehicle control device of the present embodiment will be described. FIG. 8 is a flowchart showing an example of a flow of an operation of the vehicle control device of the present embodiment. The process in this flowchart is repeatedly executed while the own vehicle M is traveling in the mode B.

(58) First, the deviation determiner **142** determines whether there is a deviation between the first left road lane marking Lcl and the second left road lane marking Lml, or a deviation between the first right road lane marking Lcr and the second right road lane marking Lmr (step S100).

(59) In a case where it is determined that there is no deviation between the first left road lane marking Lcl and the second left road lane marking Lml, or there is no deviation between the first right road lane marking Lcr and the second right road lane marking Lmr, the deviation determiner **142** executes the process in step S100 again.

(60) On the other hand, in a case where it is determined that there is a deviation between the first left road lane marking Lcl and the second left road lane marking Lml, or there is a deviation between the first right road lane marking Lcr and the second right road lane marking Lmr, the deviation determiner **142** then determines whether or not there is a deviation both between the first left road lane marking Lcl and the second left road lane marking Lml and between the first right road lane marking Lcr and the second right road lane marking Lmr (step S101). In a case where it is determined that there is a deviation both between the first left road lane marking Lcl and the second left road lane marking Lml and between the first right road lane marking Lcr and the second right road lane marking Lmr, the mode determiner **150** changes the driving mode from the mode B to the mode C (or a driving mode in which a task is heavier).

(61) On the other hand, in a case where it is determined that there is no deviation either between the first left road lane marking Lcl and the second left road lane marking Lml or between the first right road lane marking Lcr and the second right road lane marking Lmr, the deviation determiner **142** determines whether or not the traveling trajectory MT of the preceding vehicle M1 recognized by the recognizer **130** intersects the first left road lane marking Lcl or the first right road lane marking Lcr (step S103). In a case where it is determined that the traveling trajectory MT of the preceding vehicle M1 recognized by the recognizer **130** intersects the first left road lane marking Lcl or the first right road lane marking Lcr, the mode determiner **150** changes the driving mode from the mode B to the mode C (or a driving mode in which a task is heavier).

(62) On the other hand, in a case where it is determined that the traveling trajectory MT of the preceding vehicle M1 recognized by the recognizer **130** does not intersect with the first left road lane marking Lcl or the first right road lane marking Lcr, the travel path center setter **144** sets the predetermined width Wo on the basis of a smaller width out of the width We between the first left road lane marking Lcl and the first right road lane marking Lcr and the width Wm between the second left road lane marking Lml and the second right road lane marking Lmr, and sets a position at which the predetermined width Wo is offset from the lane marking for which it is determined that there is no deviation to the other lane marking as the center CP of a travel path on which the own vehicle M is to travel in the future (step S104). Next, the action plan generator **140** generates a target trajectory such that the center of the own vehicle M passes through the set center CP of the

travel path (step S105). Consequently, the process in this flowchart is finished.

(63) According to the present embodiment described above, a pair of left and right road lane markings recognized by the camera **10** and a pair of left and right road lane markings indicated by the second map information **62** are compared with each other, and in a case where a deviation occurs only in one pair of road lane markings, a position at which a predetermined width is offset from the other pair of road lane markings is set as the center CP of a travel path on which the own vehicle M is to travel in the future, and a target trajectory is generated such that the own vehicle M will pass through the center CP. Consequently, vehicle travel control can be performed more appropriately.

(64) The embodiment described above may be expressed as follows.

(65) A vehicle control device including: a storage device that stores a program; and a hardware processor, in which the hardware processor executes the program stored in the storage device to on the basis of an output from a detection device that detects a surrounding situation of a vehicle, recognize a pair of left and right road lane markings that divides a lane in which the vehicle is located, and output the left and right road lane markings as a first left road lane marking and a first right road lane marking, respectively, recognize a pair of left and right road lane markings that divides the lane in which the vehicle is located on the basis of map information, and output the left and right road lane markings as a second left road lane marking and a second right road lane marking, respectively, determine whether or not there is a deviation between the first left road lane marking and the second left road lane marking, and determine whether or not there is a deviation between the first right road lane marking and the second right road lane marking, in a case where it is determined that a deviation is present only in one of a pair of the first left road lane marking and the second left road lane marking and a pair of the first right road lane marking and the second right road lane marking, set a position at which a predetermined width is offset from the other of the pair of the first left road lane marking and the second left road lane marking and the pair of the first right road lane marking and the second right road lane marking to the one pair, as a center of a travel path on which the vehicle is to travel in the future, generate the travel path on the basis of the center of the travel path, and set the predetermined width on the basis of a smaller width out of a width between the first left road lane marking and the first right road lane marking and a width between the second left road lane marking and the second right road lane marking.

(66) As mentioned above, the mode for carrying out the present invention has been described by using the embodiment, but the present invention is not limited to the embodiment, and various modifications and replacements may occur within the scope without departing from the spirit of the present invention.

Claims

1. A vehicle control device comprising: a storage device that stores a program; and a hardware processor, wherein the hardware processor executes the program stored in the storage device to: recognize a left road lane marking and a right road lane marking that identifies a lane in which a vehicle is located based on an output received from a camera that detects a surrounding situation of the vehicle, and output a left camera road lane marking and a right camera road lane marking as a first left road lane marking and a first right road lane marking; recognize the left road lane marking and the right road lane marking based on map information, and output a left map road lane marking and a right map road lane marking as a second left road lane marking and a second right road lane marking; determine whether or not there is a left deviation between the first left road lane marking and the second left road lane marking on a left side, and determine whether or not there is a right deviation between the first right road lane marking and the second right road lane marking on a right side; in response to determining that only one of the left deviation and the right deviation is present, set a position at which a predetermined width value is offset from one of the first left road

lane marking and the second left road lane marking, or the first right road lane marking and the second right road lane marking on the side with no deviation, as a center of a target travel path on which the vehicle is to travel in the future; generate the target travel path based on the center of the target travel path; set the predetermined width value based on a smaller width value based on a comparison of a first width value as measured between the first left road lane marking and the first right road lane marking and a second width value as measured between the second left road lane marking and the second right road lane marking; control the vehicle to travel on the target travel path, wherein the hardware processor determines whether or not there is a left deviation based on a left deviation amount between the first left road lane marking and the second left road lane marking, and determines whether or not there is a right deviation based on a right deviation amount between the first right road lane marking and the second right road lane marking, wherein the left deviation amount relates to at least one of a lateral distance between the first left road lane marking and the second left road lane marking, and an angle between the first left road lane marking and the second left road lane marking, and wherein the right deviation amount relates to at least one of a lateral distance between the first right road lane marking and the second right road lane marking, and an angle between the first right road lane marking and the second right road lane marking, wherein the processor determines that there is a left deviation if the lateral distance between the first left road lane marking and the second left road marking is a first threshold value or more and a second threshold value or less, and the angle between the first left road lane marking and the second left road lane marking is a third threshold value or more and a fourth threshold value or less, and wherein the processor determines that there is a right deviation if the lateral distance between the first right road lane marking and the second right road lane marking is the first threshold value or more and the second threshold value or less, and the angle between the first right road lane marking and the second right road lane marking is the third threshold value or more and the fourth threshold value or less.

2. The vehicle control device according to claim 1, wherein the hardware processor determines the left deviation is present in a case where the left deviation amount is equal to or more than a threshold value, and wherein the hardware processor sets the threshold value based on an amount of change in curvature of the first left road lane marking or the first right road lane marking.

3. The vehicle control device according to claim 1, wherein the hardware processor controls steering and acceleration/deceleration of the vehicle regardless of an operation of a driver of the vehicle, wherein the hardware processor determines a driving mode of the vehicle as one of a plurality of driving modes including a first driving mode and a second driving mode, the second driving mode being a driving mode in which a task imposed on the driver requires attentive and inactive driver participation as compared with the first driving mode, some of a plurality of driving modes including at least the second driving mode being controlled by the hardware processor, wherein the hardware processor changes the driving mode of the vehicle to a driving mode in which the task requires attentive and active driver participation when the task related to the determined driving mode is not being executed by the driver, and wherein the hardware processor continues the second driving mode in a case where the driving mode of the vehicle is the second driving mode and the hardware processor generates the target travel path.

4. The vehicle control device according to claim 3, wherein the hardware processor recognizes a traveling trajectory of a preceding vehicle, and wherein, in a case where the traveling trajectory intersects the first left road lane marking or the first right road lane marking, the hardware processor changes the driving mode of the vehicle from the second driving mode to the first driving mode.

5. A vehicle control method to be executed by a computer mounted on a vehicle, the vehicle control method comprising: recognizing a left camera road lane marking and a right camera road lane marking that identifies a lane in which the vehicle is located based on an output received from a camera that detects a surrounding situation of the vehicle, and outputting the left camera road lane

marking and the right camera road lane marking as a first left road lane marking and a first right road lane marking; recognizing a left map road lane marking and a right map road lane marking based on map information, and outputting the left map road lane marking and the right map road lane marking as a second left road lane marking and a second right road lane marking; determining whether or not there is a left deviation between the first left road lane marking and the second left road lane marking on a left side, and determining whether or not there is a right deviation between the first right road lane marking and the second right road lane marking on a right side; in response to determining that only one of the left deviation and the right deviation is present, setting a position at which a predetermined width value is offset from one of the first left road marking and the second left road marking on the side with no deviation as a center of a target travel path on which the vehicle is to travel in the future; generating the target travel path based on the center of the target travel path; setting the predetermined width value based on a smaller width value based on a comparison of a first width value as measured between the first left road lane marking and the first right road lane marking and a second width value as measured between the second left road lane marking and the second right road lane marking; controlling the vehicle to travel on the target travel path; determining whether or not there is a left deviation based on a left deviation amount between the first left road lane marking and the second left road lane marking; determining whether or not there is a right deviation based on a right deviation amount between the first right road lane marking and the second right road lane marking, wherein the left deviation amount relates to at least one of a lateral distance between the first left road lane marking and the second left road lane marking an angle between the first left road lane marking and the second left road lane marking, and wherein the right deviation amount relates to at least one of a lateral distance between the first right road lane marking and the second right road lane marking, and an angle between the first right road lane marking and the second right road lane marking; determining that there is a left deviation if the lateral distance between the first left road lane marking and the second left road marking is a first threshold value or more and a second threshold value or less, and the angle between the first left road lane marking and the second left road lane marking is a third threshold value or more and a fourth threshold value or less; and determining that there is a right deviation if the lateral distance between the first right road lane marking and the second right road lane marking is the first threshold value or more and the second threshold value or less, and the angle between the first right road lane marking and the second right road lane marking is the third threshold value or more and the fourth threshold value or less.

6. A non-transitory computer readable medium storing a program for causing a computer mounted on a vehicle to: recognize a left road lane marking and right road lane marking that identifies a lane in which the vehicle is located based on an output received from a camera that detects a surrounding situation of the vehicle, and output a left camera road lane marking and a right camera road lane marking as a first left road lane marking and a first right road lane marking; recognize the left road lane marking and the right road lane marking based on map information, and output a left map road lane marking and a right map road lane marking as a second left road lane marking and a second right road lane marking; determine whether or not there is a left deviation between the first left road lane marking and the second left road lane marking on a left side, and determine whether or not there is a right deviation between the first right road lane marking and the second right road lane marking on the right side; in response to determining that only one of the left deviation and the right deviation is present set a position at which a predetermined width value is offset from one of the first left road marking and the second left road marking, or the first right road marking and the second right road marking on the side with no deviation as a center of a target travel path on which the vehicle is to travel in the future; generate the target travel path based on the center of the target travel path; set the predetermined width value based on a smaller width value based on a comparison of a first width value as measured between the first left road lane marking and the first right road lane marking and a second width value as measured between the second left road lane

marking and the second right road lane marking; control the vehicle to travel on the target travel path; determine whether or not there is a left deviation based on a left deviation amount between the first left road lane marking and the second left road lane marking; determine whether or not there is a right deviation based on a right deviation amount between the first right road lane marking and the second right road lane marking, wherein the left deviation amount relates to at least one of a lateral distance between the first left road lane marking and the second left road lane marking an angle between the first left road lane marking and the second left road lane marking, and wherein the right deviation amount relates to at least one of a lateral distance between the first right road lane marking and the second right road lane marking, and an angle between the first right road lane marking and the second right road lane marking; determine that there is a left deviation if the lateral distance between the first left road lane marking and the second left road marking is a first threshold value or more and a second threshold value or less, and the angle between the first left road lane marking and the second left road lane marking is a third threshold value or more and a fourth threshold value or less; and determine that there is a right deviation if the lateral distance between the first right road lane marking and the second right road lane marking is the first threshold value or more and the second threshold value or less, and the angle between the first right road lane marking and the second right road lane marking is the third threshold value or more and the fourth threshold value or less.

7. A vehicle control device comprising: a storage device that stores a program; and a hardware processor, wherein the hardware processor executes the program stored in the storage device to: recognize a left road lane marking and a right road lane marking that identifies a lane in which a vehicle is located based on an output received from a camera that detects a surrounding situation of the vehicle, and output a left camera road lane marking and the right camera road lane marking as a first left road lane marking and a first right road lane marking; recognize the left road lane marking and the right road lane marking based on map information, and output a left map road lane marking and a right map road lane marking as a second left road lane marking and a second right road lane marking; recognize a traveling trajectory of a preceding vehicle; determine whether or not there is a left deviation between the first left road lane marking and the second left road lane marking on a left side, and determine whether or not there is a right deviation between the first right road lane marking and the second right road lane marking on a right side; in response to determining that only one of the left deviation and the right deviation is present and the recognized traveling trajectory is determined not to intersect the first left road lane marking or the first right road lane marking, set a position at which a predetermined width value is offset from one of the first left road lane marking and the second left road lane marking, or the first right road marking and the second right road lane marking on the side with no deviation, as a center of a target travel path on which the vehicle is to travel in the future; generate the target travel path based on the center of the target travel path; set the predetermined width value based on a smaller width value based on a comparison of a first width value as measured between the first left road lane marking and the first right road lane marking and a second width value as measured between the second left road lane marking and the second right road lane marking; control the vehicle to travel on the target travel path; determine whether or not there is a left deviation based on a left deviation amount between the first left road lane marking and the second left road lane marking; determine whether or not there is a right deviation based on a right deviation amount between the first right road lane marking and the second right road lane marking, wherein the left deviation amount relates to at least one of a lateral distance between the first left road lane marking and the second left road lane marking an angle between the first left road lane marking and the second left road lane marking, and wherein the right deviation amount relates to at least one of a lateral distance between the first right road lane marking and the second right road lane marking, and an angle between the first right road lane marking and the second right road lane marking; determine that there is a left deviation if the lateral distance between the first left road lane marking and the second left road marking is a

first threshold value or more and a second threshold value or less, and the angle between the first left road lane marking and the second left road lane marking is a third threshold value or more and a fourth threshold value or less; and determine that there is a right deviation if the lateral distance between the first right road lane marking and the second right road lane marking is the first threshold value or more and the second threshold value or less, and the angle between the first right road lane marking and the second right road lane marking is the third threshold value or more and the fourth threshold value or less.
