

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12388790
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Jasner; Marc E. et al.

VPN manager and monitor for VPN connection selection

Abstract

Dependence on Virtual Private Network (VPN) connections to a target source continues to increase along with the need for improved connection reliability and speed. A VPN manager provides an automatic or seamless switching of the routing of data or traffic directed to an initial VPN connection associated with an initial VPN gateway at the target source to a different VPN connection associated with a different VPN gateway of the target source. The VPN manager can select a VPN connection based on a monitored VPN session status. The VPN session status can be based on one or more VPN status parameters. The VPN session status can be customized. Switching routing from an initial VPN connection to a different VPN connection provides a VPN session with the VPN connection that meets the requirements of a user providing an enhanced the Quality of experience (QoE) of a user.

Inventors:	Jasner; Marc E. (Horsham, PA), Ogden; John D. (Media, PA)
Applicant:	ARRIS Enterprises LLC (Suwanee, GA)
Family ID:	82801701
Assignee:	ARRIS ENTERPRISES LLC (Horsham, PA)
Appl. No.:	17/574791
Filed:	January 13, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220263804 A1	Aug. 18, 2022

Related U.S. Application Data

us-provisional-application US 63148821 20210212

Publication Classification

Int. Cl.: H04L9/40 (20220101); H04L43/0811 (20220101); H04L45/30 (20220101);
H04L45/302 (20220101); H04L67/1027 (20220101)

U.S. Cl.:

CPC H04L63/0272 (20130101); H04L43/0811 (20130101); H04L45/306 (20130101);
H04L67/1027 (20130101);

Field of Classification Search

CPC: H04L (63/0272); H04L (43/0811); H04L (45/306); H04L (67/1027); H04L (43/0852);
H04L (43/0876); H04L (43/10)

USPC: 726/15

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9419944	12/2015	Chan	N/A	H04L 41/0893
9813379	12/2016	Shevade	N/A	H04L 45/24
10462171	12/2018	Weingarten	N/A	G06F 8/61
10659325	12/2019	Dam	N/A	H04L 43/045
11604880	12/2022	Robison	N/A	H04L 9/0891
11658984	12/2022	Gujarathi	713/176	H04L 9/3213
11736526	12/2022	Jeong	726/1	H04L 63/1458
11824862	12/2022	Singh	N/A	H04L 63/101
2002/0124090	12/2001	Poier	709/228	H04L 63/061
2012/0059934	12/2011	Rafiq	709/225	H04L 67/1008
2015/0382193	12/2014	Johnson	455/411	H04L 63/08
2016/0359811	12/2015	Chan	N/A	H04L 63/0272
2016/0359866	12/2015	Mixer	N/A	H04L 67/12
2017/0171156	12/2016	Schultz	N/A	H04L 63/0414
2017/0199752	12/2016	Cao	N/A	G06F 11/3409
2017/0366421	12/2016	Dam	N/A	H04L 43/50
2019/0052659	12/2018	Weingarten	N/A	H04L 67/10
2019/0132361	12/2018	Hernandez	N/A	H04L 47/20
2022/0116273	12/2021	Cunningham	N/A	H04L 43/0811
2022/0263804	12/2021	Jasner	N/A	H04L 45/306
2022/0343157	12/2021	Mankowitz	N/A	G06N 3/008
2023/0007030	12/2022	Weingarten	N/A	H04L 41/0894
2023/0061123	12/2022	Low	N/A	H04L 9/30
2023/0119545	12/2022	Kelly	709/238	H04L 45/70
2023/0135587	12/2022	Wraback	726/1	H04L 63/20
2023/0344899	12/2022	Zhu	N/A	H04L 67/1008
2024/0288584	12/2023	Uyeno	N/A	G01S 7/4817

OTHER PUBLICATIONS

Primary Examiner: Arani; Taghi T

Assistant Examiner: Barzegar; Pegah

Attorney, Agent or Firm: Wenderoth, Lind & Ponack, L.L.P.

Background/Summary

BACKGROUND

(1) Many users whether private or associated with entities or organizations are increasingly communicating over multiple types of networks, connections, and systems from multiple locations or sites. Each user may utilize any number of different types of devices with these devices networked together so as to provide access to shared data, resources or services. For example, many users are accessing data, resources and services remotely. Such remote access can create security issues especially with respect to the transmission of and access to sensitive or personal data. A virtual private network (VPN) can provide a secure connection through which users can transmit, send, access, or receive remote data, resources, or services.

(2) With this dependence on VPN to provide secure connections, a need exists to provide increased network performance, for example, increased reliability and speed. Ideally, a VPN connection would provide the best-suited network connection, for example, the fastest, the highest bandwidth and lowest latency, network connection. Generally, VPN client software of a client device allows a user to select a VPN gateway from a list of multiple available gateways. A VPN connection is established between the client device and the VPN gateway and this VPN connection to the VPN gateway is maintained for the client device throughout a VPN session or until disconnection. A VPN connection is established on a per client device basis such that each client device must establish a VPN connection with a selected VPN gateway. This selected VPN gateway is static such that the VPN connection to the selected VPN gateway remains a one-to-one connection until disconnection.

(3) Once a VPN connection is established between a client device and a selected VPN gateway, that VPN connection is maintained even if a different VPN gateway would provide increased network performance or an improved user experience. Thus, there is a need to provide a more dynamic VPN connection experience so as to provide an overall improved network performance and/or user experience.

SUMMARY

(4) Network environments, especially those network environments associated with remote access, can now serve multiple functions for various types of users and client devices that need to connect to remote data, resources or services. For example, the same network can be required to support a variety of users and client devices as well as a variety of VPN connections to various selected VPN gateways so as to provide the users with access to remote data, resources and services. Given the various network activities and access requirements that include substantial reliance on Internet access, especially Wi-Fi Internet access, and increased access to network data, resources and services, it is becoming imperative to provide the best optimized and secure connections to remote data, resources and services to all users and/or client devices in a network environment. These secure connections can be provided using a VPN client software that establishes a VPN connection to a selected VPN gateway. VPN connections are generally made on a per client device basis, with each client device requiring an associated distinct VPN client. A VPN manager that manages and

monitors one or more VPN connections can improve one or more network parameters and/or user experience. For example, the VPN manager can provide various improvements to accessing a VPN gateway via a VPN connection. The VPN manager can be configured to connect to a VPN gateway via one or more corresponding VPN connections, maintain the one or more VPN connections, monitor a status (such as a health status or any other network or connectivity status) of the one or more VPN connections, automatically and transparently route traffic over the VPN connection based on one or more factors, such as the associated status or health of the VPN connection, allow a plurality of client devices to route traffic over any one or more of the VPN connections similar to the way a router allows multiple network devices connected to use the same wide area network (WAN) connection, allow customization of network packet or traffic routing through the different VPN client sessions associated with the VPN connections, provide a control interface for managing the VPN client sessions either locally or remotely, provide access through the VPN client sessions without having to configure the VPN client interface on any given locally connected client device, any combination thereof. Providing an automatic switching of a VPN connection via a selected VPN gateway to a different VPN connection via another VPN gateway that provides an increased or improved network performance can enhance the quality of experience (QoE) of a user associated with a client device.

(5) One or more novel solutions of the present disclosure provide a VPN management device 2 that can comprise a VPN manager. The VPN manager can comprise a VPN configuration manager, a VPN routing manager, a VPN connection monitor, one or more VPN connections, and any combination thereof. The one or more VPN connections provide access to one or more corresponding VPN gateways so that any client device within a network environment can access data, resources or services via the corresponding VPN gateway. The VPN manager can switch routing of traffic or packets via a first VPN connection to another VPN connection based on a status associated with a VPN session and/or one or more VPN connections based on one or more VPN status parameters. The switch can be made automatically so that the user does not experience in any noticeable interruption in the access to data, resources or services.

(6) An aspect of the present disclosure provides a method for a virtual private network (VPN) manager to manage a plurality of VPN connections to a target source via a plurality of VPN gateways. The method comprises receiving, from one or more client devices, data directed to the target source, determining a VPN session status associated with one or more of the plurality of VPN connections, wherein each of the plurality of VPN connections corresponds to a separate one of the plurality of VPN gateways, selecting a first VPN connection of the plurality of VPN connections based on the VPN session status, and routing the data to the first VPN connection.

(7) In an aspect of the present disclosure, the method is such that determining the VPN session status comprises analyzing one or more VPN session status criteria associated with the one or more of the plurality of VPN connections.

(8) In an aspect of the present disclosure, the method further comprises monitoring the VPN session status of the one or more of the plurality of VPN connections, selecting a second VPN connection of the plurality of VPN connections based on the VPN session status, and switching routing of the data from the first VPN connection to the second VPN connection.

(9) In an aspect of the present disclosure, the method is such that monitoring the VPN session status is performed based on a timed interval.

(10) In an aspect of the present disclosure, the method is such that determining the VPN session status comprises performing a load balancing of the plurality of VPN connections.

(11) In an aspect of the present disclosure, the method further comprises determining a type of data associated with the data, wherein determining the VPN session status is based on the type of data, wherein the first VPN connection is associated with a first type of data and a second VPN connection is associated with a second type of data.

(12) In an aspect of the present disclosure, the method further comprises receiving additional data

from an additional client device, determining an additional VPN session status, selecting a second VPN connection of the plurality of VPN connections based on the VPN session status, and routing the additional data to the second VPN connection.

(13) An aspect of the present disclosure provides a virtual private network (VPN) management device. the VPN manager comprises a VPN configuration manager that manages a plurality of VPN connections to a target source via a plurality of VPN gateways, wherein each of the plurality of VPN connections corresponds to a separate one of the plurality of VPN gateways, a VPN connection monitor that determines the VPN session status associated with one or more of the plurality of VPN connections, and a VPN routing manager that receives data from one or more client devices directed to the target source, selects a first VPN connection of the plurality of VPN connections based on the VPN session status, and routes the data to the first VPN connection.

(14) In an aspect of the present disclosure, the VPN manager is such that determining the VPN session status comprises analyzing one or more VPN session status criteria associated with the one or more of the plurality of VPN connections, wherein the VPN session status criteria comprise any of a connection state, a ping speed, a speed test, a throughput rate, a bandwidth, a latency, a received signal strength indicator, and any combination thereof.

(15) In an aspect of the present disclosure, the VPN connection monitor further monitors the VPN session status of the one or more of the plurality of VPN connections, and the VPN routing manager further selects a second VPN connection of the plurality of VPN connections based on the VPN session status and switches routing of the data from the first VPN connection to the second VPN connection.

(16) In an aspect of the present disclosure, the monitoring the VPN session status is performed based on a timed interval.

(17) In an aspect of the present disclosure, the determining the VPN session status comprises performing a load balancing of the plurality of VPN connections.

(18) In an aspect of the present disclosure, the VPN routing manager further determines a type of data associated with the data, the determining the VPN session status is based on the type of data, and the first VPN connection is associated with a first type of data and the second VPN connection is associated with a second type of data.

(19) In an aspect of the present disclosure, the routing manager further receives additional data from an additional client device, the VPN connection monitor determines an additional VPN session status, and the VPN routing manager further selects a second VPN connection of the plurality of VPN connections based on the additional VPN session status and routes the additional data to the second VPN connection.

(20) An aspect of the present disclosure provides a non-transitory computer-readable medium storing one or more instructions for managing a plurality of virtual private network (VPN) connections to a target source via a plurality of VPN gateways. The one or more instructions, that when executed by a processor, cause the processor to perform one or more operations including the steps of the methods described above.

(21) The above-described network device(s) or electronic apparatus(es), such as a target source, a VPN management device, an access point device, an extender access point device, a client device, and any other network devices, may be implemented as any of a residential network access point device, an electronic device (for example, a server, a mobile phone, a computing device such as a notebook computer, or both) according to some example embodiments.

(22) Thus, according to various aspects of the present disclosure described herein, it is possible to automatically switch a VPN connection associated with a client device from an original VPN gateway to a different VPN gateway to enhance the network performance and/or QoE of a user.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) In the drawings, like reference numbers generally indicate identical, functionally similar, and/or structurally similar elements.
- (2) FIG. 1A is a schematic diagram of a network environment, according to one or more aspects of the present disclosure;
- (3) FIG. 1B is a schematic diagram of a network environment, according to one or more aspects of the present disclosure;
- (4) FIG. 2 is a more detailed block diagram illustrating various components of an exemplary VPN management device, client device, and extender access point device implemented in a network environment of FIG. 1A and/or FIG. 1B, according to one or more aspects of the present disclosure;
- (5) FIG. 3 is a block diagram illustrating various connections between a client device and a target source utilizing a VPN manager, according to one or more aspects of the present disclosure;
- (6) FIG. 4 is an illustration of switching a VPN connection to a VPN gateway utilizing a VPN manager, according to one or more aspects of the present disclosure;
- (7) FIGS. 5A, 5B, 5C, and 5D are block diagrams illustrating various connections between a client device and one or more VPN gateways, according to one or more aspects of the present disclosure;
- (8) FIG. 6 is an illustration of one or more components of a VPN management device, according to one or more embodiments of the present disclosure; and
- (9) FIG. 7 is a flow chart illustrating managing, monitoring and configuring a VPN connection utilizing a VPN manager, according to one or more aspects of the present disclosure.

DETAILED DESCRIPTION

- (10) The following detailed description is made with reference to the accompanying drawings and is provided to assist in a comprehensive understanding of various example embodiments of the present disclosure. The following description includes various details to assist in that understanding, but these are to be regarded merely as examples and not for the purpose of limiting the present disclosure as defined by the appended claims and their equivalents. The words and phrases used in the following description are merely used to enable a clear and consistent understanding of the present disclosure. In addition, descriptions of well-known structures, functions, and configurations may have been omitted for clarity and conciseness. Those of ordinary skill in the art will recognize that various changes and modifications of the examples described herein can be made without departing from the spirit and scope of the present disclosure.
- (11) FIG. 1A is a schematic diagram of a network environment **100A**, according to one or more aspects of the present disclosure.
- (12) It should be appreciated that various example embodiments of inventive concepts disclosed herein are not limited to specific numbers or combinations of devices, and there may be one or multiple of some of the aforementioned electronic apparatuses or network devices in the network environment, which may itself consist of multiple communication networks and various known or future developed wireless connectivity technologies, protocols, devices, and the like.
- (13) As shown in FIG. 1A, the main elements of the network environment **100A** include a network comprising a VPN management device **2** connected to a target source **102** via Internet or WAN **6**, for example, by connecting to an Internet Service Provider (ISP) **1**. VPN management device **2** can also be connected to different wireless devices and/or network devices such as one or more wireless extender access point devices **3**, one or more client devices **4**, or both. The network environment **100A** shown in FIG. 1A includes wired and/or wireless network devices (e.g., extender access point devices **3** and client devices **4**) that may be connected in one or more wireless networks (e.g., private, guest, iControl, backhaul network, or Internet of things (IoT) network) within the network environment **100A**. Additionally, there could be some overlap between network devices (e.g., extender access point devices **3** and client devices **4**) in the different networks. That

is, one or more network or wireless devices could be located in more than one network. For example, the extender access point devices **3** could be located both in a private network for providing content and information to a client device **4** and also included in a backhaul network or an iControl network.

(14) The ISP **1** can be, for example, a content provider or any computer for connecting the VPN Management device **2** to the Internet **6**, the target source **102**, or both. For example, Internet **6** can be a cloud-based service that provides access to a target source **102**. In one or more embodiments, target source **102** may be accessible via one or more VPN gateways located within or coupled to the target source **102** which allow for one or more VPN connections. The connections **14** between the Internet **6** and the ISP **1** and target source **102** and the connection **13** between the ISP **1** and the VPN management device **2** can be implemented using a WAN, a VPN, metropolitan area networks (MANs), system area networks (SANs), a data over cable service interface specification (DOCSIS) network, a fiber optics network (e.g., FTTH (fiber to the home) or FTTX (fiber to the x), or hybrid fiber-coaxial (HFC)), a digital subscriber line (DSL), a public switched data network (PSDN), a global Telex network, or a 2G, 3G, 4G, 5G, or 6G network, for example.

(15) The connection **13** can further include as some portion thereof a broadband mobile phone network connection, an optical network connection, or other similar connections. For example, the connection **13** can also be implemented using a fixed wireless connection that operates in accordance with, but is not limited to, 3rd Generation Partnership Project (3GPP) Long Term Evolution (LTE), 5G, or 6G protocols. It is also contemplated by the present disclosure that connection **13** is capable of providing connections between the VPN management device **2** and a wireless area network (WAN), a local area network (LAN), a VPN, a MAN, a personal area network (PAN), a wireless local area network (WLAN), a SAN, a DOCSIS network, a fiber optics network (e.g., FTTH, FTTX, or HFC), a PSDN, a global Telex network, or a 2G, 3G, 4G, 5G or 6G network, for example.

(16) The VPN management device **2** can comprise, for example, an access point and/or a hardware electronic device that may be a combination modem and gateway that combines the functions of a modem, an access point (AP), a router, a network switch, a gateway, a Wi-Fi hotspot device, any other suitable network device, and/or any combination thereof for providing data and/or traffic received from the target source **102** via ISP **1** to one or more network devices (e.g., wireless extender access point devices **3** and client devices **4**) in the network environment **100A**. In one or more embodiments, the VPN management device **2** is included within or part of any of a client device **4**, a remote server (as discussed with reference to FIG. **1A**, one or more network devices, or any combination thereof. It is also contemplated by the present disclosure that the VPN management device **2** can include the function of, but is not limited to, a universal plug and play (UPnP) simple network management protocol (SNMP), an Internet Protocol/Quadrature Amplitude Modulator (IP/QAM) set-top box (STB) or smart media device (SMD) that is capable of decoding audio/video content, and playing over-the-top (OTT) or multiple system operator (MSO) provided content. The VPN management device **2** may also be referred to as a router, server, residential gateway, a home network gateway, or a wireless access point (AP), and any combination thereof. The VPN management device **2** can provide access to a target source **102** by the one or more client devices via a VPN connection.

(17) The connection **9** between the VPN management device **2**, the wireless extender access point devices **3**, and client devices **4** can be implemented using any of a wired connection, a wireless connection in accordance with any IEEE 802.11 Wi-Fi protocols, Bluetooth protocols, BLE, or other short range protocols that operate in accordance with a wireless technology standard for exchanging data over short distances using any licensed or unlicensed band such as the citizens broadband radio service (CBRS) band, 2.4 GHz bands, 5 GHz bands, 6 GHz bands, or 60 GHz bands, or any combination thereof. Additionally, the connection **9** can be implemented using a wireless connection that operates in accordance with, but is not limited to, RF 4CE protocol,

ZigBee protocol, Z-Wave protocol, IEEE 802.15.4 protocol, any other protocol, or any combination thereof. It is also contemplated by the present disclosure that the connection **9** can include connections to a media over coax (MoCA) network. One or more of the connections **9** can also be a wired Ethernet connection. Any one or more of connections **9** can carry information on any of one or more channels that are available for use.

(18) The extender access point devices **3** can be, for example, wireless hardware electronic devices such as access points (APs), extenders, repeaters, etc. used to extend the wireless network by receiving the signals transmitted by the VPN management device **2** and rebroadcasting the signals to, for example, client devices **4**, which may be out of range of the access point device **2**. The extender access point devices **3** can also receive signals from the client devices **4** and rebroadcast the signals to the VPN management device **2**, or other client devices **4**.

(19) The connection **11** between the extender access point devices **3** and the client devices **4** are implemented through a wireless connection that operates in accordance with any IEEE 802.11 Wi-Fi protocols, Bluetooth protocols, Bluetooth low energy (BLE), or other short range protocols that operate in accordance with a wireless technology standard for exchanging data over short distances using any licensed or unlicensed band such as the CBRS band, 2.4 GHz bands, 5 GHz bands, 6 GHz bands or 60 GHz bands. Additionally, the connection **11** can be implemented using a wireless connection that operates in accordance with, but is not limited to, RF4CE protocol, ZigBee protocol, Z-Wave protocol, IEEE 802.15.4 protocol, any other protocol, or any combination thereof. Also, one or more of the connections **11** can be a wired Ethernet connection. Any one or more connections **11** can carry information on any one or more channels that are available for use.

(20) The client devices **4** can be, for example, hand-held computing devices, personal computers, electronic tablets, mobile phones, smart phones, smart speakers, Internet-of-Things (IoT) devices, iControl devices, portable music players with smart capabilities capable of connecting to the Internet, cellular networks, and interconnecting with other devices via any of a wired connection, Wi-Fi, Bluetooth, and any combination thereof, or other wireless hand-held consumer electronic devices capable of accessing a wireless network. For example, any one or more client devices **4** can be a mobile network device capable of connecting to a wireless network and provisioning the VPN management device **2** to provide a 6 GHz wireless frequency band network. Additionally, any one or more client devices **4** can be a television (TV), an IP/QAM set-top box (STB) or a streaming media decoder that is capable of decoding audio/video content, and playing over OTT or MSO provided content received through the VPN management device **2**.

(21) The connection **10** between the VPN management device **2** and the client device **4** can be implemented through a wired connection, a wireless connection that operates in accordance with, but is not limited to, any IEEE 802.11 protocols, or both. Additionally, the connection **10** between the VPN management device **2** and the client device **4** can also be implemented through a WAN, a LAN, a VPN, MANs, PANs, WLANs, SANs, a DOCSIS network, a fiber optics network (e.g., FTTH, FTTX, or HFC), a PSDN, a global Telex network, or a 2G, 3G, 4G, 6G, or 5G network, for example. The connection **10** can also be implemented using a wireless connection in accordance with Bluetooth protocols, BLE, or other short range protocols that operate in accordance with a wireless technology standard for exchanging data over short distances using any licensed or unlicensed band such as the CBRS band, 2.4 GHz bands, 5 GHz bands, 6 GHz bands, or 60 GHz bands. One or more of the connections **10** can also be a wired Ethernet connection.

(22) A detailed description of the exemplary internal components of the VPN management device **2**, the extender access point devices **3**, and the client devices **4** shown in FIG. 1A and/or FIG. 1B will be provided in the discussion of FIG. 2. However, in general, it is contemplated by the present disclosure that the VPN management device **2**, the extender access point devices **3**, and the client devices **4** include electronic components or electronic computing devices operable to receive, transmit, process, store, and/or manage data and information associated with the network environment **100A**, which encompasses any suitable processing device adapted to perform

computing tasks consistent with the execution of computer-readable instructions stored in a memory or a computer-readable recording medium (e.g., a non-transitory computer-readable medium).

(23) Further, any, all, or some of the computing components in the VPN management device **2**, the extender access point devices **3**, and the client devices **4** may be adapted to execute any operating system, including Linux, UNIX, Windows, MacOS, DOS, and ChromOS as well as virtual machines adapted to virtualize execution of a particular operating system, including customized and proprietary operating systems. The VPN management device **2**, the extender access point devices **3**, and the client devices **4** are further equipped with components to facilitate communication with other computing devices or network devices over the one or more network connections to local and wide area networks, wireless and wired networks, public and private networks, and any other communication network enabling communication in the network environment **100A**.

(24) FIG. **1B** is a schematic diagram of a network environment **100B**, according to one or more aspects of the present disclosure. The various elements and connections of FIG. **1B** are similar to or the same as those of FIG. **1A** except that the VPN management device **2** is located remote from the extender access point devices **3** and the client devices **4**. The network device **104** can comprise, for example, a residential gateway, an access point and/or a hardware electronic device that may be a combination modem and gateway that combines the functions of a modem, an access point (AP), and/or a router for providing content received from the ISP **1** to one or more network devices (e.g., wireless extender access point devices **3** and client devices **4**) in the network environment **100B**. In one or more embodiments, the network device **104** is a client device **4** configured to connect to any of an ISP **1**, a VPN management device **2**, any other network devices, or a combination thereof. The functionality of the VPN management device **2** of FIG. **1B** is the same as that of FIG. **1A** except that the VPN management device **2** connects to ISP **1** via connection **14** and/or to network device **104** via connection **13**. For example, the VPN management device **2** can connect to the one or more extender access point devices **3** and client devices via a network device **104** and/or via ISP **1** to a network device **104**.

(25) FIG. **2** is a more detailed block diagram illustrating various components of an exemplary access point device, client device, and wireless extender implemented in the network environment **100** of FIG. **1**, according to one or more aspects of the present disclosure.

(26) Although FIG. **2** only shows one extender access point device **3** and one client device **4**, the extender access point device **3** and the client device **4** shown in the figure are meant to be representative of the other extender access point devices **3** and client devices **4** of a network system, for example, network environment **100A** and/or **100B** shown in FIG. **1** and/or FIG. **1B**, respectively. Similarly, the connections **9** between the VPN management device **2**, the extender access point device **3**, and the client device **4** shown in FIG. **2** are meant to be exemplary connections and are not meant to indicate all possible connections between the access point devices **2**, extender access point devices **3**, and client devices **4**. Additionally, it is contemplated by the present disclosure that the number of VPN management devices **2**, extender access point devices **3**, and client devices **4** is not limited to the number of access point devices **2**, extender access point devices **3**, and client devices **4** shown in FIGS. **1A**, **1B** and **2**.

(27) The client device **4** includes a power supply **28**, a user interface **29**, a network interface **30**, a memory **31**, and a controller **33**. The power supply **28** supplies power to the internal components of the client device **4** through the internal bus **34**. The power supply **28** can be a self-contained power source such as a battery pack with an interface to be powered through an electrical charger connected to an outlet (e.g., either directly or by way of another device). The power supply **28** can also include a rechargeable battery that can be detached allowing for replacement such as a nickel-cadmium (NiCd), nickel metal hydride (NiMH), a lithium-ion (Li-ion), or a lithium Polymer (Li-pol) battery. The user interface **29** includes, but is not limited to, push buttons, a keyboard, a

keypad, a liquid crystal display (LCD), a thin film transistor (TFT), a light-emitting diode (LED), a high definition (HD) or other similar display device including a display device having touch screen capabilities so as to allow interaction between a user and the client device **4**, for example, so as to connect to a VPN gateway via a VPN connection, as discussed with reference to FIGS. **3-5**. In one or more embodiments, user interface **29** provides an interface for a user, such as a graphical user interface, to select a VPN gateway. The network interface **30** can include, but is not limited to, various network cards, interfaces, and circuitry implemented in software and/or hardware to enable communications with the VPN management device **2**, the extender access point device **3**, ISP **1**, Internet **6**, target source **102** using any one or more of the communication protocols in accordance with connection **9** (e.g., as described with reference to FIG. **1A** and/or FIG. **1B**).

(28) The memory **31** includes a single memory, one or more memories, or one or more memory locations that include, but are not limited to, a random access memory (RAM), a dynamic random access memory (DRAM) a memory buffer, a hard drive, a database, an erasable programmable read only memory (EPROM), an electrically erasable programmable read only memory (EEPROM), a read only memory (ROM), a flash memory, logic blocks of a field programmable gate array (FPGA), a hard disk or any other various layers of memory hierarchy. The memory **31** can be used to store any type of instructions, software, or algorithms including software **32** for controlling the general function and operations of the client device **4** in accordance with the embodiments described in the present disclosure. In one or more embodiments, software **32** can be VPN client software that provides for a connection to the VPN management device **2** so as to access data, resources, and/or services via a VPN connection to a VPN gateway of the of the target source **102**. Memory **31** can store the VPN client software and information.

(29) The controller **33** controls the general operations of the client device **4** and includes, but is not limited to, a central processing unit (CPU), a hardware microprocessor, a hardware processor, a multi-core processor, a single core processor, a field programmable gate array (FPGA), a microcontroller, an application specific integrated circuit (ASIC), a digital signal processor (DSP), or other similar processing device capable of executing any type of instructions, algorithms, or software including the software **32** for controlling the operation and functions of the client device **4** in accordance with the embodiments described in the present disclosure, such as provisioning access point device **2**. Communication between the components (e.g., **28-31** and **33**) of the client device **4** may be established using an internal bus **34**.

(30) The extender access point device **3** can be, for example, any wireless hardware electronic device used to extend a wireless network by receiving the signals transmitted by the VPN management device **2** and rebroadcasting the signals to any one or more client devices **4**, which may be out of range of the access point device **2** including, but not limited to, a wireless extender, a repeater, and/or an access point. The extender access point device **3** can also receive signals from any one or more of the client devices **4** and rebroadcast the signals to the access point device **2** or any other one or more client devices **4**. In one or more embodiments, the VPN management device **2** is replaced with a network device **104** and the VPN management device **2** is remote from the extender access point device **3** and the client device **4**.

(31) As shown in FIG. **2**, the extender access point device **3** includes a user interface **46**, a power supply **47**, a network interface **48**, a memory **49**, and a controller **51**. The user interface **46** can include, but is not limited to, one or more push buttons, a keyboard, a keypad, an LCD, a TFT, an LED, an HD or other similar display device including a display device having touch screen capabilities so as to allow interaction between a user and the extender access point device **3**. The power supply **47** supplies power to the internal components of the wireless extender access point device **3** through the internal bus **53**. The power supply **47** can be connected to an electrical outlet (e.g., either directly or indirectly by way of another device) via a cable or wire. The network interface **48** can include various network cards, interfaces, and circuitry implemented in software and/or hardware to enable communications with the client device **4** and the VPN management

device **2** using the communication protocols in accordance with connection **9** (e.g., as described with reference to FIG. **1**). For example, the network interface **48** can include multiple radios or sets of radios (e.g., a 2.4 GHz radio, one or more 5 GHz radios, and/or a 6 GHz radio), which may also be referred to as WLAN interfaces. One radio or set of radios (e.g., 5 GHz and/or 6 GHz radio(s)) provides a backhaul connection between the wireless extender access point device **3** and the access point device **2**, and optionally other wireless extender access point device(s) **3**. Another radio or set of radios (e.g., 2.4 GHz, 5 GHz, and/or 6 GHz radio(s)) provides a fronthaul connection between the extender access point device **3** and one or more client device(s) **4**.

(32) The memory **49** can include a single memory or one or more memories or memory locations that include, but are not limited to, a RAM, a DRAM, a memory buffer, a hard drive, a database, an EPROM, an EEPROM, a ROM, a flash memory, logic blocks of an FPGA, hard disk or any other various layers of memory hierarchy. The memory **49** can be used to store any type of instructions, software, or algorithm including software **50** associated with controlling the general functions and operations of the wireless extender access point device **3** in accordance with the embodiments described in the present disclosure. In one or more embodiments, extender access point device **3** is a network device and software **50** includes one or more instructions for establishing a connection with the VPN management device **2**, the network device **104**, and/or a client device **4**. The controller **51** controls the general operations of the wireless extender access point device **3** and can include, but is not limited to, a CPU, a hardware microprocessor, a hardware processor, a multi-core processor, a single core processor, an FPGA, a microcontroller, an ASIC, a digital signal processor (DSP), or other similar processing device capable of executing any type of instructions, algorithms, or software for controlling the operation and functions of the wireless extender access point device **3** in accordance with the embodiments described in the present disclosure. General communication between the components (e.g., **46-51**) of the extender access point device **3** may be established using the internal bus **53**.

(33) The VPN management device **2** can be, for example, a hardware electronic device that can combine one or more functions of any of a modem, a gateway, an access point (AP), a router, or combinations thereof for providing a VPN connection between network or wireless devices (e.g., extender access point devices **3**, client devices **4**) in the system to a VPN gateway of a target source **102**. Besides providing a VPN connection, the VPN management device **2** can also provide the functionality of an IP/QAM STB, an SMD, or any other decoder that is capable of decoding audio/video content, and playing OTT or MSO provided content.

(34) As shown in FIG. **2**, the VPN management device **2** includes a user interface **20**, a network interface **21**, a power supply **22**, a wide area network (WAN) interface **23**, a memory **24**, and a controller **26**. The user interface **20** can include, but is not limited to, one or more push buttons, a keyboard, a keypad, an LCD, a TFT, an LED, an HD or other similar display device including a display device having touch screen capabilities so as to allow interaction between a user and the VPN management device **2**. In one or more embodiments, the user interface **20** provides an interface, such as a command-line interface, a graphical user interface, an interface output port for connection to a display, and/or any other type of user interface.

(35) The network interface **21** may include various network cards, and circuitry implemented in software and/or hardware to enable communications with the extender access point device **3** and the client device **4** using the communication protocols in accordance with connection **9** (e.g., as described with reference to FIG. **1**). Additionally, the various network cards, interfaces, and circuitry of the network interface **21** enable communications with a client device **4** (e.g., a mobile device) using the one or more communication protocols in accordance with connection **10** (e.g., as described with reference to FIG. **1**). For example, the network interface **21** can include an Ethernet port (also referred to as a LAN interface) and multiple radios or sets of radios (e.g., a 2.4 GHz radio, one or more 5 GHz radios, and/or a 6 GHz radio, also referred to as WLAN interfaces). One radio or set of radios (e.g., 5 GHz and/or 6 GHz radio(s)) provides a backhaul connection between

the VPN management device **2** and the wireless extender access point device(s) **3**. Another radio or set of radios (e.g., 2.4 GHz, 5 GHz, and/or 6 GHz radio(s)) provides a fronthaul connection between the access point device **2** and one or more client device(s) **4**. In one or more embodiments, the network interface **21** interfaces with a VPN gateway of the target source **102**.

(36) The power supply **22** supplies power to the internal components of the access point device **2** through the internal bus **27**. The power supply **22** can be connected to an electrical outlet (e.g., either directly or by way of another device) via a cable or wire. The wide area network (WAN) interface **23** may include various network cards, and circuitry implemented in software and/or hardware to enable communications between the VPN management device **2** and the ISP **1** using the wired and/or wireless protocols in accordance with connection **13** (e.g., as described with reference to FIG. **1**).

(37) The memory **24** includes a single memory, one or more memories, or one or more memory locations that include, but are not limited to, a RAM, a DRAM, a memory buffer, a hard drive, a database, an EPROM, an EEPROM, a ROM, a flash memory, logic blocks of a FPGA, hard disk or any other various layers of memory hierarchy. The memory **24** can be a non-transitory computer-readable storage medium used to store any type of instructions, software, or algorithm including software **25** for providing a VPN connection to a VPN gateway of the target source **102** such that any one or more client devices **4** can access one or more data, resources and/or services associated with the target source **102** via the VPN connection. In one or more embodiments, memory **24** comprises one or more elements as discussed with reference to FIG. **6**.

(38) FIG. **6** illustrates one or more components of a VPN management device **2**, in particular, memory **4**, according to one or more embodiments of the present disclosure. The VPN management device **2** can comprise a memory **24**. Memory **24** can comprise one or more storage locations for storing one or more variables and/or values associated with a software **25**, such as those discussed with respect to a VPN manager **310** in reference to FIG. **3**. For example, memory **24** can include one or more VPN session authorization parameters **630**, a VPN status parameter configuration **610** (for example, TABLE 1) and a VPN session status configuration **620** (for example, TABLE 2) as discussed with reference to FIG. **3**. VPN status parameter configuration **610** and VPN session status configuration **620** can comprise a database, a data structure, a flat-file system, any other storage medium, or any combination thereof. VPN status parameter configuration **610** can include a VPN status parameter **612** and a weight **614** associated with the VPN status parameter **612**. VPN session status configuration **620** can include a VPN gateway identifier **622**, a VPN session status criteria **624** associated with the VPN gateway identifier **622**, and a VPN session status frequency **626** associated with the VPN session status criteria **624**. In one or more embodiments, any one or more elements of the VPN status parameter configuration **610** and/or the VPN session status configuration **620** are customizable, for example, by a user, such as a representative of an employer or other entity, a superuser, an information technology specialist, any other type of user, or any combination thereof. In one or more embodiments, a VPN session status **632** can be determined and/or stored based on a VPN status parameter configuration **610**, for example.

(39) The controller **26** controls the general operations of the VPN management device **2** as well as connectivity to the network by one or more other network devices (wireless extender access point devices **3** and client device **4**). The controller **26** can include, but is not limited to, a central processing unit (CPU), a network controller, a hardware microprocessor, a hardware processor, a multi-core processor, a single core processor, a FPGA, a microcontroller, an ASIC, a DSP, or other similar processing device capable of executing any type of instructions, algorithms, or software including the software **25** in accordance with the embodiments described in the present disclosure. Communication between the components (e.g., **20-24**, and **26**) of the access point device **2** may be established using the internal bus **27**. The controller **26** may also be referred to as a processor, generally.

(40) FIG. **3** is a block diagram illustrating various connections between a client device **4** and a

target source **102** utilizing a VPN manager **310** of a VPN management device **2**, for example, a network environment **300** that is similar to or the same as a network environment **100A** or **100B** of FIG. **1A** or FIG. **1B**, respectively, according to one or more aspects of the present disclosure.

(41) The network environment **300** can include one or more client devices **4**, for example, client devices **4A**, **4B** and **4N** (collectively referred to as client device(s) **4**), where N represents any number of client devices **4**. Each client device **4** can connect to a VPN management device **2** as discussed with respect to FIGS. **1A**, **1B** and/or **2**. Each client device **4** can be associated with a single user, different users, or a plurality of users. While FIG. **3** illustrates different types of client devices **4**, such as a laptop (client device **4A**), a smart phone (client device **4B**), and a computer (client device **4N**), the present disclosure contemplates that network environment **300** can include any one or more client devices **4** of any one or more types as discussed, for example, with respect to FIG. **1A**, or a single client device **4**.

(42) The VPN management device **2** can comprise a VPN Manager **310** that manages, configures, establishes, monitors, and any combination thereof one or more VPN sessions **350** between a client device **4** and the target source **102**. The VPN Manager **310** can comprise a VPN configuration manager **302**, a VPN routing manager **304**, a VPN connection monitor **306**, and one or more VPN connections **308**, such as VPN connections **308A**, **308B**, and **308N** (collectively referred to as VPN connection(s) **308**), where N represents any number of VPN connections **308**. In one or more embodiment, the VPN manager **310** can be remotely managed, pre-configured, dynamically configured, or any combination thereof.

(43) The VPN routing manager **304** can be coupled to the VPN configuration manager **302** and VPN connection monitor **306** via a connection **312** and a connection **314**, respectively. The VPN configuration manager **304** configures any one or more VPN sessions **350** associated with any one or more client devices **4** such that data can be transmitted to and/or received from a corresponding VPN gateway **330**. The VPN configuration manager **302** can access one or more VPN session authorization parameters **630**, for example, from a memory **24**. The one or more VPN session authorization parameters **630** can comprise any of a uniform resource location (URL), client device type, one or more auxiliary applications, one or more credentials, one or more authentication parameters, any other VPN session authorization parameters associated with a VPN session **350**, or any combination thereof. In one or more embodiments, one or more VPN authorization parameters **630** can be associated with a keep alive function and/or such that the VPN manager **310** maintains or prevents expiration of any one or more VPN sessions **350** and/or corresponding VPN connections **308**. The one or more VPN session authorization parameters **630** can be utilized by the VPN configuration manager **302** to establish one or more VPN connections **308**. For example, the VPN configuration manager **302** can utilize the one or more VPN session authorization parameters to accommodate one or more configuration options of a client device **4**. The VPN configuration manager **302** can send and receive data to the one or more VPN connections **308** via one or more paths **322**. For example, the VPN configuration manager **302** can provide to the VPN connection **308** via the path **322** any required one or more VPN session authorization parameters **630** such that encrypted data or traffic **328** can be transmitted to and/or received from a VPN gateway **330**. In one or more embodiments, the VPN configuration manager **302** is a secure remote server such that the VPN manager **310** can configure a VPN connection **308** between the client device **4** and a remote resource or network as the target source, for example, an Internet address across a regional border.

(44) The VPN Routing Manager **304** receives requests from one or more client devices **4** to establish one or more VPN sessions **350** and routes data and/or traffic from the one or more client devices **4** to an associated VPN connection **308** and routes data and/or traffic from the one or more VPN connections **308** to the associated one or more client devices **4**. For example, client devices **4A**, **4B**, and **4N** can be connected to the VPN routing manager via one or more connections **320A**, **320B**, and **320N** (collectively referred to as connection(s) **320**), respectively, and can be associated with VPN sessions **350A**, **350B**, and **350N** (collectively referred to as connection(s) **350**),

respectively. The one or more connections **320** can be the same as or similar to any one or more connections discussed with reference to FIGS. **1A** and **1B**. The VPN routing manager **304** can send a command to the VPN configuration manager **302** via path **312** for the VPN configuration manager to establish one or more VPN connections **308A**, **308B**, and/or **308N** (collectively referred to as VPN connection(s) **308**, where N represents any number of VPN connections **308**) to a corresponding VPN gateway **330A**, **330B** and/or **330N** (collectively referred to as VPN gateway(s) **330**, where N represents any number of VPN gateways **330**), respectively, for an associated VPN session **350**. Any one or more VPN sessions **350** and/or one or more VPN connections **308** can be based on a VPN status parameter **612** associated with a VPN connection **308**, a VPN gateway **330**, or both. The VPN routing manager **304** routes data and/or traffic received from a client device **4** to a corresponding VPN connection **308** for transmission as encrypted data **328** to an associated gateway **330**. Similarly, the VPN routing manager **304** routes data and/or traffic received from a VPN gateway **330** as encrypted data **328** to a corresponding VPN connection **308** to the associated client device **4**. For example, the VPN Routing manager **304** can request that the VPN configuration manager **302** establish a VPN connection **308A** to VPN gateway **330A**, a VPN connection **308B** to VPN gateway **330B**, and/or a VPN connection **308N** to VPN gateway **330N** such that encrypted data and/or traffic **328A**, **328B** and/or **328N**, respectively, can be transmitted over Internet **6** between the one or more VPN gateways **330** and the associated one or more VPN connections **308**.

(45) The VPN connection monitor **306** monitors one or more VPN status parameters **612** associated with a VPN session **350** via paths **326** to the one or more VPN connections **308**. The VPN connection monitor **306** can transmit the one or more VPN status parameters **612** to the VPN routing manager **304** via path **314** based on a time parameter, such as any of routinely, periodically, at timed intervals, randomly, any other time parameter, or any combination thereof. In one or more embodiments, the VPN routing manager **304** can any of routinely, periodically, at timed intervals, randomly, any other time variable, and any combination thereof, request the one or more VPN status parameters **612** associated with a VPN session **350** from the VPN connection monitor **306**. The VPN routing manager **304** can utilize the one or more VPN status parameters **612** to determine selection of a VPN connection **308** for associating with any particular VPN session **350** such that the VPN connection **308** associated with any VPN session **350** can be switch to a different VPN connection **308**. The one or more VPN status parameters **612** can be configurable via a user interface **20** of the VPN management device **2**, a user interface **29**, or any combination thereof. In one or more embodiments, any of the one or more VPN status parameters **612** can be associated with a weight or priority **614**. For example, the weight **614** associated with a VPN status parameter **612** can be different based on a given VPN session **350**. One or more VPN status parameters **612** can comprise any one or more network connection parameters, one or more factors associated with a type of data, a type of client device **4**, a resource, and/or a service to be accessed, one or more laws, restrictions, regulations, or other access tax, location of a client device, ISP **1**, access management device **2**, or any other network device associated with the client device, or any combination thereof, type of data encryption, one or more security requirements, any other one or more factors, or any combination thereof. For example, TABLE 1 illustrates a VPN status parameter configuration **610** that has been customized such that each VPN status parameter **612** (P) has a corresponding weight **614** (W). In one or more embodiments, the weight or priority **614** can comprise any numerical value, such as a whole number, a decimal value, or any other numerical representation. In one or more embodiments, the VPN routing manager **304** can determine the VPN connection **308** to select for a given VPN session **350** associated with a client device **4** based on a VPN session status criteria **624** associated with any of the one or more VPN connections **308**. A VPN session status **632** can be determined for each VPN session **350** based on the VPN session status criteria **624**. The VPN session status criteria **624** can comprise any of one or more VPN status parameters **612**, such as any one or more of the VPN status parameters **612** listed in TABLE

1, one or more selection algorithms, or both. A selection algorithm can comprise a summation of any one or more VPN status parameters **612**, any one or more VPN status parameters **612** weighted by an associated weight **614**, a cost function that utilizes any one or more VPN status parameters **612** and/or one or more associated weights **614**, a load balancing function, an optimization algorithm that utilizes any one or more VPN status parameters **612** and/or one or more associated weights **614**, any other selection algorithm or any combination thereof. The VPN routing manager **304** can automatically or seamlessly switch the present and/or initial VPN connection **308** associated with a VPN session **350** for a client device **4** to a different VPN connection based on a VPN session status **632** associated with a VPN session **350** and/or a VPN gateway **330**.

(46) TABLE-US-00001 TABLE 1 VPN Status Parameter Configuration. WEIGHT/ VPN STATUS PARAMETER (P) PRIORITY (W) 1 Connection state of a VPN session 350 and/ W.sub.1 or VPN connection 308 2 Ping speed associated with a VPN connection 308 W.sub.2 3 Speed test associated with a VPN connection 308 W.sub.3 4 Throughput rate associated with a VPN W.sub.4 connection 308 5 Latency associated with a VPN connection 308 W.sub.5 6 Type of traffic based on packet inspection/Type of W.sub.6 data associated with a client device 4 (such as data associated with one or more data privacy restrictions, rules, or laws, encrypted data, financial data, health data, etc.) 7 Location of VPN gateway 330 W.sub.7 8 Encryption type W.sub.8 9 Bandwidth associated with a VPN connection 308 W.sub.9 10 Data privacy regulations W.sub.10 11 Load balancing W.sub.11 12 Connection type (e.g., HTTP, SSH, etc.) W.sub.12 N <additional VPN status parameter> W.sub.N

Selection Algorithm= $\sum_{i=1}^{NP} W_{sub.i}$ EQUATION 1,
where N represents any value.

(47) For example, a client devices **4A**, **4B**, and **4C** can be utilized by one or more users within a home network environment that has a subscription to a VPN service at target source **102**. Each client device **4** may be associated with a different type of traffic. A VPN status parameter configuration **610** can indicate that traffic from one or more client devices **4** is routed to a VPN connection **308** based on a type of traffic (such as the VPN status parameter **612** at row 6 of TABLE 1). For example, the VPN status parameter **612** can indicate that traffic associated with a game or financial transaction is routed to the VPN connection **308** with the lowest latency, telephone audio is routed to the VPN connection **308** with the best quality of service (QoS), data transfer traffic is routed to the VPN connection **308** with the highest throughput. In this way, the traffic associated with a client device **4** is routed by the VPN manager **310** to the VPN connection **308** that provides an efficient use of network resources and/or QoE for an associated user.

(48) In one or more embodiments, the VPN routing manager **304** can determine the VPN connection **308** for selection based on a customized VPN session status **632**. For example, a user, a system administrator, any other authorized operator, or any combination thereof can configure the VPN routing manager **304** to utilize any combination of one or more VPN status parameters **612**, one or more weights **614**, one or more VPN session status criteria **624**, any other factor, or any combination thereof to determine the VPN connection **308** for selection. For example, TABLE 2 illustrates a customized VPN session status configuration **620** associated with a VPN session **350**, such as a VPN session **350** corresponding to a VPN connection **308** to a VPN gateway **330**. Each VPN gateway **330** is associated with a VPN gateway identifier **622** that corresponds to a VPN session status criteria **624**. In one or more embodiments, any of the one or more VPN status parameters **612**, a corresponding weight **614**, or both can be customized as a VPN status parameter configuration **610**. In one or more embodiments, any of the VPN gateway identifier **622**, one or more corresponding session status frequency **626**, one or more VPN session status criteria **624**, or any combination thereof can be customized as a VPN session status configuration **620**. For example, any one or more of the customizations illustrated in TABLE 1 and/or TABLE 2 can be configured and/or created utilizing a user interface, such as one that provides local access or remote console access, at any one or more network devices, including, but not limited to, any of a VPN

management device **2**, a client device **4**, a network device connected to ISP **1** any other network device, or a combination thereof.

(49) TABLE-US-00002 TABLE 2 VPN Session Status Configuration. VPN Gateway Identifier (associated with a VPN VPN Session VPN Session Connection) Status Criteria Status Frequency 1 <VPN Gateway 330A/VPN <P.sub.1> <timed interval> connection 308A> 2 <VPN Gateway 330B/VPN <selection algorithm> <network event> connection 308B> 3 <VPN Gateway 330N/VPN <P.sub.2>,<P.sub.4>,<P.sub.5> <timed interval> connection 308N>

(50) In one or more embodiments, the VPN manager **310** allows any one or more client devices **4** to connect via a VPN connection **308** to the same VPN gateway **330**. In one or more embodiments, the VPN manager **310** comprises the VPN configuration manager **302**, the VPN routing manager **304**, and/or the VPN connection monitor **306** as contained in and/or part of a one or more software **25** or distributed between one or more network devices, such as one or more VPN management devices **2**, one or more client devices **4**, a remote server, any other network devices, or a combination thereof.

(51) While FIG. **3** illustrates VPN gateways **330A-N** located within or as part of a target source **102**, the present disclosure contemplates that any one or more VPN gateways **330** may be located within or as part of one or more target sources **102**. For example, an entity may distribute or replicate data across multiple locations such that a plurality of target sources **2** are disposed at a plurality of locations. A first target source **102** at a first location can comprise a VPN gateway **330A** and a VPN gateway **330B** while a second target source **102** at a second location can comprise a VPN gateway **330N**. The first location and the second location can be different geological locations, such as different countries, states, cities, regions, etc.

(52) FIG. **4** is an illustration of switching a VPN connection **308** to a VPN gateway **330** utilizing a VPN manager **310** that comprises a VPN routing manager **304**, a VPN configuration manager **302**, and a VPN connection monitor **306** as discussed in reference to FIG. **3**, according to one or more aspect of the present disclosure. A client device **4A** can be connected to a network, for example, a home network, a business network, or any other type of network, such as discussed with reference to network environment **100A** and/or **100B** of FIGS. **1A** and **1B**, respectively. The client device **4A** can send a request **402** to VPN routing Manager **304** that a VPN session **350** be established. For example, a user of client device **4A** may require that data be sent to and/or received from a target source **102** that is remote from the client device **4A**. The user may require that such data be communicated securely via a VPN session **350** established with one or more network devices of the target source **102**, for example, one or more VPN gateways **330**.

(53) The VPN routing manager **304** can send a connection instruction **404** to the VPN manager **302** based on the VPN session request **402**. In one or more embodiments, the VPN configuration manager **302** establish a VPN connection **308A** associated with the VPN session request **402** by sending a command **404A** to the VPN gateway **330 A** so as to establish a VPN connection **308A**. In one or more embodiments, the VPN routing manager **304** can send one or more authentication parameters to the VPN routing manager **304** so that the VPN routing manager **304** can establish a VPN connection **308A** associated with the VPN session request **402**. The VPN configuration manager **302** (and/or the VPN routing manager **304**) can also send a command **404N** to the VPN gateway **330 N** to establish a VPN connection **308N**. Once the VPN connection **308A** is established, the VPN routing manager **304** can route data and/or traffic **408** received from the client device **4A** and/or the VPN gateway **330A** to the associated VPN gateway **330A** and/or client device **4A**, respectively.

(54) During the VPN session associated with the VPN connection **308A**, the VPN routing manager **304** requests a status associated with the VPN session, any one or more VPN connections **308**, or both based on a status monitor configuration associated with the VPN session, a VPN connection **308**, a monitor setting, such as a monitor setting associated with a client device **4**, a network environment, a user, any other factor, or a combination thereof. In one or more embodiments, the

status monitor configuration is stored in a memory **24** of the VPN management device **2**, any other memory accessible by the VPN manager **310**, or both. For example, the status monitor configuration can indicate that the VPN routing manager **304** request a status **410** based on a VPN session status frequency **626**. The VPN session status frequency **626** can indicate that VPN session status **632** should be monitored any of routinely, periodically, at a timed interval, upon a command, such as from another application or program, semaphore, interrupt, and/or expiration of a timer, occurrence of a network event (including, but not limited to, a disconnection of a VPN connection **308**, a power interruption, such as a power off or power on event, a data usage threshold, a signal strength threshold, new VPN connection **308**, etc.), any other frequency, or any combination thereof. For example, any of a user, entity, and/or any other program or interface, can request that VPN routing manager **304** can send a request status **410** to the VPN connection monitor **306**. As discussed with reference to FIG. **3**, the status can be based on one or more VPN status parameters. In one or more embodiments, the VPN connection monitor **306** can continuously monitor status **412** as required, for example, by the status monitor configuration. Based on the monitor status **412**, the request status **410**, or both, the VPN connection monitor can send a status **414** to the VPN routing manager **304**.

(55) The VPN routing manager **304** can determine a VPN session status **632** for a VPN session **350**. For example, a first VPN session **350** can be associated with a VPN connection **308A** to a VPN gateway **330A** as illustrated in FIG. **4**. The VPN session status **632** can be based on the status **414** received from the VPN connection monitor **306**. In one or more embodiments, the status **414** can comprise any one or more VPN status parameters **612** as discussed with reference to FIG. **3**. The VPN routing manager **304** can determine the VPN connection **308**, for example, so as to provide an improved or enhanced connectivity experience, based on any one or more criteria, such as a value stored as part of the status monitor configuration. For example, the VPN status parameter configuration **610** can indicate that the VPN session status **632** is determined based on any of one or more VPN status parameters, one or more selection algorithms, one or more network parameters, any other factor, or any combination thereof. In one or more embodiments, the VPN connection monitor **306** sends the VPN session status **632** as part of the status **414**.

(56) Based on the VPN session status **632**, the VPN routing manager **304** selects a VPN connection **308** for continuing the VPN session **350** established for the client device **4A**. The VPN routing manager **304** can perform a routing switch **416** such that data and/or traffic **418** is routed to the switched or selected VPN gateway **330N** via an associated VPN connection **308N**. In this way, the VPN session can be automatically and/or seamlessly switched to between VPN connections **308** so that the user has an enhanced or improved QoE.

(57) FIGS. **5A**, **5B**, **5C**, and **5D** illustrate various connections between a client device **4** and one or more VPN gateways **330**, according to one or more aspects of the present disclosure. Referring to FIG. **5A**, in one or more embodiments, a client device **4** at a location **530** can comprise a VPN manager **310** of FIG. **3**. The location **530** is located remote from the target source **102**, such as a central office, an office network, a central hub, a data repository, a resource, a service, or other remote source. The target source **102** can be associated with one or more regional VPN gateways **330** at one or more regional locations **510A**, **510B**, **510N** (collectively referred to as regional location(s) **510**), where N represents any number of regional locations **510**. For example, VPN gateway **330A** at regional location **510A**, VPN gateway **330B** at regional location **510B**, and VPN gateway **330N** at regional location **510N** can be connected to the target source **502** via one or more connections **520**. A regional location **510** can be any geographical or virtual location, such as any of a city, a state, a country, a cloud computing system, a site, such as a building, any other location, or a combination thereof. In one or more embodiments, any one or more of the one or more VPN gateways **330** can be located at the same regional location **510**, different regional locations **510**, or any combination thereof. The VPN manager **310** of client device **4** can establish one or more VPN connections **308** via the Internet **6** to the one or more VPN gateways **330** so as to communicate data

328 between the target source **102** and the client device **4**.

(58) In one or more embodiments, the client device **4** includes a user interface **29** of FIG. **2** that interfaces with the VPN manager **310**. The user interface **29** allows a user to enter one or more VPN session authorization parameters **630** for one or more available VPN gateways **330**, for example, one or more of any of VPN gateway **330A**, VPN gateway **330B**, VPN gateway **330N**, or any combination thereof. The VPN manager **310** can be initiated via the user interface **29**, for example, via a user input of the user interface **29**. The VPN manager **310** can open a distinct VPN session **350** of FIG. **3** for each of the available one or more VPN gateways **330** selected or identified via the user interface **29**. The VPN manager **310** can perform an initial test of any one or more VPN status parameters **612** to determine, identify and/or select an initial VPN gateway **330** from the one or more VPN gateways **330** selected or identified. This initial VPN gateway **330** is associated with an initial VPN connection **308** for an initial VPN session **350**. The client device **4** can communicate with the target source **102** via the initial VPN gateway **330**. For example, the client device **4** can access any of data, one or more resources, and/or one or more services associated with the target source **102** via the initial VPN session **350**.

(59) The VPN manager **310** monitors the one or more VPN sessions **350** established for the one or more VPN gateways **330**, for example, as discussed with reference to FIG. **3**. Based on the monitoring, the VPN manager **310** can switch the routing of data from the client device **4** to any one or more of the VPN gateways **330** for which a VPN session **350** has been established. In one or more embodiments, the VPN manager **310** temporarily switches the routing of data from the initial gateway **330** to a different gateway **330**. For example, if the initial VPN gateway **330** experiences an outage, the VPN manager **310** can temporarily switch routing to a different VPN gateway **330**, monitor the initial VPN gateway **330**, and switch routing back to the initial gateway **330** once the initial VPN gateway **330** is back online.

(60) Turning to FIG. **5B**, a client device **4** located at a location **530** can connect via connection **320** to a VPN management device **2**. The VPN management device **2** can be configured by a entity or other user, such as by any of a corporate information technology personnel, a service provider, any other entity or person, and any combination thereof. For example, a user of client device **4** can be associated with a corporate entity that has a strategy for optimizing the one or more network resources and/or services associated with the corporate entity, such as target source **102**. Providing a user of client device **4** with a configured VPN management device **2** can also minimize security risks associated with remote access to the target source **102**. The VPN management device **2** can be located at location **530**. For example, the VPN management device **2** can be installed and/or connected to the network, such as a LAN or WLAN, associated with the client device **4**. After the VPN management device **2** is installed and/or connected to the network associated with location **530**, the VPN management device **2** can operate as discussed with respect to FIGS. **3** and/or **5A**. In one or more embodiments, the VPN manager **310** of the VPN management device **2** is configured such that the VPN manager **310** only allows data or traffic from approved client devices **4** to be routed to a particular VPN gateway **330**, such as registered, authenticated, certified and/or otherwise approved client devices **4**. For example, VPN gateways **330A-N** may be associated with a corporate data resource **102** such that any client device **4** that attempts to initiate a VPN session **350** with any one or more of the VPN gateways **330A-N** must provide login credentials or other authentication, such as username and/or password, before a VPN connection **308** is established and/or data, traffic from the client device **4** is routed to the VPN connection **308**, or both. The registration, authentication, certifications, login credentials, approved client devices **4**, other authentication, or any combination thereof can be stored as a VPN session status criteria **624**, a VPN session authorization parameter **630**, a VPN status parameter **612**, any other location in memory, or any combination thereof.

(61) Turning to FIG. **5C**, a client device **4** can be located at a location **530** and coupled to a VPN management device **2** via a connection **320**, include a VPN management device **2**, or both. The

VPN management device **2** can connect the client device **4** to a VPN service **540**. A VPN service **540** can provide access to one or more gateways **330** at one or more regional locations **510** to VPN management device **2**. For example, restrictions may be imposed for a given resource or service offered by an entity via a website or other remote login portal. A country or entity, for example, can impose a tax or pricing may be adjusted based on the originating IP address of the client device **4**. To avoid such restrictions, a user can subscribe to a VPN service **540** that data or traffic (for example, purchase requests or navigation requests) associated with the original IP address of the client device **4** is routed to a different region via tunnel to a target source **102**, such as an online retailer, via a VPN gateway **330**. The VPN service **540** can select the appropriate VPN gateway **330** to match a request from the client device **4**. For example, a user of client device **4** can request the best pricing for a product. The VPN service **540** can search for the best pricing and then route data from the client device to a VPN gateway **330** that will provide the user with access to the best pricing by bypassing the restrictions imposed by a particular country based on origination of the IP address. In one or more embodiments, the VPN service **540** can provide a configuration file to the VPN manager **310** of a VPN management device **2**, for example, one or more VPN session authorization parameters **630**. In this way, any restrictions imposed based on a location and/or IP address can be bypassed so as to provide the user with an enhanced network experience.

(62) Turning to FIG. **5D**, a client device **4** can be located at a location **530**. The location **530** may have restrictions on access to resources and/or services that are available from a target source **102**. In one or more embodiments, a target source **102** can include any of a website, a server, a data storage facility, an Internet **6**, any other resource and/or service, or any combination thereof. To overcome the restrictions, the client device **4** can connect to a VPN server **550** that includes a VPN manager **310**. The VPN manager **310** can manage a list of VPN gateways **330** that can provide access to a restricted target source **102** and/or Internet **6**. For example, the VPN server **550** can be coupled to one or more VPN gateways **330** at one or more regional locations **510** that are located outside the area where restrictions are imposed. The VPN server **550** can add and/or remove VPN gateways **330** should any VPN gateway **330** be compromised. For example, the VPN server **550** via the VPN manager **310** initially connects the client device **4** to a VPN gateway **330A**. During monitoring of the VPN gateway **330A**, the VPN manager **310** determines that the VPN manager **330A** has been comprised or traffic associated with the VPN manager **330A** is blocked, the VPN manager **310** can switch routing of data from the client device **4** to VPN gateway **330B**. An additional VPN gateway **330N** can be added and associated with another VPN session to provide additional access to a target source **102** or Internet **6** should the VPN gateway **330B** be compromised or blocked. For example, any one or more VPN gateways **330** can be located outside the country associated with location **530** such that the client device **4** can securely and unrestrictedly access a target source **102** and/or Internet **6**. In this way, the VPN server **550** can ensure that data associated with the client device **4** is automatically routed to a VPN gateway **330** that provides access to data, one or more resources, and/or one or more services, for example, as provided by target source **102** and/or Internet **6**.

(63) FIG. **7** is a flow chart illustrating a method for managing, monitoring, and configuring a VPN connection **308** utilizing a VPN manager **310**, according to one or more aspects of the present disclosure. For example, the method improves the QOE of a user and/or one or more network parameters by automatically, transparently, or seamlessly routing data and/or traffic from one or more client devices **4** to a VPN gateway **330** associated with a VPN connection **308** based on suitability of the VPN connection **308** and/or VPN gateway **330**, such as according to a VPN session status configuration **620**.

(64) A VPN management device **2** and/or a client device **4** may be programmed with one or more computer-readable instructions such as a provisioning application that when executed by a controller **26** and/or **33**, respectively, cause the VPN management device **2** and/or the client device **4** to manage, monitor, and/or configure a VPN Session, such as a VPN Connection **308** to a VPN

gateway **330** of a target source **102**, according to one or more embodiments so as to provide an enhanced QoE for users of a network environment by providing automatic or seamless switching of routing of data and/or traffic between VPN connections **308** associated with a VPN gateway **330**. In FIG. 7, it is assumed that any one or more of the devices include their respective controllers and their respective software stored in their respective memories, as discussed above in connection with FIGS. 1A, 1B, 2, 3, and/or 4, which when executed by their respective controllers perform the functions and operations in accordance with the example embodiments of the present disclosure (e.g., including performing a configuration of one or more network devices). While the steps S710-S770 are presented in a certain order, the present disclosure contemplates that any one or more steps can be performed simultaneously, substantially simultaneously, repeatedly, in any order or not at all (omitted).

(65) A method for a VPN manager **310** to manage a plurality of VPN connections **350** to a target source **102** via a plurality of VPN gateways **330** is discussed with reference to FIG. 7. At step S700, the VPN manager **310** of a VPN management device **2** can receive, from one or more client devices **4**, data directed to a target source **102**. For example, a client device **4** can be connected to a network that includes a VPN management device **2**, the client device **4** can comprise a VPN management device and/or a VPN manager **310**, the VPN management device **2** and/or the VPN manager **310** can be coupled to the network, or any combination thereof. In one or more embodiments, a first data is received from a first client device **4** while a second data is received from a second client device **4**. Both the first data and the second data can be directed to a target source **102**, such as to the same data, resource or service or to different data, resources, or services.

(66) At step S710, the VPN manager **310** routes the data to a first VPN connection, for example, **308A**, of the plurality of VPN connections **308**. Each of the plurality of VPN connections **308** corresponds to a separate one of the plurality of VPN gateways **330**. In one or more embodiments, the client device **4** can comprise a user interface **29** that allows a user or application to select one or more VPN gateways **330**. Each selected one or more VPN gateways **330** are associated with a corresponding one or more VPN sessions **350**. For example, a VPN session **350A** can be associated with a VPN gateway **330A** via a VPN connection **308A** as discussed with reference to FIG. 3. In one or more embodiments, the first data and the second data discussed with reference to S700 can be routed to the first VPN connection **308**. In one or more embodiments, prior to routing data to a VPN connection **308**, the VPN manager **310** can perform an analysis based on a VPN status parameter configuration **610** associated with a VPN session status configuration **620**, for example, as discussed with respect to steps S720-S740.

(67) At step S720, the VPN manager **310** can determine a VPN session status **632** associated with one or more of the plurality of VPN connections **308**. The determining the VPN session status **632** can comprise analyzing one or more VPN session status criteria **624** associated with the one or more of the plurality of VPN connections **308**. The VPN session status criteria **624** can be configurable such that any of each VPN connection **308**, VPN gateway **330**, client device **4**, a user associated with client device **4**, or any combination thereof can be associated with one or more VPN session status criteria **624**. In one or more embodiments, a user interface of the VPN management device **2**, a client device **4**, any other network device connected to the VPN management device **2**, or any combination thereof can be utilized to configure any of a VPN status parameter configuration **610** that can comprise one or more VPN status parameters **612** and/or a weight **614** corresponding to the one or more VPN status parameters **612**, a VPN session status configuration **620** that can comprise a VPN gateway identifier **622**, a VPN session status frequency **626**, and/or a VPN session status criteria **624**, one or more VPN session authorization parameters **630**, or any combination thereof.

(68) At step S730, the VPN manager **310** can select a second VPN connection **308** of the plurality of VPN connections **308** based on the VPN session status **632**. The VPN session status **632** for each of the one or more of the plurality of VPN connections **308** can be determined by the VPN manager

310 as discussed, for example, with reference to Table 2 and FIG. 3. For example, the VPN session status can comprise performing a load balancing of the plurality of VPN connections **308**. In one or more embodiments, a type associated with the data is determined and the VPN session status **632** is determined based on the determined type of data. For example, the first VPN connection **308** can be associated with a first type of data and the second VPN connection **308** can be associated with a second type of data. A client device **4** can initially request streaming content from a target source **102** and then switch to requesting download of sensitive encrypted information. The streaming content can be received via a first VPN connection **308** and then the VPN manager **310** can switch to a second VPN connection **308** for downloading of the sensitive encrypted information. Such switching of VPN connections **308** can be performed without any user input or disruption in service and/or interruption in the experience or Quek of the user. Continuously or otherwise periodically monitoring the one or more VPN connections **308** to determine the VPN session status **632** allows the VPN manager **310** to periodically, routinely, seamlessly, at any specified time period, any other factor, or any combination thereof to maintain or manage the VPN connections **308** such that the VPN connection **308** can be selected that enhances or fits the needs of a user, a client device **4**, or both.

(69) At step **S740**, the VPN manager **310** can switch routing of the data from the first VPN connection **308** to the second VPN connection **308**. The VPN manager **310** can automatically or seamlessly switch the routing of the data. In one or more embodiments, the VPN manager **310** switches the routing in real-time or instantaneously, for example, each time a VPN session status **632** is determined that results in the selection of a different VPN connection **308**. In one or more embodiments, the routing of the data is switched after a time period, timed interval, or other delay. In one or more embodiments, the routing of the data is switched based on a comparison of a first VPN session status **632** determined at a first time to a second VPN session status **632** determined at a second time any other function or analysis applied to one or more VPN session statuses **632**, or both. For example, after the VPN manager **310** determines that the routing of the data should be switched, the VPN manager **310** may delay for a period of time, make another VPN session status **632** determination to verify that the routing of the data should be switched, and then after this validation, the VPN manager **310** switches the routing of the data to the new VPN connection **308**. In one or more embodiments, the first data in reference to step **S 710** is switched for routing purposes to the second VPN connection **308** while the second data remains routed through the first VPN connection **308**. In this way, one or more client devices can utilize the same VPN connection **308** or different VPN connections **308** similar to the functionality of a router.

(70) According to one or more example embodiments of inventive concepts disclosed herein, there are provided novel solutions for managing, configuring, and monitoring one or more VPN sessions that are associated with one or more VPN connections to one or more respective VPN gateway which can provide an enhanced QoE for a user by automatically and/or seamlessly switching routing of data from an initial VPN connection to a different VPN connection so as to transmit encrypted data to and from a VPN gateway based on a status monitor configuration.

(71) Each of the elements of the present invention may be configured by implementing dedicated hardware or a software program on a memory controlling a processor to perform the functions of any of the components or combinations thereof. Any of the components may be implemented as a CPU or other processor reading and executing a software program from a recording medium such as a hard disk or a semiconductor memory, for example. The processes disclosed above constitute examples of algorithms that can be affected by software, applications (apps, or mobile apps), or computer programs. The software, applications, computer programs or algorithms can be stored on a non-transitory computer-readable medium for instructing a computer, such as a processor in an electronic apparatus, to execute the methods or algorithms described herein and shown in the drawing figures. The software and computer programs, which can also be referred to as programs, applications, components, or code, include machine instructions for a programmable processor, and

can be implemented in a high-level procedural language, an object-oriented programming language, a functional programming language, a logical programming language, or an assembly language or machine language.

(72) The term “non-transitory computer-readable medium” refers to any computer program product, apparatus or device, such as a magnetic disk, optical disk, solid-state storage device (SSD), memory, and programmable logic devices (PLDs), used to provide machine instructions or data to a programmable data processor, including a computer-readable medium that receives machine instructions as a computer-readable signal. By way of example, a computer-readable medium can comprise DRAM, RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium that can be used to carry or store desired computer-readable program code in the form of instructions or data structures and that can be accessed by a general-purpose or special-purpose computer, or a general-purpose or special-purpose processor. Disk or disc, as used herein, includes compact disc (CD), laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray disc. Combinations of the above are also included within the scope of computer-readable media.

(73) The word “comprise” or a derivative thereof, when used in a claim, is used in a nonexclusive sense that is not intended to exclude the presence of other elements or steps in a claimed structure or method. As used in the description herein and throughout the claims that follow, “a”, “an”, and “the” includes plural references unless the context clearly dictates otherwise. Also, as used in the description herein and throughout the claims that follow, the meaning of “in” includes “in” and “on” unless the context clearly dictates otherwise. Use of the phrases “capable of,” “configured to,” or “operable to” in one or more embodiments refers to some apparatus, logic, hardware, and/or element designed in such a way to enable use thereof in a specified manner.

(74) While the principles of the inventive concepts have been described above in connection with specific devices, apparatuses, systems, algorithms, programs and/or methods, it is to be clearly understood that this description is made only by way of example and not as limitation. The above description illustrates various example embodiments along with examples of how aspects of particular embodiments may be implemented and are presented to illustrate the flexibility and advantages of particular embodiments as defined by the following claims, and should not be deemed to be the only embodiments. One of ordinary skill in the art will appreciate that based on the above disclosure and the following claims, other arrangements, embodiments, implementations and equivalents may be employed without departing from the scope hereof as defined by the claims. It is contemplated that the implementation of the components and functions of the present disclosure can be done with any newly arising technology that may replace any of the above-implemented technologies. Accordingly, the specification and figures are to be regarded in an illustrative rather than a restrictive sense, and all such modifications are intended to be included within the scope of the present invention. The benefits, advantages, solutions to problems, and any element(s) that may cause any benefit, advantage, or solution to occur or become more pronounced are not to be construed as a critical, required, or essential features or elements of any or all the claims. The invention is defined solely by the appended claims including any amendments made during the pendency of this application and all equivalents of those claims as issued.

Claims

1. A method for a virtual private network (VPN) manager to manage a plurality of VPN connections to a target source via the Internet and a plurality of VPN gateways of the target source comprising: establishing the plurality of VPN connections of the VPN manager to the plurality of VPN gateways of the target source; receiving, from one or more client devices, data directed to the target source, wherein the target source is remote from the VPN manager; monitoring one or more VPN status parameters associated with one or more VPN sessions via one or more paths of the

VPN manager to the one or more of the plurality of VPN connections of the VPN manager, wherein each of the plurality of VPN connections corresponds to a separate one of the plurality of VPN gateways; determining a VPN session status associated with the one or more of the plurality of VPN connections based on the monitoring; selecting a first VPN connection of the plurality of VPN connections based on the VPN session status; and routing the data to the first VPN connection for transmission of the data over the Internet to the separate one or more of the plurality of VPN gateways corresponding to the first VPN connection; monitoring the VPN session status of the one or more of the plurality of VPN connections; selecting a second VPN connection of the plurality of VPN connections based on the VPN session status; and switching routing of the data from the first VPN connection to the second VPN connection.

2. The method of claim 1, wherein determining the VPN session status comprises analyzing one or more VPN session status criteria associated with the one or more of the plurality of VPN connections.

3. The method of claim 1, wherein monitoring the VPN session status is performed based on a timed interval.

4. The method of claim 1, wherein determining the VPN session status comprises performing a load balancing of the plurality of VPN connections.

5. The method of claim 1, further comprising: determining a type of data associated with the data; wherein determining the VPN session status is based on the type of data; and wherein the first VPN connection is associated with a first type of data and a second VPN connection is associated with a second type of data.

6. The method of claim 1, further comprising: receiving additional data from an additional client device; determining an additional VPN session status; selecting a second VPN connection of the plurality of VPN connections based on the additional VPN session status; and routing the additional data to the second VPN connection.

7. A virtual private network (VPN) manager, the VPN manager comprising: a memory storing one or more instructions; a processor coupled to the memory, wherein the one or more instructions are executable by the processor, and wherein the one or more instructions include: a VPN configuration manager that: establishes a plurality of VPN connections of the VPN manager to a plurality of VPN gateways of a target source; manages the plurality of VPN connections to the target source via the Internet and the plurality of VPN gateways, wherein each of the plurality of VPN connections corresponds to a separate one of the plurality of VPN gateways; a VPN connection monitor that: monitors one or more VPN status parameters associated with one or more VPN sessions via one or more paths of the VPN manager to the one or more of the plurality of VPN connections of the VPN manager; and determines a VPN session status associated with the one or more of the plurality of VPN connections based on the monitoring; and monitors the VPN session status of the one or more of the plurality of VPN connections; and a VPN routing manager that: receives data from one or more client devices directed to the target source, wherein the target source is remote from the VPN manager; selects a first VPN connection of the plurality of VPN connections based on the VPN session status; and routes the data to the first VPN connection for transmission of the data over the Internet to the separate one or more of the plurality of VPN gateways corresponding to the first VPN connection; selects a second VPN connection of the plurality of VPN connections based on the VPN session status; and switches routing of the data from the first VPN connection to the second VPN connection.

8. The VPN manager of claim 7, wherein determining the VPN session status comprises analyzing one or more VPN session status criteria associated with the one or more of the plurality of VPN connections, wherein the VPN session status criteria comprise any of a connection state, a ping speed, a speed test, a throughput rate, a bandwidth, a latency, a received signal strength indicator, and any combination thereof.

9. The VPN manager of claim 7, wherein monitoring the VPN session status is performed based on

a timed interval.

10. The VPN manager of claim 7, wherein determining the VPN session status comprises performing a load balancing of the plurality of VPN connections.

11. The VPN manager of claim 7, wherein: the VPN routing manager further determines a type of data associated with the data; the determining the VPN session status is based on the type of data; and the first VPN connection is associated with a first type of data and a second VPN connection is associated with a second type of data.

12. The VPN manager of claim 7, wherein: the routing manager further receives additional data from an additional client device; the VPN connection monitor determines an additional VPN session status; and the VPN routing manager further: selects a second VPN connection of the plurality of VPN connections based on the additional VPN session status; and routes the additional data to the second VPN connection.

13. A non-transitory computer-readable medium storing one or more instructions for managing a plurality of virtual private network (VPN) connections to a target source via the Internet and a plurality of VPN gateways, that when executed by a processor, cause the processor to perform one or more operations comprising: establishing the plurality of VPN connections of the VPN manager to the plurality of VPN gateways of the target source; receiving, from one or more client devices, data directed to the target source, wherein the target source is remote from the VPN manager; monitoring one or more VPN status parameters associated with one or more VPN sessions via one or more paths of the VPN manager to the one or more of the plurality of VPN connections of the VPN manager, wherein each of the plurality of VPN connections corresponds to a separate one of the plurality of VPN gateways; determining a VPN session status associated with the one or more of the plurality of VPN connections based on the monitoring selecting a first VPN connection of the plurality of VPN connections based on the VPN session status; and routing the data to the first VPN connection for transmission of the data over the Internet to the separate one or more of the plurality of VPN gateways corresponding to the first VPN connection; monitoring the VPN session status of the one or more of the plurality of VPN connections; selecting a second VPN connection of the plurality of VPN connections based on the VPN session status; and switching routing of the data from the first VPN connection to the second VPN connection.

14. The method of claim 13, wherein determining the VPN session status comprises analyzing one or more VPN session status criteria associated with the one or more of the plurality of VPN connections.

15. The non-transitory computer-readable medium of claim 13, wherein determining the VPN session status comprises performing a load balancing of the plurality of VPN connections.

16. The non-transitory computer-readable medium of claim 13, wherein the one or more instructions when executed by the processor, further cause the processor to perform the one or more operations further comprising: determining a type of data associated with the data; wherein determining the VPN session status is based on the type of data; and wherein the first VPN connection is associated with a first type of data and a second VPN connection is associated with a second type of data.

17. The non-transitory computer-readable medium of claim 13, wherein the one or more instructions when executed by the processor, further cause the processor to perform the one or more operations further comprising: receiving additional data from an additional client device; determining an additional VPN session status; selecting a second VPN connection of the plurality of VPN connections based on the additional VPN session status; and routing the additional data to the second VPN connection.
