

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250275501

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

PALLA; Bhanu Kiran Reddy et al.

CROP CONSTITUENT SENSING

Abstract

A crop constituent value is sensed by a crop constituent sensor on an agricultural machine. The crop constituent value is distributed among subregions covered by the agricultural machine. A vegetative index-estimated crop constituent value is obtained for each of the subregions. A weighted crop constituent value is generated for each subregion based upon the distributed constituent value for each subregion and the vegetative index-estimated constituent value for that subregion. An action signal is generated based upon the weighted crop constituent value for the subregion.

Inventors: PALLA; Bhanu Kiran Reddy (Bettendorf, IA), PARDINA-MALBRAN; Federico (Fort Collins, CO), VANDIKE; Nathan R. (Geneseo, IL)

Applicant: Deere & Company (Moline, IL)

Family ID: 86498992

Appl. No.: 19/190075

Filed: April 25, 2025

Related U.S. Application Data

parent US continuation 17550762 20211214 parent-grant-document US 12310286 child US 19190075

Publication Classification

Int. Cl.: A01D41/127 (20060101); A01B79/00 (20060101); A01D43/08 (20060101); G06Q50/02 (20240101)

U.S. Cl.:

Background/Summary

[0001] The present application is a continuation of and claims priority of U.S. patent application Ser. No. 17/550,762, filed Dec. 14, 2021, the content of which is hereby incorporated by reference in its entirety.

FIELD OF THE DESCRIPTION

[0002] The present description relates to agriculture. More specifically, the present description relates to sensing crop constituents.

BACKGROUND

[0003] There are a wide variety of different types of agricultural machines. Some agricultural machines include harvesters, such as combine harvesters, sugarcane harvesters, cotton harvesters, self-propelled forage harvesters, and windrowers. Some harvesters can also be fitted with different types of headers to harvest different types of crops. Other agricultural machines include sprayers and other application machines that can be used to apply a substance to a field.

[0004] Some current harvesters have crop constituent sensors that sense crop constituents as a crop is being harvested. The crop constituents can be used in later agricultural operations such as in applying fertilizer or other substances to the field.

[0005] The discussion above is merely provided for general background information and is not intended to be used as an aid in determining the scope of the claimed subject matter.

SUMMARY

[0006] A crop constituent value is sensed by a crop constituent sensor on an agricultural machine. The crop constituent value is distributed among subregions covered by the agricultural machine. A vegetative index-estimated crop constituent value is also obtained for each of the subregions. A weighted crop constituent value is then generated for each subregion, based upon the distributed constituent value for each subregion and the vegetative index-estimated constituent value for that subregion. An action signal is generated based upon the weighted crop constituent value for the subregion.

[0007] Example 1 is an agricultural system comprising: [0008] a crop constituent value distribution system that obtains a detected crop constituent value detected by a crop constituent sensor, the detected crop constituent value corresponding to a sensor measurement by the crop constituent sensor, the crop constituent value distribution system assigning the detected crop constituent value, as a distributed constituent value, to a set of subregions from which the detected crop constituent value was measured during the sensor measurement; [0009] a weighted constituent value generator that generates a weighted crop constituent value for each subregion in the set of subregions, the weighted crop constituent value for a subregion in the set of subregions being based on the distributed constituent value for the subregion and based on an agricultural characteristic-estimated constituent value for the subregion that is estimated based on an agricultural characteristic value for the subregion; and [0010] an action signal generator that generates an action signal based on the weighted crop constituent value for the subregions in the set of subregions.

[0011] Example 2 is the agricultural system of any or all previous examples wherein the agricultural characteristic-estimated constituent value for the subregion that is estimated based on an agricultural characteristic value for the subregion comprises a vegetative index (VI)-estimated constituent value for the subregion that is estimated based on a VI value for the subregion and further comprising: [0012] a vegetative index map processing system that accesses a VI map that includes a VI value georeferenced to each of the subregions in the set of subregions and generates

the VI-estimated constituent value for the subregion in the set of subregions based on the VI value georeferenced to the subregion in the set of subregions.

[0013] Example 3 is the agricultural system of any or all previous examples, wherein the vegetative index map processing system comprises: [0014] a VI value extraction component that accesses VI values for each of the subregions from the VI map.

[0015] Example 4 is the agricultural system of any or all previous examples, wherein the vegetative index map processing system comprises: [0016] a correlation generator that generates a VI value-to-constituent value correlation between a given VI value and a constituent value.

[0017] Example 5 is the agricultural system of any or all previous examples, wherein the vegetative index map processing system comprises: [0018] a VI-estimated constituent value generator that generates the VI-estimated constituent value for the subregion based on the VI value georeferenced to the subregion and the VI value-to-constituent value correlation.

[0019] Example 6 is the agricultural system of any or all previous examples, wherein the action signal generator generates an action signal to control a controllable subsystem on an agricultural machine based on the weighted crop constituent value.

[0020] Example 7 is the agricultural system of any or all previous examples and further comprising: [0021] a communication system that communicates with a remote system over a network, [0022] wherein the action signal generator generates an action signal to control the communication system to communicate the weighted crop constituent value to the remote system.

[0023] Example 8 is the agricultural system of any or all previous examples and further comprising: [0024] a data store, and [0025] wherein the action signal generator generates an action signal to control the data store to store the weighted crop constituent value.

[0026] Example 9 is the agricultural system of any or all previous examples and further comprising: [0027] an agricultural harvester, [0028] wherein the crop constituent sensor is deployed on the agricultural harvester to detect the crop constituent value corresponding to harvested crop during a harvesting operation.

[0029] Example 10 is a computer implemented method of controlling an agricultural system comprising: [0030] obtaining a detected crop constituent value detected by a crop constituent sensor, the detected crop constituent value corresponding to a sensor measurement by the crop constituent sensor; [0031] assigning the detected crop constituent value, as a distributed constituent value, to a set of subregions from which the detected crop constituent value was measured during the sensor measurement; [0032] generating a weighted crop constituent value for each subregion in the set of subregions, the weighted crop constituent value for a subregion in the set of subregions being based on the distributed constituent value for the subregion and based on an agricultural characteristic-estimated constituent value for the subregion that is estimated based on an agricultural characteristic value for the subregion; and [0033] generating an action signal based on the weighted crop constituent value for the subregions in the set of subregions.

[0034] Example 11 is the computer implemented method of any or all previous examples, wherein the agricultural characteristic-estimated constituent value for the subregion that is estimated based on an agricultural characteristic value for the subregion comprises a vegetative index (VI)-estimated constituent value for the subregion that is estimated based on a VI value for the subregion, the method further comprising: [0035] accessing a VI map that includes a VI value georeferenced to each of the subregions in the set of subregions; and [0036] generating the VI-estimated constituent value for the subregion in the set of subregions based on the VI value georeferenced to the subregion in the set of subregions.

[0037] Example 12 is the computer implemented method of any or all previous examples, wherein accessing a VI map comprises: [0038] accessing VI values for each of the subregions from the VI map.

[0039] Example 13 is the computer implemented method of any or all previous examples, wherein generating the VI-estimated constituent value comprises: [0040] generating a VI value-to-

constituent value correlation between a given VI value and a given crop constituent value.

[0041] Example 14 is the computer implemented method of any or all previous examples, wherein generating the VI-estimated constituent value comprises: [0042] generating the VI-estimated constituent value for the subregion based on the VI value georeferenced to the subregion and the VI value-to-constituent value correlation.

[0043] Example 15 is the computer implemented method of any or all previous examples, wherein generating an action signal comprises: [0044] generating an action signal to control a controllable subsystem on an agricultural machine based on the weighted crop constituent value.

[0045] Example 16 is the computer implemented method of any or all previous examples and further comprising: [0046] generating an action signal to control a communication system to communicate the weighted crop constituent value to a remote system.

[0047] Example 17 is the computer implemented method of any or all previous examples, wherein the agricultural system comprises a data store, and [0048] wherein generating an action signal comprises: [0049] generating an action signal to control the data store to store the weighted crop constituent value.

[0050] Example 18 is the computer implemented method of any or all previous examples, wherein the agricultural system comprises an agricultural harvester, [0051] wherein the crop constituent sensor is deployed on the agricultural harvester, and [0052] wherein obtaining a detected crop constituent value comprises: [0053] detecting the crop constituent value corresponding to harvested crop during a harvesting operation.

[0054] Example 19 is an agricultural system comprising: [0055] an agricultural vehicle configured to perform an agricultural operation in a field; [0056] a crop constituent sensor, mounted on the agricultural vehicle, that performs a sensor measurement to detect a crop constituent value during the agricultural operation; [0057] a crop constituent value distribution system that obtains the detected crop constituent value and assigns the crop constituent value, as a distributed constituent value, to a set of subregions from which the detected crop constituent value was measured during the sensor measurement; [0058] a weighted constituent value generator that generates a weighted crop constituent value for each subregion in the set of subregions, the weighted crop constituent value for a subregion in the set of subregions being based on the distributed constituent value for the subregion and based on a vegetative index (VI)-estimated constituent value for the subregion that is estimated based on a VI value for the subregion; and [0059] an action signal generator that generates an action signal based on the weighted crop constituent value for the subregions in the set of subregions.

[0060] Example 20 is the agricultural system of any or all previous examples and further comprising: [0061] a VI value extraction component that accesses VI values for each of the subregions from a VI map that includes VI values georeferenced to the subregions; [0062] a correlation generator that generates a VI value-to-constituent value correlation between a given VI value and a constituent value; and [0063] a VI-estimated constituent value generator generates the VI-estimated constituent value for the subregion based on the VI value georeferenced to the subregion and the VI value-to-constituent value correlation.

[0064] This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter. The claimed subject matter is not limited to implementations that solve any or all disadvantages noted in the background.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0065] FIG. **1** is a partial pictorial, partial schematic illustration of a self-propelled agricultural harvester **100**.

[0066] FIG. **2** is a top view of an agricultural harvester.

[0067] FIG. **3** is a pictorial illustration of an agricultural harvester and subregions in a field.

[0068] FIG. **4** is a block diagram of one example of an agricultural system.

[0069] FIG. **5A** is a flow diagram illustrating one example of the operation of an agricultural system.

[0070] FIG. **5B** is a flow diagram illustrating one example of the operation of an agricultural system.

[0071] FIG. **6** is a diagram illustrating an example of a weighted allocation of a constituent value to geo-referenced regions based upon a vegetative index-estimated constituent value.

[0072] FIG. **7** is a block diagram of one example of the agricultural system illustrated in FIG. **4** deployed a remote server architecture.

[0073] FIGS. **8-10** show examples of mobile devices.

[0074] FIG. **11** is a block diagram of one example of a computing environment that can be used in the architectures illustrated in the previous figures.

DETAILED DESCRIPTION

[0075] For the purposes of promoting an understanding of the principles of the present disclosure, reference will now be made to the examples illustrated in the drawings, and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the disclosure is intended. Any alterations and further modifications to the described devices, systems, methods, and any further application of the principles of the present disclosure are fully contemplated as would normally occur to one skilled in the art to which the disclosure relates. In particular, it is fully contemplated that the features, components, steps, or a combination thereof described with respect to one example may be combined with the features, components, steps, or a combination thereof described with respect to other examples of the present disclosure.

[0076] In some current systems, crop constituents are detected as part of the harvest operation by a constituent sensor on an agricultural harvester. Crop constituents may also be detected using a crop constituent detector on a sprayer or other agricultural machine. The crop constituent values generated by the crop constituent sensor can be geo-referenced to geographic locations based upon the geographic location from which the crop was harvested that gave rise to the crop constituent values. However, the crop constituent sensor is often a single sensor on an agricultural harvester located at a position where the harvested crop passes during processing, such as in an elevator that moves harvested crop to a clean grain tank. Therefore, the resolution of crop constituent values, with respect to geographic locations, is relatively low. That is, crop constituent sensors that take measurements from a combined population of grain is unable to provide granularity to particularly identify a location of the field associated with the sensed constituent data. This problem is exacerbated by the fact that the width of crop harvester headers is continuing to increase. Therefore, the geographic location from which the crop was harvested, and which gave rise to a crop constituent value, is large. When the crop constituent values are used for subsequent agricultural processes, such as the application of fertilizer, those subsequent agricultural processes are imprecise because localized constituent values within an area represented by the measured crop constituent value may vary.

[0077] The present description relates to using an agricultural characteristic map that has agricultural characteristic values geo-referenced to different geographic locations on a field. The agricultural characteristic values are correlated to crop constituent values so that the agricultural characteristic map can be used to obtain an agricultural characteristic-estimated crop constituent map using the correlation between the agricultural characteristic values and crop constituent values.

[0078] In one example, the agricultural characteristic map is a vegetative index map. Thus, in one example, the present description relates to using a vegetative index map that has vegetative index values geo-referenced to different geographic locations on a field. The vegetative index values are correlated to crop constituent values so that the vegetative index map can be used to obtain a vegetative index-estimated crop constituent map using the correlation between the vegetative index values and crop constituent values.

[0079] In the present description, a crop constituent sensor on an agricultural vehicle senses a crop constituent value. The crop constituent value is distributed by geo-referencing the crop constituent value to different subregions in the field based upon the width of the header and based upon other distribution criteria discussed below. The distributed crop constituent values are combined with the agricultural characteristic-estimated crop constituent values, such as the vegetative index-estimated crop constituent values, to obtain a weighted crop constituent value for each subregion. An action signal may be generated to take action based upon the weighted crop constituent values in each of the subregions.

[0080] For example, the weighted crop constituent values in each subregion may be used to generate a weighted crop constituent map for the field. In some examples, the weighted crop constituent map may be used to control an agricultural work machine, such as an agricultural harvester. For instance, it may be desirable to change or otherwise control the machine settings of the agricultural harvester based on the crop constituent values in the area in which the agricultural harvester is operating. In some situations, crop constituent values, such as protein or oil, at a particular level may result in premium market prices or in benefits when fed to livestock. To capture this value, crop is segregated at harvest and managed based upon the constituent level. Segregation may be done by directing crop to one of a plurality of on-board clean grain tanks. In other examples, the segregation may be done by off-loading grain to a grain transport vehicle as constituent level thresholds are crossed. In still other examples, the segregation may be done by managing the path a harvesting vehicle takes through the field based upon predicted constituent values. A vegetative index map maps vegetative index values, which may be indicative of vegetative growth, across different geographic locations in one or more field(s) of interest. One example of a vegetative index includes a normalized difference vegetation index (NDVI). There are many other vegetative indices, and all of these vegetative indices are within the scope of the present disclosure. In some examples, a vegetative index may be derived from sensor readings of one or more bands of electromagnetic radiation reflected by the plants. Without limitations, these bands may be in the microwave, infrared, visible, or ultraviolet portions of the electromagnetic spectrum.

[0081] A vegetative index map may be used to identify the presence and location of vegetation. In some examples, a vegetative index map enables crops to be identified and geo-referenced in the presence of bare soil, crop residue, or other plants, including crop or weeds. For instance, towards the beginning of a growing season, when a crop is in a growing state, the vegetative index can show the progress of the crop development. Therefore, if a vegetative index map is generated early in the growing season or midway through the growing season, the vegetative index map may be indicative of the progress of the development of the crop plants. For instance, the vegetative index map may indicate whether the plant is stunted or establishing a sufficient canopy. The vegetative index map may also indicate other plant attributes that are indicative of plant development.

[0082] While a vegetative index map is one example of an agricultural characteristic map, in other examples various other agricultural characteristic maps can be used, such as a soil type map which maps soil types to different geographic locations in one or more fields of interest, for instance loamy soil, sandy soil, clay soil, silt soil, peat soil, chalk soil, etc. In another example, an agricultural characteristic map can include a soil nutrient map which maps soil nutrient values to different geographic locations in one or more fields of interest, for instance nitrogen levels, phosphorous levels, potassium levels, or a combination thereof. In another example, an agricultural

characteristic map can include a crop genotype map which maps crop genotypes to different geographic locations in one or more fields of interest, for instance different crop hybrids. In another example, an agricultural characteristic map can include a historical map, such as a historical crop constituent map which maps historical crop constituent values to different geographic locations in one or more fields of interest. In another example, an agricultural characteristic map can include a soil moisture map which maps soil moisture values to different geographic locations in one or more fields of interest. In another example, an agricultural characteristic map can include a prior operation map which maps agricultural characteristic values from prior operations to different geographic locations in one or more fields of interest, such as a prior nutrient application map which maps nutrient application values to different geographic locations in one or more field(s) of interest, for instance volumes of nutrient(s) applied to different geographic locations in one or more field(s) of interest. These are merely some examples of agricultural characteristic maps. Various other agricultural characteristic maps that map various other agricultural characteristic values are also contemplated herein, such as a topographic map that maps topographic values (e.g., elevation, slope, etc.) to different geographic locations in one or more fields of interest.

[0083] In one example, a crop constituent map maps crop constituent values across different geographic locations in one or more field(s) of interest. In some instances, crop constituent maps are generated from past agricultural operations on the field(s), such as past harvesting operations. In some instances, a crop constituent map shows crop constituents in crop constituent value units. One example of a crop constituent value unit includes a numeric value, such as a percentage, weight value, or mass value that indicates an amount of a constituent in a crop. In one example, the crop constituent value indicates an amount of protein, starch, oil, nutrients, water, among various other constituents of crop or vegetation, or an amount of protein, starch, oil, nutrients, water, among various other constituents, in grain of crop plants. Some crop constituents are more transient in nature, in that the amount of the constituent contained within the crop material (such as grain) will vary over time. For instance, grain can dry or take on water throughout a span of time and thus the amount of water, as a crop constituent, will vary with the drying or moistening of the grain. Some crop constituents are more structural in nature, in that the amount of constituent (or ratios of constituents) tend to not vary as much over time, at least until the grain decomposes. As used herein, crop constituents can also refer to grain constituents, and, thus, crop constituent values can, in some examples, refer to an amount of constituent in the grain of crop plants. Crop constituent values can indicate, for example, the amount of protein, starch, oil, nutrients, water, among various other constituents, in the grain of crop plants.

[0084] In some examples, crop constituent values are derived from sensor readings of one or more crop constituent sensors. Without limitation, these crop constituent sensors utilize one or more bands of electromagnetic radiation in detecting crop constituents. For example, a crop constituent sensor utilizes the reflectance or absorption of various ranges (e.g., various wavelengths or frequencies, or both) of electromagnetic radiation by crop or other vegetation material in detecting crop constituents. In some examples, a crop constituent sensor includes an optical sensor, such as an optical spectrometer. In one example, a crop constituent sensor utilizes near-infrared spectroscopy or visible and near-infrared spectroscopy.

[0085] The present description thus proceeds with respect to examples in which an agricultural system receives an agricultural characteristic map, such as a vegetative index map, and a correlation between agricultural characteristic values and crop constituent values, such as a correlation between vegetative index values and crop constituent values. An agricultural characteristic-estimated crop constituent map, such as a vegetative index (VI)-estimated crop constituent map, is generated using the agricultural characteristic map, such as the vegetative index map, and the correlation between the agricultural characteristic values and the crop constituent values, such as the correlation between the vegetative index values and the crop constituent values. The agricultural system also receives a sensed crop constituent value corresponding to a geographic

location in a field. In one example, the sensed crop constituent value is assigned to subregions in the field based on the geographic area corresponding to the crop constituent sensor value. A weighted crop constituent value is generated for each subregion based upon a crop constituent value assigned to that subregion and based upon the agricultural characteristic-estimated crop constituent value for that subregion, such as the vegetative index-estimated crop constituent value for that subregion.

[0086] FIG. 1 is a partial pictorial, partial schematic, illustration of a self-propelled agricultural harvester **100**. In the illustrated example, agricultural harvester **100** is a combine harvester. Further, although combine harvesters are provided as examples throughout the present disclosure, it will be appreciated that the present description is also applicable to other types of harvesters, such as cotton harvesters, sugarcane harvesters, self-propelled forage harvesters, windrowers, or other agricultural work machines. Consequently, the present disclosure is intended to encompass the various types of harvesters and is, thus, not limited to combine harvesters. Moreover, the present disclosure is directed to other types of agricultural machines, such as agricultural seeders and sprayers. Consequently, the present disclosure is intended to encompass these various types of harvesters and other agricultural machines and is thus not limited to combine harvesters.

[0087] As shown in FIG. 1, agricultural harvester **100** illustratively includes an operator compartment **101**, which may have a variety of different operator interface mechanisms for controlling agricultural harvester **100**. Agricultural harvester **100** includes a front-end subsystem that has front-end equipment, such as a header **102**, and a cutter generally indicated at **104**. Agricultural harvester **100** also includes a feeder house **106**, a feed accelerator **108**, and a thresher generally indicated at **110**. The feeder house **106** and the feed accelerator **108** form part of a material handling subsystem **125**. Header **102** is pivotally coupled to a frame **103** of agricultural harvester **100** along pivot axis **105**. One or more actuators **107** drive movement of header **102** about axis **105** in the direction generally indicated by arrow **109**. Thus, a vertical position of header (the header height) above ground **111** over which the header **102** travels is controllable by actuating actuator **107**. While not shown in FIG. 1, agricultural harvester **100** may also include one or more actuators that operate to apply a tilt angle, a roll angle, or both to the header **102** or portions of header **102**. Tilt refers to an angle at which the cutter **104** engages the crop. The tilt angle is increased, for example, by controlling header **102** to point a distal edge **113** of cutter **104** more toward the ground. The tilt angle is decreased by controlling header **102** to point the distal edge **113** of cutter **104** more away from the ground. The roll angle refers to the orientation of header **102** about the front-to-back longitudinal axis of agricultural harvester **100** or about an axis parallel to the front-to-back longitudinal axis of agricultural harvester **100**.

[0088] Thresher **110** illustratively includes a separation subsystem with a threshing rotor **112**, a set of concaves **114**, and a separator **116**. Agricultural harvester **100** also includes a cleaning subsystem or cleaning shoe (collectively referred to as cleaning subsystem **118**) that includes a cleaning fan **120**, chaffer **122**, and sieve **124**. The material handling subsystem **125** also includes discharge beater **126**, tailings elevator **128**, clean grain elevator **130**, as well as unloading auger and spout **136**. The clean grain elevator moves clean grain into clean grain tank **132**. Agricultural harvester **100** also includes a residue subsystem **138** that can include chopper **140** and spreader **142**.

Agricultural harvester **100** also includes a propulsion subsystem that includes an engine that drives ground engaging components **144**, such as wheels or tracks. In some examples, an agricultural harvester **100** within the scope of the present disclosure may have more than one of any of the subsystems mentioned above. In some examples, agricultural harvester **100** may have left and right cleaning subsystems, separators, etc., which are not shown in FIG. 1.

[0089] In operation, and by way of overview, agricultural harvester **100** illustratively moves through a field in the direction indicated by arrow **147**. As agricultural harvester **100** moves, header **102** (and the associated reel **164**) engages the crop to be harvested and gathers the crop toward cutter **104**. An operator of agricultural harvester **100** can be a local human operator, a remote

human operator, or an automated system. An operator command is a command by an operator. The operator of agricultural harvester **100** may determine one or more of a height setting, a tilt angle setting, or a roll angle setting for header **102**. For example, the operator inputs a setting or settings to a control system, that controls actuator **107**. The control system may also receive a setting from the operator for establishing the tilt angle and roll angle of the header **102** and implement the inputted settings by controlling associated actuators, not shown, that operate to change the tilt angle and roll angle of the header **102**. The actuator **107** maintains header **102** at a height above ground **111** based on a height setting and, where applicable, at desired tilt and roll angles. Each of the height, roll, and tilt settings may be implemented independently of the others. The control system responds to header error (e.g., the difference between the height setting and measured height of header **102** above ground **111** and, in some examples, tilt angle and roll angle **11** errors) with a responsiveness that is determined based on a selected sensitivity level. If the **12** sensitivity level is set at a greater level of sensitivity, the control system responds to smaller header position errors, and attempts to reduce the detected errors more quickly than when the sensitivity is at a lower level of sensitivity.

[0090] Returning to the description of the operation of agricultural harvester **100**, after crops are cut by cutter **104**, the severed crop material is moved through a conveyor in feeder house toward feed accelerator **108**, which accelerates the crop material into thresher **110**. The crop material is threshed by rotor **112** rotating the crop against concaves **114**. The threshed crop material is moved by a separator rotor in separator **116** where a portion of the residue is moved by discharge beater **126** toward the residue subsystem **138**. The portion of residue transferred to the residue subsystem **138** is chopped by residue chopper **140** and spread on the field by spreader **142**. In other configurations, the residue is released from the agricultural harvester **100** in a windrow. In other examples, the residue subsystem **138** can include weed seed eliminators (not shown) such as seed baggers or other seed collectors, or seed crushers or other seed destroyers.

[0091] Grain falls to cleaning subsystem **118**. Chaffer **122** separates some larger pieces of material from the grain, and sieve **124** separates some of finer pieces of material from the clean grain. Clean grain falls to an auger that moves the grain to an inlet end of clean grain elevator **130**, and the clean grain elevator **130** moves the clean grain upwards, depositing the clean grain in clean grain tank **132**. Residue is removed from the cleaning subsystem **118** by airflow generated by cleaning fan **120**. Cleaning fan **120** directs air along an airflow path upwardly through the sieves and chaffers. The airflow carries residue rearwardly in agricultural harvester **100** toward the residue handling subsystem **138**.

[0092] Tailings elevator **128** returns tailings to thresher **110** where the tailings are re-threshed. Alternatively, the tailings also may be passed to a separate re-threshing mechanism by a tailings elevator or another transport device where the tailings are re-threshed as well.

[0093] FIG. **1** also shows that, in one example, agricultural harvester **100** includes ground speed sensor **146**, one or more separator loss sensors **148**, a clean grain camera **150**, a forward looking image capture mechanism **151**, which may be in the form of a stereo or mono camera, one or more constituent sensors **200**, **202**, a geographic positioning system **203**, and one or more loss sensors **152** provided in the cleaning subsystem **118**.

[0094] Ground speed sensor **146** senses the travel speed of agricultural harvester **100** over the ground. Ground speed sensor **146** may sense the travel speed of the agricultural harvester **100** by sensing the speed of rotation of the ground engaging components (such as wheels or tracks), a drive shaft, an axle, or other components. In some instances, the travel speed may be sensed using geographic positioning system **203**, which may be a global positioning system (GPS), a dead reckoning system, a long range navigation (LORAN) system, or a wide variety of other systems or sensors that provide an indication of a geographic positioning of agricultural harvester **100** in a global or local coordinate system. Detecting a change in position over time may provide an indication of travel speed.

[0095] Loss sensors **152** illustratively provide an output signal indicative of the quantity of grain loss occurring in both the right and left sides of the cleaning subsystem **118**. In some examples, sensors **152** are strike sensors which count grain strikes per unit of time or per unit of distance traveled to provide an indication of the grain loss occurring at the cleaning subsystem **118**. The strike sensors for the right and left sides of the cleaning subsystem **118** may provide individual signals or a combined or aggregated signal. In some examples, sensors **152** may include a single sensor as opposed to separate sensors provided for each cleaning subsystem **118**.

[0096] Separator loss sensor **148** provides a signal indicative of grain loss in the left and right separators, not separately shown in FIG. **1**. The separator loss sensors **148** may be associated with the left and right separators and may provide separate grain loss signals or a combined or aggregate signal. In some instances, sensing grain loss in the separators may also be performed using a wide variety of different types of sensors as well.

[0097] As mentioned above, agricultural harvester **100** also includes one or more crop constituent sensors **200**, **202** located at one or more different locations on agricultural harvester **100**. Crop constituent sensor **200** is shown mounted in feeder house **106**, while crop constituent sensor **202** is shown as mounted to sense crop in clean grain elevator **130**. However, one or more crop constituent sensor may be provided at one or more other locations on the agricultural harvester **100**. Without limitation, crop constituent sensors **200**, **202** utilize one or more bands of electromagnetic radiation in detecting crop constituents. For example, in some instances, crop constituent sensors **200**, **202** utilize the reflectance or absorption of various ranges (e.g., various wavelengths or frequencies, or both) of electromagnetic radiation by crop or other vegetation material, including grain, in detecting crop constituents. In some examples, a crop constituent sensor **200**, **202** includes an optical sensor, such as an optical spectrometer. In one example, a crop constituent sensor **200**, **202** utilize near-infrared spectroscopy or visible near-infrared spectroscopy.

[0098] Crop constituent sensor may be disposed at or have access to various locations within agricultural harvester **100**. For example, the crop constituent sensor **200** is disposed within the feeder house **106** (or otherwise has sensing access to crop material within feeder house **106**) and is configured to detect constituents of harvested crop material passing through the feeder house **106**. In other examples, the crop constituent sensor **202** is located at other areas within agricultural harvester **100**, for instance, on or coupled to the clean grain elevator **130**, in a clean grain auger, or in a grain tank **132**. In some examples, the crop constituent sensors **200**, **202** include a capacitive sensor, which can include, for example, a capacitor for determining dielectric properties of a crop material or other vegetation, such as dielectric properties of grain. In one example, a crop constituent sensor **200**, **202** utilizes near-infrared spectroscopy or visible near-infrared spectroscopy and is disposed within (or otherwise has sensing access to crop material within) one or more locations within agricultural harvester, such as feeder house **106**, clean grain elevator **130**, a clean grain auger, a grain tank, a crop chute, as well as various other locations or combinations thereof. In one example, a crop constituent sensor **200**, **202** utilizes near-infrared spectroscopy or visible near-infrared spectroscopy and is disposed along the flow path of the crop material through agricultural harvester **100**, the crop constituent sensor **200**, **202** can include a chamber to which crop material is diverted to from the flow path so the crop constituent sensor **200**, **202** can take a reading. It will be noted that these are merely examples of the types and locations of crop constituent sensors **200**, **202** and that various other types and locations of crop constituent sensors are contemplated.

[0099] Agricultural harvester **100** may also include other sensors and measurement mechanisms. For instance, agricultural harvester **100** may include one or more of the following sensors: a header height sensor that senses a height of header **102** above ground **111**; stability sensors that sense oscillation or bouncing motion (and amplitude) of agricultural harvester **100**; a residue setting sensor that is configured to sense whether agricultural harvester **100** is configured to chop the residue, produce a windrow, etc.; a cleaning shoe fan speed sensor to sense the speed of cleaning

fan **120**; a concave clearance sensor that senses clearance between the rotor **112** and concaves **114**; a threshing rotor speed sensor that senses a rotor speed of rotor **112**; a chaffer clearance sensor that senses the size of openings in chaffer **122**; a sieve clearance sensor that senses the size of openings in sieve **124**; a material other than grain (MOG) moisture sensor, such as a capacitive moisture sensor, that senses a moisture level of the MOG passing through agricultural harvester **100**; one or more machine setting sensors configured to sense various configurable settings of agricultural harvester **100**; a machine orientation sensor that senses the orientation of agricultural harvester **100**; and crop property sensors that sense a variety of different types of crop properties, such as crop type, crop moisture, and other crop properties. In some implementations, crop property sensors are configured to sense characteristics of the severed crop material as the crop material is being processed by agricultural harvester **100**. For example, in some instances, the crop property sensors sense grain quality, such as broken grain; MOG levels; and grain feed rate as the grain travels through the feeder house **106**, clean grain elevator **130**, or elsewhere in the agricultural harvester **100**. In some implementations, the crop property sensors sense the feed rate of biomass through feeder house **106**, through the separator **116**, or elsewhere in agricultural harvester **100**. Further, in some instances, the crop property sensors sense the feed rate as a mass flow rate of grain through elevator **130** or through other portions of the agricultural harvester **100** or provide other output signals indicative of other sensed variables.

[0100] FIG. **2** is a top view of agricultural harvester **100**. Some items in FIG. **2** are similar to those shown in FIG. **1**, and those items are similarly numbered. In FIG. **2**, agricultural harvester travels in the direction indicated by arrow **147** and harvests row crops. In the example shown in FIG. **2**, header **102** is an eight-row head, meaning that header **102** is of a width such that it can harvest eight crop rows at a time. In the example shown in FIG. **2**, the crop rows include crop rows **204**, **206**, **208**, **210**, **212**, **214**, **216**, and **218**. As agricultural harvester **100** moves through the field, the crops that are harvested in rows **204-218** are severed by the cutter on header **102**, and are moved inwardly toward a center of header **102**, and are then moved rearwardly through feeder house **106** for processing in agricultural harvester **100** by the processing subsystems described earlier. For example, the crops in rows **204**, **206**, **208**, and **210** are severed by the header **102** and are moved by a conveyor or draper belt (collectively referred to hereinafter as “conveyor”) in the **6** direction indicated by arrow **220** toward the center of header **102** where the severed crops are moved by another conveyor in the direction indicated by arrow **222** into feeder house **106**. Similarly, the crops in rows **212**, **214**, **216**, and **218**, after being severed by header **102**, are moved in the direction indicated by arrow **224** to the center portion of header **102** where the severed crops are moved in the direction indicated by arrow **222** back into feeder house **106**.

[0101] FIG. **2**, thus, shows that the crops on the outermost rows **204** and **218** move a longer distance before the crops from the outermost rows **204** and **218** are processed by the processing subsystems in agricultural harvester **100** than the crops that are in rows closer to the center of agricultural harvester **100**, such as the crops in rows **210** and **212**. This means that, for crop harvested at the same point in time along a width of the header **102**, the crop from the outermost rows **204** and **218** will reach the crop constituent sensor **202** at a time later than the crop from rows **210** and **212**. Therefore, the crop that is being sensed by crop constituent sensor **202** at any given time is taken from subregions in the field that are spaced relative to one another in the direction indicated by arrow **147**. FIG. **3** shows an example of this in more detail.

[0102] It can be seen in FIG. **3** that the crop rows **204-218** are broken up into subregions represented by the rectangles in FIG. **3**. The shaded rectangles represent subregions of crop that will all reach the crop constituent sensor **202** at roughly the same time. For instance, as agricultural harvester **100** moves in the direction indicated by arrow **147**, header **102** engages the crop in subregions **230** and **232** in rows **204** and **218**. That crop will be severed by header **102** and begin moving in the directions indicated by arrows **220** and **224**, respectively. Agricultural harvester **100** will then engage the crop in subregions **234** and **236** in rows **206** and **216** so that the crop from

subregions **234** and **236** will be at approximately the same location on the conveyors that are conveying the crop from subregions **230** and **232** toward the center of agricultural harvester **100**. As agricultural harvester **100** continues to move forward in the direction indicated by arrow **147**, the crop in subregions **238** and **240** in rows **208** and **214** will be severed and will join the crop from subregions **230**, **232**, **234**, and **236** at approximately the same location on the conveyors that are conveying the crop toward the center of header **102**. As agricultural harvester **100** continues to move forward in the direction indicated by arrow **147**, the crop from subregions **242** and **244** in rows **210** and **212** will also join the crop from the other subregions **230-240** at approximately the same location on the conveyors of header **102**. Therefore, the crop from the subregions **230-244** will all be processed by the processing subsystems in agricultural harvester **100** at approximately the same time. The crop from subregions **230-244** will thus reach the crop constituent sensor **202** at approximately the same time as well. Therefore, a measurement of crop constituent that is generated by crop constituent sensor **202** will correspond to the crop in subregions **230-244** shown in FIG. 3.

[0103] It will be noted that the size of the different subregions **230-244** may vary based upon the forward ground speed of agricultural harvester **100** and the speed of the conveyors that convey the harvested crop in the directions indicated by arrows **220**, **222**, and **224**. Therefore, the subregions **230-244** shown in FIG. 3 are shown by way of example only.

[0104] In one example, the crop constituent value generated by crop constituent sensor **202** is assigned to the subregions **230-244**. Also, as is described in greater detail below, the agricultural system in the present description obtains a map of agricultural characteristic-estimated crop constituent values for the field being harvested, such as a map of vegetative index-estimated crop constituent values for the field being harvested. The agricultural system combines the distributed crop constituent values in subregions **230-244** with the agricultural characteristic-estimated crop constituent values, such as the VI-estimated crop constituent values, in subregions **230-244** to obtain a weighted crop constituent value for each of the subregions **230-244** that may be more accurate than either the distributed crop constituent value or the agricultural characteristic-estimated crop constituent value for each subregion, such as the VI-estimated crop constituent value for each subregion.

[0105] FIG. 4 shows one example of a block diagram of such an agricultural system. FIG. shows an agricultural system **250** that can be disposed on agricultural harvester **100** or another system remote from agricultural harvester **100**. In another example, some items of agricultural system **250** are disposed on agricultural harvester **100** while other parts of agricultural system **250** are disposed at other locations, remote from agricultural harvester **100**. FIG. 4 also shows that, in one example, agricultural system **250** may be coupled to other systems **252** and other vehicles **254** over a network **256**. Other systems **252** may be remote server systems that are located in a remote server architecture, such as the cloud. Other systems **252** can be farm manager computing systems or vendor computing systems. Other systems **252** can be any of a wide variety of other systems as well. Other vehicles **254** may be other agricultural harvesters, agricultural sprayers, or other agricultural vehicles.

[0106] Network **256** may be a wide area network, a local area network, a near field communication network, a cellular communication network, or any of a wide variety of other networks or combinations of networks.

[0107] FIG. 4 also shows that agricultural system **250** can include one or more processors or servers **258**, data store **260**, crop constituent value distribution system **262**, crop constituent sensor **264**, communication system **266**, vegetative index map processing system **268**, agricultural characteristic map processing system **269**, weighted constituent value generator **270**, action signal generator **272**, and other agricultural system functionality **274**. Data store **260** can include vegetative index map **276**, one or more agricultural characteristic maps **277**, distributed constituent values **278**, VI-estimated constituent values **280**, agricultural characteristic-estimated constituent

values **281**, average VI-estimated constituent value **282**, average agricultural characteristic-estimated value **283**, weighted constituent values **284**, and other items **286**. Vegetative index map processing system **268** can include VI value extraction component **288**, correlation generator **290**, VI-estimated constituent value generator **292**, and other items **294**. Agricultural characteristic map processing system **269** can include agricultural characteristic value extraction component **289**, correlation generator **291**, agricultural characteristic-estimated constituent value generator **293**, and other items **295**.

[0108] Before describing the overall operation of agricultural system **250** in more detail, a brief description of some of the items in agricultural system **250** and the operation of those items will first be described. VI map **276** includes vegetative index maps that store geo-referenced vegetative index values for the field being harvested. Agricultural characteristic map(s) **277** include one or more agricultural characteristic maps that store geo-referenced agricultural characteristic values for the field being harvested, such as one or more of geo-referenced soil types, geo-referenced soil nutrient values, geo-referenced historical values, for instance geo-referenced historical crop constituent values, geo-referenced crop genotypes, and geo-referenced prior operation values, for instance geo-referenced prior nutrient application values. Distributed constituent values **278** are crop constituent values that are sensed by crop constituent sensor **202** (shown in FIG. 3) and distributed to the subregions corresponding to the crop that was sensed and gave rise to the sensed constituent value. In one example, the distributed constituent values **278** are generated during runtime, as agricultural harvester **100** is harvesting. In another example, the crop constituent values sensed by crop constituent sensor **202** are distributed to the subregions after the harvesting process. In one example, the crop constituent values sensed by sensor **202** are geo-referenced to the subregions using a geographic position sensor **203** on agricultural harvester **100**, the ground speed of agricultural harvester **100**, and the speed of the conveyors moving grain on header **102**, as well as any other machine delays in processing the crop.

[0109] VI-estimated constituent values **280** are geo-referenced constituent values corresponding to the field being harvested that were estimated based upon the VI values in VI map **276**. As is described in greater detail below, vegetative index map processing system **268** extracts the VI values from VI map **276** and obtains or generates a correlation between the VI values and crop constituent values. Vegetative index map processing system **268** generates the geo-referenced VI-estimated constituent values **280** for the different geographic locations in the field being harvested. In some instances, the VI-estimated constituent values **280** are contained on a map that maps the VI-estimated constituent values **280** to the different geographic positions on the field. Average VI-estimated constituent values **282** are the average of the VI-estimated constituent values **280** for the set of subregions corresponding to a measurement taken by crop constituent sensor **264**. A gain, taking the example shown in FIG. 3, the average VI-estimated constituent value is the average VI-estimated constituent value **280** for the subregions **230-244**. In one example, weighted constituent values **284** include the crop constituent values for each subregion in a field that is generated based upon the distributed constituent value **278**, the VI-estimated constituent value **280**, and the average VI-estimated constituent value **282** corresponding to that subregion. One example of generating the weighted constituent values **284** is described in greater detail below.

[0110] Agricultural characteristic-estimated values **281** are geo-referenced constituent values corresponding to the field being harvested that were estimated based upon the agricultural characteristic values in one or more agricultural characteristic maps **277**. As is described in greater detail below, agricultural characteristic map processing system **269** extracts the agricultural characteristic values from one or more agricultural characteristic maps **277** and obtains or generates a correlation between the agricultural characteristic values and crop constituent values. Agricultural characteristic map processing system **269** generates the geo-referenced agricultural characteristic-estimated constituent values **281** for the different geographic locations in the field being harvested. In some instances, the agricultural characteristic-estimated constituent values **281** are contained on

a map that maps the agricultural characteristic-estimated constituent values **281** to the different geographic positions on the field. Average agricultural characteristic-estimated constituent values **283** are the average of the agricultural characteristic-estimated constituent values **281** for the set of subregions corresponding to a measurement taken by crop constituent sensor **264**. A gain, taking the example shown in FIG. **3**, the average agricultural characteristic-estimated constituent value **283** is the average agricultural characteristic-estimated constituent value **281** for the subregions **230-244**. In one example, weighted constituent values **284** include the crop constituent values for each subregion in a field that is generated based upon the distributed constituent value **278**, the agricultural characteristic-estimated constituent value **281**, and the average agricultural characteristic-estimated constituent value **283** corresponding to that subregion. One example of generating the weighted constituent values **284** is described in greater detail below.

[0111] In some examples, the weighted constituent values include the crop constituent values for each subregion in a field that is generated based upon the distributed constituent value **278**, the VI-estimated constituent value **280**, the agricultural characteristic-estimated constituent value **281**, the average VI-estimated constituent value **282**, and the average agricultural characteristic-estimated constituent value **283** corresponding to that subregion.

[0112] Crop constituent sensor **264** may be crop constituent sensor **200** or crop constituent sensor **202** from previous figures, or crop constituent sensor **264** may be a different crop constituent sensor on agricultural harvester **100**. In some instances, crop constituent sensor **264** utilizes one or more bands of electromagnetic radiation in detecting crop constituents. For example, a crop constituent sensor **264** utilizes the reflectance or absorption of various ranges (e.g., various wavelengths or frequencies or both) of electromagnetic radiation by crop or other vegetation material, including grain of crop plants, in detecting crop constituents. In some examples, a crop constituent sensor **264** includes an optical sensor, such as an optical spectrometer. In one example, a crop constituent sensor **264** utilizes near-infrared spectroscopy or visible and near-infrared spectroscopy. In some instances, the crop constituent sensor **264** is disposed at or has access to various locations within agricultural harvester **100**. For example, in some implementations, the crop constituent sensor **264** is disposed within the feeder house **106** (or otherwise have sensing access to crop material within feeder house **106**) and is configured to detect constituents of harvested crop material passing through the feeder house **106**. In other examples, the crop constituent sensor **264** is located at other areas within the agricultural harvester. For instance, in some instances, the crop constituent sensor **264** is on, coupled to, or disposed within the clean grain elevator **130**; on, coupled to, or disposed within a clean grain auger; or on, coupled to, or disposed within a clean grain tank **132**. It will be noted that these are merely examples of the types of locations of crop constituent sensor **264** and that various other types and locations of crop constituent sensor **264** are contemplated. Crop constituent value distribution system **262** obtains a crop constituent value from crop constituent sensor **264** (or from a data store where the value is stored) and distributes the sensed crop constituent value across the different subregions corresponding to the sensor measurement that generated that value. Again, taking the example shown in FIG. **3**, crop constituent value distribution system **262** obtains a crop constituent value from crop constituent sensor **264** and distributes that value across the different subregions **230-244** that correspond to the crop which gave rise to the crop constituent value. For instance, crop constituent value distribution system **262** obtains a geographic subregions from a geographic position sensor **203** (such as a GPS receiver) and determines the geographic locations where the sensed crop constituent value is to be distributed.

[0113] In some examples, crop constituent sensor **264** relies on different types of radiation and the way in which the radiation is reflected by, absorbed by, attenuated by, or transmitted through the crop material, including grain. In some implementations, the crop constituent sensor senses other electromagnetic properties of crop material, such as electrical permittivity when the material passes between two capacitive plates. Other material properties and sensors may also be used. In some

examples, raw or processed data from crop constituent sensor **264** is presented to the operator of agricultural harvester **100** via an operator interface mechanism. The operator may be on-board of the agricultural harvester **100** or at a remote location such as at another system or in another vehicle **254**.

[0114] Communication system **266** enables communication among the items in agricultural system **250**. Communication system **266** also enables communication over network **256**. Therefore, the particular type of communication system **266** that is used in agricultural system will depend on the type of communication that it is to facilitate.

[0115] In one example, vegetative index map processing system **268** obtains VI map **276** and generates the VI-estimated constituent values **280** that are geo-referenced to the field being harvested. In one example, vegetative index map processing system **268** generates a VI-estimated constituent map that includes the VI-estimated constituent values **280**.

[0116] VI value extraction component **288** extracts the VI values from VI map **276**. Correlation generator **290** then generates a correlation between the extracted VI values and crop constituent values. Correlation generator **290** can generate a correlation during runtime, or correlation generator **290** can obtain the correlation that was previously generated and stored (such as from a previous operation on the same worksite or another worksite). Generating the correlation between VI values and crop constituent values can be done in a variety of different ways. For example, generating the correlation between VI values and the crop constituent values can include generating, as the correlation, a model. For instance, a VI value-to-crop constituent model generator (e.g., correlation generator **290**) can identify a relationship between crop constituent values at different geographic locations in the field and vegetative index values from the VI map for that same field. Based upon this relationship, a correlation or model can be generated by correlation generator **290**. The correlation or model is applied to the VI values extracted from VI map **276** by VI value extraction component **288** to generate VI-estimated constituent values **280**. For instance, VI-estimated constituent value generator **292** applies the correlation or model generated by correlation generator **290** to the different VI values corresponding to the different geographic locations on VI map **276**. VI-estimated constituent value generator **292** generates an estimated crop constituent value for each of those geographic locations. In some instances, VI-estimated constituent value generator **292** outputs the VI-estimated constituent values **280**, geo-referenced to the different locations in the field, on a map, such as a functional predictive VI-estimated constituent value map, or in other ways.

[0117] In one example, a model can be generated that models the relationship between crop constituent values and vegetative index values. The modeling can include correlating crop constituent values with vegetative index values corresponding to the same geographic locations as the crop constituent values. For instance, a VI value for a given location and a crop constituent value for that same location can be correlated (e.g., modeled). Then, the crop constituent value for a different given location (such as an unharvested location) can be estimated based on the VI value for the different given location (as derived from a VI map or other source) and the correlation (e.g., model). In one example, a VI value for a given location, such as from a VI map, and the crop constituent value detected by crop constituent sensor **264** corresponding to that given location can be correlated (e.g., modeled), and given a VI value, from the VI map, for a different given location (e.g., unharvested location) the crop constituent value for that different given location can be estimated based on the VI value and the correlation (e.g., model). The VI-estimated crop constituent values can be represented in a functional predictive VI-estimated crop constituent map that maps the VI-estimated crop constituent values to different geographic locations across the worksite, based on the correlation (e.g., model) and the VI map. The correlation (e.g., model) can be updated (e.g., remodeled, revised, etc.) based on further corresponding VI values and crop constituent values, such as further crop constituent values detected by crop constituent sensor **264**. Further, a new map can be generated based on the updated model.

[0118] It can be seen that the correlation (e.g., model) can be predictive of crop constituents (e.g., can be a predictive crop constituent correlation [e.g., model]) in that it can receive, as an input, a VI value from a VI map and generate, as an output, a predictive (e.g., estimated) crop constituent value.

[0119] Weighted constituent value generator **270** then generates a weighted crop constituent value for each subregion on the field based on the distributed constituent values **278** for the subregions in the field, the VI-estimated constituent values **280** for the subregions in the field, and the average VI-estimated constituent value **282**. In one example, weighted constituent value generator **270** may generate each of the weighted crop constituent values, for each of the different subregions in the field, using the following equation:

$$[00001] C_w = \frac{C_{\text{DISTRIBUTED}} * C_{\text{VI-EST}}}{C_{\text{AVG}}} \quad \text{Eq. 1}$$

[0120] Where: [0121] C.sub.W is the weighted crop constituent value for the subregion under analysis; [0122] C.sub.DISTRIBUTED is the distributed crop constituent value for the subregion under analysis; [0123] C.sub.VI-EST is the VI-estimated crop constituent value for the subregion under analysis; and [0124] C.sub.AVG is the average of the VI-estimated crop constituent values for all subregions corresponding to the measurement interval.

[0125] In another example, agricultural characteristic map processing system **269** obtains one or more agricultural characteristic maps **277** and generates the agricultural characteristic-estimated constituent values **281** that are geo-referenced to the field being harvested. In one example, agricultural characteristic map processing system **269** generates an agricultural characteristic-estimated constituent map that includes the agricultural characteristic-estimated constituent values **281**.

[0126] Agricultural characteristic value extraction component **289** extracts the agricultural characteristic values from one or more agricultural characteristic maps **277**. Correlation generator then generates a correlation between the extracted agricultural characteristic values and crop constituent values. Correlation generator **291** can generate a correlation during runtime, or correlation generator **291** can obtain the correlation that was previously generated and stored (such as from a previous operation on the same worksite or another worksite). Generating the correlation between agricultural characteristic values and crop constituent values can be done in a variety of different ways. For example, generating the correlation between agricultural characteristic values and the crop constituent values can include generating, as the correlation, a model. For instance, an agricultural characteristic-to-crop constituent model generator (e.g., correlation generator **291**) can identify a relationship between crop constituent values at different geographic locations in the field and agricultural characteristics values from the one or more agricultural characteristic maps for that same field. For example, a model can be generated that models the relationship between crop constituent values and agricultural characteristic values. The modeling can include correlating crop constituent values with agricultural characteristic values corresponding to the same geographic locations as the crop constituent values. Based upon this relationship, a correlation or model can be generated by correlation generator **291**. The correlation or model is applied to the agricultural characteristic values extracted from the one or more agricultural characteristic maps **277** by agricultural characteristic value extraction component **289** to generate agricultural characteristic-estimated constituent values **281**. For instance, agricultural characteristic-estimated constituent value generator **293** applies the correlation or model generated by correlation generator **291** to the different agricultural characteristic values corresponding to the different geographic locations on the one or more agricultural characteristic maps **277**. Agricultural characteristic-estimated constituent value generator **293** generates an estimated crop constituent value for each of those geographic locations. In some instances, agricultural characteristic-estimated constituent value generator **293** outputs the agricultural characteristic-estimated constituent values **281**, geo-referenced to the different locations in the field, on a map, such as a functional predictive

agricultural characteristic-estimated crop constituent map, or in other ways.

[0127] In one example, a model can be generated that models the relationship between crop constituent values and agricultural characteristic values. The modeling can include correlating **9** crop constituent values with agricultural characteristic values corresponding to the same geographic locations as the crop constituent values. For instance, one or more agricultural characteristic values for a given location and a crop constituent value for that same location can be correlated (e.g., modeled), and given the one or more agricultural characteristic values, such as from one or more agricultural characteristic maps, for another location the crop constituent value for the other location can be estimated based on the one or more agricultural characteristic values for the other location and the correlation (e.g., model). In one example, one or more agricultural characteristic values for a given location, such as from one or more agricultural characteristic maps, and the crop constituent value detected by crop constituent sensor **264** and corresponding to that given location can be correlated (e.g., modeled), and given one or more agricultural characteristic values, from the one or more agricultural characteristic maps, for a different given location (e.g., unharvested location) the crop constituent value for that different given location can **21** be estimated based on the one or more agricultural characteristic values and the correlation (e.g., model). The agricultural characteristic-estimated crop constituent values can be represented in a functional predictive agricultural characteristic-estimated crop constituent map that maps the agricultural characteristic-estimated crop constituent values to different geographic locations across the worksite, based on the correlation (e.g., model) and the one or more agricultural characteristic maps. The correlation (e.g., model) can be updated (e.g., remodeled, revised, etc.) based on further corresponding VI values and crop constituent values, such as further crop constituent values detected by crop constituent sensor **264**. Further, a new map can be generated based on the updated model.

[0128] Thus, it can be seen that the correlation (e.g., model) can be predictive of crop constituents (e.g., can be a predictive crop constituent correlation [e.g., model]) in that it can receive, as an input, a value of an agricultural characteristic from an agricultural characteristic map and generate, as an output, a predictive (e.g., estimated) crop constituent value.

[0129] Weighted constituent value generator **270** then generates a weighted crop constituent value for each subregion on the field based on the distributed constituent values **278** for the subregions in the field, the agricultural characteristic-estimated constituent values **281** for the subregions in the field, and the average agricultural characteristic-estimated constituent value **283**. In one example, weighted constituent value generator may generate each of the weighted crop constituent values, for each of the different subregions in the field, using the following equation:

[00002] $C_w = \frac{C_{\text{DISTRIB}} * C_{\text{AG-EST}}}{C_{\text{AVGAG}}}$ Eq. 2 [0130] Where C.sub.W is the weighted crop constituent value for the subregion under analysis; [0131] C.sub.DISTRIB is the distributed crop constituent value for the subregion under analysis; [0132] C.sub.AG-EST is the agricultural characteristic-estimated crop constituent value for the subregion under analysis; and [0133] C.sub.AVGAG is the average of the agricultural characteristic-estimated crop constituent values for all subregions corresponding to the measurement interval.

[0134] Weighted constituent value generator **270** generates the weighted crop constituent values on a weighted crop constituent value map of the field, or weighted constituent value generator **270** outputs the weighted crop constituent values geo-referenced to the subregions in the field in other ways.

[0135] Action signal generator **272** generates an action signal based upon the weighted crop constituent values generated by weighted constituent value generator **270**. Action signal generator **272** generates one or more different action signals based upon the weighted crop constituent values output by weighted constituent value generator **270**. For example, action signal generator **272** is used to control controllable subsystems on agricultural harvester **100** based upon the weighted crop

constituent values output by weighted constituent value generator **270**. It will be appreciated that the particular control signals that are generated and the particular controllable subsystems that are controlled may vary based upon one or more different criteria. For example, the control signals that are generated and the controllable subsystems that are controlled may be based upon whether the weighted crop constituent values are generated prior to the harvesting operation or during the harvesting operation.

[0136] In one example, the weighted crop constituent values generated by the weighted constituent value generator **270** include crop constituent values geo-referenced to locations within the field being harvested. The weighted crop constituent values may be generated prior to the harvesting operation, such as during a spraying operation or another agricultural operation. Action signal generator **272** may control the steering and propulsion subsystems of agricultural harvester to control the heading and speed of agricultural harvester **100** to control a feed rate of material or grain moving through the agricultural harvester **100** based on the weighted crop constituent values and based on a geographic location of agricultural harvester **100**. Similarly, the height of header **102** may be controlled to take in more or less material and thus control the feed rate of material through the agricultural harvester **100**. In other examples, and assuming that the weighted crop constituent values at geographic locations ahead of agricultural harvester **100** are known, action signal generator **272** determines whether the weighted crop constituent values are higher on one portion of header **102** than another portion of header **102**, resulting in a different biomass entering one side of the header **102** over the other side of the header **102**. In such a case, action signal generator **272** may control the header **102** based upon the difference in weighted crop constituent values across the header **102**. By way of example, a draper speed on one side of header may be increased or decreased relative to the draper speed on the other side of header **102** to account for additional biomass.

[0137] In another example, action signal generator **272** may generate control signals to control communication system **266** to output the weighted crop constituent values generated by weighted constituent value generator **270** over network **256** to other systems **252** or other vehicles **254**. Operations may be performed on the weighted crop constituent values at other systems **252** or in other vehicles **254**.

[0138] The examples herein describe the generation of a predictive model and, in some examples, the generation of a functional predictive map based on the predictive model. The examples described herein are distinguished from other approaches by the use of a model which is at least one of multi-variate or site-specific (i.e., georeferenced, such as map-based). Furthermore, the model is revised as the work machine is performing an operation and while additional in-situ sensor data is collected. The model may also be applied in the future beyond the current worksite. For example, the model may form a baseline (e.g., starting point) for a subsequent operation at a different worksite or at the same worksite at a future time.

[0139] The revision of the model in response to new data may employ machine learning methods. Without limitation, machine learning methods may include memory networks, Bayes systems, decisions trees, Eigenvectors, Cluster Analysis, Eigenvalues and Machine Learning, Evolutionary and Genetic Algorithms, Expert Systems/Rules, Support Vector Machines, Engines/Symbolic Reasoning, Generative Adversarial Networks (GANs), Graph Analytics and ML, Linear Regression, Logistic Regression, LSTMs and Recurrent Neural Networks (RNNs), Convolutional Neural Networks (CNNs), MCMC, Random Forests, Reinforcement Learning or Reward-based machine learning. Learning may be supervised or unsupervised.

[0140] Model implementations may be mathematical, making use of mathematical equations, empirical correlations, statistics, tables, matrices, and the like. Other model implementations may rely more on symbols, knowledge bases, and logic such as rule-based systems. Some implementations are hybrid, utilizing both mathematics and logic. Some models may incorporate random, non-deterministic, or unpredictable elements. Some model implementations may make

uses of networks of data values such as neural networks. These are just some examples of models. [0141] The predictive paradigm examples described herein differ from non-predictive approaches where an actuator or other machine parameter is fixed at the time the machine, system, or component is designed, set once before the machine enters the worksite, is reactively adjusted manually based on operator perception, or is reactively adjusted based on a sensor value.

[0142] The functional predictive map examples described herein also differ from other map-based approaches. In some examples of these other approaches, an a priori control map is used without any modification based on in-situ sensor data or else a difference determined between data from an in-situ sensor and a predictive map are used to calibrate the in-situ sensor. In some examples of the other approaches, sensor data may be mathematically combined with a priori data to generate control signals, but in a location-agnostic way; that is, an adjustment to an a priori, georeferenced predictive setting is applied independent of the location of the work machine at the worksite. The continued use or end of use of the adjustment, in the other approaches, is not dependent on the work machine being in a particular defined location or region within the worksite.

[0143] In examples described herein, the functional predictive maps and predictive actuator control rely on obtained maps and in-situ data that are used to generate predictive models. The predictive models are then revised during the operation to generate revised functional predictive maps and revised actuator control. In some examples, the actuator control is provided based on functional predictive control zone maps which are also revised during the operation at the worksite. In some examples, the revisions (e.g., adjustments, calibrations, etc.) are tied to regions or zones of the worksite rather than to the whole worksite or some non-georeferenced condition. For example, the adjustments are applied to one or more areas of a worksite to which an adjustment is determined to be relevant (e.g., such as by satisfying one or more conditions which may result in application of an adjustment to one or more locations while not applying the adjustment to one or more other locations), as opposed to applying a change in a blanket way to every location in a non-selective way.

[0144] In some examples described herein, the models determine and apply those adjustments to selective portions or zones of the worksite based on a set of a priori data, which, in some instances, is multivariate in nature. For example, adjustments may, without limitation, be tied to defined portions of the worksite based on site-specific factors such as topography, soil type, crop variety, soil moisture, as well as various other factors, alone or in combination. Consequently, the adjustments are applied to the portions of the field in which the site-specific factors satisfy one or more criteria and not to other portions of the field where those site-specific factors do not satisfy the one or more criteria. Thus, in some examples described herein, the model generates a revised functional predictive map for at least the current location or zone, the unworked part of the worksite, or the whole worksite.

[0145] As an example, in which the adjustment is applied only to certain areas of the field, consider the following. The system may determine that a detected in-situ characteristic value (e.g., detected crop constituent value) varies from a predictive value of the characteristic (e.g., predictive crop constituent value), such as by a threshold amount. This deviation may only be detected in areas of the field where the elevation of the worksite is above a certain level. Thus, the revision to the predictive value is only applied to other areas of the worksite having elevation above the certain level. In this simpler example, the predictive characteristic value and elevation at the point the deviation occurred and the detected characteristic value and elevation at the point the deviation cross the threshold are used to generate a linear equation. The linear equation is used to adjust the predictive characteristic value in unharvested areas of the worksite in the functional predictive map as a function of elevation and the predicted characteristic value. This results in a revised functional predictive map in which some values are adjusted while others remain unchanged based on selected criteria, e.g., elevation as well as threshold deviation. The revised functional map is then used to generate a revised functional control zone map for controlling the machine.

[0146] As an example, without limitation, consider an instance of the paradigm described herein which is parameterized as follows.

[0147] One or more maps of the field are obtained, such as one or more of a vegetative index map and another type of agricultural characteristic map.

[0148] In-situ sensors generate sensor data indicative of in-situ characteristic values, such as in-situ crop constituent values.

[0149] A predictive model generator generates one or more predictive models based on the one or more obtained maps and the in-situ sensor data, such as a predictive crop constituent model.

[0150] A predictive map generator generates one or more functional predictive maps based on a model generated by the predictive model generator and the one or more obtained maps. For example, the predictive map generator may generate a functional predictive crop constituent map that maps predictive crop constituent values to one or more locations on the worksite based on a predictive crop constituent model and the one or more obtained maps.

[0151] Control zones, which include machine settings values, can be incorporated into the functional predictive crop constituent map to generate a functional predictive crop constituent control zone map.

[0152] As the mobile machine continues to operate at the worksite, additional in-situ sensor data is collected. A learning trigger criteria can be detected, such as threshold amount of additional in-situ sensor data being collected, a magnitude of change in a relationship (e.g., the in-situ characteristic values varies to a certain [e.g., threshold] degree from a predictive value of the characteristic), and operator or user makes edits to the predictive map(s) or to a control algorithm, or both, a certain (e.g., threshold) amount of time elapses, as well as various other learning trigger criteria. The predictive model(s) are then revised based on the additional in-situ sensor data and the values from the obtained maps. The functional predictive maps or the functional predictive control zone maps, or both, are then revised based on the revised model(s) and the values in the obtained maps.

[0153] FIG. 5A is a flow diagram showing one example of how agricultural system **250** generates weighted constituent values **284** for a set of subregions corresponding to a measured or detected aggregated constituent value that is sensed or detected by crop constituent sensor **264** during a measurement interval.

[0154] At block **350**, crop constituent value distribution system **262** first obtains a crop constituent value for a geographic location in a field under analysis. Block **352** shows that, crop constituent value distribution system **262** may obtain the crop constituent value during runtime from crop constituent sensor **264**. Block **354** shows that crop constituent value distribution system may obtain the crop constituent value by accessing a stored crop constituent value that was obtained previously for the geographic location in the field. By way of example, it may be that a crop constituent sensor **264** is deployed on a sprayer and the sprayer generates crop constituent values corresponding to different geographic locations in the field being sprayed. The crop constituent values generated for the different geographic locations in the field being sprayed May be stored for later access by agricultural system **250**. In one example, it may be that a crop constituent sensor **264** is deployed on an agricultural harvester and the agricultural harvester generates crop constituent values corresponding to different geographic locations in the field being harvested. The crop constituent values generated for the different geographic locations in the field being harvested may be stored for later use by agricultural system **250**, such as to correctly allocate the crop constituent values to the different geographic locations in the field after the harvesting operation is complete.

[0155] Block **356** shows that crop constituent value distribution system **262** may obtain or detect the crop constituent value in other ways.

[0156] At block **358**, crop constituent value distribution system **262** then distributes the crop constituent value to a set of subregions. By way of example, and referring to FIG. 3, when crop constituent sensor **200**, **202** takes a measurement, crop constituent value distribution system can distribute the crop constituent sensor value to the subregions **230-244**. The geographic location of

the subregions may be based on one or more of the criteria in blocks **360**, **362**, **364**, **366**, and **368**. The geographic location of the subregions may be based upon a geographic location of agricultural harvester **100** at the time the measurement from crop constituent sensor **200**, **202** is taken as indicated by block **360**. Block **362** shows that the geographic location of each of the subregions **230-244** may be based upon the travel speed or ground speed of the agricultural machine (e.g., of the agricultural harvester **100** in the example shown in FIG. 3). Block **364** shows that the geographic location of the subregions **230-244** may also be based upon the location of sensor **200**, **202** on the agricultural machine (e.g., in the example shown in FIG. 3 on agricultural harvester **100**). Block **366** shows that when the agricultural machine is an agricultural harvester **100**, then the geographic location of each of the subregions **230-244** may also be based upon the crop movement speed across the header **102**, based upon the width of the header **102**, and based **6** upon other machine delays between when the crop is harvested and when it encounters crop constituent sensor **200**, **202**. For instance, the location of the sensor **200**, **202**, the location of the machine, the travel speed and heading of the agricultural machine, and the machine delays in processing and transporting the crop material to the sensor (e.g., crop movement speed across the head, width of the head, and other machine delays) may be used to identify a geographic location of the subregions. For example, there may be a time delay (e.g., latency) between when the crop is encountered by the agricultural machine and when the crop material is sensed by the sensor **200**, **202**. That time delay (e.g., latency) may be identified (e.g., based on machine delays). In some examples, the time delay (e.g., latency) may be fixed (at least for a particular machine or machine model). In other examples, the time delay (e.g., latency) may be variable and based on factors during the operation, such as the travel speed of the machine, the parameters of working parts of the machine, characteristics of the crop, as well as various other factors. The geographic location of the sensor at the time of the measurement of the crop material (as derived from the geographic position of the agricultural machine and the distance between the geographic position sensor and the sensor **200**, **202**) along with the speed and heading of the agricultural machine may be used, in combination with the identified time delay (e.g., latency), to identify a geographic location of the subregions to which the measurement corresponds. If the measurement was taken at location X, and calculated machine delay is 16 seconds, and the speed of the agricultural machine is 5 miles per hour (MPH) (or 7.33333 feet per second) heading due north, then the location of the subregions (location Y) can be identified as 117.33328 feet (16 seconds multiplied by 7.33333 feet per second) due south (as the machine was/is heading due north) of location X. This is merely an example.

[0157] Block **368** shows that crop constituent value distribution system **262** may distribute the crop constituent value to the subregions in other ways and based on other distribution criteria.

[0158] Agricultural characteristic map processing system **269** then accesses one or more agricultural characteristic maps **277** to generate the agricultural characteristic-estimated constituent values **281**. At block **370**, weighted constituent value generator **270** obtains access to the agricultural characteristic-estimated constituent values **281** for the subregions under analysis. It will be noted that in some examples agricultural characteristic map processing system **269** may access the agricultural characteristic values on the one or more agricultural characteristic maps and generate the agricultural characteristic-estimated constituent values **281** ahead of time, such as before operating at the field or before operating at a particular portion of the field, using the model or other correlation that correlates the agricultural characteristic values on the one or more agricultural characteristic maps **277** to crop constituent values. Block **372** shows that agricultural characteristic value extraction component **289** obtains the one or more agricultural characteristic maps **277** that show agricultural characteristic values for the different subregions in the field. Block **374** shows that correlation generator **291** generates or obtains a correlation between agricultural characteristic values and constituent values, and block **376** shows that agricultural characteristic-estimated constituent value generator **293** generates the agricultural characteristic-estimated constituent values **281** for the subregions in the field.

[0159] Block **378** shows that weighted constituent value generator **270** may access the agricultural characteristic-estimated constituent values **281** in other ways as well.

[0160] At block **380**, weighted constituent value generator **270** generates weighted crop constituent values for each of the subregions using the distributed crop constituent values **278** for those subregions, and the agricultural characteristic-estimated constituent values **281** for those subregions. In one example, weighted constituent value generator **270** uses the equation illustrated above in Equation 2 to generate the weighted crop constituent value for each of the subregions.

[0161] Once the weighted crop constituent values are generated for each subregion corresponding to a constituent measurement, action signal generator **272** generates an action signal based upon the weighted crop constituent values, as indicated by block **386**. In one example, action signal generator **272** generates action signals to store the weighted crop constituent values in data store **260**, as indicated by block **388**. Block **390** shows that action signal generator **272** may generate control signals to control controllable subsystems on the agricultural machine (such as agricultural harvester **100**). At block **392**, action signal generator generates control signals to control communication system **266** to communicate the weighted crop constituent values to a remote system **252** or to a remote vehicle **254**, such as another agricultural machine, for instance, another agricultural harvester. Block **394** shows that action signal generator **272** may generate other action signals in other ways as well.

[0162] FIG. 5B is a flow diagram showing one example of how agricultural system **250** generates weighted constituent values **284** for a set of subregions corresponding to a measured or detected aggregate constituent value that is sensed or detected by crop constituent sensor **264** during a measurement interval.

[0163] At block **300**, crop constituent value distribution system **262** first obtains a crop constituent value for a geographic location in a field under analysis. Block **302** shows that, crop constituent value distribution system **262** may obtain the crop constituent value during runtime from crop constituent sensor **264**. Block **304** shows that crop constituent value distribution system may obtain the crop constituent value by accessing a stored crop constituent value that was obtained previously for the geographic location in the field. By way of example, it may be that a crop constituent sensor **264** is deployed on a sprayer and the sprayer generates crop constituent values corresponding to different geographic locations in the field being sprayed. The crop constituent values generated for the different geographic locations in the field being sprayed may be stored for later access by agricultural system **250**. In one example, it may be that a crop constituent sensor **264** is deployed on an agricultural harvester and the agricultural harvester generates crop constituent values corresponding to different geographic locations in the field being harvested. The crop constituent values generated for the different geographic locations in the field being harvested may be stored for later use by agricultural system **250**, such as to correctly allocate the crop constituent values to the different geographic locations in the field after the harvesting operation is complete.

[0164] Block **306** shows that crop constituent value distribution system **262** may obtain or detect the crop constituent value in other ways.

[0165] At block **308**, crop constituent value distribution system **262** then distributes the crop constituent value to a set of subregions. By way of example, and referring to FIG. 3, when crop constituent sensor **200, 202** takes a measurement, crop constituent value distribution system can distribute the crop constituent sensor value to the subregions **230-244**. The geographic location of the subregions may be based upon a geographic location of agricultural harvester **100** at the time the measurement from crop constituent sensor **200, 202** is taken as indicated by block **310**. Block **312** shows that the geographic location of each of the subregions **230-244** may be based upon the travel speed or ground speed of the agricultural machine (e.g., of the agricultural harvester in the example shown in FIG. 3). Block **314** shows that the geographic location of the subregions **230-244** may also be based upon the location of sensor **200, 202** on the agricultural machine (e.g., in the example shown in FIG. 3 on agricultural harvester **100**). Block **316** shows that when the

agricultural machine is an agricultural harvester **100**, then the geographic location of each of the subregions **230-244** may also be based upon the crop movement speed across the header **102**, based upon the width of the header **102**, and based upon other machine delays between when the crop is harvested and when it encounters crop constituent sensor **200**, **202**. Block **318** shows that crop constituent value distribution system **262** may distribute the crop constituent value to the subregions in other ways and based on other distribution criteria.

[0166] Vegetative index map processing system **268** then accesses VI map **276** to generate the VI-estimated constituent values **280**. At block **320**, weighted constituent value generator **270** obtains access to the vegetative index (VI)-estimated constituent values **280** for the subregions under analysis. It will be noted that in some examples vegetative index map processing system **268** can access the VI values on VI map **276** and generate the VI-estimated constituent values **280** ahead of time, such as before operating at the field or before operating at a particular portion of the field, using the model or other correlation that correlates the VI values on VI map **276** to crop constituent values. Block **322** shows that VI value extraction component **288** obtains the VI map that shows VI values for the different subregions in the field. Block **324** shows that correlation generator **290** generates or obtain a correlation between VI values and constituent values, and block **326** shows that VI-estimated constituent value generator **292** generates the VI-estimated constituent values **280** for the subregions in the field.

[0167] Block **328** shows that weighted constituent value generator **270** may access the vegetative index-estimated constituent values **280** in other ways as well.

[0168] At block **330**, weighted constituent value generator **270** generates weighted crop constituent values for each of the subregions using the distributed crop constituent values **278** for those subregions, and the VI-estimated constituent values **280** for those subregions. In one example, weighted constituent value generator **270** uses the equation illustrated above in Equation to generate the weighted crop constituent value for each of the subregions.

[0169] FIG. **6** shows one example of the set of subregions **230-244** from FIG. **3** along with a table **334** that includes the crop constituent value (where the constituent is protein measured in grams/kilogram) for each of the subregions, the VI-estimated constituent value for each of the subregions, and the weighted crop constituent value for each subregion. FIG. **6** also shows that the average VI-estimated constituent value for the subregions **230-244** is 135 grams/kilogram. Row in Table **334** shows the distributed constituent value, the VI-estimated constituent value and the weighted crop constituent value for subregion **230**. Row **206** in table **334** shows the same values for subregion **234**. Row **208** in Table **334** shows the same values for subregion **238**. Row in Table **334** shows the same values for subregion **242**. Row **212** in Table **334** shows the same values for subregion **244**. Row **214** in Table **334** shows the same values for subregion **240**. Row in table **334** shows the same values for subregion **236** and row **218** in Table **334** shows the same values for subregion **232**. Applying Equation 1 to the values in Row **1** is illustrated by Equation 3 below:

$$[00003] \quad C_{W_{230}} = \frac{(120_{g/kg})(140_{g/kg})}{135_{g/kg}} \quad \text{Eq. 3}$$

$$= 124.44_{g/kg}$$

[0170] C.sub.W.sub.230 is the weighted crop constituent value for subregion **230**.

[0171] It will be noted that Equation 1 is one example of how the weighted crop constituent values can be generated based upon the distributed constituent values and VI-estimated constituent values, and other equations or mechanisms can be used to generate the weighted crop constituent values as well, such as Equation 2.

[0172] Once the weighted crop constituent values are generated for each subregion corresponding to a constituent measurement, action signal generator **272** generates an action signal based upon the weighted crop constituent values, as indicated by block **336** in the flow diagram illustrated in FIG. **5B**. In one example, action signal generator **272** generates action signals to store the weighted crop

constituent values in data store **260**, as indicated by block **338**. Block **340** shows that action signal generator **272** may generate control signals to control controllable subsystems on the agricultural machine (such as agricultural harvester **100**). At block **342**, action signal generator **272** generates control signals to control communication system **266** to communicate the weighted crop constituent values to a remote system **252** or a remote vehicle **254**, such as another agricultural machine, for instance, another agricultural harvester. Block **344** shows that action signal generator **272** generates other action signals in other ways as well. FIGS. 5A and 5B have discussed a system and methods for generating weighted crop constituent values for a set of subregions **230-244** corresponding to a measurement taken by crop constituent sensor **264** during a single measurement interval. It will be appreciated that the steps illustrated in FIGS. 5A and 5B may be taken repeatedly in order to generate the weighted crop constituent values for all subregions in a field, or for multiple different sets of subregions in a field.

[0173] It can thus be seen that the present description describes a system in which crop constituent values from a sensor are distributed to subregions within a field where the crop resides that gave rise to the sensor measurement. The distributed crop constituent values are then combined with an agricultural characteristic-estimated constituent value, such as a VI-estimated constituent value, for the same subregion to obtain a weighted crop constituent value for that subregion. Action signals may then be generated based upon the weighted crop constituent values.

[0174] The present discussion has proceeded with respect to an agricultural vehicle that comprises agricultural harvester **100**. It could just as easily, though, have proceeded with respect to a different agricultural vehicle, such as a sprayer.

[0175] The present discussion has mentioned processors and servers. In one example, the processors and servers include computer processors with associated memory and timing circuitry, not separately shown. The processors and servers are functional parts of the systems or devices to which they belong and are activated by, and facilitate the functionality of the other components or items in those systems.

[0176] Also, a number of user interface displays have been discussed. The user interface display can take a wide variety of different forms and can have a wide variety of different user actuatable input mechanisms disposed thereon. For instance, the user actuatable input mechanisms can be text boxes, check boxes, icons, links, drop-down menus, search boxes, etc. The mechanisms can also be actuated in a wide variety of different ways. For instance, the mechanisms can be actuated using a point and click device (such as a track ball or mouse). The mechanisms can be actuated using hardware buttons, switches, a joystick or keyboard, thumb switches or thumb pads, etc. The mechanisms can also be actuated using a virtual keyboard or other virtual actuators. In addition, where the screen on which the mechanisms are displayed is a touch sensitive screen, the mechanisms can be actuated using touch gestures. Also, where the device that displays them has speech recognition components, the mechanisms can be actuated using speech commands.

[0177] A number of data stores have also been discussed. It will be noted the data stores can each be broken into multiple data stores. All can be local to the systems accessing them, all can be remote, or some can be local while others are remote. All of these configurations are contemplated herein.

[0178] Also, the figures show a number of blocks with functionality ascribed to each block. It will be noted that fewer blocks can be used so the functionality is performed by fewer components. Also, more blocks can be used with the functionality distributed among more components.

[0179] It will be noted that the above discussion has described a variety of different systems, components and/or logic. It will be appreciated that such systems, components and/or logic can be comprised of hardware items (such as processors and associated memory, or other processing components, some of which are described below) that perform the functions associated with those systems, components and/or logic. In addition, the systems, components and/or logic can be comprised of software that is loaded into a memory and is subsequently executed by a processor or

server, or other computing component, as described below. The systems, components and/or logic can also be comprised of different combinations of hardware, software, firmware, etc., some examples of which are described below. These are only some examples of different structures that can be used to form the systems, components and/or logic described above. Other structures can be used as well.

[0180] FIG. 7 is a block diagram of agricultural system **250**, shown in FIG. 4, except that it communicates with elements in a remote server architecture **500**. In an example, remote server architecture **500** can provide computation, software, data access, and storage services that do not require end-user knowledge of the physical location or configuration of the system that delivers the services. In various examples, remote servers can deliver the services over a wide area network, such as the internet, using appropriate protocols. For instance, remote servers can deliver applications over a wide area network and they can be accessed through a web browser or any other computing component. Software or components shown in FIG. 4 as well as the corresponding data, can be stored on servers at a remote location. The computing resources in a remote server environment can be consolidated at a remote data center location or they can be dispersed. Remote server infrastructures can deliver services through shared data centers, even though they appear as a single point of access for the user. Thus, the components and functions described herein can be provided from a remote server at a remote location using a remote server architecture.

Alternatively, they can be provided from a conventional server, or they can be installed on client devices directly, or in other ways.

[0181] In the example shown in FIG. 7, some items are similar to those shown in FIG. 4 and they are similarly numbered. FIG. 7 specifically shows that other systems **252**, weighted constituent value generator **270**, vegetative index map processing system **268**, agricultural characteristic map processing system **269**, crop constituent value distribution system **262**, and data store **260** can be located at a remote server location **502**. Therefore, harvester **100** or other vehicles **254**, or both, access those systems through remote server location **502**.

[0182] FIG. 7 also depicts another example of a remote server architecture. FIG. 7 shows that it is also contemplated that some elements of FIG. 1 are disposed at remote server location while others are not. By way of example, data store **260** can be disposed at a location separate from location **502**, and accessed through the remote server at location **502**. Regardless of where the items are located, the items can be accessed directly by harvester **100**, through a network (either a wide area network or a local area network), they can be hosted at a remote site by a service, or the items can be provided as a service, or accessed by a connection service that resides in a remote location. Also, the data can be stored in substantially any location and intermittently accessed by, or forwarded to, interested parties. For instance, physical carriers can be used instead of, or in addition to, electromagnetic wave carriers. In such an example, where cell coverage is poor or nonexistent, another mobile machine (such as a fuel truck) can have an automated information collection system. As the agricultural harvester **100** comes close to the fuel truck for fueling, the system automatically collects the information from the agricultural harvester **100** using any type of ad-hoc wireless connection. The collected information can then be forwarded to the main network as the fuel truck reaches a location where there is cellular coverage (or other wireless coverage). For instance, the fuel truck may enter a covered location when traveling to fuel other machines or when at a main fuel storage location. All of these architectures are contemplated herein. Further, the information can be stored on the agricultural harvester **100** until the agricultural harvester **100** enters a covered location. The agricultural harvester **100**, itself, can then send the information to the main network.

[0183] It will also be noted that the elements of FIG. 1, or portions of them, can be disposed on a wide variety of different devices. Some of those devices include servers, desktop computers, laptop computers, tablet computers, or other mobile devices, such as palm top computers, cell phones, smart phones, multimedia players, personal digital assistants, etc.

[0184] FIG. 8 is a simplified block diagram of one illustrative example of a handheld or mobile computing device that can be used as a user's or client's hand held device **16**, in which the present system (or parts of it) can be deployed. For instance, a mobile device can be deployed in the operator compartment of harvester **100** for use in generating, processing, or displaying the stool width and position data. FIGS. 8-10 are examples of handheld or mobile devices.

[0185] FIG. 8 provides a general block diagram of the components of a client device **16** that can run some components shown in FIG. 4, that interacts with them, or both. In the device **16**, a communications link **13** is provided that allows the handheld device to communicate with other computing devices and under some examples provides a channel for receiving information automatically, such as by scanning. Examples of communications link **13** include allowing communication through one or more communication protocols, such as wireless services used to provide cellular access to a network, as well as protocols that provide local wireless connections to networks.

[0186] In other examples, applications can be received on a removable Secure Digital (SD) card that is connected to an interface **15**. Interface **15** and communication links **13** communicate with a processor **17** (which can also embody processors or servers from previous FIGS.) along a bus **19** that is also connected to memory **21** and input/output (I/O) components **23**, as well as clock and location system **27**.

[0187] I/O components **23**, in one example, are provided to facilitate input and output operations. I/O components **23** for various examples of the device **16** can include input components such as buttons, touch sensors, optical sensors, microphones, touch screens, proximity sensors, accelerometers, orientation sensors and output components such as a display device, a speaker, and or a printer port. Other I/O components **23** can be used as well.

[0188] Clock **25** illustratively comprises a real time clock component that outputs a time and date. It can also, illustratively, provide timing functions for processor **17**.

[0189] Location system **27** illustratively includes a component that outputs a current geographical location of device **16**. This can include, for instance, a global positioning system (GPS) receiver, a LORAN system, a dead reckoning system, a cellular triangulation system, or other positioning system. Location system **27** can also include, for example, mapping software or navigation software that generates desired maps, navigation routes and other geographic functions.

[0190] Memory **21** stores operating system **29**, network settings **31**, applications **33**, application configuration settings **35**, data store **37**, communication drivers **39**, and communication configuration settings **41**. Memory **21** can include all types of tangible volatile and non-volatile computer-readable memory devices. Memory **21** can also include computer storage media (described below). Memory **21** stores computer readable instructions that, when executed by processor **17**, cause the processor to perform computer-implemented steps or functions according to the instructions. Processor **17** can be activated by other components to facilitate their functionality as well.

[0191] FIG. 9 shows one example in which device **16** is a tablet computer **600**. In FIG. 9, computer **600** is shown with user interface display screen **602**. Screen **602** can be a touch screen or a pen-enabled interface that receives inputs from a pen or stylus. Computer **600** can also use an on-screen virtual keyboard. Of course, computer **600** might also be attached to a keyboard or other user input device through a suitable attachment mechanism, such as a wireless link or USB port, for instance. Computer **600** can also illustratively receive voice inputs as well.

[0192] FIG. 10 shows that the device can be a smart phone **71**. Smart phone **71** has a touch sensitive display **73** that displays icons or tiles or other user input mechanisms **75**. Mechanisms **75** can be used by a user to run applications, make calls, perform data transfer operations, etc. In general, smart phone **71** is built on a mobile operating system and offers more advanced computing capability and connectivity than a feature phone.

[0193] Note that other forms of the devices **16** are possible.

[0194] FIG. 11 is one example of a computing environment in which elements of FIGS. 1-10, or parts of it, (for example) can be deployed. With reference to FIG. 11, an example system for implementing some embodiments includes a general-purpose computing device in the form of a computer **810** programmed to act as described above. Components of computer **810** may include, but are not limited to, a processing unit **820** (which can comprise processors or servers from previous FIGS.), a system memory **830**, and a system bus **821** that couples various system components including the system memory to the processing unit **820**. The system bus **821** may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. Memory and programs described with respect to FIGS. 1-9 can be deployed in corresponding portions of FIG. 11.

[0195] Computer **810** typically includes a variety of computer readable media. Computer readable media can be any available media that can be accessed by computer **810** and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer readable media may comprise computer storage media and communication media. Computer storage media is different from, and does not include, a modulated data signal or carrier wave. Computer storage media includes hardware storage media including both volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information such as computer readable instructions, data structures, program modules or other data. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by computer **810**. Communication media may embody computer readable instructions, data structures, program modules or other data in a transport mechanism and includes any information delivery media. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal.

[0196] The system memory **830** includes computer storage media in the form of volatile and/or nonvolatile memory such as read only memory (ROM) **831** and random access memory (RAM) **832**. A basic input/output system **833** (BIOS), containing the basic routines that help to transfer information between elements within computer **810**, such as during start-up, is typically stored in ROM **831**. RAM **832** typically contains data and/or program modules that are immediately accessible to and/or presently being operated on by processing unit **820**. By way of example, and not limitation, FIG. 11 illustrates operating system **834**, application programs **835**, other program modules **836**, and program data **837**.

[0197] The computer **810** may also include other removable/non-removable volatile/nonvolatile computer storage media. By way of example only, FIG. 11 illustrates a hard disk drive **841** that reads from or writes to non-removable, nonvolatile magnetic media, an optical disk drive **855**, and nonvolatile optical disk **856**. The hard disk drive **841** is typically connected to the system bus **821** through a non-removable memory interface such as interface **840**, and optical disk drive **855** are typically connected to the system bus **821** by a removable memory interface, such as interface **850**.

[0198] Alternatively, or in addition, the functionality described herein can be performed, at least in part, by one or more hardware logic components. For example, and without limitation, illustrative types of hardware logic components that can be used include Field-programmable Gate Arrays (FPGAs), Application-specific Integrated Circuits (e.g., ASICs), Application-specific Standard Products (e.g., ASSPs), System-on-a-chip systems (SOCs), Complex Programmable Logic Devices (CPLDs), etc.

[0199] The drives and their associated computer storage media discussed above and illustrated in FIG. 11, provide storage of computer readable instructions, data structures, program modules and other data for the computer **810**. In FIG. 11, for example, hard disk drive **841** is illustrated as storing operating system **844**, application programs **845**, other program modules **846**, and program

data **847**. Note that these components can either be the same as or different from operating system **834**, application programs **835**, other program modules **836**, and program data **837**.

[0200] A user may enter commands and information into the computer **810** through input devices such as a keyboard **862**, a microphone **863**, and a pointing device **861**, such as a mouse, trackball or touch pad. Other input devices (not shown) may include a joystick, game pad, satellite dish, scanner, or the like. These and other input devices are often connected to the processing unit through a user input interface **860** that is coupled to the system bus, but may be connected by other interface and bus structures. A visual display **891** or other type of display device is also connected to the system bus **821** via an interface, such as a video interface **890**. In addition to the monitor, computers may also include other peripheral output devices such as speakers **897** and printer **896**, which may be connected through an output peripheral interface **895**.

[0201] The computer **810** is operated in a networked environment using logical connections (such as a controller area network-CAN, local area network-LAN, or wide area network WAN) to one or more remote computers, such as a remote computer **880**.

[0202] When used in a LAN networking environment, the computer **810** is connected to the LAN **871** through a network interface or adapter **870**. When used in a WAN networking environment, the computer **810** typically includes a modem **872** or other means for establishing communications over the WAN **873**, such as the Internet. In a networked environment, program modules may be stored in a remote memory storage device. FIG. **11** illustrates, for example, that remote application programs **885** can reside on remote computer **880**.

[0203] It should also be noted that the different examples described herein can be combined in different ways. That is, parts of one or more examples can be combined with parts of one or more other examples. All of this is contemplated herein.

[0204] Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims.

Claims

1. An agricultural system comprising: a crop constituent value distribution system configured to: obtain a crop constituent value, the crop constituent value corresponding to a sensor measurement by a crop constituent sensor; and assign the crop constituent value, as a distributed crop constituent value, to a set of subregions from which the crop constituent value was measured during the sensor measurement; and a weighted constituent value generator configured to generate a weighted crop constituent value for each subregion in the set of subregions, the weighted crop constituent value for each subregion in the set of subregions being based on an agricultural characteristic-estimated constituent value for the corresponding subregion that is estimated based on an agricultural characteristic value for the corresponding subregion.
2. The agricultural system of claim 1 and further comprising an action signal generator configured to control one or more controllable subsystems of an agricultural machine based, at least, on the weighted crop constituent value for each subregion in the set of subregions.
3. The agricultural system of claim 2, wherein the crop constituent sensor is disposed on an additional agricultural machine, different than the agricultural machine.
4. The agricultural system of claim 3, wherein the agricultural machine and the additional agricultural machine are each of a different machine type.
5. The agricultural system of claim 3, wherein the additional agricultural machine is configured to perform a first agricultural operation, wherein the action signal generator is configured to control one or more controllable subsystems of the agricultural machine during a second agricultural operation based, at least, on the weighted crop constituent value for each subregion in the set of

subregions, wherein the additional agricultural machine is configured to perform the first agricultural operation, prior to the second agricultural operation, and wherein the crop constituent sensor disposed on the additional agricultural machine is configured to detect the crop constituent value during the first agricultural operation.

6. The agricultural system of claim 1 and further comprising: a communication system configured to communicate the weighted crop constituent value for each subregion in the set of subregions to a remote system.

7. The agricultural system of claim 6, wherein the remote system comprises a remote computing system.

8. The agricultural system of claim 6, wherein the remote system comprises a remote agricultural machine.

9. The agricultural system of claim 1 and further comprising: an agricultural characteristic map processing system configured to access a map that includes the agricultural characteristic value corresponding to each subregion georeferenced to the corresponding subregion and to generate the agricultural characteristic-estimated constituent value corresponding to each subregion in the set of subregions based on the agricultural characteristic value georeferenced to the corresponding subregion in the map.

10. The agricultural system of claim 9, wherein the agricultural characteristic map processing system comprises: a correlation generator configured to generate an agricultural characteristic value-to-constituent value correlation between agricultural characteristic values and constituent values; and an agricultural characteristic-estimated constituent value generator configured to generate the agricultural characteristic-estimated constituent value corresponding to each subregion in the set of subregions based on the agricultural characteristic value georeferenced to the corresponding subregion and the agricultural characteristic value-to-constituent value correlation.

11. A computer implemented method comprising: obtaining a crop constituent value, the crop constituent value corresponding to a sensor measurement by a crop constituent sensor disposed on a first agricultural machine; assigning the crop constituent value, as a distributed crop constituent value, to a set of subregions from which the crop constituent value was measured during the sensor measurement; and generating a weighted crop constituent value for each subregion in the set of subregions, the weighted crop constituent value for each subregion in the set of subregions being based on an agricultural characteristic-estimated constituent value for the corresponding subregion that is estimated based on an agricultural characteristic value for the corresponding subregion.

12. The computer implemented method of claim 11 and further comprising: controlling a controllable subsystem of a second agricultural machine based, at least, on the weighted crop constituent value for at least one subregion in the set of subregions, the second agricultural machine different than the first agricultural machine.

13. The computer implemented method of claim 12, wherein controlling the controllable subsystem of the second agricultural machine comprises controlling the controllable subsystem of the second agricultural machine as the second agricultural machine performs a second agricultural operation, the second agricultural operation after a first agricultural operation performed by the first agricultural machine during which the sensor measurement takes place.

14. The computer implemented method of claim 11 and further comprising: communicating the weighted crop constituent value for each subregion in the set of subregions to a remote system.

15. The computer implemented method of claim 11 and further comprising: accessing a map that includes the agricultural characteristic value corresponding to each subregion georeferenced to the corresponding subregion; and generating the agricultural characteristic-estimated constituent value corresponding to each subregion in the set of subregions based on the agricultural characteristic value georeferenced to the corresponding subregion in the map.

16. The computer implemented method of claim 15 and further comprising: generating an agricultural characteristic value-to-constituent value correlation between agricultural characteristic

values and constituent values; and generating the agricultural characteristic-estimated constituent value corresponding to each subregion in the set of subregions based on the agricultural characteristic value georeferenced to the corresponding subregion and the agricultural characteristic value-to-constituent value correlation.

17. An agricultural machine comprising: one or more controllable subsystems; one or more processors; and memory storing instructions that, when executed by the one or more processors, cause the agricultural machine to: obtain a weighted crop constituent value for each subregion in a set of subregions of an agricultural worksite, the weighted crop constituent value for each subregion in the set of subregions being based on an agricultural characteristic-estimated constituent value for the corresponding subregion that is estimated based on an agricultural characteristic value for the corresponding subregion; and control the one or more controllable subsystems based on the weighted crop constituent value for each subregion in the set of subregions of the agricultural worksite.

18. The agricultural machine of claim 17, wherein the weighted constituent value for each subregion in the set of subregions of the agricultural worksite is further based on a distributed crop constituent value, the distributed crop constituent value distributed based on a detected crop constituent value detected by a crop constituent sensor during a sensor measurement corresponding to the set of subregions of the agricultural worksite.

19. The agricultural machine of claim 18, wherein the crop constituent sensor is disposed on an additional agricultural machine, different than the agricultural machine, and is configured to detect the detected crop constituent value during the sensor measurement as the additional agricultural machine performs a first agricultural operation, the first agricultural operation prior to a second agricultural operation performed by the agricultural machine.

20. The agricultural machine of claim 19, wherein the agricultural characteristic value corresponding to each subregion is derived from a map that includes the agricultural characteristic value corresponding to each subregion georeferenced to the corresponding subregion and wherein the agricultural characteristic-estimated constituent value corresponding to each subregion in the set of subregions of the agricultural worksite is based further on an agricultural characteristic value-to-constituent value correlation between agricultural characteristic values and constituent values.
