

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280428

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Sambhwani; Sharad et al.

COOPERATIVE COMMUNICATION FOR USER EQUIPMENT GROUPS

Abstract

User equipment in close proximity may transfer data and control information. For example, the user equipment may exchange data or data sets between each other. Each user equipment can receive and transmit data using radio access technologies. A group of user equipments may include active user equipment and passive user equipment. Active user equipment connects with one or more base stations and transfers data on a wireless communication network via the base station. The active user equipment may communicate with other active user equipment and passive user equipment. Passive user equipment may not connect to any base station and/or the wireless communication network and may communicate with other passive user equipment and active user equipment (e.g., via a sidelink, peer-to-peer, or device-to-device channel).

Inventors: Sambhwani; Sharad (San Diego, CA), Nickisch; Dirk (Oberpfammern, DE), Shanbhag; Madhukar K (Santa Clara, CA), Nabar; Rohit U. (Sunnyvale, CA), Balasubramanian; Sanjeevi (San Jose, CA), Narra; Shiva Krishna (San Jose, CA), Subramanian; Sriram (Santa Clara, CA), Tabet; Tarik (San Diego, CA), Kamala Govindaraju; Vishwanth (Mountain View, CA), Sun; Yakun (San Jose, CA), Subrahmanya; Parvathanathan (Sunnyvale, CA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 86228815

Appl. No.: 19/210609

Filed: May 16, 2025

Related U.S. Application Data

parent US continuation 17880613 20220803 parent-grant-document US 12317294 child US 19210609

us-provisional-application US 63278438 20211111

Publication Classification

Int. Cl.: **H04W72/30** (20230101); **H04L5/00** (20060101); **H04W4/08** (20090101); **H04W48/12** (20090101); **H04W48/16** (20090101); **H04W56/00** (20090101); **H04W68/00** (20090101); **H04W76/10** (20180101); **H04W76/14** (20180101); **H04W76/15** (20180101); **H04W76/19** (20180101); **H04W76/30** (20180101); **H04W76/40** (20180101); **H04W80/04** (20090101)

U.S. Cl.:

CPC **H04W72/30** (20230101); **H04L5/0048** (20130101); **H04L5/0051** (20130101); **H04W4/08** (20130101); **H04W48/12** (20130101); **H04W48/16** (20130101); **H04W56/001** (20130101); **H04W68/005** (20130101); **H04W76/10** (20180201); **H04W76/14** (20180201); **H04W76/15** (20180201); **H04W76/19** (20180201); **H04W76/30** (20180201); **H04W76/40** (20180201); **H04W80/04** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. application Ser. No. 17/880,613, filed Aug. 3, 2022, entitled “COOPERATIVE COMMUNICATION FOR USER EQUIPMENT GROUPS,” which claims priority to U.S. Provisional Application No. 63/278,438, filed Nov. 11, 2021, entitled “COOPERATIVE COORDINATION SCHEMES FOR MULTI-NODE DEVICES,” each of which is hereby incorporated by reference in its entirety for all purposes.

BACKGROUND

[0002] The present disclosure relates generally to wireless communication, and more specifically to cooperative communication for user equipment in a group of user equipment.

[0003] User equipment density has increased rapidly over the years. User equipment may also support several radio access technologies (RATs) simultaneously in close proximity to one another. Moreover, with the use of high spectrum frequencies (e.g., the millimeter wave (mmW) frequency range, the terahertz (THz) frequency range), the coverage range of wireless communication networks may be limited in terms of signal loss. Additionally, communication between each user equipment and a wireless communication network may be performed through point-to-point connections without cooperation of nearby user equipment.

SUMMARY

[0004] A summary of certain embodiments disclosed herein is set forth below. It should be understood that these aspects are presented merely to provide the reader with a brief summary of these certain embodiments and that these aspects are not intended to limit the scope of this disclosure. Indeed, this disclosure may encompass a variety of aspects that may not be set forth below.

[0005] In one embodiment, a method includes receiving, at a first user equipment of a group of user equipments, a request for data from a target user equipment, wherein the group of user equipments comprises the target user equipment. The method also includes receiving, at the first user equipment, a first set of the data from a first base station, the first base station configured to receive the first set from a server. The method also includes receiving, at the first user equipment, a second set of the data from a second base station, the first base station configured to receive the second set from the server and assembling, at the first user equipment, the data based at least in part on the first set and the second set. The method also includes transmitting, from the first user

equipment, the first set, the second set, the data, or any combination thereof to the target user equipment, the target user equipment being disconnected from the first base station, the second base station, or both.

[0006] In another embodiment, a method includes receiving, at a base station, a request for data and receiving, at the base station, the data from a server. The method also includes transmitting a first set of the data to a first user equipment communicatively coupled to the base station, a group of user equipments comprising the first user equipment and transmitting a second set of the data to a second user equipment communicatively coupled to the base station, the group of user equipments comprising the second user equipment. The method also includes causing the first user equipment to send, via a device-to-device communication link, the first set of the data to a target user equipment that is disconnected from the base station, the group of user equipments comprising the target user equipment and causing the second user equipment to send, via a device-to-device communication link, the second set of the data to the target user equipment.

[0007] In yet another embodiment, a method includes receiving, at a first user equipment communicatively coupled to a base station, a first data and receiving, at the first user equipment, a first set of the data and a second set of the data. The method also includes transmitting the first set, the second set, the first data, or any combination thereof to the base station and transmitting, via device-to device communication to a second user equipment communicatively coupled to the base station, the first set, the second set, the first data, or any combination thereof. The method also includes causing the second user equipment to send the first set, the second set, the first data, or any combination thereof to the base station.

[0008] Various refinements of the features noted above may exist in relation to various aspects of the present disclosure. Further features may also be incorporated in these various aspects as well. These refinements and additional features may exist individually or in any combination. For instance, various features discussed below in relation to one or more of the illustrated embodiments may be incorporated into any of the above-described aspects of the present disclosure alone or in any combination. The brief summary presented above is intended only to familiarize the reader with certain aspects and contexts of embodiments of the present disclosure without limitation to the claimed subject matter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] Various aspects of this disclosure may be better understood upon reading the following detailed description and upon reference to the drawings described below in which like numerals refer to like parts.

[0010] FIG. 1 is a block diagram of user equipment, according to embodiments of the present disclosure;

[0011] FIG. 2 is a functional diagram of the user equipment of FIG. 1, according to embodiments of the present disclosure;

[0012] FIG. 3 is a schematic diagram of a communication system including the user equipment of FIG. 1 communicatively coupled to a wireless communication network supported by base stations, according to embodiments of the present disclosure;

[0013] FIG. 4 is a schematic diagram of another embodiment of a communication system including a group of user equipment communicatively coupled to the wireless communication network of FIG. 3, according to embodiments of the present disclosure;

[0014] FIG. 5 is a flowchart of a method to download data to active user equipment of the group of user equipment of FIG. 4 using the wireless communication network, according to embodiments of the present disclosure;

[0015] FIG. 6 is a flowchart of a method to download data to active user equipment and passive user equipment of the group of user equipment of FIG. 4 using the wireless communication network, according to embodiments of the present disclosure;

[0016] FIG. 7 is a flowchart of a method to upload data to base stations of the wireless communication network of FIG. 3 using active user equipment of the group of user equipment, according to embodiments of the present disclosure;

[0017] FIG. 8 is a flowchart of a method to upload data to base stations of the wireless communication network of FIG. 3 using active user equipment and passive user equipment of the group of user equipment, according to embodiments of the present disclosure;

[0018] FIG. 9 is a flowchart of a method to download data to active user equipment of the group of user equipment of FIG. 4 using multiple base stations, according to embodiments of the present disclosure;

[0019] FIG. 10 is a flowchart of a method to download data to active user equipment and passive user equipment of the group of user equipment of FIG. 4 using multiple base stations, according to embodiments of the present disclosure;

[0020] FIG. 11 is a block diagram of Open Systems interconnection (OSI) model layers of the user equipment of FIG. 1, according to embodiments of the present disclosure;

[0021] FIG. 12 is a flowchart of a method to download data at an internet protocol layer of the user equipment of FIG. 1, according to embodiments of the present disclosure;

[0022] FIG. 13 is a block diagram of network protocol layers of a server of the wireless communication network of FIG. 3, according to embodiments of the present disclosure;

[0023] FIG. 14 is a flowchart of a method to download data using Internet Protocol (IP) addresses of active user equipment of the group of user equipment of FIG. 4, according to embodiments of the present disclosure;

[0024] FIG. 15 is a flowchart of a method to download data using a first base station communicatively coupled to a server and a second base station disconnected from the server of the wireless communication network of FIG. 3, according to embodiments of the present disclosure;

[0025] FIG. 16 is a flowchart of a method to download control messages to active user equipment and passive user equipment of the group of user equipment of FIG. 4, according to embodiments of the present disclosure;

[0026] FIG. 17 is a flowchart of a method to establish connection with the group of user equipment of FIG. 4, according to embodiments of the present disclosure;

[0027] FIG. 18 is a flowchart of a method to download paging messages for the group of user equipment of FIG. 4, according to embodiments of the present disclosure; and

[0028] FIG. 19 is a flowchart of a method to download radio bearers to the group of user equipment of FIG. 4 using the wireless communication network of FIG. 3, according to embodiments of the present disclosure.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

[0029] One or more specific embodiments will be described below. In an effort to provide a concise description of these embodiments, not all features of an actual implementation are described in the specification. It should be appreciated that in the development of any such actual implementation, as in any engineering or design project, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which may vary from one implementation to another. Moreover, it should be appreciated that such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure.

[0030] When introducing elements of various embodiments of the present disclosure, the articles “a,” “an,” and “the” are intended to mean that there are one or more of the elements. The terms “comprising,” “including,” and “having” are intended to be inclusive and mean that there may be

additional elements other than the listed elements. Additionally, it should be understood that references to “one embodiment” or “an embodiment” of the present disclosure are not intended to be interpreted as excluding the existence of additional embodiments that also incorporate the recited features. Furthermore, the particular features, structures, or characteristics may be combined in any suitable manner in one or more embodiments. Use of the terms “approximately,” “near,” “about,” “close to,” and/or “substantially” should be understood to mean including close to a target (e.g., design, value, amount), such as within a margin of any suitable or contemplable error (e.g., within 0.1% of a target, within 1% of a target, within 5% of a target, within 10% of a target, within 25% of a target, and so on). Moreover, it should be understood that any exact values, numbers, measurements, and so on, provided herein, are contemplated to include approximations (e.g., within a margin of suitable or contemplable error) of the exact values, numbers, measurements, and so on. Additionally, the term “set” may include one or more. That is, a set may include a unitary set of one member, but the set may also include a set of multiple members. Furthermore, as used herein, a set may include a portion (e.g., a subset, all) of data and/or information. While the data is described herein as including two data sets or three data sets, this is intended to be illustrative of certain embodiments. As such, the data may include any suitable number of data sets (e.g., two data sets, three data sets, four data sets, eight data sets, and so forth). Additionally, as used herein, a first set of user equipment may include the same user equipment as another set of user equipment, different user equipment than another set of user equipment, additional user equipment than another set of user equipment, fewer user equipment than another set of user equipment, and so forth.

[0031] The present disclosure relates generally to wireless communication, and more specifically to cooperative communication for user equipment in a group of user equipment. Wireless device density has increased rapidly over the years. Wireless communication between user equipment (UE) and wireless communication networks may occur directly through a point-to-point connection without regards to nearby user equipment. Wireless UE may also support several radio access technologies (RATs) simultaneously in close proximity to one another. Moreover, with the use of high spectrum frequencies (mmW, THz), the range of communication may be limited due to signal dissipation. Employing local communications (e.g., device-to-device communications, sidelink, peer-to-peer) may facilitate and improve the range, coverage, reliability and efficiency of communications between user equipment and wireless communication networks. This disclosure relates to systems, apparatuses, and techniques to enable user equipment to cooperate with adjacent user equipment to improve coverage and capacity.

[0032] User equipment may establish groups to facilitate and coordinate communication with wireless communication networks. Cooperative communication between user equipment may be beneficial for offloading data and controlling transmissions to one or more designated user equipment within a group of user equipment. Data sharing (e.g., via a device-to-device communication link) may also reduce power consumption for user equipment in the group when compared to directly (e.g., without an intervening or intermediate device) communicating with a network. Embodiments herein provide various systems, apparatuses, and techniques to provide cooperative communication for a group of user equipment. In particular, a communication network (e.g., a 5.sup.th generation (5G)/New Radio (NR) network, a 4.sup.th generation (4G)/long term evolution (LTE®) network, a 6.sup.th generation (6G) or greater than 6G network, and so on), via a base station, may communicate with the group of user equipment via one or more active user equipment (e.g., user equipment connected to or directly connected to the communication network). The active user equipment may communicate with passive user equipment (e.g., user equipment disconnected from the communication network). In particular, the user equipment in the group may communicate using a personal area network (PAN), a local area network (LAN) or wireless local area network (WLAN), and/or a wide area network (WAN).

[0033] User equipment in close proximity with one another may transfer data and control

information. For example, the user equipment may exchange data or data sets between each other. Each user equipment can receive and transmit data using RATs. The user equipment may transmit and receive data from a wireless communication network via any number of base stations. A group of user equipment may include active user equipment and passive user equipment. An active user equipment connects with one or more base stations and transfers data on a wireless communication network via the base station. That is, the active user equipment may be directly connected with one or more base stations. Additionally, the active user equipment may communicate with other active user equipment and passive user equipment. Passive user equipment may not connect to any base station and/or the wireless communication network and may communicate with other passive user equipment and active user equipment (e.g., via a sidelink, peer-to-peer, or device-to-device channel). That is, the passive user equipment may communicate indirectly with the base station and/or the wireless communication network via an active user device.

[0034] One or more of the active user equipment may be designated as a primary user equipment. The primary user equipment may control the group membership, define configuration for a device-to-device communication link, and may add or release user equipment from the group. In particular, primary user equipment may control roles for other user equipment in a local network. For example, a first user equipment, such as a portable electronic device may control and communicate with secondary user equipment, such as a television, a tablet, a computer, and so forth. In some instances, one or more active user equipment and one or more passive user equipment may act as relay user equipment. A relay user equipment may act as an intermediary device and may transfer data from one user equipment to another user equipment in the group. Additionally, the relay user equipment may facilitate communication with the wireless communication network by transferring (e.g., tunneling) data from the base station to other user equipment in the group.

[0035] The base stations of the wireless communication network may facilitate communication and provide access for active user equipment to receive and transfer data to and from an application server and/or a communication network. In certain instances, the base stations may be operated and/or controlled by separate carriers or operators. Additionally, the base stations may operate using the same or different communication technologies, such as one or more RATs and/or local networks.

[0036] One or more active user equipment may receive data or a data set. The active user equipment may transmit the data or the sets of data to other active user equipment and passive user equipment in the group. That is, the active user equipment may receive the data and/or the data sets and may cooperate and coordinate to facilitate communication of the data from a base station to other user equipment. In certain instances, each active user equipment may connect to one or more base stations. Moreover, the active user equipment may receive the same and/or different data or data sets from different base stations. Additionally, the different base stations may communicate with the active user equipment using the same or different communication technologies. The passive user equipment may receive the data or the data sets from other passive user equipment and/or the active user equipment. As such, a set of the user equipment (e.g., any number of active user equipment, any number of passive user equipment, or any combination thereof) may receive the data sets either directly (e.g., from the base station) and/or indirectly (e.g., from one or more active user equipment, from one or more passive user equipment, or any combination thereof) from the wireless communication network. The user equipment in the group may assemble the data based on the data sets.

[0037] In certain instances, the application server may split data into one or more data sets and may transfer the one or more sets to one or more base stations. The active user equipment may receive the sets from the base stations. For example, a first active user equipment may receive a first set from the first access point and a second active user equipment may receive a second set from the second base station. The active user equipment may exchange the data sets between each other and

each active user equipment may reassemble the sets to form the data. Additionally or alternatively, the base stations may split data into data sets and/or may split data sets into data subsets.

[0038] In some instances, a first set of the active user equipment may utilize a second set of the active user equipment to receive and transfer one or more data sets. In particular, the active user equipment may cooperate and coordinate to transmit the same data and/or the same data sets. Additionally or alternatively, the first set of the active user equipment may not transmit its received data set. The first set of the active user equipment may receive one or more data sets from the second set of the active user equipment. Accordingly, only the first set of the active user equipment may receive all data sets and may reassemble the data. Additionally, the active user equipment may transmit one or more data sets to one or more passive user equipment. Alternatively, the active user equipment may transmit the data to one or more passive user equipment. In some instances, a first passive user equipment may transmit one or more data sets or the data to a second passive user equipment. Additionally, the active user equipment may cooperate to transmit the same data set to one or more base stations simultaneously, concurrently, consecutively, overlapping, separately, and so forth. Moreover, a passive user equipment may transmit the same data set to several active user equipment for transmission to the base stations. In certain instances, the passive user equipment may transmit the same data set sequentially or broadcast concurrently to several active user equipment.

[0039] In order to transfer data and/or data sets consistently and efficiently, the base stations and/or the active user equipment may split the data into data sets and may transfer the data sets to user equipment within the group. The user equipment may then transfer the data and/or the data sets to other user equipment in the group using local networks and local connections. Once received, the user equipment may assemble the data sets. Data transfer, data splitting, and/or data assembly may be implemented in different layers of various communication protocols. In some instances, the data may be split in the Packet Data Convergence Protocol (PDCP) dataplane layer. The PDCP layer of the base station splits the data into any number of data sets and transfers the data sets to two or more active user equipment. In certain instances, the base station may transfer multiple data sets to an active user equipment and/or the same data sets to multiple active user equipment. The active user equipment may receive the data, shares the data, and assembles the data on the PDCP level. For upload, active user equipment may apply a PDCP duplication procedure and share a redundant copy of the data with one or more other active user equipment. Accordingly, the active user equipment may then transmit the same set of PDCP data to the base station. The base station may then receive the data and provide it to the application server. In another instance, the data may be split in the physical layer. In yet another instance, the data may be split in a new sub-layer of the Internet Protocol (IP) Network layer. The new sub-layer may be defined as a Data Split and Scheduling Layer. The new sub-layer may split the data stream into one or more data sets and map the data sets to IP addresses of one or more active user equipment.

[0040] Additionally, the data may be steered to particular or target active user equipment. For example, the application server may determine a first data set to transmit to a first active user equipment, a second data set to transmit to a second active user equipment, and so forth. Additionally or alternatively, a first base station may determine a third data set to transmit to a second base station based on a connection status between the second base station and the application server.

[0041] In certain embodiments, the application server and/or the base stations may generate and/or provide routing information associated with the data. The routing information may include a path (e.g., sequence of user equipment that receive the data, ordering of user equipment that receive the data, and so forth). For example, the base station may generate and/or receive the routing information based on information associated with the group of user equipment. The information may include a list of device-to-device communication links (e.g., current communication links, historical communication links, available communication links, and so forth) between the user

equipment. The base station may generate and/or receive a path for transmission of the data to the target user equipment. The base station may first transmit the routing information to one or more active user equipment communicatively coupled to the base station. The routing information may specify one or more active user equipment to receive the data and/or the routing information from the base station. In certain embodiments, the routing information may specify one or more passive user equipment to receive the data and/or the routing information from the one or more active user equipment. Additionally or alternatively, the routing information may specify one or more active user equipment and/or one or more passive user equipment to transmit the data and/or the routing information to the target user equipment. As such, the routing information may specify a path or routing for the data and/or the routing information to take from the application server to the base stations to the user equipment (e.g., active user equipment, passive user equipment, target user equipment).

[0042] In some embodiments, the routing information may specify a first set of active user equipment to transmit the data and/or the routing information to from a first base station. Additionally or alternatively, the routing information may specify a second set of active user equipment to transmit the data and/or the routing information to from a second base station. As such, the routing information may include a path or routing for the data and/or the routing information from the application server to one or more active user equipment within the group of user equipment via the base stations. In certain embodiments, the routing information may specify a first set of passive user equipment to transmit the data and/or the routing information to from the first set of active user equipment. Additionally or alternatively, the routing information may specify a second set of passive user equipment to transmit the data and/or the routing information to from the second set of active user equipment. The routing information may also specify active user equipment transmit the data and/or the routing information to other active user equipment. The routing information may also specify passive user equipment transmit the data and/or the routing information to other passive user equipment. The routing information may also specify the target user equipment to receive the data and/or the routing information. While the above describes paths or routing for data from an application server to target user equipment, routing information may also be used to specify a path or routing for data from any user equipment to the application server via active user equipment, passive user equipment, base stations, and so forth. Additionally or alternatively, the routing information may be transmitted (e.g., by the base stations, by the user equipment) concurrently with the data, subsequently to transmission of the data, prior to transmission of the data, or any other suitable timing.

[0043] Active user equipment may be controlled using control channels based on the direct connection to the base station. Passive user equipment may have an indirect connection and may be accessible via an updated control channel path. Control channels provide configuration data to user equipment for paging the user equipment and scheduling data reception and transmission. Active user equipment may identify that a paging message, a configuration message, and/or control data is intended for passive user equipment. The active user equipment may perform the identification based on an identifier associated with a protocol layer format. For example, a MAC Control Element (MAC CE) may be utilized as an identifier. In some instances, the MAC CE may be applicable for all user equipment within a group of user equipment and may be received by a first active user equipment and transmitted to any number of other active user equipment and passive user equipment. In another instance, the MAC CE may be applicable to a single user equipment, including passive user equipment.

[0044] A Radio Resource Control (RRC) message may provide configuration data to user equipment. The base station may transmit the RRC message to an active user equipment that in turn transmits the message to a passive user equipment. Responses may be transmitted to the base station via the active user equipment (e.g., in some cases, from passive user equipment). Downlink Control Information (DCI) and Uplink Control Information (UCI) may be utilized to control the

physical layer operation.

[0045] Moreover, the user equipment may utilize various criteria for entering and/or leaving a group of user equipment. The criteria may include a network signal quality of the user equipment, a power connection, a battery level of the user equipment, a time window, a geographic area of the user equipment, user equipment capabilities (e.g., communication capabilities, computing and/or processing capabilities, sensing capabilities, and so forth), a device-to-device connection, a trust level between user equipment, and so forth. The network signal quality of the user equipment may be compared to a threshold. When below the threshold, there may be a risk that service is interrupted. If another user equipment or a group of user equipment are in close proximity, the user equipment may attempt to form a group or enter the previously formed group. If a user equipment is connected to an electrical grid (e.g., such that it is not powered via its battery), it may no longer require the benefits of shared resources within a group and may leave the group. Alternatively, when connected to electrical grid, the user equipment may receive additional tasks within the group.

[0046] User equipment may be permitted to search for and join a group of user equipment during a particular time window. Additionally, the user equipment may search for and enter a group of user equipment when within a particular geographic area or in proximity or range of a set of user equipment, such as a home or an office. Alternatively, the user equipment may leave a group when leaving the particular geographic area or the proximity or range of the set of user equipment. User equipment that lacks radio technology or does not support particular frequencies may search for and enter a group of user equipment with different and/or greater user equipment capabilities. Additionally, the user equipment may determine whether the user equipment capabilities permit the user equipment to communicate with other user equipment in the group. The user equipment may determine whether a stable device-to-device connection is available with one or more user equipment in the group based on the Received Signal Strength Indicator (RSSI) and signal to noise ratio (SNR), or other signal characteristics. User equipment trust may be established based on previously entering the group of user equipment.

[0047] Entering a group of user equipment may begin with group discovery. One or more user equipment within the group may transmit reference signals on a local communications frequency. The reference signals may include specialized wake-up signals that reduce power consumption. User equipment outside the group may periodically search for and attempt to detect the reference signals. The user equipment may measure the reference signals and join the group. The next step of entering the group includes establishing device-to-device connections. The device-to-device connection may be direct or through a local network connection. The user equipment may also exchange user equipment capabilities. The user equipment capabilities may be utilized to determine preferred communication frequencies, the types of communication technologies of the group and the new user equipment, a current battery status of the user equipment, a current thermal status of the user equipment, and so forth. Each user equipment may periodically send a keep alive message to at least one primary user equipment in the group.

[0048] To maintain the group, the number of active user equipment and/or the number of passive user equipment may be controlled (e.g., by the primary user equipment). For example, if an active user equipment leaves coverage of a base station, the active user equipment may be reassigned as a passive user equipment. A primary user equipment may fall below a battery threshold and a new primary user equipment may be assigned. The primary user equipment may receive regular updates from other user equipment in the group regarding battery status, thermal status, and link status of the user equipment. Additionally, the primary user equipment may maintain a list of candidates from the active user equipment to be assigned as a new primary user equipment. The primary user equipment may send a request to one of the candidates to become a new primary user equipment.

[0049] FIG. 1 is a block diagram of user equipment **10** (e.g., a mobile electronic device), according to embodiments of the present disclosure. The user equipment **10** may include, among other things,

one or more processors **12** (collectively referred to herein as a single processor for convenience, which may be implemented in any suitable form of processing circuitry), memory **14**, nonvolatile storage **16**, a display **18**, input structures **22**, an input/output (I/O) interface **24**, a network interface **26**, and a power source **29**. The various functional blocks shown in FIG. **1** may include hardware elements (including circuitry), software elements (including machine-executable instructions) or a combination of both hardware and software elements (which may be referred to as logic). The processor **12**, memory **14**, the nonvolatile storage **16**, the display **18**, the input structures **22**, the input/output (I/O) interface **24**, the network interface **26**, and/or the power source **29** may each be communicatively coupled directly or indirectly (e.g., through or via another component, a communication bus, a network) to one another to transmit and/or receive data between one another. It should be noted that FIG. **1** is merely one example of a particular implementation and is intended to illustrate the types of components that may be present in the user equipment **10**.

[0050] By way of example, the user equipment **10** may include any suitable computing device, including a desktop or notebook computer (e.g., in the form of a MacBook®, MacBook® Pro, MacBook Air®, iMac®, Mac® mini, or Mac Pro® available from Apple Inc. of Cupertino, California), a portable electronic or handheld electronic device such as a wireless electronic device or smartphone (e.g., in the form of a model of an iPhone® available from Apple Inc. of Cupertino, California), a tablet (e.g., in the form of a model of an iPad® available from Apple Inc. of Cupertino, California), a wearable electronic device (e.g., in the form of an Apple Watch® by Apple Inc. of Cupertino, California), and other similar devices. It should be noted that the processor **12** and other related items in FIG. **1** may be embodied wholly or in part as software, hardware, or both. Furthermore, the processor **12** and other related items in FIG. **1** may be a single contained processing module or may be incorporated wholly or partially within any of the other elements within the user equipment **10**. The processor **12** may be implemented with any combination of general-purpose microprocessors, microcontrollers, digital signal processors (DSPs), field programmable gate array (FPGAs), programmable logic devices (PLDs), controllers, state machines, gated logic, discrete hardware components, dedicated hardware finite state machines, or any other suitable entities that may perform calculations or other manipulations of information. The processors **12** may include one or more application processors, one or more baseband processors, or both, and perform the various functions described herein.

[0051] In the user equipment **10** of FIG. **1**, the processor **12** may be operably coupled with a memory **14** and a nonvolatile storage **16** to perform various algorithms. Such programs or instructions executed by the processor **12** may be stored in any suitable article of manufacture that includes one or more tangible, computer-readable media. The tangible, computer-readable media may include the memory **14** and/or the nonvolatile storage **16**, individually or collectively, to store the instructions or routines. The memory **14** and the nonvolatile storage **16** may include any suitable articles of manufacture for storing data and executable instructions, such as random-access memory, read-only memory, rewritable flash memory, hard drives, and optical discs. In addition, programs (e.g., an operating system) encoded on such a computer program product may also include instructions that may be executed by the processor **12** to enable the user equipment **10** to provide various functionalities.

[0052] In certain embodiments, the display **18** may facilitate users to view images generated on the user equipment **10**. In some embodiments, the display **18** may include a touch screen, which may facilitate user interaction with a user interface of the user equipment **10**. Furthermore, it should be appreciated that, in some embodiments, the display **18** may include one or more liquid crystal displays (LCDs), light-emitting diode (LED) displays, organic light-emitting diode (OLED) displays, active-matrix organic light-emitting diode (AMOLED) displays, or some combination of these and/or other display technologies.

[0053] The input structures **22** of the user equipment **10** may enable a user to interact with the user equipment **10** (e.g., pressing a button to increase or decrease a volume level). The I/O interface **24**

may enable user equipment **10** to interface with various other electronic devices, as may the network interface **26**. In some embodiments, the I/O interface **24** may include an I/O port for a hardwired connection for charging and/or content manipulation using a standard connector and protocol, such as the Lightning connector provided by Apple Inc. of Cupertino, California, a universal serial bus (USB), or other similar connector and protocol. The network interface **26** may include, for example, one or more interfaces for a personal area network (PAN), such as an ultra-wideband (UWB) or a BLUETOOTH® network, a local area network (LAN) or wireless local area network (WLAN), such as a network employing one of the IEEE 802.11x family of protocols (e.g., WI-FI®), and/or a wide area network (WAN), such as any standards related to the Third Generation Partnership Project (3GPP), including, for example, a 3.sup.rd generation (3G) cellular network, universal mobile telecommunication system (UMTS), 4.sup.th generation (4G) cellular network, long term evolution (LTE®) cellular network, long term evolution license assisted access (LTE-LAA) cellular network, 5.sup.th generation (5G) cellular network, and/or New Radio (NR) cellular network, a 6.sup.th generation (6G) or greater than 6G cellular network, a satellite network, a non-terrestrial network, and so on. In particular, the network interface **26** may include, for example, one or more interfaces for using a Release-15 cellular communication standard of the 5G specifications that include the millimeter wave (mmWave) frequency range (e.g., 24.25-300 gigahertz (GHz)) and/or any other cellular communication standard release (e.g., Release-16, Release-17, any future releases) that define and/or enable frequency ranges used for wireless communication. The network interface **26** of the user equipment **10** may allow communication over the aforementioned networks (e.g., 5G, Wi-Fi, LTE-LAA, and so forth).

[0054] The network interface **26** may also include one or more interfaces for, for example, broadband fixed wireless access networks (e.g., WIMAX®), mobile broadband Wireless networks (mobile WIMAX®), asynchronous digital subscriber lines (e.g., ADSL, VDSL), digital video broadcasting-terrestrial (DVB-T®) network and its extension DVB Handheld (DVB-H®) network, ultra-wideband (UWB) network, alternating current (AC) power lines, and so forth.

[0055] FIG. **2** is a functional diagram of the user equipment **10** of FIG. **1**, according to embodiments of the present disclosure. As illustrated, the processor **12**, the memory **14**, the transceiver **30**, a transmitter **52**, a receiver **54**, and/or antennas **55** (illustrated as **55A-55N**, collectively referred to as an antenna **55**) may be communicatively coupled directly or indirectly (e.g., through or via another component, a communication bus, a network) to one another to transmit and/or receive data between one another.

[0056] The user equipment **10** may include the transmitter **52** and/or the receiver **54** that respectively enable transmission and reception of data between the user equipment **10** and an external device via, for example, a network (e.g., including base stations or access points) or a direct connection. As illustrated, the transmitter **52** and the receiver **54** may be combined into the transceiver **30**. The user equipment **10** may also have one or more antennas **55A-55N** electrically coupled to the transceiver **30**. The antennas **55A-55N** may be configured in an omnidirectional or directional configuration, in a single-beam, dual-beam, or multi-beam arrangement, and so on. Each antenna **55** may be associated with a one or more beams and various configurations. In some embodiments, multiple antennas of the antennas **55A-55N** of an antenna group or module may be communicatively coupled a respective transceiver **30** and each emit radio frequency signals that may constructively and/or destructively combine to form a beam. The user equipment **10** may include multiple transmitters, multiple receivers, multiple transceivers, and/or multiple antennas as suitable for various communication standards. In some embodiments, the transmitter **52** and the receiver **54** may transmit and receive information via other wired or wireline systems or means.

[0057] Moreover, the various components of the user equipment **10** may be coupled together by a bus system **56**. The bus system **56** may include a data bus, for example, as well as a power bus, a control signal bus, and a status signal bus, in addition to the data bus. The components of the user equipment **10** may be coupled together or accept or provide inputs to each other using some other

mechanism.

[0058] FIG. 3 is a schematic diagram of a communication system **100** including the user equipment **10** of FIG. 1 communicatively coupled to a wireless communication network **102** supported by base stations **104A**, **104B** (collectively **104**), according to embodiments of the present disclosure. In particular, the base stations **104** may include Next Generation NodeB (gNodeB or gNB) base stations and may provide 5G/NR coverage via the wireless communication network **102** to the user equipment **10**. The base stations **104** may include any suitable electronic device, such as a communication hub or node, that facilitates, supports, and/or implements the network **102**. In some embodiments, the base stations **104** may include Evolved NodeB (eNodeB) base stations and may provide 4G/LTE coverage via the wireless communication network **102** to the user equipment **10**. Each of the base stations **104** may include at least some of the components of the user equipment **10** shown in FIGS. 1 and 2, including one or more processors **12**, the memory **14**, the storage **16**, the transceiver **30**, the transmitter **52**, and the receiver **54**. It should be understood that while the present disclosure may use 5G/NR as an example specification or standard, the embodiments disclosed herein may apply to other suitable specifications or standards (e.g., such as the 4G/LTE specification). Moreover, the network **102** may include any suitable number of base stations **104** (e.g., one or more base stations **104**, four or more base stations **104**, ten or more base stations **104**, and so on). Additionally or alternatively, the base stations **104** may include any number of user equipment **10** that communicatively couple to the wireless communication network.

[0059] FIG. 4 is a schematic diagram of a communication system **200** including the base stations **104** (e.g., base stations **104A**, **104B**, **104C**), an application server **202**, and a group of user equipment **206**. The application server **202** may include any suitable electronic device (e.g., a desktop personal computer, a laptop, a mobile electronic device, a tablet, a smartphone, a wearable device, or any other suitable computing device) and may include at least some of the components of the user equipment **10** shown in FIGS. 1 and 2, including one or more processors **12**, the memory **14**, the storage **16**, the transceiver **30**, the transmitter **52**, and the receiver **54**. The communication system **200** may include any suitable number of application servers **202** (e.g., one or more application servers **202**, four or more application servers **202**, and so on). The base stations **104** may provide access for the group of user equipment **206** to transfer data and/or control information to and from the application server **202**. In certain embodiments, a first base station **104A** may be associated with a different carrier or operator from a second base station **104B**. Additionally or alternatively, one or more of the base stations **104** may operate using the same carrier. The group of user equipment **206** may cooperate for transferring data and/or control information. The group of user equipment **206** may include any number of active user equipment **208A**, **208B**, **208C** (referred to collectively as active user equipment **208**) and/or any number of passive user equipment **210A**, **210B** (referred to collectively as passive user equipment **210**). Each user equipment (e.g., active user equipment **208**, passive user equipment **210**) may include any suitable electronic device and may be an example of the user equipment **10** shown in FIGS. 1 and 2. As such, each of the user equipment may include at least some of the components of the user equipment **10**, such as one or more processors **12**, the memory **14**, the storage **16**, the transceiver **30**, the transmitter **52**, and the receiver **54**. Additionally, the group of user equipment **206** may include any suitable number of user equipment (e.g., any suitable number of active user equipment **208**, any suitable number of passive user equipment **210**).

[0060] Each of the active user equipment **208** may be communicatively coupled to the wireless communication network **102** (e.g., via at least one of the base stations **104**). Additionally or alternatively, the active user equipment **208** may be communicatively coupled to other active user equipment **208** and/or at least one passive user equipment **210**. For example, the active user equipment **208** may be communicatively coupled via any suitable communication technique, such as a device-to-device communication link, sidelink communication, peer-to-peer communication, and so forth. In certain embodiments, the active user equipment **208A** may serve as a relay for at

least one active user equipment **208** and/or at least one passive user equipment **210**. For example, the active user equipment **208A** may transfer data and/or control information received from one user equipment (e.g., active user equipment **208B**, passive user equipment **210A**) in the group **206** to another user equipment (e.g., active user equipment **208C**, passive user equipment **210B**) in the group **206**.

[0061] In certain embodiments, any suitable number of active UE **208** may be communicatively coupled with any number of base stations **104**. A target UE (e.g., first active UE **208A**, first passive UE **210B**) may request data from the wireless communication network **102**. The group of UE **206** may coordinate and cooperate to transmit the request to the wireless communication network **102**. Each active UE **208** may receive the data **204** and/or one or more sets **204A**, **204B** (e.g., a portion, a subset) of the data from the wireless communication network **102** via base stations **104**. The active UEs **208** may transfer the sets of data to other active UEs **208** within the group of user equipment **206**. The active UEs **208** may assemble the data based at least in part on the received sets of the data. The group of user equipment **206** may coordinate and cooperate to provide the data to the target UE. Accordingly, the target UE may receive the data and/or the data sets and may assemble the data based on the data sets.

[0062] With the foregoing in mind, FIG. 5 is a flowchart of a method **300** to download data to active user equipment **208** of the group of user equipment **206** of FIG. 4 using the wireless communication network **102**, according to embodiments of the present disclosure. Any suitable device (e.g., a controller) that may control components of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, such as one or more respective processors **12** of these devices, may perform the method **300**. In some embodiments, the method **300** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the one or more respective memories **14** or storages **16** of these devices, using the processors **12**. For example, the method **300** may be performed at least in part by one or more software components, such as one or more respective operating systems of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, one or more software applications of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210** and the like. While the method **300** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0063] In process block **302**, the network **102** and/or the application server **202** broadcasts or transmits data to the base stations **104**. The data may be transmitted to the network **102** via a source user equipment and intended (e.g., addressed) for a destination user equipment (which may include an active UE **208** or a passive UE **210**). The base stations **104** may receive the data and may generate (block **304**) any number of data sets. For example, the base station **104** may receive information associated with a number of active UEs **208** in the group of user equipment **206**, a number of passive UEs **210** in the group of user equipment **206**, and/or a number of UEs **10** (e.g., sum of number of active UEs and passive UEs) in the group of user equipment **206**. The base station **104** may generate a number of data sets based at least in part on the number of active UEs **208**, the number of passive UEs **210**, and/or the number of UEs **10** in the group of user equipment **206**. For example, the base station **104** may receive (e.g., generate) a number of data sets equal to a number of active UEs **208**. As such, each active UE **208** may receive at least one data set from the wireless communication network **102**. Alternatively, the base station may receive a number of data sets less than or greater than the number of active UEs **208**. The base station **104** may transmit (block **306**) the data sets to a set of active UEs **208** (e.g., all active UEs **208**, active UEs **208** communicatively coupled to a particular base station **104**, and so forth). The first active UE **208A**

may receive (block **308**) a first data set of the data and a second active UE **208B** may receive (block **310**) a second data set of the data.

[0064] After receiving the second data set, the second active UE **208B** may determine (block **312**) whether the data has been received. For example, the second data set may include an indicator of a number of data sets that in the data. As such, the second active UE **208B** may compare the indicator with a number of received data sets. If the data has not been received (NO path of block **312**), the second active UE **208B** may transmit (block **314**) a request for data sets to any number of active UEs **208** in the group of user equipment **206**. For example, the second active UE **208B** may transmit a request to the first active UE **208A**. The first active UE **208A** may receive the request and may transmit (block **316**) the first data set to one or more active UEs **208**, such as the second active UE **208B**, based on the request.

[0065] Additionally or alternatively, the first active UE **208A** may transmit the first data set based on receiving the first data set. For example, the first active UE **208A** may transmit the first data set via a device-to-device communication link to any UE **10** within the group of UEs **206** communicatively coupled to the first active UE **208A**. Moreover, the second active UE **208B** may transmit the second data set to one or more active UEs **208**, such as the first active UE **208A**, based on a request and/or based on receiving the second data set. For example, the second active UE **208B** may determine a number of active UEs **208** communicatively coupled to the second active UE **208B** and may transmit the second data set to at least a portion of those active UEs **208**.

[0066] In certain embodiments, the second active UE **208B** may transmit an instruction to cause the first active UE **208A** to transmit and/or broadcast the first data set to a set of UEs of the group of UEs **206**. For example, the set of UEs may include the second active UE **208B**, any number of other active UEs **208**, any number of passive UEs **210**, or any combination thereof. Additionally or alternatively, the first active UE **208A** may transmit an instruction to cause the second active UE **208B** to transmit and/or broadcast the second data set to a second set of UEs of the group of UEs **206**. For example, the second set of UEs may include the first active UE **208A**, any number of other active UEs **208**, any number of passive UEs **210**, or any combination thereof. The second active UE **208B** may receive (block **318**) the first data set from the first active UE **208A** via a device-to-device communication link. The second active UE **208B** may assemble (block **320**) the data based at least in part on the first data set and the second data set. In some embodiments, the active UE **208** may transmit and/or broadcast the data and/or the data sets to additional UEs within the group of UEs **206**. For example, the active UE **208** may transmit the data and/or the data sets to other active UEs **208**, passive UEs **210**, or any combination thereof via the device-to-device connection.

[0067] In certain embodiments, the target UE may include a passive UE **210** and may request data from the wireless communication network **102**. Each passive UE **210** may be disconnected from the wireless communication network **102** and/or each of the base stations **104**. Each active UE **208** may be directly communicatively coupled to the wireless communication network **102** and/or one or more of the base stations **104** without any intermediate or intervening UE between the active UE **208** and the base stations **104**. Alternatively, each passive UE **210** may be indirectly communicatively coupled to the wireless communication network **102** and/or one or more of the base stations **104** through at least one intermediary or intervening user equipment (e.g., at least one active UE **208**, at least one active UE **208** and at least one passive UE **210**). Additionally or alternatively, each passive UE **210** may not include a communication link to any of the base stations **104** or establish a communication session with the wireless communication network **102** and/or the base stations **104**. As such, the passive UE **210** may transmit and receive data from the wireless communication network **102** and/or the base stations **104** via one or more intervening or intermediary UE. Each active UE **208** may receive the data and/or one or more sets (e.g., a portion, a subset) of the data from the wireless communication network **102** via base stations **104**. The active UEs **208** may transmit the sets of data to other active UEs **208** and/or passive UEs **210**

within the group of user equipment **206**. The active UEs **208** and/or passive UEs **210** may assemble the data based at least in part on the received sets of the data. The group of user equipment **206** may coordinate and cooperate to provide the data to the target passive UE. Accordingly, the target passive UE may receive the data and/or the data sets and may assemble the data based on the data sets.

[0068] With the foregoing in mind, FIG. **6** is a flowchart of a method **400** to download data to active user equipment **208** and passive user equipment **210** of the group of user equipment **206** of FIG. **4** using the wireless communication network **102**, according to embodiments of the present disclosure. Any suitable device (e.g., a controller) that may control components of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, such as one or more respective processors **12** of these devices, may perform the method **400**. In some embodiments, the method **400** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the one or more respective memories **14** or storages **16** of these devices, using the processors **12**. For example, the method **400** may be performed at least in part by one or more software components, such as one or more respective operating systems of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, one or more software applications of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210** and the like. While the method **400** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0069] In process block **402**, the network **102** and/or the application server **202** broadcasts or transmits data to the base stations **104**. The base stations **104** may receive the data and may generate (block **404**) any number of data sets. For example, the base station **104** may receive information associated with a number of active UEs **208** in the group of user equipment **206**, a number of passive UEs **210** in the group of user equipment **206**, and/or a number of UEs **10** (e.g., sum of number of active UEs and passive UEs) in the group of user equipment **206**. The base station **104** may generate a number of data sets based at least in part on the number of active UEs **208**, the number of passive UEs **210**, and/or the number of UEs **10**. For example, the base station **104** may receive (e.g., generate) a number of sets of the data equal to a number of active UEs **208**. The base station **104** may transmit (block **406**) the data sets to a set of active UEs **208** (e.g., all active UEs **208**, active UEs **208** communicatively coupled to a particular base station **104**, and so forth).

[0070] The active UEs **208** may determine (block **408**) whether each active UE **208** of the set of active UEs **208** have received the data sets. For example, one or more active UEs **208** may request the data and/or the data sets from another active UEs **208**. In response to a request for missing data (NO path of block **408**), one or more active UEs **208** may transmit (block **410**) the data and/or the data sets to one or more other active UEs **208** within the group of UEs **206**. The active UEs **208** may also transmit (block **412**) the data and/or the data sets to a set of passive UEs **210**. Based on each active UE **208** receiving the data sets (YES path of block **408**), the active UEs **208** may transmit (block **412**) the data and/or the data sets to the set of passive UEs **210**. At block **414**, the passive UEs **210** may determine whether the set of passive UEs **210** have received the data and/or the data sets. Additionally or alternatively, the passive UEs **210** may determine whether the target UE has received the data and/or the data sets. In certain embodiments, one or more passive UEs **210** may request the data and/or the data sets from another passive UEs **210**. In response to a request for missing data (NO path of block **414**), the passive UEs **210** may transmit (block **416**) the data and/or the data sets to one or more other passive UEs **210**. If the set of passive UEs **210** received the data and/or the data sets (YES path of block **414**), the passive UEs **210** may also

receive an acknowledgement message from the set of passive UEs **210** indicating the set of passive UEs **210** received the data and/or the data sets. The passive UEs **210** may transmit (block **418**) the acknowledgement message to the active UEs **208**. The active UEs **208** may receive the acknowledgment message and may transmit (block **420**) the acknowledgement message to the wireless communication network **102** via the base stations **104**. As such, the base stations **104** may receive (block **422**) the acknowledgment message. Accordingly, the wireless communication network **102** may transmit data to the group of UEs **206** and a passive UE **210** may receive and assemble the data based on one or more data sets.

[0071] In certain embodiments, a target UE (e.g., first active UE **208A**, first passive UE **210B**) may transmit (e.g., directly, indirectly via intervening or intermediary UE) data to the wireless communication network **102**. Active UEs **208** may receive the data and/or one or more sets (e.g., a portion, a subset) of the data from other UEs (e.g., active UEs **208**, passive UEs **210**) in the group of user equipment **206**. The active UEs **208** may transmit the sets of data to other active UEs **208** within the group of user equipment **206**. The active UEs **208** may assemble the data based at least in part on the received sets of the data and may transmit the data and/or the data sets to the base stations **104**. As such, the group of user equipment **206** may coordinate and cooperate to provide the data to the wireless communication network and/or the base stations **104**.

[0072] With the foregoing in mind, FIG. **7** is a flowchart of a method **500** to upload data to base stations **104** of the wireless communication network **102** of FIG. **3** using active user equipment **208** of the group of user equipment **206**, according to embodiments of the present disclosure. Any suitable device (e.g., a controller) that may control components of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, such as one or more respective processors **12** of these devices, may perform the method **500**. In some embodiments, the method **500** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the one or more respective memories **14** or storages **16** of these devices, using the processors **12**. For example, the method **500** may be performed at least in part by one or more software components, such as one or more respective operating systems of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, one or more software applications of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210** and the like. While the method **500** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0073] One or more active UEs **208** may receive data and may generate any number of data sets based on the data. For example, the second active UE **208B** may receive data from passive UEs **210**. Additionally or alternatively, the second active UE **208B** may receive the data sets from the passive UEs **210** and/or another active UEs **208**. In other instances, the second active UE **208B** may generate the data and/or the data sets. At block **502**, the second active UE **208B** may transmit a first data set to a first active UE **208A**. The second active UE **208B** may also transmit (block **504**) a second data set to the wireless communication network **102** via the base stations **104**. The first active UE **208A** may receive the first data set and may transmit (block **506**) the first data set to the wireless communication network **102** via the base stations **104**. As such, the wireless communication network **102** may receive the data via wireless communication with multiple active UEs **208** within the group of UEs **206**. Additionally, the active UEs **208** may transmit the data to multiple base stations **104**. For example, the first active UE **208A** may transmit the first data set to the first base station **104A** and the second active UE **208B** may transmit the second data set to the second base station **104B**.

[0074] At block **508**, the base station **104** may receive the first data set and the second data set. The

base station **104** may assemble (block **510**) the data based at least in part on the first data set and the second data set and may transmit (block **512**) the data and/or the data sets to the application server **202**. The application server **202** may receive (block **514**) the data and/or the data sets. As such, the group of UEs **206** may transmit data to the wireless communication network through coordination and cooperation between one or more active UEs **208**. In certain embodiments, one or more active UEs **208** may transmit (e.g., simultaneously, concurrently, consecutively, overlapping, separately, and so forth) the data and/or the data sets. As such, the group of UEs **206** may provide redundant transmission of data to provide better coverage and reliability.

[0075] In certain embodiments, the target UE may be a passive UE **210** and may indirectly transmit data to the wireless communication network **102**. As such, the passive UEs **210** may transmit data to one or more intervening or intermediary UEs. Active UEs **208** and/or other passive UEs **210** may receive the data and/or one or more sets (e.g., a portion, a subset) of the data from the target UE. The active UEs **208** may transmit the sets of data to other active UEs **208** and/or passive UEs **210** within the group of user equipment **206**. The active UEs **208** and/or passive UEs **210** may assemble the data based at least in part on the received sets of the data. The active UEs **208** may transmit (e.g., simultaneously, concurrently, consecutively, overlapping, separately, and so forth) the data and/or the data sets to the wireless communication network **102** and/or the base stations **104**. As such, the group of user equipment **206** may coordinate and cooperate to provide the data from a passive UE **210** to the wireless communication network **102** and/or the base stations **104**.

[0076] With the foregoing in mind, FIG. **8** is a flowchart of a method **600** to upload data to base stations **104** of the wireless communication network **102** of FIG. **3** using active user equipment **208** and passive user equipment **210** of the group of user equipment **206**, according to embodiments of the present disclosure. Any suitable device (e.g., a controller) that may control components of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, such as one or more respective processors **12** of these devices, may perform the method **600**. In some embodiments, the method **600** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the one or more respective memories **14** or storages **16** of these devices, using the processors **12**. For example, the method **600** may be performed at least in part by one or more software components, such as one or more respective operating systems of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, one or more software applications of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210** and the like. While the method **600** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0077] One or more passive UEs **210** may receive data and may receive (e.g., generate) any number of data sets based on the data. For example, the second passive UE **210A** may receive data and/or the data sets from the first passive UE **210A**. Additionally or alternatively, the second passive UE **210B** may receive the data and/or the data sets from active UEs **208**. In other instances, the second passive UE **210B** may generate the data and/or the data sets. At block **602**, the passive UEs **210** may transmit data to another set of passive UEs **210**. The passive UEs **210** may also transmit (block **604**) the data to a set of active UEs **208**. The active UEs **208** may determine (block **606**) whether the set of active UEs **208** received the data. If one or more active UEs **208** did not receive the data (NO path of block **606**), the active UEs **208** may transmit (block **608**) the data to other active UEs **208** within the group of UEs **206**. If the active UEs **208** did receive the data (YES path of block **606**), each active UE **208** that received the data may transmit (block **610**) the data to the base stations **104**.

[0078] At block **612**, the base station **104** may receive the data and may transmit (block **614**) the

data to the application server **202**. The application server **202** may receive (block **616**) the data. As such, the group of UEs **206** may transmit data to the wireless communication network **102** through coordination and cooperation between one or more active UEs **208** and/or one or more passive UEs **210**. In certain embodiments, one or more active UEs **208** may transmit (e.g., simultaneously, concurrently, consecutively, overlapping, separately, and so forth) the data and/or data sets to the wireless communication network **102** and/or to other active UEs **208**. As such, the group of UEs **206** may provide redundant transmission of data to provide better coverage and reliability. Additionally or alternatively, one or more passive UEs **210** may transmit (e.g., simultaneously, concurrently, consecutively, overlapping, separately, and so forth) the data and/or data sets to other passive UEs **210** and/or active UEs **208**.

[0079] In some embodiments, the application server **202** may split data into one or more data sets and may transfer the one or more data sets to one or more base stations **104**. For example, the application server **202** may split the data into a number of data sets equal to or greater than the number of base stations **104** of the wireless communication network **102**. Additionally or alternatively, the application server **202** may split the data into a number of data sets equal to or greater than a number of active UEs **208** in the group of UE **210**. The base stations **104** may transmit the data and/or the data sets to the active UEs **208**. The active UEs **208** may receive the data sets from the base stations **104**. For example, the first active UE **208A** may receive a first data set from the first base station **104A** and a second active UE **208B** may receive a second data set from the second base station **104B**. The active UE **208** may exchange the data sets between each other and each active UE **208** may reassemble the data set to form the data.

[0080] With the foregoing in mind, FIG. **9** is a flowchart of a method **700** to download data to active user equipment **208** of the group of user equipment **206** of FIG. **4** using multiple base stations **104**, according to embodiments of the present disclosure. Any suitable device (e.g., a controller) that may control components of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, such as one or more respective processors **12** of these devices, may perform the method **700**. In some embodiments, the method **700** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the one or more respective memories **14** or storages **16** of these devices, using the processors **12**. For example, the method **700** may be performed at least in part by one or more software components, such as one or more respective operating systems of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, one or more software applications of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210** and the like. While the method **700** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0081] At block **702**, the application server **202** may receive and/or generate data sets based on a number of base stations **104** communicatively coupled to the wireless communication network **102**. In some embodiments, the application server **202** may receive data sets equal to a number of base stations **104** within the wireless communication network **102**. For example, the number of base stations **104** may include base stations directly coupled to the application server **202** and base stations indirectly (e.g., via one or more intermediary or intervening base stations **104**) coupled to the application server **202**. The application server **202** may transmit (block **704**) the data and/or the data sets to the base stations **104**. For example, the application server **202** may transmit a first data set to the first base station **104A** and a second data set to the second base station **104B**.

[0082] The first base station **104A** may receive the first data set and may transmit (block **706**) the first data set to a first set of active UEs **208**. At block **708**, the second base station **104B** may receive the second data set and may transmit the second data set to a second set of active UEs **208**.

For example, the first active UE **208A** may receive (block **710**) the first data set and the second active UE **208B** may receive (block **712**) the second data set. The second active UE **208B** may determine (block **714**) whether the data has been received. If the second active UE **208B** has not received the data (NO path of block **714**), the second active UE **208B** may request (block **716**) additional data sets from one or more other active UEs **208**. For example, the second active UE **208B** may request the first data set from the first active UE **208A**. The first active UE **208A** may receive the request and may transmit (block **718**) the first data set to the second set of active UEs **208**. Additionally or alternatively, the first active UE **208A** may transmit the first data set to the second set of active UEs **208** and/or another set of active UEs **208** in response to receiving the first data set. For example, the base station **104** may transmit an instruction to transmit the first data set to the second set of active UEs **208**. Moreover, the second active UE **208B** may transmit the second data set to the first set of active UEs **208** and/or another set of active UEs **208**. The second active UE **208B** may receive (block **720**) the first data set and may assemble (block **722**) the data based at least in part on the first data set and the second data set.

[0083] In some embodiments, the base stations **104** may split the data into one or more data sets. For example, a first base station **104A** may split the data into data sets and may transmit and/or broadcast the data sets to other base stations **104B**. Additionally or alternatively, the base stations **104** may transmit and/or broadcast the data and/or the data sets to the active UEs **208**. The active UEs **208** may receive the data sets from the base stations **104**. For example, the first active UE **208A** may receive a first data set from the first base station **104A** and the second active UE **208B** may receive a second data set from the second base station **104B**. The active UEs **208** may exchange the data sets between each other and each active UEs **208** may reassemble the data sets to form the data. Additionally or alternatively, the active UEs **208** may transmit the data and/or the data sets to the passive UEs **210** and the passive UEs **210** may reassemble the data sets to form the data.

[0084] With the foregoing in mind, FIG. **10** is a flowchart of a method **800** to download data to active user equipment **208** and passive user equipment **210** of the group of user equipment **206** of FIG. **4** using multiple base stations **104**, according to embodiments of the present disclosure. Any suitable device (e.g., a controller) that may control components of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, such as one or more respective processors **12** of these devices, may perform the method **700**. In some embodiments, the method **700** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the one or more respective memories **14** or storages **16** of these devices, using the processors **12**. For example, the method **700** may be performed at least in part by one or more software components, such as one or more respective operating systems of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, one or more software applications of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210** and the like. While the method **700** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0085] At block **802**, the first base station **104A** may receive a first data set. For example, the first base station **104A** may receive data and may generate the first data set based on the data. The first base station **104A** may transmit (block **804**) the first data set to a first set of active UEs **208** that may include the first active UE **208A**. At block **806**, the first active UE **208A** may receive the first data set and may transmit (block **808**) the first data set to a first set of passive UEs **210**.

[0086] The passive UEs **210** may receive (block **810**) the first data set and may determine (block **812**) whether the data has been received. If not all data sets have been received (NO path of block

812), the passive UEs **210** may request (block **814**) additional data sets from one or more active UEs **208**. For example, the second base station **104B** may receive (block **816**) and may transmit (block **818**) a second data set to a second set of active UEs **208** that may include a second active UE **208B**. The second active UE **208B** may receive (block **820**) the second data set. The second active UE **208B** may transmit (block **822**) the second data set to a second set of passive UEs **210**. Additionally or alternatively, the second active UE **208B** may transmit the second data set in response to receiving the second data set and/or an instruction from the wireless communication network **102** and/or the base station **104**. In some embodiments, the second active UE **208B** may transmit (block **824**) the second data set based on the request from the passive UEs **210**. The passive UEs **210** may receive the second data set and may assemble (block **826**) the data based at least in part on the first data set and the second data set. If all data sets have been received (YES path of block **812**), the passive UEs **210** may assemble the data based at least in part on the data sets.

[0087] Data transmission between the group of UE **206** and the wireless communication network **102** and/or between UEs **10** within the group of UE **206** may be implemented in different layers of various communication protocols. In some instances, the data may be split in the Packet Data Convergence Protocol (PDCP) dataplane layer. The PDCP layer of the access point may split the data into any number of data sets and may transfer the data and/or the data sets to two or more active UEs **208**. The active UEs **208** receive the data and/or the data sets, transmit the data and/or the data sets, and aggregate the data and/or the data sets on the PDCP level. For upload, an active UE **208** may apply a PDCP duplication procedure and share a redundant copy of data with one or more other active UEs **208**. Each active UE **208** may then transmit the same PDCP data to the base station **104**. The base station **104** may then receive the data and transmit the data to the application server **202**.

[0088] With the foregoing in mind, FIG. **11** is a block diagram of a model **900** of Open Systems interconnection (OSI) model layers of the UE **10**, according to embodiments of the present disclosure. The UE **10** may receive data and/or any number of data sets from the wireless communication network **102** at the PDCP dataplane layer **902**. Additionally, the UE **10** may transmit the data and/or the data sets to other UE **10** within the group **206** at the PDCP dataplane layer **902**. As such, the UE **10** may transmit redundant copies of the data and/or the datasets to other active UEs **208** within the group **206**. Accordingly, any active UEs **208** that receives the data and/or the data sets may transmit the same set of PDCP data to the wireless communication network **102** via the base stations **104**. Moreover, the UEs **10** may assemble the data based on any number of data sets at the PDCP dataplane layer **902**.

[0089] Additionally or alternatively, the UE **10** may receive data at the physical layer **904**. The physical layer **904** may be associated with any number of physical connections between UEs **10** and any other computing devices. The UE **10** may also split the data into any number of data sets at the physical layer **904**. As such, the UE **10** may transmit the data and/or the data sets to other UEs **10** within the group of UE **206**. The UE **10** may transmit redundant copies of the data and/or the data sets to other active UEs **208** within the group **206**. Accordingly, any active UEs **208** that receives the data and/or the data sets may transmit the same set of physical layer data to the wireless communication network **102**. In certain embodiments, the base station **104** may receive the data sets and may assemble the data. In certain embodiments, the UE **10** may receive control messages at the physical layer **904**. For example, the UE **10** may receive control messages that include downlink control data and/or uplink control data. The control messages may facilitate control of operations at the physical layer **904**. Additionally, the UE **10** may transmit the control messages to other UEs within the group of UE **206**.

[0090] In some embodiments, the UE **10** may receive control messages at the media access control (MAC) layer **906**. The MAC layer **906** may include a sublayer of a data link layer. The MAC layer **906** may control hardware that facilitates interaction with wired, optical, and/or wireless

transmission media. The control messages may include a MAC control element that may control one or more procedures for the UE **10**. Any number of active UEs **208** may receive the control messages at the MAC layer **906**. In certain embodiments, the control messages may include a set of UE identifiers. The UE **10** may utilize the UE identifiers to identify and transmit the control messages to other UEs within the group of UE **206**. Additionally or alternatively, the active UEs **208** may transmit the control messages at the MAC layer **906** to all UEs within the group **206**. [0091] In certain embodiments, the UE **10** may receive control messages at the Radio Resource Control (RRC) layer **908**. The control messages may include configuration data and may facilitate control of Access Stratum and non-Access Stratum procedures of the UE **10**. In some embodiments, RRC control messages may include a set of device identifiers to assist the group of UE **206** in identifying UEs that may receive the RRC control messages. For example, a first active UE **208A** may receive the RRC control messages and may select any number of active UEs **208** and/or passive UEs **210** as intended recipients of the RRC control message based on the set of device identifiers.

[0092] FIG. **12** is a flowchart of a method **1000** to download data at an internet protocol layer of the user equipment **10** of FIG. **1**, according to embodiments of the present disclosure. Any suitable device (e.g., a controller) that may control components of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, such as one or more respective processors **12** of these devices, may perform the method **1000**. In some embodiments, the method **1000** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the one or more respective memories **14** or storages **16** of these devices, using the processors **12**. For example, the method **1000** may be performed at least in part by one or more software components, such as one or more respective operating systems of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, one or more software applications of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210** and the like. While the method **1000** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0093] At block **1002**, the application server **202** may transmit data to base station **104**. The base station **104** may receive the data and may receive and/or generate (block **1004**) data sets at an IP Network Layer. The base station **104** may transmit (block **1006**) the data sets to a set of active UEs **208**. For example, a first active UE **208A** may receive (block **1008**) the first data set at the IP Network Layer and the second active UE **208B** may receive (block **1010**) the second data set at the IP Network Layer. The second active UE **208B** may determine (block **1012**) whether all data sets have been received at the second active UE **208B**. If not all data sets have been received (NO path of block **1012**), the second active UE **208B** may request (block **1014**) the first data set from other active UEs **208**, such as the first active UE **208A**. The first active UE **208A** may receive the request and may transmit (block **1016**) the first data set to the second active UE **208B**. The second active UE **208B** may receive (block **1018**) at the IP Network Layer and may assemble (block **1020**) the data at the IP Network Layer based on the data sets. If all data sets have been received (YES path of block **1012**), the second active UE **208B** may assemble the data at the IP Network Layer based on the data sets.

[0094] In certain embodiments, the data may be split in a new sub-layer of the IP Network Layer protocol. The new layer may be defined as a Data Split and Scheduling Layer. The new layer may split the data into one or more data sets and map the data sets to IP addresses of one or more active UEs **208** within the group of UE **206**. The base station **104** may receive the data and/or the data sets and may transmit the data and/or the data sets to a set of active UEs **208** based on the mapping. The

active UEs **208** may receive the data sets and may cooperate and coordinate with other UEs within the group of UEs **206** to transmit the data sets based on the mapping. The active UEs **208** may assemble the data based on the data sets.

[0095] FIG. **13** is a block diagram of IP network layers of the application server **202**, according to embodiments of the present disclosure. The application layer **1102** may specify shared communications protocols and/or interface methods that may be utilized in a communications network, such as the wireless communications network **102**. In certain embodiments, the application layer **1102** may utilize Hypertext Transfer Protocol (HTTP), Domain Name System (DNS), Transport Layer Security (TLS), and any other suitable communication protocol. The transport layer **1104** may specify transport protocols that provide end-to-end communication services, such as connection-oriented communication, reliability, flow control, multiplexing, and so forth, for various applications. As such, the transport layer **1104** may facilitate delivery of data to appropriate applications executing on the UE **10**. The transport layer **1104** may utilize the transmission control protocol (TCP), the User Datagram Protocol, the Datagram Congestion Control Protocol (DCCP), the Stream Control Transmission Protocol (SCTP) and any other suitable transport protocol. The network layer **1106** may specify protocols, methods, and specifications that facilitate transportation of network packets from UEs **10** and across boundaries of the communication network. The network layer **1106** may utilize Internet Protocol (IP), Internet Protocol version 4 (IPv4), Internet Protocol version 6 (IPv6), and any other suitable network protocol. The network layer **1106** may include any number of sublayers, such as a data split and scheduling layer **1108**. The application server **202** may split the data into any number of data sets at the data split and scheduling layer **1108**. Additionally, the application server **202** may generate a mapping between the data sets and any number of IP addresses associated with active UEs **208** of the group of UE **206**. For example, the application server **202** may map one or more data sets to each IP address. Additionally or alternatively, the application server **202** may map one or more data sets to IP addresses that correspond to a set of active UEs **208**. In certain embodiments, the application server **202** may map the same data sets to multiple active UEs **208**. As such, the base station **104** may transmit the same data sets to two active UEs **208**, three active UEs **208**, and so forth. Accordingly, the base station **104** may transmit the data sets and/or the data based on the mapping.

[0096] With the foregoing in mind, FIG. **14** is a flowchart of a method **1200** to download data using Internet Protocol (IP) addresses of active user equipment **208** of the group of user equipment **206** of FIG. **4**, according to embodiments of the present disclosure. Any suitable device (e.g., a controller) that may control components of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, such as one or more respective processors **12** of these devices, may perform the method **1200**. In some embodiments, the method **1200** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the one or more respective memories **14** or storages **16** of these devices, using the processors **12**. For example, the method **1200** may be performed at least in part by one or more software components, such as one or more respective operating systems of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, one or more software applications of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210** and the like. While the method **1200** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0097] At block **1202**, the application server **202** may receive and/or generate data and/or data sets at an IP Network Layer. The application server **202** may map (block **1204**) the data sets to

corresponding IP addresses of active UEs **208** within a group of UE **206**. At block **1206**, the application server **202** may transmit the data sets and/or the mapping to the base station **104**. As such, the base station **104** may receive the data sets and the mapping and may transmit (block **1208**) the data sets to active UEs **208** based on the mapping. For example, the base station **104** may transmit a first data set to a first set of active UEs **208**, a second data set to a second set of active UEs **208**, a third data set to a third set of active UEs **208**, and so forth.

[0098] Accordingly, the first active UE **208A** may receive (block **1210**) a first data set and the second active UE **208B** may receive (block **1212**) the second data set. The second active UE **208B** may determine (block **1214**) whether all data sets have been received. If not all data sets have been received (NO path of block **1214**), the second active UE **208B** may request (block **1216**) the first data set from a set of active UEs **208**. For example, the first active UE **208A** may receive the request and may transmit (block **1218**) the first data set to one or more active UEs **208**, such as the second active UE **208B** based on the request. The second active UE **208B** may receive (block **1220**) the first data set and may assemble (block **1222**) the data based at least in part on the first data set and the second data set.

[0099] The data may be steered to particular active UEs **208**. For example, the application server **202** may determine a first data set to transmit to the first active UE **208A**, a second data set to transmit to the second active UE **208B**, and so forth. Additionally or alternatively, a first base station **104A** may determine a third data set to transmit to a second base station **104B** based on a connection status between the second base station **104B** and the application server **202**.

[0100] With the foregoing in mind, FIG. **15** is a flowchart of a method **1300** to download data using the first base station **104A** communicatively coupled to the application server **202** and a second base station **104B** disconnected from the application server **202** of the wireless communication network **102** of FIG. **3**, according to embodiments of the present disclosure. Any suitable device (e.g., a controller) that may control components of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, such as one or more respective processors **12** of these devices, may perform the method **1300**. In some embodiments, the method **1300** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the one or more respective memories **14** or storages **16** of these devices, using the processors **12**. For example, the method **1300** may be performed at least in part by one or more software components, such as one or more respective operating systems of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, one or more software applications of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210** and the like. While the method **1300** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0101] At block **1302**, the first base station **104A** may receive data and/or data sets from the application server **202**. For example, the first base station **104A** may receive the data and may generate the data sets based on a number of other base stations **104** included in the wireless communication network **102**. The first base station **104A** may determine (block **1304**) the second base station **104B** is disconnected from the application server **202**. That is, the first base station **104A** may act as an intervening or intermediary base station **104** to permit communication between the second base station **104B** and the application server **202**. The first base station **104A** may transmit (block **1306**) the first data set to a first set of active UEs **208**. For example, the first active UE **208A** may receive (block **1308**) the first data set and may transmit (block **1310**) the first data set to a set of active UEs **208**, a set of passive UEs **210**, or a combination thereof. For example, the first active UE **208A** may transmit the first data set to the second active UE **208B**.

[0102] Additionally or alternatively, the first base station **104A** may transmit (block **1312**) the second data set to a set of base stations **104**, such as second base station **104B**. The second base station **104B** may receive (block **1314**) the second data set from the first base station **104A**. The second base station **104B** may also transmit (block **1316**) the second data set to a second set of active UEs **208**, such as the second active UE **208B**. As such, the second active UE **208B** may receive (block **1318**) the first data set and the second data set. Accordingly, the second active UE **208B** may assemble (block **1320**) the data based at least in part on the first data set and the second data set.

[0103] Active UEs **208** may be controlled using control channels due to the direct connection to the base station **104**. Passive UEs **210** have an indirect connection and may require an updated control channel path. Control channels provide configuration data to UEs **10** for paging the UEs **10** and scheduling data reception and transmission. Active UEs **208** may identify that a paging message, a configuration message, and/or control data is intended for passive UEs **210**. The active UEs **208** may perform the identification based on an identifier associated with a protocol layer format. A MAC Control Element (MAC CE) may be utilized as an identifier. In some instances, the MAC CE may be applicable for all UEs **10** within the group of UE **206** and may be received by the first active UE **208A** and transmitted to any number of other active UEs **208** and passive UEs **210**. In another instance, the MAC CE may be applicable to passive UEs **210** only. A Radio Resource Control (RRC) message may provide configuration data to UEs **10**. The base station **104** may transmit the RRC message to active UEs **208** that may transmit the message to other active UEs **208** and/or passive UEs **210**. Responses may be transmitted to the base station **104** via the active UEs **208**. Downlink Control Information (DCI) and Uplink Control Information (UCI) may be utilized to control the physical layer operation.

[0104] With the foregoing in mind, FIG. **16** is a flowchart of a method **1400** to download control messages to active user equipment **208** and passive user equipment **210** of the group of user equipment **206** of FIG. **4**, according to embodiments of the present disclosure. Any suitable device (e.g., a controller) that may control components of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, such as one or more respective processors **12** of these devices, may perform the method **1400**. In some embodiments, the method **1400** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the one or more respective memories **14** or storages **16** of these devices, using the processors **12**. For example, the method **1400** may be performed at least in part by one or more software components, such as one or more respective operating systems of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, one or more software applications of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210** and the like. While the method **1400** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0105] At block **1402**, the base station **104** may transmit a control message to a first set of active UEs **208**. For example, the base station **104** may transmit the control message to the first active UE **208A** that is communicatively coupled to the base station **104**. The first active UE **208A** may receive (block **1404**) the control message and may perform an operation based on the control message. For example, the first active UE **208A** may utilize the control message to control a procedure. In certain embodiments, the control message may include a set of UE identifiers that may indicate recipients (e.g., one or more active UEs **208**, one or more passive UEs **210**, or a combination thereof) for the control message. As such, the first active UE **208A** may transmit (block **1406**) the control message to a second set of active UEs **208** based on the set of UE

identifiers and may also transmit (block **1408**) the control message to a set of passive UEs **210** based on the set of UE identifiers. The set of passive UEs **210** may receive (block **1410**) the control message and may perform an operation based on the control message. Additionally, the second active UE **208B** may receive (block **1412**) the control message and may transmit (block **1414**) the control message to a second set of passive UEs **210** based on the set of device identifiers. As such, the group of UE **206** may coordinate and cooperate to receive and transmit control messages from a communication network and transmit the control messages to intended UEs based on a set of UE identifiers included in the control message.

[0106] In some embodiments, the UEs **10** may utilize criteria for entering and/or leaving the group of UE **206**. The criteria may include a network signal quality of the UEs **10**, a power connection, a battery level of the UEs **10**, a time window, a geographic area of the UEs **10**, UE capabilities, a device-to-device connection, a trust level between UEs **10**, and so forth. In certain embodiments, the UE **10** may be at an edge of the coverage area for the wireless communication network **102**. The network signal quality of the UE **10** may be compared to a threshold. When below the threshold, there may be a risk that service is interrupted. If another UE **10** or the group of UE **206** are in close proximity, the UE **10** may attempt to form a group or enter the group of UE **206**. If a UE **10** is connected to electrical power, it may no longer require the benefits of shared resources within a group and may leave the group. Alternatively, when connected to electrical power, the UE **10** may receive additional tasks within the group. Moreover, the UE **10** may instruct other UEs within the group to enter a power-saving mode when the UE **10** is connected to electrical power. As such, the other UEs may offload tasks to the UE **10** with the highest battery level and/or the UE **10** that is currently connected to electrical power. Additionally or alternatively, the UE **10** may compare the battery level to a battery threshold. For example, when below the threshold, the UE **10** may search for and/or join the group in order to offload tasks and enter a power-saving mode. Alternatively, when above the threshold, the UE **10** may exit the power-saving mode and may leave the group.

[0107] In certain embodiments, the UEs **10** may search for and/or enter one or more groups based on a current time. For example, the UE **10** may receive an input indicative of a particular time period when group search and/or group formation is permitted. Additionally or alternatively, the UE **10** may search for and/or enter groups based on a current location of the UE **10**. For example, the UE **10** may determine the UE **10** is within a particular location, such as a home or office, and/or may detect other known UEs within proximity (e.g., distance threshold, communication threshold, local network) of the UE **10**. Additionally, the UE **10** may determine the current location of the UE **10** is outside of the particular location and may request and leave the group. In some embodiments, the UE **10** may have limited capabilities compared to other UEs within proximity of the UE **10**. For example, the UE **10** may support fewer RATs, may support fewer frequency bands for radio communication, may support fewer local communication technologies, and the like. As such, the UE **10** may search for and enter the group to provide additional coverage and efficiency for data transfer and reception.

[0108] A UE **10** that lacks radio technology or does not support particular frequencies may search for and enter a group of UE **206** with additional and/or greater UE capabilities. Additionally, the UE **10** may determine whether the UE capabilities permit the UE **10** to communicate with other UEs **10** in the group of UE **206**. The UE **10** may determine whether a stable device-to-device connection is available with one or more UEs **10** in the group of UE **206** based on the Received Signal Strength (RSSI) and signal to noise ratio (SNR), or any other suitable signal characteristics. UE trust may be established based on previously entering the group of UE **206**. Additionally, the UE **10** may determine a data rate of the local connection to the group of UE **206** and may compare the data rate to a threshold data rate. For example, certain applications may necessitate higher data rates for data communication. As such, the UE **10** may determine whether the local connection with the group **206** satisfies a data communication criteria (e.g., meets or exceeds the threshold data

rate). If the UE and/or group capabilities meet or exceed any number of criteria, the UE **10** may request and join the group of UE **206**. Alternatively, if any of the UE and/or group capabilities fail to satisfy any number of criteria, the UE **10** may not join the group and/or may request and leave the group.

[0109] The UE **10** may also determine a trust level associated with one or more UEs within the group of UE **206** and/or a trust level of the group of UE **206**. For example, the UE **10** may have previously joined a group with one or more of the UEs, may have previously shared data with one or more of the UEs, may have previously connected to the same local network, may currently be connected to the same local network, and so forth. Additionally, the UE **10** may determine whether any other UEs are previously known, such as based on a previous local network connection, a shared account, and the like. In some embodiments, the UE **10** may receive an input indicative of one or more user preferences for group membership, such as group formation, group entry, group exit, UE roles (e.g., primary UE, active UE, passive UE), UE tasks, and the like. For example, the UE **10** may receive input indicative of particular geographic areas, particular local networks, particular time of day, particular days, and the like for group membership. Additionally or alternatively, the UE **10** and/or the group of UE **206** may utilize signatures to determine trust levels and form, enter, and/or leave a group. In some embodiments, a machine learning model may be utilized to determine group formation, group entry, group exit, UE roles, and the like based on any number of criteria described herein. The machine learning model may be trained based on training data including previous group formations, group entries, group exits, UE roles, and the like.

[0110] Entering a group of UE **206** may begin with group discovery. One or more UEs **10** (e.g., active UEs **208**) within the group of UE **206** may transmit reference signals on a local communications frequency. The reference signals may be specialized wake-up signals optimized for low power consumption. UE **10** outside the group of UE **206** may periodically search for and try to detect the reference signals. The UE **10** can measure the reference signals and join the group of UE **206**. The next step of entering the group of UE **206** includes establishing device-to-device connections. The device-to-device connection may be direct or through a local network connection (e.g., wired, wireless, Ethernet, Wi-Fi, peer-to-peer, or any other suitable local network connection). The UE **10** may also exchange UE capabilities. The UE capabilities may be utilized to determine preferred communication frequencies, the types of communication technologies of the group of UE **206** and the new UE **10**, a current battery status of the UE **10**, a current thermal status of the UE **10**, and so forth. Each UE **10** may periodically send a keep alive message to at least one active UE **208** in the group of UE **206**.

[0111] To maintain the group of UE **206**, the number of passive UEs **210** may be controlled. For example, if an active UE **208** leaves coverage of the wireless communication network **102** and/or the base station **104**, the active UE **208** may be reassigned as a passive UE **210**. Additionally or alternatively, an active UE **208** may fall below a battery threshold and a new active UE **208** may be assigned. The active UEs **208** may receive regular updates from other UEs **10** in the group regarding battery status, thermal status, and link status of the UE **10**. At least one of the active UE **208** may additionally be assigned as a primary UE. The primary UEs may maintain a list of candidates from the active UEs **208** to be assigned as a new primary UE. The primary UEs may send a request to one of the candidates to become a new primary UE. Additionally or alternatively, a candidate UE may send a request to assign the candidate UE as a new primary UE. One or more current primary UEs may transmit a signal to assign the candidate UE as a new primary UE. For example, the current primary UE may transmit the signal to a portion of the UEs within the group of UEs.

[0112] With the foregoing in mind, FIG. **17** is a flowchart of a method **1500** to establish connection with the group of user equipment **206** of FIG. **4**, according to embodiments of the present disclosure. Any suitable device (e.g., a controller) that may control components of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active

UEs **208**, and/or the passive UEs **210**, such as one or more respective processors **12** of these devices, may perform the method **1500**. In some embodiments, the method **1500** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the one or more respective memories **14** or storages **16** of these devices, using the processors **12**. For example, the method **1500** may be performed at least in part by one or more software components, such as one or more respective operating systems of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, one or more software applications of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210** and the like. While the method **1500** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0113] At block **1502**, the first active UE **208A** may transmit and/or broadcast a reference signal. In certain embodiments, the first active UE **208A** may periodically transmit and/or broadcast the reference signal. Additionally or alternatively, the first active UE **208A** may transmit and/or broadcast the reference signal based on detection of other nearby UEs **10**. The UEs **10** may receive (block **1504**) the reference signal and may measure the reference signal. The UEs **10** may transmit (block **1506**) and/or broadcast a set of attributes associated with the UEs **10**. For example, the UEs **10** may transmit UE capabilities and/or UE statuses associated with the UEs. The first active UE **208A** may receive (block **1508**) the set of UE attributes and may receive (block **1510**) a set of group criteria. For example, the first active UE **208A** may retrieve the set of group criteria from the memory **14** and/or the storage **16**. Additionally or alternatively, another active UE **208**, such as a primary UE of the group of UE **206**, may transmit and/or broadcast the set of group criteria. As such, the first active UE **208A** may receive the set of group criteria from another active UE **208**.

[0114] At block **1512**, the first active UE **208A** may determine whether any number of the set of UE attributes satisfy the set of group criteria. In some embodiments, the set of group criteria may include a communication technology criterion. The communication technology criterion may indicate any number of acceptable communication technologies that provide communication between the UE within the group of UE **206**. As such, UE **10** requesting to join the group of UE **206** may include at least one of the acceptable communication technologies to satisfy the communication technology criterion. As another example, the set of group criteria may include a location criterion. The location criterion may indicate whether any UEs **10** requesting entry to the group of UE **206** are located within a particular geographic area and/or within a threshold distance from any UEs within the group of UE **206**. Additionally or alternatively, the set of group criteria may include a signal strength criterion. For example, the signal strength criterion may include a threshold signal strength and the first active UE **208A** may compare the RSSI and/or the signal-to-noise ratio from the requesting UE **10** to the threshold signal strength to determine satisfaction of the signal strength criterion. Moreover, the set of group criterion may include a network connection criterion that may indicate any number of acceptable local network connections for requesting UEs **10**. The first active UE **208A** may receive information including a list of active local network connections from the requesting UEs **10** and may compare the list with the acceptable local network connections. Additionally or alternatively, the first active UE **208A** may determine whether the requesting UEs **10** are capable of establishing a local network connection based on the communication technologies of the requesting UEs **10**. Accordingly, the first active UE **208A** may determine satisfaction of the network connection criterion based on active connections of the requesting UEs **10** and/or network connection capabilities of the requesting UEs **10**.

[0115] If the UE attributes satisfy the group criteria (YES path of block **1512**), the first active UE **208A** may establish (block **1514**) a connection with the requesting UE **10**. For example, the first active UE **208A** may establish a device-to-device connection with the requesting UE **10**.

Additionally or alternatively, the first active UE **208A** may establish a local network connection with the requesting UE **10** or any other suitable connection. In certain embodiments, the first active UE **208A** may determine a number of group criteria satisfied by the UE attributes and may establish the connection based on satisfaction of a threshold number of group criteria. Alternatively, the first active UE **208A** may establish the connection based on satisfaction of a single group criterion or all group criteria

[0116] If the UE attributes fail to satisfy (NO path of block **1512**) the group criteria (e.g., one criterion, a threshold number of criterion, the set of group criterion, and so forth), the first active UE **208A** may return to block **1502** and transmit the reference signal. For example, the first active UE **208A** may periodically transmit the reference signal. Additionally or alternatively, the first active UE **208A** may transmit a notification indicative of denying the request to establish and/or join the group of UE **206**. The UE **10** may receive the notification and may display the notification on the display **18**. In some embodiments, the notification may indicate one or more failed group criteria.

[0117] With the foregoing in mind, FIG. **18** is a flowchart of a method **1600** to download paging messages for the group of user equipment **206** of FIG. **4**, according to embodiments of the present disclosure. Any suitable device (e.g., a controller) that may control components of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, such as one or more respective processors **12** of these devices, may perform the method **1600**. In some embodiments, the method **1600** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the one or more respective memories **14** or storages **16** of these devices, using the processors **12**. For example, the method **1600** may be performed at least in part by one or more software components, such as one or more respective operating systems of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, one or more software applications of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210** and the like. While the method **1600** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0118] At block **1602**, a first set of active UEs **208** may transmit a corresponding set of paging identifiers. Each paging identifier may identify a corresponding active UE **208**. The first active UE **208A** may receive (block **1604**) the set of paging identifiers and may store the set of paging identifiers. Additionally or alternatively, a set of passive UEs **210** may transmit (block **1606**) a corresponding second set of paging identifiers. Each paging identifier of the second set of paging identifiers may identify a corresponding passive UE **210**. The first active UE **208A** may receive (block **1608**) the second set of paging identifiers and may store the second set of paging identifiers.

[0119] The first active UE **208A** may receive (block **1610**) a paging message. For example, the first active UE **208A** may periodically monitor for incoming paging messages from the wireless communication network **102**. In certain embodiments, the paging message may provide notification of an incoming call or an information change. The first active UE **208A** may determine the paging message is addressed to a set of UEs **10** in the group of UE **206**. For example, the paging message may include a set of paging identifiers and the first active UE **208A** may retrieve and compare with the stored paging identifiers. As such, the first active UE **208A** may determine a set of target UEs based on the paging identifiers included with the paging message. Accordingly, the first active UE **208A** may transmit (block **1612**) the paging message to the set of UEs **10** based on the set of paging identifiers associated with the paging message.

[0120] As such, the first active UE **208A** may act as a paging UE for any number of UEs within the group **206**. For example, a set of active UEs **208** and/or set of passive UEs **210** may transmit

corresponding paging identifiers to the first active UE **208A**. Additionally, the set of active UEs **208** and/or set of passive UEs **210** may enter an idle mode (e.g., cease monitoring for paging messages) in order to reduce power consumption. The paging UEs (e.g., the first active UE **208A**) may then wake up (e.g., send a wake-up signal to) or otherwise activate the UE(s) (e.g., of the set of active UEs **208** and/or set of passive UEs **210**) for which the paging message is intended. Accordingly, cooperation and coordination between the group of UE **206** may reduce power consumption for any number of the UEs by offloading paging to one or more active UEs **208**.

[0121] With the foregoing in mind, FIG. **19** is a flowchart of a method **1700** to download radio bearers to the group of user equipment **206** of FIG. **4** using the wireless communication network **102** of FIG. **3**, according to embodiments of the present disclosure. Any suitable device (e.g., a controller) that may control components of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, such as one or more respective processors **12** of these devices, may perform the method **1700**. In some embodiments, the method **1700** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the one or more respective memories **14** or storages **16** of these devices, using the processors **12**. For example, the method **1700** may be performed at least in part by one or more software components, such as one or more respective operating systems of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210**, one or more software applications of the network **102**, the base stations **104**, the application server **202**, the group of user equipment (UE) **206**, the active UEs **208**, and/or the passive UEs **210** and the like. While the method **1700** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0122] At block **1702**, the application server **202** may receive and/or generate data. In certain embodiments, the data may include a first radio bearer and a second radio bearer. In certain embodiments, a bearer service includes a link between two points that is defined by a set of characteristics. Services, such as RATs and/or local networks, provided to UEs **10** are associated with a radio bearer that specifies the configuration for the data link layer (e.g., layer **2**) and the physical layer. As such, the radio bearer may facilitate defining the quality of service (QoS) that provides a description or measurement of the overall performance of the service. Radio bearers may include channels provided by the data link layer to higher layers (e.g., the network layer, the transport layer, the application layer, and so forth) to facilitate transfer of user and/or control data. As such, the data link layer may provide information transmission as a service between the UE and the wireless communication network **102** via the radio bearers and signaling radio bearers. Accordingly, the radio bearers may function as access points between the data link layer and the upper layers. In certain embodiments, the first radio bearer may be associated with signaling data. For example, the first radio bearer may include a Signaling Radio Bearer (SRB) that carries signal data. The UEs **10** may utilize the SRB during connection establishment. The SRB may facilitate establishing Radio Access Bearers (RABs) and may also provide signaling data during connection with the wireless communication network **102**, such as to perform a handover, reconfiguration, release, and any other suitable signaling procedure. The application server **202** may transmit (block **1704**) the data to the first base station **104A**. The first base station **104A** may receive (block **1706**) the first radio bearer associated with the signaling data and may receive (block **1708**) the second radio bearer. The first base station **104A** may determine (block **1710**) the second base station **104B** is disconnected from the application server **202**. For example, the second base station **104B** may be indirectly communicatively coupled to the application server **202** via the first base station **104A**. The first base station **104A** may transmit (block **1712**) the first radio bearer to a first set of base station **104** that may include the second base station **104B**. In certain embodiments, the first set of

base station **104** may include any base station that is disconnected from the application server **202**. [0123] The second base station **104B** may receive the first radio bearer and may transmit (block **1714**) the first radio bearer to a first set of active UEs **208**. Additionally, the first base station **104A** may transmit (block **1716**) the second radio bearer to a second set of active UEs **208**. The active UEs **208** may receive and transmit the first and second radio bearers to other active UEs **208** within the group **206**. Moreover, the active UEs **208** may transmit (block **1718**) the first radio bearer and the second radio bearer to the passive UEs **210** within the group **206**. For example, the active UEs **208** may transmit the first radio bearer to a first set of passive UEs **210** and may transmit the second radio bearer to a second set of passive UEs **210**. The passive UEs **210** may receive (block **1720**) the first radio bearer and the second radio bearer. In certain embodiments, the first passive UE **210A** may receive the first radio bearer and the second passive UE **210B** may receive the second radio bearer. Accordingly, the active UEs **208**, the passive UEs **210**, or a combination thereof may cooperate and coordinate to transmit the first radio bearer and the second radio bearer to each UE **10** within the group **206**.

[0124] In an embodiment, a method includes receiving, a request for data from a target user equipment at a first user equipment of a group of user equipments. The group of user equipments includes the target user equipment. The method also includes receiving a first set of the data from a first base station at the first user equipment. The first base station may receive the first set from a server. The method also includes receiving a second set of the data from a second base station at the first user equipment. The first base station may receive the second set from the server. The method may also include assembling, at the first user equipment, the data based at least in part on the first set and the second set and transmitting, from the first user equipment, the first set, the second set, the data, or any combination thereof to the target user equipment. The target user equipment may be disconnected from the first base station, the second base station, or both.

[0125] The method may also include receiving, via a device-to-device communication link from a second user equipment, a third set of the data at the first user equipment. The second user equipment may be communicatively coupled to the first base station, the second base station, or both. Additionally, the group of user equipments may include the second user equipment. The method may also include assembling, at the first user equipment, the data based at least in part on the first set, the second set, and the third set.

[0126] Additionally, transmitting, from the first user equipment, the data to the target user equipment may include transmitting, via a device-to-device communication link, the first set, the second set, the data, or any combination thereof to the second user equipment and causing the second user equipment to send the data to the target user equipment.

[0127] The method may also include causing the second user equipment to assemble the data based at least in part on the first set, the second set, and the third set. The method may also include receiving, at the first user equipment, second data, transmitting, via device-to-device communication to a second user equipment, a set of the second data, and causing the second user equipment to send the set of the second data to the first base station, the second base station, or both.

[0128] The method may also include transmitting, from the first user equipment, the second data, the set of the second data, or both to the first base station, the second base station, or both. The second data may be received at the first user equipment via the device-to-device communication link from a third user equipment.

[0129] The method may also include transmitting, via the device-to-device communication link to the second user equipment, the second data and causing the second user equipment to send the second data to the first base station, the second base station, or both.

[0130] The method may also include receiving routing information associated with the data, wherein the routing information includes a path for transmission of the data to the target user equipment. The method may also include receiving a first set of user equipment to receive the data

based on the routing information. The method may also include transmitting the data to the first set of user equipment based on the routing information.

[0131] In another embodiment, a method may include receiving, at a base station, a request for data and receiving, at the base station, the data from a server, transmitting a first set of the data to a first user equipment communicatively coupled to the base station. A group of user equipments may include the first user equipment. The method may also include transmitting a second set of the data to a second user equipment communicatively coupled to the base station. The group of user equipments may include the second user equipment. The method may also include causing the first user equipment to send, via a device-to-device communication link, the first set of the data to a target user equipment that is disconnected from the base station. The group of user equipments may include the target user equipment. The method may also include causing the second user equipment to send, via a device-to-device communication link, the second set of the data to the target user equipment.

[0132] The method may also include transmitting the second set of the data to the first user equipment and causing the first user equipment to send, via a device-to-device communication link, the second set of the data to the target user equipment.

[0133] The method may also include receiving, at the base station, a third set of second data from the first user equipment; receiving, at the base station, a fourth set of second data from the second user equipment; and generating, at the base station, the second data based at least in part on the third set of the second data, the fourth set of the second data, or a combination thereof.

[0134] The third set of second data may be received at the first user equipment from a third user equipment that is disconnected from the base station. The group of user equipments may include the third user equipment.

[0135] The method may also include receiving, at the base station, third data from the first user equipment and receiving, at the base station, the third data from the second user equipment. A fifth set of the third data may be received at the second user equipment via a device-to-device communication link from the first user equipment.

[0136] A sixth set of the third data may be received at the first user equipment via a device-to-device communication link from the second user equipment. The method may also include receiving, at the base station, the first set of the data and the second set of the data based at least in part on the data.

[0137] In yet another embodiment, a method includes receiving, at a first user equipment communicatively coupled to a base station, a first data and receiving, at the first user equipment, a first set of the first data and a second set of the first data. The method also includes transmitting the first set, the second set, the first data, or any combination thereof to the base station and transmitting, via device-to device communication to a second user equipment communicatively coupled to the base station, the first set, the second set, the first data, or any combination thereof. The method also includes causing the second user equipment to send the first set, the second set, the first data, or any combination thereof to the base station.

[0138] The method may also include transmitting the first set, the second set, the first data, or any combination thereof to a second base station. The first user equipment may be communicatively coupled to the second base station. The method may also include receiving, at the first user equipment, a third set of a second data and transmitting the third set to the base station. A fourth set of the second data is received at the base station from a third user equipment communicatively coupled to the base station.

[0139] The method may also include splitting, at the first user equipment, the first data into the first set and the second set. The method may also include transmitting the first data to the base station and transmitting, via a device-to-device communication link to the second user equipment, the first data. The method may also include causing the second user equipment to send the first data to the base station. The first data may be received at the first user equipment via a device-to-device

communication link from a third user equipment that is disconnected from the base station.

[0140] In yet another embodiment, a method includes receiving, at a first base station, data from a server based on a request associated with a group of user equipments and determining, at the first base station, that a second base station is disconnected from the server. The method also includes transmitting, from the first base station, a first set of the data to a first user equipment communicatively coupled to the first base station. The group of user equipments may include the first user equipment. The method also includes transmitting, from the first base station, a second set of the data to the second base station communicatively coupled to the first user equipment. The second base station may transmit the second set to the first user equipment.

[0141] The method may also include receiving, at the first base station, the first set and the second set and transmitting, from the first base station, the second set to the first user equipment.

[0142] The method may also include causing the second base station to transmit the second set to a second user equipment communicatively coupled to the second base station. The group of user equipments may include the second user equipment.

[0143] The method may also include causing the first user equipment to transmit, via a device-to-device communication link, the first set to the second user equipment.

[0144] The method may also include transmitting, from the first base station, the data to the second base station and causing the second base station to send the data to a third user equipment communicatively coupled to the second base station. The group of user equipments may include the third user equipment.

[0145] The method may also include causing a third base station to transmit the data to a fourth user equipment communicatively coupled to the third base station. The group of user equipments may include the fourth user equipment. The data may be received at the third base station from the server.

[0146] The method may also include splitting, at an internet protocol network layer of the first base station, the data into the first set and the second set.

[0147] In yet another embodiment, a method includes receiving, at a first user equipment, a first set of data from a first base station. The first base station may receive the first set from a server. The method also includes receiving, at the first user equipment, a second set of the data via a device-to-device communication link from a second user equipment. The second user equipment may receive the second set from a second base station. The method also includes assembling, at the first user equipment, the data based at least in part on the first set and the second set.

[0148] The method may also include receiving, at an internet protocol layer of the first user equipment, the first set and the second set.

[0149] The method may also include aggregating, at the internet protocol layer, the set of data based at least in part on the first set and the second set.

[0150] The second base station may be disconnected from the server.

[0151] The second base station may receive the second set from the first base station.

[0152] The second base station may receive the second set from the server.

[0153] The second base station may receive the data from the server.

[0154] The method may also include receiving, at a first user equipment of a group of user equipments, data from a base station and receiving, at the first user equipment, a control element that includes a user equipment identifier associated with a set of user equipment of the group of user equipments. The set of user equipment may include at least one user equipment that is disconnected from the base station. The method may also include transmitting, based on the user equipment identifier, a first set of the data to the set of user equipment.

[0155] The method may also include generating, at an internet protocol network layer of the first user equipment, the first set of the data based at least in part on the user equipment identifier.

[0156] The method may also include receiving, at the first user equipment, a second control element that includes a second user equipment identifier associated with a second set of user

equipment. The group of user equipments may include the second set of user equipment. The method may also include transmitting the second control element to the second set of user equipment based on the second user equipment identifier.

[0157] The method may also include transmitting the control element to the set of user equipment based on the user equipment identifier.

[0158] The method may also include transmitting the control element to a second user equipment based on the user equipment identifier and causing the second user equipment to transmit the control element to the at least one user equipment. The set of user equipment may include the second user equipment.

[0159] The method may also include receiving, at the first user equipment, a third control element associated with a third set of user equipment of the group of user equipments. The third set of user equipment may receive the third control element from the base station.

[0160] In yet another embodiment, a method includes receiving a set of membership criteria associated with a group of user equipments and receiving a set of user equipment attributes associated with a user equipment. The method also includes receiving a reference signal associated with the group of user equipments based on the set of membership criteria and at least one of the set of user equipment attributes and establishing a connection with at least one user equipment of the group of user equipments based on the reference signal.

[0161] The method may also include transmitting the set of user equipment attributes to the at least one user equipment based on establishing the connection and receiving a set of group attributes associated with the group of user equipments.

[0162] The set of group attributes may include a set of communication frequencies, a set of communication protocols, or both.

[0163] The method may also include transmitting a keep-alive request to the at least one user equipment based on an elapsed time from establishing the connection exceeding a threshold time period.

[0164] The method may also include transmitting an exit request to the at least one user equipment; and causing the at least one user equipment to terminate the connection.

[0165] The set of user equipment attributes may include a battery level associated with the user equipment, a geographical location associated with the user equipment, a power connection associated with the user equipment, or any combination thereof. The set of criteria may include a battery threshold, an electrical power connection, a time window, a geographical area, a set of user equipment capabilities, or any combination thereof.

[0166] The connection may include a user equipment-to-user equipment connection, a network connection, or both.

[0167] In yet another embodiment, a method includes receiving, at a first user equipment of a group of user equipments, a set of paging identifiers associated with a set of user equipment of the group of user equipments and receiving, at the first user equipment, a first paging message associated with at least one user equipment of the set of user equipment. The method also includes transmitting, via user equipment-to-user equipment communication, the first paging message to at least one user equipment of the at least one user equipment based on the set of paging identifiers.

[0168] The first user equipment may include a first Subscriber Identification Module (SIM) card associated with a first carrier and a second SIM card associated with a second carrier.

[0169] The method may also include receiving, at the first user equipment, a first set of data from a first base station associated with the first carrier and receiving, at the first user equipment, a second set of data from a second base station associated with the second carrier.

[0170] The second base station may be disconnected from a server.

[0171] The second base station may receive the second set of data from the first base station.

[0172] The method may also include receiving, at the first user equipment, a paging identifier associated with a second user equipment. The group of user equipments may include the second

user equipment.

[0173] The method may also include receiving, at the first user equipment, a second paging message and transmitting the second paging message to the second user equipment based at least in part on the paging identifier and the second paging message.

[0174] In yet another embodiment, a method includes receiving, at a first base station associated with a first carrier, a first set of data from a server. The first set may include a first radio bearer associated with signaling data. The method also includes transmitting the first set of data to a user equipment communicatively coupled to the first base station. The user equipment may receive a second set of data user equipment from a second base station associated with a second carrier. The second set may include a second radio bearer.

[0175] The method may also include receiving, at the first base station, the data from the server and determining, at the first base station, that the second base station is disconnected from the server. The method may also include transmitting the second set to the second base station.

[0176] The method may also include causing the second base station to send the second set to the user equipment.

[0177] The method may also include determining, at the first base station, the user equipment is disconnected from the first base station and determining, at the first base station, the user equipment is communicatively coupled to the second base station. The method may also include transmitting the first set to the second base station.

[0178] The method may also include causing the second base station to transmit the first set to the user equipment.

[0179] The second base station may receive the second set from the server.

[0180] The specific embodiments described above have been shown by way of example, and it should be understood that these embodiments may be susceptible to various modifications and alternative forms. It should be further understood that the claims are not intended to be limited to the particular forms disclosed, but rather to cover all modifications, equivalents, and alternatives falling within the spirit and scope of this disclosure.

[0181] The techniques presented and claimed herein are referenced and applied to material objects and concrete examples of a practical nature that demonstrably improve the present technical field and, as such, are not abstract, intangible or purely theoretical. Further, if any claims appended to the end of this specification contain one or more elements designated as “means for [perform]ing [a function] . . . ” or “step for [perform]ing [a function] . . . ,” it is intended that such elements are to be interpreted under 35 U.S.C. 112(f). However, for any claims containing elements designated in any other manner, it is intended that such elements are not to be interpreted under 35 U.S.C. 112(f).

[0182] It is well understood that the use of personally identifiable information should follow privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining the privacy of users. In particular, personally identifiable information data should be managed and handled so as to minimize risks of unintentional or unauthorized access or use, and the nature of authorized use should be clearly indicated to users.

Claims

1. A method, comprising: receiving, at a first user equipment of a group of user equipments, a request for data from a target user equipment, wherein the group of user equipments comprises the target user equipment; receiving, at the first user equipment, a first data set associated with the data from a server via a first base station; receiving, at the first user equipment, a second data set associated with the data from the server via a second base station; assembling, at the first user equipment, the data based at least in part on the first data set and the second data set; and causing, at the first user equipment, transmission of the data to the target user equipment, the target user

equipment being disconnected from the first base station, the second base station, or both.

2. The method of claim 1, comprising receiving, via a device-to-device communication link from a second user equipment, a third data set associated with the data at the first user equipment, the second user equipment being communicatively coupled to the first base station, the second base station, or both, the group of user equipments comprising the second user equipment.
3. The method of claim 2, wherein causing, at the first user equipment, transmission of the data to the target user equipment comprises causing, via the device-to-device communication link, transmission of the first data set, the second data set, the data, or any combination thereof to the second user equipment.
4. The method of claim 2, comprising assembling, at the first user equipment, the data based at least in part on the first data set, the second data set, and the third data set.
5. The method of claim 1, comprising: receiving, at the first user equipment, second data; and causing, via a device-to-device communication link to a second user equipment, transmission of a data set associated with the second data.
6. The method of claim 5, comprising causing, at the first user equipment, transmission of the second data, the data set of the second data, or both to the first base station, the second base station, or both, wherein the second data is received at the first user equipment via a second device-to-device communication link from a third user equipment.
7. The method of claim 5, comprising: causing, via the device-to-device communication link to the second user equipment, transmission of the second data, wherein the second data comprises routing information having a path for transmission of the second data, and wherein the routing information is configured to cause the second user equipment to send the second data to the first base station; and based on the routing information, causing the second user equipment to send the second data to the first base station, the second base station, or both.
8. A non-transitory, computer-readable medium comprising instructions, that when executed by processing circuitry, cause the processing circuitry to: receive a request for data from a target user equipment; receive a first data set associated with the data from a first base station; receive a second data set associated with the data from a second base station; assemble the data based at least in part on the first data set and the second data set; and prepare the data for transmission to the target user equipment, the target user equipment being disconnected from the first base station, the second base station, or both.
9. The non-transitory, computer-readable medium of claim 8, wherein the instructions, when executed, cause the processing circuitry to: receive a third data set associated with the data from a first user equipment; and assemble the data based at least in part on the first data set, the second data set, and the third data set.
10. The non-transitory, computer-readable medium of claim 9, wherein the instructions, when executed, cause the processing circuitry to prepare the first data set, the second data set, the data, or any combination thereof for transmission to the first user equipment.
11. The non-transitory, computer-readable medium of claim 10, wherein the instructions, when executed, cause the processing circuitry to cause the first user equipment to assemble the data based at least in part on the first data set, the second data set, and the third data set.
12. The non-transitory, computer-readable medium of claim 8, wherein the instructions, when executed, cause the processing circuitry to: receive second data; and prepare a data set associated with the second data for transmission to a first user equipment.
13. The non-transitory, computer-readable medium of claim 12, wherein the instructions, when executed, cause the processing circuitry to cause the first user equipment to send the data set associated with the second data to the first base station, the second base station, or both.
14. The non-transitory, computer-readable medium of claim 12, wherein the instructions, when executed, cause the processing circuitry to prepare the second data for transmission to the first user equipment, wherein the second data comprises routing information having a path for transmission

of the second data.

15. The non-transitory, computer-readable medium of claim 14, wherein the instructions, when executed, cause the processing circuitry to cause the first user equipment to send the second data to the first base station, the second base station, or both, based on the routing information.

16. Processing circuitry coupled to a transmitter and a receiver, the processing circuitry configured to: cause the receiver to receive a request for data from a target user equipment, wherein a group of user equipments comprises the target user equipment; cause the receiver to receive a first data set associated with the data from a first base station; cause the receiver to receive a second data set associated with the data from a second base station; assemble the data based at least in part on the first data set and the second data set; and cause the transmitter to transmit the data, or any combination thereof to the target user equipment, the target user equipment being disconnected from the first base station, the second base station, or both.

17. The processing circuitry of claim 16, wherein the processing circuitry is configured to cause the receiver to receive a third data set associated with the data from a second user equipment.

18. The processing circuitry of claim 17, wherein the group of user equipments comprises the second user equipment.

19. The processing circuitry of claim 17, wherein the processing circuitry is configured to cause the second user equipment to send the data to the target user equipment assemble the data based at least in part on the first data set, the second data set, and the third data set.

20. The processing circuitry of claim 16, wherein the processing circuitry is configured to cause the transmitter to transmit the first data set, the second data set, the data, or any combination thereof to a second user equipment.
