

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402825
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Scharf; Christoph et al.

Cardiac analysis user interface system and method

Abstract

Methods of generating a graphical representation of cardiac information on a display screen are provided. The method comprises: electronically creating or acquiring an anatomical model of the heart including multiple cardiac locations; electronically determining a data set of source information corresponding to cardiac activity at the multiple cardiac locations; electronically rendering the data set of source information in relation to the multiple cardiac locations on the display screen. Systems and devices for providing a graphical representation of cardiac information are also provided.

Inventors: Scharf; Christoph (Horgen, CH), Beatty; Graydon E. (Bloomington, MN), Scharf; Gunter (Zurich, CH), Werneth; Randell L. (Boise, ID), Corvi; Timothy J. (Carlsbad, CA), Flaherty; J. Christopher (Auburndale, FL), Flaherty; Maxwell R. (Auburndale, FL)

Applicant: ENCHANNEL MEDICAL, LTD. (Irvine, CA)

Family ID: 54196289

Assignee: ENCHANNEL MEDICAL, LTD. (Irvine, CA)

Appl. No.: 18/582299

Filed: February 20, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250017508 A1	Jan. 16, 2025

Related U.S. Application Data

continuation parent-doc US 17578522 20220119 US 11931157 child-doc US 18582299
continuation parent-doc US 15128563 US 11278231 20220322 WO PCT/US2015/022187

Publication Classification

Int. Cl.: **A61B90/00** (20160101); **A61B5/00** (20060101); **A61B5/287** (20210101); **A61B5/339** (20210101); **A61B8/00** (20060101); **A61B8/12** (20060101); **A61B18/14** (20060101); **A61B5/318** (20210101); **A61B18/00** (20060101)

U.S. Cl.:

CPC **A61B5/339** (20210101); **A61B5/287** (20210101); **A61B5/6858** (20130101); **A61B5/7425** (20130101); **A61B5/743** (20130101); **A61B8/12** (20130101); **A61B8/445** (20130101); **A61B8/4483** (20130101); **A61B18/1492** (20130101); **A61B90/37** (20160201); **A61B5/318** (20210101); **A61B2018/00148** (20130101); **A61B2018/00267** (20130101); **A61B2018/00357** (20130101); **A61B2018/00577** (20130101); **A61B2505/05** (20130101); **A61B2576/023** (20130101)

Field of Classification Search

CPC: **A61B** (18/1492); **A61B** (2018/00148); **A61B** (2018/00267); **A61B** (2018/00357); **A61B** (2018/00577); **A61B** (2505/05); **A61B** (2576/023); **A61B** (5/287); **A61B** (5/318); **A61B** (5/339); **A61B** (5/6858); **A61B** (5/7425); **A61B** (5/743); **A61B** (8/12); **A61B** (8/445); **A61B** (8/4483); **A61B** (90/37); **G16H** (30/40)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4173228	12/1978	Van Steenwyk et al.	N/A	N/A
4841977	12/1988	Griffith et al.	N/A	N/A
5020540	12/1990	Chamoun	N/A	N/A
5041973	12/1990	Lebron et al.	N/A	N/A
5156151	12/1991	Imran	N/A	N/A
5293868	12/1993	Nardella	N/A	N/A
5482472	12/1995	Garoni et al.	N/A	N/A
5499981	12/1995	Kordis	N/A	N/A
5555883	12/1995	Avitall	N/A	N/A
5595183	12/1996	Swanson et al.	N/A	N/A
5601084	12/1996	Sheehan et al.	N/A	N/A
5647367	12/1996	Lum et al.	N/A	N/A
5662108	12/1996	Budd et al.	N/A	N/A
5722402	12/1997	Swanson et al.	N/A	N/A
5722416	12/1997	Swanson et al.	N/A	N/A
5740808	12/1997	Panescu et al.	N/A	N/A
5749833	12/1997	Hakki et al.	N/A	N/A
5759158	12/1997	Swanson	N/A	N/A
5782239	12/1997	Webster, Jr.	N/A	N/A
5795298	12/1997	Vesley et al.	N/A	N/A

5795299	12/1997	Eaton et al.	N/A	N/A
5820568	12/1997	Willis	N/A	N/A
5830144	12/1997	Vesely	N/A	N/A
5846198	12/1997	Killmann	N/A	N/A
5876336	12/1998	Swanson et al.	N/A	N/A
5928228	12/1998	Kordis et al.	N/A	N/A
5944022	12/1998	Nardella et al.	N/A	N/A
5968040	12/1998	Swanson et al.	N/A	N/A
6014590	12/1999	Whayne et al.	N/A	N/A
6024703	12/1999	Zanelli et al.	N/A	N/A
6066096	12/1999	Smith et al.	N/A	N/A
6086532	12/1999	Panescu et al.	N/A	N/A
6107699	12/1999	Swanson	N/A	N/A
6115626	12/1999	Whayne et al.	N/A	N/A
6187032	12/2000	Ohyu et al.	N/A	N/A
6188928	12/2000	Noren et al.	N/A	N/A
6216027	12/2000	Willis et al.	N/A	N/A
6216043	12/2000	Swanson et al.	N/A	N/A
6240307	12/2000	Beatty et al.	N/A	N/A
6277077	12/2000	Briskin et al.	N/A	N/A
6301496	12/2000	Reisfeld	N/A	N/A
6396198	12/2001	Okimura et al.	N/A	N/A
6400981	12/2001	Govari	N/A	N/A
6490474	12/2001	Willis et al.	N/A	N/A
6514249	12/2002	Maguire et al.	N/A	N/A
6556695	12/2002	Packer et al.	N/A	N/A
6574492	12/2002	Ben-Haim et al.	N/A	N/A
6640119	12/2002	Budd et al.	N/A	N/A
6695785	12/2003	Briskin et al.	N/A	N/A
6716166	12/2003	Govari	N/A	N/A
6728562	12/2003	Budd et al.	N/A	N/A
6772004	12/2003	Rudy	N/A	N/A
6773402	12/2003	Govari et al.	N/A	N/A
6824515	12/2003	Suorsa et al.	N/A	N/A
6826420	12/2003	Beatty et al.	N/A	N/A
6826421	12/2003	Beatty et al.	N/A	N/A
6839588	12/2004	Rudy	N/A	N/A
6895267	12/2004	Panescu et al.	N/A	N/A
6939309	12/2004	Beatty et al.	N/A	N/A
6950689	12/2004	Willis et al.	N/A	N/A
6970733	12/2004	Willis et al.	N/A	N/A
6978168	12/2004	Beatty et al.	N/A	N/A
6990370	12/2005	Beatty et al.	N/A	N/A
7187964	12/2006	Khoury	N/A	N/A
7187973	12/2006	Hauck	N/A	N/A
7258674	12/2006	Hillstead et al.	N/A	N/A
7263397	12/2006	Hauck et al.	N/A	N/A
7285094	12/2006	Nohara et al.	N/A	N/A
7285119	12/2006	Stewart et al.	N/A	N/A
7289843	12/2006	Beatty et al.	N/A	N/A

7291146	12/2006	Steinke et al.	N/A	N/A
7351914	12/2007	Kaneto et al.	N/A	N/A
7479141	12/2008	Kleen et al.	N/A	N/A
7505810	12/2008	Harlev et al.	N/A	N/A
7536218	12/2008	Govari et al.	N/A	N/A
7573182	12/2008	Savage	N/A	N/A
7689261	12/2009	Mohr et al.	N/A	N/A
7715907	12/2009	Koertge et al.	N/A	N/A
7766838	12/2009	Yagi et al.	N/A	N/A
7841986	12/2009	He et al.	N/A	N/A
7848789	12/2009	Govari et al.	N/A	N/A
7918793	12/2010	Altmann et al.	N/A	N/A
7953475	12/2010	Harlev et al.	N/A	N/A
8086303	12/2010	Zhang et al.	N/A	N/A
8103327	12/2011	Harlev et al.	N/A	N/A
8147486	12/2011	Honour et al.	N/A	N/A
8150499	12/2011	Gelbart et al.	N/A	N/A
8155756	12/2011	Yang et al.	N/A	N/A
8175680	12/2011	Panescu	N/A	N/A
8200314	12/2011	Bladen et al.	N/A	N/A
8208998	12/2011	Beatty et al.	N/A	N/A
8221411	12/2011	Francischelli et al.	N/A	N/A
8233972	12/2011	Zhang	N/A	N/A
8290575	12/2011	Tarassenko et al.	N/A	N/A
8311613	12/2011	Danehorn	N/A	N/A
8320711	12/2011	Altmann et al.	N/A	N/A
8346339	12/2012	Kordis et al.	N/A	N/A
8360786	12/2012	Duryea	N/A	N/A
8364234	12/2012	Kordis et al.	N/A	N/A
8412307	12/2012	Willis et al.	N/A	N/A
8417313	12/2012	Scharf et al.	N/A	N/A
8428690	12/2012	Li et al.	N/A	N/A
8447377	12/2012	Harlev et al.	N/A	N/A
8454596	12/2012	Ma et al.	N/A	N/A
8465433	12/2012	Zwirn	N/A	N/A
8478388	12/2012	Nguyen et al.	N/A	N/A
8512255	12/2012	Scharf et al.	N/A	N/A
8571647	12/2012	Harlev et al.	N/A	N/A
8583228	12/2012	Li et al.	N/A	N/A
8641705	12/2013	Leo et al.	N/A	N/A
8700119	12/2013	Scharf et al.	N/A	N/A
8740840	12/2013	Foley et al.	N/A	N/A
8755861	12/2013	Harlev et al.	N/A	N/A
8825130	12/2013	Just et al.	N/A	N/A
8825134	12/2013	Danehorn	N/A	N/A
8903488	12/2013	Callas et al.	N/A	N/A
8903510	12/2013	Rosenberg et al.	N/A	N/A
8918158	12/2013	Scharf et al.	N/A	N/A
8929975	12/2014	Zhang et al.	N/A	N/A
8934988	12/2014	Persson et al.	N/A	N/A

8948837	12/2014	Harlev et al.	N/A	N/A
8968299	12/2014	Kauphusman et al.	N/A	N/A
8979839	12/2014	De La Rama et al.	N/A	N/A
8986207	12/2014	Li et al.	N/A	N/A
8989842	12/2014	Li et al.	N/A	N/A
9002442	12/2014	Harley et al.	N/A	N/A
9005198	12/2014	Long et al.	N/A	N/A
9011423	12/2014	Brewster et al.	N/A	N/A
9023027	12/2014	Bar-Tal et al.	N/A	N/A
9026196	12/2014	Curran et al.	N/A	N/A
9031642	12/2014	Ghosh	N/A	N/A
9037259	12/2014	Mathur	N/A	N/A
9044245	12/2014	Condie et al.	N/A	N/A
9113807	12/2014	Koyrakh et al.	N/A	N/A
9167982	12/2014	Scharf et al.	N/A	N/A
9173638	12/2014	Govari et al.	N/A	N/A
9186081	12/2014	Afonso et al.	N/A	N/A
9186212	12/2014	Nabutovsky et al.	N/A	N/A
9192318	12/2014	Scharf et al.	N/A	N/A
9220425	12/2014	Shachar et al.	N/A	N/A
9220432	12/2014	Bukhman	N/A	N/A
9241687	12/2015	McGee	N/A	N/A
9271680	12/2015	Dubois et al.	N/A	N/A
9314620	12/2015	Long et al.	N/A	N/A
9351789	12/2015	Novichenok et al.	N/A	N/A
D758596	12/2015	Perryman et al.	N/A	N/A
9358398	12/2015	Moffitt et al.	N/A	N/A
9380953	12/2015	Houben et al.	N/A	N/A
9456759	12/2015	Lian et al.	N/A	N/A
9474486	12/2015	Eliason et al.	N/A	N/A
9480525	12/2015	Lopes et al.	N/A	N/A
9486355	12/2015	Gustus et al.	N/A	N/A
9492227	12/2015	Lopes et al.	N/A	N/A
9492228	12/2015	Lopes et al.	N/A	N/A
9498192	12/2015	Hashimshony et al.	N/A	N/A
9504395	12/2015	Scharf et al.	N/A	N/A
9526573	12/2015	Lopes et al.	N/A	N/A
9549708	12/2016	Mercanzini et al.	N/A	N/A
9560982	12/2016	Kordis et al.	N/A	N/A
9579149	12/2016	Kelly et al.	N/A	N/A
D782686	12/2016	Werneth et al.	N/A	N/A
9585588	12/2016	Marecki et al.	N/A	N/A
9591990	12/2016	Chen et al.	N/A	N/A
9603651	12/2016	Ghosh	N/A	N/A
9610024	12/2016	Scharf et al.	N/A	N/A
9662033	12/2016	Severino	N/A	N/A
9675266	12/2016	Afonso et al.	N/A	N/A
9689759	12/2016	Fandrey et al.	N/A	N/A
9693699	12/2016	Spector et al.	N/A	N/A
9713730	12/2016	Mathur et al.	N/A	N/A

9717555	12/2016	Chan et al.	N/A	N/A
9717559	12/2016	Ditter et al.	N/A	N/A
9730602	12/2016	Harlev et al.	N/A	N/A
9757044	12/2016	Scharf et al.	N/A	N/A
9775578	12/2016	Katz	N/A	N/A
9827039	12/2016	Dandler et al.	N/A	N/A
9833161	12/2016	Govari	N/A	N/A
9888862	12/2017	Harlev et al.	N/A	N/A
9901303	12/2017	Olson	N/A	N/A
9913589	12/2017	Scharf et al.	N/A	N/A
9955917	12/2017	Bitzer	N/A	N/A
9968268	12/2017	Scharf et al.	N/A	N/A
10004459	12/2017	Werneth et al.	N/A	N/A
10028706	12/2017	Brockway et al.	N/A	N/A
10045706	12/2017	Geistert et al.	N/A	N/A
10045707	12/2017	Govari	N/A	N/A
10049771	12/2017	Voth et al.	N/A	N/A
10082395	12/2017	Koyrakh et al.	N/A	N/A
10135815	12/2017	Lecun et al.	N/A	N/A
10201311	12/2018	Chou et al.	N/A	N/A
10258249	12/2018	Talkachova et al.	N/A	N/A
10296707	12/2018	Passerini et al.	N/A	N/A
10299692	12/2018	Kalinin et al.	N/A	N/A
D851774	12/2018	Werneth et al.	N/A	N/A
10314497	12/2018	Scharf et al.	N/A	N/A
10335051	12/2018	Harlev et al.	N/A	N/A
10362955	12/2018	Arunachalam et al.	N/A	N/A
10376171	12/2018	Scharf et al.	N/A	N/A
10405828	12/2018	Deladi et al.	N/A	N/A
10413206	12/2018	Scharf et al.	N/A	N/A
10424045	12/2018	Park et al.	N/A	N/A
10456056	12/2018	Govari et al.	N/A	N/A
10463267	12/2018	Scharf et al.	N/A	N/A
10506948	12/2018	Wodlinger et al.	N/A	N/A
10517670	12/2018	Bar-Tal et al.	N/A	N/A
10593234	12/2019	Zhu et al.	N/A	N/A
10621790	12/2019	Perlman et al.	N/A	N/A
10653318	12/2019	Welsh et al.	N/A	N/A
10667753	12/2019	Werneth et al.	N/A	N/A
10728242	12/2019	Lecun et al.	N/A	N/A
10828011	12/2019	Werneth et al.	N/A	N/A
10842561	12/2019	Viswanathan et al.	N/A	N/A
10856827	12/2019	Katz	N/A	N/A
11013444	12/2020	Scharf et al.	N/A	N/A
11033329	12/2020	Stewart et al.	N/A	N/A
11096741	12/2020	Govari et al.	N/A	N/A
11179112	12/2020	Li et al.	N/A	N/A
11179199	12/2020	Everling	N/A	N/A
11278209	12/2021	Scharf et al.	N/A	N/A
11278231	12/2021	Scharf	N/A	A61B 5/743

11344366	12/2021	Chou et al.	N/A	N/A
D954970	12/2021	Werneth et al.	N/A	N/A
11839481	12/2022	Severino	N/A	N/A
11931157	12/2023	Scharf	N/A	A61B 18/1492
2001/0007070	12/2000	Stewart et al.	N/A	N/A
2002/0026118	12/2001	Govari	N/A	N/A
2002/0045810	12/2001	Ben-Haim	N/A	N/A
2002/0099292	12/2001	Briskén et al.	N/A	N/A
2002/0128565	12/2001	Rudy	N/A	N/A
2002/0165441	12/2001	Coleman et al.	N/A	N/A
2003/0036696	12/2002	Willis et al.	N/A	N/A
2003/0065271	12/2002	Khoury	N/A	N/A
2003/0078494	12/2002	Panescu et al.	N/A	N/A
2003/0120318	12/2002	Hauck	N/A	N/A
2003/0153907	12/2002	Suorsa et al.	N/A	N/A
2003/0158477	12/2002	Panescu	N/A	N/A
2003/0163046	12/2002	Nohara et al.	N/A	N/A
2003/0176799	12/2002	Beatty et al.	N/A	N/A
2003/0231789	12/2002	Willis et al.	N/A	N/A
2003/0236466	12/2002	Tarjan et al.	N/A	N/A
2004/0039312	12/2003	Hillstead et al.	N/A	N/A
2004/0082870	12/2003	Rudy et al.	N/A	N/A
2004/0082948	12/2003	Stewart et al.	N/A	N/A
2004/0113498	12/2003	Kroenke	N/A	N/A
2004/0254437	12/2003	Hauck et al.	N/A	N/A
2005/0059880	12/2004	Mathias et al.	N/A	N/A
2005/0101874	12/2004	Beatty et al.	N/A	N/A
2005/0113665	12/2004	Mohr et al.	N/A	N/A
2005/0148836	12/2004	Kleen et al.	N/A	N/A
2005/0203375	12/2004	Willis et al.	N/A	N/A
2005/0267453	12/2004	Wong et al.	N/A	N/A
2006/0052716	12/2005	Beatty et al.	N/A	N/A
2006/0058663	12/2005	Willis et al.	N/A	N/A
2006/0058676	12/2005	Yagi et al.	N/A	N/A
2006/0058692	12/2005	Beatty et al.	N/A	N/A
2006/0058693	12/2005	Beatty et al.	N/A	N/A
2006/0084884	12/2005	Beatty et al.	N/A	N/A
2006/0084970	12/2005	Beatty et al.	N/A	N/A
2006/0084971	12/2005	Beatty et al.	N/A	N/A
2006/0084972	12/2005	Beatty et al.	N/A	N/A
2006/0116576	12/2005	McGee et al.	N/A	N/A
2006/0244177	12/2005	Kaneto et al.	N/A	N/A
2007/0016007	12/2006	Govari et al.	N/A	N/A
2007/0055150	12/2006	Donaldson et al.	N/A	N/A
2007/0060832	12/2006	Levin	N/A	N/A
2007/0083194	12/2006	Kunis et al.	N/A	N/A
2007/0106146	12/2006	Altmann et al.	N/A	N/A
2007/0167722	12/2006	Bladen et al.	N/A	N/A
2007/0232949	12/2006	Saksena	N/A	N/A

2008/0009758	12/2007	Voth	N/A	N/A
2008/0146937	12/2007	Lee et al.	N/A	N/A
2008/0214945	12/2007	Koertge et al.	N/A	N/A
2008/0221438	12/2007	Chen et al.	N/A	N/A
2008/0281216	12/2007	Zhang et al.	N/A	N/A
2008/0287777	12/2007	Li et al.	N/A	N/A
2008/0300487	12/2007	Govari et al.	N/A	N/A
2008/0319297	12/2007	Danehorn	N/A	N/A
2009/0024086	12/2008	Zhang et al.	N/A	N/A
2009/0076483	12/2008	Danehorn	N/A	N/A
2009/0082691	12/2008	Denison et al.	N/A	N/A
2009/0131930	12/2008	Gelbart et al.	N/A	N/A
2009/0143651	12/2008	Kallback et al.	N/A	N/A
2009/0148012	12/2008	Altmann et al.	N/A	N/A
2009/0157136	12/2008	Yang et al.	N/A	N/A
2009/0171274	12/2008	Harlev et al.	N/A	N/A
2009/0203992	12/2008	Govari et al.	N/A	N/A
2009/0259266	12/2008	Zhang et al.	N/A	N/A
2009/0264781	12/2008	Scharf et al.	N/A	N/A
2010/0023004	12/2009	Francischelli et al.	N/A	N/A
2010/0049069	12/2009	Tarassenko et al.	N/A	N/A
2010/0076426	12/2009	de la Rama et al.	N/A	N/A
2010/0094279	12/2009	Kauphusman et al.	N/A	N/A
2010/0168578	12/2009	Garson, Jr. et al.	N/A	N/A
2010/0198041	12/2009	Christian et al.	N/A	N/A
2010/0256627	12/2009	Ma et al.	N/A	N/A
2010/0279263	12/2009	Duryea	N/A	N/A
2010/0286551	12/2009	Harlev et al.	N/A	N/A
2010/0298690	12/2009	Scharf et al.	N/A	N/A
2010/0298826	12/2009	Leo et al.	N/A	N/A
2010/0305462	12/2009	Callas et al.	N/A	N/A
2011/0028894	12/2010	Foley et al.	N/A	N/A
2011/0045130	12/2010	Edens et al.	N/A	N/A
2011/0077526	12/2010	Zwirn	N/A	N/A
2011/0092809	12/2010	Nguyen et al.	N/A	N/A
2011/0112379	12/2010	Li et al.	N/A	N/A
2011/0118726	12/2010	De La Rama et al.	N/A	N/A
2011/0125172	12/2010	Gelbart et al.	N/A	N/A
2011/0144510	12/2010	Ryu et al.	N/A	N/A
2011/0166613	12/2010	Li et al.	N/A	N/A
2011/0172658	12/2010	Gelbart et al.	N/A	N/A
2011/0184274	12/2010	Rosenberg et al.	N/A	N/A
2011/0190659	12/2010	Long et al.	N/A	N/A
2011/0201951	12/2010	Zhang	N/A	N/A
2011/0213231	12/2010	Hall et al.	N/A	N/A
2011/0224540	12/2010	Hauck et al.	N/A	N/A
2011/0230775	12/2010	Barley et al.	N/A	N/A
2011/0270237	12/2010	Werneth et al.	N/A	N/A
2012/0078077	12/2011	Harlev et al.	N/A	N/A
2012/0082969	12/2011	Schwartz et al.	N/A	N/A

2012/0123296	12/2011	Hashimshony et al.	N/A	N/A
2012/0136231	12/2011	Markel	N/A	N/A
2012/0143298	12/2011	Just et al.	N/A	N/A
2012/0165667	12/2011	Altmann et al.	N/A	N/A
2012/0172702	12/2011	Koyrakh et al.	N/A	N/A
2012/0172859	12/2011	Condie et al.	N/A	N/A
2012/0184858	12/2011	Harley et al.	N/A	N/A
2012/0184863	12/2011	Harlev et al.	N/A	N/A
2012/0220998	12/2011	Long et al.	N/A	N/A
2012/0265054	12/2011	Olson	N/A	N/A
2012/0271138	12/2011	Kordis et al.	N/A	N/A
2012/0271139	12/2011	Kordis et al.	N/A	N/A
2012/0277574	12/2011	Panescu	N/A	N/A
2012/0302912	12/2011	Moffitt et al.	N/A	N/A
2012/0310064	12/2011	McGee	N/A	N/A
2013/0006238	12/2012	Ditter et al.	N/A	N/A
2013/0085361	12/2012	Mercanzini et al.	N/A	N/A
2013/0096432	12/2012	Hauck	N/A	N/A
2013/0158537	12/2012	Deladi et al.	N/A	N/A
2013/0165916	12/2012	Mathur	N/A	N/A
2013/0172715	12/2012	Just et al.	N/A	N/A
2013/0190587	12/2012	Lopes et al.	N/A	N/A
2013/0197614	12/2012	Gustus et al.	N/A	N/A
2013/0204311	12/2012	Kunis	N/A	N/A
2013/0225983	12/2012	Willis et al.	N/A	N/A
2013/0226017	12/2012	Scharf et al.	N/A	N/A
2013/0241929	12/2012	Massarwa et al.	N/A	N/A
2013/0245433	12/2012	Deladi et al.	N/A	N/A
2013/0245621	12/2012	Persson et al.	N/A	N/A
2013/0253298	12/2012	Harlev et al.	N/A	N/A
2013/0267853	12/2012	Dausch et al.	N/A	N/A
2013/0274582	12/2012	Afonso et al.	N/A	N/A
2013/0282084	12/2012	Mathur et al.	N/A	N/A
2013/0304062	12/2012	Chan et al.	N/A	N/A
2013/0304065	12/2012	Lopes et al.	N/A	N/A
2013/0310827	12/2012	Brewster et al.	N/A	N/A
2013/0324871	12/2012	Dubois et al.	N/A	N/A
2013/0330701	12/2012	Rubinstein et al.	N/A	N/A
2014/0024910	12/2013	Scharf et al.	N/A	N/A
2014/0068740	12/2013	LeCun et al.	N/A	N/A
2014/0081114	12/2013	Shachar et al.	N/A	N/A
2014/0081264	12/2013	Fandrey et al.	N/A	N/A
2014/0095105	12/2013	Koyrakh et al.	N/A	N/A
2014/0100563	12/2013	Govari et al.	N/A	N/A
2014/0121470	12/2013	Scharf et al.	N/A	N/A
2014/0148677	12/2013	Liempde et al.	N/A	N/A
2014/0180150	12/2013	Scharf et al.	N/A	N/A
2014/0200429	12/2013	Spector et al.	N/A	N/A
2014/0200489	12/2013	Behar et al.	N/A	N/A
2014/0221803	12/2013	Bar-Tal et al.	N/A	N/A

2014/0235988	12/2013	Ghosh	N/A	N/A
2014/0235989	12/2013	Wodlinger et al.	N/A	N/A
2014/0249505	12/2013	Bukhman	N/A	N/A
2014/0257069	12/2013	Eliason et al.	N/A	N/A
2014/0257071	12/2013	Curran et al.	N/A	N/A
2014/0275921	12/2013	Harlev et al.	N/A	N/A
2014/0276733	12/2013	VanScoy et al.	N/A	N/A
2014/0276746	12/2013	Nabutovsky et al.	N/A	N/A
2014/0276789	12/2013	Dandler et al.	N/A	N/A
2014/0278129	12/2013	Voth et al.	N/A	N/A
2014/0303469	12/2013	Kordis et al.	N/A	N/A
2014/0358143	12/2013	Novichenok et al.	N/A	N/A
2014/0366113	12/2013	Lecun et al.	N/A	N/A
2014/0378803	12/2013	Geistert et al.	N/A	N/A
2015/0038862	12/2014	Gijsbers et al.	N/A	N/A
2015/0045647	12/2014	Katz	N/A	N/A
2015/0080752	12/2014	Lian et al.	N/A	N/A
2015/0196217	12/2014	Harlev et al.	N/A	N/A
2015/0196219	12/2014	Scharf et al.	N/A	N/A
2015/0208938	12/2014	Houben et al.	N/A	N/A
2015/0223757	12/2014	Werneth	600/301	A61B 5/283
2015/0223863	12/2014	Ghosh	N/A	N/A
2015/0257732	12/2014	Ryan	N/A	N/A
2015/0257825	12/2014	Kelly et al.	N/A	N/A
2015/0282729	12/2014	Harlev et al.	N/A	N/A
2015/0294082	12/2014	Passerini et al.	N/A	N/A
2015/0342491	12/2014	Marecki et al.	N/A	N/A
2015/0359484	12/2014	Bitzer	N/A	N/A
2015/0366508	12/2014	Chou et al.	N/A	N/A
2015/0374252	12/2014	de la Rama et al.	N/A	N/A
2016/0007869	12/2015	Scharf et al.	N/A	N/A
2016/0038051	12/2015	Scharf et al.	N/A	N/A
2016/0051321	12/2015	Salahieh et al.	N/A	N/A
2016/0100770	12/2015	Afonso et al.	N/A	N/A
2016/0128771	12/2015	Ditter et al.	N/A	N/A
2016/0128772	12/2015	Reinders et al.	N/A	N/A
2016/0166310	12/2015	Stewart et al.	N/A	N/A
2016/0183824	12/2015	Severino	N/A	N/A
2016/0192902	12/2015	Werneth et al.	N/A	N/A
2016/0228023	12/2015	Govari	N/A	N/A
2016/0256112	12/2015	Brockway et al.	N/A	N/A
2016/0317093	12/2015	Berenfeld et al.	N/A	N/A
2016/0338611	12/2015	Kalinin et al.	N/A	N/A
2017/0014181	12/2016	Bar-Tal et al.	N/A	N/A
2017/0035486	12/2016	Lopes et al.	N/A	N/A
2017/0042436	12/2016	Harlev et al.	N/A	N/A
2017/0065204	12/2016	Ludwin et al.	N/A	N/A
2017/0100049	12/2016	Scharf et al.	N/A	N/A
2017/0128119	12/2016	Lambert et al.	N/A	N/A
2017/0156595	12/2016	Katz	N/A	N/A

2017/0156616	12/2016	Talkachova et al.	N/A	N/A
2017/0172442	12/2016	Govari	N/A	N/A
2017/0202469	12/2016	Scharf et al.	N/A	N/A
2017/0224238	12/2016	Arunachalam et al.	N/A	N/A
2017/0258347	12/2016	Scharf et al.	N/A	N/A
2017/0311833	12/2016	Afonso et al.	N/A	N/A
2017/0319180	12/2016	Henneken et al.	N/A	N/A
2017/0319279	12/2016	Fish et al.	N/A	N/A
2017/0367580	12/2016	DiMaio et al.	N/A	N/A
2018/0055374	12/2017	Scharf et al.	N/A	N/A
2018/0085160	12/2017	Viswanathan et al.	N/A	N/A
2018/0132938	12/2017	Everling	N/A	N/A
2018/0146948	12/2017	Chou et al.	N/A	N/A
2018/0214044	12/2017	Scharf et al.	N/A	N/A
2018/0271381	12/2017	Scharf et al.	N/A	N/A
2018/0296110	12/2017	Scharf et al.	N/A	N/A
2018/0296114	12/2017	Welsh et al.	N/A	N/A
2018/0315347	12/2017	Zhu et al.	N/A	N/A
2018/0368716	12/2017	Govari et al.	N/A	N/A
2018/0374193	12/2017	Park et al.	N/A	N/A
2019/0021673	12/2018	Werneth et al.	N/A	N/A
2019/0046113	12/2018	Nikolic	N/A	N/A
2019/0124079	12/2018	Lecun et al.	N/A	N/A
2019/0159729	12/2018	Chou et al.	N/A	N/A
2019/0200886	12/2018	Welsh et al.	N/A	N/A
2019/0216525	12/2018	Stewart et al.	N/A	N/A
2019/0246930	12/2018	Zhu et al.	N/A	N/A
2019/0313910	12/2018	Vignon et al.	N/A	N/A
2019/0343401	12/2018	Scharf et al.	N/A	N/A
2020/0015876	12/2019	Chou et al.	N/A	N/A
2020/0046423	12/2019	Viswanathan et al.	N/A	N/A
2020/0121261	12/2019	Li et al.	N/A	N/A
2020/0138317	12/2019	Scharf et al.	N/A	N/A
2020/0187801	12/2019	Scharf et al.	N/A	N/A
2020/0205686	12/2019	Severino	N/A	N/A
2020/0352439	12/2019	Welsh et al.	N/A	N/A
2021/0000423	12/2020	Werneth et al.	N/A	N/A
2021/0068694	12/2020	Chou et al.	N/A	N/A
2021/0153843	12/2020	Werneth et al.	N/A	N/A
2021/0169394	12/2020	Chou et al.	N/A	N/A
2022/0095980	12/2021	Scharf et al.	N/A	N/A
2022/0202338	12/2021	Zhu et al.	N/A	N/A
2022/0226046	12/2021	Mariappan et al.	N/A	N/A
2022/0386927	12/2021	Scharf et al.	N/A	N/A
2022/0401146	12/2021	Asconeguy et al.	N/A	N/A
2023/0000361	12/2022	Scharf et al.	N/A	N/A
2023/0048656	12/2022	Chou et al.	N/A	N/A
2023/0218231	12/2022	Chou et al.	N/A	N/A
2024/0115314	12/2023	Falahatpisheh et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2825736	12/2007	CA	N/A
2829626	12/2011	CA	N/A
1856213	12/2005	CN	N/A
101048100	12/2006	CN	N/A
101254096	12/2007	CN	N/A
201223445	12/2008	CN	N/A
201275144	12/2008	CN	N/A
102770085	12/2011	CN	N/A
103354730	12/2012	CN	N/A
104462650	12/2014	CN	N/A
104812297	12/2014	CN	N/A
1125549	12/2000	EP	N/A
1166714	12/2001	EP	N/A
1415608	12/2003	EP	N/A
1760661	12/2006	EP	N/A
1779787	12/2006	EP	N/A
1852824	12/2006	EP	N/A
2051625	12/2008	EP	N/A
2252203	12/2009	EP	N/A
2491883	12/2011	EP	N/A
2683293	12/2013	EP	N/A
2711676	12/2013	EP	N/A
2818104	12/2013	EP	N/A
2954867	12/2014	EP	N/A
2953550	12/2015	EP	N/A
08501477	12/1995	JP	N/A
08504333	12/1995	JP	N/A
08164140	12/1995	JP	N/A
10137207	12/1997	JP	N/A
11504541	12/1998	JP	N/A
2000510030	12/1999	JP	N/A
2000510250	12/1999	JP	N/A
2000358299	12/1999	JP	N/A
2001070269	12/2000	JP	N/A
2001522288	12/2000	JP	N/A
2002051998	12/2001	JP	N/A
2002113004	12/2001	JP	N/A
2002522106	12/2001	JP	N/A
2003509145	12/2002	JP	N/A
2003511098	12/2002	JP	N/A
2004305704	12/2003	JP	N/A
2004350702	12/2003	JP	N/A
2005131367	12/2004	JP	N/A
2005536313	12/2004	JP	N/A
2006511296	12/2005	JP	N/A
2006525072	12/2005	JP	N/A
2007021218	12/2006	JP	N/A

2008149132	12/2007	JP	N/A
2009505737	12/2008	JP	N/A
2009135109	12/2008	JP	N/A
2009136679	12/2008	JP	N/A
2010082446	12/2009	JP	N/A
2010510851	12/2009	JP	N/A
2011504363	12/2010	JP	N/A
2011507656	12/2010	JP	N/A
2012509701	12/2011	JP	N/A
2013188476	12/2012	JP	N/A
2014503319	12/2013	JP	N/A
2014506171	12/2013	JP	N/A
2014511737	12/2013	JP	N/A
2014514031	12/2013	JP	N/A
2014516723	12/2013	JP	N/A
2015036124	12/2014	JP	N/A
2015528352	12/2014	JP	N/A
2016511026	12/2015	JP	N/A
2016123870	12/2015	JP	N/A
2016144642	12/2015	JP	N/A
2017047213	12/2016	JP	N/A
2017514553	12/2016	JP	N/A
2018534957	12/2017	JP	N/A
2018200716	12/2017	JP	N/A
2019005566	12/2018	JP	N/A
2019005572	12/2018	JP	N/A
9406349	12/1993	WO	N/A
9905971	12/1998	WO	N/A
0007501	12/1999	WO	N/A
0040166	12/1999	WO	N/A
0245608	12/2001	WO	N/A
03026722	12/2002	WO	N/A
2004026134	12/2003	WO	N/A
2006060613	12/2005	WO	N/A
2007024920	12/2006	WO	N/A
2008014629	12/2007	WO	N/A
2009065042	12/2008	WO	N/A
2009090547	12/2008	WO	N/A
2011136867	12/2010	WO	N/A
2012068471	12/2011	WO	N/A
2012087899	12/2011	WO	N/A
2012092016	12/2011	WO	N/A
2012097067	12/2011	WO	N/A
2012100184	12/2011	WO	N/A
2012100185	12/2011	WO	N/A
2012110942	12/2011	WO	N/A
2012122517	12/2011	WO	N/A
2014124231	12/2012	WO	N/A
2013101257	12/2012	WO	N/A
2013123549	12/2012	WO	N/A

2014036439	12/2013	WO	N/A
2014059308	12/2013	WO	N/A
2014130169	12/2013	WO	N/A
2014137897	12/2013	WO	N/A
2015038607	12/2014	WO	N/A
2015148470	12/2014	WO	N/A
2016183179	12/2015	WO	N/A
2016183285	12/2015	WO	N/A
2016183468	12/2015	WO	N/A
2017040581	12/2016	WO	N/A
2017053921	12/2016	WO	N/A
2017192769	12/2016	WO	N/A
2017192775	12/2016	WO	N/A
2018010659	12/2017	WO	N/A
2018071490	12/2017	WO	N/A
2018144765	12/2017	WO	N/A
2019040458	12/2018	WO	N/A
2019083982	12/2018	WO	N/A
2019144103	12/2018	WO	N/A
2019152986	12/2018	WO	N/A
2019195354	12/2018	WO	N/A
2019217430	12/2018	WO	N/A
2020097438	12/2019	WO	N/A
2020214962	12/2019	WO	N/A
2020247619	12/2019	WO	N/A
2021102230	12/2020	WO	N/A
2022178077	12/2021	WO	N/A
2023009586	12/2022	WO	N/A
2023009589	12/2022	WO	N/A
2023018937	12/2022	WO	N/A

OTHER PUBLICATIONS

Japanese Office Action dated Jan. 7, 2020 issued in Japanese Application No. 2016558799, with machine translation to English. cited by applicant

Japanese Office Action dated Jul. 23, 2019 issued in Japanese Application No. 2016542062, with machine translation to English. cited by applicant

Japanese Office Action dated Jul. 28, 2020 issued in Japanese Application No. 2018-195960, with machine translation to English. cited by applicant

Japanese Office Action dated Jun. 27, 2017 issued in Japanese Application No. 2015530101, with English translation. cited by applicant

Japanese Office Action dated Jun. 29, 2021 issued in Japanese Application No. 2020-081074, with machine translation to English. cited by applicant

Japanese Office Action dated Jun. 30, 2020 issued in Japanese Application No. 2017559317, with machine translation to English. cited by applicant

Japanese Office Action dated Mar. 10, 2020 issued in Japanese Application No. 2017559320, with machine translation to English. cited by applicant

Japanese Office Action dated Mar. 17, 2020 issued in Japanese Application No. 2019071004, with machine translation to English. cited by applicant

Japanese Office Action dated Nov. 2, 2021 issued in Japanese Application No. 2020-192741, with English translation. cited by applicant

Japanese Office Action dated Oct. 10, 2017 issued in Japanese Application No. 2015557091, with machine translation to English. cited by applicant

Japanese Office Action dated Oct. 15, 2019 issued in Japanese Application No. 2018195960, with machine translation to English. cited by applicant

Japanese Office Action dated Sep. 26, 2017 issued in Japanese Application No. 2017155346, with English translation. cited by applicant

Summons To Attend Oral Proceedings dated Dec. 20, 2019 issued in European Application No. 13763151.1. cited by applicant

Summons to Attend Oral Proceedings dated May 9, 2023 issued in European Application No. 16793622.8. cited by applicant

Cuesta-Frau et al. "Unsupervised classification of ventricular extrasystoles using bounded clustering algorithms and morphology matching", Medical & Biological Engineering & Computing, vol. 45, No. 3, Nov. 9, 2006, pp. 229-239, XP019486699, ISSN: 1741-0444. cited by applicant

Della Bella et al. "Non-contact mapping to guide catheter ablation of untolerated ventricular tachycardia" European Heart Journal, May 2002, 23(9)742-752. cited by applicant

Gupta et al. "Point of View Cardiac Mapping: Utility or Futility?", Indian Pacing and Electrophysiology Journal, vol. 2, No. 1, 2002, pp. 20-32. cited by applicant

He et al. "An equivalent body surface charge model representing three-dimensional bioelectrical activity" IEEE Transactions on Biomedical Engineering, 42.7 (Jul. 7, 1995) pp. 637-646. cited by applicant

Jackson, JD, "Surface Distributions of Charges and Dipoles and Discontinuities in the Electric Field and Potential", Classical Electrodynamics, 3rd edition, Dec. 1998, pp. 31-34. cited by applicant

Leif et al., "Geometric modeling based on polygonal meshes". Eurographics 2000 Tutorial, Aug. 21, 2000. cited by applicant

Partial European Search Report dated Apr. 29, 2014 issued in European Application No. 13176658. cited by applicant

Pullan et al. "The inverse problem of electrocardiology" Northeastern University Electrical and Computer Engineering, Feb. 23, 2007. cited by applicant

Ravelli et al. "Wave Similarity Mapping Shows the Spatiotemporal Distribution of Fibrillatory Wave Complexity in the Human Right Atrium During Paroxysmal and Chronic Atrial Fibrillation", Journal of Cardiovascular Electrophysiology, vol. 16, No. 10 (Oct. 2005) pp. 1071-1076. cited by applicant

Stevenson et al. "Recording Techniques for Clinical Electrophysiology", Journal of Cardiovascular Electrophysiology, vol. 16, No. 9, Sep. 2005, pp. 1017-1022. cited by applicant

Van Oosterom A: "Solidifying the solid angle." 2002 Journal of Electrocardiology 2002 Vol. 35 Suppl pp. 181-192 ISSN: 0022-0736. cited by applicant

Wolfgang Nolting: Elektrodynamik—Grundkurs Theoretische Physik 3, Springer Spectrum, p. 89-91. cited by applicant

Extended European Search Report dated Dec. 6, 2022 issued in European Application No. 20791578.6. cited by applicant

Extended European Search Report dated Jul. 23, 2021 issued in European Application No. 21150862.7. cited by applicant

Extended European Search Report dated Jul. 8, 2016 issued in European Application No. 14748567.6. cited by applicant

Extended European Search Report dated Mar. 14, 2017 issued in European Application No. 14843283.4. cited by applicant

Extended European Search Report dated Nov. 17, 2023 issued in European Application No. 20890919.2. cited by applicant

Extended European Search Report dated Nov. 26, 2019 issued in European Application No. 19184148.5. cited by applicant

Extended European Search Report dated Oct. 18, 2017 issued in European Application No. 15768711. cited by applicant

Extended European Search Report dated Oct. 4, 2018 issued in European Application No. 16793503.0. cited by applicant

Extended European Search Report dated Sep. 29, 2014 issued in European Application No. 13176658. cited by applicant

International Search Report and Written Opinion dated Apr. 8, 2019 issued in International Application No. PCT/US19/14498. cited by applicant

International Search Report and Written Opinion dated Aug. 11, 2016 issued in International Application No. PCT/US2016/032017. cited by applicant

International Search Report and Written Opinion dated Aug. 18, 2016 issued in International Application No. PCT/US16/32420. cited by applicant

International Search Report and Written Opinion dated Aug. 4, 2017 issued in International Application No. PCT/US17/30915. cited by applicant

International Search Report and Written Opinion dated Aug. 8, 2016 issued in European Application No. PCT/US2016/031823. cited by applicant

International Search Report and Written Opinion dated Dec. 12, 2017 issued in International Application No. PCT/US2017/056064. cited by applicant

International Search Report and Written Opinion dated Jan. 14, 2020 issued in International Application No. PCT/US2019/060433. cited by applicant

International Search Report and Written Opinion dated Jul. 21, 2020 issued in International Application No. PCT/US2020/028779. cited by applicant

International Search Report and Written Opinion dated Jul. 23, 2019 issued in International Application No. PCT/US2019/031131. cited by applicant

International Search Report and Written Opinion dated Jul. 7, 2022 issued in International Application No. PCT/US22/16722. cited by applicant

International Search Report and Written Opinion dated Jun. 26, 2015 issued in International Application No. PCT/US2015/022187. cited by applicant

International Search Report and Written Opinion dated Jun. 5, 2014 issued in International Application No. PCT/US2013/057579. cited by applicant

International Search Report and Written Opinion dated Mar. 10, 2015 issued in International Application No. PCT/US14/54942. cited by applicant

International Search Report and Written Opinion dated Mar. 26, 2021 issued in International Application No. PCT/US20/61458. cited by applicant

International Search Report and Written Opinion dated Mar. 5, 2013 issued in International Application No. PCT/US2012/028593. cited by applicant

International Search Report and Written Opinion dated May 20, 2014 issued in International Application No. PCT/US14/15261. cited by applicant

International Search Report and Written Opinion dated Nov. 18, 2022 issued in International Application No. PCT/US2022/040163. cited by applicant

International Search Report and Written Opinion dated Oct. 25, 2022 issued in International Application No. PCT/US2022/038464. cited by applicant

International Search Report and Written Opinion dated Oct. 31, 2022 issued in International Application No. PCT/US2022/038461. cited by applicant

International Search Report and Written Opinion dated Oct. 7, 2009 issued in International Application No. PCT/IB2009/000071. cited by applicant

International Search Report and Written Opinion dated Sep. 14, 2020 issued in International Application No. PCT/US2020/036110. cited by applicant

International Search Report and Written Opinion dated Sep. 25, 2017 issued in Application No. PCT/US17/30922. cited by applicant

International Search Report issued Apr. 21, 2008 in International Application No. PCT/CH2007/000380. cited by applicant

Invitation to Pay Additional Fees issued on Jan. 8, 2014 in International Application No. PCT/US2013/057579. cited by applicant

Israel Office Action dated Dec. 5, 2023 issued in Israel Application No. 281160, with English translation. cited by applicant

Japanese Notice of Allowance dated Feb. 27, 2018 issued in Japanese Application No. 2015530101. cited by applicant

Japanese Notice of Allowance dated Jul. 11, 2017 issued in Japanese Application No. 2013557926, with English language summary. cited by applicant

Japanese Notice of Allowance dated Jul. 7, 2020 issued in Japanese Application No. 2016558799, with English translation of allowed claims. cited by applicant

Japanese Notice of Allowance dated Jun. 11, 2019 issued in Japanese Application No. 2018024907, with English translation. cited by applicant

Japanese Notice of Allowance dated Mar. 5, 2019 issued in Japanese Application No. 2018061040, with English translation. cited by applicant

Japanese Notice of Allowance dated Sep. 1, 2020 issued in Japanese Application No. 2017-559320 with English summary. cited by applicant

Japanese Notice of Allowance dated Sep. 18, 2018 issued in Japanese Application No. 2015557091, with English language translation. cited by applicant

Japanese Office Action dated Apr. 23, 2024 issued in Japanese Application No. 2021-572320, with machine translation to English. cited by applicant

Japanese Office Action dated Aug. 28, 2018 issued in Japanese Application No. 2016542062, with machine translation to English. cited by applicant

Japanese Office Action dated Aug. 29, 2023 issued in Japanese Application No. 2020540418, with machine translation to English. cited by applicant

Japanese Office Action dated Dec. 11, 2018 issued in Japanese Application No. 2018024907, with machine translation to English. cited by applicant

Japanese Office Action dated Feb. 16, 2016 issued in Japanese Application No. 2013557926, with English language summary. cited by applicant

Japanese Office Action dated Feb. 19, 2019 issued in Japanese Application No. 2016558799, with machine translation to English. cited by applicant

Japanese Office Action dated Feb. 20, 2024 issued in Japanese Application No. 2021560399, with English translation. cited by applicant

Japanese Office Action dated Jan. 10, 2023 issued in Japanese Application No. 2020-540418, with machine translation to English. cited by applicant

Japanese Office Action dated Jan. 31, 2017 issued in Japanese Application No. 2013557926, with English language summary. cited by applicant

Anatomy Warehouse, "Axis Heart Model", 2014, pp. 1-3, at <http://www.anatomywarehouse.com/axis-scientific-2-part-deluxe-life-size-human-heart-a-104269>. (Year: 2014). cited by applicant

Christoph Scharf et al. Declaration under 37 C.F.R. 1.132, Nov. 15, 2012. cited by applicant

Australian Examination Report dated Feb. 8, 2019 issued in Australian Application No. 2018250516. cited by applicant

Australian Examination Report dated Jun. 28, 2018 issued in Australian Patent Application No. 2014318872. cited by applicant

Australian Office Action dated Dec. 22, 2019 issued in Australian Application No. 2018278959. cited by applicant

Australian Office Action dated Feb. 26, 2018 issued in Australian Application No. 2017201560.
cited by applicant

Australian Office Action dated Jan. 15, 2020 issued in Australian Application No. 2016262547.
cited by applicant

Australian Office Action dated Jan. 26, 2019 issued in Australian Application No. 2018211348.
cited by applicant

Australian Office Action dated Jul. 6, 2017 issued in Australian Application No. 2014214756. cited
by applicant

Australian Office Action dated Jun. 14, 2018 issued in Australian Application No. 2014214756.
cited by applicant

Australian Office Action dated Jun. 27, 2017 issued in Australian Application No. 2013308531.
cited by applicant

Australian Office Action dated Mar. 16, 2020 issued in Australian Application No. 2016260522.
cited by applicant

Australian Office Action dated Mar. 17, 2018 issued in Australian Application No. 2013308531.
cited by applicant

Australian Office Action dated May 30, 2016 issued in Australian Application No. 2012225250.
cited by applicant

Australian Office Action dated Nov. 10, 2023 issued in Australian Application No. 2019209440.
cited by applicant

Australian Office Action dated Sep. 21, 2016 issued in Australian Application No. 2012225250.
cited by applicant

Canadian Office Action dated Apr. 26, 2017 issued in Canadian Application No. 2932956. cited by
applicant

Canadian Office Action dated Apr. 27, 2016 issued in Canadian Application No. 2747859. cited by
applicant

Canadian Office Action dated Dec. 22 2015 issued in Canadian Application No. 2656898. cited by
applicant

Canadian Office Action dated Jan. 22, 2018 issued in Canadian Application No. 2932956. cited by
applicant

Canadian Office Action dated Jul. 12, 2019 issued in Canadian Application No. 2881457. cited by
applicant

Canadian Office Action dated Mar. 30, 2017 issued in Canadian Application No. 2747859. cited by
applicant

Canadian Office Action dated May 20, 2020 issued in Canadian Application No. 2881457. cited by
applicant

Canadian Office Action dated Nov. 27, 2017 issued in Canadian Application No. 2829626. cited by
applicant

Canadian Office Action dated Nov. 7, 2018 issued in Canadian Application No. 2932956. cited by
applicant

Canadian Office Action dated Oct. 29, 2018 issued in Canadian Application No. 2829626. cited by
applicant

Canadian Office Action dated Oct. 4, 2013 issued in Canadian Application No. 2659898. cited by
applicant

Chinese Office Action dated Apr. 17, 2017 issued in Chinese Application No. 201480018328.4.
cited by applicant

Chinese Office Action dated Apr. 8, 2020 issued in Chinese Application No. 201810153436.2. cited
by applicant

Chinese Office Action dated Jan. 9, 2023 issued in Chinese Application No. 201980009337.X.
cited by applicant

Chinese Office Action dated Sep. 8, 2021 issued in Chinese Application No. 201680040709.1, with English translation. cited by applicant
Communication Under Rule 71(3) EPC dated Nov. 15, 2021 issued in European Application No. 15768711.2. cited by applicant
Decision dated Jan. 16, 2018 issued for European Patent Application No. 09702094.5. cited by applicant
Decision dated Jan. 18, 2018 issued for European Patent Application No. 13176658.6. cited by applicant
European Office Action dated Apr. 23, 2018 issued in European Application No. 07785075.8. cited by applicant
European Office Action dated Apr. 28, 2014 issued in European Application No. 09702094.5. cited by applicant
European Office Action dated Feb. 29, 2016 issued in European Application No. 07785075.8. cited by applicant
European Office Action dated Feb. 6, 2019 issued in European Application No. 14843283.4. cited by applicant
European Office Action dated Jan. 28, 2019 issued in European Application No. 14748567.6. cited by applicant
European Office Action dated Jan. 31, 2018 issued in European Application No. 13763151.1. cited by applicant
European Office Action dated Jun. 15, 2020 issued in European Application No. 15768711.2. cited by applicant
European Office Action dated Mar. 21, 2017 issued in European Application No. 07785075.8. cited by applicant
European Office Action dated Mar. 27, 2024 issued in European Application No. 21192952.6. cited by applicant
European Office Action dated Mar. 9, 2016 issued in European Application No. 09702094.5. cited by applicant
European Office Action dated Mar. 9, 2016 issued in European Application No. 13176658.6. cited by applicant
European Office Action dated Nov. 7, 2017 issued in European Application No. 15768711. cited by applicant
European Office Action dated Oct. 4, 2023 issued in European Application No. 20749999.7. cited by applicant
Extended European Search Report dated Aug. 10, 2021 issued in European Application No. 19741310.7. cited by applicant
Extended European Search Report dated Dec. 13, 2021 issued in European Application No. 19800090.3. cited by applicant
Extended European Search Report dated Dec. 5, 2018 issued in European Application No. 16793622.8. cited by applicant

Primary Examiner: Morales; Jon Eric C

Attorney, Agent or Firm: Onello & Mello, P.C.

Background/Summary

CROSS REFERENCES TO RELATED APPLICATIONS (1) The present application is a continuation application of U.S. patent application Ser. No. 17/578,522, entitled "Cardiac Analysis User Interface System and Method", filed on Jan. 19, 2022, which is a continuation application of U.S. patent application Ser. No. 15/128,563, entitled "Cardiac Analysis User Interface System and Method", filed on Sep. 23, 2016, which is a U.S. National Stage entry of International Patent Application No.: PCT/US2015/022187, filed Mar. 24, 2015, which claims priority under 35 USC 119 (e) to U.S. Provisional Application Ser. No. 61/970,027, entitled CARDIAC ANALYSIS USER INTERFACE SYSTEM AND METHOD, filed Mar. 25, 2014, which is incorporated herein by reference in its entirety. (2) The present application, while not claiming priority to, may be related to Applicant's co-pending US Design patent application Ser. No. 29/475,273, entitled Transducer-Electrode Arrangement, filed Dec. 2, 2013, the entirety of which is incorporated herein by reference. (3) The present application, while not claiming priority to, may be related to Applicant's co-pending U.S. patent application Ser. No. 14/422,941, entitled Catheter System and Methods of Medical Uses of Same. Including Diagnostic and Treatment Uses for the Heart, filed Feb. 5, 2015, and International Application No. PCT/US2013/057579, entitled Catheter System and Methods of Medical Uses of Same. Including Diagnostic and Treatment Uses for the Heart, filed Aug. 30, 2013, which claimed priority to U.S. Provisional Patent Application No. 61/695,535, entitled System and Method for Diagnosing and Treating Heart Tissue, filed Aug. 31, 2012, each of which is hereby incorporated by reference. (4) The present application, while not claiming priority to, may be related to Applicant's co-pending U.S. patent application Ser. No. 14/003,671, entitled Device and Method For the Geometric Determination of Electrical Dipole Densities on the Cardiac Wall, filed Mar. 9, 2012, and International Application No. PCT/US2012/028593, entitled Device and Method for the Geometric Determination of Electrical Dipole Densities on the Cardiac Wall, filed Mar. 9, 2012, which claimed priority to U.S. Provisional Patent Application No. 61/451,357, entitled Device and Method for the Geometric Determination of Electrical Dipole Densities on the Cardiac Wall, filed Mar. 10, 2011, each of which is hereby incorporated by reference. (5) The present application, while not claiming priority to, may be related to U.S. patent application Ser. No. 13/946,712, entitled A Device and Method for the Geometric Determination of Electrical Dipole Densities on the Cardiac Wall, filed Jul. 19, 2013, which is a continuation of U.S. Pat. No. 8,512,255, entitled A Device and Method for the Geometric Determination of Electrical Dipole Densities on the Cardiac Wall, filed Jul. 16, 2010, published as US20100298690, which was a 35 USC 371 a national stage application of Patent Cooperation Treaty Application No. PCT/IB09/00071 filed Jan. 16, 2009, entitled A Device and Method for the Geometric Determination of Electrical Dipole Densities on the Cardiac Wall, published as WO 2009/090547, which claimed priority to Swiss Patent Application 00068/08 filed Jan. 17, 2008, each of which is hereby incorporated by reference. (6) The present application, while not claiming priority to, may be related to U.S. patent application Ser. No. 14/547,258, entitled Method and Device for Determining and Presenting Surface Charge and Dipole Densities on Cardiac Walls, filed Nov. 14, 2014, which is a continuation of U.S. patent application Ser. No. 13/858,715, entitled Method and Device for Determining and Presenting Surface Charge and Dipole Densities on Cardiac Walls, filed Apr. 8, 2013, which is a continuation of U.S. Pat. No. 8,417,313, entitled Method and Device for Determining and Presenting Surface Charge and Dipole Densities on Cardiac Walls, filed Feb. 3, 2009, published as US2009264781, which was a 35 USC 371 national stage filing of PCT Application No. CH2007/000380, entitled Method and Device for Determining and Presenting Surface Charge and Dipole Densities on Cardiac Walls, filed Aug. 3, 2007, published as WO 2008/014629, which claimed priority to Swiss Patent Application No. 1251/06 filed Aug. 3, 2006, each of which is hereby incorporated by reference.

FIELD OF INTEREST

(1) The invention relates to the field of systems and methods for analyzing cardiac activity and for

diagnosing and treating cardiac related abnormalities, and in particular to systems and methods that display cardiac-related information useful in such activities.

BACKGROUND

(2) For identifying the origin(s) of cardiac arrhythmias it is common practice to measure the electric potentials located on the inner surface of the heart with electroanatomic mapping systems. For example, for this purpose electrode catheters can be inserted into the heart and moved around while recording cardiac potentials during normal heart rhythm or cardiac arrhythmia. If the arrhythmia has a regular activation sequence, the timing of local activation measured from the cardiac potentials at each site visited by the electrode can be combined across many sites and over many heart beats during the arrhythmia, to create a three dimensional “Local Activation Time” (LAT) map of the electric activation. By doing this, information on the location of the source of arrhythmia(s) and mechanisms, i.e., foci and reentry circuits, can be diagnosed to initiate or guide treatment (e.g., radiofrequency ablation).

(3) This mapping procedure is often aided by computer systems generating three dimensional maps of catheter positions by localizing the catheter with the help of magnetic fields (the so called Carto System) or transthoracic impedances (by Localisa and NavX). Because all the points of such maps are obtained by electrode positions in contact with the cardiac surface, this mapping system is called “conventional contact mapping”. It has the inherent limitation that cardiac activation can only be assessed simultaneously at the points in contact with the myocardium. Hence, an instantaneous map of the entire cardiac activation is impossible because the entire heart chamber cannot be contacted simultaneously without compromising blood circulation. Instantaneous mapping of the entire electric activation of the heart chamber, however, might be advantageous in unstable arrhythmias of short duration, for which the conventional mapping procedures (moving the electrode around during the arrhythmia) are too time-consuming compared to this short duration and are therefore unable to capture a clinically relevant electric activation map. In addition, an instantaneous map of cardiac electric activation might be advantageous during irregular arrhythmias or arrhythmias with non-constant activation sequences that render accumulation of activation times from contact mapping impossible. Finally, instantaneous maps of cardiac activation are probably also faster and easier obtained, than a contact map generated by time consuming catheter movements to different areas of the heart in all sorts of cardiac arrhythmias.

(4) The disadvantage of contact mapping can be overcome by “non-contact mapping,” which allows for mapping cardiac activation of a heart chamber simultaneously without contact to the cardiac wall. For this purpose, for instance, a multi electrode array mounted on an inflatable balloon can be inserted into the heart. The geometry of the heart chamber is obtained either (i) by reconstruction of a contact map, which is obtained from an accumulation of 3D surface positions during movements with an electrode catheter within the heart chamber, or (ii) by importing imaging data from computed tomography or MRI (magnetic resonance imaging).

(5) Once the geometry of the cardiac chamber is outlined in a map the information of a simultaneous recording of cardiac far field potentials (unipoles) by the multi electrode array can be extrapolated to the desired cardiac map using advanced mathematical methods. This non-contact mapping has the advantage that it provides the entire electric activation measured by far field unipolar potentials either in sinus rhythm or during arrhythmia without the need for moving an electrode catheter around the cardiac chamber. This information allows for a single beat analysis of cardiac activation and, therefore, unstable, irregular or multifocal arrhythmias can be tracked and treated. However, the disadvantage of non-contact mapping is that it relies on far field potentials, which do not allow for the same precision in localization as contact mapping (i.e. measuring local electrograms (potentials) of cardiac activation by touching the endocardium at the site of interest with a mapping electrode).

(6) Furthermore, non-contact mapping is more prone to artifact generation and interference from

potentials generated by cardiac re-polarization and adjacent heart chambers (atria/ventricles). These drawbacks can be overcome to a certain extent with several filtering techniques. However, in many cases these drawbacks also render the localization of cardiac arrhythmias a time-consuming and frustrating intervention.

(7) Therefore, the advantages of non-contact mapping, i.e. the instantaneous cardiac activation maps, have to be balanced against the disadvantages, i.e. the decreased spatial resolution due to recording of far field signals, filtering of artifacts, etc.

(8) Another method for the non-invasive localization of cardiac arrhythmias is body surface mapping. In this technique multiple electrodes are attached to the entire surface of the thorax and the information of the cardiac electrical activation is simultaneously measured from the body surface potentials, called the electrocardiogram (ECG), which are assimilated into LAT maps. Complex mathematical methods are required in order to determine the local time of electric activation in a heart model, for instance, one obtained from CT or MRI imaging giving information on cardiac size and orientation within the thoracic cavity.

(9) The disadvantage of both mapping methods, i.e. contact and non-contact types, is the representation of the electric activity of the heart by means of potentials, which are the result of a summation of ionic charge-sources within the membrane of all cardiac cells spanning the entire 3D volume of the cardiac tissue. This summation of electric forces generated by the ionic charge-sources in cardiac cells provides for the potentials that are measured by current mapping systems.

(10) Research has indicated that the use of the surface charge densities (i.e. their distribution) or dipole densities (i.e. their distribution) to generate a distribution map (or maps), if successfully, practicably, and reliably determined, can lead to more detailed and precise information on electric ionic activity of local cardiac cells than the conventional determination made using potentials (or voltages). Surface charge density or dipole densities represent a precise and sharp set of information of the electric activity with good spatial resolution, whereas potentials resulting from a summation of charge densities provide only a diffuse picture of electric activity. The electric nature of cardiac cell membranes comprising ionic charges of proteins and soluble ions can be precisely described by surface charge and dipole densities, but not by conventional measures of potential. The surface charge densities and/or dipole densities cannot be directly measured in the heart, but instead must be mathematically and accurately calculated starting from measured potentials. In other words, the information of voltage maps obtained by conventional mapping systems can be greatly refined when calculating surface charge densities or dipole densities from these. However, determining surface and dipole densities from voltage information and maps is not a trivial mathematical exercise. U.S. Pat. Nos. 8,417,313 B2 and 8,512,255 B2, each to Scharf et al., describe approach for determining surface and dipole densities from voltage information and maps.

(11) Surface charge density means surface charge (Coulombs) per unit area (cm^2). A dipole, as such, is a neutral element, wherein one part comprises a positive charge and the other part comprises the same, but negative charge. A dipole or surface charge map could be considered to represent the electric nature of cellular membranes better than voltage maps, because in a biological environment, ion charges are not macroscopically separated.

(12) Currently, mapping systems display cardiac images and activity based on measured potentials, not dipole or surface charge densities. As discussed above, this inherently includes inaccuracies, since voltages are averaged and/or smoothed field data and dipole or surface charge densities are much more accurate source data. Additionally, such display systems do not provide a real-time or near real-time display of the heart or cardiac activity because the volume of rapidly changing cardiac-generated voltage data tends to be far too large for real-time or near real-time mapping using such systems. In fact, such mapping and display systems represent an image of the heart that is not accurate, such as due to left atrial enlargement that can occur during mapping and treatment procedures. A displayed image of the heart cannot be rapidly and accurately updated using current systems, so the practitioner must work with the inaccurate cardiac image. This is particularly

troublesome, for example, when the practitioner is attempting to precisely locate heart tissue for ablation-which requires some amount of guesswork by the practitioner using conventional imaging and display systems.

SUMMARY

(13) Methods of generating a graphical representation of cardiac information on a display screen are provided. The method comprises: electronically creating or acquiring an anatomical model of the heart including multiple cardiac locations; electronically determining a data set of source information corresponding to cardiac activity at the multiple cardiac locations; electronically rendering the data set of source information in relation to the multiple cardiac locations on the display screen. Systems and devices for providing a graphical representation of cardiac information are also provided.

(14) In accordance with one aspect of the present disclosure, provided is a method of generating a graphical representation of cardiac information on a display screen. The method comprises: electronically creating an anatomical model of the heart including multiple cardiac locations; electronically determining a data set of source information corresponding to cardiac activity at the multiple cardiac locations; and electronically rendering the data set of source information in relation to the multiple cardiac locations on the display screen.

(15) In various embodiments, the source information can be data representing, at a location in 3D space, a physical property or properties discrete to the specific location in 3D space.

(16) In various embodiments, the source information can comprise recording signals from at least one sensor.

(17) In various embodiments, the at least one sensor can comprise multiple sensors.

(18) In various embodiments, the multiple sensors can be mounted to an expandable array constructed and arranged for placement within a cardiac chamber.

(19) In various embodiments, the at least one sensor can comprise: electrode; pH sensor; temperature sensor; or combinations of two or more thereof.

(20) In various embodiments, the source information can comprise: dipole density information; surface charge density information; pH information; temperature information; or combinations of two or more thereof.

(21) In various embodiments, electronically determining a data set of source information can comprise electronically determining multiple sequential data sets of source information representing different phases of at least one cardiac cycle.

(22) In various embodiments, the at least one cardiac cycle can comprise multiple cardiac cycles.

(23) In various embodiments, the multiple sequential data sets can represent dynamic data sets that are updated at least thirty times per second.

(24) In various embodiments, the multiple sequential data sets can represent or include dynamic data sets that are updated at least once per second.

(25) In various embodiments, the multiple sequential data sets can represent or include dynamic data sets that are updated at least once every 30 minutes.

(26) In various embodiments, the source information can be presented in the form of or using a differentiating map.

(27) In various embodiments, the differentiating map can comprise a color map.

(28) In various embodiments, the differentiating map can comprise a map of value differentiating parameters including: color; contrast; brightness; hue; saturation level; or combinations of two or more thereof.

(29) In various embodiments, the method can comprise electronically rendering the anatomical model of the heart on the display screen.

(30) In various embodiments, the anatomical model can be created using signals from at least one ultrasound transducer.

(31) In various embodiments, the method can comprise displaying a static image of the heart on the

display screen.

(32) In various embodiments, the static image can comprise an image of the heart temporally proximate the end of systole.

(33) In various embodiments, the static image can comprise an image of the heart temporally proximate the end of diastole.

(34) In various embodiments, the static image of the heart can be updated at least once every thirty minutes.

(35) In various embodiments, the method can comprise displaying a dynamic image of the heart comprising multiple images of a cardiac cycle on the display screen.

(36) In various embodiments, the method can comprise displaying a dynamic image of the heart comprising multiple images of multiple cardiac cycles on the display screen.

(37) In various embodiments, the method can comprise updating the multiple images of a cardiac cycle at least once every thirty minutes.

(38) In various embodiments, the method can comprise rendering a data set of field information on the display screen.

(39) In various embodiments, the data set of field information can comprise a data set of voltage information.

(40) In various embodiments, the data set of field information can correspond to the multiple cardiac locations and can be optionally associated with the multiple cardiac locations on the display screen.

(41) In various embodiments, the method can comprise displaying the data set of field information in a side-by-side arrangement with the data set of source information.

(42) In various embodiments, the method can comprise displaying the data set of field information in an overlay arrangement with the data set of source information.

(43) In various embodiments, the method can comprise displaying the data set of field information in an alternating arrangement with the data set of source information.

(44) In various embodiments, the method can comprise producing calculated information and electronically rendering the calculated information on the display screen.

(45) In various embodiments, the calculated information can be electronically rendered on the display screen in relation to one or more cardiac locations.

(46) In various embodiments, the calculated information can comprise information based on recordings from at least one ultrasound transducer.

(47) In various embodiments, the calculated information can comprise information based on recordings from an array of ultrasound transducers positioned in a cardiac chamber.

(48) In various embodiments, the calculated information can comprise: cardiac chamber volume; cardiac wall thickness; average cardiac wall thickness; a cardiac chamber dimension; ejection fraction; cardiac output; cardiac flow rate; cardiac contractility; cardiac wall motion; or combinations of two or more thereof.

(49) In various embodiments, the calculated information can comprise information based on recordings from at least one electrode.

(50) In various embodiments, the calculated information can comprise information based on recordings from an array of electrodes positioned in a cardiac chamber.

(51) In various embodiments, the calculated information can comprise: voltage at a heart surface location; dipole state at a heart surface location; or combinations of two or more thereof.

(52) In various embodiments, the calculated information can comprise quantitative information.

(53) In various embodiments, the calculated information can be rendered on the display in a form including: numerals; bar chart; pie chart; or combinations of two or more thereof.

(54) In various embodiments, the calculated information can comprise mathematically processed recorded information.

(55) In various embodiments, the recorded information can comprise information recorded by a

component including: one or more electrodes; one or more ultrasound transducers; one or more sensors; or combinations of two or more thereof.

(56) In various embodiments, the mathematical processing can comprise processing including: summing; averaging; integrating; differentiating; finding the mean; finding a maximum; finding a minimum; or combinations of two or more thereof.

(57) In various embodiments, the recorded information can comprise information recorded by one or more electrodes.

(58) In various embodiments, the calculated information can comprise information including: dipole density information; surface charge density information; or combinations of two or more thereof.

(59) In various embodiments, the calculated information can comprise mathematically processed dipole density or surface charge density information.

(60) In various embodiments, the mathematical processing can comprise processing including: summing; averaging; integrating; differentiating; finding the mean; finding a maximum; finding a minimum; or combinations of two or more thereof.

(61) In various embodiments, the recorded information can comprise information recorded by one or more ultrasound transducers.

(62) In various embodiments, the calculated information can represent a measure of heart contractility, and wherein the calculated information is rendered on the display screen.

(63) In various embodiments, the method can comprise identifying an undesired contractility decrease based on the calculated information.

(64) In various embodiments, the calculated information can represent a measure of heart enlargement, and wherein the calculated information is rendered on the display screen.

(65) In various embodiments, the calculated information can represent a measure of left atrial enlargement.

(66) In various embodiments, the method can comprise identifying an undesired heart enlargement based on the calculated information.

(67) In various embodiments, the calculated information can comprise a measurement of a change in patient information over a time period.

(68) In various embodiments, the calculated information can comprise a comparison of patient information to a threshold.

(69) In various embodiments, the method can comprise changing the appearance of the calculated information on the display screen when the threshold is exceeded.

(70) In various embodiments, changing the appearance can comprise changing a parameter including: color; boldness; font; size; static or dynamic presentation, or combinations of two or more thereof.

(71) In various embodiments, the method can comprise activating an alert when the threshold is exceeded.

(72) In various embodiments, the method can comprise electronically rendering additional patient information on the display screen.

(73) In various embodiments, the additional patient information can comprise information including: age; sex; race; height; weight; patient ID; or combinations of two or more thereof.

(74) In various embodiments, the additional patient information can comprise information including: blood pressure; heart rate; cardiac cycle length; pulse oximetry; respiration rate; or combinations of two or more thereof.

(75) In various embodiments, the additional patient information can comprise quantitative information.

(76) In various embodiments, the method can comprise representing the quantitative information on the display screen by a graphic element including: numerals; bar chart; pie chart; graph; plot; or combinations of two or more thereof.

- (77) In various embodiments, the method can comprise performing a therapeutic procedure on the patient based on at least the determined source information.
- (78) In various embodiments, the therapeutic procedure can be performed based on the rendered source information.
- (79) In various embodiments, the therapeutic procedure can comprise a cardiac ablation procedure.
- (80) In various embodiments, the cardiac ablation procedure can comprise ablating at least tissue of the left atrium.
- (81) In various embodiments, display of the data set of source information in relation to the multiple cardiac locations can be a user interactive display.
- (82) In various embodiments, user interactive display can be responsive to a user input to: pause, initiate, and/or record dynamic display of cardiac activity; store, display, or output a data value associated with at least one cardiac location; display or output an associated information in a secondary window or frame providing graphical, numerical, or textual information relating to cardiac activity represented by the data set; zoom in on, zoom out from, and/or rotate a cardiac image; isolate a portion of the cardiac image; reveal a cross-section or slice through the cardiac image; or combinations of two or more thereof.
- (83) In various embodiments, associated information can include an ECG, EKG, or both.
- (84) In accordance with various aspects of the present invention, provided is a system configured and arranged to provide a graphical representation of cardiac information on a display screen. The system comprises: a first receiver configured to receive cardiac geometry information and to create an anatomical model of the heart including multiple cardiac locations; a second receiver configured to receive information including: source information; field information; or combinations of two or more thereof, and to determine a set of source information corresponding to cardiac activity at the multiple cardiac locations; and a display screen configured to provide the data set of source information in relation to the multiple cardiac locations.
- (85) In various embodiments, the source information can be data representing, at a location in 3D space, a physical property or properties discrete to the specific location in 3D space.
- (86) In various embodiments, the source information can include dipole density data determined for a point on the surface of the heart.
- (87) In various embodiments, the source information can comprise: dipole density information; surface charge density information; pH information; temperature information; or combinations of two or more thereof.
- (88) In various embodiments, the system can comprise at least one ultrasound transducer configured to provide the cardiac geometry information to the first receiver.
- (89) In various embodiments, the at least one ultrasound transducer can comprise multiple ultrasound transducers.
- (90) In various embodiments, the multiple ultrasound transducers can be constructed and arranged in an expandable array.
- (91) In various embodiments, the system can comprise at least one sensor configured to provide the information received by the second receiver.
- (92) In various embodiments, the at least one sensor can comprise an electrode.
- (93) In various embodiments, the at least one sensor can comprise: pH sensor; temperature sensor; or combinations of two or more thereof.
- (94) In various embodiments, the system can comprise an imaging device configured to provide the cardiac geometry information to the first receiver.
- (95) In various embodiments, the imaging device can comprise: a Computed Tomography apparatus; an MRI apparatus; an Ultrasound apparatus; a multi-electrode mapping catheter; a multi-transducer imaging catheter such as an imaging catheter comprising an array of ultrasound transducers; or combinations of two or more thereof.
- (96) In various embodiments, the system display of the data set of source information in relation to

the multiple cardiac locations can be a user interactive display.

(97) In various embodiments, the system user interactive display can be responsive to a user input to: pause, initiate, and/or record dynamic display of cardiac activity; store, display, or output a data value associated with at least one cardiac location; display or output an associated information in a secondary window or frame providing graphical, numerical, or textual information relating to cardiac activity represented by the data set; zoom in on, zoom out from, and/or rotate a cardiac image; isolate a portion of the cardiac image; reveal a cross-section or slice through the cardiac image; or combinations of two or more thereof.

(98) In various embodiments, the system associated information can include an ECG, EKG, or both.

(99) In various embodiments, the system can comprise a therapeutic device configured to treat the patient based on the source information provided on the display.

(100) In various embodiments, the therapeutic device can be an ablation catheter.

(101) In accordance with aspects of the present invention, provided is a cardiac information display method as shown and described in reference to the figures herein.

(102) In accordance with aspects of the present invention, provided is a cardiac information display system as shown and described in reference to the figures herein.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present invention will become more apparent in view of the attached drawings and accompanying detailed description. The embodiments depicted therein are provided by way of example, not by way of limitation, wherein like reference numerals refer to the same or similar elements. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating aspects of the invention. In the drawings:

(2) FIG. 1 illustrates a block diagram of an embodiment of a device for determining a database table of dipole densities $d(y)$ and/or surface charge densities $\rho(P',t)$ of at least one heart chamber, in accordance with aspects of the present invention;

(3) FIG. 2 illustrates a flow chart of an embodiment of a preferred method for determining a database table of dipole densities and/or surface charge densities $\rho(P',t)$ of at least one heart chamber, in accordance with aspects of the present invention:

(4) FIG. 3 illustrates a schematic view of an embodiment of a system for determining a database table of dipole densities and/or surface charge densities $\rho(P',t)$ of at least one heart chamber with help of the solid angle $\{\text{acute over } (\omega)\}(x,y)$, in accordance with aspects of the present invention:

(5) FIG. 4 is an exemplary embodiment of a system for determining a database table of dipole and/or surface charge densities and for displaying such density information, in accordance with aspects of the present invention:

(6) FIG. 5A is a perspective view of the distal portion of a system for treating a patient including an ablation catheter slidably received by the shaft of a diagnostic catheter and FIG. 5B is a perspective view of the system of FIG. 5A, with the ablation catheter in a bent configuration for treating a patient, in accordance with aspects of the present invention:

(7) FIG. 5C is a perspective view of the distal portion of a system for determining a database of dipole and/or surface charge densities, in accordance with aspects of the present invention:

(8) FIG. 6 is an exemplary embodiment of a computer architecture forming part of the system of FIG. 4, in accordance with aspects of the present invention:

(9) FIG. 7 is an example embodiment of a method of determining and storing surface charge densities, in accordance with aspects of the present invention:

(10) FIG. 8 is an example embodiment of a method of determining and storing dipole densities, in

accordance with aspects of the present invention:

(11) FIG. 9 is an example embodiment of a method of displaying dipole and/or surface charge densities, in accordance with aspects of the present invention:

(12) FIG. 10 is an exemplary embodiment of a user interface display of dipole and/or surface charge density information that can be generated on one or more displays, in accordance with aspects of the present invention:

(13) FIG. 11 is another embodiment of a user interface display of dipole and/or surface charge density information that can be generated on one or more devices, in accordance with aspects of the present invention; and

(14) FIG. 12 is an example embodiment of a method of producing a model of a heart including the geometry of the cardiac surfaces, in accordance with aspects of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

(15) Various exemplary embodiments will be described more fully hereinafter with reference to the accompanying drawings, in which some exemplary embodiments are shown. The present inventive concept may, however, be embodied in many different forms and should not be construed as limited to the exemplary embodiments set forth herein.

(16) It will be understood that, although the terms first, second, etc. are used herein to describe various elements, these elements should not be limited by these terms. These terms are used to distinguish one element from another, but not to imply a required sequence of elements. For example, a first element can be termed a second element, and, similarly, a second element can be termed a first element, without departing from the scope of the present invention. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

(17) It will be understood that when an element is referred to as being “on” or “connected” or “coupled” to another element, it can be directly on or connected or coupled to the other element or intervening elements can be present. In contrast, when an element is referred to as being “directly on” or “directly connected” or “directly coupled” to another element, there are no intervening elements present. Other words used to describe the relationship between elements should be interpreted in a like fashion (e.g., “between” versus “directly between,” “adjacent” versus “directly adjacent.” etc.).

(18) The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises,” “comprising,” “includes” and/or “including,” when used herein, specify the presence of stated features, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, steps, operations, elements, components, and/or groups thereof.

(19) Spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper” and the like may be used to describe an element and/or feature's relationship to another element(s) and/or feature(s) as, for example, illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use and/or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as “below” and/or “beneath” other elements or features would then be oriented “above” the other elements or features. The device may be otherwise oriented (e.g., rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

(20) To the extent that functional features, operations, and/or steps are described herein, or otherwise understood to be included within various embodiments of the inventive concept, such functional features, operations, and/or steps can be embodied in functional blocks, units, modules, operations and/or methods. And to the extent that such functional blocks, units, modules, operations and/or methods include computer program code, such computer program code can be

stored in a computer readable medium, e.g., such as non-transitory memory and media, that is executable by at least one computer processor.

(21) As used herein, the terms “subject” and “patient” refer to any animal, such as a mammal like livestock, pets, and preferably a human. Specific examples of “subjects” and “patients” include, but are not limited, to individuals requiring medical assistance, diagnosis, and/or treatment, for example, patients with an arrhythmia, such as atrial fibrillation (AF).

(22) Surface charge density means surface charge (Coulombs) per unit area (cm.^{sup.2}). A dipole, as such, is a neutral element, wherein one part comprises a positive charge and the other part comprises the same, but negative charge. A dipole or surface charge map could be considered to represent an electric nature of cellular membranes better than voltage maps, because in a biological environment, ion charges are not macroscopically separated.

(23) The terms “map” and “mapping” can include “electrical map”, “electrical mapping”, “anatomical map”, “anatomical mapping”, “device map” and “device mapping”, each of which is defined herein below.

(24) The terms “electrical map” and “electrical mapping” can include recording, processing and/or displaying electrical information, such as electrical information recorded by one or more electrodes of the present invention. This electrical information includes, but is not limited to: cardiac or other tissue voltage measurements; cardiac or other tissue bipolar and/or unipolar electrograms; cardiac or other tissue surface charge data; cardiac or other tissue dipole density data; cardiac or other tissue monophasic action potentials; and combinations of these.

(25) The terms “anatomical map” and “anatomical mapping” can include recording, processing and/or displaying anatomical information, such as anatomical information provided by one or more ultrasound transducers of the present invention and/or one or more electrodes of the present invention. This anatomical information includes, but is not limited to: two or three dimensional representations of tissue such as one or more chambers of a heart; tissue wall thicknesses such as the thickness of an atrial or ventricular wall; distance between two tissue surfaces; and combinations of these. In some embodiments, a dipole density map is provided by using information provided by multiple electrodes and multiple ultrasound transducers, such as is described in U.S. Pat. No. 8,512,255 B2.

(26) The terms “device map” and “device mapping” can include recording, processing and/or displaying of device distance information, such as information comprising the distance between a device or device component and another object, such as tissue or another device or device component.

(27) The term “patient information” can include physiologic and other information related to the patient, including but not limited to source information and field information, as defined herein, that relates to the patient's heart or other patient location. Patient information can include information which is derived from or is otherwise based on recordings made by one or more sensors, such as one or more electrodes, ultrasound transducers and/or other sensors of the present invention. Patient information can include mathematically processed patient information, such as patient information that is averaged, summed, integrated, differentiated and/or otherwise mathematically processed to create new patient information. Patient information can include patient demographic information, including but not limited to: age; sex; race; height; weight; and patient ID (e.g. an ID assigned to the patient by a hospital).

(28) The term “cardiac information” can include patient physiologic and other information related to the patient's heart, including but not limited to source information and field information, as defined herein, that relates to the patient's heart and/or cardiac activity.

(29) The systems and device of the present invention include one or more sensors or transducers, such as electrodes and ultrasound transducers. In various embodiments, any pair of electrodes can be constructed and arranged to provide distance information, such as the distance between that pair of electrodes, or the distance between one of the electrodes and one or more proximate components

(e.g., a component at a known distance from one or both of the electrodes in the pair). By delivering and recording an electric signal between electrodes of known separation distances, the signal can be processed and/or calibrated according to one or more known separation distances (e.g., the separation distance between two electrodes fixedly mounted to a rigid structure at a pre-determined distance). Calibrated signal values can be combined across adjacent sets of electrode pairs to accurately estimate the distance between any pair (e.g. any arbitrary pair of electrodes on any one or more devices of the system) of electrodes for which the separation distance is not known. Known and calculated separation distances can be used as “reference” electrodes and combined to triangulate the unknown position of one or more “marker” electrodes, such as an electrode positioned on the present invention or on a separate or external device and positioned proximate the present invention. The process of triangulation can be used to dynamically localize the multi-dimensional position of any or all of the electrodes either individually and/or as a combined entity in multi-dimensional space. Numerous distance measurement techniques can be used.

(30) Further, any or all electrodes can be used to deliver electric energy, such as radiofrequency energy.

(31) FIGS. **1-12** illustrate embodiments of devices, systems and methods that can be used for determining dipole (or surface charge) densities from the cardiac activity of a patient or subject. However, the present invention is not limited to these particular configurations. The description will generally refer to “dipole densities,” which should be interpreted to include, either additionally or alternatively, surface charge densities, unless otherwise stated, understood by those skilled in the art.

(32) Referring now to FIG. **1**, a block diagram of an embodiment of a dipole and/or surface charge density system including device **100** configured to determine a database table of dipole and/or surface charge densities of at least one heart chamber of a patient is illustrated.

(33) Device **100** can include a plurality of receivers, e.g., receivers (1), (2) . . . (n), configured to receive one or more types of information from a patient, associated system, and/or other sensors. In this embodiment, device **100** includes a first receiver **110** configured to receive electrical potentials from a separate device, such as a device including a multi-electrode mapping catheter (e.g., placed in the circulating blood within a chamber of the patient's heart). Device **100** can further include a second receiver **120** configured to receive cardiac geometry information (e.g., the geometric contour of the cardiac chamber wall), such as from an instrument including, but not limited to: Computed Tomography; MRI; Ultrasound; a multi-electrode mapping catheter; a multi-transducer imaging catheter such as an imaging catheter comprising an array of ultrasound transducers; and combinations of these. In some embodiments, first receiver **110** receives information from an array of electrodes placed in a chamber of the heart, and second receiver **120** receives information from an array of ultrasound transducers also placed in a chamber of the heart. In these embodiments, the electrodes and ultrasound transducers can be included on a single deployable basket or other expandable assembly, such as is described herebelow in reference to FIG. **5A** or **5C**. Alternatively or additionally, a standard geometry can be loaded representing a model of the heart, such as a model including the geometry of the cardiac chamber. In some embodiments, a receiver, e.g., receiver (n), can be provided to enable device **100** to receive information from electrodes or other types of sensors that collect “source information,” e.g., temperature or pH sensors. As used herein, “source information” is data representing, at a location in 3D space, a physical property or properties discrete to the specific location in 3D space. As contrasted to “field information,” which, as used herein, is data representing, at a location in 3D space, a physical property or properties of a continuum extending through the 3D space.

(34) Device **100** further includes a dipole density module **130** which comprises mathematical processing elements, such as a computer or other electronic module including software and/or hardware for performing mathematical or other calculations when executed by at least one

computer processor. Dipole density module **130** receives electrical mapping information and/or other information (hereinafter “mapping information”) from first receiver **110** and cardiac geometry information from second receiver **120**. Dipole density module **130** preferably uses one or more algorithms to correlate and/or otherwise process the received mapping and geometry information, such as to produce a database table of dipole and/or surface charge densities (e.g. comprising multiple sequential data sets that represent one or more phases of one or more cardiac cycles). In some embodiments, the dipole and/or surface charge density information (or other source information) is updated at least once per second. In other embodiments, the dipole density information (or other source information) is updated at least once per 10 seconds. Accordingly, dipole density module **130** can be configured to produce a database or database table of dipole densities, surface charge densities, or both.

(35) In some embodiments, the geometrical model of the cardiac chamber is processed by dipole density module **130** into multiple small polygons, such as multiple small triangles or other polygons (e.g., trapezoids, squares, rectangles, pentagons, hexagons, octagons, and so forth), hereinafter, collectively referred to as “triangles.” When the triangles or other polygons are sufficiently small, the dipole and/or surface charge density at each triangle can be regarded as constant. In a preferred embodiment, a standard cardiac chamber of 4-6 cm diameter is divided up into over 1000 triangles. In another preferred embodiment, the number of triangles determined by dipole density module **130** is based on the size of the heart chamber. With the electrodes positioned in a cardiac chamber by a clinician, such as an electrophysiologist, the potentials at each electrode are recorded. Each triangle is seen by the corresponding electrode under a certain solid angle.

(36) As used herein, the term “solid angle” is the angle subtended by a triangle on the heart wall at a position x of observation. When viewed from location x , straight lines are drawn from point x to the boundaries of the triangle, and a sphere is constructed of radius $r=1$ with a center of x . The straight lines then define the spherical triangle on the surface of the sphere. The solid angle is proportional to the surface area of the projection of that object onto a sphere centered at the point x .

(37) The dipole density module **130** computes the solid angle $\{\text{acute over } (\omega)\}(x,y)$ subtended by each triangle at position y on each electrode at position x on the multi-electrode catheter. If the dipole density at the triangle is $d(y)$, the triangle contributes $\{\text{acute over } (\omega)\}(x,y)$ times $d(y)$ to the potential $V(x)$ at the position x on the multi-electrode catheter. The total measured potential $V(x)$ is the sum resulting from all the triangles. A detailed description is provided in reference to FIG. **3** herein below.

(38) In some embodiments, dipole density module **130** can implement a progressive algorithm that can be modified and/or refined in order to improve spatial and/or time resolution of the database of dipole densities that are produced. The dipole densities $d(y)$ are obtained by solving a linear system of equations. This calculation requires some care to avoid numerical instabilities. Thereby a map of dipole and/or surface charge densities can be created at corresponding time intervals. The synthesis of the maps generates a cascade of the activation sequence of each corresponding heart beat (also referred to herein as “cardiac cycle”) that can be used to define the origin of the electrical activity, arrhythmias and/or diagnose cardiac disease.

(39) The measuring electrodes used can be placed in the blood flow in a heart chamber, a relatively homogeneous condition, such that the mathematical analysis is well applicable. In a preferred embodiment, skin electrodes are also implemented such that dipole density module **130** can use the information received from the skin electrodes to calculate and/or recalculate the dipole densities for the cardiac wall. The spatial resolution which can be obtained by invasive (i.e., placed in the chamber) multi-electrode potential measurements correlates to the number of electrodes that can be placed in any cardiac chamber, such as the Left Atrium (LA). Skin placed electrodes, such as electrodes placed on the thorax, are not space limited and can be used to enhance calculations of the dipole densities. Application of electrical information measured from skin electrodes at known locations on the torso can enhance the accuracy of dipole and/or surface charge density calculations

by adding independent complementary information from the opposite side of the dipole layer, as compared to information obtained from an electrode located within the heart chamber.

(40) Due mainly to the inhomogeneous structure of the body, it is difficult to localize the actual sources of the skin electrode measured potentials. A highly complicated boundary value problem must be solved with boundary conditions that are poorly known, and previous attempts at determining the “action potential” from body surface ECG (alone) have not been very successful. The badly defined boundary value problem can be avoided by an additional measurement (in addition to the skin electrode measurements) of the chamber-inserted multi-electrode array of the present invention. A small sinusoidal voltage $V_{sub.l}$ is applied to each electrode $l=1, \dots, L$ on the electrode array in the heart, and the resulting voltages $W_{sub.k}, k=1, \dots, K$ is measured at the surface electrodes. This yields the $K \times L$ transition matrix $A_{sub.kl}$

$$(41) \quad W_k = \sum_{l=1}^L A_{kl} V_l \quad (1)$$

(42) Calculating solid angles produces the linear transformation B_{ln} between the electrode array potentials $V_{sub.l}$ and the dipole densities $d_{sub.n}, n=1, \dots, N$ of N regions of the heart wall:

$$(43) \quad V_l = \sum_{n=1}^N B_{ln} d_n \quad (2)$$

N is chosen to be $N=K+L$ where K is the number of surface electrodes and L is the number of internally placed array electrodes.

(44) Substituting equation (2) into (1) we have:

$$(45) \quad W_k = \sum_{l=1}^L A_{kl} \sum_{n=1}^N B_{ln} d_n \quad (3)$$

(46) Therefore, by simultaneous measuring of the potentials of the cardiac activity with all $K+L$ electrodes, $N=K+L$ dipole densities of N regions on the heart wall can be calculated. This method yields a higher spatial resolution than the L array electrodes alone. In the solution of the linear system of equations (2)+(3), regularization techniques must be used (e.g. Tikhonov regularization and its modifications) in order to avoid numerical instabilities.

(47) In some embodiments, other types of information can be captured, such as a temperature from a temperature sensor (e.g. a thermocouple) or pH from a pH sensor. The associated sensor can be placed at multiple locations along a cardiac surface while data is recorded. Module **130** can be used to correlate the recordings provided by the sensor to the anatomical information.

(48) Referring now to FIG. 2, an embodiment of a preferred method for determining a database table of dipole (and/or surface charge) densities of at least one heart chamber of a patient is illustrated. In Step **10**, a multi-electrode array catheter device is placed within the corresponding heart chamber. In Step **20**, a model of the heart including the geometry of the corresponding heart chamber is created (i.e. electronically created). In some embodiments, the model of the heart is created in relation to the multi-electrode array position. In some embodiments, the model of the heart comprises a static model comprising the geometry of one or more cardiac chambers representing that geometry at one particular reference point in a cardiac cycle (e.g. temporally proximate the end of systole or the end of diastole). The geometry of the static heart model can comprise a single image (e.g. created one time) or it can be updated over time (e.g. updated by capturing chamber geometry information at the same reference point in multiple sequential or non-sequential cardiac cycles). In some embodiments, the static heart model is updated at least once every thirty minutes. Alternatively or additionally, the model of the heart comprises a dynamic model (also referred to as a “beating heart model”). The dynamic model can comprise the cardiac geometry at multiple reference points of a single cardiac cycle (i.e. multiple images for a single heart beat) or it can be updated over time (e.g. by capturing sets of images at similar reference points in the cardiac cycle over multiple heart beats). In some embodiments, the dynamic heart model is updated at least 30 times per second (e.g. to provide a continuous image of the heart at 30

frames of video per second). In other embodiments, the dynamic heart model is updated at least once every 100 milliseconds, at least once every second, at least once every minute, or at least once every thirty minutes. In some embodiments, source information and/or field information is updated at least 30 times per second (e.g. to provide a continuous image of changing source information and/or field information at 30 frames of video per second). In other embodiments, source information and/or field information is updated at least once every 100 milliseconds, at least once every second, at least once every minute, or at least once every thirty minutes.

(49) In some embodiments, the heart chamber geometry is provided by image-producing sensors (e.g. ultrasound sensors) from the same catheter device or a separate catheter device placed in the heart chamber. Alternatively or additionally, the model of the heart including heart chamber geometry is created (i.e. electronically created) from information provided by an imaging device external to the patient (e.g. a fluoroscope, computer tomography device, ultrasound imager, MRI) before and/or after the multi-electrode array of electrodes has been placed in the heart chamber. The surface of the geometry of the corresponding heart chamber model can be divided into small triangles, typically at least 1000 small triangles.

(50) In Step **30**, the dipole density $d(y)$ can be calculated (i.e. electronically determined) from the measured potential values and the calculated solid angles. The measurements can be repeated successively during the cardiac cycle, such as to achieve sufficient resolution over time. The information of the time dependent dipole densities can be depicted as an activation map of the corresponding heart chamber for the given heartbeat. The information can be used to diagnose and/or treat a patient with a cardiac disease or disorder, such as atrial fibrillation or other cardiac arrhythmia. Alternatively or additionally, the surface charge density can be calculated in Step **30**. In either or both cases, the dipole and/or surface charge densities can be stored in a database or database table, in Step **30**.

(51) In various embodiments, the information can be used to determine cardiac wall treatment locations for lesion creation to treat an arrhythmia, such as a lesion created in the Left or Right atrium, by an RF, microwave, laser, ultrasound and/or cryogenic ablation catheter. In some embodiments, the multiple electrode mapping array is placed in a ventricle and the dipole densities are determined for the ventricular wall, such as to detect ischemia or quantify myocardial function.

(52) Referring now to FIG. **3**, an embodiment of a system for determining a database table of dipole densities and/or other information of at least one heart chamber of a patient is illustrated.

(53) System **300** includes device **100**, which can be configured to create a database (or table) of dipole densities $d(y)$ based on electrical potential measurements within the heart chamber and image information relating to the heart chamber, as has been described herein above. Alternatively or additionally, device **100** can be configured to create a database of other information, such as other local information regarding surface charge densities, temperature and/or pH levels at a cardiac surface. System **300** further includes imaging unit **220**, which is configured to provide a two or three-dimensional image of the heart chamber relative to information provided by device **100**. Imaging unit **220** can perform at least one of fluoroscopy, Computed Tomography, MRI and/or ultrasound imaging, as examples of imaging technologies. Imaging unit **220** can produce any form of real or virtual models of the cardiac chambers, such that a mesh analysis (e.g. using triangles, polygons, etc.) is possible.

(54) System **300** further includes mapping catheter **310**, which includes shaft **311**, shown inserted into a chamber of a patient's heart, such as the Left Atrium (LA). At the proximal end of shaft **311** is handle **312**. At the distal end of shaft **311** is an array **315** including multiple electrodes **316** and/or multiple other sensors configured to record local information and/or field information. Array **315** is shown in a basket construction, but numerous other constructions can be used including multiple independent arms, spiral arrays, electrode, ultrasound sensor and/or other sensor-covered balloons, and other constructions configured to place multiple sensors and/or transducers into a two or three-dimensional arrangement. In a preferred embodiment, any catheter with a multi-

dimensional array of electrodes or other sensors can be used to supply the mapping or other information to device **100**. In various embodiments, alternatively or additionally, the electrodes and/or sensors can include sensors to sense other types of “source information,” e.g., temperature and pH, as examples. Handle **312** can include one or more controls, not shown but such as one or more controls to steer shaft **311** and/or control one or more sensors or transducers of array **315**, such as to activate one or more electrodes **316**.

(55) In some embodiments, catheter **310** can include one or more types of imaging transducers, such as ultra-sound transducers (USTs) built into catheter **310** or array **315**, such as is described herebelow in reference to catheter **500** of FIG. 5A or catheter **500'** of FIG. 5C. Such imaging transducers could be used to obtain imaging information to generate, maintain, update and/or augment the image of the heart, in conjunction with imaging unit **220**.

(56) Electrodes **316** are connected to wires, not shown, but traveling proximally, passing through handle **312** to cable **317**, which is electrically connected to a mapping unit **210**, such as an electrocardiogram (ECG) unit. Mapping unit **210** includes a monitor for displaying information, such as the potentials recorded by electrodes **316**, as well as the dipole density or other information produced by device **100**. In an alternative embodiment, device **100** further includes a monitor, not shown, but configured to display one or more of: dipole density information; surface charge information; potentials recorded by electrodes **316**; information recorded by one or more sensors such as one or more temperature and/or pH sensors; and cardiac chamber contours and other geometry information. In a preferred embodiment, dipole density and/or recorded potentials information is shown in reference to a multi-dimensional representation of the heart chamber into which catheter **310** is inserted. In an alternative embodiment, imaging unit **220** can include a device configured to create an image of the cardiac chamber from signals recorded from a sensor array catheter, such as catheter **310** of FIG. 3, catheter **500** of FIG. 5A or catheter **500'** of FIG. 5C.

(57) System **300** can include a device for treating a cardiac arrhythmia, such as ablation source **230**, which is electrically attached to electrodes **316** via cable **318**. Alternatively or additionally, ablation source **230** can be operably attached (e.g. via wires, fluid delivery tubes and/or optical fibers) to a different ablation catheter, such as a single or multiple ablation element catheter configured to deliver ablation energy such as RF energy, microwave energy, laser energy, ultrasound energy, cryogenic energy, or other tissue disrupting energy.

(58) As shown in FIG. 3, triangle **T1**, defined by device **100**, is at location Y. Array **315** includes multiple electrodes **316**, such as electrode **316a** positioned at location X. The geometric relationship between triangle **T1** and location X is defined by the solid angle, angle {acute over (ω)}(X,Y). Device **100** includes dipole density module **130** such that each triangle at location y contributes {acute over (ω)}(x,y) times the dipole density $d(y)$ to the potential $V(x)$ at the position x for each electrode of array **315**. Solid angle {acute over (ω)}(x,y), as defined above, corresponds to the triangle at a location y and the electrode at positions x on the multi-electrode array **315**. The dipole density module **130** of device **100** determines from the total measured potential $V(x)$, which is the sum resulting from all the triangles defined by device **100**, the desired dipole density $d(y)$.

(59) When sufficient potential values $V(x)$ are measured (e.g. from 10 to 10,000 with increasing number of measured potentials providing more accurate and/or spatially detailed results), the dipole density $d(y)$ at many equally distributed regions y on the cardiac wall is calculated by solving a linear equation system. By interpolation of the measured potentials (e.g. with help of splines) their number of regions used in the calculation can be increased. The solid angle {acute over (ω)}(x,y) of a region is the sum of the solid angles of the individual triangles in the region on the cardiac wall. This calculation of dipole density results, such as via an automatic computer program forming at least part of dipole density module **130**.

(60) In some embodiments, the results are presented in a visual, anatomical format, such as depicting the dipole densities on a geometric image of the cardiac wall in relation to time (t). This format allows a clinician, such as an electrophysiologist, to determine the activation sequence on

the cardiac wall, such as to determine treatment locations for a cardiac arrhythmia. The results can be shown on a display of mapping unit **210**, or on a separate unit such as a display included with device **100**, display not shown but preferably a color monitor. In a preferred embodiment, the device of the present invention is implemented as, or includes, a software program that is executable by at least one processor. The software program can be integrated into one or more of: an ECG system; a cardiac tissue ablation system; an imaging system; a computer; and combinations of these.

(61) In some embodiments, the multi-electrode catheter **310** includes at least 10 electrodes **316** and/or other sensor, configured to provide local information and/or field information in relation to a multi-dimensional representation of a heart. The electrodes **316** are preferably positioned in a spherical geometry, such as a spherical geometry created in a basket catheter. Elliptical electrode array geometries can be used, such as those provided in the Ensite Array Catheter, manufactured by St. Jude Medical of St. Paul Minnesota. In an alternative embodiment, multiple catheters are inserted into the heart chamber to provide the multiple electrodes.

(62) In some embodiments, the electrodes **316** of the multi-electrode mapping array **315** are repositioned during the method of determining dipole densities. Repositioning of electrodes **316** and/or other sensors or transducers of array **315** can be beneficial to increase the number of measured potential values, if electrode **316** positions are known. Therefore, repositioning is in concordance with adjustment of the geometry map in relation to the multi-electrode mapping array **315**.

(63) In some embodiments, array **315** further comprises one or more transducers, such as one or more ultrasound transducers (USTs), as described variously herein. Also in some embodiments, either alternatively or in addition to the electrodes **316**, array **315** can include non-electrode sensors, such as temperature sensors and/or pH sensors.

(64) FIG. 4 shows an example embodiment of a system **400** configured to determine a database table of dipole and/or surface charge densities of at least one heart chamber of a patient, e.g., as an embodiment of system **300** above. That is, system **400** can be considered to be a somewhat simplified version of system **300**, used to describe an approach for determining dipole and/or surface charge densities using voltage measurements representing cardiac activity. System **400** can be used to map activity of a heart **452** of a patient **450**, e.g., a human. In order to generate a map of surface charge densities (e.g., a surface charge density distribution), the geometry of the given heart chamber is determined or obtained in any of a variety of manners such as those described herein. The multi-dimensional geometry of the cardiac chamber can be assessed, in various embodiments, by currently available and common mapping systems (so-called locator systems) or, alternatively, by integrating anatomical data from CT/MRI scans.

(65) System **400** can include a computer **410** having known types of input devices and output devices, such as a display **420** and printer **430**, and a probe system **440**. For the measurement of potentials, contact and/or non-contact mapping methods can be used. The mapping methods can use probe electrode system **442**, which is connected to the computer **410** via a cable and forms part of probe system **440** as shown in FIG. 4. Probe system **440** can take the form of, or include, a catheter. The computer **410** can be configured to include at least one processor and computer storage device, comprising a set of executable functional modules that perform various tasks to determine dipole and/or surface charge density using cardiac potential information from the probe system **440**.

(66) The probe electrode **442** can take the form of a multi-electrode array with elliptic or spherical shape, in some embodiments. The spherical shape of such an array can have certain advantages for the subsequent data analysis. Alternatively or additionally, other types or even several independent electrodes could be used to measure $V_{sub.e}$ (i.e., the voltage on the endocardium). For example, when considering a cardiac cavity within the endocardium and taking a probe electrode with a surface $S_{sub.P}$, which is located in the blood (i.e. non-contacting), it is possible to measure the

potential $V(x,y,z)$ at point x,y,z on the surface $S_{sub.P}$. In order to calculate the potential at the endocardial surface $S_{sub.e}$ the Laplace equation:

$$(67) \quad V = \left(\frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial y^2} + \frac{\partial^2}{\partial z^2} \right) V = 0 \quad (4)$$

needs to be solved, wherein V is the potential and x,y,z denote the three dimensional coordinates. The boundary conditions for this equation are $V(x,y,z)=V_{sub.P}(x,y,z)$ on $S_{sub.P}$, wherein $V_{sub.P}$ is the potential on surface of the probe $S_{sub.P}$.

(68) The solution is an integral that allows for calculating the potential $V(x'y'z')$ at any point $x'y'z'$ in the whole volume of the heart chamber that is filled with blood. For calculating said integral numerically, a discretization of the cardiac surface is necessary and the so called boundary element method (BEM) can be used.

(69) The boundary element method is a numerical computational method for solving linear integral equations (i.e. in surface integral form). The method is applied in many areas of engineering and science, including fluid mechanics, acoustics, electromagnetics, and fracture mechanics.

(70) The boundary element method is often more efficient than other methods, including the finite element method. Boundary element formulations typically give rise to fully populated matrices after discretization. This result means that the storage requirements and computational time, using BEM, will tend to grow according to the square of the problem size. By contrast, finite element matrices are typically banded (elements are only locally connected) and the storage requirements for the system matrices typically grow quite linearly with the problem size.

(71) With the above in mind, all potentials $V_{sub.P}(x_1',y_1',z_1')$ on the surface of the probe can be measured. To calculate the potential $V_{sub.e}$ on the wall of the heart chamber, the known geometry of the surface of the heart chamber are divided into discrete parts to use the boundary element method. The endocardial potentials $V_{sub.e}$ are then given by a linear matrix transformation T from the probe potentials $V_{sub.P}$: $V_{sub.e}=TV_{sub.P}$.

(72) After measuring and calculating one or more electric potential(s) $V_{sub.e}$ of cardiac cells in one or more position(s) $P(x,y,z)$ of the at least one given heart chamber at a given time t , the surface charge and/or dipole densities are determined. The surface charge density and the dipole density are related to potential according to the following two Poisson equations:

$$(73) \quad V_e = \frac{1}{4\pi\epsilon_0} \int_{S_e} \frac{\rho(P)}{|P-P'|} d(P') \quad (5) \quad V_e = \frac{1}{4\pi\epsilon_0} \int_{S_e} \frac{\nabla \cdot \delta_{sub.S_{sub.e}}(P)}{|P-P'|} d(P') \quad (6)$$

wherein $\rho(P)$ is the surface charge density in position $P=x,y,z$, $\delta_{sub.S_{sub.e}}(P)$ is the delta-distribution concentrated on the surface of the heart chamber $S_{sub.e}$ and ∇ is the dipole density.

(74) A relationship exists between the potential $V_{sub.e}$ on the surface of the wall of the heart chamber and the surface charge (7) or dipole densities (8).

$$(75) \quad V_e(P) = -\frac{1}{4\pi\epsilon_0} \int_{S_e} \frac{\rho(P')}{|P-P'|} d(P') \quad (7)$$

$$V_e(P) = \frac{1}{4\pi\epsilon_0} \int_{S_e} \nabla \cdot \delta_{sub.S_{sub.e}}(P') \frac{1}{|P-P'|} d(P') \quad (8)$$

(For a review see Jackson J D. *Classical Electrodynamics*, 2nd edition, Wiley, New York 1975.)

(76) The boundary element method again provides a code for transforming the potential $V_{sub.e}$ in formulas 7 and 8 into the desired surface charge densities and dipole densities, which can be recorded in a database of surface charge densities and/or dipole densities.

(77) In another embodiment, the electric potential(s) $V_{sub.e}$ is (are) determined by contact mapping. In this case the steps for calculating the electric potential $V_{sub.e}$ are not necessary, because the direct contact of the electrode to the wall of the heart chamber already provides the electric potential $V_{sub.e}$.

(78) In an example embodiment, the probe electrode comprises a shape that allows for calculating precisely the electric potential $V_{sub.e}$ and, thus, simplifies the calculations for transforming

V.sub.e into the discrete charge or dipole densities. That is, the geometry of the electrode can be ellipsoidal or spherical in such an embodiment.

(79) In order to employ the method for determining a database (or table) of surface charge densities of at least one given heart chamber in the context of the present invention, a system comprising at least the following can be used: a) one unit for measuring and recording electric potentials V at a given position $P(x,y,z)$ on the surface of a given heart chamber (contact mapping) or a probe electrode positioned within the heart, but without direct wall contact (noncontact mapping) b) one a/d-converter for converting the measured electric potentials into digital data, c) one memory (e.g., computer memory) to save the measured and/or transformed data, and d) one processor unit for transforming the digital data into digital surface charge density or dipole density data.

(80) It is noted that numerous devices for localizing and determining electric potentials of cardiac cells in a given heart chamber by invasive and non-invasive methods are well known in the art and have been employed by medical practitioners over many years. Hence, the present invention is not limited to any particular types of electrodes or other sensors or transducers. Instead, the invention provides a new and advantageous processing of the available data that will allow for an increase in precision, accuracy and spatial resolution of cardiac activation mapping when compared to prior art systems based on electric surface potentials in the heart only. The present invention provides enhanced diagnostic means for diagnosing cardiac diseases and disorders (e.g. arrhythmias) and other electric status of heart cells including metabolic and functional information.

(81) Catheters and other devices as used in the context of the present invention can include numerous forms of diagnostic catheters such as catheters including one or more electrodes, or therapeutic catheters such as tissue ablation catheters, such as, for example, the catheters described in U.S. patent application Ser. No. 14/422,941, filed Feb. 5, 2015, entitled Catheter System and Methods of Medical Use of Same. Including Diagnostic and Treatment Uses for the Heart. Catheters can be introduced percutaneously into a patient's heart, such as to record electrical activity, measure distances between structures, or deliver energy. External devices and systems can be included, such as body surface electrodes used to record an electrical signal and/or deliver an electric signal, or visualization devices such as external ultrasound or fluoroscopic imaging systems. Any of these catheters or other devices can include one or more electrodes, one or more ultrasound transducers, and/or one or more other sensors or transducers. These electrodes, ultrasound transducers, and/or other sensors or transducers can be positioned at any location on the device, for example at a distal or proximal portion of the device, and can be positioned internal or external to a patient's body.

(82) Any or all of the ultrasound transducers can be used to measure a distance between the transducer and a surface, as is known in the art. One example includes measuring the distance between the ultrasound transducer and a wall of the cardiac chamber. Another example includes measuring the distance between the ultrasound transducer and a component of the same or a separate device.

(83) Any or all of the electrodes of such catheters can be used to record electric "signals" (e.g. voltages and/or currents) at or between the electrode locations. Recorded electric signals can be used to map electrical activity of tissue, such as when an electrode is positioned away from tissue (e.g. in the circulating blood) or when an electrode is in contact with tissue. Algorithms, such as those described hereabove, can be used to correlate recorded signals at multiple non-contacting locations to signals present at one or more tissue locations. The mapped electrical activity and/or other electrical signals can be further processed (e.g. in terms of sources of charge and charge density and correlated with various physiologic parameters related to the function of the heart) and the mapped electrical activity and other recorded and calculated information can be provided visually to one or more operators of the system of the present invention.

(84) Any or all of the electrodes can be used to deliver and/or record electric signals that are generated by the system. Such delivered signals can be emitted from any one or more electrodes,

and can be delivered between any two or more electrodes. Recorded signals can comprise a signal present at a single electrode location or at multiple electrode locations (e.g. a signal representing a comparison of two or more signals present at two or more electrode locations). Recorded signals can be measured, for example, synchronously or asynchronously in terms of voltage and/or current. Recorded signals can be further processed in terms of, for example, resistive and reactive components of impedance and/or the combined magnitude of impedance with any original or processed signal "values" (e.g. those represented by a parameter selected from the group consisting of: instantaneous amplitude; phase; peak; Root-Mean-Square; demodulated magnitude; and combinations of these).

(85) Referring now to FIGS. 5A and 5B, perspective views of the distal portion of a system for diagnosing and/or treating a heart disease or disorder, such as atrial fibrillation and/or ventricular tachycardia, is illustrated. The system can be an embodiment of array **315** of FIG. 3, array **530'** of FIG. 5C, and/or probe electrode system **442** of FIG. 4, or portions thereof. FIG. 5A illustrates an ablation catheter slidingly received by the shaft of a diagnostic catheter and FIG. 5B illustrates the ablation catheter of FIG. 5A in a bent configuration, in accordance with aspects of the present invention.

(86) The probe system **440** includes a diagnostic catheter **500** which is constructed and arranged for insertion into a body location, such as the chamber of a heart. Catheter **500** includes shaft **502**, typically constructed of sufficiently flexible material to allow insertion through the tortuosity imposed by the patient's vascular system. On the distal portion of shaft **502** is an expandable assembly **530**, which includes a plurality of electrodes **541** coupled thereon. Additionally, a plurality of ultrasound transducers **551** are coupled to expandable assembly **530** in this embodiment. Electrodes **541** and USTs **551** are each electrically attached to one or more wires which travel proximally within shaft **502**, connecting to one or more receivers such as receivers **110** and **120** described hereabove in reference to FIG. 1. In some embodiments, catheter **500**, expandable assembly **530**, electrodes **541** and/or ultrasound transducers **551** are constructed and arranged as the similar components described in Applicant's co-pending U.S. patent application Ser. No. 14/003,671, entitled Device and Method for the Geometric Determination of Electrical Dipole Densities on the Cardiac Wall, filed Sep. 6, 2013, the entirety of which is incorporated herein by reference. The number and pattern of electrodes (or other sensors) and USTs can be different in different embodiments; the invention is not limited to the embodiment depicted in FIGS. 5A and 5B which includes a pattern of two electrodes **541** between pairs of USTs **551**. In some embodiments, a repeating pattern of a single electrode **541** followed by a single UST **551** and so on is included, such as is shown in FIG. 5C. In some embodiments, catheter **500** can include other types of electrodes or other sensors, e.g., temperature and/or pH sensors, either in addition to or as an alternative to the electrodes shown.

(87) The system further comprises an ablation catheter **520**, which includes shaft **522**. Shaft **522** includes at least one ablation element **561**, located at a tip or otherwise on a distal portion of shaft **522**. Ablation element **561** is constructed and arranged to deliver energy to tissue, such as when ablation catheter **520** is attached to a source of energy.

(88) Shaft **502** includes a lumen **526** traveling from at least a proximal portion of shaft **502** (e.g. from a handle, not shown but typically positioned on shaft **502**'s proximal end) to a distal portion of shaft **502** (e.g. to shaft **502**'s distal end). Shaft **502** of ablation catheter **520** and lumen **526** of diagnostic catheter **500** are constructed and arranged to allow shaft **522** of ablation catheter **520** to be slidingly received by lumen **526**. Lumen **526** can be further configured to slidingly receive additional catheters or other elongate devices, such as prior to insertion of diagnostic catheter **500** into a body, or after diagnostic catheter **500** has been inserted into a body.

(89) Diagnostic catheter **500** can be used for mapping tissue such as an organ or portion of an organ (e.g. a portion of a heart wall). Multi-dimensional anatomical mapping information collected by diagnostic catheter **500** can be used by the system (e.g., computer system **400**) to create a multi-

dimensional display of an anatomical location of which at least a portion is to be treated by ablation catheter **520**. Diagnostic catheter **500** can be coupled to a computer system, e.g., computer system **400**) configured to display anatomical mapping information generated by diagnostic catheter **500**, such as volumes, locations, shapes, contours, and movement of organs, nerves, and other tissue within the body. Diagnostic catheter **500** can be coupled to the computer system **400** to display the electrical mapping information generated by diagnostic catheter **500**, such as to display dipole mapping or other information as has been described above. Additionally, the location of ablation catheter **520** or other inserted devices can be displayed, such as their position relative to tissue or diagnostic catheter **500**. For example, diagnostic catheter **500** can be used to map the heart, while ablation catheter **520** can be directed to a tissue location in the heart targeted for treatment (e.g. targeted for treatment based on information provided by diagnostic catheter **500** and/or another component of system **400**). For example, ablation catheter **520** can be configured to ablate cardiac tissue to treat a patient suffering from a cardiac arrhythmia, such as atrial fibrillation, atrial flutter, supraventricular tachycardias (SVT), Wolff-Parkinson-White syndrome, and ventricular tachycardias (VT). An ablation catheter will be described herein as a form of a treatment device for purposes of conveying aspects of the invention, but a different type of treatment device (e.g., a pacing device; a defibrillation device; a stent delivery device; a drug delivery device, a stem cell delivery device, or the like) can be used in other embodiments in combination with diagnostic catheter **500**. In some embodiments, one or more of these treatment devices is inserted through a lumen of diagnostic catheter **500**.

(90) In some embodiments, the system is configured to access the left atrium of the patient while utilizing a single transseptal puncture through which all the catheter components of system access the left atrium (and subsequently the left ventricle in some cases). In other embodiments, the system is configured to access the left ventricle of the patient while utilizing a single crossing of the aortic valve through which all the catheter components of the system access the left ventricle (and subsequently the left atrium in some cases).

(91) The system can include sheath **504**, for example a standard access sheath, such as a standard transseptal access sheath. In some methods, sheath **504** can be inserted through the atrial septum and into the left atrium, followed by the insertion of diagnostic catheter **500** through a lumen of sheath **504**. Subsequently, ablation catheter **520** can be inserted through lumen **526** of diagnostic catheter **500**. In other methods, sheath **504** is inserted into the left atrium, followed by the simultaneous insertion of diagnostic catheter **500** and ablation catheter **520** (e.g. diagnostic catheter **500** is inserted with ablation catheter **520** residing at least partially within lumen **526**). In some embodiments, sheath **504** can comprise a steerable sheath. Shaft **502** comprises a diameter along the majority of its length such as to be slidably received by sheath **504**. In some embodiments, shaft **502** comprises a diameter less than or equal to 15 Fr. In some embodiments, diagnostic catheter **500** and/or ablation catheter **520** can be steerable, so that manual, semi-automatic or automatic steering can be performed by an operator and/or a robotic control assembly of the system, as shown in FIG. 5B.

(92) Diagnostic catheter **500** can be positioned in the left atrium and can provide information selected from the group consisting of: electrical information, such as voltage information (e.g. voltage information which is analyzed to produce surface charge information); anatomical geometry information, such as heart wall surface information or heart wall thickness information; other physiologic and anatomical information, such as those described herein; and combinations of these. Shaft **502** of diagnostic catheter **500** can be configured to be inserted into the heart via the venous system, for example a vein in a leg or a vein in a neck. Shaft **502** can include a braid within its outer and inner surfaces, not shown but typically a braid of plastic or metal fibers that enhance the structural integrity and performance of shaft **502**. In some embodiments, the braid of shaft **502** can include conductors (e.g. one or more conductors connected to an electrode **541** and/or an ultrasound transducer **551**).

(93) As described above, diagnostic catheter **500** includes lumen **526** extending from a proximal portion to a distal portion of shaft **502**, for example from a proximal end to a distal end of shaft **502** so as to allow a separate catheter or other elongate device to be inserted therethrough, such as ablation catheter **520**, as shown. Alternatively or additionally, the inserted catheter or other elongate device can include a diagnostic catheter, such as a diagnostic catheter configured to record signals from a location selected from the group consisting of: the left atrium; the right atrium; the Bundle of HIS; the right ventricular apex; a pulmonary vein; the coronary sinus. Alternatively or additionally, the inserted catheter can comprise another catheter device.

(94) Diagnostic catheter **500** can include expandable assembly **530**, which is positioned at the distal end of shaft **502**—here in the form of a basket array. As illustrated, expandable assembly **530** includes an array of splines **531**, each spline **531** having proximal segment **532**, middle portion **534**, and distal segment **533**. Proximal segment **532** of each spline **531** connects to shaft **502**, via connection point **527**. The distal ends of each spline **531** connect in a circumferential ring configuration to form opening **535**. Opening **535** allows a device to pass through, such as a device inserted into lumen **526**, for example shaft **522** of ablation catheter **520**. In some embodiments, expandable assembly **530** can include one or more guide elements configured to guide a device through opening **535**.

(95) Expandable assembly **530** can be constructed and arranged to be positioned in the expanded shape shown in FIGS. 5A and 5B. The expanded geometry of assembly **530**, including at least two or more splines **531** in an expanded or partially expanded state (hereinafter “expanded state”), can be described as a “basket” having a substantially hollow center and spaces between adjacent splines **531**. In the illustrated embodiment, the basket is spherical, but can include any suitable shape, for example an ellipsoid or other symmetric or asymmetric shape. Thus, in other embodiments, assembly **530** can comprise different shapes or combination of shapes, such as an array of splines **531** where two or more splines **531** comprise similar or dissimilar shapes, dimensions or configurations. In some embodiments, two or more splines **531** include a varied radius of curvature.

(96) Expandable assembly **530** can be biased in an expanded or non-expanded state. In an example embodiment, assembly **530** can be self-expanding such that splines **531** are resiliently biased in the curved geometry shown in FIGS. 5A and 5B. Assembly **530** can automatically expand when assembly **530** exits the distal end of sheath **504**, such as by advancement of shaft **522** and/or retraction of sheath **504**. Alternatively, assembly **530** can be manually expanded, for example via retraction of a rod (not shown) that slides within shaft **502** and is connected to distal end of assembly **530**.

(97) Splines **531** can be constructed of a material selected from the group consisting of: one or more thermoplastic polymers such as polyether block amide, polyurethane and/or polyether ether ketone; one or more of thermoset polymers such as silicon and/or tetrafluoroethylene; one or more metals such as stainless steel and/or shape memory alloys such as nickel titanium alloy; one or more shape memory polymers such as triple shape acrylic; and combinations of these. Generally, any of a number of materials or compositions that are biocompatible, flexible or bendable, and possess any necessary application specific electrical properties can be used for splines **531**.

(98) Splines **531** can include one or more electrodes **541** and/or one or more ultrasound transducers **551** arranged in any combination. For example, in some embodiments, one or more of the following configurations is included: each spline **531** includes at least four, six or eight electrodes **541**; each spline **531** includes at least four, six or eight ultrasound transducers **551**; and combinations of these. In some embodiments, at least one electrode **541** is positioned between two ultrasound transducers **551** on a single spline **531** (such as in the alternating pattern shown in FIG. 5C). In some embodiments, at least two electrodes **541** are positioned between two ultrasound transducers **551** on a single spline **531**.

(99) Each spline **531** can include a similar or dissimilar arrangement of electrodes **541** and/or

ultrasound transducers **551** such as an adjacent spline **531** or any other spline **531** in assembly **530**. In some embodiments, assembly **530** includes eight splines **531**, where each spline **531** can include two to eight electrodes **541** and two to eight ultrasound transducers **551**. In some embodiments, assembly **530** includes six splines **531**, where each spline **531** can include eight electrodes **541** and eight ultrasound transducers **551**. In some embodiments, one or more splines **531** include a number of electrodes **541** that comprises a quantity within one of the quantity of ultrasound transducers **551** that are included on that spline **531**. For example, a spline **531** can include seven electrodes **541** and either six or eight ultrasound transducers **551**. In some embodiments, a set of electrodes **541** and ultrasound transducers **551** can be arranged in an alternating arrangement, such that one or more single ultrasound transducers **551** lies between two electrodes **541**. In some embodiments, some sets of electrodes **541** and ultrasound transducers **551** can be arranged such that one or more single electrodes **541** is positioned between two ultrasound transducers **551**.

(100) Electrodes **541** can be configured to record electric signals such as voltage and/or current signals. The system can utilize the recorded signals to produce electrogram information; dipole mapping information; surface charge information; distance information such as the distance between any device and/or component of the system; and other information or combinations of information described in detail herein. Any or all electrodes **541** can comprise a dipole and/or surface charge mapping electrode, such as an electrode with an impedance or other electrical property configured to provide information related to surface charge or other dipole mapping parameter. In some embodiments, the electrodes **541** are of sufficiently low impedance, such as in the range less than 10,000 ohms, such as to achieve high-fidelity recording of signal frequencies greater than or equal to 0.1 Hz. In some embodiments, one or more electrodes **541** include an iridium oxide coating, such as to reduce the impedance of electrodes **541**. Alternatively or additionally, numerous forms of coatings or other treatments can be included with one or more electrodes **541**, such as a platinum black coating or a carbon nanotube layer. In addition or as an alternative to recording electric signals, electrodes **541** can be constructed and arranged to deliver electric energy, such as radiofrequency energy. In some embodiments, diagnostic catheter **500** can deliver therapy, such as an ablation therapy delivered to tissue, in addition to its function as a diagnostic catheter, e.g. providing electrical, anatomical and/or device mapping information. In some embodiments, one or more electrodes **541** each comprise one or more coils, such as when the one or more coils are configured to create one or more magnetic fields.

(101) Electrodes **541** can include various materials such as non-polarizing metals and/or polarizing metals. In some embodiments, one or more electrodes **541** comprise at least one non-noble metal such that electrodes **541** oxidize when in contact with at least one of blood, blood plasma or saline solutions. In some embodiments, electrodes **541** include a coating, for example a coating selected from the group consisting of: a metal oxide coating; a conductive polymer coating; and combinations of these. In some embodiments, one or more electrodes **541** can include an outer layer and an inner layer, such as when the outer layer comprises an impedance lowering coating or other layer and the inner layer comprises a layer configured to bond the outer layer to the metallic and/or other remaining portion of the one or more electrodes **541**.

(102) Ultrasound transducers **551** can be configured to record distance information such as the distance between any device and/or component of the system and tissue such as cardiac wall or other solid tissue. Ultrasound transducers **551** can include a construction comprising: single or multi-element piezoelectric ceramics; piezoelectric micro-machined ultrasound transducers (pMUT); capacitive micro-machined ultrasound transducers (cMUT); piezoelectric polymers; and combinations of these.

(103) In some embodiments, diagnostic catheter **500** can include a multi-layer or laminate construction, for example where shaft **502** includes a tube inside of another tube; where shaft **502** includes a liner such as a liner constructed of a lubricous material such as PTFE; where shaft **502** includes a braided construction such as a braid positioned between two layers of shaft **502**; and

combinations of these. In some embodiments, diagnostic catheter **500** can be steerable, for example via the incorporation of a pull wire and anchor (not shown). Typically, diagnostic catheter shaft **502** outer diameter is less than 15 Fr.

(104) Ablation catheter **520** of FIGS. **5A** and **5B** includes ablation element **561** positioned on shaft **522**, for example on a distal portion or the distal tip of shaft **522**. Ablation element **561** can include a functional element selected from the group consisting of: one or more electrodes; a vessel or port configured to deliver cryogenic energy; a laser diode; an optical fiber configured to deliver ablative light energy; a microwave energy delivery element; an ultrasound energy delivery element; a drug, stem cell, or other agent delivery element; an abrasive or other mechanical ablative energy delivery element; and combinations of these. In the case where ablation element **561** includes one or more electrodes, the electrodes can include electrodes constructed and arranged to deliver radiofrequency (RF) energy. In the case of multiple electrodes, the electrodes can be configured for monopolar and/or bipolar RF energy delivery. In some embodiments, ablation element **561** can include an array of elements. Ablation catheter **520** can be operably connected to a device configured to deliver energy to ablation element **561**, such as ablation source **230** of FIG. **3**. Typical energy delivered by ablation element **561** comprises an energy selected from the group consisting of: electromagnetic energy such as radiofrequency energy; cryogenic energy; laser energy; light energy; microwave energy; ultrasound energy; chemical energy; and combinations of these.

(105) In FIG. **5B**, ablation catheter **520** can be steerable, similar to diagnostic catheter **500** and sheath **504**, such as via a pull wire and anchor. Here, ablation catheter **520** has been steered in a curved geometry **525**, as shown, to cause ablation element **561** to exit expandable assembly **530** of diagnostic catheter **500**, passing between two middle portions **534** of two splines **531**. Ablation catheter **520** can be steered and advanced by an operator such as a clinician, so as to exit at any opening of the expandable assembly **530**, including the space between two splines **531** or through opening **535**, such as to be further advanced to contact or move proximate to cardiac tissue, e.g., for ablation.

(106) Various timing sequences can be used for sending and/or recording signals to and/or from electrodes **541** and/or USTs **551** on splines **531** of expandable assembly **530** in FIGS. **5A** and **5B**. In the preferred embodiment, a timing sequence is used that provides a pattern of “ringing” the USTs that alternates between splines. The timing sequence can also include timing of driving some of the spline electrodes and skin patch electrodes (optionally included) for localization. In some embodiments, electrodes **541** are continuously recorded. In some embodiments, an electrode **541** and a UST **551** share a common conductor, and an electrode **541** does not record when the UST **551** sharing the common conductor is receiving a ring signal. The timing sequence of sending and/or recording signals can be computer controlled. A full cycle of a timing sequence can be, for example, 100 ms or less (e.g. a cycle in which a series of sequential ring signals are sent to each UST **551**). In some embodiments, a timing sequence is modified over time, such as to change the time of a full cycle and/or to modify the order in which signals are sent (e.g. to ring a UST **551**) or recorded (e.g. from an electrode **541**).

(107) Referring now to FIG. **5C**, a perspective view of an alternative layout of electrodes and ultrasound transducers (USTs) positioned on an expandable array is illustrated, in accordance with aspects of the present invention. Probe system **440** includes mapping catheter **500'** and sheath **504** through which the distal portion of mapping catheter **500'** has been inserted. Mapping catheter **500'** includes array **530'** positioned on the distal end of shaft **502'**. Array **530'** comprises multiple splines **531** upon which an alternating pattern of a single electrode **541** followed by a single UST **551** is positioned, as shown. Electrodes **541** and USTs **551** are each electrically attached to one or more wires which travel proximally within shaft **502'**, connecting to one or more receivers such as receivers **110** and **120** described hereabove in reference to FIG. **1**. System **440** can include an ablation catheter, such as an ablation catheter similar to ablation catheter **520** of FIGS. **5A** and **5B**. The ablation catheter can be advanced into the heart alongside shaft **502'** and sheath **504**. In some

embodiments, shaft **502'** comprises a lumen, such as shaft **502** of FIGS. **5A** and **5B**, through which an ablation catheter or other device can be inserted.

(108) FIG. **6** provides an example embodiment of a computer architecture **600** that can form part of system **400** configured to determine a database table of dipole densities of at least one heart chamber of a patient, which can communicate with the probe system **440** of FIGS. **4**, **5A** and/or **5C**, as examples. Architecture **600** can include standard interface modules **610** for probe system **440** (and electrodes **442** and/or catheters **500**, **500'** and **520**) and interface modules **620** for interfacing with output devices **420**, **430**. Architecture **600** can further include cardiac information display controller **650** for receiving, interpreting, generating, processing and/or providing cardiac information. The computer **410** includes at least one processor **640** and at least one computer memory **680** connected to elements **610**, **620**, **630**, **640** and/or **650** via bus **660** as shown. The architecture **600** further includes an electrical potential to surface charge density and/or dipole density converter module **630**. Module **630** includes executable computer instructions necessary for carrying out the methods described herein, when executed by processor **640**, wherein the results of such processing are stored in memory (e.g., a database, data storage system, or data storage device) **680**—as would be understood by one skilled in the art having the benefit of this disclosure. That is, module **630** is preferably configured to determine dipole and/or surface charge densities from data received, at least in part, from probe system **440**, as described herein or otherwise.

(109) FIG. **7** and FIG. **8** summarize embodiments of methods for determining and storing surface charge densities and dipole densities in accordance with aspects of the present invention, respectively, which have been described in detail above.

(110) In method **700** of FIG. **7**, in Step **702**, system **400** is used to measure and/or calculate one or more electric potential(s) $V_{sub.e}$ into one or more position(s) P within a heart chamber at a given time t . In Step **704**, $V_{sub.e}$ is transformed into a surface charge density $\rho(P',t)$. In Step **706**, the surface charge density $\rho(P',t)$ is stored in a database table. The method is repeated if there is another P , in Step **708**.

(111) In method **800** of FIG. **8**, in Step **802**, mapping system **400** is used to measure and/or calculate one or more electric potential(s) $V_{sub.e}$ in one or more position(s) P within a heart chamber at a given time t . In Step **804**, $V_{sub.e}$ is transformed into said dipole density $v(P',t)$ by using an algorithm suitable for transforming an electric potential into surface charge density. In Step **806**, the dipole density $v(P',t)$ is stored in a database table. The method is repeated if there is another P , in Step **808**.

(112) In accordance with aspects of the present invention, the architecture **600** further includes a cardiac information display (CID) controller **650**. In this embodiment, CID controller **650** is configured to generate and/or provide information sufficient for at least one display device to render cardiac information, which can include, but is not limited to, dipole density and/or surface charge density information. The cardiac information could also include cardiac voltage (or potential) information, a graphical model of a heart or portion of a heart (or other organ), images of a heart or portions thereof (or other organ), other local information such as temperature and/or pH information, other field information (e.g. other than voltage information), or combinations thereof. The rendering of the heart and/or portion of the heart (or other organ) could be two-dimensional (2-D), three-dimensional (3-D), or combinations thereof. Such cardiac information can also include an electrocardiogram (EKG or ECG), e.g., such as a graph of the heart's electrical activity versus time. The above types of cardiac information could be displayed in various combinations, e.g., to include dipole density and/or surface charge density information, and displayed in 2-D, 3-D, or combinations thereof.

(113) Such cardiac information could be stored in memory **680** for real-time, near real-time, or subsequent display. The display could be a computer monitor, tablet, smartphone, television, or other type of display device or device comprising such a display. The display(s) could be local, remote, or combinations thereof (if more than one display). The display(s) could be wired, wireless,

or combinations thereof (e.g. if more than one).

(114) For purposes of describing the differences in the display of information, different types of information can be distinguished. For example, dipole and charge density information is different from voltage (or potential) information. For example, dipole and charge density information, e.g., from methods **700** and **800**, can be considered to be types of “source information,” which is data representing, at a location in 3D space, a physical property or properties discrete to the specific location in 3D space, e.g., similar to temperature or pH information which is also source information. In contrast, voltage (or potential) information can be considered to be “field information,” which is data representing, at a location in 3D space, a physical property or properties of a continuum extending through the 3D space.

(115) FIG. **9** describes an embodiment of a method **900** of displaying dipole and/or charge density information in at least one electronic or computer display, preferably in conjunction with at least one image of a heart. The method can be implemented by system **400**, as an example. In this embodiment, in Step **902**, voltages are measured from multiple cardiac locations (e.g. within or on the endocardial surface of a heart chamber) using at least one electrode, as field information. In Step **904**, from the voltages (or field information), a plurality of dipole and/or charge densities (or source information) are determined by the computer processor, e.g., on multiple locations on the surface of the heart, from the measured voltages. In Step **906**, at least one image of the heart is electronically rendered on at least one (local and/or remote) display screen. In Step **908**, a distribution of dipole and/or charge densities is electronically rendered on the at least one display screen, e.g., in conjunction with the image(s) of the heart. In Step **910**, which is an optional step, a voltage information is electronically rendered on the at least one display screen, e.g., in conjunction with the image(s) of the heart. In various embodiments, Step **910** can be a user selectable options, wherein, for example, voltage information could be toggled on and off under the user's control.

(116) In some embodiments, Step **902** comprises measuring voltages from an array of electrodes, serially or sequentially. In some embodiments, Step **902** further comprises moving one or more electrodes from a first location to one or more different locations and measuring voltages from the one or more electrodes at each location.

(117) In some embodiments, Step **908** comprises rendering a series of dipole and/or charge densities on the display screen, such as a series of images representing a complete cardiac cycle (i.e., heartbeat). In these embodiments, the series of images representing a complete cardiac cycle can be repeated (i.e. looped). Alternatively or additionally, the series of images representing a complete cardiac cycle can be updated (e.g. continuously updated and/or updated at discrete time intervals). In some embodiments, a series of images representing a complete cardiac cycle can be displayed with a static image of the heart (e.g. a single heart image rendered on the screen in Step **906**, such as an image representing the end of systole or diastole). Alternatively, a series of images representing a complete cardiac cycle can be displayed with a corresponding series (e.g. a temporally corresponding series) of images of the heart that show the contraction and expansion of the heart during a cardiac cycle.

(118) FIG. **10** is an exemplary embodiment of a display **1000** of dipole and/or surface charge density information that can be generated on one or more devices, in accordance with aspects of the present invention. In this example, dipole density information is shown, but in other embodiments, additionally or alternatively, surface charge density, pH information, temperature information and/or other source or field information could be included. Display **1000** could comprise any now known or hereafter developed graphical display, such as a computer monitor, tablet, cellphone, television, display panel, Google glass, and so forth. Alternatively or additionally, information provided on display **1000** could be provided on paper such as via a printer, or sent wirelessly to a separate device. Display **1000** can include a patient information box, display area **1002** that provides relevant information about the patient (e.g. patient name, age, hospital patient ID, and the like) from whom the cardiac information was collected.

(119) Voltage is a “force field” that spreads out from “dipolar” sources of charge, (e.g. foci in AF diagnostics), so is field information, as that term is used herein. Region of influence typically spans several centimeters in a chamber of the heart. Voltage presents a broad, blurred view of the physiologic state, similar to de-focusing a camera lens. Voltage measurements include far-field interference from adjacent locations such as adjacent chambers. In contrast, dipolar charge sources (e.g. “focal pockets”) are source information, as that term is used herein, that can be derived from multiple voltage measurements (i.e., field information). Dipole and surface charge density images represent a refined, high-resolution view of physiologic information that span a very small area (e.g., –1 mm or smaller). Far-field interference from adjacent locations is reduced or eliminated. Therefore, the dipole density method is similar to re-focusing a camera lens to significantly improve resolution of local physiologic state and activity.

(120) In this embodiment, display **1000** includes a dipole (or surface charge) density display area **1010** in which dipole (or surface charge) density information can be displayed, as a form of source information. In this example, the dipole (or surface charge) density information ($v(P',t)$) **1012** is displayed overlaid on an image of a heart, heart image **1011**. In other embodiments, heart image **1011** is not included. Heart image **1011** can be an image or model of the particular heart being analyzed or a representative model of a heart, either of which can be stored in computer memory. The dipole density information **1012** is shown for only a portion of the heart image **1011**, which can be a user selectable portion. In some embodiments, the dipole density information **1012** can be displayed over substantially all of heart image **1011**. In still other embodiments, the system, e.g., the electrical potential to surface charge/dipole density converter module **630**, can be configured to render the dipole density information **1012** for a portion of the heart to which the system attributes abnormal behavior or indications, as diagnosed using the dipole (or surface charge) density information and/or voltage measurement information. The dipole density information **1012** and/or the heart image **1011** can represent a dynamic series of information sets, presented in a dynamic format (e.g. series of sequential frame of images). In some embodiments, dipole density information **1012** is updated throughout one or more cardiac cycles and presented on a static or dynamic heart image **1011**, as described hereabove in reference to the method of FIG. **9**. The dipole density information **1012** or other patient information included in display **1000** can be shown via a differentiating map, such as a display that differentiates values of information by varying a parameter selected from the group consisting of: color (e.g. a color map); contrast; brightness; hue; saturation level; and combinations thereof.

(121) In some embodiments, display **1000** can include one or more other display areas provided in conjunction with the dipole (or surface charge) density area **1010**. Such other display areas can be secondary display areas displaying information related to (e.g. related to and/or mathematically derived from) the dipole (or surface charge) density information in area **1010**. As an example, a dipole (or surface charge) density time-plot display area **1014** can be provided that can be configured to dynamically show a plot of dipole density versus time at one or more heart chamber surface locations (one shown), which could correspond to dynamically changing dipole density information displayed in the dipole (or surface charge) density area **1010** (e.g. shown in synchrony with the information displayed in area **1010**). In some embodiments, the surface locations are operator selectable.

(122) The dynamically displayed information (e.g. area **1010**, area **1014** and/or other dynamically displayed information displayed on display **1000**) can preferably be played, paused, stopped, rewound, fast forwarded and/or otherwise controlled, using controls **1030**. The dipole (or surface charge) density area **1010**, dipole density time-plot area **1014** and/or other information of displayed on display **1000** can be independently controlled (e.g. via controls **1030**) and/or temporally linked (e.g. temporally linked in static or dynamic views), in some embodiments. Another optional secondary display area could be an analysis display area **1016**. In this embodiment, analysis area **1016** includes diagnostic information determined from the dipole density data. More specifically, in

this case, the analysis area **1016** indicates an assessment of a heart condition and/or a cause of a heart condition (e.g., a rotor or other aberrant electrical activity resulting in an arrhythmia such as atrial fibrillation), at least in part, from the dipole density data. The indication could include one or more dipole density values and associated time stamps corresponding to dynamically displayed dipole density information in area **1010** that is automatically (e.g. by the system) and/or manually (e.g. by an operator of the system) marked for future viewing and/or assessment.

(123) In various embodiments, the display **1000** can optionally include a second display area **1020** (or voltage measurement information area **1020**), within which can be electronically rendered the voltage measurement information **1022** in conjunction with heart image **1011**. Here, in this example, the measured voltages **1022** are projected or overlaid onto a surface of heart image **1011**. Therefore, in accordance with aspects of the present invention, the system and display can overlay the distribution of dipole densities **1012** on the surface of heart image **1011** and project the measured voltages **1022** on the surface of the second heart image **1011**, e.g., at the same time and in synchrony, as shown. As described hereabove, the dynamically displayed information in area **1020** can preferably be played, paused, stopped, rewound, fast forwarded and/or otherwise controlled, using controls **1030** (e.g. independently or in synchrony with area **1010**).

(124) In other embodiments, a static, single image of the heart can be shown and the user can have the ability to selectively overlay or project dipole density information, surface charge density information, and/or measured voltage measurement information on the single image. Therefore, display **1000** can include one or more controls (e.g. touch screen controls) responsive to user interaction to selectively toggle between the rendering of the dipole densities, surface charge densities, and/or voltage measurements on the image of the heart on the display screen (e.g. sequentially and/or simultaneously such as by using an overlay as described herebelow in reference to FIG. **11**).

(125) In some embodiments, display **1000** can include one or more other display areas (e.g. in conjunction with the voltage measurement information area **1020**). Such other areas can be secondary areas displaying information related to the voltage measurement information area **1020**. As an example, a voltage measurement time-plot **1024** can be provided that can be configured to dynamically show a plot of measure voltage versus time at one or more heart chamber surface locations (one shown), which could correspond to dynamically changing voltage measurement information displayed in the voltage measurement information area **1020**—at one or more endocardial surface locations (e.g. synchronized to one or more operator selected surface locations) on the same time scale. That is, the time scale is the same as the time scale in the dipole density area **1010**, and related secondary areas. In various embodiments, the user can select whether or not areas **1010** and **1020** are synchronized, and whether or not secondary areas are synchronized with the corresponding primary area **1010** and **1020**. The dynamically displayed information can preferably be paused, stopped, rewound, and/or fast forwarded. The voltage measurement information area **1020** and voltage measurement information time-plot area **1024** and/or other information displayed on display **1000** can be independently controlled (e.g. via controls **1030**) and/or temporally linked (e.g. temporally linked in static or dynamic views), in some embodiments.

(126) Another optional secondary area could be an analysis area **1026**. In this embodiment, analysis area **1026** includes diagnostic information determined from the voltage measurement information. More specifically, in this case, the analysis area **1026** indicates a heart condition (e.g., atrial fibrillation) determined, at least in part, from the voltage measurement information. The indication could include a voltage measurement information value and time stamp corresponding to the dynamically displayed voltage measurement information in area **1020**.

(127) In various embodiments, display **1000** can include one or more graphical mechanisms or other controls responsive to user interaction to change an orientation in two-dimensional (2D) or three-dimensional (3D) space of the image of the heart **1011** with overlaid dipole densities **1012**. For example, one or more areas can include controls **1032** to zoom in and out or controls **1034** to

rotate or turn the heart and overlaid information in an area (e.g., areas **1010** and **1020**).

(128) In various embodiments, as noted, the displays in areas **1010** and **1020** can be dynamically updated, where the system dynamically updates the distribution of dipole densities by altering visual characteristics thereof corresponding to changes in the dipole densities and/or measured voltages over time. Altering the visual characteristics can comprise altering at least one of color, intensity, hue, and shape of at least a portion of the rendered distribution of dipole densities **1012** and/or voltage measurement information **1022**. The electronic rendering of the distribution of dipole densities **1012** on the display screen can be performed in real-time in response to voltage measurements obtained in real-time using the at least one electrode, as described above. The electronic rendering of the distribution of dipole densities on the display screen can be performed as post processing and/or analysis based on voltage measurements stored in at least one computer memory.

(129) The display **1000** can include one or more graphical controls **1040** responsive to user interaction to record the user interactions with the display, e.g., on the same temporal time scale as the information displayed in areas **1010** and **1020**, and related secondary areas (if any). For example, the system could be configured to receive audio inputs from a user interacting with the display **1000**. Inputs that could be recorded and/or saved can include, but are not limited to: text inputs, audio inputs, and graphical inputs (or interactions). In such cases, a Practitioner Notes box **1042** could be included for textual inputs by a user and an audio input control **1044** can be included on enable and disable audio inputs. Controls **1030** can be used to play, rewind, and fast forward changes in the rendering of the distribution of dipole densities on the display screen over time, along with any recorded user interactions.

(130) FIG. **11** is another embodiment of a user interface display **1100** of dipole and/or surface charge density information that can be generated on one or more devices, in accordance with aspects of the present invention. The display of FIG. **11** can also include any of the interactive controls or features of the display of FIG. **10**. Display **1100** includes area **1110** including one or more anatomical views of physiologic activity on one or more surfaces of a heart, such as the Right Posterior Oblique (RPO) view shown on the left and the Left Anterior Oblique (LAO) view shown on the right.

(131) The anatomic images of area **1110** include a representation of sets of varying source and/or field data correlated in 3D space with surfaces of a heart and differentiated in magnitude with a color map, in the preferred embodiment. Alternatively or additionally, data can be differentiated with other graphical properties such as contrast, brightness, hue and/or saturation levels. These value-differentiating maps can represent the magnitude of field data (e.g. voltage data) and/or source data (e.g. dipole density or charge density data), e.g., at the same point in time in each view, simultaneously (e.g. via an overlay) or sequentially (e.g. by toggling the views). In some embodiments, an image of the heart is also shown, simultaneously or sequentially with the field and/or source data, as described hereabove in reference to FIG. **10**. A heart image can comprise a static heart image (e.g. the image of the heart at the end of systole or diastole upon which field and/or source information is displayed), or a dynamic heart image such as a beating heart image. A static or dynamic heart image can be routinely updated, such as an image that is updated based on signals received from the ultrasound transducers of the present invention.

(132) In some embodiments, field information (e.g. voltage information) and source information (e.g. dipole density or surface charge density information) is overlaid, such as when voltage data is displayed as a “bottom layer” and dipole density data is partially transparently displayed “on top” of the voltage data. This overlay could be done using an algorithm that mixes the overlaid colors (a “pigment-based” mixing), or by other methods, such as methods that affect brightness, contrast, or other techniques, known to those skilled in computer color manipulation and image processing. Different layers can be turned on and off, or toggled, color schemes modified, views changed, and so on, in response to an operator instruction or input or the presence of a condition determined by

the computer, e.g., the cardiac information display controller **650** in FIG. **6**. Each view can be controlled or changed independently or together—as a related pair. Next to each image **1111A**, **1111B** a 3D frame of reference icon **1112A**, **1112B** is displayed to aid the user in understanding the orientation of the heart image provided (e.g. anterior, posterior, medial, lateral and combinations of these, all standard orientations used in clinical imaging).

(133) One or both of the views can display real (or near-real) time information that can dynamically change in response to changes in source and/or field information represented in or otherwise used in the views. For example, the information displayed in both views can dynamically change in response to measured, sensed, or calculated changes in represented source and/or field information, such as voltages, dipole density, surface charge density, temperature, pH, and so forth. Such changes can be embodied in changes in colors, hues, intensities, dynamic patterns, and so forth used in the views.

(134) In this embodiment, in conjunction with the anatomical cardiac views, there is displayed an electrocardiogram (EKG or ECG) representing electrical activity of the heart in EKG area **1120**. The EKG area **1120** and anatomical images **1111A**, **1111B** can dynamically change together, in various embodiments. EKG area **1120** translates the heart's electrical activity into line tracings on the display. In various embodiments, the EKG area **1120** can be turned on and off by the user.

(135) In this embodiment, the display includes two tables **1132** and **1134** that include data gathered from the ultrasound transducers, electrodes, and/or other sensors of the present invention. The data (as shown in table **1132**) could represent the chamber or system as a whole (Quantitative Data) and can also represent data (as shown in table **1134**) specific to a cursor position or area selected by a user (e.g., a physician), e.g., by drawing a box with a cursor or placing the cursor over the image, as with cursor C (+) in FIG. **11**.

(136) In some embodiments, display **1100** further includes area **1121**. Area **1121** can be configured to provide information provided by one or more of the ultrasound transducers, electrodes and/or other sensors of the present invention, such as ultrasound transducers **551**, electrodes **541** of FIG. **5C** described hereabove. Area **1121** can provide various patient information, such as calculated patient information (hereinafter “calculated information”) as described herein. In some embodiments, area **1121** comprises quantitative and/or qualitative patient information related to a physiologic parameter of a patient that comprises calculated information determined by the sensor information (e.g. determined by mathematically processing the sensor information). Calculated information can comprise patient information selected from the group consisting of: cardiac chamber volume; cardiac wall thickness; average cardiac wall thickness; a cardiac chamber dimension; ejection fraction; cardiac output; cardiac flow rate; cardiac contractility; cardiac wall motion; other cardiac function information; voltage at a cardiac surface location; dipole state at a cardiac surface location; and combinations thereof. In these embodiments, voltage and/or dipole information can be calculated from signals recorded by one or more electrodes. In these embodiments, signals from one or more ultrasound transducers can be used to determine cardiac geometry information. Signals from one or more ultrasound transducers can be analyzed to determine the level or status one or more of: chamber volume; average wall thickness; chamber dimensions; ejection fraction; cardiac output; flow rate; contractility; wall motion; voltage; dipole state; and wall thickness. The information recorded by the ultrasound transducers can be used to dynamically define the geometric shapes of the chambers and walls of the heart, and one or more algorithms can be included to create quantitative measures of the these cardiac parameters, avoiding the need for: transeophageal and/or Transthoracic electrocardiography (TTE/TEE) and/or Intracardiac Echo (ICE) to measure wall motion such as abnormal wall motion; Functional MRI to measure contractility, cardiac output and/or stroke work; Positron Emission Tomography (PET Scan) and/or Single-Photon Emission Computed Tomography (SPECT Scan) to measure metabolic performance; Thermodilution and/or Impedance Volumetry catheters to measure cardiac output; and combinations of these. In some embodiments, area **1121** provides patient information selected

from the group consisting of: blood pressure; heart rate; cardiac cycle length; pulse oximetry; respiration rate; and combinations of these. In some embodiments, the information provided in area **1121** and/or other areas of display **1100** is updated relatively continuously over time, e.g. at least every 10 seconds. In some embodiments, area **1121** includes an image of the heart, and cardiac information such as those listed above can be displayed in relation to the heart image (e.g. wall thickness displayed relative to the associated wall, chamber volume within the associated chamber, etc.). In some embodiments, quantitative information is displayed in numeric form (i.e. graphic elements of display **1100** comprising one or more numerals). Alternatively or additionally, quantitative information can be displayed with one or more graphic elements such as a line chart, bar chart and/or pie chart. In some embodiments, the information provided in area **1121** and/or other areas of display **1100** is updated on a periodic basis, such as once per minute, once per 5 minutes or once per 10 minutes. The information provided in area **1121** can be calculated information based on information collected over time, such as patient information that is summed, averaged, integrated, differentiated and/or otherwise mathematically processed by one or more algorithms. The patient information can comprise source information (e.g. dipole density of surface charge density information). In some embodiments, one or more algorithms find an average, a mean, a maximum level, a minimum level of one or more patient parameters. In some embodiments, one or more algorithms compare calculated information or other patient information to a threshold to produce calculated information. For example, if the level of a particular parameter exceeds a threshold (e.g. is over a maximum threshold or under a minimum threshold), the system can enter a new state such as an alert state. In some embodiments, after exceeding a threshold, the appearance of already displayed patient information can change, such as a color change (e.g. a change to red) and/or a font change (a change to italics or a change in boldness). Alternatively or additionally, an alert can be activated (e.g. an audible or tactile alert) to notify an operator of the system (e.g. a clinician) that a threshold has been exceeded.

(137) Referring now to FIG. **12**, a flow chart of an embodiment of a method for generating a model of a heart and providing a graphical representation of cardiac information on a display screen is illustrated. Method **1200** comprises displaying source information (e.g. dipole and/or surface charge density information) relative to a heart image on a display screen. Other information, such as field information (e.g. voltage information or other field information relative to the same or different cardiac locations) can be displayed, such as in a side-by-side arrangement, an overlay arrangement and/or an arrangement where the two sets of information are presented sequentially (e.g. toggled back and forth) in the same location (an “alternating arrangement”). In some embodiments, one or more cardiac parameters are quantified or otherwise determined utilizing the systems and devices of the present invention described hereabove. Cardiac parameters determined can include cardiac dimensions (e.g. chamber volume or wall thickness), cardiac function parameters (e.g. ejection fraction or cardiac output) and/or cardiac health,

(138) In Step **1210**, the distal end of a catheter of the present invention is placed into one or more body locations, such as one or more cardiac chambers of a patient. The catheter comprises at least one electrode and at least one ultrasound element. The catheter includes one or more electrodes positioned on a distal portion of the catheter and configured to record electrical activity in tissue and/or deliver ablation energy. In Step **1220**, anatomical information, such as tissue location, tissue movement, tissue thickness and/or tissue contour information can be determined via the at least one ultrasound element, typically an element configured to transmit and receive ultrasound waves as described hereabove. Alternatively or additionally, position and/or distance information can be recorded, such as position and/or distance information relative to one or more device components and/or tissue locations. In Step **1230**, source information for one or more tissue locations can be determined via the at least one electrode, e.g. by recording voltage reading from multiple locations on and/or within the chamber of the heart and calculated the source information (e.g. calculating dipole density and/or surface charge density information as described hereabove). Steps **1220** and

1230 can be performed simultaneously or sequentially, in full or partial steps, and in any order. Either or both Steps **1220** and **1230** can be performed in two or more independent time periods. (139) In Step **1240**, at least source information is provided to an operator of the system, such as via a display screen or in written form. In some embodiments, information is provided relative to a static image of the heart, such as an image at the end of systole or diastole. Alternatively or additionally, a dynamic set of heart images can be created representing a full cardiac cycle, or multiple cardiac cycles created over the course of a patient treatment procedure such as a cardiac ablation procedure performed to treat an arrhythmia such as atrial fibrillation. A dynamic set of source information can be presented on a display screen in synchrony with the dynamic set of heart images. In some embodiments, source information, field information, cardiac image information and/or cardiac parameter information are stored in memory, such as memory **680** of FIG. **6** described hereabove. In these embodiments, playback of stored information can be provided to an operator via the display screen.

(140) In some embodiments, a further analysis of the ultrasound reflections recorded and the electrical charge information is performed. The further analysis can include determining a cardiac parameter selected from the group consisting of: cardiac chamber volume; cardiac wall thickness; average cardiac wall thickness; a cardiac chamber dimension; ejection fraction; cardiac output; cardiac flow rate; cardiac contractility; cardiac wall motion; other cardiac function information; voltage at a cardiac surface location; dipole state at a cardiac surface location; and combinations thereof, each of which can be provided to the operator on a display screen (e.g. information provided in relation to a certain tissue portion of the heart such as wall thickness information provided relative to the particular cardiac wall). Alternatively or additionally, the further analysis can include producing a diagnosis and/or prognosis of a tissue portion, which can similarly be provided to the operator on a display screen (e.g. information provided in relation to a certain tissue portion of the heart such as cardiac wall motion information provided relative to the particular cardiac wall).

(141) For example, electrical information indicative of adequate electrical activity and anatomical information indicative of adequate tissue motion can correlate to the presence of healthy tissue. Additionally, electrical information indicative of adequate electrical activity and anatomical information indicative of inadequate tissue motion can correlate to presence of at least one of ischemic tissue or hibernating tissue. Conversely, electrical information indicative of inadequate electrical activity and anatomical information indicative of inadequate tissue motion can correlate to presence of scar tissue. Additionally, electrical information indicative of inadequate electrical activity and anatomical information indicative of inadequate tissue motion can correlate to the presence of a complete ablation, such as an ablation performed in a cardiac ablation performed to treat a cardiac arrhythmia (e.g. ablation of at least left atrial tissue to treat atrial fibrillation). In some embodiments, the complete ablation comprises a transmural ablation. In this use, the diagnosis and/or prognosis provided on the display screen can include the confirmation of the creation of a transmural lesion in the patient's heart tissue, such as when both tissue motion and electrical activity have been eliminated or decreased below a threshold.

(142) More specifically, the following four cases can be determined to exist: Case 1: Electrical and anatomical are adequate—Tissue is healthy, Case 2: Electrical is adequate and anatomical is inadequate—Tissue is compromised, Case 3: Electrical is inadequate and anatomical is adequate—Tissue is compromised, and Case 4: Electrical and anatomical are both inadequate—Tissue necrosis.

(143) The actual threshold for determining adequacy of electrical function of any one area of the heart is dependent upon many factors, including the degree of coordination of the activation pattern and the mass of the cells being activated. Additionally, this threshold will be different for each chamber of the heart as well as from smaller to larger patients. For example, a threshold of 0.5 mV can be appropriate, wherein an electrical potential smaller than 0.5 mV can be indicative of

inadequate electrical function and an electrical potential at or larger than 0.5 mV can be indicative of adequate electrical function. In some embodiments, the thresholds are adjustable via one or more controls of the system of the present invention.

(144) In some embodiments, tissue diagnostic algorithms can be configured to allow a clinician to assess the electrical integrity of cardiac cells. For example, the functional status of the cardiac cells can be assessed. In one embodiment, the electrical information comprises dipole density information. Additionally or alternatively, the electrical information can comprise at least one of repolarization or speed of repolarization information.

(145) In some embodiments, tissue diagnostic algorithms use recordings from one or more ultrasound transducers (e.g. one or more ultrasound transducers on an array of the present invention) to produce calculated information representing a change in cardiac geometry. The calculated information can represent a measurement of heart contractility, and an undesired level of heart contractility and/or change in heart contractility can be identified and provided on a display. The calculated information can represent a measurement of volume of one or more cardiac chambers and an undesired level of cardiac chamber volume and/or change in cardiac chamber volume (e.g. left atrial enlargement that can occur during an atrial fibrillation procedure) can be identified and provided on a display. Numerous forms of patient information can be assessed, such as via a calculation that creates a measure of a change in patient information over a time period.

(146) The information collected in Steps **1210** through **1230** and/or information derived from or otherwise calculated based on the collected information can be presented to an operator, such as when area **1121** or another area of display **1100** of FIG. **11** comprises the collected and/or calculated information.

(147) The method can further comprise the optional Step **1250** comprising ablating or otherwise treating cardiac tissue, such as an ablation performed based upon source information, tissue diagnostic information and/or other information provided on a display screen. For example, the anatomical information comprising tissue thickness information and at least one of the magnitude of ablation energy or the time period in which ablation energy is delivered, is adjusted based on the tissue thickness information recorded by one or more ultrasound sensors. Alternatively or additionally, one or more other therapeutic procedures can be performed. In these therapeutic procedures, various calculated and/or collected information (e.g. anatomic, physiologic, therapeutic device and/or therapeutic procedure information) can be provided to an operator, such as when area **1121** or another area of display **1100** of FIG. **11** comprises the collected and/or calculated information. Such information includes but is not limited to: tissue thickness information; tissue contractility information; tissue density information; tissue temperature information; therapeutic device component temperature information (e.g. temperature of an electrode); duration of energy delivery information; and combinations of these. In some embodiments, changes in information are reflected by changes in the way information is displayed, such as density information for a tissue area changing from a grey or other color to a white or other non-grey color during ablation of that tissue area.

(148) While the foregoing has described what are considered to be the best mode and/or other preferred embodiments, it is understood that various modifications can be made therein and that the invention or inventions may be implemented in various forms and embodiments, and that they may be applied in numerous applications, only some of which have been described herein. It is intended by the following claims to claim that which is literally described and all equivalents thereto, including all modifications and variations that fall within the scope of each claim.

Claims

1. A system of generating a graphical representation of cardiac information on a display screen, comprising: a processor to acquire an anatomical model of a heart including at least one cardiac

chamber, and to update the anatomical model at least once every 30 minutes; sensors to electronically determine multiple sequential data sets of source information corresponding to cardiac activity at multiple cardiac locations of the at least one cardiac chamber, the source information comprising surface potential information, temperature information, pH information, processor-determined dipole density information or surface charge information for a point on a surface of the heart, or a combination of two or more thereof, wherein the multiple sequential data sets of source information are electronically determined at least once per second; a display, wherein the processor is configured to electronically render the anatomical model of the heart on the display and then render an updated anatomical model of the heart on the display, wherein rendering the updated anatomical model includes displaying tissue motion for the at least one cardiac chamber; and the processor is configured to electronically render calculated information based on the data sets of source information in relation to the multiple cardiac locations of the anatomical model or the updated anatomical model of the heart on the display, including: rendering the calculated information as an instantaneous map of cardiac activation across the entire at least one cardiac chamber that graphically differentiates values of the calculated information overlaid on the anatomical model.

2. The system of claim 1, wherein the processor is configured to update the anatomical model at least once every minute.

3. The system of claim 1, wherein the processor is configured to update the anatomical model at least once every second.

4. The system of claim 1, wherein the processor is configured to update the anatomical model at least once every 100 milliseconds.

5. The system of claim 1, wherein the processor is configured to update the anatomical model at least 30 times per second.

6. The system of claim 1, wherein the processor is configured to create the anatomical model using data from a CT and/or an MRI scan.

7. The system of claim 1, wherein the processor is configured to create the anatomical model using signals from at least one ultrasound transducer.

8. The system of claim 7, wherein the ultrasound signals are from at least one ultrasound transducer positioned within the heart chamber.

9. The system of claim 1, wherein processor is configured to create an anatomical model of the heart that comprises a static model of the heart.

10. The system of claim 1, wherein processor is configured to create an anatomical model of the heart that comprises a dynamic model of the heart beating.

11. The system of claim 1, wherein the multiple sequential data sets of source information represent a dynamic series of information sets.

12. The system of claim 11, wherein the system is configured to update the dynamic series of information sets throughout one or more cardiac cycles.

13. The system of claim 1, wherein the source information is data representing, at a location in 3D space, a physical property or properties discrete to the specific location in 3D space.

14. The system of claim 1, wherein the source information comprises dipole density data determined for a point on the surface of the heart.

15. The system of claim 1, wherein electronically determining multiple sequential data sets of source information comprises the processor configured to record signals from at least one electrode.

16. The system of claim 15, wherein the at least one electrode comprises multiple electrodes.

17. The system of claim 16, wherein the multiple electrodes are mounted to an expandable array constructed and arranged for placement within a cardiac chamber.

18. The system of claim 1, wherein the processor is configured to present the calculated information in the form of, or using, a differentiating map.

19. The system of claim 18, wherein the differentiating map comprises a map of value differentiating parameters including: color; contrast; brightness; hue; saturation level; or combinations of two or more thereof.

20. The system of claim 1, comprising the processor configured to render a data set of field information on the display.

21. The system of claim 20, comprising the processor configured to display the data set of field information in an alternating arrangement with the data set of source information.

22. The system of claim 1, further comprising: the processor configured to acquire updated anatomical data from one or more ultrasound transducers located within the at least one cardiac chamber; and to update the anatomical model based, at least in part, on the updated anatomical data.
