

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402843
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Housel; Peter Scott et al.

System for displaying medical monitoring data

Abstract

A first medical device can receive a physiological parameter value from a second medical device. The second physiological parameter value may be formatted according to a protocol not used by the first medical device such that the first medical device is not able to process the second physiological parameter value to produce a displayable output value. The first medical device can pass the physiological parameter data from the first medical device to a separate translation module and receive translated parameter data from the translation module at the first medical device. The translated parameter data can be processed for display by the first medical device. The first medical device can output a value from the translated parameter data for display on the first medical device or an auxiliary device.

Inventors: Housel; Peter Scott (Irvine, CA), Muhsin; Bilal (Irvine, CA), Al-Ali; Ammar (San Juan Capistrano, CA), Kiani; Massi Joe E. (Laguna Niguel, CA)

Applicant: Masimo Corporation (Irvine, CA)

Family ID: 52776504

Assignee: Masimo Corporation (Irvine, CA)

Appl. No.: 17/646443

Filed: December 29, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220117564 A1	Apr. 21, 2022

Related U.S. Application Data

continuation parent-doc US 16670051 20191031 US 11241199 child-doc US 17646443
continuation parent-doc US 15919792 20180313 US 10512436 20191224 child-doc US 16670051
continuation parent-doc US 14512237 20141010 US 9943269 20180417 child-doc US 15919792

continuation-in-part parent-doc US 13651167 20121012 US 9436645 20160906 child-doc US 14512237
us-provisional-application US 61889972 20131011
us-provisional-application US 61703773 20120920
us-provisional-application US 61597120 20120209
us-provisional-application US 61547577 20111014
us-provisional-application US 61547017 20111013

Publication Classification

Int. Cl.: **A61B5/00** (20060101); **A61B5/0205** (20060101); **A61B5/021** (20060101); **A61B5/08** (20060101); **A61B5/1455** (20060101); **A61M5/172** (20060101); **A61M16/00** (20060101); **G06F21/84** (20130101); **G16H40/63** (20180101); **H04Q9/00** (20060101)

U.S. Cl.:

CPC **A61B5/742** (20130101); **A61B5/0002** (20130101); **A61B5/002** (20130101); **A61B5/02055** (20130101); **A61B5/021** (20130101); **A61B5/0816** (20130101); **A61B5/14551** (20130101); **A61B5/743** (20130101); **A61M16/0051** (20130101); **A61M16/021** (20170801); **G06F21/84** (20130101); **G16H40/63** (20180101); **H04Q9/00** (20130101); A61B5/4821 (20130101); A61B5/4836 (20130101); A61B2560/0214 (20130101); A61B2560/045 (20130101); A61B2562/08 (20130101); A61B2562/227 (20130101); A61M5/172 (20130101); A61M2205/18 (20130101); A61M2205/3368 (20130101); A61M2205/3375 (20130101); A61M2205/3561 (20130101); A61M2205/3569 (20130101); A61M2205/3584 (20130101); A61M2205/3592 (20130101); A61M2205/505 (20130101); A61M2209/086 (20130101); A61M2230/04 (20130101); A61M2230/10 (20130101); A61M2230/201 (20130101); A61M2230/202 (20130101); A61M2230/205 (20130101); A61M2230/208 (20130101); A61M2230/30 (20130101); A61M2230/42 (20130101); A61M2230/432 (20130101); A61M2230/50 (20130101)

Field of Classification Search

CPC: A61B (5/002); A61B (5/14532); G06F (19/3406)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3646606	12/1971	Buxton et al.	N/A	N/A
3690313	12/1971	Weppner et al.	N/A	N/A
3810102	12/1973	Parks, III et al.	N/A	N/A
3815583	12/1973	Scheidt	N/A	N/A
3972320	12/1975	Kalman	N/A	N/A
3978849	12/1975	Geneen	N/A	N/A
4108166	12/1977	Schmid	N/A	N/A
4231354	12/1979	Kurtz et al.	N/A	N/A
4589415	12/1985	Haaga	N/A	N/A
4662378	12/1986	Thomis	N/A	N/A

4838275	12/1988	Lee	N/A	N/A
4852570	12/1988	Levine	N/A	N/A
4960128	12/1989	Gordon et al.	N/A	N/A
4964408	12/1989	Hink et al.	N/A	N/A
5041187	12/1990	Hink et al.	N/A	N/A
5069213	12/1990	Polczynski	N/A	N/A
5092340	12/1991	Yamaguchi et al.	N/A	N/A
5140519	12/1991	Friesdorf et al.	N/A	N/A
5159932	12/1991	Zanetti et al.	N/A	N/A
5161539	12/1991	Evans et al.	N/A	N/A
5163438	12/1991	Gordon et al.	N/A	N/A
5262944	12/1992	Weisner et al.	N/A	N/A
5277189	12/1993	Jacobs	N/A	N/A
5278627	12/1993	Aoyagi et al.	N/A	N/A
5282474	12/1993	Valdes Sosa et al.	N/A	N/A
5296688	12/1993	Hamilton et al.	N/A	N/A
5307263	12/1993	Brown	N/A	N/A
5309918	12/1993	Schraag	N/A	N/A
5318037	12/1993	Evans et al.	N/A	N/A
5319355	12/1993	Russek	N/A	N/A
5331549	12/1993	Crawford, Jr.	N/A	N/A
5333106	12/1993	Lanpher et al.	N/A	N/A
5337744	12/1993	Branigan	N/A	N/A
5341805	12/1993	Stavridi et al.	N/A	N/A
5348008	12/1993	Bornn et al.	N/A	N/A
5358519	12/1993	Grandjean	N/A	N/A
D353195	12/1993	Savage et al.	N/A	N/A
D353196	12/1993	Savage et al.	N/A	N/A
5375599	12/1993	Shimizu	N/A	N/A
5375604	12/1993	Kelly et al.	N/A	N/A
5377676	12/1994	Vari et al.	N/A	N/A
5390238	12/1994	Kirk et al.	N/A	N/A
5400794	12/1994	Gorman	N/A	N/A
5406952	12/1994	Barnes et al.	N/A	N/A
D357982	12/1994	Dahl et al.	N/A	N/A
5416695	12/1994	Stutman et al.	N/A	N/A
5420606	12/1994	Begum et al.	N/A	N/A
D359546	12/1994	Savage et al.	N/A	N/A
5431170	12/1994	Mathews	N/A	N/A
5434611	12/1994	Tamura	N/A	N/A
5436499	12/1994	Namavar et al.	N/A	N/A
D361840	12/1994	Savage et al.	N/A	N/A
D362063	12/1994	Savage et al.	N/A	N/A
5452717	12/1994	Branigan et al.	N/A	N/A
D363120	12/1994	Savage et al.	N/A	N/A
5456252	12/1994	Vari et al.	N/A	N/A
5477146	12/1994	Jones	N/A	N/A
5479934	12/1995	Imran	N/A	N/A
5482036	12/1995	Diab et al.	N/A	N/A
5483968	12/1995	Adam et al.	N/A	N/A

5490505	12/1995	Diab et al.	N/A	N/A
5494041	12/1995	Wilk	N/A	N/A
5494043	12/1995	O'Sullivan et al.	N/A	N/A
5503149	12/1995	Beavin	N/A	N/A
5505202	12/1995	Mogi et al.	N/A	N/A
5533511	12/1995	Kaspari et al.	N/A	N/A
5534851	12/1995	Russek	N/A	N/A
5537289	12/1995	Dahl	N/A	N/A
5544649	12/1995	David et al.	N/A	N/A
5553609	12/1995	Chen et al.	N/A	N/A
5558638	12/1995	Evers et al.	N/A	N/A
5561275	12/1995	Savage et al.	N/A	N/A
5562002	12/1995	Lalin	N/A	N/A
5566676	12/1995	Rosenfeldt et al.	N/A	N/A
5576952	12/1995	Stutman et al.	N/A	N/A
5579001	12/1995	Dempsey et al.	N/A	N/A
5590649	12/1996	Caro et al.	N/A	N/A
5602924	12/1996	Durand et al.	N/A	N/A
5619991	12/1996	Sloane	N/A	N/A
5632272	12/1996	Diab et al.	N/A	N/A
5638816	12/1996	Kiani-Azarbayjany et al.	N/A	N/A
5638818	12/1996	Diab et al.	N/A	N/A
5640953	12/1996	Bishop et al.	N/A	N/A
5640967	12/1996	Fine et al.	N/A	N/A
5645440	12/1996	Tobler et al.	N/A	N/A
5651368	12/1996	Napolitano	N/A	N/A
5671914	12/1996	Kalkhoran et al.	N/A	N/A
5685299	12/1996	Diab et al.	N/A	N/A
5685314	12/1996	Geheb et al.	N/A	N/A
5687717	12/1996	Halpern et al.	N/A	N/A
5687732	12/1996	Inagaki	N/A	N/A
5694020	12/1996	Lang et al.	N/A	N/A
5724580	12/1997	Levin et al.	N/A	N/A
5724983	12/1997	Selker et al.	N/A	N/A
5725308	12/1997	Smith et al.	N/A	N/A
5726440	12/1997	Kalkhoran et al.	N/A	N/A
5734739	12/1997	Sheehan et al.	N/A	N/A
D393830	12/1997	Tobler et al.	N/A	N/A
5743262	12/1997	Lepper, Jr. et al.	N/A	N/A
5747806	12/1997	Khalil et al.	N/A	N/A
5750994	12/1997	Schlager	N/A	N/A
5758079	12/1997	Ludwig et al.	N/A	N/A
5758644	12/1997	Diab et al.	N/A	N/A
5760910	12/1997	Lepper, Jr. et al.	N/A	N/A
5769785	12/1997	Diab et al.	N/A	N/A
5772585	12/1997	Lavin et al.	N/A	N/A
5772586	12/1997	Heinonen et al.	N/A	N/A
5782757	12/1997	Diab et al.	N/A	N/A
5782805	12/1997	Meinzer	N/A	N/A

5785659	12/1997	Caro et al.	N/A	N/A
5791347	12/1997	Flaherty et al.	N/A	N/A
5801637	12/1997	Lomholt	N/A	N/A
5810734	12/1997	Caro et al.	N/A	N/A
5813403	12/1997	Soller et al.	N/A	N/A
5822544	12/1997	Chaco et al.	N/A	N/A
5822546	12/1997	George	N/A	N/A
5823950	12/1997	Diab et al.	N/A	N/A
5829723	12/1997	Brunner	N/A	N/A
5830131	12/1997	Caro et al.	N/A	N/A
5833618	12/1997	Caro et al.	N/A	N/A
5855550	12/1998	Lai et al.	N/A	N/A
5860919	12/1998	Kiani-Azarbayjany et al.	N/A	N/A
5876351	12/1998	Rohde	N/A	N/A
5885214	12/1998	Monroe et al.	N/A	N/A
5890929	12/1998	Mills et al.	N/A	N/A
5895359	12/1998	Peel, III	N/A	N/A
5904654	12/1998	Wohlmann et al.	N/A	N/A
5910139	12/1998	Cochran et al.	N/A	N/A
5919134	12/1998	Diab	N/A	N/A
5921920	12/1998	Marshall et al.	N/A	N/A
5924074	12/1998	Evans	N/A	N/A
5931160	12/1998	Gilmore et al.	N/A	N/A
5931791	12/1998	Saltzstein et al.	N/A	N/A
5934925	12/1998	Tobler et al.	N/A	N/A
5940182	12/1998	Lepper, Jr. et al.	N/A	N/A
5942986	12/1998	Shabot et al.	N/A	N/A
5987343	12/1998	Kinast	N/A	N/A
5987519	12/1998	Peifer et al.	N/A	N/A
5995855	12/1998	Kiani et al.	N/A	N/A
5997343	12/1998	Mills et al.	N/A	N/A
6002952	12/1998	Diab et al.	N/A	N/A
6006119	12/1998	Soller et al.	N/A	N/A
6010937	12/1999	Karam et al.	N/A	N/A
6011986	12/1999	Diab et al.	N/A	N/A
6014346	12/1999	Malone	N/A	N/A
6018673	12/1999	Chin et al.	N/A	N/A
6024699	12/1999	Surwit et al.	N/A	N/A
6027452	12/1999	Flaherty et al.	N/A	N/A
6032678	12/1999	Rottem	N/A	N/A
6035230	12/1999	Kang et al.	N/A	N/A
6036642	12/1999	Diab et al.	N/A	N/A
6036718	12/1999	Ledford et al.	N/A	N/A
6040578	12/1999	Malin et al.	N/A	N/A
6045509	12/1999	Caro et al.	N/A	N/A
6045527	12/1999	Appelbaum et al.	N/A	N/A
6057758	12/1999	Dempsey et al.	N/A	N/A
6066204	12/1999	Haven	N/A	N/A
6067462	12/1999	Diab et al.	N/A	N/A

6081735	12/1999	Diab et al.	N/A	N/A
6088607	12/1999	Diab et al.	N/A	N/A
6093146	12/1999	Filangeri	N/A	N/A
6101478	12/1999	Brown	N/A	N/A
6106463	12/1999	Wilk	N/A	N/A
6108199	12/1999	Bonardi et al.	N/A	N/A
6110522	12/1999	Lepper, Jr. et al.	N/A	N/A
6115673	12/1999	Malin et al.	N/A	N/A
6124597	12/1999	Shehada	N/A	N/A
6128521	12/1999	Marro et al.	N/A	N/A
6129675	12/1999	Jay	N/A	N/A
6132218	12/1999	Benja-Athon	N/A	N/A
6139494	12/1999	Cairnes	N/A	N/A
6144868	12/1999	Parker	N/A	N/A
6151516	12/1999	Kiani-Azarbayjany et al.	N/A	N/A
6152754	12/1999	Gerhardt et al.	N/A	N/A
6157850	12/1999	Diab et al.	N/A	N/A
6165005	12/1999	Mills et al.	N/A	N/A
6167258	12/1999	Schmidt et al.	N/A	N/A
D437058	12/2000	Gozani	N/A	N/A
6168563	12/2000	Brown	N/A	N/A
6171237	12/2000	Avitall et al.	N/A	N/A
6175752	12/2000	Say et al.	N/A	N/A
6183417	12/2000	Gehab et al.	N/A	N/A
6184521	12/2000	Coffin, IV et al.	N/A	N/A
6185448	12/2000	Borovsky	N/A	N/A
6195576	12/2000	John	N/A	N/A
6206830	12/2000	Diab et al.	N/A	N/A
6221012	12/2000	Maschke et al.	N/A	N/A
6224553	12/2000	Nevo	N/A	N/A
6229856	12/2000	Diab et al.	N/A	N/A
6230142	12/2000	Benigno et al.	N/A	N/A
6232609	12/2000	Snyder et al.	N/A	N/A
6236872	12/2000	Diab et al.	N/A	N/A
6241683	12/2000	Macklem et al.	N/A	N/A
6241684	12/2000	Amano et al.	N/A	N/A
6251113	12/2000	Appelbaum	N/A	N/A
6253097	12/2000	Aronow et al.	N/A	N/A
6255708	12/2000	Sudharsanan et al.	N/A	N/A
6256523	12/2000	Diab et al.	N/A	N/A
6263222	12/2000	Diab et al.	N/A	N/A
6267723	12/2000	Matsumura et al.	N/A	N/A
6269262	12/2000	Kandori et al.	N/A	N/A
6275378	12/2000	Lee et al.	N/A	N/A
6278522	12/2000	Lepper, Jr. et al.	N/A	N/A
6280213	12/2000	Tobler et al.	N/A	N/A
6280381	12/2000	Malin et al.	N/A	N/A
6285896	12/2000	Tobler et al.	N/A	N/A
6301493	12/2000	Marro et al.	N/A	N/A

6304767	12/2000	Soller et al.	N/A	N/A
6308089	12/2000	von der Ruhr et al.	N/A	N/A
6312378	12/2000	Bardy	N/A	N/A
6317627	12/2000	Ennen et al.	N/A	N/A
6321100	12/2000	Parker	N/A	N/A
6322502	12/2000	Schoenberg et al.	N/A	N/A
6325761	12/2000	Jay	N/A	N/A
6329139	12/2000	Nova et al.	N/A	N/A
6334065	12/2000	Al-Ali et al.	N/A	N/A
6338039	12/2001	Lonski et al.	N/A	N/A
6343224	12/2001	Parker	N/A	N/A
6344025	12/2001	Inagaki et al.	N/A	N/A
6349228	12/2001	Kiani et al.	N/A	N/A
6352504	12/2001	Ise	N/A	N/A
6354235	12/2001	Davies	N/A	N/A
6360114	12/2001	Diab et al.	N/A	N/A
6364834	12/2001	Reuss et al.	N/A	N/A
6364839	12/2001	Little et al.	N/A	N/A
6368283	12/2001	Xu et al.	N/A	N/A
6371921	12/2001	Caro et al.	N/A	N/A
6377829	12/2001	Al-Ali	N/A	N/A
6385476	12/2001	Osadchy et al.	N/A	N/A
6385589	12/2001	Trusheim et al.	N/A	N/A
6388240	12/2001	Schulz et al.	N/A	N/A
6397091	12/2001	Diab et al.	N/A	N/A
6407335	12/2001	Franklin-Lees	N/A	N/A
6411373	12/2001	Garside et al.	N/A	N/A
6415167	12/2001	Blank et al.	N/A	N/A
6430437	12/2001	Marro	N/A	N/A
6430525	12/2001	Weber et al.	N/A	N/A
6440072	12/2001	Schuman et al.	N/A	N/A
6463311	12/2001	Diab	N/A	N/A
6470199	12/2001	Kopotic et al.	N/A	N/A
6470893	12/2001	Boesen	N/A	N/A
6487429	12/2001	Hockersmith et al.	N/A	N/A
6501975	12/2001	Diab et al.	N/A	N/A
6505059	12/2002	Kollias et al.	N/A	N/A
6515273	12/2002	Al-Ali	N/A	N/A
6516289	12/2002	David et al.	N/A	N/A
6519487	12/2002	Parker	N/A	N/A
6524240	12/2002	Thede	N/A	N/A
6525386	12/2002	Mills et al.	N/A	N/A
6526300	12/2002	Kiani et al.	N/A	N/A
6534012	12/2002	Hazen et al.	N/A	N/A
6541756	12/2002	Schulz et al.	N/A	N/A
6542764	12/2002	Al-Ali et al.	N/A	N/A
6544173	12/2002	West et al.	N/A	N/A
6544174	12/2002	West et al.	N/A	N/A
6551243	12/2002	Bocionek et al.	N/A	N/A
6570592	12/2002	Sajdak et al.	N/A	N/A

6578428	12/2002	Dromms et al.	N/A	N/A
6580086	12/2002	Schulz et al.	N/A	N/A
6584336	12/2002	Ali et al.	N/A	N/A
6587196	12/2002	Stippick et al.	N/A	N/A
6587199	12/2002	Luu	N/A	N/A
6594762	12/2002	Doub et al.	N/A	N/A
6595316	12/2002	Cybulski et al.	N/A	N/A
6597932	12/2002	Tian et al.	N/A	N/A
6597933	12/2002	Kiani et al.	N/A	N/A
6606511	12/2002	Ali et al.	N/A	N/A
6616606	12/2002	Peterson et al.	N/A	N/A
6632181	12/2002	Flaherty et al.	N/A	N/A
6635559	12/2002	Greenwald et al.	N/A	N/A
6639668	12/2002	Trepagnier	N/A	N/A
6640116	12/2002	Diab	N/A	N/A
6640117	12/2002	Makarewicz et al.	N/A	N/A
6641533	12/2002	Causey et al.	N/A	N/A
6643530	12/2002	Diab et al.	N/A	N/A
6646556	12/2002	Smith et al.	N/A	N/A
6650917	12/2002	Diab et al.	N/A	N/A
6650939	12/2002	Takpke, II et al.	N/A	N/A
6654624	12/2002	Diab et al.	N/A	N/A
D483872	12/2002	Cruz et al.	N/A	N/A
6658276	12/2002	Kianl et al.	N/A	N/A
6661161	12/2002	Lanzo et al.	N/A	N/A
6663570	12/2002	Mott et al.	N/A	N/A
6671531	12/2002	Al-Ali et al.	N/A	N/A
6678543	12/2003	Diab et al.	N/A	N/A
6684090	12/2003	Ali et al.	N/A	N/A
6684091	12/2003	Parker	N/A	N/A
6694180	12/2003	Boesen	N/A	N/A
6697656	12/2003	Al-Ali	N/A	N/A
6697657	12/2003	Shehada et al.	N/A	N/A
6697658	12/2003	Al-Ali	N/A	N/A
RE38476	12/2003	Diab et al.	N/A	N/A
6699194	12/2003	Diab et al.	N/A	N/A
6707476	12/2003	Hochstedler	N/A	N/A
6714804	12/2003	Al-Ali et al.	N/A	N/A
RE38492	12/2003	Diab et al.	N/A	N/A
6719694	12/2003	Weng et al.	N/A	N/A
6721582	12/2003	Trepagnier et al.	N/A	N/A
6721585	12/2003	Parker	N/A	N/A
6725075	12/2003	Al-Ali	N/A	N/A
6725086	12/2003	Marinello	N/A	N/A
6728560	12/2003	Kollias et al.	N/A	N/A
6735459	12/2003	Parker	N/A	N/A
6738652	12/2003	Mattu et al.	N/A	N/A
6745060	12/2003	Diab et al.	N/A	N/A
6746406	12/2003	Lia et al.	N/A	N/A
6749566	12/2003	Russ	N/A	N/A

6750463	12/2003	Riley	N/A	N/A
6751492	12/2003	Ben-haim	N/A	N/A
6760607	12/2003	Al-Ali	N/A	N/A
6766188	12/2003	Soller	N/A	N/A
6770028	12/2003	Ali et al.	N/A	N/A
6771172	12/2003	Robinson	40/661.12	A61B 5/332
6771994	12/2003	Kiani et al.	N/A	N/A
6773396	12/2003	Flach et al.	N/A	N/A
6783492	12/2003	Dominguez	N/A	N/A
6788965	12/2003	Ruchti et al.	N/A	N/A
6790178	12/2003	Mault et al.	N/A	N/A
6792300	12/2003	Diab et al.	N/A	N/A
6795724	12/2003	Hogan	N/A	N/A
6796186	12/2003	Lia et al.	N/A	N/A
6804656	12/2003	Rosenfeld	N/A	N/A
6807050	12/2003	Whitehorn et al.	N/A	N/A
6813511	12/2003	Diab et al.	N/A	N/A
6816241	12/2003	Grubisic	N/A	N/A
6816741	12/2003	Diab	N/A	N/A
6817979	12/2003	Nihtila et al.	N/A	N/A
6822564	12/2003	Al-Ali	N/A	N/A
6826419	12/2003	Diab et al.	N/A	N/A
6830711	12/2003	Mills et al.	N/A	N/A
6837848	12/2004	Bonner et al.	N/A	N/A
6841535	12/2004	Divita et al.	N/A	N/A
6850787	12/2004	Weber et al.	N/A	N/A
6850788	12/2004	Al-Ali	N/A	N/A
6852083	12/2004	Caro et al.	N/A	N/A
6855112	12/2004	Kao et al.	N/A	N/A
6860266	12/2004	Blike	N/A	N/A
6861639	12/2004	Al-Ali	N/A	N/A
6876931	12/2004	Lorenz et al.	N/A	N/A
6897788	12/2004	Khair et al.	N/A	N/A
6898452	12/2004	Al-Ali et al.	N/A	N/A
6907237	12/2004	Dorenbosch et al.	N/A	N/A
6915149	12/2004	Ben-haim	N/A	N/A
6920345	12/2004	Al-Ali et al.	N/A	N/A
6931268	12/2004	Kiani-Azarbayjany et al.	N/A	N/A
6934570	12/2004	Kiani et al.	N/A	N/A
6939305	12/2004	Flaherty et al.	N/A	N/A
6943348	12/2004	Coffin, IV	N/A	N/A
6950687	12/2004	Al-Ali	N/A	N/A
6952340	12/2004	Son et al.	N/A	N/A
6956649	12/2004	Acosta et al.	N/A	N/A
6961598	12/2004	Diab	N/A	N/A
6970792	12/2004	Diab	N/A	N/A
6979812	12/2004	Ai-Ali	N/A	N/A
6980419	12/2004	Smith et al.	N/A	N/A

6983179	12/2005	Ben-haim	N/A	N/A
6985764	12/2005	Mason et al.	N/A	N/A
6988989	12/2005	Weiner et al.	N/A	N/A
6990087	12/2005	Rao et al.	N/A	N/A
6990364	12/2005	Ruchti et al.	N/A	N/A
6993371	12/2005	Kiani et al.	N/A	N/A
6996427	12/2005	Ali et al.	N/A	N/A
6997884	12/2005	Ulmsten	N/A	N/A
6998247	12/2005	Monfre et al.	N/A	N/A
6999904	12/2005	Weber et al.	N/A	N/A
7003338	12/2005	Weber et al.	N/A	N/A
7003339	12/2005	Diab et al.	N/A	N/A
7015451	12/2005	Dalke et al.	N/A	N/A
7024233	12/2005	Ali et al.	N/A	N/A
7025729	12/2005	De Chazal et al.	N/A	N/A
7027849	12/2005	Al-Ali	N/A	N/A
7030749	12/2005	Al-Ali	N/A	N/A
7033761	12/2005	Shafer	N/A	N/A
7035686	12/2005	Hogan	N/A	N/A
7039449	12/2005	Al-Ali	N/A	N/A
7041060	12/2005	Flaherty et al.	N/A	N/A
7044918	12/2005	Diab	N/A	N/A
7044930	12/2005	Stromberg	N/A	N/A
7048687	12/2005	Reuss et al.	N/A	N/A
7059769	12/2005	Potega	N/A	N/A
7061428	12/2005	Amir et al.	N/A	N/A
7063666	12/2005	Weng et al.	N/A	N/A
7067893	12/2005	Mills et al.	N/A	N/A
7079035	12/2005	Bock et al.	N/A	N/A
D526719	12/2005	Richie, Jr. et al.	N/A	N/A
7096052	12/2005	Mason et al.	N/A	N/A
7096054	12/2005	Abdul-Hafiz et al.	N/A	N/A
D529616	12/2005	Deros et al.	N/A	N/A
7132641	12/2005	Schulz et al.	N/A	N/A
7133710	12/2005	Acosta et al.	N/A	N/A
7142901	12/2005	Kiani et al.	N/A	N/A
7149561	12/2005	Diab	N/A	N/A
7186966	12/2006	Al-Ali	N/A	N/A
7188621	12/2006	DeVries et al.	N/A	N/A
7190261	12/2006	Al-Ali	N/A	N/A
7208119	12/2006	Kurtock et al.	N/A	N/A
7215984	12/2006	Diab	N/A	N/A
7215986	12/2006	Diab	N/A	N/A
7221971	12/2006	Diab	N/A	N/A
7225006	12/2006	Al-Ali et al.	N/A	N/A
7225007	12/2006	Al-Ali	N/A	N/A
RE39672	12/2006	Shehada et al.	N/A	N/A
7229415	12/2006	Schwartz	N/A	N/A
7239905	12/2006	Kiani-Azarbayjany et al.	N/A	N/A

7241287	12/2006	Shehada et al.	N/A	N/A
7244251	12/2006	Shehada et al.	N/A	N/A
7245373	12/2006	Soller et al.	N/A	N/A
7245953	12/2006	Parker	N/A	N/A
7252659	12/2006	Shehada et al.	N/A	N/A
7254429	12/2006	Schurman et al.	N/A	N/A
7254431	12/2006	Al-Ali	N/A	N/A
7254433	12/2006	Diab et al.	N/A	N/A
7254434	12/2006	Schulz et al.	N/A	N/A
7256708	12/2006	Rosenfeld	N/A	N/A
7261697	12/2006	Berstein	N/A	N/A
7264616	12/2006	Shehada et al.	N/A	N/A
7267671	12/2006	Shehada et al.	N/A	N/A
7272425	12/2006	Al-Ali	N/A	N/A
7273454	12/2006	Raymond et al.	N/A	N/A
7274955	12/2006	Kiani et al.	N/A	N/A
D554263	12/2006	Al-Ali	N/A	N/A
7280858	12/2006	Al-Ali et al.	N/A	N/A
7285090	12/2006	Stivoric et al.	N/A	N/A
7289835	12/2006	Mansfield et al.	N/A	N/A
7292883	12/2006	De Felice et al.	N/A	N/A
7294105	12/2006	Islam	N/A	N/A
7295866	12/2006	Al-Ali	N/A	N/A
7307543	12/2006	Rosenfeld	N/A	N/A
7312709	12/2006	Kingston	N/A	N/A
7313423	12/2006	Griffin et al.	N/A	N/A
7314446	12/2007	Byrd et al.	N/A	N/A
7315825	12/2007	Rosenfeld	N/A	N/A
7321862	12/2007	Rosenfeld	N/A	N/A
7322971	12/2007	Shehada et al.	N/A	N/A
7328053	12/2007	Diab et al.	N/A	N/A
7332784	12/2007	Mills et al.	N/A	N/A
7340287	12/2007	Mason et al.	N/A	N/A
7341559	12/2007	Schulz et al.	N/A	N/A
7343186	12/2007	Lamego et al.	N/A	N/A
D566282	12/2007	Al-Ali et al.	N/A	N/A
7355512	12/2007	Al-Ali	N/A	N/A
7356178	12/2007	Ziel et al.	N/A	N/A
7356365	12/2007	Schurman	N/A	N/A
7371981	12/2007	Abdul-Hafiz	N/A	N/A
7373193	12/2007	Al-Ali et al.	N/A	N/A
7373194	12/2007	Weber et al.	N/A	N/A
7374535	12/2007	Schoenberg et al.	N/A	N/A
7376453	12/2007	Diab et al.	N/A	N/A
7377794	12/2007	Ali et al.	N/A	N/A
7377899	12/2007	Weber et al.	N/A	N/A
7378975	12/2007	Smith et al.	N/A	N/A
7382247	12/2007	Welch et al.	N/A	N/A
7383070	12/2007	Diab et al.	N/A	N/A
7390299	12/2007	Weiner et al.	N/A	N/A

7395158	12/2007	Monfre et al.	N/A	N/A
7395216	12/2007	Rosenfeld	N/A	N/A
7411509	12/2007	Rosenfeld	N/A	N/A
7413546	12/2007	Agutter et al.	N/A	N/A
7415297	12/2007	Al-Ali et al.	N/A	N/A
7419483	12/2007	Shehada	N/A	N/A
7428432	12/2007	Ali et al.	N/A	N/A
7433827	12/2007	Rosenfeld	N/A	N/A
7438683	12/2007	Al-Ali et al.	N/A	N/A
7439856	12/2007	Weiner et al.	N/A	N/A
7440787	12/2007	Diab	N/A	N/A
7454240	12/2007	Diab et al.	N/A	N/A
7454359	12/2007	Rosenfeld	N/A	N/A
7454360	12/2007	Rosenfeld	N/A	N/A
7462151	12/2007	Childre et al.	N/A	N/A
7467002	12/2007	Weber et al.	N/A	N/A
7467094	12/2007	Rosenfeld	N/A	N/A
7469157	12/2007	Diab et al.	N/A	N/A
7471969	12/2007	Diab et al.	N/A	N/A
7471971	12/2007	Diab et al.	N/A	N/A
7475019	12/2008	Rosenfeld	N/A	N/A
7483729	12/2008	Al-Ali et al.	N/A	N/A
7483730	12/2008	Diab et al.	N/A	N/A
7489250	12/2008	Bock et al.	N/A	N/A
7489958	12/2008	Diab et al.	N/A	N/A
7496391	12/2008	Diab et al.	N/A	N/A
7496393	12/2008	Diab et al.	N/A	N/A
D587657	12/2008	Al-Ali et al.	N/A	N/A
7497828	12/2008	Wilk et al.	N/A	N/A
7499741	12/2008	Diab et al.	N/A	N/A
7499835	12/2008	Weber et al.	N/A	N/A
7500950	12/2008	Al-Ali et al.	N/A	N/A
7509154	12/2008	Diab et al.	N/A	N/A
7509494	12/2008	Al-Ali	N/A	N/A
7510849	12/2008	Schurman et al.	N/A	N/A
7514725	12/2008	Wojtczuk et al.	N/A	N/A
7515043	12/2008	Welch et al.	N/A	N/A
7515044	12/2008	Welch et al.	N/A	N/A
7519406	12/2008	Blank et al.	N/A	N/A
7526328	12/2008	Diab et al.	N/A	N/A
D592507	12/2008	Wachman et al.	N/A	N/A
7530942	12/2008	Diab	N/A	N/A
7530949	12/2008	Al Ali et al.	N/A	N/A
7530955	12/2008	Diab et al.	N/A	N/A
7532919	12/2008	Soyemi et al.	N/A	N/A
7549961	12/2008	Hwang	N/A	N/A
7551717	12/2008	Tome et al.	N/A	N/A
7559520	12/2008	Quijano et al.	N/A	N/A
7563110	12/2008	Al-Ali et al.	N/A	N/A
7577475	12/2008	Consentino et al.	N/A	N/A

7590950	12/2008	Collins et al.	N/A	N/A
7593230	12/2008	Abul-Haj et al.	N/A	N/A
7596398	12/2008	Al-Ali et al.	N/A	N/A
7597665	12/2008	Wilk et al.	N/A	N/A
7606608	12/2008	Blank et al.	N/A	N/A
7612999	12/2008	Clark et al.	N/A	N/A
7616303	12/2008	Yang et al.	N/A	N/A
7618375	12/2008	Flaherty	N/A	N/A
7620674	12/2008	Ruchti et al.	N/A	N/A
D606659	12/2008	Kiani et al.	N/A	N/A
7629039	12/2008	Eckerbom et al.	N/A	N/A
7639145	12/2008	Lawson et al.	N/A	N/A
7640140	12/2008	Ruchti et al.	N/A	N/A
7647083	12/2009	Al-Ali et al.	N/A	N/A
7650291	12/2009	Rosenfeld	N/A	N/A
D609193	12/2009	Al-Ali et al.	N/A	N/A
7654966	12/2009	Westinskow et al.	N/A	N/A
7684845	12/2009	Juan	N/A	N/A
7689437	12/2009	Teller et al.	N/A	N/A
RE41236	12/2009	Seely	N/A	N/A
D614305	12/2009	Al-Ali et al.	N/A	N/A
7693697	12/2009	Westinskow et al.	N/A	N/A
7697966	12/2009	Monfre et al.	N/A	N/A
7698105	12/2009	Ruchti et al.	N/A	N/A
RE41317	12/2009	Parker	N/A	N/A
RE41333	12/2009	Blank et al.	N/A	N/A
7722542	12/2009	Lia et al.	N/A	N/A
7729733	12/2009	Al-Ali et al.	N/A	N/A
7734320	12/2009	Al-Ali	N/A	N/A
7736318	12/2009	Consentino et al.	N/A	N/A
7740590	12/2009	Bernstein	N/A	N/A
7761127	12/2009	Al-Ali et al.	N/A	N/A
7761128	12/2009	Al-Ali et al.	N/A	N/A
7763420	12/2009	Strizker et al.	N/A	N/A
7764982	12/2009	Dalke et al.	N/A	N/A
D621515	12/2009	Chua et al.	N/A	N/A
D621516	12/2009	Kiani et al.	N/A	N/A
7766818	12/2009	Iketani et al.	N/A	N/A
7772799	12/2009	Wu	N/A	N/A
7774060	12/2009	Westenskow et al.	N/A	N/A
7778851	12/2009	Schoenberg et al.	N/A	N/A
7791155	12/2009	Diab	N/A	N/A
7794407	12/2009	Rothenberg	N/A	N/A
7801581	12/2009	Diab	N/A	N/A
7806830	12/2009	Bernstein	N/A	N/A
7820184	12/2009	Strizker et al.	N/A	N/A
7822452	12/2009	Schurman et al.	N/A	N/A
RE41912	12/2009	Parker	N/A	N/A
7831450	12/2009	Schoenberg	N/A	N/A
7841986	12/2009	He et al.	N/A	N/A

7844313	12/2009	Kiani et al.	N/A	N/A
7844314	12/2009	Al-Ali	N/A	N/A
7844315	12/2009	Al-Ali	N/A	N/A
7848935	12/2009	Gotlib	N/A	N/A
7858322	12/2009	Tymianski et al.	N/A	N/A
7865222	12/2010	Weber et al.	N/A	N/A
7865232	12/2010	Krishnaswamy et al.	N/A	N/A
7873497	12/2010	Weber et al.	N/A	N/A
7880606	12/2010	Al-Ali	N/A	N/A
7880626	12/2010	Al-Ali et al.	N/A	N/A
7881892	12/2010	Soyemi et al.	N/A	N/A
7884314	12/2010	Hamada	N/A	N/A
7890156	12/2010	Ooi et al.	N/A	N/A
7891355	12/2010	Al-Ali et al.	N/A	N/A
7894868	12/2010	Al-Ali et al.	N/A	N/A
7899507	12/2010	Al-Ali et al.	N/A	N/A
7899518	12/2010	Trepagnier et al.	N/A	N/A
7904132	12/2010	Weber et al.	N/A	N/A
7907945	12/2010	Deprun	N/A	N/A
7909772	12/2010	Popov et al.	N/A	N/A
7910875	12/2010	Al-Ali	N/A	N/A
7914514	12/2010	Calderon	N/A	N/A
7919713	12/2010	Al-Ali et al.	N/A	N/A
7937128	12/2010	Al-Ali	N/A	N/A
7937129	12/2010	Mason et al.	N/A	N/A
7937130	12/2010	Diab et al.	N/A	N/A
7941199	12/2010	Kiani	N/A	N/A
7951086	12/2010	Flaherty et al.	N/A	N/A
7957780	12/2010	Lamego et al.	N/A	N/A
7962188	12/2010	Kiani et al.	N/A	N/A
7962190	12/2010	Diab et al.	N/A	N/A
7963927	12/2010	Kelleher et al.	N/A	N/A
7967749	12/2010	Hutchinson et al.	N/A	N/A
7976472	12/2010	Kiani	N/A	N/A
7988637	12/2010	Diab	N/A	N/A
7988639	12/2010	Starks	N/A	N/A
7990382	12/2010	Kiani	N/A	N/A
7991446	12/2010	Ali et al.	N/A	N/A
7991463	12/2010	Kelleher et al.	N/A	N/A
7991625	12/2010	Rosenfeld	N/A	N/A
8000761	12/2010	Al-Ali	N/A	N/A
8008088	12/2010	Bellott et al.	N/A	N/A
RE42753	12/2010	Kiani-Azarbayjany et al.	N/A	N/A
8019400	12/2010	Diab et al.	N/A	N/A
8027846	12/2010	Schoenberg	N/A	N/A
8028701	12/2010	Al-Ali et al.	N/A	N/A
8029765	12/2010	Bellott et al.	N/A	N/A
8033996	12/2010	Behar	N/A	N/A
8036727	12/2010	Schurman et al.	N/A	N/A

8036728	12/2010	Diab et al.	N/A	N/A
8036736	12/2010	Snyder et al.	N/A	N/A
8038625	12/2010	Afonso et al.	N/A	N/A
8046040	12/2010	Ali et al.	N/A	N/A
8046041	12/2010	Diab et al.	N/A	N/A
8046042	12/2010	Diab et al.	N/A	N/A
8048040	12/2010	Kiani	N/A	N/A
8050728	12/2010	Al-Ali et al.	N/A	N/A
8068104	12/2010	Rampersad	N/A	N/A
8073707	12/2010	Teller et al.	N/A	N/A
8094013	12/2011	Lee et al.	N/A	N/A
8107397	12/2011	Bagchi et al.	N/A	N/A
RE43169	12/2011	Parker	N/A	N/A
8118620	12/2011	Al-Ali et al.	N/A	N/A
8126528	12/2011	Diab et al.	N/A	N/A
8128572	12/2011	Diab et al.	N/A	N/A
8130105	12/2011	Al-Ali et al.	N/A	N/A
8145287	12/2011	Diab et al.	N/A	N/A
8150487	12/2011	Diab et al.	N/A	N/A
D659836	12/2011	Bensch et al.	N/A	N/A
8170887	12/2011	Rosenfeld	N/A	N/A
8175672	12/2011	Parker	N/A	N/A
8175895	12/2011	Rosenfeld	N/A	N/A
8180420	12/2011	Diab et al.	N/A	N/A
8182429	12/2011	Mason	N/A	N/A
8182443	12/2011	Kiani	N/A	N/A
8185180	12/2011	Diab et al.	N/A	N/A
8190223	12/2011	Al-Ali et al.	N/A	N/A
8190227	12/2011	Diab et al.	N/A	N/A
8200308	12/2011	Zhang et al.	N/A	N/A
8203438	12/2011	Kiani et al.	N/A	N/A
8203704	12/2011	Merritt et al.	N/A	N/A
8204566	12/2011	Schurman et al.	N/A	N/A
8206312	12/2011	Farquhar	N/A	N/A
8214007	12/2011	Baker et al.	N/A	N/A
8216136	12/2011	Addison	600/301	A61B 5/0205
8219172	12/2011	Schurman et al.	N/A	N/A
8224411	12/2011	Al-Ali et al.	N/A	N/A
8228181	12/2011	Al-Ali	N/A	N/A
8229532	12/2011	Davis	N/A	N/A
8229533	12/2011	Diab et al.	N/A	N/A
8233955	12/2011	Al-Ali et al.	N/A	N/A
8235907	12/2011	Wilk et al.	N/A	N/A
8239780	12/2011	Manetta et al.	N/A	N/A
8241213	12/2011	Lynn et al.	N/A	N/A
8244325	12/2011	Al-Ali et al.	N/A	N/A
8249815	12/2011	Taylor	N/A	N/A
8255026	12/2011	Al-Ali	N/A	N/A
8255027	12/2011	Al-Ali et al.	N/A	N/A

8255028	12/2011	Al-Ali et al.	N/A	N/A
8260577	12/2011	Weber et al.	N/A	N/A
8265723	12/2011	McHale et al.	N/A	N/A
8274360	12/2011	Sampath et al.	N/A	N/A
8280473	12/2011	Al-Ali	N/A	N/A
8294588	12/2011	Fisher et al.	N/A	N/A
8294716	12/2011	Lord et al.	N/A	N/A
8301217	12/2011	Al-Ali et al.	N/A	N/A
8306596	12/2011	Schurman et al.	N/A	N/A
8310336	12/2011	Muhsin et al.	N/A	N/A
8311747	12/2011	Taylor	N/A	N/A
8311748	12/2011	Taylor et al.	N/A	N/A
8315683	12/2011	Al-Ali et al.	N/A	N/A
8315812	12/2011	Taylor	N/A	N/A
8315813	12/2011	Taylor et al.	N/A	N/A
8315814	12/2011	Taylor et al.	N/A	N/A
8321150	12/2011	Taylor	N/A	N/A
RE43860	12/2011	Parker	N/A	N/A
8326649	12/2011	Rosenfeld	N/A	N/A
8328793	12/2011	Birkenbach et al.	N/A	N/A
8337403	12/2011	Al-Ali et al.	N/A	N/A
8346330	12/2012	Lamego	N/A	N/A
8353842	12/2012	Al-Ali et al.	N/A	N/A
8355766	12/2012	MacNeish, III et al.	N/A	N/A
8359080	12/2012	Diab et al.	N/A	N/A
8360936	12/2012	Dibenedetto et al.	N/A	N/A
8364223	12/2012	Al-Ali et al.	N/A	N/A
8364226	12/2012	Diab et al.	N/A	N/A
8374665	12/2012	Lamego	N/A	N/A
8385995	12/2012	Al-Ali et al.	N/A	N/A
8385996	12/2012	Smith et al.	N/A	N/A
D679018	12/2012	Fullerton et al.	N/A	N/A
8388353	12/2012	Kiani et al.	N/A	N/A
8399822	12/2012	Al-Ali	N/A	N/A
8401602	12/2012	Kiani	N/A	N/A
8401874	12/2012	Rosenfeld	N/A	N/A
8405608	12/2012	Al-Ali et al.	N/A	N/A
8414499	12/2012	Al-Ali et al.	N/A	N/A
8418524	12/2012	Al-Ali	N/A	N/A
8423106	12/2012	Lamego et al.	N/A	N/A
8428967	12/2012	Olsen et al.	N/A	N/A
8430817	12/2012	Al-Ali et al.	N/A	N/A
8437825	12/2012	Dalvi et al.	N/A	N/A
8455290	12/2012	Siskavich	N/A	N/A
8457703	12/2012	Al-Ali	N/A	N/A
8457707	12/2012	Kiani	N/A	N/A
8463349	12/2012	Diab et al.	N/A	N/A
8466286	12/2012	Bellot et al.	N/A	N/A
8471713	12/2012	Poeze et al.	N/A	N/A
8473020	12/2012	Kiani et al.	N/A	N/A

8483787	12/2012	Al-Ali et al.	N/A	N/A
8489167	12/2012	Buxton et al.	N/A	N/A
8489364	12/2012	Weber et al.	N/A	N/A
8498684	12/2012	Weber et al.	N/A	N/A
8504128	12/2012	Blank et al.	N/A	N/A
8506480	12/2012	Banet et al.	N/A	N/A
8509867	12/2012	Workman et al.	N/A	N/A
8514086	12/2012	Harper et al.	N/A	N/A
8515509	12/2012	Bruinsma et al.	N/A	N/A
8523781	12/2012	Al-Ali	N/A	N/A
8529301	12/2012	Al-Ali et al.	N/A	N/A
8532727	12/2012	Ali et al.	N/A	N/A
8532728	12/2012	Diab et al.	N/A	N/A
D692145	12/2012	Al-Ali et al.	N/A	N/A
8547209	12/2012	Kiani et al.	N/A	N/A
8548548	12/2012	Al-Ali	N/A	N/A
8548549	12/2012	Schurman et al.	N/A	N/A
8548550	12/2012	Al-Ali et al.	N/A	N/A
8549600	12/2012	Shedrinsky	N/A	N/A
8560032	12/2012	Al-Ali et al.	N/A	N/A
8560034	12/2012	Diab et al.	N/A	N/A
8565847	12/2012	Buxton et al.	N/A	N/A
8570167	12/2012	Al-Ali	N/A	N/A
8570503	12/2012	Vo et al.	N/A	N/A
8571617	12/2012	Reichgott et al.	N/A	N/A
8571618	12/2012	Lamego et al.	N/A	N/A
8571619	12/2012	Al-Ali et al.	N/A	N/A
8577431	12/2012	Lamego et al.	N/A	N/A
8578082	12/2012	Medina et al.	N/A	N/A
8579813	12/2012	Causey, III et al.	N/A	N/A
8581732	12/2012	Al-Ali et al.	N/A	N/A
8584345	12/2012	Al-Ali et al.	N/A	N/A
8588880	12/2012	Abdul-Hafiz et al.	N/A	N/A
8588924	12/2012	Dion	N/A	N/A
8597287	12/2012	Benamou et al.	N/A	N/A
8600467	12/2012	Al-Ali et al.	N/A	N/A
8600777	12/2012	Schoenberg	N/A	N/A
8606342	12/2012	Diab	N/A	N/A
8620678	12/2012	Gotlib	N/A	N/A
8626255	12/2013	Al-Ali et al.	N/A	N/A
8630691	12/2013	Lamego et al.	N/A	N/A
8634889	12/2013	Al-Ali et al.	N/A	N/A
8641631	12/2013	Sierra et al.	N/A	N/A
8652060	12/2013	Al-Ali	N/A	N/A
8663107	12/2013	Kiani	N/A	N/A
8666468	12/2013	Al-Ali	N/A	N/A
8667967	12/2013	Al-Ali et al.	N/A	N/A
8670811	12/2013	O'Reilly	N/A	N/A
8670814	12/2013	Diab et al.	N/A	N/A
8676286	12/2013	Weber et al.	N/A	N/A

8682407	12/2013	Al-Ali	N/A	N/A
RE44823	12/2013	Parker	N/A	N/A
RE44875	12/2013	Kiani et al.	N/A	N/A
8688183	12/2013	Bruinsma et al.	N/A	N/A
8690771	12/2013	Wekell et al.	N/A	N/A
8690799	12/2013	Telfort et al.	N/A	N/A
8700112	12/2013	Kiani	N/A	N/A
8702627	12/2013	Telfort et al.	N/A	N/A
8706179	12/2013	Parker	N/A	N/A
8712494	12/2013	MacNeish, III et al.	N/A	N/A
8715206	12/2013	Telfort et al.	N/A	N/A
8718735	12/2013	Lamego et al.	N/A	N/A
8718737	12/2013	Diab et al.	N/A	N/A
8718738	12/2013	Blank et al.	N/A	N/A
8720249	12/2013	Al-Ali	N/A	N/A
8721541	12/2013	Al-Ali et al.	N/A	N/A
8721542	12/2013	Al-Ali et al.	N/A	N/A
8723677	12/2013	Kiani	N/A	N/A
8737048	12/2013	Fidacaro et al.	N/A	N/A
8740792	12/2013	Kiani et al.	N/A	N/A
8743148	12/2013	Gegner	345/660	G06F 3/0481
8753274	12/2013	Ziv et al.	N/A	N/A
8754776	12/2013	Poeze et al.	N/A	N/A
8755535	12/2013	Telfort et al.	N/A	N/A
8755856	12/2013	Diab et al.	N/A	N/A
8755872	12/2013	Marinow	N/A	N/A
8758020	12/2013	Burdea et al.	N/A	N/A
8761850	12/2013	Lamego	N/A	N/A
D709846	12/2013	Oswaks	N/A	N/A
8764671	12/2013	Kiani	N/A	N/A
8768423	12/2013	Shakespeare et al.	N/A	N/A
8771204	12/2013	Telfort et al.	N/A	N/A
8777634	12/2013	Kiani et al.	N/A	N/A
8781543	12/2013	Diab et al.	N/A	N/A
8781544	12/2013	Al-Ali et al.	N/A	N/A
8781549	12/2013	Al-Ali et al.	N/A	N/A
8788003	12/2013	Schurman et al.	N/A	N/A
8790268	12/2013	Ai-Ali	N/A	N/A
8792950	12/2013	Larsen et al.	N/A	N/A
8801613	12/2013	Al-Ali et al.	N/A	N/A
8818477	12/2013	Soller	N/A	N/A
8821397	12/2013	Al-Ali et al.	N/A	N/A
8821415	12/2013	Al-Ali et al.	N/A	N/A
8830449	12/2013	Lamego et al.	N/A	N/A
8831700	12/2013	Schurman et al.	N/A	N/A
8840549	12/2013	Al-Ali et al.	N/A	N/A
8847740	12/2013	Kiani et al.	N/A	N/A
8849365	12/2013	Smith et al.	N/A	N/A
8852094	12/2013	Al-Ali et al.	N/A	N/A

8852994	12/2013	Wojtczuk et al.	N/A	N/A
8866620	12/2013	Amir	N/A	N/A
8868147	12/2013	Stippick et al.	N/A	N/A
8868150	12/2013	Al-Ali et al.	N/A	N/A
8870792	12/2013	Al-Ali et al.	N/A	N/A
8873035	12/2013	Yang et al.	N/A	N/A
8878888	12/2013	Rosenfeld	N/A	N/A
8882666	12/2013	Goldberg et al.	N/A	N/A
8886271	12/2013	Kiani et al.	N/A	N/A
8888539	12/2013	Al-Ali et al.	N/A	N/A
8888708	12/2013	Diab et al.	N/A	N/A
8892180	12/2013	Weber et al.	N/A	N/A
8897847	12/2013	Al-Ali	N/A	N/A
8907287	12/2013	Vanderpohl	N/A	N/A
8909310	12/2013	Lamego et al.	N/A	N/A
8909330	12/2013	McCombie et al.	N/A	N/A
8911377	12/2013	Al-Ali	N/A	N/A
8912909	12/2013	Al-Ali et al.	N/A	N/A
8920317	12/2013	Al-Ali et al.	N/A	N/A
8921699	12/2013	Al-Ali et al.	N/A	N/A
8922382	12/2013	Al-Ali et al.	N/A	N/A
8929964	12/2014	Al-Ali et al.	N/A	N/A
8942777	12/2014	Diab et al.	N/A	N/A
8948834	12/2014	Diab et al.	N/A	N/A
8948835	12/2014	Diab	N/A	N/A
8951248	12/2014	Messerly et al.	N/A	N/A
8956292	12/2014	Wekell et al.	N/A	N/A
8965471	12/2014	Lamego	N/A	N/A
8983564	12/2014	Al-Ali	N/A	N/A
8989831	12/2014	Al-Ali et al.	N/A	N/A
8996085	12/2014	Kiani et al.	N/A	N/A
8998809	12/2014	Kiani	N/A	N/A
9028429	12/2014	Telfort et al.	N/A	N/A
9037207	12/2014	Al-Ali et al.	N/A	N/A
9041730	12/2014	Johnson et al.	N/A	N/A
9057689	12/2014	Soller	N/A	N/A
9060721	12/2014	Reichgott et al.	N/A	N/A
9066666	12/2014	Kiani	N/A	N/A
9066680	12/2014	Al-Ali et al.	N/A	N/A
9072474	12/2014	Al-Ali et al.	N/A	N/A
9078560	12/2014	Schurman et al.	N/A	N/A
9084569	12/2014	Weber et al.	N/A	N/A
9095291	12/2014	Soller	N/A	N/A
9095316	12/2014	Welch et al.	N/A	N/A
9104789	12/2014	Gross et al.	N/A	N/A
9106038	12/2014	Telfort et al.	N/A	N/A
9107625	12/2014	Telfort et al.	N/A	N/A
9107626	12/2014	Al-Ali et al.	N/A	N/A
9113831	12/2014	Al-Ali	N/A	N/A
9113832	12/2014	Al-Ali	N/A	N/A

9119595	12/2014	Lamego	N/A	N/A
9125578	12/2014	Grunwald	N/A	N/A
9131881	12/2014	Diab et al.	N/A	N/A
9131882	12/2014	Al-Ali et al.	N/A	N/A
9131883	12/2014	Al-Ali	N/A	N/A
9131917	12/2014	Telfort et al.	N/A	N/A
9138180	12/2014	Coverston et al.	N/A	N/A
9138182	12/2014	Al-Ali et al.	N/A	N/A
9138192	12/2014	Weber et al.	N/A	N/A
9142117	12/2014	Muhsin et al.	N/A	N/A
9153112	12/2014	Kiani et al.	N/A	N/A
9153121	12/2014	Kiani et al.	N/A	N/A
9161696	12/2014	Al-Ali et al.	N/A	N/A
9161713	12/2014	Al-Ali et al.	N/A	N/A
9167995	12/2014	Lamego et al.	N/A	N/A
9176141	12/2014	Al-Ali et al.	N/A	N/A
9186102	12/2014	Bruinsma et al.	N/A	N/A
9192312	12/2014	Al-Ali	N/A	N/A
9192329	12/2014	Al-Ali	N/A	N/A
9192351	12/2014	Telfort et al.	N/A	N/A
9195385	12/2014	Al-Ali et al.	N/A	N/A
D745167	12/2014	Canas et al.	N/A	N/A
9211072	12/2014	Kiani	N/A	N/A
9211095	12/2014	Al-Ali	N/A	N/A
9218454	12/2014	Kiani et al.	N/A	N/A
9226696	12/2015	Kiani	N/A	N/A
9241662	12/2015	Al-Ali et al.	N/A	N/A
9245668	12/2015	Vo et al.	N/A	N/A
9259185	12/2015	Abdul-Hafiz et al.	N/A	N/A
9262586	12/2015	Steiger et al.	N/A	N/A
9265429	12/2015	St. Pierre	N/A	A61B 5/7475
9267572	12/2015	Barker et al.	N/A	N/A
9277880	12/2015	Poeze et al.	N/A	N/A
9289167	12/2015	Diab et al.	N/A	N/A
9295421	12/2015	Kiani et al.	N/A	N/A
9307928	12/2015	Al-Ali et al.	N/A	N/A
9323894	12/2015	Kiani	N/A	N/A
D755392	12/2015	Hwang et al.	N/A	N/A
9326712	12/2015	Kiani	N/A	N/A
9333316	12/2015	Kiani	N/A	N/A
9339220	12/2015	Lamego et al.	N/A	N/A
9341565	12/2015	Lamego et al.	N/A	N/A
9351673	12/2015	Diab et al.	N/A	N/A
9351675	12/2015	Al-Ali et al.	N/A	N/A
9364181	12/2015	Kiani et al.	N/A	N/A
9368671	12/2015	Wojtczuk et al.	N/A	N/A
9370325	12/2015	Al-Ali et al.	N/A	N/A
9370326	12/2015	McHale et al.	N/A	N/A
9370335	12/2015	Al-ali et al.	N/A	N/A

9375185	12/2015	Ali et al.	N/A	N/A
9386953	12/2015	Al-Ali	N/A	N/A
9386961	12/2015	Al-Ali et al.	N/A	N/A
9392945	12/2015	Al-Ali et al.	N/A	N/A
9397448	12/2015	Al-Ali et al.	N/A	N/A
9408542	12/2015	Kinast et al.	N/A	N/A
9414784	12/2015	Berme et al.	N/A	N/A
9436645	12/2015	Al-Ali et al.	N/A	N/A
9445759	12/2015	Lamego et al.	N/A	N/A
9466919	12/2015	Kiani et al.	N/A	N/A
9474474	12/2015	Lamego et al.	N/A	N/A
9480422	12/2015	Al-Ali	N/A	N/A
9480435	12/2015	Olsen	N/A	N/A
9492110	12/2015	Al-Ali et al.	N/A	N/A
9510779	12/2015	Poeze et al.	N/A	N/A
9517024	12/2015	Kiani et al.	N/A	N/A
9529762	12/2015	Gisler et al.	N/A	N/A
9532722	12/2016	Lamego et al.	N/A	N/A
9538949	12/2016	Al-Ali et al.	N/A	N/A
9538980	12/2016	Telfort et al.	N/A	N/A
9549696	12/2016	Lamego et al.	N/A	N/A
9554737	12/2016	Schurman et al.	N/A	N/A
9560996	12/2016	Kiani	N/A	N/A
9560998	12/2016	Al-Ali et al.	N/A	N/A
9566019	12/2016	Al-Ali et al.	N/A	N/A
9579039	12/2016	Jansen et al.	N/A	N/A
9591975	12/2016	Dalvi et al.	N/A	N/A
9622692	12/2016	Lamego et al.	N/A	N/A
9622693	12/2016	Diab	N/A	N/A
D788312	12/2016	Al-Ali et al.	N/A	N/A
9636055	12/2016	Al-Ali et al.	N/A	N/A
9636056	12/2016	Al-Ali	N/A	N/A
9649054	12/2016	Lamego et al.	N/A	N/A
9662052	12/2016	Al-Ali et al.	N/A	N/A
9668679	12/2016	Schurman et al.	N/A	N/A
9668680	12/2016	Bruinsma et al.	N/A	N/A
9668703	12/2016	Ai-Ali	N/A	N/A
9675286	12/2016	Diab	N/A	N/A
9687160	12/2016	Kiani	N/A	N/A
9693719	12/2016	Al-Ali et al.	N/A	N/A
9693737	12/2016	Al-Ali	N/A	N/A
9697928	12/2016	Al-Ali et al.	N/A	N/A
9717425	12/2016	Kiani et al.	N/A	N/A
9717458	12/2016	Lamego et al.	N/A	N/A
9724016	12/2016	Al-Ali et al.	N/A	N/A
9724024	12/2016	Al-Ali	N/A	N/A
9724025	12/2016	Kiani et al.	N/A	N/A
9730640	12/2016	Diab et al.	N/A	N/A
9743887	12/2016	Al-Ali et al.	N/A	N/A
9749232	12/2016	Sampath et al.	N/A	N/A

9750442	12/2016	Olsen	N/A	N/A
9750443	12/2016	Smith et al.	N/A	N/A
9750461	12/2016	Telfort	N/A	N/A
9775545	12/2016	Al-Ali et al.	N/A	N/A
9775546	12/2016	Diab et al.	N/A	N/A
9775570	12/2016	Al-Ali	N/A	N/A
9778079	12/2016	Al-Ali et al.	N/A	N/A
9782077	12/2016	Lamego et al.	N/A	N/A
9782110	12/2016	Kiani	N/A	N/A
9787568	12/2016	Lamego et al.	N/A	N/A
9788735	12/2016	Al-Ali	N/A	N/A
9788768	12/2016	Al-Ali et al.	N/A	N/A
9795300	12/2016	Al-Ali	N/A	N/A
9795310	12/2016	Al-Ali	N/A	N/A
9795358	12/2016	Telfort et al.	N/A	N/A
9795739	12/2016	Al-Ali et al.	N/A	N/A
9801556	12/2016	Kiani	N/A	N/A
9801588	12/2016	Weber et al.	N/A	N/A
9808188	12/2016	Perea et al.	N/A	N/A
9814418	12/2016	Weber et al.	N/A	N/A
9820691	12/2016	Kiani	N/A	N/A
9833152	12/2016	Kiani et al.	N/A	N/A
9833180	12/2016	Shakespeare et al.	N/A	N/A
9839379	12/2016	Al-Ali et al.	N/A	N/A
9839381	12/2016	Weber et al.	N/A	N/A
9847002	12/2016	Kiani et al.	N/A	N/A
9847749	12/2016	Kiani et al.	N/A	N/A
9848800	12/2016	Lee et al.	N/A	N/A
9848806	12/2016	Al-Ali et al.	N/A	N/A
9848807	12/2016	Lamego	N/A	N/A
9861298	12/2017	Eckerbom et al.	N/A	N/A
9861304	12/2017	Al-Ali et al.	N/A	N/A
9861305	12/2017	Weber et al.	N/A	N/A
9867578	12/2017	Al-Ali et al.	N/A	N/A
9872623	12/2017	Al-Ali	N/A	N/A
9876320	12/2017	Coverston et al.	N/A	N/A
9877650	12/2017	Muhsin et al.	N/A	N/A
9877686	12/2017	Al-Ali et al.	N/A	N/A
9891079	12/2017	Dalvi	N/A	N/A
9895107	12/2017	Al-Ali et al.	N/A	N/A
9913617	12/2017	Al-Ali et al.	N/A	N/A
9924893	12/2017	Schurman et al.	N/A	N/A
9924897	12/2017	Abdul-Hafiz	N/A	N/A
9936917	12/2017	Poeze et al.	N/A	N/A
9943269	12/2017	Al-Ali et al.	N/A	N/A
9949676	12/2017	Al-Ali	N/A	N/A
9955937	12/2017	Telfort	N/A	N/A
9965946	12/2017	Al-Ali et al.	N/A	N/A
9980667	12/2017	Kiani et al.	N/A	N/A
D820865	12/2017	Muhsin et al.	N/A	N/A

9986919	12/2017	Lamego et al.	N/A	N/A
9986952	12/2017	Dalvi et al.	N/A	N/A
9989560	12/2017	Poeze et al.	N/A	N/A
9993207	12/2017	Al-Ali et al.	N/A	N/A
10007758	12/2017	Al-Ali et al.	N/A	N/A
D822215	12/2017	Al-Ali et al.	N/A	N/A
D822216	12/2017	Barker et al.	N/A	N/A
10010031	12/2017	Liu et al.	N/A	N/A
10010276	12/2017	Al-Ali et al.	N/A	N/A
10032002	12/2017	Kiani et al.	N/A	N/A
10039482	12/2017	Al-Ali et al.	N/A	N/A
10052037	12/2017	Kinast et al.	N/A	N/A
10058275	12/2017	Al-Ali et al.	N/A	N/A
10064562	12/2017	Al-Ali	N/A	N/A
10086138	12/2017	Novak, Jr.	N/A	N/A
10092200	12/2017	Al-Ali et al.	N/A	N/A
10092249	12/2017	Kiani et al.	N/A	N/A
10098550	12/2017	Al-Ali et al.	N/A	N/A
10098591	12/2017	Al-Ali et al.	N/A	N/A
10098610	12/2017	Al-Ali et al.	N/A	N/A
10111591	12/2017	Dyell et al.	N/A	N/A
D833624	12/2017	DeJong et al.	N/A	N/A
10123726	12/2017	Al-Ali et al.	N/A	N/A
10123729	12/2017	Dyell et al.	N/A	N/A
10130289	12/2017	Al-Ali et al.	N/A	N/A
10130291	12/2017	Schurman et al.	N/A	N/A
D835282	12/2017	Barker et al.	N/A	N/A
D835283	12/2017	Barker et al.	N/A	N/A
D835284	12/2017	Barker et al.	N/A	N/A
D835285	12/2017	Barker et al.	N/A	N/A
10149616	12/2017	Al-Ali et al.	N/A	N/A
10154815	12/2017	Al-Ali et al.	N/A	N/A
10159412	12/2017	Lamego et al.	N/A	N/A
10188296	12/2018	Al-Ali et al.	N/A	N/A
10188331	12/2018	Al-Ali et al.	N/A	N/A
10188348	12/2018	Kiani et al.	N/A	N/A
RE47218	12/2018	Ali-Ali	N/A	N/A
RE47244	12/2018	Kiani et al.	N/A	N/A
RE47249	12/2018	Kiani et al.	N/A	N/A
10194847	12/2018	Al-Ali	N/A	N/A
10194848	12/2018	Kiani et al.	N/A	N/A
10201298	12/2018	Al-Ali et al.	N/A	N/A
10205272	12/2018	Kiani et al.	N/A	N/A
10205291	12/2018	Scruggs et al.	N/A	N/A
10213108	12/2018	Al-Ali	N/A	N/A
10219706	12/2018	Al-Ali	N/A	N/A
10219746	12/2018	McHale et al.	N/A	N/A
10226187	12/2018	Al-Ali et al.	N/A	N/A
10226576	12/2018	Kiani	N/A	N/A
10231657	12/2018	Al-Ali et al.	N/A	N/A

10231670	12/2018	Blank et al.	N/A	N/A
10231676	12/2018	Al-Ali et al.	N/A	N/A
RE47353	12/2018	Kiani et al.	N/A	N/A
10251585	12/2018	Al-Ali et al.	N/A	N/A
10251586	12/2018	Lamego	N/A	N/A
10255994	12/2018	Sampath et al.	N/A	N/A
10258265	12/2018	Poeze et al.	N/A	N/A
10258266	12/2018	Poeze et al.	N/A	N/A
10271748	12/2018	Al-Ali	N/A	N/A
10278626	12/2018	Schurman et al.	N/A	N/A
10278648	12/2018	Al-Ali et al.	N/A	N/A
10279247	12/2018	Kiani	N/A	N/A
10292628	12/2018	Poeze et al.	N/A	N/A
10292657	12/2018	Abdul-Hafiz et al.	N/A	N/A
10292664	12/2018	Al-Ali	N/A	N/A
10299708	12/2018	Poeze et al.	N/A	N/A
10299709	12/2018	Perea et al.	N/A	N/A
10299720	12/2018	Brown et al.	N/A	N/A
10305775	12/2018	Lamego et al.	N/A	N/A
10307111	12/2018	Muhsin et al.	N/A	N/A
10325681	12/2018	Sampath et al.	N/A	N/A
10327337	12/2018	Triman et al.	N/A	N/A
10327713	12/2018	Barker et al.	N/A	N/A
10332630	12/2018	Al-Ali	N/A	N/A
10335033	12/2018	Al-Ali	N/A	N/A
10335068	12/2018	Poeze et al.	N/A	N/A
10335072	12/2018	Al-Ali et al.	N/A	N/A
10342470	12/2018	Al-Ali et al.	N/A	N/A
10342487	12/2018	Al-Ali et al.	N/A	N/A
10342497	12/2018	Al-Ali et al.	N/A	N/A
10349895	12/2018	Telfort et al.	N/A	N/A
10349898	12/2018	Al-Ali et al.	N/A	N/A
10354504	12/2018	Kiani et al.	N/A	N/A
10357206	12/2018	Weber et al.	N/A	N/A
10357209	12/2018	Al-Ali	N/A	N/A
10366787	12/2018	Sampath et al.	N/A	N/A
10368787	12/2018	Reichgott et al.	N/A	N/A
10376190	12/2018	Poeze et al.	N/A	N/A
10376191	12/2018	Poeze et al.	N/A	N/A
10383520	12/2018	Wojtczuk et al.	N/A	N/A
10383527	12/2018	Al-Ali	N/A	N/A
10388120	12/2018	Muhsin et al.	N/A	N/A
10398320	12/2018	Kiani et al.	N/A	N/A
10405804	12/2018	Al-Ali	N/A	N/A
10413666	12/2018	Al-Ali et al.	N/A	N/A
10420493	12/2018	Al-Ali et al.	N/A	N/A
D864120	12/2018	Forrest et al.	N/A	N/A
10433776	12/2018	Al-Ali	N/A	N/A
10441181	12/2018	Telfort et al.	N/A	N/A
10441196	12/2018	Eckerbom et al.	N/A	N/A

10448844	12/2018	Al-Ali et al.	N/A	N/A
10448871	12/2018	Al-Ali	N/A	N/A
10456038	12/2018	Lamego et al.	N/A	N/A
10463340	12/2018	Telfort et al.	N/A	N/A
10471159	12/2018	Lapotko et al.	N/A	N/A
10505311	12/2018	Al-Ali et al.	N/A	N/A
10512436	12/2018	Muhsin et al.	N/A	N/A
10524738	12/2019	Olsen	N/A	N/A
10532174	12/2019	Al-Ali	N/A	N/A
10537285	12/2019	Sherim et al.	N/A	N/A
10542903	12/2019	Al-Ali et al.	N/A	N/A
10555678	12/2019	Dalvi et al.	N/A	N/A
10568553	12/2019	O'Neil et al.	N/A	N/A
RE47882	12/2019	Al-Ali	N/A	N/A
10608817	12/2019	Haider et al.	N/A	N/A
D880477	12/2019	Forrest et al.	N/A	N/A
10617302	12/2019	Al-Ali et al.	N/A	N/A
10617335	12/2019	Al-Ali et al.	N/A	N/A
10637181	12/2019	Al-Ali et al.	N/A	N/A
D886849	12/2019	Muhsin et al.	N/A	N/A
D887548	12/2019	Abdul-Hafiz et al.	N/A	N/A
D887549	12/2019	Abdul-Hafiz et al.	N/A	N/A
10667764	12/2019	Ahmed et al.	N/A	N/A
D890708	12/2019	Forrest et al.	N/A	N/A
10721785	12/2019	Al-Ali	N/A	N/A
10736518	12/2019	Al-Ali et al.	N/A	N/A
10750984	12/2019	Pauley et al.	N/A	N/A
D897098	12/2019	Al-Ali	N/A	N/A
10779098	12/2019	Iswanto et al.	N/A	N/A
10827961	12/2019	Iyengar et al.	N/A	N/A
10828007	12/2019	Telfort et al.	N/A	N/A
10832818	12/2019	Muhsin et al.	N/A	N/A
10849554	12/2019	Shreim et al.	N/A	N/A
10856750	12/2019	Indorf	N/A	N/A
10869602	12/2019	Al-Ali	N/A	N/A
D906970	12/2020	Forrest et al.	N/A	N/A
D908213	12/2020	Abdul-Hafiz et al.	N/A	N/A
10912524	12/2020	Al-Ali et al.	N/A	N/A
10918281	12/2020	Al-Ali et al.	N/A	N/A
10925550	12/2020	Al-Ali et al.	N/A	N/A
10932705	12/2020	Muhsin et al.	N/A	N/A
10932729	12/2020	Kiani et al.	N/A	N/A
10939878	12/2020	Kiani et al.	N/A	N/A
10943450	12/2020	Kiani et al.	N/A	N/A
10956950	12/2020	Al-Ali et al.	N/A	N/A
D916135	12/2020	Indorf et al.	N/A	N/A
D917046	12/2020	Abdul-Hafiz et al.	N/A	N/A
D917550	12/2020	Indorf et al.	N/A	N/A
D917564	12/2020	Indorf et al.	N/A	N/A
D917704	12/2020	Al-Ali et al.	N/A	N/A

10987066	12/2020	Chandran et al.	N/A	N/A
10991135	12/2020	Al-Ali et al.	N/A	N/A
D919094	12/2020	Al-Ali et al.	N/A	N/A
D919100	12/2020	Al-Ali et al.	N/A	N/A
11006867	12/2020	Al-Ali	N/A	N/A
D921202	12/2020	Al-Ali et al.	N/A	N/A
11024064	12/2020	Muhsin et al.	N/A	N/A
11026604	12/2020	Chen et al.	N/A	N/A
D925597	12/2020	Chandran et al.	N/A	N/A
D927699	12/2020	Al-Ali et al.	N/A	N/A
11076777	12/2020	Lee et al.	N/A	N/A
11083397	12/2020	Al-Ali et al.	N/A	N/A
11114188	12/2020	Poeze et al.	N/A	N/A
D933232	12/2020	Al-Ali et al.	N/A	N/A
D933233	12/2020	Al-Ali et al.	N/A	N/A
D933234	12/2020	Al-Ali et al.	N/A	N/A
11145408	12/2020	Sampath et al.	N/A	N/A
11147518	12/2020	Al-Ali et al.	N/A	N/A
11179114	12/2020	Al-Ali et al.	N/A	N/A
11185262	12/2020	Al-Ali et al.	N/A	N/A
11191484	12/2020	Kiani et al.	N/A	N/A
11241199	12/2021	Housel et al.	N/A	N/A
D946596	12/2021	Ahmed	N/A	N/A
D946597	12/2021	Ahmed	N/A	N/A
D946598	12/2021	Ahmed	N/A	N/A
D946617	12/2021	Ahmed	N/A	N/A
11272839	12/2021	Al-Ali et al.	N/A	N/A
11289199	12/2021	Al-Ali	N/A	N/A
RE49034	12/2021	Al-Ali	N/A	N/A
11298021	12/2021	Muhsin et al.	N/A	N/A
D950580	12/2021	Ahmed	N/A	N/A
D950599	12/2021	Ahmed	N/A	N/A
D950738	12/2021	Al-Ali et al.	N/A	N/A
D957648	12/2021	Al-Ali	N/A	N/A
11382567	12/2021	O'Brien et al.	N/A	N/A
11389093	12/2021	Triman et al.	N/A	N/A
11406286	12/2021	Al-Ali et al.	N/A	N/A
11417426	12/2021	Muhsin et al.	N/A	N/A
11439329	12/2021	Lamego	N/A	N/A
11445948	12/2021	Scruggs et al.	N/A	N/A
D965789	12/2021	Al-Ali et al.	N/A	N/A
D967433	12/2021	Al-Ali et al.	N/A	N/A
11464410	12/2021	Muhsin	N/A	N/A
11484205	12/2021	Al-Ali	N/A	N/A
11504058	12/2021	Sharma et al.	N/A	N/A
11504066	12/2021	Dalvi et al.	N/A	N/A
D971933	12/2021	Ahmed	N/A	N/A
D973072	12/2021	Ahmed	N/A	N/A
D973685	12/2021	Ahmed	N/A	N/A
D973686	12/2021	Ahmed	N/A	N/A

D974193	12/2022	Forrest et al.	N/A	N/A
D979516	12/2022	Al-Ali et al.	N/A	N/A
D980091	12/2022	Forrest et al.	N/A	N/A
11596363	12/2022	Lamego	N/A	N/A
11627919	12/2022	Kiani et al.	N/A	N/A
11637437	12/2022	Al-Ali et al.	N/A	N/A
D985498	12/2022	Al-Ali et al.	N/A	N/A
11653862	12/2022	Dalvi et al.	N/A	N/A
D989112	12/2022	Muhsin et al.	N/A	N/A
D989327	12/2022	Al-Ali et al.	N/A	N/A
11678829	12/2022	Al-Ali et al.	N/A	N/A
11679579	12/2022	Al-Ali	N/A	N/A
11684296	12/2022	Vo et al.	N/A	N/A
11692934	12/2022	Normand et al.	N/A	N/A
11701043	12/2022	Al-Ali et al.	N/A	N/A
D997365	12/2022	Hwang	N/A	N/A
11721105	12/2022	Ranasinghe et al.	N/A	N/A
11730379	12/2022	Ahmed et al.	N/A	N/A
D998625	12/2022	Indorf et al.	N/A	N/A
D998630	12/2022	Indorf et al.	N/A	N/A
D998631	12/2022	Indorf et al.	N/A	N/A
D999244	12/2022	Indorf et al.	N/A	N/A
D999245	12/2022	Indorf et al.	N/A	N/A
D999246	12/2022	Indorf et al.	N/A	N/A
11766198	12/2022	Pauley et al.	N/A	N/A
D1000975	12/2022	Al-Ali et al.	N/A	N/A
11786183	12/2022	Kiani et al.	N/A	N/A
11803623	12/2022	Kiani et al.	N/A	N/A
11832940	12/2022	Diab et al.	N/A	N/A
D1013179	12/2023	Al-Ali et al.	N/A	N/A
11872156	12/2023	Telfort et al.	N/A	N/A
11879960	12/2023	Ranasinghe et al.	N/A	N/A
11883129	12/2023	Olsen	N/A	N/A
11900775	12/2023	Kiani et al.	N/A	N/A
11918353	12/2023	Al-Ali et al.	N/A	N/A
D1022729	12/2023	Forrest et al.	N/A	N/A
11951186	12/2023	Krishnamani et al.	N/A	N/A
11963736	12/2023	Welch et al.	N/A	N/A
11974833	12/2023	Forrest et al.	N/A	N/A
11986067	12/2023	Al-Ali et al.	N/A	N/A
11986289	12/2023	Dalvi et al.	N/A	N/A
11986305	12/2023	Al-Ali et al.	N/A	N/A
D1031729	12/2023	Forrest et al.	N/A	N/A
12004869	12/2023	Kiani et al.	N/A	N/A
12014328	12/2023	Wachman et al.	N/A	N/A
D1036293	12/2023	Al-Ali	N/A	N/A
D1037462	12/2023	Al-Ali et al.	N/A	N/A
12029844	12/2023	Pauley et al.	N/A	N/A
12048534	12/2023	Vo et al.	N/A	N/A
12064217	12/2023	Ahmed et al.	N/A	N/A

12066426	12/2023	Lapotko et al.	N/A	N/A
D1041511	12/2023	Indorf et al.	N/A	N/A
D1042596	12/2023	DeJong et al.	N/A	N/A
D1042852	12/2023	Hwang	N/A	N/A
12076159	12/2023	Belur Nagaraj et al.	N/A	N/A
12082926	12/2023	Sharma et al.	N/A	N/A
D1044828	12/2023	Chandran et al.	N/A	N/A
D1048571	12/2023	Yu et al.	N/A	N/A
D1048908	12/2023	Al-Ali et al.	N/A	N/A
12106752	12/2023	Campbell et al.	N/A	N/A
12109022	12/2023	Al-Ali et al.	N/A	N/A
12114974	12/2023	Al-Ali et al.	N/A	N/A
12126683	12/2023	Koo et al.	N/A	N/A
12127838	12/2023	Olsen et al.	N/A	N/A
12128213	12/2023	Kiani et al.	N/A	N/A
12131661	12/2023	Pauley et al.	N/A	N/A
D1050910	12/2023	Al-Ali et al.	N/A	N/A
12178572	12/2023	Pauley et al.	N/A	N/A
12178581	12/2023	Telfort et al.	N/A	N/A
12178852	12/2023	Kiani et al.	N/A	N/A
D1057159	12/2024	DeJong et al.	N/A	N/A
D1057160	12/2024	DeJong et al.	N/A	N/A
12198790	12/2024	Al-Ali	N/A	N/A
12200421	12/2024	Campbell et al.	N/A	N/A
12207901	12/2024	Lapotko et al.	N/A	N/A
D1060680	12/2024	Al-Ali et al.	N/A	N/A
D1061585	12/2024	Indorf	N/A	N/A
D1063893	12/2024	DeJong et al.	N/A	N/A
12220207	12/2024	Telfort et al.	N/A	N/A
12235941	12/2024	Kiani et al.	N/A	N/A
12236767	12/2024	Muhsin	N/A	N/A
D1066244	12/2024	Lim et al.	N/A	N/A
D1066672	12/2024	Al-Ali et al.	N/A	N/A
D1072837	12/2024	Ahmed et al.	N/A	N/A
2001/0011355	12/2000	Kawai	N/A	N/A
2001/0028674	12/2000	Edlis et al.	N/A	N/A
2001/0031922	12/2000	Weng et al.	N/A	N/A
2001/0034477	12/2000	Mansfield et al.	N/A	N/A
2001/0039199	12/2000	Shinzaki	N/A	N/A
2001/0039483	12/2000	Brand et al.	N/A	N/A
2001/0046366	12/2000	Susskind	N/A	N/A
2001/0046862	12/2000	Coppinger et al.	N/A	N/A
2001/0055978	12/2000	Herrod et al.	N/A	N/A
2002/0010401	12/2001	Bushmakina et al.	N/A	N/A
2002/0013517	12/2001	West	N/A	N/A
2002/0032386	12/2001	Sackner et al.	N/A	N/A
2002/0038392	12/2001	De La Huerga	N/A	N/A
2002/0044059	12/2001	Reeder et al.	N/A	N/A
2002/0045836	12/2001	Alkawwas	N/A	N/A
2002/0052311	12/2001	Solomon et al.	N/A	N/A

2002/0058864	12/2001	Mansfield et al.	N/A	N/A
2002/0063690	12/2001	Chung et al.	N/A	N/A
2002/0133080	12/2001	Apruzzese et al.	N/A	N/A
2002/0140675	12/2001	Ali et al.	N/A	N/A
2002/0165462	12/2001	Westbrook et al.	N/A	N/A
2002/0177473	12/2001	Skinner et al.	N/A	N/A
2002/0177758	12/2001	Schoenberg	N/A	N/A
2002/0179470	12/2001	Lee	N/A	N/A
2002/0198445	12/2001	Dominguez et al.	N/A	N/A
2003/0013975	12/2002	Kiani	N/A	N/A
2003/0018243	12/2002	Gerhardt et al.	N/A	N/A
2003/0027326	12/2002	Ulmsten et al.	N/A	N/A
2003/0052787	12/2002	Zerhusen et al.	N/A	N/A
2003/0058838	12/2002	Wengrovitz	N/A	N/A
2003/0083113	12/2002	Chua et al.	N/A	N/A
2003/0144582	12/2002	Cohen et al.	N/A	N/A
2003/0154108	12/2002	Fletcher-Haynes et al.	N/A	N/A
2003/0156288	12/2002	Barnum et al.	N/A	N/A
2003/0158466	12/2002	Lynn et al.	N/A	N/A
2003/0208113	12/2002	Mault	N/A	N/A
2003/0212312	12/2002	Coffin, IV et al.	N/A	N/A
2003/0216670	12/2002	Beggs	N/A	N/A
2003/0235029	12/2002	Doherty	N/A	N/A
2004/0009787	12/2003	Oh et al.	N/A	N/A
2004/0013647	12/2003	Solomon et al.	N/A	N/A
2004/0029619	12/2003	Liang et al.	N/A	N/A
2004/0034289	12/2003	Teller	N/A	N/A
2004/0106163	12/2003	Workman, Jr. et al.	N/A	N/A
2004/0122787	12/2003	Avinash et al.	N/A	N/A
2004/0126007	12/2003	Ziel et al.	N/A	N/A
2004/0139571	12/2003	Chang et al.	N/A	N/A
2004/0147818	12/2003	Levy et al.	N/A	N/A
2004/0186357	12/2003	Soderberg et al.	N/A	N/A
2004/0230118	12/2003	Shehada et al.	N/A	N/A
2004/0230132	12/2003	Shehada et al.	N/A	N/A
2004/0230179	12/2003	Shehada et al.	N/A	N/A
2004/0243017	12/2003	Causevic	N/A	N/A
2004/0249291	12/2003	Honda et al.	N/A	N/A
2004/0249670	12/2003	Noguchi et al.	N/A	N/A
2004/0254431	12/2003	Shehada et al.	N/A	N/A
2004/0254432	12/2003	Shehada et al.	N/A	N/A
2004/0267103	12/2003	Li et al.	N/A	N/A
2005/0020918	12/2004	Wilk et al.	N/A	N/A
2005/0038332	12/2004	Saidara et al.	N/A	N/A
2005/0038680	12/2004	McMahon	N/A	N/A
2005/0055276	12/2004	Kiani et al.	N/A	N/A
2005/0080336	12/2004	Byrd et al.	N/A	N/A
2005/0096542	12/2004	Weng et al.	N/A	N/A

2005/0113648	12/2004	Yang	128/903	G16H 40/67
2005/0113653	12/2004	Fox et al.	N/A	N/A
2005/0124864	12/2004	Mack et al.	N/A	N/A
2005/0125256	12/2004	Schoenberg	N/A	N/A
2005/0164933	12/2004	Tymianski et al.	N/A	N/A
2005/0171444	12/2004	Ono et al.	N/A	N/A
2005/0188083	12/2004	Biondi et al.	N/A	N/A
2005/0191294	12/2004	Arap et al.	N/A	N/A
2005/0228297	12/2004	Banet et al.	N/A	N/A
2005/0234317	12/2004	Kiani	N/A	N/A
2005/0261598	12/2004	Banet et al.	N/A	N/A
2005/0268401	12/2004	Dixon et al.	N/A	N/A
2005/0277872	12/2004	Colby, Jr. et al.	N/A	N/A
2005/0288571	12/2004	Perkins	N/A	N/A
2006/0047214	12/2005	Fraden	N/A	N/A
2006/0047215	12/2005	Barnes et al.	N/A	N/A
2006/0049936	12/2005	Collins, Jr. et al.	N/A	N/A
2006/0052718	12/2005	Parnagian	N/A	N/A
2006/0058647	12/2005	Strommer et al.	N/A	N/A
2006/0073719	12/2005	Kiani	N/A	N/A
2006/0087606	12/2005	Munyon	N/A	N/A
2006/0089543	12/2005	Kim et al.	N/A	N/A
2006/0094936	12/2005	Russ	N/A	N/A
2006/0122517	12/2005	Banet et al.	N/A	N/A
2006/0149393	12/2005	Calderon	N/A	N/A
2006/0154642	12/2005	Scannell, Jr.	N/A	N/A
2006/0155175	12/2005	Ogino et al.	N/A	N/A
2006/0161054	12/2005	Reuss et al.	N/A	N/A
2006/0189871	12/2005	Al-Ali et al.	N/A	N/A
2006/0200009	12/2005	Wekell et al.	N/A	N/A
2006/0217684	12/2005	Shehada et al.	N/A	N/A
2006/0217685	12/2005	Shehada et al.	N/A	N/A
2006/0224413	12/2005	Kim et al.	N/A	N/A
2006/0235300	12/2005	Weng et al.	N/A	N/A
2006/0252418	12/2005	Quinn et al.	N/A	N/A
2006/0253042	12/2005	Stahmann et al.	N/A	N/A
2007/0000490	12/2006	DeVries et al.	N/A	N/A
2007/0002533	12/2006	Kogan et al.	N/A	N/A
2007/0021675	12/2006	Childre et al.	N/A	N/A
2007/0027368	12/2006	Collins et al.	N/A	N/A
2007/0030116	12/2006	Feher	N/A	N/A
2007/0032733	12/2006	Burton et al.	N/A	N/A
2007/0055116	12/2006	Clark et al.	N/A	N/A
2007/0055544	12/2006	Jung et al.	N/A	N/A
2007/0060798	12/2006	Krupnik et al.	N/A	N/A
2007/0073116	12/2006	Kiani et al.	N/A	N/A
2007/0079012	12/2006	Walker	N/A	N/A
2007/0088406	12/2006	Bennett et al.	N/A	N/A
2007/0096897	12/2006	Weiner	N/A	N/A

2007/0100222	12/2006	Mastrototaro et al.	N/A	N/A
2007/0118399	12/2006	Avinash et al.	N/A	N/A
2007/0118853	12/2006	Kreitzer et al.	N/A	N/A
2007/0140475	12/2006	Kurtock et al.	N/A	N/A
2007/0156033	12/2006	Causey et al.	N/A	N/A
2007/0157285	12/2006	Frank et al.	N/A	N/A
2007/0159332	12/2006	Koblasz	N/A	N/A
2007/0163589	12/2006	DeVries et al.	N/A	N/A
2007/0180140	12/2006	Welch et al.	N/A	N/A
2007/0185390	12/2006	Perkins et al.	N/A	N/A
2007/0197881	12/2006	Wolf et al.	N/A	N/A
2007/0232941	12/2006	Rabinovich	N/A	N/A
2007/0244377	12/2006	Cozad et al.	N/A	N/A
2007/0244724	12/2006	Pendergast et al.	N/A	N/A
2007/0254593	12/2006	Jollota et al.	N/A	N/A
2007/0255114	12/2006	Ackermann et al.	N/A	N/A
2007/0255116	12/2006	Mehta et al.	N/A	N/A
2007/0255250	12/2006	Moberg et al.	N/A	N/A
2007/0282212	12/2006	Sierra et al.	N/A	N/A
2007/0282478	12/2006	Al-Ali et al.	N/A	N/A
2007/0293906	12/2006	Cowan et al.	N/A	N/A
2008/0000479	12/2007	Elaz et al.	N/A	N/A
2008/0003200	12/2007	Arap et al.	N/A	N/A
2008/0020799	12/2007	Itamiya et al.	N/A	N/A
2008/0021854	12/2007	Jung et al.	N/A	N/A
2008/0033661	12/2007	Syroid et al.	N/A	N/A
2008/0039701	12/2007	Ali et al.	N/A	N/A
2008/0053438	12/2007	DeVries et al.	N/A	N/A
2008/0058657	12/2007	Schwartz et al.	N/A	N/A
2008/0064965	12/2007	Jay et al.	N/A	N/A
2008/0076972	12/2007	Dorogusker et al.	N/A	N/A
2008/0090626	12/2007	Griffin et al.	N/A	N/A
2008/0091089	12/2007	Guillory et al.	N/A	N/A
2008/0091090	12/2007	Guillory et al.	N/A	N/A
2008/0091471	12/2007	Michon et al.	N/A	N/A
2008/0094228	12/2007	Welch et al.	N/A	N/A
2008/0097167	12/2007	Yudkovitch et al.	N/A	N/A
2008/0099366	12/2007	Niemiec et al.	N/A	N/A
2008/0103375	12/2007	Kiani	N/A	N/A
2008/0108884	12/2007	Kiani	N/A	N/A
2008/0119412	12/2007	Tymianski et al.	N/A	N/A
2008/0138278	12/2007	Scherz et al.	N/A	N/A
2008/0169922	12/2007	Issokson	N/A	N/A
2008/0171919	12/2007	Stivoric et al.	N/A	N/A
2008/0188795	12/2007	Katz et al.	N/A	N/A
2008/0194918	12/2007	Kulik et al.	N/A	N/A
2008/0198822	12/2007	Magnusson et al.	N/A	N/A
2008/0208912	12/2007	Garibaldi	N/A	N/A
2008/0215627	12/2007	Higgins et al.	N/A	N/A
2008/0221396	12/2007	Garces et al.	N/A	N/A

2008/0221418	12/2007	Al-Ali et al.	N/A	N/A
2008/0228045	12/2007	Gao et al.	N/A	N/A
2008/0228077	12/2007	Wilk et al.	N/A	N/A
2008/0259551	12/2007	Gavenda et al.	N/A	N/A
2008/0275309	12/2007	Stivoric et al.	N/A	N/A
2008/0281167	12/2007	Soderberg et al.	N/A	N/A
2008/0281168	12/2007	Gibson et al.	N/A	N/A
2008/0281181	12/2007	Manziona et al.	N/A	N/A
2008/0287751	12/2007	Stivoric et al.	N/A	N/A
2008/0292172	12/2007	Assmann et al.	N/A	N/A
2008/0300020	12/2007	Nishizawa et al.	N/A	N/A
2008/0319275	12/2007	Chiu et al.	N/A	N/A
2008/0319354	12/2007	Bell et al.	N/A	N/A
2009/0005651	12/2008	Ward et al.	N/A	N/A
2009/0005703	12/2008	Fasciano	600/300	A61B 5/742
2009/0018409	12/2008	Banet et al.	N/A	N/A
2009/0018808	12/2008	Bronstein et al.	N/A	N/A
2009/0024008	12/2008	Brunner et al.	N/A	N/A
2009/0036759	12/2008	Ault et al.	N/A	N/A
2009/0043172	12/2008	Zagorchev et al.	N/A	N/A
2009/0052623	12/2008	Tome et al.	N/A	N/A
2009/0054735	12/2008	Higgins et al.	N/A	N/A
2009/0062682	12/2008	Bland et al.	N/A	N/A
2009/0069642	12/2008	Gao et al.	N/A	N/A
2009/0081951	12/2008	Erdmann et al.	N/A	N/A
2009/0093687	12/2008	Telfort et al.	N/A	N/A
2009/0095926	12/2008	MacNeish, III	N/A	N/A
2009/0099480	12/2008	Salgo et al.	N/A	N/A
2009/0119330	12/2008	Sampath et al.	N/A	N/A
2009/0119843	12/2008	Rodgers et al.	N/A	N/A
2009/0124867	12/2008	Hirsch et al.	N/A	N/A
2009/0131759	12/2008	Sims et al.	N/A	N/A
2009/0143832	12/2008	Saba	N/A	N/A
2009/0147024	12/2008	Sadler	345/629	G06T 11/206
2009/0154432	12/2008	Hassan et al.	N/A	N/A
2009/0157058	12/2008	Ferren et al.	N/A	N/A
2009/0171170	12/2008	Li et al.	N/A	N/A
2009/0171225	12/2008	Gadodia et al.	N/A	N/A
2009/0177090	12/2008	Grunwald et al.	N/A	N/A
2009/0182287	12/2008	Kassab	N/A	N/A
2009/0221887	12/2008	Mannheimer et al.	N/A	N/A
2009/0226372	12/2008	Ruoslahti et al.	N/A	N/A
2009/0247984	12/2008	Lamego et al.	N/A	N/A
2009/0264778	12/2008	Markowitz et al.	N/A	N/A
2009/0275809	12/2008	Starr	N/A	N/A
2009/0275813	12/2008	Davis	N/A	N/A
2009/0275844	12/2008	Ai-Ali	N/A	N/A
2009/0281462	12/2008	Heliot et al.	N/A	N/A

2009/0295328	12/2008	Griffin, Jr.	N/A	N/A
2009/0299157	12/2008	Telfort et al.	N/A	N/A
2009/0309755	12/2008	Williamson	N/A	N/A
2009/0322540	12/2008	Richardson et al.	N/A	N/A
2009/0326386	12/2008	Sethi et al.	N/A	N/A
2009/0326395	12/2008	Watson	N/A	N/A
2010/0004518	12/2009	Vo et al.	N/A	N/A
2010/0030040	12/2009	Poeze et al.	N/A	N/A
2010/0030094	12/2009	Lundback	N/A	N/A
2010/0036209	12/2009	Ferren et al.	N/A	N/A
2010/0060747	12/2009	Woodman	N/A	N/A
2010/0069725	12/2009	Al-Ali	N/A	N/A
2010/0081895	12/2009	Zand	N/A	N/A
2010/0099964	12/2009	O'Reilly et al.	N/A	N/A
2010/0114254	12/2009	Kornet	N/A	N/A
2010/0125188	12/2009	Schilling et al.	N/A	N/A
2010/0125217	12/2009	Kuo et al.	N/A	N/A
2010/0130875	12/2009	Banet et al.	N/A	N/A
2010/0144627	12/2009	Vitek et al.	N/A	N/A
2010/0145146	12/2009	Melder	N/A	N/A
2010/0173532	12/2009	Czyz et al.	N/A	N/A
2010/0177100	12/2009	Carnes et al.	N/A	N/A
2010/0182518	12/2009	Kirmse et al.	N/A	N/A
2010/0185101	12/2009	Sakai et al.	N/A	N/A
2010/0198622	12/2009	Gajic et al.	N/A	N/A
2010/0210958	12/2009	Manwaring et al.	N/A	N/A
2010/0234706	12/2009	Gilland	N/A	N/A
2010/0234718	12/2009	Sampath et al.	N/A	N/A
2010/0240945	12/2009	Bikko	N/A	N/A
2010/0241115	12/2009	Benamou et al.	N/A	N/A
2010/0249540	12/2009	Lisogurski	N/A	N/A
2010/0250975	12/2009	Gill et al.	N/A	N/A
2010/0261979	12/2009	Kiani	600/301	G16H 40/63
2010/0270257	12/2009	Wachman et al.	N/A	N/A
2010/0280339	12/2009	Russ	N/A	N/A
2010/0298651	12/2009	Moon et al.	N/A	N/A
2010/0298657	12/2009	McCombie et al.	N/A	N/A
2010/0298659	12/2009	McCombie et al.	N/A	N/A
2010/0298661	12/2009	McCombie et al.	N/A	N/A
2010/0298742	12/2009	Perlman et al.	N/A	N/A
2010/0305412	12/2009	Darrah et al.	N/A	N/A
2010/0312103	12/2009	Gorek et al.	N/A	N/A
2010/0317936	12/2009	Al-Ali et al.	N/A	N/A
2010/0317951	12/2009	Rutkowski et al.	N/A	N/A
2010/0331631	12/2009	MacLaughlin	N/A	N/A
2011/0001605	12/2010	Kiani et al.	N/A	N/A
2011/0004489	12/2010	Schoenberg et al.	N/A	N/A
2011/0015533	12/2010	Cox et al.	N/A	N/A
2011/0021930	12/2010	Mazzeo et al.	N/A	N/A

2011/0023130	12/2010	Gudgel et al.	N/A	N/A
2011/0028806	12/2010	Merritt et al.	N/A	N/A
2011/0028809	12/2010	Goodman	N/A	N/A
2011/0040197	12/2010	Welch et al.	N/A	N/A
2011/0046495	12/2010	Osyпка	N/A	N/A
2011/0066045	12/2010	Moon et al.	N/A	N/A
2011/0066051	12/2010	Moon et al.	N/A	N/A
2011/0077473	12/2010	Lisogurski	N/A	N/A
2011/0077487	12/2010	Buxton et al.	N/A	N/A
2011/0078596	12/2010	Rawlins et al.	N/A	N/A
2011/0080294	12/2010	Tanishima et al.	N/A	N/A
2011/0082711	12/2010	Poeze et al.	N/A	N/A
2011/0084850	12/2010	Jiang et al.	N/A	N/A
2011/0087081	12/2010	Kiani et al.	N/A	N/A
2011/0087083	12/2010	Poeze et al.	N/A	N/A
2011/0087084	12/2010	Jeong et al.	N/A	N/A
2011/0087117	12/2010	Tremper et al.	N/A	N/A
2011/0087756	12/2010	Biondi	N/A	N/A
2011/0098583	12/2010	Pandia et al.	N/A	N/A
2011/0105854	12/2010	Kiani et al.	N/A	N/A
2011/0105956	12/2010	Hirth	N/A	N/A
2011/0118561	12/2010	Tari et al.	N/A	N/A
2011/0118573	12/2010	Mckenna	N/A	N/A
2011/0118616	12/2010	Vajdic et al.	N/A	N/A
2011/0125060	12/2010	Telfort et al.	N/A	N/A
2011/0137297	12/2010	Kiani et al.	N/A	N/A
2011/0148622	12/2010	Judy et al.	N/A	N/A
2011/0149871	12/2010	Liu et al.	N/A	N/A
2011/0152629	12/2010	Eaton et al.	N/A	N/A
2011/0172498	12/2010	Olsen et al.	N/A	N/A
2011/0172967	12/2010	Al-Ali et al.	N/A	N/A
2011/0184252	12/2010	Archer et al.	N/A	N/A
2011/0184253	12/2010	Archer et al.	N/A	N/A
2011/0193704	12/2010	Harper et al.	N/A	N/A
2011/0208015	12/2010	Welch et al.	N/A	N/A
2011/0208018	12/2010	Kiani	N/A	N/A
2011/0208073	12/2010	Matsukawa et al.	N/A	N/A
2011/0209915	12/2010	Telfort et al.	N/A	N/A
2011/0212090	12/2010	Pedersen et al.	N/A	N/A
2011/0212746	12/2010	Sarkar et al.	N/A	N/A
2011/0213212	12/2010	Al-Ali	N/A	N/A
2011/0227739	12/2010	Gilham et al.	N/A	N/A
2011/0230733	12/2010	Al-Ali	N/A	N/A
2011/0237911	12/2010	Lamego et al.	N/A	N/A
2011/0237969	12/2010	Eckerbom et al.	N/A	N/A
2011/0257544	12/2010	Kaasinen et al.	N/A	N/A
2011/0257554	12/2010	Banet et al.	N/A	N/A
2011/0263950	12/2010	Larson et al.	N/A	N/A
2011/0270047	12/2010	O'Brien	600/301	A61M 5/1723

2011/0288383	12/2010	Diab	N/A	N/A
2011/0295094	12/2010	Doyle et al.	N/A	N/A
2011/0301444	12/2010	Al-Ali	N/A	N/A
2011/0307274	12/2010	Thompson et al.	N/A	N/A
2012/0004579	12/2011	Luo et al.	N/A	N/A
2012/0029300	12/2011	Paquet	N/A	N/A
2012/0029879	12/2011	Sing et al.	N/A	N/A
2012/0041316	12/2011	Al-Ali et al.	N/A	N/A
2012/0046557	12/2011	Kiani	N/A	N/A
2012/0059230	12/2011	Teller et al.	N/A	N/A
2012/0059267	12/2011	Lamego et al.	N/A	N/A
2012/0071771	12/2011	Behar	N/A	N/A
2012/0075464	12/2011	Derenne et al.	N/A	N/A
2012/0088984	12/2011	Al-Ali et al.	N/A	N/A
2012/0101353	12/2011	Reggiardo et al.	N/A	N/A
2012/0102455	12/2011	Ambat et al.	N/A	N/A
2012/0108917	12/2011	Libbus et al.	N/A	N/A
2012/0116175	12/2011	Al-Ali et al.	N/A	N/A
2012/0123231	12/2011	O'Reilly	N/A	N/A
2012/0123799	12/2011	Nolen et al.	N/A	N/A
2012/0127103	12/2011	Qualey et al.	N/A	N/A
2012/0136221	12/2011	Killen et al.	N/A	N/A
2012/0165629	12/2011	Merritt et al.	N/A	N/A
2012/0179006	12/2011	Jansen et al.	N/A	N/A
2012/0184120	12/2011	Basta et al.	N/A	N/A
2012/0197619	12/2011	Namer Yelin et al.	N/A	N/A
2012/0198341	12/2011	Pekarske et al.	N/A	N/A
2012/0203078	12/2011	Sze et al.	N/A	N/A
2012/0209082	12/2011	Al-Ali	N/A	N/A
2012/0209084	12/2011	Olsen et al.	N/A	N/A
2012/0221634	12/2011	Treu et al.	N/A	N/A
2012/0224694	12/2011	Lu et al.	N/A	N/A
2012/0226117	12/2011	Lamego et al.	N/A	N/A
2012/0226160	12/2011	Kudoh	N/A	N/A
2012/0227739	12/2011	Kiani	N/A	N/A
2012/0239434	12/2011	Breslow et al.	N/A	N/A
2012/0242501	12/2011	Tran et al.	N/A	N/A
2012/0265039	12/2011	Kiani	N/A	N/A
2012/0275392	12/2011	Haddad	N/A	N/A
2012/0282583	12/2011	Thaler et al.	N/A	N/A
2012/0283524	12/2011	Kiani et al.	N/A	N/A
2012/0284053	12/2011	Rosenfeld	N/A	N/A
2012/0286955	12/2011	Welch et al.	N/A	N/A
2012/0294801	12/2011	Scherz et al.	N/A	N/A
2012/0296178	12/2011	Lamego et al.	N/A	N/A
2012/0302894	12/2011	Diab et al.	N/A	N/A
2012/0303476	12/2011	Krzyzanowski et al.	N/A	N/A
2012/0319816	12/2011	Al-Ali	N/A	N/A
2012/0330112	12/2011	Lamego et al.	N/A	N/A
2013/0006131	12/2012	Narayan et al.	N/A	N/A

2013/0006151	12/2012	Main et al.	N/A	N/A
2013/0023775	12/2012	Lamego et al.	N/A	N/A
2013/0035603	12/2012	Jarausch et al.	N/A	N/A
2013/0041591	12/2012	Lamego	N/A	N/A
2013/0046197	12/2012	Dlugos, Jr. et al.	N/A	N/A
2013/0046204	12/2012	Lamego et al.	N/A	N/A
2013/0060108	12/2012	Schurman et al.	N/A	N/A
2013/0060147	12/2012	Welch et al.	N/A	N/A
2013/0079610	12/2012	Al-Ali	N/A	N/A
2013/0092805	12/2012	Funk et al.	N/A	N/A
2013/0096405	12/2012	Garfio	N/A	N/A
2013/0096936	12/2012	Sampath et al.	N/A	N/A
2013/0109929	12/2012	Menzel	N/A	N/A
2013/0109935	12/2012	Al-Ali et al.	N/A	N/A
2013/0123616	12/2012	Merritt et al.	N/A	N/A
2013/0162433	12/2012	Muhsin et al.	N/A	N/A
2013/0178718	12/2012	Tran et al.	N/A	N/A
2013/0178749	12/2012	Lamego	N/A	N/A
2013/0190581	12/2012	Al-Ali et al.	N/A	N/A
2013/0191513	12/2012	Kamen et al.	N/A	N/A
2013/0197328	12/2012	Diab et al.	N/A	N/A
2013/0197364	12/2012	Han	N/A	N/A
2013/0211214	12/2012	Olsen	N/A	N/A
2013/0243021	12/2012	Siskavich	N/A	N/A
2013/0253334	12/2012	Al-Ali et al.	N/A	N/A
2013/0261494	12/2012	Bloom et al.	N/A	N/A
2013/0267793	12/2012	Meador et al.	N/A	N/A
2013/0267804	12/2012	Al-Ali	N/A	N/A
2013/0274571	12/2012	Diab et al.	N/A	N/A
2013/0274572	12/2012	Al-Ali et al.	N/A	N/A
2013/0279109	12/2012	Lindblad et al.	N/A	N/A
2013/0286853	12/2012	Shi et al.	N/A	N/A
2013/0296672	12/2012	O'Neil et al.	N/A	N/A
2013/0296713	12/2012	Al-Ali et al.	N/A	N/A
2013/0317327	12/2012	Al-Ali et al.	N/A	N/A
2013/0317370	12/2012	Dalvi et al.	N/A	N/A
2013/0317393	12/2012	Weiss et al.	N/A	N/A
2013/0324804	12/2012	McKeown et al.	N/A	N/A
2013/0324808	12/2012	Al-Ali et al.	N/A	N/A
2013/0324817	12/2012	Diab	N/A	N/A
2013/0331054	12/2012	Kodali	N/A	N/A
2013/0331660	12/2012	Al-Ali et al.	N/A	N/A
2013/0331670	12/2012	Kiani	N/A	N/A
2013/0332011	12/2012	Ziarno	N/A	N/A
2013/0338461	12/2012	Lamego et al.	N/A	N/A
2013/0340176	12/2012	Stevens et al.	N/A	N/A
2013/0344872	12/2012	Nukala et al.	N/A	N/A
2013/0345921	12/2012	Al-Ali et al.	N/A	N/A
2014/0012100	12/2013	Al-Ali et al.	N/A	N/A
2014/0022081	12/2013	Ribble et al.	N/A	N/A

2014/0025306	12/2013	Weber et al.	N/A	N/A
2014/0031637	12/2013	Fidacaro et al.	N/A	N/A
2014/0031650	12/2013	Weber et al.	N/A	N/A
2014/0034353	12/2013	Al-Ali et al.	N/A	N/A
2014/0046674	12/2013	Rosenfeld	N/A	N/A
2014/0051952	12/2013	Reichgott et al.	N/A	N/A
2014/0051953	12/2013	Lamego et al.	N/A	N/A
2014/0051954	12/2013	Al-Ali et al.	N/A	N/A
2014/0058230	12/2013	Abdul-Hafiz et al.	N/A	N/A
2014/0066783	12/2013	Kiani et al.	N/A	N/A
2014/0073167	12/2013	Al-Ali et al.	N/A	N/A
2014/0077956	12/2013	Sampath et al.	N/A	N/A
2014/0081097	12/2013	Al-Ali et al.	N/A	N/A
2014/0081100	12/2013	Muhsin et al.	N/A	N/A
2014/0081175	12/2013	Telfort	N/A	N/A
2014/0094667	12/2013	Schurman et al.	N/A	N/A
2014/0100434	12/2013	Diab et al.	N/A	N/A
2014/0114199	12/2013	Lamego et al.	N/A	N/A
2014/0120564	12/2013	Workman et al.	N/A	N/A
2014/0121482	12/2013	Merritt et al.	N/A	N/A
2014/0121483	12/2013	Kiani	N/A	N/A
2014/0127137	12/2013	Bellott et al.	N/A	N/A
2014/0128696	12/2013	Al-Ali	N/A	N/A
2014/0128699	12/2013	Al-Ali et al.	N/A	N/A
2014/0129702	12/2013	Lamego et al.	N/A	N/A
2014/0135588	12/2013	Al-Ali et al.	N/A	N/A
2014/0142399	12/2013	Al-Ali et al.	N/A	N/A
2014/0142401	12/2013	Al-Ali et al.	N/A	N/A
2014/0142402	12/2013	Al-Ali et al.	N/A	N/A
2014/0152673	12/2013	Lynn et al.	N/A	N/A
2014/0155712	12/2013	Lamego et al.	N/A	N/A
2014/0163344	12/2013	Ai-Ali	N/A	N/A
2014/0163402	12/2013	Lamego et al.	N/A	N/A
2014/0166076	12/2013	Kiani et al.	N/A	N/A
2014/0171763	12/2013	Diab	N/A	N/A
2014/0180038	12/2013	Kiani	N/A	N/A
2014/0180154	12/2013	Sierra et al.	N/A	N/A
2014/0180160	12/2013	Brown et al.	N/A	N/A
2014/0187973	12/2013	Brown et al.	N/A	N/A
2014/0188516	12/2013	Kamen	N/A	N/A
2014/0194709	12/2013	Al-Ali et al.	N/A	N/A
2014/0194711	12/2013	Al-Ali	N/A	N/A
2014/0194766	12/2013	Al-Ali et al.	N/A	N/A
2014/0200422	12/2013	Weber et al.	N/A	N/A
2014/0206963	12/2013	Al-Ali	N/A	N/A
2014/0213864	12/2013	Abdul-Hafiz et al.	N/A	N/A
2014/0243627	12/2013	Diab et al.	N/A	N/A
2014/0257057	12/2013	Reis Cunha et al.	N/A	N/A
2014/0266787	12/2013	Tran	N/A	N/A
2014/0266790	12/2013	Al-Ali et al.	N/A	N/A

2014/0275808	12/2013	Poeze et al.	N/A	N/A
2014/0275835	12/2013	Lamego et al.	N/A	N/A
2014/0275871	12/2013	Lamego et al.	N/A	N/A
2014/0275872	12/2013	Merritt et al.	N/A	N/A
2014/0275881	12/2013	Lamego et al.	N/A	N/A
2014/0276115	12/2013	Dalvi et al.	N/A	N/A
2014/0288400	12/2013	Diab et al.	N/A	N/A
2014/0296664	12/2013	Bruinsma et al.	N/A	N/A
2014/0303520	12/2013	Telfort et al.	N/A	N/A
2014/0309506	12/2013	Lamego et al.	N/A	N/A
2014/0309559	12/2013	Telfort et al.	N/A	N/A
2014/0316217	12/2013	Purdon et al.	N/A	N/A
2014/0316218	12/2013	Purdon et al.	N/A	N/A
2014/0316228	12/2013	Blank et al.	N/A	N/A
2014/0323825	12/2013	Al-Ali et al.	N/A	N/A
2014/0323897	12/2013	Brown et al.	N/A	N/A
2014/0323898	12/2013	Purdon et al.	N/A	N/A
2014/0330092	12/2013	Al-Ali et al.	N/A	N/A
2014/0330098	12/2013	Merritt et al.	N/A	N/A
2014/0330099	12/2013	Al-Ali et al.	N/A	N/A
2014/0333440	12/2013	Kiani	N/A	N/A
2014/0336481	12/2013	Shakespeare et al.	N/A	N/A
2014/0343436	12/2013	Kiani	N/A	N/A
2014/0343889	12/2013	Ben Shalom et al.	N/A	N/A
2014/0357966	12/2013	Al-Ali et al.	N/A	N/A
2014/0371548	12/2013	Al-Ali et al.	N/A	N/A
2014/0371632	12/2013	Al-Ali et al.	N/A	N/A
2014/0378784	12/2013	Kiani et al.	N/A	N/A
2015/0001302	12/2014	Gelay et al.	N/A	N/A
2015/0005600	12/2014	Blank et al.	N/A	N/A
2015/0006089	12/2014	Pagels	N/A	N/A
2015/0007075	12/2014	Choi et al.	N/A	N/A
2015/0011907	12/2014	Purdon et al.	N/A	N/A
2015/0012231	12/2014	Poeze et al.	N/A	N/A
2015/0018650	12/2014	Al-Ali et al.	N/A	N/A
2015/0025406	12/2014	Al-Ali	N/A	N/A
2015/0032029	12/2014	Al-Ali et al.	N/A	N/A
2015/0038859	12/2014	Dalvi et al.	N/A	N/A
2015/0045637	12/2014	Dalvi	N/A	N/A
2015/0051462	12/2014	Olsen	N/A	N/A
2015/0073241	12/2014	Lamego	N/A	N/A
2015/0080754	12/2014	Purdon et al.	N/A	N/A
2015/0087936	12/2014	Al-Ali et al.	N/A	N/A
2015/0094546	12/2014	Al-Ali	N/A	N/A
2015/0094618	12/2014	Russell et al.	N/A	N/A
2015/0097701	12/2014	Al-Ali et al.	N/A	N/A
2015/0099950	12/2014	Al-Ali et al.	N/A	N/A
2015/0099951	12/2014	Al-Ali et al.	N/A	N/A
2015/0099955	12/2014	Al-Ali et al.	N/A	N/A
2015/0101844	12/2014	Al-Ali et al.	N/A	N/A

2015/0106121	12/2014	Muhsin et al.	N/A	N/A
2015/0112151	12/2014	Muhsin et al.	N/A	N/A
2015/0116076	12/2014	Al-Ali et al.	N/A	N/A
2015/0126830	12/2014	Schurman et al.	N/A	N/A
2015/0133755	12/2014	Smith et al.	N/A	N/A
2015/0140863	12/2014	Al-Ali et al.	N/A	N/A
2015/0141781	12/2014	Weber et al.	N/A	N/A
2015/0165312	12/2014	Kiani	N/A	N/A
2015/0196237	12/2014	Lamego	N/A	N/A
2015/0196249	12/2014	Brown et al.	N/A	N/A
2015/0201874	12/2014	Diab	N/A	N/A
2015/0208966	12/2014	Al-Ali	N/A	N/A
2015/0216459	12/2014	Al-Ali et al.	N/A	N/A
2015/0230755	12/2014	Al-Ali et al.	N/A	N/A
2015/0238722	12/2014	Al-Ali	N/A	N/A
2015/0245773	12/2014	Lamego et al.	N/A	N/A
2015/0245794	12/2014	Al-Ali	N/A	N/A
2015/0257689	12/2014	Al-Ali et al.	N/A	N/A
2015/0264506	12/2014	Balabanis et al.	N/A	N/A
2015/0272514	12/2014	Kiani et al.	N/A	N/A
2015/0351697	12/2014	Weber et al.	N/A	N/A
2015/0358314	12/2014	Glik et al.	N/A	N/A
2015/0359429	12/2014	Al-Ali et al.	N/A	N/A
2015/0366472	12/2014	Kiani	N/A	N/A
2015/0366507	12/2014	Blank et al.	N/A	N/A
2015/0374298	12/2014	Al-Ali et al.	N/A	N/A
2015/0380875	12/2014	Coverston et al.	N/A	N/A
2016/0000362	12/2015	Diab et al.	N/A	N/A
2016/0007930	12/2015	Weber et al.	N/A	N/A
2016/0029932	12/2015	Al-Ali	N/A	N/A
2016/0029933	12/2015	Al-Ali et al.	N/A	N/A
2016/0045118	12/2015	Kiani	N/A	N/A
2016/0051205	12/2015	Al-Ali et al.	N/A	N/A
2016/0058338	12/2015	Schurman et al.	N/A	N/A
2016/0058347	12/2015	Reichgott et al.	N/A	N/A
2016/0066823	12/2015	Al-Ali et al.	N/A	N/A
2016/0066824	12/2015	Al-Ali et al.	N/A	N/A
2016/0066879	12/2015	Telfort et al.	N/A	N/A
2016/0072429	12/2015	Kiani et al.	N/A	N/A
2016/0073967	12/2015	Lamego et al.	N/A	N/A
2016/0081552	12/2015	Wojtczuk et al.	N/A	N/A
2016/0095543	12/2015	Telfort et al.	N/A	N/A
2016/0095548	12/2015	Al-Ali et al.	N/A	N/A
2016/0103598	12/2015	Al-Ali et al.	N/A	N/A
2016/0113527	12/2015	Al-Ali	N/A	N/A
2016/0143548	12/2015	Al-Ali	N/A	N/A
2016/0166182	12/2015	Al-Ali et al.	N/A	N/A
2016/0166183	12/2015	Poeze et al.	N/A	N/A
2016/0166188	12/2015	Bruinsma et al.	N/A	N/A
2016/0166210	12/2015	Al-Ali	N/A	N/A

2016/0192869	12/2015	Kiani et al.	N/A	N/A
2016/0196388	12/2015	Lamego	N/A	N/A
2016/0197436	12/2015	Barker et al.	N/A	N/A
2016/0213281	12/2015	Eckerbom et al.	N/A	N/A
2016/0216117	12/2015	Bandyopadhyay et al.	N/A	N/A
2016/0228043	12/2015	O'Neil et al.	N/A	N/A
2016/0233632	12/2015	Scruggs et al.	N/A	N/A
2016/0234944	12/2015	Triman et al.	N/A	N/A
2016/0246781	12/2015	Cabot	N/A	N/A
2016/0270717	12/2015	Luna et al.	N/A	N/A
2016/0270735	12/2015	Diab et al.	N/A	N/A
2016/0271445	12/2015	Kolloff	N/A	N/A
2016/0283665	12/2015	Sampath et al.	N/A	N/A
2016/0287786	12/2015	Kiani	N/A	N/A
2016/0296169	12/2015	McHale et al.	N/A	N/A
2016/0310052	12/2015	Al-Ali et al.	N/A	N/A
2016/0314260	12/2015	Kiani	N/A	N/A
2016/0324486	12/2015	Al-Ali et al.	N/A	N/A
2016/0324488	12/2015	Olsen	N/A	N/A
2016/0327984	12/2015	Al-Ali et al.	N/A	N/A
2016/0331332	12/2015	Al-Ali	N/A	N/A
2016/0367173	12/2015	Dalvi et al.	N/A	N/A
2017/0000394	12/2016	Al-Ali et al.	N/A	N/A
2017/0007134	12/2016	Al-Ali et al.	N/A	N/A
2017/0014083	12/2016	Diab et al.	N/A	N/A
2017/0014084	12/2016	Al-Ali et al.	N/A	N/A
2017/0024748	12/2016	Haider	N/A	N/A
2017/0042488	12/2016	Muhsin	N/A	N/A
2017/0055851	12/2016	Al-Ali et al.	N/A	N/A
2017/0055882	12/2016	Al-Ali et al.	N/A	N/A
2017/0055887	12/2016	Al-Ali	N/A	N/A
2017/0055896	12/2016	Al-Ali et al.	N/A	N/A
2017/0079594	12/2016	Telfort et al.	N/A	N/A
2017/0086723	12/2016	Al-Ali et al.	N/A	N/A
2017/0143281	12/2016	Olsen	N/A	N/A
2017/0147774	12/2016	Kiani	N/A	N/A
2017/0156620	12/2016	Al-Ali et al.	N/A	N/A
2017/0173632	12/2016	Al-Ali	N/A	N/A
2017/0187146	12/2016	Kiani et al.	N/A	N/A
2017/0188919	12/2016	Al-Ali et al.	N/A	N/A
2017/0196464	12/2016	Jansen et al.	N/A	N/A
2017/0196470	12/2016	Lamego et al.	N/A	N/A
2017/0224262	12/2016	Al-Ali	N/A	N/A
2017/0228516	12/2016	Sampath et al.	N/A	N/A
2017/0245790	12/2016	Al-Ali et al.	N/A	N/A
2017/0251974	12/2016	Shreim et al.	N/A	N/A
2017/0251975	12/2016	Shreim et al.	N/A	N/A
2017/0258403	12/2016	Abdul-Hafiz et al.	N/A	N/A
2017/0311851	12/2016	Schurman et al.	N/A	N/A

2017/0311891	12/2016	Kiani et al.	N/A	N/A
2017/0325728	12/2016	Al-Ali et al.	N/A	N/A
2017/0332976	12/2016	Al-Ali et al.	N/A	N/A
2017/0340293	12/2016	Al-Ali et al.	N/A	N/A
2017/0360310	12/2016	Kiani et al.	N/A	N/A
2017/0367632	12/2016	Al-Ali et al.	N/A	N/A
2018/0008146	12/2017	Al-Ali et al.	N/A	N/A
2018/0013562	12/2017	Haider et al.	N/A	N/A
2018/0014752	12/2017	Al-Ali et al.	N/A	N/A
2018/0028124	12/2017	Al-Ali et al.	N/A	N/A
2018/0055385	12/2017	Al-Ali	N/A	N/A
2018/0055390	12/2017	Kiani et al.	N/A	N/A
2018/0055430	12/2017	Diab et al.	N/A	N/A
2018/0064381	12/2017	Shakespeare et al.	N/A	N/A
2018/0069776	12/2017	Lamego et al.	N/A	N/A
2018/0070867	12/2017	Smith et al.	N/A	N/A
2018/0082767	12/2017	Al-Ali et al.	N/A	N/A
2018/0085068	12/2017	Telfort	N/A	N/A
2018/0087937	12/2017	Al-Ali et al.	N/A	N/A
2018/0103874	12/2017	Lee et al.	N/A	N/A
2018/0103905	12/2017	Kiani	N/A	N/A
2018/0110478	12/2017	Al-Ali	N/A	N/A
2018/0116575	12/2017	Perea et al.	N/A	N/A
2018/0125368	12/2017	Lamego et al.	N/A	N/A
2018/0125430	12/2017	Al-Ali et al.	N/A	N/A
2018/0125445	12/2017	Telfort et al.	N/A	N/A
2018/0130325	12/2017	Kiani et al.	N/A	N/A
2018/0132769	12/2017	Weber et al.	N/A	N/A
2018/0132770	12/2017	Lamego	N/A	N/A
2018/0146901	12/2017	Al-Ali et al.	N/A	N/A
2018/0146902	12/2017	Kiani et al.	N/A	N/A
2018/0153442	12/2017	Eckerbom et al.	N/A	N/A
2018/0153446	12/2017	Kiani	N/A	N/A
2018/0153447	12/2017	Al-Ali et al.	N/A	N/A
2018/0153448	12/2017	Weber et al.	N/A	N/A
2018/0161499	12/2017	Al-Ali et al.	N/A	N/A
2018/0168491	12/2017	Al-Ali et al.	N/A	N/A
2018/0174679	12/2017	Sampath et al.	N/A	N/A
2018/0174680	12/2017	Sampath et al.	N/A	N/A
2018/0182484	12/2017	Sampath et al.	N/A	N/A
2018/0184917	12/2017	Kiani	N/A	N/A
2018/0192924	12/2017	Al-Ali	N/A	N/A
2018/0192953	12/2017	Shreim et al.	N/A	N/A
2018/0192955	12/2017	Al-Ali et al.	N/A	N/A
2018/0199871	12/2017	Pauley et al.	N/A	N/A
2018/0206795	12/2017	Al-Ali	N/A	N/A
2018/0206815	12/2017	Telfort	N/A	N/A
2018/0213583	12/2017	Al-Ali	N/A	N/A
2018/0214031	12/2017	Kiani et al.	N/A	N/A
2018/0214090	12/2017	Al-Ali et al.	N/A	N/A

2018/0216370	12/2017	Ishiguro et al.	N/A	N/A
2018/0218792	12/2017	Muhsin et al.	N/A	N/A
2018/0225960	12/2017	Al-Ali et al.	N/A	N/A
2018/0238718	12/2017	Dalvi	N/A	N/A
2018/0242853	12/2017	Al-Ali	N/A	N/A
2018/0242921	12/2017	Muhsin et al.	N/A	N/A
2018/0242923	12/2017	Al-Ali et al.	N/A	N/A
2018/0242924	12/2017	Barker et al.	N/A	N/A
2018/0242926	12/2017	Muhsin et al.	N/A	N/A
2018/0247353	12/2017	Al-Ali et al.	N/A	N/A
2018/0247712	12/2017	Muhsin et al.	N/A	N/A
2018/0249933	12/2017	Schurman et al.	N/A	N/A
2018/0253947	12/2017	Muhsin et al.	N/A	N/A
2018/0256087	12/2017	Al-Ali et al.	N/A	N/A
2018/0256113	12/2017	Weber et al.	N/A	N/A
2018/0285094	12/2017	Housel et al.	N/A	N/A
2018/0289325	12/2017	Poeze et al.	N/A	N/A
2018/0289337	12/2017	Al-Ali et al.	N/A	N/A
2018/0296161	12/2017	Shreim et al.	N/A	N/A
2018/0300919	12/2017	Muhsin et al.	N/A	N/A
2018/0310822	12/2017	Indorf et al.	N/A	N/A
2018/0310823	12/2017	Al-Ali et al.	N/A	N/A
2018/0317826	12/2017	Muhsin	N/A	N/A
2018/0317841	12/2017	Novak, Jr.	N/A	N/A
2018/0333055	12/2017	Lamego et al.	N/A	N/A
2018/0333087	12/2017	Al-Ali	N/A	N/A
2019/0000317	12/2018	Muhsin et al.	N/A	N/A
2019/0000362	12/2018	Kiani et al.	N/A	N/A
2019/0015023	12/2018	Monfre	N/A	N/A
2019/0021638	12/2018	Al-Ali et al.	N/A	N/A
2019/0029574	12/2018	Schurman et al.	N/A	N/A
2019/0029578	12/2018	Al-Ali et al.	N/A	N/A
2019/0038143	12/2018	Al-Ali	N/A	N/A
2019/0053286	12/2018	Cho et al.	N/A	N/A
2019/0058280	12/2018	Al-Ali et al.	N/A	N/A
2019/0058281	12/2018	Al-Ali et al.	N/A	N/A
2019/0069813	12/2018	Al-Ali	N/A	N/A
2019/0069814	12/2018	Al-Ali	N/A	N/A
2019/0076028	12/2018	Al-Ali et al.	N/A	N/A
2019/0082979	12/2018	Al-Ali et al.	N/A	N/A
2019/0090748	12/2018	Al-Ali	N/A	N/A
2019/0090760	12/2018	Kinast et al.	N/A	N/A
2019/0090764	12/2018	Ai-Ai	N/A	N/A
2019/0104973	12/2018	Poeze et al.	N/A	N/A
2019/0110719	12/2018	Poeze et al.	N/A	N/A
2019/0117070	12/2018	Muhsin et al.	N/A	N/A
2019/0117139	12/2018	Al-Ali et al.	N/A	N/A
2019/0117140	12/2018	Al-Ali et al.	N/A	N/A
2019/0117141	12/2018	Al-Ali	N/A	N/A
2019/0117930	12/2018	Al-Ali	N/A	N/A

2019/0122763	12/2018	Sampath et al.	N/A	N/A
2019/0133525	12/2018	Al-Ali et al.	N/A	N/A
2019/0142283	12/2018	Lamego et al.	N/A	N/A
2019/0142344	12/2018	Telfort et al.	N/A	N/A
2019/0150856	12/2018	Kiani et al.	N/A	N/A
2019/0167161	12/2018	Al-Ali et al.	N/A	N/A
2019/0175019	12/2018	Al-Ali et al.	N/A	N/A
2019/0192076	12/2018	McHale et al.	N/A	N/A
2019/0200941	12/2018	Chandran et al.	N/A	N/A
2019/0201623	12/2018	Kiani	N/A	N/A
2019/0209025	12/2018	Al-Ali	N/A	N/A
2019/0214778	12/2018	Scruggs et al.	N/A	N/A
2019/0216319	12/2018	Poeze et al.	N/A	N/A
2019/0216379	12/2018	Al-Ali et al.	N/A	N/A
2019/0221966	12/2018	Kiani et al.	N/A	N/A
2019/0223804	12/2018	Blank et al.	N/A	N/A
2019/0231199	12/2018	Al-Ali et al.	N/A	N/A
2019/0231241	12/2018	Al-Ali et al.	N/A	N/A
2019/0231270	12/2018	Abdul-Hafiz et al.	N/A	N/A
2019/0239787	12/2018	Pauley et al.	N/A	N/A
2019/0239824	12/2018	Muhsin et al.	N/A	N/A
2019/0254578	12/2018	Lamego	N/A	N/A
2019/0261857	12/2018	Al-Ali	N/A	N/A
2019/0269370	12/2018	Al-Ali et al.	N/A	N/A
2019/0274606	12/2018	Kiani et al.	N/A	N/A
2019/0274627	12/2018	Al-Ali et al.	N/A	N/A
2019/0274635	12/2018	Al-Ali et al.	N/A	N/A
2019/0290136	12/2018	Dalvi et al.	N/A	N/A
2019/0298270	12/2018	Al-Ali et al.	N/A	N/A
2019/0304601	12/2018	Sampath et al.	N/A	N/A
2019/0304605	12/2018	Al-Ali	N/A	N/A
2019/0307377	12/2018	Perea et al.	N/A	N/A
2019/0320906	12/2018	Olsen	N/A	N/A
2019/0320959	12/2018	Al-Ali	N/A	N/A
2019/0320988	12/2018	Ahmed et al.	N/A	N/A
2019/0325722	12/2018	Kiani	N/A	N/A
2019/0374139	12/2018	Kiani et al.	N/A	N/A
2019/0374173	12/2018	Kiani et al.	N/A	N/A
2019/0374713	12/2018	Kiani et al.	N/A	N/A
2020/0060629	12/2019	Muhsin et al.	N/A	N/A
2020/0060869	12/2019	Telfort et al.	N/A	N/A
2020/0111552	12/2019	Ahmed	N/A	N/A
2020/0113435	12/2019	Muhsin	N/A	N/A
2020/0113488	12/2019	Al-Ali et al.	N/A	N/A
2020/0113496	12/2019	Scruggs et al.	N/A	N/A
2020/0113497	12/2019	Triman et al.	N/A	N/A
2020/0113520	12/2019	Abdul-Hafiz et al.	N/A	N/A
2020/0138288	12/2019	Al-Ali et al.	N/A	N/A
2020/0138368	12/2019	Kiani et al.	N/A	N/A
2020/0163597	12/2019	Dalvi et al.	N/A	N/A

2020/0196877	12/2019	Vo et al.	N/A	N/A
2020/0253474	12/2019	Muhsin et al.	N/A	N/A
2020/0253544	12/2019	Belur Nagaraj et al.	N/A	N/A
2020/0275841	12/2019	Telfort et al.	N/A	N/A
2020/0288983	12/2019	Telfort et al.	N/A	N/A
2020/0321793	12/2019	Al-Ali et al.	N/A	N/A
2020/0329983	12/2019	Al-Ali et al.	N/A	N/A
2020/0329984	12/2019	Al-Ali et al.	N/A	N/A
2020/0329993	12/2019	Al-Ali et al.	N/A	N/A
2020/0330037	12/2019	Al-Ali et al.	N/A	N/A
2021/0022628	12/2020	Telfort et al.	N/A	N/A
2021/0104173	12/2020	Pauley et al.	N/A	N/A
2021/0113121	12/2020	Diab et al.	N/A	N/A
2021/0117525	12/2020	Kiani et al.	N/A	N/A
2021/0118581	12/2020	Kiani et al.	N/A	N/A
2021/0121582	12/2020	Krishnamani et al.	N/A	N/A
2021/0161465	12/2020	Barker et al.	N/A	N/A
2021/0236729	12/2020	Kiani et al.	N/A	N/A
2021/0256267	12/2020	Ranasinghe et al.	N/A	N/A
2021/0256835	12/2020	Ranasinghe et al.	N/A	N/A
2021/0275101	12/2020	Vo et al.	N/A	N/A
2021/0290060	12/2020	Ahmed	N/A	N/A
2021/0290072	12/2020	Forrest	N/A	N/A
2021/0290080	12/2020	Ahmed	N/A	N/A
2021/0290120	12/2020	Al-Ali	N/A	N/A
2021/0290177	12/2020	Novak, Jr.	N/A	N/A
2021/0290184	12/2020	Ahmed	N/A	N/A
2021/0296008	12/2020	Novak, Jr.	N/A	N/A
2021/0330228	12/2020	Olsen et al.	N/A	N/A
2021/0386382	12/2020	Olsen et al.	N/A	N/A
2021/0402110	12/2020	Pauley et al.	N/A	N/A
2022/0026355	12/2021	Normand et al.	N/A	N/A
2022/0039707	12/2021	Sharma et al.	N/A	N/A
2022/0053892	12/2021	Al-Ali et al.	N/A	N/A
2022/0071562	12/2021	Kiani	N/A	N/A
2022/0096603	12/2021	Kiani et al.	N/A	N/A
2022/0151521	12/2021	Krishnamani et al.	N/A	N/A
2022/0218244	12/2021	Kiani et al.	N/A	N/A
2022/0287574	12/2021	Telfort et al.	N/A	N/A
2022/0296161	12/2021	Al-Ali et al.	N/A	N/A
2022/0361819	12/2021	Al-Ali et al.	N/A	N/A
2022/0379059	12/2021	Yu et al.	N/A	N/A
2022/0392610	12/2021	Kiani et al.	N/A	N/A
2023/0028745	12/2022	Al-Ali	N/A	N/A
2023/0038389	12/2022	Vo	N/A	N/A
2023/0045647	12/2022	Vo	N/A	N/A
2023/0058052	12/2022	Al-Ali	N/A	N/A
2023/0058342	12/2022	Kiani	N/A	N/A
2023/0069789	12/2022	Koo et al.	N/A	N/A
2023/0087671	12/2022	Telfort et al.	N/A	N/A

2023/0110152	12/2022	Forrest et al.	N/A	N/A
2023/0111198	12/2022	Yu et al.	N/A	N/A
2023/0115397	12/2022	Vo et al.	N/A	N/A
2023/0116371	12/2022	Mills et al.	N/A	N/A
2023/0135297	12/2022	Kiani et al.	N/A	N/A
2023/0138098	12/2022	Telfort et al.	N/A	N/A
2023/0145155	12/2022	Krishnamani et al.	N/A	N/A
2023/0147750	12/2022	Barker et al.	N/A	N/A
2023/0210417	12/2022	Al-Ali et al.	N/A	N/A
2023/0222805	12/2022	Muhsin et al.	N/A	N/A
2023/0222887	12/2022	Muhsin et al.	N/A	N/A
2023/0226331	12/2022	Kiani et al.	N/A	N/A
2023/0284916	12/2022	Telfort	N/A	N/A
2023/0284943	12/2022	Scruggs et al.	N/A	N/A
2023/0301562	12/2022	Scruggs et al.	N/A	N/A
2023/0346993	12/2022	Kiani et al.	N/A	N/A
2023/0368221	12/2022	Haider	N/A	N/A
2023/0371893	12/2022	Al-Ali et al.	N/A	N/A
2023/0389837	12/2022	Krishnamani et al.	N/A	N/A
2024/0016418	12/2023	Devadoss et al.	N/A	N/A
2024/0016419	12/2023	Devadoss et al.	N/A	N/A
2024/0047061	12/2023	Al-Ali et al.	N/A	N/A
2024/0049310	12/2023	Al-Ali et al.	N/A	N/A
2024/0049986	12/2023	Al-Ali et al.	N/A	N/A
2024/0081656	12/2023	DeJong et al.	N/A	N/A
2024/0122486	12/2023	Kiani	N/A	N/A
2024/0180456	12/2023	Al-Ali	N/A	N/A
2024/0188872	12/2023	Al-Ali et al.	N/A	N/A
2024/0245855	12/2023	Vo et al.	N/A	N/A
2024/0252046	12/2023	Jansen et al.	N/A	N/A
2024/0260894	12/2023	Olsen	N/A	N/A
2024/0267698	12/2023	Telfort et al.	N/A	N/A
2024/0277233	12/2023	Al-Ali	N/A	N/A
2024/0277280	12/2023	Al-Ali	N/A	N/A
2024/0298920	12/2023	Fernkbist et al.	N/A	N/A
2024/0306985	12/2023	Vo et al.	N/A	N/A
2024/0324953	12/2023	Telfort	N/A	N/A
2024/0380246	12/2023	Moran	N/A	N/A
2024/0380247	12/2023	Moran	N/A	N/A
2024/0404549	12/2023	Campbell et al.	N/A	N/A
2025/0000458	12/2024	Abdul-Hafiz et al.	N/A	N/A
2025/0037836	12/2024	Kiani	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
0 735 499	12/1995	EP	N/A
1 110 503	12/2000	EP	N/A
2 144 181	12/2009	EP	N/A
2 335 569	12/2010	EP	N/A

02-050694	12/1989	JP	N/A
08-275926	12/1995	JP	N/A
09-187428	12/1996	JP	N/A
10-336064	12/1997	JP	N/A
2000-312668	12/1999	JP	N/A
2002-513602	12/2001	JP	N/A
2002-165764	12/2001	JP	N/A
2002-172096	12/2001	JP	N/A
2002-233512	12/2001	JP	N/A
2002-535026	12/2001	JP	N/A
2002-542493	12/2001	JP	N/A
2004-513732	12/2003	JP	N/A
2004-321603	12/2003	JP	N/A
2005-038417	12/2004	JP	N/A
2005-065721	12/2004	JP	N/A
2008-067931	12/2004	JP	N/A
2005-199064	12/2004	JP	N/A
2005-218036	12/2004	JP	N/A
2005-523755	12/2004	JP	N/A
2005-295375	12/2004	JP	N/A
2005-532849	12/2004	JP	N/A
2007-021213	12/2006	JP	N/A
2007-095365	12/2006	JP	N/A
2007-174051	12/2006	JP	N/A
2008-080136	12/2007	JP	N/A
2008-519635	12/2007	JP	N/A
2008-541045	12/2007	JP	N/A
2009-017959	12/2008	JP	N/A
2009-207836	12/2008	JP	N/A
2009-536868	12/2008	JP	N/A
2010-500051	12/2009	JP	N/A
2010-503134	12/2009	JP	N/A
2010-093543	12/2009	JP	N/A
2010-524510	12/2009	JP	N/A
2011-519607	12/2010	JP	N/A
2011-519684	12/2010	JP	N/A
2011-152261	12/2010	JP	N/A
2012-519547	12/2011	JP	N/A
2012-532363	12/2011	JP	N/A
2013-507228	12/2012	JP	N/A
2008-0091089	12/2007	KR	N/A
WO 98/029790	12/1997	WO	N/A
WO 99/013766	12/1998	WO	N/A
WO 99/056613	12/1998	WO	N/A
WO 00/063713	12/1999	WO	N/A
WO 01/043821	12/2000	WO	N/A
WO 2004/056266	12/2003	WO	N/A
WO 2004/059551	12/2003	WO	N/A
WO 2006/051461	12/2005	WO	N/A
WO 2007/143626	12/2006	WO	N/A

WO 2009/134724	12/2008	WO	N/A
WO 2010/054409	12/2009	WO	N/A
WO 2011/001302	12/2010	WO	N/A
WO 2011/002904	12/2010	WO	N/A
WO 2011/021948	12/2010	WO	N/A
WO 2011/025549	12/2010	WO	N/A
WO 2011/041017	12/2010	WO	N/A
WO 2013/056160	12/2012	WO	N/A
WO 2013/119982	12/2012	WO	N/A
WO 2015/054665	12/2014	WO	N/A

OTHER PUBLICATIONS

US 8,845,543 B2, 09/2014, Diab et al. (withdrawn) cited by applicant

US 2022/0192529 A1, 06/2022, Al-Ali et al. (withdrawn) cited by applicant

US 2024/0016391 A1, 01/2024, Lapotko et al. (withdrawn) cited by applicant

“The Identification of Peaks in Physiological Signals”—by Bryan S. Todd and David C. Andrews; 14 pages, dated Feb. 17, 1998 (Year: 1998). cited by examiner

Wikipedia entry for “Envelope (waves)” —6 pages, retrieved on May 22, 2024 (Year: 2024). cited by examiner

U.S. Appl. No. 16/411,689, Physiological Measurement Device, filed May 14, 2019. cited by applicant

U.S. Appl. No. 16/670,051, System for Displaying Medical Monitoring Data, filed Oct. 31, 2019. cited by applicant

Capuano et al., “Remote Telemetry—New Twists for Old Technology”, Nursing Management, Jul. 1995, vol. 26, No. 7, pp. 26-32. cited by applicant

Elmer-Dewitt, Philip, “Apple's iWatch: The killer apps may be in hospitals, not health clubs”, Fortune.com, Feb. 3, 2014, <http://fortune.com/2014/02/03/apples-iwatch-the-killer-apps-may-be-in-hospitals-not-health-clubs/>, 4 pages. cited by applicant

Grundy et al., “Telemedicine in Critical Care: An Experiment in Health Care Delivery”, JACEP, Oct. 1977, vol. 6, No. 10, pp. 439-444. cited by applicant

Grundy et al., “Telemedicine in Critical Care: Problems in Design, Implementation and Assessment”, Jul. 1982, vol. 10, No. 7, pp. 471-475. cited by applicant

Hudson, T.L., “Maximizing a Transport Platform Through Computer Technology”, Computers, Informatics, Nursing: Mar.-Apr. 2003, vol. 21, No. 2, pp. 72-79. cited by applicant

Liu, Chun-Hung, “A Source Coding and Modulation Method for Power Saving and Interference Reduction in DS-CDMA Sensor Network Systems”, Proceedings of the American Control Conference Anchorage, AK, May 8-10, 2002, pp. 3003-3008. cited by applicant

Rysavy, Peter, “Making the Call with Two-Way Paging”, Network Computing, Published Jan. 15, 1997, www.rysavy.com/Articles/twoway.htm, pp. 5. cited by applicant

Wachter et al., “The Employment of an Iterative Design Process to Develop a Pulmonary Graphical Display”, Journal of the American Medical Informatics Association, vol. 10, No. 4, Jul./Aug. 2003, pp. 363-372. cited by applicant

International Search Report & Written Opinion in PCT Application No. PCT/US2013/025384, dated Aug. 6, 2013. cited by applicant

International Preliminary Report on Patentability & Written Opinion in PCT Application No. PCT/US2013/025384, dated Aug. 21, 2014. cited by applicant

International Search Report & Written Opinion in PCT Application No. PCT/US2012/060109, dated Jun. 5, 2013. cited by applicant

International Preliminary Report on Patentability in PCT Application No. PCT/US2012/060109, dated Apr. 24, 2014. cited by applicant

International Search Report & Written Opinion in PCT Application No. PCT/US2014/060177, dated Dec. 19, 2014. cited by applicant
International Preliminary Report on Patentability & Written Opinion in PCT Application No. PCT/US2014/060177, dated Apr. 21, 2016. cited by applicant
U.S. Appl. No. 17/126,567, Modular Patient Monitor, filed Dec. 18, 2020. cited by applicant
U.S. Appl. No. 17/126,567, Modular Patient Monitor, Dec. 18, 2020. cited by applicant
U.S. Appl. No. 17/305,155, Wireless Patient Monitoring Device, filed Jun. 30, 2021. cited by applicant
U.S. Appl. No. 17/451,554, Medical Monitoring Hub, filed Oct. 20, 2021. cited by applicant
U.S. Appl. No. 17/138,595, Wireless Patient Monitoring System, filed Dec. 30, 2020. cited by applicant
U.S. Appl. No. 18/471,992, Wireless Patient Monitoring Device, filed Sep. 21, 2023. cited by applicant
U.S. Appl. No. 17/646,443, System for Displaying Medical Monitoring Data, filed Dec. 29, 2021. cited by applicant
U.S. Appl. No. 14/815,232, Physiological Measurement Communications Adapter, filed Jul. 31, 2015. cited by applicant
U.S. Appl. No. 17/952,632, Physiological Measurement Device, filed Sep. 26, 2022. cited by applicant
U.S. Appl. No. 17/141,732, Modular Patient Monitor, filed Jan. 5, 2021. cited by applicant
U.S. Appl. No. 12/840,209, Wireless Patient Monitoring System, filed Jul. 20, 2010. cited by applicant
U.S. Appl. No. 13/010,653, Wireless Patient Monitoring System, filed Jan. 20, 2011. cited by applicant
U.S. Appl. No. 18/606,807, Wireless Patient Monitoring System, filed Mar. 14, 2024. cited by applicant
U.S. Appl. No. 12/973,392, Modular Patient Monitor, filed Dec. 20, 2010. cited by applicant
U.S. Appl. No. 18/540,010, Modular Patient Monitor, filed Dec. 14, 2023. cited by applicant
U.S. Appl. No. 16/182,457, Wireless Patient Monitoring Device, filed Nov. 6, 2018. cited by applicant
U.S. Appl. No. 18/819,373, Wireless Patient Monitoring Device, filed Aug. 29, 2024. cited by applicant
U.S. Appl. No. 18/465,542, Medical Monitoring Hub, filed Sep. 12, 2023. cited by applicant

Primary Examiner: Misiura; Brian T

Attorney, Agent or Firm: Knobbe, Martens, Olson & Bear, LLP

Background/Summary

RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 16/670,051, filed Oct. 31, 2019, titled "System for Displaying Medical Monitoring Data," which is a continuation of U.S. application Ser. No. 15/919,792, filed Mar. 13, 2018, titled "System for Displaying Medical Monitoring Data," which application is a continuation of U.S. application Ser. No. 14/512,237, filed Oct. 10, 2014, titled "System for Displaying Medical Monitoring Data," which application is a non-provisional of U.S. Provisional Application No. 61/889,972, filed Oct. 11, 2013, titled "System for Displaying Medical Monitoring Data," and is also a continuation-in-part of U.S. application Ser. No. 13/651,167, filed Oct. 12, 2012, titled "Medical Monitoring Hub,"

which is a non-provisional of each of the following U.S. Provisional Patent Applications: (2) TABLE-US-00001 Ser. No. Date Title 61/547,017, Oct. 13, 2011, Visual Correlation of Physiological Information, 61/547,577, Oct. 14, 2011, Visual Correlation of Physiological Information, 61/597,120, Feb. 9, 2012, Visual Correlation of Physiological Information, 61/703,773, Sep. 20, 2012, Medical Monitoring Hub (3) All of the above applications are incorporated by reference herein in their entirety.

FIELD OF THE DISCLOSURE

(1) The present disclosure relates generally to patient monitoring devices and specifically to a patient monitor and medical data communication hub.

BACKGROUND OF THE DISCLOSURE

(2) Today's patient monitoring environments are crowded with sophisticated and often electronic medical devices servicing a wide variety of monitoring and treatment endeavors for a given patient. Generally, many if not all of the devices are from differing manufactures, and many may be portable devices. The devices may not communicate with one another and each may include its own control, display, alarms, configurations and the like. Complicating matters, caregivers often desire to associate all types of measurement and use data from these devices to a specific patient. Thus, patient information entry often occurs at each device. Sometimes, the disparity in devices leads to a need to simply print and store paper from each device in a patient's file for caregiver review.

(3) The result of such device disparity is often a caregiver environment scattered with multiple displays and alarms leading to a potentially chaotic experience. Such chaos can be detrimental to the patient in many situations including surgical environments where caregiver distraction is unwanted, and including recovery or monitoring environments where patient distraction or disturbance may be unwanted.

(4) Various manufacturers produce multi-monitor devices or devices that modularly expand to increase the variety of monitoring or treatment endeavors a particular system can accomplish. However, as medical device technology expands, such multi-monitor devices begin to be obsolete the moment they are installed.

SUMMARY

(5) This disclosure describes embodiments of a medical monitoring hub as the center of monitoring for a monitored patient. The hub can include configurable medical ports and serial ports for communicating with other medical devices in the patient's proximity. Moreover, the hub can communicate with a portable patient monitor. The monitor, when docked with the hub, may provide display graphics different from when undocked. The display graphics can include anatomical information. The hub can assemble the often vast amount of electronic medical data, associate it with the monitored patient, and in some embodiments, communicate the data to the patient's medical records.

(6) Some aspects of the disclosure describe a first medical device having digital logic circuitry receives a physiological signal associated with a patient from a physiological sensor, obtains a first physiological parameter value based on the physiological signal, and outputs the first physiological parameter value for display. The first medical device can also receive a second physiological parameter value from a second medical device other than the first medical device, where the second physiological parameter value is formatted according to a protocol not used by the first medical device, such that the first medical device is not able to process the second physiological parameter value to produce a displayable output value. The first medical device can pass the physiological parameter data from the first medical device to a separate translation module, receive translated parameter data from the translation module at the first medical device, where the translated parameter data is able to be processed for display by the first medical device, and output a second value from the translated parameter data for display. The first medical device may be, for example,

a monitoring hub, a portable physiological monitor, or a multi-patient monitoring system, and the second medical device may be an infusion pump, ventilator, or the like.

(7) For purposes of summarizing the disclosure, certain aspects, advantages and novel features are discussed herein. It is to be understood that not necessarily all such aspects, advantages or features will be embodied in any particular embodiment of the invention and an artisan would recognize from the disclosure herein a myriad of combinations of such aspects, advantages or features.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The following drawings and the associated descriptions are provided to illustrate embodiments of the present disclosure and do not limit the scope of the claims.

(2) FIGS. 1A-1C illustrate perspective views of an exemplary medical monitoring hub according to an embodiment of the disclosure. For example, FIG. 1A illustrates the hub with an exemplary docked portable patient monitor, FIG. 1B illustrates the hub with a set of medical ports and a noninvasive blood pressure input, and FIG. 1C illustrates the hub with various exemplary temperature sensors attached thereto, all according to various embodiments of the disclosure.

(3) FIG. 2 illustrates a simplified block diagram of an exemplary monitoring environment including the hub of FIG. 1, according to an embodiment of the disclosure.

(4) FIG. 3 illustrates a simplified exemplary hardware block diagram of the hub of FIG. 1, according to an embodiment of the disclosure.

(5) FIG. 4 illustrates a perspective view of an exemplary removable docking station of the hub of FIG. 1, according to an embodiment of the disclosure.

(6) FIG. 5 illustrates a perspective view of exemplary portable patient monitors undocked from the hub of FIG. 1, according to an embodiment of the disclosure. Moreover, FIG. 5 illustrates an exemplary alternative docking station.

(7) FIG. 6 illustrates a simplified block diagram of traditional patient device electrical isolation principles.

(8) FIG. 7A illustrates a simplified block diagram of an exemplary optional patient device isolation system according to an embodiment of the disclosure, while FIG. 7B adds exemplary optional non-isolation power levels for the system of FIG. 7A, also according to an embodiment of the disclosure.

(9) FIG. 8 illustrates a simplified exemplary universal medical connector configuration process, according to an embodiment of the disclosure.

(10) FIGS. 9A-9B, 10, 11A-11F, 11G1-11G2, and 11H-11K illustrate simplified block diagrams of exemplary universal medical connectors having a size and shape smaller in cross section than traditional isolation requirements.

(11) FIG. 10 illustrates a perspective view of a side of the hub of FIG. 1, showing exemplary instrument-side channel inputs for exemplary universal medical connectors, according to an embodiment of the disclosure.

(12) FIGS. 11A-11F, 11G1-11G2, and 11H-11K illustrate various views of exemplary male and mating female universal medical connectors, according to embodiments of the disclosure.

(13) FIG. 12 illustrates a simplified block diagram of a channel system for the hub of FIG. 1, according to an embodiment of the disclosure.

(14) FIG. 13 illustrates an exemplary logical channel configuration, according to an embodiment of the disclosure.

(15) FIG. 14 illustrates a simplified exemplary process for constructing a cable and configuring a channel according to an embodiment of the disclosure.

(16) FIG. 15 illustrates a perspective view of the hub of FIG. 1, including an exemplary attached

board-in-cable to form an input channel, according to an embodiment of the disclosure.

(17) FIG. 16 illustrates a perspective view of a back side of the hub of FIG. 1, showing an exemplary instrument-side serial data inputs, according to an embodiment of the disclosure.

(18) FIG. 17A illustrates an exemplary monitoring environment with communication through the serial data connections of FIG. 16, according to embodiments of the disclosure.

(19) FIG. 17B illustrates an exemplary connectivity display of the hub of FIG. 1, according to embodiments of the disclosure.

(20) FIG. 18 illustrates a simplified exemplary patient data flow process, according to an embodiment of the disclosure.

(21) FIGS. 19A-19J illustrate exemplary displays of anatomical graphics for the portable patient monitor of FIG. 1 docked with the hub of FIG. 1, according to embodiments of the disclosure.

(22) FIGS. 20A-20C illustrate exemplary displays of measurement data showing data separation and data overlap on a display of the hub of FIG. 1, respectively, according to embodiments of the disclosure.

(23) FIGS. 21A and 21B illustrate exemplary displays of measurement data showing data separation and data overlap on a display of the portable patient monitor of FIG. 1, respectively, according to embodiments of the disclosure.

(24) FIGS. 22A and 22B illustrate exemplary analog display indicia according to an embodiment of the disclosure.

(25) FIGS. 23A-23F illustrate exemplary displays of measurement data showing, for example, data presentation in FIGS. 23A-23D when a depth of consciousness monitor is connected to a channel port of the hub of FIG. 1, data presentation in FIG. 23E when temperature and blood pressure sensors communicate with the hub of FIG. 1 and data presentation in FIG. 23F when an acoustic sensor is also communicating with the hub of FIG. 1, according to embodiments of the disclosure.

(26) FIG. 24 illustrates another embodiment of a monitoring environment including the hub of FIG. 1.

(27) FIG. 25 illustrates an embodiment of a translation message handling process.

(28) FIGS. 26-39 illustrate additional example hub displays, including displays of measurement data.

(29) FIG. 40A illustrates an example first medical device and an example second medical device that communicate with one another via a translation module.

(30) FIG. 40B illustrates an example first medical device and an example second medical device that communicate with one another via a translation module and a communication bus.

(31) FIG. 41A illustrates an example input message received by the translation module.

(32) FIG. 41B illustrates an example message header segment of an input message that has been parsed into fields.

(33) FIG. 41C illustrates an example encoded version of the parsed message header segment of FIG. 41B.

(34) FIG. 41D illustrates an example output message of the translation module based on the input message of FIG. 41A.

(35) FIG. 42 illustrates an example translation process for generating an output message based on an input message and a comparison with translation rules associated with the translation module.

(36) FIG. 43A illustrates an example translation process in which the translation module facilitates communication of an HL7 message from a Hospital Information System ("HIS") having a first HL7 format to an intended recipient medical device having a second HL7 format.

(37) FIG. 43B illustrates an example translation process in which the translation module facilitates communication of an HL7 message from a medical device having a first HL7 format to a HIS having a second HL7 format.

(38) FIG. 44 illustrates an example screenshot from a messaging implementation tool for manually configuring translation rules to be used by the translation module.

(39) FIGS. 45A and 45B illustrate example automatic rule configuration processes that can be performed by the translation module.

(40) FIGS. 45C and 45D illustrate example automatic rule configuration processes that can be performed by the translation module for messages utilizing the HL7 protocol.

(41) FIGS. 46-71 illustrate additional example hub displays, including displays of measurement data.

(42) While the foregoing “Brief Description of the Drawings” references generally various embodiments of the disclosure, an artisan will recognize from the disclosure herein that such embodiments are not mutually exclusive. Rather, the artisan would recognize a myriad of combinations of some or all of such embodiments.

DETAILED DESCRIPTION

I. Introduction

(43) Based on at least the foregoing, a solution is needed that coordinates the various medical devices treating or monitoring a patient. Embodiments of such a solution should provide patient identification seamlessly across the device space and embodiments of such a solution should expand for future technologies without necessarily requiring repeated software upgrades. In addition, embodiments of such a solution may include patient electrical isolation where desired.

(44) Therefore, the present disclosure relates to a patient monitoring hub that is the center of patient monitoring and treatment activities for a given patient. Embodiments of the patient monitoring hub interface with legacy devices without necessitating legacy reprogramming, provide flexibility for interfacing with future devices without necessitating software upgrades, and offer optional patient electrical isolation. In an embodiment, the hub includes a large display dynamically providing information to a caregiver about a wide variety of measurement or otherwise determined parameters. Additionally, in an embodiment, the hub includes a docking station for a portable patient monitor. The portable patient monitor may communicate with the hub through the docking station or through various wireless paradigms known to an artisan from the disclosure herein, including WiFi, Bluetooth, Zigbee, or the like.

(45) In still other embodiments, the portable patient monitor modifies its screen when docked. The undocked display indicia is in part or in whole transferred to a large dynamic display of the hub and the docked display presents one or more anatomical graphics of monitored body parts. For example, the display may present a heart, lungs, a brain, kidneys, intestines, a stomach, other organs, digits, gastrointestinal systems or other body parts when it is docked. In an embodiment, the anatomical graphics may advantageously be animated. In an embodiment, the animation may generally follow the behavior of measured parameters, such as, for example, the lungs may inflate in approximate correlation to the measured respiration rate and/or the determined inspiration portion of a respiration cycle, and likewise deflate according to the expiration portion of the same. The heart may beat according to the pulse rate, may beat generally along understood actual heart contraction patterns, and the like. Moreover, in an embodiment, when the measured parameters indicate a need to alert a caregiver, a changing severity in color may be associated with one or more displayed graphics, such as the heart, lungs, brain, or the like. In still other embodiments, the body portions may include animations on where, when or how to attach measurement devices to measurement sites on the patient. For example, the monitor may provide animated directions for CCHD screening procedures or glucose strip reading protocols, the application of a forehead sensor, a finger or toe sensor, one or more electrodes, an acoustic sensor, and ear sensor, a cannula sensor or the like.

(46) The present disclosure relates to a medical monitoring hub configured to be the center of monitoring activity for a given patient. In an embodiment, the hub comprises a large easily readable display, such as an about ten (10) inch display dominating the majority of real estate on a front face of the hub. The display could be much larger or much smaller depending upon design constraints. However, for portability and current design goals, the preferred display is roughly sized

proportional to the vertical footprint of one of the dockable portable patient monitors. Other considerations are recognizable from the disclosure herein by those in the art.

(47) The display provides measurement data for a wide variety of monitored parameters for the patient under observation in numerical or graphic form, and in various embodiments, is automatically configured based on the type of data and information being received at the hub. In an embodiment, the hub is moveable, portable, and mountable so that it can be positioned to convenient areas within a caregiver environment. For example, the hub is collected within a singular housing.

(48) In an embodiment, the hub may advantageously receive data from a portable patient monitor while docked or undocked from the hub. Typical portable patient monitors, such as oximeters or co-oximeters can provide measurement data for a large number of physiological parameters derived from signals output from optical and/or acoustic sensors, electrodes, or the like. The physiological parameters include, but not limited to oxygen saturation, carboxy hemoglobin, methemoglobin, total hemoglobin, glucose, pH, bilirubin, fractional saturation, pulse rate, respiration rate, components of a respiration cycle, indications of perfusion including perfusion index, signal quality and/or confidences, plethysmograph data, indications of wellness or wellness indexes or other combinations of measurement data, audio information responsive to respiration, ailment identification or diagnosis, blood pressure, patient and/or measurement site temperature, depth of sedation, organ or brain oxygenation, hydration, measurements responsive to metabolism, combinations of the same or the like, to name a few. In other embodiments, the hub may output data sufficient to accomplish closed-loop drug administration in combination with infusion pumps or the like.

(49) In an embodiment, the hub communicates with other devices in a monitoring environment that are interacting with the patient in a number of ways. For example, the hub advantageously receives serial data from other devices without necessitating their reprogramming or that of the hub. Such other devices include pumps, ventilators, all manner of monitors monitoring any combination of the foregoing parameters, ECG/EEG/EKG devices, electronic patient beds, and the like. Moreover, the hub advantageously receives channel data from other medical devices without necessitating their reprogramming or that of the hub. When a device communicates through channel data, the hub may advantageously alter the large display to include measurement information from that device. Additionally, the hub accesses nurse call systems to ensure that nurse call situations from the device are passed to the appropriate nurse call system.

(50) The hub also communicates with hospital systems to advantageously associate incoming patient measurement and treatment data with the patient being monitored. For example, the hub may communicate wirelessly or otherwise to a multi-patient monitoring system, such as a server or collection of servers, which in turn many communicate with a caregiver's data management systems, such as, for example, an Admit, Discharge, Transfer (“ADT”) system and/or an Electronic Medical Records (“EMR”) system. The hub advantageously associates the data flowing through it with the patient being monitored thereby providing the electronic measurement and treatment information to be passed to the caregiver's data management systems without the caregiver associating each device in the environment with the patient.

(51) In an embodiment, the hub advantageously includes a reconfigurable and removable docking station. The docking station may dock additional layered docking stations to adapt to different patient monitoring devices. Additionally, the docking station itself is modularized so that it may be removed if the primary dockable portable patient monitor changes its form factor. Thus, the hub is flexible in how its docking station is configured.

(52) In an embodiment, the hub includes a large memory for storing some or all of the data it receives, processes, and/or associates with the patient, and/or communications it has with other devices and systems. Some or all of the memory may advantageously comprise removable SD memory.

(53) The hub communicates with other devices through at least (1) the docking station to acquire data from a portable monitor, (2) innovative universal medical connectors to acquire channel data, (3) serial data connectors, such as RJ ports to acquire output data, (4) Ethernet, USB, and nurse call ports, (5) Wireless devices to acquire data from a portable monitor, (6) other wired or wireless communication mechanisms known to an artisan. The universal medical connectors advantageously provide optional electrically isolated power and communications, are designed to be smaller in cross section than isolation requirements. The connectors and the hub communicate to advantageously translate or configure data from other devices to be usable and displayable for the hub. In an embodiment, a software developers kit (“SDK”) is provided to a device manufacturer to establish or define the behavior and meaning of the data output from their device. When the output is defined, the definition is programmed into a memory residing in the cable side of the universal medical connector and supplied as an original equipment manufacture (“OEM”) to the device provider. When the cable is connected between the device and the hub, the hub understands the data and can use it for display and processing purposes without necessitating software upgrades to the device or the hub. In an embodiment, the hub can negotiate the schema and even add additional compression and/or encryption. Through the use of the universal medical connectors, the hub organizes the measurement and treatment data into a single display and alarm system effectively and efficiently bringing order to the monitoring environment.

(54) As the hub receives and tracks data from other devices according to a channel paradigm, the hub may advantageously provide processing to create virtual channels of patient measurement or treatment data. In an embodiment, a virtual channel may comprise a non-measured parameter that is, for example, the result of processing data from various measured or other parameters. An example of such a parameter includes a wellness indicator derived from various measured parameters that give an overall indication of the wellbeing of the monitored patient. An example of a wellness parameter is disclosed in U.S. patent application Ser. Nos. 13/269,296, 13/371,767 and 12/904,925, by the assignee of the present disclosure and incorporated by reference herein. By organizing data into channels and virtual channels, the hub may advantageously time-wise synchronize incoming data and virtual channel data.

(55) The hub also receives serial data through serial communication ports, such as RJ connectors. The serial data is associated with the monitored patient and passed on to the multi-patient server systems and/or caregiver backend systems discussed above. Through receiving the serial data, the caregiver advantageously associates devices in the caregiver environment, often from varied manufactures, with a particular patient, avoiding a need to have each individual device associated with the patient and possible communicating with hospital systems. Such association is vital as it reduces caregiver time spent entering biographic and demographic information into each device about the patient. Moreover, in an embodiment, through the SDK the device manufacturer may advantageously provide information associated with any measurement delay of their device, thereby further allowing the hub to advantageously time-wise synchronize serial incoming data and other data associated with the patient.

(56) In an embodiment, when a portable patient monitor is docked, and it includes its own display, the hub effectively increases its display real estate. For example, in an embodiment, the portable patient monitor may simply continue to display its measurement and/or treatment data, which may be now duplicated on the hub display, or the docked display may alter its display to provide additional information. In an embodiment, the docked display, when docked, presents anatomical graphical data of, for example, the heart, lungs, organs, the brain, or other body parts being measured and/or treated. The graphical data may advantageously animate similar to and in concert with the measurement data. For example, lungs may inflate in approximate correlation to the measured respiration rate and/or the determined inspiration/expiration portions of a respiration cycle, the heart may beat according to the pulse rate, may beat generally along understood actual heart contraction patterns, the brain may change color or activity based on varying depths of

sedation, or the like. In an embodiment, when the measured parameters indicate a need to alert a caregiver, a changing severity in color may be associated with one or more displayed graphics, such as the heart, lungs, brain, organs, circulatory system or portions thereof, respiratory system or portions thereof, other body parts or the like. In still other embodiments, the body portions may include animations on where, when or how to attach measurement devices.

(57) The hub may also advantageously overlap parameter displays to provide additional visual information to the caregiver. Such overlapping may be user definable and configurable. The display may also incorporate analog-appearing icons or graphical indicia.

(58) In the interest of clarity, not all features of an actual implementation are described in this specification. An artisan will of course be appreciate that in the development of any such actual implementation (as in any development project), numerous implementation-specific decisions must be made to achieve a developers' specific goals and subgoals, such as compliance with system- and business-related constraints, which will vary from one implementation to another. Moreover, it will be appreciated that such a development effort might be complex and time-consuming, but would nevertheless be a routine undertaking of device engineering for those of ordinary skill having the benefit of this disclosure.

(59) To facilitate a complete understanding of the disclosure, the remainder of the detailed description describes the disclosure with reference to the drawings, wherein like reference numbers are referenced with like numerals throughout.

II. Example Hub Embodiments

(60) FIG. 1A illustrates a monitoring environment including a perspective view of an exemplary medical monitoring hub **100** with an exemplary docked portable patient monitor **102** according to an embodiment of the disclosure. The hub **100** includes a display **104**, and a docking station **106**, which in an embodiment is configured to mechanically and electrically mate with the portable patient monitor **102**, each housed in a movable, mountable and portable housing **108**. The housing **108** includes a generally upright inclined shape configured to rest on a horizontal flat surface, although the housing **108** can be affixed in a wide variety of positions and mountings and comprise a wide variety of shapes and sizes.

(61) In an embodiment, the display **104** may present a wide variety of measurement and/or treatment data in numerical, graphical, waveform, or other display indicia **110**. In an embodiment, the display **104** occupies much of a front face of the housing **108**, although an artisan will appreciate the display **104** may comprise a tablet or tabletop horizontal configuration, a laptop-like configuration or the like. Other embodiments may include communicating display information and data to a table computer, smartphone, television, or any display system recognizable to an artisan. The upright inclined configuration of FIG. 1A presents display information to a caregiver in an easily viewable manner.

(62) FIG. 1B shows a perspective side view of an embodiment of the hub **100** including the housing **108**, the display **104**, and the docking station **106** without a portable monitor docked. Also shown is a connector for noninvasive blood pressure.

(63) In an embodiment, the housing **108** may also include pockets or indentations to hold additional medical devices, such as, for example, a blood pressure monitor or temperature sensor **112**, such as that shown in FIG. 1C.

(64) The portable patient monitor **102** of FIG. 1A may advantageously comprise an oximeter, co-oximeter, respiratory monitor, depth of sedation monitor, noninvasive blood pressure monitor, vital signs monitor or the like, such as those commercially available from Masimo Corporation of Irvine, CA, and/or disclosed in U.S. Pat. Pub. Nos. 2002/0140675, 2010/0274099, 2011/0213273, 2012/0226117, 2010/0030040; U.S. Pat. App. Ser. Nos. 61/242,792, 61/387,457, 61/645,570, 13/554,908 and U.S. Pat. Nos. 6,157,850, 6,334,065, and the like. The monitor **102** may communicate with a variety of noninvasive and/or minimally invasive devices such as optical sensors with light emission and detection circuitry, acoustic sensors, devices that measure blood

parameters from a finger prick, cuffs, ventilators, and the like. The monitor **102** may include its own display **114** presenting its own display indicia **116**, discussed below with reference to FIGS. **19A-19J**. The display indicia may advantageously change based on a docking state of the monitor **102**. When undocked, the display indicia may include parameter information and may alter orientation based on, for example, a gravity sensor or accelerometer.

(65) In an embodiment, the docking station **106** of the hub **100** includes a mechanical latch **118**, or mechanically releasable catch to ensure that movement of the hub **100** doesn't mechanically detach the monitor **102** in a manner that could damage the same.

(66) Although disclosed with reference to particular portable patient monitors **102**, an artisan will recognize from the disclosure herein a large number and wide variety of medical devices that may advantageously dock with the hub **100**. Moreover, the docking station **106** may advantageously electrically and not mechanically connect with the monitor **102**, and/or wirelessly communicate with the same.

(67) FIG. **2** illustrates a simplified block diagram of an exemplary monitoring environment **200** including the hub **100** of FIG. **1**, according to an embodiment of the disclosure. As shown in FIG. **2**, the environment may include the portable patient monitor **102** communicating with one or more patient sensors **202**, such as, for example, oximetry optical sensors, acoustic sensors, blood pressure sensors, respiration sensors or the like. In an embodiment, additional sensors, such as, for example, a NIBP sensor or system **211** and a temperature sensor or sensor system **213** may communicate directly with the hub **100**. The sensors **202**, **211** and **213** when in use are typically in proximity to the patient being monitored if not actually attached to the patient at a measurement site.

(68) As disclosed, the portable patient monitor **102** communicates with the hub **100**, in an embodiment, through the docking station **106** when docked and, in an embodiment, wirelessly when undocked, however, such undocked communication is not required. The hub **100** communicates with one or more multi-patient monitoring servers **204** or server systems, such as, for example, those disclosed with in U.S. Pat. Pub. Nos. 2011/0105854, 2011/0169644, and 2007/0180140. In general, the server **204** communicates with caregiver backend systems **206** such as EMR and/or ADT systems. The server **204** may advantageously obtain through push, pull or combination technologies patient information entered at patient admission, such as demographical information, billing information, and the like. The hub **100** accesses this information to seamlessly associate the monitored patient with the caregiver backend systems **206**. Communication between the server **204** and the monitoring hub **100** may be any recognizable to an artisan from the disclosure herein, including wireless, wired, over mobile or other computing networks, or the like.

(69) FIG. **2** also shows the hub **100** communicating through its serial data ports **210** and channel data ports **212**. As disclosed in the forgoing, the serial data ports **210** may provide data from a wide variety of patient medical devices, including electronic patient bed systems **214**, infusion pump systems **216** including closed loop control systems, ventilator systems **218**, blood pressure or other vital sign measurement systems **220**, or the like. Similarly, the channel data ports **212** may provide data from a wide variety of patient medical devices, including any of the foregoing, and other medical devices. For example, the channel data ports **212** may receive data from depth of consciousness monitors **222**, such as those commercially available from SEDLine, brain or other organ oximeter devices **224**, noninvasive blood pressure or acoustic devices **226**, or the like. In an embodiment, channel device may include board-in-cable ("BIC") solutions where the processing algorithms and the signal processing devices that accomplish those algorithms are mounted to a board housed in a cable or cable connector, which in some embodiments has no additional display technologies. The BIC solution outputs its measured parameter data to the channel port **212** to be displayed on the display **104** of hub **100**. In an embodiment, the hub **100** may advantageously be entirely or partially formed as a BIC solution that communicates with other systems, such as, for example, tablets, smartphones, or other computing systems.

(70) Although disclosed with reference to a single docking station **106**, the environment **200** may include stacked docking stations where a subsequent docking station mechanically and electrically docks to a first docking station to change the form factor for a different portable patient monitor as discussed with reference to FIG. 5. Such stacking may include more than 2 docking stations, may reduce or increase the form factor for mechanical compliance with mating mechanical structures on a portable device.

(71) FIG. 3 illustrates a simplified exemplary hardware block diagram of the hub **100** of FIG. 1, according to an embodiment of the disclosure. As shown in FIG. 3, the housing **108** of the hub **100** positions and/or encompasses an instrument board **302**, the display **104**, memory **304**, and the various communication connections, including the serial ports **210**, the channel ports **212**, Ethernet ports **305**, nurse call port **306**, other communication ports **308** including standard USB or the like, and the docking station interface **310**. The instrument board **302** comprises one or more substrates including communication interconnects, wiring, ports and the like to enable the communications and functions described herein, including inter-board communications. A core board **312** includes the main parameter, signal, and other processor(s) and memory, a portable monitor board (“RIB”) **314** includes patient electrical isolation for the monitor **102** and one or more processors, a channel board (“MID”) **316** controls the communication with the channel ports **212** including optional patient electrical isolation and power supply **318**, and a radio board **320** includes components configured for wireless communications. Additionally, the instrument board **302** may advantageously include one or more processors and controllers, busses, all manner of communication connectivity and electronics, memory, memory readers including EPROM readers, and other electronics recognizable to an artisan from the disclosure herein. Each board comprises substrates for positioning and support, interconnect for communications, electronic components including controllers, logic devices, hardware/software combinations and the like to accomplish the tasks designated above and others.

(72) An artisan will recognize from the disclosure herein that the instrument board **302** may comprise a large number of electronic components organized in a large number of ways. Using different boards such as those disclosed above advantageously provides organization and compartmentalization to the complex system.

(73) FIG. 4 illustrates a perspective view of an exemplary removable docking station **400** of the hub **100** of FIG. 1, according to an embodiment of the disclosure. As shown in FIG. 4, the docking station **400** provides a mechanical mating to portable patient monitor **102** to provide secure mechanical support when the monitor **102** is docked. The docking station **400** includes a cavity **402** shaped similar to the periphery of a housing of the portable monitor **102**. The station **400** also includes one or more electrical connectors **404** providing communication to the hub **100**. Although shown as mounted with bolts, the docking station **400** may snap fit, may use movable tabs or catches, may magnetically attach, or may employ a wide variety or combination of attachment mechanisms known to an artisan from the disclosure herein. In an embodiment, the attachment of the docking station **400** should be sufficiently secure that when docked, the monitor **102** and docking station cannot be accidentally detached in a manner that could damage the instruments, such as, for example, if the hub **100** was accidentally bumped or the like, the monitor **102** and docking station **400** should remain intact.

(74) The housing **108** of the hub **100** also includes cavity **406** housing the docking station **400**. To the extent a change to the form factor for the portable patient monitor **102** occurs, the docking station **400** is advantageously removable and replaceable. Similar to the docking station **400**, the hub **100** includes within the cavity **406** of the housing **108** electrical connectors **408** providing electrical communication to the docking station **400**. In an embodiment, the docking station **400** includes its own microcontroller and processing capabilities, such as those disclosed in U.S. Pat. Pub. No. 2002/0140675. In other embodiments, the docking station **400** passes communications through to the electrical connector **408**.

(75) FIG. 4 also shows the housing **108** including openings for channel ports **212** as universal medical connectors discussed in detail below.

(76) FIG. 5 illustrates a perspective view of exemplary portable patient monitors **502** and **504** undocked from the hub **100** of FIG. 1, according to an embodiment of the disclosure. As shown in FIG. 5, the monitor **502** may be removed and other monitors, like monitor **504** may be provided. The docking station **106** includes an additional docking station **506** that mechanically mates with the original docking station **106** and presents a form factor mechanically matable with monitor **504**. In an embodiment, the monitor **504** mechanically and electrically mates with the stacked docking stations **506** and **106** of hub **100**. As can be readily appreciated by and artisan from the disclosure herein, the stackable function of the docking stations provides the hub **100** with an extremely flexible mechanism for charging, communicating, and interfacing with a wide variety of patient monitoring devices. As noted above, the docking stations may be stacked, or in other embodiments, removed and replaced.

(77) FIG. 6 illustrates a simplified block diagram of traditional patient electrical isolation principles. As shown in FIG. 6, a host device **602** is generally associated with a patient device **604** through communication and power. As the patient device **604** often comprises electronics proximate or connected to a patient, such as sensors or the like, certain safety requirements dictate that electrical surges of energy from, for example, the power grid connected to the host device, should not find an electrical path to the patient. This is generally referred to a “patient isolation” which is a term known in the art and includes herein the removing of direct uninterrupted electrical paths between the host device **602** and the patient device **604**. Such isolation is accomplished through, for example, isolation devices **606** on power conductors **608** and communication conductors **610**. Isolation devices **606** can include transformers, optical devices that emit and detect optical energy, and the like. Use of isolation devices, especially on power conductors, can be expensive component wise, expensive size wise, and drain power. Traditionally, the isolation devices were incorporated into the patient device **604**, however, the patient devices **604** are trending smaller and smaller and not all devices incorporate isolation.

(78) FIG. 7A illustrates a simplified block diagram of an exemplary optional patient isolation system according to an embodiment of the disclosure. As shown in FIG. 7A, the host device **602** communicates with an isolated patient device **604** through isolation devices **606**. However, a memory **702** associated with a particular patient device informs the host **602** whether that device needs isolated power. If a patient device **708** does not need isolated power, such as some types of cuffs, infusion pumps, ventilators, or the like, then the host **602** can provide non-isolated power through signal path **710**. This power may be much higher than what can cost-effectively be provided through the isolated power conductor **608**. In an embodiment, the non-isolated patient devices **708** receive isolated communication as such communication is typically at lower voltages and is not cost prohibitive. An artisan will recognize from the disclosure herein that communication could also be non-isolated. Thus, FIG. 7A shows a patient isolation system **700** that provides optional patient isolation between a host **602** and a wide variety of potential patient devices **604**, **708**. In an embodiment, the hub **100** includes the channel ports **212** incorporating similar optional patient isolation principles.

(79) FIG. 7B adds an exemplary optional non-isolation power levels for the system of FIG. 7A according to an embodiment of the disclosure. As shown in FIG. 7B, once the host **602** understands that the patient device **604** comprises a self-isolated patient device **708**, and thus does not need isolated power, the host **602** provides power through a separate conductor **710**. Because the power is not isolated, the memory **702** may also provide power requirements to the host **602**, which may select from two or more voltage or power levels. In FIG. 7B, the host **602** provides either high power, such as about 12 volts, but could have a wide range of voltages or very high power such as about 24 volts or more, but could have a wide range of voltages, to the patient device **708**. An artisan will recognize that supply voltages can advantageously be altered to meet the specific needs

of virtually any device **708** and/or the memory could supply information to the host **602** which provided a wide range of non-isolated power to the patient device **708**.

(80) Moreover, using the memory **702**, the host **602** may determine to simply not enable any unused power supplies, whether that be the isolated power or one or more of the higher voltage non-isolated power supplies, thereby increasing the efficiency of the host.

(81) FIG. **8** illustrates a simplified exemplary universal medical connector configuration process **800**, according to an embodiment of the disclosure. As shown in FIG. **8**, the process includes step **802**, where a cable is attached to a universal medical connector incorporating optional patient isolation as disclosed in the foregoing. In step **804**, the host device **602** or the hub **100**, more specifically, the channel data board **316** or EPROM reader of the instrument board, reads the data stored in the memory **702** and in step **806**, determines whether the connecting device requires isolated power. In step **808**, when the isolated power is required, the hub **100** may advantageously enable isolated power and in step **810**, enable isolated communications. In step **806**, when isolated power is not needed, the hub **100** may simply in optional step **812** enable non-isolated power and in embodiments where communications remain isolated, step **810** enable isolated communications. In other optional embodiments, in step **806**, when isolated power is not needed, the hub **100** in step **814** may use information from memory **702** to determine the amount of power needed for the patient device **708**. When sufficient power is not available, because for example, other connected devices are also using connected power, in step **816** a message may be displayed indicating the same and power is not provided. When sufficient power is available, optional step **812** may enable non-isolated power. Alternatively, optional step **818** may determine whether memory **702** indicates higher or lower power is desired. When higher power is desired, the hub **100** may enable higher power in step **820** and when not, may enable lower power in step **822**. The hub **100** in step **810** then enables isolated communication. In an embodiment, the hub **100** in step **818** may simply determine how much power is needed and provide at least sufficient power to the self-isolated device **708**.

(82) An artisan will recognize from the disclosure herein that hub **100** may not check to see if sufficient power is available or may provide one, two or many levels of non-isolated voltages based on information from the memory **702**.

(83) FIGS. **9A** and **9B** illustrate simplified block diagrams of exemplary universal medical connectors **900** having a size and shape smaller in cross section than tradition isolation requirements. In an embodiment, the connector **900** physically separates non-isolated signals on one side **910** from isolated signals on another side **920**, although the sides could be reversed. The gap between such separations may be dictated at least in part by safety regulations governing patient isolation. In an embodiment, the distance between the sides **910** and **920** may appear to be too small.

(84) As shown from a different perspective in FIG. **9B**, the distance between connectors “x” appears small. However, the gap causes the distance to includes a non-direct path between conductors. For example, any short would have to travel path **904**, and the distance of such path is within or beyond such safety regulations, in that the distance is greater than “x.” It is noteworthy that the non-straight line path **904** occurs throughout the connector, such as, for example, on the board connector side where solder connects various pins to a PCB board.

(85) FIG. **10** illustrates a perspective view of a side of the hub **100** of FIG. **1**, showing exemplary instrument-side channel inputs **1000** as exemplary universal medical connectors. As shown in FIG. **10**, the inputs include the non-isolated side **910**, the isolated side **920**, and the gap. In an embodiment, the memory **710** communicates through pins on the non-isolated side.

(86) FIGS. **11A-11K** illustrate various views of exemplary male and mating female universal medical connectors, according to embodiments of the disclosure. For example, FIGS. **11G1** and **11G2** shows various preferred but not required sizing, and FIG. **11H** shows incorporation of electronic components, such as the memory **702** into the connectors. FIGS. **11I-11K** illustrate wiring diagrams and cabling specifics of the cable itself as it connects to the universal medical

connectors.

(87) FIG. 12 illustrates a simplified block diagram of a channel system for the hub of FIG. 1, according to an embodiment of the disclosure. As shown in FIG. 12, a male cable connector, such as those shown in FIG. 11 above, includes a memory such as an EPROM. The memory advantageously stores information describing the type of data the hub 100 can expect to receive, and how to receive the same. A controller of the hub 100 communicates with the EPROM to negotiate how to receive the data, and if possible, how to display the data on display 104, alarm when needed, and the like. For example, a medical device supplier may contact the hub provider and receive a software developers' kit ("SDK") that guides the supplier through how to describe the type of data output from their device. After working with the SDK, a map, image, or other translation file may advantageously be loaded into the EPROM, as well as the power requirements and isolation requirements discussed above. When the channel cable is connected to the hub 100 through the channel port 212, the hub 100 reads the EPROM and the controller of the hub 100 negotiates how to handle incoming data.

(88) FIG. 13 illustrates an exemplary logical channel configuration that may be stored in the EPROM of FIG. 12. As shown in FIG. 13, each incoming channel describes one or more parameters. Each parameter describes whatever the hub 100 should know about the incoming data. For example, the hub 100 may want to know whether the data is streaming data, waveform data, already determined parameter measurement data, ranges on the data, speed of data delivery, units of the data, steps of the units, colors for display, alarm parameters and thresholds, including complex algorithms for alarm computations, other events that are parameter value driven, combinations of the same or the like. Additionally, the parameter information may include device delay times to assist in data synchronization or approximations of data synchronization across parameters or other data received by the hub 100. In an embodiment, the SDK presents a schema to the device supplier which self-describes the type and order of incoming data. In an embodiment, the information advantageously negotiates with the hub 100 to determine whether to apply compression and/or encryption to the incoming data stream.

(89) Such open architecture advantageously provides device manufacturers the ability to port the output of their device into the hub 100 for display, processing, and data management as disclosed in the foregoing. By implementation through the cable connector, the device manufacturer avoids any reprogramming of their original device; rather, they simply let the hub 100 know through the cable connector how the already existing output is formatted. Moreover, by describing the data in a language already understood by the hub 100, the hub 100 also avoids software upgrades to accommodate data from "new-to-the-hub" medical devices.

(90) FIG. 14 illustrates a simplified exemplary process for configuring a channel according to an embodiment of the disclosure. As shown in FIG. 14, the hub provider provides a device manufacturer with an SDK in step 1402, who in turn uses the SDK to self-describe the output data channel from their device in step 1404. In an embodiment, the SDK is a series of questions that guide the development, in other embodiments, the SDK provides a language and schema to describe the behavior of the data.

(91) Once the device provider describes the data, the hub provider creates a binary image or other file to store in a memory within a cable connector in step 1405; however, the SDK may create the image and simply communicated it to the hub provider. The cable connector is provided as an OEM part to the provider in step 1410, who constructs and manufactures the cable to mechanically and electrically mate with output ports on their devices in step 1412.

(92) Once a caregiver has the appropriately manufactured cable, with one end matching the device provider's system and the other OEM'ed to match the hub 100 at its channel ports 212, in step 1452 the caregiver can connect the hub between the devices. In step 1454, the hub 100 reads the memory, provides isolated or non-isolated power, and the cable controller and the hub 100 negotiate a protocol or schema for data delivery. In an embodiment, a controller on the cable may

negotiated the protocol, in an alternative embodiment, the controller of the hub **100** negotiates with other processors on the hub the particular protocol. Once the protocol is set, the hub **100** can use, display and otherwise process the incoming data stream in an intelligent manner.

(93) Through the use of the universal medical connectors described herein, connection of a myriad of devices to the hub **100** is accomplished through straightforward programming of a cable connector as opposed to necessitating software upgrades to each device.

(94) FIG. **15** illustrates a perspective view of the hub of FIG. **1** including an exemplary attached board-in-cable (“BIC”) to form an input channel according to an embodiment of the disclosure. As shown in FIG. **15**, a SEDLine depth of consciousness board communicates data from an appropriate patient sensor to the hub **100** for display and caregiver review. As described, the provider of the board need only use the SDK to describe their data channel, and the hub **100** understands how to present the data to the caregiver.

(95) FIG. **16** illustrates a perspective view of a back side of the hub **100** of FIG. **1**, showing an exemplary serial data inputs. In an embodiment, the inputs include such as RJ 45 ports. As is understood in the art, these ports include a data ports similar to those found on computers, network routers, switches and hubs. In an embodiment, a plurality of these ports are used to associate data from various devices with the specific patient identified in the hub **100**. FIG. **16** also shows a speaker, the nurse call connector, the Ethernet connector, the USBs, a power connector and a medical grounding lug.

(96) FIG. **17A** illustrates an exemplary monitoring environment with communication through the serial data connections of the hub **100** of FIG. **1**, according to an embodiment of the disclosure. As shown and as discussed in the foregoing, the hub **100** may use the serial data ports **210** to gather data from various devices within the monitoring environment, including an electronic bed, infusion pumps, ventilators, vital sign monitors, and the like. The difference between the data received from these devices and that received through the channel ports **212** is that the hub **100** may not know the format or structure of this data. The hub **100** may not display information from this data or use this data in calculations or processing. However, porting the data through the hub **100** conveniently associates the data with the specifically monitored patient in the entire chain of caregiver systems, including the foregoing server **214** and backend systems **206**. In an embodiment, the hub **100** may determine sufficient information about the incoming data to attempt to synchronize it with data from the hub **100**.

(97) In FIG. **17B**, a control screen may provide information on the type of data being received. In an embodiment, a green light next to the data indicates connection to a device and on which serial input the connection occurs.

(98) FIG. **18** illustrates a simplified exemplary patient data flow process, according to an embodiment of the disclosure. As shown, once a patient is admitted into the caregiver environment at step **1802**, data about the patient is populated on the caregiver backend systems **206**. The server **214** may advantageously acquire or receive this information in step **1804**, and then make it accessible to the hub **100**. When the caregiver at step **1806** assigns the hub **100** to the patient, the caregiver simply looks at the presently available patient data and selects the particular patient being currently monitored. The hub **100** at step **1808** then associates the measurement, monitoring and treatment data it receives and determines with that patient. The caregiver need not again associate another device with the patient so long as that device is communicating through the hub **100** by way of (1) the docking station, (2) the universal medical connectors, (3) the serial data connectors, or (4) other communication mechanisms known to an artisan. At step **1810**, some or the entirety of the received, processed and/or determined data is passed to the server systems discussed above.

(99) FIGS. **19A-19J** illustrate exemplary displays of anatomical graphics for the portable patient monitor docked with the hub **100** of FIG. **1**, according to embodiments of the disclosure. As shown in FIG. **19A**, the heart, lungs and respiratory system are shown while the brain is not highlighted. Thus, a caregiver can readily determine that depth of consciousness monitoring or brain oximetry

systems are not currently communicating with the hub **100** through the portable patient monitor connection or the channel data ports. However, it is likely that acoustic or other respiratory data and cardiac data is being communicated to or measured by the hub **100**. Moreover, the caregiver can readily determine that the hub **100** is not receiving alarming data with respect to the emphasized body portions. In an embodiment, the emphasized portion may animate to show currently measured behavior or, alternatively, animate in a predetermined fashion.

(100) FIG. **19B** shows the addition of a virtual channel showing an indication of wellness. As shown in FIG. **19B**, the indication is positive as it is a “34” on an increasingly severity scale to “100.” The wellness indication may also be shaded to show problems. In contrast to FIG. **19B**, FIG. **19C** shows a wellness number that is becoming or has become problematic and an alarming heart graphic. Thus, a caregiver responding to a patient alarm on the hub **100** or otherwise on another device or system monitoring or treating the patient can quickly determine that a review of vital signs and other parameters relating to heart function is needed to diagnose and/or treat the patient.

(101) FIGS. **19D** and **19E** show the brain included in the emphasized body portions meaning that the hub **100** is receiving data relevant to brain functions, such as, for example, depth of sedation data or brain oximetry data. FIG. **19E** additionally shows an alarming heart function similar to FIG. **19C**.

(102) In FIG. **19F**, additional organs, such as the kidneys are being monitored, but the respiratory system is not. In FIG. **19G**, an alarming hear function is shown, and in FIG. **19H**, an alarming circulatory system is being shown. FIG. **19I** shows the wellness indication along with lungs, heart, brain and kidneys. FIG. **19J** shows alarming lungs, heart, and circulatory system as well as the wellness indication. Moreover, FIG. **19J** shows a severity contrast, such as, for example, the heart alarming red for urgent while the circulatory system alarms yellow for caution. An artisan will recognize other color schemes that are appropriate from the disclosure herein.

(103) FIGS. **20A-20C** illustrate exemplary displays of measurement data showing data separation and data overlap, respectively, according embodiments of the disclosure. FIGS. **21A** and **21B** illustrate exemplary displays of measurement data also showing data separation and data overlap, respectively, according embodiments of the disclosure.

(104) For example, acoustic data from an acoustic sensor may advantageously provide breath sound data, while the plethysmograph and ECG or other signals can also be presented in separate waveforms (FIG. **20A**, top of the screen capture). The monitor may determine any of a variety of respiratory parameters of a patient, including respiratory rate, expiratory flow, tidal volume, minute volume, apnea duration, breath sounds, riles, rhonchi, stridor, and changes in breath sounds such as decreased volume or change in airflow. In addition, in some cases a system monitors other physiological sounds, such as heart rate to help with probe off detection, heart sounds (S1, S2, S3, S4, and murmurs), and change in heart sounds such as normal to murmur or split heart sounds indicating fluid overload.

(105) Providing a visual correlation between multiple physiological signals can provide a number of valuable benefits where the signals have some observable physiological correlation. As one example of such a correlation, changes in morphology (e.g., envelope and/or baseline) of the plethysmographic signal can be indicative of patient blood or other fluid levels. And, these changes can be monitored to detect hypovolemia or other fluid-level related conditions. A pleth variability index may provide an indication of fluid levels, for example. And, changes in the morphology of the plethysmographic signal are correlated to respiration. For example, changes in the envelope and/or baseline of the plethysmographic signal are correlated to breathing. This is at least in part due to aspects of the human anatomical structure, such as the mechanical relationship and interaction between the heart and the lungs during respiration.

(106) Thus, superimposing a plethysmographic signal and a respiratory signal (FIG. **20B**) can give operators an indication of the validity of the plethysmographic signal or signals derived therefrom,

such as a pleth variability index. For example, if bursts in the respiration signal indicative of inhalation and exhalation correlate with changes in peaks and valleys of the plethysmographic envelope, this gives monitoring personnel a visual indication that the plethysmographic changes are indeed due to respiration, and not some other extraneous factor. Similarly, if the bursts in the respiration signal line up with the peaks and valleys in the plethysmographic envelope, this provides monitoring personnel an indication that the bursts in the respiration signal are due to patient breathing sounds, and not some other non-targeted sounds (e.g., patient non-breathing sounds or non-patient sounds).

(107) The monitor may also be configured to process the signals and determine whether there is a threshold level of correlation between the two signals, or otherwise assess the correlation. However, by additionally providing a visual indication of the correlation, such as by showing the signals superimposed with one another, the display provides operators a continuous, intuitive and readily observable gauge of the particular physiological correlation. For example, by viewing the superimposed signals, users can observe trends in the correlation over time, which may not be otherwise ascertainable.

(108) The monitor can visually correlate a variety of other types of signals instead of, or in addition to plethysmographic and respiratory signals. For example, FIG. 20C depicts a screen shot of another example monitoring display. As shown in the upper right portion of FIG. 20C, the display superimposes a plethysmographic signal, an ECG signal, and a respiration signal. In other configurations, more than three different types of signals may be overlaid onto one another.

(109) In one embodiment, the hub 100 provides an interface through which the user can move the signals together to overlay on one another. For example, the user may be able to drag the respiration signal down onto the plethysmographic signal using a touch screen interface. Conversely, the user may be able to separate the signals, also using the touch screen interface. In another embodiment, the monitor includes a button the user can press, or some other user interface allowing the user to overlay and separate the signals, as desired. FIGS. 21A and 21B show similar separation and joining of the signals.

(110) In certain configurations, in addition to providing the visual correlation between the plethysmographic signal and the respiratory signal, the monitor is additionally configured to process the respiratory signal and the plethysmographic signal to determine a correlation between the two signals. For example, the monitor may process the signals to determine whether the peaks and valleys in the changes in the envelope and/or baseline of the plethysmographic signal correspond to bursts in the respiratory signal. And, in response to the determining that there is or is not a threshold level of correlation, the monitor may provide some indication to the user. For example, the monitor may provide a graphical indication (e.g., a change in color of pleth variability index indicator), an audible alarm, or some other indication. The monitor may employ one or more envelope detectors or other appropriate signal processing componentry in making the determination.

(111) In certain embodiments, the system may further provide an audible indication of the patient's breathing sounds instead of, or in addition to the graphical indication. For example, the monitor may include a speaker, or an earpiece (e.g., a wireless earpiece) may be provided to the monitoring personnel providing an audible output of the patient sounds. Examples of sensors and monitors having such capability are described in U.S. Pat. Pub. No. 2011/0172561 and are incorporated by reference herein.

(112) In addition to the above described benefits, providing both the acoustic and plethysmographic signals on the same display in the manner described can allow monitoring personnel to more readily detect respiratory pause events where there is an absence of breathing, high ambient noise that can degrade the acoustic signal, improper sensor placement, etc.

(113) FIGS. 22A-22B illustrate exemplary analog display indicia, according to an embodiment of the disclosure. As shown in FIGS. 22A and 22B, the screen shots displays health indicators of

various physiological parameters, in addition to other data. Each health indicator can include an analog indicator and/or a digital indicator. In embodiments where the health indicator includes an analog and a digital indicator, the analog and digital indicators can be positioned in any number of formations, such as side-by-side, above, below, transposed, etc. In the illustrated embodiment, the analog indicators are positioned above and to the sides of the digital indicators. As shown more clearly in FIG. 22B, the analog displays may include colored warning sections, dashes indicating position on the graph, and digital information designating quantitative information from the graph. In FIG. 22B, for example, the pulse rate PR graph shows that from about 50 to about 140 beats per minute, the graph is either neutral or beginning to be cautionary, whereas outside those numbers the graph is colored to indicate a severe condition. Thus, as the dash moves along the arc, a caregiver can readily see where in the range of acceptable, cautionary, and extreme the current measurements fall.

(114) Each analog indicator of the health indicator can include a dial that moves about an arc based on measured levels of monitored physiological parameters. As the measured physiological parameter levels increase the dial can move clockwise, and as the measured physiological parameter levels decrease, the dial can move counter-clockwise, or vice versa. In this way, a user can quickly determine the patient's status by looking at the analog indicator. For example, if the dial is in the center of the arc, the observer can be assured that the current physiological parameter measurements are normal, and if the dial is skewed too far to the left or right, the observer can quickly assess the severity of the physiological parameter levels and take appropriate action. In other embodiments, normal parameter measurements can be indicated when the dial is to the right or left, etc.

(115) In some embodiments, the dial can be implemented as a dot, dash, arrow, or the like, and the arc can be implemented as a circle, spiral, pyramid, or other shape, as desired. Furthermore, the entire arc can be lit up or only portions of the arc can be lit up based on the current physiological parameter measurement level. Furthermore, the arc can turn colors or be highlighted based on the current physiological parameter level. For example, as the dial approaches a threshold level, the arc and/or dial can turn from green, to yellow, to red, shine brighter, flash, be enlarged, move to the center of the display, or the like.

(116) Different physiological parameters can have different thresholds indicating abnormal conditions. For example, some physiological parameters may upper a lower threshold levels, while others only have an upper threshold or a lower threshold. Accordingly, each health indicator can be adjusted based on the physiological parameter being monitored. For example, the SpO2 health indicator can have a lower threshold that when met activates an alarm, while the respiration rate health indicator can have both a lower and upper threshold, and when either is met an alarm is activated. The thresholds for each physiological parameter can be based on typical, expected thresholds and/or user-specified thresholds.

(117) The digital indicator can provide a numerical representation of the current levels of the physiological parameter the digital indicator may indicate an actual level or a normalized level and can also be used to quickly assess the severity of a patient condition. In some embodiments, the display includes multiple health indicators for each monitored physiological parameter. In certain embodiments, the display includes fewer health indicators than the number of monitored physiological parameters. In such embodiments, the health indicators can cycle between different monitored physiological parameters.

(118) FIGS. 23A-23F illustrate exemplary displays of measurement data showing, for example, data presentation in FIGS. 23A-23D when a depth of consciousness monitor is connected to a channel port of the hub of FIG. 1. As shown in FIGS. 23A-23C, the hub 100 advantageously roughly bifurcates its display 104 to show various information from the, for example, SEDLine device, commercially available from Masimo Corp. of Irvine, CA. In FIG. 23D, the hub 100 includes an attached PhaseIn device, commercially available by PHASEIN AB of Sweden,

providing, for example, information about the patient's respiration. The hub **100** also includes the SEDLine information, so the hub **100** has divided the display **104** appropriately. In FIG. **23E**, temperature and blood pressure sensors communicate with the hub of FIG. **1** and the hub **100** creates display real estate appropriate for the same. In FIG. **23F**, an acoustic sensor is also communicating with the hub of FIG. **1**, as well as the forgoing blood pressure and temperature sensor. Accordingly, the hub **100** adjust the display real estate to accommodate the data from each attached device.

(119) The term “and/or” herein has its broadest least limiting meaning which is the disclosure includes A alone, B alone, both A and B together, or A or B alternatively, but does not require both A and B or require one of A or one of B. As used herein, the phrase “at least one of” A, B, “and” C should be construed to mean a logical A or B or C, using a non-exclusive logical or.

(120) The term “plethysmograph” includes its ordinary broad meaning known in the art which includes data responsive to changes in volume within an organ or whole body (usually resulting from fluctuations in the amount of blood or air it contains).

III. Additional Monitoring Environment Embodiments

(121) FIG. **24** illustrates another embodiment of a monitoring environment **2000** including the hub **100** of FIG. **1**. The monitoring environment **2000** may include all the features of the monitoring environment **200** of FIG. **2**, as well as any of the other features described above. In addition, the monitoring environment **2000** depicts another embodiment of the multi-patient monitoring system **204**, namely, the multi-patient monitoring system (MMS) **2004**. The MMS **2004** includes a translation module **2005** that can receive serial data, translate the serial data into a format recognizable by the monitoring hub **100**, and provide the serial data to the monitoring hub **100** (among possibly other devices). Also shown is an auxiliary device **2040** that may communicate with the MMS **2004**, the monitoring hub **100**, or the PPM **102**, wired or wirelessly.

(122) As described above, the hub **100** may receive serial data from a variety of medical equipment, including the patient's bed **214**, infusion pumps **216**, a ventilator **218**, and other vital signs monitors **220**. The hub **100** can pass serial data from these sources on to the MMS **2004**. As described above, the MMS **2004** may then store the serial data in a caregiver backend system **206** such as an EMR system or ADT system.

(123) The medical equipment providing this serial data may use a variety of different proprietary protocols, messaging infrastructure, and the like that may not be natively recognizable by the hub **100**. Accordingly, the hub **100** may not have native capability to read parameter values or other data from this medical equipment, and as a result, may not have the capability to display parameter values or other data from these devices. Advantageously, however, the translation module **2005** at the MMS **2004** can receive serial data from these devices, translate the serial data into a format recognizable by the monitoring hub **100**, and provide the serial data to the monitoring hub **100**. The monitoring hub **100** can then read parameter values and other data from the translated information and output these values or data to a display, such as any of the displays described above.

(124) In an embodiment, the translation module **2005** applies one or more translation rules to the serial data to translate or transform the serial data from one format to another format. The serial data may be formatted according to a Health Level Seven (“HL7”) protocol in one embodiment. The HL7 protocol has been developed to provide a messaging framework for the communication of clinical messages between medical computer systems and devices. However, the HL7 standard is quite flexible and merely provides a framework of guidelines. Consequently, medical devices or clinical computer systems that are all HL7-compliant may still be unable to communicate with each other. For example, the medical equipment **214-220** may each implement a version of the HL7 protocol, but these implementations may be different from an HL7 protocol implemented by the monitoring hub **100**. Accordingly, the monitoring hub **100** may not be able to parse or read messages from the medical equipment **214-220**, even though both use the HL7 standard. Further, the translation module **2005** may translate between different implementations of a common

standard other than the HL7 protocol implemented by the hub **100** and medical equipment **214-220** in some embodiments.

(125) In addition to translating between different implementations of a common electronic medical communication protocol (e.g., different formatting of HL7 messages), the translation module **2005** can also translate between input and output messages adhering to different communication protocols. In some embodiments, the translation module **2005** is capable of responding to and translating messages from, for example, one medical communication protocol to a separate medical communication protocol. For example, the translation module **2005** can facilitate communication between messages sent according to the HL7 protocol, the ISO 11073 protocol, other open protocols, or proprietary protocols. Accordingly, the translation module **2005** can translate an input message sent according to the HL7 protocol to an output message according to a different protocol, or vice-versa. In certain embodiments, the translation module **2005** can implement any of the translation features described below in greater detail under the section entitled “Translation Module Embodiments,” as well as further in U.S. application Ser. No. 14/032,132, filed Sep. 19, 2013, titled “Medical Monitoring System,” the disclosure of which is hereby incorporated by reference in its entirety.

(126) Advantageously, in certain embodiments, the translation module **2005** can pass translated serial data back to the hub **100** or PPM **102**. Since the translated data is in a format readable by the hub **100** or PPM **102**, the hub **100** or PPM **102** can output the data from the medical equipment **214-220** on the display of the hub **100** or PPM **102**. In addition, the translation module **2005** can provide the translated data to devices other than the hub **100**, including clinician devices (such as cell phones, tablets, or pagers) and an auxiliary device **2040** that will be described below. Moreover, since the serial data provided by the medical equipment **214-220** may include alarm notifications, the translation module **2005** can pass these alarm notifications to the hub **100** or PPM **102**. The hub **100** or PPM **102** can therefore generate visual or audible alarms responsive to these alarm notifications. Further, the translation module **2005** can provide the alarm notifications to clinician devices, e.g., over a hospital network or wide area network (such as the Internet). In addition, the translation module **2005** can provide the alarm notifications to the auxiliary device **2040**.

(127) The translation module **2005** is shown as implemented in the MMS **2004** because it may be beneficial to maintain and update the translation rules of the translation module **2005** in a single location. However, in other embodiments, the translation module **2005** may also be (or instead be) implemented in the hub **100** or PPM **102**. Accordingly, the hub **100** or PPM **102** can access an internal translation module **2005** to translate serial data for output to the display of the hub **100** or PPM **102**.

(128) The auxiliary device **2040** can be a computing device having physical computer hardware, a display, and the like. For example, the auxiliary device **2040** may be a handheld computing device used by a clinician, such as a tablet, laptop, cellphone or smartphone, personal digital assistant (PDA), a wearable computer (such as a smart watch or glasses), or the like. The auxiliary device **2040** may also be simply a display device, such as a computer monitor or digital television. In an embodiment, the auxiliary device **2040** provides second screen functionality for the hub **100**, PPM **102**, or MMS **2004**. As such, the auxiliary device **2040** can communicate wirelessly or through a wired connection with the hub **100**, MMS **2004**, or PPM **102**.

(129) As a second screen device, the auxiliary device **2040** can depict a copy of at least a portion of the display of the hub **100** (or the PPM **102**) or a different version of the hub **100** (or the PPM **102**) display. For instance, the auxiliary device **2040** can receive physiological parameter data, trend data, or waveforms from the hub **100**, PPM **102**, or MMS **2004** and display the parameter data, trend data, or waveforms. The auxiliary device **2040** can output any information available to the hub **100**, PPM **102**, or MMS **2004**. One use of the auxiliary device **2040** is as a clinician device usable by a clinician to view data from the hub **100**, PPM **102**, or MMS **2004** while away from a

patient's room (or even while in a patient's room). A clinician can use the auxiliary device **2040** to view more detailed information about physiological parameters than is displayed on the hub **100** or PPM **102** in an embodiment (see, e.g., FIG. **39**). For instance, the auxiliary device **2040** may include zoom functionality or the like that enables a clinician to zoom into trends or waveforms to more closely inspect parameter activity.

(130) One example reason for copying at least a portion of the display of the hub **100** or PPM **102** is to enable different clinicians to have the same view of the data during a surgical procedure. In some surgical procedures, for instance, two anesthesiologists monitor a patient, one anesthesiologist monitoring the brain function and brain oxygenation of the patient, while the other monitors peripheral oxygenation of the patient. A brain sensor, such as has been described above, may be attached to the patient and provide brain monitoring and oxygenation data that is output to the hub **100** or the PPM **102** for presentation to the first anesthesiologist. A finger or toe/foot optical sensor can also be attached to the patient and output data to the hub **100** or PPM **102**. The hub **100** or PPM **102** can transmit this data to the auxiliary device **2040**, which the second anesthesiologist can monitor to observe oxygenation in the patient's peripheral limbs. The second anesthesiologist may also need to know the oxygenation at the brain to help interpret the seriousness or lack thereof of poor peripheral oxygenation values. However, in many surgical procedures, a curtain or screen is placed over the patient as part of the procedure, blocking the second anesthesiologist's view of the hub **100** or PPM **102**. Accordingly, the hub **100** or PPM **102** can output a copy of at least a portion of its display to the auxiliary device **2040** so that the second anesthesiologist can monitor brain function or oxygenation.

(131) In one embodiment, the auxiliary device has a larger display area than the display of the hub **100**. For instance, the hub **100** may have a relatively smaller display, such as about 10 inches, while the auxiliary device **2040** may be a television monitor or the like that has a 40 inch or larger display (although any size display may be used for the auxiliary device **2040**). In an embodiment, the auxiliary device **2040** as a television can include a hardware module that includes a processor, memory, and a wireless or wired networking interface or the like. The processor can execute programs from the memory, including programs for displaying physiological parameters, trends, and waveforms on the display of the television. Since a television monitor is larger than embodiments of the hub **100**, the television monitor version of the auxiliary device **2040** can display more fine detail of patient waveforms and trends in some embodiments (see, e.g., FIG. **39**).

(132) In another embodiment, the auxiliary device **2040** may display one portion of any of the displays described herein while the hub **100** displays another portion thereof. For instance, the auxiliary device **2040** may display any of the anatomical graphics described above with respect to FIGS. **19A-19J**, while the hub **100** displays any of the parameter displays described above with respect to FIGS. **20A-23F** (or vice versa). Likewise, the auxiliary device **2040** may display the translated data received from the translation module **2005** while the hub **100** displays channel data (or vice versa). In another embodiment, the auxiliary device **2040** can display both translated data and channel data (see, e.g., FIG. **38**).

(133) In still other embodiments, the auxiliary device **2040** can perform at least some processing of physiological parameters, including any of the functionality of the monitoring hub **100**. For instance, the auxiliary device **2040** may include the translation module **2005** and perform the features thereof.

(134) FIG. **25** illustrates an embodiment of a translation message handling process **2100**. The process **2100** can be implemented by the translation module **2005** described above or by any other computing system. In an embodiment, at block **2502**, the translation module **2005** receives a message from the hub **100** (or PPM **102**) that includes a message from a medical device not natively compatible with the hub **100** (or PPM **102**). At block **2504**, the translation module **2005** translates the message based on one or more translation rules to produce a translated output message that can be processed by the hub **100** (or PPM **102**). At block **2506**, the translation module

provides the translated output message to the hub **100** for display at the hub **100** (or PPM **102**) or at an auxiliary device **2040**. The hub **100** (or PPM **102**) may route the translated data to the auxiliary device **2040**, or the auxiliary device **2040** may receive the translated data directly from the translation module **2005**.

(135) For example, in one embodiment, a first medical device having digital logic circuitry receives a physiological signal associated with a patient from a physiological sensor, obtains a first physiological parameter value based on the physiological signal, and outputs the first physiological parameter value for display. The first medical device can also receive a second physiological parameter value from a second medical device other than the first medical device, where the second physiological parameter value is formatted according to a protocol not used by the first medical device, such that the first medical device is not able to process the second physiological parameter value to produce a displayable output value. The first medical device can pass the physiological parameter data from the first medical device to a separate translation module, receive translated parameter data from the translation module at the first medical device, where the translated parameter data is able to be processed for display by the first medical device, and output a second value from the translated parameter data for display. The first medical device may be, for example, the hub **100**, PPM **102**, or MMS **2004**, and the second medical device may be the infusion pump **216** or ventilator **218** or the like.

(136) FIGS. **26-38** and **46-71** illustrate additional example hub displays, including displays of measurement data. Each of these displays may be implemented by the auxiliary device **2040**, although similar displays may also be output on the hub **100** (or PPM **102**) directly. The example Figures shown are depicted as being implemented for a tablet computer that includes touchscreen functionality. Touchscreen functionality is optional and be replaced by other suitable input devices, such as keyboards, mice, track wheels, and the like.

(137) Turning to FIG. **26**, the user interface shown depicts a device connected to the auxiliary device **2040**. The device shown is “Omar's Hawk,” which can be an embodiment of the monitoring hub **100**. The auxiliary device **2040** is connected wirelessly to the hub **100** in this embodiment so as to receive data from the hub **100**. The auxiliary device could also connect wirelessly to the MMS **2004** or PPM **102** in other embodiments.

(138) FIG. **27** depicts a default parameter view on the auxiliary device **2040**. Parameter values are shown together with waveforms in an upper portion of the display, and other parameters (such as SpHb, SpMet, PVI, etc.) are shown at the bottom of the display without their corresponding waveforms. Any of these parameters at the bottom of the display may be dragged and dropped onto the upper portion of the display to cause their waveforms to be shown. For instance, FIG. **28** depicts a similar display as in FIG. **27** except that the SpHb parameter has been dragged and dropped onto the upper portion of the display, causing the SpHb waveform and additional details on alarm limits (18 and 7) to be shown. Similarly, FIG. **29** shows the same display as FIG. **28** except that the SpMet parameter has been dragged and dropped on the upper portion of the display, causing its waveform and alarm limit (3) to be shown.

(139) In each of the displays of FIGS. **27-29**, a time window button is shown in the upper right corner. This time window button says “1 hr” in FIGS. **27-29** but may be selected by a user to change the time window, which can affect the window of trend or waveform data shown in the display. A user selection of this time window button and change to a 10 minute window is shown in FIG. **30**. As can be seen, the waveforms in FIG. **30** are shown in a smaller window of time than in the previous Figures.

(140) FIG. **31** shows another version of the display of FIG. **29** with stacked waveforms, including a stacked SpO2 and respiratory waveform, similar to other stacked waveforms described elsewhere herein. FIG. **32** shows a similar display to FIG. **29** with the pulse rate (PR) and SpMet (methemoglobin) parameters highlighted as being in alarm condition. The alarm condition can be represented as a red box around the parameter values and waveforms in an embodiment, or with

red transparency coloring at least a portion of the box. The red box or transparency may also flash in an embodiment, and an audible alarm may sound. Other ways to represent an alarm condition are used in other embodiments.

(141) FIG. 33 shows a popup interface that enables a user to adjust alarm limits for a parameter (in this embodiment, SpHb or total hemoglobin). The popup interface includes scroll wheels that allow a user to quickly scroll among and select possible parameter limit values.

(142) FIGS. 34-38 show landscape display views in contrast to the portrait-oriented displays of FIGS. 26-33. These landscape display views may be accessed by rotating the auxiliary device 2040 (such as tablet etc.) to a landscape orientation. FIG. 34 shows a first set of parameters, while FIGS. 35 and 36 add additional drag-and-dropped parameters with their waveforms and additional alarm limit details, similar to those described above with respect to FIGS. 27-29. FIG. 37 depicts stacked parameter waveforms, stacking SpO2 and respiratory waveforms. FIG. 38 depicts both channel parameters (such as SpO2, PR (pulse rate), and RRa (acoustically-measured respiratory rate)) while also showing translated serial data parameters 2210, including parameters from a pump and a vent. These translated serial data parameters 2210 may have been received from the translation module 2005, either through the hub 100 or directly from the MMS 2004.

(143) Referring again to FIG. 24, as described above, the hub 100 or PPM 102 can output a copy of at least a portion of the display to the auxiliary device 2040. In other embodiments, the hub 100 or PPM 102 can output data with respect to a subset of the full parameters shown on the hub 100 or PPM 102 to the auxiliary device 2040. For instance, the hub 100 or PPM 102 may provide functionality for a clinician to select one or more of the parameters displayed thereon to see just that one or more parameters displayed on the auxiliary device 2040. Doing so may allow the auxiliary device 2040 to show more detail about the selected one or more parameters because fewer parameters may be shown on the auxiliary device's 2040 display than on the hub 100 or PPM 102.

(144) FIG. 39 depicts one example display of an auxiliary device 2040 that depicts data with respect to one parameter, respiratory rate. Unlike the main display of the hub 100 or PPM 102, the display shown in FIG. 39 includes more than just the current value 2215, a recent trend 2230, and small waveform of the respiratory rate. In addition, the display depicts a histogram 2220 of historical highs and lows (e.g., for the past several days) of the patient being monitored. In addition, a detailed waveform 2240 is shown, which may be larger than the waveforms shown on the main display of the hub 100 or PPM 102, which may give the user more detailed insight into the patient's respiratory condition. A user may choose to zoom into the waveform 2240 (or other aspects of the display), causing the waveform 2242 to be enlarged to fill the display in place of the other elements of the display, or the like. Other graphs, tables, waveforms, and data may be shown for the respiratory parameter on the auxiliary device display 2040. Of course, parameters other than respiratory rate may also be selected for detailed display on the auxiliary device 2040.

IV. Translation Module Embodiments

(145) Any of the following features described with respect to FIGS. 40A through 45D can be implemented by the translation module 2005 of FIG. 24 or together with any of the devices described above with respect to FIG. 24.

(146) Healthcare costs have been increasing and the demand for reasonably-priced, high-quality patient care is also on the rise. Health care costs can be reduced by increasing the effectiveness of hospital information systems. One factor which may affect the efficacy of a health institution is the extent to which the various clinical computer systems employed at the health institution can interact with one another to exchange information.

(147) Hospitals, patient care facilities, and healthcare provider organizations typically include a wide variety of different clinical computer systems for the management of electronic healthcare information. Each of the clinical computer systems of the overall IT or management infrastructure can help fulfill a particular category or aspect of the patient care process. For example, a hospital can include patient monitoring systems, medical documentation and/or imaging systems, patient

administration systems, electronic medical record systems, electronic practice management systems, business and financial systems (such as pharmacy and billing), and/or communications systems, etc.

(148) The quality of care in a hospital or other patient care facility could be improved if each of the different clinical computer systems across the IT infrastructure (or even within the same hospital room; see, e.g., FIGS. 1 and 24) were able to effectively communicate with each other. This could allow for the exchange of patient data that is collected by one clinical computer system with another clinical computer system that could benefit from such patient data. For example, this may allow decisions relating to patient care to be made, and actions to be taken, based on a complete analysis of all the available information.

(149) In current practice, individual clinical computer systems can be, and often are, provided by different vendors. As a result, individual clinical computer systems may be implemented using a proprietary network or communication infrastructure, proprietary communication protocols, etc.; the various clinical computer systems used in the hospital cannot always effectively communicate with each other.

(150) Medical device and medical system vendors sometimes develop proprietary systems that cannot communicate effectively with medical devices and systems of other vendors in order to increase their market share and to upsell additional products, systems, and/or upgrades to the healthcare provider. Thus, healthcare providers are forced to make enterprise or system-wide purchase decisions, rather than selecting the best technology available for each type of individual clinical computer system in use.

(151) One example where this occurs is in the area of life-saving technology available for patient monitoring. For example, many different bedside devices for monitoring various physiological parameters are available from different vendors or providers. One such provider may offer a best-in-class device for monitoring a particular physiological parameter, while another such provider may offer the best-in-class device for another physiological parameter. Accordingly, it may be desirable in some circumstances for a hospital to have the freedom to use monitoring devices from more than one manufacturer, but this may not be possible if devices from different manufacturers are incapable of interfacing and exchanging patient information. Accordingly, the ability to provide reasonably-priced, high-quality patient care can be compromised. In addition, since each hospital or patient care facility may also implement its own proprietary communication protocols for its clinical computer network environment, the exchange of information can be further hindered.

(152) As described above, the Health Level Seven (“HL7”) protocol has been developed to provide a messaging framework for the communication of clinical messages between medical computer systems and devices. The HL7 communication protocol specifies a number of standards, guidelines, and methodologies which various HL7-compliant clinical computer systems can use to communicate with each other.

(153) The HL7 communication protocol has been adopted by many medical device manufacturers. However, the HL7 standard is quite flexible, and merely provides a framework of guidelines (e.g., the high-level logical structure of the messages); consequently, each medical device or medical system manufacturer or vendor may implement the HL7 protocol somewhat differently while still remaining HL7-compliant. For example, the format of the HL7 messages can be different from implementation to implementation, as described more fully herein. In some cases, the HL7 messages of one implementation can also include information content that is not included in messages according to another HL7 implementation. Accordingly, medical devices or clinical computer systems that are all HL7-compliant still may be unable to communicate with each other.

(154) Consequently, a translation module can be provided that can improve the communication of medical messages between medical devices or systems that use different allowed implementations of an established communication protocol (e.g., HL7), thereby increasing the quality of patient care through the integration of multiple clinical computer systems.

(155) FIG. 40A illustrates a first medical device **2405** and a second medical device **2410** that communicate with one another via a translation module **2415**. The first medical device **2405** is configured to transmit and receive messages according to a first allowed format or implementation of an accepted electronic medical communication protocol, while the second medical device **2410** is configured to transmit and receive messages according to a second allowed format or implementation of the electronic medical communication protocol. In some embodiments, the first and second protocol formats are different implementations of the HL7 communication protocol. Other electronic medical communication protocols besides HL7 can also be used.

(156) The translation module **2415** receives input messages having the first protocol format from the first medical device **2405** and generates output messages to the second medical device **2410** having the second protocol format. The translation module **2415** also receives input messages having the second protocol format from the second medical device **2410** and generates output messages to the first medical device **2405** having the first protocol format. Thus, the translation module **2415** can enable the first and second medical devices **2405**, **2410** to effectively and seamlessly communicate with one another without necessarily requiring modification to the communication equipment or protocol implemented by each device.

(157) In certain embodiments, the translation module **2415** determines the protocol format expected by an intended recipient of the input message based on, for example, the information in the input message or by referencing a database that stores the protocol format used by various devices, and then generates the output message based on the protocol format used by the intended recipient device or system. The output message can be generated based upon a comparison with, and application of, a set of translation rules **2420** that are accessible by the translation module **2415**.

(158) The translation rules **2420** can include rules that govern how to handle possible variations between formatting implementations within a common protocol. Examples of variations in formatting implementation of an electronic medical communication protocol include, for example, the delimiter or separator characters that are used to separate data fields, whether a particular field is required or optional, the repeatability of portions of the message (e.g., segments, fields, components, sub-components), the sequence of portions of the message (e.g., the order of fields or components), whether a particular portion of a message is included, the length of the message or portions of the message, and the data type used for the various portions of the message.

(159) In certain embodiments, the translation rules **2420** define additions, deletions, swappings, and/or modifications that should be performed in order to “translate” an input message that adheres to a first HL7 implementation into an output message that adheres to a second HL7 implementation. The output message can have, for example, different formatting than the input message, while maintaining all, or a portion of, the substance or content of the input message.

(160) In addition to translating between different implementations of a common electronic medical communication protocol (e.g., different formatting of HL7 messages), the translation module **2415** can also translate between input and output messages adhering to different communication protocols. In some embodiments, the translation module **2415** is capable of responding to and translating messages from, for example, one medical communication protocol to a separate medical communication protocol. For example, the translation module **2415** can facilitate communication between messages sent according to the HL7 protocol, the ISO 11073 protocol, other open protocols, and/or proprietary protocols. Accordingly, an input message sent according to the HL7 protocol can be translated to an output message according to a different protocol, or vice-versa.

(161) The operation of the translation module **2415** and the translation rules **2420** will be described in more detail below. Various embodiments of system architectures including the translation module **2415** will now be described.

(162) In certain embodiments, the first medical device **2405**, the second medical device **2410**, and the translation module **2415** are communicatively coupled via connection to a common

communications network or directly (via cables or wirelessly), for example, through the hub **100**, PPM **102**, and/or MMS **2004**. In some embodiments, the translation module **2415** can be communicatively coupled between the first medical device **2405** and the second medical device **2410** (with or without a communications network) such that all messages between the first and second medical devices **2405**, **2410** are routed through the translation module **2415**. Other architectures are also possible.

(163) The first and second medical devices **2405**, **2410** and the translation module **2415** can be included in, for example, a portion of the monitoring environments of FIG. **1** or **24** described above. The first medical device **2405** may be, for example, the infusion pump(s) **216** or ventilator **218**, while the second medical device **2410** may be, for example, the monitoring hub **100**, PPM **102**, MMS **2004**, or auxiliary device **2040**. The translation module **2415** is an example implementation of the translation module **2005**.

(164) In certain embodiments, the translation module **2415** can facilitate communication across multiple networks within a hospital environment. In other embodiments, the translation module **2415** can facilitate communication of messages across one or more networks extending outside of the hospital or clinical network environment. For example, the translation module **2415** can provide a communications interface with banking institutions, insurance providers, government institutions, outside pharmacies, other hospitals, nursing homes, or patient care facilities, doctors' offices, and the like.

(165) In some embodiments, the translation module **2415** of FIG. **40** can be a component of, for example, the environment **2000** described above with respect to FIG. **24**. For example, the translation module **2415** can be communicatively coupled with a hospital network or other networks or monitoring environments described above. In such embodiments, the translation module **2415** can facilitate the exchange of patient monitoring information, including, for example, physiological parameter measurements, physiological parameter trend information, and physiological parameter alarm conditions between bedside medical monitor devices, nurses' monitoring stations, a Hospital or Clinical Information System (which may store Electronic Medical Records), and/or many other medical devices and systems. The translation module **2415** can enable seamless communication between different medical devices and systems, each of which may use a different implementation of an electronic medical communication protocol such as, for example, the HL7 communication protocol, within a clinical or hospital network environment.

(166) In certain embodiments, the translation module **2415** can also facilitate communication between a first medical device that is part of the patient monitoring sub-system and a second medical device that is not part of, or is external to, the patient monitoring system **200**. As such, the translation module **2415** can be capable of responding to externally-generated medical messages (such as patient information update messages, status query messages, and the like from an HIS or CIS) and generating external reporting messages (such as event reporting messages, alarm notification messages, and the like from patient monitors or nurses' monitoring stations).

(167) In another embodiment, first and second medical devices **2405**, **2410** communicate with each other over a communication bus **2421**. Communication bus **2421** can include any one or more of the communication networks, systems, and methods described above, including the Internet, a hospital WLAN, a LAN, a personal area network, etc. For example, any of the networks describe above can be used to facilitate communication between a plurality of medical devices, including first and second medical devices **2405**, **2410**, discussed above. One such embodiment is illustrated in FIG. **40B**.

(168) In FIG. **40B**, first medical device **2405** provides a message to the communication bus **2421**. The message is intended for receipt by the second medical device **2410**; however, because first and second medical devices **2405**, **2410** communicate according to different communication protocol format, second medical device **2410** is unable to process the message.

(169) Translation module **2415** monitors the communication bus **2421** for such messages.

Translation module receives the message and determines that first medical device **2405** is attempting to communicate with second medical device **2410**. Translation module **2415** determines that message translation would facilitate communication between first and second medical devices **2405**, **2410**. Translation module **2415** therefore utilizes an appropriate translation rule stored in a translation module **2420**. Translation module **2420** can include a memory, EPROM, RAM, ROM, etc.

(170) The translation module **2415** translates the message from the first medical device **2405** according to any of the methods described herein. Once translated, the translation module **2415** delivers the translated message to the communication bus **2421**. The second medical device **2410** receives the translated message and responds appropriately. For example, the second medical device may perform a function and/or attempt to communication with the first medical device **2405**. The translation module **2415** facilitates communication from the second medical device **2410** to the first medical device **2405** in a similar manner.

(171) The first medical device **2405** and the second medical device **2410** can be, for example, any of the medical devices or systems communicatively coupled to a hospital network or hub **100**, PPM **102**, and/or MMS **2004**. These medical devices or systems can include, for example, point-of-care devices (such as bedside patient monitors), data storage units or patient record databases, hospital or clinical information systems, central monitoring stations (such as a nurses' monitoring station), and/or clinician devices (such as pagers, cell phones, smart phones, personal digital assistants (PDAs), laptops, tablet PCs, personal computers, pods, and the like).

(172) In some embodiments, the first medical device **2405** is a patient monitor for communicatively coupling to a patient for tracking a physiological parameter (e.g., oxygen saturation, pulse rate, blood pressure, etc.), and the second medical device **2410** is a hospital information system ("HIS") or clinical information system ("CIS"). In some embodiments, the patient monitor can communicate physiological parameter measurements, physiological parameter alarms, or other physiological parameter measurement information generated during the monitoring of a patient to the HIS or CIS for inclusion with the patient's electronic medical records maintained by the HIS or CIS.

(173) In some embodiments, the first medical device **2405** is an HIS or CIS and the second medical device **2410** is a nurses' monitoring station, as described herein. However, the translation module **2415** can facilitate communication between a wide variety of medical devices and systems that are used in hospitals or other patient care facilities. For example, the translation module **2415** can facilitate communication between patient physiological parameter monitoring devices, between a monitoring device and a nurses' monitoring station, etc.

(174) Using the translation module **2415**, a patient monitoring sub-system, such as those described herein (e.g., physiological monitoring system **200**), can push data to the HIS or pull data from the HIS even if the HIS uses a different implementation of the HL7 protocol, or some other electronic medical communication protocol.

(175) In certain embodiments, the patient monitoring sub-system can be configured to push/pull data at predetermined intervals. For example, a patient monitor or clinician monitoring station can download patient data automatically from the HIS at periodic intervals so that the patient data is already available when a patient is connected to a patient monitor. The patient data sent from the HIS can include admit/discharge/transfer ("ADT") information received upon registration of the patient. ADT messages can be initiated by a hospital information system to inform ancillary systems that, for example, a patient has been admitted, discharged, transferred or registered, that patient information has been updated or merged, or that a transfer or discharge has been canceled.

(176) In other embodiments, the patient monitoring sub-system can be configured to push/pull data to/from the HIS only when the HIS is solicited by a query. For example, a clinician may make a request for information stored in a patient's electronic medical records on the HIS.

(177) In still other embodiments, the patient monitoring sub-system can be configured to push/pull

data to/from the HIS in response to an unsolicited event. For example, a physiological parameter of a patient being monitored can enter an alarm condition, which can automatically be transmitted to the HIS for storing in the patient's electronic medical records. In yet other embodiments, any combination of the above methods or alternative methods for determining when to communicate messages to and from the HIS can be employed.

(178) Example system architectures and example triggers for the communication of messages involving the translation module **2415** have been described. Turning now to the operation of the translation module, FIGS. **25A-25D** illustrate an example medical message at different phases or steps of a translation process. The translation process will be described in more detail below in connection with FIGS. **26**, **27A** and **27B**.

(179) FIG. **41A** illustrates an example ADT input message **2505** received by the translation module **2415** from an HIS. The ADT input message **2505** is implemented according to the HL7 communication protocol and contains information related to the admission of a patient to a hospital. The ADT message **2505** includes multiple segments, including a message header segment **2506**, an event segment, a patient identification segment, a patient visit segment, role segments, a diagnosis segment, and multiple custom segments.

(180) In some embodiments, the message header (“MSH”) segment **2506** defines how the message is being sent, the field delimiters and encoding characters, the message type, the sender and receiver, etc. The first symbol or character after the MSH string can define the field delimiter or separator (in this message, a “caret” symbol). The next four symbols or characters can define the encoding characters. The first symbol defines the component delimiter (“~”), the second symbol defines the repeatable delimiter (“|”), the third symbol defines the escape delimiter (“\”), and the fourth symbol defines the sub-component delimiter (“&”). All of these delimiters can vary between HL7 implementations.

(181) In some embodiments, the example header segment **2506** further includes the sending application (“VAFC PIMS”), the receiving application (“NPTF-508”), the date/time of the message (“20091120104609-0600”), the message type (“ADT~A01”), the message control ID (“58103”), the processing ID (“P”), and the country code (“USA”). As represented by the consecutive caret symbols, the header segment also contains multiple empty fields.

(182) FIG. **41B** illustrates the message header segment **2506** after it has been parsed into fields or elements based on an identified field delimiter (the caret symbol). In certain embodiments, the parsed input message comprises an XML message that is configured to be transformed according to extensible stylesheet language transformation (XSLT) rules.

(183) In certain embodiment, the parsed input message can be encoded. FIG. **41C** illustrates the parsed message header segment of the input message after being encoded (e.g., using a Unicode Transformation Format-8 (“UTF-8”) encoding scheme).

(184) The encoded message header segment shows some of the various data types that can be used in the message. For example, the sending application (“VAFC PIMS”) of the third parsed field and the receiving application (“NPTF-508”) of the fifth parsed field are represented using a hierarchic designator (“HD”) name data type. The date/time field (the seventh parsed field) is represented using the time stamp (“TS”) data type. The processing ID field (the eleventh parsed field) is represented using the processing type (“PT”) data type. The fields that do not include a data type identifier are represented using the string (“ST”) data type. Other possible data types include, for example, coded element, structured numeric, timing quantity, text data, date, entry identifier, coded value, numeric, and sequence identification. The data types used for the various fields or attributes of the segments can vary between formatting implementations.

(185) FIG. **41D** illustrates an example output message **2510** from the translation module **2415** based on the example input message **2505** of FIG. **41A**. The output message **2510** includes a message acknowledgement segment **2512**.

(186) Turning to the operation of the translation module, the translation module **2415** can, for

example, create, generate, or produce an output message that is reflective of the input message based on an application of the set of translation rules **2420**. In some embodiments, the translation module **2415** can, for example, translate, transform, convert, reformat, configure, change, rearrange, modify, adapt, alter, or adjust the input message based on a comparison with, and application of, the set of translation rules **2420** to form the output message. In some embodiments, the translation module **2415** can, for example, replace or substitute the input message with an output message that retains the content of the input message but has a new formatting implementation based upon a comparison with, and application of, the set of translation rules **2420**.

(187) FIG. **42** illustrates a translation process **2600** for generating an output message based on an input message and a comparison with the set of translation rules **2420** associated with the translation module **2415**. The translation process **2600** starts at block **2602** where the translation module **2415** receives an input message from a first medical device.

(188) At block **2604**, the translation module **2415** determines the formatting implementation of the input message and the formatting implementation to be used for the output message. In certain embodiments, the input message can include one or more identifiers indicative of the formatting implementation. In some embodiments, the determination of the formatting implementation can be made, for example, by analyzing the message itself by identifying the delimiter or encoding characters used, the field order, the repeatability of segments, fields, or components, the data type of the fields, or other implementation variations. In certain embodiments, the translation module **2415** can separate or parse out the formatting from the content of the message (as shown in FIG. **41B**) to aid in the determination of the formatting implementation. In some embodiments, the translation module **2415** determines the formatting implementation of the input message by referencing a database that stores the implementation used by each device with which the translation module **2415** has been configured to interface.

(189) In certain embodiments, the determination of the formatting implementation used by the output message can also be determined from the input message. For example, the input message can include a field that identifies the intended recipient application, facility, system, device, and/or destination. The input message can alternatively include a field that identifies the type of message being sent (e.g., ADT message) and the translation module **2415** can determine the appropriate recipient from the type of message being sent and/or the sending application, device, or system. The translation module **2415** can then determine the formatting implementation required by the intended recipient of the input message.

(190) At decision block **2605**, the translation module **2415** determines whether a rule set has been configured for the translation from the identified formatting implementation of the input message to the identified formatting implementation to be used for the output message. The rule set may have been manually configured prior to installation of the translation module software or may have been automatically configured prior to receipt of the input message. If a rule set has already been configured, then the translation process **2600** continues to block **2606**. If a rule set has not been configured, then a rule set is configured at block **2607**. The configuration of the rule set can be performed as described below in connection with FIGS. **44** and **45A-2459D**. The translation process **2600** then continues to block **2608**.

(191) At block **2606**, the translation module **2415** identifies the pre-configured rules from the set of translation rules **2420** that govern translation between the determined formatting implementation of the input message and the formatting implementation of the output message. In some embodiments, the identification of the pre-configured rules can be made manually.

(192) At block **2608**, the translation module **2415** generates an output message based on the configured rule set(s) of the translation rules **2420**. In certain embodiments, the output message retains all, or at least a portion of, the content of the input message but has the format expected and supported by the intended recipient of the input message.

(193) The translation rules **2420** can include, for example, unidirectional rules and/or bidirectional

rules. A unidirectional rule can be one, for example, that may be applied in the case of a message from a first medical device (e.g., **2405**) to a second medical device (e.g., **2410**) but is not applied in the case of a message from the second medical device to the first medical device. For example, a unidirectional rule could handle a difference in the delimiters used between fields for two different formatting implementations of, for example, the HL7 communication protocol. The translation module **2415** can apply a field delimiter rule to determine if the field delimiter is supported by the intended recipient of the input message. If the field delimiter of the input message is not supported by the intended recipient, the field delimiter rule can replace the field delimiter of the input message with a field delimiter supported by the intended recipient.

(194) For example, an input message from an input medical device can include a formatting implementation that uses a “caret” symbol (“{circumflex over ()}”) as the field delimiter or separator. However, the formatting implementation recognized by the intended recipient medical device may use a “pipe” symbol (“|”) as the field delimiter. The translation module **2415** can identify the field delimiter symbol used in the formatting implementation recognized by the intended recipient medical device from the set of translation rules **2420** and generate an output message based on the input message that uses the pipe field delimiter symbol instead of the caret field delimiter symbol used in the input message. The rule to substitute a pipe symbol for a caret symbol would, in this case, only apply to messages that are sent to a recipient device that recognizes the pipe symbol as a field delimiter. This rule could be accompanied by a complementary rule that indicates that a caret symbol should be substituted for a pipe symbol in the case of a message that is intended for a recipient device that is known to recognize the caret symbol as the field delimiter.

(195) Another unidirectional rule can handle the presence or absence of certain fields between different formatting implementations. For example, an input message from an input medical device can include fields that would not be recognized by the intended recipient medical device. The translation module **2415** can generate an output message that does not include the unrecognized or unsupported fields. In situations where an input message does not include fields expected by the intended recipient medical device, the set of translation rules **2420** can include a rule to insert null entries or empty “ ” strings in the fields expected by the intended recipient medical device and/or to alert the recipient device of the absence of the expected field. The sender device may also be notified by the translation module **2415** that the recipient device does not support certain portions of the message.

(196) Other unidirectional rules can facilitate, for example, the conversion of one data type to another (for example, string (“ST”) to text data (“TX”) or structured numeric (“SN”) to numeric (“NM”)), and the increase or decrease in the length of various portions of the message.

Unidirectional rules can also be used to handle variations in repeatability of portions of the message. For example, the translation module **2415** can apply a field repeatability rule to repeated instances of a segment, field, component, or sub-component of the message to determine how many such repeated instances are supported by the recipient device, if any, and deleting or adding any repeated instances if necessary. For example, a phone number field of a patient identification segment can be a repeatable field to allow for entry of home, work, and cell phone numbers.

(197) Bidirectional rules can also be used. Such rules may apply equally to messages between first and second medical devices (e.g., **2405**, **2410**) regardless of which device is the sender and which is the recipient. A bidirectional rule can be used to handle changes in sequence, for example. In certain implementations, an input message from an input medical device can include a patient name field, or fields, in which a first name component appears before a last name component. However, the intended recipient medical device may be expecting an implementation where the last name component appears before the first name component. Accordingly, the set of translation rules **2420** can include a bidirectional rule to swap the order of the first and last name components when communicating between the two medical devices, or between the two formatting implementations.

In general, field order rules can be applied to determine whether the fields, components, or sub-components are in the correct order for the intended recipient and rearranging them if necessary. Other bidirectional rules can be included to handle, for example, other sequential variations between formatting implementations or other types of variations.

(198) The translation rules **2420** can also include compound rules. For example, a compound rule can include an if-then sequence of rules, wherein a rule can depend on the outcome of another rule. Some translation rules **2420** may employ computations and logic (e.g., Boolean logic or fuzzy logic), etc.

(199) As discussed above, the messages communicated over the hospital-based communication network can employ the HL7 protocol. FIGS. **43A** and **43B** illustrate translation processes **2700A**, **2700B** in which HL7 messages are communicated between a HIS and a medical device over a hospital-based communications network or a clinical network. The translation processes **2700A**, **2700B** will be described with the assumption that the rules governing “translation” between the first and second HL7 formats have already been configured.

(200) FIG. **43A** illustrates a translation process **2700A** in which the translation module **2415** facilitates communication of an HL7 message, such as the ADT message of FIG. **41A**, from an HIS having a first HL7 format to an intended recipient medical device, such as a patient monitor or a clinician monitoring station, having a second HL7 format.

(201) The translation process **2700A** starts at block **2701**, where the translation module **2415** receives an input message having a first HL7 format from the HIS. In certain embodiments, the input message includes information regarding, for example, the admission of a patient and/or patient identification and patient medical history information from an electronic medical records database.

(202) At block **2703**, the translation module **2415** determines the formatting implementation of the input message and the formatting implementation to be used for the output message. These determinations can be made in a similar manner to the determinations discussed above in connection with block **2604** of FIG. **42**.

(203) At block **2705**, the translation module **2415** identifies the rules that govern translation between the determined HL7 format of the input message and the HL7 format of the output message and generates an output message having the second HL7 format based on the identified rules. In certain embodiments, the output message retains the content of the input message sent by the HIS but has the format expected and supported by the intended recipient of the input message.

(204) At block **2707**, the translation module **2415** can output the output message to the intended recipient over the hospital-based communications network. In certain embodiments, the intended recipient can transmit an acknowledgement message back to the hospital information system acknowledging successful receipt or reporting that an error occurred.

(205) FIG. **43B** illustrates a translation process **2700B** in which the translation module **2415** facilitates communication of an HL7 message from a medical device, such as a patient monitor, having a first HL7 format to an HIS having a second HL7 format. For example, the patient monitor can transmit reporting event data m such as patient alarm data, to the HIS to store in the patient's electronic medical records.

(206) The translation process **2700B** starts at block **2702**, where the translation module **2415** receives an input message having a first HL7 format from the medical device. In certain embodiments, the input message includes patient monitoring data or alarm data regarding one or more physiological parameters of the patient being monitored for storage in an electronic medical records database associated with the HIS.

(207) At block **2704**, the translation module **2415** determines the formatting implementation of the input message and the formatting implementation to be used for the output message. These determinations can be made in a similar manner to the determinations discussed above in connection with block **2604** of FIG. **42**.

(208) At block **2706**, the translation module **2415** identifies the rules that govern translation between the determined HL7 format of the input message and the HL7 format of the output message and generates an output message having the second HL7 format based on the identified rules. In certain embodiments, the output message retains the content of the input message sent by the medical device but has the format expected and supported by the HIS.

(209) At block **2708**, the translation module **2415** can output the output message to the hospital information system over the hospital-based communications network. In certain embodiments, the HIS can transmit an acknowledgement message back to the medical device acknowledging successful receipt or reporting that an error occurred.

(210) FIGS. **42**, **43A** and **43B** described the operation of the translator module **2415**. FIGS. **44** and **45A-45D** will be used to illustrate the description of the configuration of the translation rules **2420**.

(211) The translation rules **2420** can be implemented as one or more stylesheets, hierarchical relationship data structures, tables, lists, other data structures, combinations of the same, and/or the like. In certain embodiments, the translation rules **2420** can be stored in local memory within the translation module **2415**. In other embodiments, the translation rules **2420** can be stored in external memory or on a data storage device communicatively coupled to the translation module **2415**.

(212) The translation module **2415** can include a single rule set or multiple rule sets. For example, the translation module **2415** can include a separate rule set for each medical device/system and/or for each possible communication pair of medical devices/systems coupled to the network or capable of being coupled to the network. In some embodiments, the translation module **2415** can include a separate rule set for each possible pair of formatting implementations that are allowed under a medical communication protocol such as, for example, the HL7 protocol.

(213) In certain embodiments, the translation rules **2420** can be manually inputted using, for example, the messaging implementation software tool **2800** illustrated in FIG. **44**. For example, the software developer for a particular hospital network can determine the protocol message formats used by the devices and/or systems that are or can be coupled to the hospital network and then manually input rules to facilitate “translation” between the various protocol message formats supported or recognized by the devices and/or systems.

(214) FIG. **44** illustrates an example screenshot from a messaging implementation software tool **2800** for manually configuring translation rules **2420** to be used by the translation module **2415**. The screenshot from the messaging implementation software tool **2800** illustrates various parameters that may differ between formatting implementations of an electronic medical communication protocol, such as HL7. The screenshot also includes areas where a user can input information that defines, or is used to define, translation rules for converting between different HL7 implementations. In some embodiments, the messaging implementation software tool **2800** stores a variety of pre-configured rule sets based, for example, on known communication protocol implementations of various medical devices. In such embodiments, a user may configure one or more translation rules **2420** to be used in communications involving such devices by entering identification information, such as the device manufacturer, model number, etc. Based on this identification information, the messaging implementation tool **2800** can identify a pre-configured set of translation rules for communication with that device.

(215) In other embodiments, the translation rules **2420** can be automatically generated. For example, the automatic generation of a new set, or multiple sets, of rules can be triggered by the detection of a newly recognized “communicating” medical device or system on a network. In certain embodiments, the automatic generation of a new set or multiple sets of rules can occur at the time a first message is received from or sent to a new “communicating” medical device or system coupled to the network. In still other embodiments, the automatic generation of rule sets includes updating or dynamically modifying a pre-existing set of rules.

(216) The automatic generation of translation rule sets can be carried out in a variety of ways. For example, in some embodiments, the translation module **2415** can automatically initiate usage of a

pre-configured set of translation rules **2420** based upon, for example, the make and model of a new device that is recognized on the network. In certain embodiments, the translation module **2415** can request one or more messages from the new device or system and then analyze the messages to determine the type of formatting being implemented, as illustrated by the automatic rule configuration process **2900A** of FIG. **45A**. The automatic rule configuration process **2900A** starts at block **2901**, where the translation module **2415** receives one or more messages from a detected medical device or system on the network. The messages can be received upon transmission to an intended recipient medical device or system or in response to a query sent by the translation module **2415** or another medical device or system coupled to the network.

(217) At block **2903**, the translation module **2415** determines the protocol of the one or more received messages by, for example, analyzing the message or by consulting a database that indicates what communication protocol/format is implemented by each medical device or system on the network. In certain embodiments, the translation module **2415** is configured to handle medical messages implemented using a single common protocol, such as HL7. Accordingly, if a determination is made that the received messages are implemented using a non-supported or non-recognized protocol, the translation module can ignore the messages received from the detected medical device or system, output an alert or warning, or allow the messages to be sent without being translated.

(218) At block **2905**, the translation module **2415** determines the formatting implementation of the received message(s). In certain embodiments, the received messages can include one or more identifiers indicative of the formatting implementation. In other embodiments, the determination of the formatting implementation can be made, for example, by analyzing the message itself by checking field order, the delimiter or encoding characters used, or other implementation variations. In certain embodiments, the translation module **2415** can separate or parse out the formatting from the content of the message to aid in the determination of the formatting implementation.

(219) At block **2907**, the translation module **2415** configures one or more rules or rule sets to handle messages received from and/or sent to the detected medical device or system. In certain embodiments, the configuration of the rules involves the creation or generation of new rules. In other embodiments, the configuration of the rules involves the alteration or updating of existing rules. The configured rules or rule sets can be included with the translation rules **2420**. If a set of rules already exists for the formatting implementation used by the new device or system, then the configuration of new translation rules may not be required. Instead, existing translation rules can be associated with the new device or system for use in communication involving that device or system. In other embodiments, the translation module **2415** can create a new set of rules geared specifically for the new device or system or can modify an existing set of rules based on subtle formatting variations identified.

(220) In other embodiments, the translation module **2415** can generate test message(s) that may be useful in identifying the communication protocol and implementation used by a device or system. For example, the translation module can generate test messages to cause the newly detected device or system to take a particular action (e.g., store information) and then query information regarding the action taken by the newly detected device to determine whether or how the test message was understood. This is illustrated by the automatic rule configuration process **2900B** of FIG. **45B**.

(221) The automatic rule configuration process **2900B** starts at block **2902**, where the translation module **2415** transmits one or more test, or initialization, messages to a remote device or system detected on a network. The test messages can be configured, for example, to instruct the remote device or system to take a particular action (e.g., store patient information). In certain embodiments, the test messages can be configured to generate a response indicative of the type of formatting recognized or supported by the remote device or system. In other embodiments, the test messages can be configured such that only devices or systems supporting a particular formatting implementation will understand and properly act on the test messages.

(222) At block **2904**, the translation module **2415** queries the remote device or system to receive information regarding the action taken based on the test message sent to the remote device or system to determine whether the test message was understood. For example, if the test message instructed the remote device or system to store patient information in a particular location, the translation module **2415** can query the information from the location to determine whether the test message was understood. If the test message was not understood, the translation module **2415** can, for example, continue sending test messages of known formatting implementations until a determination is made that the test message has been understood.

(223) At block **2906**, the translation module **2415** determines the protocol and formatting implementation based on the information received. As an example, in certain embodiments, the test message can include an instruction to store patient name information. The test message can include a patient name field having a first name component followed by a surname component. The translation module **2415** can then query the remote device or system to return the patient surname. Depending on whether the patient surname or the first name is returned, this query can be useful in determining information about the order of fields in the formatting implementation being used by the remote device or system. As another example, the test messages can instruct the detected device or system to store repeated instances of a component. The translation module **2415** can then query the device or system to return the repeated instances to see which, if any, were stored. This repeatability information can also be useful in determining whether certain fields are allowed to be repeated in the formatting implementation being used by the remote device for system, and, if so, how many repeated instances are permitted.

(224) At block **2908**, the translation module **2415** configures one or more rules to handle messages received from and/or sent to the detected medical device or system. For example, the rules can convert messages from the message format used by a first medical device to that used by a second medical device, as described herein. In certain embodiments, the configuration of the rules involves the creation or generation of new rules. In other embodiments, the configuration of the rules involves the alteration or updating of existing rules. If a set of rules already exists for the formatting implementation used by the new device or system, then the configuration of new translation rules may not be required. Instead, existing translation rules can be associated with the new device or system for use in communication involving that device or system.

(225) FIGS. **29C** and **29D** illustrate automatic rule configuration processes performed by the translation module **2415** for messages utilizing the HL7 protocol. The HL7 protocol can be used, for example, to communicate electronic messages to support administrative, logistical, financial, and clinical processes. For example, HL7 messages can include patient administration messages, such as ADT messages, used to exchange patient demographic and visit information across various healthcare systems.

(226) The automatic rule configuration process **2900C** illustrated in FIG. **45C** is similar to the process **2900A** illustrated in FIG. **45A**. At block **2911**, the translation module **2415** receives one or more messages from an HL7 medical device. At block **2915**, the translation module **2415** determines the formatting implementation of the HL7 medical device from the one or more messages received. As discussed above, the determination of the formatting implementation can be made, for example, by checking field order or sequence, field delimiter characters, repeatability, cardinality, and other HL7 implementation variations.

(227) At block **2917**, the translation module **2415** configures one or more rules to handle messages received from and/or sent to the HL7 medical device. In certain embodiments, the configuration of the rules involves the creation or generation of new rules for the detected formatting implementation. In other embodiments, the configuration of the rules involves the dynamic alteration or updating of existing rules. If a set of rules already exists for the formatting implementation used by the new HL7 medical device, then the configuration of new translation rules may not be required. Instead, existing translation rules can be associated with the new HL7

medical device for use in communication involving that device.

(228) The automatic rule configuration process **2900D** illustrated in FIG. **45D** is similar to the process **2900B** illustrated in FIG. **45B**. At block **2912**, the translation module **2415** transmits one or more test, dummy, or initialization messages to an HL7 medical device. In other embodiments, the translation module **2415** can cause one or more test messages to be transmitted to the new HL7 medical device from another HL7 medical device. As described above, the test messages can include messages having known HL7 formats configured to determine whether the HL7 device understands the test messages. The test messages can include test ADT messages, for example.

(229) At block **2914**, the translation module **2415** queries the HL7 medical device to receive information regarding an action taken or information stored in response to the test message. At block **2916**, the translation module **2415** determines the formatting implementation of the HL7 device based on the information received. In certain embodiments, the translation module **2415** can analyze the information received to determine whether the test message or messages were properly understood. If none of the test messages were properly understood, the translation module **2415** can send additional test messages having other known HL7 formats and repeat blocks **2914** and **2916**.

(230) At block **2918**, the translation module **2415** configures one or more translation rules to handle messages received from and/or sent to the detected HL7 medical device. In certain embodiments, the configuration of the translation rules involves the creation or generation of new translation rules. In other embodiments, the configuration of the rules involves the alteration or updating of existing rules. If a set of translation rules already exists for the formatting implementation used by the new HL7 medical device, then the configuration of new translation rules may not be required. Instead, existing translation rules can be associated with the new HL7 medical device for use in communication involving that HL7 medical device.

(231) The automatic rule configuration processes described above can be triggered by the detection of a network device or system by the translation module **2415**. The medical devices referred to in FIGS. **45A-45D** can include any of the devices or systems illustrated in FIG. **1** or **24**.

(232) In some embodiments, the automatic generation of translation rules can advantageously occur post-installation and post-compilation of the messaging sub-system software, which includes the translation module **2415**. In certain embodiments, the automatic generation or dynamic modification of the translation rules **2420** can occur without having to recompile or rebuild the translation module software. This feature can be advantageous in terms of efficiently complying with U.S. Food and Drug Administration (“FDA”) requirements regarding validation of software used in healthcare environments.

(233) Take, for example, a situation where a medical device manufacturer plans to use the translation module **2415** to facilitate communication between a particular medical device or system that is to be installed in a hospital (e.g., a patient monitoring system, as described herein), or other patient care facility, and other devices or systems that are already installed at the hospital (e.g., the HIS or CIS). Any software required for the operation of the new medical device to be installed may be at least partially validated for FDA compliance prior to installation at the hospital despite the fact that, for example, the HL7 implementations of other existing devices or systems at the hospital may still be unknown. For example, any aspects of the software for the new medical device that are dependent upon receiving messages from other hospital devices can be validated pre-installation as being capable of fully and correctly operating when the expected message format is received. Then, once the medical device is installed at the hospital, the validation of the software can be completed by showing that the translation module **2415** is able to provide messages of the expected format to the newly installed device. In this way, FDA validation tasks can be apportioned to a greater extent to the pre-installation timeframe where they can be more easily carried out in a controlled manner rather than in the field.

(234) In addition, the translation module **2415** can further help streamline FDA validation, for example, when a medical device or system is expected to be installed at different hospitals whose

existing devices use, for example, different implementations of the HL7 protocol. Normally, this type of situation could impose the requirement that the entire functionality of the software for the new medical device be completely validated at each hospital. However, if the translation module 2415 is used to interface between the new medical device and the hospital's existing devices, then much of the software functionality could possibly be validated a single time prior to installation, as just described. Then, once installed at each hospital, the software validation for the medical device can be completed by validating that correct message formats are received from the translation module (the translation rules for which are field-customizable). This may result in making on-site validation procedures significantly more efficient, which will advantageously enable more efficient FDA compliance in order to bring life-saving medical technology to patients more quickly by the use of field-customizable translation rules.

V. Example Embodiments

(235) In certain embodiments, a system for providing medical data translation for output on a medical monitoring hub can include a portable physiological monitor comprising a processor that can: receive a physiological signal associated with a patient from a physiological sensor, calculate a physiological parameter based on the physiological signal, and provide a first value of the physiological parameter to a monitoring hub for display. The monitoring hub can include a docking station that can receive the portable physiological monitor. The monitoring hub can: receive the first value of the physiological parameter from the portable physiological monitor; output the first value of the physiological parameter for display; receive physiological parameter data from a medical device other than the portable physiological monitor, the physiological parameter data formatted according to a protocol other than a protocol natively readable or displayable by the monitoring hub; pass the physiological parameter data to a translation module; receive translated parameter data from the translation module, where the translated parameter data can be readable and displayable by the monitoring hub; and output a second value from the translated parameter data for display.

(236) The system of the preceding paragraph can be combined with any subcombination of the following features: the monitoring hub is further configured to output the first value of the physiological parameter and the second value from the translated parameter data on separate displays; the monitoring hub is further configured to output the second value from the translated parameter data to an auxiliary device having a separate display from a display of the monitoring hub; the auxiliary device is selected from the group consisting of a television, a tablet, a phone, a wearable computer, and a laptop; the physiological parameter data comprises data from an infusion pump; the physiological parameter data comprises data from a ventilator; and the translation module is configured to translate the physiological parameter data from a first Health Level 7 (HL7) format to a second HL7 format.

(237) In certain embodiments, a method of providing medical data translation for output on a medical monitoring hub can include: under the control of a first medical device comprising digital logic circuitry, receiving a physiological signal associated with a patient from a physiological sensor; obtaining a first physiological parameter value based on the physiological signal; outputting the first physiological parameter value for display; receiving a second physiological parameter value from a second medical device other than the first medical device, where the second physiological parameter value is formatted according to a protocol not used by the first medical device, such that the first medical device is not able to process the second physiological parameter value to produce a displayable output value; passing the physiological parameter data from the first medical device to a separate translation module; receiving translated parameter data from the translation module at the first medical device, the translated parameter data able to be processed for display by the first medical device; and outputting a second value from the translated parameter data for display.

(238) The method of the preceding paragraph can be combined with any subcombination of the

following features: further including translating the message by at least translating the message from a first Health Level 7 (HL7) format to a second HL7 format; the message can include data from a physiological monitor; the message can include data from an infusion pump or a ventilator; and the message can include data from a hospital bed.

(239) In certain embodiments, a system for providing medical data translation for output on a medical monitoring hub can include a first medical device including electronic hardware that can: obtain a first physiological parameter value associated with a patient; output the first physiological parameter value for display; receive a second physiological parameter value from a second medical device other than the first medical device, the second physiological parameter value formatted according to a protocol not used by the first medical device, such that the first medical device is not able to process the second physiological parameter value to produce a displayable output value; pass the physiological parameter data from the first medical device to a translation module; receive translated parameter data from the translation module at the first medical device, the translated parameter data able to be processed for display by the first medical device; and output a second value from the translated parameter data for display.

(240) The system of the preceding paragraph can be combined with any subcombination of the following features: the first medical device can also output the first value of the physiological parameter and the second value from the translated parameter data on the same display; the first medical device can also output the first value of the physiological parameter and the second value from the translated parameter data on separate displays; the first medical device can also output the second value from the translated parameter data to an auxiliary device; the auxiliary device can be a television monitor; the auxiliary device can be selected from the group consisting of a tablet, a phone, a wearable computer, and a laptop; the first medical device can include the translation module; the first medical device can also pass the physiological parameter data to the translation module over a network; and the physiological parameter data can include data from an infusion pump or a ventilator.

VI. Terminology

(241) Many other variations than those described herein will be apparent from this disclosure. For example, depending on the embodiment, certain acts, events, or functions of any of the algorithms described herein can be performed in a different sequence, can be added, merged, or left out altogether (e.g., not all described acts or events are necessary for the practice of the algorithms). Moreover, in certain embodiments, acts or events can be performed concurrently, e.g., through multi-threaded processing, interrupt processing, or multiple processors or processor cores or on other parallel architectures, rather than sequentially. In addition, different tasks or processes can be performed by different machines and/or computing systems that can function together.

(242) It is to be understood that not necessarily all such advantages can be achieved in accordance with any particular embodiment of the embodiments disclosed herein. Thus, the embodiments disclosed herein can be embodied or carried out in a manner that achieves or optimizes one advantage or group of advantages as taught herein without necessarily achieving other advantages as may be taught or suggested herein.

(243) The various illustrative logical blocks, modules, and algorithm steps described in connection with the embodiments disclosed herein can be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. The described functionality can be implemented in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the disclosure.

(244) The various illustrative logical blocks and modules described in connection with the

embodiments disclosed herein can be implemented or performed by a machine, such as a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor can be a microprocessor, but in the alternative, the processor can be a controller, microcontroller, or state machine, combinations of the same, or the like. A processor can include electrical circuitry or digital logic circuitry configured to process computer-executable instructions. In another embodiment, a processor includes an FPGA or other programmable device that performs logic operations without processing computer-executable instructions. A processor can also be implemented as a combination of computing devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. A computing environment can include any type of computer system, including, but not limited to, a computer system based on a microprocessor, a mainframe computer, a digital signal processor, a portable computing device, a device controller, or a computational engine within an appliance, to name a few.

(245) The steps of a method, process, or algorithm described in connection with the embodiments disclosed herein can be embodied directly in hardware, in a software module stored in one or more memory devices and executed by one or more processors, or in a combination of the two. A software module can reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, a CD-ROM, or any other form of non-transitory computer-readable storage medium, media, or physical computer storage known in the art. An example storage medium can be coupled to the processor such that the processor can read information from, and write information to, the storage medium. In the alternative, the storage medium can be integral to the processor. The storage medium can be volatile or nonvolatile. The processor and the storage medium can reside in an ASIC.

(246) Conditional language used herein, such as, among others, “can,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or states. Thus, such conditional language is not generally intended to imply that features, elements and/or states are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or states are included or are to be performed in any particular embodiment. The terms “comprising,” “including,” “having,” and the like are synonymous and are used inclusively, in an open-ended fashion, and do not exclude additional elements, features, acts, operations, and so forth. Also, the term “or” is used in its inclusive sense (and not in its exclusive sense) so that when used, for example, to connect a list of elements, the term “or” means one, some, or all of the elements in the list. Further, the term “each,” as used herein, in addition to having its ordinary meaning, can mean any subset of a set of elements to which the term “each” is applied.

(247) Disjunctive language such as the phrase “at least one of X, Y, or Z,” unless specifically stated otherwise, is otherwise understood with the context as used in general to present that an item, term, etc., may be either X, Y, or Z, or any combination thereof (e.g., X, Y, and/or Z). Thus, such disjunctive language is not generally intended to, and should not, imply that certain embodiments require at least one of X, at least one of Y, or at least one of Z to each be present.

(248) Unless otherwise explicitly stated, articles such as “a” or “an” should generally be interpreted to include one or more described items. Accordingly, phrases such as “a device configured to” are intended to include one or more recited devices. Such one or more recited devices can also be collectively configured to carry out the stated recitations. For example, “a processor configured to carry out recitations A, B and C” can include a first processor configured to carry out recitation A

working in conjunction with a second processor configured to carry out recitations B and C. (249) While the above detailed description has shown, described, and pointed out novel features as applied to various embodiments, it will be understood that various omissions, substitutions, and changes in the form and details of the devices or algorithms illustrated can be made without departing from the spirit of the disclosure. As will be recognized, certain embodiments of the inventions described herein can be embodied within a form that does not provide all of the features and benefits set forth herein, as some features can be used or practiced separately from others. (250) Additionally, all publications, patents, and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication, patent, or patent application was specifically and individually indicated to be incorporated by reference.

Claims

1. A method of displaying medical data, the method comprising: by a first medical device comprising digital logic circuitry, receiving a first physiological signal from a physiological sensor; determining, based on the first physiological signal, a first physiological parameter value of a first physiological parameter associated with a patient; outputting, in a first section of a display, the first physiological parameter value for display together with a corresponding waveform of the first physiological parameter; receiving a second physiological parameter value of a second physiological parameter associated with the patient; outputting, in a second section of the display, the second physiological parameter value for display; outputting, in the first section of the display, indications of alarm limits associated with the first physiological parameter, wherein the indications of the alarm limits are displayed adjacent to the displayed first physiological parameter value, and wherein the second physiological parameter value is displayed in the second section of the display without indications of corresponding alarm limits; in response to receiving a first user input dragging the second physiological parameter value from the second section of the display to the first section of the display, causing the second physiological parameter value together with a corresponding waveform of the second physiological parameter to be displayed in the first section of the display adjacent to the first physiological parameter value together with the corresponding waveform of the first physiological parameter; and in response to receiving a second user input dragging the corresponding waveform of the second physiological parameter onto the corresponding waveform of the first physiological parameter: causing the corresponding waveforms of the first and second physiological parameters to overlay on one another in a same portion of the display such that both of the corresponding waveforms are visible, continuous, and aligned in time, wherein the corresponding waveforms comprise a plethysmograph and respiration; determining a level of correlation between the first physiological signal and a second physiological signal associated with the second physiological parameter, wherein the first physiological signal comprises a plethysmographic signal, wherein the second physiological signal comprises a respiratory signal, and wherein determining the level of correlation comprises determining a correlation between (1) peaks or valleys in the plethysmographic signal, and (2) bursts in the respiratory signal; and in response to the determined level of correlation satisfying a correlation threshold, outputting at least one of: a graphical indication, or an audible alarm.

2. The method of claim 1, wherein: the second physiological parameter value is outputted for display in the second section of the display without the corresponding waveform of the second physiological parameter.

3. The method of claim 2 further comprising: by the first medical device comprising digital logic circuitry: in response to determining an alarm condition associated with the second physiological parameter, causing highlighting of a portion of the first section of the display surrounding the displayed second physiological parameter value and the corresponding waveform of the second physiological parameter.

4. The method of claim 3, wherein the highlighting comprises a colored box surrounding the displayed second physiological parameter value and the corresponding waveform of the second physiological parameter.

5. The method of claim 2 further comprising: by the first medical device comprising digital logic circuitry: further in response to receiving the first user input dragging and dropping the second physiological parameter value from the second section of the display to the first section of the display, causing indications of alarm limits associated with the second physiological parameter to be displayed in the first section of the display adjacent to the second physiological parameter value.

6. The method of claim 5, wherein the alarm limits comprise adjustable alarm limits, and wherein the method further comprises, by the first medical device comprising digital logic circuitry: in response to receiving a third user input, causing display of a popup user interface adjacent to the waveform of the second physiological parameter in the first section of the display and configured to receive adjustments to the alarm limits for the second physiological parameter.

7. The method of claim 1 further comprising: by the first medical device comprising digital logic circuitry: obtaining from a second medical device, a third physiological parameter value formatted according to a protocol not used by the first medical device, such that the first medical device is not able to process the third physiological parameter value to produce a displayable output value; passing the third physiological parameter value from the first medical device to a translation module; receiving translated parameter data from the translation module at the first medical device, the translated parameter data able to be processed for display by the first medical device; and outputting the third physiological parameter value from the translated parameter data for display.

8. The method of claim 7 further comprising: by the first medical device comprising digital logic circuitry: determining the translated parameter data by translating the third physiological parameter value from a first Health Level 7 (HL7) format to a second HL7 format.

9. The method of claim 8, wherein the third physiological parameter value comprises data from at least one of: a physiological monitor, an infusion pump, a ventilator, or a hospital bed.

10. The method of claim 7 further comprising: by the first medical device comprising digital logic circuitry: outputting the first physiological parameter value and the third physiological parameter value from the translated parameter data for display on the same display.

11. The method of claim 7 further comprising: by the first medical device comprising digital logic circuitry: outputting the third physiological parameter value from the translated parameter data to an auxiliary device having a separate display from the display of the first medical device.

12. The method of claim 11, wherein the auxiliary device is configured to: display, in the separate display, at least one of: a histogram of highs and lows for the past several days of the patient, or a detailed waveform that is larger than the waveforms shown on the display of the first medical device; and in response to receiving a third user input, zooming the detailed waveform to cause the detailed waveform to be enlarged to fill the separate display in place of the other elements of the separate display.

13. The method of claim 1 further comprising: by the first medical device comprising digital logic circuitry: displaying, in the display, a time window button selectable by a user to change a time window of displayed waveforms.

14. A system for displaying medical data, the system comprising: a first medical device comprising electric hardware configured to: receive a first physiological signal from a physiological sensor; determine, based on the first physiological signal, a first physiological parameter value of a first physiological parameter associated with a patient; output, in a first section of a display, the first physiological parameter value for display together with a corresponding waveform of the first physiological parameter; receive a second physiological parameter value of a second physiological parameter associated with the patient; output, in a second section of the display, the second physiological parameter value for display; output, in the first section of the display, indications of alarm limits associated with the first physiological parameter, wherein the indications of the alarm

limits are displayed adjacent to the displayed first physiological parameter value, and wherein the second physiological parameter value is displayed in the second section of the display without indications of corresponding alarm limits; in response to receiving a first user input dragging the second physiological parameter value from the second section of the display to the first section of the display, cause the second physiological parameter value together with a corresponding waveform of the second physiological parameter to be displayed in the first section of the display adjacent to the first physiological parameter value together with the corresponding waveform of the first physiological parameter; and in response to receiving a second user input dragging the corresponding waveform of the second physiological parameter onto the corresponding waveform of the first physiological parameter: cause the corresponding waveforms of the first and second physiological parameters to overlay on one another in a same portion of the display such that both of the corresponding waveforms are visible, continuous, and aligned in time, wherein the corresponding waveforms comprise a plethysmograph and respiration; determine a level of correlation between the first physiological signal and a second physiological signal associated with the second physiological parameter, wherein the first physiological signal comprises a plethysmographic signal, wherein the second physiological signal comprises a respiratory signal, and wherein determining the level of correlation comprises determining a correlation between (1) peaks or valleys in the plethysmographic signal, and (2) bursts in the respiratory signal; and in response to the determined level of correlation satisfying a correlation threshold, output at least one of: a graphical indication, or an audible alarm.

15. The system of claim 14, wherein: the second physiological parameter value is outputted for display in the second section of the display without the corresponding waveform of the second physiological parameter.

16. The system of claim 15, wherein the first medical device is further configured to: in response to determining an alarm condition associated with the second physiological parameter, cause highlighting of a portion of the first section of the display surrounding the displayed second physiological parameter value and the corresponding waveform of the second physiological parameter.

17. The system of claim 16, wherein the highlighting comprises a colored box surrounding the displayed second physiological parameter value and the corresponding waveform of the second physiological parameter.

18. The system of claim 15, wherein the first medical device is further configured to: further in response to receiving the first user input dragging and dropping the second physiological parameter value from the second section of the display to the first section of the display, cause indications of alarm limits associated with the second physiological parameter to be displayed in the first section of the display adjacent to the second physiological parameter value.

19. The system of claim 18, wherein the alarm limits comprise adjustable alarm limits, and wherein the first medical device is further configured to: in response to receiving a third user input, cause display of a popup user interface adjacent to the waveform of the second physiological parameter in the first section of the display and configured to receive adjustments to the alarm limits for the second physiological parameter.

20. The system of claim 14, wherein the first medical device is further configured to: obtain from a second medical device, a third physiological parameter value formatted according to a protocol not used by the first medical device, such that the first medical device is not able to process the third physiological parameter value to produce a displayable output value; pass the third physiological parameter value from the first medical device to a translation module; receive translated parameter data from the translation module at the first medical device, the translated parameter data able to be processed for display by the first medical device; and output the third physiological parameter value from the translated parameter data for display.

21. The system of claim 20, wherein the first medical device is further configured to: determine the

translated parameter data by translating the third physiological parameter value from a first Health Level 7 (HL7) format to a second HL7 format.

22. The system of claim 21, wherein the third physiological parameter value comprises data from at least one of: a physiological monitor, an infusion pump, a ventilator, or a hospital bed.

23. The system of claim 20, wherein the first medical device is further configured to: output the first physiological parameter value and the third physiological parameter value from the translated parameter data for display on the same display.

24. The system of claim 20, wherein the first medical device is further configured to: output the third physiological parameter value from the translated parameter data to an auxiliary device having a separate display from the display of the first medical device.

25. The system of claim 24, wherein the auxiliary device is configured to: display, in the separate display, at least one of: a histogram of highs and lows for the past several days of the patient, or a detailed waveform that is larger than the waveforms shown on the display of the first medical device; and in response to receiving a third user input, zooming the detailed waveform to cause the detailed waveform to be enlarged to fill the separate display in place of the other elements of the separate display.

26. The system of claim 14, wherein the first medical device is further configured to: display, in the display, a time window button selectable by a user to change a time window of displayed waveforms.
