

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404068
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Mitten; Robert T. et al.

Hinged lid packaging

Abstract

A pack for consumer goods includes an outer packaging container and an inner packaging container. The outer packaging container includes a lower box portion with an upper lid portion hingedly connected thereto. The inner packaging container includes a dispensing opening with a resealable closure, a front panel, a back panel, a top panel, a bottom panel, and opposing side panels; each side panel having an inner panel and an outer panel, the inner panel having a first width defining a width of the inner packaging container, and the outer panel including at least a portion having a second width defining flanges having a width greater than the first width. The inner packaging container is insertable within the outer packaging container such that the flanges extending from the back panel of the inner packaging container exert a biasing force on the hinged lid of the outer packaging container to assure lid closure is maintained.

Inventors: Mitten; Robert T. (Mechanicsville, VA), Hession; Christopher J. (Mechanicsville, VA)

Applicant: Altria Client Services LLC (Richmond, VA)

Family ID: 46245094

Assignee: Altria Client Services LLC (Richmond, VA)

Appl. No.: 17/901091

Filed: September 01, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230009504 A1	Jan. 12, 2023

Related U.S. Application Data

continuation parent-doc US 16218918 20181213 US 11434043 child-doc US 17901091
continuation parent-doc US 15172898 20160603 US 10059506 20180828 child-doc US 15235492

Publication Classification

Int. Cl.: **B65D5/66** (20060101); **B65D5/42** (20060101); **B65D5/50** (20060101); **B65D5/54** (20060101); **B65D85/10** (20060101)

U.S. Cl.:

CPC **B65D5/662** (20130101); **B65D5/4266** (20130101); **B65D5/5045** (20130101); **B65D5/543** (20130101); **B65D85/1045** (20130101);

Field of Classification Search

CPC: B65D (5/662)

USPC: 220/268

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1790370	12/1930	Earman	N/A	N/A
1864871	12/1931	Straus	N/A	N/A
2031029	12/1935	Breneman	N/A	N/A
2109100	12/1937	Brophy	N/A	N/A
2163828	12/1938	Chalmers	N/A	N/A
2346407	12/1943	Wright	N/A	N/A
2354239	12/1943	Williamson	N/A	N/A
2396150	12/1945	Bonville	N/A	N/A
2445001	12/1947	Pence	N/A	N/A
2922565	12/1959	Roderick et al.	N/A	N/A
2944555	12/1959	Peel et al.	N/A	N/A
2950043	12/1959	Ringler	N/A	N/A
2992766	12/1960	Guyer	N/A	N/A
3093292	12/1962	Ahlbor	N/A	N/A
3099382	12/1962	Talbert	N/A	N/A
3167238	12/1964	Smith	N/A	N/A
3231170	12/1965	Robinson	N/A	N/A
3327888	12/1966	Chalmers et al.	N/A	N/A
3608812	12/1970	Hamilton	N/A	N/A
3708108	12/1972	Rosenburg, Jr.	N/A	N/A
3818676	12/1973	Russell et al.	N/A	N/A
3874581	12/1974	Fox et al.	N/A	N/A
3948389	12/1975	Molins	229/87.13	B65D 77/32
3977520	12/1975	Grimm	N/A	N/A
RE29887	12/1978	Fox et al.	N/A	N/A

4196842	12/1979	Focke et al.	N/A	N/A
4216898	12/1979	Davies	N/A	N/A
4251022	12/1980	Focke	N/A	N/A
4267926	12/1980	Toimil	N/A	N/A
4267958	12/1980	Focke et al.	N/A	N/A
4300676	12/1980	Focke	206/264	B65D 85/1045
4303155	12/1980	Focke	229/87.05	B65D 85/1045
4303191	12/1980	Foster et al.	N/A	N/A
4375260	12/1982	Focke et al.	N/A	N/A
4534463	12/1984	Bouchard	N/A	N/A
4586605	12/1985	Newsome	N/A	N/A
4632299	12/1985	Holmberg	N/A	N/A
4646960	12/1986	Challand	N/A	N/A
4732276	12/1987	Knecht	N/A	N/A
4753384	12/1987	Focke et al.	N/A	N/A
4763779	12/1987	Focke	206/268	B65D 85/1036
4771882	12/1987	Lowe et al.	N/A	N/A
4850482	12/1988	Campbell	N/A	N/A
4912910	12/1989	Lowe et al.	N/A	N/A
4948038	12/1989	Moeller	229/149	B65D 5/6611
5080227	12/1991	Focke	N/A	N/A
5121879	12/1991	Focke et al.	N/A	N/A
5158664	12/1991	Colgan et al.	N/A	N/A
5205432	12/1992	Gullan	N/A	N/A
5207322	12/1992	Focke et al.	N/A	N/A
5301804	12/1993	Focke et al.	N/A	N/A
5314062	12/1993	Wu et al.	N/A	N/A
5341925	12/1993	Fleenor et al.	N/A	N/A
5358105	12/1993	Boriani et al.	N/A	N/A
5435440	12/1994	Focke et al.	N/A	N/A
5511658	12/1995	Focke et al.	N/A	N/A
5513752	12/1995	Gottlieb	N/A	N/A
5588281	12/1995	Boriani et al.	N/A	N/A
5806671	12/1997	Focke et al.	N/A	N/A
5904244	12/1998	Focke et al.	N/A	N/A
6164444	12/1999	Bray	206/268	B65D 75/5838
6199687	12/2000	Tambo et al.	N/A	N/A
6244436	12/2000	Boriani et al.	N/A	N/A
6334532	12/2001	Tambo et al.	N/A	N/A
6412630	12/2001	Focke et al.	N/A	N/A
6478149	12/2001	Parker	N/A	N/A
6505735	12/2002	Parker	206/268	B65D 85/1045
6612429	12/2002	Dennen	N/A	N/A
6742652	12/2003	Focke et al.	N/A	N/A
6826889	12/2003	Parker	N/A	N/A

6874623	12/2004	Bray	N/A	N/A
6889827	12/2004	Stringfield	N/A	N/A
7048115	12/2005	Stringfield	N/A	N/A
7370756	12/2007	Bray et al.	N/A	N/A
7395924	12/2007	Tambo	N/A	N/A
7438183	12/2007	Focke et al.	N/A	N/A
7467711	12/2007	Tambo	N/A	N/A
7500558	12/2008	Tambo	N/A	N/A
7506755	12/2008	Buse et al.	N/A	N/A
7537113	12/2008	Tambo	N/A	N/A
7617930	12/2008	Jones et al.	N/A	N/A
7717260	12/2009	Buse	N/A	N/A
7717261	12/2009	Pham et al.	N/A	N/A
7770724	12/2009	Ghini et al.	N/A	N/A
7827769	12/2009	Bertuzzi et al.	N/A	N/A
7828143	12/2009	Tosaka et al.	N/A	N/A
7832556	12/2009	Ghini et al.	N/A	N/A
7857122	12/2009	Williams et al.	N/A	N/A
7857128	12/2009	Deevi	206/274	B32B 15/20
7870953	12/2010	Tambo et al.	N/A	N/A
8464867	12/2012	Holloway et al.	N/A	N/A
9714134	12/2016	Tacchi	N/A	B65D 5/548
2003/0047470	12/2002	Parker	206/268	B65D 75/5855
2007/0193896	12/2006	Tambo et al.	N/A	N/A
2008/0093233	12/2007	Jones	206/268	B65D 85/1072
2008/0121538	12/2007	Buse	N/A	N/A
2008/0128301	12/2007	Bourgoin	206/268	B65D 85/1054
2008/0230410	12/2007	Steven Jones	206/268	B65D 5/6691
2009/0038965	12/2008	Tambo et al.	N/A	N/A
2009/0152138	12/2008	Ghini et al.	N/A	N/A
2009/0321437	12/2008	Polloni et al.	N/A	N/A
2010/0084424	12/2009	Gelardi	N/A	N/A
2010/0230303	12/2009	Buse	206/268	B65D 75/5838
2010/0252462	12/2009	Marchetti et al.	N/A	N/A
2010/0270184	12/2009	McKenzie	493/51	A24F 23/04
2011/0147443	12/2010	Igo	229/117.34	G09F 23/00
2011/0233080	12/2010	Bertuzzi	206/268	B65D 85/10564
2013/0284623	12/2012	Groulx	206/268	B65D 5/6691
2016/0159557	12/2015	Kahawaiolaa	206/268	B65D 75/5838
2018/0022538	12/2017	Li Vigni	206/259	B65D 81/2061
2020/0156843	12/2019	Bellamah	N/A	B65D 65/14

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
8901535	12/1988	DE	N/A
4134567	12/1992	DE	N/A
19851201	12/1999	DE	N/A
0007423	12/1979	EP	N/A
0395249	12/1989	EP	N/A
0608909	12/1993	EP	N/A
30067	12/1910	GB	N/A
259165	12/1925	GB	N/A
311957	12/1928	GB	N/A
449353	12/1935	GB	N/A
505544	12/1938	GB	N/A
578319	12/1945	GB	N/A
613944	12/1947	GB	N/A
904632	12/1961	GB	N/A
1102398	12/1967	GB	N/A
1149296	12/1968	GB	N/A
1336081	12/1972	GB	N/A
1341587	12/1972	GB	N/A
1496352	12/1976	GB	N/A
1555748	12/1978	GB	N/A
2038765	12/1979	GB	N/A
2236737	12/1990	GB	N/A
2264287	12/1992	GB	N/A
2451180	12/2008	GB	N/A
WO-98/22367	12/1997	WO	N/A
WO-98/49072	12/1997	WO	N/A
WO-01/94238	12/2000	WO	N/A
WO-02/079052	12/2001	WO	N/A
WO-2004/063032	12/2003	WO	N/A
WO-2004/074123	12/2003	WO	N/A
WO-2007/071745	12/2006	WO	N/A
WO-2009/004421	12/2008	WO	N/A
WO-2010/012370	12/2009	WO	N/A

OTHER PUBLICATIONS

International Search Report and the Written Opinion of the International Searching Authority issued Apr. 19, 2012 by the International Searching Authority in International Application No. PCT/US2011/064925. cited by applicant

International Search Report and the Written Opinion of the International Searching Authority dated Apr. 19, 2012 by the International Searching Authority in International Application No. PCT/US2011/064925. cited by applicant

International Preliminary Report on Patentability dated Jun. 18, 2013 for corresponding International Application No. PCT/US2011/064925. cited by applicant

Japanese Notice of Reasons for Refusal dated Nov. 10, 2015 for corresponding Japanese Application No. 2013-544745, and English-language translation thereof. cited by applicant

Written Opinion dated Mar. 9, 2016 for corresponding Japanese Application No. 2013- 544745, and English-language translation thereof. cited by applicant

Decision of Refusal dated Sep. 6, 2016 for corresponding Japanese Application No. 2013-544745,

Primary Examiner: Stashick; Anthony D

Assistant Examiner: Sanghera; Symren K

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation patent application of U.S. patent application Ser. No. 16/218,918, filed Dec. 13, 2018, which is a divisional patent application of U.S. patent application Ser. No. 15/235,492, filed Aug. 12, 2016, which is a continuation patent application of U.S. patent application Ser. No. 15/172,898, filed Jun. 3, 2016, which issued as U.S. Pat. No. 10,059,506 on Aug. 28, 2018, which is a divisional patent application of U.S. patent application Ser. No. 13/325,803, filed Dec. 14, 2011, which issued as U.S. Pat. No. 9,382,062 on Jul. 5, 2016, which claims priority under 35 U.S.C. § 119(e) to U.S. Provisional Application Ser. No. 61/422,975 filed Dec. 14, 2010, the entire contents of each of which is incorporated by reference herein.

FIELD OF THE DISCLOSURE

(1) The disclosure relates to a packaging container having an inner packaging container adapted to hold a number of consumer items, and in particular to a hinged lid packaging container having an inner resealable packaging container, preferably for accommodating smokeless tobacco pouches or pre-portioned smokeless tobacco (all referenced as “portions of smokeless tobacco”).

WORKING ENVIRONMENT

(2) Smokeless tobacco products are sold in round metal, plastic or paperboard cans which have removable metal or plastic lids. However, different forms of packaging may appeal and provide conveniences to consumers such as smokers more familiar with hinged-lid packaging.

SUMMARY

(3) Disclosed herein is a combination of a resealable inner box and outer box packaging arrangement, particularly suited for smokeless tobacco products.

(4) According to one embodiment, a pack for consumer goods comprises an outer packaging container and an inner packaging container. The outer packaging container includes a generally rectangular lower box portion with an upper lid portion hingedly connected thereto for movement between opened and closed positions, said box defining an inner box width; wherein said upper lid portion includes a lid back panel, a lid front panel, and a lid top panel. The inner packaging container includes a generally rectangular box having a dispensing opening with a resealable closure; wherein the rectangular box includes a front panel, a back panel, a top panel, a bottom panel, and opposing side panels; wherein each said side panel includes an inner panel and an outer panel, said inner panel having a first width defining a width of the inner packaging container, and said outer panel including at least a portion having a second width defining a width greater than the first width. The second width is greater than the inner box width in one embodiment. The inner packaging container is insertable within said outer packaging container.

(5) According to another embodiment, a blank for forming an inner packaging container for insertion into a hinged lid box comprises a front panel defined by a first pair of parallel first and second score lines and a second pair of parallel third and fourth score lines; a bottom panel connected to the front panel along the first score line and further including first top and first bottom flaps connected at top and bottom score lines; an outer left side panel connected to the front panel

along the third score line; an outer right side panel connected to the front panel along the fourth score line; a top panel connected to the front panel along the second score line and further including second top and second bottom flaps connected at top and bottom score lines and a fifth score line parallel to the second score line; a back panel connected to the top panel along the fifth score line and further including a sixth score line parallel to the fifth score line thereby forming a third pair of parallel score lines, and a fourth pair of parallel seventh and eighth score lines; an inner left side panel connected to the back panel along the seventh score line; an inner right side panel connected to the back panel along the eighth score line; and a glue flap connected to the back panel along the sixth score line. The inner left and right side panels have a first width defining a width of the inner packaging container and at least a portion of said outer left and right side panels have a second width greater than the first width.

Description

BRIEF DESCRIPTION OF THE DRAWING FIGURES

- (1) FIG. 1 shows a perspective view of the pack in a fully folded closed state.
- (2) FIG. 2 shows a planar view of the outer packaging container blank in an unfolded state.
- (3) FIG. 3 shows a perspective view of the inner packaging container in a fully closed state.
- (4) FIG. 4 shows a planar view of the inner packaging container blank in an unfolded state.
- (5) FIG. 5 shows a perspective view of the pack in an open state during loading of the inner packaging container within the outer packaging container.
- (6) FIG. 6 shows a perspective view of the pack in a closed state with the inner packaging container fully loaded within the outer packaging container.
- (7) FIGS. 7A-7E show the pack during erecting, folding, gluing and loading of the inner packaging container within the outer container packing.
- (8) FIG. 8 is a detail view of one of the side panels of the inner box of a preferred embodiment.

DETAILED DESCRIPTION

- (9) Referring to FIGS. 1 and 3, a pack **300** is described herein, the pack **300** comprising an outer packaging container (outer box) **100** having an inner packaging container (inner box) **200** therewithin. When the pack **300** is adapted for containing discrete portions of smokeless tobacco, the outer box is configured preferably smaller than a traditional cigarette hinged lid box and can have a height of about 3 inches, a width of about 2 inches and a depth of about $\frac{3}{4}$ inch. The inner box is sized to fit snugly in the outer box as described below. As used herein in connection with dimensions, “about” means $\pm 10\%$.
- (10) The pack **300** is adaptable for containing other articles, such as smoking articles, in which case the overall dimensions may mimic customary dimensions of existing hinge lid boxes.
- (11) Outer packaging container **100** is preferably a hinged lid type of container formed from a paper or paperboard blank. As best shown in FIG. 2, the blank for outer packaging container **100** comprises a front panel **10**; a back panel **20**; a left side panel **30** connected between a side edge of the back panel **20** along a longitudinal fold line **23** and a side edge of the front panel **10** along a longitudinal fold line **25**; a right side panel **40** connected to an opposite side edge of the front panel **10** along another longitudinal fold line **24**; and a glue flap **45** connected to an opposite side edge of the back panel **20** along longitudinal fold line **22**. When folded, as described in greater detail below, glue flap **45** is glued to an inner surface of side panel **40** to form a rectangular shape. As used herein, the term “glued” should be understood to include any type of gluing, securing, thermal sealing or otherwise adhering one surface to an opposing surface.
- (12) The outer packaging container **100** further includes an inner top closure panel **60** connected to the back panel **20** along a transverse fold line **26**; an outer top closure panel **50** connected to the front panel **10** along a transverse fold line **27**; an inner bottom closure panel **70** connected to the

back panel **20** along a transverse fold line **28**; and an outer bottom closure panel **80** connected to the front panel **10** along a transverse fold line **29**. When folded, inner top closure panel **60** is adhered to an inner surface of outer top panel closure panel **50** and inner bottom closure panel **70** is adhered to an inner surface of outer bottom closure panel **80**.

(13) Outer packaging container **100** also comprises upper and lower dust flaps **12**, **16** connected to left side panel **30** along upper and lower transverse fold lines **31**, **32**, respectively, and upper and lower dust flaps **14**, **18** connected to right side panel **40** along upper and lower transverse fold lines **33**, **34**, respectively.

(14) As mentioned above, outer packaging container **100** is preferably a hinged lid type of container in that a pivotable hinged lid portion **90** is provided in order to gain access to the contents therein. In order to obtain this functionality from a one-piece blank, the blank is pre-cut to define the perimeter of hinged lid portion **90**. As best illustrated in FIG. 2, hinged lid portion **90** is preferably formed by cut line **91** along glue flap **45**, cut line **92** along side panel **30**, cut line **93** across the front panel **10** which defines the hinged lid front panel **96** thereabove, and cut line **94** along side panel **40**. Cut lines **91**, **92**, **93** and **94** that define the hinge lid include “nicks” or “breaks” **802** at spaced locations such that correlated adjoining panels remain connected through folding, gluing, erecting and loading, until the consumer chooses to break open the lid of a completed pack **300**. In addition, a score line **95** is provided along back panel **20** to define the hinge between the upper lid back panel **97** and the lower portion of the back panel **20** such that the hinged lid portion **90** is pivotal about score line **95**. The outer box is not limited to the exact shape and angles illustrated for hinged lid portion **90**, as one skilled in the art will appreciate that other configurations of the same are possible. For example, the cut extending across front panel **10** and defining the front panel of hinged lid portion may optionally include a semi-circular cut-away portion **98** below cut line **93** so as to form a thumb notch (cutaway) region allowing easy opening of hinged lid portion **90**; the cut line **93** preferably extends straight across the front panel. Any other configuration may be used.

(15) The outer blank **100** is a blank configuration which is laterally folded and “glued” to form the intended box structure.

(16) As best shown in FIG. 4, a paper or paperboard blank for inner packaging container **200** comprises a front panel **110**; a back panel **120**; a top panel **130** connected between a top edge of the back panel **120** along a longitudinal fold line **125** and a top edge of the front panel **110** along a longitudinal fold line **123**; a bottom panel **140** connected to a bottom edge of the back panel **120** along another longitudinal fold line **122**; and a glue flap **145** connected to a bottom edge of the front panel **110** along longitudinal fold line **124**. When folded, as described in greater detail below, glue flap **145** is adhered to an inner surface of the bottom panel **140** to form a rectangular shape.

(17) The inner packaging container blank **200** further includes an inner side closure left panel **160** connected to the back panel **120** along a longitudinal fold line **126**; an outer side closure left panel **150** connected to the front panel **110** along a longitudinal fold line **127**; an inner side closure right panel **170** connected to the back panel **120** along a longitudinal fold line **128**; and an outer side closure right panel **180** connected to the front panel **110** along a longitudinal fold line **129**. When folded, inner side closure left panel **160** is adhered to an inner surface of outer side closure left panel closure panel **150** and inner side closure right panel **170** is adhered to an inner surface of outer side closure right panel **180**.

(18) Inner packaging container blank **200** also comprises left and right side dust flaps **112**, **116** connected to bottom panel **140** along left and right longitudinal fold lines **131**, **132**, respectively, and left and right dust flaps **114**, **118** connected to top panel **130** along left and right longitudinal fold lines **133**, **134**, respectively.

(19) Inner packaging container blank **200** further comprises a dispensing door **192** which is provided to allow access and removal of the contents within inner packaging container **200**. Door **192** is formed by establishing the perimeter thereof preferably with a score line **195** located

partially across a central portion of the upper back panel **120** and with a perforated cut line **193** into central portions of the front and top panels **110** and **130** of the inner packaging container blank **200**, as shown best in FIGS. **3** and **4**. As illustrated therein, fold lines **123**, **125** extend across door **192** and the score line **195** is provided along a rear edge of door **192**, thus allowing door **192** to be opened and reclosed in a foldable manner. In one embodiment, the dispensing door **192** is also covered by a resealable label **198**, thereby permitting inner packaging container **200** to be resealed after the initial opening by the consumer. Resealable label **198** may comprise a single layer of polymer material and include a permanently tacky material on one side thereof, permanent bonding adhesive, or the like, permitting repeated opening and closing of dispensing door **192**, or any other suitable reclosing mechanism. Preferably, a permanent bonding adhesive may cover the undersurface of label **198** which superposes the door **192**, and, preferably, edge portions of the label **198** beyond the edges of dispensing door **192** are provided with a peel-and-reseal adhesive sufficient to maintain a sealed closure.

(20) Alternatively, the door **192** may be an opening of the same or comparable perimeter of lines **195** and **193**, covered only by a label **198**.

(21) The left and right outer side closure panels **150**, **180** of the inner packaging container **200** have an upper side width “W1” that is slightly greater than the lower side width “W2” thereof. The upper side width W1 of the left and right side closure panels **150**, **180** is also slightly greater than the side width “W3” of the left and right inner side closure panels **160**, **170**, the width W3 thereof preferably being substantially equal to width W2. Moreover, the upper side width W1 of the left and right side closure panels **150**, **180** is also slightly greater than the inner width defined within outer packaging container **100**. As a result of the slightly greater width W1 of the upper portion of the left and right outer side closure panels **150**, **180**, when inner packaging container **200** is folded, glued and sealed, the inner packaging container **200** comprises rearwardly projecting flanges **190**, as best shown in FIGS. **3** and **5**. The projecting flanges **190** cooperate with other features of the box **100** to assure and retain a complete closure of the lid **90** of the outer packaging container **100**.

(22) More particularly, in one preferred embodiment, flanges **190** have a gradually increasing width from W2 to W1 which feature facilitates insertion of an erected inner box into an erected outer box. Referring now to FIG. **8**, preferably, each outer side panel **150**, **180** includes from top to bottom: an operative flange portion **400** of a width W1; a transition portion **402** and a lower portion **404** of a width W2. Preferably, the operative flange portion includes straight, rear flange edge **408** which extends from a rounded, upper rear corner portion **406** of the side panels **150**, **180** to the inclined edge **410** of the transition portion **402**. The length of the straight flange edge **408** (or the flange portion **400**) may be adjusted both as to relative position and/or length so as to achieve a desired biasing effect regardless of variations in relative dimensions and materials of a particular pack **300**. Generally, a longer flange edge **408** will increase biasing force against the inner surfaces of the lid during and upon reclosure of the lid. In the preferred embodiment, the operative flange portion **400**, the transition portion **402** and the lower portion **404** are of essentially equal length (from a direction of top to bottom of the pack **300**).

(23) The flange portion **400** and its biasing action also serve in essence to “lock” the inner box **200** within the outer box **100** with a friction fit such that the inner box **200** remains steadfast during handling by the consumer, even when the lid has been opened and product is removed. In addition, a small amount of adhesive (not shown) can be applied between the exterior surface of the bottom of the inner box **200** and the interior surface of the bottom of the outer box **100** to further assure the desired positioning of the inner box **200** within the outer box **100**.

(24) Preferably, both the outer box **100** and the inner box **200** are constructed of 12 or 14 point paper board, preferably 12 point board is used for the inner box **200** and 14 point board is used for the outer box **100**. Most preferably, a laminated or metalized board is used in the construction of the inner box **200**, which promotes product stability and shelf life and serves as a barrier against transfer of adhesives, inks or other agents from either of the boxes to the product to be contained

therein.

(25) In a preferred embodiment, the outer box has a height of about 3 inches, a width of about 2 inches and a thickness of about $\frac{3}{4}$ inch, more preferably $2\frac{15}{16}$ inches $\times$ 2 inches $\times$ $\frac{11}{16}$ inch. The hinge lid **90** can have a height of about 1 inch at the front of the outer box and the hinge line at the rear of the box can be located about $1\frac{3}{4}$ inches from the bottom of the outer box. To snugly fit within the outer box, the inner box preferably has a height of about $2\frac{13}{16}$ inches, a width of about $1\frac{7}{8}$ inches and a thickness of about $\frac{5}{8}$ inch. The inner box **200** preferably holds about fifteen portions of smokeless tobacco. The door **192** can have a width of about $1\frac{1}{4}$ inches at hinge line **195** and length of about $1\frac{1}{2}$ inches from the hinge line **195** to a free end of the door. The door is more narrow at the free end with side edges tapering inward 4 to 5° and joining the free end at rounded corners having a radius of about $\frac{3}{8}$ inch. The flanges **190** preferably have a length of about $1\frac{1}{4}$ inches and extend outwardly from the rear of the inner box by about $\frac{1}{16}$ to $\frac{1}{8}$ inch and ends of the flanges are rounded with a radius of about $\frac{1}{8}$ inch.

(26) In a preferred embodiment, the inner box **200** is approximately of a same height as that of the outer box **100** (with accommodation for the layers of board at the upper and lower panels of the outer box **100**). It is envisioned that with the inclusion of flanges **190** (or comparable arrangement to bias an upper edge portion of the inner box **200**), the inner box **200** may be of a height less than that comparable to the outer box **100**.

(27) Referring to FIG. 5, when inner packaging container **200** is loaded into outer packaging container **100** during manufacture or after a consumer removes the inner packaging to remove product therein and then places the inner packaging back in the outer packaging, the rearwardly projecting flanges **190** engage the back panel **20** near the side panels of the outer packaging container **100** close to fold lines **22** and **23**. The engagement of the rear flanges **190** with the back panel of the outer packaging container **100** causes the upper portion of inner packaging container **200** to be biased forward toward the front panel **10** of the outer packaging container **100**. As a result, when the hinged-top portion **90** of the outer packaging container **100** is reclosed, the inside face of the front lid panel **96** slidingly engages upper front face portion **97** of the inner box **200** such that position of the inner packaging container **200** assists in securing and maintaining the hinged-top portion **90** in a closed position, as shown in FIG. 6. The width **W1** can be selected as desired to define a width greater than width **W2** and the inner width within outer packaging container **100**, so long as inner packaging container **200** can still be inserted within outer container **100** and the hinged lid top portion **90** maintains the desired closed position.

(28) A method of making the pack **300** according to one embodiment is described below.

(29) Referring to FIG. 7A, a flat blank for the inner packaging container blank **200** is provided and the resealable label **198** is disposed over the dispensing door **192**. As shown in FIG. 7B, inner packaging container blank **200** is folded by first pre-breaking fold lines **124**, **125** and then folding the blank 180° along fold lines **123** and **122** so as to form a collapsed, erectable structure **701**. In so doing, the outer surface of glue flap **145** is glued to the inner surface of bottom panel **140**. Inner packaging container blank **200** is then erected from the collapsed, erectable structure **701** by, for example, squeezing the top and bottom surfaces to erect the box **701** into an open, rectangular structure **702**. Alternatively, the open, rectangular structure **702** can be obtained by applying suction to the front and back surfaces of the collapsed, erectable structure **701** alone or in combination with the squeezing. One side of the open, rectangular structure **702** is then also folded and glued to form a partially closed structure **703**. In the illustrated embodiment, dust flaps **116** and **118** are folded along fold lines **132** and **134**, respectively, and then an outer surface of right side inner closure panel **170** is glued to an inner surface of right side outer closure panel **180** so as to seal the right side of the inner packaging container blank **200**.

(30) Product is then loaded into the partially closed structure **703** through the remaining open side of the structure **703**, for example, the left side as in the illustrated embodiment. The open side of the container is then sealed in a similar manner by folding the dust flaps and side closure panels. In

the illustrated embodiment, for example, dust flaps **112**, **114** are folded along fold lines **131**, **133**, respectively, and then an outer surface of left side inner closure panel **160** is glued to an inner surface of left side outer closure panel **150** so as to completely seal inner packaging container **200** and the contents therein. Although a preferred practice in an embodiment includes closing one side of the inner box before insertion of product, it is envisioned that product could be inserted before closure of either side.

(31) It is to be noted that the erection of the inner blank **200** is in a “longitudinal” sense, i.e. the end panels are rotated during erection.

(32) Referring to FIG. 7C, the outer packaging container blank **100** is folded and glued. More particularly, in one embodiment, glue flap **45** is glued to an inner surface of side panel **40** to form a collapsed erectable structure **710**. The outer container is then formed into an open rectangular structure **712** by, for example, squeezing the opposing sides of the erectable structure **710**.

Alternatively, the open rectangular structure **712** can be obtained by applying suction to the front and back surfaces of the collapsed erectable structure **710** alone or in combination with the squeezing. Dust flaps **16** and **18** are then folded inwardly along fold lines **32** and **34**, respectively. Inner bottom closure panel **70** is folded inwardly along fold line **28** and an outer surface thereof is glued to an inner surface of outer bottom panel closure **80** which is folded inwardly along fold line **29**, thereby closing one end of the open structure **712** to form a partially closed structure **714**. It is to be noted that the erection of the outer blank **100** is “lateral” or “transverse” in that the side panels are rotated during erection. Thereafter, as schematically shown in FIG. 7D, sealed inner packaging container **200** is loaded into the one open end of outer packaging container **100**, such as the top end of outer packaging container **100**. The top end of outer packaging container **100** is then closed and glued. More particularly, in one embodiment, dust flaps **12** and **14** are folded inwardly along fold lines **31**, **33**, respectively. Inner top closure panel **60** is folded inwardly along fold line **26**, outer top closure panel **50** is folded inwardly along fold line **27**, and an outer surface of inner top closure panel **60** is glued to outer top closure panel **50**, thereby forming finished pack **300**. As shown in FIG. 7E, cut lines **91-94** (with nicks) formed in the blank for outer packaging container **100** form hinged lid portion **90** which is openable by the consumer by breaking the nicks to gain access to the inner packaging container **200**. Inner packaging container **200** includes, in turn, dispensing door **192** which, in one embodiment, is repeatedly openable and closable by way of resealable label **198**.

(33) The box structure of the pack **300** and its manner of erection and loading provides: a resealable feature which prolongs freshness; the resealable flap **198** that may be pressed against opposing portions of the top panel of **130** to assure adhesion and may be reinforced by the board structure of the door **192**; the inclined edge **410** of the flanges **190** of the inner box **200** facilitates insertion of the inner box **200** into the outer box **100** during packing; having one of the boxes **100**, **200** erectable in a lateral sense (e.g. box **100**) and the other being erectable in a longitudinal sense (e.g. box **200**), assures rectangularity in the pack **300** once the pack **300** has been fully assembled; and the flanges **190** bias an upper front edge portion of the inner box **200** against an inner front surface of the lid during and after reclosure so as to assure a complete reclosure and to maintain it fully closed (the avoidance of a “smile” along the lid line).

(34) While the above pack and the method of packaging have been described in detail with reference to specific embodiments thereof, it will be apparent to those skilled in the art that various changes and modifications can be made, and equivalents employed, without departing from the scope of the appended claims.

Claims

1. A pack for consumer goods comprising: an outer box including, a box portion, and a lid portion flexibly connected to the box portion and configured to move between an open position and a

closed position, the lid portion including, a lid back panel, a lid front panel that is parallel with the lid back panel, and a lid top panel; and an inner box within the outer box, the inner box defining a dispensing opening, the inner box including, a front panel, a back panel that is parallel with the front panel and the lid back panel, a top panel that is parallel with the lid top panel, a bottom panel that is parallel with the top panel, and opposing side panels, the opposing side panels including, a first set of the opposing side panels, the first set of opposing side panels including, a first inner panel connected to a first edge of the back panel, and a first outer panel connected to a first edge of the front panel, the first outer panel including, a first operative flange portion having a first width and a first length, a first lower portion having a second width and a second length, the second width being less than the first width, the second length being the same as the first length, and a first transition portion joining the first operative flange portion and the first lower portion, the first transition portion having a third length, the third length being the same as the second length, and a second set of the opposing side panels, the second set of opposing side panels including, a second inner panel connected to a second edge of the back panel, and a second outer panel connected to a second edge of the front panel, the second outer panel including, a second operative flange portion having a third width and a fourth length, a second lower portion having a fourth width and a fifth length, the fourth width being less than the third width, the fifth length being the same as the fourth length, and a second transition portion joining the first operative flange portion and the first lower portion, the second transition portion having a sixth length, the sixth length being the same as the fifth length.

2. The pack of claim 1, wherein the dispensing opening extends along the top panel and the front panel of the inner box.
3. The pack of claim 2, wherein the dispensing opening is accessible when the lid portion of the outer box is in the open position.
4. The pack of claim 1, wherein the dispensing opening includes a resealable closure.
5. The pack of claim 4, wherein the resealable closure includes a label having a tacky surface.
6. The pack of claim 4, wherein the resealable closure includes a label including polymer material.
7. The pack of claim 4, wherein the resealable closure includes a label including bonding material on a surface thereof, the label adhered to the back panel of the inner box.
8. The pack of claim 4, wherein the resealable closure includes a label, at least part of the label between the top panel of the inner box and the lid top panel when the lid portion is in the closed position.
9. The pack of claim 4, wherein the resealable closure includes a label, and the label covers the dispensing opening when the lid portion is in the closed position.
10. The pack of claim 1, wherein the inner box is comprised of laminated board.
11. The pack of claim 1, wherein the inner box is comprised of metalized board.
12. The pack of claim 1, wherein the inner box further includes dust flaps connected to the top panel.
13. The pack of claim 1, wherein the inner box is comprised of 12 or 14 point board.
14. The pack of claim 1, wherein the dispensing opening includes round corners.
15. The pack of claim 1, wherein the dispensing opening has a width at least one half of a width of the inner box.
16. The pack of claim 1, wherein the inner box is adhered to the outer box.
17. The pack of claim 1, wherein the inner box contains smoking articles.
18. The pack of claim 1, wherein the inner box contains smokeless tobacco products.
19. The pack of claim 1, wherein the inner box is friction fit inside the outer box.
20. The pack of claim 1, wherein the first inner panel has a single width.
21. The pack of claim 20, wherein the single width of the first inner panel is a fifth width, the fifth width being less than the first width.
22. The pack of claim 21, wherein the fifth width is the same as the second width.

23. The pack of claim 21, wherein the second inner panel has a single width.
 24. The pack of claim 23, wherein the single width of the second inner panel is a sixth width, the sixth width being less than the third width.
 25. The pack of claim 24, wherein the sixth width is the same as the fourth width.
-