

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404717
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Smith; Stephen P. et al.

Cordless retractable roller shade for window coverings

Abstract

A cordless retractable shade including an operating system for the shade that varies a biasing force of a spring to counterbalance the shade. The bottom rail of a retractable shade can be raised or lowered, and due to the operating system remains in any selected position of the covering between fully extended and fully retracted, without the use of operating cords. The system includes a method of negating and reversing the spring bias effect at a strategic position whereby the flexible vanes of the shade can be adjusted between open and closed.

Inventors: Smith; Stephen P. (Denver, CO), Smith; Kent A. (Broomfield, CO), Rhodes; Galen B. (Henderson, CO), Winters; Stephen M. (Erie, CO), Faller; Kenneth M. (Thornton, CO)

Applicant: Hunter Douglas Inc. (New York, NY)

Family ID: 47756786

Assignee: Hunter Douglas Inc. (New York, NY)

Appl. No.: 18/089254

Filed: December 27, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230138944 A1	May. 04, 2023

Related U.S. Application Data

continuation parent-doc US 17152005 20210119 US 11566469 child-doc US 18089254
continuation parent-doc US 16042995 20180723 US 10907406 20210202 child-doc US 17152005
continuation parent-doc US 15155304 20160516 US 10030439 20180724 child-doc US 16042995
continuation parent-doc US 14240304 US 9353570 20160531 WO PCT/US2012/052514 20120827

Publication Classification

Int. Cl.: **E06B9/32** (20060101); **E06B9/24** (20060101); **E06B9/262** (20060101); **E06B9/264** (20060101); **E06B9/322** (20060101); **E06B9/38** (20060101); **E06B9/40** (20060101); **E06B9/44** (20060101); **E06B9/56** (20060101); **E06B9/80** (20060101); **E06B9/90** (20060101)

U.S. Cl.:

CPC **E06B9/322** (20130101); **E06B9/24** (20130101); **E06B9/262** (20130101); **E06B9/264** (20130101); **E06B9/38** (20130101); **E06B9/40** (20130101); **E06B9/44** (20130101); **E06B9/56** (20130101); **E06B9/80** (20130101); **E06B9/90** (20130101); E06B2009/2435 (20130101)

Field of Classification Search

CPC: E06B (9/322); E06B (9/24); E06B (9/262); E06B (9/264); E06B (9/38); E06B (9/40); E06B (9/44); E06B (9/56); E06B (9/80); E06B (9/90); E06B (2009/2435)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
778660	12/1903	Hadden	N/A	N/A
1416071	12/1921	Smurr	N/A	N/A
1786512	12/1929	Whitworth	N/A	N/A
4346749	12/1981	Singletary et al.	N/A	N/A
4427050	12/1983	Toppen	N/A	N/A
5078198	12/1991	Tedeschi	N/A	N/A
5437324	12/1994	Sternquist	N/A	N/A
5996923	12/1998	Junquera	N/A	N/A
6467714	12/2001	Rasmussen	N/A	N/A
6470951	12/2001	Tao	N/A	N/A
6782938	12/2003	Colson et al.	N/A	N/A
7546866	12/2008	Strand et al.	N/A	N/A
7549455	12/2008	Harper et al.	N/A	N/A
8186413	12/2011	Fujita et al.	N/A	N/A
8210230	12/2011	Glasi	N/A	N/A
8662139	12/2013	Anthony et al.	N/A	N/A
8752607	12/2013	Anderson et al.	N/A	N/A
8800633	12/2013	Mullet et al.	N/A	N/A
8807196	12/2013	Mullet et al.	N/A	N/A
9353570	12/2015	Smith et al.	N/A	N/A
11566469	12/2022	Smith	N/A	E06B 9/264
2001/0001414	12/2000	Colson et al.	N/A	N/A
2002/0189771	12/2001	Colson et al.	N/A	N/A

2004/0182526	12/2003	Strand et al.	N/A	N/A
2005/0269041	12/2004	Anderson et al.	N/A	N/A
2006/0137837	12/2005	Costello et al.	N/A	N/A
2006/0162876	12/2005	Kwak	N/A	N/A
2008/0223532	12/2007	Auger	N/A	N/A
2009/0223641	12/2008	Cheng	N/A	N/A
2010/0018656	12/2009	Fujita et al.	N/A	N/A
2010/0122780	12/2009	Cheng	N/A	N/A
2014/0096920	12/2013	Macdonald	N/A	N/A
2014/0216666	12/2013	Smith et al.	N/A	N/A
2015/0082706	12/2014	Rejc	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101641488	12/2009	CN	N/A
20 2009 001 070	12/2008	DE	N/A
H03-16400	12/1990	JP	N/A
H0-6559	12/1993	JP	N/A
HEI 8-028168	12/1995	JP	N/A
HEI 8-049484	12/1995	JP	N/A
2004-238827	12/2003	JP	N/A
2006-257865	12/2005	JP	N/A
4017040	12/2006	JP	N/A
2009-102916	12/2008	JP	N/A
2009-155892	12/2008	JP	N/A
4355741	12/2008	JP	N/A
2011-038340	12/2010	JP	N/A
M322459	12/2006	TW	N/A

OTHER PUBLICATIONS

Opposition filed Nov. 22, 2017 in related Japanese Patent No. 6145093 (71 pages). cited by applicant

English translation of Opposition filed Nov. 22, 2017 in related Japanese Patent No. 6145093 (93 pages). cited by applicant

English translation of Office Action issued in related Japanese Patent Application No. 2016-230841 (3 pages). cited by applicant

PCT International Search Report and Written Opinion dated Nov. 6, 2012, PCT Application No. PCT/US2012/052314, 15 pages. cited by applicant

Office Action dated Aug. 13, 2018, issued in related Taiwanese Patent Application No. 106116777, 8 pages. cited by applicant

List of Patents or Patent Applications Treated as Related dated Dec. 27, 2022, 2 pages. cited by applicant

Primary Examiner: Stephan; Beth A

Attorney, Agent or Firm: Dority & Manning, P.A.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The application is a continuation of U.S. application Ser. No. 17/152,005 filed Jan. 19, 2021, which is a continuation of U.S. application Ser. No. 16/042,995 filed Jul. 23, 2018, now U.S. Pat. No. 10,907,406, issued Feb. 2, 2021, which is a continuation of U.S. application Ser. No. 15/155,304, filed May 16, 2016, now U.S. Pat. No. 10,030,439, issued Jul. 24, 2018, which is a continuation of U.S. application Ser. No. 14/240,304, filed Feb. 21, 2014, now U.S. Pat. No. 9,353,570, issued May 31, 2016, which is a 371 of international patent application No. PCT/US2012/052514, filed Aug. 27, 2012, which claims the benefit of priority under 35 U.S.C. § 119(e) to U.S. Application No. 61/527,820, filed Aug. 26, 2011, which are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(1) The present disclosure relates generally to retractable shades for architectural openings and more particularly to such a shade that does not include operating or lift cords, but rather is operable between selected extended conditions of the shade by manual movement of the bottom rail of the shade.

BACKGROUND

(2) Retractable shades have been popular for many years and generally extend across or are retracted from covering architectural openings such as windows, doorways, archways, and the like. Such retractable coverings may include a roller rotatably supported with a shade material suspended therefrom. The shade material can either be wrapped about the roller when retracting the shade or unwrapped from the roller when extending the shade.

(3) Some retractable coverings such as Venetian blinds do not have a shade material that wraps around or unwraps from a roller, but rather a rotatable shaft in the head rail that is adapted to wrap or unwrap lift cords thereabout. The lift cords generally may extend downwardly through the slats of the blind to a bottom rail to raise or lower the bottom rail when retracting or extending the blind.

(4) Many retractable coverings are operated with flexible operating cords which may extend, for example, downwardly through the shade material to the bottom rail of the covering from the head rail and be operated from free ends of the cords. The free ends of the cords may be exposed adjacent to one end of a head rail for manipulation of an operator.

(5) Operating and pull cords can be an issue with retractable coverings, as in some instances the cords may become tangled and difficult to use, fray or break, damage the covering from repeated wear, and may sometimes form loops that may present a risk to users.

SUMMARY

(6) The cordless retractable shade of the present disclosure includes an operating system that applies a counterbalancing force to support the shade element at any level of extension selected by the user. Where the shade includes operable vanes, the operating system may also include a vane orientation mechanism. The vane orientation mechanism allows the user to position the vanes in an open orientation, or in a closed orientation.

(7) The present disclosure includes an operating system configured to act on a collapsible shade element rotatably positioned in a head rail. The collapsible shade element is connected along its upper edge to the roller for wrapping about and unwrapping therefrom. The shade material includes vertically suspended front and rear sheets of flexible translucent or transparent material, such as sheer fabric, and a plurality of horizontally extending, vertically spaced flexible vanes preferably of a translucent or opaque material. The vanes are secured along front and rear edges to the front and rear sheets along horizontal lines of attachment. The front and rear sheets are attached to the roller at circumferentially spaced locations so that pivotal movement of the roller moves the front and rear sheets vertically relative to each other to shift or rotate the vanes gradually between closed and open positions.

(8) In the closed position the front and rear sheets are spaced close together and the depth dimension of vanes are aligned generally parallel to or along the direction of the front and rear

sheets. When positioned in an architectural opening, the depth dimension of the closed vanes would extend generally vertically in coplanar contiguous relationship with the front and rear sheets. In the open position, the front and rear sheets are spaced apart by a distance defined by the depth of the vanes, and the vanes are generally perpendicular to the front and rear sheets. When positioned in an architectural opening, the depth dimension of the open vanes would extend generally horizontally. The vanes are in the closed position when wrapped around the roller, and when extended from the roller to the fully extended position.

(9) A bottom rail may be secured to the lower edge of the shade element with bottom edges of the front and rear sheets of the shade material secured along front and rear edges of the bottom rail.

(10) An operating system is provided that includes a biasing element (or also a biasing component) operably engaged between the head rail and the roller to apply a counterbalancing force to the roller that allows the shade element to be positioned in any location between fully retracted and fully extended. The configuration of the operating system is designed to increase the tension in the biasing element (i.e. increase the spring load where a spring is utilized), as the roller is rotated in the direction to extend the shade element. This increased load in the bias element is then converted by the operating system to apply a rotational force to the roller in the direction of retracting the shade element. To do this, in the operating system the bias element is operably engaged between the head rail and the roller in order to convert the load in the bias element into a rotational bias applied to the roller. The operating system could be oriented to create the operating bias in the direction of extension if desired.

(11) The rotational bias applied to the roller is a counterbalancing force to compensate for the increasing weight of the shade as the shade extends. The force increases with the extension of the shade because the bias element in the operating system develops an increasing load as the shade extends. As the shade retracts, the load on the bias element decreases and the rotational bias force decreases. The counterbalancing force created in the operating system may be set to fully support the shade element in any position, or it may be set to have a greater or lesser level. In some scenarios, the counterbalancing force co-acts with the friction in the operating system to combine together to provide sufficient rotational force to support the shade in any position of extension. The operating system may apply a slight rotational bias to the roller in the fully retracted position.

(12) A vane orientation stop structure is another aspect of the disclosure that may either be used independent of or in combination with the operational system described herein. The vane orientation stop structure operates on the fully extended shade element to allow the vanes to be positioned in at least a fully opened position even where the rotational bias of the operating system is acting on the roller. The vane orientation stop structure may be implemented in the operating system and specifically in conjunction with the drive mechanism.

(13) In one example of the operating system, the biasing component is a spring motor in the form of a coil spring positioned inside the roller to extend along a portion of the roller's length. One end of the coil spring is operably connected to the roller at a fixed location for unitary rotation therewith. An opposite end of the coil is movably connected to the roller for unitary rotation with the roller and reversible translation along the length of the roller. The movable end of the coil spring is driven or moved by a drive system or drive mechanism that includes a longitudinally extending threaded shaft fixed to the head rail so that the roller can rotate thereabout. A nut connected to the movable end of the coil spring is operably mounted on the threaded shaft for reversibly translatable movement along the length of the threaded shaft upon rotation of the roller. As the roller rotates, the nut moves along the threaded length of the shaft and also along the length of the roller. Movement of the nut along the shaft causes the coil spring to extend (placing tension and bias in the spring) or retract (relieving such tension and bias) depending upon the direction of movement of the nut. The spring generally retains a degree of extension, even with the shade in the fully retracted position, so as to at least slightly bias the bottom rail, through the operating system, upwardly toward the head rail. Movement of the bottom rail downwardly away from the head rail

causes the roller to rotate, which thereby causes the nut to extend the spring and increase the rotational bias or force applied to the roller. Movement of the bottom rail upwardly toward the head rail causes the nut to move toward the fixed end of the coil spring to reduce the bias of the spring. (14) The coil spring thereby assists an operator in raising the bottom rail. A predetermined amount of friction is built into the system via the inter-relationship of the nut to the threaded shaft so as to help retain the bottom rail at any displaced relationship from the head rail. The amount of built-in friction is determined by the variable operative strength of the spring at various displacements of the bottom rail from the head rail.

(15) The fixed position of the first end of the spring is further adjustable between predetermined fixed positions so that the effective strength of the coil spring can be set for a predetermined size and weight of shade material to thereby cooperate with the built-in friction in assuring the bottom rail remains in any predetermined position.

(16) In another example of the present disclosure, the operating system may include a biasing element in the form of a spring motor including a clock spring structure. The spring motor in this example may include one or more counter-balancing spring motors. The counter-balancing motors in this example may include a spring that may provide a counter-balancing force against the weight of the shade. The counter-balancing motors may include one anchored or fixed member and one rotatable member, with a clock spring operably connected to each the anchored member and the rotatable member. The rotatable member may be keyed to the roller, such that as the roller rotates, such as to extend or retract the shade, the rotatable member may rotate therewith. Because one end of the spring is anchored and one end is connected to the rotatable member, the spring may be wound around itself as the roller rotates to extend the shade (which builds up tension in the spring) and the spring may be unwound as the roller rotates in the opposite direction to retract the shade (which reduces the tension in the spring). Varying the number of spring windings by rotating the roller correspondingly changes a biasing force exerted by the spring, which acts to balance the load exerted by the shade in substantially any position of the shade.

(17) In a general depiction of the disclosure herein, a cordless retractable shade is described, which includes a shade element, a rotatable roller operably connected to the shade element, whereby the shade element is wrapped around the roller when in a retracted configuration, and is at least partially unwrapped from around the roller when in an at least partially extended configuration. A biasing component is operably associated with the roller and configured to exert a variable biasing force on the roller to counterbalance a weight of that portion of the shade element at least partially extended from the roller. The biasing component is configured to apply greater amounts of force to the roller as greater amounts of the shade element is extending from the roller. The biasing component engages the roller with sufficient biasing force to support the shade for at least one amount of shade extension from the roller, and may support the shade in many positions of extension.

(18) Additionally to this first example, the cordless retractable shade includes a non-rotatable element operably associated with the roller, wherein the biasing component further comprises a spring operably connected between the roller and the non-rotatable element. Rotation of the roller in a first direction increases a biasing force exerted by the spring on the roller, and rotation of the roller in a second direction decreases the biasing force exerted by the spring on the roller.

(19) With respect to the general depiction of the disclosure here, a vane orientation stop mechanism may be provided. In this vane orientation stop mechanism, the shade component includes a front sheet, a back sheet, and at least one vane positioned between the front sheet and back sheet, the vane engaging the front sheet along a front edge and engaging the back sheet along a rear edge. The roller is operably engaged with the front sheet and back sheet to transition the vane from a closed configuration to an open configuration when substantially the entire shade element is extended from the roller. A vane orientation stop mechanism is operably engaged with the biasing component, the vane orientation stop mechanism is operable to selectively engage the roller in at

least one orientation where the at least one vane is oriented in an open configuration.

(20) Additionally, the vane orientation stop mechanism may define more than one engagement position, each corresponding to a discrete open configuration of the at least one vane.

(21) With respect to a first example of the disclosure, and based on the general depiction provided above, a first end of the spring is operably connected to the roller at a fixed position, and the second end of the spring is reversibly translatable along at least a portion of a length of the roller, wherein as the second end of the spring translates along a portion of the length of the roller, the spring extends or retracts to vary the biasing force exerted by the spring on the roller.

(22) A head rail may rotatably receiving the roller, and a drive mechanism is adjacent to the second end of the spring for reversibly moving the second end along the length of the roller upon rotation of the roller. The drive mechanism is operably connected to the head rail. There is a predetermined amount of friction between selected relatively movable parts of the shade.

(23) The drive mechanism may include a nut operably mounted on the non-rotatable shaft, the nut movable along the length of the non-rotatable shaft upon rotation of the roller. The nut may be keyed to the roller to rotate therewith.

(24) The non-rotatable shaft is a threaded shaft fixed relative to the head rail and extending longitudinally thereof, and the movable connector is fixed to one end of the spring with the opposite end of the spring fixed relative to the roller. The movable connector has an internal thread received on the threaded shaft for both rotation about the threaded shaft and translation there along. The movable connector translates along the length of the threaded shaft upon rotation of the roller to vary the effective length of the spring. There may be an abutment formed on the threaded shaft adapted to engage the internal thread to limit translating movement of the movable connector in one direction.

(25) A vane orientation stop mechanism may be associated with this first example of the disclosure herein. The vane orientation stop mechanism is adjacent to the abutment to releasably retain the movable connector adjacent to the abutment. The vane orientation stop mechanism may include a releasably directed end of the thread on the threaded shaft against which an end of the internal thread on the movable connector stationarily abuts. The end of the internal thread on the movable connector defines a releasably directed end of the internal thread, wherein each of the releasably directed ends forms a respective tab. Each respective tab extends at a reverse angle to the respective thread. The transition from the thread on the threaded shaft to the tab forms a first apex, and the transition from the thread on the movable connector to the tab forms a second apex. The relative movement between the movable nut and the threaded shaft causes the first apex to pass the second apex where the tab on the threaded shaft engages the tab on the movable connector.

(26) The first example of the disclosure herein also may include a bottom rail including a front edge and a rear edge, the shade element including a front sheet and a rear sheet, each of the front and rear sheets having bottom edges operably connected respectively to the front and rear edges of the bottom rail, and a plurality of horizontally extending vertically spaced flexible vanes operably connected to the front and rear sheets along respective front and rear edges thereof. Tilting the bottom rail to raise or lower the front and rear edges moves the vanes between a closed vertically oriented position and an open substantially horizontal position.

(27) A second example of the disclosure herein, based on the general depiction provided above, includes a first end of the spring operably connected to the roller in a manner to resist radial movement relative to an axis of the roller. The second end of the spring is operably connected to the roller to rotate with the roller, and is positioned at a location spaced at least radially from the first end. The rotation of the second end of the spring in conjunction with the roller acts to coil or uncoil the spring to vary the biasing force exerted by the spring on the roller.

(28) Additionally, a head rail may rotatably receiving the roller, and an elongated member, which may be an elongated shaft or rod, may be operably connected with the head rail in a non-rotatable manner and positioned within the roller. The first end of the spring defines an anchor and engages

the elongated member. The second end of the spring may be rotationally keyed with the roller. The elongated member extends along at least a portion of the length of the roller. The anchor may be an arbor for connecting to the first end of the spring. The second end of the spring may engage a housing, and the housing may be rotationally keyed to the roller.

(29) Further to this second example of the disclosure, the spring may be a clock spring having a radially inner end and a radially outer end. The first end is the radially inner end, which is operably secured in a rotationally stable manner with the roller, and the second end is the radially outer end. The clock spring is received in a housing, and the housing is attached to the radially outer end, and keyed with the roller. The arbor is received in an open center of the clock spring and attached to the radially inner end. The arbor is connected to the shaft in a non-rotatable manner.

(30) Additionally to the second example of the disclosure herein, the shaft defines a threaded outer portion extending along a portion of the length of the shaft. A screw limit nut is keyed to the roller such that rotation of the roller rotates the screw limit nut to translate the nut along a threaded portion of the non-rotatable shaft. A stop is disposed on the non-rotatable shaft and engages the screw limit nut at an end point of travel along the threaded portion of the non-rotatable shaft, end point is substantially corresponding to the full extension of the shade material from the roller.

(31) The stop may include a protrusion extending radially outward from a surface of the non-rotatable shaft, the protrusion configured to engage a knuckle disposed on the screw limit nut when the screw limit nut reaches the end point. When the screw limit nut is adjacent the end point, the roller may be further rotated to open the shade and to thereby move the screw limit nut such that a center of the knuckle moves over the protrusion to thereby hold the roller in place. The stop may include a collar fixed to the non-rotatable shaft, the collar and the screw limit nut together having a detent structure configured to engage when the screw limit nut reaches the end point. The detent structure engages when the roller rotates to open the shade.

(32) The detent structure includes a pin disposed on the screw limit nut, the pin configured to engage a groove disposed on the collar. The detent structure may alternatively include a pin disposed on the collar, the pin configured to engage a groove disposed on the screw limit nut. The detent structure may alternatively include a molded spring disposed on the screw limit nut, the molded spring configured to engage a groove disposed on the collar. The detent structure may alternatively include a leaf spring disposed on the screw limit nut, the leaf spring configured to engage a groove or recess disposed on the collar. The detent structure may include a pin disposed on the screw limit nut, the pin configured to engage a plurality of grooves disposed on the collar.

(33) A method of using the operating system aspect of the disclosure includes a method for counterbalancing the load of a shade element extending from a roller shade structure comprising the steps of unrolling the shade element to a desired extended position by rotating the roller in a first direction, creating an amount of biasing force in an operating system by rotation of the roller in a first direction, applying the amount of biasing force to the roller in a second direction opposite the first direction, wherein the amount biasing force sufficient to counterbalance the load of the shade element.

(34) The amount of biasing force may be sufficient to maintain the shade in the selected extended position, or it may be less or more than the amount needed to maintain the shade in the selected extended position. Additionally, a predetermined level of friction may be created between components of the operating system, wherein the amount of biasing force in addition to the friction is sufficient to maintain the shade in the selected extended position. The biasing force may be a spring motor, which in turn may be a coil spring or a clock spring.

(35) Further, the shade element may include a shade element extending from a roller shade structure, where the shade element includes a front sheet, a rear sheet, and at least one vane connected along a front edge to the front sheet and along a back edge to a back sheet, where the relative motion of the front and rear sheets move the at least one vane between open and closed orientations. In this case, the method comprises the steps of unrolling the shade element to a fully

extended position, with at least one vane in a closed orientation; further rotating the roller in a first direction to cause the front sheet and back sheet to move relatively to orient the at least one vane in an open position; and engaging a vane orientation stop mechanism to overcome the biasing force and hold the roller in position to maintain the open orientation of the at least one vane.

(36) This summary of the disclosure is given to aid understanding, and one of skill in the art will understand that each of the various aspects and features of the disclosure may advantageously be used separately in some instances, or in combination with other aspects and features of the disclosure in other instances.

(37) Other aspects, features and details of the present disclosure can be more completely understood by reference to the following detailed description of a preferred embodiment, taken in conjunction with the drawings and from the appended claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is an isometric of a retractable shade in accordance with the present disclosure in a fully extended open position with vanes adjusted to allow light to pass through and mounted within an architectural opening shown in dashed lines.
- (2) FIG. 2 is an isometric similar to FIG. 1 with the shade partially retracted.
- (3) FIG. 3 is a front elevation of the shade of FIG. 1 in a fully extended position, and the horizontal vanes in the open position to allow light to pass through.
- (4) FIG. 4 is a front elevation of the shade in the partially retracted position of FIG. 2.
- (5) FIG. 5 is an enlarged fragmentary section taken along line 5-5 of FIG. 3.
- (6) FIG. 6 is an enlarged fragmentary section taken along line 6-6 of FIG. 4.
- (7) FIG. 7A is an enlarged section taken along line 7-7 of FIG. 3.
- (8) FIG. 7B is a section similar to FIG. 7A showing the bottom rail.
- (9) FIG. 7C is a section similar to FIG. 7B showing the bottom rail and vanes slightly tilted.
- (10) FIG. 8 is an enlarged section taken along line 8-8 of FIG. 3.
- (11) FIG. 9 is an enlarged fragmentary section taken along line 9-9 of FIG. 4.
- (12) FIG. 10 is a fragmentary isometric showing the left end cap of the head rail and the roller connected thereto.
- (13) FIG. 11A is an isometric showing the threaded screw mounted on the left end cap.
- (14) FIG. 11B is an isometric of the coil spring and other components of the operating system of the present disclosure.
- (15) FIG. 12 is an exploded view of the operating system shown in FIG. 11 B.
- (16) FIG. 13 is an isometric showing the drive mechanism for the operating system.
- (17) FIG. 14 is an exploded isometric of the mechanism shown in FIG. 13.
- (18) FIG. 15 is an enlarged fragmentary section taken along line 15-15 of FIG. 5.
- (19) FIG. 16 is a further enlarged section taken along line 16-16 of FIG. 15.
- (20) FIG. 17 is a further enlarged section taken along line 17-17 of FIG. 15.
- (21) FIG. 18 is an isometric looking at the threaded end of the nut portion of the drive mechanism.
- (22) FIG. 19 is a section taken along line 19-19 of FIG. 18.
- (23) FIG. 20 is a section taken along line 20-20 of FIG. 18.
- (24) FIG. 21 is an enlarged fragmentary section taken along line 21-21 of FIG. 5.
- (25) FIG. 22 is a fragmentary section taken along line 22-22 of FIG. 21.
- (26) FIG. 23 is a section similar to FIG. 21 showing a system and a tool for adjusting the fixed end of the coil spring.
- (27) FIG. 24 is a section taken along line 24-24 of FIG. 23 with the tool having been inserted a further distance.

(28) FIG. 25 is a section similar to FIG. 5 showing another example of the disclosure.

(29) FIG. 26 is a section similar to FIG. 6 of the example of FIG. 25.

(30) FIG. 27 is an exploded isometric of the example of FIGS. 25 and 26.

(31) FIG. 28 is an exploded isometric of the example of FIGS. 25-27 showing the operating system connection to the end caps.

(32) FIG. 29 is a plan view of an architectural opening having a shade mounted therewith in a partially extended configuration.

(33) FIG. 30 is a plan view of an architectural opening having a shade mounted therewith in a fully extended configuration.

(34) FIG. 31 is an exploded view of an example of the present invention utilizing a counter balancing spring motor in the form of a clock spring.

(35) FIG. 32 is a section taken along line 32-32 of FIG. 29.

(36) FIG. 33 is a section taken along line 33-33 of FIG. 30.

(37) FIG. 34 is an enlarged perspective view of an open end of a roller.

(38) FIG. 35 is a hub that is received in an open end of the roller.

(39) FIG. 36 is a threaded post forming part of one of the examples of the drive mechanism of the operating system.

(40) FIG. 37 is a section taken along the line 37-37 of FIG. 30.

(41) FIG. 38 is a perspective view of a counter balancing unit in the form of a piano spring.

(42) FIG. 39 is an exploded view of the counter balancing unit of FIG. 38.

(43) FIG. 40 is a section taken along the line 40-40 of FIG. 38.

(44) FIG. 41 is an end view of an anchor.

(45) FIG. 42 is a perspective view of the anchor.

(46) FIG. 43 is an end view of the anchor from the opposite end than FIG. 41.

(47) FIG. 44 is a section similar to that of FIG. 37.

(48) FIG. 45 is a perspective view of a screw limit nut.

(49) FIG. 46 is a perspective view of a shade having a vane orientation limit stop, and having part of the shade cut away.

(50) FIG. 47 is an enlarged partial view of a vane orientation stop mechanism such as that shown on FIG. 46.

(51) FIG. 48 is an enlarged partial view of a vane orientation stop, similar to that of FIG. 47.

(52) FIGS. 49A-49D are schematic representations of the engagement of a portion of the screw limit nut and a protrusion forming part of the vane orientation stop configuration of FIG. 46.

(53) FIG. 50 is an exploded view of a shade including another example of the vane orientation stop.

(54) FIG. 51 is a representative section of the roller tube, the drive mechanism and counter balancing units shown in FIG. 50.

(55) FIG. 52 is a representative section similar to that of FIG. 51, wherein the vane orientation limit stop is positioned to one end.

(56) FIG. 53 is a section view similar to that of FIG. 37.

(57) FIG. 54 is a perspective view of a counter balancing unit having a spacer positioned thereabout.

(58) FIG. 55 is a section view similar to that of FIG. 37.

(59) FIG. 56 is a perspective view of a nut structure.

(60) FIG. 57 is a perspective view of a collar.

(61) FIG. 58 is a schematic representation of a pin having engaging a detent recess formed on a portion of the collar of FIG. 57.

(62) FIG. 59 is a schematic representation of another example of pin engaging a detent recess formed on a portion of the collar of FIG. 57.

(63) FIG. 60 is a perspective view of a shade having another example of a vane orientation limit stop, and having part of the shade cut away.

(64) FIG. **61** is an enlarged section view taken along line **61-61** of FIG. **60**.

(65) FIG. **62** is an enlarged partial view of the vane orientation stop structure of **61** with the pin engaging a recess.

(66) FIG. **63** is a section view taken along line **63-63** of FIG. **62**.

(67) FIG. **64** is a plan view of a collar having recess structures for the detent engagement of a vane orientation limit stop, and showing the angle on the face of the collar.

(68) FIG. **65** is a perspective view of a shade having another example of a vane orientation limit stop, and having part of the shade cut away.

(69) FIG. **66** is an enlarged view of the vane orientation stop mechanism of FIG. **65**.

(70) FIG. **67** is a reverse angle perspective of the vane orientation limit stop mechanism of FIG. **66**.

(71) FIG. **68** is a perspective view of a shade having another example of a vane orientation limit stop, and having part of the shade cut away.

(72) FIG. **69** is a section taken along line **69-69** of FIG. **68**.

(73) FIG. **70** is a perspective view of a shade having another example of a vane orientation limit stop, and having part of the shade cut away.

(74) FIG. **71** is a section taken along line **71-71** of FIG. **70**.

DETAILED DESCRIPTION

(75) The present disclosure provides a retractable covering that includes a counterbalance that allows the shade material to be stopped at a number of different locations, selected by the user, along a drop length of the shade. Conventional cordless operating systems may generally have a finite number of stop positions for the extension of the shade and/or generally may be limited to shades in which the only function is to raise and lower, and are not capable of adjusting the graduated amount of light passing through the shading when in the fully extended position. As such, these systems are not capable of operating shades with a plurality of tiltable horizontal vanes. However, the covering and operating system of the present disclosure may provide for a shade that may vary light passage there through when in the fully extended position, as well as be positionable at substantially any position between full extension and full retraction.

(76) Referring to FIGS. **1** and **2**, the retractable shade **30** of the present disclosure is a cordless roll-up shade including a head rail **32**, a bottom rail **34**, and a flexible shade material **36** extending therebetween. The shade material includes vertically suspended front **44** and rear **45** sheets of flexible translucent or transparent material, such as sheer fabric, and a plurality of horizontally extending, vertically spaced flexible vanes **46**. The vanes are preferably of a translucent or opaque material and are secured along front and rear edges to the front and rear sheets along horizontal lines of attachment. However, in other instances, the shade material may be substantially any type of material, such as but not limited to: woven, non-woven, knits, or the like. Additionally, the shade may be non-translucent or opaque, or may include a combination of opaque and translucent or semi-translucent materials.

(77) The front and rear sheets are attached to a roller **42** at circumferentially spaced locations (see FIG. **7A**) so that pivotal movement of the roller, when the shade is fully extended, moves the front and rear sheets vertically (relative to each other) to shift the vane material between open and closed positions. Rotation of the roller causes the shade material in its closed position of FIG. **2** to wrap around or unwrap from the roller depending upon the direction of rotation. In the closed position of the shade material, the vanes extend vertically in coplanar contiguous relationship with the front and rear sheets. The front and rear sheets are relatively close together in the closed configuration. In the open position of FIG. **1**, the front and rear sheets are horizontally spaced with the vanes extending substantially horizontally therebetween.

(78) The shade includes an operating system whereby an operator of the shade can manually lift or lower the bottom rail of the shade and leave it in any desired position between and including fully retracted and fully extended and it will maintain this position until moved again. The operating system for maintaining the extension of the shade in a desired position between fully retracted and

fully extended may include many different types of counter-balancing units, or also referred to as biasing components. For example, a coil spring (one example of a counter balancing spring motor) operably associated with the operating system and extending laterally (to create a counter balancing spring force to hold the desired position of the shade) within the roller positioned in the head rail may be used. A piano spring oriented orthogonally to the lateral extension of the roller, and positioned inside the roller, may alternatively be used as a counter balancing spring motor or unit. In addition, the horizontal vanes may be tilted to control the amount of light passing through the shade. The shade does not require an operating cord or cords, and so may reduce risk presented to children, infants, or animals.

(79) Before describing the details of the system, it is felt helpful to understand that in a retractable shade of the type described in detail hereafter, the effective weight of the shade material increases as the shade is extended. In some embodiments described herein, in order to maintain the bottom rail at any desired position between fully retracted and fully extended, a system combining the friction of relatively movable parts within the operating system and the strength and spring rate of a spring motor (which may be, for example, a coil biasing spring **38** or other type of spring structure, such as a clock spring) in the head rail **32** are utilized. In one example, the spring motor is mounted in relation to the head rail, and the operating system is designed to increase the load on the spring motor (thus increasing the bias force in the spring) as the bottom rail **34** is lowered (which increases the effective weight of the shade material extended off the roller). To complement the bias force of the spring motor, a predetermined coefficient of friction is built into relatively moving parts of the operating system of the shade so that the friction within the system, in combination with the bias force of the coil spring, will equal, overcome or generally counterbalance the gravity force acting on the bottom rail and shade material, so that the bottom rail will remain positioned at any user selected location between fully retracted and fully extended. In other words, the biasing force (biased towards retracting the shade) exerted by a counterbalancing spring motor may counter the effective force exerted by the shade, and as the effective weight of the shade varies, the biasing force may also vary. This may allow the counter-balancing spring motor to balance the weight of the shade to hold the shade at substantially any position along an extension length of the shade. Note that the counterbalance properties of the spring motor in the operating system may either include the effects of the friction in the operating system, or it may not include the effects of the friction in the operating system. Also, the term “counterbalance” is interpreted to include creating a force equal to the load caused by the extended shade, or a force less than or greater than, the force equal to the load, unless defined explicitly or by clear intention otherwise. Additionally, it should be noted that the shade element utilized with the operating system does not need to have operable vanes. The operating system can be implemented to provide a counterbalancing bias force roller used with many different shade elements that are rolled up on a roller. In this instance, the vane orientation stop mechanism(s) as described below would simply not be utilized.

(80) As will be appreciated with the description hereafter, the bias force of the spring motor is also adjustable as a fine-tuning mechanism to complement the fixed built-in friction of the system. Alternatively or additionally, the system may include single springs, multiple springs or other counter-balancing units or spring structures to complement the friction of the system, and to achieve the desired counterbalance against the weight of a selected shade. As used herein, the spring motor utilized in the operating system may also be referred to as a bias component or bias element, or variations thereof.

(81) As can be appreciated by reference to FIGS. **1** and **2**, the retractable shade **30** is shown mounted within an architectural opening **40** which is illustrated as a window opening, but could be a doorway, archway, room dividers, or the like. The shade material illustrated could be any one of numerous, flexible materials that can be wrapped on or unwrapped from a roller **42**. The shade material may be shifted from the open position of FIG. **1** to the closed position of FIG. **2** upon initial rotation of the roller as will be described in more detail hereafter. Reverse movement of the

shade material from the closed position of FIG. 2 to the open position of FIG. 1 may be accomplished by opposite rotation of the roller under the force of a spring motor or motors.

(82) FIGS. 3 and 4 are front elevations of FIGS. 1 and 2, respectively, and show diagrammatically components of the operating system for the shade 30 in dashed lines.

(83) FIG. 5 is a section taken along line 5-5 of FIG. 3 and is therefore a horizontal section through the head rail 32 with the roller 42 and an operating system being shown. FIG. 6 is a section similar to FIG. 5 taken along line 6-6 of FIG. 4 therefore illustrating the retractable shade 30 with a portion of the shade material 36 wrapped about the roller within the head rail.

(84) Referring to FIGS. 7A and 7B, the roller 42 is shown as a two-part roller having an inner component 48 that is cylindrical in nature with a plurality of radiating longitudinally extending ribs 50 around its periphery. The larger of the ribs are sized to support the inner component 48 concentrically within an outer component 52 of the roller. The outer component 52 is also generally cylindrical in configuration, with the outer component having a pair of diametrically opposed longitudinally extending channels 54 formed therein that open through the outer surface of the outer component through a relatively small slot 56. The opposed channels 54 are provided to anchor the upper edges of the front 44 and rear 45 sheets, respectively, of the shade material. For example, an anchor strip 58 may be used to secure the fabric, such as by forming a loop in the upper edge of the sheets of material, inserting the loop into an associated channel of the outer roller component and inserting the anchor strip to render a connection of the associated sheet with the associated channel in the roller. Alternatively, the shade may be glued, sewed, or otherwise connected to the anchor strip and/or roller with or without the channels 54.

(85) FIG. 8 is a section similar to FIG. 7A taken at a different location along the length of the roller 42, but again illustrating the two-component roller and the connection of the shade material 36 thereto. As can be appreciated from FIGS. 7A, 7B and 8, the shade material is shown in its open position with the front 44 and rear 45 sheets of material being separated and the vanes 46 disposed substantially horizontally therebetween. It can be appreciated, however, that if the roller were to rotate 90 degrees in either direction, the front and rear sheets of the shade material would move vertically relative to each other and into closer adjacent relationship. If the roller is rotated 180 degrees or more, in a counter-clockwise direction, the flexible vanes would be substantially vertically oriented in a vertical plane and in a horizontally stacked relationship with the front and rear sheets as seen, for example, in the closed position of the covering of FIG. 9.

(86) FIG. 9 is a vertical section through the head rail 32 showing the shade material 36 partially wrapped about the two-component roller 42. As will also be appreciated by referencing FIGS. 7A-9, the bottom rail 34 is horizontally disposed when the shade material is open as shown in FIGS. 7A and 8 but may become substantially vertically oriented when the shade material is closed (FIG. 7C) as when the front and rear sheets are shifted vertically relative to each other upon a 180 degree rotation of the roller.

(87) With reference to FIGS. 10 and 15, the two-component roller 42 is shown with some parts removed to illustrate the inner cylindrical component 48 mounted within outer cylindrical component 52. The inner cylindrical component is abutted against a splined hub or bearing 60 mounted on a left bearing plate 61 of an end cap 62 of the head rail 32. The two-component roller 42 is rotatable relative to the left bearing plate 61 and head rail 32. The outer component 52 of the roller, in the completed assembly, may extend over the inner component, as well as the hub or bearing, so as to have its end generally contiguous with the inner surface of the left end wall of the head rail, albeit in sliding relationship therewith.

(88) The outer cylindrical component 52 extends the full width of the shade fabric. However, the inner cylindrical component 48 need only be sufficiently long to contain the full length of the spring 38, as shown in more detail below.

(89) One example of the operating system for the retractable shade of the present disclosure is shown in FIGS. 11-22. Referring first to FIG. 11, the spring motor or biasing component, in this

example an elongated coil spring **38**, used to variably counterbalance at least a portion of the weight of the shade material **36** is seen. It should be noted, that in other examples, a counterbalancing spring motor having one or more counter-balancing spring motors may be used to counterbalance the weight of the shade (see, for example, FIGS. **32** and **33**).

(90) In this example, the spring may extend along a portion of the length of the inner cylindrical component **48**, and is disposed within the component **48**. The effective length of the coil spring when the shade is extended is shown in FIG. **11 B**, which is contrasted with its at-rest length shown in FIG. **11A** (no spring is shown in FIG. **11A**, however the end piece **104** represents the position of the end of the spring). Thus, the tension and effective roller bias force of the spring is varied with the length of the spring caused by the actuation of the operating system. For instance, referring to FIG. **11 B**, when the shade is extended to its fullest extent, the left end of the spring **38** is moved to the left end of the roller (loading the spring) while the right end of the spring remains anchored. As can be seen in FIGS. **11** and **12**, the spring has a fixed end connector **64** (also referred to as a non-rotatable element) at its right end, which fixed connector **64** is axially fixed in position by engagement with the inner wall of the inner component **48** of the roller **42**, as described in more detail with respect to FIGS. **21-24**. This non-rotatable element is thus fixed in position relative to the head rail and the roller. And as seen in FIG. **11**, the spring has a movable end connector **66** (also referred to as the actuatable end) at its left end that moves along the threaded shaft upon rotation of the roller, which extends the spring **68** upon extension of the shade, and shortens the length of the spring **68** upon retraction of the shade. It should be appreciated for purposes of the present disclosure that a left hand mount or end cap is illustrated, but as will be evident to those in the art and from the following description, a right hand mount would be the mirror image thereof. The non-rotatable element is an anchor against which the spring motor acts, in this example, to increase the bias force. The static position of the fixed connector is referenced herein as being relative to the head rail. It is contemplated that the fixed end of the spring motor may be attached to a structure outside the head rail, such as a wall or frame of an architectural opening as non-limiting examples, and result in the same effect of anchoring an end of the spring motor. Having the anchor position on or in the head rail allows the shade to be a self-contained unit not relying on attachment or affixation with anything outside the head rail.

(91) The movable end connector **66** may be a nut with both the fixed **64** and movable **66** end connectors supporting a portion of the spring **38** in a connective manner. This connection configuration allows the spring to be extended or retracted without losing its grip on the fixed and movable end connectors. For example, in this configuration the grooves **106** on movable end connector **66** and the grooves **124** on the fixed end connector **64**, as described in more detail below, are sized and oriented to receive the spiral winding of the spring **38** along at least a portion of the length of the grooves on the connector to secure the relative ends of the spring **68** to each of the fixed **64** and movable **66** end connectors.

(92) With reference to FIG. **13**, which is exploded in FIG. **14**, the movable end connector **66**, as mentioned above, is a nut that is adapted to be reversibly translated, as the roller is rotated, along the fixed threaded shaft **68**. The threaded shaft **68** is fixably mounted to the left end cap **62** of the head rail **32** on an inwardly directed hub **70** fixed with the bearing plate **61** on the left end cap. The hub **70** may be integral with the bearing plate **61** as shown, or may be a separate component piece attached to the bearing plate **61** by a fastener. The hub **70** defines a set of longitudinally extending radiating ribs **72** adapted to be received in corresponding grooves (not seen) in a cylindrical body **76** of the threaded shaft. The receiving grooves in the cylindrical body **76** cooperate with the ribs **72** on the hub **70** to act as a key between the cylindrical body **76** and the hub **70** to prevent the threaded shaft from rotating by fixing the shaft **68** relative to the hub **70** and the left end cap **62** of the head rail **32**.

(93) The outer hub or bearing sleeve **60** fits over the threaded shaft **68** and has a generally cylindrical passage **84** there through. The bearing walls forming the passage **84** define an end wall

85 at its innermost end (i.e. the end positioned away from the end cap **62**) through which the passage **84** extends, but with a reduced diameter inner end **92**. The end wall defines a plurality of ribs **90** that extend axially relative to the bearing **60** from the end wall **85**, and also extend radially to just short of the outer wall of the bearing **60**. The hub **60** defines a plurality of longitudinally-extending outwardly radiating ribs **86** around its cylindrical body **88** which are substantially alignable (see FIG. **10**) with the external longitudinally extending radial ribs **50** on the inner component **48** of the roller **42**. An open left end of the inner roller component **48** is received onto seated upon the plurality of ribs **90** on the reduced diameter inner end **92** of the bearing sleeve **60** with the radiating ribs **90** on the reduced diameter inner end supporting the inner surface of the inner roller component **48** in abutting axially aligned contiguous relationship with the bearing sleeve. The outer wall of the bearing **60** and the outer wall of the roller component **48** may be flush with one another. The bearing sleeve **60** is therefore rotatably seated on the outer surface of the cylindrical body **76** at one end of the threaded or screw shaft **68** so as to rotate with the roller and relative to the fixed screw shaft **68**.

(94) The cylindrical body **76** of the threaded shaft extends (inwardly) from the face **78** and has a reduced diameter cylindrical surface **79** (FIG. **14**). An annular groove **94** is formed in the cylindrical surface a short distance from the face **78**. The annular groove **94** is adapted to releasably receive a retaining C-clip **96** for retaining the components during the assembly process. A complement of spherical bearing (see FIGS. **14** and **15**) elements **93** are positioned in an annular cavity **95** formed between lateral face **78** of the screw shaft **68** and lateral face **97** inside the bearing sleeve **60**, and between horizontal lower face **79** (inner race) and horizontal upper face **81** (outer race) formed on the inside of the bearing sleeve **60**. The spherical bearing elements **93** transfer axial thrust loads created by the spring tension, while providing minimal rotational friction between outer bearing **60** and screw shaft **68**.

(95) As best appreciated in FIGS. **13-20**, the threaded shaft **68** continues to extend axially and inwardly away from the left end cap **62** from the innermost end of the cylindrical body **76** and has a large thread **98** formed thereon. The thread **98** has a relatively large thread pitch (also a low thread count) so that the movable connector **66** can rotate relatively easily and move axially the desired distance per rotation of the roller. The thread **98** on the shaft terminates in a particular manner at its outermost end adjacent to the bearing **60** as will be described hereafter. At a predetermined spacing from the outermost end **100** (the end adjacent the end cap **62**) of the thread **98**, a radial abutment stop **102** is formed on the outer surface of the cylindrical body of the shaft **68**, which stop **102** engages the movable connector **66** to keep it from further rotating (which generally defines the limit of extension of the shade since the roller can no longer rotate). This is explained in more detail below.

(96) With reference to FIGS. **12-20**, the movable connector or nut **66** may have a relatively long cylindrical body **104** with external threads **106** extending along the length of the hollow cylindrical body **104** to a stopping location spaced from a generally circular enlarged head **110**. FIGS. **18-20** show the movable stop **64** in perspective and cross-section views to show the features described herein. The generally circular head **110** has four circumferential flat surfaces to facilitate the use of wrench type tools during assembly of the nut **66** and spring **38**. The external thread **106** is adapted to receive and be threaded into the spiral wound left end of the coil spring **38** so that the coil spring is mounted on and fixed to the movable connector **66**. The left end of the spring and the movable connector **66** thereby become joined for unitary rotation and translation with each other. A cylindrical passage **112** through the movable connector **66** has a single thread **114** (FIG. **15**) formed at its outermost end within, adjacent to, or aligned with the body or head **110**. This thread **114** is adapted to mate with the external thread **98** on the threaded shaft **68** so that as the roller rotates about the shaft **68**, the movable connector rotates with the roller and moves along the length of the shaft **68**. Thus, the relative rotation between the movable connector **66** and the shaft **68** causes the movable connector **66** to translate along the length of the shaft in the direction dictated by the

direction of rotation of the roller and the threads **98**. The head **110** on the movable connector has diametrically opposed ribs **116** (see FIGS. **16** and **18**) adapted to be received in diametrically opposed internal grooves **118** formed in the inner component **48** of the roller **42** as seen in FIGS. **7**, **9**, **16** and **18**. The internal grooves extend along at least a portion of the length of the inner component roller **48**, and are extend linearly. The length of extension of the internal grooves is sufficient to allow for the movable connector **66** to move with the end of the spring **38** from its length when the shade is retracted to its length when the shade is extended. This assures that the movable connector will rotate in unison with the roller during operation of the shade but can translate along the length of the roller (along the length of the internal grooves) as it is rotated about the threaded shaft.

(97) As will be appreciated from the above, as the roller **42** rotates with its support bearing **60** at the left end thereof, it causes the movable connector **66** to rotate about the fixed threaded shaft **68** and also translate along the length of the shaft **68**, which causes the coil spring **38** to be lengthened or shortened thereby affecting the axial bias of the spring. The threaded shaft **68** may be axially compressed in the direction towards, and against, the rotatable bearing **60** due to the thrust forces created by the spring tension, with the compression force of the spring being exerted at least in part along the fixed shaft between the movable nut **66** and the fixed nut **64**. The spring thus biases the movable nut **66** (as the spring extends) towards the fixed nut **64**. The threaded shaft is secured to the left end cap so as not to be rotatable relative to the head rail **32**. Accordingly, rotation of the roller **42** around the fixed threaded shaft **68** will effect controlled translation of the movable connector **66** along the shaft and affect the axial bias of the coil spring. For instance, the axial bias of the spring **38** will relatively increase as the spring is extended (shade is extended), and relatively decrease when the spring is shortened (shade is retracted).

(98) The counter balancing spring motor in this first example is the spring **38**, which acts through the movable connector **66** to apply a biasing force to the roller **52** in the direction to urge the roller **52** to rotate in the direction of retracting the shade. From the fully extended position, the movable connector is urged by the tension in the spring **38** toward the fixed connector **64**. The tension force applied to the movable connector **66** urges it to rotate along the threads **98** of the shaft **68** toward the fixed connector. The movable connector **66** thus rotates around the shaft **68** as it translates along its length. Since the movable connector **66** is rotationally keyed to the roller, yet free to translate relative to the roller, the rotation of the movable connector **66** urges the roller to rotate in the direction to retract the shade. The force applied by the counter balancing spring motor may or may not be sufficient to cause the roller to rotate independently of a user lifting the bottom rail. The drive mechanism of the operating system of this first example may include the shaft **68**, the spring **38**, the fixed nut **64**, and the movable nut **66**, or any subcombination thereof. The shaft **68** is fixed to the head rail, and the end of the spring **38** attached to the movable nut **66** is slidably attached to the roller. In this way, the driving mechanism biases or urges roller **52** and shade **44** in the retracting direction. The spring **38** of the operating system is indirectly connected to the roller **52**, through the movable nut **66** rotating as it moves along the shaft **68**, and thus indirectly applies a biasing or urging force to the roller **52**.

(99) As is best appreciated by reference to FIGS. **15-20**, a shaft or screw limit stop mechanism is shown and described. When the roller **42** is rotating in a direction that causes the movable connector **66** to translate toward the left end cap **62** (the shade is extending), thereby tensioning and effectively lengthening the coil spring **38**, the movement of the movable connector **66** it is limited by the abutment stop **102** protruding radially from the threaded shaft **68**. The abutment stop **102** may be formed on the threaded shaft **68** spaced away from the terminal end of the thread **98** so as to be positioned at an outermost end **120** of the internal thread **114** of the movable connector (see FIG. **17**) when the internal thread **114** and abutment stop **102** are engaged. When the portion of the thread **114** of the moveable connector **66** engages the abutment stop **102** and the movement of the connector **66** is halted, the other end **122** of the single thread **114**, as best seen in FIG. **17**, becomes

aligned near or at the end **100** of the thread **98A** on the threaded shaft **68**. The shaft or screw limit stop includes the abutment stop **102** extending outwardly from the threaded shaft **68**. This shaft or screw limit stop interferes with the rotation of the thread **114** formed on the inside surface of the movable connector **66**. This position denotes the full extension of the shade.

(100) A vane orientation stop mechanism is described with reference to FIGS. **17** and **19**. A terminal thread **98A** is formed at the end portion of thread **98**. A knuckle **123** is formed in thread **98A**, at or near the terminus of thread **98**, that defines an apex or transition in the thread direction, and at which the thread **98A** reverses direction or angle at least a slight amount. The portion of thread **98A** that extends beyond the knuckle **123** and that is in the reverse direction from the balance of thread **98** before the knuckle is defined as the end tab. The end tab **125** of the thread **98A** is angled back towards the previous extensions of thread **98**. In this manner, the terminal thread **98A** defines the knuckle **123** that defines an apex directed towards the end of the shaft **68**.

(101) The internal threads **114** defined on movable nut **66** have corresponding features defined thereon to aid in the operative engagement with the knuckle **123** and tab **125** on the thread **98** of the shaft **68**. The thread **114** defines a knuckle **114A** (FIG. **19**), at which point a terminus portion of the thread **114** forms a tab **114B** with an angle slightly reversed from the earlier extension of thread **114**. The knuckle **114A** and the tab **114B** are shaped and formed similarly to that described with respect to the knuckle **123** and tab **125** on thread **98**.

(102) When the knuckle **114A** passes knuckle **123** (FIG. **17**) as the movable connector rotates near the end of its travel, the end tab **125** on thread **98** will come into engagement with the tab **114B** on thread **114**, and the respective reverse angles at which each tab extends forms an over-center latch or position that anchors or resists the movement of the movable connector **66** back towards the fixed nut under the tension of the spring **38** (retraction of the shade). This is because beyond the respective knuckles **123**, **114A**, the end tab portions **125**, **114B** of the threads **98**, **114** angle in a direction reverse to the direction of the rest of the thread **98** and **114**. The position of the knuckle **114A** and tab **114B** on the movable nut **66** in an orientation to connect with the end tab **125** thus interferes with the rotation of the roller in a direction to retract the shade from the fully extended position. So, as the movable connector **66** translates towards the left end cap **62**, and the single thread **114** is aligned with the end **100** of the thread **98A**, the knuckle **123** and tab **126** (which is reversed in a spiral direction from the rest of the thread) defines a seat. The seat defined by the knuckle **123** and tab **125** encourages the movable connector or nut **66**, when knuckle **114A** and tab **114B** are positioned at the seat to remain in the over-center position past the knuckle **123**. In other words, the reversed direction of the spiral thread at the knuckle **123** near the end **100** of the shaft, as shown in FIG. **17**, provides an over-center relationship between the movable connector and the thread on the shaft to selectively and releasably hold the movable connector in position under the tension of the spring **38**. This also corresponds generally with the position of the maximum bias provided by the coil spring **38**, which also generally corresponds with the limit of the extension of the shade. Also, when the thread **114** engages the end tab **125** and is held in that bottom-most position by the tension applied by the spring **38**, the thread **114** may also be in contact with the abutment stop **102**. At this bottom position, the bottom rail is oriented so as to cause the front and back sheets to move relative to one another and become spaced apart, which orients the vanes in a relatively horizontal (or open) position, such as the orientation shown, for instance, in FIG. **7B**. The knuckle **123** formed on the thread **98** is included in the vane orientation stop mechanism, which causes the thread **114** to engage the end tab **125** and holds the vanes in an open position. Other examples of the vane orientation stop mechanism described above are provided below.

(103) The movable connector **66** is selectively and releasably prevented from reversing direction due to the engagement of the end **122** of its thread **114** with the reversed end tab **125** on the main thread **98** of the shaft **68**, which is positioned past the knuckle **123** (FIG. **17**). Movement of the roller **42** in an opposite direction causes the internal thread **114** of the movable connector as viewed in FIG. **17** to move over the knuckle off its over-centered relationship with the end **100** of the

thread **98A** on the shaft **68** to allow the roller to retract the shade with the assistance of the spring tension. During the retraction of the roller, the movable connector **66** begins to rotate and follow the thread on the shaft back towards the fixed connector **65**.

(104) Rotation of the roller **42** in a forward or rearward direction is caused by creating downward tension on either the front **44** or back **45** vertical sheets of the shade material (FIG. 7), respectively. This may be accomplished by a user pressing down on the front or back edge of the bottom rail **34**, which is attached respectively to the bottom edges of the front **44** and back **45** vertical sheets. In other words, the operator can place the shade in an extended position with the vanes open by pulling down on the back edge of the bottom rail, which rotates roller **42** to its limit and places the end tab **125** portion of the thread **98A** into the over-centered and seated position (FIG. 17). In the over-centered and seated position, the thread **98** negates or resists the bias exerted by the spring that may otherwise rotate the roller tube in a direction to cause the orientation of the bottom rail to change and the vanes to close.

(105) When the vanes are open in this bottom-most over-center position, the operator can push down on the front of the bottom rail, effectively tensioning panel **44** and causing the roller **42** to rotate in a direction which turns connector **66** and overcomes the rotational resistance created in the over-center seated position. This causes the vanes to close. The angle of the thread **98** before the knuckle **123** is relatively steep, and the reverse angle of the thread **98A** forming the tab **125** after the knuckle **123** may be relatively steep or shallow. The apex of the knuckle itself may be rounded, to allow the movable connector **66** to disengage as selectively desired by the user by pulling down on the front edge of the bottom rail, as is described below. The angle of the thread **114** before the knuckle **114A** is relatively steep, and the reverse angle of the thread forming the tab **114B** after the knuckle **114A** may be relatively steep or shallow. The apex of the knuckle **114A** itself may be rounded. The over-centered position can thus be overcome relatively easily to allow retraction of the shade. Note that the thread angle before and after the knuckle on either of the threads **98** or **114** is not limited to that described or shown herein.

(106) When the shade is lifted as by raising the bottom rail, the nut will rotate and translate toward the opposite or right end of the roller in the direction of the fixed connector **44**. In other words, as the movable nut **66** is rotated on the threaded shaft **68** under the tension bias of the spring **38**, it assists the roller to rotate with it, the movable nut **66** translates along the length of the roller (and shaft **68**) to retract the coil spring and assist in the lifting of the shade into the partially or fully retracted position.

(107) As can be appreciated from the above, when the end **122** of the thread **114** is in its over-centered and seated position past the knuckle **123**, the shade is in the fully open and extended position of the FIG. 7A or 7B. It will be appreciated in the fully opened position that the vanes **46** are substantially horizontally disposed so that there is substantially full vision through the shade. By lowering the front edge of the bottom rail, as shown in FIG. 7C, the front sheet **44** of the fabric material is pulled downwardly relative to the rear sheet **45** so that the vanes **46** become slightly inclined thereby reducing the amount of the vision obtained through the shade. The position of the vanes illustrated in FIG. 7C occurs substantially at the time the end **122** of thread **114** is aligned with the knuckle **123**. Once the end **122** of the thread **114** is moved past the knuckle **123** by lowering the front edge of the bottom rail as shown in FIG. 7C, the shade material will move to its fully closed position of FIG. 2. With the shade material closed, it can be raised by lifting the bottom rail toward the head rail of the covering, which allows the fabric material to wrap automatically around the roller **42** under the bias of the coil spring. Of course, the movement of the bottom rail toward the head rail can be stopped at any position and the shade will remain in that position until the bottom rail is raised or lowered.

(108) With reference to FIGS. 5, 6, 8, 11, 12, 21 and 22, the right end of the coil spring is seen anchored to the fixed end connector **64**. The fixed connector (see FIG. 12) has an external thread **124** formed on a cylindrical body **126** thereof adapted to receive the right end of the coil spring **38**

by screwing the connector into the right end of the spring. The fixed end connector also has tabs **127** (see FIG. **8**) that are received in the internal grooves **118** of the inner roller component **48** to assure unitary rotation of the connector **64** and the roller. The fixed connector **64** is adjustably located in any desired fixed location within the inner component **48** of the roller **42** by a pivotal plate **128** that is slid into and within an open cavity **130** in a larger diameter semi-cylindrical portion **132** of the fixed connector **64**. The pivotal plate **128** is movable between a gripping position, as shown, for example in FIG. **22**, where the outer edge **134** of the movable plate **128** is in contact with and wedged against the inner surface of the inner component **48** of the roller **42**, and a release position, as shown, for example in FIG. **24**, where the pivotal plate **128** has been pivoted in a counterclockwise direction to release the engagement thereof with the inner wall of the inner component **48** of the roller **42**. The pivotal plate **128** is biased into its gripping position of FIG. **22** by a spring plate **136** integrally formed on the fixed connector. In this example the spring plate is in the form of a cantilever member extending at an angle off an edge of the fixed connector **64**.

(109) As will be appreciated in FIGS. **5** and **6**, in combination with the above description, the position of the fixed end **64** of the spring **38** relative to the left end of the roller **42** determines the amount of bias force the coil spring **38** can apply to the shade. Shifting the fixed end **64** of the spring **38** to the right away from the left end (i.e. bearing sleeve **60**) will obviously provide a stronger or more powerful bias of the coil spring while shifting the fixed position of the fixed connector to the left will weaken the spring. In some examples, the spring bias is configured to be sufficient to raise the weight of the shade fabric, but is not sufficient to raise the fabric and the bottom rail. Therefore, the shade remains in a static position until a person manually lifts the bottom rail. As will be discussed in more detail below, in other examples, the bias force of the spring may be varied in other manners.

(110) Referring to FIGS. **23** and **24**, the position of the fixed end connector **64** is shown being moved with an auxiliary tool **138**. The auxiliary tool **138** may include a plunger **140** adapted to be inserted through the outer open end of the fixed connector **64** and into engagement with the pivot plate **128**. The plunger **140**, once inserted, depresses the plate **128** as shown in FIG. **24** against the bias of the spring plate **136**. By doing so, the fixed connector **64** is free to slide within the inner component **48** of the roller **42** either to the left or to the right, and grippers **138** are provided on the tool to grip a disk **140** on the outer end of the fixed connector so that it can be pulled to the right if desired. By releasing the grippers and pulling the plunger out of the fixed connector **64**, the pivotal plate **128** will re-engage the inner wall of the inner component **48** of the roller so that the fixed connector **64** will remain in position.

(111) Referring to FIGS. **5** and **6**, it will be appreciated the right end of the roller **42** is rotatably mounted on a bearing **142** that sits on a cylindrical stub shaft **144** that projects inwardly from a right end plate **146** of the head rail **32**. In this manner, the roller **52** may be rotatably supported by the bearing **142** at its right end and the bearing **60** at its left end and the outer component **52** of the roller can extend fully from one end plate to the other so that a shade material **36** extending substantially the full width of the head rail between the end plates **146** and **62** can be supported by the roller **42**.

(112) It will be evident from the above that there are relatively movable parts within the operating system of the present disclosure such as between the movable end connector **66** and the threaded shaft **68**, and the left and right end bearings **60** and **142**, respectively, supporting the roller **42** on the left and right end plates of the head rail **32**. Pursuant to the present disclosure throughout, a level of predetermined level of friction may be built or designed into the moving parts of the operating system at these and maybe other locations, which friction would be within a range of coefficients of friction, the range being dependent upon the weight of the shade material combined with the weight of the bottom rail.

(113) As mentioned previously, the combination of the friction between the relatively movable parts in the operating system and the upward bias force generated by the coil spring **38** and applied

to the shade and bottom rail **34** support the shade against the action of gravity thereon. In other words, without the spring or the friction, the bottom rail would fall by gravity to the extended position of the covering, such as defined by the bottom of the architectural opening in which the shade is mounted. However, the combination of the bias of the spring and the friction built into the system cooperates to hold the bottom rail (and shade) against movement at any predetermined position of the bottom rail within the architectural opening. This occurrence helps mitigate the need to have an exact upward bias force needed by the spring to allow the positioning of the shade in between the fully extended and fully retracted positions. The friction in the system may help temper the effect of gravity where the spring force may be slightly lower than desired, and the friction in the system may also temper the effect of a spring having a slightly higher bias force than is desired.

(114) The coil spring may generally provide the primary anti-gravity or counter-balancing support for the bottom rail and shade, while the friction may fine-tune that anti-gravity support. Since the bias in the coil spring can be adjusted by selecting a spring with the appropriate spring rate and adjusting the fixed location of the fixed end connector **64** along the length of the roller **42**, the bias of the coil spring **38** may be made to by itself precisely counteract the weight of the shade fabric at any extension position and regardless of the effect of the friction in the system. It should be appreciated, as previously mentioned, the effective weight of the shade fabric increases as the shade is extended. It should also be appreciated the bias of the coil spring increases as the movable end connector **66** moves to the left increasing the bias of the spring. The combination of the variable bias of the spring and the built-in friction of the relatively movable parts has been found to offset gravity on the combined weight of the shade material and the bottom rail to prevent movement of the bottom rail by gravity at any selected position within the architectural opening in which the bottom rail is manually placed. It is contemplated that while the bias force varies, as described throughout, with the extension of the shade element, the operating system may be designed to include a transmission mechanism that would allow the bias force to be constant or decrease throughout the extension of the shade element if a level or decreasing bias force was desired.

(115) As will be appreciated from the above, an operator can easily retract or extend the shade by simply lifting or lowering the bottom rail and can tilt the vanes to adjust the amount of vision and light permitted through the shade material by tilting the bottom rail when in the extended position. The effort of the operator in combination with the bias of the coil spring make the movement very simple and substantially effortless.

(116) Referring to FIGS. **25-28**, another example of the covering is illustrated. This embodiment may be substantially similar to the embodiment illustrated in FIGS. **1-24**. However, in this example, the system utilized for anchoring the right end of the spring **38** may be varied. Accordingly, the below description of the embodiment of FIGS. **25-28**, may refer to the system for mounting the fixed end of the spring even though reference numerals are included as they occurred in the description of the first embodiment.

(117) With reference to FIG. **27**, the threaded shaft **68**, bearings **93**, the hub or bearing **60**, the c-clip **96**, the moveable end connector **66**, the inner-cylindrical component **48** of the roller and the coil-biasing spring **38** may be identical to the first described embodiment. However, in this example, the system for anchoring the fixed end of the coil spring includes an elongated threaded bolt **150**, a fixed end anchor **152**, an end plug **154** for the inner-roller component **48**, large **156** and small **158** bearing washers, and an adjustable nut **160** adapted to be threaded onto the bolt. The outer spiral wrap element **162** (which could also be used in the first described embodiment) may be used for dampening spring vibration and may prevent the spring from banging or running against the inner wall of the roller component **48**. Looking first at the fixed end anchor **152**, it may be substantially identical to the moveable end anchor **66**, except that the fixed end anchor **152** has a short cylindrical extension **166** from its threaded end **168**. The cylindrical extension **166** may

include a hexagonal socket **170** formed in its axial end for receipt of the nut **160** to prevent the nut from rotating relative to the fixed end spring anchor. As with moveable end anchor **66**, threads **172** are provided thereon so that the fixed end of the coil spring **38** can be screwed onto the fixed end anchor to fix the fixed end of the spring to the fixed end anchor. The end plug **154** for the roller component **48** is a cylindrical plug having a small diameter portion **174** adapted for insertion into the open right end of the roller component **48** and a larger cylindrical component **176** that abuts the adjacent end of the roller component **48**. The plug has a centered passage **178** there through for slideable receipt of the threaded bolt. The large **156** and small **158** bearing washers also have passages there through for alignment with the passage through the plug **154** so that the bolt **150** can also pass through the bearing washers with a hexagonal head **180** of the bolt then being exposed at the right end of the roller tube **48**.

(118) The threaded rod is inserted through the washers and the end plug and subsequently through the fixed end anchor for the spring and then receives the threaded hexagonal nut **160** thereon, which is seated within the socket **170** at the free end of the cylindrical extension on the fixed end anchor.

(119) In as much as generally the coil spring **38** may always have some bias, meaning for instance and similar to that of the first embodiment described above, at its length of extension when the shade is in a fully retracted position, the coil spring tends to bias the fixed end anchor to the left, thereby encouraging the hexagonal nut to remain within the socket at the left end of the fixed end anchor.

(120) With this arrangement, by rotating the threaded bolt **150** with a socket-type tool (not shown) by engaging the hexagonal head **180** of the bolt it can be rotated causing the nut **160** to translate along the length of the bolt. As the nut **160** translates along the bolt length, it thereby moves the fixed end anchor along the length of the bolt to vary the tension or bias of the coil spring. Thus, the desired bias of the spring is easily manipulated by rotation of the bolt with an appropriate socket-type tool or other tool inserted through the open end of the roller **42** where it can engage the head of the bolt as possibly best appreciated by reference to FIG. **28**.

(121) The inner plug **164** supports and centers the free end of the bolt **150**, which extends into the center hole in plug **164**. The plug **164** also serves as a safety stop to contain the spring energy in the event that a component in the assembly should fail. The inner plug **164** is sized to fit within the inside of the coil spring.

(122) The right end of the outer roller component **52** receives a splined bearing **182** such that they rotate together. The bearing **182** rotatably sits on a cylindrical hub **184** integral with bearing plate **61** which is in turn connected to the end cap **62** with a fastener **186**.

(123) The operating system may include different examples the operating system including the drive mechanism, screw limit stops, counterbalance mechanisms and/or orientation stops. In one example, the counter-balancing mechanisms may include one or more windable springs that may be operably connected to a non-rotatable shaft or rod at one end, and operably connected to the roller so as to move with the rotation of the roller. As the roller rotates, such as due to a user retracting or extending the shade upward or downward, the rotatable springs may wind around a fixed axle or rod at right angles to the rod's length to vary the biasing force or strength of the spring. For example, the rotatable springs may compress (increase bias force) or decompress (decrease bias force) as one end is wrapped and unwrapped around the non-rotatable shaft.

(124) A first example of an alternative counter-balancing system is described with reference to FIGS. **29** and **30**. FIG. **29** is a front elevation view of an architectural covering incorporating an alternative example of the operating system with a shade partially retracted. FIG. **30** is a front elevation view of an architectural covering including another example of the operating system with a shade partially retracted. The covering **200** may include a head rail **232**, a roller and drive mechanism (not shown), a shade **236**, and an end rail **234**. The head rail **232** may be operably connected to two end caps **262** (See FIG. **32**) that may be secured to opposing ends of the head rail

232. As noted above and described in further detail below, the shade **236** is attached to the roller for retraction onto and extension there from. As shown in FIG. **31**, the architectural covering may also include one or more top stops **226**, which keep the bottom rail from wrapping over the top. The shade **236** may be substantially similar to the shade **36** illustrated in FIG. **1**, and may include a front sheet **244**, a rear sheet **245** (See FIG. **55**), and one or more vanes **246**. Referring now to FIGS. **31** and **32**, the covering **200** may also include an operating system **202** to assist in extending and retracting the shade **236**, as well as to open and close the vanes when the shade is in the extended position. FIG. **31** is an exploded view of an operating system **202** or drive mechanism including one or more counter balancing spring motors **204** and/or an orientation stop mechanism **206**. As shown in FIG. **32**, the counter-balancing spring motor **204** and the orientation stop mechanism **206** may be disposed in an interior of a roller **242**, which operably connects to the shade **236**, such as in the manner described above with respect to the first example. The orientation stop mechanism **206** will be discussed in more detail below, but generally may assist in retaining the shade **236** in an extended position with the vanes **246** in one or more than one open configuration.

(125) The counter balancing spring motor **204** may apply a biasing force to the roller **242**, directly or indirectly, to balance the weight of the shade **236** in order to allow the shade **236** to be positioned in a fixed location along any point along the length of extension of the shade **236**. In other words, the shade **236** may be positioned at substantially any location between the fully extended and fully retracted positions. Since the counter-balancing spring motor **204** eliminates the need for operating cords and acts as a cordless shade position mechanism or lock, it may help reduce accidents or injuries resulting from people or animals interacting with operating cords.

(126) The counter-balancing spring motor **204** may include one or more spring units **302**, **304** that may vary a biasing force exerted on a roller operably connected to the shade **236**. The biasing force is applied to the roller in the direction opposite the direction of rotation of the roller when the shade is extending. The biasing force is related to the extended position of the shade **236** relative to the roller. As the shade **236** transitions from the retracted position to the extended position, the biasing force exerted on the roller **242** by the one or more springs in the direction of retracting the shade may increase in order to counteract the increase of the effective weight of the shade **236** due to the shade extending away from the head rail **232**. Because the biasing or urging force of the counter balancing spring motor **204** varies with the amount of extension and retraction of the shade, the biasing force exerted by the counter-balancing spring motor **204**, in addition to inherent friction within the operating system of the covering **200**, provides a sufficient counter-balancing force to allow the shade **236** to be held in position along any location between extended and retracted positions. It should be noted that in the fully retracted position, the counter balancing spring motor may apply a biasing or urging force to the roller to assist the shade in maintaining its retracted position, and to reduce any looseness or the like experienced by the user when first extending the shade from the fully retracted position.

(127) The counter balancing spring motor **204** may be disposed within an interior cavity **243** of the roller **242**. In this location, the counter balancing spring motor **204** is operably connected to a support rod **218**, which is fixed in position relative to the end cap **262**, and thus does not rotate along with the roller **242**. The support rod **218** provides a fixed point of connection for the motor **204**. As shown in FIGS. **32** and **33**, the support rod **218** may be fixedly mounted within the head rail **232** such that it does not rotate with the roller. The spring motor **204** defines a fixed end which anchors to the rod **218**, against which the spring motor winds-up to increase the spring force biasing the roller towards retraction when the shade is being extended.

(128) FIGS. **31**, **32**, and **33** show the general assembly of the covering **200**, including the end plates **262**, roller **242**, and the operating system of this example. The operating system of this example includes the counter balancing spring motor **204**, and rod **218**. The roller **242** is rotatably mounted between the side plates **262** in a manner to allow rotation of the roller **242** relative to the side plates **262**. The mounting of the roller **242** to each side plate **262** using hubs **260A** and **260B** is identical,

so the structure associated with only one end of the roller **242** is described. A hub **260A** is received in the open end **243** of the roller **242**, and itself defines a central bore **284** (FIG. **35**). The central bore **284** is rotatably received over an outer end **412** of an elongated tubular post **208**, which outer end **412** is in turn is secured to the side plate **262** by a central boss **264** and fastener **222**. The outer end **412** of the post **208** acts as a bearing, and the hub **260A** rotates thereon as the roller **242** rotates during extension and retraction of the shade. The post **208** does not rotate relative to the side plate **262**.

(129) Still referring to FIGS. **31-33**, the operating system is positioned within the roller, and engages the roller as well as the side plate at one end of the roller (the left end in FIGS. **32** and **33**). The operating system includes a counter balancing spring motor **204**, which has one actuatable end (outer shell **306**, FIG. **37**) engaging the roller **242**, and another fixed or anchor end **352** (inner tab) (FIG. **40**) positioned inside the roller. As the roller rotates during the extension of the shade, the counter-balancing spring motor **204** also rotates, which increases the bias force between the actuatable end and the fixed end, the bias force being in the direction against the direction of rotation of the roller during extension of the shade. The counter-balancing spring motor **204** is mounted on an elongated rod **218**, with the fixed end of the counter balancing spring motor **204** anchored on the rod **218** to maintain its position during rotation of the roller **242**. One end of the rod **218** is attached by a collar or cap **219** to the inner end **414** of the post **208**, and held there in a fixed orientation so as to not rotate, thus providing a basis against which the counter-balancing spring motor **204** can increase its bias force during extension of the shade off of the roller **242**. A screw limit nut **205** is threadedly engaged around an outer surface of the post **208**, and engages at least a portion of its perimeter **211** the inner wall **247** of the roller **242** so that it rotates with the roller **242**, but is allowed to move axially along at least a portion of the length of the roller. The screw limit nut **205** functions with the vane orientation stop to set the extension limit of the shade, as well as to allow the vanes of the shade to be held in an open position when at the extension limit. With reference to FIGS. **32** and **33**, the roller **242** has an elongated cylindrical shape, and defines an internal cavity **243** having a generally elongated cylindrical shape defined by the inner surface **247** of the wall of the roller. The roller **242** may be made of metal, plastic, wood, or other suitable materials, and may include a single piece, or more than one piece permanently or temporarily secured together. The roller may be received within an elongated cavity defined by the head rail **232**, and the shade **236** may extend from the roller **242**. With the hubs **260A** and **260B** mounted in the ends of the roller **242**, the rotatably engaging the side plates **262** of the head rail, the roller may rotate in the head rail as controlled by the user. The roller acts to retract or extend the shade, or hold the shade in a fixed position of extension as desired by the user.

(130) As shown in FIG. **34**, the internal cavity **243** of roller **242** may define a diameter D and may define a shade securing groove **256** extending longitudinally along the length of the roller **242**. The groove **256** extends into the inner cavity **243** of the roller **242**. The shade-securing groove **256** may operably receive the shade **236** by an anchor strip **214** positioned into and secured within the shade-securing groove **256**. The anchor strip holds the fabric of the shade that extends over the roller between the front **244** and rear **245** sheets in the groove. The shade-securing groove **256** may define, in radial cross-section, a larger dimension at the bottom or radially inward end **278**, and a narrower neck that opens through the outer surface of the roller **242**. The groove **256** may extend the entirety of the length of the roller.

(131) The roller **242** may include retaining lips **266**, **268** on opposite edges of the groove **256**. The lips **266**, **268** extend over an internal cavity portion of the groove **256** to define the narrow neck or mouth of the groove. The lips **266**, **268** act as a retaining structure to help secure the anchor strip **214** and the shade **236** in position within the groove **256**. After the shade material is positioned over the groove, the anchor strip is positioned in the groove by being slid in from an end of the roller or positioned through the neck of the groove. Once positioned in the groove, the anchor strip is held therein by the lips **266**, **268**, and secures the fabric in the groove, and the shade to the roller.

The anchor strip **214** may be secured to the shade material **236**, such as through adhesive, fasteners, or the like. In other examples, one or more ends of the shade **236** may be positioned within the shade-securing groove **256** and the anchor strip **214** may be positioned over the shade material, securing it to the roller **242**. As another example, the anchor strip **214** may be received within a loop or pocket formed within one or more ends of the shade material and then positioned within the groove. It should be noted that in other examples, such as shown in FIG. **50**, the roller **242** may include two separate grooves, each for receiving the top edge of each of the front and rear sheets. Alternatively, the shade **236** may be otherwise operably connected to the roller **242**, such as by sewing, gluing, adhering, or otherwise.

(132) The groove **256** extends into the inner cavity **243** and creates a key structure **258**, which engages and receives a matching-shaped cut-out in the rim of the screw limit nut **205** (as described herein below) to both cause the limit nut **205** to rotate with the roller, as well as guide or translate the limit nut **205** along the length of the tube. The key structure **258** may also engage the actuating portion of the counter-balancing spring motor to cause it to rotate with the roller **242**. The specific connections of the orientation stop mechanism and motor **204** are discussed in more detail below.

(133) The key structure **258** has a general wedge-shape defined by sidewalls **272** and **274**, with the narrower dimension adjacent the outer peripheral wall of the roller **242**, and the wider dimension positioned toward the central axis of the roller. A bottom surface **276** may extend between terminating edges of each of the sidewalls **272**, **274**, and thus the sidewalls **272**, **274** and the bottom surface **276** may define the pocket of the receiving groove **256**.

(134) It should be noted that the roller **242** might be otherwise configured. For example, the roller **242** may include multiple keying structures to operably connect to the motor **204** or other components. Additionally or alternatively, the roller **242** may include multiple grooves or other elements that may be used to operably connect the shade **236** thereto.

(135) With reference to FIG. **35**, the hub **260A** includes a main body **290** defining a generally cylindrical passage **284** there through, a collar **288** extending radially outwardly from a first end of the main body **290**, and a plurality of radially extending ribs **292** running longitudinally along the main body **290**, abutting the underside of the collar **288** at a first end, and terminating generally at the other end of the main body **290**. The ribs **292** extend radially to a dimension just less than the radial dimension of the collar **288**, leaving an annular strip **289** around the periphery of the underside of the flange. The hub **260A** may further include a radially extending groove **286** defined in the wall forming the cylindrical passage **284**. The groove **286** extends in an axial direction along at least a portion of the length of the hub. The groove **286** allows for clearance of the protrusion **430** on the post **208**. With the hub **260A** positioned in the end of the roller **242**, the roller **242** can be received over the post **208** during assembly by lining up the groove **286** with the protrusion **430** prior to positioning the roller **242** onto the post **208**. Once the roller **242** is positioned over the post **208**, the hub **260A** is axially spaced away from the protrusion **430**, and there is no interference between the two as the hub **260A** and roller **242** rotate about the post **208**. Hub **260B**, for use in the other end of the roller **242**, may be similar or identical to hub **260A**. The open end **243** of the roller **242** receives hub **260A**, with the ribs **292** engaging the inner surface of the sidewalls **247** of the roller **242**, and the annular strip **289** engaging the axial end of the roller so that the periphery of the collar on the hub **260A** is flush or near flush with the outer surface of the roller **242**. With the hub **260A** in place, the central passage **284** through the hub **260A** defines a reduced dimensioned opening into the interior of the roller **242**. The collar **288** may form an end cap for the roller **242** and may be positioned between an end of the roller **242** and the end cap **262** for the head rail.

(136) The post **208** is best shown in FIGS. **32**, **33** and **36**. The post **208** has an elongated main body **213** having a generally cylindrical exterior surface **406** and a central passageway **410** defined by a generally cylindrical interior surface **408** (see FIG. **33**). The central passageway **410** extends axially along a length of the post **208**. A cylindrical inner wall **418** is positioned concentrically in the central passageway **410** and extends from the outermost end **412** of the post **208** a short

distance through the central passage way **410**. The inner wall **418** defines a central bore **420** is spaced away from the interior surface **406** of the central passageway **410** by struts **419** positioned around the periphery of the inner wall **418**. The inner wall **418** may also be attached around the circumference of its innermost end to the interior surface **406** of the central passage way **410**, forming an axially facing annular bearing shoulder **413** (FIG. 33).

(137) The external surface **406** of the post **208** defines threads **504** from a midpoint along its length to the innermost end **414**. The outermost end **412** of the post **208** defines a smooth outer bearing surface **415**. A protrusion **430** extends outwardly from the surface **406** of the post **208**, and is positioned near the outermost end of the threaded section **504** of the post. The protrusion **430** is a structure related to the vane orientation stop mechanism **206**, which is described in greater detail below.

(138) Continuing to refer to FIGS. 31, 32 and 36, the post **208** is affixed to the end plate **262** by a fastener **222**. A cylindrical screw seat boss **264** having a threaded internal bore extends at right angles from a central region of the end plate **262**. The boss **264** is sized to fit within the passageway defined by inner wall **418** of the post **208**. The length of the screw seat boss **264** is slightly shorter than the length of the inner wall **418**. To attach the post to the end plate **262**, the post **208** is positioned over the screw seat boss **264** to receive the screw seat boss in the bore **420** defined by the inner wall **418**. The interior dimension of the bore **420** is sized to closely receive the outer dimension of the screw seat boss **264**, and provide a solid, aligned engagement between the post **208** and the end plate **262**. The outermost end **412** of the post **208** abuts the end plate **262**, and the axially extending alignment nubs **215** on the outermost end **412** of the post **208** are seated in corresponding alignment indentations **217** formed in the end plate **264** (see FIG. 31). A fastener, such as screw **222**, is threadedly engaged with the threaded internal bore of the screw boss **264**. When tightened, the flange head of the screw **222** engages the bearing shoulder **413** of the post and draws it tightly toward the end plate **264**. The alignment nubs **215** engaged tightly against the alignment recesses **217** help keep the post **208** from rotating relative to the end plate **264**, either from the roller rotating about the post or the counter-balancing spring motor **204** applying a torque load to the rod **218**. A second post **210** is positioned to extend from the side plate **262** on the opposite end of the head rail, as shown in FIG. 32. The second post **210** is secured to the side plate in the same manner and by the same structure as post **208**. There is no cap on the second post **210**, but there may be if needed or desired.

(139) The inner end **414** of the post **208**, as best shown in FIGS. 32 and 33, receives a cap **219**. The cap **219** is generally cup-shaped, and has rim walls **221** substantially closed at one end **223** and open at the opposite end **225**. The open end **225** receives the inner end **414** of the post **208**, and is secured in a rotationally-fixed manner so as not to rotate. The closed end **223** defines aperture for receiving an end of the rod **218**, and the aperture is keyed to receive the rod **218** and inhibit the rod from rotating within the cap **219**. The rod **218** extends into the post **208** a portion of its length through the keyed aperture in the cap **219**. A length of the rod **218** extends outwardly away from the post **208** for engagement by the counter balancing spring motor **204**, as is described in further detail below. Thus, the rod **218** is anchored in a non-rotatable manner to the head rail by affixing to the cap **219** in a non-rotatable manner, with the cap **219** engaging the post **208** in a non-rotatable manner, and the post **208** engaging the side plates **262** in a non-rotatable manner.

(140) The rod **218**, referring to FIG. 32, extends through the motors **302** and **304**, and its distal end **249** extends into the interior cavity **251** of the second post **210**. The distal end **249** of the rod **218** is not supported within the roller. The distal rod **218** is held in a non-rotational fixed position by the cap **219** on post **208**, and is supported at a midpoint along its length by engagement with the motors **304** and **306**. It should be noted that the distal end **249** of the rod **218** may be supported in the opposing post **210**, using a cap similar to cap **219** received on post **208**. Supporting the rod **218** at one end simplifies assembly and reduces the number of parts used for the product.

(141) With reference to FIGS. 37-40, the operating system for supporting the bottom rail of a shade

in a desired position may use different types of counter-balancing spring motors **204**, such as the spring **38** described above positioned within the roller and extending along a portion of the length thereof, or clock-type springs positioned inside the roller and oriented orthogonally to the length of the roller **242**. The counter balancing spring motor **204** may urge the roller through an indirectly engagement, such as with the spring **38**, or may urge the roller through a direct engagement with the roller, such as with the clock spring example described below. In one example, the counter-balancing spring motor **204** used herein may be a clock-spring model, which includes an actuatable end, for example housing **306**, which may be an outer end of a clock spring and operably associated with the roller **242**, and an anchor end, such as inner tab **356**, which may be an inner end of a piano spring and operably associated with a stationary anchor rod **218** positioned inside the roller **242**. The actuatable end is operably associated with the roller **242**, such as by an attached engagement to cause the actuatable end to rotate with the roller **242**. The anchored end is operably associated with the rod **218** to fix the anchored end from moving with the roller or the actuatable end. As the actuatable end moves with the rotation of the roller **242**, the bias force in the spring, acting in the opposite direction of the rotation of the roller, increase. This bias force then creates the counter-balancing force to help hold the shade at the users selected position of shade extension.

(142) As can be seen in FIGS. **31** and **32**, the counter-balancing spring motor **302** is positioned inside the roller, and is received on the rod **218**. The motor **302** is positioned inside the roller at a location spaced generally mid-way between the ends of the roller. The motor **204** may be located at any point along the length dimension of the roller **242**, and if more than one motor **204** is used, the motors may be located in any effective position relative to each other and in any effective position along the length of the roller. One or more than one motor **204** may be used in any particular shade, depending on the desired bias force required for the size and properties (width, length, depth, material density) of the shade. The motors are rated to indicate particular load limit based on the motor's design. Since each motor **204** used in the same shade applies its bias force directly on the roller, load capability of more than one motor **204** of this type used in an operating system is calculated by adding the load rating of each motor.

(143) With respect to FIG. **37** and FIG. **38**, the counter balancing spring motor **302** will now be discussed in more detail. The counter balancing spring motor **204** is referenced above with respect to FIG. **31** and other figures to generally refer to a rotational bias source or motor, which could be made up of one or more motors **304** or other bias sources. Here, individual motors of the clock-spring configuration defined herein, are referred to individually as counter balancing spring motor **304**. It should be noted that the second counter-balancing spring motor **304** shown in FIGS. **31**, **32**, and **33** may be substantially identical to the first counter-balancing spring motor **302**, accordingly the discussion with respect to the first counter-balancing spring motor **302** may be applied to the second counter-balancing spring motor **304**. However, it should be noted that in other embodiments, the counter-balancing spring motors might be configured differently from each other.

(144) The counter-balancing spring motor **302** may include an outer housing or shell **306** having a generally cylindrical shape. A flat spring **308** is wound around an anchor **310** and together they are positioned inside the housing **306**. The radially inner end **344** of the flat spring forms an inner tab **256**, which engages the anchor **310**, and together form the portion fixed to the stationary rod **218**. The flat spring is wound around itself into a relatively tight spiral similar to a clock spring, and the radially outer end forms an outer tab **354** which engages the housing **306**, the housing **306** and end **354** together form one example of the actuatable portion. The housing **306** is operably connected to the roller **242** as described below, and configured to rotate with the roller **242**. The anchor **310** is operably connected to the spring **308**, and is operably connected to fixed support rod **218**.

(145) The operation of the counter-balancing spring motors **302**, **304** will be discussed in more detail below, but generally because the spring **308** is operably connected to the housing **306** which rotates with the roller **242**, and also connected to the anchor **310**, which does not rotate, As the roller **242** rotates, the actuatable end of the motor (housing **306** and outer tab **354**) rotates also, which

winds the spring more tightly around the fixed end (inner tab **356** and anchor **310**). With every rotation of the roller the bias force urging the roller in the opposite direction increases.

(146) With reference to FIG. **39**, the housing **306** includes a generally cylindrical body having an open first end and a closed second end. The housing **306** define a spring cavity **332** that receives the spring **308** and a portion of the anchor **310**. The second end of the housing **306** may include an aperture **334** for receiving a terminal end of the anchor **310**, discussed in more detail below.

(147) The housing **306**, continuing with FIG. **39**, may include a tab pocket **316** for receiving and securing the outer tab **354** of the spring **308**. The tab pocket is defined between a sidewall **318** of the cavity **332** and an outer wall **336** of the housing **306**. An entry aperture **338** into the pocket **316** is defined between a tip **320** of the sidewall **318** and the outer wall **336** of the housing **306**. The tip **320** of the sidewall **318** is sharply “V” or triangular shaped. The tab pocket **316** receives a portion **354** of the spring **308**, which bends sharply around the tip **320** to help secure the engagement of the spring with the housing. Other pockets **322** and **324** are defined in the outer wall **336**. The pockets **322** and **324** are circumferentially spaced from one another, and may be used to operably connect a different example of the spring **308**, or may be used to reduce the weight of the housing **306**. A roller-engagement groove **314** may be defined in the outer surface of the housing **306**. The engagement groove **314** may be a recessed portion of the housing **306** that may be bordered by two sidewalls **326**, **328** on opposite sides. In one example, the groove **314** is positioned between the portions of the housing defining the recesses **322**, **324**.

(148) The engagement groove **314** extends axially along the length of the housing **306** and may have a width that in general corresponds with the width of the keying surface **258** on the roller **242**. In this embodiment, the keying surface **258** may be received into the groove **314** to operably couple the housing **306** to the roller **242** to cause the housing **306** to rotate together with the roller **242**. With reference to FIG. **37**, the two sidewalls **326**, **328** may extend around the keying surface **258** to retain the keying surface **258** within the engagement groove **314** and keep the housing **306** from rotating independently of the roller **242**. Other portions of the housing **306** may intentionally or incidentally engage the wall of the roller **242**, or the housing **306** may be positioned in a spacer or adapter to allow it to fit inside a roller having a larger diameter, which is described in more detail below. This is described in more detail below.

(149) With reference to FIGS. **39** and **40**, the spring **308** for use in this example of the counter-balancing spring motor **302** is a flat strip of material, typically metal, that is wound around itself in a coil, such as a clock spring. The spring **308** stores mechanical energy when wound more tightly in the direction of the coil, and exerts a force or torque in a direction opposite to a direction of the winding. The exerted force may generally be proportional to the amount of winding. The spring **308** may include a core **352** having an inner tab **356** and an outer tab **354**. In at least one example, the outer tab **354** is the actuable end (in combination with the housing **306**), and the inner tab is the fixed or anchor tab (in combination with the arbor **310** as described below). The actuable tab **354** is operably associated with and rotates together with the roller during use, which winds or unwinds the spring coil **308**. The anchor or fixed tab **356** is operably associated with and is fixed in position to not move with the roller. The relative motion between the two ends during the extension of the shade creates a spring force used to counterbalance the weight of the shade and bias the shade in the retracting direction.

(150) Between the two tabs **354**, **356**, the spring **308** may have a plurality of coiled windings **358**. The number of windings **358** may be varied, as well as the diameter of each of the windings **358**. For example, as the outer tab **354** is moved (and the inner tab is held in a fixed position) in the direction to create more coils that are tighter and more tightly spaced, the biasing force of the spring increases. Where the outer tab **354** is moved in a direction to create fewer, less tightly spaced coils, the biasing force of the spring decreases.

(151) The inner tab **356** is a bent-end of the spring **308**, and the inner tab **356** represents the innermost winding of the spring which defines an central bore **352**. The windings **358** may be

wound around the inner tab **356** of the spring **308** all the way out to the terminal end at the outer tab **354**. The outer tab **354** may be formed on a second end of the spring **308** and may be defined by a crease or sharp bend, and forms the outer portion of the spring **308**. The outer tab is bent in a direction away from the coil windings in order to be secured in the housing as described herein.

(152) The spring **308** has a rest position where the spring **308** is not under a load. At this rest position the spring **308** has a diameter, and there is a number of full coil windings that are generally present in this neutral rest position. From this position, if the outer tab **354** is rotated in a first direction, and the inner tab **356** is secured in a fixed position, the diameter of the windings **358** is reduced and the number of windings **358** is increased as the core wraps around itself. This increases the spring bias in the direction to unwind (which is the biasing force used to retract the shade elsewhere described herein). Alternatively, with reference to FIG. **40**, if the outer tab **354** is rotated in a second direction and the inner tab **356** is secured in place, the number of windings **358** may be reduced as the spring may be un-wound, and as this occurs the diameter of the remaining windings **358** may be increased as the spring **308** expands to accommodate the rotation.

(153) In some examples, the spring **308** may have 4 to 20 windings **358**, and the number of windings **358** may depend on the desired biasing force for the counter-balancing spring motor. The biasing force may depend on the length or width of the shade and/or the weight of the shade material. In some instances, the spring **308** may have a thickness of 0.003" to 0.005" and may have a width ranging between 0.8" to 1.5," depending on the desired biasing force. Additionally, in some instances, the motor **302** may have a set number of "pre-windings," or windings that may be used to maintain a minimum biasing force, when mounted in the operating system in the roller **242**. The pre-load helps keep the spring in a slightly tensioned configuration, which helps the operation of the shade. As an example, the spring **308** may include 4 pre-windings and may then be wound due to rotation of the roller to include an additional **14** winds. In this example, the spring **308** for each counter-balancing spring motor **302**, **304** may generally be configured to balance the weight of a shade **236** having a drop length of approximately 96" and the total number of winds when the shade is fully extended may be 18. However, the number of windings, material, and dimension of the spring may be varied depending on a number of factors, such as but not limited to, material of the shade, drop length of the shade, width of the shade, weight of the end rail, and/or number of counter-balancing spring motors.

(154) The counter-balancing spring motors **302**, **304** may each include the anchor or arbor **310** to rotationally secure the inner end **356** to the rod **218**, and help retain the spring **308** into the spring cavity **332** of the housing **206** and keep the spring **308** from coming out of the housing **306**. The anchor is positioned into the bore **352** of the spring **308**. See FIG. **39**. With reference to FIGS. **41-43**, the anchor **310** may include an anchor end plate **342** extending from a first end of an elongated anchor body **350**. The anchor body **350** received and positioned in the spring cavity **332** and extend through the exit aperture **334** defined in the housing **306**. The anchor end plate **342** may serve as an end cap for the spring cavity **332** to prevent the spring **308** from leaving the cavity **332**.

(155) The anchor body **350** may be a generally cylindrical body with a rod cavity **312** defined there through. The rod cavity **312** receives the support rod **218**. Additionally, an internal wall surrounding the rod cavity **312** may include a securing key feature **344** extending into the cavity **312**. The securing feature **344** may be a triangular shaped protrusion that may match to a corresponding securing channel **345** defined longitudinally along a length of the support rod **218** to rotationally secure the anchor **310** to the support rod **218**. As the support rod **218** is fixed to or operably associated with at least one of the end caps **262**, and is non-rotatable, the anchor **310** is prevented from rotating relative to the support rod **218**. As will be discussed in more detail below, the non-rotatable connection of the anchor **310** to the support rod **218** allows for the spring **308** to wind/unwind around the anchor **310** as the roller is rotated.

(156) An outer surface of the anchor body **350** defines an elongated spring recess **346** and a spring blocking protrusion **348**. The spring recess **346** and blocking protrusion **348** help secure the spring

308 to the anchor **310**. For example, the spring recess **346** may receive a bent inner end portion of the spring **308**, and the blocking protrusion **348** may prevent the received portion of the spring **308** from sliding along the shaft **350** and out of the recess **346**. Additionally, the blocking protrusion **348** may also help to retain the anchor **310** within the housing **306**, such as by preventing the end of the anchor body **350** from sliding out of the exit aperture **334** defined in the housing **306**.

(157) The spring recess **346** may be defined longitudinally along the length of the anchor body **350**, or a portion thereof. In some embodiments, the spring recess **346** may have a length generally corresponding to a width of the spring **308**, and thus may be varied based on the width of the spring. However, in some embodiments it may be desirable for the spring recess **346** to have a longer length than a width of the spring **308**. In these embodiments, the spring **308** may slide along the length of the spring recess **346**, which may provide additional flexibility for torsion forces, and may cushion torsion forces that could otherwise disengage the spring **308** with the anchor **310**. For example, in instances where the spring is back-wound while in an un-tensioned configuration, the diameter of the windings may increase, but due to the sliding and releasable engagement of the spring with the spring recess, the tab received into the recess may release, preventing the spring from bending backwards and deforming. If the bent inner end of the spring deforms, it may not re-engage with the spring recess **346** and the spring would need to be removed from the housing to repair the inner end of the spring.

(158) The inner tab **356** may be releasably received within the spring recess **346** defined in the anchor **310**, as is discussed below and with reference to FIG. **39**. The inner tab **356** may disengage from the spring recess **346** in instances where the spring is rotated in the unwinding direction prior to spring tension being increased by rotating the spring the other way. As the spring **308** disengages, the spring **308** may be prevented from being damaged or deformed. Conventional clock springs may generally have both ends of the core secured in position, which may result in the spring being damaged or over-stressed if rotated in the back-wind direction. Accordingly, the connection of the spring **308** to the anchor **310** as illustrated in FIG. **43** may help reduce damage to the spring in instances where the spring may be rotated in a back-wind direction.

(159) It should be noted that the spring recess **346** might allow some slippage in retaining the spring **308**. Because the spring recess **346** may not tightly secure the spring **308** therein, the end of the spring received in the recess may be able to disengage from the spring recess **346**. For example, in instances where the spring **308** may be back-wound or otherwise wound in an opposite direction than as configured to rotate, the end of the spring **308** may disengage from the recess **346**. The blocking protrusion may prevent the spring **308** from bending or breaking when wound in the back direction. However, when the spring **308** is wound again in the forward direction, the end may slip back into the spring recess **346**, re-engaging the spring with the anchor **310**.

(160) As briefly discussed above, the anchor end plate **342** may help to retain the spring **308** within the spring cavity **332**. In some embodiments, the anchor end plate **342** may be a cylindrically shaped disk or collar that extends radially from the anchor body **350**. The anchor end plate **342** may have the same diameter as the spring cavity **332** defined in the housing **306**, or may have a different diameter. For example, the anchor end plate **342** may have a smaller diameter than the spring cavity **332** and may be partially received therein. However, in other embodiments, the anchor end plate **342** may have a larger diameter and may be configured to extend to the outer wall **336** of the housing **306**.

(161) The support rod **218** extends from the first non-rotatable shaft **208** and extends in the direction to the other non-rotatable shaft **210**. Additionally, the counter-balancing spring motor **204**, specifically, the counter-balancing spring motors **302**, **304** may be operably connected to and received on the support rod **218** as it extends between the two shafts **208**, **201**. The housing **306** of each counter-balancing spring motors **302**, **304** may be rotatably coupled to the support rod **218**, whereas the anchor **310** of the counter-balancing spring motors **302**, **204** may be non-rotatably coupled to the support rod **218**. In this manner, as will be discussed in more detail below, the spring

308 may wind around itself to accommodate the rotation of the housing **306** in light of the non-rotatable anchor **310**.

(162) In some instances, the counter balancing spring motors **302**, **304** may include an adapter to accommodate rollers having a larger diameter, such as the roller **642** shown in FIG. **50**. For instance, depending on the shade **236** material or length, the roller diameter may be increased to provide additional strength, and accommodate additional fabric or the like. In these instances the housing **306** diameters for each counter-balancing spring motor **302**, **304** may be increased and/or an adapter may be positioned over the housing **306** counter-balancing spring motors **302**, **304** to effectively increase the diameter of the counter-balancing spring motors and provide adequate engagement between the motor **302** and the housing.

(163) As shown in FIG. **54**, the adapter **360** may be a generally cylindrical member and be configured to receive the housing **306** of the counter-balancing spring motor **302** in a manner than fixes the rotation of the housing and the adapter. The adapter **360** may include axially aligned and radially extending engaging fins **362** spaced apart from one another around an outer surface of the adapter **360**. The engaging fins **362** engage an interior surface of the roller **242** to operably connect the adapter **360** and counter-balancing spring motor **302** to the roller **242**. In some instances, two or more of the engaging fins **362** may together define a keying groove **366** to receive the keying structure **258** of the roller **242**. The engagement between the keying groove **366** and the keying structure **258** of the roller **242** provides an a structural engagement that causes the adapter and roller to rotate together. The adapter **360** may also include an interfacing key extension **364** extending inwards from an interior surface of the adapter **360**. The interfacing extension **364** may be a generally rectangular shaped protrusion that is sized and shaped to be received in the engagement groove **314** of the housing **306**. With the extension **364** received in the engagement groove **314** of the housing **306**, the housing **306** and the adapter rotate together. Generally, the engagement groove **314** of the counter-balancing spring motor **302** operably connects the counter-balancing spring motor **302** to the roller, and so in instances where the adapter **360** is used, the engagement groove **314** may be received around the interfacing extension **364** to operably connect the counter-balancing spring motor to the adapter **360**. In other words, the interfacing extension **364** engages with the engagement groove **314** to key the two structures together.

(164) The adapter **360** may be used with the larger diameter roller **642**, shown in FIG. **50**. FIG. **50** is an exploded view that includes another example of the operating system for a covering for architectural openings. The operating or control system **500** may be substantially similar the operating system **200** shown in FIG. **31**; however, in this example, a roller **642** for supporting the shade **236** may have an increased diameter, as well as a second shade securing groove.

(165) Specifically, referring to FIG. **53**, the roller **642** may include a first shade securing groove **556A** and a second shade securing groove **556B**. The two shade securing grooves **556A**, **556B** may both be positioned on a top half of the roller **242** as viewed in FIG. **55**. As with the roller **242**, the shade securing grooves **556A**, **556B** may be used to operably connect the shade **236** to the roller **642**. However, because the roller **642** includes two grooves **556A**, **556B**, and the top edge of the front sheet **244** may be operably connected to one groove and the top edge of the rear sheet **245** may be operably connected to the other groove. In this manner, the front sheet and the rear sheet may be spaced apart from each other by the roller **642**.

(166) Each shade securing groove **556A**, **556B** may include a keying structure **558A**, **558B** that operably connects the housing **306** of the counter-balancing spring motors **302**, **304** to the roller **642**. However, in some instances, the roller **642** may have a larger diameter than the housing **306** of the counter-balancing spring motors **302**, **304**, and in these embodiments, the adapter **360** as shown in FIG. **54**, may be operably connected to the housing **306**. Thus, the keying structures **558A**, **558B** may be configured to key to the exterior of the adapter **360** rather than the housing **306** of the counter-balancing spring motors **302**, **304**. For example, the cavity **570** in the roller **544** may have a sufficiently larger diameter to accommodate the adapter **360**, as well as the counter-balancing

spring motors **302**, **304**.

(167) The keying structures **558A**, **558B** may each include a first sidewall **572A**, **572B** and a second sidewall **574A**, **574B** that may each be connected to a bottom surface **576A**, **576B**. As with the keying structure **258**, the sidewalls **572A**, **572B**, **574A**, **574B** may help to retain the counter-balancing spring motor **302**, **304** in engagement with the roller **642** as the roller **642** rotates.

(168) Each shade securing groove **556A**, **556B** may include two retaining lips **566A**, **566B**, **568A**, **568B** positioned on opposing edges of the respective groove **556A**, **556B**. As with the roller **242**, the retaining lips **566A**, **566B**, **568A**, **568B** may secure the anchor strips **514**, **516** within the respective groove **556A**, **556B**, which may secure the front sheet and rear sheet of the shade **236** to the roller **642**.

(169) Operation of the counter-balancing spring motor **204** will now be discussed in more detail. With reference generally to FIGS. **29** to **44**, in the retracted position, the spring **308** within each of the counter-balancing spring motors **302**, **304** may be in a first biasing force position. In other words, the spring **308** may have a predetermined number of windings **358** that may, along with inherent friction within the system, counterbalance the shade **236** to hold the shade **236** in the retracted position. In some instances, the spring or biasing force exerted by the spring **308** in the retracted position may be the normal or un-tensioned spring value. This may be selected to be the minimum (plus some error value, if desired), to balance the weight of the shade **236**.

(170) The roller **242** rotates as the user extends the shade from the retracted position to an extended position, or somewhere in between the retracted and fully extended positions. For example, referring to FIG. **29**, the user may pull a handle on the bottom rail **234** to exert a downward force on the shade **236**, which may cause the roller **242** to rotate within the head rail **232**. As the roller **242** rotates, the keying structure **258** may engage the engagement groove **314** defined within the housing **306**, or in instances where the adapter **360** is used, may engage the adapter **360**. With the engagement between the roller **242** and the housing **306** of the counter-balancing spring motors **302**, **304** (either directly or indirectly through the adapter), the housing **306** rotate correspondingly with the roller **242**.

(171) As the outer tab **354** of the spring **308** is secured within the tab pocket **316**, and the inner tab **352** is secured to the anchor **310** and prevented from rotating, the outer end of the spring **308** may be wrapped around the remaining portions of the spring **308**. In other words, one end of the spring **308** rotates around the remaining portions of the spring, to increase the number of windings **358**, and wrap the spring **308** more tightly around the anchor shaft or arbor **310**. As the outer tab **354** rotates around the body of the spring **308**, the biasing force exerted by the spring **308** may increase as the tension force may be building up within the spring **308**.

(172) If the user stops exerting a force downward on the shade **236**, such as to stop the shade **236** at the extended position or a position between the retracted and extended positions, the increased tension on the spring **308** may be sufficient to counterbalance the shade **236**, although the overall weight of the shade **236** may have been increased from the retracted position. That is, as the shade **236** extends from the roller **242**, the effective weight of the shade may increase due to the additional material hanging from the roller **242**.

(173) Since the roller **242** is keyed to the counter-balancing spring motors **302**, **304** though either the housing **306** of reach respective counter-balancing spring motors **302**, **304** or through the adapter **360** operably connected to each, the number of windings **358** may be increased or decreased correspondingly with the number of rotations of the roller **242**. In other words, the spring **308** may be rotated around itself as many times as the roller **242** completes a full rotation within the head rail **232**. It should be noted that the rotation of the spring might not be a direct one to one relationship with the rotation of the roller **242**. For example, the counter-balancing spring motors may be geared or otherwise movably connected to the roller **242**, such as indirectly through a gear train, so that each roller rotation may result in a partial rotation of the spring **308** around itself. In this manner, the roller **242** may have to be rotated fewer or more times in order for the spring **308**

to increase its windings by one.

(174) Generally, as the roller **242** rotates in a particular direction, such as to either wrap or unwrap the shade **236**, the weight of the shade **236** may correspondingly increase or decrease. In other words, the more the shade **236** is unwrapped from the roller **242**, the heavier the effective weight of the shade **236**. Because the spring **308** windings **358** also correspond to the rotation of the roller **242**, the more the shade **236** is unwrapped from the roller **242**, the more the biasing force is increased by the spring **308**. The same effect is seen as the shade **236** is wrapped onto the roller **242**. As the roller **242** rotates in a second direction to wrap the shade **236** around the roller **242**, the spring **308** may be rotated with the roller **242** to decrease the number of windings **358**, and thus reduce the biasing force. It should be noted that in some instances, as the roller rotates to wrap the shade around the outer surface, the spring **308** may exert a biasing force in the direction of rotation, to assist the roller in rotating.

(175) As the effective weight of the shade **236** decreases as it is retracted, the biasing force of the spring **308** also decreases. Thus, the counter-balancing spring motor **204** may generally balance the load or force exerted by the shade **236** to hold the shade in a desired position, and as the load due to the shade varies, so does the biasing force exerted by the counter-balancing spring motor **204**. Accordingly, at substantially any position of the shade **236**, the shade may be balanced to remain in a desired position, without requiring an operating cord, or an operating cord lock.

(176) As discussed above, the counter-balancing spring motor **204** may be modified based on the weight of the shade **236**, which may depend on the weight of the fabric, as well as the dimensions of the shade **236** (a larger shade may weigh more than a smaller shade of similar fabric). In some instances, the counter-balancing spring motor **204** may include three or more counter-balancing spring motors, each counter-balancing spring motor including one or more springs. Conversely, in instances where the weight of the shade **236** may be lighter, the counter-balancing spring motor **204** may be a single counter-balancing spring motor.

(177) When the shade is in its fully extended position, such as in FIG. **30** (and as explained above with respect to FIGS. **16-19** above, the vane orientation stop structure and mechanism allows the vanes to be oriented in a closed position, fully opened position, or some orientation in between. The vane orientation stop mechanism is actuated by moving the rear edge of the bottom rail in a downward direction to pull the rear sheet downwardly. This motion of the bottom rail actuates the vane orientation stop mechanism to resist the biasing force urging applied by the counter balance motor to the roller, and shifts the front and rear sheets relative to one another in a vertical direction, which in turn controls the orientation angle of the vanes. The vane orientation stop mechanism is deactuated by pulling the front edge of the bottom rail downwardly, which rotates the roller in a direction to disconnect the orientation mechanism and shift the front and rear sheets relative to one another in an opposite direction, which closes the vanes.

(178) With reference to FIGS. **31**, **32**, and **33** the orientation stop mechanism **206** includes a screw limit nut **205** that is in operative engagement with the roller **242** such that the screw limit nut **205** is reversibly translated along a threaded portion of the post **208** as the roller **242** rotates. The extent to which the screw limit nut **205** may travel along the threaded portion of the post **208** is limited such that the screw limit nut **205** reaches a stop structure or other end point that substantially corresponds to the shade **236** being fully extended. The screw limit nut **205** may move into an over-travel region that is past the point where the screw limit nut **205** makes initial contact with the stop. In the over-travel region, friction or other mechanical forces between the screw limit nut **205** and the stop may inhibit movement of the screw limit nut in the inward direction. In this way, the screw limit nut **205**, and thus the roller **242**, may be selectively locked or otherwise held in place despite the bias force of the counter-balancing spring motor **204** which might otherwise rotate the roller **242** to retract the shade.

(179) In one embodiment, as shown in FIG. **34**, the protrusion **430** disposed on the exterior surface **406** of the post **208** may provide a stopping location for the screw limit nut **205**. The post **208** may

have a threaded portion **502** that includes any number of external screw threads **504** on the exterior surface **406** of the post **208**. The external screw threads **504** may extend from the innermost end **414** of the post **208** to the protrusion **430**. The external screw threads **504** on the post **208** are adapted to mate with the internal screw threads **506** of the screw limit nut **205**. The screw limit nut **205** can be seen in greater detail in the enlarged perspective view of FIG. **45**. As shown in FIG. **45**, the internal screw threads **506** are disposed on the interior of a ring **508** portion of the screw limit nut **205**. The internal screw threads **506** are adapted to allow the screw limit nut **205** to be movably attached to the threaded portion **502** of the post **208**. In FIG. **33**, the screw limit nut **205** is in contact with the protrusion **430** and thus is disposed at its outermost point of travel along the threaded portion of the post **208**.

(180) Continuing with FIG. **45**, the screw limit nut **205** is adapted to engage the roller **242** such that the screw limit nut **205** rotates around the post **208** as the roller **242** rotates to extend or retract the shade **236**. In order for the screw limit nut **205** to rotate with the roller **242**, the screw limit nut **205** may contain an engagement groove **510** that is adapted to engage the internal keying structure **258** of the roller **242**. The engagement groove **510** may be formed as a recess in a tab **512** portion of the screw limit nut **205**. The tab **512** may be integrally formed with the ring **508** and may extend radially outward therefrom. The engagement groove **510** may be formed in the tab **512** such that the tab **512** includes two fingers **514**, **516** that extend away from an inner engagement surface **518** of the engagement groove **510**. Each finger **514**, **516** may contain an inner surface **520**, **522**, each of which connects on opposite ends to the inner engagement surface **518** to form a continuous U-shaped curved surface of the engagement groove **510**.

(181) The engagement groove **510** may engage the internal keying structure **258** of the roller **242**, as shown in FIG. **44**. FIG. **44** is a cross-sectional view taken along line **44** shown in the FIG. **33**. In the assembled configuration shown in FIG. **44**, the screw limit nut **205** is movably connected to the threaded portion **502** of the post **208**. The post **208** and the screw limit nut **205** are received within the inner cavity **270** of the roller **242**. The screw limit nut **205** is positioned within the inner cavity **270** of the roller **242** such that internal keying structure **258** of the roller **242** is received in the engagement groove **510** of the screw limit nut **205**. In this position, the internal keying structure **258** may contact the tab **512** portion of the screw limit nut **205** to rotate the screw limit nut **205** with the roller **242**. Specifically, when the roller **242** rotates in a first (clockwise from the perspective of FIG. **44**) rotational direction **D1**, the sidewall **274** of the keying structure **258** may contact the inner surface **522** of the finger **516** to also rotate the screw limit nut **205** in the first rotational direction **D1**. Similarly, when the roller **242** rotates in a second (counter clockwise from the perspective of FIG. **44**) rotational direction **D2**, the sidewall **272** of the keying structure **258** may contact the inner surface **520** of the finger **516** to also rotate the screw limit nut **205** in the second rotational direction **D2**.

(182) As the roller **242** rotates the screw limit nut **205** around the threaded portion of the post **208**, the external screw threads **504** on the post **208** acts on the internal screw threads **506** of the screw limit nut **205** to translate the nut **205** along the threaded portion **502** of the post **208**. Specifically, when the roller **242** rotates in the first rotational direction **D1** (retraction of shade), the external screw threads **504** move the screw limit nut **205** in an inward direction, away from the end cap **262**. Similarly, when the roller **242** rotates in the second rotational direction **D2** (extension of shade) the external screw threads **504** move the screw limit nut **205** in an outward direction, toward the end cap **262**.

(183) Movement of the roller **242** in the second direction occurs when a user pulls down on the end rail **234** to extend the shade. Here, the roller **242** rotates in the second direction, feeding out shade material from the roller **242** to thereby extend the shade **236**. Movement of the roller **242** in the first direction occurs when the counter balancing spring motor **204** turns the roller **242** to retract the shade **236**. Here, the user lifts end rail **234** to lighten the load on the counter balancing spring motor **204** such that the counter balancing spring motor **204** is able to rotate the roller **242** to

thereby retract the shade **236** material back onto the roller **242**.

(184) Thus, when a user pulls down on the end rail **234** to extend the shade **236**, the accompanying movement of the roller **242** in the second rotational direction **D2** moves the screw limit nut **205** in an outward direction along the threaded portion **502** of the post **208** (extension of shade). If the user continues to pull the bottom rail downwardly to extend the shade, eventually after a number of rotations, the screw limit nut will engage the protrusion **430**. Similarly, when the counter balancing spring motor **204** turns the roller **242** to retract the shade **236**, the accompanying movement of the roller **242** in the first rotational direction **D1** moves the screw limit nut **205** in an inward direction along the threaded portion **502** of the post **208** (retraction of shade). This movement of the screw limit nut **205** along the threaded portion **502** of the post **208** is illustrated in FIG. **32** and FIG. **33**. In FIG. **32**, which is a cross-sectional view taken along line **32** in FIG. **29**, the shade **236** is partially extended and so a certain amount of shade **236** material is present on the roller **242**. Here, the screw limit nut **205** is in an intermediate position between the innermost end **414** of the post **208** and the protrusion **430**. In FIG. **33**, which is a cross-sectional view taken along line **33** in FIG. **30**, the shade **236** is fully extended and so the shade **236** material is fully fed out from the roller **242**. Here, the screw limit nut **205** is at its outermost point of travel along the threaded portion **502** of the post **208**, and the screw limit nut **205** is in contact with the protrusion **420**.

(185) Note that a shade such as that shown in FIGS. **9** and **44** extend off the back of the roller when being moved from a retracted to a fully extended position. Regarding the rotation of a roller to extend and retract a shade, in FIG. **9** the front of the head rail **32** is to the left, and to extend the shade the roller would be rotated clockwise, which would cause the shade to extend off the back-side of the roller. In contrast, FIG. **44** shows the front of the head rail **32** to the right, which means that to extend the shade from the roller, the roller must be rotated in a counter-clockwise direction (**D2**) to extend the shade off the back of the roller **242**.

(186) As shown in FIG. **45**, the screw limit nut **205** contains a knuckle **524** (also referred to as an apex) that is disposed on an outward-facing surface **526** of the ring **508**. The knuckle may be, for example, a bump, protrusion, extension, surface irregularity, surface portion with increased frictional properties, or the like. Functionally, the knuckle physically engages the protrusion **30** and holds (for instance under a compressive force if the knuckle is a bump, or frictional force if the knuckle is a surface portion with increased surface friction) the screw limit nut from rotating under the bias force of the counter-balancing unit(s) (i.e. motor(s)). As the screw limit nut **205** reaches its outermost point of travel along the threaded portion **502** of the post **208**, the knuckle **524** on the screw limit nut **205** makes contact with the protrusion **430**. Once the knuckle **524** and the protrusion **430** make contact, the screw limit nut **205** may move into an over-travel region where friction or other mechanical forces between the knuckle **524** and the protrusion **430** may inhibit the rotation of the screw limit nut in the inward direction (retraction of shade) without being physically urged by a user to disengage the knuckle **524** from the protrusion **430**. Movement of the screw limit nut **205** into the over-travel region may correspond to the user rotating the end rail **234** in order to cause the vanes to move to a generally horizontal position, and thus open the shade **236**. This engagement between the knuckle **524** and the protrusion **430** is illustrated in greater detail in FIGS. **46-49D**, where the knuckle is in the form of a bump or protrusion.

(187) FIGS. **49A-49D** are schematic illustrations of the engagement between the screw limit nut **205** and the protrusion **430** disposed on the surface of the post **208**. FIGS. **49A** through **49D** illustrate the movement of the screw limit nut **205** as the screw limit nut **205** is rotated by the rotation of the roller in the second rotational direction **D2** (extension of shade). The shade, with reference to FIG. **49A**, at this point is in its fully extended position, and the vanes are closed, such as in FIG. **9**. To actuate the vanes to open either partially or fully, the roller **242** must be further rotated to cause the front and rear sheets to separate and extend the vanes. To make this happen, the bottom rail may be rotated to pull the rear edge of the bottom rail **34** downwardly (in FIG. **9**, the rear edge is oriented upwardly), which rotates the roller **242** further in the **D2** direction (to extend

the shade off the back of the roller). As the screw limit nut **205** is further rotated in the rotational direction **D2** by pulling down on the rear edge of the bottom rail, the knuckle **524** comes into operative contact with the protrusion **430**, which indicates that the shade is at or near the fully extended position. As can be seen in FIG. **49A**, the knuckle **524** includes a sloped engagement surface **526** that is disposed in a location such that the engagement surface **526** makes initial contact with the protrusion **430**. The engagement surface **526** slopes outwardly from a surface of the screw limit nut **205** to a point **530**. The knuckle additionally includes a more steeply sloped rear surface **528**. As can be seen in FIG. **49A**, the rear surface **528** and the engagement surface **526** meet at the point **530**, which is set off a distance from the surface of the screw limit nut **205**.

(188) In FIG. **49B**, the screw limit nut **205** is rotated along the rotational direction **D2** such that the engagement surface **526** comes into an initial contact with the protrusion **430**. The orientation of the knuckle **524** and the protrusion **430** shown in FIG. **49B** may correspond to the shade being fully extended as shown in FIG. **30**.

(189) From the position shown in **49B**, the user may rotate the end rail **324** such that the screw limit nut **205** moves into an over-travel region, which is shown in FIGS. **49C** and **D**. In so doing, the user may open the veins **246** of the shade **236**. As can be seen in FIG. **49C**, when the user rotates the lower rail **234** the knuckle **524** moves over the top of the protrusion **430**. In this position, the friction or other mechanical forces between the knuckle **524** and the protrusion **430** may inhibit the screw limit nut **205** from moving off of the protrusion **430** by a rotation in the first rotational direction **D1** under the bias of the counter-balancing spring motor. Accordingly, the friction or other mechanical forces hold the screw limit nut **205** in place against the force exerted by the counter-balancing spring motor **204** which might otherwise move the roller **242** and thus screw limit nut **205**. This position of the knuckle **524** relative to the protrusion **430**, held in place by the friction or compression force or both between the two, may orient the vanes in a position where they are partially open, meaning the vanes are angled between generally vertical (closed) and generally horizontal (fully open), such as in FIG. **7C**. In this position, the protrusion **430** may deflect, or the screw limit nut **205** may deflect, or the knuckle may compress, or a combination of one or more of these mechanisms may occur, to allow the knuckle to rest on top of the protrusion **430** and be under a compressive or frictional load.

(190) In FIG. **49D**, the screw limit nut **205** is moved further along in the over-travel region such that the point **530** of the knuckle **524** passes over the protrusion **430** such that the rear surface **528** of the knuckle **524** comes to rest on the opposite side of the protrusion **430**. Again, to allow the knuckle to pass over the protrusion **430**, the protrusion **430** may deflect, or the screw limit nut **205** may deflect, or the knuckle may compress, or a combination of one or more of these mechanisms may occur, to allow the knuckle to pass over the protrusion **430**. In this position, the vanes are more open they would be in FIGS. **49C**, and may be open to a full extent where the vanes are approximately horizontal (such as in FIG. **7B**).

(191) FIG. **50** illustrates an alternative example for the orientation stop mechanism **650**. As can be seen in FIG. **50**, an orientation stop mechanism **650** may include a screw limit nut **654** provided in association with a collar **652**. Both the collar **652** and the screw limit nut **654** are adapted to be received on the threaded portion of the post **208** as shown in FIGS. **51** and **52**. FIG. **51** is a cross-sectional view that substantially corresponds to a cross section taken along the line **32** shown in FIG. **29**. FIG. **52** is a cross-sectional view that substantially corresponds to a cross section taken along the line **33** shown in FIG. **30**. In accordance with embodiments discussed herein, the screw limit nut **654** and the collar **652** employ a detent structure that holds the screw limit nut **654** in place at or near its furthest most point of travel along the threaded portion of the post **208**, which is generally where the shade is fully extended. In one embodiment, such as that shown in FIG. **51**, the detent structure includes a pin **656** mounted on the screw limit nut **654**. The pin **656** is adapted to be received in the groove **658**, which is disposed on the inward facing surface of the collar **652**. The collar **652** is positioned on the post **208** such that the pin **656** reaches the groove **658** when the

screw limit nut is at a position corresponding to the shade 236 being fully extended. This position of the screw limit nut 654 can be seen in FIG. 52. In FIG. 52, the pin 656 is received within the groove 658 and the end of the pin 656 engages the bottom of the groove 658, such that a frictional force, or compressive force, or both, is created. In this position the screw limit nut 654 is inhibited by the friction or compressive force from rotating in the rotational direction D1 under the bias of the counter-balancing units, such that the screw limit nut 654 would move in the inward direction away from the end cap 262. Here, the screw limit nut 654 is held in place against the force of the spring motors 604 which might otherwise move the screw limit nut 654 by rotating the roller 642. To move the pin into the position shown in FIG. 52, the rear edge of the bottom rail is moved downwardly, as described above, to further rotate the roller in the extension direction, and cause the vanes to at least partially open (depending on how much further the roller is rotated by the actuation of the rear edge of the vane).

(192) Turning now to FIGS. 58 and 59, which are close ups of the pin 656 and groove 658, and schematically illustrate the entry and exit wall angles of the groove 658. The schematic sections 58 and 59 are representative of sections taken along a circumferential line passing through the groove 658 and extending orthogonally with the plane of FIG. 52. As shown in FIG. 58, the groove 658 includes a bottom surface 664, which is bounded on each side by sloped walls of the groove 658. As shown in FIG. 58, the groove 658 includes an entry wall 662 which the pin 656 passes and may contact when it first enters the groove 658. The groove 658 additionally includes an exit wall 660 opposite from the entry wall 662. The pin 656 passes along, and possibly engages, the exit wall 660 when the pin moves into the groove 658 as the screw limit nut 654 further rotates. In the embodiment shown in FIG. 58 the exit wall 660 and the entry wall 662 have substantially the same slope. In this embodiment, the groove 658 is configured to have a similar feel when the screw limit nut 654 is rotated such that the pin 656 either enters or exits the groove 658. As the screw limit nut 654 is rotated and moves both axially closer to the collar 652 and rotates relative to the collar, the pin 656 moves further towards the collar 652 and engages the collar on the leading side of the groove, or may be received in the groove to contact its side or bottom walls to inhibit the rotation of the nut 654 under the force of the counter-balance units.

(193) In an alternative embodiment shown in FIG. 59, the groove 658 includes an exit wall 660 having a differing slope from the entry wall 664. In this configuration the groove 658 produces a different tactile feel when the pin 656 enters the groove 658 in comparison to when the pin 656 exits the groove 658.

(194) In accordance with additional examples shown in FIGS. 60-64, the detent structure may include a number of grooves disposed on a sloped surface such that the pin 656 may engage one or a number of grooves as it rotates and moves along the threaded portion of the post 208 closer to the collar 652 while rotating relative to the collar 652. As can be seen in FIG. 62, the collar 652 may include a sloped surface 712 having a first groove 714, second groove 716, third groove 718 and a fourth groove 719. The surface 712 circumferentially slopes gradually away from the nut 654 in the clock-wise direction, as represented in FIG. 64. Note the diminishing distance between the dashed line 721 and the base of each successive groove 714, 716, 718, and 719. This results in the actuator pin 656 entering and exiting each successive groove 714, 716, 718, 719 with the same force and tactile feel compared to a face 712 that was perpendicular to the threaded post 208. This is because as the nut 654 turns around the threaded post 208, it moves close to the nut 654, and the engagement with each successive groove and related entry and exit walls would be more forceful. Alternatively, with a little less modulation of the tactile feel, if each successive groove was deeper than the previous one, or the localized area around each successive groove was removed to move it slightly away from the nut 654 as the nut moved axially toward the collar, a similar effect can be created to modulate or even-out the tactile feel of the pin entering and exiting the successive grooves.

(195) Continuing with FIG. 62, as the screw limit nut 654 is rotated in the second rotational

direction D2 (to extend the shade) and reaches the point of fullest extension, the pin 656 disposed on the screw limit nut 654 engages the grooves 714, 716, 718, 719 successively as the screw limit nut rotates relative to the collar 652 (such as by moving the rear edge of the bottom rail downwardly). The different grooves provide individual stopping points for the screw limit nut 654 such that the vanes of the shade 236 are held in various degrees of openness and the veins 246 let through variable amounts of light. For instance, if the pin were positioned in groove 714, the vanes would be slightly opened (i.e. between the positions shown in FIG. 9 and FIG. 7c, more vertical than horizontal). If the pin was positioned in groove 716, the vanes would be opened more than if the pin was in groove 714 (such as in FIG. 7c). If the pin were positioned in groove 718, the vanes would be more opened (closer to horizontal, such as between FIGS. 7c and 7b) than if the pin were in groove 716. If the pin were positioned in groove 719, the vanes would be more opened than if the pin were positioned in groove 718 (substantially horizontal, such as in FIG. 7b). Note that the pin in this example may be spring loaded to resiliently move axially into or toward the nut 654, which resilient axial motion would make the movement of the pin into and out of the groove less vigorous feeling than if the pin was solid and not axially movable. Additionally, the pin in FIGS. 60-64 may include a spherical tip 657 which is spring loaded relative to the pin 656. The spherical outer shape of the ball 657 would smooth out the tactile feel of the pin entering and exiting each groove 714, 716, 718, and 719. The spring-loaded ball 657 would even further reduce and control the abruptness of the tactile feel. The spring-loaded engagement of the ball 657 within any of the grooves would still, however, resist the rotation of the nut relative to the collar under the bias force of the counter-balance unit. The spring loaded tip is not required to be spherical, but instead may be square, cylindrical, oval, or some other shape that would ride into and out of a groove as described herein and maintain sufficient engagement to resist the retraction force created by the counter-balance units.

(196) As shown in FIGS. 60-64, the detent structure includes a pin 656 disposed on the screw limit nut 654 and grooves 714, 716, 718, and 719 disposed on the collar 652. FIGS. 65-67 illustrate an alternative embodiment for the detent structure that includes a pin 656, which is mounted on the collar 652. Specifically, the pin 656 is disposed through a pinhole, which extends from the outward facing side of the collar to the inward facing side of the collar 652. The pin 656 is secured in place with a nut 702, which is fastened to the first side of the collar 652. The pin 656 disposed on the collar 652 is provided in association with grooves 714, 716, 718, and 719, which are disposed on the screw limit nut 654. The pin 656 in this example may include a spring-loaded ball 657 as noted above. As shown in FIGS. 65-67, the collar 652 and the screw limit nut 654 are attached to the post 208. The collar 652 is fixed to the post 208 such that the collar 652 does not move along the length of the post 208. The screw limit nut 654, however, is movable along the threaded portion of the post 208 through engagement between the internal keying structures of the roller 242 and the engagement grooves or threads of the screw limit nut 654.

(197) FIGS. 68-69 are an alternative embodiment for the detent structure. As can be seen in FIGS. 68-69 the detent may include a molded spring 706 which is disposed on, integrally formed with, or mounted on the second surface of the screw limit nut 654. The molded spring may be plastic, or may be made of another material such as metal (in which case it would likely be mounted on the nut 654). The molded spring 706 includes a cantilever arm positioned in a recess formed in the screw limit nut. The arm of the molded spring 706 is in the plane of the facial surface of the screw limit nut nearest the collar. The arm terminates in a protruding peak or other engaging shape (which may be rounded) that extends above the plane of the screw limit nut. As the screw limit nut and the collar come into proximity with one another, the peak engages the facial surface of the collar and the arm flexes to bias the peak against the collar. The peak or other rounded structure is adapted to move into and out of the grooves 714, 716, 718, and 719 under the urging of the flexed arm as the screw limit nut and the collar move relative to one another.

(198) In accordance with an alternative embodiment, the detent structure may include a leaf spring

708 mounted to the screw limit nut 654, as shown in FIG. 70-71. As can be seen in FIGS. 70-71, the leaf spring 708 is connected at one end, such as in a cantilever fashion, to the screw limit nut 654 so as to flex and resiliently return to its position. The leaf spring is attached to the to the screw limit nut 654 by a screw 710, or by welding, adhesive, epoxy, adhesive, or otherwise attached to the screw limit nut. A recess is formed in the nut 654 below the free end of the leaf spring, and is of sufficient depth to allow the leaf spring to deflect into the recess without having interfering contact with the nut 652. The leaf spring 708 terminates in an end having a pimple 725 or other rounded structure adapted to resiliently engage the grooves 714, 716, 718, and 719 disposed on the collar 652 and resist the bias to retract caused by the counter balancing unit.

(199) A method of using the operating system aspect of the disclosure includes a method for counterbalancing the load of a shade element extending from a roller shade structure comprising the steps of unrolling the shade element to a desired extended position by rotating the roller in a first direction, creating an amount of biasing force in an operating system by rotation of the roller in a first direction, applying the amount of biasing force to the roller in a second direction opposite the first direction, wherein the amount biasing force sufficient to counterbalance the load of the shade element.

(200) The amount of biasing force may be sufficient to maintain the shade in the selected extended position, or it may be less or more than the amount needed to maintain the shade in the selected extended position. Additionally, a predetermined level of friction may be created between components of the operating system, wherein the amount of biasing force in addition to the friction is sufficient to maintain the shade in the selected extended position. The biasing force may be a spring motor, which in turn may be a coil spring or a clock spring.

(201) Further, the shade element may include a shade element extending from a roller shade structure, where the shade element includes a front sheet, a rear sheet, and at least one vane connected along a front edge to the front sheet and along a back edge to a back sheet, where the relative motion of the front and rear sheets move the at least one vane between open and closed orientations. In this case, the method comprises the steps of unrolling the shade element to a fully extended position, with at least one vane in a closed orientation; further rotating the roller in a first direction to cause the front sheet and back sheet to move relatively to orient the at least one vane in an open position; and engaging a vane orientation stop mechanism to overcome the biasing force and hold the roller in position to maintain the open orientation of the at least one vane.

(202) Although the present disclosure has been described with a certain degree of particularity, it is understood the disclosure has been made by way of example, and changes in detail or structure may be made without departing from the spirit of the disclosure as defined in the appended claims.

(203) The foregoing description has broad application. For example, while examples disclosed herein may focus on the particular operating elements and particular spring types and arrangements, vane orientation stop mechanism structures, etc. it should be appreciated that the concepts disclosed herein may equally apply to other structures that have the same or similar capability to perform the same or similar functions as described herein. Similarly, the discussion of any embodiment or example is meant only to be explanatory and is not intended to suggest that the scope of the disclosure, including the claims, is limited to these examples.

(204) All directional references (e.g., proximal, distal, upper, lower, upward, downward, left, right, lateral, longitudinal, front, back, top, bottom, above, below, vertical, horizontal, radial, axial, clockwise, and counterclockwise) are only used for identification purposes to aid the reader's understanding of the present disclosure, and do not create limitations, particularly as to the position, orientation, or use of this disclosure. Connection references (e.g., attached, coupled, connected, and joined) are to be construed broadly and may include intermediate members between a collection of elements and relative movement between elements unless otherwise indicated. As such, connection references do not necessarily infer that two elements are directly connected and in

fixed relation to each other. The drawings are for purposes of illustration only and the dimensions, positions, order and relative sizes reflected in the drawings attached hereto may vary.

Claims

1. A retractable shade comprising: a rotatable roller having an internal cavity; a longitudinal member having a longitudinal length that extends at least partially within the internal cavity of the rotatable roller; a moveable member extending at least partially within the internal cavity of the rotatable roller, the moveable member translatable and non-rotatable with respect to the rotatable roller, and the moveable member further rotatable about and translatable along the longitudinal length of the longitudinal member with a first frictional resistance; and a holding mechanism associated with the moveable member and the longitudinal member wherein an engagement portion of the moveable member is configured to engage a holding portion of the longitudinal member to further increase frictional resistance to; resist while permitting rotation and translation of the moveable member with respect to the longitudinal member with a second frictional resistance greater than the first frictional resistance, and resist rotation of the rotatable roller.
2. The retractable shade of claim 1, wherein the longitudinal member comprises a first thread extending at a first angle along and with respect to the longitudinal length of the longitudinal member, the first thread of the longitudinal member having first and second terminal ends and engageable with a second thread on the moveable member such that the moveable member in response to rotation of said roller rotates with the roller and translates along the longitudinal length of the longitudinal member, the second thread on the moveable member extending at a first angle and having first and second terminal ends.
3. The retractable shade of claim 2, wherein the first thread of the longitudinal member has at or near one of its terminal ends a first knuckle that defines a transition that decreases the first angle of the first thread.
4. The retractable shade of claim 3, wherein the second thread of the moveable member has at or near one of its terminus ends a second knuckle that defines a transition that decreases the first angle of the second thread.
5. The retractable shade of claim 3, wherein the first angle forms a steep angle with respect to the longitudinal length of the longitudinal member.
6. The retractable shade of claim 3, wherein the longitudinal member has at or near one of its terminal ends an end tab wherein the first thread of the longitudinal member extends at a second angle that is less than the first angle of the first thread of the longitudinal member, and the second knuckle has an end tab wherein the second thread of the moveable member extends at a second angle that is less than the first angle of the second thread of the moveable member.
7. The retractable shade of claim 3, wherein the first knuckle of the longitudinal member is shaped the same as the second knuckle of the moveable member.
8. The retractable shade of claim 3, wherein the first knuckle of the longitudinal member and the second knuckle of the moveable member form an over-center-latch that resists movement of the moveable member.
9. The retractable shade of claim 1, wherein said moveable member is keyed to the rotatable roller to rotate with the rotatable roller.
10. The retractable shade of claim 1, further comprising a biasing component operably connected to the rotatable roller and configured to exert a biasing force on the rotatable roller to rotate the rotatable roller in a retraction direction and wherein the holding mechanism is configured to resist rotation of the rotatable roller in the retraction direction.
11. The retractable shade of claim 1, further comprising a shade material operably connected to the rotatable roller, wherein the shade material is wrappable about and unwrappable about the rotatable roller for retraction and extension of the shade material respectively, wherein at an extended

position of said shade material from said rotatable roller, the frictional resistance of the holding mechanism between the moveable member and the longitudinal member increases to the second frictional resistance to restrict movement of the rotatable roller in a retraction direction to restrict retraction of said shade material; and rotation of the rotatable roller to retract said shade material disengages the engagement portion of the moveable member from the holding portion of the longitudinal member to permit retraction of the shade material.

12. The retractable shade of claim 1, wherein the holding portion comprises a protrusion and the engagement portion comprises a knuckle wherein forces between the protrusion and the knuckle inhibit the moveable member from disengaging the protrusion.

13. The retractable shade of claim 12, wherein the moveable member is in the form of a collar that rotates about the longitudinal member.

14. The retractable shade of claim 12, wherein the knuckle has a sloped front engagement surface that operatively engages the protrusion.

15. The retractable shade of claim 12, wherein the knuckle has a sloped rear surface, the sloped rear surface being more steeply sloped than the sloped front engagement surface.

16. The retractable shade of claim 1, wherein the holding portion is located at or near an end of the longitudinal member to increase frictional resistance with the moveable member at or near the end of the longitudinal member to resist rotation of the rotatable roller while permitting movement of the moveable member with respect to the longitudinal member.

17. The retractable shade of claim 1, wherein engagement of the holding portion with the engagement portion increases frictional resistance to rotation of the rotatable member while permitting further rotational movement of the rotatable roller in either a retraction or an extension direction.

18. A retractable shade comprising: a rotatable roller having an internal cavity; a shade material attached to the rotatable roller, wherein rotation of the rotatable roller in a first direction extends the shade material from the rotatable roller, and rotation of said rotatable roller in a second opposite direction retracts the shade material onto the rotatable roller; a biasing assembly associated with the rotatable roller to apply a biasing force to said roller in the second opposite direction to retract the shade material onto the rotatable roller; a longitudinal member having a longitudinal length that extends at least partially within the internal cavity of the rotatable roller; a moveable member extending at least partially within the internal cavity of the rotatable roller, the moveable member moveable along the longitudinal length of the longitudinal member and moveable within the internal cavity of the rotatable roller with a first frictional resistance; and a holding mechanism associated with the moveable member and the longitudinal member wherein an engagement portion of the moveable member is configured to engage a holding portion of the longitudinal member to further increase frictional resistance to; resist while permitting rotation and translation of the moveable member with respect to the longitudinal member with a second resistance greater than the first frictional force, and resist rotation of the rotatable roller.

19. The retractable shade of claim 18, wherein the longitudinal member has a first knuckle that defines a transition in a direction of a first thread and the moveable member has a second knuckle that defines a transition in a direction of a second thread, wherein the first knuckle forms the holding portion of the longitudinal member and the second knuckle forms the engagement portion of the moveable member wherein the first knuckle is configured to engage the second knuckle to resist rotation of the rotatable roller.

20. The retractable shade of claim 19, wherein the first knuckle and the second knuckle are configured to form an over-center-latch that resists movement of the rotatable roller.

21. The retractable shade of claim 18, wherein the holding portion comprises a protrusion and the engagement portion comprises an engagement knuckle wherein the protrusion and the engagement knuckle are configured to engage to generate forces between the protrusion and the engagement knuckle to inhibit the moveable member from disengaging the protrusion.

22. The retractable shade of claim 21, wherein the moveable member is in the form of a collar having an internal thread that corresponds with an external thread on the longitudinal member, and the engagement knuckle protrudes from the collar and has a sloped front engagement surface that is configured to operatively engage the protrusion and resist rotatable roller from rotating.

23. The retractable shade of claim 18 wherein the biasing assembly is configured to exert a variable biasing force on the roller in the retraction direction to at least in part counterbalance a weight of that portion of the shade material that is unwrapped from the rotatable roller.

24. The retractable shade of claim 18, wherein the shade material is wrappable about and unwrappable about the rotatable roller for retraction and extension of the shade material respectively, wherein at an extended position of said shade material from said rotatable roller, the frictional resistance of the holding mechanism between the moveable member and the longitudinal member increases to the second frictional resistance to restrict movement of the rotatable roller in a retraction direction to restrict retraction of said shade material; and rotation of the rotatable roller to retract said shade material disengages the engagement portion of the moveable member from the holding portion of the longitudinal member to permit retraction of the shade material.

25. The retractable shade of claim 18, wherein the longitudinal member comprises a first thread extending at a first angle along and with respect to the longitudinal length of the longitudinal member, the first thread of the longitudinal member having first and second terminal ends and engageable with a second thread on the moveable member such that the moveable member in response to rotation of said roller rotates with the roller and translates along the longitudinal length of the longitudinal member, the second thread on the moveable member extending at a first angle and having first and second terminal ends.

26. The retractable shade of claim 25, wherein the first thread of the longitudinal member has at or near one of its terminal ends a first knuckle that defines a transition that decreases the first angle of the first thread.

27. The retractable shade of claim 26, wherein the second thread of the moveable member has at or near one of its terminus ends a second knuckle that defines a transition that decreases the first angle of the second thread.

28. The retractable shade of claim 26, wherein the first angle forms a steep angle with respect to the longitudinal length of the longitudinal member.

29. The retractable shade of claim 18, wherein the holding portion is located at or near an end of the longitudinal member to increase frictional resistance with the moveable member at or near the end of the longitudinal member to the second frictional resistance, wherein the increased frictional resistance to the second frictional resistance increases resistance to rotation of the rotatable roller while permitting movement of the moveable member with respect to the longitudinal member.

30. The retractable shade of claim 18, wherein engagement of the holding portion with the engagement portion increases frictional resistance to the second frictional resistance resists rotation of the rotatable member while permitting further rotational movement of the rotatable roller in either a retraction or an extension direction.

31. A retractable shade comprising: a rotatable roller having an internal cavity; a shade material attached to said roller, wherein rotation of said rotatable roller in a first direction extends the shade material from the rotatable roller, and rotation of the rotatable roller in a second opposite direction retracts the shade material onto the rotatable roller, the shade material comprising at least one vane configured to transition from a closed position to an open position when substantially the entire shade is extended from the rotatable roller; a longitudinal member having external threads extending at least partially within the internal cavity of the rotatable roller; at least one biasing member positioned at least partially within the internal cavity of the rotatable roller; a movable member having internal threads for engaging the external threads of the longitudinal member, wherein said movable member is mounted on said longitudinal member such that the movable member translates along the longitudinal member during rotation of the rotatable roller to vary a

biasing force provided to said roller by the biasing member; and a vane orientation holding mechanism associated with the moveable member and configured to hold the at least one vane in the open position, wherein the moveable member comprises an engagement portion configured to increase frictional resistance to inhibit rotation of the rotatable roller to hold the at least one vane in the open position.
