

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12405507
B2
September 02, 2025
Brown; Robert D. et al.

Transparent waveguide display with grating lamina that both couple and extract modulated light

Abstract

One embodiment provides an apparatus for displaying an image comprising: a first optical substrate comprising at least one waveguide layer configured to propagate light in a first direction, wherein the at least one waveguide layer of the first optical substrate comprises at least one grating lamina configured to extract the light from the first substrate along the first direction; and a second optical substrate comprising at least one waveguide layer configured to propagate the light in a second direction, wherein the at least one waveguide layer of the second optical substrate comprises at least one grating lamina configured to extract light from the second substrate along the second direction; wherein the at least one grating lamina of at least one of the first and second optical substrates comprises an SBG in a passive mode.

Inventors: Brown; Robert D. (Lake Oswego, OR), Grant; Alastair John (San Jose, CA), Hendrick; Wyatt L. (San Diego, CA), Popovich; Milan Momcilo (Leicester, GB), Stanley; James H. (Palo Alto, CA), Waldern; Jonathan David (Diablo, CA)

Applicant: DigiLens Inc. (Sunnyvale, CA); Rockwell Collins, Inc. (Cedar Rapids, IA)

Family ID: 49619798

Assignee: DigiLens Inc. (Sunnyvale, CA); Rockwell Collins, Inc. (Cedar Rapids, IA)

Appl. No.: 17/933462

Filed: September 19, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230081115 A1	Mar. 16, 2023

Related U.S. Application Data

continuation parent-doc US 17153588 20210120 US 11448937 child-doc US 17933462
continuation parent-doc US 15943590 20180402 ABANDONED child-doc US 17153588
continuation parent-doc US 14044676 20131002 US 9933684 20180403 child-doc US 15943590
continuation-in-part parent-doc US 13844456 20130315 US 11320571 20220503 child-doc US 14044676
us-provisional-application US 61849853 20130204
us-provisional-application US 61796632 20121116

Publication Classification

Int. Cl.: **G02F1/29** (20060101); **G02B5/18** (20060101); **G02B27/01** (20060101); **G02B27/42** (20060101); F21V8/00 (20060101)

U.S. Cl.:

CPC **G02F1/29** (20130101); **G02B5/1814** (20130101); **G02B27/0172** (20130101); **G02B27/4272** (20130101); G02B6/0013 (20130101); G02B2027/0118 (20130101); G03H2260/34 (20130101)

Field of Classification Search

CPC: G02F (1/29); G02B (5/1814); G02B (27/0172); G02B (27/4272); G02B (6/0013); G02B (2027/0118); G03H (2260/34)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1043938	12/1911	Huttenlocher	N/A	N/A
2141884	12/1937	Sonnefeld	N/A	N/A
3482498	12/1968	Becker	N/A	N/A
3620601	12/1970	Leonard et al.	N/A	N/A
3741716	12/1972	Johne et al.	N/A	N/A
3804496	12/1973	Crane et al.	N/A	N/A
3843231	12/1973	Borel et al.	N/A	N/A
3851303	12/1973	Muller	N/A	N/A
3885095	12/1974	Wolfson et al.	N/A	N/A
3940204	12/1975	Withrington	N/A	N/A
3965029	12/1975	Arora	N/A	N/A
3975711	12/1975	McMahon	N/A	N/A
4028725	12/1976	Lewis	N/A	N/A
4035068	12/1976	Rawson	N/A	N/A
4066334	12/1977	Fray et al.	N/A	N/A
4082432	12/1977	Kirschner	N/A	N/A
4099841	12/1977	Ellis	N/A	N/A
4133152	12/1978	Penrose	N/A	N/A
4178074	12/1978	Heller	N/A	N/A
4218111	12/1979	Withrington et al.	N/A	N/A

4232943	12/1979	Rogers	N/A	N/A
4248093	12/1980	Andersson et al.	N/A	N/A
4251137	12/1980	Knop et al.	N/A	N/A
4309070	12/1981	St. Leger Searle	N/A	N/A
4322163	12/1981	Schiller	N/A	N/A
4386361	12/1982	Simmonds	N/A	N/A
4389612	12/1982	Simmonds et al.	N/A	N/A
4403189	12/1982	Simmonds	N/A	N/A
4403827	12/1982	Bryan et al.	N/A	N/A
4418993	12/1982	Lipton	N/A	N/A
4472037	12/1983	Lipton	N/A	N/A
4523226	12/1984	Lipton et al.	N/A	N/A
4544267	12/1984	Schiller	N/A	N/A
4562463	12/1984	Lipton	N/A	N/A
4566758	12/1985	Bos et al.	N/A	N/A
4583117	12/1985	Lipton et al.	N/A	N/A
4643515	12/1986	Upatnieks	N/A	N/A
4647967	12/1986	Kirschner et al.	N/A	N/A
4688900	12/1986	Doane et al.	N/A	N/A
4711512	12/1986	Upatnieks	N/A	N/A
4714320	12/1986	Banbury	N/A	N/A
4728547	12/1987	Vaz et al.	N/A	N/A
4729640	12/1987	Sakata et al.	N/A	N/A
4741926	12/1987	White et al.	N/A	N/A
4743083	12/1987	Schimpe	N/A	N/A
4749256	12/1987	Bell et al.	N/A	N/A
4765703	12/1987	Suzuki et al.	N/A	N/A
4775218	12/1987	Wood et al.	N/A	N/A
4791788	12/1987	Simmonds et al.	N/A	N/A
4792850	12/1987	Liptoh et al.	N/A	N/A
4794021	12/1987	Potter	N/A	N/A
4799765	12/1988	Ferrer	N/A	N/A
4811414	12/1988	Fishbine et al.	N/A	N/A
4848093	12/1988	Simmonds et al.	N/A	N/A
4852988	12/1988	Velez et al.	N/A	N/A
4854688	12/1988	Hayford et al.	N/A	N/A
4860294	12/1988	Winzer et al.	N/A	N/A
4884876	12/1988	Lipton et al.	N/A	N/A
4890902	12/1989	Doane et al.	N/A	N/A
4928301	12/1989	Smoot	N/A	N/A
4933976	12/1989	Fishbine et al.	N/A	N/A
4938568	12/1989	Margerum et al.	N/A	N/A
4946245	12/1989	Chamberlin et al.	N/A	N/A
4960311	12/1989	Moss et al.	N/A	N/A
4964701	12/1989	Dorschner et al.	N/A	N/A
4967268	12/1989	Lipton et al.	N/A	N/A
4970129	12/1989	Ingwall et al.	N/A	N/A
4971719	12/1989	Vaz et al.	N/A	N/A
4994204	12/1990	Doane et al.	N/A	N/A
5004323	12/1990	West	N/A	N/A

5007711	12/1990	Wood et al.	N/A	N/A
5009483	12/1990	Rockwell et al.	N/A	N/A
5011624	12/1990	Yamagishi et al.	N/A	N/A
5016953	12/1990	Moss et al.	N/A	N/A
5033814	12/1990	Brown et al.	N/A	N/A
5035734	12/1990	Honkanen et al.	N/A	N/A
5053834	12/1990	Simmonds	N/A	N/A
5063441	12/1990	Lipton et al.	N/A	N/A
5076664	12/1990	Migozzi	N/A	N/A
5079416	12/1991	Filipovich	N/A	N/A
5096282	12/1991	Margerum et al.	N/A	N/A
5099343	12/1991	Margerum et al.	N/A	N/A
5109465	12/1991	Klopotek	N/A	N/A
5110034	12/1991	Simmonds et al.	N/A	N/A
5117285	12/1991	Nelson et al.	N/A	N/A
5117302	12/1991	Lipton	N/A	N/A
5119454	12/1991	McMahon et al.	N/A	N/A
5124821	12/1991	Antier et al.	N/A	N/A
5138687	12/1991	Horie et al.	N/A	N/A
5139192	12/1991	Simmonds et al.	N/A	N/A
5142357	12/1991	Lipton et al.	N/A	N/A
5142644	12/1991	Vansteenkiste et al.	N/A	N/A
5148302	12/1991	Nagano et al.	N/A	N/A
5150234	12/1991	Takahashi et al.	N/A	N/A
5151958	12/1991	Honkanen	N/A	N/A
5153751	12/1991	Ishikawa et al.	N/A	N/A
5159445	12/1991	Gitlin et al.	N/A	N/A
5160523	12/1991	Honkanen et al.	N/A	N/A
5166989	12/1991	Kurdi et al.	N/A	N/A
5181133	12/1992	Lipton	N/A	N/A
5183545	12/1992	Branca et al.	N/A	N/A
5187597	12/1992	Kato et al.	N/A	N/A
5193000	12/1992	Lipton et al.	N/A	N/A
5198912	12/1992	Ingwall et al.	N/A	N/A
5198914	12/1992	Arns	N/A	N/A
5200861	12/1992	Moskovich et al.	N/A	N/A
5210624	12/1992	Matsumoto et al.	N/A	N/A
5210801	12/1992	Fournier et al.	N/A	N/A
5218360	12/1992	Goetz et al.	N/A	N/A
5218480	12/1992	Moskovich et al.	N/A	N/A
5224198	12/1992	Jachimowicz et al.	N/A	N/A
5225918	12/1992	Taniguchi et al.	N/A	N/A
5239372	12/1992	Lipton	N/A	N/A
5240636	12/1992	Doane et al.	N/A	N/A
5241337	12/1992	Betensky et al.	N/A	N/A
5242476	12/1992	Bartel et al.	N/A	N/A
5243413	12/1992	Gitlin et al.	N/A	N/A
5251048	12/1992	Doane et al.	N/A	N/A
5264950	12/1992	West et al.	N/A	N/A
5268792	12/1992	Kreitzer et al.	N/A	N/A

5284499	12/1993	Harvey et al.	N/A	N/A
5289315	12/1993	Makita et al.	N/A	N/A
5295208	12/1993	Caulfield et al.	N/A	N/A
5296967	12/1993	Moskovich et al.	N/A	N/A
5299289	12/1993	Omae et al.	N/A	N/A
5303085	12/1993	Rallison	N/A	N/A
5306923	12/1993	Kazmierski et al.	N/A	N/A
5309283	12/1993	Kreitzer et al.	N/A	N/A
5313330	12/1993	Betensky	N/A	N/A
5315324	12/1993	Kubelik et al.	N/A	N/A
5315419	12/1993	Saupe et al.	N/A	N/A
5315440	12/1993	Betensky et al.	N/A	N/A
5317405	12/1993	Kuriki et al.	N/A	N/A
5327269	12/1993	Tilton et al.	N/A	N/A
5329363	12/1993	Moskovich et al.	N/A	N/A
5341230	12/1993	Smith	N/A	N/A
5343147	12/1993	Sager et al.	N/A	N/A
5351151	12/1993	Levy	N/A	N/A
5359362	12/1993	Lewis et al.	N/A	N/A
5363220	12/1993	Kuwayama et al.	N/A	N/A
5368770	12/1993	Saupe et al.	N/A	N/A
5369511	12/1993	Amos	N/A	N/A
5371626	12/1993	Betensky	N/A	N/A
5400069	12/1994	Braun et al.	N/A	N/A
5408346	12/1994	Trissel et al.	N/A	N/A
5410370	12/1994	Janssen	N/A	N/A
5410376	12/1994	Cornsweet et al.	N/A	N/A
5416510	12/1994	Lipton et al.	N/A	N/A
5416514	12/1994	Janssen et al.	N/A	N/A
5418584	12/1994	Larson	N/A	N/A
5418871	12/1994	Revelli et al.	N/A	N/A
5428480	12/1994	Betensky et al.	N/A	N/A
5437811	12/1994	Doane et al.	N/A	N/A
5438357	12/1994	McNelley	N/A	N/A
5452385	12/1994	Izumi et al.	N/A	N/A
5453863	12/1994	West et al.	N/A	N/A
5455693	12/1994	Wreede et al.	N/A	N/A
5455713	12/1994	Kreitzer et al.	N/A	N/A
5462700	12/1994	Beeson et al.	N/A	N/A
5463428	12/1994	Lipton et al.	N/A	N/A
5465311	12/1994	Caulfield et al.	N/A	N/A
5471326	12/1994	Hall et al.	N/A	N/A
5473222	12/1994	Thoeny et al.	N/A	N/A
5476611	12/1994	Nolan et al.	N/A	N/A
5481321	12/1995	Lipton	N/A	N/A
5481385	12/1995	Zimmerman et al.	N/A	N/A
5485313	12/1995	Betensky	N/A	N/A
5493430	12/1995	Lu et al.	N/A	N/A
5493448	12/1995	Betensky et al.	N/A	N/A
5496621	12/1995	Makita et al.	N/A	N/A

5499140	12/1995	Betensky	N/A	N/A
5500671	12/1995	Andersson et al.	N/A	N/A
5500769	12/1995	Betensky	N/A	N/A
5510913	12/1995	Hashimoto et al.	N/A	N/A
5515184	12/1995	Caulfield et al.	N/A	N/A
5516455	12/1995	Jacobine et al.	N/A	N/A
5524272	12/1995	Podowski et al.	N/A	N/A
5528720	12/1995	Winston et al.	N/A	N/A
5530566	12/1995	Kumar	N/A	N/A
5532736	12/1995	Kuriki et al.	N/A	N/A
5532875	12/1995	Betensky	N/A	N/A
5537232	12/1995	Biles	N/A	N/A
RE35310	12/1995	Moskovich	N/A	N/A
5543950	12/1995	Lavrentovich et al.	N/A	N/A
5544268	12/1995	Bischel et al.	N/A	N/A
5559637	12/1995	Moskovich et al.	N/A	N/A
5572248	12/1995	Allen et al.	N/A	N/A
5572250	12/1995	Lipton et al.	N/A	N/A
5576888	12/1995	Betensky	N/A	N/A
5579026	12/1995	Tabata	N/A	N/A
5583795	12/1995	Smyth	N/A	N/A
5585035	12/1995	Nerad et al.	N/A	N/A
5593615	12/1996	Nerad et al.	N/A	N/A
5604611	12/1996	Saburi et al.	N/A	N/A
5606433	12/1996	Yin et al.	N/A	N/A
5612733	12/1996	Flohr	N/A	N/A
5612734	12/1996	Nelson et al.	N/A	N/A
5619254	12/1996	McNelley	N/A	N/A
5619586	12/1996	Sibbald et al.	N/A	N/A
5621529	12/1996	Gordon et al.	N/A	N/A
5621552	12/1996	Coates et al.	N/A	N/A
5625495	12/1996	Moskovich et al.	N/A	N/A
5629259	12/1996	Akada et al.	N/A	N/A
5631107	12/1996	Tarumi et al.	N/A	N/A
5633100	12/1996	Mickish et al.	N/A	N/A
5646785	12/1996	Gilboa et al.	N/A	N/A
5648857	12/1996	Ando et al.	N/A	N/A
5661577	12/1996	Jenkins et al.	N/A	N/A
5661603	12/1996	Hanano et al.	N/A	N/A
5665494	12/1996	Kawabata et al.	N/A	N/A
5668614	12/1996	Chien et al.	N/A	N/A
5668907	12/1996	Veligdan	N/A	N/A
5677797	12/1996	Betensky et al.	N/A	N/A
5680231	12/1996	Grinberg et al.	N/A	N/A
5680411	12/1996	Ramdane et al.	N/A	N/A
5682255	12/1996	Friesem et al.	N/A	N/A
5686931	12/1996	Fuenfschilling et al.	N/A	N/A
5686975	12/1996	Lipton	N/A	N/A
5691795	12/1996	Doane et al.	N/A	N/A
5694230	12/1996	Welch	N/A	N/A

5695682	12/1996	Doane et al.	N/A	N/A
5701132	12/1996	Kollin et al.	N/A	N/A
5706108	12/1997	Ando et al.	N/A	N/A
5706136	12/1997	Okuyama et al.	N/A	N/A
5707925	12/1997	Akada et al.	N/A	N/A
5710645	12/1997	Phillips et al.	N/A	N/A
5724189	12/1997	Ferrante	N/A	N/A
5724463	12/1997	Deacon et al.	N/A	N/A
5726782	12/1997	Kato et al.	N/A	N/A
5727098	12/1997	Jacobson	N/A	N/A
5729242	12/1997	Margerum et al.	N/A	N/A
5731060	12/1997	Hirukawa et al.	N/A	N/A
5731853	12/1997	Taketomi et al.	N/A	N/A
5736424	12/1997	Prybyla et al.	N/A	N/A
5742262	12/1997	Tabata et al.	N/A	N/A
5745266	12/1997	Smith et al.	N/A	N/A
5745301	12/1997	Betensky et al.	N/A	N/A
5748272	12/1997	Tanaka et al.	N/A	N/A
5748277	12/1997	Huang et al.	N/A	N/A
5751452	12/1997	Tanaka et al.	N/A	N/A
5757546	12/1997	Lipton et al.	N/A	N/A
5760931	12/1997	Saburi et al.	N/A	N/A
5760960	12/1997	Lin et al.	N/A	N/A
5764414	12/1997	King et al.	N/A	N/A
5771320	12/1997	Stone	N/A	N/A
5790288	12/1997	Jager et al.	N/A	N/A
5790314	12/1997	Duck et al.	N/A	N/A
5798641	12/1997	Spagna et al.	N/A	N/A
5804609	12/1997	Ohnishi et al.	N/A	N/A
5808804	12/1997	Moskovich	N/A	N/A
5812608	12/1997	Valimaki et al.	N/A	N/A
5822089	12/1997	Phillips et al.	N/A	N/A
5822127	12/1997	Chen et al.	N/A	N/A
5825448	12/1997	Bos et al.	N/A	N/A
5831700	12/1997	Li et al.	N/A	N/A
5835661	12/1997	Tai et al.	N/A	N/A
5841507	12/1997	Barnes	N/A	N/A
5841587	12/1997	Moskovich et al.	N/A	N/A
5847787	12/1997	Fredley et al.	N/A	N/A
5856842	12/1998	Tedesco	N/A	N/A
5857043	12/1998	Cook et al.	N/A	N/A
5867238	12/1998	Miller et al.	N/A	N/A
5867618	12/1998	Ito et al.	N/A	N/A
5868951	12/1998	Schuck, III et al.	N/A	N/A
5870228	12/1998	Kreitzer et al.	N/A	N/A
5875012	12/1998	Crawford et al.	N/A	N/A
5877826	12/1998	Yang et al.	N/A	N/A
5886822	12/1998	Spitzer	N/A	N/A
5892598	12/1998	Asakawa et al.	N/A	N/A
5892599	12/1998	Bahuguna	N/A	N/A

5898511	12/1998	Mizutani et al.	N/A	N/A
5900987	12/1998	Kreitzer et al.	N/A	N/A
5900989	12/1998	Kreitzer	N/A	N/A
5903395	12/1998	Rallison et al.	N/A	N/A
5903396	12/1998	Rallison	N/A	N/A
5907416	12/1998	Hegg et al.	N/A	N/A
5907436	12/1998	Perry et al.	N/A	N/A
5917459	12/1998	Son et al.	N/A	N/A
5926147	12/1998	Sehm et al.	N/A	N/A
5929946	12/1998	Sharp et al.	N/A	N/A
5929960	12/1998	West et al.	N/A	N/A
5930433	12/1998	Williamson et al.	N/A	N/A
5936776	12/1998	Kreitzer	N/A	N/A
5937115	12/1998	Domash	N/A	N/A
5942157	12/1998	Sutherland et al.	N/A	N/A
5945893	12/1998	Plessky et al.	N/A	N/A
5949302	12/1998	Sarkka	N/A	N/A
5949508	12/1998	Kumar et al.	N/A	N/A
5956113	12/1998	Crawford	N/A	N/A
5962147	12/1998	Shalhub et al.	N/A	N/A
5963375	12/1998	Kreitzer	N/A	N/A
5966223	12/1998	Friesem et al.	N/A	N/A
5969874	12/1998	Moskovich	N/A	N/A
5969876	12/1998	Kreitzer et al.	N/A	N/A
5973727	12/1998	McGrew et al.	N/A	N/A
5974162	12/1998	Metz et al.	N/A	N/A
5985422	12/1998	Krauter	N/A	N/A
5986746	12/1998	Metz et al.	N/A	N/A
5991087	12/1998	Rallison	N/A	N/A
5999089	12/1998	Carlson et al.	N/A	N/A
5999282	12/1998	Suzuki et al.	N/A	N/A
5999314	12/1998	Asakura et al.	N/A	N/A
6014187	12/1999	Taketomi et al.	N/A	N/A
6023375	12/1999	Kreitzer	N/A	N/A
6042947	12/1999	Asakura et al.	N/A	N/A
6043585	12/1999	Plessky et al.	N/A	N/A
6046585	12/1999	Simmonds	N/A	N/A
6052540	12/1999	Koyama	N/A	N/A
6061107	12/1999	Yang	N/A	N/A
6061463	12/1999	Metz et al.	N/A	N/A
6069728	12/1999	Huignard et al.	N/A	N/A
6075626	12/1999	Mizutani et al.	N/A	N/A
6078427	12/1999	Fontaine et al.	N/A	N/A
6084998	12/1999	Straayer	N/A	N/A
6094311	12/1999	Moskovich	N/A	N/A
6097551	12/1999	Kreitzer	N/A	N/A
6104448	12/1999	Doane et al.	N/A	N/A
6107943	12/1999	Schroeder	N/A	N/A
6115152	12/1999	Popovich et al.	N/A	N/A
6118908	12/1999	Bischel et al.	N/A	N/A

6121899	12/1999	Theriault	N/A	N/A
6124954	12/1999	Popovich et al.	N/A	N/A
6127066	12/1999	Ueda et al.	N/A	N/A
6128058	12/1999	Walton et al.	N/A	N/A
6133971	12/1999	Silverstein et al.	N/A	N/A
6133975	12/1999	Li et al.	N/A	N/A
6137630	12/1999	Tsou et al.	N/A	N/A
6141074	12/1999	Bos et al.	N/A	N/A
6141154	12/1999	Kreitzer et al.	N/A	N/A
6151142	12/1999	Phillips et al.	N/A	N/A
6154190	12/1999	Yang et al.	N/A	N/A
6156243	12/1999	Kosuga et al.	N/A	N/A
6167169	12/1999	Brinkman et al.	N/A	N/A
6169594	12/2000	Aye et al.	N/A	N/A
6169613	12/2000	Amitai et al.	N/A	N/A
6169636	12/2000	Kreitzer et al.	N/A	N/A
6172792	12/2000	Jepsen et al.	N/A	N/A
6176837	12/2000	Foxlin	N/A	N/A
6185015	12/2000	Reinhorn et al.	N/A	N/A
6185016	12/2000	Popovich	N/A	N/A
6188462	12/2000	Lavrentovich et al.	N/A	N/A
6191887	12/2000	Michaloski et al.	N/A	N/A
6195206	12/2000	Yona et al.	N/A	N/A
6195209	12/2000	Kreitzer et al.	N/A	N/A
6204835	12/2000	Yang et al.	N/A	N/A
6211976	12/2000	Popovich et al.	N/A	N/A
6215579	12/2000	Bloom et al.	N/A	N/A
6218316	12/2000	Marsh	N/A	N/A
6222297	12/2000	Perdue	N/A	N/A
6222675	12/2000	Mall et al.	N/A	N/A
6222971	12/2000	Veligdan et al.	N/A	N/A
6249386	12/2000	Yona et al.	N/A	N/A
6259423	12/2000	Tokito et al.	N/A	N/A
6259559	12/2000	Kobayashi et al.	N/A	N/A
6266166	12/2000	Katsumata et al.	N/A	N/A
6268839	12/2000	Yang et al.	N/A	N/A
6269203	12/2000	Davies et al.	N/A	N/A
6275031	12/2000	Simmonds et al.	N/A	N/A
6278429	12/2000	Ruth et al.	N/A	N/A
6281457	12/2000	Chang	N/A	N/A
6285813	12/2000	Schultz et al.	N/A	N/A
6297860	12/2000	Moskovich et al.	N/A	N/A
6301056	12/2000	Kreitzer et al.	N/A	N/A
6301057	12/2000	Kreitzer et al.	N/A	N/A
6317083	12/2000	Johnson et al.	N/A	N/A
6317227	12/2000	Mizutani et al.	N/A	N/A
6317228	12/2000	Popovich et al.	N/A	N/A
6317528	12/2000	Gadkaree et al.	N/A	N/A
6320563	12/2000	Yang et al.	N/A	N/A
6321069	12/2000	Piirainen	N/A	N/A

6323970	12/2000	Popovich	N/A	N/A
6323989	12/2000	Jacobson et al.	N/A	N/A
6324014	12/2000	Moskovich et al.	N/A	N/A
6327089	12/2000	Hosaki et al.	N/A	N/A
6330109	12/2000	Ishii et al.	N/A	N/A
6333819	12/2000	Svedenkrans	N/A	N/A
6335224	12/2001	Peterson et al.	N/A	N/A
6339486	12/2001	Popovich	N/A	N/A
6340540	12/2001	Ueda et al.	N/A	N/A
6351273	12/2001	Lemelson et al.	N/A	N/A
6351333	12/2001	Araki et al.	N/A	N/A
6356172	12/2001	Koivisto et al.	N/A	N/A
6356674	12/2001	Davis et al.	N/A	N/A
6359730	12/2001	Tervonen	N/A	N/A
6359737	12/2001	Stringfellow	N/A	N/A
6366281	12/2001	Lipton et al.	N/A	N/A
6366369	12/2001	Ichikawa et al.	N/A	N/A
6366378	12/2001	Tervonen et al.	N/A	N/A
6377238	12/2001	McPheters	N/A	N/A
6377321	12/2001	Khan et al.	N/A	N/A
6388797	12/2001	Lipton et al.	N/A	N/A
6392812	12/2001	Howard	N/A	N/A
6407724	12/2001	Waldern et al.	N/A	N/A
6409687	12/2001	Foxlin	N/A	N/A
6411444	12/2001	Moskovich et al.	N/A	N/A
6414760	12/2001	Lopez et al.	N/A	N/A
6417971	12/2001	Moskovich et al.	N/A	N/A
6437563	12/2001	Simmonds et al.	N/A	N/A
6437886	12/2001	Trepanier et al.	N/A	N/A
6445512	12/2001	Moskovich et al.	N/A	N/A
6449095	12/2001	Ohtaki et al.	N/A	N/A
6456584	12/2001	Nagata et al.	N/A	N/A
6470132	12/2001	Nousiainen et al.	N/A	N/A
6473209	12/2001	Popovich	N/A	N/A
6476974	12/2001	Kreitzer et al.	N/A	N/A
6483303	12/2001	Simmonds et al.	N/A	N/A
6486997	12/2001	Bruzzzone et al.	N/A	N/A
6504518	12/2002	Kuwayama et al.	N/A	N/A
6504629	12/2002	Popovich et al.	N/A	N/A
6509937	12/2002	Moskovich et al.	N/A	N/A
6510263	12/2002	Maisenhoelder et al.	N/A	N/A
6518747	12/2002	Sager et al.	N/A	N/A
6519088	12/2002	Lipton	N/A	N/A
6522794	12/2002	Bischel et al.	N/A	N/A
6522795	12/2002	Jordan et al.	N/A	N/A
6524771	12/2002	Maeda et al.	N/A	N/A
6529336	12/2002	Kreitzer et al.	N/A	N/A
6534977	12/2002	Duncan et al.	N/A	N/A
6538775	12/2002	Bowley et al.	N/A	N/A

6545778	12/2002	Ono et al.	N/A	N/A
6545808	12/2002	Ehbets et al.	N/A	N/A
6550949	12/2002	Bauer et al.	N/A	N/A
6552789	12/2002	Modro	N/A	N/A
6557413	12/2002	Nieminen et al.	N/A	N/A
6559813	12/2002	DeLuca et al.	N/A	N/A
6560019	12/2002	Nakai	N/A	N/A
6563648	12/2002	Gleckman et al.	N/A	N/A
6563650	12/2002	Moskovich et al.	N/A	N/A
6567014	12/2002	Hansen et al.	N/A	N/A
6567573	12/2002	Domash et al.	N/A	N/A
6577411	12/2002	David et al.	N/A	N/A
6577429	12/2002	Kurtz et al.	N/A	N/A
6580529	12/2002	Amitai et al.	N/A	N/A
6583838	12/2002	Hoke et al.	N/A	N/A
6583873	12/2002	Goncharov et al.	N/A	N/A
6587619	12/2002	Kinoshita	N/A	N/A
6594090	12/2002	Kruschwitz et al.	N/A	N/A
6596193	12/2002	Coates et al.	N/A	N/A
6597176	12/2002	Simmonds et al.	N/A	N/A
6597475	12/2002	Shirakura et al.	N/A	N/A
6598987	12/2002	Parikka	N/A	N/A
6600590	12/2002	Roddy et al.	N/A	N/A
6608720	12/2002	Freeman	N/A	N/A
6611253	12/2002	Cohen	N/A	N/A
6618104	12/2002	Date et al.	N/A	N/A
6624943	12/2002	Nakai et al.	N/A	N/A
6625381	12/2002	Roddy et al.	N/A	N/A
6646772	12/2002	Popovich et al.	N/A	N/A
6646810	12/2002	Harter, Jr. et al.	N/A	N/A
6661578	12/2002	Hedrick	N/A	N/A
6667134	12/2002	Sutherland et al.	N/A	N/A
6674578	12/2003	Sugiyama et al.	N/A	N/A
6677086	12/2003	Sutehrland et al.	N/A	N/A
6678093	12/2003	Scobey et al.	N/A	N/A
6680720	12/2003	Lee et al.	N/A	N/A
6686815	12/2003	Mirshekarl-Syahkal et al.	N/A	N/A
6690516	12/2003	Aritake et al.	N/A	N/A
6692666	12/2003	Sutherland et al.	N/A	N/A
6699407	12/2003	Sutehrland et al.	N/A	N/A
6706086	12/2003	Emig et al.	N/A	N/A
6706451	12/2003	Sutherland et al.	N/A	N/A
6721096	12/2003	Bruzzo et al.	N/A	N/A
6730442	12/2003	Sutherland et al.	N/A	N/A
6731434	12/2003	Hua et al.	N/A	N/A
6738105	12/2003	Hannah et al.	N/A	N/A
6741189	12/2003	Gibbons, II et al.	N/A	N/A
6744478	12/2003	Asakura et al.	N/A	N/A
6747781	12/2003	Trisnadi et al.	N/A	N/A

6748342	12/2003	Dickhaus	N/A	N/A
6750941	12/2003	Satoh et al.	N/A	N/A
6750995	12/2003	Dickson	N/A	N/A
6750996	12/2003	Jagt et al.	N/A	N/A
6757105	12/2003	Niv et al.	N/A	N/A
6771403	12/2003	Endo et al.	N/A	N/A
6776339	12/2003	Piikivi	N/A	N/A
6781701	12/2003	Sweetser et al.	N/A	N/A
6791629	12/2003	Moskovich et al.	N/A	N/A
6791739	12/2003	Ramanujan et al.	N/A	N/A
6804066	12/2003	Ha et al.	N/A	N/A
6805490	12/2003	Levola	N/A	N/A
6821457	12/2003	Natarajan et al.	N/A	N/A
6822713	12/2003	Yaroshchuk et al.	N/A	N/A
6825987	12/2003	Repetto et al.	N/A	N/A
6829095	12/2003	Amitai	N/A	N/A
6830789	12/2003	Doane et al.	N/A	N/A
6833955	12/2003	Niv	N/A	N/A
6836369	12/2003	Fujikawa et al.	N/A	N/A
6842563	12/2004	Zhang et al.	N/A	N/A
6844212	12/2004	Bond et al.	N/A	N/A
6844980	12/2004	He et al.	N/A	N/A
6844989	12/2004	Jo et al.	N/A	N/A
6847274	12/2004	Salmela et al.	N/A	N/A
6847488	12/2004	Travis	N/A	N/A
6850210	12/2004	Lipton et al.	N/A	N/A
6853491	12/2004	Ruhle et al.	N/A	N/A
6853493	12/2004	Kreitzer et al.	N/A	N/A
6861107	12/2004	Klasen-memmer et al.	N/A	N/A
6864861	12/2004	Schehrer et al.	N/A	N/A
6864927	12/2004	Cathey	N/A	N/A
6864931	12/2004	Kumar et al.	N/A	N/A
6867888	12/2004	Sutherland et al.	N/A	N/A
6873443	12/2004	Joubert et al.	N/A	N/A
6876791	12/2004	Murashima et al.	N/A	N/A
6878494	12/2004	Sutehrland et al.	N/A	N/A
6885483	12/2004	Takada	N/A	N/A
6903872	12/2004	Schrader	N/A	N/A
6909345	12/2004	Salmela et al.	N/A	N/A
6917375	12/2004	Akada et al.	N/A	N/A
6919003	12/2004	Ikeda et al.	N/A	N/A
6922267	12/2004	Endo et al.	N/A	N/A
6926429	12/2004	Barlow et al.	N/A	N/A
6927570	12/2004	Simmonds et al.	N/A	N/A
6927694	12/2004	Smith et al.	N/A	N/A
6940361	12/2004	Jokio et al.	N/A	N/A
6943788	12/2004	Tomono	N/A	N/A
6950173	12/2004	Sutherland et al.	N/A	N/A
6950227	12/2004	Schrader	N/A	N/A

6951393	12/2004	Koide	N/A	N/A
6952312	12/2004	Weber et al.	N/A	N/A
6952435	12/2004	Lai et al.	N/A	N/A
6958662	12/2004	Salmela et al.	N/A	N/A
6958868	12/2004	Pender	N/A	N/A
6963454	12/2004	Martins et al.	N/A	N/A
6972788	12/2004	Robertson et al.	N/A	N/A
6975345	12/2004	Lipton et al.	N/A	N/A
6980365	12/2004	Moskovich	N/A	N/A
6985296	12/2005	Lipton et al.	N/A	N/A
6987908	12/2005	Bond et al.	N/A	N/A
6999239	12/2005	Martins et al.	N/A	N/A
7002618	12/2005	Lipton et al.	N/A	N/A
7002753	12/2005	Moskovich et al.	N/A	N/A
7003075	12/2005	Miyake et al.	N/A	N/A
7003187	12/2005	Frick et al.	N/A	N/A
7006732	12/2005	Gunn, III et al.	N/A	N/A
7009773	12/2005	Chaoulov et al.	N/A	N/A
7018563	12/2005	Sutherland et al.	N/A	N/A
7018686	12/2005	Sutehrland et al.	N/A	N/A
7018744	12/2005	Otaki et al.	N/A	N/A
7019793	12/2005	Moskovich et al.	N/A	N/A
7021777	12/2005	Amitai	N/A	N/A
7026892	12/2005	Kajiya	N/A	N/A
7027671	12/2005	Huck et al.	N/A	N/A
7034748	12/2005	Kajiya	N/A	N/A
7046439	12/2005	Kaminsky et al.	N/A	N/A
7050674	12/2005	Lee et al.	N/A	N/A
7053735	12/2005	Salmela et al.	N/A	N/A
7053991	12/2005	Sandusky	N/A	N/A
7054045	12/2005	McPheters et al.	N/A	N/A
7058434	12/2005	Wang et al.	N/A	N/A
7068405	12/2005	Sutherland et al.	N/A	N/A
7068898	12/2005	Buretea et al.	N/A	N/A
7072020	12/2005	Sutherland et al.	N/A	N/A
7075273	12/2005	O'Gorman et al.	N/A	N/A
7077984	12/2005	Natarajan et al.	N/A	N/A
7081215	12/2005	Natarajan et al.	N/A	N/A
7088457	12/2005	Zou et al.	N/A	N/A
7088515	12/2005	Lipton	N/A	N/A
7095562	12/2005	Peng et al.	N/A	N/A
7099080	12/2005	Lipton et al.	N/A	N/A
7101048	12/2005	Travis	N/A	N/A
7108383	12/2005	Mitchell et al.	N/A	N/A
7110184	12/2005	Yona et al.	N/A	N/A
7119965	12/2005	Rolland et al.	N/A	N/A
7123418	12/2005	Weber et al.	N/A	N/A
7123421	12/2005	Moskovich et al.	N/A	N/A
7126418	12/2005	Hunton et al.	N/A	N/A
7126583	12/2005	Breed	N/A	N/A

7132200	12/2005	Ueda et al.	N/A	N/A
7133084	12/2005	Moskovich et al.	N/A	N/A
7139109	12/2005	Mukawa	N/A	N/A
RE39424	12/2005	Moskovich	N/A	N/A
7145729	12/2005	Kreitzer et al.	N/A	N/A
7149385	12/2005	Parikka et al.	N/A	N/A
7151246	12/2005	Fein et al.	N/A	N/A
7158095	12/2006	Jenson et al.	N/A	N/A
7167286	12/2006	Anderson et al.	N/A	N/A
7167616	12/2006	Ling et al.	N/A	N/A
7175780	12/2006	Sutherland et al.	N/A	N/A
7181105	12/2006	Teramura et al.	N/A	N/A
7181108	12/2006	Levola	N/A	N/A
7184002	12/2006	Lipton et al.	N/A	N/A
7184615	12/2006	Levola	N/A	N/A
7186567	12/2006	Sutherland et al.	N/A	N/A
7190849	12/2006	Katase	N/A	N/A
7198737	12/2006	Natarajan et al.	N/A	N/A
7199934	12/2006	Yamasaki	N/A	N/A
7205960	12/2006	David	N/A	N/A
7205964	12/2006	Yokoyama et al.	N/A	N/A
7206107	12/2006	Levola	N/A	N/A
7212175	12/2006	Magee et al.	N/A	N/A
7218817	12/2006	Magnusson et al.	N/A	N/A
7230767	12/2006	Walck et al.	N/A	N/A
7230770	12/2006	Kreitzer et al.	N/A	N/A
7242527	12/2006	Spitzer et al.	N/A	N/A
7248128	12/2006	Mattila et al.	N/A	N/A
7248765	12/2006	Lee et al.	N/A	N/A
7256915	12/2006	Sutherland et al.	N/A	N/A
7259906	12/2006	Islam	N/A	N/A
7265882	12/2006	Sutherland et al.	N/A	N/A
7265903	12/2006	Sutherland et al.	N/A	N/A
7268946	12/2006	Wang	N/A	N/A
7280722	12/2006	Temkin et al.	N/A	N/A
7285903	12/2006	Cull et al.	N/A	N/A
7286272	12/2006	Mukawa	N/A	N/A
7289069	12/2006	Ranta	N/A	N/A
RE39911	12/2006	Moskovich	N/A	N/A
7299983	12/2006	Piikivi	N/A	N/A
7301601	12/2006	Lin et al.	N/A	N/A
7312906	12/2006	Sutherland et al.	N/A	N/A
7313291	12/2006	Okhotnikov et al.	N/A	N/A
D559250	12/2007	Pombo	N/A	N/A
7319573	12/2007	Nishiyama	N/A	N/A
7320534	12/2007	Sugikawa et al.	N/A	N/A
7323275	12/2007	Otaki et al.	N/A	N/A
7333685	12/2007	Stone et al.	N/A	N/A
7336271	12/2007	Ozeki et al.	N/A	N/A
7339737	12/2007	Urey et al.	N/A	N/A

7339742	12/2007	Amitai et al.	N/A	N/A
7349612	12/2007	Nishii et al.	N/A	N/A
7356218	12/2007	Kato et al.	N/A	N/A
7356224	12/2007	Levner et al.	N/A	N/A
7369911	12/2007	Volant et al.	N/A	N/A
7375870	12/2007	Schorpp	N/A	N/A
7375886	12/2007	Lipton et al.	N/A	N/A
7376068	12/2007	Khoury	N/A	N/A
7376307	12/2007	Singh et al.	N/A	N/A
7389023	12/2007	Yeo et al.	N/A	N/A
7391573	12/2007	Amitai	N/A	N/A
7394865	12/2007	Borran et al.	N/A	N/A
7394961	12/2007	Kornilovich et al.	N/A	N/A
7395181	12/2007	Foxlin	N/A	N/A
7397606	12/2007	Peng et al.	N/A	N/A
7401920	12/2007	Kranz et al.	N/A	N/A
7404644	12/2007	Evans et al.	N/A	N/A
7410286	12/2007	Travis	N/A	N/A
7411637	12/2007	Weiss	N/A	N/A
7413678	12/2007	Natarajan et al.	N/A	N/A
7413679	12/2007	Sutherland et al.	N/A	N/A
7415173	12/2007	Kassamakov et al.	N/A	N/A
7416818	12/2007	Sutherland et al.	N/A	N/A
7418170	12/2007	Mukawa et al.	N/A	N/A
7420733	12/2007	Natarajan et al.	N/A	N/A
7433116	12/2007	Islam	N/A	N/A
7436568	12/2007	Kuykendall, Jr.	N/A	N/A
D581447	12/2007	Yee	N/A	N/A
7447967	12/2007	Onggosanusi et al.	N/A	N/A
7453612	12/2007	Mukawa	N/A	N/A
7454103	12/2007	Parriaux	N/A	N/A
7457040	12/2007	Amitai	N/A	N/A
7466994	12/2007	Pihlaja et al.	N/A	N/A
7477206	12/2008	Cowan et al.	N/A	N/A
7479354	12/2008	Ueda et al.	N/A	N/A
7480215	12/2008	Makela et al.	N/A	N/A
7482996	12/2008	Larson et al.	N/A	N/A
7483604	12/2008	Levola	N/A	N/A
7492512	12/2008	Niv et al.	N/A	N/A
7496293	12/2008	Shamir et al.	N/A	N/A
7499217	12/2008	Cakmakci et al.	N/A	N/A
7500104	12/2008	Goland	N/A	N/A
7511891	12/2008	Messerschmidt	N/A	N/A
7513668	12/2008	Peng et al.	N/A	N/A
7522344	12/2008	Curatu et al.	N/A	N/A
7525448	12/2008	Wilson et al.	N/A	N/A
7528385	12/2008	Volodin et al.	N/A	N/A
7542210	12/2008	Chirieleison	N/A	N/A
7545429	12/2008	Travis	N/A	N/A
7550234	12/2008	Otaki et al.	N/A	N/A

7558446	12/2008	Wimberger-friedl et al.	N/A	N/A
7567372	12/2008	Schorpp	N/A	N/A
7570322	12/2008	Sutherland et al.	N/A	N/A
7570405	12/2008	Sutherland et al.	N/A	N/A
7570429	12/2008	Maliah et al.	N/A	N/A
7572555	12/2008	Takizawa et al.	N/A	N/A
7573640	12/2008	Nivon et al.	N/A	N/A
7576916	12/2008	Amitai	N/A	N/A
7577326	12/2008	Amitai	N/A	N/A
7579119	12/2008	Ueda et al.	N/A	N/A
7583423	12/2008	Sutherland et al.	N/A	N/A
7587110	12/2008	Singh et al.	N/A	N/A
7588863	12/2008	Takizawa et al.	N/A	N/A
7589900	12/2008	Powell	N/A	N/A
7589901	12/2008	DeJong et al.	N/A	N/A
7592988	12/2008	Katase	N/A	N/A
7593575	12/2008	Houle et al.	N/A	N/A
7597447	12/2008	Larson et al.	N/A	N/A
7599012	12/2008	Nakamura et al.	N/A	N/A
7600893	12/2008	Laino et al.	N/A	N/A
7602552	12/2008	Blumenfeld	N/A	N/A
7605719	12/2008	Wenger et al.	N/A	N/A
7605774	12/2008	Brandt et al.	N/A	N/A
7605882	12/2008	Sutherland et al.	N/A	N/A
7616270	12/2008	Hirabayashi et al.	N/A	N/A
7617022	12/2008	Wood et al.	N/A	N/A
7618750	12/2008	Ueda et al.	N/A	N/A
7619739	12/2008	Sutherland et al.	N/A	N/A
7619825	12/2008	Peng et al.	N/A	N/A
7629086	12/2008	Otaki et al.	N/A	N/A
7639208	12/2008	Ha et al.	N/A	N/A
7639911	12/2008	Lee et al.	N/A	N/A
7643214	12/2009	Amitai	N/A	N/A
7643225	12/2009	Tsai	N/A	N/A
7656585	12/2009	Powell et al.	N/A	N/A
7660047	12/2009	Travis et al.	N/A	N/A
7672024	12/2009	Kuan	N/A	N/A
7672055	12/2009	Amitai	N/A	N/A
7672549	12/2009	Ghosh et al.	N/A	N/A
7675021	12/2009	Lapstun	N/A	N/A
7675684	12/2009	Weissman et al.	N/A	N/A
7691248	12/2009	Ikeda et al.	N/A	N/A
7710622	12/2009	Takabayashi et al.	N/A	N/A
7710654	12/2009	Ashkenazi et al.	N/A	N/A
7711228	12/2009	Noda et al.	N/A	N/A
7724441	12/2009	Amitai	N/A	N/A
7724442	12/2009	Amitai	N/A	N/A
7724443	12/2009	Amitai	N/A	N/A
7733571	12/2009	Li	N/A	N/A

7733572	12/2009	Brown et al.	N/A	N/A
7740387	12/2009	Schultz et al.	N/A	N/A
7747113	12/2009	Mukawa et al.	N/A	N/A
7751122	12/2009	Amitai	N/A	N/A
7751662	12/2009	Kleemann et al.	N/A	N/A
7764413	12/2009	Levola	N/A	N/A
7777819	12/2009	Simmonds	N/A	N/A
7778305	12/2009	Parriaux et al.	N/A	N/A
7778508	12/2009	Hirayama	N/A	N/A
7843642	12/2009	Shaoulov et al.	N/A	N/A
7847235	12/2009	Krupkin et al.	N/A	N/A
7864427	12/2010	Korenaga et al.	N/A	N/A
7865080	12/2010	Hecker et al.	N/A	N/A
7866869	12/2010	Karakawa	N/A	N/A
7872707	12/2010	Sutherland et al.	N/A	N/A
7872804	12/2010	Moon et al.	N/A	N/A
7884593	12/2010	Simmonds et al.	N/A	N/A
7884985	12/2010	Amitai et al.	N/A	N/A
7887186	12/2010	Watanabe	N/A	N/A
7903921	12/2010	Ostergard	N/A	N/A
7907342	12/2010	Simmonds et al.	N/A	N/A
7920787	12/2010	Gentner et al.	N/A	N/A
7928862	12/2010	Matthews	N/A	N/A
7936513	12/2010	Wu et al.	N/A	N/A
7936519	12/2010	Mukawa et al.	N/A	N/A
7944428	12/2010	Travis	N/A	N/A
7944616	12/2010	Mukawa	N/A	N/A
7949214	12/2010	DeJong et al.	N/A	N/A
D640310	12/2010	Suzuki et al.	N/A	N/A
7961117	12/2010	Zimmerman et al.	N/A	N/A
7969644	12/2010	Tilleman et al.	N/A	N/A
7969657	12/2010	Cakmakci et al.	N/A	N/A
7970246	12/2010	Travis et al.	N/A	N/A
7976208	12/2010	Travis	N/A	N/A
7984884	12/2010	Iliev et al.	N/A	N/A
7999982	12/2010	Endo et al.	N/A	N/A
8000020	12/2010	Amitai et al.	N/A	N/A
8000491	12/2010	Brodkin et al.	N/A	N/A
8004765	12/2010	Amitai	N/A	N/A
8014050	12/2010	McGrew	N/A	N/A
8016475	12/2010	Travis	N/A	N/A
8018579	12/2010	Krah	N/A	N/A
8022942	12/2010	Bathiche et al.	N/A	N/A
8023783	12/2010	Mukawa et al.	N/A	N/A
RE42992	12/2010	David	N/A	N/A
8073296	12/2010	Mukawa et al.	N/A	N/A
8077274	12/2010	Sutherland et al.	N/A	N/A
8079713	12/2010	Ashkenazi	N/A	N/A
8082222	12/2010	Rangarajan et al.	N/A	N/A
8086030	12/2010	Gordon et al.	N/A	N/A

8089568	12/2011	Brown et al.	N/A	N/A
8093451	12/2011	Spangenberg et al.	N/A	N/A
8098439	12/2011	Amitai et al.	N/A	N/A
8105662	12/2011	Cherkaoui et al.	N/A	N/A
8107023	12/2011	Simmonds et al.	N/A	N/A
8107780	12/2011	Simmonds	N/A	N/A
8120548	12/2011	Barber	N/A	N/A
8120848	12/2011	Isano	N/A	N/A
8132948	12/2011	Owen et al.	N/A	N/A
8132976	12/2011	Odell et al.	N/A	N/A
8134434	12/2011	Diederichs et al.	N/A	N/A
8136690	12/2011	Fang et al.	N/A	N/A
8137981	12/2011	Andrew et al.	N/A	N/A
8142016	12/2011	Legerton et al.	N/A	N/A
8149086	12/2011	Klein et al.	N/A	N/A
8152315	12/2011	Travis et al.	N/A	N/A
8152353	12/2011	Yang et al.	N/A	N/A
8155489	12/2011	Saarikko et al.	N/A	N/A
8159752	12/2011	Wertheim et al.	N/A	N/A
8160409	12/2011	Large	N/A	N/A
8160411	12/2011	Levola et al.	N/A	N/A
D659137	12/2011	Matsumoto	N/A	N/A
8167173	12/2011	Simmonds et al.	N/A	N/A
8186874	12/2011	Sinbar et al.	N/A	N/A
8188925	12/2011	DeJean	N/A	N/A
8189263	12/2011	Wang et al.	N/A	N/A
8189973	12/2011	Travis et al.	N/A	N/A
D661334	12/2011	Cho et al.	N/A	N/A
D661335	12/2011	Jeon	N/A	N/A
8194325	12/2011	Levola et al.	N/A	N/A
8199803	12/2011	Hauske et al.	N/A	N/A
8202405	12/2011	Meneghini et al.	N/A	N/A
8213065	12/2011	Mukawa	N/A	N/A
8213755	12/2011	Mukawa et al.	N/A	N/A
8220966	12/2011	Mukawa	N/A	N/A
8224133	12/2011	Popovich et al.	N/A	N/A
8233204	12/2011	Robbins et al.	N/A	N/A
8253914	12/2011	Kajiya et al.	N/A	N/A
8254031	12/2011	Levola	N/A	N/A
8264498	12/2011	Vanderkamp et al.	N/A	N/A
8294749	12/2011	Cable	N/A	N/A
8295710	12/2011	Marcus	N/A	N/A
8301031	12/2011	Gentner et al.	N/A	N/A
8305577	12/2011	Kivioja et al.	N/A	N/A
8306423	12/2011	Gottwald et al.	N/A	N/A
8310327	12/2011	Willers et al.	N/A	N/A
8314819	12/2011	Kimmel et al.	N/A	N/A
8314993	12/2011	Levola et al.	N/A	N/A
8320032	12/2011	Levola	N/A	N/A
8321810	12/2011	Heintze	N/A	N/A

8325166	12/2011	Akutsu et al.	N/A	N/A
8329773	12/2011	Fäcke et al.	N/A	N/A
8335040	12/2011	Mukawa et al.	N/A	N/A
8335414	12/2011	Zinoviev et al.	N/A	N/A
D673996	12/2012	Kim et al.	N/A	N/A
8351744	12/2012	Travis et al.	N/A	N/A
8354640	12/2012	Hamre et al.	N/A	N/A
8354806	12/2012	Travis et al.	N/A	N/A
8355610	12/2012	Simmonds	N/A	N/A
8369019	12/2012	Baker et al.	N/A	N/A
8376548	12/2012	Schultz	N/A	N/A
8382293	12/2012	Phillips, III et al.	N/A	N/A
8384504	12/2012	Diederichs et al.	N/A	N/A
8384694	12/2012	Powell et al.	N/A	N/A
8384730	12/2012	Vanderkamp et al.	N/A	N/A
8396339	12/2012	Mukawa et al.	N/A	N/A
8396341	12/2012	Lee et al.	N/A	N/A
8398242	12/2012	Yamamoto et al.	N/A	N/A
8403490	12/2012	Sugiyama et al.	N/A	N/A
8422840	12/2012	Large	N/A	N/A
8427439	12/2012	Larsen et al.	N/A	N/A
8432363	12/2012	Saarikko et al.	N/A	N/A
8432372	12/2012	Butler et al.	N/A	N/A
8432614	12/2012	Amitai	N/A	N/A
8441731	12/2012	Sprague	N/A	N/A
8447365	12/2012	Imanuel	N/A	N/A
8466953	12/2012	Levola	N/A	N/A
8472119	12/2012	Kelly	N/A	N/A
8472120	12/2012	Border et al.	N/A	N/A
8477261	12/2012	Travis et al.	N/A	N/A
8481130	12/2012	Harding et al.	N/A	N/A
8482858	12/2012	Sprague	N/A	N/A
8488246	12/2012	Border et al.	N/A	N/A
8491121	12/2012	Tilleman et al.	N/A	N/A
8491136	12/2012	Travis et al.	N/A	N/A
8493366	12/2012	Bathiche et al.	N/A	N/A
8493562	12/2012	Kopp et al.	N/A	N/A
8493662	12/2012	Noui	N/A	N/A
8494229	12/2012	Jarvenpaa et al.	N/A	N/A
8503841	12/2012	Kopp et al.	N/A	N/A
8508848	12/2012	Saarikko	N/A	N/A
8520309	12/2012	Sprague	N/A	N/A
D691192	12/2012	Stanley et al.	N/A	N/A
8547638	12/2012	Levola	N/A	N/A
8548290	12/2012	Travers et al.	N/A	N/A
8565560	12/2012	Popovich et al.	N/A	N/A
D694310	12/2012	Cho et al.	N/A	N/A
D694311	12/2012	Cho et al.	N/A	N/A
8578038	12/2012	Kaikuranta et al.	N/A	N/A
8581831	12/2012	Travis	N/A	N/A

8582206	12/2012	Travis	N/A	N/A
8593734	12/2012	Laakkonen	N/A	N/A
8611014	12/2012	Valera et al.	N/A	N/A
8619062	12/2012	Powell et al.	N/A	N/A
D697130	12/2013	Lövgren	N/A	N/A
8633786	12/2013	Ermolov et al.	N/A	N/A
8634120	12/2013	Popovich et al.	N/A	N/A
8634139	12/2013	Brown et al.	N/A	N/A
8639072	12/2013	Popovich et al.	N/A	N/A
8643691	12/2013	Rosenfeld et al.	N/A	N/A
8643948	12/2013	Amitai et al.	N/A	N/A
8649099	12/2013	Schultz et al.	N/A	N/A
8654420	12/2013	Simmonds	N/A	N/A
8659826	12/2013	Brown et al.	N/A	N/A
D701206	12/2013	Luckey et al.	N/A	N/A
8670029	12/2013	McEldowney	N/A	N/A
8693087	12/2013	Nowatzky et al.	N/A	N/A
8698705	12/2013	Burke	N/A	N/A
8731350	12/2013	Lin et al.	N/A	N/A
8736802	12/2013	Kajiya et al.	N/A	N/A
8736963	12/2013	Robbins et al.	N/A	N/A
8742952	12/2013	Bold	N/A	N/A
8746008	12/2013	Mauritsen et al.	N/A	N/A
8749886	12/2013	Gupta	N/A	N/A
8749890	12/2013	Wood et al.	N/A	N/A
8767294	12/2013	Chen et al.	N/A	N/A
8786923	12/2013	Chuang et al.	N/A	N/A
8810600	12/2013	Bohn et al.	N/A	N/A
8810913	12/2013	Simmonds et al.	N/A	N/A
8810914	12/2013	Amitai	N/A	N/A
8814691	12/2013	Haddick et al.	N/A	N/A
8816578	12/2013	Peng et al.	N/A	N/A
8817350	12/2013	Robbins et al.	N/A	N/A
8824836	12/2013	Sugiyama	N/A	N/A
8830143	12/2013	Pitchford et al.	N/A	N/A
8830584	12/2013	Saarikko et al.	N/A	N/A
8830588	12/2013	Brown et al.	N/A	N/A
8842368	12/2013	Simmonds et al.	N/A	N/A
8859412	12/2013	Jain	N/A	N/A
8872435	12/2013	Kreitzer et al.	N/A	N/A
8873149	12/2013	Bohn et al.	N/A	N/A
8873150	12/2013	Amitai	N/A	N/A
D718304	12/2013	Heinrich	N/A	N/A
D718366	12/2013	Mehin et al.	N/A	N/A
8885112	12/2013	Popovich et al.	N/A	N/A
8885997	12/2013	Nguyen et al.	N/A	N/A
8903207	12/2013	Brown et al.	N/A	N/A
8906088	12/2013	Pugh et al.	N/A	N/A
8913324	12/2013	Schrader	N/A	N/A
8913865	12/2013	Bennett	N/A	N/A

8917453	12/2013	Bohn	N/A	N/A
8917962	12/2013	Nichol et al.	N/A	N/A
8929589	12/2014	Publicover et al.	N/A	N/A
8933144	12/2014	Enomoto et al.	N/A	N/A
8934743	12/2014	Nishiwaki et al.	N/A	N/A
8937771	12/2014	Robbins et al.	N/A	N/A
8937772	12/2014	Burns et al.	N/A	N/A
8938141	12/2014	Magnusson	N/A	N/A
8950867	12/2014	Macnamara	N/A	N/A
8964298	12/2014	Haddick et al.	N/A	N/A
8965152	12/2014	Simmonds	N/A	N/A
D725102	12/2014	Lee et al.	N/A	N/A
8985803	12/2014	Bohn	N/A	N/A
8989535	12/2014	Robbins	N/A	N/A
D726180	12/2014	Roat et al.	N/A	N/A
9019595	12/2014	Jain	N/A	N/A
9025253	12/2014	Hadad et al.	N/A	N/A
9035344	12/2014	Jain	N/A	N/A
D733709	12/2014	Kawai	N/A	N/A
9075184	12/2014	Popovich et al.	N/A	N/A
9081178	12/2014	Simmonds et al.	N/A	N/A
9097890	12/2014	Miller et al.	N/A	N/A
9103978	12/2014	Nishiwaki et al.	N/A	N/A
9122015	12/2014	Shimizu	N/A	N/A
9128226	12/2014	Fattal et al.	N/A	N/A
9129295	12/2014	Border et al.	N/A	N/A
9164290	12/2014	Robbins et al.	N/A	N/A
9176324	12/2014	Scherer et al.	N/A	N/A
9188717	12/2014	Nishiwaki	N/A	N/A
9201270	12/2014	Fattal et al.	N/A	N/A
9215293	12/2014	Miller	N/A	N/A
D746896	12/2015	Markovitz et al.	N/A	N/A
9239507	12/2015	Chen et al.	N/A	N/A
9244275	12/2015	Li	N/A	N/A
9244280	12/2015	Tiana et al.	N/A	N/A
9244281	12/2015	Zimmerman et al.	N/A	N/A
D749074	12/2015	Cazalet et al.	N/A	N/A
9253359	12/2015	Takahashi	N/A	N/A
9269854	12/2015	Jain	N/A	N/A
D751551	12/2015	Ho et al.	N/A	N/A
D752129	12/2015	Lee et al.	N/A	N/A
9274338	12/2015	Robbins et al.	N/A	N/A
9274339	12/2015	Brown et al.	N/A	N/A
9274349	12/2015	Popovich et al.	N/A	N/A
D754782	12/2015	Kokinakis et al.	N/A	N/A
9310566	12/2015	Valera et al.	N/A	N/A
9316786	12/2015	Nishiwaki et al.	N/A	N/A
9329325	12/2015	Simmonds et al.	N/A	N/A
9335548	12/2015	Cakmakci et al.	N/A	N/A
9335604	12/2015	Popovich et al.	N/A	N/A

9341846	12/2015	Popovich et al.	N/A	N/A
9354366	12/2015	Jain	N/A	N/A
9366862	12/2015	Haddick et al.	N/A	N/A
9366864	12/2015	Brown et al.	N/A	N/A
9372347	12/2015	Levola et al.	N/A	N/A
9377623	12/2015	Robbins et al.	N/A	N/A
9377852	12/2015	Shapiro et al.	N/A	N/A
9389415	12/2015	Fattal et al.	N/A	N/A
9400395	12/2015	Travers et al.	N/A	N/A
9423360	12/2015	Kostamo et al.	N/A	N/A
9429692	12/2015	Saarikko et al.	N/A	N/A
9431794	12/2015	Jain	N/A	N/A
9435961	12/2015	Jiang	N/A	N/A
9456744	12/2015	Popovich et al.	N/A	N/A
9459451	12/2015	Saarikko et al.	N/A	N/A
9464779	12/2015	Popovich et al.	N/A	N/A
9465213	12/2015	Simmonds	N/A	N/A
9465227	12/2015	Popovich et al.	N/A	N/A
9484482	12/2015	Hsu et al.	N/A	N/A
9494799	12/2015	Robbins et al.	N/A	N/A
9507150	12/2015	Stratton et al.	N/A	N/A
9513480	12/2015	Saarikko et al.	N/A	N/A
9516193	12/2015	Aramaki	N/A	N/A
9519089	12/2015	Brown et al.	N/A	N/A
9519115	12/2015	Yashiki et al.	N/A	N/A
9523852	12/2015	Brown et al.	N/A	N/A
9535253	12/2016	Levola et al.	N/A	N/A
9541383	12/2016	Abovitz et al.	N/A	N/A
9541763	12/2016	Heberlein et al.	N/A	N/A
9547174	12/2016	Gao et al.	N/A	N/A
9551468	12/2016	Jones	N/A	N/A
9551874	12/2016	Amitai	N/A	N/A
9551880	12/2016	Amitai	N/A	N/A
9599813	12/2016	Stratton et al.	N/A	N/A
9612403	12/2016	Abovitz et al.	N/A	N/A
9632226	12/2016	Waldern et al.	N/A	N/A
9635352	12/2016	Henry et al.	N/A	N/A
9648313	12/2016	Henry et al.	N/A	N/A
9651368	12/2016	Abovitz et al.	N/A	N/A
9664824	12/2016	Simmonds et al.	N/A	N/A
9664910	12/2016	Mansharof et al.	N/A	N/A
9671612	12/2016	Kress et al.	N/A	N/A
9674413	12/2016	Tiana et al.	N/A	N/A
9678345	12/2016	Melzer et al.	N/A	N/A
9679367	12/2016	Wald	N/A	N/A
9715067	12/2016	Brown et al.	N/A	N/A
9715110	12/2016	Brown et al.	N/A	N/A
D793468	12/2016	Yu et al.	N/A	N/A
D795865	12/2016	Porter et al.	N/A	N/A
D795866	12/2016	Porter et al.	N/A	N/A

9726540	12/2016	Popovich et al.	N/A	N/A
9727772	12/2016	Popovich et al.	N/A	N/A
9733475	12/2016	Brown et al.	N/A	N/A
9739950	12/2016	Sqalli et al.	N/A	N/A
9746688	12/2016	Popovich et al.	N/A	N/A
9754507	12/2016	Wenger et al.	N/A	N/A
9762895	12/2016	Henry et al.	N/A	N/A
9766465	12/2016	Tiana et al.	N/A	N/A
9785231	12/2016	Zimmerman	N/A	N/A
9791694	12/2016	Haverkamp et al.	N/A	N/A
9791696	12/2016	Woltman et al.	N/A	N/A
9791703	12/2016	Vallius et al.	N/A	N/A
9804316	12/2016	Drolet et al.	N/A	N/A
9804389	12/2016	Popovich et al.	N/A	N/A
9823423	12/2016	Waldern et al.	N/A	N/A
9857605	12/2017	Popovich et al.	N/A	N/A
9874931	12/2017	Koenck et al.	N/A	N/A
9891436	12/2017	Wall et al.	N/A	N/A
9899800	12/2017	Ferrotti et al.	N/A	N/A
9915825	12/2017	Robbins et al.	N/A	N/A
9933684	12/2017	Brown et al.	N/A	N/A
9939577	12/2017	Inoue et al.	N/A	N/A
9939628	12/2017	Basset et al.	N/A	N/A
9959818	12/2017	Bohn	N/A	N/A
9977247	12/2017	Brown et al.	N/A	N/A
9989763	12/2017	Woltman et al.	N/A	N/A
10025093	12/2017	Wall et al.	N/A	N/A
D827641	12/2017	Morisawa	N/A	N/A
10067347	12/2017	Vallius et al.	N/A	N/A
10088675	12/2017	Brown et al.	N/A	N/A
10088686	12/2017	Robbins et al.	N/A	N/A
10089516	12/2017	Popovich et al.	N/A	N/A
10095045	12/2017	Robbins et al.	N/A	N/A
10107966	12/2017	Horibe et al.	N/A	N/A
10114220	12/2017	Grey et al.	N/A	N/A
10126552	12/2017	Brown et al.	N/A	N/A
10156681	12/2017	Waldern et al.	N/A	N/A
10162181	12/2017	Webster et al.	N/A	N/A
10185154	12/2018	Popovich et al.	N/A	N/A
D840454	12/2018	Han et al.	N/A	N/A
10197804	12/2018	Stenberg et al.	N/A	N/A
10209517	12/2018	Popovich et al.	N/A	N/A
10216061	12/2018	Popovich et al.	N/A	N/A
10234696	12/2018	Popovich et al.	N/A	N/A
10241330	12/2018	Popovich et al.	N/A	N/A
10241332	12/2018	Vallius	N/A	N/A
10247943	12/2018	Yu et al.	N/A	N/A
10281725	12/2018	Yokoyama	N/A	N/A
10330777	12/2018	Popovich et al.	N/A	N/A
10345519	12/2018	Miller et al.	N/A	N/A

10359627	12/2018	Wall et al.	N/A	N/A
10359635	12/2018	Grey et al.	N/A	N/A
10359736	12/2018	Popovich et al.	N/A	N/A
D855687	12/2018	Villalpando	N/A	N/A
D859510	12/2018	Harmon et al.	N/A	N/A
10409144	12/2018	Popovich et al.	N/A	N/A
10423222	12/2018	Popovich et al.	N/A	N/A
10423813	12/2018	Popovich et al.	N/A	N/A
10437051	12/2018	Popovich et al.	N/A	N/A
10437064	12/2018	Popovich et al.	N/A	N/A
10444510	12/2018	Lee et al.	N/A	N/A
10459145	12/2018	Popovich et al.	N/A	N/A
10459311	12/2018	Popovich et al.	N/A	N/A
D871494	12/2018	Yamada et al.	N/A	N/A
10509241	12/2018	Robbins et al.	N/A	N/A
D872170	12/2019	Evans et al.	N/A	N/A
D872794	12/2019	Wilkins	N/A	N/A
10527797	12/2019	Waldern et al.	N/A	N/A
10532594	12/2019	Akahane et al.	N/A	N/A
10545346	12/2019	Waldern et al.	N/A	N/A
10551616	12/2019	Wall et al.	N/A	N/A
10560688	12/2019	Robbins	N/A	N/A
10569449	12/2019	Curts et al.	N/A	N/A
10578876	12/2019	Lam et al.	N/A	N/A
10591756	12/2019	Popovich et al.	N/A	N/A
10598938	12/2019	Huang et al.	N/A	N/A
D880575	12/2019	Thixton	N/A	N/A
10613268	12/2019	Colburn et al.	N/A	N/A
10642058	12/2019	Popovich et al.	N/A	N/A
10649119	12/2019	Mohanty et al.	N/A	N/A
10670876	12/2019	Popovich et al.	N/A	N/A
10678053	12/2019	Waldern et al.	N/A	N/A
10690831	12/2019	Calafiore	N/A	N/A
10690851	12/2019	Waldern et al.	N/A	N/A
10690915	12/2019	Popovich et al.	N/A	N/A
10690916	12/2019	Popovich et al.	N/A	N/A
10698214	12/2019	Vallius et al.	N/A	N/A
10705281	12/2019	Fattal et al.	N/A	N/A
10712571	12/2019	Popovich et al.	N/A	N/A
10725312	12/2019	Popovich et al.	N/A	N/A
10732351	12/2019	Colburn et al.	N/A	N/A
10732569	12/2019	Waldern et al.	N/A	N/A
10746989	12/2019	Brown et al.	N/A	N/A
10747982	12/2019	Popovich et al.	N/A	N/A
10795160	12/2019	Stanley et al.	N/A	N/A
10823887	12/2019	Calafiore et al.	N/A	N/A
10859768	12/2019	Popovich et al.	N/A	N/A
10859837	12/2019	Adema et al.	N/A	N/A
10890707	12/2020	Waldern et al.	N/A	N/A
10914950	12/2020	Waldern et al.	N/A	N/A

10942430	12/2020	Waldern et al.	N/A	N/A
10983257	12/2020	Colburn et al.	N/A	N/A
10983340	12/2020	Popovich et al.	N/A	N/A
10983346	12/2020	Vallius et al.	N/A	N/A
11009699	12/2020	Popovich et al.	N/A	N/A
11103892	12/2020	Liao et al.	N/A	N/A
11106048	12/2020	Popovich et al.	N/A	N/A
11107972	12/2020	Diest et al.	N/A	N/A
11137603	12/2020	Zhang	N/A	N/A
11169314	12/2020	Popovich	N/A	G02B 6/0016
11175512	12/2020	Waldern et al.	N/A	N/A
11194098	12/2020	Waldern et al.	N/A	N/A
11194159	12/2020	Popovich et al.	N/A	N/A
11194162	12/2020	Waldern et al.	N/A	N/A
11204540	12/2020	Popovich et al.	N/A	N/A
11231544	12/2021	Lin et al.	N/A	N/A
11243333	12/2021	Ouderkirk et al.	N/A	N/A
11256155	12/2021	Popovich et al.	N/A	N/A
11281013	12/2021	Popovich et al.	N/A	N/A
11287666	12/2021	Popovich et al.	N/A	N/A
11300795	12/2021	Stanley et al.	N/A	N/A
11306193	12/2021	Lane et al.	N/A	N/A
11307357	12/2021	Mohanty	N/A	N/A
11307432	12/2021	Popovich et al.	N/A	N/A
11320571	12/2021	Brown et al.	N/A	N/A
11340386	12/2021	Ouderkirk et al.	N/A	N/A
11378732	12/2021	Waldern et al.	N/A	N/A
11391950	12/2021	Calafiore	N/A	N/A
11402801	12/2021	Waldern et al.	N/A	N/A
11442222	12/2021	Waldern et al.	N/A	N/A
11448937	12/2021	Brown et al.	N/A	N/A
11460621	12/2021	Popovich	N/A	G02B 27/0176
11513350	12/2021	Waldern et al.	N/A	N/A
11543594	12/2022	Grant et al.	N/A	N/A
11579455	12/2022	Stanley et al.	N/A	N/A
11586046	12/2022	Waldern et al.	N/A	N/A
11604314	12/2022	Popovich et al.	N/A	N/A
11703645	12/2022	Waldern et al.	N/A	N/A
11726332	12/2022	Waldern et al.	N/A	N/A
11754842	12/2022	Popovich et al.	N/A	N/A
11815781	12/2022	Brown	N/A	G02B 27/4272
11874477	12/2023	Popovich et al.	N/A	N/A
12140764	12/2023	Popovich et al.	N/A	N/A
12248150	12/2024	Waldern et al.	N/A	N/A
2001/0024177	12/2000	Popovich	N/A	N/A
2001/0033400	12/2000	Sutherland et al.	N/A	N/A
2001/0036012	12/2000	Nakai et al.	N/A	N/A

2001/0043163	12/2000	Waldern et al.	N/A	N/A
2001/0046142	12/2000	Van Santen et al.	N/A	N/A
2001/0050756	12/2000	Lipton et al.	N/A	N/A
2002/0003509	12/2001	Lipton et al.	N/A	N/A
2002/0009299	12/2001	Lipton	N/A	N/A
2002/0011969	12/2001	Lipton et al.	N/A	N/A
2002/0012064	12/2001	Yamaguchi	N/A	N/A
2002/0018040	12/2001	Aye et al.	N/A	N/A
2002/0021407	12/2001	Elliott	N/A	N/A
2002/0021461	12/2001	Ono et al.	N/A	N/A
2002/0036825	12/2001	Lipton et al.	N/A	N/A
2002/0047837	12/2001	Suyama et al.	N/A	N/A
2002/0071472	12/2001	Dickson et al.	N/A	N/A
2002/0075240	12/2001	Lieberman et al.	N/A	N/A
2002/0093701	12/2001	Zhang et al.	N/A	N/A
2002/0110077	12/2001	Drobot et al.	N/A	N/A
2002/0126332	12/2001	Popovich	N/A	N/A
2002/0127497	12/2001	Brown et al.	N/A	N/A
2002/0131175	12/2001	Yagi et al.	N/A	N/A
2002/0150032	12/2001	Nishiuchi et al.	N/A	N/A
2002/0150337	12/2001	Fujimaki	N/A	N/A
2002/0167462	12/2001	Lewis et al.	N/A	N/A
2002/0196332	12/2001	Lipton et al.	N/A	N/A
2003/0007070	12/2002	Lipton et al.	N/A	N/A
2003/0025881	12/2002	Hwang	N/A	N/A
2003/0030912	12/2002	Gleckman et al.	N/A	N/A
2003/0038912	12/2002	Broer et al.	N/A	N/A
2003/0039442	12/2002	Bond et al.	N/A	N/A
2003/0063042	12/2002	Friesem et al.	N/A	N/A
2003/0063884	12/2002	Smith et al.	N/A	N/A
2003/0067685	12/2002	Niv	N/A	N/A
2003/0076590	12/2002	Kramer	N/A	N/A
2003/0086670	12/2002	Moridaira et al.	N/A	N/A
2003/0107809	12/2002	Chen et al.	N/A	N/A
2003/0129542	12/2002	Shih et al.	N/A	N/A
2003/0149346	12/2002	Arnone et al.	N/A	N/A
2003/0175004	12/2002	Garito et al.	N/A	N/A
2003/0184868	12/2002	Geist	N/A	N/A
2003/0193709	12/2002	Mallya et al.	N/A	N/A
2003/0197154	12/2002	Manabe et al.	N/A	N/A
2003/0197157	12/2002	Sutherland et al.	N/A	N/A
2003/0202247	12/2002	Niv et al.	N/A	N/A
2003/0206329	12/2002	Ikeda et al.	N/A	N/A
2003/0228019	12/2002	Eichler et al.	N/A	N/A
2004/0004767	12/2003	Song	N/A	N/A
2004/0004989	12/2003	Shigeoka	N/A	N/A
2004/0012833	12/2003	Newswanger et al.	N/A	N/A
2004/0047938	12/2003	Kosuga et al.	N/A	N/A
2004/0057138	12/2003	Tanijiri et al.	N/A	N/A
2004/0075830	12/2003	Miyake et al.	N/A	N/A

2004/0089842	12/2003	Suthehrland et al.	N/A	N/A
2004/0108971	12/2003	Waldern et al.	N/A	N/A
2004/0109234	12/2003	Levola	N/A	N/A
2004/0112862	12/2003	Smith et al.	N/A	N/A
2004/0125454	12/2003	Kawasaki et al.	N/A	N/A
2004/0130797	12/2003	Leigh	N/A	N/A
2004/0141217	12/2003	Endo et al.	N/A	N/A
2004/0156008	12/2003	Reznikov et al.	N/A	N/A
2004/0174348	12/2003	David	N/A	N/A
2004/0175627	12/2003	Sutherland et al.	N/A	N/A
2004/0179764	12/2003	Melikechi et al.	N/A	N/A
2004/0184156	12/2003	Gunn, III et al.	N/A	N/A
2004/0188617	12/2003	Devitt et al.	N/A	N/A
2004/0200368	12/2003	Ogino et al.	N/A	N/A
2004/0208446	12/2003	Bond et al.	N/A	N/A
2004/0208466	12/2003	Mossberg et al.	N/A	N/A
2004/0225025	12/2003	Sullivan et al.	N/A	N/A
2004/0263969	12/2003	Lipton et al.	N/A	N/A
2004/0263971	12/2003	Lipton et al.	N/A	N/A
2005/0018304	12/2004	Lipton et al.	N/A	N/A
2005/0047705	12/2004	Domash et al.	N/A	N/A
2005/0079663	12/2004	Masutani et al.	N/A	N/A
2005/0083564	12/2004	Mallya et al.	N/A	N/A
2005/0105909	12/2004	Stone	N/A	N/A
2005/0122395	12/2004	Lipton et al.	N/A	N/A
2005/0134404	12/2004	Kajiya et al.	N/A	N/A
2005/0135747	12/2004	Greiner et al.	N/A	N/A
2005/0136260	12/2004	Garcia	N/A	N/A
2005/0141066	12/2004	Ouchi	N/A	N/A
2005/0141811	12/2004	Yang et al.	N/A	N/A
2005/0169579	12/2004	Temkin et al.	N/A	N/A
2005/0174321	12/2004	Ikeda et al.	N/A	N/A
2005/0180687	12/2004	Amitai	N/A	N/A
2005/0195276	12/2004	Lipton et al.	N/A	N/A
2005/0218377	12/2004	Lawandy	N/A	N/A
2005/0231774	12/2004	Hayashi et al.	N/A	N/A
2005/0232530	12/2004	Kekas	N/A	N/A
2005/0254752	12/2004	Domash et al.	N/A	N/A
2005/0259217	12/2004	Lin et al.	N/A	N/A
2005/0259302	12/2004	Metz et al.	N/A	N/A
2005/0259944	12/2004	Anderson et al.	N/A	N/A
2005/0265585	12/2004	Rowe	N/A	N/A
2005/0269481	12/2004	David et al.	N/A	N/A
2005/0271258	12/2004	Rowe	N/A	N/A
2005/0286133	12/2004	Lipton	N/A	N/A
2006/0002274	12/2005	Kihara et al.	N/A	N/A
2006/0012878	12/2005	Lipton et al.	N/A	N/A
2006/0013977	12/2005	Duke et al.	N/A	N/A
2006/0043938	12/2005	O'Gorman et al.	N/A	N/A
2006/0055993	12/2005	Kobayashi et al.	N/A	N/A

2006/0093012	12/2005	Singh et al.	N/A	N/A
2006/0093793	12/2005	Miyakawa et al.	N/A	N/A
2006/0114564	12/2005	Sutherland et al.	N/A	N/A
2006/0119837	12/2005	Raguin et al.	N/A	N/A
2006/0119916	12/2005	Sutherland et al.	N/A	N/A
2006/0126179	12/2005	Levola	N/A	N/A
2006/0132914	12/2005	Weiss et al.	N/A	N/A
2006/0142455	12/2005	Agarwal et al.	N/A	N/A
2006/0146422	12/2005	Koike	N/A	N/A
2006/0159864	12/2005	Natarajan et al.	N/A	N/A
2006/0164593	12/2005	Peyghambarian et al.	N/A	N/A
2006/0171647	12/2005	Ye et al.	N/A	N/A
2006/0177180	12/2005	Tazawa et al.	N/A	N/A
2006/0181683	12/2005	Bhowmik et al.	N/A	N/A
2006/0191293	12/2005	Kuczma	N/A	N/A
2006/0215244	12/2005	Yosha et al.	N/A	N/A
2006/0215976	12/2005	Singh et al.	N/A	N/A
2006/0221063	12/2005	Ishihara	N/A	N/A
2006/0221448	12/2005	Nivon et al.	N/A	N/A
2006/0228073	12/2005	Mukawa et al.	N/A	N/A
2006/0262250	12/2005	Hobbs	N/A	N/A
2006/0268104	12/2005	Cowan et al.	N/A	N/A
2006/0268412	12/2005	Downing et al.	N/A	N/A
2006/0279662	12/2005	Kapellner et al.	N/A	N/A
2006/0284974	12/2005	Lipton et al.	N/A	N/A
2006/0285205	12/2005	Lipton et al.	N/A	N/A
2006/0291021	12/2005	Mukawa	N/A	N/A
2006/0291052	12/2005	Lipton et al.	N/A	N/A
2006/0292493	12/2005	Shinotsuka et al.	N/A	N/A
2007/0012777	12/2006	Tsikos et al.	N/A	N/A
2007/0019152	12/2006	Caputo et al.	N/A	N/A
2007/0019297	12/2006	Stewart et al.	N/A	N/A
2007/0034600	12/2006	Willson et al.	N/A	N/A
2007/0041684	12/2006	Popovich et al.	N/A	N/A
2007/0045596	12/2006	King et al.	N/A	N/A
2007/0052929	12/2006	Allman et al.	N/A	N/A
2007/0053032	12/2006	Popovich	N/A	N/A
2007/0070476	12/2006	Yamada et al.	N/A	N/A
2007/0070504	12/2006	Akutsu et al.	N/A	N/A
2007/0070859	12/2006	Hirayama	N/A	N/A
2007/0089625	12/2006	Grinberg et al.	N/A	N/A
2007/0097502	12/2006	Lipton et al.	N/A	N/A
2007/0109400	12/2006	Woodgate et al.	N/A	N/A
2007/0109401	12/2006	Lipton et al.	N/A	N/A
2007/0115553	12/2006	Chang-Hasnain et al.	N/A	N/A
2007/0116409	12/2006	Bryan et al.	N/A	N/A
2007/0127348	12/2006	Ooi et al.	N/A	N/A
2007/0133089	12/2006	Lipton et al.	N/A	N/A

2007/0133920	12/2006	Lee et al.	N/A	N/A
2007/0133983	12/2006	Traff	N/A	N/A
2007/0146624	12/2006	Duston et al.	N/A	N/A
2007/0146625	12/2006	Ooi et al.	N/A	N/A
2007/0154153	12/2006	Fomitchov et al.	N/A	N/A
2007/0160325	12/2006	Son et al.	N/A	N/A
2007/0177007	12/2006	Lipton et al.	N/A	N/A
2007/0182915	12/2006	Osawa et al.	N/A	N/A
2007/0183650	12/2006	Lipton et al.	N/A	N/A
2007/0188602	12/2006	Cowan et al.	N/A	N/A
2007/0188837	12/2006	Shimizu et al.	N/A	N/A
2007/0195409	12/2006	Yun et al.	N/A	N/A
2007/0206155	12/2006	Lipton	N/A	N/A
2007/0211164	12/2006	Olsen et al.	N/A	N/A
2007/0236560	12/2006	Lipton et al.	N/A	N/A
2007/0237456	12/2006	Blauvelt et al.	N/A	N/A
2007/0247687	12/2006	Handschy et al.	N/A	N/A
2007/0258138	12/2006	Cowan et al.	N/A	N/A
2007/0263169	12/2006	Lipton	N/A	N/A
2008/0001909	12/2007	Lim	N/A	N/A
2008/0018851	12/2007	Lipton et al.	N/A	N/A
2008/0024598	12/2007	Perlin et al.	N/A	N/A
2008/0043334	12/2007	Itzkovitch et al.	N/A	N/A
2008/0049100	12/2007	Lipton et al.	N/A	N/A
2008/0062259	12/2007	Lipton et al.	N/A	N/A
2008/0089073	12/2007	Hikmet	N/A	N/A
2008/0106775	12/2007	Amitai et al.	N/A	N/A
2008/0106779	12/2007	Peterson et al.	N/A	N/A
2008/0112053	12/2007	Levner et al.	N/A	N/A
2008/0117289	12/2007	Schowengerdt et al.	N/A	N/A
2008/0136916	12/2007	Wolff	N/A	N/A
2008/0136923	12/2007	Inbar et al.	N/A	N/A
2008/0138013	12/2007	Parriaux	N/A	N/A
2008/0143964	12/2007	Cowan et al.	N/A	N/A
2008/0143965	12/2007	Cowan et al.	N/A	N/A
2008/0149517	12/2007	Lipton et al.	N/A	N/A
2008/0151370	12/2007	Cook et al.	N/A	N/A
2008/0151379	12/2007	Amitai	N/A	N/A
2008/0186573	12/2007	Lipton	N/A	N/A
2008/0186574	12/2007	Robinson et al.	N/A	N/A
2008/0186604	12/2007	Amitai	N/A	N/A
2008/0193085	12/2007	Singh et al.	N/A	N/A
2008/0198471	12/2007	Amitai	N/A	N/A
2008/0225187	12/2007	Yamanaka	N/A	N/A
2008/0226281	12/2007	Lipton	N/A	N/A
2008/0239067	12/2007	Lipton	N/A	N/A
2008/0239068	12/2007	Lipton	N/A	N/A
2008/0273081	12/2007	Lipton	N/A	N/A
2008/0278812	12/2007	Amitai	N/A	N/A
2008/0285137	12/2007	Simmonds et al.	N/A	N/A

2008/0285140	12/2007	Amitai	N/A	N/A
2008/0297731	12/2007	Powell et al.	N/A	N/A
2008/0297807	12/2007	Feldman et al.	N/A	N/A
2008/0298649	12/2007	Ennis et al.	N/A	N/A
2008/0298740	12/2007	Hlousek et al.	N/A	N/A
2008/0303895	12/2007	Akka et al.	N/A	N/A
2008/0303896	12/2007	Lipton et al.	N/A	N/A
2008/0304111	12/2007	Queenan et al.	N/A	N/A
2008/0309586	12/2007	Vitale	N/A	N/A
2008/0316303	12/2007	Chiu et al.	N/A	N/A
2008/0316375	12/2007	Lipton et al.	N/A	N/A
2009/0001632	12/2008	Stumpe et al.	N/A	N/A
2009/0010135	12/2008	Ushiro et al.	N/A	N/A
2009/0017424	12/2008	Yoeli et al.	N/A	N/A
2009/0019222	12/2008	Verma et al.	N/A	N/A
2009/0052017	12/2008	Sasaki	N/A	N/A
2009/0052046	12/2008	Amitai	N/A	N/A
2009/0052047	12/2008	Amitai	N/A	N/A
2009/0067774	12/2008	Magnusson	N/A	N/A
2009/0074356	12/2008	Sanchez et al.	N/A	N/A
2009/0097122	12/2008	Niv	N/A	N/A
2009/0097127	12/2008	Amitai	N/A	N/A
2009/0116790	12/2008	Mossberg et al.	N/A	N/A
2009/0121301	12/2008	Chang	N/A	N/A
2009/0122413	12/2008	Hoffman et al.	N/A	N/A
2009/0122414	12/2008	Amitai	N/A	N/A
2009/0128495	12/2008	Kong et al.	N/A	N/A
2009/0128781	12/2008	Li	N/A	N/A
2009/0128902	12/2008	Niv et al.	N/A	N/A
2009/0128911	12/2008	Itzkovitch et al.	N/A	N/A
2009/0136246	12/2008	Murakami	N/A	N/A
2009/0141324	12/2008	Mukawa	N/A	N/A
2009/0153437	12/2008	Aharoni	N/A	N/A
2009/0169152	12/2008	Oestergard	N/A	N/A
2009/0190222	12/2008	Simmonds et al.	N/A	N/A
2009/0213208	12/2008	Glatt	N/A	N/A
2009/0237804	12/2008	Amitai et al.	N/A	N/A
2009/0242021	12/2008	Petkie et al.	N/A	N/A
2009/0296218	12/2008	Ryytty	N/A	N/A
2009/0303599	12/2008	Levola	N/A	N/A
2009/0316246	12/2008	Asai et al.	N/A	N/A
2010/0014312	12/2009	Travis et al.	N/A	N/A
2010/0039796	12/2009	Mukawa	N/A	N/A
2010/0053565	12/2009	Mizushima et al.	N/A	N/A
2010/0060551	12/2009	Sugiyama et al.	N/A	N/A
2010/0060990	12/2009	Wertheim et al.	N/A	N/A
2010/0065726	12/2009	Zhong et al.	N/A	N/A
2010/0079841	12/2009	Levola	N/A	N/A
2010/0079865	12/2009	Saarikko et al.	N/A	N/A
2010/0084261	12/2009	Lee et al.	N/A	N/A

2010/0086256	12/2009	Ben Bakir et al.	N/A	N/A
2010/0092124	12/2009	Magnusson et al.	N/A	N/A
2010/0096562	12/2009	Klunder et al.	N/A	N/A
2010/0097674	12/2009	Kasazumi et al.	N/A	N/A
2010/0097820	12/2009	Owen et al.	N/A	N/A
2010/0103078	12/2009	Mukawa et al.	N/A	N/A
2010/0134534	12/2009	Seesselberg et al.	N/A	N/A
2010/0135615	12/2009	Ho et al.	N/A	N/A
2010/0136319	12/2009	Imai et al.	N/A	N/A
2010/0141555	12/2009	Rorberg et al.	N/A	N/A
2010/0141905	12/2009	Burke	N/A	N/A
2010/0149073	12/2009	Chaum et al.	N/A	N/A
2010/0165465	12/2009	Levola	N/A	N/A
2010/0165660	12/2009	Weber et al.	N/A	N/A
2010/0171680	12/2009	Lapidot et al.	N/A	N/A
2010/0177388	12/2009	Cohen et al.	N/A	N/A
2010/0202725	12/2009	Popovich et al.	N/A	N/A
2010/0214659	12/2009	Levola	N/A	N/A
2010/0220293	12/2009	Mizushima et al.	N/A	N/A
2010/0225834	12/2009	Li	N/A	N/A
2010/0225876	12/2009	Escuti et al.	N/A	N/A
2010/0231532	12/2009	Nho et al.	N/A	N/A
2010/0231693	12/2009	Levola	N/A	N/A
2010/0231705	12/2009	Yahav et al.	N/A	N/A
2010/0232003	12/2009	Baldy et al.	N/A	N/A
2010/0232016	12/2009	Landa et al.	N/A	N/A
2010/0245756	12/2009	Sugihara et al.	N/A	N/A
2010/0245757	12/2009	Sugihara et al.	N/A	N/A
2010/0246003	12/2009	Simmonds et al.	N/A	N/A
2010/0246004	12/2009	Simmonds	N/A	N/A
2010/0246993	12/2009	Rieger et al.	N/A	N/A
2010/0253987	12/2009	Leopold et al.	N/A	N/A
2010/0265117	12/2009	Weiss	N/A	N/A
2010/0277803	12/2009	Pockett et al.	N/A	N/A
2010/0284085	12/2009	Laakkonen	N/A	N/A
2010/0284090	12/2009	Simmonds	N/A	N/A
2010/0284180	12/2009	Popovich et al.	N/A	N/A
2010/0296163	12/2009	Saarikko	N/A	N/A
2010/0299814	12/2009	Celona et al.	N/A	N/A
2010/0315719	12/2009	Saarikko et al.	N/A	N/A
2010/0321781	12/2009	Levola et al.	N/A	N/A
2010/0322555	12/2009	Vermeulen et al.	N/A	N/A
2011/0001895	12/2010	Dahl	N/A	N/A
2011/0002143	12/2010	Saarikko et al.	N/A	N/A
2011/0013423	12/2010	Selbrede et al.	N/A	N/A
2011/0019250	12/2010	Aiki et al.	N/A	N/A
2011/0019874	12/2010	Jarvenpaa et al.	N/A	N/A
2011/0026128	12/2010	Baker et al.	N/A	N/A
2011/0026774	12/2010	Flohr et al.	N/A	N/A
2011/0032602	12/2010	Rothenberg et al.	N/A	N/A

2011/0032618	12/2010	Handerek et al.	N/A	N/A
2011/0032706	12/2010	Mukawa	N/A	N/A
2011/0038024	12/2010	Wang et al.	N/A	N/A
2011/0050548	12/2010	Blumenfeld et al.	N/A	N/A
2011/0063604	12/2010	Hamre et al.	N/A	N/A
2011/0096401	12/2010	Levola	N/A	N/A
2011/0102711	12/2010	Sutherland et al.	N/A	N/A
2011/0109880	12/2010	Nummela	N/A	N/A
2011/0157707	12/2010	Tilleman et al.	N/A	N/A
2011/0164221	12/2010	Tilleman et al.	N/A	N/A
2011/0187293	12/2010	Travis et al.	N/A	N/A
2011/0211239	12/2010	Mukawa et al.	N/A	N/A
2011/0216255	12/2010	Miyauchi et al.	N/A	N/A
2011/0221656	12/2010	Haddick et al.	N/A	N/A
2011/0232211	12/2010	Farahi	N/A	N/A
2011/0235179	12/2010	Simmonds	N/A	N/A
2011/0235365	12/2010	McCollum et al.	N/A	N/A
2011/0236803	12/2010	Weiser et al.	N/A	N/A
2011/0238399	12/2010	Ophir et al.	N/A	N/A
2011/0242349	12/2010	Izuha et al.	N/A	N/A
2011/0242661	12/2010	Simmonds	N/A	N/A
2011/0242670	12/2010	Simmonds	N/A	N/A
2011/0249309	12/2010	McPheters et al.	N/A	N/A
2011/0274435	12/2010	Fini et al.	N/A	N/A
2011/0299075	12/2010	Meade et al.	N/A	N/A
2011/0310356	12/2010	Vallius	N/A	N/A
2012/0007979	12/2011	Schneider et al.	N/A	N/A
2012/0027347	12/2011	Mathal et al.	N/A	N/A
2012/0033306	12/2011	Valera et al.	N/A	N/A
2012/0044572	12/2011	Simmonds et al.	N/A	N/A
2012/0044573	12/2011	Simmonds et al.	N/A	N/A
2012/0062850	12/2011	Travis	N/A	N/A
2012/0062998	12/2011	Schultz et al.	N/A	N/A
2012/0067864	12/2011	Kusuda et al.	N/A	N/A
2012/0075168	12/2011	Osterhout et al.	N/A	N/A
2012/0081789	12/2011	Mukawa et al.	N/A	N/A
2012/0092632	12/2011	McLeod et al.	N/A	N/A
2012/0099203	12/2011	Boubis et al.	N/A	N/A
2012/0105634	12/2011	Meidan et al.	N/A	N/A
2012/0105740	12/2011	Jannard et al.	N/A	N/A
2012/0120493	12/2011	Simmonds et al.	N/A	N/A
2012/0127577	12/2011	Desserouer	N/A	N/A
2012/0162549	12/2011	Gao et al.	N/A	N/A
2012/0162764	12/2011	Shimizu	N/A	N/A
2012/0176665	12/2011	Song et al.	N/A	N/A
2012/0183888	12/2011	Oliveira et al.	N/A	N/A
2012/0194420	12/2011	Osterhout et al.	N/A	N/A
2012/0200532	12/2011	Powell et al.	N/A	N/A
2012/0206811	12/2011	Mukawa et al.	N/A	N/A
2012/0206937	12/2011	Travis et al.	N/A	N/A

2012/0207432	12/2011	Travis et al.	N/A	N/A
2012/0207434	12/2011	Large	N/A	N/A
2012/0214089	12/2011	Hönel et al.	N/A	N/A
2012/0214090	12/2011	Weiser et al.	N/A	N/A
2012/0218481	12/2011	Popovich et al.	N/A	N/A
2012/0224062	12/2011	Lacoste et al.	N/A	N/A
2012/0235884	12/2011	Miller et al.	N/A	N/A
2012/0235886	12/2011	Border et al.	N/A	N/A
2012/0235900	12/2011	Border et al.	N/A	N/A
2012/0242661	12/2011	Takagi et al.	N/A	N/A
2012/0280956	12/2011	Yamamoto et al.	N/A	N/A
2012/0281943	12/2011	Popovich et al.	N/A	N/A
2012/0287675	12/2011	Mukawa	N/A	N/A
2012/0290973	12/2011	Robertson et al.	N/A	N/A
2012/0294037	12/2011	Holman et al.	N/A	N/A
2012/0300311	12/2011	Simmonds et al.	N/A	N/A
2012/0320460	12/2011	Levola	N/A	N/A
2012/0326950	12/2011	Park et al.	N/A	N/A
2012/0328234	12/2011	Lu et al.	N/A	N/A
2013/0016324	12/2012	Travis	N/A	N/A
2013/0016362	12/2012	Gong et al.	N/A	N/A
2013/0021392	12/2012	Travis	N/A	N/A
2013/0021586	12/2012	Lippey	N/A	N/A
2013/0027006	12/2012	Holloway et al.	N/A	N/A
2013/0033485	12/2012	Kollin et al.	N/A	N/A
2013/0039619	12/2012	Laughlin	N/A	N/A
2013/0044376	12/2012	Valera et al.	N/A	N/A
2013/0051730	12/2012	Travers et al.	N/A	N/A
2013/0059233	12/2012	Askham	N/A	N/A
2013/0069850	12/2012	Mukawa et al.	N/A	N/A
2013/0077049	12/2012	Bohn	N/A	N/A
2013/0088637	12/2012	Duparre	N/A	N/A
2013/0093893	12/2012	Schofield et al.	N/A	N/A
2013/0101253	12/2012	Popovich et al.	N/A	N/A
2013/0107186	12/2012	Ando et al.	N/A	N/A
2013/0107343	12/2012	Shekel	N/A	N/A
2013/0117377	12/2012	Miller	N/A	N/A
2013/0125027	12/2012	Abovitz et al.	N/A	N/A
2013/0128230	12/2012	Macnamara	N/A	N/A
2013/0138275	12/2012	Nauman et al.	N/A	N/A
2013/0141934	12/2012	Hartung	N/A	N/A
2013/0141937	12/2012	Katsuta et al.	N/A	N/A
2013/0143336	12/2012	Jain	N/A	N/A
2013/0163089	12/2012	Bohn	N/A	N/A
2013/0163928	12/2012	Wang et al.	N/A	N/A
2013/0170031	12/2012	Bohn et al.	N/A	N/A
2013/0176704	12/2012	Lanman et al.	N/A	N/A
2013/0184904	12/2012	Gadzinski	N/A	N/A
2013/0200710	12/2012	Robbins	N/A	N/A
2013/0207887	12/2012	Raffle et al.	N/A	N/A

2013/0224634	12/2012	Berneth et al.	N/A	N/A
2013/0229717	12/2012	Amitai	N/A	N/A
2013/0249895	12/2012	Westerinen et al.	N/A	N/A
2013/0250207	12/2012	Bohn	N/A	N/A
2013/0250380	12/2012	Fujikawa et al.	N/A	N/A
2013/0250430	12/2012	Robbins et al.	N/A	N/A
2013/0250431	12/2012	Robbins et al.	N/A	N/A
2013/0257848	12/2012	Westerinen et al.	N/A	N/A
2013/0258701	12/2012	Westerinen et al.	N/A	N/A
2013/0267309	12/2012	Robbins et al.	N/A	N/A
2013/0271731	12/2012	Popovich et al.	N/A	N/A
2013/0277890	12/2012	Bowman et al.	N/A	N/A
2013/0286053	12/2012	Fleck et al.	N/A	N/A
2013/0300997	12/2012	Popovich et al.	N/A	N/A
2013/0301014	12/2012	DeJong et al.	N/A	N/A
2013/0305437	12/2012	Weller et al.	N/A	N/A
2013/0308185	12/2012	Robinson et al.	N/A	N/A
2013/0312811	12/2012	Aspnes et al.	N/A	N/A
2013/0314789	12/2012	Saarikko et al.	N/A	N/A
2013/0314793	12/2012	Robbins et al.	N/A	N/A
2013/0322810	12/2012	Robbins	N/A	N/A
2013/0328948	12/2012	Kunkel et al.	N/A	N/A
2013/0342525	12/2012	Benko et al.	N/A	N/A
2014/0002514	12/2013	Richards	N/A	N/A
2014/0003762	12/2013	Macnamara	N/A	N/A
2014/0009809	12/2013	Pyun et al.	N/A	N/A
2014/0022616	12/2013	Popovich et al.	N/A	N/A
2014/0024159	12/2013	Jain	N/A	N/A
2014/0027006	12/2013	Foley et al.	N/A	N/A
2014/0037242	12/2013	Popovich et al.	N/A	N/A
2014/0043672	12/2013	Clarke et al.	N/A	N/A
2014/0043689	12/2013	Mason	N/A	N/A
2014/0055845	12/2013	Jain	N/A	N/A
2014/0063055	12/2013	Osterhout et al.	N/A	N/A
2014/0064655	12/2013	Nguyen et al.	N/A	N/A
2014/0071538	12/2013	Muller	N/A	N/A
2014/0098010	12/2013	Travis	N/A	N/A
2014/0104665	12/2013	Popovich et al.	N/A	N/A
2014/0104685	12/2013	Bohn et al.	N/A	N/A
2014/0118647	12/2013	Momono et al.	N/A	N/A
2014/0126029	12/2013	Fuetterer	N/A	N/A
2014/0126175	12/2013	Amitai et al.	N/A	N/A
2014/0130132	12/2013	Cahill et al.	N/A	N/A
2014/0138581	12/2013	Archetti et al.	N/A	N/A
2014/0140653	12/2013	Brown et al.	N/A	N/A
2014/0140654	12/2013	Brown et al.	N/A	N/A
2014/0146394	12/2013	Tout et al.	N/A	N/A
2014/0152778	12/2013	Ihlenburg et al.	N/A	N/A
2014/0154614	12/2013	Xie et al.	N/A	N/A
2014/0160576	12/2013	Robbins et al.	N/A	N/A

2014/0168055	12/2013	Smith	N/A	N/A
2014/0168260	12/2013	O'Brien et al.	N/A	N/A
2014/0168735	12/2013	Yuan et al.	N/A	N/A
2014/0168783	12/2013	Luebke et al.	N/A	N/A
2014/0172296	12/2013	Shtukater	N/A	N/A
2014/0176528	12/2013	Robbins	N/A	N/A
2014/0177023	12/2013	Gao et al.	N/A	N/A
2014/0185286	12/2013	Popovich et al.	N/A	N/A
2014/0198128	12/2013	Hong et al.	N/A	N/A
2014/0198896	12/2013	Hemmendorff et al.	N/A	N/A
2014/0204455	12/2013	Popovich et al.	N/A	N/A
2014/0211322	12/2013	Bohn et al.	N/A	N/A
2014/0218468	12/2013	Gao et al.	N/A	N/A
2014/0218801	12/2013	Simmonds et al.	N/A	N/A
2014/0232759	12/2013	Simmonds et al.	N/A	N/A
2014/0240834	12/2013	Mason	N/A	N/A
2014/0240842	12/2013	Nguyen et al.	N/A	N/A
2014/0255662	12/2013	Enomoto et al.	N/A	N/A
2014/0267420	12/2013	Schowengerdt et al.	N/A	N/A
2014/0268017	12/2013	Sweis et al.	N/A	N/A
2014/0268353	12/2013	Fujimura et al.	N/A	N/A
2014/0300947	12/2013	Fattal et al.	N/A	N/A
2014/0300960	12/2013	Santori et al.	N/A	N/A
2014/0300966	12/2013	Travers et al.	N/A	N/A
2014/0327970	12/2013	Bohn et al.	N/A	N/A
2014/0330159	12/2013	Costa et al.	N/A	N/A
2014/0367719	12/2013	Jain	N/A	N/A
2014/0375542	12/2013	Robbins et al.	N/A	N/A
2014/0375789	12/2013	Lou et al.	N/A	N/A
2014/0375790	12/2013	Robbins et al.	N/A	N/A
2015/0001677	12/2014	Palumbo et al.	N/A	N/A
2015/0003796	12/2014	Bennett	N/A	N/A
2015/0009550	12/2014	Misago et al.	N/A	N/A
2015/0010265	12/2014	Popovich et al.	N/A	N/A
2015/0015946	12/2014	Muller	N/A	N/A
2015/0016777	12/2014	Abovitz et al.	N/A	N/A
2015/0035744	12/2014	Robbins et al.	N/A	N/A
2015/0036068	12/2014	Fattal et al.	N/A	N/A
2015/0058791	12/2014	Robertson et al.	N/A	N/A
2015/0062675	12/2014	Ayres et al.	N/A	N/A
2015/0062707	12/2014	Simmonds et al.	N/A	N/A
2015/0086163	12/2014	Valera et al.	N/A	N/A
2015/0086907	12/2014	Mizuta et al.	N/A	N/A
2015/0107671	12/2014	Bodan et al.	N/A	N/A
2015/0109763	12/2014	Shinkai et al.	N/A	N/A
2015/0125109	12/2014	Robbins et al.	N/A	N/A
2015/0148728	12/2014	Sallum et al.	N/A	N/A
2015/0160529	12/2014	Popovich et al.	N/A	N/A
2015/0167868	12/2014	Boncha	N/A	N/A
2015/0177443	12/2014	Faecke et al.	N/A	N/A

2015/0177686	12/2014	Lee et al.	N/A	N/A
2015/0177688	12/2014	Popovich et al.	N/A	N/A
2015/0185475	12/2014	Saarikko et al.	N/A	N/A
2015/0205126	12/2014	Schowengerdt	N/A	N/A
2015/0211960	12/2014	Shimizu	N/A	N/A
2015/0219834	12/2014	Nichol et al.	N/A	N/A
2015/0235447	12/2014	Abovitz et al.	N/A	N/A
2015/0235448	12/2014	Schowengerdt et al.	N/A	N/A
2015/0243068	12/2014	Solomon	N/A	N/A
2015/0247975	12/2014	Abovitz et al.	N/A	N/A
2015/0260994	12/2014	Akutsu et al.	N/A	N/A
2015/0262424	12/2014	Tabaka et al.	N/A	N/A
2015/0268399	12/2014	Futterer	N/A	N/A
2015/0268415	12/2014	Schowengerdt et al.	N/A	N/A
2015/0277375	12/2014	Large et al.	N/A	N/A
2015/0285682	12/2014	Popovich et al.	N/A	N/A
2015/0288129	12/2014	Jain	N/A	N/A
2015/0289762	12/2014	Popovich et al.	N/A	N/A
2015/0309264	12/2014	Abovitz et al.	N/A	N/A
2015/0316768	12/2014	Simmonds	N/A	N/A
2015/0338689	12/2014	Min et al.	N/A	N/A
2015/0346490	12/2014	Tekolste et al.	N/A	N/A
2015/0346495	12/2014	Welch et al.	N/A	N/A
2015/0355394	12/2014	Leighton et al.	N/A	N/A
2016/0003847	12/2015	Ryan et al.	N/A	N/A
2016/0004090	12/2015	Popovich et al.	N/A	N/A
2016/0018673	12/2015	Wang	N/A	N/A
2016/0026253	12/2015	Bradski et al.	N/A	N/A
2016/0033705	12/2015	Fattal	N/A	N/A
2016/0033706	12/2015	Fattal et al.	N/A	N/A
2016/0038992	12/2015	Arthur et al.	N/A	N/A
2016/0041387	12/2015	Valera et al.	N/A	N/A
2016/0055822	12/2015	Bell	N/A	N/A
2016/0060529	12/2015	Hegmann et al.	N/A	N/A
2016/0077338	12/2015	Robbins et al.	N/A	N/A
2016/0085300	12/2015	Robbins et al.	N/A	N/A
2016/0097959	12/2015	Bruizeman et al.	N/A	N/A
2016/0116739	12/2015	TeKolste et al.	N/A	N/A
2016/0124223	12/2015	Shinbo et al.	N/A	N/A
2016/0124241	12/2015	Popovich et al.	N/A	N/A
2016/0132025	12/2015	Taff et al.	N/A	N/A
2016/0147067	12/2015	Hua et al.	N/A	N/A
2016/0170226	12/2015	Popovich et al.	N/A	N/A
2016/0178901	12/2015	Ishikawa	N/A	N/A
2016/0195664	12/2015	Fattal et al.	N/A	N/A
2016/0209648	12/2015	Haddick et al.	N/A	N/A
2016/0209657	12/2015	Popovich et al.	N/A	N/A
2016/0231568	12/2015	Saarikko et al.	N/A	N/A
2016/0231570	12/2015	Levola et al.	N/A	N/A
2016/0238772	12/2015	Waldern et al.	N/A	N/A

2016/0266398	12/2015	Poon et al.	N/A	N/A
2016/0274356	12/2015	Mason	N/A	N/A
2016/0274362	12/2015	Tinch et al.	N/A	N/A
2016/0283773	12/2015	Popovich et al.	N/A	N/A
2016/0291328	12/2015	Popovich et al.	N/A	N/A
2016/0299344	12/2015	Dobschal et al.	N/A	N/A
2016/0320536	12/2015	Simmonds et al.	N/A	N/A
2016/0327705	12/2015	Simmonds et al.	N/A	N/A
2016/0336033	12/2015	Tanaka	N/A	N/A
2016/0341964	12/2015	Amitai	N/A	N/A
2016/0363840	12/2015	Mizoguchi et al.	N/A	N/A
2016/0370615	12/2015	Wu et al.	N/A	N/A
2016/0377879	12/2015	Popovich et al.	N/A	N/A
2017/0003505	12/2016	Vallius et al.	N/A	N/A
2017/0010466	12/2016	Klug et al.	N/A	N/A
2017/0010488	12/2016	Klug et al.	N/A	N/A
2017/0030550	12/2016	Popovich et al.	N/A	N/A
2017/0031160	12/2016	Popovich et al.	N/A	N/A
2017/0031171	12/2016	Vallius et al.	N/A	N/A
2017/0032166	12/2016	Raguin et al.	N/A	N/A
2017/0034435	12/2016	Vallius	N/A	N/A
2017/0038579	12/2016	Yeoh et al.	N/A	N/A
2017/0052374	12/2016	Waldern et al.	N/A	N/A
2017/0052376	12/2016	Amitai et al.	N/A	N/A
2017/0059759	12/2016	Ayres et al.	N/A	N/A
2017/0059775	12/2016	Coles et al.	N/A	N/A
2017/0102543	12/2016	Vallius	N/A	N/A
2017/0115487	12/2016	Travis et al.	N/A	N/A
2017/0123208	12/2016	Vallius	N/A	N/A
2017/0131460	12/2016	Lin et al.	N/A	N/A
2017/0131545	12/2016	Wall et al.	N/A	N/A
2017/0131546	12/2016	Woltman et al.	N/A	N/A
2017/0131551	12/2016	Robbins et al.	N/A	N/A
2017/0138789	12/2016	Ivanov	N/A	N/A
2017/0160546	12/2016	Bull et al.	N/A	N/A
2017/0160548	12/2016	Woltman et al.	N/A	N/A
2017/0176747	12/2016	Vallius et al.	N/A	N/A
2017/0180404	12/2016	Bersch et al.	N/A	N/A
2017/0180408	12/2016	Yu et al.	N/A	N/A
2017/0192246	12/2016	Popovich et al.	N/A	N/A
2017/0192499	12/2016	Trail	N/A	N/A
2017/0199333	12/2016	Waldern et al.	N/A	N/A
2017/0212295	12/2016	Vasylyev	N/A	N/A
2017/0219841	12/2016	Popovich et al.	N/A	N/A
2017/0235142	12/2016	Wall et al.	N/A	N/A
2017/0236463	12/2016	Chi et al.	N/A	N/A
2017/0255257	12/2016	Tiana et al.	N/A	N/A
2017/0270637	12/2016	Perreault et al.	N/A	N/A
2017/0276940	12/2016	Popovich et al.	N/A	N/A
2017/0299793	12/2016	Fattal	N/A	N/A

2017/0299794	12/2016	Fattal	N/A	N/A
2017/0299860	12/2016	Wall et al.	N/A	N/A
2017/0299865	12/2016	Vallius et al.	N/A	N/A
2017/0307800	12/2016	Fattal	N/A	N/A
2017/0322426	12/2016	Tervo	N/A	N/A
2017/0329075	12/2016	Yeoh et al.	N/A	N/A
2017/0329140	12/2016	Yeoh et al.	N/A	N/A
2017/0356801	12/2016	Popovich et al.	N/A	N/A
2017/0357841	12/2016	Popovich et al.	N/A	N/A
2018/0003805	12/2017	Popovich et al.	N/A	N/A
2018/0011324	12/2017	Popovich et al.	N/A	N/A
2018/0052277	12/2017	Schowengerdt et al.	N/A	N/A
2018/0059305	12/2017	Popovich et al.	N/A	N/A
2018/0067251	12/2017	Baldwin et al.	N/A	N/A
2018/0067318	12/2017	St. Hilaire	N/A	N/A
2018/0074265	12/2017	Waldern et al.	N/A	N/A
2018/0074340	12/2017	Robbins et al.	N/A	N/A
2018/0074352	12/2017	Popovich et al.	N/A	N/A
2018/0081190	12/2017	Lee et al.	N/A	N/A
2018/0082644	12/2017	Bohn	N/A	N/A
2018/0088325	12/2017	Brown et al.	N/A	N/A
2018/0107011	12/2017	Lu et al.	N/A	N/A
2018/0112097	12/2017	Raghavanpillai et al.	N/A	N/A
2018/0113303	12/2017	Popovich et al.	N/A	N/A
2018/0120669	12/2017	Popovich et al.	N/A	N/A
2018/0129060	12/2017	Lee et al.	N/A	N/A
2018/0143438	12/2017	Oh	N/A	N/A
2018/0143449	12/2017	Popovich et al.	N/A	N/A
2018/0164583	12/2017	Wall et al.	N/A	N/A
2018/0172995	12/2017	Lee et al.	N/A	N/A
2018/0188542	12/2017	Waldern et al.	N/A	N/A
2018/0188691	12/2017	Fattal	N/A	N/A
2018/0203230	12/2017	Vallius et al.	N/A	N/A
2018/0210198	12/2017	Brown et al.	N/A	N/A
2018/0210205	12/2017	Grey et al.	N/A	N/A
2018/0210396	12/2017	Popovich et al.	N/A	N/A
2018/0232048	12/2017	Popovich et al.	N/A	N/A
2018/0246354	12/2017	Popovich et al.	N/A	N/A
2018/0252869	12/2017	Ayres et al.	N/A	N/A
2018/0265774	12/2017	Huang et al.	N/A	N/A
2018/0275350	12/2017	Oh et al.	N/A	N/A
2018/0275402	12/2017	Popovich et al.	N/A	N/A
2018/0275410	12/2017	Yeoh et al.	N/A	N/A
2018/0284440	12/2017	Popovich et al.	N/A	N/A
2018/0338131	12/2017	Robbins	N/A	N/A
2018/0348524	12/2017	Blum et al.	N/A	N/A
2018/0373115	12/2017	Brown et al.	N/A	N/A
2019/0041634	12/2018	Popovich et al.	N/A	N/A
2019/0042827	12/2018	Popovich et al.	N/A	N/A

2019/0064526	12/2018	Connor	N/A	N/A
2019/0064735	12/2018	Waldern et al.	N/A	N/A
2019/0072723	12/2018	Waldern et al.	N/A	N/A
2019/0072767	12/2018	Vallius et al.	N/A	N/A
2019/0094548	12/2018	Nicholson et al.	N/A	N/A
2019/0113751	12/2018	Waldern et al.	N/A	N/A
2019/0113829	12/2018	Waldern et al.	N/A	N/A
2019/0114484	12/2018	Keech et al.	N/A	N/A
2019/0121027	12/2018	Popovich et al.	N/A	N/A
2019/0129085	12/2018	Waldern et al.	N/A	N/A
2019/0162962	12/2018	Leighton et al.	N/A	N/A
2019/0162963	12/2018	Leighton et al.	N/A	N/A
2019/0171031	12/2018	Popovich et al.	N/A	N/A
2019/0179153	12/2018	Popovich et al.	N/A	N/A
2019/0187474	12/2018	Bhargava et al.	N/A	N/A
2019/0187538	12/2018	Popovich et al.	N/A	N/A
2019/0188471	12/2018	Osterhout et al.	N/A	N/A
2019/0212195	12/2018	Popovich et al.	N/A	N/A
2019/0212557	12/2018	Waldern et al.	N/A	N/A
2019/0212573	12/2018	Popovich et al.	N/A	N/A
2019/0212588	12/2018	Waldern et al.	N/A	N/A
2019/0212589	12/2018	Waldern et al.	N/A	N/A
2019/0212596	12/2018	Waldern et al.	N/A	N/A
2019/0212597	12/2018	Waldern et al.	N/A	N/A
2019/0212698	12/2018	Waldern et al.	N/A	N/A
2019/0212699	12/2018	Waldern et al.	N/A	N/A
2019/0219822	12/2018	Popovich et al.	N/A	N/A
2019/0226830	12/2018	Edwin et al.	N/A	N/A
2019/0243142	12/2018	Tekolste et al.	N/A	N/A
2019/0265486	12/2018	Hansotte et al.	N/A	N/A
2019/0278224	12/2018	Schlottau et al.	N/A	N/A
2019/0285796	12/2018	Waldern et al.	N/A	N/A
2019/0293880	12/2018	Nishiwaki et al.	N/A	N/A
2019/0319426	12/2018	Lu et al.	N/A	N/A
2019/0339558	12/2018	Waldern et al.	N/A	N/A
2019/0361096	12/2018	Popovich et al.	N/A	N/A
2020/0012839	12/2019	Popovich et al.	N/A	N/A
2020/0026072	12/2019	Brown et al.	N/A	N/A
2020/0026074	12/2019	Waldern et al.	N/A	N/A
2020/0033190	12/2019	Popovich et al.	N/A	N/A
2020/0033801	12/2019	Waldern et al.	N/A	N/A
2020/0033802	12/2019	Popovich et al.	N/A	N/A
2020/0041787	12/2019	Popovich et al.	N/A	N/A
2020/0057353	12/2019	Popovich et al.	N/A	N/A
2020/0064637	12/2019	Popovich et al.	N/A	N/A
2020/0081317	12/2019	Popovich et al.	N/A	N/A
2020/0089319	12/2019	Popovich et al.	N/A	N/A
2020/0096692	12/2019	Popovich	N/A	G02B 6/0035
2020/0096772	12/2019	Adema et al.	N/A	N/A

2020/0103661	12/2019	Kamakura	N/A	N/A
2020/0116997	12/2019	Lee et al.	N/A	N/A
2020/0142131	12/2019	Waldern et al.	N/A	N/A
2020/0150469	12/2019	Popovich et al.	N/A	N/A
2020/0159023	12/2019	Bhargava et al.	N/A	N/A
2020/0159026	12/2019	Waldern et al.	N/A	N/A
2020/0183163	12/2019	Waldern et al.	N/A	N/A
2020/0192088	12/2019	Yu et al.	N/A	N/A
2020/0201042	12/2019	Wang et al.	N/A	N/A
2020/0201051	12/2019	Popovich et al.	N/A	N/A
2020/0209630	12/2019	Schultz et al.	N/A	N/A
2020/0225471	12/2019	Waldern et al.	N/A	N/A
2020/0241304	12/2019	Popovich et al.	N/A	N/A
2020/0247016	12/2019	Calafiore	N/A	N/A
2020/0247017	12/2019	Waldern et al.	N/A	N/A
2020/0249484	12/2019	Waldern et al.	N/A	N/A
2020/0249491	12/2019	Popovich et al.	N/A	N/A
2020/0249568	12/2019	Rao et al.	N/A	N/A
2020/0264378	12/2019	Grant et al.	N/A	N/A
2020/0271973	12/2019	Waldern et al.	N/A	N/A
2020/0292745	12/2019	Waldern et al.	N/A	N/A
2020/0292840	12/2019	Popovich et al.	N/A	N/A
2020/0319404	12/2019	Waldern et al.	N/A	N/A
2020/0333606	12/2019	Popovich et al.	N/A	N/A
2020/0341194	12/2019	Waldern et al.	N/A	N/A
2020/0341272	12/2019	Popovich et al.	N/A	N/A
2020/0348519	12/2019	Waldern et al.	N/A	N/A
2020/0348531	12/2019	Popovich et al.	N/A	N/A
2020/0363771	12/2019	Waldern et al.	N/A	N/A
2020/0372236	12/2019	Popovich et al.	N/A	N/A
2020/0386947	12/2019	Waldern et al.	N/A	N/A
2020/0400946	12/2019	Waldern et al.	N/A	N/A
2021/0026297	12/2020	Waldern et al.	N/A	N/A
2021/0033857	12/2020	Waldern et al.	N/A	N/A
2021/0055551	12/2020	Chi et al.	N/A	N/A
2021/0063634	12/2020	Waldern et al.	N/A	N/A
2021/0063672	12/2020	Bodiya	N/A	N/A
2021/0088705	12/2020	Drazic et al.	N/A	N/A
2021/0109285	12/2020	Jiang et al.	N/A	N/A
2021/0109353	12/2020	Nicholson et al.	N/A	N/A
2021/0191122	12/2020	Yaroshchuk et al.	N/A	N/A
2021/0199873	12/2020	Shi et al.	N/A	N/A
2021/0199971	12/2020	Lee et al.	N/A	N/A
2021/0216040	12/2020	Waldern et al.	N/A	N/A
2021/0223585	12/2020	Waldern et al.	N/A	N/A
2021/0231874	12/2020	Popovich et al.	N/A	N/A
2021/0231955	12/2020	Waldern et al.	N/A	N/A
2021/0238374	12/2020	Ye et al.	N/A	N/A
2021/0239984	12/2020	Popovich et al.	N/A	N/A
2021/0247560	12/2020	Waldern et al.	N/A	N/A

2021/0247620	12/2020	Popovich et al.	N/A	N/A
2021/0247719	12/2020	Waldern et al.	N/A	N/A
2021/0255463	12/2020	Popovich et al.	N/A	N/A
2021/0278739	12/2020	Brown et al.	N/A	N/A
2021/0349328	12/2020	Popovich et al.	N/A	N/A
2021/0364803	12/2020	Schowengerdt et al.	N/A	N/A
2021/0364836	12/2020	Waldern et al.	N/A	N/A
2021/0405299	12/2020	Grant et al.	N/A	N/A
2021/0405365	12/2020	Popovich et al.	N/A	N/A
2021/0405514	12/2020	Waldern et al.	N/A	N/A
2022/0019015	12/2021	Calafiore et al.	N/A	N/A
2022/0043287	12/2021	Grant et al.	N/A	N/A
2022/0057749	12/2021	Popovich et al.	N/A	N/A
2022/0075196	12/2021	Waldern et al.	N/A	N/A
2022/0075242	12/2021	Popovich et al.	N/A	N/A
2022/0082739	12/2021	Franke et al.	N/A	N/A
2022/0091323	12/2021	Yaroshchuk et al.	N/A	N/A
2022/0099898	12/2021	Waldern et al.	N/A	N/A
2022/0128754	12/2021	Popovich	N/A	G02B 6/0031
2022/0155623	12/2021	Waldern et al.	N/A	N/A
2022/0163728	12/2021	Waldern et al.	N/A	N/A
2022/0163801	12/2021	Waldern et al.	N/A	N/A
2022/0187692	12/2021	Popovich et al.	N/A	N/A
2022/0204790	12/2021	Zhang et al.	N/A	N/A
2022/0206232	12/2021	Zhang et al.	N/A	N/A
2022/0214503	12/2021	Waldern et al.	N/A	N/A
2022/0244559	12/2021	Popovich et al.	N/A	N/A
2022/0260838	12/2021	Popovich et al.	N/A	N/A
2022/0260847	12/2021	Popovich et al.	N/A	N/A
2022/0283377	12/2021	Popovich et al.	N/A	N/A
2022/0308352	12/2021	Stanley et al.	N/A	N/A
2022/0317356	12/2021	Popovich	N/A	G02B 6/005
2023/0061090	12/2022	Popovich et al.	N/A	N/A
2023/0081115	12/2022	Brown	385/10	G02B 5/1814
2023/0114549	12/2022	Brown et al.	N/A	N/A
2023/0168514	12/2022	Waldern et al.	N/A	N/A
2023/0221493	12/2022	Grant et al.	N/A	N/A
2023/0314810	12/2022	Delapp et al.	N/A	N/A
2023/0358962	12/2022	Popovich et al.	N/A	N/A
2023/0359028	12/2022	Waldern	N/A	G02B 27/0103
2023/0359035	12/2022	Waldern et al.	N/A	N/A
2023/0359146	12/2022	Waldern et al.	N/A	N/A
2024/0012247	12/2023	Popovich et al.	N/A	N/A
2024/0019640	12/2023	Waldern et al.	N/A	N/A
2024/0027670	12/2023	Waldern	N/A	G02B 27/4205

2024/0134244	12/2023	Brown	N/A	G02B 5/1814
2024/0151890	12/2023	Popovich	N/A	G02B 27/0172
2024/0255760	12/2023	Popovich et al.	N/A	N/A
2024/0295703	12/2023	Grant et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
PI0720469	12/2013	BR	N/A
2889727	12/2013	CA	N/A
303019849	12/2013	CA	N/A
1066936	12/1991	CN	N/A
1320217	12/2000	CN	N/A
1357010	12/2001	CN	N/A
1886680	12/2005	CN	N/A
200944140	12/2006	CN	N/A
101103297	12/2007	CN	N/A
101151562	12/2007	CN	N/A
101241348	12/2007	CN	N/A
101263412	12/2007	CN	N/A
100492099	12/2008	CN	N/A
101589326	12/2008	CN	N/A
101688977	12/2009	CN	N/A
101726857	12/2009	CN	N/A
101793555	12/2009	CN	N/A
101881936	12/2009	CN	N/A
101910900	12/2009	CN	N/A
101945612	12/2010	CN	N/A
102314092	12/2011	CN	N/A
102360093	12/2011	CN	N/A
102393548	12/2011	CN	N/A
102498425	12/2011	CN	N/A
102608762	12/2011	CN	N/A
102782563	12/2011	CN	N/A
102928981	12/2012	CN	N/A
103000188	12/2012	CN	N/A
103031557	12/2012	CN	N/A
103389580	12/2012	CN	N/A
103562802	12/2013	CN	N/A
103777282	12/2013	CN	N/A
103823267	12/2013	CN	N/A
103946732	12/2013	CN	N/A
103959133	12/2013	CN	N/A
104035157	12/2013	CN	N/A
104040308	12/2013	CN	N/A
104040410	12/2013	CN	N/A
104136952	12/2013	CN	N/A
104204901	12/2013	CN	N/A

104246626	12/2013	CN	N/A
104520751	12/2014	CN	N/A
303217936	12/2014	CN	N/A
104956252	12/2014	CN	N/A
105074537	12/2014	CN	N/A
105074539	12/2014	CN	N/A
105190407	12/2014	CN	N/A
105229514	12/2015	CN	N/A
105393159	12/2015	CN	N/A
105408801	12/2015	CN	N/A
105408802	12/2015	CN	N/A
105408803	12/2015	CN	N/A
105531716	12/2015	CN	N/A
105705981	12/2015	CN	N/A
105940451	12/2015	CN	N/A
106125308	12/2015	CN	N/A
106575034	12/2016	CN	N/A
106716223	12/2016	CN	N/A
106842397	12/2016	CN	N/A
106950744	12/2016	CN	N/A
107466372	12/2016	CN	N/A
107533137	12/2017	CN	N/A
107873086	12/2017	CN	N/A
108107506	12/2017	CN	N/A
108474945	12/2017	CN	N/A
108681067	12/2017	CN	N/A
108780224	12/2017	CN	N/A
109073889	12/2017	CN	N/A
109154717	12/2018	CN	N/A
208621784	12/2018	CN	N/A
103823267	12/2018	CN	N/A
110383117	12/2018	CN	N/A
107873086	12/2019	CN	N/A
111025657	12/2019	CN	N/A
111323867	12/2019	CN	N/A
111386495	12/2019	CN	N/A
111566571	12/2019	CN	N/A
305973971	12/2019	CN	N/A
111615655	12/2019	CN	N/A
111684362	12/2019	CN	N/A
111902768	12/2019	CN	N/A
107466372	12/2020	CN	N/A
109073889	12/2020	CN	N/A
108780224	12/2020	CN	N/A
113424095	12/2020	CN	N/A
108474945	12/2020	CN	N/A
113692544	12/2020	CN	N/A
113728075	12/2020	CN	N/A
113728258	12/2020	CN	N/A
113759555	12/2020	CN	N/A

111684362	12/2021	CN	N/A
114207492	12/2021	CN	N/A
114341686	12/2021	CN	N/A
109154717	12/2021	CN	N/A
111566571	12/2021	CN	N/A
114450608	12/2021	CN	N/A
114721242	12/2021	CN	N/A
113759555	12/2023	CN	N/A
19751190	12/1998	DE	N/A
10221837	12/2002	DE	N/A
102006003785	12/2006	DE	N/A
102006036831	12/2007	DE	N/A
102012108424	12/2013	DE	N/A
102013209436	12/2013	DE	N/A
001747551-0002	12/2011	EM	N/A
007234190-0001	12/2018	EM	N/A
0795775	12/1996	EP	N/A
0822441	12/1997	EP	N/A
1347641	12/2002	EP	N/A
1413972	12/2003	EP	N/A
1526709	12/2004	EP	N/A
1748305	12/2006	EP	N/A
1938152	12/2007	EP	N/A
1413972	12/2007	EP	N/A
2110701	12/2008	EP	N/A
2196729	12/2009	EP	N/A
2225592	12/2009	EP	N/A
2244114	12/2009	EP	N/A
2326983	12/2010	EP	N/A
2381290	12/2010	EP	N/A
1828832	12/2012	EP	N/A
2733517	12/2013	EP	N/A
1573369	12/2013	EP	N/A
2748670	12/2013	EP	N/A
2634605	12/2014	EP	N/A
2929378	12/2014	EP	N/A
2748670	12/2014	EP	N/A
2995986	12/2015	EP	N/A
1402298	12/2015	EP	N/A
2995986	12/2016	EP	N/A
3198192	12/2016	EP	N/A
3245444	12/2016	EP	N/A
3245551	12/2016	EP	N/A
3248026	12/2016	EP	N/A
3256888	12/2016	EP	N/A
3359999	12/2017	EP	N/A
2494388	12/2017	EP	N/A
3398007	12/2017	EP	N/A
3433658	12/2018	EP	N/A
3433659	12/2018	EP	N/A

2842003	12/2018	EP	N/A
3499278	12/2018	EP	N/A
3245551	12/2018	EP	N/A
3548939	12/2018	EP	N/A
3698214	12/2019	EP	N/A
3710876	12/2019	EP	N/A
3710887	12/2019	EP	N/A
3710893	12/2019	EP	N/A
3710894	12/2019	EP	N/A
3245444	12/2020	EP	N/A
3894938	12/2020	EP	N/A
3924759	12/2020	EP	N/A
3927793	12/2020	EP	N/A
3938821	12/2021	EP	N/A
3980825	12/2021	EP	N/A
4004615	12/2021	EP	N/A
4022370	12/2021	EP	N/A
2831659	12/2022	EP	N/A
3433658	12/2022	EP	N/A
3256888	12/2023	EP	N/A
4350422	12/2023	EP	N/A
3433659	12/2023	EP	N/A
20176157	12/2018	FI	N/A
20176158	12/2018	FI	N/A
20176161	12/2018	FI	N/A
2677463	12/1991	FR	N/A
2975506	12/2011	FR	N/A
2115178	12/1982	GB	N/A
2140935	12/1983	GB	N/A
2500631	12/2012	GB	N/A
2508661	12/2013	GB	N/A
2509536	12/2013	GB	N/A
2512077	12/2013	GB	N/A
2514658	12/2013	GB	N/A
1204684	12/2014	HK	N/A
1205563	12/2014	HK	N/A
1205793	12/2014	HK	N/A
1206101	12/2014	HK	N/A
S49092850	12/1973	JP	N/A
57089722	12/1981	JP	N/A
02186319	12/1989	JP	N/A
03239384	12/1990	JP	N/A
H04303812	12/1991	JP	N/A
H04303813	12/1991	JP	N/A
H05066427	12/1992	JP	N/A
5-224018	12/1992	JP	N/A
06294952	12/1993	JP	N/A
7-66383	12/1994	JP	N/A
07098439	12/1994	JP	N/A
0990312	12/1996	JP	N/A

H09185313	12/1996	JP	N/A
2689851	12/1996	JP	N/A
H10503279	12/1997	JP	N/A
10096903	12/1997	JP	N/A
11109320	12/1998	JP	N/A
11142806	12/1998	JP	N/A
2953444	12/1998	JP	N/A
H11271535	12/1998	JP	N/A
2000056259	12/1999	JP	N/A
2000511306	12/1999	JP	N/A
2000261706	12/1999	JP	N/A
2000267042	12/1999	JP	N/A
2000321962	12/1999	JP	N/A
2001027739	12/2000	JP	N/A
2001296503	12/2000	JP	N/A
2002090858	12/2001	JP	N/A
2002122906	12/2001	JP	N/A
2002156617	12/2001	JP	N/A
2002162598	12/2001	JP	N/A
2002523802	12/2001	JP	N/A
2002529790	12/2001	JP	N/A
2002311379	12/2001	JP	N/A
2003066428	12/2002	JP	N/A
2003270419	12/2002	JP	N/A
2003315540	12/2002	JP	N/A
2004157245	12/2003	JP	N/A
2005037872	12/2004	JP	N/A
2005222963	12/2004	JP	N/A
2006350129	12/2005	JP	N/A
2007011057	12/2006	JP	N/A
2007094175	12/2006	JP	N/A
2007199699	12/2006	JP	N/A
2007219106	12/2006	JP	N/A
2007279313	12/2006	JP	N/A
2008112187	12/2007	JP	N/A
2008145619	12/2007	JP	N/A
2009036955	12/2008	JP	N/A
2009515225	12/2008	JP	N/A
2009132221	12/2008	JP	N/A
2009133999	12/2008	JP	N/A
2009211091	12/2008	JP	N/A
4367775	12/2008	JP	N/A
2010044326	12/2009	JP	N/A
2010256631	12/2009	JP	N/A
2011075681	12/2010	JP	N/A
2011158907	12/2010	JP	N/A
2011164545	12/2010	JP	N/A
2011232510	12/2010	JP	N/A
2012137616	12/2011	JP	N/A
2012163642	12/2011	JP	N/A

2012533089	12/2011	JP	N/A
2013061480	12/2012	JP	N/A
5303928	12/2012	JP	N/A
2013235256	12/2012	JP	N/A
2014132328	12/2013	JP	N/A
5588794	12/2013	JP	N/A
5646748	12/2013	JP	N/A
2015053163	12/2014	JP	N/A
2015523586	12/2014	JP	N/A
2015172713	12/2014	JP	N/A
2016030503	12/2015	JP	N/A
2017528739	12/2016	JP	N/A
2018508037	12/2017	JP	N/A
2018512562	12/2017	JP	N/A
2018533069	12/2017	JP	N/A
2019512745	12/2018	JP	N/A
2019520595	12/2018	JP	N/A
6598269	12/2018	JP	N/A
6680793	12/2019	JP	N/A
2020514783	12/2019	JP	N/A
1664536	12/2019	JP	N/A
6734933	12/2019	JP	N/A
2020-537187	12/2019	JP	N/A
2021509488	12/2020	JP	N/A
2021509736	12/2020	JP	N/A
2021509737	12/2020	JP	N/A
2021509739	12/2020	JP	N/A
6895451	12/2020	JP	N/A
2022509083	12/2021	JP	N/A
2022513896	12/2021	JP	N/A
2022-520472	12/2021	JP	N/A
2022-523365	12/2021	JP	N/A
2022-525165	12/2021	JP	N/A
2022091982	12/2021	JP	N/A
2022535460	12/2021	JP	N/A
2023044680	12/2022	JP	N/A
7250799	12/2022	JP	N/A
7612592	12/2023	JP	N/A
20060132474	12/2005	KR	N/A
100803288	12/2007	KR	N/A
20100092059	12/2009	KR	N/A
20140140063	12/2013	KR	N/A
20140142337	12/2013	KR	N/A
20160084416	12/2015	KR	N/A
20170031357	12/2016	KR	N/A
20170039655	12/2016	KR	N/A
30-1061010	12/2019	KR	N/A
10-2020-0106932	12/2019	KR	N/A
10-2020-0108030	12/2019	KR	N/A
2020-0106170	12/2019	KR	N/A

20200104402	12/2019	KR	N/A
20210100174	12/2020	KR	N/A
10-2021-0127237	12/2020	KR	N/A
10-2021-0138609	12/2020	KR	N/A
20210134763	12/2020	KR	N/A
10-2022-0036963	12/2021	KR	N/A
1020220038452	12/2021	KR	N/A
10-2022-0054386	12/2021	KR	N/A
102745805	12/2023	KR	N/A
20250004154	12/2024	KR	N/A
200535633	12/2004	TW	N/A
200801583	12/2007	TW	N/A
201314263	12/2012	TW	N/A
201600943	12/2015	TW	N/A
201604601	12/2015	TW	N/A
9216880	12/1991	WO	N/A
1997001133	12/1996	WO	N/A
1997027519	12/1996	WO	N/A
1998004650	12/1997	WO	N/A
1999009440	12/1998	WO	N/A
9931658	12/1998	WO	N/A
1999052002	12/1998	WO	N/A
2000016136	12/1999	WO	N/A
2000023830	12/1999	WO	N/A
2000023832	12/1999	WO	N/A
2000023847	12/1999	WO	N/A
2000028369	12/1999	WO	N/A
2000028369	12/1999	WO	N/A
2001050200	12/2000	WO	N/A
2001090822	12/2000	WO	N/A
2002082168	12/2001	WO	N/A
02093204	12/2001	WO	N/A
2003081320	12/2002	WO	N/A
2004023174	12/2003	WO	N/A
2004053531	12/2003	WO	N/A
2004102226	12/2003	WO	N/A
2004109349	12/2003	WO	N/A
2004109349	12/2004	WO	N/A
2005001753	12/2004	WO	N/A
2005006065	12/2004	WO	N/A
2005006065	12/2004	WO	N/A
2005047988	12/2004	WO	N/A
2005073798	12/2004	WO	N/A
2006002870	12/2005	WO	N/A
2006064301	12/2005	WO	N/A
2006064325	12/2005	WO	N/A
2006064334	12/2005	WO	N/A
2006102073	12/2005	WO	N/A
2006132614	12/2005	WO	N/A
2006102073	12/2006	WO	N/A

2007015141	12/2006	WO	N/A
2007029032	12/2006	WO	N/A
2007058348	12/2006	WO	N/A
2007085682	12/2006	WO	N/A
2007130130	12/2006	WO	N/A
2007141587	12/2006	WO	N/A
2007141589	12/2006	WO	N/A
2008011066	12/2007	WO	N/A
2008038058	12/2007	WO	N/A
2008011066	12/2007	WO	N/A
2008081070	12/2007	WO	N/A
2008100545	12/2007	WO	N/A
2008011066	12/2007	WO	N/A
2009013597	12/2008	WO	N/A
2009013597	12/2008	WO	N/A
2009077802	12/2008	WO	N/A
2009077803	12/2008	WO	N/A
2009101238	12/2008	WO	N/A
2007130130	12/2008	WO	N/A
2009155437	12/2008	WO	N/A
2009155437	12/2009	WO	N/A
2010023444	12/2009	WO	N/A
2010057219	12/2009	WO	N/A
2010067114	12/2009	WO	N/A
2010067117	12/2009	WO	N/A
2010078856	12/2009	WO	N/A
2010104692	12/2009	WO	N/A
2010122330	12/2009	WO	N/A
2010125337	12/2009	WO	N/A
2010125337	12/2009	WO	N/A
2010131046	12/2009	WO	N/A
2011012825	12/2010	WO	N/A
2011032005	12/2010	WO	N/A
2011042711	12/2010	WO	N/A
2011051660	12/2010	WO	N/A
2011055109	12/2010	WO	N/A
2011042711	12/2010	WO	N/A
2011073673	12/2010	WO	N/A
2011107831	12/2010	WO	N/A
2011110821	12/2010	WO	N/A
2011131978	12/2010	WO	N/A
2012052352	12/2011	WO	N/A
2012062658	12/2011	WO	N/A
2012136970	12/2011	WO	N/A
2012158950	12/2011	WO	N/A
2012172295	12/2011	WO	N/A
2013027004	12/2012	WO	N/A
2013027006	12/2012	WO	N/A
2013033274	12/2012	WO	N/A
2013034879	12/2012	WO	N/A

2013049012	12/2012	WO	N/A
2013054972	12/2012	WO	N/A
2013102759	12/2012	WO	N/A
2013163347	12/2012	WO	N/A
2013167864	12/2012	WO	N/A
2013190257	12/2012	WO	N/A
2014064427	12/2013	WO	N/A
2014080155	12/2013	WO	N/A
2014085734	12/2013	WO	N/A
2014090379	12/2013	WO	N/A
2014091200	12/2013	WO	N/A
2014093601	12/2013	WO	N/A
2014100182	12/2013	WO	N/A
2014113506	12/2013	WO	N/A
2014116615	12/2013	WO	N/A
2014130383	12/2013	WO	N/A
2014144526	12/2013	WO	N/A
2014156167	12/2013	WO	N/A
2014159621	12/2013	WO	N/A
2014164901	12/2013	WO	N/A
2014176695	12/2013	WO	N/A
2014179632	12/2013	WO	N/A
2014188149	12/2013	WO	N/A
2014209733	12/2013	WO	N/A
2014209819	12/2013	WO	N/A
2014209820	12/2013	WO	N/A
2014209821	12/2013	WO	N/A
2014210349	12/2013	WO	N/A
2015006784	12/2014	WO	N/A
2015015138	12/2014	WO	N/A
2015017291	12/2014	WO	N/A
2015069553	12/2014	WO	N/A
2015081313	12/2014	WO	N/A
2015117039	12/2014	WO	N/A
2015145119	12/2014	WO	N/A
2016010289	12/2015	WO	N/A
2016020630	12/2015	WO	N/A
2016020643	12/2015	WO	N/A
2016025350	12/2015	WO	N/A
2016020630	12/2015	WO	N/A
2016042283	12/2015	WO	N/A
2016044193	12/2015	WO	N/A
2016046514	12/2015	WO	N/A
2016048729	12/2015	WO	N/A
2016054092	12/2015	WO	N/A
2016069606	12/2015	WO	N/A
2016087442	12/2015	WO	N/A
2016103263	12/2015	WO	N/A
2016111706	12/2015	WO	N/A
2016111707	12/2015	WO	N/A

2016111708	12/2015	WO	N/A
2016111709	12/2015	WO	N/A
2016113533	12/2015	WO	N/A
2016113534	12/2015	WO	N/A
2016116733	12/2015	WO	N/A
2016118107	12/2015	WO	N/A
2016122679	12/2015	WO	N/A
2016130509	12/2015	WO	N/A
2016135434	12/2015	WO	N/A
2016113533	12/2015	WO	N/A
2016156776	12/2015	WO	N/A
2016162606	12/2015	WO	N/A
2016181108	12/2015	WO	N/A
2016046514	12/2016	WO	N/A
2017060665	12/2016	WO	N/A
2017094129	12/2016	WO	N/A
2017120320	12/2016	WO	N/A
2017134412	12/2016	WO	N/A
2017160367	12/2016	WO	N/A
2017162999	12/2016	WO	N/A
2017178781	12/2016	WO	N/A
2017180403	12/2016	WO	N/A
2017182771	12/2016	WO	N/A
2017203200	12/2016	WO	N/A
2017203201	12/2016	WO	N/A
2017207987	12/2016	WO	N/A
2018102834	12/2017	WO	N/A
2018102834	12/2017	WO	N/A
2018096359	12/2017	WO	N/A
2018129398	12/2017	WO	N/A
2017162999	12/2017	WO	N/A
2018150163	12/2017	WO	N/A
2018206487	12/2017	WO	N/A
2019046649	12/2018	WO	N/A
2019077307	12/2018	WO	N/A
2019079350	12/2018	WO	N/A
2019079350	12/2018	WO	N/A
2019046649	12/2018	WO	N/A
2019122806	12/2018	WO	N/A
2019135784	12/2018	WO	N/A
2019135796	12/2018	WO	N/A
2019135837	12/2018	WO	N/A
2019136470	12/2018	WO	N/A
2019136471	12/2018	WO	N/A
2019136473	12/2018	WO	N/A
2019171038	12/2018	WO	N/A
2019185973	12/2018	WO	N/A
2019185975	12/2018	WO	N/A
2019185976	12/2018	WO	N/A
2019185977	12/2018	WO	N/A

2019217453	12/2018	WO	N/A
2020023779	12/2019	WO	N/A
2020123506	12/2019	WO	N/A
2020149956	12/2019	WO	N/A
2020163524	12/2019	WO	N/A
2020168348	12/2019	WO	N/A
2020172681	12/2019	WO	N/A
2020186113	12/2019	WO	N/A
2020212682	12/2019	WO	N/A
2020219092	12/2019	WO	N/A
2020227236	12/2019	WO	N/A
2020247930	12/2019	WO	N/A
2021016371	12/2020	WO	N/A
2021021926	12/2020	WO	N/A
2021032982	12/2020	WO	N/A
2021032983	12/2020	WO	N/A
2021041949	12/2020	WO	N/A
2021044121	12/2020	WO	N/A
2021138607	12/2020	WO	N/A
2021242898	12/2020	WO	N/A
2021262759	12/2020	WO	N/A
2022015878	12/2021	WO	N/A
2022099312	12/2021	WO	N/A
2022109615	12/2021	WO	N/A
2022150841	12/2021	WO	N/A

OTHER PUBLICATIONS

Extended European Search Report for EP Application No. 13192383.1, dated Apr. 2, 2014, 7 pgs. cited by applicant

Extended European Search Report for European Application No. 13765610.4 dated Feb. 16, 2016, 6 pgs. cited by applicant

Extended European Search Report for European Application No. 15187491.4, search completed Jan. 15, 2016, mailed Jan. 28, 2016, 5 pgs. cited by applicant

Extended European Search Report for European Application No. 18867522.7, Search completed Sep. 15, 2021, Mailed Sep. 24, 2021, 9 Pgs. cited by applicant

Extended European Search Report for European Application No. 18898154.2, Search completed Aug. 13, 2021, Mailed Aug. 23, 2021, 7 pgs. cited by applicant

Extended European Search Report for European Application No. 19736108.2, Search completed Sep. 15, 2021, Mailed Sep. 27, 2021, 8 pgs. cited by applicant

Extended European Search Report for European Application No. 18727645.6, Search completed Oct. 14, 2020, Mailed Oct. 23, 2020, 13 pgs. cited by applicant

Extended Search Report for European Application No. 18898841.4, Search completed Mar. 18, 2021, Mailed Mar. 26, 2021, 10 pgs. cited by applicant

Supplementary Partial European Search Report for European Application No. 18727645.6, Search completed Jul. 2, 2020, Mailed Jul. 13, 2020, 13 pgs. cited by applicant

International Preliminary Report on Patentability for International Application No.

PCT/GB2010/000835, issued Nov. 1, 2011, mailed Nov. 10, 2011, 9 pgs. cited by applicant

International Preliminary Report on Patentability for International Application No.

PCT/GB2010/001920, issued Apr. 11, 2012, mailed Apr. 19, 2012, 10 pgs. cited by applicant

International Preliminary Report on Patentability for International Application No.

PCT/GB2010/001982, report issued May 1, 2012, mailed May 10, 2012, 7 pgs. cited by applicant
International Preliminary Report on Patentability for International Application No.
PCT/GB2013/000273, issued Dec. 23, 2014, mailed Dec. 31, 2014, 8 pgs. cited by applicant
International Preliminary Report on Patentability for International Application No.
PCT/GB2015/000203, issued Mar. 21, 2017, mailed Mar. 30, 2017, 8 pgs. cited by applicant
International Preliminary Report on Patentability for International Application No.
PCT/GB2016/000036, issued Aug. 29, 2017, mailed Sep. 8, 2017, 8 pgs. cited by applicant
International Preliminary Report on Patentability for International Application No.
PCT/GB2016/000065, issued Oct. 3, 2017, mailed Oct. 12, 2017, 8 pgs. cited by applicant
International Preliminary Report on Patentability for International Application No.
PCT/US2018/012227, Report issued Jul. 30, 2019, Mailed Aug. 8, 2019, 7 Pgs. cited by applicant
International Preliminary Report on Patentability for International Application No.
PCT/US2019/012758, Report issued Jul. 14, 2020, Mailed Jul. 23, 2020, 4 Pgs. cited by applicant
International Preliminary Report on Patentability for International Application No.
PCT/US2019/012759, Report issued Jul. 14, 2020, Mailed Jul. 23, 2020, 6 Pgs. cited by applicant
International Preliminary Report on Patentability for International Application PCT
/US2018/015553, Report issued Jun. 4, 2019, Mailed Jun. 13, 2019, 6 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/GB2009/051676, issued Jun. 14, 2011, mailed Jun. 23, 2011, 6 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/GB2011/000349, issued Sep. 18, 2012, mailed Sep. 27, 2012, 10 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/GB2012/000331, issued Oct. 8, 2013, mailed Oct. 17, 2013, 8 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/GB2012/000677, issued Feb. 25, 2014, mailed Mar. 6, 2014, 5 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/GB2013/000005, issued Jul. 8, 2014, mailed Jul. 17, 2014, 12 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/GB2014/000295, issued Feb. 2, 2016, mailed Feb. 11, 2016, 4 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/GB2015/000225, issued Feb. 14, 2017, mailed Feb. 23, 2017, 8 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/GB2015/000228, issued Feb. 14, 2017, mailed Feb. 23, 2017, 11 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/GB2015/000274, Issued Mar. 28, 2017, mailed Apr. 6, 2017, 8 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/GB2016/000014, issued Jul. 25, 2017, mailed Aug. 3, 2017, 7 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/GB2017/000040, Report issued Sep. 25, 2018, Mailed Oct. 4, 2018, 7 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/GB2017/000055, issued Oct. 16, 2018, Mailed Oct. 25, 2018, 9 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/US2014/011736, issued Jul. 21, 2015, mailed Jul. 30, 2015, 9 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/US2016/017091, issued Aug. 15, 2017, mailed Aug. 24, 2017, 5 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/US2018/012691, issued Jul. 9, 2019, Mailed Jul. 18, 2019, 10 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/US2019/012764, Report issued Jul. 14, 2020, Mailed Jul. 23, 2020, 5 pgs. cited by applicant
International Preliminary Report on Patentability for International Application

PCT/US2019/043496 Report issued Jan. 26, 2021, Mailed Feb. 4, 2021, 5 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/US2019/047097 issued Sep. 28, 2021, Mailed on Nov. 4, 2021, 7 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/US2019/065478, Report issued Jun. 8, 2021, mailed on Jun. 24, 2021, 9 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/US2020/019549, Report issued Aug. 10, 2021, Mailed Sep. 2, 2021, 7 pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/US2020/022482, issued Aug. 25, 2021, Mailed Sep. 23, 2021, 7 Pgs. cited by applicant
International Preliminary Report on Patentability for International Application
PCT/US2020/031363, issued Nov. 2, 2021, Mailed Nov. 18, 2021, 7 pgs. cited by applicant
International Preliminary Report on Patentability for PCT Application No. PCT/US2013/038070, dated Oct. 28, 2014, 6 pgs. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/GB2010/000835, completed Oct. 26, 2010, mailed Nov. 8, 2010, 12 pgs. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/GB2010/001920, completed Mar. 29, 2011, mailed Apr. 6, 2011, 15 pgs. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/GB2015/000228, Search completed May 4, 2011, Mailed Jul. 15, 2011, 15 Pgs. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/GB2016/000036, completed Jul. 4, 2016, mailed Jul. 13, 2016, 10 pgs. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/GB2016/000065, completed Jul. 14, 2016, mailed Jul. 27, 2016, 10 pgs. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/GB2017/000015, Search completed Apr. 25, 2017, Mailed May 8, 2017, 10 pgs. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/GB2017/000055, Search completed Jul. 19, 2017, Mailed Jul. 26, 2017, 12 pgs. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/IB2008/001909, Search completed Feb. 4, 2009, Mailed Feb. 17, 2009, 6 pgs. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/US2013/038070, completed Aug. 12, 2013, mailed Aug. 14, 2013, 12 pgs. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/US2014/011736, completed Apr. 18, 2014, mailed May 8, 2014, 10 pgs. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/US2018/012227, Search completed Feb. 28, 2018, Mailed Mar. 14, 2018, 8 Pgs. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/US2018/012691, completed Mar. 10, 2018, mailed Mar. 28, 2018, 16 pgs. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/US2018/015553, completed Aug. 6, 2018, Mailed Sep. 19, 2018, 12 pgs. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/US2018/037410, Search completed Aug. 16, 2018, Mailed Aug. 30, 2018, 11 pgs. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/US2018/048636, Search completed Nov. 1, 2018, Mailed Nov. 15, 2018, 16 pgs. cited by

applicant

International Search Report and Written Opinion for International Application No.

PCT/US2018/048960, Search completed Dec. 14, 2018, Mailed Jan. 8, 2019, 14 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2018/056150, Search completed Dec. 4, 2018, Mailed Dec. 26, 2018, 10 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2018/062835, Search completed Jan. 14, 2019, Mailed Jan. 31, 2019, 14 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2019/012758, completed Mar. 12, 2019, mailed Mar. 27, 2019, 9 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2019/012764, completed Mar. 1, 2019, mailed Mar. 18, 2019, 9 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2019/031163, Search completed Jul. 9, 2019, Mailed Jul. 29, 2019, 11 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2019/043496, Search completed Sep. 28, 2019, Mailed Nov. 14, 2019, 12 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2019/064765, Search completed Feb. 3, 2020, Mailed Mar. 18, 2020, 11 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2019/065478, Search completed Jan. 29, 2020, Mailed Feb. 11, 2020, 14 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2020/018686, Search completed Apr. 25, 2020, Mailed May 22, 2020, 11 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2020/019549, Search completed Apr. 14, 2020, Mailed May 22, 2020, 12 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2020/022482, Search completed May 12, 2020, Mailed Jun. 9, 2020, 11 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2020/031363, completed May 28, 2020, Mailed Jun. 10, 2020, 8 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2020/036654, Search completed Aug. 21, 2020, Mailed Sep. 4, 2020, 14 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2020/043107, Search completed Sep. 28, 2020, Mailed Oct. 15, 2020, 12 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2020/048590, Search completed Dec. 7, 2020, Mailed Jan. 11, 2021, 19 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2020/067737, Search completed Mar. 3, 2021, Mailed Mar. 25, 2021, 12 pgs. cited by applicant

International Search Report and Written Opinion for International Application No.

PCT/US2021/072287, Search completed Jan. 10, 2022, Mailed Feb. 17, 2022, 11 pgs. cited by applicant
International Search Report and Written Opinion for International Application
PCT/GB2009/051676, completed May 10, 2010, mailed May 18, 2010, 7 pgs. cited by applicant
International Search Report and Written Opinion for International Application
PCT/GB2016/000181, completed Dec. 21, 2016, mailed Feb. 27, 2017, 21 pgs. cited by applicant
International Search Report and Written Opinion for International Application
PCT/US2016/017091, completed by the European Patent Office on Apr. 20, 2016, 7 pgs. cited by applicant
International Search Report and Written Opinion for International Application
PCT/US2019/012759, completed Mar. 14, 2019, mailed Apr. 15, 2019, 12 pgs. cited by applicant
International Search Report and Written Opinion for International Application
PCT/US2019/047097, completed Nov. 22, 2015, mailed Dec. 16, 2019, 10 pgs. cited by applicant
International Search Report for International Application PCT/GB2014/000295, completed Nov. 18, 2014, mailed Jan. 5, 2015, 4 pgs. cited by applicant
International Search Report for International Application PCT/GB2017/000040, mailed Jul. 18, 2017, completed Jul. 10, 2017, 3 pgs. cited by applicant
International Search Report for PCT/GB2010/001982, completed by the European Patent Office on Feb. 24, 2011, 4 pgs. cited by applicant
International Search Report for PCT/GB2011/000349, completed by the European Patent Office on Aug. 17, 2011, 4 pgs. cited by applicant
International Search Report for PCT/GB2012/000331, completed by the European Patent Office on Aug. 29, 2012, 4 pgs. cited by applicant
International Search Report for PCT/GB2012/000677, completed by the European Patent Office on Dec. 10, 2012, 4 pgs. cited by applicant
International Search Report for PCT/GB2013/000005, completed by the European Patent Office on Jul. 16, 2013, 3 pgs. cited by applicant
International Search Report for PCT/GB2013/000210, completed by the European Patent Office on Aug. 12, 2013, 3 pgs. cited by applicant
International Search Report for PCT/GB2013/000273, completed by the European Patent Office on Aug. 30, 2013, 4 pgs. cited by applicant
International Search Report for PCT/GB2014/000197, Completed by the European Patent Office on Jul. 31, 2014, 3 pgs. cited by applicant
International Search Report for PCT/GB2015/000203, completed by the European Patent Office on Oct. 9, 2015, 4 pgs. cited by applicant
International Search Report for PCT/GB2015/000225, completed by the European Patent Office on Nov. 10, 2015, mailed Dec. 2, 2016, 5 pgs. cited by applicant
International Search Report for PCT/GB2015/000274, completed by the European Patent Office on Jan. 7, 2016, 4 pgs. cited by applicant
International Search Report for PCT/GB2016/000003, Completed by the European Patent Office May 31, 2016, 6 pgs. cited by applicant
International Search Report for PCT/GB2016/000005, completed by the European Patent Office on May 27, 2016, 4 pgs. cited by applicant
International Search Report for PCT/GB2016/000014, completed by the European Patent Office on Jun. 27, 2016, 4 pgs. cited by applicant
International Search Report for PCT/GB2016/000051, Completed Aug. 11, 2016, 3 Pgs. cited by applicant
Written Opinion for International Application No. PCT/GB2010/001982, search completed Feb. 24, 2011, mailed Mar. 8, 2011, 6 pgs. cited by applicant
Written Opinion for International Application No. PCT/GB2011/000349, completed Aug. 17, 2011,

mailed Aug. 25, 2011, 9 pgs. cited by applicant
Written Opinion for International Application No. PCT/GB2012/000331, completed Aug. 29, 2012, mailed Sep. 6, 2012, 7 pgs. cited by applicant
Written Opinion for International Application No. PCT/GB2012/000677, completed Dec. 10, 2012, mailed Dec. 17, 2012, 4 pgs. cited by applicant
Written Opinion for International Application No. PCT/GB2013/000005, search completed Jul. 16, 2013, mailed Jul. 24, 2013, 11 pgs. cited by applicant
Written Opinion for International Application No. PCT/GB2013/000273, completed Aug. 30, 2013, mailed Sep. 9, 2013, 7 pgs. cited by applicant
Written Opinion for International Application No. PCT/GB2014/000197, Search completed Jul. 31, 2014, Mailed Aug. 7, 2014, 6 Pgs. cited by applicant
Written Opinion for International Application No. PCT/GB2014/000295, search completed Nov. 18, 2014, mailed Jan. 5, 2015, 3 pgs. cited by applicant
Written Opinion for International Application No. PCT/GB2015/000203, completed Oct. 29, 2015, mailed Nov. 16, 2015, 7 pgs. cited by applicant
Written Opinion for International Application No. PCT/GB2015/000225, search completed Nov. 10, 2015, mailed Feb. 4, 2016, 7 pgs. cited by applicant
Written Opinion for International Application No. PCT/GB2015/000274, search completed Jan. 7, 2016, mailed Jan. 19, 2016, 7 pgs. cited by applicant
Written Opinion for International Application No. PCT/GB2016/000014, search completed Jun. 27, 2016, mailed Jul. 7, 2016, 6 pgs. cited by applicant
Written Opinion for International Application No. PCT/GB2016/000051, Search completed Aug. 11, 2016, Mailed Aug. 22, 2016, 6 Pgs. cited by applicant
Written Opinion for International Application No. PCT/GB2017/000040, search completed Jul. 10, 2017, mailed Jul. 18, 2017, 6 pgs. cited by applicant
Written Opinion for International Application PCT/GB2013/000210, completed Aug. 12, 2013, Mailed Aug. 20, 2013, 5 pgs. cited by applicant
Written Opinion for International Application PCT/GB2016/000003, completed May 31, 2016, mailed Aug. 12, 2016, 10 pgs. cited by applicant
Written Opinion for International Application PCT/GB2016/000005, search completed May 27, 2016, mailed Jun. 6, 2016, 6 pgs. cited by applicant
Digi Lens: Waveguides, announced unknown, [online], [site visited Nov. 6, 2020]. Available from Internet, <URL: <https://www.digilens.com/technology/waveguides/>> (Year: 2020). cited by applicant
Google search: “digilens waveguide” [site visited Sep. 14, 2020], https://www.google.com/search?q=digilens+waveguide&sxsrf=ALeKk02RFwZAZ0vrlxVH0M_2fiXFkhW1FA:1604777621684&source=lnms&tbm=isch&sa=X&ved=2ah_UKEwjyNXAlvHsAh_U_Rh_HI EHTufCvsQ_AUoAnoECBwQBA&biw=1200&bih=1777. cited by applicant
Google search: “eyewear display devices” [site visited Sep. 14, 2020], https://www.google.com/search?q=eyewear+display+devices&sxsrf=ALeKk01WWfnOAgQR_bhydJaYK3e37r_JLg:1604779001617&source=lnms&tbm=isch&sa=X&ved=2ah_UKEwi99txSm_HsAhVaoHIEHawtD8QQ_AUoAnoECC8QBA&biw=1200&bih=1777. cited by applicant
Google search: “smart glasses” [site visited Sep. 14, 2020], https://www.google.com/search?q=smart+glasses&sxsrf=ALeKk01KN1wj23-NqP-KCnrcsUpCgxyKA:1604779046920&source=lnms&tbm=isch&sa=X&ved=2ah_UKEwipkqPom_HsAhVKhXIEHQGF8Q_AUoBHoECCgQBg&biw=1200&bih=1777. cited by applicant
“Agilent ADNS-2051 Optical Mouse Sensor: Data Sheet”, Agilent Technologies, Jan. 9, 2002, 40 pgs. cited by applicant

"Application Note—Moxtek ProFlux Polarizer use with LCOS displays", CRL Opto Limited, <http://www.crlpto.com>, 2003, 6 pgs. cited by applicant

"Application Note AN16: Optical Considerations for Bridgelux LED Arrays", BridgeLux, Jul. 31, 2010, 23 pgs. cited by applicant

"Application Note: Variable Attenuator for Lasers", Technology and Applications Center, Newport Corporation, www.newport.com, 2006, DS-08067, 6 pgs. cited by applicant

"Bae Systems to Unveil Q-Sight Family of Helmet-Mounted Display at AUSA Symposium", Released on Tuesday, Oct. 9, 2007, 1 pg. cited by applicant

"Beam Steering Using Liquid Crystals", Boulder Nonlinear Systems, Inc., info@bnonlinear.com, May 8, 2001, 4 pgs. cited by applicant

"BragGrate—Deflector: Transmitting Volume Bragg Grating for angular selection and magnification", 2015, www.OptiGrate.com. cited by applicant

"Cree XLamp XP-E LEDs", Cree, Inc., Retrieved from www.cree.com/Xlamp, CLD-DS18 Rev 17, 2013, 17 pgs. cited by applicant

"Desmodur N 3900", Bayer MaterialScience AG, Mar. 18, 2013, www.bayercoatings.com, 4 pgs. cited by applicant

"Digilens—Innovative Augmented Reality Display and Sensor Solutions for OEMs", Jun. 6, 2017, 31 pgs. cited by applicant

"Exotic Optical Components", Building Electro-Optical Systems, Making It All Work, Chapter 7, John Wiley & Sons, Inc., pp. 233-261. cited by applicant

"FHS Lenses Series", Fraen Corporation, www.fraen.com, Jun. 16, 2003, 10 pgs. cited by applicant

"FLP Lens Series for Luxeontm Rebel and Rebel ES LEDs", Fraen Corporation, www.fraensrl.com, Aug. 7, 2015, 8 pgs. cited by applicant

"Head-up Displays, See-through display for military aviation", BAE Systems, 2016, 3 pgs. cited by applicant

"Holder for Luxeon Rebel—Part No. 180", Polymer Optics Ltd., 2008, 12 pgs. cited by applicant

"LED 7-Segment Displays", Lumex, uk.digikey.com, 2003, UK031, 36 pgs. cited by applicant

"LED325W UVTOP UV LED with Window", Thorlabs, Specifications and Documentation, 21978-S01 Rev. A, Apr. 8, 2011, 5 pgs. cited by applicant

"Liquid Crystal Phases", Phases of Liquid Crystals, <http://plc.cwru.edu/tutorial/enhanced/files/lc/phase>, Retrieved on Sep. 21, 2004, 6 pgs. cited by applicant

"LiteHUD Head-up display", BAE Systems, 2016, 2 pgs. cited by applicant

"LiteHUD Head-up display infographic", BAE Systems, 2017, 2 pgs. cited by applicant

"Luxeon C: Power Light Source", Philips Lumileds, www.philipslumileds.com, 2012, 18 pgs. cited by applicant

"Luxeon Rebel ES: Leading efficacy and light output, maximum design flexibility", Luxeon Rebel ES Datasheet DS61 20130221, www.philipslumileds.com, 2013, 33 pgs. cited by applicant

"Mobile Display Report", Insight Media, LLC, Apr. 2012, vol. 7, No. 4, 72 pgs. cited by applicant

"Molecular Imprints Imprio 55", Engineering at Illinois, Micro + Nanotechnology Lab, Retrieved from <https://mntl.illinois.edu/facilities/cleanrooms/equipment/Nano-Imprint.asp>, Dec. 28, 2015, 2 pgs. cited by applicant

"Navy awards SGB Labs a contract for HMDs for simulation and training", Press releases, DigiLens, Oct. 2012, pp. 1-2. cited by applicant

"Optical measurements of retinal flow", Industrial Research Limited, Feb. 2012, 18 pgs. cited by applicant

"Osterhout Design Group Develops Next-Generation, Fully-integrated Smart Glasses Using Qualcomm Technologies", ODG, www.osterhoutgroup.com, Sep. 18, 2014, 2 pgs. cited by applicant

"Plastic has replaced glass in photochromic lens", www.plastemart.com, 2003, 1 page. cited by

applicant

“Range Finding Using Pulse Lasers”, Osram, Opto Semiconductors, Sep. 10, 2004, 7 pgs. cited by applicant

“Response time in Liquid-Crystal Variable Retarders”, Meadowlark Optics, Inc., 2005, 4 pgs. cited by applicant

“Secondary Optics Design Considerations for SuperFlux LEDs”, Lumileds, application brief AB20-5, Sep. 2002, 23 pgs. cited by applicant

“Solid-State Optical Mouse Sensor with Quadrature Outputs”, IC Datasheet, UniqueICs, Jul. 15, 2004, 11 pgs. cited by applicant

“SVGA TransparentVLSITM Microdisplay Evaluation Kit”, Radiant Images, Inc., Product Data Sheet, 2003, 3 pgs. cited by applicant

“Technical Data Sheet LPR1”, Luminus Devices, Inc., Luminus Projection Chipset, Release 1, Preliminary, Revision B, Sep. 21, 2004, 9 pgs. cited by applicant

“The Next Generation of TV”, SID Information Display, Nov./Dec. 2014, vol. 30, No. 6, 56 pgs. cited by applicant

“Thermal Management Considerations for SuperFlux LEDs”, Lumileds, application brief AB20-4, Sep. 2002, 14 pgs. cited by applicant

“USAF Awards SBG Labs an SBIR Contract for Wide Field of View HUD”, Press Release, SBG Labs DigiLens, Apr. 2014, 2 pgs. cited by applicant

“UVTOP240”, Roithner LaserTechnik GmbH, v 2.0, Jun. 24, 2013, 6 pgs. cited by applicant

“UVTOP310”, Roithner LaserTechnik GmbH, v 2.0, Jun. 24, 2013, 6 pgs. cited by applicant

“Velodyne's HDL-64E: A High Definition Lidar Sensor for 3-D Applications”, High Definition Lidar, white paper, Oct. 2007, 7 pgs. cited by applicant

“VerLASE Gets Patent for Breakthrough Color Conversion Technology That Enables Full Color MicroLED Arrays for Near Eye Displays”, Cision PRweb, Apr. 28, 2015, Retrieved from the Internet <http://www.prweb.com/releases/2015/04/prweb12681038.htm>, 3 pgs. cited by applicant

“X-Cubes—Revisited for LCOS”, Basid, RAF Electronics Corp. Rawson Optics, Inc., Oct. 24, 2002, 16 pgs. cited by applicant

Aachen, “Design of plastic optics for LED applications”, Optics Colloquium 2009, Mar. 19, 2009, 30 pgs. cited by applicant

Abbate et al., “Characterization of LC-polymer composites for opto-electronic application”, Proceedings of OPTOEL'03, Leganes-Madrid, Spain, Jul. 14-16, 2003, 4 pgs. cited by applicant

Al-Kalbani et al., “Ocular Microtremor laser speckle metrology”, Proc. of SPIE, 2009, vol. 7176 717606-1, 12 pgs., doi:10.1117/12.808855. cited by applicant

Almanza-Workman et al., “Planarization coating for polyimide substrates used in roll-to-roll fabrication of active matrix backplanes for flexible displays”, HP Laboratories, HPL-2012-23, Feb. 6, 2012, 12 pgs. cited by applicant

Amitai et al., “Visor-display design based on planar holographic optics”, Applied Optics, vol. 34, No. 8, Mar. 10, 1995, pp. 1352-1356. cited by applicant

Amundson et al., “Morphology and electro-optic properties of polymer-dispersed liquid-crystal films”, Physical Review E, Feb. 1997, vol. 55, No. 2, pp. 1646-1654. cited by applicant

An et al., “Speckle suppression in laser display using several partially coherent beams”, Optics Express, Jan. 5, 2009, vol. 17, No. 1, pp. 92-103, first published Dec. 22, 2008. cited by applicant

Apter et al., “Electrooptical Wide-Angle Beam Deflector Based on Fringing-Field-Induced Refractive Inhomogeneity in a Liquid Crystal Layer”, 23rd IEEE Convention of Electrical and Electronics Engineers in Israel, Sep. 6-7, 2004, pp. 240-243. cited by applicant

Arnold et al., “52.3: An Improved Polarizing Beamsplitter LCOS Projection Display Based on Wire-Grid Polarizers”, Society for Information Display, Jun. 2001, pp. 1282-1285. cited by applicant

Ayras et al., “Exit pupil expander with a large field of view based on diffractive optics”, Journal of

the Society for Information Display, May 18, 2009, vol. 17, No. 8, pp. 659-664, DOI: 10.1889/JSID17.8.659. cited by applicant

Baets et al., “Resonant-Cavity Light-Emitting Diodes: a review”, Proceedings of SPIE, 2003, vol. 4996, pp. 74-86. cited by applicant

Bayer et al., “Introduction to Helmet-Mounted Displays”, 2016, pp. 47-108. cited by applicant

Beckel et al., “Electro-optic properties of thiol-ene polymer stabilized ferroelectric liquid crystals”, Liquid Crystals, vol. 30, No. 11, Nov. 2003, pp. 1343-1350, DOI: 10.1080/02678290310001605910. cited by applicant

Bergkvist, “Biospeckle-based Study of the Line Profile of Light Scattered in Strawberries”, Master Thesis, Lund Reports on Atomic Physics, LRAP-220, Lund 1997, pp. 1-62. cited by applicant

Bernards et al., “Nanoscale porosity in polymer films: fabrication and therapeutic applications”, Soft Matter, Jan. 1, 2010, vol. 6, No. 8, pp. 1621-1631, doi:10.1039/B922303G. cited by applicant

Bhuvaneshwaran et al., “Spectral response of Bragg gratings in multimode polymer waveguides”, Applied Optics, Dec. 1, 2017, vol. 56. No. 34, pp. 9573-9582, doi: 10.1364/AO.56.009573. cited by applicant

Bleha et al., “Binocular Holographic Waveguide Visor Display”, SID Symposium Digest of Technical Papers, Holoeye Systems Inc., Jun. 2014, San Diego, CA, 4 pgs. cited by applicant

Bleha et al., “D-ILA Technology for High Resolution Projection Displays”, Sep. 10, 2003, Proceedings, vol. 5080, 11 pgs., doi:10.1117/12.497532. cited by applicant

Bone, “Design Obstacles for LCOS Displays in Projection Applications “Optics architectures for LCOS are still evolving,”” Aurora Systems Inc., Bay Area SID Seminar, Mar. 27, 2001, 22 pgs. cited by applicant

Born et al., “Optics of Crystals”, Principles of Optics 5th Edition 1975, pp. 705-707. cited by applicant

Bourzac, “Magic Leap Needs to Engineer a Miracle”, Intelligent Machines, Jun. 11, 2015, 7 pgs. cited by applicant

Bowen et al., “Optimisation of interdigitated electrodes for piezoelectric actuators and active fibre composites”, J Electroceram, Jul. 2006, vol. 16, pp. 263-269, DOI 10.1007/s10832-006-9862-8. cited by applicant

Bowley et al., “Variable-wavelength switchable Bragg gratings formed in polymer-dispersed liquid crystals”, Applied Physics Letters, Jul. 2, 2001, vol. 79, No. 1, pp. 9-11, DOI: 10.1063/1.1383566. cited by applicant

Bronnikov et al., “Polymer-Dispersed Liquid Crystals: Progress in Preparation, Investigation and Application”, Journal of Macromolecular Science Part B, published online Sep. 30, 2013, vol. 52, pp. 1718-1738, DOI: 10.1080/00222348.2013.808926. cited by applicant

Brown, “Waveguide Displays”, Rockwell Collins, 2015, 11 pgs. cited by applicant

Bruzzo et al., “Compact, high-brightness LED illumination for projection systems”, Journal of the Society for Information Display, vol. 17, No. 12, Dec. 2009, pp. 1043-1049, DOI: 10.1189/JSID17.12.1043. cited by applicant

Buckley, “Colour holographic laser projection technology for heads-up and instrument cluster displays”, Conference: Proc. SID Conference 14th Annual Symposium on Vehicle Displays, Jan. 2007, 5 pgs. cited by applicant

Buckley, “Pixtronix DMS technology for head-up displays”, Pixtronix, Inc., Jan. 2011, 4 pgs. cited by applicant

Buckley et al., “Full colour holographic laser projector HUD”, Light Blue Optics Ltd., Aug. 10, 2015, 5 pgs. cited by applicant

Buckley et al., “Rear-view virtual image displays”, in Proc. SID Conference 16th Annual Symposium on Vehicle Displays, Jan. 2009, 5 pgs. cited by applicant

Bunning et al., “Effect of gel-point versus conversion on the real-time dynamics of holographic polymer-dispersed liquid crystal (HPDLC) formation”, Proceedings of SPIE—vol. 5213, Liquid

Crystals VII, Iam-Choon Khoo, Editor, Dec. 2003, pp. 123-129. cited by applicant

Bunning et al., "Electro-optical photonic crystals formed in H-PDLCs by thiol-ene photopolymerization", American Physical Society, Annual APS, Mar. 3-7, 2003, abstract #R1.135. cited by applicant

Bunning et al., "Holographic Polymer-Dispersed Liquid Crystals (H-PDLCs)1", Annual Review of Material Science, 2000, vol. 30, pp. 83-115. cited by applicant

Bunning et al., "Morphology of Anisotropic Polymer Dispersed Liquid Crystals and the Effect of Monomer Functionality", Journal of Polymer Science: Part B: Polymer Physics, Jul. 30, 1997, vol. 35, pp. 2825-2833. cited by applicant

Busbee et al., "SiO₂ Nanoparticle Sequestration via Reactive Functionalization in Holographic Polymer-Dispersed Liquid Crystals", Advanced Materials, Sep. 2009, vol. 21, pp. 3659-3662, DOI: 10.1002/adma.200900298. cited by applicant

Butler et al., "Diffractive Properties of Highly Birefringent Volume Gratings: Investigation", Journal of Optical Society of America, Feb. 2002, vol. 19, No. 2, pp. 183-189. cited by applicant

Cai et al., "Recent advances in antireflective surfaces based on nanostructure arrays", Materials Horizons, 2015, vol. 2, pp. 37-53, DOI: 10.1038/c4mh00140k. cited by applicant

Cameron, "Optical Waveguide Technology & Its Application in Head Mounted Displays", Proc. of SPIE, May 22, 2012, vol. 8383, pp. 83830E-1-83830E-11, doi: 10.1117/12.923660. cited by applicant

Cameron, "The Application of Holographic Optical Waveguide Technology to Q-Sight™ Family of Helmet Mounted Displays", Proc. of SPIE, 2009, vol. 7326, 11 pages, doi:10.1117/12.818581. cited by applicant

Caputo et al., "POLICRYPS Composite Materials: Features and Applications", Advances in Composite Materials—Analysis of Natural and Man-Made Materials, www.intechopen.com, Sep. 2011, pp. 93-118. cited by applicant

Caputo et al., "POLICRYPS Switchable Holographic Grating: A Promising Grating Electro-Optical Pixel for High Resolution Display Application", Journal of Display Technology, Mar. 2006, vol. 2, No. 1, pp. 38-51, DOI: 10.1109/JDT.2005.864156. cited by applicant

Caputo et al., "POLICRYPS: a liquid crystal composed nano/microstructure with a wide range of optical and electro-optical applications", Journal of Optics A: Pure and Applied Optics, Jan. 15, 2009, vol. 11, No. 2, 13 pgs., doi:10.1088/1464-4258/11/2/024017. cited by applicant

Carclo Optics, "Guide to choosing secondary optics", Carclo Optics, Dec. 15, 2014, www.carclo-optics.com, 48 pgs. cited by applicant

Carothers, "Polymers and polyfunctionality", Transactions of the Faraday Society, Jan. 1, 1936, vol. 32, pp. 39-49, doi:10.1039/TF9363200039. cited by applicant

Chen et al., "Polarization rotators fabricated by thermally-switched liquid crystal alignments based on rubbed poly(N-vinyl carbazole) films", Optics Express, Apr. 11, 2011, vol. 19, No. 8, pp. 7553-7558, first published Apr. 5, 2011. cited by applicant

Cheng et al., "Design of an ultra-thin near-eye display with geometrical waveguide and freeform optics", Optics Express, Aug. 2014, 16 pgs., DOI:10.1364/OE.22.020705. cited by applicant

Chi et al., "Ultralow-refractive-index optical thin films through nanoscale etching of ordered mesoporous silica films", Optic Letters, May 1, 2012, vol. 37, No. 9, pp. 1406-1408, first published Apr. 19, 2012. cited by applicant

Chigrinov et al., "Photo-aligning by azo-dyes: Physics and applications", Liquid Crystals Today, Sep. 6, 2006, <http://www.tandfonline.com/action/journalInformation?journalCode=tlcy20>, 15 pgs. cited by applicant

Cho et al., "Electro-optic Properties of CO₂ Fixed Polymer/Nematic LC Composite Films", Journal of Applied Polymer Science, Nov. 5, 2000, vol. 81, Issue 11, pp. 2744-2753. cited by applicant

Cho et al., "Optimization of Holographic Polymer Dispersed Liquid Crystals for Ternary Monomers", Polymer International, Nov. 1999, vol. 48, pp. 1085-1090. cited by applicant

Colegrove et al., "P-59: Technology of Stacking HPDLC for Higher Reflectance", SID 00 Digest, May 2000, pp. 770-773. cited by applicant

Crawford, "Electrically Switchable Bragg Gratings", Optics & Photonics News, Apr. 2003, pp. 54-59. cited by applicant

Cruz-Arreola et al., "Diffraction of beams by infinite or finite amplitude-phase gratings", Investigacio´ N Revista Mexicana De Fi´sica, Feb. 2011, vol. 57, No. 1, pp. 6-16. cited by applicant

Dabrowski, "High Birefringence Liquid Crystals", Crystals, Sep. 3, 2013, vol. 3, No. 3, pp. 443-482, doi:10.3390/cryst3030443. cited by applicant

Dainty, "Some statistical properties of random speckle patterns in coherent and partially coherent illumination", Optica Acta, Mar. 12, 1970, vol. 17, No. 10, pp. 761-772. cited by applicant

Date, "Alignment Control in Holographic Polymer Dispersed Liquid Crystal", Journal of Photopolymer Science and Technology, Nov. 2, 2000, vol. 13, No. 2, pp. 289-294. cited by applicant

Date et al., "52.3: Direct-viewing Display Using Alignment-controlled PDLC and Holographic PDLC", Society for Information Display Digest, May 2000, pp. 1184-1187, DOI: 10.1889/1.1832877. cited by applicant

Date et al., "Full-color reflective display device using holographically fabricated polymer-dispersed liquid crystal (HPDLC)", Journal of the SID, 1999, vol. 7, No. 1, pp. 17-22. cited by applicant

De Bitetto, "White light viewing of surface holograms by simple dispersion compensation", Applied Physics Letters, Dec. 15, 1966, vol. 9, No. 12, pp. 417-418. cited by applicant

De Sarkar et al., "Effect of Monomer Functionality on the Morphology and Performance of the Holographic Transmission Gratings Recorded on Polymer Dispersed Liquid Crystals", Macromolecules, 2003, vol. 36, No. 3, pp. 630-638. cited by applicant

Developer World, "Create customized augmented reality solutions", printed Oct. 19, 2017, LMX-001 holographic waveguide display, Sony Developer World, 3 pgs. cited by applicant

Dhar et al., "Recording media that exhibit high dynamic range for digital holographic data storage", Optics Letters, Apr. 1, 1999, vol. 24, No. 7, pp. 487-489. cited by applicant

Domash et al., "Applications of switchable Polaroid holograms", SPIE Proceedings, vol. 2152, Diffractive and Holographic Optics Technology, Jan. 23-29, 1994, Los Angeles, CA, pp. 127-138, ISBN: 0-8194-1447-6. cited by applicant

Doolittle, "Studies in Newtonian Flow. II. The Dependence of the Viscosity of Liquids on Free-Space", Journal of Applied Physics, 1951, vol. 22, Issue 12, pp. 1471-1475, published online Apr. 29, 2004, <https://doi.org/10.1063/1.1699894>. cited by applicant

Drake et al., "Waveguide Hologram Fingerprint Entry Device", Optical Engineering, Sep. 1996, vol. 35, No. 9, pp. 2499-2505. cited by applicant

Drevensek-Olenik et al., "In-Plane Switching of Holographic Polymer-Dispersed Liquid Crystal Transmission Gratings", Mol. Cryst. Liq. Cryst., 2008, vol. 495, pp. 177/[529]-185/[537], DOI: 10.1080/15421400802432584. cited by applicant

Drevensek-Olenik et al., "Optical diffraction gratings from polymer-dispersed liquid crystals switched by interdigitated electrodes", Journal of Applied Physics, Dec. 1, 2004, vol. 96, No. 11, pp. 6207-6212, DOI: 10.1063/1.1807027. cited by applicant

Ducharme, "Microlens diffusers for efficient laser speckle generation", Optics Express, Oct. 29, 2007, vol. 15, No. 22, pp. 14573-14579. cited by applicant

Duong et al., "Centrifugal Deposition of Iron Oxide Magnetic Nanorods for Hyperthermia Application", Journal of Thermal Engineering, Yildiz Technical University Press, Istanbul, Turkey, Apr. 2015, vol. 1, No. 2, pp. 99-103. cited by applicant

Escuti et al., "Holographic photonic crystals", Society of Photo-Optical Instrumentation Engineers, Sep. 2004, vol. 43, No. 9, pp. 1973-1987, DOI: 10.1117/1.1773773. cited by applicant

Fattal et al., "A multi directional backlight for a wide-angle glasses-free three-dimensional display", Nature, Mar. 21, 2012, vol. 495, pp. 348-351. cited by applicant

Flory, "Molecular size distribution in three-dimensional polymers. I. Gelation", J. Am. Chem. Soc., Nov. 1941, vol. 63, pp. 3083-3090. cited by applicant

Fontecchio et al., "Spatially Pixelated Reflective Arrays from Holographic Polymer Dispersed Liquid Crystals", SID 00 Digest, May 2000, pp. 774-776. cited by applicant

Forman et al., "Materials development for PhotoINhibited SuperResolution (PINSR) lithography", Proc. of SPIE, 2012, vol. 8249, pp. 824904-1-824904-9, doi: 10.1117/12.908512. cited by applicant

Forman et al., "Radical diffusion limits to photoinhibited superresolution lithography", Phys. Chem. Chem. Phys., May 31, 2013, vol. 15, pp. 14862-14867, DOI: 10.1039/c3cp51512. cited by applicant

Friedrich-Schiller, "Spatial Noise and Speckle", Version 1.12.2011, Dec. 2011, Abbe School of Photonics, Jena, Germany, 27 pgs. cited by applicant

Fries et al., "Real-time beam shaping without additional optical elements", Light Science & Applications, Jun. 20, 2018, vol. 7, No. 18, doi: 10.1038/s41377-018-0014-0. cited by applicant

Fuh et al., "Thermally and Electrically Switchable Gratings Based Upon the Polymer-Balls Type Polymer-Dispersed Liquid Crystal Films", Appl. Phys. vol. 41, No. 22, Aug. 1, 2002, pp. 4585-4589. cited by applicant

Fujii et al., "Nanoparticle-polymer-composite volume gratings incorporating chain-transfer agents for holography and slow-neutron optics", Optics Letters, Apr. 25, 2014, vol. 39, Issue 12, 5 pgs. cited by applicant

Funayama et al., "Proposal of a new type thin film light-waveguide display device using", The International Conference on Electrical Engineering, 2008, No. P-044, 5 pgs. cited by applicant

Gabor, "Laser Speckle and its Elimination", BM Research and Development, Eliminating Speckle Noise, Sep. 1970, vol. 14, No. 5, pp. 509-514. cited by applicant

Gardiner et al., "Bistable liquid-crystals reduce power consumption for high-efficiency smart glazing", SPIE, 2009, 10.1117/2.1200904.1596, 2 pgs. cited by applicant

Gerritsen et al., "Application of Kogelnik's two-wave theory to deep, slanted, highly efficient, relief transmission gratings", Applied Optics, Mar. 1, 1991, vol. 30; No. 7, pp. 807-814. cited by applicant

Giancola, "Holographic Diffuser, Makes Light Work of Screen Tests", Photonics Spectra, 1996, vol. 30, No. 8, pp. 121-122. cited by applicant

Golub et al., "Bragg properties of efficient surface relief gratings in the resonance domain", Optics Communications, Feb. 24, 2004, vol. 235, pp. 261-267, doi: 10.1016/j.optcom.2004.02.069. cited by applicant

Goodman, "Introduction to Fourier Optics", Second Edition, Jan. 1996, 457 pgs. cited by applicant

Goodman, "Some fundamental properties of speckle", J. Opt. Soc. Am., Nov. 1976, vol. 66, No. 11, pp. 1145-1150. cited by applicant

Goodman, "Statistical Properties of Laser Speckle Patterns", Applied Physics, 1975, vol. 9, Chapter 2, Laser Speckle and Related Phenomena, pp. 9-75. cited by applicant

Goodman et al., "Speckle Reduction by a Moving Diffuser in Laser Projection Displays", The Optical Society of America, 2000, 15 pgs. cited by applicant

Guldin et al., "Self-Cleaning Antireflective Optical Coatings", Nano Letters, Oct. 14, 2013, vol. 13, pp. 5329-5335. cited by applicant

Guo et al., "Analysis of the effects of viscosity, volume, and temperature in photopolymer material for holographic applications", Proc. SPIE, May 2013, vol. 8776, pp. 87760J-1-87760-J15, DOI:10.1117/12.2018330. cited by applicant

Guo et al., "Review Article: A Review of the Optimisation of Photopolymer Materials for Holographic Data Storage", Physics Research International, vol. 2012, Article ID 803439, Academic Editor: Sergi Gallego, 16 pages, <http://dx.doi.org/10.1155/2012/803439>, May 4, 2012. cited by applicant

Han et al., "Study of Holographic Waveguide Display System", Advanced Photonics for

Communications, 2014, 4 pgs. cited by applicant

Harbers et al., "I-15.3: LED Backlighting for LCD-HDTV", Journal of the Society for Information Display, 2002, vol. 10, No. 4, pp. 347-350. cited by applicant

Harbers et al., "Performance of High Power LED Illuminators in Color Sequential Projection Displays", Lumileds Lighting, 2007, 4 pgs. cited by applicant

Harbers et al., "Performance of High Power LED Illuminators in Color Sequential Projection Displays", Lumileds, Aug. 7, 2001, 11 pgs. cited by applicant

Harbers et al., "Performance of High-Power LED illuminators in Projection Displays", Proc. Int. Disp. Workshops, Japan. vol. 10, 2003, pp. 1585-1588. cited by applicant

Harding et al., "Reactive Liquid Crystal Materials for Optically Anisotropic Patterned Retarders", Merck, licrivue, 2008, ME-GR-RH-08-010, 20 pgs. cited by applicant

Harding et al., "Reactive Liquid Crystal Materials for Optically Anisotropic Patterned Retarders", SPIE Lithography Asia-Taiwan, 2008, Proceedings vol. 7140, Lithography Asia 2008; 71402J, doi: 10.1117/12.805378. cited by applicant

Hariharan, "Optical Holography: Principles, techniques and applications", Cambridge University Press, 1996, pp. 231-233. cited by applicant

Harris, "Photonic Devices", EE 216 Principals and Models of Semiconductor Devices, Autumn 2002, 20 pgs. cited by applicant

Harrold et al., "3D Display Systems Hardware Research at Sharp Laboratories of Europe: an update", Sharp Laboratories of Europe, Ltd., 7 pgs. cited by applicant

Harthong et al., "Speckle phase averaging in high-resolution color holography", J. Opt. Soc. Am. A, vol. 14, No. 2, Feb. 1997, pp. 405-409. cited by applicant

Hasan et al., "Tunable-focus lens for adaptive eyeglasses", Optics Express, Jan. 23, 2017, vol. 25, No. 2, 1221, 13 pgs. cited by applicant

Hasman et al., "Diffractive Optics: Design, Realization, and Applications", Fiber and Integrated Optics, vol. 16, 1997, pp. 1-25. cited by applicant

Hata et al., "Holographic nanoparticle-polymer composites based on step-growth thiol-ene photopolymerization", Optical Materials Express, vol. 1, No. 2, Jun. 1, 2011, pp. 207-222. cited by applicant

He et al., "Dynamics of peristrophic multiplexing in holographic polymer-dispersed liquid crystal", Liquid Crystals, Mar. 26, 2014, vol. 41, No. 5, pp. 673-684. cited by applicant

He et al., "Holographic 3D display based on polymer-dispersed liquid-crystal thin films", Proceedings of China Display/Asia Display 2011, pp. 158-160. cited by applicant

He et al., "Properties of Volume Holograms Recording in Photopolymer Films with Various Pulse Exposures Repetition Frequencies", Proceedings of SPIE vol. 5636, Bellingham, WA, 2005, pp. 842-848, doi: 10.1117/12.580978. cited by applicant

He et al., "Transmission Holographic Gratings Using Siloxane Containing Liquid Crystalline Compounds, Importance of Chemical Structure of Polymer Matrix Components", Polymer Journal, Jun. 9, 2006, vol. 38, No. 7, pp. 678-685. cited by applicant

Herman et al., "Production and Uses of Diffractionless Beams", J. Opt. Soc. Am. A., Jun. 1991, vol. 8, No. 6, pp. 932-942. cited by applicant

Hisano, "Alignment layer-free molecular ordering induced by masked photopolymerization with nonpolarized light", Appl. Phys. Express 9, Jun. 6, 2016, pp. 072601-1-072601-4. cited by applicant

Hoepfner et al., "LED Front Projection Goes Mainstream", Luminus Devices, Inc., Projection Summit, 2008, 18 pgs. cited by applicant

Holmes et al., "Controlling the Anisotropy of Holographic Polymer-Dispersed Liquid-Crystal Gratings", Physical Review E, Jun. 11, 2002, vol. 65, pp. 066603-1-066603-4. cited by applicant

Hoyle et al., "Advances in the Polymerization of Thiol-Ene Formulations", Heraeus Noblelight Fusion UV Inc., 2003 Conference, 6 pgs. cited by applicant

Hua, "Sunglass-like displays become a reality with free-form optical technology", Illumination & Displays 3D Visualization and Imaging Systems Laboratory (3DVIS) College of Optical Sciences University of Arizona Tucson, AZ. 2014, 3 pgs. cited by applicant

Huang et al., "Diffraction properties of substrate guided-wave holograms", Optical Engineering, Oct. 1995, vol. 34, No. 10, pp. 2891-2899. cited by applicant

Huang et al., "Theory and characteristics of holographic polymer dispersed liquid crystal transmission grating with scaffolding morphology", Applied Optics, Jun. 20, 2012, vol. 51, No. 18, pp. 4013-4020. cited by applicant

Iannacchione et al., "Deuterium NMR and morphology study of copolymer-dispersed liquid-crystal Bragg gratings", Europhysics Letters, 1996, vol. 36, No. 6, pp. 425-430. cited by applicant

Irie, "Photochromic diarylethenes for photonic devices", Pure and Applied Chemistry, 1996, pp. 1367-1371, vol. 68, No. 7, IUPAC. cited by applicant

Jang et al., "Low Driving Voltage Holographic Polymer Dispersed Liquid Crystals with Chemically Incorporated Graphene Oxide", Journal of Materials Chemistry, 2011, vol. 21, pp. 19226-19232, doi.10.1039/1jm13827h. cited by applicant

Jeng et al., "Aligning liquid crystal molecules", SPIE, 2012, 10.1117/2.1201203.004148, 2 pgs. cited by applicant

Jeong et al., "Memory Effect of Polymer Dispersed Liquid Crystal by Hybridization with Nanoclay", express Polymer Letters, vol. 4, No. 1, 2010, pp. 39-46, DOI: 10.3144/expresspolymlett.2010.7. cited by applicant

Jo et al., "Control of Liquid Crystal Pretilt Angle using Polymerization of Reactive Mesogen", IMID 2009 Digest, P1-25, 2009, pp. 604-606. cited by applicant

Juhl, "Interference Lithography for Optical Devices and Coatings", Dissertation, University of Illinois at Urbana-Champaign, 2010. cited by applicant

Juhl et al., "Holographically Directed Assembly of Polymer Nanocomposites", ACS Nano, Oct. 7, 2010, vol. 4, No. 10, pp. 5953-5961. cited by applicant

Jurbergs et al., "New recording materials for the holographic industry", Proc. of SPIE, 2009 vol. 7233, pp. 72330K-1-72330L-10, doi: 10.1117/12.809579. cited by applicant

Kahn et al., "Private Line Report on Large Area Display", Kahn International, Jan. 7, 2003, vol. 8, No. 10, 9 pgs. cited by applicant

Kakiuchida et al., "Multiple Bragg Diffractions with Different Wavelengths and Polarizations Composed of Liquid Crystal/Polymer Periodic Phases", ACS Omega, Sep. 22, 2017, pp. 6081-6090, doi: 10.1021/acsomega.7b01149. cited by applicant

Karasawa et al., "Effects of Material Systems on the Polarization Behavior of Holographic Polymer Dispersed Liquid Crystal Gratings", Japanese Journal of Applied Physics, Oct. 1997, vol. 36, No. 10, pp. 6388-6392. cited by applicant

Karp et al., "Planar micro-optic solar concentration using multiple imaging lenses into a common slab waveguide", Proc. of SPIE vol. 7407, 2009 SPIE, pp. 74070D-1-74070D-11, CCC code: 0277-786X/09, doi: 10.1117/12.826531. cited by applicant

Karp et al., "Planar micro-optic solar concentrator", Optics Express, Jan. 18, 2010, vol. 18, No. 2, pp. 1122-1133. cited by applicant

Kato et al., "Alignment-Controlled Holographic Polymer Dispersed Liquid Crystal (HPDLC) for Reflective Display Devices", SPIE, 1998, vol. 3297, pp. 52-57. cited by applicant

Kessler, "Optics of Near to Eye Displays (NEDs)", Oasis 2013, Tel Aviv, Feb. 19, 2013, 37 pgs. cited by applicant

Keuper et al., "26.1: RGB LED Illuminator for Pocket-Sized Projectors", SID 04 Digest, 2004, ISSN/0004-0966X/04/3502, pp. 943-945. cited by applicant

Keuper et al., "P-126: Ultra-Compact LED based Image Projector for Portable Applications", SID 03 Digest, 2003, ISSN/0003-0966X/03/3401-0713, pp. 713-715. cited by applicant

Kim et al., "Effect of Polymer Structure on the Morphology and Electro optic Properties of UV

Curable PNLCS", Polymer, Feb. 2000, vol. 41, pp. 1325-1335. cited by applicant

Kim et al., "Enhancement of electro-optical properties in holographic polymer-dispersed liquid crystal films by incorporation of multiwalled carbon nanotubes into a polyurethane acrylate matrix", Polym. Int., Jun. 16, 2010, vol. 59, pp. 1289-1295. cited by applicant

Kim et al., "Fabrication of Reflective Holographic PDLC for Blue", Molecular Crystals and Liquid Crystals Science, 2001, vol. 368, pp. 3845-3853. cited by applicant

Kim et al., "Optimization of Holographic PDLC for Green", Mol. Cryst. Liq. Cryst., vol. 368, 2001, pp. 3855-3864. cited by applicant

Klein, "Optical Efficiency for Different Liquid Crystal Colour Displays", Digital Media Department, HPL-2000-83, Jun. 29, 2000, 18 pgs. cited by applicant

Kogelnik, "Coupled Wave Theory for Thick Hologram Gratings", The Bell System Technical Journal, vol. 48, No. 9, Nov. 1969, pp. 2909-2945. cited by applicant

Kotakonda et al., "Electro-optical Switching of the Holographic Polymer-dispersed Liquid Crystal Diffraction Gratings", Journal of Optics A: Pure and Applied Optics, Jan. 1, 2009, vol. 11, No. 2, 11 pgs. cited by applicant

Kress et al., "Diffractive and Holographic Optics as Optical Combiners in Head Mounted Displays", UbiComp '13, Sep. 9-12, 2013, Session: Wearable Systems for Industrial Augmented Reality Applications, pp. 1479-1482. cited by applicant

Kwon et al., "Polymer waveguide notch filter using two stacked thermooptic long-period gratings", IEEE Photonics Technology Letters, Apr. 4, 2005, vol. 17, Issue 4, pp. 792-794, DOI: 10.1109/LPT.2005.844008. cited by applicant

Lauret et al., "Solving the Optics Equation for Effective LED Applications", Gaggione North America, LLFY System Design Workshop 2010, Oct. 28, 2010, 26 pgs. cited by applicant

Lee, "Patents Shows Widespread Augmented Reality Innovation", PatentVue, May 26, 2015, 5 pgs. cited by applicant

Levin et al., "A Closed Form Solution to Natural Image Matting", Illumination & Displays 3D Visualization and Imaging Systems Laboratory (3DVIS) College of Optical Sciences University of Arizona Tucson, 2014, 8 pgs. cited by applicant

Levola, "Diffractive optics for virtual reality displays", Journal of the SID, 2006, 14/5, pp. 467-475. cited by applicant

Levola et al., "Near-to-eye display with diffractive exit pupil expander having chevron design", Journal of the SID, 2008, 16/8, pp. 857-862. cited by applicant

Levola et al., "Replicated slanted gratings with a high refractive index material for in and outcoupling of light", Optics Express, vol. 15, Issue 5, 2007, pp. 2067-2074. cited by applicant

Li et al., "A low cost, label-free biosensor based on a novel double-sided grating waveguide coupler with sub-surface cavities", Sensors and Actuators B: Chemical, Jan. 2015, vol. 206, pp. 371-380, <https://doi.org/10.1016/j.snb.2014.09.065>. cited by applicant

Li et al., "Design and Optimization of Tapered Light Pipes", Proceedings vol. 5529, Nonimaging Optics and Efficient Illumination Systems, Sep. 29, 2004, doi: 10.1117/12.559844, 10 pgs. cited by applicant

Li et al., "Dual Paraboloid Reflector and Polarization Recycling Systems for Projection Display", Proceedings vol. 5002, Projection Displays IX, Mar. 28, 2003, doi: 10.1117/12.479585, 12 pgs. cited by applicant

Li et al., "Light Pipe Based Optical Train and its Applications", Proceedings vol. 5524, Novel Optical Systems Design and Optimization VII, Oct. 24, 2004, doi: 10.1117/12.559833, 10 pgs. cited by applicant

Li et al., "Novel Projection Engine with Dual Paraboloid Reflector and Polarization Recovery Systems", Wavien Inc., SPIE EI 5289-38, Jan. 21, 2004, 49 pgs. cited by applicant

Li et al., "Polymer crystallization/melting induced thermal switching in a series of holographically patterned Bragg reflectors", Soft Matter, Jul. 11, 2005, vol. 1, pp. 238-242. cited by applicant

Lin et al., “Ionic Liquids in Photopolymerizable Holographic Materials”, in book: Holograms—Recording Materials and Applications, Nov. 9, 2011, 21 pgs. cited by applicant

Liu et al., “Effect of Surfactant on the Electro-Optical Properties of Holographic Polymer Dispersed Liquid Crystal Bragg Gratings”, *Optical Materials*, 2005, vol. 27, pp. 1451-1455, available online Dec. 25, 2004, doi: 10.1016/j.optmat.2004.10.010. cited by applicant

Liu et al., “Holographic Polymer Dispersed Liquid Crystals” *Materials, Formation and Applications*, *Advances in OptoElectronics*, Nov. 30, 2008, vol. 2008, Article ID 684349, 52 pgs. cited by applicant

Liu et al., “Realization and Optimization of Holographic Waveguide Display System”, *Acta Optica Sinica*, vol. 37, Issue 5, Issuing date—May 10, 2017, pp. 310-317. cited by applicant

Lorek, “Experts Say Mass Adoption of augmented and Virtual Reality is Many Years Away”, *Siliconhills*, Sep. 9, 2017, 4 pgs. cited by applicant

Loungnot et al., “Polymers for holographic recording: VI. Some basic ideas for modelling the kinetics of the recording process”, *Pure and Applied Optics: Journal of the European Optical Society Part A*, 1997, vol. 6, No. 2, pp. 225-245, <https://doi.org/10.1088/0963-9659/6/2/007>. cited by applicant

Lowenthal et al., “Speckle Removal by a Slowly Moving Diffuser Associated with a Motionless Diffuser”, *Journal of the Optical Society of America*, Jul. 1971, vol. 61, No. 7, pp. 847-851. cited by applicant

Lu et al., “Polarization switch using thick holographic polymer-dispersed liquid crystal grating”, *Journal of Applied Physics*, vol. 95, No. 3, Feb. 1, 2004, pp. 810-815. cited by applicant

Lu et al., “The Mechanism of electric-field-induced segregation of additives in a liquid-crystal host”, *Phys Rev E Stat Nonlin Soft Matter Phys.*, Nov. 27, 2012, 14 pgs. cited by applicant

Ma et al., “Holographic Reversed-Mode Polymer-Stabilized Liquid Crystal Grating”, *Chinese Phys. Lett.*, 2005, vol. 22, No. 1, pp. 103-106. cited by applicant

Mach et al., “Switchable Bragg diffraction from liquid crystal in colloid-templated structures”, *Europhysics Letters*, Jun. 1, 2002, vol. 58, No. 5, pp. 679-685. cited by applicant

Magarinos et al., “Wide Angle Color Holographic infinity optics display”, *Air Force Systems Command*, Brooks Air Force Base, Texas, AFHRL-TR-80-53, Mar. 1981, 100 pgs. cited by applicant

Marino et al., “Dynamical Behaviour of Polycrystalline Gratings”, *Electronic-Liquid Crystal Communications*, Feb. 5, 2004, 10 pgs. cited by applicant

Massenot et al., “Multiplexed holographic transmission gratings recorded in holographic polymer-dispersed liquid crystals: static and dynamic studies”, *Applied Optics*, 2005, vol. 44, Issue 25, pp. 5273-5280. cited by applicant

Matay et al., “Planarization of Microelectronic Structures by Using Polyimides”, *Journal of Electrical Engineering*, 2002, vol. 53, No. 3-4, pp. 86-90. cited by applicant

Mathews, “The LED FAQ Pages”, Jan. 31, 2002, 23 pgs. cited by applicant

Matic, “Blazed phase liquid crystal beam steering”, *Proc. of the SPIE*, 1994, vol. 2120, pp. 194-205. cited by applicant

McLeod, “Axicons and Their Uses”, *Journal of the Optical Society of America*, Feb. 1960, vol. 50, No. 2, pp. 166-169. cited by applicant

Mcmanamon et al., “A Review of Phased Array Steering for Narrow-Band Electrooptical Systems”, *Proceedings of the IEEE*, Jun. 2009, vol. 97, No. 6, pp. 1078-1096. cited by applicant

Mcmanamon et al., “Optical Phased Array Technology”, *Proceedings of the IEEE*, Feb. 1996, vol. 84, Issue 2, pp. 268-298. cited by applicant

Miller, “Coupled Wave Theory and Waveguide Applications”, *The Bell System Technical Journal*, Short Hills, NJ, Feb. 2, 1954, 166 pgs. cited by applicant

Missinne et al., “Flexible thin polymer waveguide Bragg grating sensor foils for strain sensing”, *Proc. SPIE*, 10101, *Organic Photonic Materials and Devices*, Feb. 16, 2017,

<https://doi.org/10.1117/12.2250823>. cited by applicant

Moffitt, “Head-Mounted Display Image Configurations”, retrieved from the internet on Dec. 19, 2014, dated May 2008, 25 pgs. cited by applicant

Moharam et al., “Diffraction characteristics of photoresist surface-relief gratings”, *Applied Optics*, Sep. 15, 1984, vol. 23, pp. 3214-3220. cited by applicant

Nair et al., “Enhanced Two-Stage Reactive Polymer Network Forming Systems”, *Polymer (Guildf)*. May 25, 2012, vol. 53, No. 12, pp. 2429-2434, doi:10.1016/j.polymer.2012.04.007. cited by applicant

Nair et al., “Two-Stage Reactive Polymer Network Forming Systems”, *Advanced Functional Materials*, 2012, pp. 1-9, DOI: 10.1002/adfm.201102742. cited by applicant

Naqvi et al., “Concentration-dependent toxicity of iron oxide nanoparticles mediated by increased oxidative stress”, *International Journal of Nanomedicine*, Dovepress, Nov. 13, 2010, vol. 5, pp. 983-989. cited by applicant

Natarajan et al., “Electro Optical Switching Characteristics of Volume Holograms in Polymer Dispersed Liquid Crystals”, *Journal of Nonlinear Optical Physics and Materials*, 1997, vol. 5, No. 1, pp. 666-668. cited by applicant

Natarajan et al., “Electro-Optical Switching Characteristics of Volume Holograms in Polymer Dispersed Liquid Crystals”, *Journal of Nonlinear Optical Physics and Materials*, Jan. 1996, vol. 5, No. 1, pp. 89-98. cited by applicant

Natarajan et al., “Holographic polymer dispersed liquid crystal reflection gratings formed by visible light initiated thiol-ene photopolymerization”, *Polymer*, vol. 47, May 8, 2006, pp. 4411-4420. cited by applicant

Naydenova et al., “Low-scattering Volume Holographic Material”, DIT PhD Project, <http://www.dit.ie/ieo/>, Oct. 2017, 2 pgs. cited by applicant

Neipp et al., “Non-local polymerization driven diffusion based model: general dependence of the polymerization rate to the exposure intensity”, *Optics Express*, Aug. 11, 2003, vol. 11, No. 16, pp. 1876-1886. cited by applicant

Nielsen et al., “Grating Couplers for Fiber-to-Fiber Characterizations of Stand-Alone Dielectric Loaded Surface Plasmon Waveguide Components”, *Journal of Lightwave Technology*, Oct. 1, 2012, vol. 30, No. 19, pp. 3118-3125, DOI: 10.1109/JLT.2012.2212418. cited by applicant

Nishikawa et al., “Mechanically and Light Induced Anchoring of Liquid Crystal on Polyimide Film”, *Mol. Cryst. Liq. Cryst.*, Aug. 1999, vol. 329, 8 pgs. cited by applicant

Nishikawa et al., “Mechanism of Unidirectional Liquid-Crystal Alignment on Polyimides with Linearly Polarized Ultraviolet Light Exposure”, *Applied Physics Letters*, May 11, 1998, vol. 72, No. 19, 4 pgs. cited by applicant

Nordin et al., “Diffraction Properties of Stratified Volume Holographic Optical Elements”, *Journal of the Optical Society of America A*. Dec. 1992, vol. 9, No. 12, pp. 2206-2217. cited by applicant

Ogiwara et al., “Temperature Dependence of Anisotropic Diffraction in Holographic Polymer-Dispersed Liquid Crystal Memory”, *Applied Optics*, Sep. 10, 2013, vol. 52, No. 26, pp. 6529-6536. cited by applicant

Ogiwara et al., “Thermo-Driven Light Controller by Using Thermal Modulation of Diffraction Wavelength in Holographic Polymer Dispersed Liquid Crystal Grating”, *Proc. SPIE*, Feb. 19, 2014, 9004, Article 90040Q, 8 pgs., doi: 10.1117/12.2039104. cited by applicant

Oh et al., “Achromatic diffraction from polarization gratings with high efficiency”, *Optic Letters*, Oct. 15, 2008, vol. 33, No. 20, pp. 2287-2289. cited by applicant

Olson et al., “Templating Nanoporous Polymers with Ordered Block Copolymers”, *Chemistry of Materials*, Web publication Nov. 27, 2007, vol. 20, pp. 869-890. cited by applicant

Ondax, Inc., “Volume Holographic Gratings (VHG)”, 2005, 7 pgs. cited by applicant

Orcutt, “Coming Soon: Smart Glasses That Look Like Regular Spectacles”, *Intelligent Machines*, Jan. 9, 2014, 4 pgs. cited by applicant

Osredkar, "A study of the limits of spin-on-glass planarization process", Informacije MITEM, 2001, vol. 31, 2, ISSN0352-9045, pp. 102-105. cited by applicant

Osredkar et al., "Planarization methods in IC fabrication technologies", Informacije MITEM, 2002, vol. 32, 3, ISSN0352-9045, 5 pgs. cited by applicant

Ou et al., "A Simple LCOS Optical System (Late News)", Industrial Technology Research Institute/OES Lab. Q100/Q200, SID 2002, Boston, USA, 2 pgs. cited by applicant

Paolini et al., "High-Power LED Illuminators in Projection Displays", Lumileds, Aug. 7, 2001, 19 pgs. cited by applicant

Park et al., "Aligned Single-Wall Carbon Nanotube Polymer Composites Using an Electric Field", Journal of Polymer Science: Part B: Polymer Physics, Mar. 24, 2006, DOI 10.1002/polb.20823, pp. 1751-1762. cited by applicant

Park et al., "Fabrication of Reflective Holographic Gratings with Polyurethane Acrylates (PUA)", Current Applied Physics, Jun. 2002, vol. 2, pp. 249-252. cited by applicant

Peng et al., "Low Voltage Driven and Highly Diffractive Holographic Polymer Dispersed Liquid Crystals with Spherical Morphology", RSC Advances, 2017, vol. 7, pp. 51847-51857, doi: 10.1039/c7ra08949. cited by applicant

Pierantoni et al., "Efficient modeling of 3-D photonic crystals for integrated optical devices", IEEE Photonics Technology Letters, Feb. 2006, vol. 18, No. 2, pp. 319-321, DOI: 10.1109/LPT.2005.861991. cited by applicant

Plawsky et al., "Engineered nanoporous and nanostructured films", MaterialsToday, Jun. 2009, vol. 12, No. 6, pp. 36-45. cited by applicant

Pogue et al., "Electrically Switchable Bragg Gratings from Liquid Crystal/Polymer Composites", Applied Spectroscopy, 2000, vol. 54, Issue 1, pp. 12A-28A. cited by applicant

Potenza, "These smart glasses automatically focus on what you're looking at", The Verge, Voc Media, Inc., Jan. 29, 2017, <https://www.theverge.com/2017/1/29/14403924/smart-glasses-automatic-focus-presbyopia-ces-2017>, 6 pgs. cited by applicant

Presnyakov et al., "Electrically tunable polymer stabilized liquid-crystal lens", Journal of Applied Physics, Apr. 29, 2005, vol. 97, pp. 103101-1-103101-6. cited by applicant

Prokop et al., "Air-Suspended SU-8 Polymer Waveguide Grating Couplers", Journal of Lightwave Technology, Sep. 1, 2016, vol. 34, No. 17, pp. 3966-3971, DOI: 10.1109/JLT.2016.2593025. cited by applicant

Qi et al., "P-111: Reflective Display Based on Total Internal Reflection and Grating-Grating Coupling", Society for Information Display Digest, May 2003, pp. 648-651, DOI: 10.1889/1.1832359. cited by applicant

RAMÓN, "Formation of 3D micro- and nanostructures using liquid crystals as a template", Technische Universiteit Eindhoven, Apr. 17, 2008, Thesis, 117 pgs., DOI:<http://dx.doi.org/10.6100/IR634422>. cited by applicant

Ramsey, "Holographic Patterning of Polymer Dispersed Liquid Crystal Materials for Diffractive Optical Elements", Thesis, The University of Texas at Arlington, Dec. 2006, 166 pgs. cited by applicant

Ramsey et al., "Holographically recorded reverse-mode transmission gratings in polymer-dispersed liquid crystal cells", Applied Physics B: Laser and Optics, Sep. 10, 2008, vol. 93, Nos. 2-3, pp. 481-489. cited by applicant

Reid, "Thin film silica nanocomposites for anti-reflection coatings", Oxford Advance Surfaces, www.oxfordsurfaces.com, Oct. 18, 2012, 23 pgs. cited by applicant

Riechert, "Speckle Reduction in Projection Systems", Dissertation, University Karlsruhe, 2009, 178 pgs. cited by applicant

Rossi et al., "Diffractive Optical Elements for Passive Infrared Detectors", Submitted to OSA Topical Meeting "Diffractive Optics and Micro-Optics", Quebec, Jun. 18-22, 2000, 3 pgs. cited by applicant

Roussel et al., "Photopolymerization Kinetics and Phase Behavior of Acrylate Based Polymers Dispersed Liquid Crystals", *Liquid Crystals*, 1998, vol. 24, Issue 4, pp. 555-561. cited by applicant

Sabel et al., "Simultaneous formation of holographic surface relief gratings and volume phase gratings in photosensitive polymer", *Materials Research Letters*, May 30, 2019, vol. 7, No. 10, pp. 405-411, doi: 10.1080/21663831.2019.1621956. cited by applicant

Sagan et al., "Electrically Switchable Bragg Grating Technology for Projection Displays", *Proc. SPIE*. vol. 4294, Jan. 24, 2001, pp. 75-83. cited by applicant

Sakhno et al., "Deep surface relief grating in azobenzene-containing materials using a low-intensity 532 nm laser", *Optical Materials: X*, Jan. 23, 2019, 100006, pp. 3-7, doi: 10.1016/j.omx.2019.100006. cited by applicant

Saleh et al., "Fourier Optics: 4.1 Propagation of light in free space, 4.2 Optical Fourier Transform, 4.3 Diffraction of Light, 4.4 Image Formation, 4.5 Holography", *Fundamentals of Photonics* 1991, Chapter 4, pp. 108-143. cited by applicant

Saraswat, "Deposition & Planarization", *EE 311 Notes*, Aug. 29, 2017, 28 pgs. cited by applicant

Schreiber et al., "Laser display with single-mirror MEMS scanner", *Journal of the SID* 17/7, 2009, pp. 591-595. cited by applicant

Seiberle et al., "Photo-aligned anisotropic optical thin films", *Journal of the SID* 12/1, 2004, 6 pgs. cited by applicant

Serebriakov et al., "Correction of the phase retardation caused by intrinsic birefringence in deep UV lithography", *Proc. of SPIE*, May 21, 2010, vol. 5754, pp. 1780-1791. cited by applicant

Shechter et al., "Compact beam expander with linear gratings", *Applied Optics*, vol. 41, No. 7, Mar. 1, 2002, pp. 1236-1240. cited by applicant

Shi et al., "Design considerations for high efficiency liquid crystal decentered microlens arrays for steering light", *Applied Optics*, vol. 49, No. 3, Jan. 20, 2010, pp. 409-421. cited by applicant

Shriyan et al., "Analysis of effects of oxidized multiwalled carbon nanotubes on electro-optic polymer/liquid crystal thin film gratings", *Optics Express*, Nov. 12, 2010, vol. 18, No. 24, pp. 24842-24852. cited by applicant

Simonite, "How Magic Leap's Augmented Reality Works", *Intelligent Machines*, Oct. 23, 2014, 7 pgs. cited by applicant

Smith et al., "RM-Plus—Overview", *Licrivue*, Nov. 5, 2013, 16 pgs. cited by applicant

Sony Global, "Sony Releases the Transparent Lens Eyewear 'SmartEyeglass Developer Edition'", printed Oct. 19, 2017, Sony Global—News Releases, 5 pgs. cited by applicant

Steranka et al., "High-Power LEDs—Technology Status and Market Applications", *Lumileds*, Jul. 2002, 23 pgs. cited by applicant

Stumpe et al., "Active and Passive LC Based Polarization Elements", *Mol. Cryst. Liq. Cryst.*, 2014, vol. 594: pp. 140-149. cited by applicant

Stumpe et al., "New type of polymer-LC electrically switchable diffractive devices—Poliphem", May 19, 2015, p. 97. cited by applicant

Subbarayappa et al., "Bistable Nematic Liquid Crystal Device", Jul. 30, 2009, 14 pgs. cited by applicant

Sun et al., "Effects of multiwalled carbon nanotube on holographic polymer dispersed liquid crystal", *Polymers Advanced Technologies*, Feb. 19, 2010, DOI: 10.1002/pat.1708, 8 pgs. cited by applicant

Sun et al., "Low-birefringence lens design for polarization sensitive optical systems", *Proceedings of SPIE*, 2006, vol. 6289, pp. 6289DH-1-6289DH-10, doi: 10.1117/12.679416. cited by applicant

Sun et al., "Transflective Multiplexing of Holographic Polymer Dispersed Liquid Crystal Using Si Additives", *eXPRESS Polymer Letters*, 2011, vol. 5, No. 1, pp. 73-81. cited by applicant

Sutherland et al., "Bragg Gratings in an Acrylate Polymer Consisting of Periodic Polymer-Dispersed Liquid-Crystal Planes", *Chem. Mater.*, 1993, vol. 5, pp. 1533-1538. cited by applicant

Sutherland et al., "Electrically switchable volume gratings in polymer-dispersed liquid crystals",

Applied Physics Letters, Feb. 28, 1994, vol. 64, No. 9, pp. 1074-1076. cited by applicant

Sutherland et al., "Enhancing the electro-optical properties of liquid crystal nanodroplets for switchable Bragg gratings", Proc. of SPIE, 2008, vol. 7050, pp. 705003-1-705003-9, doi: 10.1117/12.792629. cited by applicant

Sutherland et al., "Liquid crystal bragg gratings: dynamic optical elements for spatial light modulators", Hardened Materials Branch, Hardened Materials Branch, AFRL-ML-WP-TP-2007-514, Jan. 2007, Wright-Patterson Air Force Base, OH, 18 pgs. cited by applicant

Sutherland et al., "Phenomenological model of anisotropic volume hologram formation in liquid-crystal-photopolymer mixtures", Journal of Applied Physics, Jun. 30, 2004, vol. 96, No. 2, pp. 951-965, <https://doi.org/10.1063/1.1762713>. cited by applicant

Sutherland et al., "The physics of photopolymer liquid crystal composite holographic gratings", presented at SPIE: Diffractive and Holographic Optics Technology San Jose, CA, 1996, SPIE, vol. 2689, pp. 158-169. cited by applicant

Sweatt, "Achromatic triplet using holographic optical elements", Applied Optics, May 1977, vol. 16, No. 5, pp. 1390-1391. cited by applicant

Tahata et al., "Effects of Polymer Matrix on Electro-Optic Properties of Liquid Crystal Mixed With Polymer", Proc SPIE, Mar. 11, 1996, vol. 2651, pp. 101-106, doi: 10.1117/12.235342. cited by applicant

Talukdar, "Technology Forecast: Augmented reality", Changing the economics of Smartglasses, Issue 2, 2016, 5 pgs. cited by applicant

Tao et al., "TiO₂ nanocomposites with high refractive index and transparency", J. Mater. Chem., Oct. 4, 2011, vol. 21, pp. 18623-18629. cited by applicant

Titus et al., "Efficient, Accurate Liquid Crystal Digital Light Deflector", Proc. SPIE 3633, Diffractive and Holographic Technologies, Systems, and Spatial Light Modulators VI, 1 Jun. 1, 1999, doi: 10.1117/12.349334, 10 pgs. cited by applicant

Tiziani, "Physical Properties of Speckles", Speckle Metrology, Chapter 2, Academic Press, Inc., 1978, pp. 5-9. cited by applicant

Tominaga et al., "Fabrication of holographic polymer dispersed liquid crystals doped with gold nanoparticles", 2010 Japanese Liquid Crystal Society Annual Meeting, 2 pgs. cited by applicant

Tomita, "Holographic assembly of nanoparticles in photopolymers for photonic applications", The International Society for Optical Engineering, SPIE Newsroom, 2006, 3 pgs., doi: 10.1117/2.1200612.0475. cited by applicant

Tondiglia et al., "Holographic Formation of Electro-Optical Polymer-Liquid Crystal Photonic Crystals", Advanced Materials, 2002, Published Online Nov. 8, 2001, vol. 14, No. 3, pp. 187-191. cited by applicant

Trisnadi, "Hadamard Speckle Contrast Reduction", Optics Letters, Jan. 1, 2004, vol. 29, No. 1, pp. 11-13. cited by applicant

Trisnadi, "Speckle contrast reduction in laser projection displays", Proc. SPIE 4657, 2002, 7 pgs. cited by applicant

Tzeng et al., "Axially symmetric polarization converters based on photo-aligned liquid crystal films", Optics Express, Mar. 17, 2008, vol. 16, No. 6, pp. 3768-3775. cited by applicant

Upatnieks et al., "Color Holograms for white light reconstruction", Applied Physics Letters, Jun. 1, 1996, vol. 8, No. 11, pp. 286-287. cited by applicant

Urey, "Diffractive exit pupil expander for display applications", Applied Optics, Nov. 10, 2001, vol. 40, Issue 32, pp. 5840-5851. cited by applicant

Ushenko, "The Vector Structure of Laser Biospeckle Fields and Polarization Diagnostics of Collagen Skin Structures", Laser Physics, 2000, vol. 10, No. 5, pp. 1143-1149. cited by applicant

Valoriani, "Mixed Reality: Dalle demo a un prodotto", Disruptive Technologies Conference, Sep. 23, 2016, 67 pgs. cited by applicant

Van Gerwen et al., "Nanoscaled interdigitated electrode arrays for biochemical sensors", Sensors

and Actuators, Mar. 3, 1998, vol. B 49, pp. 73-80. cited by applicant

Vecchi, "Studi Esr Di Sistemi Complessi Basati Su Cristalli Liquidi", Thesis, University of Bologna, Department of Physical and Inorganic Chemistry, 2004-2006, 110 pgs. cited by applicant

Veltri et al., "Model for the photoinduced formation of diffraction gratings in liquid-crystalline composite materials", Applied Physics Letters, May 3, 2004, vol. 84, No. 18, pp. 3492-3494. cited by applicant

Vita, "Switchable Bragg Gratings", Thesis, Universita degli Studi di Napoli Federico II, Nov. 2005, 103 pgs. cited by applicant

Vuzix, "M3000 Smart Glasses, Advanced Waveguide Optics", brochure, Jan. 1, 2017, 2 pgs. cited by applicant

Waldern et al., "Waveguide Optics for All Day Wearable Displays", Jun. 20, 2017, 35 pgs. cited by applicant

Wang et al., "Liquid-crystal blazed-grating beam deflector", Applied Optics, Dec. 10, 2000, vol. 39, No. 35, pp. 6545-6555. cited by applicant

Wang et al., "Optical Design of Waveguide Holographic Binocular Display for Machine Vision", Applied Mechanics and Materials, Sep. 27, 2013, vols. 427-429, pp. 763-769. cited by applicant

Wang et al., "Speckle reduction in laser projection systems by diffractive optical elements", Applied Optics, Apr. 1, 1998, vol. 37, No. 10, pp. 1770-1775. cited by applicant

Weber et al., "Giant Birefringent Optics in Multilayer Polymer Mirrors", Science, Mar. 31, 2000, vol. 287, pp. 2451-2456. cited by applicant

Webster, "Webster's Third New International Dictionary 433", (1986), 3 pages. cited by applicant

Wei An, "Industrial Applications of Speckle Techniques", Doctoral Thesis, Royal Institute of Technology, Department of Production Engineering, Chair of Industrial Metrology & Optics, Stockholm, Sweden 2002, 76 pgs. cited by applicant

Welde et al., "Investigation of methods for speckle contrast reduction", Master of Science in Electronics, Jul. 2010, Norwegian University of Science and Technology, Department of Electronics and Telecommunications, 127 pgs. cited by applicant

White, "Influence of thiol-ene polymer evolution on the formation and performance of holographic polymer dispersed liquid crystals", The 232nd ACS National Meeting, San Francisco, CA, Sep. 10-14, 2006, 1 pg. cited by applicant

Wicht et al., "Nanoporous Films with Low Refractive Index for Large-Surface Broad-Band Anti-Reflection Coatings", Macromol. Mater. Eng., 2010, 295, DOI: 10.1002/mame.201000045, 9 pgs. cited by applicant

Wilderbeek et al., "Photoinitiated Bulk Polymerization of Liquid Crystalline Thiolene Monomers", Macromolecules, 2002, vol. 35, pp. 8962-8969. cited by applicant

Wilderbeek et al., "Photo-Initiated Polymerization of Liquid Crystalline Thiol-Ene Monomers in Isotropic and Anisotropic Solvents", J. Phys. Chem. B, 2002, vol. 106, No. 50, pp. 12874-12883. cited by applicant

Wisely, "Head up and head mounted display performance improvements through advanced techniques in the manipulation of light", Proc. of SPIE, 2009, 10 pages, vol. 7327. cited by applicant

Wofford et al., "Liquid crystal bragg gratings: dynamic optical elements for spatial light modulators", Hardened Materials Branch, Survivability and Sensor Materials Division, AFRL-ML-WP-TP-2007-551, Air Force Research Laboratory, Jan. 2007, Wright-Patterson Air Force Base, OH, 17 pgs. cited by applicant

Yang et al., "Robust and Accurate Surface Measurement Using Structured Light", IEEE, Apr. 30, 2008, vol. 57, Issue 6, pp. 1275-1280, DOI:10.1109/TIM.2007.915103. cited by applicant

Yaqoob et al., "High-speed two-dimensional laser scanner based on Bragg grating stored in photothermorefractive glass", Applied Optics, Sep. 10, 2003, vol. 42, No. 26, pp. 5251-5262. cited by applicant

Yaroshchuk et al., "Stabilization of liquid crystal photoaligning layers by reactive mesogens", Applied Physics Letters, Jul. 14, 2009, vol. 95, pp. 021902-1-021902-3. cited by applicant

Ye, "Three-dimensional Gradient Index Optics Fabricated in Diffusive Photopolymers", Thesis, Department of Electrical, Computer and Energy Engineering, University of Colorado, 2012, 224 pgs. cited by applicant

Yemtsova et al., "Determination of liquid crystal orientation in holographic polymer dispersed liquid crystals by linear and nonlinear optics", Journal of Applied Physics, Oct. 13, 2008, vol. 104, pp. 073115-1-073115-4. cited by applicant

Yeralan et al., "Switchable Bragg grating devices for telecommunications applications", Opt. Eng., Aug. 2012, vol. 41, No. 8, pp. 1774-1779. cited by applicant

Yokomori, "Dielectric surface-relief gratings with high diffraction efficiency", Applied Optics, Jul. 15, 1984, vol. 23; No. 14, pp. 2303-2310. cited by applicant

Yoshida et al., "Nanoparticle-Dispersed Liquid Crystals Fabricated by Sputter Doping", Adv. Mater., 2010, vol. 22, pp. 622-626. cited by applicant

Youcef et al., "Phase Behavior of Poly(N-Butyl Acrylate) and Poly(2-Ethylhexyl Acrylate) in Nematic Liquid Crystal E7", Macromol. Symp. 2011, vol. 303, pp. 10-16, doi: 10.1002/masy.201150502. cited by applicant

Zeller et al., "Laminated Air Structured and Fluid Infiltrated Polymer Waveguides", in IEEE Photonics Technology Letters, Nov. 2, 2011, vol. 23, Issue: 21, pp. 1564-1566, first published Aug. 12, 2011, DOI: 10.1109/LPT.2011.2164396. cited by applicant

Zhang et al., "Dynamic Holographic Gratings Recorded by Photopolymerization of Liquid Crystalline Monomers", J. Am. Chem. Soc., 1994, vol. 116, pp. 7055-7063. cited by applicant

Zhang et al., "Switchable Liquid Crystalline Photopolymer Media for Holography", J. Am. Chem. Soc., 1992, vol. 114, pp. 1506-1507. cited by applicant

Zhao et al., "Designing Nanostructures by Glancing Angle Deposition", Proc. of SPIE, Oct. 27, 2003, vol. 5219, pp. 59-73. cited by applicant

Zhao et al., "Diffusion Model of Hologram Formation in Dry Photopolymer Materials", Journal of Modern Optics, 1994. vol. 41, No. 10, pp. 1929-1939, <https://doi.org/10.1080/09500349414551831>. cited by applicant

Zhao et al., "Extension of a diffusion model for holographic photopolymers", Journal of Modern Optics, 1995, vol. 42, No. 12, pp. 2571-2573, <https://doi.org/10.1080/713824349>. cited by applicant

Zheng et al., "Holographic Polymer-Dispersed Liquid Crystal Grating with Low Scattering Losses", Liquid Crystals, Mar. 2012, vol. 39, Issue 3, pp. 387-391, , <http://dx.doi.org/10.1080/02678292.2012.656716>. cited by applicant

Złebacz, "Dynamics of nano and micro objects in complex liquids", Ph.D. dissertation, Institute of Physical Chemistry of the Polish Academy of Sciences, Warsaw 2011, 133 pgs. cited by applicant

Zou et al., "Functionalized nano interdigitated electrodes arrays on polymer with integrated microfluidics for direct bio-affinity sensing using impedimetric measurement", Sensors and Actuators A, Jan. 16, 2007, vol. 136, pp. 518-526, doi:10.1016/j.sna.2006.12.006. cited by applicant

Zyga, "Liquid crystals controlled by magnetic fields may lead to new optical applications", Nanotechnology, Nanophysics, Retrieved from <http://phys.org/news/2014-07-liquid-crystals-magnetic-fields-optical.html>, Jul. 9, 2014, 3 pgs. cited by applicant

"Compact linear Fresnel reflector", Wikipedia, Sep. 16, 2019, https://en.wikipedia.org/wiki/Compact_linear_Fresnel_reflector. cited by applicant

Extended European Search Report for European Application No. 18897932.2, Search completed Dec. 22, 2021, Mailed Jan. 12, 2022, 8 pgs. cited by applicant

Extended European Search Report for European Application No. 19897355.4, Search completed Jul. 12, 2022, Mailed Jul. 21, 2022, 8 Pgs. cited by applicant

Extended European Search Report for European Application No. 20755316.5, Search completed Nov. 17, 2022, Mailed Nov. 25, 2022, 9 Pgs. cited by applicant
International Preliminary Report on Patentability for International Application No. PCT/GB2016/000005, Report issued Jul. 18, 2017, Mailed Jul. 27, 2017, 7 pgs. cited by applicant
International Preliminary Report on Patentability for International Application No. PCT/GB2016/000051, Report issued Sep. 19, 2017, Mailed Sep. 28, 2017, 7 Pgs. cited by applicant
International Preliminary Report on Patentability for International Application No. PCT/IB2008/001909, Report issued Jan. 26, 2010, Mailed Jan. 26, 2010, 5 pgs. cited by applicant
International Preliminary Report on Patentability for International Application No. PCT/US2018/037410, Report issued Jul. 14, 2020, Mailed Jul. 23, 2020, 7 pgs. cited by applicant
International Preliminary Report on Patentability for International Application No. PCT/US2018/048636, Report issued Jul. 14, 2020, Mailed Jul. 23, 2020, 9 pgs. cited by applicant
International Preliminary Report on Patentability for International Application No. PCT/US2018/062835, Report issued Jul. 14, 2020, Mailed Jul. 23, 2020, 7 pgs. cited by applicant
International Preliminary Report on Patentability for International Application PCT/GB2013/000210, issued Nov. 11, 2014, Mailed Nov. 20, 2014, 6 pgs. cited by applicant
International Preliminary Report on Patentability for International Application PCT/GB2014/000197, issued Nov. 24, 2015, mailed Dec. 3, 2015, 7 pgs. cited by applicant
International Preliminary Report on Patentability for International Application PCT/GB2016/000003, issued Jul. 18, 2017, mailed Jul. 27, 2017, 11 pgs. cited by applicant
International Preliminary Report on Patentability for International Application PCT/GB2017/000015, Report Completed Aug. 7, 2018, Mailed Aug. 16, 2018, 7 pgs. cited by applicant
International Preliminary Report on Patentability for International Application PCT/US2018/048960, Report issued on Mar. 3, 2020, Mailed on Mar. 12, 2020, 7 pgs. cited by applicant
International Preliminary Report on Patentability for International Application PCT/US2018/056150, Report Issued on Apr. 21, 2020, Mailed on Apr. 30, 2020, 6 pgs. cited by applicant
International Preliminary Report on Patentability for International Application PCT/US2019/031163, Report issued Nov. 10, 2020, Mailed Nov. 19, 2020, 6 pgs. cited by applicant
International Preliminary Report on Patentability for International Application PCT/US2019/064765, Report issued Oct. 19, 2020, Mailed Oct. 28, 2020, 27 pgs. cited by applicant
International Preliminary Report on Patentability for International Application PCT/US2020/018686, Report issued Aug. 10, 2021, Mailed Aug. 26, 2021, 6 pgs. cited by applicant
International Preliminary Report on Patentability for International Application PCT/US2020/036654, Report issued Dec. 7, 2021, Mailed Dec. 16, 2021, 9 pgs. cited by applicant
International Preliminary Report on Patentability for International Application PCT/US2020/043107, Report issued Jan. 25, 2022, Mailed on Feb. 3, 2022, 6 pgs. cited by applicant
International Preliminary Report on Patentability for International Application PCT/US2020/044060, Report issued Feb. 1, 2022, Mailed on Feb. 10, 2022, 7 pgs. cited by applicant
International Preliminary Report on Patentability for International Application PCT/US2020/048590, Report issued Mar. 1, 2022, Mailed on Mar. 10, 2022, 12 pgs. cited by applicant
International Preliminary Report on Patentability for International Application

PCT/US2020/067737, Report issued Jul. 5, 2022, Mailed Jul. 14, 2022, 6 pgs. cited by applicant
International Search Report and Written Opinion for International Application No.
PCT/US2020/044060, Search completed Oct. 9, 2020, Mailed Nov. 9, 2020, 12 pgs. cited by applicant
International Search Report and Written Opinion for International Application No.
PCT/US2021/038542, search Completed Sep. 21, 2021, Mailed Oct. 20, 2021 16 pgs. cited by applicant
International Search Report and Written Opinion for International Application No.
PCT/US2021/072548, Search completed Jan. 25, 2022, Mailed Feb. 8, 2022, 15 pgs. cited by applicant
International Search Report and Written Opinion for International Application No.
PCT/US2022/070095, Search completed Mar. 10, 2022, Mailed Mar. 22, 2022, 13 pgs. cited by applicant
International Search Report and Written Opinion for International Application
PCT/US2020/016875, Report Completed Apr. 9, 2020, Mailed Apr. 29, 2020, 11 pgs. cited by applicant
Gaylord et al., "Thin and thick gratings: terminology clarification", Applied Optics, Oct. 1, 1981, vol. 20, pp. 3271-3273. cited by applicant
Konuray et al., "State of the Art in Dual-Curing Acrylate Systems", Polymers, Feb. 12, 2018, vol. 10, No. 178, 24 pgs. doi: 10.3390/polym10020178. cited by applicant
Matsushima et al., "Thiol-Isocyanate-Acrylate Ternary Networks by Selective Thiol-Click Chemistry", Journal of Polymer Science: Part A: Polymer Chemistry, Apr. 16, 2010, vol. 48, 3255-3264, doi: 10.1002/pola.24102. cited by applicant
Mulik, "Adhesion Enhancement of Polymeric Films on Glass Surfaces by a Silane Derivative of Azobisisobutyronitrile (AIBN).", Polymer Preprints, American Chemical Society (ACS), Jan. 2008, 3 pgs. cited by applicant
Peng et al., "Facile Image Patterning via Sequential Thiol-Michael/Thiol-Yne Click Reactions", Chemistry of Materials, Nov. 20, 2014, vol. 26, pp. 6819-6826, doi: 10.1021/cm5034436. cited by applicant
Peng et al., "High Performance Graded Rainbow Holograms via Two-Stage Sequential Orthogonal Thiol-Click Chemistry", Macromolecules, Mar. 28, 2014, vol. 47, pp. 2306-2315, doi: 10.1021/ma500167x. cited by applicant
Extended European Search Report for European Application No. 24158294.9, Search completed Apr. 25, 2024, Mailed May 6, 2024, 7 pgs. cited by applicant

Primary Examiner: Jordan; Andrew

Attorney, Agent or Firm: KPPB LLP

Background/Summary

RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/153,588, filed Jan. 20, 2021, which is a continuation of U.S. patent application Ser. No. 15/943,590, filed Apr. 2, 2018, which is a continuation of U.S. patent application Ser. No. 14/044,676, filed Oct. 2, 2013, which is a continuation-in-part application of U.S. patent application Ser. No. 13/844,456, filed Mar. 15, 2013, which claims priority to U.S. Provisional Patent Application Nos. 61/796,632, filed Nov. 16, 2012, and 61/849,853, filed Feb. 4, 2013, the disclosures of which are hereby incorporated by reference in their entireties. (2) There is a need for

a compact transparent data display capable of displaying image content ranging from symbols and alphanumeric arrays to high-resolution pixelated images. Examples of transparent displays include HMDs, HUDs, HDDs and others. One important factor in each case is that the display should be highly transparent and the displayed image content should be clearly visible when superimposed over a bright background scene. The display should provide full color with an enhanced color gamut for optimal data visibility and impact—although monochrome will suffice in many applications. One important factor for Helmet Mounted Displays is that the display should be easy to attach to standard helmets or replicas thereof designed for training. The eye relief and pupil should be big enough to avoid image loss during head movement even for demanding military and sports activities. The image generator should be compact, solid state and have low power consumption. In automotive applications the ergonomic demands are equally challenging and aesthetic considerations make yet further demands on the form factor of the display, which ideally should be capable of being hidden within a dashboard when not in use. There is a growing need for more compact, cheaper and more efficient designs in many other application areas. The inventors note the growing demand for HUDs in airliners and small aircraft. Car manufactures are also looking to provide HUDs and HDDs in their future models. The systems described herein may be applicable to a helmet mounted head worn display for use in Augmented Immersive Team Training (AITT), essentially a live simulated training system for observer training that augments or replaces indirect fires and aircraft sorties needed to certify or sustain observer skills. (3) The above goals are not achieved by current technology. Current designs only manage to deliver see-through, adequate pupils, eye relief and field of view and high brightness simultaneously at the expense of cumbersome form factors. In many helmet-mounted display designs, weight is distributed in the worst possible place, in front of the eye. The most common approach to providing see-through displays relies on reflective or diffractive visors illuminated by off axis light. Microdisplays, which provide high-resolution image generators in tiny flat panels, do not necessarily help with miniaturization because the need for very high magnifications inevitably results in large diameter optics. The ideal transparent display is one that: firstly, preserves situational awareness by offering a panoramic see-through view with high transparency; and secondly, provides high-resolution, wide-field-of-view imagery. Such a system should also be unobtrusive; that is, compact, light-weight, and comfortable, where comfort comes from having a generous exit pupil and eye motion box/exit pupil (>15 mm), adequate eye relief (≥ 25 mm), ergonomic center of mass, focus at infinity, and compatibility with protective head gear. Current and future conventional refractive optics cannot satisfy this suite of demands. Other important discriminators include: full color capability, field of view, pixel resolution, see-throughness (transparency), luminance, dynamic grayscale and power consumption levels. Even after years of highly competitive development, head-mounted displays based on refractive optics exhibit limited fields of view and are not adequately compact, light-weight, or comfortable. (4) Displays based on waveguide technology substrate guided displays have demonstrated the capability of meeting many of these basic demands. The concept has been around for well over a decade. Of particular relevance is a U.S. Pat. No. 5,856,842 awarded to Kaiser Optical Systems Inc. in 1999 which teaches how light can be coupled into a waveguide by employing a diffractive element at the input and coupled out of the same waveguide by employing a second diffractive element at the output. According to U.S. Pat. No. 5,856,842, the light incident on the waveguide needs to be collimated in order to maintain its image content as it propagates along the waveguide. That is, the light must be collimated before it enters the waveguide. This can be accomplished in a variety of ways and is not a concern here. With this design approach, light leaving the waveguide will be naturally collimated, which is the condition needed to make the imagery appear focused at infinity. Light propagates along a waveguide only over a limited range of internal angles. Light propagating parallel to the surface will (by definition) travel along the waveguide without bouncing. Light not propagating parallel to the surface will travel along the waveguide bouncing back and forth between the surfaces, provided

the angle of incidence with respect to the surface normal is greater than some critical angle. For BK-7 glass, this critical angle is approximately 42 degrees. This can be lowered slightly by using a reflective coating (but this unfortunately diminishes the see-through performance of the substrate) or by using a higher-index material. Regardless, the range of internal angles over which light will propagate along the waveguide does not vary significantly. Thus, for glass, the maximum range of internal angles is ≤ 50 degrees. This translates into a range of angles exiting the waveguide (i.e., angles in air) smaller than 40 degrees and generally less, when other design factors are taken into account. To date, Substrate Guided Optics (SGO) technology has not gained wide-spread acceptance. This is largely due to the fact that waveguide optics can be used to expand the exit pupil but they cannot be used to expand the field of view or improve the digital resolution. That is, the underlying physics, which constrains the range of internal angles that can undergo TIR within the waveguide, limits the achievable field of view with waveguide optics to at most 40° and the achievable digital resolution to that of the associated imager. Nevertheless, the lure of a compact, light-weight HMD based on waveguide optics continues to inspire interest. One way to create a much larger field of view is to parse it into a set of smaller fields of view (each compatible with the optical limitations of the waveguide) and to time sequentially display them rapidly enough that the eye perceives them as a unified wide-angle display. One way to do this is with holographic elements that can be sequentially switched on and off very rapidly such as a Switchable Bragg Grating (SBG).

(5) The optical design benefits of diffractive optical elements (DOEs) are well known including unique and efficient form factors and the ability to encode complex optical functions such as optical power and diffusion into thin layers. Bragg gratings (also commonly termed volume phase grating or holograms), which offer the highest diffraction efficiencies, have been widely used in devices such as Head Up Displays (HUDs). An important class of Bragg grating devices is known as a Switchable Bragg Grating (SBG). An SBG is a diffractive device formed by recording a volume phase grating, or hologram, in a polymer dispersed liquid crystal (PDLC) mixture. Typically, SBG devices are fabricated by first placing a thin film of a mixture of photopolymerizable monomers and liquid crystal material between parallel glass plates or substrates. Techniques for making and filling glass cells are well known in the liquid crystal display industry. One or both glass substrates support electrodes, typically transparent indium tin oxide films, for applying an electric field across the PDLC layer. Other types of transparent conductive coating may also be used. A volume phase grating is then recorded by illuminating the liquid material with two mutually coherent laser beams, which interfere to form the desired grating structure. During the recording process, the monomers polymerize and the holographic polymer-dispersed liquid crystals (HPDLC) mixture undergoes a phase separation, creating regions densely populated by liquid crystal micro-droplets, interspersed with regions of clear polymer. The alternating liquid crystal-rich and liquid crystal-depleted regions form the fringe planes of the grating. The resulting volume phase grating can exhibit very high diffraction efficiency, which may be controlled by the magnitude of the electric field applied across the PDLC layer. When an electric field is applied to the hologram (e.g., a suitably optimized hologram) via transparent electrodes, the natural orientation of the LC droplets is changed causing the refractive index modulation of the fringes to reduce and the hologram diffraction efficiency to drop to very low levels. Note that the diffraction efficiency of the device can be adjusted, by means of the applied voltage, over a continuous range from near 100% efficiency with no voltage applied to almost zero efficiency with a sufficiently high voltage applied. SBGs may be used to provide transmission or reflection gratings for free space applications. SBGs may be implemented as waveguide devices in which the HPDLC forms either the waveguide core or an evanescently coupled layer in proximity to the waveguide. In one particular configuration to be referred to here as Substrate Guided Optics (SGO), the parallel glass plates used to form the HPDLC cell provide a total internal reflection (TIR) light guiding structure. Light is “coupled” out of the SBG when the switchable grating diffracts the light at an angle beyond the TIR condition. SGOs are currently of interest in a range of

display and sensor applications. Although much of the earlier work on HPDLC has been directed at reflection holograms, transmission devices are proving to be much more versatile as optical system building blocks. (6) Typically, the HPDLC used in SBGs comprise liquid crystal (LC), monomers, photoinitiator dyes, and coinitiators. The mixture frequently includes a surfactant. The patent and scientific literature contains many examples of material systems and processes that may be used to fabricate SBGs. Two fundamental patents are: U.S. Pat. No. 5,942,157 by Sutherland, and U.S. Pat. No. 5,751,452 by Tanaka et al. Both filings describe monomer and liquid crystal material combinations suitable for fabricating SBG devices. (7) One of the known attributes of transmission SBGs is that the LC molecules tend to align normal to the grating fringe planes. The effect of the LC molecule alignment is that transmission SBGs efficiently diffract P polarized light (i.e., light with the polarization vector in the plane of incidence), but have nearly zero diffraction efficiency for S polarized light (i.e., light with the polarization vector normal to the plane of incidence). Transmission SBGs may not be used at near-grazing incidence as the diffraction efficiency of any grating for P polarization falls to zero when the included angle between the incident and reflected light is small. A glass light guide in air will propagate light by total internal reflection if the internal incidence angle is greater than about 42 degrees. Thus the invention may be implemented using transmission SBGs if the internal incidence angles are in the range of 42 to about 70 degrees, in which case the light extracted from the light guide by the gratings will be predominantly p-polarized. Normally SBGs diffract when no voltage is applied and are switching into their optically passive state when a voltage is applied at other times. However SBGs can be designed to operate in reverse mode such that they diffract when a voltage is applied and remain optically passive at all other times. Methods for fabricating reverse mode SBGs are disclosed in U.S. Provisional Patent Application No. 61/573,066 with filing date 24 Aug. 2012 by the present inventors entitled IMPROVEMENTS TO HOLOGRAPHIC POLYMER DISPERSED LIQUID CRYSTAL MATERIALS AND DEVICES. The same reference also discloses how SBGs may be fabricated using flexible plastic substrates to provide the benefits of improved ruggedness, reduce weight and safety in near eye applications. (8) In a prior filing the inventors have disclosed a waveguide (SGO) display that produces a large field of view by parsing it into a set of smaller fields of view (each compatible with the optical limitations of the waveguide) and to time sequentially display them so fast that the eye perceives them as a unified image. This process is sometimes referred to as field of view tiling. One way to do this is with holographic elements that can be sequentially switched on and off very rapidly. In an earlier PCT Application No.: PCT/GB2010/000835, with International Filing date 26 Apr. 2010, by the present inventors entitled COMPACT HOLOGRAPHIC EDGE ILLUMINATED EYEGLASS DISPLAY (and also referenced by the Applicant's docket number SBG073PCT) which is incorporated by reference herein in its entirety, the inventors have shown how multiple SBGs can be stacked together in the same waveguide and activated in rapid succession to time-sequentially tile a high-resolution, ultra-wide-field of view. Moreover, each subfield of view has the full digital resolution of the associated imager, allowing the formation of images that approach or even exceed the visual acuity limit of the human eye. While the tiling disclosed in this earlier filing overcomes the twin deficiencies of standard guided-wave architectures: limited field of view and limited pixel resolution, it has limitations when it is necessary to tile vertically and horizontally over large fields of view. For monochrome displays with modest FOV and expansion in only one direction, tiling can be accomplished by simply stacking the grating planes. However, when the field of view is expanded in both directions and color is added, the number of layers needed with this approach quickly becomes impractical. Each subfield of view is limited by the diffraction efficiency and angular bandwidth of the SBG. SBG grating devices typically have angular bandwidths in air of approximately $\pm 5^\circ$ (subject to material properties, index modulation beam geometry and thickness). The inventors have found that larger angles can be achieved in practice by using thinner SBGs typically, smaller than 3 microns. The increased bandwidth resulting from thinner SBGs will result in lower peak diffraction efficiency.

Therefore it is usually necessary to increase the refractive index modulation. One way to avoid the need for separate RGB SBGs is to use multiplexed SBGs, in which the illumination is provided from opposite ends of the light guide as R and B/G illumination, compromising the color gamut somewhat. However, multiplexed gratings raise issues of fabrication complexity and cross talk. (9) An elegant solution to the tiling problem disclosed in United States Provisional Patent with a filing date of 25 Apr. 2012 by the present inventors entitled WIDE ANGLE COLOR HEAD MOUNTED DISPLAY, which is also referenced by 61/687,436, is to compress the stack by interlacing or tessellating the SBGs, as opposed to simply stacking the gratings. The display disclosed in Application No. 61/687,436 comprises two elements: firstly, a multilayer waveguide device comprises layers of tessellated SBG arrays referred to as the DigiLens and, secondly, an optical system for providing input image data from one or more microdisplays referred to as an Input Image Node (IIN) which, in addition to the microdisplays, contains laser illumination modules, collimation and relay optics waveguide links and grating devices. The same terminology will be retained for the purposes of describing the present invention. In very basic terms the DigiLens provides the eyepiece while the IIN provides a compact image generation module that will typically be located above or to the side of the DigiLens according to the ergonomic constraints of the application. In Application No. 61/687,436, all SBG elements sharing a given prescription are activated simultaneously such that they diffract collimated wave guided image light into a predetermined FOV tile. The number of images that can be tiled is only limited by the input display refresh rate. The SBG elements would typically be a few millimeters in size. While this approach achieves significant economy in terms of layers, it suffers from the problems of illumination ripple owing to tessellated grating pattern used in the DigiLens), scatter from electrodes, and general optical and electrical complexity. (10) The motivation behind the present disclosure is to reduce the need for tessellating the DigiLens. A further problem of the prior art is that coupling the IIN output image into the waveguides is very inefficient, thus resulting in thick waveguides. A more efficient way of sampling the input image field is needed overcome this problem.

SUMMARY

- (1) In view of the foregoing, the Inventors have recognized and appreciated the advantages of a display and more particularly to a transparent display that combines Substrate Guided Optics (SGO) and Switchable Bragg Gratings (SBGs).
- (2) Accordingly, provided in one aspect of some embodiments is an apparatus for displaying an image, the apparatus comprising: a first optical substrate comprising at least one waveguide layer configured to propagate light in a first direction, wherein the at least one waveguide layer of the first optical substrate comprises at least one grating lamina configured to extract the light from the first substrate along the first direction; and a second optical substrate comprising at least one waveguide layer configured to propagate the light in a second direction, wherein the at least one waveguide layer of the second optical substrate comprises at least one grating lamina configured to extract light from the second substrate along the second direction. The at least one grating lamina of at least one of the first and second optical substrates may comprise an SBG in a passive mode.
- (3) In one embodiment, the at least one waveguide of at least one of the first and second optical substrates comprises a plurality of grating laminas, at least two of the plurality having the same surface grating frequency.
- (4) In one embodiment, the at least one grating lamina of at least one of the first and second optical substrates comprises non-switching Bragg grating recorded in a HPDLC material in at least one of forward and reverse modes. While the grating lamina may be an SBG in some instances, it need not be. Other types of suitable materials may also be used.
- (5) In one embodiment, the first and second optical substrates comprise an SBG in a passive mode.
- (6) In one embodiment, at least one of the first and second optical substrates comprises a plurality of waveguide layers, and each of the pluralities of waveguide layers is configured to propagate at

least one of red, green, blue, blue/green mixed light, and one of a multiplicity of sub Field of Views (FOVs). In one instance, at least one of the first and second optical substrates comprises a plurality of waveguide layers, and when the plurality comprises three waveguide layers, the three waveguide layers are configured to propagate red, green, and blue light. Alternatively, when the plurality comprises two waveguide layers, the three waveguide layers are configured to propagate red light and mixed blue and green light.

(7) In one embodiment, the at least one waveguide layer of the at least one of the first and second optical substrates comprises holograms with superimposed different color prescriptions.

(8) In one embodiment, the at least one waveguide layer in at least one of the first and second optical substrates is lossy.

(9) In one embodiment, the at least one grating lamina of at least one of the first and second optical substrates has a thickness that is less than about 3 microns. For example, the thickness may be less than about 2.5 microns, 2 microns, 1.5 microns, 1.2 microns, 1 micron, 0.5 micron, or even smaller.

(10) In one embodiment, the at least one grating lamina of at least one of the first and second optical substrates has a varying thickness along the respective direction of light propagation.

(11) In one embodiment, the apparatus described herein is a part of a device, wherein the device is a part of at least one of HMD, HUD, and HDD.

(12) Provided in another aspect of some embodiments is an apparatus for displaying an image comprising: an input image node for providing image modulated light; a first optical substrate comprising at least one waveguide layer configured to propagate the modulated light in a first direction, wherein the at least one waveguide layer of the first optical substrate comprises at least one grating lamina configured to extract the modulated light from the first substrate along the first direction; a second optical substrate comprising at least one waveguide layer configured to propagate the modulated light in a second direction, wherein the at least one waveguide layer of the second optical substrate comprises at least one grating lamina configured to extract the modulated light from the second substrate along the second direction. The at least one grating lamina of the first optical substrate may be configured to couple the modulated light into the first substrate. The at least one grating lamina of the second optical substrate may be configured to couple the modulated light extracted from the first substrate into the second substrate. The at least one grating lamina of at least one of the first and second optical substrates may have a k-vector that varies along the respective direction of light propagation.

(13) In one embodiment, the input image node comprises at least one of microdisplay, laser, and collimating optics. A microdisplay may be any type of microdisplay commonly used, including, for example, an emissive microdisplay. An emissive microdisplay may be an OLED, a QPI, and the like.

(14) In one embodiment, the at least one grating lamina of at least one of the first and second optical substrates has a varying thickness. For example, the thickness may increase in a direction that is at least one of (i) parallel to a direction of the light propagation and (ii) orthogonal to the light propagation. Alternatively, the thickness may increase and then decrease (or vice versa) along the aforescribed direction. The geometry is not limited.

(15) In one embodiment, the at least one grating lamina of at least one of the first and second optical substrates comprises an SBG that is in a switching mode or in a passive mode.

(16) In one embodiment, the at least one grating lamina in at least one of the first and second substrates comprises multiplex gratings of at least two different monochromatic prescriptions.

(17) In one embodiment, the apparatus comprises multiple grating laminas having the same surface grating frequency but different k-vectors, wherein the multiple grating laminas are configured to divide the input image field of view into multiple angular intervals.

(18) In one embodiment, at least one of the first and second optical substrates is curved in at least one orthogonal plane.

(19) In one embodiment, the light extracted from the first and second optical substrates provides

uniform illumination in any field of view direction.

(20) Provided in another aspect of some embodiments is a method of displaying an image, the method comprising: coupling a modulated light from an input image into a first optical substrate; extracting the light from the first substrate; and coupling the extracted light from the first substrate into the second substrate. The first optical substrate may comprise at least one waveguide layer configured to propagate light in a first direction, wherein the at least one waveguide layer of the first optical substrate comprises at least one grating lamina configured to extract light from the first substrate along the first direction. The second optical substrate may comprise at least one waveguide layer configured to propagate light in a second direction, wherein the at least one waveguide layer of the second optical substrate comprises at least one grating lamina configured to extract light from the second substrate along the second direction. The at least one grating lamina of at least one of the first and second optical substrates may comprise an SBG in a passive mode.

(21) In one embodiment, the method further comprises sampling the input image into a plurality of angular intervals, each of the plurality of angular intervals having an effective exit pupil that is a fraction of the size of the full pupil. In one stance, this surprisingly provides an advantage that the thickness of the first waveguide can be much smaller in comparison to pre-existing devices.

Accordingly, the size and placement of the input gratings may be advantageously affected.

(22) In one embodiment, the method further comprising improving the displaying of the image by modifying at least one of the following of the at least one grating lamina of at least one of the first and second optical substrates: grating thickness, refractive index modulation, k-vector roll profile, surface grating period, and hologram-substrate index difference.

(23) Provided in another embodiment is an apparatus for displaying an image comprising: an input image node for providing image modulated light; first and second optical waveguiding substrates; a first optical means for coupling image modulated light into said first substrate; and a second optical means for coupling light extracted from the first substrate into the second substrate. The first optical substrate comprises at least one waveguiding layer that propagates light in a first direction. Each waveguiding layer contains at least one grating lamina operative to extract light from the first substrate, the light extraction taking place along the first direction. The second optical substrate comprise at least one waveguiding layer. Each waveguiding layer propagates light in a second direction. Each waveguiding layer contains at least one grating lamina operative to extract light for display from the second substrate, the light extraction taking place along the second direction. In one embodiment the first optical substrate selectively samples portions of the image modulated light, each portion being characterized by either angular field or spatial field.

(24) It should be appreciated that all combinations of the foregoing concepts and additional concepts discussed in greater detail below (provided such concepts are not mutually inconsistent) are contemplated as being part of the inventive subject matter disclosed herein. In particular, all combinations of claimed subject matter appearing at the end of this disclosure are contemplated as being part of the inventive subject matter disclosed herein. It should also be appreciated that terminology explicitly employed herein that also may appear in any disclosure incorporated by reference should be accorded a meaning most consistent with the particular concepts disclosed herein.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The skilled artisan will understand that the drawings primarily are for illustrative purposes and are not intended to limit the scope of the inventive subject matter described herein. The drawings are not necessarily to scale; in some instances, various aspects of the inventive subject matter disclosed herein may be shown exaggerated or enlarged in the drawings to facilitate an

understanding of different features. In the drawings, like reference characters generally refer to like features (e.g., functionally similar and/or structurally similar elements).

(2) FIG. 1A is a schematic illustration of the optical geometry of a Bragg grating in the tangential plane.

(3) FIG. 1B is a schematic illustration of the optical geometry of a Bragg grating in the sagittal plane.

(4) FIG. 2A is a schematic side elevation view showing a first operational state in one embodiment.

(5) FIG. 2B is a schematic side elevation view showing a second operational state in one embodiment.

(6) FIG. 2C is a schematic front elevation view of one embodiment.

(7) FIG. 3 is a schematic three dimensional view of the components of one embodiment.

(8) FIG. 4 is a schematic side elevation view of the components of one embodiment.

(9) FIG. 5 is a flow chart representing the formation of an image in one embodiment.

(10) FIG. 6 is a schematic side elevation view of one embodiment.

(11) FIG. 7 is a schematic side elevation view of one embodiment.

(12) FIG. 8 is a schematic side elevation view of one embodiment.

(13) FIG. 9 is a chart showing the diffraction efficiency characteristics of one embodiment.

(14) FIG. 10 is a schematic cross sectional view of a horizontal beam expander in one embodiment.

(15) FIG. 11 is a table provide diffraction efficiency characteristic of SBGs used in one embodiment.

(16) FIG. 12A is a schematic three dimensional view showing a first operational state of one embodiment.

(17) FIG. 12B is a schematic three dimensional view showing a second operational state of one embodiment.

(18) FIG. 13A is a schematic three dimensional view showing a third operational state of one embodiment.

(19) FIG. 13B is a schematic three dimensional view showing a fourth operational state of one embodiment.

(20) FIG. 14A is an artist's impression of a first aspect of a HMD implement of the invention.

(21) FIG. 14B is an artist's impression of a second aspect of a HMD implement of the invention.

(22) FIG. 14C is an artist's impression of a third aspect of a HMD implement of the invention.

(23) FIG. 15 is a schematic cross section view of a wedged profile waveguide grating used in one embodiment.

(24) FIG. 16 is a schematic side elevation view of one embodiment

(25) FIG. 17 is chart shown diffraction efficiency versus angle characteristics of one embodiment

(26) FIG. 18 is a schematic side elevation view of one embodiment

(27) FIG. 19A is a schematic side elevation view showing a first operational state of one embodiment.

(28) FIG. 19B is a schematic side elevation view showing a second operational state of one embodiment.

(29) FIG. 20A is a schematic side elevation view showing a first operational state of an input image node in one embodiment.

(30) FIG. 20B is a schematic side elevation view showing a second operational state of an input image node in one embodiment.

(31) FIG. 21 is a schematic plan view of a HBE containing slanted grating stripes.

(32) FIG. 22 is a schematic three dimensional view of one embodiment using a HBE containing slanted grating stripes.

(33) FIG. 23A is a schematic side elevation view showing a first operational state of a HUD provided by one embodiment.

(34) FIG. 23B is a schematic side elevation view showing a second operational state of a HUD

provided by one embodiment.

(35) FIG. **24** is a schematic side elevation view of a HUD provided by one embodiment.

(36) FIG. **25** is a schematic side elevation view of a HUD provided by one embodiment.

(37) FIG. **26** is a schematic illustration of a prior art collimated image display.

(38) FIG. **27** is a schematic side elevation view of a HUD according to the principles of the invention.

(39) FIG. **28** is a schematic side elevation view of a holographic mirror.

(40) FIG. **29** is a schematic side elevation view of a HUD provided by one embodiment.

(41) FIG. **30** is a schematic side elevation view of a HUD provided by one embodiment.

(42) FIG. **31** is a schematic side elevation view of a HUD provided by one embodiment.

(43) FIG. **32A** is a three dimension view of a color display provided by one embodiment

(44) FIG. **32B** is a chart showing the spectral characteristics of a light source used in a color display provided by one embodiment.

(45) FIG. **32C** is a table showing the spectral characteristics of a light source used in a color display provided by one embodiment.

(46) FIG. **33** is a cross sectional view of a HUD integrated in a windscreen in one embodiments of the invention

(47) FIG. **34** is a cross sectional view of a HUD integrated in a windscreen in one embodiments of the invention

(48) FIG. **35** is a three dimensional view of a display provided by one embodiment

(49) FIG. **36** is a three dimensional view of a display provided by one embodiment

(50) FIG. **37** is a schematic side elevation view of a color display provided by one embodiment.

(51) FIG. **38** is a schematic three dimensional view of a color display provided by one embodiment.

(52) FIG. **39A** is a schematic side elevation view of one embodiment

(53) FIG. **39B** is a schematic front elevation view of one embodiment

(54) FIG. **40** is a cross sectional view of a HUD integrated in a windscreen in one embodiment

(55) FIG. **41** is a flow chart illustrating image formation in a HUD in one embodiment

(56) FIG. **42A** is a chart show a first diffraction efficiency versus angle characteristic of a multiplexed DigiLens in one embodiment.

(57) FIG. **42B** is a chart show a second diffraction efficiency versus angle characteristic of a multiplexed DigiLens in one embodiment.

(58) FIG. **43** is a schematic three dimensional view of a color multiplexed display in one embodiment.

(59) FIG. **44** is a schematic side elevation view of a DigiLens used in a color multiplexed display in one embodiment.

(60) FIG. **45** is a three dimensional illustration of an embodiment of a display in one embodiment in which there are provided three HBE waveguides and three DigiLens waveguides.

(61) FIG. **46** is a schematic side elevation view showing the formation of a projected stop by the IIN.

(62) FIG. **47** is a schematic plan view illustrating the coupling of light from the IIN into the HBE waveguide.

(63) FIG. **48** shows a detail of the HBE waveguide of FIG. **47**. The image input end illustrating the interaction of the beam with the gratings.

(64) FIG. **49** is a schematic cross-sectional view of a four layer HBE in one embodiment.

(65) FIG. **50** is a table showing the gratings used in the embodiment of FIG. **49**.

(66) FIG. **51** is a chart showing overlapping DE versus angle profiles in the embodiment of FIG. **49**.

(67) FIG. **52** is a three dimensional view of a wedge SBG grating in one embodiment.

(68) FIG. **53A** is a schematic illustration of a first operational state of the HBE in one embodiment.

(69) FIG. 53B is a schematic illustration of a second operational state of the HBE in one embodiment.

(70) FIG. 53C is a schematic illustration of a third operational state of the HBE in one embodiment.

(71) FIGS. 54A-54B illustrates projection schemes in one embodiment that do not result in a projected pupil of the type discussed earlier in the description; the pupil may be formed inside the projection lens (FIG. 54A) or before the projection lens using the aperture 562 (FIG. 54B).

(72) FIG. 55 shows a schematic illustration of the use of rolled k-vector gratings to maximize the peak DE of in-couple light in one embodiment.

(73) FIG. 56 shows a schematic illustration showing the propagation of a typical ray through a waveguide section 580 containing rolled k-vector gratings in one embodiment.

(74) FIG. 57 shows a plan view showing the HBE 590 and the VBE 591 in one embodiment.

(75) FIG. 58 shows a schematic side elevation view of the HBE and the VBE in one embodiment.

(76) FIG. 59 shows an unfolded view of the HBE showing the beam propagation inside the waveguide in one embodiment.

(77) FIG. 60 illustrates an apparatus for fabricating the HBE using a contact copying process in one embodiment.

(78) FIGS. 61A-61C, respectively, show a cross section of the Z=L end of the HBE 590 with the wider end of a cone shaped lens overlaid, a plan view of the lens, and the Z=0 end of the HBE with the narrower end of the lens overlaid in one embodiment.

(79) FIGS. 62A-62C illustrate the generation of the conic section from a cone of tip 620 and base 621; the cone is shown in side view in FIG. 62A and in-front view in FIG. 62B; a view of the cut out optics projected from the base along the cut line is shown in FIG. 62C.

(80) FIG. 63 shows the basic architecture of a waveguide in one embodiment.

(81) FIG. 64 is an illustration of a waveguide in which the input gratings 635A-635C are stacked. Each grating has a unique k-vector 636A-636C in one embodiment.

(82) FIG. 65 shows that the input gratings are disposed adjacent to each other along the waveguide propagation direction in one embodiment.

(83) FIG. 66 illustrates that the principles illustrated in FIGS. 64-65 may also be applied in the output grating in one embodiment.

(84) FIG. 67 shows a flow chart describing a process of one embodiment.

(85) FIG. 68 shows a ray trace of a monochromatic version of the design in one embodiment.

(86) FIG. 69 shows the approximate dimensions of the IIN of FIG. 63 in one embodiment.

(87) FIG. 70 provides unfolded views of the optical layout of FIG. 64 in one embodiment.

(88) FIGS. 71A and 71B illustrate the formation of a projected stop inside the HBE in one embodiment using a simplified thin lens representation of the microdisplay projection optics.

(89) FIG. 72 illustrates one embodiment, in which the HBE that comprises a coupling grating at its input end and alternating SBG stripes of two different prescription, is inclined at 45 degrees.

(90) FIG. 73 illustrates beam propagation from the IIN through a single layer of the DigiLens showing the four changes in direction that occur along the path to the exit pupil in one embodiment.

(91) FIG. 74 shows plan view of the near eye geometry of the proposed helmet mounted display in one embodiment.

(92) FIG. 75 shows side view of the near eye geometry of the proposed helmet mounted display in one embodiment.

(93) FIG. 76 shows front view of the near eye geometry of the proposed helmet mounted display in one embodiment.

(94) FIG. 77 shows the relationship of the DigiLens® aperture to the FOV, eye relief and eye box in one embodiment.

(95) FIG. 78 shows partial binocular overlap in one embodiment.

(96) FIG. 79 shows partial binocular overlap in another embodiment.

(97) FIG. **80** shows a transparent waveguide display in one embodiment.

DETAILED DESCRIPTION

(98) Following below are more detailed descriptions of various concepts related to, and embodiments of, inventive a transparent display. It should be appreciated that various concepts introduced above and discussed in greater detail below may be implemented in any of numerous ways, as the disclosed concepts are not limited to any particular manner of implementation. Examples of specific implementations and applications are provided primarily for illustrative purposes.

(99) The invention will now be further described by way of example only with reference to the accompanying drawings. It will apparent to those skilled in the art that the present invention may be practiced with some or all of the present invention as disclosed in the following description. For the purposes of explaining the invention well-known features of optical technology known to those skilled in the art of optical design and visual displays have been omitted or simplified in order not to obscure the basic principles of the invention. Unless otherwise stated the term “on-axis” in relation to a ray or a beam direction refers to propagation parallel to an axis normal to the surfaces of the optical components described in relation to the invention. In the following description the terms light, ray, beam and direction may be used interchangeably and in association with each other to indicate the direction of propagation of light energy along rectilinear trajectories. Parts of the following description will be presented using terminology commonly employed by those skilled in the art of optical design. It should also be noted that in the following description of the invention repeated usage of the phrase “in one embodiment” does not necessarily refer to the same embodiment.

(100) The present invention is made possible by two fundamental properties of SBGs that have not been exploited to date firstly the relatively wide angular bandwidth of Bragg gratings in the plane orthogonal to the plane of diffraction and secondly the wide angular bandwidths resulting from making SBGs very thin. As a result, the constraints of limiting the size of FOV tiles to around $10^\circ \times 10^\circ$ does not apply in this instance, thereby leading to the tessellation approach discussed above. Fewer bigger tiles may now be used as a result. As is shown in the following description the needed FOV may be divided into two tiles with one DigiLens for each. Other numbers of tiles may also be possible. With respect to the optical design this new approach may minimize, if not eliminate entirely, the problem of illumination ripple. By making the DigiLens passive the problems of scatter from electrodes and the not insignificant problems of wiring up large matrices of tessellation elements may be avoided. A passive SBG is no different from a switching SDBG in terms of its HPDLC formulation and recording process. The only difference is that no electrodes are needed. The diffracting properties of an SBG are normally specified in the tangential plane. In a grating design to diffract light in a plane, the tangential plane is the plane containing the incident and diffracted ray vectors and the grating vector. Following geometrical optical theory the plane orthogonal to the tangential plane is referred to as the sagittal plane. FIG. **1** illustrates the basic geometrical optics of a transmission SBG **90** containing slanted fringes such as **91** with grating vectors **K** aligned normal to the fringes. In Bragg gratings the a multiplicity of input and output rays will satisfy the Bragg condition provided the angles between the incident rays and the k-vector diffracted rays and the K-vector satisfy the Bragg equation. (Note that in practice, according to the Kogelnik theory of Bragg gratings, reasonably high diffraction will be obtain for off-Bragg angles having a small angular or wavelength deviation from the on-Bragg ray directions). In FIG. **1** these off-Bragg rays are illustrated by the ray cones **902,903** surrounding the on-Bragg (lying in the in-plane of the drawing) rays **900,901**. As shown in FIG. **1A** the locus of the on-Bragg ray-fringe intercepts is the circle **904**. As shown in FIG. **1B** rays **905,906** will also be on-Bragg. From consideration of the geometry of FIG. **1A** it should be apartment that the Bragg diffraction angular bandwidth in the tangential plane is limited by the projections of the cones **902,903** onto the tangential plane. However, turning to FIG. **1B** it should be apparent the effective angular

bandwidth (“ABW”) in the sagittal plane is much large is it is provided by the projection of cone **904** into the sagittal plane. In practice the sagittal bandwidth is mainly limited by the TIR angle constraints set by the waveguide. As a consequence of the large sagittal plane (i.e. horizontal plane for our purposes) angular bandwidth of Bragg gratings (typically around 4× the tangential bandwidth) current horizontal FOV targets may be achieved for most display applications. In practice the bandwidth is only limited only by TIR angle range that can be sustained in the waveguide.

(101) The inventors have already demonstrated that thin SBG gratings provide very wide angular bandwidths. An experimental SBG waveguide made using a low index modulation SBG RMLCM formulation has been shown to have a FWHM bandwidth of 21° with a 1 micron thick SBG layer. (102) In the following description many references to gratings are made, which should generally be understood to mean a Bragg grating and desirably an SBG. In many cases the SBGs will be operated in their normal switching mode as described above. However, in some cases SBGs will be used in a passive (e.g., completely passive) mode that is they will not be switchable. A non switching SBG is superior to a conventional passive hologram for the reason that the LC component of the HPDLC entangles much higher refractive index modulations than can be achieved in conventional holographic photopolymers. In certain embodiments of the invention the display will use a mixture of switching and non switching SBGs. The DigiLens output gratings will always be passive (non-switching), however. In one particular class of embodiments the displays will use all passive SBGs.

(103) A transparent display according to the principles of the invention is illustrated schematically in FIG. 2. The DigiLens®, which provides a thin highly transparent eye piece (or HUD combiner) comprises two waveguides **101,102** for projecting the upper and lower halves of the field of view into the eye box (not shown). The waveguides each comprise non switchable SBG layers sandwiched between transparent substrates. Each waveguide has a switchable input grating and a non switching (passive) output grating labelled as DIGI-I1, DIGI-O1 and DIGI-I2, DIGI-O2 which are also indicated by the numerals **107,109** and **108, 110** respectively. The waveguides are separated by a Half Wave Film (HWF) **106**. (Note than in other embodiments to be described below the HWF will be disposed between the DIGI-I gratings and the DIGI-O gratings will be air (or low-index material) separated). An input image node (IIN) **103** which will be discussed later contains the microdisplay, laser module, beam expansion, collimation and relay optics. Schematic side elevation views are provided in FIGS. 2A-2B and a front elevation in FIG. 2C. FIGS. 2A-2B indicate the ray paths from the IIN through the DigiLens layers for the two switched states of the display. In the first state the grating DIGI-I1 is active and diffracts incident P-polarised light **1000** from the IIN **103** into the TIR path **1001**. The TIR light is diffracted out of the waveguide along its light as indicated by **1002**. The output grating is lossy, that is the diffraction efficiency is significantly less than unity such that a portion of the guide light gets diffracted out at each beam-grating interaction. The remaining light continues to undergo repeated TIR and diffraction until all of the light has been extracted from the waveguide. Uniform illumination across the output aperture is achieved by careful optimisation of diffraction efficiency (which depends on the refractive index modulation, grating thickness and other parameters). In general low diffraction efficiency is needed at the end of the waveguide nearest the IIN and the highest efficiency at the extreme end. Note that due to lossy extraction more peak energy (at) 0° is coupled into the DigiLens than at higher angles. Thus wider angle light is available for extraction at the end of a lossy grating. While the phrase “lossy grating” is employed in some embodiments, the phrase encompasses “lossy waveguide. Not to be bound by any theory, but this is because the “lossy” may be due to a combination not the grating efficiency and waveguiding action that may result in the uniform loss along the waveguide. (104) This helps to homogenize peak and edge angular variations, particularly at the thicker end of the waveguide where the DE curve narrows. The diffracted light **1002** has its polarisation rotated through 90 degrees (becoming S-polarised) by the HWF and therefore passes the second

waveguide **102** without deviation since SBGs have relative low DE for S-polarised light. Note that one DigiLens® layer emits S-polarized light while the other emits P-polarised light. However, each SBG layer is P-diffracting.

(105) The Horizontal Beam Expander (HBE) indicated by the labels HBE1, HBE2 (also referenced by the numerals **(104, 105)**) is a multilayer SBG waveguide using lossy high ABW gratings to expand the image light across a large pupil. In the above described embodiment the HBE runs along the top edge of the DigiLens. The HBE will be discussed in more detail later. Note that air gap between the front and rear DigiLens® elements. This may be replaced by a suitable low (near unity) index material. Since the output image light is a mixture of P and S polarized light it may be necessary to mount a quarter wave film on the output surface of the DigiLens for compatibility with Polaroid type eye ware which would otherwise result in the loss of half of the field of view.

(106) Although it is referred to an HBE (and a VBE in an earlier filing) the terms horizontal and vertical in this context only have significance for the purposes of illustrating the invention. In practice the invention allows many different configurations of the components and several different ways of implement the beam steering the beam expansion may be vertical or horizontal. With regard to the term waveguide it should be noted that these may actually comprise multiple isolated waveguides stacked in layers. Finally with regard to grating components it should be understood that each of the three grating components may contain multiple gratings stack in layers, disposed adjacently in a single layer or holographically multiplexed in a single layer. The basic building block of the displays discloses is a waveguide containing a grating, normally a Bragg grating. As will be seen the function can in certain embodiments be accomplished with as few as one waveguide layer. However the number of waveguide layers will depend on the size of field of view and the color needed. The grating may be switchable (SBG) or it may be passive, that is, non switchable. Although in principle, any type of Bragg grating may be used to provide a passive grating. There is a strong advantage in using an SBG with no electrodes. SBG material has the advantage that the mixture of LC and polymer affords higher refractive index modulation than that of conventional holographic polymer materials. In the preferred embodiment of the invention the output waveguide component uses only non tessellated passive gratings. This minimizes the potential problems of scatter from electrodes and illumination non uniformities. Term grating is employed to refer to a Bragg grating unless otherwise specified. Passive grating means a grating that is not electrically switched.

(107) The display is shown in more detail in FIGS. 3-4. As a further aid to understanding how a collimated display (e.g., HMD) works, the initial focus is on the monochrome version of the design. Architecturally, the monochrome and color implementations of the HWD are very similar. As will be seen, an important difference is that the monochrome architecture can be achieved with fewer waveguiding layers and the possibility of using some passive grating components in the IIN and HBE, while a color implementation needs most components of the IIN and HBE to be switchable owing to the greater difficulty of managing the angular content of red, green and blue optical channels simultaneously. In both cases the DigiLens® remains a passive component.

(108) While the present invention has many applications in the field of transparent visual displays it is first considered one particular application namely a Helmet Mounted Display for Augmented Reality (AR) application. The objective in this case is to meet the 52° H×30° V monocular field of view specification while achieving all of our original goals of high transparency, high resolution, ultra compact (thin) form factor, light weight and generous exit pupil. The target specifications are summarized in Table 1.

(109) TABLE-US-00001 TABLE 1 Target HMD Specifications. Helmet Mounted Display Specification Color Monochrome - Extendable to Full Color Total Field of View (FOV) 85° H × 30° V Monocular Field of View 52° H × 30° V Binocular Overlap 20° Eye Box 25 mm. × 25 mm. Eye Relief 25 mm. Resolution 1080p Form Factor Ultra compact (thin) DigiLens Active Area 49.4 mm. × 33.4 mm. Transparency >95%

(110) The important components of the display are illustrated in the schematic three dimensional drawing of FIG. 3 and the side elevation view of FIG. 4. The display splits the FOV into upper and lower FOV tiles (referred to by the numerals 1, 2 in the drawing labelling) Note that the waveguide substrates of the DigiLens and HBE components have not been shown in order to simplify the explanation. The display comprises a DigiLens® comprised of two waveguide layers sandwiching a HWF is split into input and output components DIGI-I and DIGI-O. Note that wide sagittal angular bandwidth of SBGs removes the need to tile horizontally. Two Horizontal Beam Expanders HBE each comprising input gratings HBE-I and output gratings HBE-O are provided. The expanded output light from HBE-O1 enters the first DigiLens waveguide via DIGI-I11 and similarly for the second waveguide. Note that the above components are also referenced by numerals **130-145** in FIGS. 3-4. Two IIN are provided: one for the upper FOV and one for the lower FOV. The display panel in each IIN is a 1080p 5 mm×3 mm LCoS devices. One laser module may be used to illuminate both display panels. However, the invention does not place any restriction on the number of microdisplays to be used. A single microdisplay with a fast enough refresh rate and high enough resolution is likely to be sufficient for all but the most demanding display applications.

(111) The DIGI-I is the most challenging grating in the system since it needs high input coupling efficiency at the projected pupil output point from the HBE-O, across the full angular range. The DIGI-I gratings switch, sampling the 52° horizontal x 30° vertical field output by the HBE-O into the two DigiLens waveguides. It is desirable that this grating needs a high angular bandwidth and high DE. The DIGI-I comprises 2 SBGs each operating over 8.5° angular bandwidths overlapping to provide at least 15°. DIGI-I uses two 3 micron SBGs of DE approximately 87% with angular bandwidth of 8.5°-9.0° in air. The vertical field from -15° to 0° is switched by DIGI-I1 and the vertical field from 0° to +15° into DIGI-2. Hence DIGI-I1 provides 52° horizontal x -15° vertical and DIGI-I2 provides 52° horizontal x +15° vertical. All gratings in the DIGI-O are passive, and therefore can be thin gratings. One of each pair is for red and the other for blue/green. DIGI-O1 the rear grating providing the lower 15° and the front grating DIGI-O2 providing the upper 15° giving a total 52° horizontal x 30° vertical. As shown in FIG. 4 the DigiLens® is tilted at a rake angle of ~ 8-10°. This is found from ray-tracing analysis to give better DE than simply projecting image light normally into the DigiLens®.

(112) A flow chart representing the interaction between the IIN, HBE and DigiLens in the image formation process is provided in FIG. 5. Since diffractive optical elements are dispersive it is usually desirable where more than one grating is combined to configure them in a complementary fashion such that the dispersions introduced by the gratings cancel. Complementary is normally achieved by designing the gratings to have the same grating pitch (that is, the spatial frequencies of the intersections of the Bragg gratings with the substrates are identical). It should be noted that HBE-I2 and HBE-O2 need to be complementary in the embodiment described above. However, HBE-I1 and HBE-I2 do not need to be complementary.

(113) In one embodiment shown in FIG. 6 the HWF between the DigiLens waveguides (overlapping the DIGI-O gratings) is removed and a HWD is inserted in the spaced between the DigiLens DIGI-I input gratings. The air gap left by the HWP may be filled with a low index nanoporous material. Quarter Wavelength Film (QWF) is applied to opposing faces **157,158** of the front and rear waveguides with the effect that each TIR bounce results in a 90° polarization rotation allowing an approximately ×4 thinner grating and no interaction between the front and rear DigiLens®. FIG. 7 shows the propagation of upper and lower FOV light in the two DigiLens waveguides as represented by the ray paths **1010, 1012, 1014** in the first waveguide and **1011, 1013, 1015**. The components shown in FIGS. 6-7 are also referenced by the numerals **150-159**. FIG. 8 is a view of one of the DigiLens waveguides **160** illustrating the function of the QWF layer **162** in more detail. Input light from the HBE **1020** is deflected into the TIR path **1021** by the DIGI-I grating **161**. Rays such as **1022** incident on the QWF coating have their polarization converted

from P to circularly polarized light of a first sense. On reflection the polarization remains circular but in an opposing sense such that after passing through the QWF the second time the light emerges as S-polarized **1023**. The S light is not diffracted by the SBG and therefore continues to undergo TIR. On the next reflection at the QWF film the light is converted to P polarized light **1024**, which is off-Bragg with respect to DIGI-I and so does not get diffracted back towards the HBE. The TIR of the beam then proceeds onto the DIGI-O grating where it is progressively extracted from the waveguide as described above.

(114) In one embodiment the two stacked DIGI-I gratings may be provided in each DigiLens waveguide to increase the angular bandwidth. FIG. **9** is a chart showing the effect of combining the individual DE angular bandwidths to create upper and lower FOVs of approximately 15 degrees (FWHM) in air using two gratings of angular bandwidth 8.5 degrees (FWHM) in air. In other embodiments of the invention the DigiLens could comprise more layers, for example 3 DIGI-I layers combined with 2 DIGI-I layers in each waveguide. Note that DIGI-I and DIGI-O gratings do not need to be co-planar. However in fabrication terms it is advantageous to limit the number of grating, substrate, electrode layers and low index material layers to minimize material costs and process steps.

(115) FIG. **10** shows the HBEs in cross section in relation to the DigiLens **170**. There are two HBE waveguides **171**, **172** each comprising 3 stacked gratings (HBE-I1A-C and HBE-I2A-C) and two lossy output gratings (HBE-O1A-B and HBE-O2A-B). The HBEs are coupled to the DigiLens **170**. Two IINs (IIN1 and IIN2) are provided. The paths of light from the IIN to the DigiLens are indicated by rays **1030, 1031, 1034** and **1032, 1033, 1035**. Note the components are also referenced by numerals **170-183**. Each LCOS provides a FOV of 26° H $\times$ 30° V. Each HBE-I contains three gratings that operate on P-polarized light in 8.5° ABW steps to provide the 26° half horizontal field. The 30° field will couple in its entirety owing to the much increased ABW in the sagittal plane. The HBE-I SBGs are thick gratings allowing high DE but narrow ABW. There are two HBE-I implementation options to be considered: firstly, 26° H sampled by 2 HBE-I gratings, which gives lower DE, higher duty cycle SBGs; or, secondly, 26° H sampled by 3 HBE-I gratings, giving $3 \times 8.5^{\circ}$ angular bandwidth. This gives higher DE, lower duty cycle SBGs. The gratings are typically of thickness 1-2 micron and lossy such that light is extracted with uniform efficiency along the length of the grating. Lossy gratings have large ABW and low DE. The gratings of HBE-I1 and HBE-I2 do not need to be complementary (i.e. chromatic dispersion correcting). Gratings of HBE-I1 and HBE-O1 (as well as HBE-I2 and HBE-O2) need to be complementary. In a passive HBE-I a single unswitched grating needs to be thin to achieve higher angular bandwidth. With current materials roughly 30% peak DE with current materials, and 60% is within the range of expected material improvements may be achieved. In the case of a switching HBE-I a thicker grating of reduced angular bandwidth may be afforded. With current material refractive index modulations, the angular bandwidth approximately halves and DE doubles as grating thickness is increased from 1.4 to 2.0 micron. Typical DE and ABW characteristics of thin and thick SBGs are summarized in the table in FIG. **11**.

(116) FIGS. **12-13** provide a walkthrough of the process of projecting image light from one (left eye) IIN into the eyebox providing $\pm 15^{\circ}$ vertical and 0° - 26° horizontal field of view. The components are identical to the ones shown in FIGS. **3-4**. FIG. **12A** illustrates the path **1040** from the LCOS panel to the output of the IIN. FIG. **12B** shows the light path through the HBE indicating the TIR path **1042** within one of the waveguides and light extraction **1043** along its length. FIG. **13A** shows the coupling of light **1044** extracted from the HBE into the DigiLens (via DIGI-I). Finally FIG. **13B** shows the downward propagation of light **1045** in the DigiLens with the output image light **1046** providing the lower half of the FOV.

(117) FIGS. **14A-14C** shows three 3D views of the above invention implemented in a HMD **190**. Three different perspectives **191-193** are shown. The display module includes a horizontal hinge **194**. In the deployed position, the user will have full panoramic see-through with high

transparency. In the stowed position, the user will be free to use range finders, night-vision systems, or other such equipment. As indicated in the drawings spectacle wearers are accommodated and the design will can also accommodate the use of Polaroid eyewear. In an alternative embodiment a simple display retracting mechanism allows the display to be hidden in a compact module under the brow of the helmet when not in use. In yet another embodiment of the invention the display when not in use is retracted vertically into the helmet. The currently preferred implementation uses a custom helmet is linked to a belt pack via an umbilical fiber-optic communications link and power supply connection. In training applications the belt pack would be wirelessly linked to the training center.

(118) An important feature of the optical design is that the gratings used in one or both of the HBE and DigiLens will have a tailored DE profile achieved by varying the thickness of the gratings along the propagation direction as shown in FIG. **15**. The wedge grating **203** is provided by including a small wedge in of the grating substrates **201**. The second substrate **202** may be rectangular. Other ways of achieving wedge gratings will be apparent to those skilled in the art of optics. Where two stacked gratings are used the DE profiles of the two gratings would run in opposing directions. Desirably, the grating thickness may vary from 1.0-1.2 micron up to 2.8-3.0 micron, the lower thickness producing the largest bandwidth **1052** and lowest DE for a given output direction **1053**. The higher thickness produces the lowest bandwidth **1050** and higher DE for a given output direction **1051**. Note that the wedge angles are tiny and will have minimal impact on illumination uniformity and image quality.

(119) A refractive index of approximately 1.585 is needed to support waveguide TIR angles typically not greater than 70° with respect to the TIR surface. In general it is desirable to limit the use of higher angles within the waveguide to avoid low numbers of interactions of the ray bundle with outcoupling grating which creates gaps in the waveguide. Higher angles (approximately) 85° can lead to image fold over where gratings are designed to provide very high angular bandwidth. Polycarbonates will enable a TIR angles up to approximately 72° .

(120) While a monochrome display can be achieved with mostly passive grating components, in the case of a full color display HBE-I and HBE-O and the DigiLens input gratings DIGI-I are active with the only passive grating being the output grating DIGI-O. A further difference between monochrome and color HMDs is that in the latter separate waveguides are used in the HBE and to cover red and blue/green wavelengths. FIG. **16** illustrates a DigiLens used in an embodiment of the invention for color displays comprising two DigiLens doublet waveguides. Each doublet waveguide is similar to the embodiments of FIGS. **6-7**. However, in each DigiLens waveguide doublet one of the waveguides operates on red light and the second one operates on a mixture of blue and green light. Note also that in each doublet, the red grating is placed after the B/G grating, i.e. closer to the eye. The input and output DigiLens gratings are represented by DIGI-IR and DIGI-OR in the case of the red doublet and DIGI-IB/G and DIGI-OB/G in the case of the blue/green doublet. The output grating portions of the waveguides sandwich a HWF. The input grating portions may sandwich an air gap as illustrated or preferably a low index material. QWFs are applied to the opposing face of the waveguides in each doublet. The components are also labelled by numerals **210-227**. The red and blue/green waveguides are optically separated by air or a low index (near unity) material such as mesoporous silica which are not illustrated but will be described later. A HWF converts the rear output from P to S. As SBG gratings are P-sensitive, this prevents re-coupling of the light with gratings in front. The rake angle) ($8-10^\circ$) affords higher angular bandwidth, and lower chromatic dispersion enabling shared blue/green gratings. In most cases color imaging may need high index substrates and special coatings for enhancing the blue TIR angular range.

(121) The ray paths for red light are indicated by the rays **1071**, **1073**, **1075**. The ray paths for the blue/green light are indicated by **1070**, **1072**, **1074**. As shown in the drawing, some of this light will couple into the second waveguide doublet, that is the light paths indicated by **1076**, **1078**

(blue/green) and **1077,1079** (red). The risk of light diffracted from the rear waveguide interacting with the light on the layer above and coupling back into the waveguide is avoided in our HMD design. The red and blue/green gratings do not cross-couple due to the polarization management. Each color channel can cross couple with itself. However, this is mitigated by TIR occurring in the forward grating and reciprocity ensuring that outcoupling is in the correct output direction. The offset of the front and rear out-coupled beams due the staggered path helps to homogenize the output light. The effects on throughput of light getting re-coupled back into the DigiLens® are negligibly small. To provide immunity from grating coupling a HWP can be introduced at one layer in the passive waveguide stack. A half wave retarder layer converts the rear output light from P to S. The SBG gratings are P-sensitive only, and so this prevents re-coupling of the light with gratings in front. A 10° rake angle alleviates demands on grating prescription affording higher ABW and lower chromatic dispersion. This enables shared blue/green gratings. However, in most embodiments of the invention red may need a separate grating.

(122) The graph in FIG. **17** shows calculated DE versus angles for each grating and the output DE for the layer minus the light coupled back into TIR. It is assumed that this light is not coupled back out again. The composite output of the gratings including the single interaction coupling loss is represented by circular symbols. Note that with the 2*1/e offset of the peak DE profile, and accounting for re-coupling effects of the rear grating into the front grating, that an effective doubling in the FWHM of a single grating is achieved. With secondary output coupling of re-coupled light, the profile will approach the lossless composite grating profile (triangular symbols).

(123) FIG. **18** shows a further embodiment of the invention for color image. The DigiLens comprises two separated monochromatic doublet waveguides **230,231** one for red (DIGI-O1A, DIGI-O1B) and one for blue-green (DIGI-O2A, DIGI-O2B). The input SBGs (DIGI1A-1D, DIGI2A-2D) comprising a stack of four monochromatic red or blue-green gratings indicated by A-D. In all other respects the architecture is very similar to the embodiment of FIG. **16**. HWF and QWFs are disposed as in FIG. **16**. The doublets may be air separated or may sandwich a low index material. The components are also labelled by the numerals **230-246**.

(124) In an alternative embodiment of the invention similar to the one of FIG. **1** shown in FIG. **19** each DigiLens waveguide comprises a single SBG layer that supports red, green and blue TIR. Starting from the IIN the paths are illustrated by numerals **1080,1082, 1083** in the first waveguide **250** and **1081,1084,1085** in the second waveguide **251**. In each case the red, green and blue paths are referenced by characters R,G,B. The system components are labelled as in FIG. **1** and additionally referenced in FIG. **19** by the numerals **250-258**. It should be appreciated that such an implementation of the invention needs careful control of the TIR angles to ensure that the diffracted light paths for the three colors overlap exactly. The inventors have found that additional coatings may be needed to improve the reflection at the blue end of the spectrum. In an alternative embodiment of FIG. **19** the DIGI-O gratings could be implemented as a multiplexed grating.

(125) An IIN design for use with the invention is shown in FIG. **20**. The optical system comprises a waveguide **260** containing overlapping SBG elements **261,262**, overlapping SBG elements **263,264** a beam splitter layer **265** a curved mirror **266**, a prism **267** a projection lens **268** and a microdisplay panel **269**. An air gap **270** between the curved mirror elements is provided to enable TIR of reflected light. As illustrated separate SBG input and output gratings are provided for each image field. The waveguide **260** and the gratings **263,264** in particular may provide the input gratings of the HBE. Alternatively it waveguide **260** may be used to couple light into the input grating of the HBE. It should be appreciated that the IIN may be configured in many different ways to satisfy constraints of space, cost and optical efficiency. In the embodiment illustrated half the image from the microdisplay is imaged into the HBE sequentially. Hence in FIG. **20A** the gratings **261, 264** are in their active state and the others are inactive. Light from the image portion **1090** is projected into the path **1091** by the projection lens. It is then reflected by the prism into the ray path **1092** reflected at the curved mirror **266** into the path **1093** diffractive by grating **261** into the path **1094**

undergoes TIR into the path **1095** and is diffracted out of the waveguide by the grating **264**. FIG. **20B** illustrate the light paths from the second image field **1097**. Now the gratings **261,264** are switched to their inactive states and gratings **262,263** are switched to their active states. The path from the microdisplays is indicated by **1098-1104**. In some embodiments of the invention the IIN couples the entire image into the HBE. However, splitting the input image into two enables more optimal coupling of the image into waveguide paths. In the following discussion also consider monochrome implementations only. Initial design calculation by the inventors show that the fundamental approach is sound, meeting near diffraction limited performance across the field in a compact design form while including features such as projected pupil (20 mm. ahead of the grating coupling point), telecentricity, a re-imaged stop and less than 2% geometric distortion. The design wavelength for the monochrome implementation of the IIN is 532 nm. The resolution is matched to 1080p LCOS vertically (LCOS pixel pitch: 2.8 micron; Nyquist frequency 178 lp/mm.). Note that a feature of the design is that IIN/HBE can be located on the same side of the waveguide as the eye without compromising grating reciprocity.

(126) Light is projected from each LCOS at F/2.8 (focal length: 5.65 mm.) to provide a FOV of 26° H×30° V. Light enters the HBE-I grating at angles from 0° to +26°. The IIN is inclined at angle of 13°. For a typical 0° (input)/52° (in glass) grating, angular this increases angular bandwidth is increased by approximately 20%. Note that red colored rays in FIG. **13** strike the HBE-I at 0°, and diffract into TIR. The green colored rays strike the SBG at approximately 26°/n where the refractive index n is 1.592 (polycarbonate). Note that S-BAL25 glass which has a very similar refractive index to polycarbonate can be used for prototyping. The design can be extended to two and three colors. Initial results show that the fundamental approach is sound, meeting near diffraction limited performance across the field in a compact design form while including features such as projected pupil (20 mm. ahead of the grating coupling point), telecentricity, a re-imaged stop and less than 2% geometric distortion. The design wavelength is 532 nm. The resolution is matched to 1080p LCoS vertically (LCOS pixel pitch: 2.8 micron; Nyquist frequency 178 lp/mm.). Preliminary specifications for the IIN are provided in Table 2.

(127) TABLE-US-00002 TABLE 2 Input Image Node (IIN) Specification. Input Image Node (IIN) Optical Specification Glass Polycarbonate (can use S-BAL25 glass for prototyping). Image Format LCoS aspect ratio of 3:2 in portrait. Pupil Diameter 2 mm. projected pupil (20 mm. ahead of the grating coupling point) LCoS Projection Lens FOV of 26° H × 30° V; F/2.8; focal length 5.65 mm. Color Monochrome 532 nm. (proof-of-design); extendable to color. Resolution Near diffraction limited across the field; matched to 1080p LCoS vertical pixel pitch: 2.8 micron; Nyquist frequency 178 line pair/mm.). Geometric Distortion <2%. Telecentricity Fully telecentric.

(128) In one embodiment there is no hard physical stop in the projection optics but instead a projected stop is provided. The benefits of a projected stop are decreased waveguide thickness. In one embodiment the stop is projected midway up the HBE to minimize aperture diameter within the waveguides, and hence minimizing the aperture width of the DigiLens waveguide coupler.

(129) In one embodiment a graduated reflection profile underneath the SBG layer is used to control (or assist) with grating DE variation along length of the DigiLens waveguides. This normally achieved in SBG grating using index modulation. This may offer advantages the HBE where a low percentage of light is out coupled in 1.sup.st bounce, but high percentage is coupled out at the other end of the waveguide.

(130) The volume of the IIN design is currently×20×40 cubic mm. However, it will be clear from consideration of the drawings that there are many different ways to reduce the overall volume of the IIN design. For example the refractive elements of the design such as the bird bath mirror and the projection lens system could be replaced by diffractive optical elements. An SBG waveguide could be introduced in front of the microdisplay to provide a polarizing grating beamsplitter for illuminating the microdisplay and allowing polarization rotated reflected light to proceed through said wave guided towards the curved mirror.

(131) In one embodiment illustrated in FIGS. **21-22** a HBE **281** comprises a coupling grating **283** (e.g., the HBE-I of the earlier embodiments) at its input end and an output grating (e.g., the HBE-O) comprising alternating SBG stripes of two different prescription **284, 285** inclined at typically 45 degrees. Although the stripes are shown as equally spaced their size and spacing may be varied for better illumination and image sampling control. However, making the strips too narrow may degrade the system MTF. In general the stripe geometry may need careful optimisation. FIG. **22** shows the HBE integrated in a display with a DigiLens **287** comprising DIGI-I **288** and DIGI-O **289** and an IIN **286**. The ray paths from the IIN are indicated by **1105-1110** where the TIR paths in the HBE and DIGI-O are indicated by **1107,1109**. The light coupled output of the HBE into the DigiLens (DIGI-I) is indicated by **1108**. The output light from display from the DIGI-O is indicated by **1110**.

(132) FIG. **80** provides a transparent waveguide display in another embodiment. In this embodiment of the waveguide **8001**, the amplitude of the refractive index modulation in at least one of the input grating **8003** and output grating **8002** varies by a small amount along the x direction. In this embodiment, the input and output grating pitches should be identical to satisfy the reciprocity requirement. The index modulation may also be varied in the z direction. In one instance, the design of this embodiment may help control the output light homogeneity, The principles illustrated in this embodiment may be applied to the vertical and horizontal beam expanders. In one instance, where switchable gratings are used the index modulation may be time-varied to adapt to temporal variations in the input image content.

(133) In any of the embodiments of the invention efficient waveguiding may need that the TIR beams are confined between low index media. Air gaps are difficult to fabricate and maintain while the refractive indices of currently available low index materials such as Magnesium Fluoride (1.46) and Silicon Dioxide (1.39) are much too high to meet the tight TIR angle constraints needed in full color implementations of the HMD. The proposed solution is to use nanoporous (Mesoporous Silicon) materials. Nanoporous materials (e.g., mesoporous Silicon) are currently being used in many optical applications including anti reflection coatings and planar optical waveguides. Their high porosity enables the fabrication of high-quality low-dielectric constant thin films. Nanoporous materials can be fabricated in thin layers in a single coating step. To achieve very low, near unity, index the porosities need to be very high, approaching 95%. High transparency and low index can be achieved simultaneously with these films. Since they are highly efficient at absorbing water they must be carefully sealed against moisture. The best approach may be to seal the passive gratings, HWP and material together. SBG Labs is also investigating the potential role of nanoporous materials as high refractive index media. This would increase the range of TIR angles that can be sustained in our waveguides with potential for increasing the horizontal FOV from 40° to around 45°. Nanoporous materials are currently being used in many optical applications including anti reflection coatings and planar optical waveguides. It is reasonable to assume therefore that the technology will be accessible for our project. The manufacturing process should be translatable to specification desired. Nanoporous materials can be fabricated in single coating step. Alternatively graded index multi layer architectures can be used. SBG Labs is also investigating the potential role of nanoporous materials as high refractive index media. This would increase the range of TIR angles that can be sustained in our waveguides. In summary the chief benefits are a monolithic structure will provide greater mechanical stability and durability and better beam confinement leading to higher FOV.

(134) Embodiments for Automotive HUDs

(135) As already discussed, the invention may be used in many different applications. Some embodiments of the invention directed specifically at automobile HUDs will be discussed in the following paragraphs.

(136) FIG. **23** is a schematic side elevation view of an in car HUD **300** with more than one exit pupil integrating DigiLens waveguides for the driver **301** and passenger **302**. The display may be

based on any of the embodiments described above. The DigiLens elements are integrated within a common waveguide structure with the input imagery being produced by an IIN **303** as described above. The ray paths to the driver exit pupil are indicated by the rays **1110-1113** with the pupil indicated by **1113**. The ray paths to the passenger exit pupil are indicated by the rays **1114-1116** with the pupil indicated by **1117**.

(137) FIG. **25** is a schematic side elevation view of a show an embodiment of the invention similar to the one of FIG. **23** the exit pupil of the driver display is tiled using multiple overlapping DigiLens elements **305,306** to provide the abutting exit pupils **1120,1121**. Ray paths to the pupil are indicated by **1118-1120**.

(138) FIG. **25** is a schematic side elevation view of a further embodiment of the invention based on the one of FIG. **23** in which overlapping DigiLens elements **311,312** are used to tile the FOV as indicated by **1131** with the abutting field of view tiles **1132** while providing a common exit pupil **1133**.

(139) In one embodiment waveguide a DigiLens may be used to form a pixelated collimated image. A simple classical analogue of such a display which is shown in the schematic side elevation view of FIG. **26** comprises a pixelated display panel **321** located at the focal surface of a collimating lens **320**. A waveguide holographic version of this display is shown in FIG. **27**. The input image is provided by a pixelated SBG **323** comprising a two dimensional array of switchable elements such as the one labelled by **324**. Each element diffracts incident collimated light into a TIR path within the waveguide. The SBG array is illuminated by collimated light indicated by **1142,1143** from an external source which is not shown. The pixel **324** is illuminated by the collimated light **1145**. Advantageously, the SBG pixels will have diffusing characteristics. The DigiLens elements **325,326** are not simple planar gratings such as the ones described so far but have optical power such that light originating at points on the surface of the SBG array is collimated to provide switchable fields of view (FOV tiles) bounded by the rays **1146,1147** for viewing through a pupil **1148**. Hence the DigiLens elements provided a diffractive analogue of the lens in FIG. **27**. The DigiLens elements are configure to tile the FOV as in the embodiment of FIG. **25**.

(140) In one embodiment a DigiLens as described above may be configured to provide a mirror. FIG. **28** shows how a rear view mirror for automotive applications can be provided using transmission SBG **333** sandwiched between the substrates **330,331** and a mirror coating **332** overlaying the DigiLens. The SBG diffraction angles are designed such that light incident on the DigiLens following the path labelled by R1,R2 is diffracted by the SBG layer and reflected at the mirror layer while that the reflected path labelled R3,R4 leading to the drivers eyebox is off Bragg or in other words falls outside the angular range for diffraction by the SBG. The light paths are also labelled by the numerals **1151-1154**. It should be apparent from consideration of FIG. **28** that the DigiLens can be configured to provide a range of different reflection angles by a suitable choice of grating prescription.

(141) FIG. **29** shows a HUD **335** for relaying an external image to a viewing pupil near to the driver. Light **1155** from the external image source enters the waveguide via the DigiLens **338** undergoes TIR as indicated by **1156-1157** and is coupled out of the waveguide towards the viewer as light **1158** by DigiLens **336**. This embodiment may be useful for viewing blind spots. The apparatus of FIG. **29** further comprises a beam splitter layer **337** which by splitting incident TIR light into multiple paths, can improve homogeneity and eliminate gaps in the output illumination. This principle may be applied in any of the other embodiments of the invention.

(142) FIG. **30** is a front elevation view of a car HUD **340** comprising a IIN **341** and a DigiLens **342** according to the principles of the invention and further comprises a structured light source **343** emitting infrared light **1159** and detector **344** for detecting return infrared light **1159** for sensing driver hand movements for display control.

(143) FIG. **31** is an embodiment of the invention similar to that of FIG. **26** in which the information contained in the field of view tiles (FOV Tile1,2) is presented at different ranges indicated by

D1,D2. Image light from the IIN **351** is converted into wave guided light **1170**. The DigiLens **354** forms an image at range D2 with an FOV of **1174** centered on the direction **1173** and the DigiLens **355** forms an image at D1 with FOV of **1171** centered on the direction **1172**. The two FOV tiles are viewed through the pupil **1175**.

(144) In most applications of the invention the preferred light source is a laser particular where tight constraints on collimating and waveguide confinement need to be met. However, the invention may, with some modifications, be applied using LEDs and other relatively narrow band incoherent light source. FIG. **32A** illustrates an embodiment of the invention in which SBGs are used to compensate for the spectral bandwidth of RGB LEDs in a color HUD. The red LED illustrated has a peak output at 639 nm, and FWHM bandwidth defined at the wavelengths 634 nm, and 644 nm. as shown in FIG. **32B**. The DigiLens comprises a stack of RGB diffracting layers, each layer comprising input and output gratings. In each layer the SBGs are recorded to provide peak diffraction efficiency vs. wavelength characteristics (along the waveguide) shifted by small increments from the peak wavelength as indicated in the Table in FIG. **32C**. The techniques for recording a Bragg grating that provides a wavelength shift in play back, which normally involve control of the construction wavelengths and recording angles, are well known to those skilled in the art of holography. The RGB SBG layers are switched sequentially and synchronously with the RGB LEDs. As shown in FIG. **32A** the color display **360** comprises red green and blue DigiLens waveguides labelled by the symbols R, G,B and comprise DIGI-I gratings indicated by **360R,360G,360B** and DIGI-O gratings indicated by **361R,361G,361B**, red, green and blue light sources **362R,362G,362B** providing light **1180** a microdisplay **363** a beam expander comprising the diffractive or holographic lenses **364,365** for providing collimated light **1182**. After being coupled into the DigiLens elements the light undergoes TIR as described above and represented by **1183** and is diffracted out of the DigiLens as the red, green, blue light **1184R, 1184G, 1184B**.

(145) In one embodiment illustrated in FIGS. **33-34** the DigiLens is combined with a windscreen. A DigiLens is eminently suitably for such an implementation as it can be designed to operate in a curved waveguide and can be built up from very thin layers using substrates as thin as 100 microns sandwiching SBG layers of thickness 1.8-3 microns. The DigiLenses are separated by thin layers of mesoporous materials of the type described above. It should also be noted that typical car windscreens have radii of curvature typically of several thousand mm which does not present a great challenge for maintaining waveguiding.

(146) In one embodiment the DigiLens is formed as a flexible layer **371** that can be bonded onto an existing windscreen **370** to the inner or exterior surfaces as shown in FIG. **33**. The IIN **372** would typically be located below the dashboard.

(147) Alternatively, the DigiLens layers can be integrated within a windscreen as part of the screen fabrication process as shown in FIG. **34**. Typically, a windscreen comprises an outer toughened glass layer **373**; two or more layers of PVB **374,376** for UV blocking and an inner toughened Glass layer **377**. The DigiLens **375** would be sandwiched by two of the PVB layers. In one embodiment the windscreen integrated DigiLens fabrication processes includes the steps of spraying RMLCM onto PVB film and sandwiching it with a second PVB film prior to recording an SBG in a holographic recording step.

(148) In one embodiment shown in FIG. **35** there is provided a transparent display comprising the waveguide components DIGI-I. DIGI-O HBE-I, HBE-O and an IIN similar to the ones described above. However in this case each said waveguide component comprises a single SBG layer. Note that only the SBG layers in the above waveguides are illustrated with the substrates and electrodes being omitted. The ray paths from the IIN are indicated by **1200-1203** include the TIR path in the HBE **1201**, the extraction of the expanded beam from the HBE **1202**, TIR within the DigiLens **1203** and extraction of light for display **1204** from the DigiLens. The components are also reference by the numerals **390-394**.

(149) In one embodiment shown in FIG. **36** there is provided a transparent display DIGI-O, HBE-I

and an IIN similar to the ones described above. The two waveguide components HBE-O and DIGI-I are combined into a single waveguide component labelled HBE-O/DIGI-I that performs the dual functions of beams expansion and beam turning. The advantage of this arrangement is the change in beam direction is accomplished without the need to exit and then re-enter the waveguide gratis as for example in FIG. 35 and most of the other embodiments. This may need that the grating in the DIGI-I is slanted in the plane of the drawing, in most cases of practical interest at an angle of 45 degrees. Hence within the DIGI-I waveguide the TIR path is rotated through 90 degrees and proceeds into the DIGI-O. The ray paths from the IIN are indicated by **1205-1208**. The components of the displays are also referenced by the numerals **400-403**.

(150) It should be apparent from the drawing and early description that in this case and indeed in most of the embodiments of the inventions the HBE-I and HBE-O and the DIGI-I and DIGI-O may be implemented in a single SBG layer. However while this reduces the number of layers overall there is the penalty the overall size of the display will increase. The widths of the HBE and DIGI-O will to a large extent be terminated by the microdisplay dimensions and the field of view needed. While in HUD and HDD applications the space needed to implement the DIGI-O and HBE components are small relative to the size of the DIGI-O, the trade-off becomes more challenging in HMD and near eye applications which will use similar size microdisplays and will have more demanding FOV demand, which will further increase the relative widths of the HBE and DIG-I waveguides.

(151) In a further embodiment of the invention directed at a color display illustrated in FIG. 37 the DigiLens comprises separate red green and blue waveguides. Advantageously the waveguides are optically isolated from each other which may need that they are air separated or separated by thin layers of low index film. The preferred option is to use nanoporous materials. The DigiLens waveguides are shown in FIG. 37 the layers being referenced by numerals 1-3 in the DIGI-I and DIGI-O labels (the waveguide components also referenced by numerals **415-420**). The IIN and HBE components are not shown in detail but are simply indicated by **421**.

(152) Typically the DigiLens will be inclined at a rake angle of around 10° to enable the most favorable diffraction angles within the waveguides as shown in FIG. 1. The IIN and HBE may be on the side of the display nearest the eye **422** as shown in the drawing. However it should be apparent that many other configurations are possible. A ray path to the eye is indicated by the rays **1210-1212**. FIG. 3 is a three dimension view of the same display shown the three DigiLens lenses.

(153) FIG. 38 shows a color display based on the embodiment of FIG. 35. This implementation has three DigiLens layers **410-412**, one for each color, with the DIGI-I and HBE-I being combined in turning/beam expansion gratings such as the ones indicated by **436**. Red green and blue ray paths from the IIN are indicated by **1220-1223** with red, green and blue being labeled by the symbols R,G,B. Note that the HBE-I component which is not illustrated will be similar to the one shown in FIG. 35 but with separate layers for red, green and blue.

(154) In auto HMDs fields of view are relatively modest compared with those of HMDs a field of view of 10 degree vertical by 25 deg. horizontal is considered to be a long term goal. Such angular content can easily be handled by a waveguide using a single layer SBG. However since there is interest in color this will make further demands on the information handling capacity of the waveguides. In one embodiment shown in FIG. 39 there is provided a passive single SBG layer DigiLens which waveguides and diffracts at least two colors using holographic multiplexing. Multiplexing is the ability to record multiple Bragg gratings in the same layer. Firstly it can be used to produce improved angular profiles by combining two gratings of similar prescription to extend the diffraction efficiency angular bandwidth and giving better luminance uniformity and color balance across the exit pupil and field of view. Secondly multiplexing may be used to encode two distinct diffraction prescriptions which may be designed to project light into distinct fields of regions or diffract light of two different wavelengths into a given field of view region. Multiplexing also offers the significant benefit of reducing the number of layers in the waveguiding structure. Care is

needed to ensure that there is no competition between gratings during recording leading to unequal Des and cross talk between gratings in playback. The apparatus of FIG. 39 is similar to that of FIG. 35 differing mainly in that the DIGI-O component is now a multiplexed grating. The components are also referenced by the numerals 470-474 and ray paths from the IIN through the HBE and DigiLens by numerals 1240-1243. Advantageously, the Horizontal Beam Expander (HBE) would run along bottom edge of the DigiLens® to enable the IIN to be hidden below the dashboard. Typically such a HUD would have an eyebox of 145 mm. horizontal by 80 mm. vertical at an eye relief of 800-900 mm. The target field of view would be 10°-15° vertical×10°-15° horizontal. The windscreen would have a transparency greater than 75%. Typically windscreens have curvature of Horizontal: 3000 mm.; Vertical 9000 mm. The IIN could be accommodated within a volume of 1-2 litres.

(155) The integration of the DigiLens into the windscreen is shown in FIG. 40. The stack of layers in the windscreen comprises Glass (External) 1.60 mm.; PVB (3 layers): 0.8 mm.; Glass (Internal): 2.0 mm. TOTAL 4.4 mm. The SBG layer would comprise an SBG of 5 microns sandwiched by substrates of 50-100 microns, the SBG cell sandwiched by low index layers of 0.5-2 microns thickness. A UV glue gasket line limits the SBG material fill, bounding the effective area of the display. Gaps between grating areas are filled with clear acrylic and UV-cured for full transparency. This multilayer architecture allows very strong lamination and does not rely at all on the SBG film for lamination strength. FIG. 41 is a follow chart illustrating the implementation of the embodiment of FIG. 39 in an automobile HUD.

(156) The color multiplexing used in the embodiment of FIG. 39 can be provided in two ways: firstly using two multiple gratings: for example, red and blue/green diffracting; or secondly using three multiplexed gratings: i.e. using multiplexed red green and blue gratings. The design problem is to determine the optimal prescription using two or more multiplexed gratings for a vertical (or more precisely tangential plane) field of 10 degrees. The design variables are Bragg wavelengths and TIR angles for each color; DE profiles (i.e., grating thickness and modulation. Since the DigiLens will be bonded to or in some cases embedded with a windscreen the waveguides will be sandwiched by low index material (unless air gaps can be tolerated). A nanoporous material layer refractive index of 1.2 has been assumed. For an SBG index of 1.52 this corresponds to a minimum TIR angle of 52 deg. In designing a multiplexed grating special attention may be needed to achieve the shape of the DE profile is important and, in general, narrower DE profiles are preferred to avoid crosstalk between the colors. The desired DE profiles can be achieved by optimizing the thickness and refractive modulation of the gratings. Simulated diffraction efficiency (DE) versus TIR angle profiles based on the Kogelnik diffraction theory for typical red, green and blue diffracting gratings multiplexed in a single SBG layer are shown in FIGS. 42A-42B. The curves represent the DE profiles for each of the three multiplexed gratings. The rectangular regions represent the approximate RGB TIR angle ranges. FIG. 42A shows the case where the multiplexed grating is illuminated with red light. FIG. 42B shows the case where green or blue light illuminates the grating. Note that the curves shift owing to the angles satisfying the Bragg condition shift as the illumination wavelength changes. Since the TIR range for the blue green band is below the TIR range for red, there is no cross talk between the two color bands.

(157) FIGS. 43-44 illustrated a further embodiment of the invention comprising a IIN, two HBE components each comprising a HBE-I and HBE-O; two DigiLens components each comprising a DIGI-I, DIGI-O and beam splitter (B/S) the DIG-I sandwich a half wave film (HWF). FIG. 43 shows a three dimension view. FIG. 44 is a cross sectional view of the DigiLens only showing the ray paths. The HBE-O and DIGI-O gratings multiplex red and blue-green diffracting gratings as indicated by the solid and dashed rays respectively in FIG. 44. The red rays in the rear DigiLens waveguide 460 follow the path 1231, 1232, 1239. The blue-green rays in the same waveguide follow the ray path 1230,1233,1239. The ray paths in the forward waveguide are labelled by the numerals 1234-1237. The rear and forward waveguide components are referenced by numeral 1,2

respectively and are also referenced by the numerals **440-447**. The HBE comprises two waveguiding element (i.e., two switchable SBG layers separated by suitable substrates) each supporting 20 degrees horizontal x 22.5 degrees vertically. The HBEs are switchable. Each HBE waveguide is separated from the other by a low index layer. The IIN would use a HD 1366×768 (0.37" diagonal LCoS microdisplay such as the one supplied by Himax Inc. An alternative microdisplay is the Syndiant 720P (0.37" display) supplied by Syndiant Inc. This would give a resolution of 1.76 arc min/pixel (over the full 40 degree×22.5 degree FOV). Each grating provides approximately 10 degrees in air (equivalent to about 6.5 degrees in glass) of angle width for a single color. There is a slight bias of angular space due to the HBE rake angle (on side entry of IIN) which causes the fields to be slightly unequal e.g. 18 degrees and 22 degrees Note that switching of gratings adjacent in angular space ensures cross coupling will not occur between adjacent gratings. Angles in each waveguide are minimized. Green is arranged close to TIR angle with a small tolerance margin (e.g. +0.5 to 1.0 degrees). Each waveguide is narrowband blue mirror coated to extend the waveguide angular range. The light output from each HBE into the DigiLens is: -20 to 0 degrees horizontal (approximately) x±11.25 degrees vertical; and 0 to +20 degrees g horizontal (approximately) x±11.25 degrees vertical. This gives a composite field is -20 to +20 degrees horizontal x±15 degrees (i.e., 40 degrees×22.5 degrees). The preferred material is polycarbonate (n=1.585), or equivalent. The substrate thickness is 0.5 mm. Each cell is 1.0 mm thick, so that each HBE waveguide is 2.0 mm thick. Both HBE waveguides are 4.0 mm thick with a small air or low index material gap. The HBEs would be multiplexed for color as discussed above. The HBE dimensions are: 70 mm in width×11 mm in height. Note that the height includes a 1 mm margin on vertical edges. The IIN used in the embodiment of FIGS. **43-44** has a focal length of 1.3 mm. The microdisplay (LCoS) pixel pitch is 6.0 micron. The optics F-number is 4.6. By matching the Airy disc to LCOS pixel pitch, approximately 75% contrast at the Nyquist limit is obtained. The aperture of the IIN is 2.4 mm. The optical design of FIGS. **43-44** may need two DigiLens waveguides (i.e., two SBG layers separated by suitable substrates), each supporting 11.25 degrees vertical×40 degrees horizontal. The input DIGI-I elements would be switchable. The DIGI-O elements would be passive. Both input and output gratings would be multiplexed red and green-blue gratings as described earlier. The dimension of DigiLens substrate is 50 mm width×61 mm height. In one embodiment the input gratings are switchable, and not multiplexed, that is four switchable input gratings are used in this case. Importantly, the input and output prescriptions are reciprocal. The input light must be P-polarised (since the DigiLens only diffracts P-polarised light). Each waveguide has a QW film down full length: This permits a 2× thinner waveguide. TIR reflections are rotated by a half wave (owing to the double pass through the QW film). Ray extraction from the waveguide thus occurs only at every other interaction with SBG. The output of the rear DigiLens (i.e., the one nearest the IIN as shown in FIGS. **43-44**) experiences two QW film interactions, rotates to S and therefore does not interact with the forward DigiLens. Hence the output from the display is mixed P and S polarized light.

(158) In one embodiment illustrated in FIGS. **45-52** there is provided a transparent display based on completely passive HBE and DigiLens waveguide components. As will be explained in the following description this embodiment uses a HBE-I configured for sampling the aperture and/or FOV of the image light from the IIN. This embodiment will now be described with reference to a 52 degree×30 degree FOV monochrome display such as may be used to provide a HMD. However, it should be apparent from the following description and drawings that this embodiment may with the benefit of the teachings presented herein be used to provide a wide range of different FOVs.

(159) An Embodiment Using all Passive SBGs

(160) FIG. **45** is a three dimensional illustration of an embodiment of a display in one embodiment in which there are provided three HBE waveguides and three DigiLens waveguides. The HBE waveguides are indicated by numerals **541** and the DigiLens waveguides by **542** with the HBE waveguides being labelled by symbols W-Z as before and the DigiLens waveguides by symbols P-

R. Each HBE waveguides contains a HBE-I and HBE-O also referenced by **543,544** respectively and each DigiLens contains a DIGI-I and a DIGI-O also referenced by **545,546** respectively. The IIN is indicated by **394**. A ray path from the IIN through the HBE waveguide **541Z** and DigiLens waveguide **542R** is shown using the rays **1330-1334**. Note that the pupil; has been combined before the DIGI-I so that the full 52 degree horizontal x 30 degrees vertical FOV exist at this stage.

(161) One embodiment is related to a projected stop. FIG. **46** is a schematic side elevation view showing the formation of a projected stop by the IIN. Light from an image pixels at the center and edges of the image displayed on the microdisplay **500** passes through a stop **502** to provide the marginal beams **1300,1302** and the on axis beam **1301**. The projection lens **501** collimates this light to provide the collimated beams **1303-1305** which overlap at the projected stop **1306**. Light from other points in the input is similarly converged into the projected stop. Note that the projection optics has been simplified in FIG. **46** and in practice the projection lens will be a multi-element system as discussed earlier. As will also be appreciated by those skilled in the art of optical design the need for a physical stop **502** be minimized (or even eliminated) by limiting the numerical aperture (NA) at the microdisplay by suitable design of the illumination delivery optics. It should be noted that the distance from the lens to the projected stop is very large compared to the thickness of the HBE stack.

(162) FIG. **47** is a schematic plan view illustrating the coupling of light from the IIN into the HBE waveguide **503**. The input grating or HBE-I comprises the two gratings **504,505** having a small separation along the waveguide propagation axis. Importantly, the two gratings have substantially non-overlapping DE versus angle characteristics. The HBE-O grating is located further down the waveguide as indicated by **506**. In contrast to the input gratings the output grating multiplexed two different grating prescriptions as will be explained below. The advantage of this coupling scheme is that it enables mapping of the angular content of the input light to defined gratings areas **504,505** allowing the input gratings (HBE-I) of the HBE to be separated along the waveguide optical axis. This effect is accentuated by having small entrance pupil diameters. For simplicity illustrated herein are just two ray paths through the waveguide. In the first path an incident rays **1307** is diffracted into a first TIR path **1309** by the first grating element **504** of the HBE-I. In the second path incident ray **1308** is diffracted into a second TIR path **1308** by the second grating element **505**.

(163) The interaction of the beam with the gratings is illustrated in more detail in FIG. **48** which shows a portion of the HBE waveguide containing the input gratings of FIG. **47**. The incident ray **1307** is diffracted by the first grating **504** into the ray path **1311**. After the first TIR reflection the reflected ray **1312** is off Bragg and therefore passes through the first grating without deviation. After the second reflection the ray just skirts the trailing edge of the first grating avoiding diffraction. TIR now proceeds to the next grating. After the third reflection the ray **1314** skirts the leading edge of the second grating. After the fourth reflection the resulting ray **1315** is off Bragg. Finally, after a fifth reflection the ray **1316** skirts the edge trailing of the second grating and proceeds to the HBE-O. Clearly this simplistic explanation only applies to the chief ray and does not adequately describe the behavior of a divergent beam which will result in unwanted diffractions of rays that intercept the gratings. However, the narrow beam angles within the waveguide will reduce the impact of unwanted beam-grating intersections.

(164) FIG. **49** is a schematic cross-sectional view of the four layer HBE shown in FIG. **45**. Following the above description each waveguide layer comprises a HBE-I gratings comprising two separate gratings and a HBE-O comprise a multiplexed grating. The waveguides may be separated by air gaps or preferably by thin layers of nanoporous low index material. The input gratings are labelled by the numerals **511,512** and the output grating by the numerals **510** with the waveguide layers being referenced by the symbols W, X, Y, and Z. The drawing shows input rays from the projection lens **514** interacting with each of the input gratings in each layer. Note that the output light from waveguide layer W may interact with one or more of layers X-Z. However, as already discussed the property of grating reciprocity maintains the beam angle for any such interactions.

The result beam shifts resulting from such interlayer interactions may provide beamsplitter or homogenizer. For example, consider the input ray **1320**. This ray is diffracted by the first grating **511W** into a TIR path **1321** which propagates through the second grating **512W** without deviation and continues its TIR path **1322**. At the output grating **510W** a portion of this light is diffracted into the ray **1323** in waveguide **510X**. On entering the second waveguide a portion of this light is diffracted into the TIR path **1324** the remainder proceeding in the direction **1323**. Further interactions with the grating **510Y** are indicated by the rays **1325** and **1326**.

(165) FIG. **50** is a table showing the pairings of multiplexed gratings used in each waveguide layer of the embodiment of FIG. **48**. Each pair of gratings must have DE versus angle bandwidths with sufficient separation to avoid appreciable overlap. Since the gratings will be lossy thin gratings characterized by low DE peaks and wide angular bandwidths this separation needs to be quite large. FIG. **51** is a chart showing one possible scheme for overlapping the DE versus angle profiles in the embodiment of FIG. **45**. Each pair of gratings corresponds to a 26 degree chief ray angular separation. It is assumed that the total horizontal FOV is 52 degrees. For a thin (low peak DE, high ABW) grating the ABW is approximately 13 degrees. Assuming that the input HBE gratings have ABWs of 6.5 degrees referring to the angle ranges: -6.6 degrees to 0 degrees as A and the angle range: 0 degrees to 6.5 degrees as B. It is recognized that A and B should not be used in the same waveguide owing to: firstly, DE versus angle overlap and secondly, lack of reciprocity. The grating separations are based on the FWHM. However, other measures may provide better optimization of the overall illumination profile. For example the grating overlaps could be at the 30% of peak angles. Assuming FWHM this gives 8 gratings to span a FOV of 52 degrees (i.e., 8×6.5 degrees).

(166) Achieving high illumination uniformity is an important issue in SGO design. The chief design parameters are thickness and index modulation. As discussed earlier, applying a small wedge angle to the grating layer allows the peak DE and angular bandwidth to be tuned along the waveguide. However, the light remaining in the waveguide at the end of the propagation path will tend to accumulate at larger angles leading to uneven output illumination. At present the inventors believe that this effect may not be very significant. A more sophisticated strategy in cases where very tight illumination control is needed is to shape the grating layer by applying tilt in two directions. As a further refinement the surfaces of the grating could be curved. Since the needed grating thickness variations are very tiny typically 1-2 microns across the waveguide the effect on collimation and MTF are negligible in most implementations. FIG. **51** is a three dimensional view of an SBG grating **530** characterized by two orthogonal slants. The four different corner heights with respect the plane of the waveguide resulting from the orthogonal slants are indicated by **531-532**. However, preliminary ray-tracing analysis by the inventors has yielded some evidence that the optimal DE profile needed within the waveguide is a one dimensional function and is a function of the length of the waveguide not the number of bounces of the beam within the waveguide. The ray angle displacements (i.e., $\pm$ angles) around the chief ray) appear to need the same grating thickness profile as the chief ray (as a function of the length of the waveguide). This suggests that a 2D profile may not be needed for optimum uniformity. Note that to first order DE must scale as the reciprocal of the difference between the waveguide length and the distance traveled by the beam.

(167) FIGS. **53A-53C** are schematic illustrations of a three operational states of the HBE in one embodiment. A portion of the waveguide **551** and the projection of the IIN projection lens **550** is shown in each case with three collimate beam portions indicated by **1341-1342**. The shaded areas correspond to the HBE cross sections seen by each DigiLens waveguide for each of the three separate 10 degree vertical FOV bands coupled into one of the DigiLens waveguides to give the 30 degree total vertical FOV. The shaded areas in FIGS. **53A-53C** also show the portion of the DIGI-I that accepts light from the HBE-O for the three vertical FOV regions. Only $\frac{1}{3}$ of the aperture is collected by DIGI-I in each state. By keeping the effective aperture low in this way it is ensured that the DigiLens waveguides do not need a large thickness. It is estimated that the total thickness needed for the three DigiLens waveguides using the above aperture method (as well as the

polarization management mentioned earlier in the description) will result in an overall thickness of 6 mm. This assumes a rectangular exit pupil. If a circular pupil is acceptable the need to achieve the extreme diagonal angles is removed resulting in a lower overall thickness

(168) Although all passive grating as described above is feasible in monochrome it is likely that switching will need to be introduced to provide full color to ensure that crosstalk is overcome.

(169) It is important to note that a unique feature of the above embodiment is the way in which the HBE selectively samples portions of the input image each portion being characterized by either angular field or spatial field. This approach ensures that the waveguides in particular the DigiLens can be made very thin. This is a particularly important feature in HMDs and near eye. The process of sampling the input image described above should be distinguished from the process of switching the entire input image into the waveguides used in FOV tiling, as disclosed in earlier filings.

(170) Exemplary Features

(171) In one embodiment optical power may be provided in at least one of the gratings used in the HBE and DigiLens waveguides. The recording of lens prescriptions in diffractive optical elements is well known. In the present invention this offers potential for fine tuning the focus of the display without the need for auxiliary lenses. Such a lens could also be used for correcting aberrations. A switching hologram offers the potential for a solid state (no moving parts) solution for providing images at different ranges. This may need multiple layers. This would provide an attractive feature in HUD and HDD applications. Recording holographic lens of appreciable optical power may need careful attention to overcoming off-axis holographic aberrations. The construction optics are potentially more complicated but once a master hologram is made, the contact copy process is the same as any other hologram.

(172) In one embodiment a multilayer thin film coating is applied to a reflection surface of the DigiLens waveguide is to enhance the waveguiding range beyond the TIR range. Glasses and plastics do not allow the range of TIR angles need for large field of view. For example Rays below 39° are not supported by polycarbonate TIR (refractive index at 532 nm=1.585). The problem boils down to achieving a minimum waveguide angle 30 degree angle which is well below critical angle for plastics and low cost glasses. The coating design problem is to achieve a reflectivity coating prescription that achieves the needed reflectivity, without image degradation or loss of see-through transmission. The coating may need optimizing for wavelength polarisation, angle, scatter, Losses from absorption. One benefit of applying dielectric films on the substrate significantly reduces the amount of diffractive power needed, thereby improving grating angular bandwidth. The dielectric coating has the following characteristics: a) high reflectivity for S&P light for angles of 30° (in glass) to 39° (TIR angle). b) high transmission for $0^\circ \pm 13^\circ$ (in glass) for P-light; equates to $35^\circ \times 20^\circ$ corner fields in air; c) good angular control of reflectivity can be achieved due to narrow band nature of sources; and d) high see through for non-laser notch wavelengths on all layers.

(173) In one embodiment the input gratings in at least one of the HBE or DigiLens, i.e., the gratings HBE-I and DIGI-I, comprises stacks of gratings of different k-vectors to provided DE versus angles characteristically distributed uniformly over the range of beam angles to be transmitted through the HBE and DigiLens. Typically the gratings will be separated by 200 micron (or even 100 micron) substrates) to keep the stack as thin as possible. Ultimately, the inventors believe that the minimum practical grating stack thickness can be achieved using spin coating techniques.

(174) In one embodiment an alternative scheme of multiplexed gratings of different k-vectors avoids the need for stacking.

(175) Any of the above-described embodiments using laser illumination may incorporate a despeckler device for eliminating laser speckle disposed at any point in the illumination path from the laser path to the eyeglass. Advantageously, the despeckler is an electro-optic device. Desirably, the despeckler is based on a HPDLC device.

(176) In one embodiment the display incorporates a homogenizer that combines beam shaping and

despeckling. Desirably, the SBG array used to perform the above functions are themselves diffractive waveguide devices that can be implemented seamlessly as additional SBG layers within one or more of the waveguides or in the IIN. Despeckling is achieved by a combination of angular and phase diversity. Exemplary waveguide homogenizers are disclosed in U.S. Provisional Patent Application No. 61/796,795, entitled COMPACT LASER ILLUMINATOR INCORPORATING A DESPCKLER, with filing date of 20 Nov. 2012 and PCT Application No. US2008/001909, with International Filing Date: 22 Jul. 2008, entitled LASER ILLUMINATION DEVICE. It should be apparent from consideration of the drawings and descriptions that the invention offers several opportunities for integrating such devices within the IIN and the waveguide components of the display.

(177) The invention provides a transparent display based on a DigiLens which comprises one or more passive SBG waveguides, each one projecting a portion of the vertical field of view or a specific color. The invention is enabled by improvement in diffraction efficiency angular bandwidth obtained from using thinner SBGs and taking advantage of the intrinsically broad sagittal angular bandwidth of Bragg gratings. The invention can deliver large field of view, for example 52° horizontal x 30° vertical, without sacrificing any of the usual goals of high transparency, high resolution, ultra compact (thin) form factor, light weight and generous eyebox. The waveguide components and compact input image node are consistent with a small form factor, path to curved visor, and slim-line goals. With the benefit of expected improvements in angular bandwidth and optical efficiency, it is believed that the above FOV can be increased. The display modular design approach permits ready growth from monochrome to color with no major architecture redesign being needed. Reasonable imaging performance can be delivered out to 1.0 cyc/mr for both color and monochrome solutions. Optical performance in the monochrome will exceed the 1.4 cyc/mr display pixel resolution. The best resolution will be achieved in monochrome, but good performance can be achieved also for a color display. In a HMD the invention can provide a 25 mm wide eye box at 25 mm. eye relief. This will permit 90% of the population to be accommodated without any adjustment. Substrate guided diffractive optics are used everywhere except in the Input Image Node (IIN). However, the refractive components can be replaced by diffractive elements in future developments of the design to yield further form factor compression, and manufacturing benefits. The IIN may be mounted above or to the side of and at the front or rear of the DigiLens. This allows a range of ergonomic demands to be met while preserving core DigiLens functionality. The design may need no partitioning or tessellation of the near eye DigiLens, eliminating the problems of illumination ripple and discontinuities and scatter from electrodes. A transparent display according to the principles of the invention will also benefit from results from plastic SBG technology disclosed in U.S. Provisional Patent Application No. 61/573,066 with filing date 24 Aug. 2012 by the present inventors entitled IMPROVEMENTS TO HOLOGRAPHIC POLYMER DISPERSED LIQUID CRYSTAL MATERIALS AND DEVICES which is also referenced by the Applicant's docket number SBG104.

(178) The present invention assumes the teachings of earlier filings as specified as above. In particular the invention may make use of a scheme for polarization recycling disclosed in U.S. Provisional Patent Application No. 61/687,436 with filing date 25 Apr. 2012 by the present inventors entitled WIDE ANGLE COLOR HEAD MOUNTED DISPLAY which is also referenced by the Applicant's docket number SBG109. This particular feature may be relevant in the event that polarization is not maintained with an SBG outcoupling waveguide, either by virtue of the properties of the and SBG material (current or one developed in future), or where a polarization rotation component is deliberately introduced in the waveguide, then opens the opportunity for: polarization recycling and increased device efficiency through polarization recycling. Specifically: a thinner DigiLens waveguide can be used if linearly polarized light is input into the DigiLens waveguide (i.e., p light coupled from HBE into the waveguide), and light is converted to a mixture of S and P polarized light. This may allow up to a factor of two times reduction thickness of the

waveguide.

(179) The present invention may incorporate beam splitters layers in a waveguide to achieve uniformity. As a further refinement a beam splitter offset in waveguide may be obtained—i.e., not in middle of waveguiding surfaces, but offset from waveguide midpoint to maximize uniformity following multiple bounce interactions. A yet further refinement is to use different reflectivity in beam splitter to optimize and tailor beam mixing. The concept is that by varying the reflectivity % of the beam splitter to something other than 50/50, or by varying the tx/Rx split along a B/S length, so the pupil fill can be homogenized and optimized.

(180) Note that the thickness of the holograms shown in the drawings has been exaggerated. Typically the gratings will be 1.8-3 microns in thickness sandwiched by substrates of thicknesses of 100-200 microns. The transparent electrodes applied to opposing faces of the substrates are measured in nanometers.

(181) In one embodiment, a holographic brightness enhancing film, or other narrow band reflector, is affixed to one side of the display, the purpose of which is to reflect the display illumination wavelength light only; the see-through display can be made invisible (and hence secure) in the opposite direction of view. Here the reflected display illumination is effectively mirrored and therefore blocked in one direction, making it ideal for transparent desktop display applications in customer or personal interview settings, common in bank or financial services settings.

(182) An important performance parameter in the present context is the see-through transmission of the display. The variables that have an impact on transmission are the ITO coating (0.995), the AR coatings (0.99), and the absorption of the substrates and holographic layers. There will also be Fresnel losses at the interfaces between the waveguides and the low-index bonding layers. The needed transmission for the color display is >70%, with an objective of >90%. Assuming three waveguides per display and two substrates per waveguide, the calculated transmission is 93%, meeting the stipulated objective. Note that it is our intent to implement this design using 100-micron glass substrates. With three waveguides and three substrates per waveguide (note: two holographic layers may need three substrates), the total thickness of the display of the color display is still less than 1 mm. The thicknesses of the holographic layers (including the coatings) are negligible; each contributes only 4-5 microns to the overall thickness. Since weight is always an issue, this is an extremely important feature of our approach. When plastic is employed, the weight may be reduced even further.

(183) In the preferred embodiment the SBGs operate in reverse mode such that they diffract when a voltage is applied and remain optically passive at all other times. The SBGs will be implemented as continuous SBG lamina separated by thin (as thin as 100 microns) substrate layers as shown. Ultimately the design goal is to use plastic substrates with transmissive conductive coatings (to replace ITO). Plastic SBG technology suitable for the present application is being developed in a parallel SBIR project. This is a planar monolithic design harnessing the full assets of narrow band laser illumination with monolithic holographic optics

(184) The present invention has a suite of advantages ideally suited for substrate guided optics. First, component costs are greatly reduced. The optical complexity is contained in the various holographic optical elements. Once the non-recurring engineering (NRE) associated with creating a set of masters is complete, the replication costs are relatively insignificant compared to the recurring material costs associated with discrete refractive components. Second, assembly time is greatly reduced. Not only is part count greatly reduced, but the assembly process is much faster. The planar structures can be cost-effectively laminated together with very high optical precision using alignment fiducials. The touch labor is greatly reduced compared to that of building a piece-part assembly to exacting standards. Third, the optical precision is much greater. One of the biggest challenges in designing a new optical design is controlling the roll-up of tolerances on the piece parts, the mechanical housings, and the assembly procedure. With holographic optical elements (HOEs), “gold standards” can be assembled by senior engineers and this level of quality captured

in the HOE masters during the NRE phase. Besides the fact that optical alignment of the HOEs can be accomplished with great precision, the individual HOEs are more tolerant of variations in alignment. Thus, the overall yield of high quality devices is much higher. Lastly, size and weight are greatly reduced by this monolithic design, as is the ruggedness of the entire subsystem.

(185) It will be clear that in any of the above embodiments the eye lens and retina may be replaced by any type of imaging lens and a screen. Any of the above described embodiments of the invention may be used in either directly viewed or virtual image displays. Possible applications range from miniature displays, such as those used in viewfinders, to large area public information displays. The above-described embodiments may be used in applications where a transparent display is needed. For example, the invention may be used in applications where the displayed imagery is superimposed on a background scene such as heads up displays and teleprompters. The invention may be used to provide a display device that is located at or near to an internal image plane of an optical system. For example, any of the above described embodiments may be used to provide a symbolic data display for a camera viewfinder in which symbol data is projected at an intermediate image plane and then magnified by a viewfinder eyepiece. It will be clear the invention may be applied in biocular or monocular displays. The invention may also be used in a stereoscopic wearable display. Any of the above described embodiments of the invention may be used in a rear projection television. The invention may be applied in avionic, industrial and medical displays. There are also applications in entertainment, simulation, virtual reality, training systems and sport.

(186) The preferred light source for the display is a laser which is the ideal match to the diffractive optical elements and therefore unleashes the full power of our HMD, HUD and HDD designs. In terms of brightness, resolution and color gamut, the invention could also in some applications where optical performance is not very important to be applied using LEDs.

(187) Currently, SBGs for use in one embodiment are manufactured using stand-off exposure. However, the processes can be readily converted to a contact-copy process. The IIN may be implemented as an assembly of discrete refractive components. However, it is highly desirable to convert the design to a laminated stack of planar holographic elements. With sufficient volume, such an implementation of the IIN would achieve a very attractive price point. Advantageously, the substrates used in the waveguide would be fabricated from ballistic-quality plastic substrates. Proof of feasibility has been established and process optimization activities are underway. Replacing refractive components with laminated plastic-based planar holographic elements will make displays based on the invention inherently more rugged.

Further Embodiments

(188) The following embodiments are directed at a display that uses a single waveguide HBE. This particular embodiment is presently considered to be more suitable for lower field of view devices such as HUDs. However, recognizing that the size of the HBE is likely to be manageable, there is no reason in theory why the same embodiment could not be used for higher FOV applications such as HMDs. As will be discussed, the prerequisite is a non-projected pupil.

(189) FIG. 54 illustrates projection schemes that do not result in a projected pupil of the type discussed earlier in the description. The pupil may be formed inside the projection lens, as shown in FIG. 54A, or before the projection lens using the aperture 562 as shown in FIG. 54B. Such projection schemes result in an angular diversity at some distance along the z axis or optical axis that is less than the full FOV. For example turning to FIG. 54A, if light from the source image points 1350A-1350C is considered, which is collimated by the lens 560 into the collimated ray bundles 1351A-1351C, overlap exists between the bundles 1351A, 1351B and between the bundles 1351B, 1351C. From basic geometry the angular diversity to first order is given by the projection lens exit pupil aperture D and the distance along the optical axis z.

(190) FIG. 55 is a schematic illustration of the use of rolled k-vector gratings to maximize the peak DE of in-couple light, (for example in the HBE-I grating). The k-vector roll for the grating

elements **572A-572C** in the waveguide section **570** is indicated by the differing orientates of the k-vectors **573A-573C**. The surface grating pitch P is constant along the length of the waveguide. The grating vectors are optimized to diffract the rays **1360A-1360**, representing the chief rays and off-axis rays, with high diffraction efficiency. The use of rolled k-vectors enables high efficiency input coupling into a grating, and also allows the beam spread angle to be optimized to minimize the thickness of the waveguide; this may need balancing the waveguide thickness, the angular bandwidth of the input grating, and the spread of field angles at any given point on the input grating. The low angular response of gratings as the k-vector is rolled (and surface pitch maintained) prevents output coupling, allowing the waveguide thickness to be minimized (191) FIG. **56** is a schematic illustration showing the propagation of a typical ray through a waveguide section **580** containing rolled k-vector gratings. The dimension a separating the points X and Y is approximately twice the waveguide thickness t for a 45 degree TIR angle in the waveguide. The propagation path is indicated by the rays **1370-1371**. The point X corresponds to the point at which the ray **1370** couples into the grating. The chief ray angle may be needed to change by an amount greater than or equal to the FWHM angular bandwidth of the grating. At point Y the ray angle is off Bragg. Hence, reciprocal output coupling at Y is not obtained. The design aim is to ensure maximum input coupling at X and at the same time to design the distance along z to minimize the angular diversity such that the grating thickness can be minimized without reciprocally out-coupling at position Y .

(192) FIGS. **57-59** show perspective view of an embodiment that uses k-vector rolling to provide exit pupil expansion in orthogonal directions. FIG. **57** is a plan view showing the HBE **590** and the VBE **591**. FIG. **58** is a schematic side elevation view of the HBE and the VBE. FIG. **59** is an unfolded view of the HBE showing the beam propagation inside the waveguide. A Cartesian XYZ coordinate system is provided for reference. The lossy output grating of the HBE is indicated by **592**. The input grating is indicated by **593**. The input and output gratings have common surface grating pitch. At $Z=0$ and $Z=L$ along the HBE, it may be desired to have high input coupling within the VBE. As the angular diversity diminishes as the limit $Z=L$ is approached (angular diversity scales as $1/L$), the grating thickness can be increased. This is beneficial as the beam fill W at $Z=L$ is much greater than at $Z=0$ so that light in-coupled to the VBE with thickness t will experience more grating interactions in waveguide following in-coupling. A thicker grating reduces out-coupling. The angular diversity can be used to fine-tune the thickness of the VBE.

(193) FIGS. **60-62** illustrate an apparatus for fabrication the waveguide illustrated in FIGS. **57-59**. Referring to FIG. **60**, all points along the ray **1390A** such as **600A-602C** must have identical surface grating pitches and parallel k-vectors. The k-vectors are rolled in planes orthogonal to the z axis. FIG. **60** illustrates an apparatus for fabricating the HBE using a contact copying process. FIG. **61A** shows a cross section of the $Z=L$ end of the HBE **590** with the wider end of a cone shaped lens overlaid. FIG. **61B** shows a plan view of the lens and FIG. **61C** shows the $Z=0$ end of the HBE with the narrower end of the lens overlaid. The grating layer is indicated by **611** and the rolled grating is indicated by the detail **612**. The paths of the collimated recording beam incident on the lens are indicated by **1391,1393**. The convergent rays that are used to form the rolled grating are indicated by **1392,1394**. The lens is illustrated as a refractive element. In one embodiment a diffractive lens of equivalent prescription may be used. The cone-shaped lens contact copying set-up may need careful attention to overcome holographic off-axis aberrations, which may need to be compensated at the recording stage.

(194) FIG. **62** illustrates the generation of the conic section from a cone of tip **620** and base **621**. The cone is shown in side view in FIG. **62A** which indicates the cut out optic and the cut line and in-front view in FIG. **62B**, which again indicates the cut out optic. A view of the cut out optics projected from the base along the cut line is shown in FIG. **62C**. The conic section is obtained by cutting parallel to cone edge. Rays parallel to the z -axis then remain non-deflected (i.e., with no refracted component) in the y -axis. The amount of deflection (refraction) in the x -axis is a function

of the position the ray strikes the y-axis.

(195) FIGS. **63-66** illustrate the principles of k-vector rolling. FIG. **63** shows the basic architecture of a waveguide according to the principle of the invention. The waveguide **630** comprises a multiplicity of grating lamina which can be grouped into input gratings **631** and output gratings **632**. In each case associated with each Bragg grating there will be a surface grating as indicated by **633,634**. Input image light is represented by the collimated beams **1400-1402** where characters A, B indicate the extremes rays of each beam. The corresponding output image light is represented by three collimated beams **1410-1412** with characters A, B again indicating the extreme rays. The output beam has a greatly expanded pupil owing to the extraction of light along the waveguide as discussed above. Typically the output gratings will be much longer extending over most of the length of the waveguide. The DIGI-I, HBE-I gratings discussed in relation to certain embodiments are examples of input gratings while DIG-O, HBE-O gratings are examples of output gratings. In each group multiple gratings may be stacked or disposed in a layer adjacent each other. FIG. **64** is an illustration of a waveguide in which the input gratings **635A-635C** are stacked. Each grating has a unique k-vector **636A-636C**. The k-vector **636A** is designed to give high diffraction efficiency for a field of view centered on the beam direction **1401**. The k-vectors **636B, 636C** are optimized for high diffraction efficiency around the incident beam directions **1400, 1402**, respectively. Thus the input image is sampled into a plurality of angular intervals. Each angular interval is associated with an effective exit pupil that is a fraction of the full pupil.

(196) In the embodiment as shown in FIG. **65**, the input gratings are disposed adjacent to each other along the waveguide propagation direction. The waveguides are indicated by **637A-637C** and the k-vectors by **638A-638C**. The inventors have coined the term “rolled k-vector” to describe the varying orientation of the k-vectors along the waveguide propagation direction.

(197) The principles illustrated in FIGS. **64-65** may also be applied in the output grating as illustrated in FIG. **66**. Here the output grating comprises a multiplicity of adjacently disposed gratings such as **639A-639C** with k-vectors **640A-640C**. In alternative embodiments of the invention the output grating may be comprised of stacked gratings based on the principles of FIG. **64**.

(198) A method of displaying an image is one embodiment of the invention in accordance with the basic principles of the invention is shown in the flow diagram in FIG. **67**. Referring to the flow diagram, the method may comprise the following steps:

(199) At step **650** providing: a first optical substrate for propagating light in a first direction; a second optical substrate for propagating light in a second direction; and an Input Image Node (IIN), the first and second optical substrates comprising at least one waveguide layer, each at least one waveguide layer comprising at least one grating lamina, and the at least one grating lamina comprising a passive mode SBG.

(200) At step **651** providing image modulated light using the IIN.

(201) At step **652** coupling the image light into the First Optical Substrate;

(202) At step **653** extracting light from first optical substrate along the first direction;

(203) At step **654** coupling image light into the second optical substrate;

(204) At step **655** extracting light from the first optical Substrate along the second direction;

(205) At step **656** providing image light for display.

(206) Summary of Some Embodiments

(207) At least some embodiments provided herein use separate vertical and horizontal beam expansion waveguides to provide an enlarged exit pupil (or eye box). Each waveguide contains input and output Bragg gratings. Each of the waveguides may comprise more than one waveguide layer. In color embodiments a separate monochromatic waveguide may be used for each primary color. Another option for providing color is to record multiplexed gratings, in which holograms with different color prescriptions are superimposed, into a waveguide.

(208) Collimated image light is fed into the horizontal beam expansion waveguide with a Field of

View (FOV) defined by the microdisplay and collimating optics. The invention allows the input or “coupling” optics to be configured in many different ways ranging from classical optical lens-mirror designs to more compact designs based entirely on diffractive (holographic) optics.

(209) The horizontal beam expansion waveguide is lossy, that is, it is designed to extract light out of the waveguide uniformly along its length. The extracted light is then coupled into the vertical expansion waveguide.

(210) The vertical expansion waveguide, which is also lossy, completes the beam expansion to provide a vertically and horizontally expanded exit pupil.

(211) A unique feature of the invention is that all of the above can be accomplished using passive gratings (although the use of switchable gratings is still an option for some applications).

Conventional passive gratings would not work. The chief benefit of using passive SBGs is that the refractive index modulation of the grating can be tuned from very low to very high values with a correspondingly broad range of diffraction efficiencies. The high index modulation of SBGs results from the alternating bands of polymer-rich and LC-rich regions that form the Bragg fringes.

(212) While lossy gratings are known in the prior art, the present invention is unique in achieving efficient and uniform extraction from the waveguide by varying the thickness (and modulation) across the grating. In its simplest case this entails creating a wedged grating (by inclining the cell walls) such that the hologram thickness increases in the direction of propagation. Typically, the grating thickness may vary from 1.0-1.2 micron up to 2.8-3.0 micron, the lower thickness producing the lowest efficiency (and largest angular bandwidth). The invention allows more sophisticated control of extraction by varying the thickness in orthogonal directions, using two wedge angles, or in a more general fashion by applying curvature to one or both faces of the grating.

(213) A further unique feature of the beam expansion gratings is that they can be made very thin (well below 3 micron) which results in very broad diffraction efficiency angular bandwidth which, in turn, results in a wide FOV. By optimizing thickness and refractive index modulation it is possible to meet all of the needed grating characteristics needed in the display, i.e., very high efficiency for coupling into gratings and large dynamic range for the efficient, uniform extraction needed for beam expansion.

(214) An extremely important feature of the invention that has implications for image transfer inefficiency and form factor is the use of image sampling. Coupling wide FOV image light into a waveguide would normally result in some loss of image angular content owing to the limited range of angles that can be efficiently propagated down a waveguide. Some of this light may couple out of the waveguide. The invention overcomes this problem by sampling the input image into multiple angular intervals, each of which has an effective exit pupil that is a fraction of the size of the full pupil, the thickness of the waveguide being reduced correspondingly.

(215) Uniquely, the invention combines fixed frequency surface gratings at the input and output of each waveguide with rolled k-vectors along the waveguide. The surface grating is the intersection of the Bragg fringes with the substrate edge and accounts (approximately) for the basic ray optics of the waveguide. The k-vector is the direction normal to the Bragg grating and accounts for the diffraction efficiency vs angle characteristics of the grating. By varying the k-vector direction along the waveguide propagation direction (k-vector rolling) it is possible to, firstly, provide efficient coupling of image light into the waveguide and, secondly, ensure that once coupled-in, all of the needed angular content is transmitted down the waveguide with high efficiency. The k-vector rolling would desirably be augmented by grating thickness control as discussed above. To our knowledge this principle has not been applied in the prior art.

(216) With regard to color imaging, making the input and output gratings in each waveguide have the same surface gratings frequencies as discussed above allows colors to be implemented in separate waveguides that are free from cross talk. This is believed to be a unique feature of the invention.

(217) In general, the propagate of angular content down the waveguide can be optimized by fine tuning of one or more of the following: grating thickness; refractive index modulation; k-vector rolling; surface grating period; and the hologram-substrate index difference.

(218) The apparatuses and methods described herein may be applied to HMD, HUD and HDD.

EXEMPLARY EMBODIMENTS

(219) The various aspects of the apparatus, systems, and methods described herein may be further described in the various embodiments provided below:

(220) In one embodiment the first optical substrate selectively samples portions of the image modulated light, each portion being characterized by either angular field or spatial field.

(221) In one embodiment at least one grating lamina in each optical substrate comprises an input grating operative to diffract light coupled into said substrate into a TIR path and an output grating operative to diffract light from said TIR path out of said substrate.

(222) In one embodiment extraction from said second substrate takes place through a face of the waveguiding layer.

(223) In one embodiment extraction from second substrate takes place through a waveguiding layer edge.

(224) In one embodiment the grating vectors of grating lamina in the first substrate lie in a plane substantially orthogonal to the faces of the first substrate.

(225) In one embodiment the grating vectors of grating lamina in the first substrate lie in a plane substantially parallel to the faces of the first substrate.

(226) In one embodiment the waveguide layers are transparent dielectrics.

(227) In one embodiment the waveguiding layers propagate monochromatic light.

(228) In one embodiment first, second and third waveguiding layers are provided in at least one of the first or second substrates for the purpose of propagating red, green and blue light.

(229) In one embodiment first and second waveguiding layers are provided in at least one of the first or second substrates for the purpose of propagating red light and mixed blue and green light.

(230) In one embodiment waveguiding layers in at least one of the first or second substrates sandwich a half wave film.

(231) In one embodiment waveguiding layers in at least one of the first or second substrates sandwich an air space.

(232) In one embodiment grating lamina in at least one of the first or second substrates multiplex gratings of at least two different monochromatic prescriptions.

(233) In one embodiment grating lamina in at least one of said first or second substrates multiplex gratings of at least two different colors.

(234) In one embodiment the first substrate provides pupil expansion along the first direction and the second substrate provides pupil expansion along the second direction.

(235) In one embodiment light extracted from the first and second substrates provides uniform illumination in any field of view direction.

(236) In one embodiment each grating in at least one of the first substrate or second substrates has first and second diffracting state. The first diffracting state is characterized by high diffraction efficiency and the second diffraction state is characterized by low diffraction efficiency.

(237) In one embodiment the diffracting state occurs when an electric field is applied across the grating and a non-diffracting state exists when no electric field is applied.

(238) In one embodiment the non diffracting state occurs when an electric field is applied across the grating and a diffracting state exists when no electric field is applied.

(239) In one embodiment the first and second propagation directions are orthogonal.

(240) In one embodiment at least one of the substrates is curved in at least one orthogonal plane.

(241) In one embodiment at least one of the waveguiding layers includes a beam splitter lamina.

(242) In one embodiment quarter wavelength film is applied to at least one face of the waveguiding layer in either the first substrate or the second substrate.

- (243) In one embodiment a reflective thin film coating is applied to at least one face of the waveguiding layer in either the first substrate or the second substrate.
- (244) In one embodiment the first coupling means comprises at least one grating lamina substantially overlapping a portion of the first substrate.
- (245) In one embodiment the first coupling means comprises at least one grating lamina disposed within the waveguiding layer.
- (246) In one embodiment the first coupling means comprises at least one grating lamina. Each grating lamina comprises at least two multiplexed gratings of different prescriptions. Each grating lamina substantially overlaps a portion of the first substrate.
- (247) In one embodiment the second coupling means comprises at least one grating lamina substantially overlapping the first substrate.
- (248) In one embodiment the second coupling means comprises at least one grating lamina. Each grating lamina comprises at least two multiplexed gratings of two different prescriptions. Each grating lamina substantially overlaps the first substrate.
- (249) In one embodiment the second coupling means is disposed within the second substrate.
- (250) In one embodiment grating vectors of grating lamina in the first substrate lie in a plane substantially parallel to the faces of the substrate and the first substrate grating provides the second coupling means.
- (251) The invention may be used to provide one eye piece of a HMD, a HHD or a HUD.
- (252) In one embodiment at least one grating in the first or second substrates encodes optical power.
- (253) In one embodiment the second substrate is embedded within a windscreen.
- (254) In one embodiment the waveguiding layers have at least one face in contact with a nanoporous film.
- (255) A display according to the principles of the invention may further comprise an eye tracker.
- (256) A display according to the principles of the invention may further comprise a beam homogenizer
- (257) In one embodiment the input image node comprises a microdisplay, laser and collimating optics.
- (258) In one embodiment the grating lamina are switchable Bragg gratings.
- (259) In one embodiment the grating lamina used in at least one of the first or second substrates are non switching Bragg gratings recorded in HPDLC material.
- (260) In some embodiments described herein, instead of an HPDLC material, a POIlymer Liquid CRYstal Polymer Slice ("POLICRYPS") may be employed.
- (261) HPDLC materials may be characterized by alternating bands of LC-rich (e.g., high LC concentration and low polymer concentration) and polymer-rich (e.g., high polymer concentration and low LC concentration) material. Since the LC has a droplet morphology in many instances HPDLC may suffer from two problems: scatter from the LC droplets and low grating contrast (which may ultimately limit the peak diffraction efficiency). A new class of materials, of which POLICRYPS is an example, combines LC and polymer to provide a more uniform morphology that overcomes both the above problems. While the grating is formed by a diffusion process similar to the one that occurs in HPDLC, the end result in POLICRYPS may be a grating comprising alternate bands of homogeneous highly-aligned LC and homogeneous polymer. Particulate scattering losses may be almost, if not entirely, removed by a lack of LC droplets. The grating may be of very high contrast with a refractive index modulation close to the theoretical limit set by the bulk LC birefringence. As a result, diffraction efficiency values as high as about 98% (or in some instances even higher) may be readily obtained.
- (262) Grating pitches covering the range of interest for practical displays may be achieved without difficulty; in fact, in one embodiment the material may sustain pitches as low as 0.2 microns and as high as 15 microns. In electro-optical terms, POLICRYPS may be similar to conventional HPDLC.

In some instances, the switching speed of POLICRYPS may be higher than HPDLC and the switching voltage is at least equal to or lower than that of HPDLC. In one embodiment, like HPDLC gratings POLICRYPS grating may be utilized both in transmission and in reflection and may be implemented in waveguides. The holographic recording process in POLICRYPS may be the same as that in HPDLC and may involve standard commercially-available monomers and LCS. In one embodiment, one challenge of POLICRYPS is that a high temperature process may be needed. In this embodiment, the temperature should be high enough to maintain isotropic mixture and to prevent isotropic-to-nematic transition during exposure.

(263) POLICRYPS was developed at LICRYL (Liquid Crystals Laboratory, IPCF-CNR), Center of Excellence and Department of Physics, University of Calabria, Italy). An example of POLICRYPS is described in Caputo, R. et al., *Journal of Display Technology*, Vol. 2, No. 1, March 2006, pp. 38-50, which is incorporated by reference in its entirety. Further details of POLICRYPS may be found in U.S. Patent Application No. 2007/0019152 by Caputo, R.; et al., entitled "Holographic Diffraction Grating, Process for Its Preparation and Opto-Electronic Device Incorporating It", published in Jan. 25, 2007, which is incorporated by reference in its entirety.

(264) Another uniform morphology grating technology that may be employed is POLIPHEM Liquid Crystal Polymer Holograms Electrically Manageable ("POLIPHEM"), which was developed by the Fraunhofer Institute for Applied Polymer Research, Potsdam (Germany). In one embodiment, POLIPHEM is similar to POLICRYPS in basic morphological and electro-optical terms. One advantage of using POLIPHEM over POLICRYPS is that former may avoid the high temperature processing needed in POLICRYPS in some instances by optimizing the properties and proportions of LC and monomer in the material recipe. Details of materials and methods for fabricating POLIPHEM gratings may be found in the international patent publication No.: WO2006002870 (PCT/EP2005/006950) by Stumpe, J. et al., entitled "Method for the Preparation of High Efficient, Tunable and Switchable Optical Elements Based on Polymer-Liquid Crystal Composites", published January 2006, which is incorporated by reference in its entirety.

(265) In one embodiment, it may be desirable for the gratings described here to provide both high diffraction efficiency and wide angular bandwidth. However, in one embodiment these two goals conflict in that wide angular bandwidth dictates that the gratings should be thin, while thin gratings may suffer from progressively diminishing diffraction efficiency as the thickness is reduced. One solution is to stack a multiplicity of thin gratings, such that each grating may diffract the 0-order light from the grating beneath it, so that most of the input light eventually may get diffracted. In some embodiments, the grating layers may be separated by spacers. Such a stratified grating structure may be considered to be equivalent to diffraction by a thick or volume (i.e., Bragg) grating with at least one benefit of a much wider bandwidth resulting from using thin gratings as a basic building block.

(266) In one embodiment, the thin gratings may desirably operate in the Bragg regime (rather than thin gratings according to the Raman Nath regime) to avoid higher order diffraction. In one embodiment, when the thin gratings operate in the Raman-Nath regime, careful optimization of the thickness and pitch may be employed to ensure that the relative phasing of the diffraction orders as they propagate from layer to layer give rise to a unique notched diffraction response of the +1 order (for the case of Bragg incidence). In another embodiment, Bragg gratings may be recorded in a stratified grating structure known as a Stratified Volume Holographic Element (SVHOE). An example of SVHOE is described in Nordin, G., et al., *J. Opt. Soc. Am., A*, Vol. 9, No. 12, December 1992, pp. 2206-2217, which is incorporated by reference in its entirety.

(267) A more complete understanding of the invention can be obtained by considering the following detailed description in conjunction with the accompanying drawings, wherein like index numerals indicate like parts. For purposes of clarity, details relating to technical material that is known in the technical fields related to the invention have not been described in detail.

Additional Embodiments

(268) The following embodiments are taken from the claims of the provisional application Ser. No. 61/849,853, filed Feb. 4, 2013, which is incorporated by reference in its entirety.

(269) An apparatus for displaying an image comprising: an input image node for providing image modulated light; a first optical substrate comprising at least one waveguiding layer, each said waveguiding layer propagating light in a first direction, each said waveguiding layer comprising at least one grating lamina operative to extract light from said first substrate along said first direction; a second optical substrate comprising at least one waveguiding layer, each said waveguiding layer propagating light in a second direction, each said waveguiding layer containing at least one grating lamina operative to extract light for display from said second substrate along said second direction; a first optical means for coupling said image modulated light into said first substrate; and a second optical means for coupling light extracted from said first substrate into said second substrate.

(270) The apparatus of embodiment 1 wherein said first optical substrate selectively samples portions of said image modulated light, each said portion being characterized by either angular field or spatial field.

(271) The apparatus of embodiment 1 wherein said at least one grating lamina in each said optical substrate comprises an input grating operative to diffract light coupled into said substrate into a TIR path and an output grating operative to diffract light from said TIR path out of said substrate.

(272) The apparatus of embodiment 1 wherein said extraction from said second substrate takes place through a waveguiding layer face.

(273) The apparatus of embodiment 1 wherein said extraction is carried out from second substrate through a waveguiding layer edge.

(274) The apparatus of embodiment 1 wherein grating vectors of grating lamina in said first substrate lie in a plane substantially orthogonal to the faces of said substrate.

(275) The apparatus of embodiment 1 wherein grating vectors of grating lamina in said first substrate lie in a plane substantially parallel to the faces of said substrate.

(276) The apparatus of embodiment 1 wherein said waveguide layers are transparent dielectric.

(277) The apparatus of embodiment 1 wherein said waveguiding layers propagate monochromatic light.

(278) The apparatus of embodiment 1 wherein first, second and third waveguiding layers are provided in at least one of said substrates for propagating red, green and blue.

(279) The apparatus of embodiment 1 wherein first and second waveguiding layers are provided in at least one of said substrates for propagating red light and mixed blue and green light.

(280) The apparatus of embodiment 1 wherein waveguiding layers in at least one of said first or second substrates sandwich a half wave film.

(281) The apparatus of embodiment 1 wherein waveguiding layers in at least one of said first or second substrates sandwiches an air space.

(282) The apparatus of embodiment 1 wherein grating lamina in at least one of said first and second substrates comprises multiplex gratings of at least two different monochromatic prescriptions.

(283) The apparatus of embodiment 1 wherein grating lamina in at least one of said first and second substrates comprise multiplex gratings of at least two different colors.

(284) The apparatus of embodiment 1 wherein said first substrate provides pupil expansion along said first direction and said second substrate provides pupil expansion along said second direction.

(285) The apparatus of embodiment 1 wherein said light is extracted from said first and second substrates provides uniform illumination in any field of view direction.

(286) The apparatus of embodiment 1 wherein each said grating in at least one of said first substrate or second substrate has a first diffracting state wherein said first diffracting state is characterized by a high diffraction efficiency and said second diffraction state is characterized by a low diffraction efficiency.

(287) The apparatus of embodiment 17 wherein said diffracting state occurs when an electric field

is applied across said grating and a non diffracting state exists when no electric field is applied.

(288) The apparatus of embodiment 17 wherein said non diffracting state occurs when an electric field is applied across said grating and a diffracting state exists when no electric field is applied.

(289) The apparatus of embodiment 1 wherein said first and second propagation directions are orthogonal.

(290) The apparatus of embodiment 1 wherein at least one of said substrates is curved in at least one orthogonal plane.

(291) The apparatus of embodiment 1 wherein at least one of said waveguiding layers includes a beam splitter lamina.

(292) The apparatus of embodiment 1 wherein quarter wavelength film is applied to at least one face of said waveguiding layer in either said first substrate or said second substrate.

(293) The apparatus of embodiment 1 wherein a reflective thin film coating is applied to at least one face of said waveguiding layer in either said first substrate or said second substrate.

(294) The apparatus of embodiment 1 wherein said first coupling means comprises at least one grating lamina substantially overlapping a portion of said first substrate.

(295) The apparatus of embodiment 1 wherein said first coupling means comprises at least one grating lamina disposed within said waveguiding layer.

(296) The apparatus of embodiment 1 wherein said first coupling means comprises at least one grating lamina, each said grating lamina comprising at least two multiplexed gratings of two different prescriptions, each said grating lamina substantially overlapping a portion of said first substrate.

(297) The apparatus of embodiment 1 wherein said second coupling means comprises at least one grating lamina substantially overlapping said first substrate.

(298) The apparatus of embodiment 1 wherein said second coupling means comprises at least one grating lamina, each said grating lamina comprises at least two multiplexed gratings of two different prescriptions, each said grating lamina substantially overlapping said first substrate.

(299) The apparatus of embodiment 1 wherein said second coupling means is disposed within said second substrate

(300) The apparatus of embodiment 1 wherein grating vectors of grating lamina in said first substrate lie in a plane substantially parallel to the faces of said substrate, wherein said first substrate grating provides said second coupling means.

(301) The apparatus of embodiment 1 wherein said apparatus provides one eye piece of a HMD, a HHD or a HUD.

(302) The apparatus of embodiment 1 wherein at least one grating in said substrates encodes optical power.

(303) The apparatus of embodiment 1 wherein said second substrate is embedded within a windscreen.

(304) The apparatus of embodiment 1 wherein said wave guiding layers have at least one face in contact with a nanoporous film.

(305) The apparatus of embodiment 1 further comprising an eye tracker.

(306) The apparatus of embodiment 1 wherein further comprises a beam homogenizer.

(307) The apparatus of embodiment 1 wherein said input image node comprises a microdisplay, laser and collimating optics.

(308) The apparatus of embodiment 1 wherein said grating lamina in at least one of said first or second substrates is an SBG.

(309) The apparatus of embodiment 1 wherein said grating lamina in at least one of said first or second substrates are non switching Bragg gratings recorded in HPDLC material.

(310) The apparatus of embodiment 1 wherein said grating lamina in at least one of said first or second substrates are SBGs recorded in a reverse mode material.

REFERENCES

(311) The following patent applications are incorporated by reference herein in their entireties: U.S. Provisional Patent Application No. 61/687,436 with filing date 25 Apr. 12 by the present inventors entitled WIDE ANGLE COLOUR HEAD MOUNTED DISPLAY which is also referenced by the Applicant's docket number SBG109. U.S. Provisional Patent Application No. 61/689,907 with filing date 25 Apr. 12 by the present inventors entitled HOLOGRAPHIC HEAD MOUNTED DISPLAY WITH IMPROVED IMAGE UNIFORMITY which is also referenced by the Applicant's docket number SBG113A. PCT Application No. US 2008/001909, with International Filing Date: 22 Jul. 2008, entitled LASER ILLUMINATION DEVICE; PCT Application No.: US 2006/043938, entitled METHOD AND APPARATUS FOR PROVIDING A TRANSPARENT DISPLAY; PCT Application No.: PCT/GB2010/001982 entitled COMPACT EDGE ILLUMINATED EYEGLASS DISPLAY; U.S. Provisional Patent Application No. 61/573,066 with filing date 24 Aug. 12 by the present inventors entitled IMPROVEMENTS TO HOLOGRAPHIC POLYMER DISPERSED LIQUID CRYSTAL MATERIALS AND DEVICES which is also referenced by the Applicant's docket number SBG104. PCT Application No.: PCT/GB2010/002023 filed on 2 Nov. 2010 by the present inventors entitled APPARATUS FOR REDUCING LASER SPECKLE; PCT Application No.: PCT/GB2010/000835 with International Filing Date: 26 Apr. 2010 entitled COMPACT HOLOGRAPHIC EDGE ILLUMINATED EYEGLASS DISPLAY (and also referenced by the Applicant's docket number SBG073PCT); U.S. Pat. No. 6,115,152 entitled HOLOGRAPHIC ILLUMINATION SYSTEM, issued 5 Sep. 2000; and U.S. Provisional Patent Application No. 61/796,795 entitled COMPACT LASER ILLUMINATOR INCORPORATING A DESPECKLER with filing date 20 Nov. 2012.

Additional Example

(312) FIG. **68** is a ray trace of a monochromatic version of the design. FIG. **69** shows the approximate dimensions of the IIN of FIG. **68**. FIG. **70** provides unfolded views of the optical layout of FIG. **69**.

(313) The IIN stop is formed by controlling profile of input illumination. There is currently no hard physical stop in the projection optics. The benefits of a projected stop are decreased waveguide thicknesses. A stop is projected midway up the HBE to minimize aperture diameter within the VBE, and hence minimizing the aperture width of the VBE to DigiLens waveguide coupler, i.e., reducing the width of the 1.sup.st axis expander limits the thickness of the 2nd axis expansion optic. FIGS. **71A** and **71B** illustrate the formation of a projected stop inside the HBE using a simplified thin lens representation of the microdisplay projection optics.

(314) In one embodiment a graduated reflection profile underneath SBG layer is used to control (or assist) with grating DE variation along length (normally achieved in SBG grating using index modulation). This may be useful in cases such as the HBE, where a low percentage of light is out coupled in 1.sup.st bounce, but a high percentage is coupled out at the other end of the expander.

(315) An Embodiment Using a Striped HBE

(316) In one embodiment the HBE comprises a coupling grating at its input end and alternating SBG stripes of two different prescriptions are inclined at 45 degrees within the plane as shown in FIG. **72**. Although the stripes are shown as equi-spaced, their size and spacing may be varied for better illumination and image sampling control. However the stripes should not be made too narrow as this may impact the MTF. In general, the stripe geometry may need careful optimization as there are, for example, rays from extremities of a stripe that may result in a phase difference in the pupil. The input SBGs need a large angular bandwidth and a high efficiency while the DigiLens passive gratings is lossy. Although the angular bandwidths of the gratings have pronounced center-to-edge variations, the extraction from the passive gratings is found to result in more light being diffracted from the center of a beam extracted, creating an effective inversion of the illumination profile at the end of the waveguide. This effect can be used to advantage in balancing the overall illumination profile. FIG. **73** illustrates beam propagation from the IIN through a single layer of the DigiLens showing the four changes in direction that occur along the path to the exit pupil. The

optical path is labelled by numerals 1-7.

(317) FOV, Eyebox and Eye Relief Geometry

(318) The near eye geometry of the proposed helmet mounted display is shown in plan view in FIG. 74, in side view in FIG. 75, and in front view in FIG. 76. The relationship of the DigiLens® aperture to the FOV, eye relief and eye box is also shown in FIG. 77. Note that the DigiLens® aperture will scale with eye relief.

(319) Binocular Overlap

(320) As shown in FIG. 78 and FIG. 79, partial binocular overlap can be provided using convergent or divergent optics. In either case binocular overlap can provide up to 1.4× contrast improvement. Convergent overlap may be better for avoiding binocular rivalry. As a very rough guide, mostly distance work may need only low overlap, while mostly close-up work (typically at arm's length) may need higher overlap. In general, published data on FOV vs. task performance is often anecdotal or limited to small and specialized samples. Extrapolating data from one application domain to another can be risky. There is no research that examines the FOV vs. task performance tradeoffs for a particular type of display. Consequently, the effects of eyebox, geometric distortion, form factor etc., are not fully reflected in the literature. The eyes tend to stay in the saccadic eye movement range (from 0° up to approximately +10° to) +15°. Outside this range the head will tend to move to re-center the image. If no head tracker is provided all important information must lie with the saccadic region. Some applications need a balance between adequate peripheral cue presentation and central image quality. Some research suggests that if the binocular overlap falls below around 20° binocular rivalry leading to effects such as luning (shadowing around the edges of the overlap regions) will start to become a problem for a significant number of users. The HWD overlap, in the range 20-25, has been chosen to maximize the overall horizontal field of view while minimizing the risk of binocular rivalry.

(321) Inter Pupillary Distance (IPD)

(322) The Inter-Pupillary Distance (IPD) target is to have no interpupillary distance adjustment for the majority of the adult population (90%). More than 90% of the adult population has IPDs in the range of 57 mm to 70 mm (+/-6.5 mm range). The pupil position change due to eye roll +/-20° is +/-4.5 mm. The tolerance of helmet placement/visor slip (budget) is +/-6.4 mm. Alignment may be estimated using the formula: $\text{Alignment} = \sqrt{[(\text{IPD}_{90\%} + \text{Eye Roll})^2 + \text{Slip}^2]} = \sqrt{[(6.3 \text{ mm} + 4.5 \text{ mm})^2 + 6.4 \text{ mm}^2]} = \pm 12.5 = 25.0 \text{ mm wide eye box}$. Note that for the 10% of the population with IPDs outside of the range, full field of view vision is provided. For optimal alignment only one side of the field of view will be lost for one eye only. The other eye will still see the other side of the field, i.e., 90% of the population get 100% overlap. The remaining 10% of the population (within 52 mm to 75 mm IPD) will get 100% of the field of view with some overlap dependent on IPD and display alignment. In conclusion, a 25 mm wide eye box will permit 90% of the population to be accommodated without any adjustment, assuming the above alignment parameters. Improved alignment tolerances of the visor/head gear to the eye will enable a reduction in the eye box dimensions if needed. This can be later traded off against system brightness.

(323) Low Index Materials

(324) Efficient waveguiding needs the TIR beams to be confined between low index media. Air gaps are difficult to fabricate and maintain while the refractive indices of currently available low index materials such as Magnesium Fluoride (1.46) and Silicon Dioxide (1.39) are much too high to meet the tight TIR angle constraints needed in full color implementations of the HMD. The proposed solution is to use nanoporous (Mesoporous Silicon) materials. Nanoporous materials (e.g., mesoporous Silicon) are currently being used in many optical applications including anti reflection coatings and planar optical waveguides. Their high porosity enables the fabrication of high-quality low-dielectric constant thin films. Nanoporous materials can be fabricated in thin layers in a single coating step. To achieve very low, near unity, index the porosities need to be very high, approaching 95%. High transparency and low index can be achieved simultaneously with

these films. Since they are highly efficient at absorbing water, they must be carefully sealed against moisture. The best approach may be to seal the passive gratings, HWP and material together. SBG Labs is also investigating the potential role of nanoporous materials as high refractive index media. This would increase the range of TIR angles that can be sustained in our waveguides with potential for increasing the horizontal FOV from 40° to around 45°. Nanoporous materials are currently being used in many optical applications including anti reflection coatings and planar optical waveguides. It is reasonable to assume therefore that the technology will be accessible for our project. The manufacturing process should be translatable to manufacturing needs. Nanoporous materials can be fabricated in single coating step. Alternatively, graded index multilayer architectures can be used. SBG Labs is also investigating the potential role of nanoporous materials as high refractive index media. This would increase the range of TIR angles that can be sustained in our waveguides.

CONCLUSION

(325) All literature and similar material cited in this application, including, but not limited to, patents, patent applications, articles, books, treatises, and web pages, regardless of the format of such literature and similar materials, are expressly incorporated by reference in their entirety. In the event that one or more of the incorporated literature and similar materials differs from or contradicts this application, including but not limited to defined terms, term usage, described techniques, or the like, this application controls.

(326) While the present teachings have been described in conjunction with various embodiments and examples, it is not intended that the present teachings be limited to such embodiments or examples. On the contrary, the present teachings encompass various alternatives, modifications, and equivalents, as will be appreciated by those of skill in the art.

(327) While various inventive embodiments have been described and illustrated herein, those of ordinary skill in the art will readily envision a variety of other means and/or structures for performing the function and/or obtaining the results and/or one or more of the advantages described herein, and each of such variations and/or modifications is deemed to be within the scope of the inventive embodiments described herein. More generally, those skilled in the art will readily appreciate that all parameters, dimensions, materials, and configurations described herein are meant to be exemplary and that the actual parameters, dimensions, materials, and/or configurations will depend upon the specific application or applications for which the inventive teachings is/are used. Those skilled in the art will recognize many equivalents to the specific inventive embodiments described herein. It is, therefore, to be understood that the foregoing embodiments are presented by way of example only and that, within the scope of the appended claims and equivalents thereto, inventive embodiments may be practiced otherwise than as specifically described and claimed. Inventive embodiments of the present disclosure are directed to each individual feature, system, article, material, kit, and/or method described herein. In addition, any combination of two or more such features, systems, articles, materials, kits, and/or methods, if such features, systems, articles, materials, kits, and/or methods are not mutually inconsistent, is included within the inventive scope of the present disclosure.

(328) Also, the technology described herein may be embodied as a method, of which at least one example has been provided. The acts performed as part of the method may be ordered in any suitable way. Accordingly, embodiments may be constructed in which acts are performed in an order different than illustrated, which may include performing some acts simultaneously, even though shown as sequential acts in illustrative embodiments.

(329) All definitions, as defined and used herein, should be understood to control over dictionary definitions, definitions in documents incorporated by reference, and/or ordinary meanings of the defined terms.

(330) The indefinite articles “a” and “an,” as used herein in the specification and in the claims, unless clearly indicated to the contrary, should be understood to mean “at least one.” Any ranges

cited herein are inclusive.

(331) The terms “substantially” and “about” used throughout this Specification are used to describe and account for small fluctuations. For example, they can refer to less than or equal to $\pm 5\%$, such as less than or equal to $\pm 2\%$, such as less than or equal to $\pm 1\%$, such as less than or equal to $\pm 0.5\%$, such as less than or equal to $\pm 0.2\%$, such as less than or equal to $\pm 0.1\%$, such as less than or equal to $\pm 0.05\%$.

(332) The phrase “and/or,” as used herein in the specification and in the claims, should be understood to mean “either or both” of the elements so conjoined, i.e., elements that are conjunctively present in some cases and disjunctively present in other cases. Multiple elements listed with “and/or” should be construed in the same fashion, i.e., “one or more” of the elements so conjoined. Other elements may optionally be present other than the elements specifically identified by the “and/or” clause, whether related or unrelated to those elements specifically identified. Thus, as a non-limiting example, a reference to “A and/or B”, when used in conjunction with open-ended language such as “comprising” can refer, in one embodiment, to A only (optionally including elements other than B); in another embodiment, to B only (optionally including elements other than A); in yet another embodiment, to both A and B (optionally including other elements); etc.

(333) As used herein in the specification and in the claims, “or” should be understood to have the same meaning as “and/or” as defined above. For example, when separating items in a list, “or” or “and/or” shall be interpreted as being inclusive, i.e., the inclusion of at least one, but also including more than one, of a number or list of elements, and, optionally, additional unlisted items. Only terms clearly indicated to the contrary, such as “only one of” or “exactly one of,” or, when used in the claims, “consisting of,” will refer to the inclusion of exactly one element of a number or list of elements. In general, the term “or” as used herein shall only be interpreted as indicating exclusive alternatives (i.e. “one or the other but not both”) when preceded by terms of exclusivity, such as “either,” “one of,” “only one of,” or “exactly one of.” “Consisting essentially of,” when used in the claims, shall have its ordinary meaning as used in the field of patent law.

(334) As used herein in the specification and in the claims, the phrase “at least one,” in reference to a list of one or more elements, should be understood to mean at least one element selected from any one or more of the elements in the list of elements, but not necessarily including at least one of each and every element specifically listed within the list of elements and not excluding any combinations of elements in the list of elements. This definition also allows that elements may optionally be present other than the elements specifically identified within the list of elements to which the phrase “at least one” refers, whether related or unrelated to those elements specifically identified. Thus, as a non-limiting example, “at least one of A and B” (or, equivalently, “at least one of A or B,” or, equivalently “at least one of A and/or B”) can refer, in one embodiment, to at least one, optionally including more than one, A, with no B present (and optionally including elements other than B); in another embodiment, to at least one, optionally including more than one, B, with no A present (and optionally including elements other than A); in yet another embodiment, to at least one, optionally including more than one, A, and at least one, optionally including more than one, B (and optionally including other elements); etc.

(335) In the claims, as well as in the specification above, all transitional phrases such as “comprising,” “including,” “carrying,” “having,” “containing,” “involving,” “holding,” “composed of,” and the like are to be understood to be open-ended, i.e., to mean including but not limited to. Only the transitional phrases “consisting of” and “consisting essentially of” shall be closed or semi-closed transitional phrases, respectively, as set forth in the United States Patent Office Manual of Patent Examining Procedures, Section 2111.03.

(336) The claims should not be read as limited to the described order or elements unless stated to that effect. It should be understood that various changes in form and detail may be made by one of ordinary skill in the art without departing from the spirit and scope of the appended claims. All

embodiments that come within the spirit and scope of the following claims and equivalents thereto are claimed.

Claims

1. An apparatus for displaying an image comprising: an input image node for providing image modulated light; a first optical substrate comprising at least one waveguide layer configured to propagate the modulated light in a first direction, wherein the at least one waveguide layer of the first optical substrate comprises at least one grating lamina configured to extract the modulated light from the first optical substrate along the first direction; a second optical substrate comprising at least one waveguide layer configured to propagate the modulated light in a second direction, wherein the at least one waveguide layer of the second optical substrate comprises at least one grating lamina configured to extract the modulated light from the second optical substrate along the second direction; wherein the at least one grating lamina of the first optical substrate is configured to couple the modulated light into the first optical substrate; the at least one grating lamina of the second optical substrate is configured to couple the modulated light extracted from the first optical substrate into the second optical substrate; and the at least one grating lamina of at least one of the first and second optical substrates has a k-vector that varies along the respective direction of light propagation.
 2. The apparatus of claim 1, wherein the input image node comprises at least one of microdisplay, laser, and collimating optics.
 3. The apparatus of claim 1, wherein at least one grating lamina of at least one of the first and second optical substrates has a varying thickness.
 4. The apparatus of claim 1, wherein the at least one grating lamina of at least one of the first and second optical substrates comprises an SBG that is in a switching mode or in a passive mode.
 5. The apparatus of claim 1, wherein the at least one grating lamina in at least one of the first and second optical substrates comprises multiplex gratings of at least two different monochromatic prescriptions.
 6. The apparatus of claim 1, comprising multiple grating laminas having the same surface grating frequency but different k-vectors, wherein the multiple grating laminas are configured to divide the input image field of view into multiple angular intervals.
 7. The apparatus of claim 1, wherein at least one of the first and second optical substrates is curved in at least one orthogonal plane.
 8. The apparatus of claim 1, wherein the light extracted from the first and second optical substrates provides uniform illumination in any field of view direction.
-