

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407601
Kind Code	B1
Date of Patent	September 02, 2025
Inventor(s)	Morris; Robert Paul

Routing methods, systems, and computer program products

Abstract

Methods and systems are described for routing based on a path-based protocol address. Data is detected, by a current node in a current location in a network path, in a data unit that is specified according to a network protocol and that includes a first path-based protocol address including a plurality of path segment identifiers that identify respective path segments of a network path for transmitting data from a source node to a destination node. A current-next path segment identifier is detected, based on the current location, that identifies a current-next path segment in the plurality for transmitting the data from the current node to a next node in the network path. A current-next network interface id determined, based on the current-next path segment identifier, that is included in the current-next path segment. The data is sent, via the current-next network interface, to the next node.

Inventors:	Morris; Robert Paul (Cary, NC)
Applicant:	MORRIS ROUTING TECHNOLOGIES, LLC (Plano, TX)
Family ID:	52006465
Assignee:	Morris Routing Technologies, LLC (Plano, TX)
Appl. No.:	18/357816
Filed:	July 24, 2023

Related U.S. Application Data

continuation parent-doc US 17235923 20210420 US 11784914 child-doc US 18357816
continuation parent-doc US 16796931 20200220 US 11012344 20210518 child-doc US 17235923
continuation parent-doc US 16195830 20181119 US 10594594 20200317 child-doc US 16796931
continuation parent-doc US 16181286 20181105 US 10757020 20200825 child-doc US 16195830
continuation parent-doc US 14274632 20140509 US 10904144 20210126 child-doc US 16181286
continuation-in-part parent-doc US 13727649 20121227 ABANDONED child-doc US 14274632
continuation-in-part parent-doc US 13727662 20121227 ABANDONED child-doc US 14274632

continuation-in-part parent-doc US 13727653 20121227 ABANDONED child-doc US 14274632
continuation-in-part parent-doc US 13727651 20121227 ABANDONED child-doc US 14274632
continuation-in-part parent-doc US 13727657 20121227 ABANDONED child-doc US 14274632
continuation-in-part parent-doc US 13727655 20121227 ABANDONED child-doc US 14274632
continuation-in-part parent-doc US 13727647 20121227 ABANDONED child-doc US 14274632
continuation-in-part parent-doc US 13727652 20121227 ABANDONED child-doc US 14274632
us-provisional-application US 61897234 20131030
us-provisional-application US 61833565 20130611
us-provisional-application US 61831932 20130606
us-provisional-application US 61830064 20130601
us-provisional-application US 61822978 20130514
us-provisional-application US 61822386 20130512

Publication Classification

Int. Cl.: **H04L45/16** (20220101); **H04L45/00** (20220101); **H04L45/02** (20220101); **H04L45/12** (20220101); **H04L45/50** (20220101); **H04L45/745** (20220101); **H04L49/901** (20220101); **H04L61/4511** (20220101); **H04L61/5007** (20220101)

U.S. Cl.:

CPC **H04L45/16** (20130101); **H04L45/02** (20130101); **H04L45/04** (20130101); **H04L45/22** (20130101); **H04L45/50** (20130101); **H04L45/745** (20130101); **H04L49/901** (20130101); H04L45/126 (20130101); H04L61/4511 (20220501); H04L61/5007 (20220501)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6381735	12/2001	Hunt	714/E11.209	G06F 11/3612
7451381	12/2007	Miller	714/776	H04L 1/1819
7817631	12/2009	Qian	370/392	H04L 69/164
7889743	12/2010	Evans	370/389	H04L 1/0083
8645990	12/2013	Soukup	725/34	H04N 21/23424
9112734	12/2014	Edwards	N/A	H04L 43/062
9929946	12/2017	Filsfils	N/A	H04L 69/166
10601724	12/2019	Filsfils	N/A	H04L 43/0888
2002/0191605	12/2001	Lunteren	370/389	H04L 47/43
2003/0076840	12/2002	Rajagopal	370/465	H04L 41/0213
2004/0213291	12/2003	Beshai	370/473	H04L 49/90
2005/0010420	12/2004	Russlies	704/277	G01C 21/3629
2007/0076680	12/2006	Amram	370/349	H04L 1/0083
2010/0241759	12/2009	Smith	709/233	H04L 47/10
2011/0317580	12/2010	Kozisek	370/252	H04L 43/0894

2012/0230214	12/2011	Kozisek	370/252	H04W 24/02
2012/0230338	12/2011	Ganeshalingam	370/392	H04L 45/00
2012/0271719	12/2011	Straley	705/14.66	G06Q 30/02
2012/0320784	12/2011	Edwards	370/252	H04L 43/04
2012/0330804	12/2011	Morrill	705/34	H04M 15/854
2014/0169173	12/2013	Naouri	370/237	H04L 49/351
2014/0169370	12/2013	Filsfils	370/392	H04L 69/166
2014/0269266	12/2013	Filsfils	370/228	H04L 45/02
2018/0083871	12/2017	Filsfils	N/A	H04L 45/38

OTHER PUBLICATIONS

Order Granting Request for Ex Parte Reexamination for U.S. Pat. No. 12,058,042, dated May 13, 2025. cited by applicant

Papers in Case No. 4:24-cv-00623. cited by applicant

Papers in Case No. 4:24-cv-00624. cited by applicant

Papers in Case No. 4:24-cv-00625. cited by applicant

Papers in Case No. 4:24-cv-00626. cited by applicant

Papers in U.S. Appl. No. 18/357,806 dated Jul. 15, 2025. cited by applicant

Papers in U.S. Appl. No. 19/185,200 dated Jul. 8, 2025. cited by applicant

Papers in U.S. Appl. No. 19/185,210 dated Jul. 2, 2025. cited by applicant

Primary Examiner: Chu; Wutchung

Assistant Examiner: Belete; Berhanu D

Attorney, Agent or Firm: The Caldwell Firm, LLC

Background/Summary

RELATED APPLICATIONS (1) The present application is a continuation of and claims priority to U.S. application Ser. No. 17/235,923 filed Apr. 20, 2021 and entitled “ROUTING METHODS, SYSTEMS, AND COMPUTER PROGRAM PRODUCTS” which, in turn, is a continuation of and claims priority to U.S. application Ser. No. 16/796,931 filed Feb. 20, 2020 and entitled “ROUTING METHODS, SYSTEMS, AND COMPUTER PROGRAM PRODUCTS” which, in turn, is a continuation of and claims priority to U.S. application Ser. No. 16/195,830 filed Nov. 19, 2018 and entitled “ROUTING METHODS, SYSTEMS, AND COMPUTER PROGRAM PRODUCTS” which, in turn, is a continuation of and claims priority to U.S. Application No. U.S. application Ser. No. 16/181,286 (US 2019-0149449 A1) filed Nov. 5, 2018 and entitled “ROUTING METHODS, SYSTEMS, AND COMPUTER PROGRAM PRODUCTS” which, in turn, is a continuation of and claims priority to U.S. application Ser. No. 14/274,632 (US 2014-0365682 A1) filed May 9, 2014 and entitled “Methods, Systems, and Computer Program Products for Associating a Name with a Network Path” which, in turn, is a continuation-in-part of and claims priority to: U.S. application Ser. No. 13/727,647 (US 2014-0189152 A1) filed Dec. 27, 2012 and entitled “Methods, Systems, and Computer Program Products for Identifying a Protocol Address based on Path Information,” U.S. application Ser. No. 13/727,649 (US 2014-0189081 A1) filed Dec. 27, 2012 and entitled “Methods, Systems, and Computer Program Products for Assigning an Interface Identifier to a Network Interface,” U.S. application Ser. No. 13/727,651 (US 2014-0189045 A1) filed Dec. 27, 2012 and entitled “Methods, Systems, and Computer Program Products for Routing Based on a Nested Protocol Address,” U.S. application Ser. No. 13/727,652 (US 2014-0189153 A1) filed Dec.

27, 2012 and entitled “Methods, Systems, and Computer Program Products for Routing Based on a Scope-Specific Address,” U.S. application Ser. No. 13/727,653 (US 2014-0189159 A1) filed Dec. 27, 2012 and entitled “Methods, Systems, and Computer Program Products for Identifying a Protocol Address in a Scope-Specific Address Space,” U.S. application Ser. No. 13/727,655 (US 2014-0189154 A1) filed Dec. 27, 2012 and entitled “Methods, Systems, and Computer Program Products for Determining a Shared Identifier for a Hop in a Network,” U.S. application Ser. No. 13/727,657 (US 2014-0189155 A1) filed Dec. 27, 2012 and entitled “Methods, Systems, and Computer Program Products for Determining a Protocol Address For a Node,” and U.S. application Ser. No. 13/727,662 (US 2014-0189156 A1) filed Dec. 27, 2012 and entitled “Methods, Systems, and Computer Program Products for Routing Based on a Path-Based Protocol Address,” where U.S. application Ser. No. 14/274,632 further claims priority to U.S. Provisional Application No. 61/822,978 filed May 14, 2013 and entitled “Methods, Systems, and Computer Program Products For Transmitting Data Via A Scope-Specific Protocol Address,” U.S. Provisional Application No. 61/822,386 filed May 12, 2013 and entitled “Methods, Systems, and Computer Program Products For Associating a Name With a Network Path,” U.S. Provisional Application No. 61/897,234 filed Oct. 30, 2013 and entitled “Methods, Systems, and Computer Program Products For Transmitting Data Via A Variable Length Protocol Address,” U.S. Provisional Application No. 61/830,064 filed Jun. 1, 2013 and entitled “Methods, Systems, and Computer Program Products For Adjusting A Separator Field For A Protocol Address,” U.S. Provisional Application No. 61/831,932 filed Jun. 6, 2013 and entitled “Methods, Systems, and Computer Program Products for Source Routing,” and U.S. Provisional Application No. 61/833,565 filed Jun. 11, 2013 and entitled “Methods, Systems, and Computer Program Products For Changing Protocol Address By A Network Relay,” the entire contents of all of the above are herein incorporated by reference.

BACKGROUND

- (1) It is unlikely that the designers of the early network, which is referred to as the “Internet” expected it to become as large as it has become. The fact that the global Internet Protocol (IP) address space for 32-bit addresses has been fully allocated is evidence of this. As the Internet grows, new problems will arise and some current problems are getting worse. For example, while network speeds and bandwidth are increasing, so are causes of network latency.
- (2) The Internet Engineering Task Force (IETF) has taken steps at various times in the past and are presently taking steps to address a number of problems resulting from the Internet's growth. Problems addressed by the IETF are described in a number of “Request for Comments” (RFC) documents published by the IETF. Documents referenced herein and included by reference include: “Request for Comments” (RFC) document RFC 791 edited by J. Postel, titled “Internet Protocol, DARPA Internet Protocol Specification”, published by the IETF in September, 1981; “Request for Comments” (RFC) document RFC 1519 by V. Fuller, et al, titled “Classless Inter-Domain Routing (CIDR): An Address Assignment and Aggregation Strategy”, published by the Internet Engineering Task Force (IETF), in June, 1999; “Request for Comments” (RFC) document RFC 2460 by S. Deering, et al, titled “Internet Protocol, Version 6, (IPv6) Specification”, published by the IETF in December, 1998; “Request for Comments” (RFC) document RFC 3513 by R. Hinden, et al, titled “Internet Protocol Version 6 (IPv6) Addressing Architecture”, published by the IETF in April, 2003; and “Request for Comments” (RFC) document RFC 2374 by R. Hinden, et al, titled “Aggregatable Global Unicast Address Format”, published by the IETF in July, 1998.
- (3) RFC 791 states, “The internet protocol implements two basic functions: addressing and fragmentation”. RFC 791 goes on to state, “A distinction is made between names, addresses, and routes. A name indicates what we seek. An address indicates where it is. A route indicates how to get there. The internet protocol deals primarily with addresses. It is the task of higher level (i.e., host-to-host or application) protocols to make the mapping from names to addresses. The internet module maps internet addresses to local net addresses. It is the task of lower level (i.e., local net or

gateways) procedures to make the mapping from local net addresses to routes”.

(4) As demonstrated in the RFCs listed above, addressing has been a source of a number of problems. In order to address a number of current and future problems facing the Internet, the subject matter described herein challenges the distinctions asserted in RFC 791 between and among names, addresses, and routes.

(5) Accordingly, there exists a need for methods, systems, and computer program products for routing based on a path-based protocol address.

SUMMARY

(6) The following presents a simplified summary of the disclosure in order to provide a basic understanding to the reader. This summary is not an extensive overview of the disclosure and it does not identify key/critical elements of the invention or delineate the scope of the invention. Its sole purpose is to present some concepts disclosed herein in a simplified form as a prelude to the more detailed description that is presented later.

(7) Methods and systems are described for routing based on a path-based protocol address. In one aspect, the method includes detecting, by a current node in a current location in a network path, data in a data unit that is specified according to a network protocol and that includes a first path-based protocol address including a plurality of path segment identifiers that identify respective path segments of a network path for transmitting data from a source node to a destination node. The method further includes detecting, based on the current location, a current-next path segment identifier that identifies a current-next path segment in the plurality for transmitting the data from the current node to a next node in the network path. The method still further includes determining, based on the current-next path segment identifier, a current-next network interface that is included in the current-next path segment; and. The method also includes sending, via the current-next network interface, the data to the next node. Performing at least one element identified above as included in the method includes execution of an instruction by a processor.

(8) Further, a system for routing based on a path-based protocol address is described. The system includes an in-data handler component that is operable for and/or otherwise included in detecting, by a current node in a current location in a network path, data in a data unit that is specified according to a network protocol and that includes a first path-based protocol address including a plurality of path segment identifiers that identify respective path segments of a network path for transmitting data from a source node to a destination node. The system further includes a routing component operable for and/or otherwise included in detecting, based on the current location, a current-next path segment identifier that identifies a current-next path segment in the plurality for transmitting the data from the current node to a next node in the network path. The system still further includes a forwarding component operable for and/or otherwise included in determining, based on the current-next path segment identifier, a current-next network interface that is included in the current-next path segment; and. The system still further includes an out-data handler component operable for and/or otherwise included in sending, via the current-next network interface, the data to the next node. The system also includes a processor, wherein at least one of the in-data handler component, the routing component, the forwarding component, and the out-data handler component includes an instruction that is executed by the processor during operation of the system.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Objects and advantages of the present invention will become apparent to those skilled in the art upon reading this description in conjunction with the accompanying drawings, in which like reference numerals have been used to designate like or analogous elements, and in which:

- (2) FIG. 1 is a block diagram illustrating an exemplary hardware device included in and/or otherwise providing an execution environment in which the subject matter may be implemented;
- (3) FIG. 2 is a flow diagram illustrating a method for routing based on a path-based protocol address according to an aspect of the subject matter described herein;
- (4) FIG. 3 is a block diagram illustrating an arrangement of components for routing based on a path-based protocol address according to another aspect of the subject matter described herein;
- (5) FIG. 4A is a block diagram illustrating an arrangement of components for routing based on a path-based protocol address according to another aspect of the subject matter described herein;
- (6) FIG. 4B is a block diagram illustrating an arrangement of components for routing based on a path-based protocol address according to another aspect of the subject matter described herein;
- (7) FIG. 4C is a block diagram illustrating an arrangement of components for routing based on a path-based protocol address according to another aspect of the subject matter described herein;
- (8) FIG. 5A is a network diagram illustrating an exemplary system for routing based on a path-based protocol address according to another aspect of the subject matter described herein;
- (9) FIG. 5B is a network diagram illustrating an exemplary system for routing based on a path-based protocol address according to another aspect of the subject matter described herein;
- (10) FIG. 5C is a network diagram illustrating an exemplary system for routing based on a path-based protocol address according to another aspect of the subject matter described herein;
- (11) FIG. 6A is a diagram illustrating an exemplary representation of a path-based protocol address according to another aspect of the subject matter described herein;
- (12) FIG. 6B is a diagram illustrating an exemplary representation of a path-based protocol address according to another aspect of the subject matter described herein;
- (13) FIG. 6C is a diagram illustrating an exemplary representation of a path-based protocol address according to another aspect of the subject matter described herein;
- (14) FIG. 6D is a diagram illustrating an exemplary representation of a path-based protocol address according to another aspect of the subject matter described herein;
- (15) FIG. 6E is a diagram illustrating an exemplary representation of a path-based protocol address according to another aspect of the subject matter described herein;
- (16) FIG. 7 is a flow diagram illustrating a method for determining a protocol address for a node according to an aspect of the subject matter described herein;
- (17) FIG. 8 is a block diagram illustrating an arrangement of components for determining a protocol address for a node according to another aspect of the subject matter described herein;
- (18) FIG. 9 is a flow diagram illustrating a method for routing based on a nested protocol address according to an aspect of the subject matter described herein;
- (19) FIG. 10 is a flow diagram illustrating a method for routing based on a scope-specific address space according to an aspect of the subject matter described herein;
- (20) FIG. 11 is a flow diagram illustrating a method for identifying a protocol address in a scope-specific address space according to an aspect of the subject matter described herein;
- (21) FIG. 12 is a block diagram illustrating an arrangement of components for identifying a protocol address in a scope-specific address space according to another aspect of the subject matter described herein;
- (22) FIG. 13 is a flow diagram illustrating a method for identifying a protocol address based on path information according to an aspect of the subject matter described herein;
- (23) FIG. 14 is a block diagram illustrating an arrangement of components for identifying a protocol address based on path information according to another aspect of the subject matter described herein;
- (24) FIG. 15 is a flow diagram illustrating a method for assigning an interface identifier to a network interface according to an aspect of the subject matter described herein; and
- (25) FIG. 16 is a block diagram illustrating an arrangement of components for assigning an interface identifier to a network interface according to another aspect of the subject matter

described herein.

DETAILED DESCRIPTION

(26) One or more aspects of the disclosure are described with reference to the drawings, wherein like reference numerals are generally utilized to refer to like elements throughout, and wherein the various structures are not necessarily drawn to scale. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of one or more aspects of the disclosure. It may be evident, however, to one skilled in the art, that one or more aspects of the disclosure may be practiced with a lesser degree of these specific details. In other instances, well-known structures and devices are shown in block diagram form in order to facilitate describing one or more aspects of the disclosure. It is to be understood that other embodiments and/or aspects may be utilized and structural and functional modifications may be made without departing from the scope of the subject matter disclosed herein.

(27) The use of “including”, “comprising”, “having”, and variations thereof are meant to encompass the items listed thereafter and equivalents thereof as well as additional items and equivalents thereof. Terms used to describe interoperation and/or coupling between components are intended to include both direct and indirect interoperation and/or coupling, unless otherwise indicated. Exemplary terms used in describing interoperation and/or coupling include “mounted,” “connected,” “attached,” “coupled,” “communicatively coupled,” “operatively coupled,” “invoked”, “called”, “provided to”, “received from”, “identified to”, “interoperated” and similar terms and their variants.

(28) As used herein, any reference to an entity “in” an association is equivalent to describing the entity as “included in and/or identified by” the association, unless explicitly indicated otherwise.

(29) Unless otherwise defined, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure belongs.

Although methods, components, and devices similar or equivalent to those described herein can be used in the practice or testing of the subject matter described herein, suitable methods, components, and devices are described below.

(30) All publications, patent applications, patents, and other references mentioned herein are incorporated by reference in their entirety. In case of conflict, the present disclosure, including definitions, will control. In addition, the materials, methods, and examples are illustrative only and not intended to be limiting.

(31) An exemplary device included in an execution environment that may be programmed, adapted, modified, and/or otherwise configured according to the subject matter is illustrated in FIG. 1. An “execution environment”, as used herein, is an arrangement of hardware and, in some aspects, software that may be further modified, transformed, and/or otherwise configured to include and/or otherwise host an arrangement of components to perform a method of the subject matter described herein. An execution environment includes and/or is otherwise provided by one or more devices. The execution environment is said to be the execution environment “of” the device and/or devices. An execution environment may be and/or may include a virtual execution environment including software components operating in a host execution environment. Exemplary devices included in and/or otherwise providing suitable execution environments that may be adapted, programmed, and/or otherwise modified according to the subject matter include a workstation, a desktop computer, a laptop or notebook computer, a server, a handheld computer, a mobile telephone or other portable telecommunication device, a media playing device, a gaming system, a tablet computer, a portable electronic device, a handheld electronic device, a multiprocessor device, a distributed system, a consumer electronic device, a router, a network server, or any other type and/or form of computing, telecommunications, network, and/or media device that is suitable to perform the subject matter described herein. Those skilled in the art will understand that the components illustrated in FIG. 1 are exemplary and may vary by particular execution environment.

(32) FIG. 1 illustrates a hardware device **100** included in an execution environment **102**. FIG. 1

illustrates that execution environment **102** includes a processor **104**, such as one or more microprocessors; a physical processor memory **106** including storage locations identified by addresses in a physical memory address space of processor **104**; a persistent secondary storage **108**, such as one or more hard drives and/or flash storage media; an input device adapter **110**, such as a key or keypad hardware, a keyboard adapter, and/or a mouse adapter; an output device adapter **112**, such as a display and/or an audio adapter to present information to a user; a network interface component, illustrated by a network interface adapter **114**, to communicate via a network such as a LAN and/or WAN; and a mechanism that operatively couples elements **104-114**, illustrated as a bus **116**. Elements **104-114** may be operatively coupled by various means. Bus **116** may comprise any type of bus architecture, including a memory bus, a peripheral bus, a local bus, and/or a switching fabric.

(33) As used herein a “processor” is an instruction execution machine, apparatus, or device. A processor may include one or more electrical, optical, and/or mechanical components that operate in interpreting and executing program instructions. Exemplary processors include one or more microprocessors, digital signal processors (DSPs), graphics processing units, application-specific integrated circuits (ASICs), optical or photonic processors, and/or field programmable gate arrays (FPGAs). Processor **104** may access instructions and data via one or more memory address spaces in addition to the physical memory address space. A memory address space includes addresses identifying locations in a processor memory. The addresses in a memory address space are included in defining a processor memory. Processor **104** may have more than one processor memory. Thus, processor **104** may have more than one memory address space. Processor **104** may access a location in a processor memory by processing an address identifying the location. The processed address may be identified by an operand of an instruction and/or may be identified by a register and/or other portion of processor **104**.

(34) FIG. **1** illustrates a virtual processor memory **118** spanning at least part of physical processor memory **106** and may span at least part of persistent secondary storage **108**. Virtual memory addresses in a memory address space may be mapped to physical memory addresses identifying locations in physical processor memory **106**. An address space including addresses that identify locations in a virtual processor memory is referred to as a “virtual memory address space”; its addresses are referred to as “virtual memory addresses”; and its processor memory is referred to as a “virtual processor memory” or “virtual memory”. The term “processor memory” may refer to physical processor memory, such as processor memory **106**, and/or may refer to virtual processor memory, such as virtual processor memory **118**, depending on the context in which the term is used.

(35) Physical processor memory **106** may include various types of memory technologies. Exemplary memory technologies include static random access memory (SRAM), Burst SRAM or SynchBurst SRAM (BSRAM), Dynamic random access memory (DRAM), Fast Page Mode DRAM (FPM DRAM), Enhanced DRAM (EDRAM), Extended Data Output RAM (EDO RAM), Extended Data Output DRAM (EDO DRAM), Burst Extended Data Output DRAM (BEDO DRAM), Enhanced DRAM (EDRAM), synchronous DRAM (SDRAM), JEDEC SRAM, PC **100** SDRAM, Double Data Rate SDRAM (DDR SDRAM), Enhanced SDRAM (ESDRAM), SyncLink DRAM (SLDRAM), Ferroelectric RAM (FRAM), RAMBUS DRAM (RDRAM) Direct DRAM (DRDRAM), and/or XDR™ DRAM. Physical processor memory **106** may include volatile memory as illustrated in the previous sentence and/or may include non-volatile memory such as non-volatile flash RAM (NVRAM) and/or ROM.

(36) Persistent secondary storage **108** may include one or more flash memory storage devices, one or more hard disk drives, one or more magnetic disk drives, and/or one or more optical disk drives. Persistent secondary storage may include a removable data storage medium. The drives and their associated computer readable media provide volatile and/or nonvolatile storage for computer-executable instructions, data structures, program components, and other data.

(37) Execution environment **102** may include software components stored in persistent secondary storage **108**, in remote storage accessible via a network, and/or in a processor memory. FIG. **1** illustrates execution environment **102** including an operating system **120**, one or more applications **122**, and other program code and/or data components illustrated by other libraries and subsystems **124**. In an aspect, some or all software components may be stored in locations accessible to processor **104** in a shared memory address space shared by the software components. The software components accessed via the shared memory address space may be stored in a shared processor memory defined by the shared memory address space. In another aspect, a first software component may be stored in one or more locations accessed by processor **104** in a first address space and a second software component may be stored in one or more locations accessed by processor **104** in a second address space. The first software component is stored in a first processor memory defined by the first address space and the second software component is stored in a second processor memory defined by the second address space.

(38) Execution environment **102** may receive user-provided information via one or more input devices illustrated by an input device **128**. Input device **128** provides input information to other components in execution environment **102** via input device adapter **110**. Execution environment **102** may include an input device adapter for a keyboard, a touch screen, a microphone, a joystick, a television receiver, a video camera, a still camera, a document scanner, a fax, a phone, a modem, a network interface adapter, and/or a pointing device, to name a few exemplary input devices.

(39) Input device **128** included in execution environment **102** may be included in device **100** as FIG. **1** illustrates or may be external (not shown) to device **100**. Execution environment **102** may include one or more internal and/or external input devices. External input devices may be connected to device **100** via corresponding network interfaces such as a serial port, a parallel port, and/or a universal serial bus (USB) port. Input device adapter **110** may receive input and provide a representation to bus **116** to be received by processor **104**, physical processor memory **106**, and/or other components included in execution environment **102**.

(40) An output device **130** in FIG. **1** exemplifies one or more output devices that may be included in and/or that may be external to and operatively coupled to device **100**. For example, output device **130** is illustrated connected to bus **116** via output device adapter **112**. Output device **130** may be a display device. Exemplary display devices include liquid crystal displays (LCDs), light emitting diode (LED) displays, and projectors. Output device **130** presents output of execution environment **102** to one or more users. In some embodiments, an input device may also include an output device. Examples include a phone, a joystick, and/or a touch screen. In addition to various types of display devices, exemplary output devices include printers, speakers, tactile output devices such as motion-producing devices, and other output devices producing sensory information detectable by a user. Sensory information detected by a user is referred herein to as “sensory input” with respect to the user.

(41) A device included in and/or otherwise providing an execution environment may operate in a networked environment communicating with one or more devices via one or more network interface components. FIG. **1** illustrates network interface adapter (NIA) **114** as a network interface component included in execution environment **102** to operatively couple device **100** to a network. A network interface component includes a network interface hardware (NIH) component and optionally a network interface software (NIS) component. Exemplary network interface components include network interface controllers, network interface cards, network interface adapters, and line cards. A node may include one or more network interface components to interoperate with a wired network and/or a wireless network. Exemplary wireless networks include a BLUETOOTH network, a wireless 802.11 network, and/or a wireless telephony network (e.g., AMPS, TDMA, CDMA, GSM, GPRS UMTS, and/or PCS network). Exemplary network interface components for wired networks include Ethernet adapters, Token-ring adapters, FDDI adapters, asynchronous transfer mode (ATM) adapters, and modems of various types. Exemplary wired

and/or wireless networks include various types of LANs, WANs, and/or personal area networks (PANs). Exemplary networks also include intranets and internets such as the Internet.

(42) The terms “network node” and “node” in this document both refer to a device having a network interface component to operatively couple the device to a network. Further, the terms “device” and “node” used herein refer to one or more devices and nodes, respectively, providing and/or otherwise included in an execution environment unless clearly indicated otherwise.

(43) As used herein, the term “network protocol” refers to a set of rules, conventions, and/or schemas that govern how nodes exchange information over a network. The set may define, for example, a convention and/or a data structure. The term “network path” as used herein refers to a sequence of nodes in a network that are communicatively coupled to transmit data in one or more data units of a network protocol between a pair of nodes in the network.

(44) A “data unit”, as the term is used herein, is an entity specified according to a network protocol to transmit data between a pair of nodes in a network path to send the data from a source node to a destination node that includes an identified protocol endpoint of the network protocol. A network protocol explicitly and/or implicitly specifies and/or otherwise identifies a schema that defines one or more of a rule for a format for a valid data unit and a vocabulary for content of a valid data unit. One example of a data unit is an Internet Protocol (IP) packet. The Internet Protocol defines rules for formatting an IP packet that defines a header to identify a destination address that identifies a destination node and a payload portion to include a representation of data to be delivered to the identified destination node. Various address types are specified defining a vocabulary for one or more address portions of an IP data unit. The terms “data unit”, “frame”, “data packet”, and “packet” are used interchangeably herein. One or more data units of a first network protocol may transmit a “message” of a second network protocol. For example, one or more data units of the IP protocol may include a TCP message. In another example, one or more TCP data units may transmit an HTTP message. A message may be empty.

(45) How data is packaged in one more data units for a network protocol may vary as the data traverses a network path from a source node to a destination node. Data may be transmitted in a single data unit between two consecutive nodes in a network path. Additionally, data may be exchanged between a pair of consecutive nodes in several data units each including a portion of the data. Data received in a single data unit by a node in a network path may be split into portions included in several respective data units to transmit to a next node in the network path. Portions of data received in several data units may be combined into a single data unit to transmit by a node in a network path. For purposes of describing the subject matter, a data unit in which data is received by a node is referred to as a different data unit than a data unit in which the data is forwarded by the node.

(46) A “protocol address”, as the term is used herein, for a network protocol is an identifier of a protocol endpoint that may be represented in a data unit of the network protocol. For example, 192.168.1.1 is an IP protocol address represented in a human readable format that may be represented in an address portion of an IP header to identify a source and/or a destination IP protocol endpoint. A protocol address differs from a symbolic identifier, defined below, in that a symbolic identifier, with respect to a network protocol, maps to a protocol address. Thus, “www.mynode.com” may be a symbolic identifier for a node in a network when mapped to the protocol address 192.168.1.1. An identifier may be both a symbolic identifier and a protocol address depending on its role with respect to its use for a particular network protocol.

(47) Since a protocol endpoint is included in a node and is accessible via a network via a network interface, a protocol address identifies a node and identifies a network interface of the node. A network interface may include one or more NICs operatively coupled to a network.

(48) A node in a pair of nodes in a network path at one end of the sequence of nodes in the network path and/or the other end is referred to herein as a “path end node”. Note that a node may have two NICs with one NIC at each end of a network path. A network path may be included as a portion of

another network path that communicatively couples a same pair of nodes. Data may be transmitted via the sequence of nodes in a network path between path end nodes communicatively coupled via the network path. Data may be transmitted in one or both directions depending on an ordering of the nodes in the sequence.

(49) The term “hop” as used herein refers to a pair of consecutive nodes in a network path to transmit, via a network protocol, data sent from a source node to a destination node. A “hop path” is thus a sequence of hops in a network that respectively include a sequence of pairs of consecutive nodes included in transmitting data from a first path end node of the network path to a second path end node of the network path.

(50) The term “path-based protocol address” as used herein refers to a protocol address for a network protocol that includes one or more path segment identifiers that identify one or more respective portions of a network path identified by the path-based protocol address. A “node-based protocol address” is a path-based protocol address that includes a plurality of node identifiers that identify a sequence of nodes in a network path. A “network-interface-based protocol address” is a path-based protocol address that includes a plurality of interface identifiers that identify a sequence of network interfaces in a network path. A “NIC-based protocol address” is a type of network-interface-based protocol address that includes a plurality of identifiers that identify a sequence of network interface components. A “hop-based protocol address” is a type path-based protocol address since a hop is a type of network path.

(51) Given the above definitions, note that the terms “network path” and “hop” may be defined in terms of network interfaces. A “network path” and a “hop path” include a sequence of network interfaces in a network that are included in transmitting data between a pair of path end nodes in the network. A “hop” refers to at least part of a network path that includes a pair of consecutive network interfaces in a sequence of network interfaces in a network path. A “network path” is thus a sequence of hops in a network that respectively includes a sequence of pairs of consecutive network interfaces included in transmitting data from a first path end node of the network path to a second path end node of the network path.

(52) The term “network topology” or “topology”, for short, as used herein refers to a representation of protocol endpoints and/or nodes in a network, and representations of hops representing communicative couplings between and/or among the protocol endpoints and/or nodes in the network. A network may have different network topologies with respect to different network protocols. A network topology may represent physical communicative couplings between nodes in the network. A network topology may represent logical couplings between protocol endpoints and/or nodes of a particular network protocol or a particular type of network protocol.

(53) The domain name system (DNS) of the Internet operates based on an application layer protocol defined by the DNS. The nodes in the DNS are communicatively coupled via the DNS protocol and may be represented by a logical network topology. A DNS system includes nodes connected via the DNS protocol. The DNS system has a network topology defined by nodes that include protocol endpoints of the DNS protocol. In still another example, a token-ring network has a circular topology at the link layer but may have a star topology at the physical layer.

(54) As used herein, an “entity-specific address space” refers to an address space defined for a specific entity where the addresses in the address space operate as identifiers in the context of the entity. An address from an entity-specific address space is referred to herein as an “entity-specific address”. An address is “entity-specific” in that what it identifies is based on the entity to which it is specific. Another address having the same form and content may identify a different entity when in an address space specific to another entity. Addresses in an entity-specific address space operate as identifiers in the context of an entity to which they are “specific” as defined by the specific association of the address space and the entity. Without knowledge of the entity to which an entity-specific address space is specific, what an address in the entity-specific address space identifies is indeterminate. The terms “entity-specific address” and “entity-specific identifier” are used

interchangeably herein. An entity-specific address may identify an entity included in the entity to which the address is specific or may identify an entity external to the entity to which the address is specific. The fact that an address is entity-specific does not define a scope for the address.

(55) A portion of a network is a type of entity. A type of entity-specific address space described herein is a scope-specific address space. As used herein, a “scope-specific address space”, specific to a particular region of a network, is an address space defined for the particular network region, where an address in the scope-specific protocol address operates as identifier, according to a network protocol, of a protocol endpoint in a node outside of the particular region when processed in the context of a node in the particular region. The region is indicated by the span of an indicated scope. The terms “region” and “zone” are used interchangeably herein. An address from a scope-specific address space is referred to herein as a “scope-specific protocol address”. An address is “scope-specific” in that what protocol endpoint it identifies depends on the region to which it is specific. Another address having the exact same form and content may identify a different protocol endpoint when in an address space that is specific to another region. A protocol address in a scope-specific address space serves as an identifier in the context of a node in a region to which the scope-specific address space is “specific” as defined by an association of the address space and the region indicated by the scope. Without knowledge of the particular region to which a scope-specific address space is specific, what a scope-specific protocol address in the scope-specific address space identifies is indeterminate. The terms “scope-specific protocol address” and “scope-specific protocol identifier” are used interchangeably herein. Types of scope-specific address spaces indicating exemplary spans include site-specific, LAN-specific, subnet-specific, city-specific, business-specific, and node-specific.

(56) For a network protocol, an address in a scope-specific address space serves as an identifier of a protocol endpoint in a node. Data may be received via the protocol endpoint from a network via one or more network interfaces that operatively couple the node to the network. Data may be sent via the protocol endpoint to transmit over the network via the one or more network interfaces in the node. Since a protocol endpoint of a network protocol is included in a node and is accessible via a network via a network interface, a protocol address identifying the protocol endpoint also identifies the node and identifies a network interface of the node.

(57) As used herein, a “node-specific address space” is a scope-specific address space defined for a specific node in a network, where the addresses in the node-specific address space operate as identifiers of nodes and/or network interfaces in the network when processed in the context of the specific node. An address from a node-specific address space is referred to herein as a “node-specific address”. An address is “node-specific” in that what it identifies depends on the node to which is defined as specific. Another address having the exact same form and content may identify a different node when in an address space specific to another node. Addresses in a node-specific address space operate as identifiers in the context of a node to which they are “specific” as defined by the specific association of the address space and the node. Without knowledge of the node to which a node-specific address space is specific, addresses in the node-specific address space are indeterminate. The terms “node-specific address” and “node-specific identifier” are used interchangeably herein. A node-specific address space is a type of scope-specific address space.

(58) The term “node” is defined above. Note that an identifier of a network interface in a network also identifies a node that includes the network interface. Thus, a network interface-specific address is also a node-specific address. Network interfaces in a node may have their own respective network interface-specific address spaces that are also node-specific. The network interface-specific address spaces may be combined to form a node-specific address space and/or may be managed as separate address spaces. The adjectives “node-specific” and “network interface-specific” may be used interchangeably.

(59) A scope-specific identifier differs from a scoped address as described in “Request for Comments” (RFC) document RFC 4007 by S. Deering, et al, titled “IPv6 Scoped Address

Architecture”, published by the IETF in December, 2006 and further described in application Ser. No. 11/962,285 (published US 2009-0161576 A1), by the present inventor, filed on 2007 Dec. 21, entitled “Methods and Systems for Sending Information to a zone Included in an Internet Network” which, as set forth earlier, are both incorporated by reference in their entirety. A scoped address space is shared by nodes in a given scope. While a link-local scoped address is specific to a particular node, a link-local scoped address simply identifies a network interface component local to the particular node. A loop-back internet address is specific to a node as well. Neither link-local scoped addresses nor loop-back addresses identify one node to another. As such, neither serves as a node-specific identifier as defined above.

(60) A “scoped address” is described by RFC 3513 and RFC 4007 as an identifier that, in a particular region of a network, serves as a protocol address of a network interface and/or a node in the particular region. The extent of the particular region is referred to as the scope of the region and thus the scope within which the identifier serves as a protocol address. A particular region included within a scope is indicated by its span. A scoped address is a valid protocol address only within a particular region as indicated by the address's indicated scope. Examples of scope indicators include node-scope where identifiers are valid only to a single node in the indicated span, LAN-scope where identifiers are valid for nodes in the span of a particular LAN, and subnet-scope where identifiers are valid only for nodes in a particular subnet. RFC 3513 currently defines support for link-local scope, site-local scope, and global scope. A data unit transmitted with a scoped address should not be delivered to node that does not have a network interface in the span indicated by the scope.

(61) “Path information” is any information that identifies a network path and/or a hop path for data transmitted via one or more specified network protocols. Path information may be identified by identifying network interfaces, NICs, nodes, and/or hops included in a network path. “Address information” is any information that identifies a protocol address that, for a network protocol, identifies a protocol endpoint. Address information may identify a unicast protocol address for a network protocol. In identifying a protocol endpoint, a protocol address identifies a node and a network interface.

(62) Those skilled in the art will understand upon reading the descriptions herein that the subject matter disclosed herein is not restricted to the network protocols described and/or their corresponding OSI layers. For ease of illustration, the subject matter is described in terms of protocols that correspond to OSI layer three, also referred to as network layer protocols, in general. Particular descriptions are based on versions of the Internet Protocol (IP). Address information may identify one or more protocol addresses. Exemplary protocol addresses include IP addresses, IPX addresses, DECNet addresses, VINES Internet Protocol addresses, and Datagram Delivery Protocol (DDP) addresses, HTTP URLs, TCP port and IP address pairs, and the like.

(63) The term “path-based address” is defined above. A “node-based address” is a path-based address where some or all of the address includes node identifiers that identify a sequence of nodes in a network path. A “network-interface-based address” is a path-based address where some or all of the address includes identifiers of network interfaces in a sequence in a network path. A “NIC-based address” is a type of network-interface-based address that identifies a sequence of network interface components. A “hop-based address” is a path-based address where some or all of the address identifies one or more hops in a network path. The protocol address types defined are not mutually exclusive.

(64) The term “metric space”, as used herein, refers to a set, as defined in mathematics, where a distance between elements of the set is defined according to a metric. Metric spaces defined in Euclidean geometry are well-known examples. Those skilled in the art of metric spaces, such as Euclidian spaces, will appreciate that a one-to-one mapping may be determined and/or otherwise identified for mapping addresses from a first coordinate space having a first origin for a metric space to addresses from a second coordinate space having a second origin in the metric space.

Given a mapping rule between a first scope-specific address space and a second scope-specific address space and a mapping between the second scope-specific address space and a third scope-specific address space based on a third coordinate space identifying a third origin in the metric space, a mapping from the first coordinate space to the third coordinate space may be determined. A mapping between coordinate spaces for a metric space may be included a coordinate shift and/or a rotation, for example. The mapping may be pre-specified and accessible to the nodes in one or both address spaces. Mapping between locations in a number of different metric spaces is well known in mathematics. For example, a top half of the surface of sphere may be mapped to a plane. Some will further appreciate that some metric spaces may be mapped to other metric spaces. Some of these mappings are one-to-one and/or onto.

(65) FIG. 3 illustrates an arrangement of components in a system that operates in an execution environment, such as execution environment **102** in FIG. 1. The arrangement of components in the system operates to perform the method illustrated in FIG. 2. The system illustrated includes an in-data handler component **302**, a routing component **304**, a forwarding component **306**, and an out-data handler component **308**. The execution environment includes a processor, such as the processor **104**, to process an instruction, during operation of the system, in at least one of the in-data handler component **302**, the routing component **304**, the forwarding component **306**, and the out-data handler component **308**.

(66) Some or all of the exemplary components illustrated in FIG. 3 may be adapted to perform the method illustrated in FIG. 2 in a number of execution environments. FIG. 4A, FIG. 4B, and FIG. 4C are each block diagrams illustrating the components of FIG. 3 and/or analogs of the components of FIG. 3 respectively adapted to operate in an execution environment **401a**, in an execution environment **401b**, and in an execution environment **401c** that are included in and/or that otherwise are provided by one or more nodes.

(67) Components, illustrated in FIG. 4A, FIG. 4B, and FIG. 4C, are respectively identified by a number followed with an alphanumeric suffix. A component may be referred to generically in the singular or the plural by dropping a suffix of a portion thereof of the component's identifier. For example, execution environments; such as the execution environment **401a**, the execution environment **401b**, the execution environment **401c**, and their adaptations and analogs; are referred to herein generically as an execution environment **401** or, when describing more than one, execution environments **401**. Other components identified with a suffix may similarly be referred to generically or as a group by dropping a suffix or a portion thereof.

(68) FIG. 1 illustrates key components of an exemplary device that may at least partially provide and/or otherwise be included in an execution environment. Some or all of the components illustrated in FIG. 4A, FIG. 4B, and FIG. 4C may be included in and/or otherwise may be combined with the components of FIG. 1 to create a variety of arrangements of components according to the subject matter described herein. Those skilled in the art will understand other execution environments in addition to the various adaptations of the execution environments described herein are suitable for hosting an adaptation of the arrangement in FIG. 3.

(69) FIGS. 5A-C respectively illustrate networks **500** including nodes that in various aspects may include adaptations of any of the execution environments **401**, illustrated in FIG. 4A, FIG. 4B, and FIG. 4C. The various illustrated nodes are operatively coupled via respective network interface components to the respective networks **500** in FIGS. 5A-C. For ease of illustration and description, each of FIGS. 5A-C includes nodes identified by a role played in sending data from one node to another. FIGS. 5A-C illustrate source nodes **502** configured to initiate a transmission of data to respective recipients, path nodes **504** configured to relay the data transmitted by respective source nodes **502**, and destination nodes **506** identified by the respective source nodes **502** as recipients of the data from source nodes **502**. In some of FIGS. 5A-C, one or more edge nodes **508** are illustrated for describing adaptations of the arrangement in FIG. 3 performing various aspects of the method illustrated in FIG. 2 operating in one or more of the roles identified.

(70) A network interface includes one or more NICs identified by a protocol address of a network protocol for sending data from a protocol endpoint identified by the network protocol and/or for receiving data for the protocol endpoint.

(71) In various contexts nodes illustrated as destination nodes **506**, edge nodes **508**, and/or path nodes **504** may operate as source nodes; some nodes illustrated as source nodes **502**, edge nodes **508**, and destination nodes **506** may operate as path nodes, and nodes illustrated as source nodes **502**, edge nodes, **508**, and/or path nodes **504** may operate as destination nodes. Exemplary nodes configured to operate as path nodes **504** include a router, a switch, a wireless access point, a bridge, a gateway, and the like.

(72) A path node **504** illustrated in any of FIGS. 5A-C and/or a node otherwise operating as a path node may include an adaptation of any execution environment **401** illustrated in FIG. 4A, FIG. 4B, and/or FIG. 4C. A path node **504** may include a first network interface component and a second network interface component. With respect to FIG. 5B, a first path node **504b1** may be operatively coupled to a first network **514b1** included in a network **500b** via a first network interface component and may be operatively coupled to a second network **514b2** via a second network interface component. The first path node **504b1** may forward data sent from a source node **502b** in the first network **514b1** for delivery via a second network **514b2** to a destination node **506b** in a third network **514b3**. The first network **514b1**, the second network **514b2**, and/or the third network **514b3** may respectively include and/or may be included in a local area network (LAN), an intranet, at least a portion of the Internet, and/or another wide area network (WAN).

(73) The network components in some nodes may be configured according to a layered design or architecture known to those skilled in the art as a “network stack”. Adaptations and/or analogs execution environments **401** in FIG. 4A, FIG. 4B, and FIG. 4C may include network components in a layered architecture, physically and/or logically. Other architectural models for network components may be included in other execution environments to send and/or receive data via a network and are considered within the scope of the subject matter described herein. Combinations of layered architectures and non-layered architectures are also considered to be within the scope of the subject matter described herein.

(74) Some components illustrated in FIG. 4A correspond to components of the layered architecture specified by the Open System Interconnection (OSI) model, known to those skilled in the art. For example, network components in FIG. 4A may comply with specifications for protocols included in the TCP/IP protocol suite. The OSI model specifies a seven-layer network stack. The TCP/IP protocol suite may be mapped to layer three and layer four of the seven layers. Those skilled in the art will understand that fewer or more layers may be included in various adaptations and analogs of the execution environments **401** illustrated in FIG. 4A, FIG. 4B, FIG. 4C, and their various aspects described herein; and for any other execution environment suitable for hosting an adaptation and/or analog of the arrangement of components illustrated in FIG. 3.

(75) FIG. 4A illustrates a network layer component **403a** that corresponds to layer 3 of the open systems interconnection reference (OSI) model. The Internet Protocol (IP) is an exemplary layer 3 protocol, also referred to as a network layer protocol. FIG. 4A illustrates a first NIC **405a1** configured to operatively couple a node including an adaptation and/or analog of the execution environment **401a** to a network. One or more NICs **405a** correspond to layer one, also known as the physical layer, of the OSI model for receiving and sending signals via a physical data transmission medium. Exemplary network layer protocols include an Internet Protocol (IP), DECNet routing Protocol (DRP), an Internetwork Packet Exchange (IPX) protocol, an Internet Datagram Protocol (IDP), a VINES Internet Protocol, and a Datagram Delivery Protocol (DDP).

(76) FIG. 4A also illustrates a link layer component **407a** that corresponds to layer 2, also known as the link layer, of the OSI model for communicating, via layer 1, between nodes sharing a physical data transmission medium such as nodes in a LAN. Exemplary link layer protocols include an Ethernet protocol, a Token-ring protocol, and asynchronous transfer mode (ATM) protocol, to name

a few. Some or all of a link layer component **407a** may be included in one or more NICs **405**, as illustrated in FIG. **4A**. A portion of a link layer component may be external to and operatively coupled to one or more NICs. The external portion may be realized, at least in part, as a device driver for the one or more NICs. Exemplary physical data transmission media include Ethernet cables of various types, co-axial cables, fiber optic cables, and media suitable for transporting various types of wireless signals. FIG. **4A** illustrates that some nodes included in and/or otherwise providing an adaptation and/or analog of the execution environment **401a** may include more than two NICs **405a**, as illustrated by a third NIC **405a3** through an Nth NIC **405an**.

(77) The network layer component **403a**, illustrated in FIG. **4A**, may operate to communicate across various types of link layer protocols, in various adaptations. Layer 3 protocols enable data to be exchanged between and among nodes on different networks across different types of physical data transmission media and differing link layer protocols. The Internet Protocol (IP) in the TCP/IP protocol suite is the most widely utilized network layer protocol currently in use. For ease of illustration, the description that follows provides examples based on IP networks and protocols in the TCP/IP suite due to their wide use and because they are well known in the art. Those skilled in the art will understand that the scope of the subject matter described is not limited to IP networks.

(78) In addition to the protocols described above, protocols corresponding to layers in the OSI model above the network layer may be included in communicating via a network. The term “application protocol” as used herein refers to any protocol or combination of protocols that correspond to one or more layers in the OSI reference model above the network layer. Programs and executables operating in execution environments **401** may communicate via one or more application protocols. Exemplary application protocols include the transmission control protocol (the TCP) in the TCP/IP suite, the user datagram protocol (UDP) in the TCP/IP suite, various versions of hypertext transfer protocol (HTTP), various remote procedure call (RPC) protocols, various instant messaging protocols, various email protocols, and various other protocols for real-time communications. Data exchanged between nodes in a network may be exchanged via data units of one or more network protocols. An execution environment may include layer specific protocol components respectively configured according to the one or more network protocols. Some protocols and/or protocol components may define and/or provide services from multiple layers of the OSI model layer such as the Systems Network Architecture (SNA) protocol.

(79) In addition to specifying schemas defining valid data units, a network protocol may define and/or otherwise be associated with a defined identifier space for identifying protocol endpoints defined according to the network protocol. The terms “identifier space” and “address space” are used interchangeably herein. For example, various versions of hypertext transfer protocol (HTTP) specify a format for HTTP uniform resource locators (URL). HTTP specifies a location in an HTTP header that identifies a URL as an identifier or address from the HTTP address space that identifies both a resource and recipient of an HTTP data unit. The transmission control protocol (TCP) specifies a format and vocabulary for a TCP header including a destination protocol endpoint identifier field referred to as a destination port number that, when combined with a destination protocol address from an IP packet, identifies a transport layer protocol endpoint of a receiver of data sent in a TCP data unit via a network. A source protocol endpoint is similarly identified by a source port number, included in a TCP header as defined by the TCP, along with a source protocol address from an IP data unit as defined by the Internet Protocol.

(80) Other exemplary address spaces that identify protocol endpoints in various network protocols include an email address space, a telephone number address space for various telephony protocols, instant message address spaces for various instant message protocols, and media access control (MAC) addresses for various link layer protocols, to name just a few examples. The address spaces identified are shared among the senders and receivers exchanging data via any particular protocol from among those identified herein as well as others that are known. Some address spaces are shared by senders and receivers in a LAN, an intranet, and/or in another identifiable portion of a

network. Other address spaces are shared globally. For example, the HTTP identifier space is a global address space shared across the Internet. An HTTP identifier is defined to identify the same resource regardless of the application and/or node identifying the resource via the HTTP identifier. An HTTP URL is a global identifier in an HTTP network, such as the World Wide Web (Web). Addresses in a shared address space are referred to as scoped addresses that serve as identifiers of protocol endpoints in nodes that share the address space in a region of a network defined by a scope.

(81) In delivering data via a network between protocol endpoints of a particular network protocol, addresses from address spaces of the various protocols at the various layers are typically translated and/or otherwise mapped between the various layers. For example, a unicast IP address in an IP packet is mapped to a link layer address for a link via which the IP packet is transported in a network path via a path node **504** in relaying data from a source node **502** to an identified destination node **506**. Addresses at the various layers are assigned from a suitable address space for corresponding network protocols.

(82) FIG. 5B illustrates data may be received via the protocol endpoint from a network via one or more network interfaces that operatively couple a node to the network. Data may be sent via the protocol endpoint in a transmission over the network via the one or more network interfaces in the node. In FIG. 5B, a network path communicatively coupling the source node **502b** and a second edge node **508b2** in the network **500b** includes a sequence of nodes including of the source node **502b**, a first path node **504b1**, and the second edge node **508b2**. In FIG. 5C, a first network path communicatively coupling a fifth edge node **508c5** and an eighth path node **504c8** includes a first sequence of nodes including the fifth edge node **508c5**, a ninth path node **504c9**, and the eighth path node **504c8**. The first network path is included in a second network path communicatively coupling the fifth edge node **508c5** and the second edge node **508c2** that includes a second sequence of nodes including of the nodes in the first sequence, a seventh path node **504c7**, and the second edge node **508c2**. A network path may be physical network path or logical network path based on a particular network protocol defining protocol endpoints in the path end nodes.

(83) FIG. 5B, illustrates a number of network paths communicatively coupling the source node **502b** and the destination node **506b** in the network. One network path illustrated includes a sequence of hops including a first hop **512b1**, a sixth hop **512b6**, and a seventh hop **512b7**. In FIG. 5C, the first network path described above communicatively coupling the fifth edge node **508c5** and the eighth path node **504c8** includes a first sequence of hops including a first hop **512c1** and a second hop **512c2**. A hop may be a physical hop or a logical hop based on a network protocol defining a network topology in which the hop is identified and/or otherwise represented.

(84) Given the above definitions, note that the terms “network path” and “hop” may be defined in terms of network interfaces. A “network path” is a sequence of network interfaces in a network for transmitting data in one or more data units of a specified network protocol between a pair of path end nodes in the network. A “hop” refers to a pair of consecutive network interfaces, in a pair of nodes, in a sequence of network interfaces in a network path. A hop in a sequence in a network path corresponds to a pair of network interfaces in the sequence of network interfaces in the network path. In FIG. 5B, the network path described above communicatively coupling the source node **502b** and the destination node **506b** includes a sequence of network interfaces including a network interface in the first path node **504b1** in the first hop **512b1**, a network interface in a second path **504b2** in a sixth hop **512b6**, and network interface in the destination node **506b** in a seventh hop **512b7**. The network paths in FIG. 5C described above may also be described as a sequence of network interfaces.

(85) A network topology may represent logical hops in a network. In FIG. 5B, the first network **514b1** may represented a physical topology when the first **514b1** represents a physical data transmission medium included in physically coupling nodes. The data transmission medium may be a token-ring LAN, for example. The hops **512** in FIG. 5, may illustrate logical communicative

couplings at a level of the network above the data transmission medium. The hops **512** may represent network layer hops or hops at some other layer of the network above the physical layer. The domain name system (DNS) of the Internet provides another example of nodes in a logical network topology based on DNS protocol endpoints of the DNS protocol that identifies nodes in the Internet included the network topology. Hops in a DNS based network topology correspond to communicative couplings enabled by the DNS protocol.

(86) With reference to FIG. 2, a block **202** illustrates that the method includes detecting, by a current node in a current location in a network path, data in a data unit that is specified according to a network protocol and that includes a first path-based protocol address including a plurality of path segment identifiers that identify respective path segments of a network path for transmitting data from a source node to a destination node. Accordingly, a system for routing based on a path-based protocol address includes means for detecting, by a current node in a current location in a network path, data in a data unit that is specified according to a network protocol and that includes a first path-based protocol address including a plurality of path segment identifiers that identify respective path segments of a network path for transmitting data from a source node to a destination node. For example, the arrangement illustrated in FIG. 3, includes the in-data handler component **302** that is operable for and/or otherwise is included in detecting, by a current node in a current location in a network path, data in a data unit that is specified according to a network protocol and that includes a first path-based protocol address including a plurality of path segment identifiers that identify respective path segments of a network path for transmitting data from a source node to a destination node. FIGS. 4A-C illustrate in-data handler components **402** as adaptations and/or analogs of the in-data handler component **302** in FIG. 3. One or more in-data handler components **402** operate in an execution environment **401**. In FIG. 4A, an in-data handler component **402a** is included in network layer component **403a**. In FIG. 4B and in FIG. 4C, in-data handler components **402** operate in respective line card components **409**.

(87) In transmitting data from a source protocol endpoint in a source node **502** to a destination protocol endpoint in a destination node **506**, the data is processed by a sequence of nodes in a network path that communicatively couples the source node **502** and the destination node **506**. A node in the network path, that is currently processing the data to send it to the destination **506**, is referred to herein as a “current node” with respect to the data. A node in the network path that has previously transmitted the data being processed by the current node is referred to herein as a “previous node”. A node in the network path that has not received the data being processed by the current node is referred to herein as a “next node”. For ease of description, with respect to a data unit “data” refers to data sent in the data unit via a protocol endpoint in the source node, that is being processed by a current node. As such, a source node **502** may be a current node or a previous node with respect to particular data. A path node **504** may be a current node, a previous node, or a next node with respect to the particular data. A destination node **506** may be a next node or a current node with respect to particular data.

(88) A source node **502** may be a current node with respect to data to be transmitted to a destination node **506**. The source node **502** may include an adaptation, analog, and/or instance of the execution environment **401a** in FIG. 4A. An in-data handler component **402a** operating in a network layer component **403a** in the source node **502** may detect the data. The network layer component **403a** may be configured according to a network layer protocol, such as a version of the Internet Protocol. The in-data handler component **402a** may detect data in a data unit that is to be sent to the destination node **506**. The data may be received from an application or other type of component configured to send data via a network to a recipient. For example, the application component may be an email client, a file transfer application, a network management client, and the like to be transmitted via one or more data units of the network protocol of the network layer component **403a**. The in-data handler **402a** may receive the data, directly and/or indirectly, from the application in the source node **502**. The in-data handler **402** may interoperate with an out-data

component **408a** and/or other component of the network layer component **403a** to include and/or otherwise detect the data in a data unit of the network protocol.

(89) A path node **504** may include an adaptation, analog, and/or instance of the execution environment **401a**, illustrated in FIG. 4A. Data communicated between a source node **502** and a destination node **506** may be received by the path node **504** via of a first NIC **405a1** operatively coupling the path node **504** to a previous network path including the source node **502** and the path node **504** as path end nodes. One or more link layer protocol data units may be detected by a link layer component **407a** according to a compatible link layer protocol. For example, Ethernet frames may be detected as link layer protocol data units when received via a CAT 6 Ethernet cable. Data in a received link layer protocol data unit may be provided to an in-data handler component **402a** in a network layer component **403a** according to the specification of a particular network layer protocol, such as the IP.

(90) An in-data handler component **402a** may detect one or more network layer protocol data units in data received from the link layer component **407a**. For example, the in-data handler component **402a** may detect one or more IP packets in data received in one or more Ethernet frames. The in-data handler component **402a** may detect a network layer data unit that includes data from the source node **502** to relay the data to the destination node **506** identified by a protocol address in address information in the detected network layer data unit as defined by a particular network layer protocol supported by the network layer component **403a** in the path node **504**. A network interface component **405a** in a path node **504** may receive data communicated from a source node **502** via a previous network path included in a network **500**. One or more network paths may exist to receive the data. A path node **504** may receive data from a source node **502** and may transmit the received data to a destination node **506** via a specified protocol. For example, a path node **504** may receive and transmit data in one or more data packets at a link layer as performed by an Ethernet bridge and a multiple protocol-labeling switch (MPLS). Further, a path node **504** may receive and transmit data in one or more data packets at a network layer as performed by an Internet protocol (IP) router. Still further, a path node **504** may receive and transmit data in one or more data packets at an application layer, as defined above.

(91) Accordingly, data from a source node **502** may be included in and/or may include data formatted according to a link layer protocol, a network layer protocol, and/or an application layer protocol. An in-data handler component **402a** may be configured according to a network layer protocol, a link layer protocol, and/or an application layer protocol.

(92) A network protocol defines one or more of a format defining a valid structure for a data unit and a vocabulary defining valid content of the data unit. For example, data to transmit from a source node to a destination node may be included in a payload portion of a data unit of a particular network protocol. The network protocol may define a format that identifies the payload based on one or more valid data structures for a data unit. For example, a payload portion may be identified by a location with respect to the start of a data unit or relative to another portion of the data unit. Alternatively or additionally, the network protocol may define a vocabulary defining a keyword, a bit pattern, and/or other detectable marker that when detected identifies a payload or part of a payload in a data unit. The network protocol may define one or more format rules and/or vocabulary rules that an in-data handler component may detect in identifying data and/or address information in a data unit. The term “schema” refers to a definition of a structure and/or a vocabulary for constructing and/or detecting a valid data unit with respect to a network protocol. For example, both an IPv4 data packet and an IPv6 data packet are specified according to a schema for including address information in a destination protocol address field and in a source protocol address field in an IP header based on location and size.

(93) Data received from a source node **502** by a path node **504** may be received via one or more previous path nodes **504**. Data may be received by a current node **504** from a previous node based on a previous-current path segment identifier included in a path-based protocol address that

identifies a destination node **506**. The previous-current path segment identifier identifies a network path from the previous node to the current node for transmitting the data.

(94) Returning to FIG. 2, a block **204** illustrates that the method further includes detecting, based on the current location, a current-next path segment identifier that identifies a current-next path segment in the plurality for transmitting the data from the current node to a next node in the network path. Accordingly, a system for routing based on a path-based protocol address includes means for detecting, based on the current location, a current-next path segment identifier that identifies a current-next path segment in the plurality for transmitting the data from the current node to a next node in the network path. For example, the arrangement illustrated in FIG. 3, includes the routing component **304** that is operable for and/or otherwise is included in detecting, based on the current location, a current-next path segment identifier that identifies a current-next path segment in the plurality for transmitting the data from the current node to a next node in the network path. FIGS. 4A-C illustrate routing components **404** as adaptations and/or analogs of the routing component **304** in FIG. 3. One or more routing components **404** operate in an execution environment **401**.

(95) In FIG. 4A, a routing component **404a** is illustrated as a component of a network layer component **403a**. In FIG. 4B, a routing component **404b** is illustrated operatively coupled to multiple line card components **409b** to relay data between and/or among portions of a network coupled to the line cards **409b**. Routing component **404b** may operate at a network layer of a network stack and/or at another layer. In FIG. 4C, a routing component **404c** is illustrated as distributed throughout line card components **409c** of an execution environment **401c**. The routing component in the execution environment **401c** includes a first routing agent (RA) component **404c1** in a first line card component **409c1** and a second RA component **404c2** in a second line card component **409c2**.

(96) FIGS. 6A-E illustrate a number of types of address representations **602** illustrating aspects of various address formats and vocabularies for representing a path-based protocol address. Various portions of the respective address representations **602** are illustrated as contiguous but need not be so in various embodiments. The address representations **602** in FIGS. 6A-E may be identified based on an aspect of a format of a data unit and/or an aspect of a vocabulary of a data unit as defined by a schema of a network protocol. Routing component **404a** may detect a protocol address of a next node based on a schema for including address information in a data unit of a network protocol. In another aspect, address information may be detected by an in-data handler component **402a** configured to provide some or all of the address information to the routing component **404a** to detect a protocol address of a next node in a path-based protocol address in the address information.

(97) Address representations **602** in FIGS. 6A-E are described with respect to their inclusion in data units of a network protocol. Each of the address types shown in FIGS. 6A-E may be adapted to be included in a destination protocol address portion and/or a source protocol address portion of an IPv4 packet header and/or of an IPv6 packet header. Each may be identified as a path-based protocol address, by a routing component **404a**, by a bit pattern and/or other type identifier defined to identify a protocol address type as a path-based protocol address type. The bit pattern or identifier may be located by the routing component **404a** stored in a type bits portion of an IP packet and/or in some other specified location. Those skilled in the art will realize that neither the schemas, which define a format rule(s) and/or a vocabulary rule(s) for a protocol address, described nor the protocols in which their use is described are exhaustive.

(98) FIG. 6A illustrates an address representation **602a** that may be detected by an in-data handler component **402a** and/or a routing component **404a** in a data unit or packet of an Internet Protocol or other network layer protocol. An address representation **602a** may identify a path-based protocol address identifying multiple path segments in a network path for transmitting data from a source node to a destination node via the network path. In an aspect, an address representation **602a** may

be processed by an in-data handler component **402a** and/or a routing component **404a** as including multiple portions. An address information field **606a** may include a path-based protocol address that identifies the destination node and/or the source node. An address separator field **604a** is illustrated, in FIG. **6A**, including a binary number. The exemplary binary number equals seventeen in FIG. **6A**. The value in the address separator field **604a** may be defined to identify the size in the address information field **606a** of a previous address field **608a** to identify the previous address field **608a** and a next address field **610a**. A routing component **404a**, in a current node **504**, may process information in a previous address field **608a** to identify a previous-current path segment identifier, in the path-based protocol address, that identifies the current node **504** with respect to a previous node in the network path. A routing component **404a** may identify, based on information in a next address field **610a**, a current-next path segment identifier, in the path-based protocol address, that identifies a next node in the network path. In FIG. **6A** previous portion **608a2** may be a path-segment identifier of the current node that identifies a network path in the network path from the source node to the current node. A next portion **610a2** may be a path-segment identifier of a path segment to a next node from the current node. The next node follows the current node in a sequence of nodes in a network path including the current node and the destination node.

(99) Alternatively or additionally, a routing component **404a** may identify, based on information in a next address field **610a**, a next-current path segment identifier, in the path-based protocol address, that identifies the current node with respect to a next node. A routing component **404a** interoperating with an in-data handler component **402** may determine the current-next path segment identifier, that identifies the next node, based on the next-current path segment identifier. In another aspect, a routing component may determine the next-current path segment identifier based on the current-next path segment identifier.

(100) With respect to FIG. **5A**, an address representation **602a** may be included in a data unit including data from a source node **502a** to transmit to a destination node **506a**. An address information field **606a** may include a path-based protocol address that identifies the sequence 1.2.2.3.2 that, in the data unit, identifies the destination node **506a**. Note that the source node **502a** is illustrated in a first region **510a1** in the network **500a**. A first scope-specific address space may be specific to the first region **510a1**. The sequence 1.2.2.3.2 may be represented in an address information field **606a** to identify a protocol address that, in the first scope-specific address space, identifies the destination node **506a**. Further, the sequence may be included in a path-based protocol address that identifies the destination node **506a** in a data unit including data sent from the source node **502a**.

(101) In an aspect of the method illustrated in FIG. **2**, address information in a data unit may identify a source-destination path-based protocol address that identifies a destination node with respect to a source node. Alternatively, or additionally the address information may identify a destination-source path-based protocol address that, with respect to the destination node, identifies the source node. A current-next path segment identifier may be included in at least one of the source-destination protocol address and the destination-source protocol address. The current-next path segment identifier may include one or more of a nested protocol address; a scope-specific protocol address that, in a current scope-specific address space specific to a current region including a current node, identifies a next node with respect to the current node; and a path-based protocol address that identifies a network path from the current node to the next node.

(102) At the source node **502a**, the address separator field **604a** may be set to include a size of zero for a previous address field **608a**. The address information field **606a**, thus, includes a next address field **610a** at the source node **502a** and identifies the destination node **506a** with respect to nodes in the first region **510a1** by identifying a specific network path included in transmitting data from the source node **502a** to the destination node **506a**.

(103) At a first path node **504a1**, outside the first region **510a1**, an address separator field **604a** in a data unit including the data from the source node **502a**, may include a value of 1 that identifies, in a

previous address field **608a**, a previous-current path segment identifier, in destination protocol address, identifies the first path node **504a1**. A routing component **404a** in a first path node **504a1** may detect the value. The routing component **404a** may also identify, based on the value in the address separator field **604a**, a next address field **610a** that identifies 2.2.3.2 as a current-next path segment identifier that, in the destination protocol address, also identifies the destination node **506a**. The routing component **404a** may detect the current-next path segment identifier.

(104) At the destination node **506a** a data unit including the data from the source node **502a** may include a value in an address separator field **604a** that indicates that the address information field includes only a previous address field **608a** identifying the network path 1.2.2.3.2, which is included in the destination path-based protocol address.

(105) In another aspect, the method illustrated in FIG. 2 may include detecting, in a data unit by a current node, address-separating information specified according to a network protocol to detect the next address information and/or the previous address information. The address separating information may be updated in a next data unit for identifying, by the next node, at least one of next-previous path segment identifier and next-next path segment identifier in the address information, wherein the next-previous address information includes a path segment identifier that identifies the current node as a previous node. In yet another aspect, address separating information may be updated in a data unit received by a current node to identify, by the current node, the previous address information and the next address information in the address information. As the data from the source node **502a** is transmitted from node to node in the network path the value represented in an address separator field **604a** in an address representation **602a** in a data unit including the data or a portion thereof may be adjusted to identify a path segment identifier in a path-based protocol address to identify a next node for each node operating as a current node in the network path.

(106) The above description describes an address representation **602a** processed in the role of a destination path-based protocol address in a data unit of a network protocol, such as a version of the internet protocol. An address information field **606a** may include source address information sent in one or more data units included in sending data from a source node to a destination node. Returning to FIG. 5A, a data unit including data sent from the source node **502a** to the destination node **506a** may include source address information including a representation of a source path-based protocol address in an address information field **606a**. At the second path node **504a2**, an address separator field may identify a previous address field **608a** identifying the sequence 0.0 that identifies a path segment identifier that, in the source path-based protocol address, identifies the source node **502a** to the second path node **504a2**. Note that the address 0.0 identifies the source node **502a** node to all nodes in the second region **510a2** that communicate with the source node **502a** via data units of the network protocol and may be an address in a scope-specific address space specific to the second region **510a2**. The address information field **606a** including the source address information at the second path node **504a2** may include a next address field **610a**, identified by the address separator field **604a**, identifying the sequence 0.1.0 that identifies a path segment identifier, in the source path-based protocol address, that identifies the second path node **504a2** to the destination node **506a**.

(107) FIG. 6B illustrates a variant of the address type illustrated in FIG. 6A. Instead of or in addition to including an address separator field that distinguishes a previous address field from a next address field based on a size, a bit-mask may be specified as one or more address separator fields **604b** to identify a previous address field **608b** and a next address field **610b** in an address information field **606b** in an address representation **602b** of a data unit formatted according to a particular network protocol, such as IP or IPX. Address information formatted as illustrated in FIG. 6B may be processed by a routing component **404a** interoperating with an in-data handler component **402a** in an analogous manner to that described for the address information in FIG. 6A based on the bit mask address separator field(s) **604b** rather than and/or in addition to a size address

separator field **604a** illustrated in FIG. 6A.

(108) As described above and further described below, a path-based protocol address may include and/or may otherwise be based on path information for a network path included in communicatively coupling a pair of nodes in a network. Detecting a path-based protocol address and/or a protocol address in a path-based protocol address may include determining path information identifying a network path included in communicatively coupling a pair of path end nodes included in transmitting data from a source node to a destination node.

(109) FIG. 6C illustrates an address representation **602c** identifying a path-based protocol address including path information that may be detected by a routing component **404a**. An address information field **606c** may include a path-based protocol address that may be interpreted as including a network path identifier based on address separator field(s) **604c** in a data unit. Address separator fields are specified according to a network protocol to distinguish one path segment identifier from another path segment identifier in an address information field **606c**. Each path segment identifier and/or group of consecutive path segment identifiers may be a representation of a protocol address of the network protocol of a data unit including an address representation **606c**.

(110) In an aspect, illustrated in FIG. 6C, a routing component **404a** and/or an in-data handler component **402a** may distinguish hop identifiers, since a single hop is a network path and/or a path segment. A routing component **404a** may distinguish separate hop identifiers based on changes in values in bits of consecutive address separator fields **604c**. In FIG. 6C, a first address separator field **604c1** includes one or more 1-valued bits that correspond to bit positions in the address information field **606c** to identify a previous address field referred to in FIG. 6C as a first hop information field. Network paths that include more than one hop may be distinguished similarly as shown in FIG. 6B. Combinations of hop identifiers and path segment identifiers may be distinguished by a routing component **404a** and/or an in-data handler component **402a** based on information in address separator fields **604**. The routing component **402a** may detect protocol addresses that correspond to the various combinations of hop identifiers and/or path segment identifiers. A second hop information field **604c2**, in FIG. 6C, includes two 0-valued bits to identify a second hop information field in address information field **606c**. Additional alternating sequences of 1-valued bits and 0-valued bits illustrated by address separator fields **604c3-12c** correspond to and identify other hop information fields identifying hops in a network path communicatively coupling a source node **502** and a destination node **506**.

(111) Path information may include hop information identifying a hop. Next address information may be defined by a network protocol to include next path information identifying a current-next path identifier of a next network path included in communicatively coupling a current node and destination node. Alternatively or additionally, previous address information may be defined by the network protocol to include previous path information identifying a previous-current path segment identifier of previous network path included in communicatively coupling the current node and the source node. Next path information may include next hop information identifying a hop in the next network path. Previous path information may include previous hop information identifying a hop in the previous network path. A network protocol may define a hop identifier to be a valid protocol address that identifies a protocol endpoint.

(112) In FIG. 5C, a hop may be identified by an interface identifier that may identify directly and/or indirectly one or more network interfaces in a pair of communicatively coupled nodes included in the hop. For example, the number 1 may serve as a hop identifier specific to a second path node **504c2** to identify a third hop **512c3** including the second path node **504c2** and a fourth path node **504c4**. The number 1 may also identify a network path for exchanging data between the two nodes. The number 1 may also be a protocol address that, in a path-based protocol address identifying a destination node in a data unit including data from a source node, identifies the fourth path node **504c4** in a network path from the source node to the destination node. The number 1 may also identify a hop for the fourth path node **504c4** to exchange data with the second path node

504c2 and may also be a protocol address that identifies the second path node **504c2** and identifies a particular network interface of the second path node **504c2** in a data unit sent from the fourth path node **504c4**.

(113) A source node **502c** may identify a destination node **506c** by a destination path-based protocol address. The protocol address may be based on a sequence of hop identifiers 0.1.3.2.3.0.51. Note that other network paths are illustrated for transmitting data from the source node **502c** to the destination node **506c** and may also identify path-based protocol addresses that identify the destination node **506c** to the source node **502c**.

(114) A seventh path node **504c7** in the identified network path may identify the destination node **506c** based on another sequence of hop identifiers 3.0.51 that identifies a path segment. The sequence of hop identifiers may identify a protocol address that, in the destination path-based protocol address, identifies the destination node **506c**. Note that a routing component **404a** operating in the seventh path node **504c7** may detect the path segment identifier sequence 3.0.51, in and/or otherwise based on the path-based protocol address of the destination node **506c**. Further, the routing component **404a** may detect a path segment identifier for the eighth path node **504c8** as well as a path segment identifier for the ninth path node **504c4**, in and/or otherwise based on the protocol address based on the path segment identifier 3.0.51.

(115) The destination node **506c** is illustrated in a third region **510c3**. Within the third region **510c3**, the destination node **506c** may be identified by a local scoped address 51, which identifies a path segment. Nodes in the third region **510c3** may identify nodes outside the third region **510c3** by path-based protocol addresses, and may use local scoped addresses to identify nodes in the third region **510c3**.

(116) The hop identifiers 0.1.3.2.3.0.51 may be represented in a path-based protocol address in an address representation **602c** in a data unit included in sending data from the source node **502c** to the destination node **506c**. At the seventh path node **504c7**, a routing component **404a** may determine and/or otherwise detect a path segment identifier identifying a network path to a next node based on a next address field identifying the path segment identifier 3.0.51 in the path-based protocol address. The identifiers may be given a bit or binary representation and the hop identifiers may be distinguished or separated via address separator fields **604c** as described above with respect to FIG. 6C. An address separator field analogous to that shown in FIG. 6A may also or alternatively be included and processed as described above. Assignment of hop identifiers is described in application Ser. No. 13/727,649 filed on 2012 Dec. 27, entitled "Methods, Systems, and Computer Program Products for Assigning an Interface identifier to a Network Interface", application Ser. No. 13/727,655 filed on 2012 Dec. 27, entitled "Methods, Systems, and Computer Program Products for Determining a Shared identifier for a Hop in a Network".

(117) Note that the address information that identifies one or more path segment identifiers for the seventh path node **504c7** and for the destination node **506c** in the preceding description may include information to identify a return path or a portion thereof. For example, the path-based protocol address 3.0.51 includes the path segment identifier 0.3, which may be included in a path-based protocol address that identifies the seventh path node nodes in the third region **510c3** and may be path-based protocol address that identifies the seventh path node **504c7** to the ninth path node **504c9**. The path-based protocol address 0.1.3.2 includes another path-based protocol address 2.3.1 that identifies a network path from the seventh path node **504c7** to a node having a network interface in first region **510c1**, illustrated by a second path node **504c2**.

(118) Separate source address information may be included in a data unit received by the seventh path node **504c7** that includes data sent from the source node **502c**. Address information in the data unit may include a source path-based protocol address representation **602c** that may identify 2.3.1.101 as a protocol address that identifies the source node **502c**. Note that 101 may identify a hop in the first region **510c1** from the second path node **504c2** to the source node **502c**, in some aspects. For example, subnet **514c1** may be a LAN. In another aspect, 101 may be a scoped address

that identifies the source node **502c** in the scope of the first region **510c1**. Thus, a path-based protocol address may include a scoped address, which may identify a path segment.

(119) FIG. **6D** includes an address representation **602d** illustrating a schema for representing a path-based protocol address including path information based on identifiers of network interfaces included in a hop and/or in path end nodes in a network path. A routing component **404a** and/or an in-data handler component **402a** may operate based on the schema or a portion of the schema. An address information field **606d** includes a path-based protocol address to identify a network path to communicatively couple a pair of path end nodes. FIG. **6D** illustrates that an address representation **602d** may include one or more address separator fields **604d** that correspond to and/or otherwise identify respective one or more portions of the address information field **606d** that are based on one or more pairs of identifiers of network interfaces of path end nodes. An address separator field **604d** includes series of 1-valued bits and 0-valued bits. A change from a 1-valued bit to a 0-valued bit and vice versa may indicate, to a routing component **404a** and/or an in-data handler component **402a**, a boundary separating interface identifiers. Since a protocol address may consist of a single hop, a pair of interface identifiers corresponding to an address separator portion **604d** may identify network interfaces in a hop identified in a protocol address. An address separator field **604d1** includes one 0-valued bit followed by four 1-valued bits. The 0-valued bit may be defined to indicate that a first network interface in a first hop identifier is 1 bit long with a corresponding position in the address information field **606d**. FIG. **6D** identifies the first interface identifier as the number 1 in base ten. The four 1-valued bits in the first address separator field **604d1** may be similarly defined to identify the location of a second interface identifier in the first hop identifier. The second interface identifier, as illustrated in FIG. **6D**, has the value 10 in base ten. The first hop identifier includes the numbers 1 and 10. A second hop identifier is located by the end of the series of four 1-valued bits in the first address separator field **604d1** to a series of three 0-valued bits that identify a boundary of a second address separator field **604d2** for second hop information identifying a second hop identifier, and the three 0-valued bits also identify the location of a first interface identifier in second hop information in the address information field **606d**. Two subsequent 1-valued bits identify the location in the address field **606d** of a second interface identifier in the second hop information. The second hop identifier includes the numbers 6 and 0 in base ten. The remaining address separator fields **604d** may be processed similarly.

(120) The path-based protocol address illustrated FIG. **6D** may be represented textually as 1-10.6-0.0-5.1-14.5-0.6. Note that the last hop mask does not identify a pair of identifiers and is similar to address portions identified based on address separator fields **604c** described with respect to FIG. **6C** or may be a local scoped address. This is illustrated to demonstrate that path-based protocol addresses may be uniform or non-uniform in their format and content. FIG. **6D** illustrates that hop identifiers may be protocol addresses with respect to one or both nodes in the respective hops identified by the hop identifiers. A hop identifier may serve as a protocol address to identify a next node in the context of a path node, in a network path, identified the hop. A hop identifier may serve as a protocol address to identify a previous node for a path node in the network path.

(121) In FIG. **5B**, a source node **502b** may identify a destination node **506b** by a destination path-based protocol address, where the path-based protocol address is based on pairs of interface identifiers that identify path segments as described in the previous paragraphs. For example, FIG. **5B** illustrates a sequence of pairs of interface identifiers 151-254.151-254.253-105 may be a path-based protocol address that identifies the destination node **506b**. The source node **502b** may send a data unit including an address representation **602d** illustrated in FIG. **6D**. Note that reversing the interface identifiers yields the identifier 105-253.254-151.254-151 that may be a path-based protocol address that identifies the source node **502b** in a data unit exchanged by the source node **502b** and the destination node **506b**.

(122) For the first path node **504b1**, an address representation **602d** in a data unit including data received from the source node **502b** may include previous address information, identified by a

routing component **404a** based on one or more address separator fields **604**, that identifies the path segment identifier 151-254 and/or that identifies the path segment identifier 254-151. The sequence ordered as 151-254 may be a path segment identifier, in a destination path-based protocol address, that identifies the first path node **504b1**. The sequenced ordered as 254-151 may be a path segment identifier, in source path-based protocol address, that identifies the source node.

(123) Further for the first path node **504b1**, the address representation **602d** may include next address information identified by the routing component **404a** based on one or more address separator fields **604d** that identify the sequence 151-254.253-105 in a first order and/or in a second order. The sequence 151-254.253-105 in the first order may identify a path-based protocol address that identifies the destination node **506b**. The sequence 105-253.254-151 in the second order may identify a path-based protocol address that identifies the first path node **504b1**.

(124) Still further, for the first path node **504b1**, the next address information identified by the routing component **404a** identifies the sequence 151-254 in a first order and/or in a second order. The sequence 151-254 in the first order may be a path segment identifier, in the destination path-based protocol address, that identifies a second path node **504c2** in a network path to the destination node **506b**. The sequence 254-151 in the second order may be a path segment identifier, in the source path-based protocol address, that identifies the first path node **504b1**. A sequence of hop identifiers based on interface identifiers may serve as a first path-based protocol address when processed in one order of the sequence and may serve as a second path-based protocol address when processed according to another order of the sequence.

(125) FIG. 6E illustrates an address representation **602e** that further demonstrates that an address handler component **404a** may detect a path segment identifier that identifies a network path to a next node, in a path-based protocol address. An address representation **602e** may include portions that include path information and/or portions that include scoped protocol addresses. A routing component **404a** may distinguish path segment identifiers in portions of a path-based protocol address based on address separator fields **604e**. Address separator fields **604e** may be defined to identify path segment identifiers in the portions in a manner similar to the method described for distinguishing hop identifiers in FIG. 6C. A previous address information field **606e1**, in FIG. 6E, corresponding to a first address separator field **604e1** includes a single interface identifier for an outbound network interface for the source node **502c** as described above with respect to FIG. 6A and FIG. 5C. A next address information field **606e2** corresponding to a second address separator field **604e2** may include a scoped protocol address having an inside scope, an outside scope, or both. A node processing the second address information field **606e2** may be included in a portion of a network spanned by the scope of the scoped protocol address. The node may process the scoped protocol address accordingly. See application Ser. No. 11/962,285, by the present inventor, filed on 2007 Dec. 21, entitled "Methods and Systems for Sending Information to a Zone Included in an Internet Network" for a description of addresses having outside scope and/or inside scope and processing of such addresses. A third address information field **606e3** corresponding to a third address separator field **604e3** may include a pair of identifiers as described with respect to FIG. 6D. A fourth address information field **606e4** corresponding to a fourth address separator field **604e4** may include a path segment identifier as described with respect to the next address information field **606e2** such as a local scoped address.

(126) In FIG. 5B, a source node **502b** may be included in a first region that includes network interfaces coupling nodes to a first network **514b1** included in a network **500b**. A destination node **506b** may be included in a third region that includes network interfaces coupling nodes to a third network **514b3**. Each of the two nodes may identify the other by a path-based protocol address. For example, a sequence of local scoped addresses 254.254.105 may be a sequence of path segment identifiers in a protocol address that may identify the destination node **506b** to the source node **502b** as well as to other nodes in the first region defined by the first network **514b1**. A data unit including an address representation **602e** in FIG. 6E may identify path segment identifiers based on

a sequence of scoped addresses.

(127) For a second path node **504b2**, an address representation **602e** in a data unit including data received from the source node **502b** may include previous address information identified by a routing component **404a** in the second path node **504b2** based on one or more address separator fields **604e** that identifies a previous path segment identifier 254.254 in previous address information in the address representation **602e**. The previous path segment identifier may identify a protocol address that identifies the second path node **504b2**. Further, for the second path node **504b2**, the previous address information identified by a routing component **404a** in the second path node **504b2** identifies a first path segment identifier 254 that identifies a network interface of the second path node **504b2** to nodes with network interfaces in the second network **514b2**. Yet further for the second path node **504b2**, the address representation **602e** may include next address information identified by the routing component **404a** in the second path node **504b2** based on one or more address separator fields **604e** that identifies a scoped address 105. The scoped address 105 in the scope of the third network **514b3** identifies the destination node **506b** to nodes with network interfaces in the third network **514b3**, such as the second path node **504c2**.

(128) Returning to FIG. 2, a block **206** illustrates that the method yet further includes determining, based on the current-next path segment identifier, a current-next network interface that is included in the current-next path segment. Accordingly, a system for routing based on a path-based protocol address includes means for determining, based on the current-next path segment identifier, a current-next network interface that is included in the current-next path segment. For example, the arrangement illustrated in FIG. 3, includes the forwarding component **306** that is operable for and/or otherwise is included in determining, based on the current-next path segment identifier, a current-next network interface that is included in the current-next path segment; and, FIGS. 4A-C illustrate forwarding components **406** as adaptations and/or analogs of the forwarding component **306** in FIG. 3. One or more forwarding components **406** operate in an execution environment **401**.

(129) In FIG. 4A, a routing component **404a** may provide a path segment identifier of a network path to a next node and/or forwarding information based on the path segment identifier to a forwarding component **406a** to determine a network interface to send data from a source node **502** to a destination node **506** via a next node in a network path from a current node **504** including the forwarding component **406a**. In FIG. 4A, a forwarding component **406a** is illustrated operatively coupled to a network layer component **403a** and operatively coupled to the routing component **404a**.

(130) In an aspect, determining a next network interface based on a path segment identifier of a next node may include detecting an interface identifier in the path segment identifier. In FIG. 5C, data in a data unit may be received by the seventh path node **504c7** from the source node **502c**. Address information in the data unit may identify the destination node **506c** via a protocol address 0.1.3.2.3.0.51 representing a sequence of hops in a network path including the source node **502c** and the destination node **506c**.

(131) As described above, the routing component may determine that a path segment identifier based on the sequence 3.0.51 identifies a network path to the destination node **506c**. Further, the hop identifier 3 may be a path segment identifier identifying a network path to the eighth path node **504c8** as a next node. The number 3, as described above is assigned to identify a hop including the seventh path node **504c7** and the eighth path node, and thus identifies a network interface, in the seventh path node **504c7**, that is included in the hop.

(132) Identifying a next network interface may include performing a mapping and/or lookup that maps a portion of a path segment identifier identifying a network path to a next node to an identifier that identifies a NIC **405a** to a link layer component **407a**. A next network interface may be identified by mapping a path segment identifier to a link layer address by means of a lookup table or record associating the path segment identifier with the link layer address.

(133) A path-based protocol addresses illustrated in any of FIGS. 6A-E may include a path segment

identifier identifying network path to next nodes. In some aspects, a path segment identifier of a network path to a next node includes an identifier of a network interface for transmitting data to a destination protocol address via a network path that includes the network path to the next node identified by the path segment identifier. Routing tables and/or routing policies are not required when protocol addresses include path segment identifiers.

(134) Returning to FIG. 2, a block **208** illustrates that the method yet further includes sending, via the current-next network interface, the data to the next node. Accordingly, a system for routing based on a path-based protocol address includes means for sending, via the current-next network interface, the data to the next node. For example, the arrangement illustrated in FIG. 3, includes the out-data handler component **308** that is operable for and/or otherwise is included in sending, via the current-next network interface, the data to the next node. FIGS. 4A-C illustrate out-data handler components **407a** as adaptations and/or analogs of the out-data handler component **308** in FIG. 3. One or more out-data handler components **407a** operate in an execution environment **401**.

(135) In FIG. 4A, a forwarding component **406a** may provide data to an out-data handler component **408a** to send the data to a next node via an identified network interface identified by forwarding component **406a**. The next node may be a destination node **506** or a path node **504** in a network path for transmitting data from a source node **502** to the destination node **506**. In FIG. 4A, an out-data handler **406a** is illustrated operating in a network layer component **403a**. The out-data handler component **402a** may include the data in one or more network layer protocol data units including a path-based protocol address, as described above, identifying the destination node **506** according to a network layer protocol of the network protocol component **403a**.

(136) The one or more network layer protocol data units may be provided to a link layer component **407a** as data to include in one or more link layer protocol data units to transmit via a NIC **405a** based on the network interface identified by the forwarding component **406a**. In a node with one NIC operatively coupled to a physical data transmission medium or with multiple NICs operatively coupled to the shared data transmission medium, an out-data handler component **408a** may send network layer data packets via the one NIC or any of the multiple NICs over the physical data transmission medium for delivery to the destination node **506** according to network interface identified by the forwarding component **406a**. Link layer protocol data units may be sent by the link layer component **407a** according to a compatible link layer protocol and link layer address information. For example, Ethernet frames may be sent as link layer protocol data units via an Ethernet cable operatively coupled to a NIC **405a1** included in a suitable network path for transmitting the data to the destination node **506**.

(137) FIG. 4B illustrates another exemplary execution environment **401b** that may include and/or otherwise be provided by a path node **504** in FIGS. 5A-C. In FIG. 4B, the execution environment **401b** includes a first line card **409b1** that includes a first NIC **405b1**. The first NIC **405b1** may operatively couple the path node **504** to a previous network path with respect to data from a source node **502** to relay to a destination node **506**. The execution environment **401b** also includes a second line card **409b2** including a second NIC **405b2** to operatively couple the path node **504** to a next network path with respect to the data from the source node **502**.

(138) Data sent from a source node **502** to an identified destination node **506** may be received in a data unit of a network protocol by the first NIC **405b1** in the path node **504**. The data may be detected by an in-data handler component **402b1** operatively coupled to the first NIC **405b1**. A path-based protocol address may be detected in an address representation included in the data unit according to the network protocol. The in-data handler component **402b1** may send the some or all of the path-based protocol address to a routing component **404b** via an internal communications medium **421b**, such as a bus **116** in FIG. 1, to determine a path segment identifier, in a path-based protocol address, that identifies a next node. The routing component **404b** may include, be processed by, and/or otherwise interoperate with a general processing unit **419b** and/or other hardware in processing the address information. A routing component **404b** may be included, in

some aspects, to also process protocol addresses that do not include an identifier of the next network interface component or for routing IP addresses from global address spaces as currently specified by RFC 791 and RFC 3513.

(139) The routing component **404b** may determine the path segment identifier of the next node as describe above and/or in an analogous manner. The routing component **404b** may provide some or all of the path segment identifier to a forwarding component **406b**. The forwarding component **406b** may identify a second line card **409b2** including a second NIC **405b2**, based on some or all of the path segment identifier. The forwarding component **406b** may interoperate with the GPU **419b** to configure the internal data transmission medium **421b** to deliver the data received in the data unit from the first line card **409b1** to the second line card **409b2** for final packaging in one or more data units of the network protocol by an out-data handler component **408b2**. The out-data handler component **402b2** may interoperate with a second NIC **405b** to transmit the data via a data transmission medium to which the second NIC **405b2** is operatively coupled.

(140) FIG. 4C illustrates still another exemplary execution environment **401c** that may include and/or otherwise be provided by a path node **504** illustrated in FIGS. 5A-C. In FIG. 4C, the execution environment **401c** includes a first line card **409c1** that includes a first NIC **405c1**. The first line card **405c1** may operatively couple the path node **504** to a previous network path with respect to data from a source node **502** to relay to a destination node **506**. The execution environment **401c** also includes a second line card **409c2** including a second NIC **405c2** to operatively couple the path node **504** to a next network path with respect to the data from the source node **502**.

(141) In FIG. 4C, a routing component may be a distributed component. FIG. 4C illustrates that a routing component may be realized as routing agent components **404c** included in line cards **409c** in a path node **504**. A forwarding component may also be distributed as illustrated in FIG. 4C by forwarding agent components **406c** included in the line cards **409c**. An FA component **406c1** may configure a switch interconnect unit (SIU) **421c** to provide a communication channel from a first line card **409c1** to a second line card **409c2** and vice versa, as needed. Each line card **409c** may include a switch interface (SI) component **423c** to write data to a channel configured in the SIU component **421c** and/or to read data from a channel.

(142) A routing agent (RA) component, such as a first RA component **404c1**, may identify a path segment identifier based on address information detected by a first in-data handler (IDH) component **402c1**. Based on some or all of the path segment identifier, the first FA component **406c1** may identify a next line card **409c**, such as the second line card **409c2**, to transmit data received from a source node **502** to a next node identified by the path segment identifier as described above with respect to FIG. 4A and FIG. 4B. The first FA **406c1** may setup a channel in the SIU component **421c** for communicating the data via a first SI component **423c1** to a second SI component **423c2** of the second line card **409c2**. The second SI component **423c2** may read the data communicated via the SIU component **421c** and provide the data to a second out-data handler (ODH) component **408c2** in the second line card **409c2** to transmit to the next node. Data may be relayed from the destination node **506** to the source node **502** via a second IDH component **402c2** and a first ODH component **408c1** in an analogous manner.

(143) The following aspects of the method illustrated in FIG. 2 have been described above and illustrated in the drawings identified above.

(144) Detecting the data may include receiving the data in a data unit sent by a previous node based on a previous-current path segment identifier, in the plurality, that identifies the current node with respect to the previous node.

(145) The first path-base protocol address may identify a destination node for receiving the data from a source node, via the current node and the next node, according to the network protocol. The first path-base protocol address may include the plurality in an identified first order that identifies the destination node, and the plurality in an identified second order may be included in a second

path-based protocol address for transmitting data from the destination node to the source node in one or more data units of the network protocol. The first order and/or the second order may be identified by sequence information represented separately from the plurality. The current node may be the source node. The next node may be the destination node.

(146) The first path-base protocol address may be a scope-specific protocol address that, in a source scope-specific address space specific to a first region of the network that includes the source node, identifies the destination node included in the network outside the first region. In still another aspect, the first path-base protocol address may be a nested protocol address that includes a protocol address that identifies a node in the network path other than the source node and the destination node.

(147) The current-next path segment identifier may include a local scoped address that identifies the next node in a region of the network that includes both the next network interface of the current node a network interface of the next node for receiving the data. In another aspect, the current-next path segment identifier may be included in a nested protocol address that includes a protocol address that identifies a node in a network path for transmitting the data from the current node to the next node. In an additional aspect, the current-next path segment identifier may be included in a scope-specific protocol address that, in a current scope-specific address space specific to a current region of the network that includes the current node, identifies the next node that is outside the current region.

(148) In yet another aspect, the current-next path segment identifier may include a next hop identifier that identifies a next pair of consecutive nodes in a network path from the current node to the next node for transmitting the data to the next node. One or more of the current node and the next node may be included in the next hop. The next hop identifier may identify the next hop to one or more of the current node and the next node. The next hop identifier may include one or more of a next interface identifier that identifies the network interface and next-current interface identifier that identifies a next-current network interface in the next node for receiving the data. The next hop identifier may be the smallest identifier available, according to a size criterion, in an identifier space for at least one of the current node and the next node.

(149) To the accomplishment of the foregoing and related ends, the descriptions and annexed drawings set forth certain illustrative aspects and implementations of the disclosure. These are indicative of but a few of the various ways in which one or more aspects of the disclosure may be employed. The other aspects, advantages, and novel features of the disclosure will become apparent from the detailed description included herein when considered in conjunction with the annexed drawings.

(150) It should be understood that the various components illustrated in the various block diagrams represent logical components that operate to perform the functionality described herein and may be implemented in software, hardware, or a combination of the two. Moreover, some or all of these logical components may be combined, some may be omitted altogether, and additional components may be added while still achieving the functionality described herein. Thus, the subject matter described herein may be embodied in many different variations, and all such variations are contemplated to be within the scope of what is claimed.

(151) To facilitate an understanding of the subject matter described above, many aspects are described in terms of sequences of actions that may be performed by elements of a computer system. For example, it will be recognized that the various actions may be performed by specialized circuits or circuitry (e.g., discrete logic gates interconnected to perform a specialized function), by program instructions being executed by one or more processors, or by a combination of both. The description herein of any sequence of actions is not intended to imply that the specific order described for performing that sequence must be followed.

(152) Moreover, the methods described herein may be embodied in executable instructions stored in a non-transitory computer readable medium for use by or in connection with an instruction

execution machine, system, apparatus, or device, such as a computer-based or processor-containing machine, system, apparatus, or device. As used here, a “non-transitory computer readable medium” may include one or more of any suitable media for storing the executable instructions of a computer program in one or more forms including an electronic, magnetic, optical, and electromagnetic form, such that the instruction execution machine, system, apparatus, or device may read (or fetch) the instructions from the non-transitory computer readable medium and execute the instructions for carrying out the described methods. A non-exhaustive list of conventional exemplary non-transitory computer readable media includes a portable computer diskette; a random access memory (RAM); a read only memory (ROM); an erasable programmable read only memory (EPROM or Flash memory); optical storage devices, including a portable compact disc (CD), a portable digital video disc (DVD), a high definition DVD (HD-DVD™), and a Blu-ray™ disc; and the like

(153) Thus, the subject matter described herein may be embodied in many different forms, and all such forms are contemplated to be within the scope of what is claimed. It will be understood that various details may be changed without departing from the scope of the claimed subject matter. Furthermore, the foregoing description is for the purpose of illustration only, and not for the purpose of limitation, as the scope of protection sought is defined by the claims as set forth hereinafter together with any equivalents.

(154) All methods described herein may be performed in any order unless otherwise indicated herein explicitly or by context. The use of the terms “a” and “an” and “the” and similar referents in the context of the foregoing description and in the context of the following claims are to be construed to include the singular and the plural, unless otherwise indicated herein explicitly or clearly contradicted by context. The foregoing description is not to be interpreted as indicating that any non-claimed element is essential to the practice of the subject matter as claimed.

(155) FIG. **8** illustrates an arrangement of components in a system that operates in an execution environment, such as execution environment **102** in FIG. **1**. The arrangement of components in the system operates to perform the method illustrated in FIG. **7**. The system illustrated includes a hop manager component **802**, an address space director component **804**, and a topology component **806**. The execution environment includes a processor, such as the processor **104**, to process an instruction in at least one of the hop manager component **802**, the address space director component **804**, and the topology component **806**.

(156) With reference to FIG. **7**, a block **702** illustrates that the method includes identifying a first hop identifier that is, for a first node in a network, an identifier of a first hop that includes a pair of consecutive nodes in a network path in the network. Accordingly, a system for determining a protocol address for a node includes means for identifying a first hop identifier that is, for a first node in a network, an identifier of a first hop that includes a pair of consecutive nodes in a network path in the network. For example, the arrangement illustrated in FIG. **8**, includes a hop manager component **802** operable for and/or otherwise included in identifying a first hop identifier that is, for a first node in a network, an identifier of a first hop that includes a pair of consecutive nodes in a network path in the network.

(157) In an aspect, hop information may be received in an exchange between a first node in a hop and one or more of a second node in the hop and a third node in the network. A hop may be detected in response to exchanging and/or otherwise receiving the hop information.

(158) Further, hop information for a network protocol may be detected by detecting an active protocol end point, such as a TCP port, for the network protocol and/or any network protocol included in activating the protocol endpoint.

(159) Hop information may be received in response to a user input detected by an input device. In an aspect, the hop information may be included in topology information that identifies a network topology or part of a network topology. In FIG. **5A**, the third edge node **508a3** as described above may host a topology service that maintains network topology information. Such a node may be

referred to as a topology node. Some or all of the network topology information may be received via an input device in response to a user input. A user may provide, via one or more input devices, hop information that identifies one or more of the first path node **504a1**, the second path node **504a2**, and a communicative relationship that identifies the hop.

(160) Hop information for a hop may be exchanged and/or received in response to detecting a change in a state of an operable coupling between a network and a network interface included in the hop and included in a node in the hop. Detecting the change may include detecting that the state indicates that the operable coupling is inoperative and subsequently detecting that the state indicates the operable coupling is operative. Detecting the change may include detecting that the state indicates that the operable coupling is operative and subsequently detecting that the state indicates the operable coupling is inoperative.

(161) Hop information may identify an interface identifier that identifies at least one of a first network interface by which a first node is included in a hop and a second network interface by which a second node is included in the hop.

(162) Determining that a hop identifier meets an identified hop identifier criterion may include determining that the hop identifier is the smallest, available hop identifier in an identifier space of hop identifiers.

(163) Determining that a hop identifier meets an identified hop identifier criterion may include identifying a threshold condition that is based on the hop identifier criterion. The determining may further include detecting that the threshold condition is met by the hop identifier. The hop identifier may be determined in response to detecting that the threshold condition is met. A threshold condition may be evaluated based on a count of network interfaces included in one or more nodes in a hop, a size of a location in a data storage medium to store a hop identifier, a size of a representation of a hop identifier in a signal propagated by a specified data transmission medium, a size of a hop identifier included in a protocol address in a data unit that is valid according to a network protocol, and/or a time period to process a hop identifier included in a protocol address, to name a few examples.

(164) A hop identifier criterion may specify and/or otherwise identify some or all of a schema that defines a valid format and/or a valid vocabulary for a representation of a hop identifier when included in a protocol address identifying a protocol endpoint of a network protocol. In an aspect, the schema may specify and/or otherwise identify a format rule defining a valid size of the representation in the protocol address included in a data unit of the network protocol. A size specified by a schema may identify a maximum size for a representation of a hop identifier. A size specified by a schema may identify a minimum size for a representation of a hop identifier. A size may identify an optimum or preferred size, based on a specified criterion, for a representation of a hop identifier. A size specified by a schema may identify a maximum size for an interface identifier included in a hop identifier. A size specified by a schema may identify a minimum size for an interface identifier included in a hop identifier. A size may identify an optimum or preferred size, based on a specified criterion, for an interface identifier included in a hop identifier.

(165) A hop identifier may be based on one or more network interfaces in nodes in the hop. More generally a hop identifier may be based on one or more network interfaces in one more nodes for which a hop identifier serves to identify a particular hop. Thus, with respect to the method in FIG. 7 the first hop identifier may be identified based on one or more of a first network interface in the first node and a second network interface in a node in the first hop, and/or a network interface in a node in a network path that from the first node to a node in the first hop. Further, with respect to the method in FIG. 7, the first hop identifier may include a path identifier that identifies a network path included in communicatively coupling the first node to a node in the first hop. The first hop identifier of FIG. 7 may include a protocol address for the network protocol that at least one of identifies the first node to a node in the hop and identifies a node in the hop to the first node.

(166) Returning to FIG. 7, block **704** illustrates that the method further includes receiving a first

protocol address that for a network protocol at least one of identifies the first node to a second node in the network and identifies the second node to the first node, wherein the second node is not in the first hop. Accordingly, a system for determining a protocol address for a node includes means for receiving a first protocol address that for a network protocol at least one of identifies the first node to a second node in the network and identifies the second node to the first node, wherein the second node is not in the first hop. For example, the arrangement illustrated in FIG. 8, includes an address space director component **804** operable for and/or otherwise included in receiving a first protocol address that for a network protocol at least one of identifies the first node to a second node in the network and identifies the second node to the first node, wherein the second node is not in the first hop.

(167) Returning to FIG. 7, a block **706** illustrates that the method yet further includes determining, based on the first protocol address and the first hop identifier, a second protocol address that for the network protocol at least one of identifies, to the second node, a node in the first hop that is not the first node and identifies the second node, to a node in the first hop, that is not the first node.

Accordingly, a system for determining a protocol address for a node includes means for determining, based on the first protocol address and the first hop identifier, a second protocol address that for the network protocol at least one of identifies, to the second node, a node in the first hop that is not the first node and identifies the second node, to a node in the first hop, that is not the first node. For example, the arrangement illustrated in FIG. 8, includes an topology component **806** operable for and/or otherwise included in determining, based on the first protocol address and the first hop identifier, a second protocol address that for the network protocol at least one of identifies, to the second node, a node in the first hop that is not the first node and identifies the second node, to a node in the first hop, that is not the first node.

(168) In a further aspect, a hop identifier may identify a hop to a node where the node is not in the hop.

(169) As described above, one or more nodes in a network **500**, as illustrated in FIGS. 5A-C, may individually or cooperatively operate to perform the method of FIG. 7. An adaptation, analog, and/or instance of the arrangement of components in FIG. 8 may operate in a topology service that includes a topology node in a network. Hop information and protocol addresses may be detected and/or reported to the topology node. The topology node may create, update, and/or otherwise maintain a representation of a topology of some or all of a network. The topology node may be included in a group of topology nodes in a topology service or system. Each of the topology nodes may maintain a representation of a topology for a portion of the network and/or for the entire network. As used herein, the term topology node is used interchangeably with the term topology execution environment, which is an execution environment that hosts a topology service or a portion thereof. A topology execution environment may include and/or otherwise be hosted by one or more nodes.

(170) In an aspect, a topology system may include topology nodes organized as a hierarchy of topology nodes that maintain a hierarchy of the representations of respective portions of a topology of a network. In another aspect, topology nodes may operate in a peer-to-peer system.

(171) In yet another aspect of the method, in FIG. 7, the second protocol address may be associated with a symbolic identifier of one of the path end nodes of the network path. The symbolic identifier may be resolved to the second protocol address and vice versa.

(172) With reference to FIG. 9, a block **902** illustrates that the method includes detecting, by a current node in a network, data in a data unit that is specified according to a network protocol and that includes a first protocol address including a plurality of other protocol addresses. Accordingly, a system for routing based on a nested protocol address includes means for detecting, by a current node in a network, data in a data unit that is specified according to a network protocol and that includes a first protocol address including a plurality of other protocol addresses. For example, the arrangement illustrated in FIG. 3, includes the in-data handler component **302** operable for and/or

otherwise included in detecting, by a current node in a network, data in a data unit that is specified according to a network protocol and that includes a first protocol address including a plurality of other protocol addresses. FIGS. 4A-C illustrate in-data handler components **402** as adaptations and/or analogs of the in-data handler component **302** in FIG. 3. One or more in-data handler components **402** operate in an execution environment **401**. In FIG. 4A, an in-data handler component **402a** is included in network layer component **403a**. In FIG. 4B and in FIG. 4C, in-data handler components **402** operates in respective line card components **409**.

(173) Returning to FIG. 9, a block **904** illustrates that the method further includes detecting a current-next protocol address in the plurality that identifies a next node with respect to the current node. Accordingly, a system for routing based on a nested protocol address includes means for detecting a current-next protocol address in the plurality that identifies a next node with respect to the current node. For example, the arrangement illustrated in FIG. 3, includes the routing component **304** operable for and/or otherwise included in detecting a current-next protocol address in the plurality that identifies a next node with respect to the current node. FIGS. 4A-C illustrate routing components **404** as adaptations and/or analogs of the routing component **304** in FIG. 3. One or more routing components **404** operate in an execution environment **401**.

(174) Returning to FIG. 9, a block **906** illustrates that the method yet further includes determining, based on the current-next protocol address, a next network interface. Accordingly, a system for routing based on a nested protocol address includes means for determining, based on the current-next protocol address, a next network interface. For example, the arrangement illustrated in FIG. 3, includes the forwarding component **306** operable for and/or otherwise included in determining, based on the current-next protocol address, a next network interface. FIGS. 4A-C illustrate forwarding components **406** as adaptations and/or analogs of the forwarding component **306** in FIG. 3. One or more forwarding components **406** operate in an execution environment **401**.

(175) Nested protocol addresses illustrated in FIGS. 6A-E may include protocol addresses that identify a next node. In some aspects, a protocol address of next node includes an identifier of a network interface to transmit data to a destination protocol address via a network path that includes a next node identified by the protocol address. Routing tables and/or routing policies are not required when protocol addresses include identifiers of next nodes. In some aspects, routing tables and routing policies may be supported for some addresses included in destination and/or source protocol address.

(176) Returning to FIG. 9, a block **908** illustrates that the method yet further includes sending, via the next network interface, the data to the next node. Accordingly, a system for routing based on a nested protocol address includes means for sending, via the next network interface, the data to the next node. For example, the arrangement illustrated in FIG. 3, includes the out-data handler component **308** operable for and/or otherwise included in sending, via the next network interface, the data to the next node. FIGS. 4A-C illustrate out-data handler components **408a** as adaptations and/or analogs of the out-data handler component **308** in FIG. 3. One or more out-data handler components **408a** operate in an execution environment **401**.

(177) With reference to FIG. 10, a block **1002** illustrates that the method includes receiving data, via a network from a previous node by a current node via a previous network interface operatively coupling the current node to the network, in a data unit that is specified according to a network protocol and that includes address information. Accordingly, a system for routing based on a scope-specific address space includes means for receiving data, via a network from a previous node by a current node via a previous network interface operatively coupling the current node to the network, in a data unit that is specified according to a network protocol and that includes address information. For example, the arrangement illustrated in FIG. 3, includes the in-data handler component **302** operable for and/or otherwise included in receiving data, via a network from a previous node by a current node via a previous network interface operatively coupling the current node to the network, in a data unit that is specified according to a network protocol and that

includes address information. FIGS. 4A-C illustrate in-data handler components **402** as adaptations and/or analogs of the in-data handler component **302** in FIG. 3. One or more in-data handler components **402** operate in an execution environment **401**. In FIG. 4A, an in-data handler component **402a** is included in network layer component **403a**. In FIG. 4B and in FIG. 4C, in-data handler components **402** operates in respective line card components **409**.

(178) Returning to FIG. 10, a block **1004** illustrates that the method further includes detecting, based on the address information, a current-next protocol address that, in a current scope-specific address space specific to a current region including the current node, identifies a next node. Accordingly, a system for routing based on a scope-specific address space includes means for detecting, based on the address information, a current-next protocol address that, in a current scope-specific address space specific to a current region including the current node, identifies a next node. For example, the arrangement illustrated in FIG. 3, includes the routing component **304** operable for and/or otherwise included in detecting, based on the address information, a current-next protocol address that, in a current scope-specific address space specific to a current region including the current node, identifies a next node. FIGS. 4A-C illustrate routing components **404** as adaptations and/or analogs of the routing component **304** in FIG. 3. One or more routing components **404** operate in an execution environment **401**.

(179) Address representations **602** in FIGS. 6A-E are described with respect to their inclusion in data units of a network protocol. Each may be identified as scope-specific, by a routing component **404a**, by a bit pattern or identifier defined to identify a protocol address type as a scope-specific address type. The bit pattern or identifier may be located by the routing component **404a** stored in a type bits portion of an IP packet and/or in some other specified location.

(180) FIG. 6A illustrates an address representation **602a** that may be detected by an in-data handler component **402a** and/or a routing component **404a** in a data unit or packet of an Internet Protocol or other network layer protocol. An address representation **602a** may identify one or more scope-specific addresses for a respective one or more nodes in a network path to transmit data from a source node to a destination node via the network path. A routing component **404a**, in a current node **504**, may process information in a previous protocol address field **608a** to identify a previous protocol address that, in a previous protocol address space of a previous node in the network path, identifies the current node **504**. A routing component **404a** may identify, based on information in a next protocol address field **610a**, a next protocol address, that, in a current scope-specific address space of the current node, identifies a next node in the network path. In FIG. 6A previous portion **608a2** may be a scope-specific address of the current node in a region that includes a previous node in a network path from the source node to the current node. A next portion **610a2** may be scope-specific address of a next node to the current node, where the next node is outside a region that includes the current node.

(181) Alternatively or additionally, a routing component **404a** may identify, based on information in a next protocol address field **610a**, a current protocol address, that, in a next scope-specific address space specific to a next region that includes the next node, identifies the current node. A routing component **404a** interoperating with an in-data handler component **402** may determine a next protocol address, in the current scope-specific address space, that identifies the next node, based on the current protocol address. Further, the next scope-specific address space may be a node-specific address space specific to the next node. In another aspect, a routing component may determine the current protocol address based on the next protocol address.

(182) In still another aspect, a scope-specific address may conform to a currently known schema defining a valid Internet Protocol address as specified by RFC 791 and/or RFC 3513 in a scope-specific address spaces specific to a region. The scope-specific address is processed as scope-specific as opposed to interpreting it as included in a global address space as is currently done. In one aspect, a mapping may be specified between two scope-specific address space. In another aspect, a mapping may be specified from a scope-specific address space to a global address space.

A mapping may be ruled-based and/or may be specified by associations such as represented by a lookup table.

(183) A routing component **404a** in a current node **504** may detect first address information identifying a current-first protocol address that, in a current scope-specific address space specific to a current region that includes the current node **504**, identifies a first node in the network. Second address information identifying a first-second protocol address that, in a first scope-specific address space specific to a first region that includes the first node, identifies a second node in a network path including the current node to transmit data from a source node **502** and an identified destination node **506**. The routing component **404a** operating in the current node **504** may detect a relationship between the current-first protocol address and the first-second protocol address. The routing component **404a** may generate a first-to-current mapping rule based on the relationship. The routing component **404a** may process the first-second protocol address based on the first-to-current mapping rule to determine a current-second protocol address that, in the current scope-specific address space, identifies the second node in the network path. The second node may be a next node with respect to the current node **504** and the data from the source node **502**. The second node may be the destination node **506**.

(184) A current-first protocol address 10.22.106.3 from a current scope-specific address space, may serve as an identifier with respect to the current node of a first node in the network. A first-second protocol address 40.88.58.1 in a first scope-specific address space, may serve as an identifier with respect to the first node of a second node. The current-first protocol address and first-second protocol address, in the example, include four parts. A first-first protocol address may be represented as 0.0.0.0 that, in the first scope-specific address spaces identifies the first node. A routing component **404** in the current node **504** may determine that the current-second protocol address, in the current scope-specific address space, for the second node may be calculated based on the mapping rule represented here as $40+10 \bmod 256.88+22 \bmod 256.106+58/\bmod 256.3+1 \bmod/256$, or 50.110.164.4.

(185) The mapping rule may be specific to the current scope-specific address space and the second scope-specific address space, may be specific to an identified group of scope-specific address spaces specific to a respective group of regions, and/or may apply among all scope-specific address spaces in use by nodes in a network. Those skilled in the art will see given the examples than many mapping rules exist that allow protocol addresses to be determined from previous protocol address information and next protocol address information according to the method illustrated in FIG. **10**.

(186) A next protocol address and/or a previous protocol address may be determined and/or otherwise identified based on one or more of a schema of one or more of a destination protocol address and/or a source protocol address identified in an address information portion of a data unit, a schema of a scope-specific hop identifier, a mapping between two or more of the schemas or portions thereof of two or more respective scope-specific address spaces, relationships between the nodes to which the protocol addresses are specific, relationships between the scope-specific address spaces of the protocol addresses, and relationships between the nodes in a network that includes them. Some of the relationships listed may be represented in a network topology of the network. A routing component **404** may detect some or all of the network topology in determining a next protocol address and/or a previous protocol address.

(187) Returning to FIG. **10**, a block **1006** illustrates that the method yet further includes determining, based on the current-next protocol address, a next network interface operatively coupling the current node to the network. Accordingly, a system for routing based on a scope-specific address space includes means for determining, based on the current-next protocol address, a next network interface operatively coupling the current node to the network. For example, the arrangement illustrated in FIG. **3**, includes the forwarding component **306** operable for and/or otherwise included in determining, based on the current-next protocol address, a next network interface operatively coupling the current node to the network. FIGS. **4A-C** illustrate forwarding

components **406** as adaptations and/or analogs of the forwarding component **306** in FIG. 3. One or more forwarding components **406** operate in an execution environment **401**.

(188) For scope-specific protocol addresses that do not include an identifier of a next node, a similar lookup operation may be performed. In an aspect, a scope-specific address may be mapped to another address space such as global protocol address space or subnet-specific protocol address space shared by nodes in a portion of a network such as a LAN and/or a sub-network. Performing a mapping operation may reduce the number of lookup tables and/or records that must be maintained and/or otherwise accessed.

(189) Protocol addresses illustrated in FIGS. 6A-E may include identifiers from scope-specific address spaces that identify a next node. In some aspects, a protocol address of next node includes an identifier of a network interface to transmit data to a destination protocol address via a network path that includes a next node identified by the protocol address. Routing tables and/or routing policies are not required when protocol addresses include identifiers of next nodes. In some aspects, routing tables and routing policies may be supported to support addresses from a global protocol address space and may be supported when a hop identifier identifies a pair of nodes in a network path that are communicatively coupled via one or more other path nodes.

(190) Returning to FIG. 10, a block **1008** illustrates that the method yet further includes sending, via the next network interface, the data to the next node. Accordingly, a system for routing based on a scope-specific address space includes means for sending, via the next network interface, the data to the next node. For example, the arrangement illustrated in FIG. 3, includes the out-data handler component **308** operable for and/or otherwise included in sending, via the next network interface, the data to the next node. FIGS. 4A-C illustrate out-data handler components **407a** as adaptations and/or analogs of the out-data handler component **308** in FIG. 3. One or more out-data handler components **407a** operate in an execution environment **401**.

(191) The following aspects of the method illustrated in FIG. 10 have been described above and illustrated in the drawings identified above. The address information referred to FIG. 10 may include next protocol address information for identifying one or more of the current-next protocol address and a next-current protocol address that, in a next scope-specific address space specific to a next region including the next node, identifies the current node. Further, the address information may include previous protocol address information for identifying at least one of a previous-current protocol address that, in a previous scope-specific address space specific to a previous region that includes the previous node, identifies the current node and a current-previous protocol address that, in the current scope-specific address space, identifies the previous node.

(192) A first hop including a first hop node and a second hop node, both in the network path, may be identified with respect to the previous node by a previous hop identifier in a previous scope-specific address space specific to a previous region that includes the previous node, identified with respect to the current node by a current hop identifier in the current scope-specific address space, and identified with respect to the next node by a next hop identifier in a next scope-specific address space specific to a next region that includes the next node.

(193) The first hop identifier may be assigned from a first scope-specific address space specific to a first region that includes a network interface in the first hop node to identify the first hop in response to a negotiation between the nodes in the first hop.

(194) A current-first path hop identifier that, in the current scope-specific address space, identifies the first hop and the current-first path identifier includes the first hop identifier, wherein the current-first path identifier identifies a network path that includes the current node as a path end node, the first hop node, and the second hop node. The first hop may be included in communicatively coupling the current node and one of the source node and the destination node. The current node may be either the first hop node or the second hop node. The previous-current protocol address may include the first hop identifier or the current-next protocol address may include the first hop identifier.

(195) FIG. **12** illustrates an arrangement of components in a system that operates in an execution environment, such as execution environment **102** in FIG. **1**. The arrangement of components in the system operates to perform the method illustrated in FIG. **11**. The system illustrated includes an address handler component **1202**, an address space director component **1204**, and a resolver component **1206**. A suitable execution environment includes a processor, such as processor **104**, to process an instruction in at least one of the address handler component **1202**, the address space director component **1204**, and the resolver component **1206**.

(196) With reference to FIG. **11**, block **1102** illustrates that the method includes detecting first address information that identifies at least one of a first-second protocol address that, according to a network protocol, identifies a second node to a first node in the network and a second-first protocol address that, according to the network protocol, identifies the first node to the second node. Accordingly, a system for identifying a protocol address in a scope-specific address space includes means for detecting first address information that identifies at least one of a first-second protocol address that, according to a network protocol, identifies a second node to a first node in the network and a second-first protocol address that, according to the network protocol, identifies the first node to the second node. For example, the arrangement illustrated in FIG. **12**, includes an address handler component **1202** that is operable for and/or otherwise is included in detecting first address information that identifies at least one of a first-second protocol address that, according to a network protocol, identifies a second node to a first node in the network and a second-first protocol address that, according to the network protocol, identifies the first node to the second node.

(197) As described herein, a first node may detect address information that identifies a first-second protocol address that, in a first scope-specific address space specific to a first region that includes the first node, identifies the second node. Alternatively or additionally, the second node may detect address information that identifies a second-first protocol address that, in a second scope-specific address space specific to a second region that includes the second node, identifies the first node to the second node. Alternatively or additionally, the second node may receive address information identifying the first-second protocol address. The second node may determine the second-first protocol address based on the first-second protocol address. Alternatively or additionally, the first node may receive the second-first protocol address. The first node may determine the first-second protocol address based on the second-first protocol address.

(198) Returning to FIG. **11**, block **1104** illustrates that the method further includes detecting second address information that identifies at least one of a second-third protocol address that identifies, according to the network protocol, a third node in the network to the second node and a third-second protocol address that identifies, according to the network protocol, the second node to the third node. Accordingly, a system for identifying a protocol address in a scope-specific address space includes means for detecting second address information that identifies at least one of a second-third protocol address that identifies, according to the network protocol, a third node in the network to the second node and a third-second protocol address that identifies, according to the network protocol, the second node to the third node. For example, arrangement illustrated in FIG. **12**, includes address space director component **1204** that is operable for and/or otherwise is included in detecting second address information that identifies at least one of a second-third protocol address that identifies, according to the network protocol, a third node in the network to the second node and a third-second protocol address that identifies, according to the network protocol, the second node to the third node.

(199) Returning to FIG. **11**, block **1106** illustrates that the method yet further includes determining, based on the first address information and the second address information, a first-third protocol address that, in a first scope-specific address space specific to a first region that includes the first node, identifies the third node according to the network protocol, wherein the third node is outside the first region. Accordingly, a system for identifying a protocol address in a scope-specific address space includes means for determining, based on the first address information and the second

address information, a first-third protocol address that, in a first scope-specific address space specific to a first region that includes the first node, identifies the third node according to the network protocol, wherein the third node is outside the first region. For example, the arrangement in FIG. 12, includes resolver component 1206 that is operable for and/or otherwise is included in determining, based on the first address information and the second address information, a first-third protocol address that, in a first scope-specific address space specific to a first region that includes the first node, identifies the third node according to the network protocol, wherein the third node is outside the first region.

(200) As described various types of protocol addresses may conform to various schemas defining rules for formatting valid protocol addresses and/or defining vocabularies specifying valid content of a protocol address. Given first address information identifying a first protocol address and second address information identifying a second protocol address as described above with respect to the method illustrated in FIG. 11, a resolver component may determine a scope-specific first-third protocol address based on one or more of a schema of one or more of the first protocol address, a schema of the second protocol address, a schema of the third protocol address, a mapping between two or more of the schemas or portions thereof, relationships between the nodes to which the protocol addresses are specific, relationships between the scope-specific address spaces of the protocol addresses, and/or relationships between the nodes in a network that includes them. Some of the relationships listed may be represented in a network topology of the network. A resolver component may detect some or all of the network topology in determining the first-third protocol address.

(201) A mapping rule may indicate that addresses in a first scope-specific address space have a one-to-one mapping between the first scope-specific address space and a second scope-specific address space that is based on an addend for each of the four portions of the various addresses, additionally taking the modulus of the result based on a maximum value for each address information field, and determining the absolute value to determine the final result. A third protocol address from the second scope-specific address space may serve to identify a third node in a third region. The second protocol address may be represented as, 200.10.150.33. A resolver component in the first node may determine that a third protocol address that, in the first scope-specific address space, identifies the third node may be calculated based on the mapping rule as “ $(200+30)\bmod 256$. $(10+66)\bmod 256$. $(150+198)\bmod 256$. $(33+254)\bmod 256$ ”, or 230.76.92.31.

(202) Nodes may exchange mapping information. In an aspect, the address information may identify a mapping rule when exchanged between nodes. The mapping rule may be determined by second node and sent to a first node. The mapping rule may include mapping information for mapping addresses from the third scope-specific address space to the first scope-specific address space.

(203) As described above and illustrated in the accompanying drawings, the method illustrated in FIG. 11 may include additional aspects supported by various adaptations and/or analogs of the arrangement of components in FIG. 12. With respect to FIG. 11, in one aspect one or more of the first-third protocol address and the third-first protocol address may identify a third network path for exchanging data between the first node and the third node.

(204) In another aspect, detecting the first address information may include detecting first path information identifying a first network path. The first network path includes a first sequence of nodes included in transmitting data between the first node and the second node. Analogously, detecting the second address information may include detecting second path information identifying a second network path. The second network path includes a second sequence of nodes included in exchanging data between the second node and the third node. One or more of the first-third protocol address and the third-first protocol address may be determined based on the first path information and the second path information. The first-third protocol address and/or the third-first protocol address may identify a third network path including a third sequence of nodes included in

communicatively coupling the first node and the third node.

(205) In another aspect of the method illustrated in FIG. 11, the first-second protocol address may be in the first scope-specific address space, the second-first protocol address may be in a second-scope-specific address space specific to a second region that includes the second node, the second-third protocol address may be in the second scope-specific address space, and/or the third-second protocol address may be in the third scope-specific address space. One or more of the scope-specific address spaces may be node-specific address spaces specific to the respective one or more of the first node, the second node, and the third node.

(206) Hop information may be exchanged between a first node in a hop and one or more of a second node in the hop and a third node in the network. A hop may be detected in response to exchanging the hop information. In another aspect, hop information may be exchanged in response to detecting a hop.

(207) Hop information may be received in response to a user input detected by an input device. In an aspect, the hop information may be included in topology information that identifies a network topology or part of a network topology.

(208) A hop including pair of nodes may include a first network interface in a first node in the pair and a second network interface in a second node in the pair.

(209) In another, aspect, a first node may be included in a first hop that includes a second node via a first network interface and the first node may be included in a second hop that includes the second node via a second network interface. The two NICs may be associated with different internet protocol addresses. Data units including one of the IP addresses are processed by one of the NICs and data units including the other IP address are processed by the other NIC.

(210) A first node may be included in a first hop along with a second node. The first node may be included in the first hop via a first network interface in the first node. The first node may be included in a second hop including a third node. The first node may be included in the second hop via a second network interface in the first node.

(211) A first node and a second node may be included in a first hop in a first network path from a source node to a destination node. The first node may be included in the first hop via a first network interface in the first node included in communicatively coupling the first node and the second node. The first node and the second node may be included in a second hop in a second network path from the source node to the destination node. The first node may be included in the second hop via a second network interface in the first node included in communicatively coupling the first node and the second node.

(212) Hop information for a hop may be exchanged in response to detecting a change in a state of an operable coupling between a network and a network interface included in the hop and included in a node in the hop. Detecting the change may include detecting that the state indicates that the operable coupling is inoperative and subsequently detecting that the state indicates the operable coupling is operative. Detecting the change may include detecting that the state indicates that the operable coupling is operative and subsequently detecting that the state indicates the operable coupling is inoperative.

(213) A network protocol may be specified to exchange data between and/or among nodes that include hop agent components to determine whether certain network interfaces in the nodes are operative or inoperative. The protocol may include and/or be an extension of one more existing protocols such as the address resolution protocol (ARP), the dynamic host configuration protocol (DHCP), and/or any of numerous network protocols for announcing and/or detecting the presence of a node, a network interface, and/or other resource on a network. The protocol may be a yet unspecified protocol to count network interfaces in a region of a network.

(214) An interface identifier included in hop information for a hop including a pair of nodes may be specified according to the requirements of a network protocol. The network protocol may be a network layer protocol, such the IPv4 and/or IPv6 protocols. The interface identifier may identify

at least one node in a hop to the other. The interface identifier may be suitable to include in a data unit of a network protocol to transmit data in the data unit between the nodes in the hop. Hop information for a hop may be exchanged in more than one communication sent and/or received by a node in the hop.

(215) Determining a hop identifier for a hop may include determining the hop identifier based on an interface identifier that identifies at least one network interface in the hop. The interface identifier may identify at least one of a first network interface in a first node in the hop and a second network interface in a second node in the hop to at least one of the first node and the second node.

(216) A hop identifier for a hop may be based on a first interface identifier that identifies a first network interface in a first node in the hop and/or may be based on a second interface identifier that identifies a second network interface in a second node in the hop. The first interface identifier may identify the first network interface to one or both of the nodes in the hop. The second interface identifier may identify the second network interface to at least one of the first node and the second node. The hop identifier may include the first interface identifier and/or the second interface identifier.

(217) FIG. **14** illustrates an arrangement of components in a system, that operates in an execution environment, such as execution environment **102** in FIG. **1**. The arrangement of components in the system operates to perform the method illustrated in FIG. **13**. The system illustrated includes a path detector component **1402**, an address space director component **1404**, and a path composer component **1406**. A suitable execution environment includes a processor, such as processor **104**, to process an instruction in at least one of the path detector component **1402**, the address space director component **1404**, and the path composer component **1406**.

(218) Some or all of the exemplary components illustrated in FIG. **14**, their adaptations, and/or their analogs may operate in a number of execution environments to perform the method illustrated in FIG. **13**.

(219) With reference to FIG. **13**, block **1302** illustrates that the method includes detecting first path information that identifies a first sequence of nodes in a first network path for transmitting data between a first node and a second node in a network. Accordingly, a system for identifying a protocol address based on path information includes means for detecting first path information that identifies a first sequence of nodes in a first network path for transmitting data between a first node and a second node in a network. For example, in the arrangement in FIG. **14**, detecting first path information that identifies a first sequence of nodes in a first network path for transmitting data between a first node and a second node in a network is performed via operation of the path detector component **1402**.

(220) Returning to FIG. **13**, block **1304** illustrates that the method further includes detecting second path information that identifies a second sequence of nodes in a second network path for transmitting data between the second node and a third node in the network. Accordingly, a system for identifying a protocol address based on path information includes means for detecting second path information that identifies a second sequence of nodes in a second network path for transmitting data between the second node and a third node in the network. For example, as illustrated in FIG. **14**, detecting second path information that identifies a second sequence of nodes in a second network path for transmitting data between the second node and a third node in the network is performed via operation of the address space director component **1404**.

(221) As described above and further below, path information for a network protocol may be detected in a data unit of the network protocol. The path information may be detected by a node transmitting the data unit and/or may be detected by a node receiving the data unit.

(222) In another aspect, a message may be sent to a network directory service to register a name or symbolic identifier for a node and/or a network interface of a node. The network directory service may associate the symbolic identifier with address information, which as described herein may be

path information. Path information may be detected in the registration message and/or in one or more data units of a network protocol for which an association is to be created and/or otherwise maintained by a network directory service. Further, a response to the registration message may be exchanged between the registering node and the network directory service node. The response message and/or one or more data units included in transmitting the response may include and/or otherwise identify path information that may be detected by either node. Nodes in a network path transmitting the response and/or the registration request may detect path information in one or more data units received and/or sent in relaying some or all of one or both messages. Still further, a node may send a symbolic identifier to a network directory service in a resolve message in order to resolve the symbolic identifier to a protocol address of a node and/or a network interface identified by the symbolic identifier. Path information may be detected in the resolve message and/or in one or more data units of a protocol that the symbolic identifier is associated with in an association maintained by a network directory service. Further, a response to the resolve message may be exchanged between the requesting node and the network directory service node. The response message and/or one or more data units included in transmitting the response may include and/or otherwise identify path information that may be detected by either node. Nodes in a network path transmitting the response and/or the registration request may detect path information in one or more data units that they receive and/or send in relaying some or all of one or both messages.

(223) Returning to FIG. 13, block 1306 illustrates that the method yet further includes determining, based on the first path information and the second path information, a first-third protocol address that identifies, according to a network protocol, the third node to the first node for transmitting data from the first node to the third node. Accordingly, a system for identifying a protocol address based on path information includes means for determining, based on the first path information and the second path information, a first-third protocol address that identifies, according to a network protocol, the third node to the first node for transmitting data from the first node to the third node. For example, as illustrated in FIG. 14, determining, based on the first path information and the second path information, a first-third protocol address that identifies, according to a network protocol, the third node to the first node for transmitting data from the first node to the third node is performed via operation of path composer component 1406.

(224) With respect to the method in FIG. 13 and as described above, a first-second protocol address that identifies the second node with respect to the first node may be determined and/or otherwise identified based on the first path information. Alternatively or additionally, a second-first protocol address that identifies the first node with respect to the second node may be determined and/or otherwise identified based on the first path information. Further, a second-third protocol address that identifies the third node with respect to the second node may be determined and/or otherwise identified based on the second path information. Alternatively or additionally, a third-second protocol address that identifies the second node with respect to the third node may be determined and/or otherwise identified based on the second path information. The first-third protocol address may be determined based on at least one of the first-second protocol address and the second-first protocol and based on at least one of the second-third protocol address and the third-second protocol address.

(225) In an aspect of the method illustrated in FIG. 13, the first-third protocol address may be in a first scope-specific identifier space specific to a first network region that includes the first node. Refer to application Ser. No. 13/727,653 filed on 2012 Dec. 27, entitled “Methods, Systems, and Computer Program Products for Identifying a Protocol address in a Scope-specific Address Space”.

(226) FIG. 16 illustrates an arrangement of components in a system that operates in an execution environment, such as execution environment 102 in FIG. 1. The arrangement of components in the system operates to perform the method illustrated in FIG. 15. The system illustrated includes a count component 1602, an address space condition component 1604, an address space director component 1606, and an allocate component 1608. A suitable execution environment includes a

processor, such as the processor **104**, to process an instruction in at least one of the count component **1602**, the address space condition component **1604**, the address space director (ASD) component **1606**, and the allocate component **1608**.

(227) Some or all of the exemplary components illustrated in FIG. **16** may be adapted to perform the method illustrated in FIG. **15** in a number of execution environments.

(228) As the term “network topology” is defined herein, a network may have different network topologies with respect to different layers and/or network protocols and their corresponding protocol endpoints. A network topology may represent physical communicative couplings between nodes in the network. A network topology may represent logical hops in a network. In FIG. **5B**, the first network **514b1** may represent a physical topology when the first network **514b1** represents a physical data transmission medium included in physically coupling nodes. The data transmission medium may be an Ethernet LAN, for example. The hops **512** in FIG. **5** may illustrate logical communicative couplings at a level of the network above the data transmission medium. The hops **512** may represent link layer hops, network layer hops, or hops at some other layer of the network above the data transmission medium or physical layer.

(229) With reference to FIG. **15**, a block **1502** illustrates that the method includes detecting a count of network interfaces in a first region, of a network, that includes a first network interface operatively coupling a first node to the first region. Accordingly, a system for assigning an interface identifier to a network interface includes means for detecting a count of network interfaces in a first region, of a network, that includes a first network interface operatively coupling a first node to the first region. For example, the arrangement illustrated in FIG. **16**, includes count component **1602** operable for and/or otherwise included in detecting a count of network interfaces in a first region, of a network, that includes a first network interface operatively coupling a first node to the first region.

(230) A region may include a single node with one or more network interfaces in the region and with no other network interfaces of other nodes in the region. All of the one or more network interfaces in the node may be in the region. Such a region is illustrated by a first region **510a1** including a source node **502a** in FIG. **5A**. The first region **510a1** illustrates a region that includes a single node, the source node **502a**.

(231) A node may include a network interface included in a region and may include another network interface not in the region. In FIG. **5A**, a second path node **504a2** is illustrated having a network interface included in a second region **510a2** and another network interface included in a third region **510a3**. A node may have a single network interface in a region and/or multiple network interfaces in a region.

(232) A count or a partial count of network interfaces in a node in a particular region may be detected by a node in the region or by a node in another region. Detecting a count may include receiving count information identifying the count or a portion of the count, in response to a user input detected by an input device via a node. In an aspect, a count of network interfaces and/or of NICs in one or more network interfaces in the source node **502a** may be a configuration setting set in response to an input detected from a user via an input device, such as described with respect to FIG. **1**.

(233) Detecting a count may include detecting whether network interface components in a region are in the same node. Detecting the count may further include determining that the network interface components are coupled to a same data transmission medium. Whether network interface components in the same node are coupled to a same data transmission medium may affect how network interfaces are counted. The network interface components in the network interface may be assigned the same protocol address for a particular protocol, such a network layer protocol. The internet protocol in the TCP/IP suite is an exemplary network layer protocol. Network interface components assigned the same protocol address may be counted as a single network interface when a count is for a network protocol of the protocol addresses.

(234) In another aspect, multiple network interface components in a node may be operatively coupled to a same data transmission medium and may be included in more than one network interface for counting. Thus a node that includes multiple network interface components coupled to a same data transmission medium, may have a network interface component in the multiple network interface components in one network interface and another network interface component in the multiple network interface components may be included in another network interface.

(235) As described above, detecting a change in a state of an operable coupling may include detecting that the state indicates the coupling is inoperative, and subsequently detecting that the state indicates the coupling is operative. Further, detecting a change in a state of a coupling may include detecting that the state indicates the coupling is operative and subsequently detecting that the state indicates the coupling is inoperative.

(236) A count component may monitor one or more operations included in sending data and/or receiving data via an operable coupling including a network and a network interface. Detecting a change in an operable coupling may include performing an operation to send a data unit and/or to receive a data unit via the coupling, then determining whether the operation was successful.

(237) A count may be based on whether a network interface in a region is in a node that is configured to send and/or receive a data unit of a particular network protocol via the network interface. A count of network interfaces may be performed according to the method illustrated in FIG. 15 for the purpose of assigning an identifier to a network interface for a particular network protocol.

(238) Returning to FIG. 15, a block 1504 illustrates that the method further includes determining, based on the count, a threshold condition. Accordingly, a system for assigning an interface identifier to a network interface includes means for determining, based on the count, a threshold condition. For example, the arrangement illustrated in FIG. 16, includes address space condition component 1604 operable for and/or otherwise included in determining, based on the count, a threshold condition.

(239) Returning to FIG. 15, a block 1506 illustrates that the method yet further includes identifying a first interface identifier that meets, based on a size attribute of the first interface identifier, the threshold condition. Accordingly, a system for assigning an interface identifier to a network interface includes means for identifying a first interface identifier that meets, based on a size attribute of the first interface identifier, the threshold condition. For example, the arrangement illustrated in FIG. 16, includes address space director component 1606 operable for and/or otherwise included in identifying a first interface identifier that meets, based on a size attribute of the first interface identifier, the threshold condition.

(240) Identifying a network interface may include identifying a schema or part of a schema defining a valid format and/or a valid vocabulary for a representation of an interface identifier. Interface identifiers are assigned to network interfaces for a purpose. Interface identifiers may be assigned to network interfaces for routing data, received via a network interface in a node, to another network interface component in the node to relay some or all of data received to another node. Interface identifiers may be included in a protocol address and/or may be included in generating a protocol address for a network protocol as described below. An interface identifier may be included in identifying a network path in a network and/or a hop including a pair of communicatively coupled nodes. As described above interface identifiers may be selected for saving power when processed in performing specific tasks, selected to save storage space, selected to save processing time, and/or selected to save on any number of other costs in performing one or more tasks. A schema may be defined based on one or more tasks and/or purposes associated with processing an interface identifier.

(241) Schemas explicitly and/or implicitly define rules for a valid format of an interface identifier and/or rules defining a vocabulary for defining valid content of a representation of an interface identifier. A rule may define a constraint on the format or structure of an interface identifier and/or

a constraint on the content of an interface identifier. Such constraints may specify or otherwise identify threshold conditions. A threshold condition may be specified by and/or otherwise based on a schema defining a valid protocol address to identify a protocol endpoint for a particular network protocol. The threshold condition may be determined based on size information defined by the schema for representing the protocol address in the data unit of the network protocol. The size information may identify at least one of a maximum size and a minimum size for a valid representation, according to the schema, of the protocol address in the data unit.

(242) A count of network interfaces may place a constraint on the minimum size of a representation of an interface identifier that is valid according to a specified schema. A schema may define a format rule and/or a vocabulary rule that may identify a maximum count and/or a minimum count. For example, in a schema that defines and/or otherwise allows an interface identifier to be represented by a number, the number of digits or number of identifiers in a suitable address space must be large enough to accommodate the value of the count detected. In binary, a single network interface may be represented by a single digit or bit. A count of seven network interfaces requires an identifier space that includes at least seven identifiers and at least some identifiers in the space require three digits or bits when represented in a binary or base two numeric representation. A schema may define and/or otherwise may be included in determining a constraint on the number of bits that may be used in representing an interface identifier.

(243) In FIG. 5A, the first region **510a1** is illustrated with one network interface. A schema including a rule constraining and/or otherwise allowing identifiers to be represented numerically may be determined by an address space condition component **404a** operating in the source node **502a** to determine an identifier space that includes at least one identifier.

(244) A threshold condition may be based on size information defined by the schema for representing a protocol address in the valid data unit. The size information may identify at least one of a maximum size and minimum size for a valid representation of a protocol address in a data unit.

(245) Determining an interface identifier space may include determining size information identifying at least one of a maximum size for an interface identifier. The maximum size may be based on the count, for an interface identifier; and determining the threshold condition based on the size information. The maximum size may be based on a schema rule.

(246) Returning to FIG. 15, a block **1508** illustrates that the method yet further includes providing the first interface identifier as an identifier of the first network interface. Accordingly, a system for assigning an interface identifier to a network interface includes means for providing the first interface identifier as an identifier of the first network interface. For example, the arrangement illustrated in FIG. 16, includes allocate component **1608** operable for and/or otherwise included in providing the first interface identifier as an identifier of the first network interface.

(247) An ordering of interface identifiers in an identifier space may be determined based on a metric. The metric may be for measuring of any of various attributes accessible within an execution environment. Examples of metrics for interface identifiers are provided above in describing threshold conditions.

(248) Further, an ordering of interface identifiers may correspond to an ordering of network interfaces. Interface identifiers may be assigned based on the correspondence. In an aspect, interface identifiers may be order based on a size of their respective representations in data units of a network protocol. For example, an interface identifier with the value 1 may be represented by a single bit in a data unit. An identifier with a value of '255' may require 4 bits according to a particular type of representation. Network interfaces in a node may be ordered based on one or more of data units sent and/or received; bytes sent and/or received; types of data transmission media coupled to respective network interface; a measure of congestion; a measure of energy or power utilization; measure of heat; an attribute of specified protocol configured to communicate via the network interfaces; and a role of a next node included in a hop that includes a network interface.

(249) Assigning an interface identifier to a first network interface in a first node may include receiving, via the first network interface, a message, sent via a second network interface in a second node, that includes criterion information to identify and/or assign an interface identifier. A criterion may be based on and/or may identify any of the measures described above. Assigning the interface identifier may further include determining that the first interface identifier meets the criterion. A threshold condition determined by an address space component may be determined based on such a criterion. The first interface identifier may be assigned to the first network interface in response to determining that the criterion is met by the first interface identifier.

(250) In an aspect, a first node may receive data from a second node in a data unit of a network protocol via a first network interface. The first network interface may have an assigned first interface identifier. The data may be received based on a protocol address of the network protocol that includes the first interface identifier. The protocol address may identify a third node. In an aspect, the protocol address may include a second interface identifier. The second interface identifier may be assigned to identify a second network interface in the first node. The first node may transmit the data to the third node via the second network interface identified by the second interface identifier in the protocol address. In another aspect, the protocol address may include a third interface identifier assigned to a third network interface in the third node. The third network interface may be included in communicatively coupling the first node and the third node via the second network interface in the first node. In an aspect, the first node may transmit the data to the third node via the second network interface based on an association between the third interface identifier and the second network interface.

(251) In another aspect, a first node may receive a message via a second network interface in the first node. The message may be from a second node in a network path that includes the second network interface. The message may include and/or may be received in one or more data units that include and/or identify a protocol address of a network protocol of the message or of the data units that include the message. The network protocol includes a first interface identifier assigned to a first network interface in the first node. The first node identifies the first network interface based on the first interface identifier in the protocol address. In response, the first node may send the message to a third node in a network path from the first node, where the network path includes the first network interface. The protocol address may be a valid address according to the network protocol of the third node. Alternatively, the third node may be a node in a network path to a destination node identified by the protocol address.

(252) As described in the previous paragraph, a hop may be assigned an identifier that is shared by the pair of nodes in the hop. In still another aspect, a first-second protocol address may indicate a first ordering of the first interface identifier and the second interface identifier. The first-second protocol address may identify the second node to the first node based on the first ordering. A second-first protocol address may include and/or otherwise indicate a second ordering of the first interface identifier. The second-first protocol address may identify the first node to the second node based on the second ordering.

(253) In an additional aspect, the method illustrated in FIG. 15 may include detecting a portion of a data unit, that is valid according to a network layer protocol, for representing a protocol address. The protocol address may identify a sender and/or a receiver of data included in the data unit. A hop threshold size may be determined for including a representation of a hop identifier in the detected portion. The hop threshold size may be determined based on a size of the hop identifier. A representation of the hop identifier may be stored in a hop location where the hop location has a size that meets a threshold condition based on the hop size.

(254) The method illustrated in FIG. 15 may include additional aspects supported by various adaptations and/or analogs of the arrangement of components in FIG. 16. In an aspect, the method may include determining that a protocol address, that is specified according to a network protocol, includes a first interface identifier assigned to a first network interface. Further, the method may

include determining that the protocol address includes an identifier of a second node in a network path that includes the first network interface. Determining that the second node is included in the network path that includes the first network interface may be based on the first interface identifier. The first interface identifier may identify the first network interface to transmit a data unit, of the network protocol, that includes and/or otherwise identifies the protocol address.

(255) In another aspect a count may be detected by a count component based on whether a network interface in the region is in a node configured to at least one of send and receive a data unit specified according to a network protocol.

(256) An address space condition component may determine a threshold condition based on an interface identifier space to identify a protocol endpoint of a network protocol. Determining the threshold condition may include determining, based on the count, a maximum count of interface identifiers in the interface identifier space

(257) Further, a threshold condition may be based on a metric to measure an address portion of a data unit, of a network protocol, in a data transmission when transmitted via a data transmission medium. The threshold condition may be based on a metric to measure a size of an interface identifier in a protocol address when stored in the address portion.

(258) In a further aspect identifying an interface identifier may include identifying an interface identifier space based on a threshold condition. The interface identifier interface identifier may be selected from the interface identifier space for assigning to a network interface.

(259) In another aspect a first node may receive data, from a second node via a first network interface, in a data unit including a protocol address, of a protocol endpoint of a network protocol, that includes a first interface identifier of the first network interface. The protocol address may be a valid identifier of a third node that is included in a network path that includes a second network interface in the first node. The first node may send the data to the third node via the second network interface. The protocol address includes a second interface identifier assigned to identify the second network interface.

(260) An interface identifier may be assigned to a first network interface in a first region in a node including a second network interface in a second region of a network. Assigning the first network interface may include determining that the first interface identifier is the smallest available interface identifier.

Claims

1. A method, comprising: performing at least one act that is configured to cause a transmitting node to: receive, from at least one other node in a network environment, a plurality of segment identifiers, store, in a data structure, the plurality of segment identifiers associated with nodes represented in a topology of at least a portion of the network environment, select, from the plurality of segment identifiers in the data structure and based on a specified policy, a first sequence of segment identifiers that identify a first sequence of at least one of: one or more nodes, one or more network interfaces, or one or more network regions, at least partially in a first path segment that communicatively couples the transmitting node with a receiving node in the network environment and that includes at least one particular node which is not predetermined by the first sequence of segment identifiers such that the at least one particular node is determined during routing of data between the transmitting node and the receiving node, identify, based on a segment identifier in a first subsequence, of the first sequence of segment identifiers, that precedes a second subsequence of the first sequence of segment identifiers, a first network interface of the transmitting node in the first path segment, store at least the second subsequence of the first sequence of segment identifiers in a header associated with a first packet, and transmit, via the first network interface, the first packet for delivering the data in a payload of the first packet to the receiving node in the network environment; and causing storage of a result of the at least one act on at least one non-transitory

memory.

2. The method of claim 1, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that the first sequence of segment identifiers includes a first node scoped network interface identifier that is selected based on a representation of a link from a first node to a second node in the first path segment that communicatively couples the transmitting node with the receiving node in the network environment.

3. The method of claim 2, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that the first node scoped network interface identifier is in a first node scoped identifier space that spans within the first node and identifies, for the first node, a particular network interface of the first node in the link.

4. The method of claim 3, and comprising: performing at least one additional act that is configured to cause the transmitting node to: receive an indication that the link has failed, utilizing the at least one of the link state protocol, the distance vector protocol, or the path vector protocol; and update a data structure in response to the receipt of the indication.

5. The method of claim 4, comprising: performing at least one additional act that is configured to cause the transmitting node to: determine, based on the updated data structure, a second sequence of segment identifiers that identify a second sequence of at least one of: one or more nodes, one or more network interfaces, or one or more network regions, at least partially in a second path segment that communicatively couples the transmitting node with the receiving node in the network environment, where the second sequence of segment identifiers does not include the first node scoped network interface identifier; store at least an end portion of the second sequence of segment identifiers in a header associated with a second packet; identify, based on a segment identifier that precedes the end portion of the second sequence of segment identifiers, a second network interface of the transmitting node in the second path segment; and transmit, via the second network interface, the second packet for delivering data in a payload of the second packet to the receiving node in the network environment.

6. The method of claim 5, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that the second network interface is not the first network interface.

7. The method of claim 5, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that the second sequence of segment identifiers is identical to the first sequence of segment identifiers.

8. The method of claim 5, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that the determining the second sequence of segment identifiers comprises: identifying, based on the updated data structure, a path segment identifier that is not included in the first sequence of segment identifiers and that identifies at least one of: a network interface, a node, or a region that, without utilizing the failed link, communicatively couples the first node with a path node in a portion of the first path segment that communicatively couples the first node to the receiving node; and including the path segment identifier in the second sequence of segment identifiers in a location that follows a segment identifier that identifies the first node.

9. The method of claim 8, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that the path segment identifier identifies, for at least the first node, the second node that is communicatively coupled to the first node via a particular path segment that is selectable based on the path segment identifier.

10. The method of claim 9, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that the path segment identifier includes another node scoped identifier, in the first node scoped identifier space, that identifies another network interface in another link that includes the second node.

11. The method of claim 9, and comprising: performing at least one additional act that is configured

to cause the transmitting node to operate such that the path segment communicatively couples the first node with the second node, and is selectable, based on the path segment identifier, from a routing table of the first node.

12. The method of claim 11, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that the path segment communicatively couples the first node with the second node, and is selectable from a plurality of path segments that communicatively couple the first node with the second node.

13. The method of claim 12, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that the plurality of path segments includes at least one multi-hop path segment.

14. The method of claim 9, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that both the first node and the second node are in a particular region of the network environment that is within a span of a particular identifier space that includes particular identifiers that identify at least a portion of particular nodes in the particular region.

15. The method of claim 9, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that the first node is in a particular region of the network environment that is within a span of a particular identifier space that includes particular identifiers that identify at least a portion of particular nodes in the particular region, where the second node is not in the particular region.

16. The method of claim 9, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that both the first node and the second node are in a domain of at least one of: a link state protocol, a distance vector protocol, or a path vector protocol utilized for communicating at least some segment identifiers of nodes or network interfaces within the domain.

17. The method of claim 9, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that the first node is in a domain where at least one of: a link state protocol, a distance vector protocol, or a path vector protocol utilized for communicating at least some identifiers of nodes or network interfaces within the domain and the second node is not in the domain.

18. The method of claim 8, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that the path segment identifier identifies, for at least the first node, a third node that follows the second node in the first path segment and that is communicatively coupled to the first node via a particular path segment that is selectable based on the path segment identifier.

19. The method of claim 18, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that the path segment identifier includes another node scoped identifier, in the first node scoped identifier space, that identifies another network interface in another link that includes the third node.

20. The method of claim 2, and comprising: performing at least one additional act that is configured to cause the transmitting node to operate such that the at least one of the link state protocol, the distance vector protocol, or the path vector protocol is utilized to receive, from the at least one other node in the network environment, particular data that associates the first node scoped network interface identifier and the link, wherein the particular data is based on data transmitted by the first node to the at least one other node in the network environment.

21. A non-transitory computer-readable media storing computer instructions that, when executed by one or more processors of a transmitting node, cause the transmitting node to: receive, from at least one other node in a network environment, a plurality of segment identifiers, utilizing at least one of a link state protocol, a distance vector protocol, or a path vector protocol; store, in a data structure, the plurality of segment identifiers associated with nodes represented in a topology of at least a

portion of the network environment; select, from the plurality of segment identifiers in the data structure and based on a specified policy, a first sequence of segment identifiers that identify a first sequence of at least one of: one or more nodes, one or more network interfaces, or one or more network regions, at least partially in a first path segment that communicatively couples the transmitting node with a receiving node in the network environment and that includes at least one particular node which is not predetermined by the first sequence of segment identifiers such that the at least one particular node is determined during routing of data between the transmitting node and the receiving node; identify, based on a segment identifier in a first subsequence, of the first sequence of segment identifiers, that precedes a second subsequence of the first sequence of segment identifiers, a first network interface of the transmitting node in the first path segment; store at least the second subsequence of the first sequence of segment identifiers in a header associated with a first packet; and transmit, via the first network interface, the first packet for delivering the data in a payload of the first packet to the receiving node in the network environment.

22. The non-transitory computer-readable media of claim 21, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that the first sequence of segment identifiers includes a first node scoped network interface identifier that is selected based on a representation of a link from a first node to a second node in the first path segment that communicatively couples the transmitting node with the receiving node in the network environment.

23. The non-transitory computer-readable media of claim 22, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that the first node scoped network interface identifier is in a first node scoped identifier space that spans within the first node and identifies, for the first node, a particular network interface of the first node in the link.

24. The non-transitory computer-readable media of claim 23, further including instructions that, when executed by the one or more processors, cause the transmitting node to: receive an indication that the link has failed, utilizing the at least one of the link state protocol, the distance vector protocol, or the path vector protocol; and update a data structure in response to the receipt of the indication.

25. The non-transitory computer-readable media of claim 24, further including instructions that, when executed by the one or more processors, cause the transmitting node to: determine, based on the updated data structure, a second sequence of segment identifiers that identify a second sequence of at least one of: one or more nodes, one or more network interfaces, or one or more network regions, at least partially in a second path segment that communicatively couples the transmitting node with the receiving node in the network environment, where the second sequence of segment identifiers does not include the first node scoped network interface identifier; store at least an end portion of the second sequence of segment identifiers in a header associated with a second packet; identify, based on a segment identifier that precedes the end portion of the second sequence of segment identifiers, a second network interface of the transmitting node in the second path segment; and transmit, via the second network interface, the second packet for delivering data in a payload of the second packet to the receiving node in the network environment.

26. The non-transitory computer-readable media of claim 25, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that the second network interface is not the first network interface.

27. The non-transitory computer-readable media of claim 25, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that the second sequence of segment identifiers is identical to the first sequence of segment identifiers.

28. The non-transitory computer-readable media of claim 25, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that the determining the second sequence of segment identifiers comprises: identifying, based on the

updated data structure, a path segment identifier that is not included in the first sequence of segment identifiers and that identifies at least one of: a network interface, a node, or a region that, without utilizing the failed link, communicatively couples the first node with a path node in a portion of the first path segment that communicatively couples the first node to the receiving node; and including the path segment identifier in the second sequence of segment identifiers in a location that follows a segment identifier that identifies the first node.

29. The non-transitory computer-readable media of claim 28, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that the path segment identifier identifies, for at least the first node, the second node that is communicatively coupled to the first node via a particular path segment that is selectable based on the path segment identifier.

30. The non-transitory computer-readable media of claim 29, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that the path segment identifier includes another node scoped identifier, in the first node scoped identifier space, that identifies another network interface in another link that includes the second node.

31. The non-transitory computer-readable media of claim 29, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that the path segment communicatively couples the first node with the second node, and is selectable, based on the path segment identifier, from a routing table of the first node.

32. The non-transitory computer-readable media of claim 31, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that the path segment communicatively couples the first node with the second node, and is selectable from a plurality of path segments that communicatively couple the first node with the second node.

33. The non-transitory computer-readable media of claim 32, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that the plurality of path segments includes at least one multi-hop path segment.

34. The non-transitory computer-readable media of claim 29, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that both the first node and the second node are in a particular region of the network environment that is within a span of a particular identifier space that includes particular identifiers that identify at least a portion of particular nodes in the particular region.

35. The non-transitory computer-readable media of claim 29, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that the first node is in a particular region of the network environment that is within a span of a particular identifier space that includes particular identifiers that identify at least a portion of particular nodes in the particular region, where the second node is not in the particular region.

36. The non-transitory computer-readable media of claim 29, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that both the first node and the second node are in a domain of at least one of: a link state protocol, a distance vector protocol, or a path vector protocol utilized for communicating at least some segment identifiers of nodes or network interfaces within the domain.

37. The non-transitory computer-readable media of claim 29, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that the first node is in a domain where at least one of: a link state protocol, a distance vector protocol, or a path vector protocol utilized for communicating at least some identifiers of nodes or network interfaces within the domain and the second node is not in the domain.

38. The non-transitory computer-readable media of claim 28, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that the path segment identifier identifies, for at least the first node, a third node that follows the second node in the first path segment and that is communicatively coupled to the first node via a particular

path segment that is selectable based on the path segment identifier.

39. The non-transitory computer-readable media of claim 38, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that the path segment identifier includes another node scoped identifier, in the first node scoped identifier space, that identifies another network interface in another link that includes the third node.

40. The non-transitory computer-readable media of claim 22, further including instructions that, when executed by the one or more processors, cause the transmitting node to operate such that the at least one of the link state protocol, the distance vector protocol, or the path vector protocol is utilized to receive, from the at least one other node in the network environment, particular data that associates the first node scoped network interface identifier and the link, wherein the particular data is based on data transmitted by the first node to the at least one other node in the network environment.
