

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407756
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Beckhardt; Steven

Mirrored queues

Abstract

Embodiments disclosed herein involve a first playback device, associated with a first household, where the first playback device is configured to mirror a playback queue that is associated with a second playback device, where the second playback device is associated with a second household. For instance, a device associated with the first household, such as a controller, may send a command to the first playback device to mirror the playback queue associated with the second playback device. Based on the received command, the first playback device may mirror the playback queue that is associated with the second playback device such that contents of a playback queue that is associated with the first playback device are the same as contents of the playback queue that is associated with the second playback device.

Inventors:	Beckhardt; Steven (Boston, MA)
Applicant:	Sonos, Inc. (Santa Barbara, CA)
Family ID:	54190698
Assignee:	Sonos, Inc. (Goleta, CA)
Appl. No.:	18/520507
Filed:	November 27, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240171636 A1	May. 23, 2024

Related U.S. Application Data

continuation parent-doc US 17896385 20220826 US 11831721 child-doc US 18520507
continuation parent-doc US 16813223 20200309 US 11431804 20220830 child-doc US 17896385
continuation parent-doc US 14231911 20140401 US 10587693 20200310 child-doc US 16813223

Publication Classification

Int. Cl.: H04L67/125 (20220101); G06F16/438 (20190101); G06F16/68 (20190101);
G06Q50/00 (20240101)

U.S. Cl.:

CPC H04L67/125 (20130101); G06F16/4387 (20190101); G06F16/686 (20190101);
G06Q50/01 (20130101); H04R2227/003 (20130101); H04R2227/005 (20130101)

Field of Classification Search

CPC: G06F (16/4387); G06F (16/686); G06Q (50/01); H04L (67/125); H04R (2227/003);
H04R (2227/005)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4296278	12/1980	Cullison et al.	N/A	N/A
4816989	12/1988	Finn et al.	N/A	N/A
5182552	12/1992	Paynting	N/A	N/A
5239458	12/1992	Suzuki	N/A	N/A
5299266	12/1993	Lumsden	N/A	N/A
5406634	12/1994	Anderson et al.	N/A	N/A
5440644	12/1994	Farinelli et al.	N/A	N/A
5467342	12/1994	Logston et al.	N/A	N/A
5491839	12/1995	Schotz	N/A	N/A
5553222	12/1995	Milne et al.	N/A	N/A
5668884	12/1996	Clair, Jr. et al.	N/A	N/A
5673323	12/1996	Schotz et al.	N/A	N/A
5751819	12/1997	Dorrough	N/A	N/A
5761320	12/1997	Farinelli et al.	N/A	N/A
5808662	12/1997	Kinney et al.	N/A	N/A
5815689	12/1997	Shaw et al.	N/A	N/A
5856827	12/1998	Sudo	N/A	N/A
5867691	12/1998	Shiraishi	N/A	N/A
5875354	12/1998	Charlton et al.	N/A	N/A
5887143	12/1998	Saito et al.	N/A	N/A
5923902	12/1998	Inagaki	N/A	N/A
5946343	12/1998	Schotz et al.	N/A	N/A
5956088	12/1998	Shen et al.	N/A	N/A
6002862	12/1998	Takaike	N/A	N/A
6009457	12/1998	Moller	N/A	N/A
6026150	12/1999	Frank et al.	N/A	N/A
6031818	12/1999	Lo et al.	N/A	N/A
6032202	12/1999	Lea et al.	N/A	N/A
6108686	12/1999	Williams, Jr.	N/A	N/A
6128318	12/1999	Sato	N/A	N/A

6157957	12/1999	Berthaud	N/A	N/A
6175872	12/2000	Neumann et al.	N/A	N/A
6181316	12/2000	Little et al.	N/A	N/A
6185737	12/2000	Northcutt et al.	N/A	N/A
6195436	12/2000	Scibora et al.	N/A	N/A
6199169	12/2000	Voth	N/A	N/A
6226672	12/2000	Demartin et al.	N/A	N/A
6255961	12/2000	Van et al.	N/A	N/A
6256554	12/2000	DiLorenzo	N/A	N/A
6308207	12/2000	Tseng et al.	N/A	N/A
6324586	12/2000	Johnson	N/A	N/A
6332147	12/2000	Moran et al.	N/A	N/A
6349339	12/2001	Williams	N/A	N/A
6351821	12/2001	Voth	N/A	N/A
6404811	12/2001	Cvetko et al.	N/A	N/A
6430353	12/2001	Honda et al.	N/A	N/A
6469633	12/2001	Wachter	N/A	N/A
6487296	12/2001	Allen et al.	N/A	N/A
6522886	12/2002	Youngs et al.	N/A	N/A
6526325	12/2002	Sussman et al.	N/A	N/A
6587127	12/2002	Leeke et al.	N/A	N/A
6598172	12/2002	Vandeusen et al.	N/A	N/A
6611537	12/2002	Edens et al.	N/A	N/A
6631410	12/2002	Kowalski et al.	N/A	N/A
6674803	12/2003	Kesselring	N/A	N/A
6728531	12/2003	Lee et al.	N/A	N/A
6732155	12/2003	Meek	N/A	N/A
6757517	12/2003	Chang	N/A	N/A
6778869	12/2003	Champion	N/A	N/A
6826283	12/2003	Wheeler et al.	N/A	N/A
6836788	12/2003	Kim et al.	N/A	N/A
6898642	12/2004	Chafle et al.	N/A	N/A
6912610	12/2004	Spencer	N/A	N/A
6920373	12/2004	Xi et al.	N/A	N/A
6934766	12/2004	Russell	N/A	N/A
6985694	12/2005	De Bonet et al.	N/A	N/A
7007106	12/2005	Flood et al.	N/A	N/A
7017118	12/2005	Carroll	N/A	N/A
7020048	12/2005	McComas	N/A	N/A
7020791	12/2005	Aweya et al.	N/A	N/A
7043651	12/2005	Aweya et al.	N/A	N/A
7047308	12/2005	Deshpande	N/A	N/A
7113833	12/2005	Brown et al.	N/A	N/A
7113999	12/2005	Pestoni et al.	N/A	N/A
7115017	12/2005	Laursen et al.	N/A	N/A
7117451	12/2005	Sielken	N/A	N/A
7130608	12/2005	Hollstrom et al.	N/A	N/A
7130616	12/2005	Janik	N/A	N/A
7143141	12/2005	Morgan et al.	N/A	N/A
7143939	12/2005	Henzerling	N/A	N/A

7162315	12/2006	Gilbert	N/A	N/A
7185090	12/2006	Kowalski et al.	N/A	N/A
7187947	12/2006	White et al.	N/A	N/A
7206367	12/2006	Moore	N/A	N/A
7209795	12/2006	Sullivan et al.	N/A	N/A
7218708	12/2006	Berezowski et al.	N/A	N/A
7236739	12/2006	Chang	N/A	N/A
7236773	12/2006	Thomas	N/A	N/A
7293060	12/2006	Komsi	N/A	N/A
7295548	12/2006	Blank et al.	N/A	N/A
7312785	12/2006	Tsuk et al.	N/A	N/A
7324857	12/2007	Goddard	N/A	N/A
7333519	12/2007	Sullivan et al.	N/A	N/A
7358960	12/2007	Mak	N/A	N/A
7372846	12/2007	Zwack	N/A	N/A
7392102	12/2007	Sullivan et al.	N/A	N/A
7483538	12/2008	McCarty et al.	N/A	N/A
7483958	12/2008	Elabbady et al.	N/A	N/A
7555291	12/2008	Wassingbo et al.	N/A	N/A
7571014	12/2008	Lambourne et al.	N/A	N/A
7574274	12/2008	Holmes	N/A	N/A
7599685	12/2008	Goldberg et al.	N/A	N/A
7603385	12/2008	Panabaker	709/248	H04L 67/125
7617278	12/2008	Edelman et al.	N/A	N/A
7630501	12/2008	Blank et al.	N/A	N/A
7634068	12/2008	Flammer	N/A	N/A
7643894	12/2009	Braithwaite et al.	N/A	N/A
7657224	12/2009	Goldberg et al.	N/A	N/A
7657644	12/2009	Zheng	N/A	N/A
7657910	12/2009	McAulay et al.	N/A	N/A
7668990	12/2009	Krzyzanowski et al.	N/A	N/A
7669219	12/2009	Scott et al.	N/A	N/A
7675943	12/2009	Mosig et al.	N/A	N/A
7676142	12/2009	Hung	N/A	N/A
7702279	12/2009	Ko et al.	N/A	N/A
7720096	12/2009	Klemets	N/A	N/A
7742740	12/2009	Goldberg et al.	N/A	N/A
7805682	12/2009	Lambourne	N/A	N/A
7827259	12/2009	Heller et al.	N/A	N/A
7835689	12/2009	Goldberg et al.	N/A	N/A
7853341	12/2009	McCarty et al.	N/A	N/A
7865137	12/2010	Goldberg et al.	N/A	N/A
7885622	12/2010	Krampf et al.	N/A	N/A
7890661	12/2010	Spurgat et al.	N/A	N/A
7916877	12/2010	Goldberg et al.	N/A	N/A
7917082	12/2010	Goldberg et al.	N/A	N/A
7934239	12/2010	Dagman	N/A	N/A
7937422	12/2010	Ferguson, Jr.	N/A	N/A
7958441	12/2010	Heller et al.	N/A	N/A
7987294	12/2010	Bryce et al.	N/A	N/A

8014423	12/2010	Thaler et al.	N/A	N/A
8023663	12/2010	Goldberg	N/A	N/A
8028038	12/2010	Weel	N/A	N/A
8028323	12/2010	Weel	N/A	N/A
8045952	12/2010	Qureshey et al.	N/A	N/A
8050652	12/2010	Qureshey et al.	N/A	N/A
8065708	12/2010	Smyth et al.	N/A	N/A
8074253	12/2010	Nathan	N/A	N/A
8086752	12/2010	Millington et al.	N/A	N/A
8103009	12/2011	McCarty et al.	N/A	N/A
8112032	12/2011	Ko et al.	N/A	N/A
8131390	12/2011	Braithwaite et al.	N/A	N/A
8169938	12/2011	Duchscher et al.	N/A	N/A
8214431	12/2011	Miyajima et al.	N/A	N/A
8214873	12/2011	Weel	N/A	N/A
8230099	12/2011	Weel	N/A	N/A
8234395	12/2011	Millington	N/A	N/A
8290603	12/2011	Lambourne	N/A	N/A
8315555	12/2011	Ko et al.	N/A	N/A
8370678	12/2012	Millington et al.	N/A	N/A
8423659	12/2012	Millington	N/A	N/A
8443038	12/2012	Robbin et al.	N/A	N/A
8483853	12/2012	Lambourne	N/A	N/A
8484089	12/2012	Lin et al.	N/A	N/A
8588949	12/2012	Lambourne et al.	N/A	N/A
8752769	12/2013	Biderman	N/A	N/A
8775546	12/2013	Millington	N/A	N/A
8818538	12/2013	Sakata	N/A	N/A
9003462	12/2014	Walker et al.	N/A	N/A
9137564	12/2014	Reimann	N/A	N/A
9247363	12/2015	Triplett et al.	N/A	N/A
9411942	12/2015	Commons et al.	N/A	N/A
9524487	12/2015	Yagnik et al.	N/A	N/A
9674587	12/2016	Triplett et al.	N/A	N/A
10268352	12/2018	Coburn, IV et al.	N/A	N/A
2001/0009604	12/2000	Ando et al.	N/A	N/A
2001/0022823	12/2000	Renaud	N/A	N/A
2001/0032188	12/2000	Miyabe et al.	N/A	N/A
2001/0042107	12/2000	Palm	N/A	N/A
2002/0002039	12/2001	Qureshey et al.	N/A	N/A
2002/0002562	12/2001	Moran et al.	N/A	N/A
2002/0003548	12/2001	Krusche et al.	N/A	N/A
2002/0022453	12/2001	Balog et al.	N/A	N/A
2002/0026442	12/2001	Lipscomb et al.	N/A	N/A
2002/0034374	12/2001	Barton	N/A	N/A
2002/0042844	12/2001	Chiazzese	N/A	N/A
2002/0049843	12/2001	Barone et al.	N/A	N/A
2002/0065926	12/2001	Hackney et al.	N/A	N/A
2002/0072816	12/2001	Shdema et al.	N/A	N/A
2002/0073228	12/2001	Cognet et al.	N/A	N/A

2002/0090914	12/2001	Kang et al.	N/A	N/A
2002/0093478	12/2001	Yeh	N/A	N/A
2002/0109710	12/2001	Holtz et al.	N/A	N/A
2002/0112244	12/2001	Liou et al.	N/A	N/A
2002/0124097	12/2001	Isely et al.	N/A	N/A
2002/0129156	12/2001	Yoshikawa	N/A	N/A
2002/0143998	12/2001	Rajagopal et al.	N/A	N/A
2002/0163361	12/2001	Parkin	N/A	N/A
2002/0165921	12/2001	Sapieyevski	N/A	N/A
2002/0178191	12/2001	Sielken	N/A	N/A
2002/0188762	12/2001	Tomassetti et al.	N/A	N/A
2003/0002609	12/2002	Faller et al.	N/A	N/A
2003/0020763	12/2002	Mayer et al.	N/A	N/A
2003/0023741	12/2002	Tomassetti et al.	N/A	N/A
2003/0035444	12/2002	Zwack	N/A	N/A
2003/0041173	12/2002	Hoyle	N/A	N/A
2003/0041174	12/2002	Wen et al.	N/A	N/A
2003/0043924	12/2002	Haddad et al.	N/A	N/A
2003/0066094	12/2002	Van Der Schaar et al.	N/A	N/A
2003/0099212	12/2002	Anjum et al.	N/A	N/A
2003/0099221	12/2002	Rhee	N/A	N/A
2003/0126211	12/2002	Anttila et al.	N/A	N/A
2003/0157951	12/2002	Hasty, Jr.	N/A	N/A
2003/0195964	12/2002	Mane	N/A	N/A
2003/0198257	12/2002	Sullivan et al.	N/A	N/A
2003/0210796	12/2002	McCarty et al.	N/A	N/A
2003/0231871	12/2002	Ushimaru	N/A	N/A
2003/0235304	12/2002	Evans et al.	N/A	N/A
2004/0001484	12/2003	Ozguner	N/A	N/A
2004/0001591	12/2003	Mani et al.	N/A	N/A
2004/0008852	12/2003	Also et al.	N/A	N/A
2004/0010727	12/2003	Fujinami	N/A	N/A
2004/0015252	12/2003	Aiso et al.	N/A	N/A
2004/0024478	12/2003	Hans et al.	N/A	N/A
2004/0024925	12/2003	Cypher et al.	N/A	N/A
2004/0025185	12/2003	Goci et al.	N/A	N/A
2004/0027166	12/2003	Mangum et al.	N/A	N/A
2004/0032348	12/2003	Lai et al.	N/A	N/A
2004/0066736	12/2003	Kroeger	N/A	N/A
2004/0075767	12/2003	Neuman et al.	N/A	N/A
2004/0078383	12/2003	Mercer et al.	N/A	N/A
2004/0078812	12/2003	Calvert	N/A	N/A
2004/0131192	12/2003	Metcalf	N/A	N/A
2004/0170383	12/2003	Mazur	N/A	N/A
2004/0203378	12/2003	Powers	N/A	N/A
2004/0215611	12/2003	Jawa et al.	N/A	N/A
2004/0249965	12/2003	Huggins et al.	N/A	N/A
2004/0249982	12/2003	Arnold et al.	N/A	N/A
2004/0252400	12/2003	Blank et al.	N/A	N/A

2004/0261040	12/2003	Radcliffe et al.	N/A	N/A
2005/0010691	12/2004	Oyadomari et al.	N/A	N/A
2005/0013394	12/2004	Rausch et al.	N/A	N/A
2005/0021590	12/2004	Debique et al.	N/A	N/A
2005/0047605	12/2004	Lee et al.	N/A	N/A
2005/0058149	12/2004	Howe	N/A	N/A
2005/0081213	12/2004	Suzuoki et al.	N/A	N/A
2005/0108320	12/2004	Lord et al.	N/A	N/A
2005/0114538	12/2004	Rose	N/A	N/A
2005/0125357	12/2004	Saadat et al.	N/A	N/A
2005/0166157	12/2004	Ollis et al.	N/A	N/A
2005/0177643	12/2004	Xu	N/A	N/A
2005/0181348	12/2004	Carey et al.	N/A	N/A
2005/0195205	12/2004	Abrams, Jr.	N/A	N/A
2005/0281255	12/2004	Davies et al.	N/A	N/A
2005/0283820	12/2004	Richards et al.	N/A	N/A
2005/0288805	12/2004	Moore et al.	N/A	N/A
2005/0289224	12/2004	Deslippe et al.	N/A	N/A
2006/0095516	12/2005	Wijeratne	N/A	N/A
2006/0107237	12/2005	Kim	N/A	N/A
2006/0119497	12/2005	Miller et al.	N/A	N/A
2006/0143236	12/2005	Wu	N/A	N/A
2006/0168340	12/2005	Heller et al.	N/A	N/A
2006/0253782	12/2005	Stark et al.	N/A	N/A
2006/0277216	12/2005	Shukhman	N/A	N/A
2007/0038999	12/2006	Millington	N/A	N/A
2007/0048713	12/2006	Plastina et al.	N/A	N/A
2007/0054680	12/2006	Mo et al.	N/A	N/A
2007/0142022	12/2006	Madonna et al.	N/A	N/A
2007/0142944	12/2006	Goldberg et al.	N/A	N/A
2007/0143493	12/2006	Mullig et al.	N/A	N/A
2007/0169115	12/2006	Ko et al.	N/A	N/A
2007/0180137	12/2006	Rajapakse	N/A	N/A
2007/0255752	12/2006	Miller	N/A	N/A
2007/0271388	12/2006	Bowra et al.	N/A	N/A
2007/0288470	12/2006	Kauniskangas et al.	N/A	N/A
2007/0299778	12/2006	Haveson et al.	N/A	N/A
2008/0005690	12/2007	Van Vugt	N/A	N/A
2008/0016465	12/2007	Foxenland	N/A	N/A
2008/0022320	12/2007	Ver Steeg	N/A	N/A
2008/0091771	12/2007	Allen et al.	N/A	N/A
2008/0120429	12/2007	Millington et al.	N/A	N/A
2008/0144861	12/2007	Melanson et al.	N/A	N/A
2008/0168185	12/2007	Robbin et al.	N/A	N/A
2008/0168391	12/2007	Robbin et al.	N/A	N/A
2008/0168526	12/2007	Robbin et al.	N/A	N/A
2009/0006479	12/2008	Fujita et al.	N/A	N/A
2009/0031336	12/2008	Chavez et al.	N/A	N/A
2009/0157905	12/2008	Davis	N/A	N/A
2009/0222115	12/2008	Malcolm et al.	N/A	N/A

2009/0222392	12/2008	Martin et al.	N/A	N/A
2009/0228919	12/2008	Zott et al.	N/A	N/A
2010/0017474	12/2009	Kandekar et al.	N/A	N/A
2010/0049835	12/2009	Ko et al.	N/A	N/A
2010/0082731	12/2009	Haughay et al.	N/A	N/A
2010/0131567	12/2009	Dorogusker et al.	N/A	N/A
2010/0228740	12/2009	Cannistraro et al.	N/A	N/A
2010/0257203	12/2009	Sun	N/A	N/A
2010/0284389	12/2009	Ramsay et al.	N/A	N/A
2011/0066943	12/2010	Brillon et al.	N/A	N/A
2011/0067099	12/2010	Barton et al.	N/A	N/A
2011/0135283	12/2010	Poniatowski et al.	N/A	N/A
2011/0218656	12/2010	Bishop et al.	N/A	N/A
2011/0246689	12/2010	Naito et al.	N/A	N/A
2011/0252118	12/2010	Pantos	709/219	G06F 3/0484
2011/0264732	12/2010	Robbin et al.	N/A	N/A
2012/0029671	12/2011	Millington et al.	N/A	N/A
2012/0030366	12/2011	Collart et al.	N/A	N/A
2012/0060046	12/2011	Millington	N/A	N/A
2012/0088477	12/2011	Cassidy	N/A	N/A
2012/0117026	12/2011	Cassidy	N/A	N/A
2012/0129446	12/2011	Ko et al.	N/A	N/A
2012/0158531	12/2011	Dion et al.	N/A	N/A
2012/0190406	12/2011	Chen	N/A	N/A
2012/0191816	12/2011	Beckhardt et al.	N/A	N/A
2012/0215684	12/2011	Kidron	N/A	N/A
2013/0024880	12/2012	Moloney-Egnatios et al.	N/A	N/A
2013/0031216	12/2012	Willis et al.	N/A	N/A
2013/0073613	12/2012	Ferguson, Jr.	N/A	N/A
2013/0080599	12/2012	Ko et al.	N/A	N/A
2013/0080658	12/2012	Ferguson, Jr.	N/A	N/A
2013/0159858	12/2012	Joffray et al.	N/A	N/A
2013/0191454	12/2012	Oliver et al.	N/A	N/A
2013/0228063	12/2012	Turner	N/A	N/A
2013/0339397	12/2012	Herasymchuk	N/A	N/A
2014/0052823	12/2013	Gavade et al.	N/A	N/A
2014/0140674	12/2013	Jallad et al.	N/A	N/A
2014/0204076	12/2013	Kuper et al.	N/A	N/A
2014/0223099	12/2013	Kidron	N/A	N/A
2014/0358951	12/2013	Luna et al.	N/A	N/A
2015/0025661	12/2014	Vega-Zayas et al.	N/A	N/A
2015/0063774	12/2014	Brown, Jr. et al.	N/A	N/A
2015/0067871	12/2014	Commons et al.	N/A	N/A
2015/0074059	12/2014	Bilinski et al.	N/A	N/A
2015/0193069	12/2014	Di Censo	345/173	H04N 21/42202
2015/0220498	12/2014	Munoz et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
0251584	12/1987	EP	N/A
0672985	12/1994	EP	N/A
1111527	12/2000	EP	N/A
1389853	12/2003	EP	N/A
199525313	12/1994	WO	N/A
199961985	12/1998	WO	N/A
200147248	12/2000	WO	N/A
200153994	12/2000	WO	N/A
2003093950	12/2002	WO	N/A
2005013047	12/2004	WO	N/A

OTHER PUBLICATIONS

Advisory Action mailed on Dec. 5, 2016, issued in connection with U.S. Appl. No. 14/231,911, filed Apr. 1, 2014, 3 pages. cited by applicant

Advisory Action mailed on Dec. 1, 2017, issued in connection with U.S. Appl. No. 14/231,911, filed Apr. 1, 2014, 5 pages. cited by applicant

Advisory Action mailed on Sep. 5, 2018, issued in connection with U.S. Appl. No. 14/231,911, filed Apr. 1, 2014, 3 pages. cited by applicant

Akyildiz et al., "Multimedia Group Synchronization Protocols for Integrated Services Networks," IEEE Journal on Selected Areas in Communications, 1996 pp. 162-173, vol. 14, No. 1. cited by applicant

AudioTron Quick Start Guide, Version 1.0, Mar. 2001, 24 pages. cited by applicant

AudioTron Reference Manual, Version 3.0, May 2002, 70 pages. cited by applicant

AudioTron Setup Guide, Version 3.0, May 2002, 38 pages. cited by applicant

Benslimane Abderrahim, "A Multimedia Synchronization Protocol for Multicast Groups,"

Proceedings of the 26th Euromicro Conference, 2000, pp. 456-463, vol. 1. cited by applicant

Biersack et al., "Intra- and Inter-Stream Synchronization for Stored Multimedia Streams," IEEE International Conference on Multimedia Computing and Systems, 1996, pp. 372-381. cited by applicant

Bluetooth. "Specification of the Bluetooth System: The ad hoc Scatternet for affordable and highly functional wireless connectivity," Core, Version 1.0 A, Jul. 26, 1999, 1068 pages. cited by applicant

Bluetooth. "Specification of the Bluetooth System: Wireless connections made easy," Core, Version 1.0 B, Dec. 1, 1999, 1076 pages. cited by applicant

Bretl W.E., et al., MPEG2 Tutorial [online], 2000 [retrieved on Jan. 13, 2009] Retrieved from the Internet:(<http://www.bretl.com/mpeghtml/MPEGindex.htm>), pp. 1-23. cited by applicant

Dell, Inc. "Dell Digital Audio Receiver: Reference Guide," Jun. 2000, 70 pages. cited by applicant

Dell, Inc. "Start Here," Jun. 2000, 2 pages. cited by applicant

"Denon 2003-2004 Product Catalog," Denon, 2003-2004, 44 pages. cited by applicant

Final Office Action mailed on Feb. 11, 2022, issued in connection with U.S. Appl. No. 16/813,223, filed Mar. 9, 2020, 7 pages. cited by applicant

Final Office Action mailed on Jul. 26, 2017, issued in connection with U.S. Appl. No. 14/231,911, filed Apr. 1, 2014, 53 pages. cited by applicant

Final Office Action mailed on Jun. 27, 2018, issued in connection with U.S. Appl. No. 14/231,911, filed Apr. 1, 2014, 55 pages. cited by applicant

Final Office Action mailed on Sep. 28, 2016, issued in connection with U.S. Appl. No. 14/231,911, filed Apr. 1, 2014, 24 pages. cited by applicant

First Action Interview Office Action Summary mailed on Apr. 18, 2016, issued in connection with U.S. Appl. No. 14/231,911, filed Apr. 1, 2014, 12 pages. cited by applicant

Huang C.M., et al., "A Synchronization Infrastructure for Multicast Multimedia at the Presentation Layer," IEEE Transactions on Consumer Electronics, 1997, pp. 370-380, vol. 43, No. 3. cited by applicant

Ishibashi et al., "A Group Synchronization Mechanism for Live Media in Multicast Communications," IEEE Global Telecommunications Conference, 1997, pp. 746-752, vol. 2. cited by applicant

Ishibashi et al., "A Group Synchronization Mechanism for Stored Media in Multicast Communications," IEEE Information Revolution and Communications, 1997, pp. 692-700, vol. 2. cited by applicant

Jo et al., "Synchronized One-to-many Media Streaming with Adaptive Playout Control," Proceedings of SPIE, 2002, pp. 71-82, vol. 4861. cited by applicant

Jones, Stephen, "Dell Digital Audio Receiver: Digital upgrade for your analog stereo," Analog Stereo, Jun. 24, 2000 <http://www.reviewsonline.com/articles/961906864.htm> retrieved Jun. 18, 2014, 2 pages. cited by applicant

Louderback, Jim, "Affordable Audio Receiver Furnishes Homes With MP3," TechTV Vault. Jun. 28, 2000 retrieved Jul. 10, 2014, 2 pages. cited by applicant

Mills David L., "Network Time Protocol (Version 3) Specification, Implementation and Analysis," Network Working Group, Mar. 1992, 7 pages. cited by applicant

Mills, David L., "Precision Synchronization of Computer Network Clocks," ACM SIGCOMM Computer Communication Review, 1994, pp. 28-43, vol. 24, No. 2. cited by applicant

Motorola, "Simplefi, Wireless Digital Audio Receiver, Installation and User Guide," Dec. 31, 2001, 111 pages. cited by applicant

Nilsson, M., "ID3 Tag Version 2," Mar. 26, 1998, 28 pages. cited by applicant

Non-Final Office Action mailed on Jan. 3, 2017, issued in connection with U.S. Appl. No. 14/231,911, filed Apr. 1, 2014, 39 pages. cited by applicant

Non-Final Office Action mailed on Jan. 11, 2018, issued in connection with U.S. Appl. No. 14/231,911, filed Apr. 1, 2014, 48 pages. cited by applicant

Non-Final Office Action mailed on Apr. 12, 2023, issued in connection with U.S. Appl. No. 17/896,385, filed Aug. 26, 2022, 6 pages. cited by applicant

Non-Final Office Action mailed on Aug. 25, 2021, issued in connection with U.S. Appl. No. 16/813,223, filed Mar. 9, 2020, 13 pages. cited by applicant

Non-Final Office Action mailed on Nov. 30, 2018, issued in connection with U.S. Appl. No. 14/231,911, filed Apr. 1, 2014, 64 pages. cited by applicant

North American MPEG-2 Information, "The MPEG-2 Transport Stream," Retrieved from the Internet: URL: <http://www.coolstf.com/mpeg/#ts>, 2006, pp. 1-5. cited by applicant

Notice of Allowance mailed on Jul. 15, 2019, issued in connection with U.S. Appl. No. 14/231,911, filed Apr. 1, 2014, 20 pages. cited by applicant

Notice of Allowance mailed on Apr. 21, 2022, issued in connection with U.S. Appl. No. 16/813,223, filed Mar. 9, 2020, 7 pages. cited by applicant

Notice of Allowance mailed on Oct. 23, 2019, issued in connection with U.S. Appl. No. 14/231,911, filed Apr. 1, 2014, 7 pages. cited by applicant

Notice of Allowance mailed on Jul. 26, 2023, issued in connection with U.S. Appl. No. 17/896,385, filed Aug. 26, 2022, 7 pages. cited by applicant

Palm, Inc., "Handbook for the Palm VII Handheld," May 2000, 311 pages. cited by applicant

Park et al., "Group Synchronization in MultiCast Media Communications," Proceedings of the 5th Research on Multicast Technology Workshop, 2003, 5 pages. cited by applicant

Polycom Conference Composer User Guide, copyright 2001, 29 pages. cited by applicant

Preinterview Office Action mailed on Feb. 29, 2016, issued in connection with U.S. Appl. No. 14/231,911, filed Apr. 1, 2014, 10 pages. cited by applicant

Presentations at WinHEC 2000, May 2000, 138 pages. cited by applicant

Prismiq, Inc., "Prismiq Media Player User Guide," 2003, 44 pages. cited by applicant
Reisinger, Don, "Make Your House Rock from Any Room," PCWorld, Jul. 19, 2011, pp. 1-4. cited by applicant
Rothermel et al., "An Adaptive Stream Synchronization Protocol," 5th International Workshop on Network and Operating System Support for Digital Audio and Video, 1995, 13 pages. cited by applicant
Schulzrinne H., et al., "RTP: A Transport Protocol for Real-Time Applications, RFC 3550," Network Working Group, 2003, pp. 1-89. cited by applicant
United States Patent and Trademark Office, U.S. Appl. No. 60/490,768, filed Jul. 28, 2003, entitled "Method for synchronizing audio playback between multiple networked devices," 13 pages. cited by applicant
United States Patent and Trademark Office, U.S. Appl. No. 60/825,407, filed Sep. 12, 2006, entitled "Controlling and manipulating groupings in a multi-zone music or media system," 82 pages. cited by applicant
UPnP; "Universal Plug and Play Device Architecture," Jun. 8, 2000; version 1.0; Microsoft Corporation; pp. 1-54. cited by applicant
Yamaha DME 32 manual; copyright 2001. cited by applicant
Yamaha DME 64 Owner's Manual; copyright 2004, 80 pages. cited by applicant
Yamaha DME Designer 3.5 setup manual guide; copyright 2004, 16 pages. cited by applicant
Yamaha DME Designer 3.5 User Manual; Copyright 2004, 507 pages. cited by applicant

Primary Examiner: Spieler; William

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of and claims priority to U.S. patent application Ser. No. 17/896,385, filed on Aug. 26, 2022, which is a continuation of and claims priority to U.S. patent application Ser. No. 16/813,223, filed on Mar. 9, 2020, and issued as U.S. Pat. No. 11,431,804, which is a continuation of and claims priority to U.S. patent application Ser. No. 14/231,911, filed on Apr. 1, 2014, and issued as U.S. Pat. No. 10,587,693, each of which is hereby incorporated by reference in its entirety for all purposes.

FIELD OF THE DISCLOSURE

(1) The disclosure is related to consumer goods and, more particularly, to methods, systems, products, features, services, and other elements directed to media playback or some aspect thereof.

BACKGROUND

(2) Options for accessing and listening to digital audio in an out-loud setting were limited until in 2003, when SONOS, Inc. filed for one of its first patent applications, entitled "Method for Synchronizing Audio Playback between Multiple Networked Devices," and began offering a media playback system for sale in 2005. The Sonos Wireless HiFi System enables people to experience music from many sources via one or more networked playback devices. Through a software control application installed on a smartphone, tablet, or computer, one can play what he or she wants in any room that has a networked playback device. Additionally, using the controller, for example, different songs can be streamed to each room with a playback device, rooms can be grouped together for synchronous playback, or the same song can be heard in all rooms synchronously.

(3) Given the ever growing interest in digital media, there continues to be a need to develop consumer-accessible technologies to further enhance the listening experience.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Features, aspects, and advantages of the presently disclosed technology may be better understood with regard to the following description, appended claims, and accompanying drawings where:
- (2) FIG. 1 shows an example media playback system configuration in which certain embodiments may be practiced;
- (3) FIG. 2 shows a functional block diagram of an example playback device;
- (4) FIG. 3 shows a functional block diagram of an example control device;
- (5) FIG. 4 shows an example controller interface;
- (6) FIG. 5 shows an example flow diagram for mirroring playback queues according to an example embodiment;
- (7) FIG. 6 shows an example household configuration for mirroring playback queues;
- (8) FIG. 7 shows a system including a cloud-based network and two local playback networks;
- (9) FIG. 8A shows two example user interfaces prior to mirroring;
- (10) FIG. 8B shows two example user interfaces after mirroring; and
- (11) FIG. 9 shows example communication across multiple households.
- (12) The drawings are for the purpose of illustrating example embodiments, but it is understood that the inventions are not limited to the arrangements and instrumentality shown in the drawings.

DETAILED DESCRIPTION

I. Overview

- (13) Embodiments disclosed herein provide a first media playback system that may “mirror” the playback queue of a second media playback system such that the playback queue of the first media playback system is the same as the playback queue of the second media playback system. Upon such mirroring of a playback queue, updates to the playback queue of the second media playback system may be reflected in the playback queue of the first media playback system. In this way, a user of the first playback system may, in some respects, turn control of his/her listening experience over to a user of the second playback system.
- (14) Handing over control of the listening experience may allow the user of the second playback system to act as a “remote DJ” by controlling the “mirrored” playback queue of the first media playback system from a remote location. And the user of the second playback system may also control multiple other playback systems, such that users from all across the world can “mirror” their respective playback queue and thereby hand over control of the “mirrored” queues to the “remote DJ”.
- (15) For example, a first media playback system (i.e., a first “household,” as described further below) may include at least a first playback device having a playback queue (i.e., a first playback queue). Further, a second media playback system (i.e. a second “household”) may include at least a second playback device having a playback queue (i.e. a second playback queue). The first playback device may mirror the second playback queue such that the contents (e.g. multimedia items) of the first playback queue match the contents of the first playback queue.
- (16) In one example, a device associated with the first household, such as a controller, may send a command to the first playback device to mirror the playback queue that is associated with the second playback device. Based on the received command, the first playback device may then mirror the playback queue that is associated with the second playback device.
- (17) Once the playback queue is mirrored, control of the mirrored playback queue of the first media playback system by devices associated with the first household may be limited in some respects. For example, the first playback device (as well as other devices associated with first household) may be unable to control playback of the mirrored playback queue. In this case, playback of the

mirrored playback queue may be carried out by one or more devices associated with the second household.

(18) As indicated above, the present application involves a first playback device, associated with a first household, which is configured to mirror a playback queue that is associated with a second playback device, where the second playback device is associated with a second household.

(19) In one aspect, a device is provided. The device includes a first playback device, where the first playback device includes a processor, a network interface, a non-transitory computer-readable storage medium, and program logic stored on the non-transitory computer-readable medium and executable by the processor to perform functions. The functions include receiving a command, the command indicating that the first playback device is to mirror a playback queue that is associated with a second playback device, where the first playback device is associated with a first household, and where the second playback device is associated with a second household. The functions also include, based on the command, mirroring the playback queue that is associated with the second playback device such that contents of a playback queue that is associated with the first playback device are the same as contents of the playback queue that is associated with the second playback device.

(20) In another aspect, a method is provided. The method involves receiving a command, at a first playback device that is associated with a first household, the command indicating that the first playback device is to mirror a playback queue that is associated with a second playback device, where the second playback device is associated with a second household. The method also involves, based on the command, mirroring the playback queue that is associated with the second playback device such that contents of a playback queue that is associated with the first playback device are the same as contents of the playback queue that is associated with the second playback device.

(21) In yet another aspect, a non-transitory computer readable memory is provided. The non-transitory computer readable memory has stored thereon instructions executable by a processor to cause the processor to perform functions. The functions include associating the first playback device with a first household. The functions also include receiving a command, the command indicating that the first playback device is to mirror a playback queue that is associated with a second playback device, where the second playback device is associated with a second household. The functions further include, based on the command, mirroring the playback queue that is associated with the second playback device such that contents of a playback queue that is associated with the first playback device are the same as contents of the playback queue that is associated with the second playback device.

(22) It will be understood by one of ordinary skill in the art that this disclosure includes numerous other embodiments.

II. Example Operating Environment

(23) FIG. 1 shows an example configuration of a media playback system **100** in which one or more embodiments disclosed herein may be practiced or implemented. The media playback system **100** as shown is associated with an example home environment having several rooms and spaces, such as for example, a master bedroom, an office, a dining room, and a living room. As shown in the example of FIG. 1, the media playback system **100** includes playback devices **102-124**, control devices **126** and **128**, and a wired or wireless network router **130**.

(24) Further discussions relating to the different components of the example media playback system **100** and how the different components may interact to provide a user with a media experience may be found in the following sections. While discussions herein may generally refer to the example media playback system **100**, technologies described herein are not limited to applications within, among other things, the home environment as shown in FIG. 1. For instance, the technologies described herein may be useful in environments where multi-zone audio may be desired, such as, for example, a commercial setting like a restaurant, mall or airport, a vehicle like a

sports utility vehicle (SUV), bus or car, a ship or boat, an airplane, and so on.

a. Example Playback Devices

(25) FIG. 2 shows a functional block diagram of an example playback device **200** that may be configured to be one or more of the playback devices **102-124** of the media playback system **100** of FIG. 1. The playback device **200** may include a processor **202**, software components **204**, memory **206**, audio processing components **208**, audio amplifier(s) **210**, speaker(s) **212**, and a network interface **214** including wireless interface(s) **216** and wired interface(s) **218**. In one case, the playback device **200** may not include the speaker(s) **212**, but rather a speaker interface for connecting the playback device **200** to external speakers. In another case, the playback device **200** may include neither the speaker(s) **212** nor the audio amplifier(s) **210**, but rather an audio interface for connecting the playback device **200** to an external audio amplifier or audio-visual receiver.

(26) In one example, the processor **202** may be a clock-driven computing component configured to process input data according to instructions stored in the memory **206**. The memory **206** may be a tangible computer-readable medium configured to store instructions executable by the processor **202**. For instance, the memory **206** may be data storage that can be loaded with one or more of the software components **204** executable by the processor **202** to achieve certain functions. In one example, the functions may involve the playback device **200** retrieving audio data from an audio source or another playback device. In another example, the functions may involve the playback device **200** sending audio data to another device or playback device on a network. In yet another example, the functions may involve pairing of the playback device **200** with one or more playback devices to create a multi-channel audio environment.

(27) Certain functions may involve the playback device **200** synchronizing playback of audio content with one or more other playback devices. During synchronous playback, a listener will preferably not be able to perceive time-delay differences between playback of the audio content by the playback device **200** and the one or more other playback devices. U.S. Pat. No. 8,234,395 entitled, “System and method for synchronizing operations among a plurality of independently clocked digital data processing devices,” which is hereby incorporated by reference, provides in more detail some examples for audio playback synchronization among playback devices.

(28) The memory **206** may further be configured to store data associated with the playback device **200**, such as one or more zones and/or zone groups the playback device **200** is a part of, audio sources accessible by the playback device **200**, or a playback queue that the playback device **200** (or some other playback device) may be associated with. The data may be stored as one or more state variables that are periodically updated and used to describe the state of the playback device **200**. The memory **206** may also include the data associated with the state of the other devices of the media system, and shared from time to time among the devices so that one or more of the devices have the most recent data associated with the system. Other embodiments are also possible.

(29) The audio processing components **208** may include one or more digital-to-analog converters (DAC), an audio preprocessing component, an audio enhancement component or a digital signal processor (DSP), and so on. In one embodiment, one or more of the audio processing components **208** may be a subcomponent of the processor **202**. In one example, audio content may be processed and/or intentionally altered by the audio processing components **208** to produce audio signals. The produced audio signals may then be provided to the audio amplifier(s) **210** for amplification and playback through speaker(s) **212**. Particularly, the audio amplifier(s) **210** may include devices configured to amplify audio signals to a level for driving one or more of the speakers **212**. The speaker(s) **212** may include an individual transducer (e.g., a “driver”) or a complete speaker system involving an enclosure with one or more drivers. A particular driver of the speaker(s) **212** may include, for example, a subwoofer (e.g., for low frequencies), a mid-range driver (e.g., for middle frequencies), and/or a tweeter (e.g., for high frequencies). In some cases, each transducer in the one or more speakers **212** may be driven by an individual corresponding audio amplifier of the audio amplifier(s) **210**. In addition to producing analog signals for playback by the playback device **200**,

the audio processing components **208** may be configured to process audio content to be sent to one or more other playback devices for playback.

(30) Audio content to be processed and/or played back by the playback device **200** may be received from an external source, such as via an audio line-in input connection (e.g., an auto-detecting 3.5 mm audio line-in connection) or the network interface **214**.

(31) The network interface **214** may be configured to facilitate a data flow between the playback device **200** and one or more other devices on a data network. As such, the playback device **200** may be configured to receive audio content over the data network from one or more other playback devices in communication with the playback device **200**, network devices within a local area network, or audio content sources over a wide area network such as the Internet. In one example, the audio content and other signals transmitted and received by the playback device **200** may be transmitted in the form of digital packet data containing an Internet Protocol (IP)-based source address and IP-based destination addresses. In such a case, the network interface **214** may be configured to parse the digital packet data such that the data destined for the playback device **200** is properly received and processed by the playback device **200**.

(32) As shown, the network interface **214** may include wireless interface(s) **216** and wired interface(s) **218**. The wireless interface(s) **216** may provide network interface functions for the playback device **200** to wirelessly communicate with other devices (e.g., other playback device(s), speaker(s), receiver(s), network device(s), control device(s) within a data network the playback device **200** is associated with) in accordance with a communication protocol (e.g., any wireless standard including IEEE 802.11a, 802.11b, 802.11g, 802.11n, 802.11ac, 802.15, 4G mobile communication standard, and so on). The wired interface(s) **218** may provide network interface functions for the playback device **200** to communicate over a wired connection with other devices in accordance with a communication protocol (e.g., IEEE 802.3). While the network interface **214** shown in FIG. 2 includes both wireless interface(s) **216** and wired interface(s) **218**, the network interface **214** may in some embodiments include only wireless interface(s) or only wired interface(s).

(33) In one example, the playback device **200** and one other playback device may be paired to play two separate audio components of audio content. For instance, playback device **200** may be configured to play a left channel audio component, while the other playback device may be configured to play a right channel audio component, thereby producing or enhancing a stereo effect of the audio content. The paired playback devices (also referred to as “bonded playback devices”) may further play audio content in synchrony with other playback devices.

(34) In another example, the playback device **200** may be sonically consolidated with one or more other playback devices to form a single, consolidated playback device. A consolidated playback device may be configured to process and reproduce sound differently than an unconsolidated playback device or playback devices that are paired, because a consolidated playback device may have additional speaker drivers through which audio content may be rendered. For instance, if the playback device **200** is a playback device designed to render low frequency range audio content (i.e. a subwoofer), the playback device **200** may be consolidated with a playback device designed to render full frequency range audio content. In such a case, the full frequency range playback device, when consolidated with the low frequency playback device **200**, may be configured to render only the mid and high frequency components of audio content, while the low frequency range playback device **200** renders the low frequency component of the audio content. The consolidated playback device may further be paired with a single playback device or yet another consolidated playback device.

(35) By way of illustration, SONOS, Inc. presently offers (or has offered) for sale certain playback devices including a “PLAY:1,” “PLAY:3,” “PLAY:5,” “PLAYBAR,” “CONNECT:AMP,” “CONNECT,” and “SUB.” Any other past, present, and/or future playback devices may additionally or alternatively be used to implement the playback devices of example embodiments

disclosed herein. Additionally, it is understood that a playback device is not limited to the example illustrated in FIG. 2 or to the SONOS product offerings. For example, a playback device may include a wired or wireless headphone. In another example, a playback device may include or interact with a docking station for personal mobile media playback devices. In yet another example, a playback device may be integral to another device or component such as a television, a lighting fixture, or some other device for indoor or outdoor use.

b. Example Playback Zone Configurations

(36) Referring back to the media playback system **100** of FIG. 1, the environment may have one or more playback zones, each with one or more playback devices. The media playback system **100** may be established with one or more playback zones, after which one or more zones may be added, or removed to arrive at the example configuration shown in FIG. 1. Each zone may be given a name according to a different room or space such as an office, bathroom, master bedroom, bedroom, kitchen, dining room, living room, and/or balcony. In one case, a single playback zone may include multiple rooms or spaces. In another case, a single room or space may include multiple playback zones.

(37) As shown in FIG. 1, the balcony, dining room, kitchen, bathroom, office, and bedroom zones each have one playback device, while the living room and master bedroom zones each have multiple playback devices. In the living room zone, playback devices **104**, **106**, **108**, and **110** may be configured to play audio content in synchrony as individual playback devices, as one or more bonded playback devices, as one or more consolidated playback devices, or any combination thereof. Similarly, in the case of the master bedroom, playback devices **122** and **124** may be configured to play audio content in synchrony as individual playback devices, as a bonded playback device, or as a consolidated playback device.

(38) In one example, one or more playback zones in the environment of FIG. 1 may each be playing different audio content. For instance, the user may be grilling in the balcony zone and listening to hip hop music being played by the playback device **102** while another user may be preparing food in the kitchen zone and listening to classical music being played by the playback device **114**. In another example, a playback zone may play the same audio content in synchrony with another playback zone. For instance, the user may be in the office zone where the playback device **118** is playing the same rock music that is being playing by playback device **102** in the balcony zone. In such a case, playback devices **102** and **118** may be playing the rock music in synchrony such that the user may seamlessly (or at least substantially seamlessly) enjoy the audio content that is being played out-loud while moving between different playback zones.

Synchronization among playback zones may be achieved in a manner similar to that of synchronization among playback devices, as described in previously referenced U.S. Pat. No. 8,234,395.

(39) As suggested above, the zone configurations of the media playback system **100** may be dynamically modified, and in some embodiments, the media playback system **100** supports numerous configurations. For instance, if a user physically moves one or more playback devices to or from a zone, the media playback system **100** may be reconfigured to accommodate the change(s). For instance, if the user physically moves the playback device **102** from the balcony zone to the office zone, the office zone may now include both the playback device **118** and the playback device **102**. The playback device **102** may be paired or grouped with the office zone and/or renamed if so desired via a control device such as the control devices **126** and **128**. On the other hand, if the one or more playback devices are moved to a particular area in the home environment that is not already a playback zone, a new playback zone may be created for the particular area.

(40) Further, different playback zones of the media playback system **100** may be dynamically combined into zone groups or split up into individual playback zones. For instance, the dining room zone and the kitchen zone **114** may be combined into a zone group for a dinner party such

that playback devices **112** and **114** may render audio content in synchrony. On the other hand, the living room zone may be split into a television zone including playback device **104**, and a listening zone including playback devices **106**, **108**, and **110**, if the user wishes to listen to music in the living room space while another user wishes to watch television.

c. Example Control Devices

(41) FIG. **3** shows a functional block diagram of an example control device **300** that may be configured to be one or both of the control devices **126** and **128** of the media playback system **100**. As shown, the control device **300** may include a processor **302**, memory **304**, a network interface **306**, and a user interface **308**. In one example, the control device **300** may be a dedicated controller for the media playback system **100**. In another example, the control device **300** may be a network device on which media playback system controller application software may be installed, such as for example, an iPhone™, iPad™ or any other smart phone, tablet or network device (e.g., a networked computer such as a PC or Mac™).

(42) The processor **302** may be configured to perform functions relevant to facilitating user access, control, and configuration of the media playback system **100**. The memory **304** may be configured to store instructions executable by the processor **302** to perform those functions. The memory **304** may also be configured to store the media playback system controller application software and other data associated with the media playback system **100** and the user.

(43) In one example, the network interface **306** may be based on an industry standard (e.g., infrared, radio, wired standards including IEEE 802.3, wireless standards including IEEE 802.11a, 802.11b, 802.11g, 802.11n, 802.11ac, 802.15, 4G mobile communication standard, and so on). The network interface **306** may provide a means for the control device **300** to communicate with other devices in the media playback system **100**. In one example, data and information (e.g., such as a state variable) may be communicated between control device **300** and other devices via the network interface **306**. For instance, playback zone and zone group configurations in the media playback system **100** may be received by the control device **300** from a playback device or another network device, or transmitted by the control device **300** to another playback device or network device via the network interface **306**. In some cases, the other network device may be another control device.

(44) Playback device control commands such as volume control and audio playback control may also be communicated from the control device **300** to a playback device via the network interface **306**. As suggested above, changes to configurations of the media playback system **100** may also be performed by a user using the control device **300**. The configuration changes may include adding/removing one or more playback devices to/from a zone, adding/removing one or more zones to/from a zone group, forming a bonded or consolidated player, separating one or more playback devices from a bonded or consolidated player, among others. Accordingly, the control device **300** may sometimes be referred to as a controller, whether the control device **300** is a dedicated controller or a network device on which media playback system controller application software is installed.

(45) The user interface **308** of the control device **300** may be configured to facilitate user access and control of the media playback system **100**, by providing a controller interface such as the controller interface **400** shown in FIG. **4**. The controller interface **400** includes a playback control region **410**, a playback zone region **420**, a playback status region **430**, a playback queue region **440**, and an audio content sources region **450**. The user interface **400** as shown is just one example of a user interface that may be provided on a network device such as the control device **300** of FIG. **3** (and/or the control devices **126** and **128** of FIG. **1**) and accessed by users to control a media playback system such as the media playback system **100**. Other user interfaces of varying formats, styles, and interactive sequences may alternatively be implemented on one or more network devices to provide comparable control access to a media playback system.

(46) The playback control region **410** may include selectable (e.g., by way of touch or by using a cursor) icons to cause playback devices in a selected playback zone or zone group to play or pause,

fast forward, rewind, skip to next, skip to previous, enter/exit shuffle mode, enter/exit repeat mode, enter/exit cross fade mode. The playback control region **410** may also include selectable icons to modify equalization settings, and playback volume, among other possibilities.

(47) The playback zone region **420** may include representations of playback zones within the media playback system **100**. In some embodiments, the graphical representations of playback zones may be selectable to bring up additional selectable icons to manage or configure the playback zones in the media playback system, such as a creation of bonded zones, creation of zone groups, separation of zone groups, and renaming of zone groups, among other possibilities.

(48) For example, as shown, a “group” icon may be provided within each of the graphical representations of playback zones. The “group” icon provided within a graphical representation of a particular zone may be selectable to bring up options to select one or more other zones in the media playback system to be grouped with the particular zone. Once grouped, playback devices in the zones that have been grouped with the particular zone will be configured to play audio content in synchrony with the playback device(s) in the particular zone. Analogously, a “group” icon may be provided within a graphical representation of a zone group. In this case, the “group” icon may be selectable to bring up options to deselect one or more zones in the zone group to be removed from the zone group. Other interactions and implementations for grouping and ungrouping zones via a user interface such as the user interface **400** are also possible. The representations of playback zones in the playback zone region **420** may be dynamically updated as playback zone or zone group configurations are modified.

(49) The playback status region **430** may include graphical representations of audio content that is presently being played, previously played, or scheduled to play next in the selected playback zone or zone group. The selected playback zone or zone group may be visually distinguished on the user interface, such as within the playback zone region **420** and/or the playback status region **430**. The graphical representations may include track title, artist name, album name, album year, track length, and other relevant information that may be useful for the user to know when controlling the media playback system via the user interface **400**.

(50) The playback queue region **440** may include graphical representations of audio content in a playback queue associated with the selected playback zone or zone group. In some embodiments, each playback zone or zone group may be associated with a playback queue containing information corresponding to zero or more audio items for playback by the playback zone or zone group. For instance, each audio item in the playback queue may comprise a uniform resource identifier (URI), a uniform resource locator (URL) or some other identifier that may be used by a playback device in the playback zone or zone group to find and/or retrieve the audio item from a local audio content source or a networked audio content source, possibly for playback by the playback device.

(51) In one example, a playlist may be added to a playback queue, in which case information corresponding to each audio item in the playlist may be added to the playback queue. In another example, audio items in a playback queue may be saved as a playlist. In a further example, a playback queue may be empty, or populated but “not in use” when the playback zone or zone group is playing continuously streaming audio content, such as Internet radio that may continue to play until otherwise stopped, rather than discrete audio items that have playback durations. In an alternative embodiment, a playback queue can include Internet radio and/or other streaming audio content items and be “in use” when the playback zone or zone group is playing those items. Other examples are also possible.

(52) When playback zones or zone groups are “grouped” or “ungrouped,” playback queues associated with the affected playback zones or zone groups may be cleared or re-associated. For example, if a first playback zone including a first playback queue is grouped with a second playback zone including a second playback queue, the established zone group may have an associated playback queue that is initially empty, that contains audio items from the first playback queue (such as if the second playback zone was added to the first playback zone), that contains

audio items from the second playback queue (such as if the first playback zone was added to the second playback zone), or a combination of audio items from both the first and second playback queues. Subsequently, if the established zone group is ungrouped, the resulting first playback zone may be re-associated with the previous first playback queue, or be associated with a new playback queue that is empty or contains audio items from the playback queue associated with the established zone group before the established zone group was ungrouped. Similarly, the resulting second playback zone may be re-associated with the previous second playback queue, or be associated with a new playback queue that is empty, or contains audio items from the playback queue associated with the established zone group before the established zone group was ungrouped. Other examples are also possible.

(53) Referring back to the user interface **400** of FIG. **4**, the graphical representations of audio content in the playback queue region **440** may include track titles, artist names, track lengths, and other relevant information associated with the audio content in the playback queue. In one example, graphical representations of audio content may be selectable to bring up additional selectable icons to manage and/or manipulate the playback queue and/or audio content represented in the playback queue. For instance, a represented audio content may be removed from the playback queue, moved to a different position within the playback queue, or selected to be played immediately, or after any currently playing audio content, among other possibilities. A playback queue associated with a playback zone or zone group may be stored in a memory on one or more playback devices in the playback zone or zone group, on a playback device that is not in the playback zone or zone group, and/or some other designated device.

(54) The audio content sources region **450** may include graphical representations of selectable audio content sources from which audio content may be retrieved and played by the selected playback zone or zone group. Discussions pertaining to audio content sources may be found in the following section.

d. Example Audio Content Sources

(55) As indicated previously, one or more playback devices in a zone or zone group may be configured to retrieve for playback audio content (e.g. according to a corresponding URI or URL for the audio content) from a variety of available audio content sources. In one example, audio content may be retrieved by a playback device directly from a corresponding audio content source (e.g., a line-in connection). In another example, audio content may be provided to a playback device over a network via one or more other playback devices or network devices.

(56) Example audio content sources may include a memory of one or more playback devices in a media playback system such as the media playback system **100** of FIG. **1**, local music libraries on one or more network devices (such as a control device, a network-enabled personal computer, or a networked-attached storage (NAS), for example), streaming audio services providing audio content via the Internet (e.g., the cloud), or audio sources connected to the media playback system via a line-in input connection on a playback device or network device, among other possibilities.

(57) In some embodiments, audio content sources may be regularly added or removed from a media playback system such as the media playback system **100** of FIG. **1**. In one example, an indexing of audio items may be performed whenever one or more audio content sources are added, removed or updated. Indexing of audio items may involve scanning for identifiable audio items in all folders/directory shared over a network accessible by playback devices in the media playback system, and generating or updating an audio content database containing metadata (e.g., title, artist, album, track length, among others) and other associated information, such as a URI or URL for each identifiable audio item found. Other examples for managing and maintaining audio content sources may also be possible.

(58) The above discussions relating to playback devices, controller devices, playback zone configurations, and media content sources provide only some examples of operating environments within which functions and methods described below may be implemented. Other operating

environments and configurations of media playback systems, playback devices, and network devices not explicitly described herein may also be applicable and suitable for implementation of the functions and methods.

III. Example Mirroring of Playback Queues

(59) As discussed above, embodiments described herein may involve a first playback device that may mirror a playback queue associated with a second playback device.

(60) Method **500** shown in FIG. 5 presents an embodiment of a method that can be implemented within an operating environment involving, for example, the media playback system **100** of FIG. 1, one or more of the playback device **200** of FIG. 2, and one or more of the control device **300** of FIG. 3. Method **500** may include one or more operations, functions, or actions as illustrated by one or more of blocks **502-506**. Although the blocks are illustrated in sequential order, these blocks may also be performed in parallel, and/or in a different order than those described herein. Also, the various blocks may be combined into fewer blocks, divided into additional blocks, and/or removed based upon the desired implementation.

(61) In addition, for the method **500** and other processes and methods disclosed herein, the flowchart shows functionality and operation of one possible implementation of present embodiments. In this regard, each block may represent a module, a segment, or a portion of program code, which includes one or more instructions executable by a processor for implementing specific logical functions or steps in the process. The program code may be stored on any type of computer readable medium, for example, such as a storage device including a disk or hard drive. The computer readable medium may include non-transitory computer readable medium, for example, such as computer-readable media that stores data for short periods of time like register memory, processor cache and Random Access Memory (RAM). The computer readable medium may also include non-transitory media, such as secondary or persistent long term storage, like read only memory (ROM), optical or magnetic disks, compact-disc read only memory (CD-ROM), for example. The computer readable media may also be any other volatile or non-volatile storage systems. The computer readable medium may be considered a computer readable storage medium, for example, or a tangible storage device. In addition, for the method **500** and other processes and methods disclosed herein, each block in FIG. 5 may represent circuitry that is wired to perform the specific logical functions in the process.

(62) In the following discussions of FIG. 5, reference is made to FIG. 6. Therefore, a brief description of FIG. 6 is now provided. FIG. 6 shows a first example household configuration **600** (“household **600**”) that includes playback devices **604A-604E**, router **606**, and controller **608**. Additionally, FIG. 6 shows a second example household configuration **602** (“household **602**”) that includes playback devices **610A-610E**, router **612**, and controller **614**. The playback devices, routers, and controllers may be any of the corresponding devices as described above in association with FIGS. 1-3, among other examples. Further, households **600** and **602** may also be referred to as media playback systems and may be configured to include any of the features of system **100** as described above in association with of FIG. 1.

(63) The first household **600** is shown as including a number of example “zones,” including a party room zone, a family room zone, and a bathroom zone. However, this configuration is for purposes of example only, and additional and/or alternative zones may be included within the household. The family room zone and the bathroom zone each have one playback device (i.e., **604D** and **604E**, respectively), while the party room zone has multiple playback devices (i.e., **604A**, **604B**, and **604C**). In the party room zone, one or more of playback devices **604A**, **604B**, and **604C** may be configured to play audio content in synchrony. As shown, router **606** is in the office and controller **608** is in the party room. However, the router **606** and controller **608** may alternatively be located anywhere in the first household **600**. Other zone configurations in first household **600** are also possible.

(64) Similarly, the second household **602** may include a party room zone, a family room zone, a

kitchen zone, and a first bedroom zone. The family room zone, the kitchen zone, and the first bedroom zone each have one playback device (i.e., **610C**, **610D**, and **610E**, respectively), while the party room zone has multiple playback devices. In the party room zone, playback devices **610A** and **610B** may be configured to play audio content in synchrony. As shown, router **612** is in the second bedroom and controller **614** is in the party room. However, the router **612** and controller **614** may alternatively be located anywhere in the second household **602**. Other zone configurations in second household **602** may also be possible.

(65) a. Associating a First Playback Device with a First Household

(66) At block **502**, method **500** involves associating a first playback device with a first household.

(67) The term “household” as used herein may be understood to refer to a given media playback system, where the household (or media playback system) includes one or more playback devices. In accordance with block **502**, for instance, the first household may be first household **600** of FIG. **6** as described above. For illustration purposes only, the first playback device may be playback device **604A** of first household **600**. Therefore, for purposes of explanation, the first playback device may also be referred to as playback device **604A**. However, note that embodiments described herein may apply to any of the playback devices of household **600** and thus, any of the playback devices of household **600** may play the role of a first playback device. Further, it should be understood that household **600** presents just one example of a household for purposes of example and explanation, and that other example households may exist. Yet further, note that while the term “household” is used herein, a media playback system may be located anywhere.

(68) The first playback device may be associated with the first household, in accordance with block **502**, in any suitable manner. For example, playback devices may be communicatively coupled directly or indirectly to a data network that may be distributed in and around a media playback system. For instance, a data network can be a wired network, a wireless network, or a combination of both wired and wireless networks. To illustrate, consider the network interface **214** as discussed above in association with FIG. **2**. The network interface **214** may be configured to facilitate a data flow between the playback device **200** and one or more other devices on a data network. As such, the playback device **200** may be configured to receive audio content over the data network from one or more other playback devices in communication with the playback device **200**, network devices within a local area network, or audio content sources over a wide area network such as the Internet.

(69) In one implementation, associating the first playback device with the first household involves the first playback device carrying out functions to become associated with the household. For example, connecting a playback device to a broadband router (e.g., router **606**) may form a data network. Other playback devices may then be added, wired or wirelessly, to the data network. For instance, a playback device (e.g., device **604A**) may be added to the media playback system (e.g., household **600**) by a user pressing a button on the playback device itself (or by performing some other action), which enables a connection from the playback device to the data network.

(70) Additionally and/or alternatively, associating the first playback device with the first household may involve a controller of the first household directing the first playback device to be associated with the first household. For example, consider the commands described above in association with control device **300** of FIG. **3**. In particular, data may be communicated between control device **300** and other devices via the network interface **306**. For instance, changes to configurations of the media playback system **100** may be performed by a user using the control device **300** in order to associate a first playback device with a first household.

(71) The configuration changes may include adding/removing one or more playback devices to/from a zone, adding/removing one or more zones to/from a zone group, forming a bonded or consolidated player, or separating one or more playback devices from a bonded or consolidated player, among others. Further, the user interface **308** of the control device **300** may be configured to facilitate user access and control of the media playback system **100**, by including a controller

interface such as the controller interface **400** shown in FIG. **4**.

(72) Accordingly, a control device such as controller **608** of household **600** may similarly include a user interface configured to facilitate user access and control of household **600**. For example, devices associated with household **600** may receive commands from controller **608** indicating changes to configurations of the playback system as described above in association with FIG. **3**. For instance, playback device **604A** may receive a command to join a zone (e.g., the party room zone) that includes playback devices **604B-C**. Once the command is executed, playback device **604A** may be configured to play audio content in synchrony with playback devices **604B-C**. As a result, device **604A** may then be associated with household **600** in accordance with block **602**. Other examples may also be possible.

(73) Note that, in some cases, an example method, or some functions thereof, may be carried out after associating a first playback device with a first household. In other words, associating a first playback device with a first household may be performed at a point in time prior to the beginning of the example method. For instance, an example method may begin with block **504** as described below. In such an instance, the first playback device may have been previously associated with the first household. Other cases may also be possible.

(74) b. Receiving a Command to Mirror a Playback Queue

(75) At block **504**, method **500** involves receiving a command, the command indicating that the first playback device is to mirror a playback queue that is associated with a second playback device, where the second playback device is associated with a second household.

(76) As noted above, the term “household” as used herein may be understood to refer to a given media playback system, where the household (or media playback system) includes one or more playback devices. In one example, the second household may be second household **602** of FIG. **6** as described above. To illustrate, the second playback device may be playback device **610A** of the second household **602**. Accordingly, for purposes of explanation, the second playback device may also be referred to as playback device **610A**. However, note that embodiments described herein may apply to any of the playback devices of household **602** and thus, any of the playback devices of household **602** may play the role of a second playback device, among other examples. Further, it should be understood that household **602** presents an illustration of a household for purposes of example and explanation, and that other example households may exist.

(77) Further, as discussed above in accordance with block **502**, devices associated with the first household (e.g., household **600**) may receive commands from a controller (e.g., controller **608**). For example, a received command may indicate that the first playback device (e.g., playback device **604A**) is to mirror a playback queue that is associated with a second playback device (e.g., playback device **610A**), where the second playback device is associated with a second household (e.g., household **602**). Note that the command may be communicated from any device of household **600**. Also, note that a playback queue may be configured to include any of the features described above in association with playback queue region **440** of FIG. **4**.

(78) The command may be received as a result of user input gathered via a user interface of the controller device, where the user interface may be configured to facilitate user access and control of household **600**. For example, referring back to the user interface **400** of FIG. **4**, the graphical representations of audio content in the playback queue region **440** may include track titles, artist names, track lengths, and other relevant information associated with the audio content in the playback queue.

(79) Accordingly, a user interface of controller **608** may include selectable icons to manage and/or manipulate the playback queue of a playback device, such as selectable icons to initiate a command indicating that a first playback device is to mirror a playback queue that is associated with a second playback device, where the second playback device is associated with a second household. As such, the command may be received by playback device **604A** as a result of user input received via a user interface of the controller **608**. Other examples may also be possible.

(80) c. Mirroring the Playback Queue

(81) At block **506**, method **500** involves, based on the command, mirroring the playback queue that is associated with the second playback device such that contents of a playback queue that is associated with the first playback device are the same as contents of the playback queue that is associated with the second playback device.

(82) Mirroring a playback queue may involve functions such as establishing access, via the playback queue associated with the first playback device, to the same audio content as presented in the playback queue associated with the second playback device. For example, the playback queue associated with the second playback device may include an audio track “A”, among other possible audio tracks. The audio track “A” may have been retrieved, for example, from a source such as a streaming content provider. As a result, the second playback device may provide information to the first playback device indicating particular steps for retrieving audio track “A” from the streaming content provider. The first playback device may then, in turn, add the track to the playback queue and subsequently use the obtained information to retrieve audio track “A” from the streaming content provider.

(83) Similarly, the first playback device may receive information from the second playback device for retrieving other audio content presented in the playback queue associated with the second playback device. The first playback device may then use the information to retrieve the audio content such that audio content of the playback queue that is associated with the first playback device is the same as audio content of the playback queue that is associated with the second playback device.

(84) An exchange of information between the first playback device and the second playback device for the purposes of mirroring a playback queue may require communication between the first playback device and the second playback device. Hence, one or more devices associated with the first household may communicate with one or more devices associated with the second household in a number of different manners as described below.

(85) In one embodiment, households **600** and **602** may communicate via a direct communication link with one another. For instance, playback devices **604A** and **610A** may communicate via a direct communication link to share and/or transmit information. Note that any device of household **600** may communicate via a direct communication link with any device of household **602** (e.g., controller **614** may communicate via a direct communication link with playback device **604E**).

(86) In another embodiment, households **600** and **602** may communicate via a remote server (e.g., a cloud server). To illustrate, consider FIG. 7 showing a system **700** that includes a remote server **710**, which may be a part of a cloud-based network, and local playback networks (i.e., households **600** and **602**). In some embodiments, a local playback network may include a plurality of playback devices or players, though it is understood that the playback network may contain only one playback device. In certain embodiments, each playback device may be configured to retrieve its content for playback. Control and content retrieval can be distributed or centralized, for example. Input can include streaming content provider input, third party application input, mobile device input, user input, and/or other playback network input into the cloud server for local distribution and playback.

(87) A remote server **710** may be used for communication between households **600** and **602**. For instance, the household may share information for mirroring a playback queue. Such information may include, for example: a name of an audio track, a source for obtaining an audio track, and one or more playback commands, among other possibilities. For example, household **600** may make information available on the server **710** which may then be retrieved from the server **710** by household **602**, and vice versa.

(88) Additionally or alternatively, the remote server **710** may be used for communications with content providers. For example, a multimedia audio system server **720**, a mobile device **730**, a third party application **740**, a content provider **750** and so on may provide multimedia content (requested

or otherwise) to households **600** and **602** via server **710**. Note that zones featuring multiple playback devices (e.g., party room zone of household **600** and party room zone of household **602**) are denoted by dotted arrows connecting playback devices as shown in FIG. 7. Additionally, note that separate servers may be used for different purposes (e.g., a first server for mirroring and a second server for obtaining content). Other examples may also be possible.

(89) To further illustrate the concept of mirroring a playback queue, consider FIG. 8A showing example user interface **800** and example user interface **802**. User interface **800** may be presented on controller **608** of household **600** or any other device in household **600**. Additionally, user interface **802** may be presented on controller **614** of household **602** or any other device in household **602**. Note that user interfaces **800** and **802** may be configured to include any of the features described above in association with controller interface **400** as shown in FIG. 4.

(90) User interface **800** includes a playback queue region **806**, which may include graphical representations of audio content in a playback queue associated with the selected playback zone (e.g., party room zone of household **600**). Additionally, user interface **802** includes a playback queue region **808**, which may include graphical representations of audio content in a playback queue associated with the selected playback zone (e.g., party room zone of household **602**). Note that queue regions **806** and **808** may be configured to include any of the features described above in association with playback queue region **440** as shown in FIG. 4.

(91) In particular, FIG. 8A is meant to illustrate the state of playback queue region **806** prior to mirroring the playback queue associated with device **610A** of household **602**. For example, queue region **806** shows that the playback queue of the party room zone in household **600** includes tracks A-D prior to mirroring. On the other hand, queue region **808** shows that the playback queue of the party room zone in household **602** includes tracks E-H.

(92) As noted above, once mirrored, the contents of a playback queue that is associated with the first playback device (i.e., device **604A**) are the same (or similar in some respects) as contents of the playback queue that is associated with the second playback device (i.e., device **610A**). To further illustrate this concept, consider FIG. 8B showing user interfaces **800** and **802**, previously presented in FIG. 8B, after mirroring is carried out.

(93) As shown, queue region **806** now provides graphical representations of the mirrored playback queue where the contents of the playback queue that is associated with device **604A** are the same as contents of the playback queue that is associated with device **610A**. In other words, queue region **808** shows that the playback queue of the party room zone in household **602** includes tracks E-H and, after mirroring, queue region **806** shows that the playback queue of the party room zone in household **600** also includes tracks E-H. Additionally, queue region **806** may also provide an indicator to a user that a particular playback queue has been mirrored. For example, in FIG. 8B, queue region **806** shows an indication **810** presented as “Queue: mirrored from Mike's party room”. Other examples may also be possible.

(94) Once the command for device **604A** (i.e., first playback device) to mirror a playback queue associated with device **610A** (i.e., second playback device) is carried out, the mirrored playback queue that is associated with device **604A** may be further distributed to devices of the party room zone in household **600**. After distribution, the mirrored playback queue may become available for synchronous playback among the devices of the party room zone in household **600**.

(95) In another case, the mirrored playback queue that is associated with device **604A** may become available for playback among any combination of devices in household **600**. In yet another case, the mirrored playback queue may become available for playback only on device **604A**. Note that the availability of the mirrored playback queue among devices in household **600** may depend on predetermined user preferences. Further, in some cases, playback of the mirrored queue in one zone (such as party room zone of household **600**) may occur simultaneously with playback of a different queue in another zone (such as the bathroom zone). The different queue in another zone may be a different mirrored queue (perhaps mirrored from a different device in household **602**) or a non-

mirrored queue. Other examples and combinations may also be possible.

(96) Note that, before receiving the command discussed in accordance with block **504**, a request to mirror the playback queue that is associated with the second playback device (i.e., playback device **610A**) may be sent to the second household **602** via a direct communication link or via the cloud server **710**. For example, the playback queue that is associated with device **610A** may be made available on the cloud server **710** by a user of household **602**. However, the availability of the playback queue for mirroring by another household may be restricted.

(97) In one case, availability of one or more items of audio content in the playback queue for mirroring may be restricted due to the items having been obtained (e.g., streamed) by the device **610A** from a third-party content provider. For example, the third-party content provider may restrict access to such audio content to paid subscribers and, thus, device **604A** may not have access to such audio content without a subscription. In another case, mirroring of the playback queue by device **604A** of household **600** may require access permission from household **602**. Such access permission may be obtained after a request to mirror the playback queue that is associated with device **610A** is sent by any device on household **600**. Other cases may also be possible.

(98) Once device **604A** has been permitted to mirror the playback queue, the access permission can be maintained to allow mirroring of the playback queue in the future without having to request permission again. Alternatively, a request may have to be sent every time that device **604A** seeks to mirror the playback queue (i.e., the access permission may be temporary). Additionally, certain households or devices may not require permission to mirror the queue while other households or devices may require permission (this may be due to predetermined user settings). Further, in another example, the playback queue that is associated with device **610A** may not be made available on the cloud server **710**. Therefore, a request to mirror a playback queue may also include a request to make a playback queue associated with device **610A** available for mirroring (via a direct communication link or via the cloud server **710**).

IV. Additional Features

(99) a. Controlling the Mirrored Playback Queue

(100) In one case, based on the command described above, control of the mirrored playback queue that is associated with device **604A** by devices associated with the first household **600** may be limited. For example, the playback queue associated with device **604A** in household **600** may mirror the playback queue associated with device **610A** in household **602**. However, device **604A** (as well as other devices in household **600**) may be unable to control any aspect of the mirrored playback queue. In this case, control of the mirrored playback queue that is associated with device **604A** may be carried out by one or more devices associated with household **602**.

(101) In another case, control of the mirrored playback queue that is associated with device **604A** by devices associated with the first household **600** may be partially limited. For instance, devices of household **600** may be able to control certain aspects of the playback queue (e.g. pausing multimedia items) while being unable to control other aspects (e.g., addition of multimedia items to the queue). Note that control of the mirrored playback queue may depend on predetermined user preferences or settings of devices associated with household **600** and/or predetermined user preferences or settings of devices associated with household **602**.

(102) In yet another case, control of the mirrored playback queue that is associated with device **604A** by devices associated with the first household **600** may be unlimited. For instance, devices of household **600** may control every aspect of the mirrored playback queue. In this case, control of the mirrored playback queue may be carried out by devices of both households **600** and **602** thus allowing for a collaborative playback queue. Alternatively, control of the mirrored playback queue may apply only to devices of household **600**. Note that other examples and combinations of controlling the playback queue may also be possible.

(103) Various processes may be used to control the mirrored playback queue that is associated with device **604A**. For example, playback device **604A** may receive a message from a device associated

with the first household **600** (e.g., given permission to control the mirrored playback queue) or from a device associated with the second household **602**. The message may be received via a direct communication link from the device or may be received via the cloud server **710**. For instance, the message may include an instruction to modify the mirrored playback queue that is associated with the first playback device and/or an indication that the playback queue associated with second playback device **610A** has been altered (and therefore the mirrored playback queue may be updated to maintain the mirroring). Within examples, updating and/or modifying the playback queue may involve one or more of the following: adding multimedia items to the playback queue, removing multimedia items from the playback queue, and renaming multimedia items in the playback queue, among other possibilities. Note that the tracks shown in queue regions **806** and **808** may also be referred to as multimedia items.

(104) In another example, playback device **604A** may receive a playback command to modify playback of a multimedia item identified in the mirrored playback queue that is associated with device **604A**. The playback command may be received via a direct communication link from a device associated with the second household **602** or may be received via the cloud server **710**. Based on the received playback command, playback of the identified multimedia item may be modified. For instance, a user of household **602** may act as a “remote DJ” for household **600** by modifying playback of multimedia items in the mirrored playback queue from a remote location.

(105) Within examples, modifying playback of the identified multimedia item may include one or more of the following: playing the multimedia item, skipping the multimedia item to the next multimedia item, skipping the multimedia item to the previous multimedia item, stopping playback of the multimedia item, pausing playback of the multimedia item, fast forwarding or rewinding the multimedia item, changing playback volume of the multimedia item, changing the equalization of the multimedia item, enter/exit repeat mode, and enter/exit cross fade mode. Other examples may also be possible.

(106) b. Mirroring the Playback Queue to Multiple Households

(107) In some cases, a user of a media playback system (e.g., household **602**) may seek to make a playback queue available for mirroring to multiple households. To illustrate, consider FIG. **9** showing household **602** in communication with multiple households (including household **600**), where the multiple households may be located anywhere. In one example, the multiple households may be in communication with household **602** via direct communication links. In another example, the multiple household may communicate with household **602** via the cloud server **710**.

(108) For instance, a playback queue associated with device **610A** can be made available for mirroring on cloud server **710** by a user of household **602**. The playback queue may then be mirrored by multiple household via the cloud server **710**. The user of household **602** may then control the mirrored playback queue that is associated with the multiple households, via any device associated with household **602**, of one or more households that selected to mirror the playback queue associated with device **610A**. In other words, a user of household **602** may act as a “remote DJ” for multiple household located anywhere around the world.

(109) c. Maintaining a List of Friends

(110) In an example embodiment, it may be advantageous for a user of a media playback system (e.g., household **602**) to maintain a list of friends (e.g., contacts), where each friend is associated with a playback queue that is available for mirroring. Such a list of friends may then be transmitted to and maintained on a controller device (e.g., controller **614**) or any other device associated with the playback system. The list of friends may then be accessed via a user interface (e.g., of the controller) that is configured to facilitate user access and control of the list of friends. Each friend from the list of friends may have one or more queues available for mirroring (e.g., each zone within a friend's household may have a different queue). Additionally, a first user of a media playback system may mirror a second user's (of a different system) playback queue at any time as long as the second user is on the first user's list of friends.

(111) In one example, friends may be added to the list of friends by searching a database of users, via the interface, where the database may be located on a remote server (e.g., server **720**). In another example, the interface may be configured to allow a user to send recommendations to a friend from the list of friends, where the recommendations may include a suggested friend for addition or a suggested playback queue for mirroring. In yet another example, the interface may be configured to alert the user if a first friend from the list of friends has selected to mirror a playback queue associated with the household of a second friend from the list of friends. This may be advantageous as the user may see if two of his friends are currently mirroring each other's queues. Other examples may also be possible.

(112) d. Reviews of a "Remote DJ"

(113) In an example embodiment, a user of a media playback system may desire to review a friend (e.g., a "remote DJ") or a friend's playback queue. For instance, a first playback device (e.g. device **604A**) may receive a command from a controller device (e.g., controller **608**), where the command indicates that the first playback device is to transmit a review of a playback queue. Consequently, based on the received command, the review may be transmitted to a second playback device (e.g., device **610A**) associated with a second household **602**. The transmission may be via a direct communication link or may be carried out via the cloud server **710**. A review of a playback queue can be made available on the cloud sever **710** such that other users may have access to the review. Additionally, a review may include: a rating based on numbers, a rating based on symbols (e.g., stars), and comments, among other possibilities.

(114) In some cases, a user of a media playback system may sort (via the interface of a controller) playback queues, friends and/or other users based on reviews and other factors. For example, friends may be sorted based on the number of times their playback queues have been mirrored. In another example, playback queues may be sorted based on a rating. Other examples of sorting may also be possible.

(115) e. Stopping Mirroring of the Playback Queue

(116) In an example embodiment, a first playback device (e.g., device **604A**) may receive a command indicating that the first playback device is to stop mirroring of the playback queue that is associated with the second playback device (e.g, device **610A**). In response to the received command, the first playback device may stop mirroring of the playback queue that is associated with the second playback device. Subsequently, the first playback device may restore a prior playback queue that is associated with the first playback device. Content in the playback queue of the first playback device may have been stored prior to the first playback device mirroring the playback queue of the second playback device.

(117) The command to stop mirroring may be received from any device associated with household **600** or any device associated with household **602**. In particular, the command may be received via a direct communication link or may be received via the cloud server **710**. Further, the restored playback queue may be the most recent playback queue associated the first playback device, a prior playback queue that is not the most recent playback queue, or a default playback queue, among other possibilities. For example, after mirroring has stopped, device **604A** may restore the playback queue presented in queue region **806** of FIG. **8A**. Other examples may also be possible.

V. Conclusion

(118) The description above discloses, among other things, various example systems, methods, apparatus, and articles of manufacture including, among other components, firmware and/or software executed on hardware. It is understood that such examples are merely illustrative and should not be considered as limiting. For example, it is contemplated that any or all of the firmware, hardware, and/or software aspects or components can be embodied exclusively in hardware, exclusively in software, exclusively in firmware, or in any combination of hardware, software, and/or firmware. Accordingly, the examples provided are not the only way(s) to implement such systems, methods, apparatus, and/or articles of manufacture.

(119) As indicated above, the present application involves a first playback device, associated with a first household, which is configured to mirror a playback queue that is associated with a second playback device, where the second playback device is associated with a second household.

(120) In one aspect, a device is provided. The device includes first playback device, where the first playback device includes a processor, a network interface, a non-transitory computer-readable storage medium, and program logic stored on the non-transitory computer-readable medium and executable by the processor to perform functions. The functions include receiving a command, the command indicating that the first playback device is to mirror a playback queue that is associated with a second playback device, where the first playback device is associated with a first household, and where the second playback device is associated with a second household. The functions include, based on the command, mirroring the playback queue that is associated with the second playback device such that contents of a playback queue that is associated with the first playback device are the same as contents of the playback queue that is associated with the second playback device.

(121) In another aspect, a method is provided. The method involves receiving a command, at a first playback device that is associated with a first household, the command indicating that the first playback device is to mirror a playback queue that is associated with a second playback device, where the second playback device is associated with a second household. The method also involves, based on the command, mirroring the playback queue that is associated with the second playback device such that contents of a playback queue that is associated with the first playback device are the same as contents of the playback queue that is associated with the second playback device.

(122) In yet another aspect, a non-transitory computer readable memory is provided. The non-transitory computer readable memory has stored thereon instructions executable by a processor to cause the processor to perform functions. The functions include associating the first playback device with a first household. The functions also include receiving a command, the command indicating that the first playback device is to mirror a playback queue that is associated with a second playback device, where the second playback device is associated with a second household. The functions further include, based on the command, mirroring the playback queue that is associated with the second playback device such that contents of a playback queue that is associated with the first playback device are the same as contents of the playback queue that is associated with the second playback device.

(123) Additionally, references herein to “embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment can be included in at least one example embodiment of an invention. The appearances of this phrase in various places in the specification are not necessarily all referring to the same embodiment, nor are separate or alternative embodiments mutually exclusive of other embodiments. As such, the embodiments described herein, explicitly and implicitly understood by one skilled in the art, can be combined with other embodiments.

(124) The specification is presented largely in terms of illustrative environments, systems, procedures, steps, logic blocks, processing, and other symbolic representations that directly or indirectly resemble the operations of data processing devices coupled to networks. These process descriptions and representations are typically used by those skilled in the art to most effectively convey the substance of their work to others skilled in the art. Numerous specific details are set forth to provide a thorough understanding of the present disclosure. However, it is understood to those skilled in the art that certain embodiments of the present disclosure can be practiced without certain, specific details. In other instances, well known methods, procedures, components, and circuitry have not been described in detail to avoid unnecessarily obscuring aspects of the embodiments. Accordingly, the scope of the present disclosure is defined by the appended claims rather than the foregoing description of embodiments.

(125) When any of the appended claims are read to cover a purely software and/or firmware implementation, at least one of the elements in at least one example is hereby expressly defined to include a tangible, non-transitory medium such as a memory, DVD, CD, Blu-ray, and so on, storing the software and/or firmware.

Claims

1. A controller device comprising: at least one processor; at least one non-transitory computer-readable medium; and program instructions stored on the at least one non-transitory computer-readable medium that are executable by the at least one processor such that the controller device is configured to: receive an input indicating that a playback queue of a first media playback system operating on a local area network (LAN) is to be mirrored by a second playback queue of a second media playback system, wherein the second media playback system is not operating on the LAN and does not include the controller device; and after receiving the input: transmit, via a remote server, a command to the second media playback system to mirror the first playback queue and thereby cause the second media playback system to, based on the command, mirror the first playback queue of the first media playback system such that a media content in the first playback queue of the first media playback system matches a media content in the second playback queue of the second media playback system; and cause the second media playback system to play back the media content concurrently with the first media playback system.
2. The controller device of claim 1, wherein the remote server is used to provide media content to the second media playback system from a source of the media content that is separate from the first media playback system and the second media playback system.
3. The controller device of claim 1, further comprising program instructions stored on the at least one non-transitory computer-readable medium that are executable by the at least one processor such that the controller device is configured to cause any update to the first playback queue of the first media playback system to be reflected in the second playback queue of the second media playback system; and wherein the program instructions that are executable by the at least one processor such that the controller device is configured to cause the second media playback system to play back the media content concurrently with the first media playback system comprise program instructions that are executable by the at least one processor such that the controller device is configured to cause the second media playback system to play back the second playback queue when the first media playback system is playing back the first playback queue.
4. The controller device of claim 1, wherein: the LAN is a first LAN; the second media playback system is operating on a second LAN different from the first LAN; and the first media playback system is: (i) outside of a communication range of the second LAN and (ii) connected to the second media playback system via a wide area network.
5. The controller device of claim 1, further comprising program instructions stored on the at least one non-transitory computer-readable medium that are executable by the at least one processor such that the controller device is configured to: cause the second media playback system to be (i) capable of controlling at least one playback functionality related to playback of the media content by the first and second media playback systems and (ii) incapable of controlling at least one other playback functionality related to playback of the media content by the first and second media playback systems.
6. The controller device of claim 1, wherein the second media playback system further comprises at least one playback device.
7. The controller device of claim 6, wherein the program instructions that are executable by the at least one processor such that the controller device is configured to cause the second media playback system to play back the media content comprise program instructions that are executable by the at least one processor such that the controller device is configured to cause the at least one

playback device to play back the media content.

8. The controller device of claim 6, further comprising program instructions stored on the at least one non-transitory computer-readable medium that are executable by the at least one processor such that the controller device is configured to: communicate with the at least one playback device via the remote server; and communicate with the first media playback system via the LAN.

9. The controller device of claim 6, wherein the at least one playback device comprises headphones.

10. A non-transitory computer-readable medium, wherein the non-transitory computer-readable medium is provisioned with program instructions that, when executed by at least one processor, cause a controller device to: receive an input indicating that a playback queue of a first media playback system operating on a local area network (LAN) is to be mirrored by a second playback queue of a second media playback system, wherein the second media playback system is not operating on the LAN and does not include the controller device; and after receiving the input: transmit, via a remote server, a command to the second media playback system to mirror the first playback queue and thereby cause the second media playback system to, based on the command, mirror the first playback queue of the first media playback system such that a media content in the first playback queue of the first media playback system matches a media content in the second playback queue of the second media playback system; and cause the second media playback system to play back the media content concurrently with the first media playback system.

11. The non-transitory computer-readable medium of claim 10, wherein the remote server is used to provide media content to the second media playback system from a source of the media content that is separate from the first media playback system and the second media playback system.

12. The non-transitory computer-readable medium of claim 10, wherein the non-transitory computer-readable medium is also provisioned with program instructions that, when executed by at least one processor, cause the controller device to cause any update to the first playback queue of the first media playback system to be reflected in the second playback queue of the second media playback system; and wherein the program instructions that, when executed by at least one processor, cause the controller device to cause the second media playback system to play back the media content concurrently with the first media playback system comprise program instructions that, when executed by at least one processor, cause the controller device to cause the second media playback system to play back the second playback queue when the first media playback system is playing back the first playback queue.

13. The non-transitory computer-readable medium of claim 10, wherein: the LAN is a first LAN; the second media playback system is operating on a second LAN different from the first LAN; and the first media playback system is: (i) outside of a communication range of the first LAN and (ii) connected to the second media playback system via a wide area network.

14. The non-transitory computer-readable medium of claim 10, wherein the non-transitory computer-readable medium is also provisioned with program instructions that, when executed by at least one processor, cause the controller device to: cause the second media playback system to be (i) capable of controlling at least one playback functionality related to playback of the media content by the first and second media playback systems and (ii) incapable of controlling at least one other playback functionality related to playback of the media content by the first and second media playback systems.

15. The non-transitory computer-readable medium of claim 10, wherein the second media playback system further comprises at least one playback device.

16. The non-transitory computer-readable medium of claim 15, wherein the program instructions that, when executed by at least one processor, cause the controller device to cause the second media playback system to play back the media content comprise program instructions that, when executed by at least one processor, cause the controller device to cause the at least one playback device to play back the media content.

17. The non-transitory computer-readable medium of claim 15, wherein the non-transitory computer-readable medium is also provisioned with program instructions that, when executed by at least one processor, cause the controller device to: communicate with the at least one playback device via the remote server; and communicate with the first media playback system via the LAN.
18. The non-transitory computer-readable medium of claim 10, wherein the first media playback system comprises the controller device.
19. The non-transitory computer-readable medium of claim 10, wherein the program instructions that, when executed by at least one processor, cause the controller device to transmit, via the remote server, the command to the second media playback system to mirror the first playback queue comprise program instructions that, when executed by at least one processor, cause the controller device to transmit, via the remote server, the command to the second media playback system to mirror the first playback queue and thereby further cause the second media playback system to, based on the command, obtain the first playback queue.
20. A method implemented by a controller device, the method comprising: receiving an input indicating that a playback queue of a first media playback system operating on a local area network (LAN) is to be mirrored by a second playback queue of a second media playback system, wherein the second media playback system is not operating on the LAN and does not include the controller device; and after receiving the input: transmitting, via a remote server, a command to the second media playback system to mirror the first playback queue and thereby causing the second media playback system to, based on the command, mirror the first playback queue of the first media playback system such that a media content in the first playback queue of the first media playback system matches a media content in the second playback queue of the second media playback system; and causing the second media playback system to play back the media content concurrently with the first media playback system.
-