

US Patent & Trademark Office

Patent Public Search | Text View

United States Reissue Patent
Kind Code
Date of Reissued Patent
Inventor(s)

RE50572
E
September 02, 2025
Cronin; John et al.

Wearable health interface for controlling internet of things devices

Abstract

A system and method enabling a wearable device to control an Internet of Things device. The wearable device includes at least one sensor, a communications interface configured to transmit an action command to the Internet of Things device in response to a triggering event, and a processor configured to analyze sensor data and determine whether a triggering event has occurred. When a triggering event occurs, the wearable device transmits an action command to control the Internet of Things device.

Inventors:	Cronin; John (Bonita Springs, FL), Huffines; Christopher (Bonita Springs, FL)
Applicant:	KONINKLIJKE PHILIPS N.V. (Eindhoven, NL)
Family ID:	53969092
Assignee:	Koninklijke Philips N.V. (Eindhoven, NL)
Appl. No.:	17/380161
Filed (or PCT Filed):	March 07, 2016
PCT No.:	PCT/EP2016/054787
PCT Pub. No.:	WO2016/142338
PCT Pub. Date:	September 15, 2016

Foreign Application Priority Data

EP	15177443	Jul. 20, 2015
----	----------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **G06F1/16** (20060101); **A61B5/00** (20060101); **A61B5/0205** (20060101); **H04L67/12** (20220101); **H04W4/80** (20180101)

U.S. Cl.:

CPC **G06F1/163** (20130101); **A61B5/0002** (20130101); A61B5/02055 (20130101); A61B2562/16 (20130101); H04L67/12 (20130101); H04W4/80 (20180201)

Field of Classification Search

CPC: B23K (20/023); A61B (2562/16); A61B (5/0002); A61B (5/02055); G06F (1/163); H04L (67/12); H04L (67/125); H04W (4/80)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9682622	12/2016	Kim	N/A	G08B 21/06
10798547	12/2019	Gold	N/A	G06Q 30/0207
2014/0368336	12/2013	Felix	340/539.13	H04W 4/90
2015/0035680	12/2014	Li et al.	N/A	N/A
2015/0057808	12/2014	Cook	700/275	G05B 13/04

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2876907	12/2014	EP	N/A

Primary Examiner: Ke; Peng

Background/Summary

RELATED APPLICATION DATA (1) This application is the U.S. National Phase application under 35 U.S.C. § 371 of International Application No. PCT/EP2016/054787, filed on Mar. 7, 2016, which claims the benefit of European Application No. 15177443.7, filed Jul. 20, 2015, and Provisional Application Ser. No. 62/130,171, filed Mar. 9, 2015. These applications are hereby incorporated by reference herein.

FIELD OF THE INVENTION

(1) The present disclosure generally relates to the field of wearable devices. In particular, the present disclosure is directed to a wearable health interface for controlling Internet of Things devices.

BACKGROUND

(2) The Internet of Things is the network of physical objects that enables the collection and exchange of data. Any object capable of communicating data to a network can be a component of the Internet of Things, including but not limited to vehicles, smartphones, appliances, thermostats, lighting fixtures, and many more objects. Objects within the Internet of Things network typically include one or more sensors to obtain information, and a wired or wireless communication system that enables communication of the sensor data to the network.

(3) Some current-generation wearable technology devices, such as smartwatches, fitness bands, and health wearables, for example, include one or more sensors for measuring various conditions or states of the wearer. Such sensors include pulse sensors for measuring the wearer's pulse, temperature sensors for measuring the wearer's temperature, and accelerometers for measuring the wearer's movement. However, current-generation wearable technology devices are limited in their usefulness, because they are typically only capable of being used within certain software and hardware environments, which are usually defined by a particular manufacturer. Consequently, users are not able to use wearable devices to their full potential. Additionally, current-generation wearable technology devices are only able to communicate with other devices, such as objects within the Internet of Things, if the devices are specifically pre-programmed or designed to communicate. This significantly limits the number of devices that wearable technology devices can communicate with, and thus inhibits the potential functionality of wearable technology devices.

(4) Accordingly, there is a continued need in the art for wearable technology devices that can communicate and interact with other objects within the Internet of Things.

SUMMARY

(5) The present disclosure is directed to inventive methods and systems for enabling a wearable device to control an Internet of Things device. By utilizing various aspects of this disclosure, users can define relationships between wearable device sensor readings and various Internet of Things devices. For example, a user may configure one or more wearable devices using the teachings herein to activate a shower when a certain level of sweat is detected on the user's body. Similarly, a user may configure a wearable device to activate a cleaning device when the user is experiencing a certain amount of fatigue. By enabling direct control of Internet of Things devices via a wearable device, complicated and proprietary hardware can be avoided, allowing users to use wearable devices to a fuller potential.

(6) In one implementation, the present disclosure is directed to a method of enabling a wearable device to control an Internet of Things device, the method being implemented on a wearable device. The method comprises: receiving sensor data from one or more wearable sensors; executing one or more wearable apps as a function of the sensor data to produce one or more action commands; and transmitting one or more device commands to an Internet of Things device as a function of the one or more action commands.

(7) In another implementation, the present disclosure is directed to a machine-readable storage medium containing machine-executable instructions for performing a method of enabling a wearable device to control an Internet of Things device, the method being implemented on a wearable device. The method comprises: receiving sensor data from one or more wearable sensors; executing one or more wearable apps as a function of the sensor data to produce one or more action commands; and transmitting one or more device commands to an Internet of Things device as a function of the one or more action commands.

(8) According an aspect is a method for controlling an Internet of Things device using a wearable device. The method includes the steps of: (i) providing a wearable device comprising at least one sensor, a processor, a wearable application database including one or more wearable applications, and a communications interface; (ii) receiving sensor data from the at least one sensor; (iii) selecting, based on the received sensor data, at least one of the one or more wearable applications in the wearable application database to analyze the received sensor data; (iv) analyzing the received sensor data with the selected wearable application to determine whether the received sensor data

comprises a triggering event; (v) generating, if the received sensor data comprises a triggering event, an action command for a remote Internet of Things device; and (vi) transmitting the action command to the remote Internet of Things device.

(9) According to an embodiment, the method further includes the step of receiving, from a user, input regarding which of the one or more wearable applications in the wearable application database to use to analyze the received sensor data.

(10) According to an embodiment, the wearable device further includes a wearable device ID, and wherein the method further comprises the step of communicating the wearable device ID.

(11) According to an embodiment, the action command includes a command to control one or more of: a light, a lock, a thermostat, a food preparation device, a cleaning device, a first responder emergency call, an appliance, a reward item, exercise equipment, and a shower.

(12) According to an embodiment, the at least one sensor comprises a GPS, a camera, a pulse oximeter, a temperature sensor, an accelerometer, or a galvanic skin sweat sensor.

(13) According to an embodiment, the method further includes the step of downloading, from an application network, a wearable application to the wearable device.

(14) According to an embodiment, the method further includes the step of downloading, from an application database of the Internet of Things device, a wearable application to the wearable device.

(15) According to an aspect is a system for controlling an Internet of Things device using a wearable device. The system includes: an application network comprising an application network database comprising one or more wearable applications, and a communications interface; an Internet of Things device comprising a wearable application database comprising one or more wearable applications, a communications interface, and an actuator; and a wearable device comprising at least one sensor, a processor, a wearable application database comprising one or more wearable applications, and a communications interface, wherein the wearable device is configured to: (i) select, based on the received sensor data, at least one of the one or more wearable applications in the wearable application database to analyze the received sensor data; (ii) analyze the received sensor data with the selected wearable application; (iii) generate, if the received sensor data comprises a triggering event, an action command for the Internet of Things device; and (iv) transmit the action command to the Internet of Things device.

(16) According to an embodiment, the wearable device is further configured to establish communication with the application network, and download a wearable application from the application network database.

(17) According to an embodiment, the wearable device is further configured to establish communication with the wearable application database of the Internet of Things device, and download a wearable application.

(18) According to an embodiment, the wearable device comprises a user interface configured to receive input from a user.

(19) According to an embodiment, the Internet of Things device is configured to activate the actuator in response to receiving the action command from the wearable device.

(20) According to an embodiment, the Internet of Things device is configured to determine, based on the action command transmitted by the wearable device, whether to activate the actuator.

(21) According to an aspect is a wearable device configured to control a remote Internet of Things device. The wearable device includes: at least one sensor; a communications interface configured to transmit an action command to the remote Internet of Things device in response to a triggering event; a wearable application database comprising one or more wearable applications; and a processor, wherein the processor is configured to: (i) receive sensor data from the at least one sensor; (ii) select, based on the received sensor data, at least one of the one or more wearable applications from the wearable application database to analyze the received sensor data; (iii) analyze the received sensor data with the selected wearable application; (iv) generate, if the

received sensor data comprises a triggering event, an action command for the Internet of Things device; and (iv) induce the communications interface to transmit the action command to the Internet of Things device.

(22) In various implementations, a processor or controller may be associated with one or more storage media (generically referred to herein as “memory,” e.g., volatile and non-volatile computer memory such as RAM, PROM, EPROM, and EEPROM, floppy disks, compact disks, optical disks, magnetic tape, etc.). As used herein, the term “non-transitory machine-readable medium” will be understood to encompass both volatile and non-volatile memories, but to exclude transitory signals. In some implementations, the storage media may be encoded with one or more programs that, when executed on one or more processors and/or controllers, perform at least some of the functions discussed herein. Various storage media may be fixed within a processor or controller or may be transportable, such that the one or more programs stored thereon can be loaded into a processor or controller so as to implement various aspects of the present invention discussed herein. The terms “program” or “computer program” are used herein in a generic sense to refer to any type of computer code (e.g., software or microcode) that can be employed to program one or more processors or controllers.

(23) In one network implementation, one or more devices coupled to a network may serve as a controller for one or more other devices coupled to the network (e.g., in a master/slave relationship). In another implementation, a networked environment may include one or more dedicated controllers that are configured to control one or more of the devices coupled to the network. Generally, multiple devices coupled to the network each may have access to data that is present on the communications medium or media; however, a given device may be “addressable” in that it is configured to selectively exchange data with (i.e., receive data from and/or transmit data to) the network, based, for example, on one or more particular identifiers (e.g., “addresses”) assigned to it.

(24) The term “network” as used herein refers to any interconnection of two or more devices (including controllers or processors) that facilitates the transport of information (e.g. for device control, data storage, data exchange, etc.) between any two or more devices and/or among multiple devices coupled to the network. As should be readily appreciated, various implementations of networks suitable for interconnecting multiple devices may include any of a variety of network topologies and employ any of a variety of communication protocols. Additionally, in various networks according to the present disclosure, any one connection between two devices may represent a dedicated connection between the two systems, or alternatively a non-dedicated connection. In addition to carrying information intended for the two devices, such a non-dedicated connection may carry information not necessarily intended for either of the two devices (e.g., an open network connection). Furthermore, it should be readily appreciated that various networks of devices as discussed herein may employ one or more wireless, wire/cable, and/or fiber optic links to facilitate information transport throughout the network.

(25) It should be appreciated that all combinations of the foregoing concepts and additional concepts discussed in greater detail below (provided such concepts are not mutually inconsistent) are contemplated as being part of the inventive subject matter disclosed herein. In particular, all combinations of claimed subject matter appearing at the end of this disclosure are contemplated as being part of the inventive subject matter disclosed herein. It should also be appreciated that terminology explicitly employed herein that also may appear in any disclosure incorporated by reference should be accorded a meaning most consistent with the particular concepts disclosed herein.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) In the drawings, like reference characters generally refer to the same parts throughout the different views. Also, the drawings are not necessarily to scale, emphasis instead generally being placed upon illustrating the principles of the invention. It should be understood that the present disclosure is not limited to the precise arrangements and instrumentalities shown in the drawings, wherein:
 - (2) FIG. 1 is a flowchart of a method for utilizing a wearable health interface to control Internet of Things devices, in accordance with an embodiment.
 - (3) FIG. 2 is a schematic representation of a system including a wearable health interface for controlling Internet of Things devices, in accordance with an embodiment.
 - (4) FIG. 3 is an example matrix of sensor data and calculated data and actions that can be associated with the data, in accordance with an embodiment.
 - (5) FIG. 4 is an example of a wearable sensor database, in accordance with an embodiment.
 - (6) FIG. 5 is a flow diagram illustrating wearable base software, in accordance with an embodiment.
 - (7) FIG. 6 is an example of a wearable app match database, in accordance with an embodiment.
 - (8) FIG. 7 is an schematic representation of a wearable device, in accordance with an embodiment.
 - (9) FIG. 8A is a schematic representation of a wearable device, in accordance with an embodiment.
 - (10) FIG. 8B is an example of a wearable device graphical user interface, in accordance with an embodiment.
 - (11) FIG. 8C is a flow diagram illustrating a wearable device algorithm, in accordance with an embodiment.
 - (12) FIG. 9 is a flow diagram illustrating a wearable device algorithm, in accordance with an embodiment.
 - (13) FIG. 10 is an example of a wearable device graphical user interface, in accordance with an embodiment.
 - (14) FIG. 11 is a flow diagram of an Internet of Things device base program, in accordance with an embodiment.
 - (15) FIG. 12 is a flow diagram of an Internet of Things device trigger program, in accordance with an embodiment.
 - (16) FIG. 13 is an example of an Internet of Things device command database, in accordance with an embodiment.
 - (17) FIG. 14 is a flow chart of a method implemented in the context of a wearable health interface for controlling Internet of Things devices, in accordance with an embodiment.
 - (18) FIG. 15 is a schematic representation of a computing system for utilizing a wearable health interface to control one or more Internet of Things devices, in accordance with an embodiment.
- ## DETAILED DESCRIPTION
- (19) Applicant has recognized and appreciated that there is a need for wearable devices to be able to trigger Internet of Things (“IoT”) devices based on wearable sensor data. Accordingly, the present disclosure is directed to inventive methods and systems enabling a wearable to download, e.g., through an application programming interface (“API”) or app store, software associated with any Internet of Things device, where the Internet of Things device uses the wearable-standard format and communications. The system enables automatic connection between the wearable and the Internet of Things device, and the wearable can trigger actions of the Internet of Things device based on its sensory readings. In some embodiments, such software may be downloaded in the form of one or more applications (or “apps”) and/or may be downloaded from a health data network.
- (20) At a high level, aspects of the present disclosure are directed to systems, methods, and software for controlling Internet of Things devices via a wearable device interface. According to an

embodiment, users may specify triggers that specify when and how data derived from wearable devices should lead to activation or control of Internet of Things devices. Referring to FIG. 1, in one embodiment, is a method **100** that may be used with a wearable health interface for controlling Internet of Things devices, which may comprise a step **105** of receiving sensor data from one or more wearable sensors, a step **110** of executing one or more wearable apps as a function of the sensor data to produce one or more action commands, and a step **115** of transmitting one or more device commands to an Internet of Things device as a function of the one or more action commands.

(21) Receiving sensor data from one or more wearable sensors at step **105** may comprise receiving any type of sensor data from any type of wearable sensor. For example, a heart rate sensor may provide readings of a user's heart rate in beats per minute, a temperature sensor may provide readings of a user's temperature in degrees Fahrenheit, and/or a pedometer may provide readings corresponding to a number of steps a user has taken, among other types of sensor data.

(22) Executing one or more wearable apps as a function of the sensor data to produce one or more action commands at step **110** may comprise comparing readings received from one or more wearable sensors to predetermined triggers. Such triggers may specify that, for example, a particularly high reading of a user's temperature, which may indicate fever, should cause a thermostat to increase its temperature to help the user overcome the fever, or lower the thermostat to make the user more comfortable. Transmitting one or more device commands to an Internet of Things device as a function of the one or more action commands at step **115** may comprise recognizing that a trigger specifies that, e.g., a particularly high reading of a user's temperature should cause a thermostat to increase its temperature to help the user overcome the fever and, based on that recognition, transmitting a device command to a smart thermostat to cause it to increase ambient air temperature. By using a system like the embodiment depicted in FIG. 2 to implement a method like that of FIG. 1, users can quickly and easily control Internet of Things devices via a wearable device interface.

(23) Referring to FIG. 2, in one embodiment, is a system **200** that may be used to implement one or more steps of the method of FIG. 1 and includes a wearable device and interface for controlling one or more Internet of Things devices. System **200** may comprise, for example, a wearable device **204**, an Internet of Things device **208**, and an application network **212**. Each component may be connected to each other through the Internet **216**, and these connections may comprise any suitable form of digital communication such as 3G, 4G, and/or 5G cellular, Wi-Fi™, and/or TCP/IP or other wired Internet connections, among others. The wearable device **204** and Internet of Things device **208** may communicate directly via any suitable means, and in some embodiments they may communicate to each other and/or to the Internet **216** through a home network hub **220** or gateway device, which intermediates between the entire Internet of Things home network and the Internet **216** and which may be a device such as a router, firewall, and/or a central hub, among other devices.

(24) According to an embodiment, wearable device **204** is a device worn or carried by an individual or by another living thing, such as a pet, which records data about the wearer and/or his environment. Based on that data, wearable device **204** may take certain actions and/or send certain commands. Wearable device **204** may comprise wearable base software **224**, which is the basic software the wearable device runs that controls its various operable pieces. Wearable device **204** may further comprise a wearable trigger program **228**, which is a software program that governs whether or not, and when, data will be sent to the home network hub **220**, the Internet **216**, the Internet of Things device **208**, and/or a wearable apps database **232**. Wearable apps database **232** is a database containing wearable applications, or “apps,” **1** through **N** **236** that may be stored on and/or executed by a wearable device. In some embodiments, one or more wearable apps **236** may determine whether or not particular sensor data warrants sending a command to an Internet of Things device **208**. Wearable device **204** may further comprise a device identifier (“ID”) **240**,

which may be a unique ID associated with each wearable device that allows the wearable device to be identified. Wearable device **204** may further comprise wearable sensors **1** through **N 244**, which may be sensors that record data associated with the wearer or the wearer's environment. Sensors **244** may include, but are not limited to, sensors such as pulse oximeter sensors, which can detect pulse, blood pressure, and blood oxygen level. Sensors **244** may detect the wearer's temperature, the wearer's movement, the wearer's location, ambient noise levels, humidity levels, ambient carbon monoxide, oxygen, and other gas levels, the ambient temperature, a level of particulate matter, and/or light levels, among many others.

(25) Wearable device **204** may further include a wearable communications interface **248**, or “comm,” which is a communications module that may utilize Bluetooth, low-power Bluetooth, 3G, 4G, 5G, Wi-Fi™, laser, visible, infrared, microwave, and/or any other suitable method for communicating wirelessly and/or via a wired connection such as an Ethernet port, a USB port, etc. Wearable device **204** may also include a wearable sensor database **252**, which may contain data generated by wearable sensors **1** through **N 244**, and a wearable app match database **256** that software may utilize to determine which of the wearable apps **1** through **N 236** should be applied to the data generated by wearable sensors **1** through **N 244**. As shown in FIG. 2, the wearable device **204** may also include a clock **260** for recording date and time and a wearable graphical user interface or “GUI” **264** that can be used to input or view data on the wearable device.

(26) Wearable device **204** may also comprise a processor **246** configured or programmed to perform various functions discussed herein, and can be utilized in combination with a memory comprising one or more sets of instructions executable by processor **246**, and which cause the wearable device **204** and/or system **200** to execute one or more of the steps of the methods described herein. According to an embodiment, processor **246** is in communication with sensors **244** to obtain and/or store sensor data. Processor **246** can also be in communication with and execute one or more modules or components of wearable base software **224**, wearable trigger program **228**, and wearable apps **232**. The processor can also facilitate communication with home network hub **220**, Internet **216**, Internet of Things device **208**, and/or wearable apps database **232**, via wearable communications interface **248**.

(27) According to an embodiment, Internet of Things device **208** is a device connected to the Internet of Things, a set of hitherto dumb devices, which by virtue of being Internet of Things devices are equipped with the mechanisms to interact intelligently with the Internet and/or with other devices. Accordingly, for example, a “dumb” refrigerator may be manufactured with and/or retrofitted to be an Internet of Things refrigerator and to have smart functionality to allow it to scan its surroundings, its contents, communicate with one or more users, etc. In some embodiments, Internet of Things device **208** may be something that is a possession of but not necessarily wearable by a user. According to an embodiment, Internet of Things device **208** executes an Internet of Things device trigger program **266**, which is a program that receives and passes on one or more triggers and/or action commands that are sent from wearable trigger program **228**. Internet of Things device base software **268** is the software that governs the device's general operations. Actuators **1** through **N 270** of the Internet of Things device are any device, component, or mechanism by which Internet of Things device **208** may take an action. For example, in the context of a refrigerator, such actuators **270** may comprise a mechanism that may open and/or close the door, activate the icemaker, and/or adjust the temperature inside the refrigerator or freezer component. Actuator **270** may comprise, for example, a display on the inside or outside of the refrigerator and a sensor inside the refrigerator. Internet of Things device communications interface **272** is a communications module that may be identical to, or different from, wearable communications interface **248**. The device command database **274** is a database that correlates action commands sent from wearable device **204** to specific commands and/or specific actuators **270** in Internet of Things device **208** and is further described in the context of FIG. 13 below. Internet of Things device app database **276** contains apps that the wearable device **204** may

download and store as one or more wearable apps **1** through **N 236**. According to an embodiment, wearable apps **236** stored in or available from the Internet of Things device app database **276** can be specific to interacting with and/or controlling Internet of Things device **208**, although other app functionality is possible.

(28) As shown in FIG. 2, app network **212** contains one or more apps and may be called upon to download or provide one or more of these apps to Internet of Things device **208** and/or wearable device **204**. App network **212** may comprise app network software **278**, which governs the communications and the choice of download. App database **280**, which contains the apps themselves, can be similar to Internet of Things device app database **276**, and the API **282** can translate those apps into a form, or language, that the wearable device **204** may use. If wearable device **204** is capable of using extended wearable device language, operating system, or protocol, then the API **282** may translate apps that may not exist in that wearable specific language or protocol into such an extended language before sending it to Internet of Things device **208** or wearable device **204**. While the app network **212** is described in this embodiment as constituting a “network,” it will be apparent that in other embodiments the app “network” **212** may instead be implemented in a single device, such as a server or a virtual machine in a cloud computing environment.

(29) In operation, a user may utilize wearable device **204** to download one or more wearable apps **236** and/or an app database **232**, which may come directly from app network **212** or via Internet of Things device **208**. Once an app is loaded and while the user wears wearable device **204**, wearable sensors **244** may record data that may then be fed into wearable apps **236**. The sensor data is processed, and if wearable app **236** determines that an Internet of Things device **208** should take action based upon that data, wearable trigger program **228** may utilize the wearable communications interface **248** to send an action command to the Internet of Things device. Internet of Things device **208** trigger program may then consult device command database **274**, retrieve the specific commands which must be performed by one or more actuators **1** through **N 270** to effectuate the action command, and transmit those commands to one or more actuators **1** through **N 270**.

(30) Referring to FIG. 3, in one embodiment, is an exemplary matrix **300** of sensor data **305**, calculated data **310**, and actions **315** that can be associated with one or both of each. The sensor data and calculated data is data determined by one or more wearable sensors **244** and/or calculated directly therefrom. For example, the “Accelerometer” sensor data **305** shown in FIG. 3 corresponds to an accelerometer that records movement of a wearable device. Calculated data **310** can be calculated directly from that accelerometer data, including but not limited to a number of steps taken, if the wearable is acting like a pedometer, and/or calories burned, which can be determined by taking the number of steps data and applying one or more mathematical algorithms. Listed along one side of the matrix are actions **315** that may be taken in response to the sensor data and/or the calculated data. Each black dot indicates where a sensor and/or calculated data may lead to an action. For example, a pulse oximeter sensor may cause actions such as activating food preparation, activating cleaning of a space, calling first responders, locking or unlocking doors, activating one or more appliances, and/or setting one or more appliances. As another example, if a wearer has been exercising, their clothing may need to be washed more rigorously than it might otherwise. In some embodiments, the pulse oximeter data may be associated with a reward item if the user chooses to use a system of rewards. In some embodiments, actions may activate specific exercise equipment. For example, a treadmill may attempt to keep a user at a certain heart rate by speeding up or slowing down. Further, actions may activate a shower. For example, as described further herein, when a user finishes exercising their heart rate decreases, so a decrease in heart rate may correspond to an action that turns on the user's shower.

(31) Similarly, with calculated data, inebriation can be measured from accelerometer data, galvanic skin data, and/or others, and one or more corresponding actions may activate light control to dim

lights in the case of a hangover, lock out a user's automobile once they have had too much to drink, change a thermostat setting in order to help wake up a user, activate food preparation or cleaning, and/or call first responders, depending on the level of inebriation and/or other factors. In some embodiments, actions may unlock doors to assist an inebriated user in getting home safely, activate an appliance, set appliance settings, release a reward item, activate specific exercise equipment or a shower, etc. It should be noted that the sensors, calculated data, and actions contained in the matrix of FIG. 3 are not exhaustive, as the matrix is merely a representative sample of the types of sensor/action correspondences that could be created.

(32) FIG. 4 shows an example of a wearable sensor database 252, which contains data reported by one or more wearable sensors 244. The first column specifies the sensor, which is the identity of the wearable sensor that recorded the data. In this case, two examples are given, the pulse oximeter and the accelerometer. The next column is the data type; this is the specific type of data recorded by each sensor. As shown, each sensor may in some embodiments record two or more different types of data; a pulse oximeter may report both pulse and blood pressure, while an accelerometer may report motion data and steps data derived from the motion data. The third and fourth columns specify the date and time of the sensor recording, and the fifth column specifies the actual datum, i.e., the unique data drawn from each of the sensors. As shown, the pulse oximeter may record a pulse of 99 beats per minute or “bpm” in the first row and a blood pressure of 110 over 80. On the other hand, the accelerometer may record motion by saving data or a link to a data file specifying such motion, which illustrates that in some cases data files may be recorded instead of or in addition to unique datums. The accelerometer also shows a reading for steps of 268, which shows that this data can also be additive, where the next sensor information recorded may be 268 plus however many steps were taken since 11:15.

(33) Referring to FIG. 5, in one embodiment, is an exemplary method 500 that wearable base software 224 may be configured to perform. In this example, method 500 begins by receiving sensor data from one or more wearable sensors 244 and/or tethered sensors at step 505. Next, at step 510, method 500 may save the sensor data to wearable sensor database 252, as shown in FIG. 4. Next, at step 515, method 500 may match sensor data to wearable apps 236; as described further in the context of FIG. 6 below, wearable app match database 256 can be used for that purpose. Next, method 500 may execute a decision step at step 520: are there matching wearable apps? If no, method 500 may return to step 505. If yes, method 500 may proceed to step 525 and activate trigger program 266 with the sensor data as an input. After trigger program 266 is activated, method 500 may return to step 505.

(34) Referring to FIG. 6, in one embodiment, is an example of wearable app match database 256, which can be used to match data types with specific wearable apps 236. The first column is the data type; in this example, there are two possibilities shown: the first is sleep and the second is for accelerometer and pulse data. The next column is the wearable app associated with the data type; these correspond to the wearable apps 1 through N 236 that are associated with the data types shown in the first column. As shown, information related to a NoDoze Driving app and a Shower Starter app may be included in wearable app match database 256. The third column shows the wearable app file name, which may be the location on wearable device 204 in memory where that specific app can be found. The fourth column specifies one or more Internet of Things devices that will receive an action command from the wearable app. As shown, the NoDoze Driving app is associated with the user's Ford 150 truck that has a certain serial number, and the Shower Starter app is associated with the Delta Spa system with its serial number. The fifth column specifies action commands that will be sent by the wearable app one or more of various corresponding terms or requirements are met. For example, the NoDoze Driving app may send an action command to lock out the car when a user is determined to be sleepy, while the Shower Starter may send an action command to start a post-workout shower. Although not shown in FIG. 6, it is possible that an app may have more than one related action command, depending on the exact data it is

receiving. Accordingly, for example, a NoDoze Driving app may lock out a car initially when a user is sleepy, but then after the user has slept for a certain amount of time, as determined by the sleep data, the app may unlock the car.

(35) Example System Architecture for a Wearable Device

(36) Referring to FIG. 7, in one embodiment, is a schematic representation of an exemplary wearable computing device **700** that may be configured to implement any one or more of various features and/or processes of the present disclosure, such as the features and processes illustrated in other figures of this disclosure, as well as features and processes that would be apparent to those of ordinary skill in the art after reading this entire disclosure. As shown, computing device **700** may include a memory interface **704**, one or more data processors, image processors and/or central processing units **708**, and a peripherals interface **712**. Memory interface **704**, one or more processors **708**, and/or peripherals interface **712** may be separate components or may be integrated in one or more integrated circuits. The various components in computing device **700** may be coupled by one or more communication buses or signal lines.

(37) Sensors, devices, and subsystems may be coupled to peripherals interface **712** to facilitate one or more functionalities. For example, a motion sensor **716**, a light sensor **720**, and a proximity sensor **724** may be coupled to peripherals interface **712** to facilitate orientation, lighting, and/or proximity functions. Other sensors **728** may also be connected to peripherals interface **712**, such as a global navigation satellite system (GNSS) (e.g., GPS receiver), a temperature sensor, a biometric sensor, and/or one or more other sensing devices, to facilitate related functionalities.

(38) A camera subsystem **732** and an optical sensor **736**, e.g., a charged coupled device (CCD) or a complementary metal-oxide semiconductor (CMOS) optical sensor, may be utilized to facilitate camera functions, such as recording images and/or video. Camera subsystem **732** and optical sensor **736** may be used to collect images of a user to be used during authentication of a user, e.g., by performing facial recognition analysis.

(39) Communication functions may be facilitated through one or more wireless communication subsystems **740**, which may include radio frequency receivers and transmitters and/or optical (e.g., infrared) receivers and transmitters. The specific design and implementation of communication subsystem **740** may depend on the communication network(s) over which computing device **700** is intended to operate. For example, computing device **700** may include communication subsystems **740** designed to operate over a GSM network, a GPRS network, an EDGE network, a Wi-Fi™ or WiMax™ network, and/or a Bluetooth™ network. In particular, wireless communication subsystems **740** may include hosting protocols such that one or more devices **700** may be configured as a base station for other wireless devices.

(40) An audio subsystem **744** may be coupled to a speaker **748** and a microphone **752** to facilitate voice-enabled functions, such as speaker recognition, voice replication, digital recording, and/or telephony functions. Audio subsystem **744** may be configured to facilitate processing voice commands, voice-printing, and voice authentication.

(41) I/O subsystem **756** may include a touch-surface controller **760** and/or other input controller(s) **764**. Touch-surface controller **760** may be coupled to a touch surface **768**. Touch surface **768** and touch-surface controller **760** may, for example, detect contact and movement or a lack thereof using one or more of any of a plurality of touch sensitivity technologies, including but not limited to capacitive, resistive, infrared, and/or surface acoustic wave technologies, optionally as well as other proximity sensor arrays and/or other elements for determining one or more points of contact with touch surface **768**.

(42) Other input controller(s) **764** may be coupled to other input/control devices **772**, such as one or more buttons, rocker switches, thumb-wheel, infrared port, USB port, and/or a pointer device such as a stylus. One or more related buttons or other controls (not shown) may include one or more sets of up/down buttons for volume and/or amplitude control of speaker **748** and/or microphone **752**. Using the same or similar buttons or other controls, a user may activate a voice

control, or voice command, module that enables the user to speak commands into microphone to cause device **700** to execute the spoken command. The user may customize functionality of one or more buttons or other controls. Touch surface **768** may, for example, also be used to implement virtual or soft buttons and/or a keyboard.

(43) In some implementations, computing device **700** may present recorded audio and/or video files, such as MP3, AAC, and/or MPEG files. In some implementations, computing device **700** may include the functionality of an MP3 player, such as an iPod™. Computing device **700** may, therefore, include a 36-pin connector that is compatible with related iPod™ hardware. Other input/output and control devices may also be used.

(44) As shown, memory interface **704** may be coupled to one or more types of memory **776**. Memory **776** may include high-speed random access memory and/or non-volatile memory, such as one or more magnetic disk storage devices, one or more optical storage devices, and/or flash memory (e.g., NAND, NOR). Memory **776** may store an operating system **780**, such as Darwin™, RTXC, LINUX, UNIX, OS X™, WINDOWS™, and/or an embedded operating system such as VxWorks. Operating system **780** may include instructions for handling basic system services and/or for performing hardware dependent tasks. In some implementations, operating system **780** may comprise a kernel (e.g., UNIX kernel). Further, in some implementations, operating system **780** may include instructions for performing voice authentication.

(45) Memory **776** may also store communication instructions **782** to facilitate communicating with one or more additional devices, one or more computers, and/or one or more servers. Additionally or alternatively, memory **776** may include: graphical user interface instructions **784** to facilitate graphic user interface processing; sensor processing instructions **786** to facilitate sensor-related processing and functions; phone instructions **788** to facilitate phone-related processes and functions; electronic messaging instructions **790** to facilitate electronic-messaging related processes and functions; web browsing instructions **792** to facilitate web browsing-related processes and functions; media processing instructions **794** to facilitate media processing-related processes and functions; GNSS/Navigation instructions **796** to facilitate GNSS and navigation-related processes and instructions; and/or camera instructions **797** to facilitate camera-related processes and functions. Memory **776** may store other software instructions **798** to facilitate other processes and functions. For example, other software instructions **798** may include instructions for counting steps the user takes when device **700** is worn.

(46) Memory **776** may also store other software instructions (not shown), such as web video instructions to facilitate web video-related processes and functions and/or web shopping instructions to facilitate web shopping-related processes and functions. In some implementations, media processing instructions **794** may be divided into audio processing instructions and video processing instructions to facilitate audio processing-related processes and functions and video processing-related processes and functions, respectively. An activation record and International Mobile Equipment Identity (IMEI) **799** or similar hardware identifier may also be stored in memory **776**.

(47) Each of the above identified instructions and applications may correspond to a set of instructions for performing one or more functions described herein. These instructions need not necessarily be implemented as separate software programs, procedures, or modules. Memory **776** may include additional instructions or fewer instructions. Further, various functions of computing device **700** may be implemented in hardware and/or in software, including in one or more signal processing and/or application specific integrated circuits.

(48) Referring to FIG. **8A**, in one embodiment, is a schematic representation of the components **800** of the wearable app, in this case showing details of the Shower Starter app. Within the wearable app there is an algorithm **804**, which is described further in the context of FIG. **8C**, and an app GUI **808**, an example of which is shown in FIG. **8B**. The wearable app may contain a profile **812**, which may comprise data that is used by the algorithm. In this case, profile **812** includes a

match file (e.g., Match.dat), a pulse decrease every five minutes, which in this case is 20 beats per minute, and a rest pulse, which is 100 beats per minute. As shown in FIG. 8C and described in detail below, the profile data can be utilized by algorithm **804**.

(49) Referring to FIG. 8B, in one embodiment, is an example of app GUI **808**, which the user may use to either set or modify the information shown in the profile, among other information. As shown, GUI **808** may include an inquiry asking the user whether they wish to set accelerometer and pulse to match last exercise set, a set of yes/no buttons the user can manipulate to provide an answer to the inquiry, and a text entry field through which the user may set a resting pulse rate decrease, which may indicate the level below which their pulse rate should be considered a resting pulse rate. The App GUI **808** may further include a submit button to submit entered data to the profile.

(50) Referring to FIG. 8C, in one embodiment, is an example algorithm **804** that can be used by a wearable app. For example, the algorithm may be utilized by the wearable app to determine whether or not to send an action command. As shown, the algorithm may begin with receiving sensor data, which is data that is sent by the wearable base software **224**. Next is a decision step: does the accelerometer data match the completed exercise? The answer to this decision may be determined as a function of a match file stored in the profile in the wearable app, in this example "Match.dat." If a match is found, then the user has completed their exercise set and they proceed to the next step. If there is no match, the algorithm may end. As shown, the next step may be a decision step: has pulse decreased 20 beats per minute in the last five minutes? Such a decrease may correspond to the user starting to cool off from their exercise routine. If the answer is yes, the algorithm may proceed to the next step. If not, the algorithm may end. At the next step, the algorithm may determine: is the pulse less than or equal to 100 beats per minute? That is, is the user done cooling off and about to go upstairs? If the answer is yes, then the wearable app may send the action command like the action command found in FIG. 6, which may start a post-workout shower. Again, if the answer is no, then the algorithm may end.

(51) Referring to FIG. 9, in one embodiment, is an exemplary method **900** that wearable trigger program **228** may be configured to perform, which may determine whether the wearable app should be run and, based on that output, whether data should be sent to an Internet of Things device **208**. In this example, method **900** begins at step **905** by receiving activation and sensor data from base software of the wearable device **204**. Next, method **900** may, at step **910**, match sensor data to wearable apps **236**, which may involve the same functionality of the match sensor data to wearable apps step **515** of FIG. 5. At this step, the sensor data that is received may be matched to the wearable apps found in wearable app match database **256** to determine which, if any, wearable apps should be run. Next, method **900** may run one or more matching wearable apps using sensor data as inputs, the apps being specified by the file names in wearable app match database **256**. Next, at step **920**, method **900** may receive one or more outputs of wearable apps **236**, which, in this case, would be action commands. Next, method **900** may, at step **925**, execute the decision step: did the outputs include action commands? If the answer is no, method **900** may return to step **905**. If the answer is yes, then method **900** may advance to step **930**, which involves retrieving the wearable device ID **240**. Method **900** may then send the action command and wearable device ID **240** to wearable communication interface **248** at step **935** for transmission to a designated Internet of Things device **208**, as designated in the wearable app match database **256**.

(52) Referring to FIG. 10, in one embodiment, is an example of a wearable GUI **264**, which in this example contains two drop-down menus. The first drop-down menu enables a user to select the app source, which is the source of the app the user wishes to download to their wearable device **204**. Such app sources may include, for example, George's Licensed App Store, which is a third party app store, Delta Apps, which is the manufacturer of an Internet of Things device **208**, and Delta Spa system number 9876541231564, which is an Internet of Things device itself from which wearable device **204** may download one or more wearable apps **236**. In this case, Delta Apps is

selected, so the next drop-down menu asks the user to select an app from that app source. In this example, three apps are shown in the menu: Shower Starter, Water Shut off, and Hot Tub, and the user has selected Shower Starter. There are also two soft-selection buttons shown: a save button, which a user may use to save their current preferences, and a load selected apps button, which a user may use to download the selected apps.

(53) Referring to FIG. 11, in one embodiment, is an exemplary method **1100** that Internet of Things device base software **268** may be configured to perform. In this example, method **1100** begins at step **1105** by polling the device communication interface **272** of Internet of Things device **208** for action commands. Next, at step **1110**, method **1100** may execute a decision step: received action command? That is, has an action command been received? If yes, then method **1100** may proceed to step **1115**, i.e., send the action command and wearable device ID **240** to Internet of Things device trigger program **266**. If no, then method **1100** may skip step **1115**. Method **1100** may then proceed to step **1120** and inquire: is the user requesting an app upload from the device? If the answer is no, method **1100** may return to step **1105**. If the answer is yes, then method **1100** may proceed to step **1125** and upload the requested app.

(54) Referring to FIG. 12, in one embodiment, is an exemplary method **1200** that Internet of Things device trigger program **266** may be configured to perform, which may be activated as a result of the middle step of FIG. 11. In this example, method **1200** begins at step **1205** by receiving the action command and the wearable ID from the base software and then, at step **1210**, retrieving the device commands and actuator IDs from a device command database **274**, which is further described in the context of FIG. 13. Method **1200** may then proceed to step **1215** and send the device commands to the designated actuators **270**.

(55) Referring to FIG. 13, in one embodiment, is an example of an Internet of Things device command database **274**, which allows the Internet of Things device **208** to receive an action command from a wearable device **204** and translate it into specific commands for specific actuators **270**. In this case, the database includes the device commands associated with the action command “start post-workout shower” from wearable device JC4567. If the device, which in this case may be the Delta Spa mentioned previously, receives that action command, then it may activate two device commands, one each for two different actuators **270**. For example, the first device command may issue a “start now” command to an in-line hot water heater, which may cause the water heater to start heating up, and the second device command may issue a “start in five minutes” command to the shower faucet. Notably, in this case, the Internet of Things shower faucet and in-line water heater are both part of a smart spa. Thus, in this example, when wearable device **204** sends the “start post-workout shower” action command, Internet of Things device **208** will immediately start the hot water heating and in five minutes will start the shower so that the user may come up from their exercise, disrobe, and immediately step into a hot shower.

(56) Referring to FIG. 14, in one embodiment, is an example of a method **1400** that can be implemented in the context of a wearable health interface for controlling Internet of Things devices. Such a method may begin with providing a wearable device **204** containing wearable base software **224**, a wearable trigger program **228**, one or more wearable sensors **1** through **N** **244**, a wearable communication interface **248**, a sensor database, a wearable app match database **256**, a clock **260**, a wearable GUI **264**, a device ID **240**, and a wearable apps database **232**. Next, the method may involve providing an Internet of Things device **208** containing Internet of Things base software, an Internet of Things device trigger program **266**, an Internet of Things device communication interface, a device command database **274**, and one or more actuators **1** through **N** **270**. Next, the method may involve providing an app network **212** containing app network software **278**, an app database **280**, and an API **282**, the app network being connected to wearable device **204** and Internet of Things device **208** by the Internet **216** and/or an optional home network hub **220**. Next, the method may involve allowing the user to download one or more wearable apps **236** from the app network **212** or from the Internet of Things device **208**. Next, the method may involve

receiving sensor data from one or more wearable sensors **244** and then executing one or more wearable apps **236** as a function of the sensor data. The method may then involve determining whether the results of the wearable app execution triggers one or more Internet of Things devices and then determining whether one or more Internet of Things devices are triggered. If the answer is no, the method may terminate. If the answer is yes, the method may proceed to the next step, which may entail sending action commands to the Internet of Things device **208** or devices and then activating actuators **270** in response to action commands.

(57) Referring to FIG. **15**, in one embodiment, is a diagrammatic representation of one embodiment of a computing device in the exemplary form of a computer system **1500** within which a set of instructions for causing a control system, such as any one or more of various systems of the present disclosure, including the systems illustrated in other figures of this disclosure as well as systems that would be apparent to those of ordinary skill in the art after reading this entire disclosure, to perform any one or more of the aspects and/or methodologies of the present disclosure may be executed. It is also contemplated that multiple computing devices may be utilized to implement a specially configured set of instructions for causing one or more of the devices to perform any one or more of the aspects and/or methodologies of the present disclosure.

(58) According to an embodiment, computer system **1500** includes a processor **1504** and a memory **1508** that communicate with each other, and with other components, via a bus **1512**. Bus **1512** may include any of several types of bus structures including, but not limited to, a memory bus, a memory controller, a peripheral bus, a local bus, and any combinations thereof, using any of a variety of bus architectures. Memory **1508** may include various components (e.g., machine-readable media) including, but not limited to, a random access memory component, a read only component, and any combinations thereof. In one example, a basic input/output system **1516** (BIOS), including basic routines that help to transfer information between elements within computer system **1500**, such as during start-up, may be stored in memory **1508**. Memory **1508** may also include (e.g., stored on one or more machine-readable media) instructions (e.g., software) **1520** embodying any one or more of the aspects and/or methodologies of the present disclosure. In another example, memory **1508** may further include any number of program modules including, but not limited to, an operating system, one or more application programs, other program modules, program data, and any combinations thereof.

(59) Computer system **1500** may also include a storage device **1524**. Examples of a storage device (e.g., storage device **1524**) include, but are not limited to, a hard disk drive, a magnetic disk drive, an optical disc drive in combination with an optical medium, a solid-state memory device, and any combinations thereof. Storage device **1524** may be connected to bus **1512** by an appropriate interface (not shown). Example interfaces include, but are not limited to, SCSI, advanced technology attachment (ATA), serial ATA, universal serial bus (USB), IEEE 1394 (FIREWIRE), and any combinations thereof. In one example, storage device **1524** (or one or more components thereof) may be removably interfaced with computer system **1500** (e.g., via an external port connector (not shown)). Particularly, storage device **1524** and an associated machine-readable medium **1528** may provide nonvolatile and/or volatile storage of machine-readable instructions, data structures, program modules, and/or other data for computer system **1500**. In one example, software **1520** may reside, completely or partially, within machine-readable medium **1528**. In another example, software **1520** may reside, completely or partially, within processor **1504**.

(60) Computer system **1500** may also include an input device **1532**. In one example, a user of computer system **1500** may enter commands and/or other information into computer system **1500** via input device **1532**. Examples of an input device **1532** include, but are not limited to, an alphanumeric input device (e.g., a keyboard), a pointing device, a joystick, a gamepad, an audio input device (e.g., a microphone, a voice response system, etc.), a cursor control device (e.g., a mouse), a touchpad, an optical scanner, a video capture device (e.g., a still camera, a video camera), a touchscreen, and any combinations thereof. Input device **1532** may be interfaced to bus **1512** via

any of a variety of interfaces (not shown) including, but not limited to, a serial interface, a parallel interface, a game port, a USB interface, a FIREWIRE interface, a direct interface to bus **1512**, and any combinations thereof. Input device **1532** may include a touch screen interface that may be a part of or separate from display **1536**, discussed further below. Input device **1532** may be utilized as a user selection device for selecting one or more graphical representations in a graphical interface as described above.

(61) A user may also input commands and/or other information to computer system **1500** via storage device **1524** (e.g., a removable disk drive, a flash drive, etc.) and/or network interface device **1540**. A network interface device, such as network interface device **1540**, may be utilized for connecting computer system **1500** to one or more of a variety of networks, such as network **1544**, and one or more remote devices **1548** connected thereto. Examples of a network interface device include, but are not limited to, a network interface card (e.g., a mobile network interface card, a LAN card), a modem, and any combination thereof. Examples of a network include, but are not limited to, a wide area network (e.g., the Internet, an enterprise network), a local area network (e.g., a network associated with an office, a building, a campus or other relatively small geographic space), a telephone network, a data network associated with a telephone/voice provider (e.g., a mobile communications provider data and/or voice network), a direct connection between two computing devices, and any combinations thereof. A network, such as network **1544**, may employ a wired and/or a wireless mode of communication. In general, any network topology may be used. Information (e.g., data, software **1520**, etc.) may be communicated to and/or from computer system **1500** via network interface device **1540**.

(62) Computer system **1500** may further include a video display adapter **1552** for communicating a displayable image to a display device, such as display device **1536**. Examples of a display device include, but are not limited to, a liquid crystal display (LCD), a cathode ray tube (CRT), a plasma display, a light emitting diode (LED) display, and any combinations thereof. Display adapter **1552** and display device **1536** may be utilized in combination with processor **1504** to provide graphical representations of aspects of the present disclosure. In addition to a display device, computer system **1500** may include one or more other peripheral output devices including, but not limited to, an audio speaker, a printer, and any combinations thereof. Such peripheral output devices may be connected to bus **1512** via a peripheral interface **1556**. Examples of a peripheral interface include, but are not limited to, a serial port, a USB connection, a FIREWIRE connection, a parallel connection, and any combinations thereof.

(63) It is to be noted that any one or more of the aspects and embodiments described herein may be conveniently implemented using one or more machines (e.g., one or more computing devices that are utilized as a user computing device for an electronic document, one or more server devices, such as a document server, etc.) programmed according to the teachings of the present specification, as will be apparent to those of ordinary skill in the computer art. Appropriate software coding can readily be prepared by skilled programmers based on the teachings of the present disclosure, as will be apparent to those of ordinary skill in the software art. Aspects and implementations discussed above employing software and/or software modules may also include appropriate hardware for assisting in the implementation of the machine executable instructions of the software and/or software module.

(64) Such software may be a computer program product that employs a machine-readable storage medium. A machine-readable storage medium may be any medium that is capable of storing and/or encoding a sequence of instructions for execution by a machine (e.g., a computing device) and that causes the machine to perform any one of the methodologies and/or embodiments described herein. Examples of a machine-readable storage medium include, but are not limited to, a magnetic disk, an optical disc (e.g., CD, CD-R, DVD, DVD-R, etc.), a magneto-optical disk, a read-only memory “ROM” device, a random access memory “RAM” device, a magnetic card, an optical card, a solid-state memory device, an EPROM, an EEPROM, and any combinations thereof. A machine-

readable medium, as used herein, is intended to include a single medium as well as a collection of physically separate media, such as, for example, a collection of compact discs or one or more hard disk drives in combination with a computer memory. As used herein, a machine-readable storage medium does not include transitory forms of signal transmission.

(65) Such software may also include information (e.g., data) carried as a data signal on a data carrier, such as a carrier wave. For example, machine-executable information may be included as a data-carrying signal embodied in a data carrier in which the signal encodes a sequence of instruction, or portion thereof, for execution by a machine (e.g., a computing device) and any related information (e.g., data structures and data) that causes the machine to perform any one of the methodologies and/or embodiments described herein.

(66) Examples of a computing device include, but are not limited to, an electronic book reading device, a computer workstation, a terminal computer, a server computer, a handheld device (e.g., a tablet computer, a smartphone, etc.), a web appliance, a network router, a network switch, a network bridge, any machine capable of executing a sequence of instructions that specify an action to be taken by that machine, and any combinations thereof. In one example, a computing device may include and/or be included in a kiosk.

(67) The foregoing has been a detailed description of illustrative embodiments of the invention. Various modifications and additions can be made without departing from the spirit and scope of this invention. Features of each of the various embodiments described above may be combined with features of other described embodiments as appropriate in order to provide a multiplicity of feature combinations in associated new embodiments. Furthermore, while the foregoing describes a number of separate embodiments, what has been described herein is merely illustrative of the application of the principles of the present invention. Additionally, although particular methods herein may be illustrated and/or described as being performed in a specific order, the ordering is highly variable within ordinary skill to achieve various aspects of the present disclosure. Accordingly, this description is meant to be taken only by way of example, and not to otherwise limit the scope of this invention.

(68) Exemplary embodiments have been disclosed above and illustrated in the accompanying drawings. It will be understood by those skilled in the art that various changes, omissions and additions may be made to that which is specifically disclosed herein without departing from the spirit and scope of the present invention.

Claims

1. A method for controlling an Internet of Things device via a wearable device remote from the Internet of Things device or IoT device, the method comprising the steps of: providing a wearable device, configured to be worn or carried, that comprises a unique wearable device ID, at least one sensor, a processor, a wearable device application database.[.for storing one or more wearable device applications.], and a communications interface; receiving sensor data from the at least one sensor; determining a data type of the received sensor data; matching the received sensor data with [.the.] one or more [.of the.] wearable device applications stored in the wearable device application database .Iadd.and an application database of an application network .Iaddend.based on the determined data type of the received sensor data; selecting, based on at least one match, at least one of the one or more wearable device applications [.stored in the wearable device application database.] to analyze the received sensor data; analyzing the received sensor data via the selected at least one of the one or more wearable device applications by comparing the received sensor data to a predetermined trigger of a respective wearable device application of the selected at least one of the one or more wearable device applications to determine whether or not the received sensor data comprises a triggering event; generating, if the received sensor data comprises a triggering event, one or more action command for a remote Internet of Things device; and transmitting both (i) the

one or more action command and (ii) the unique wearable device ID to the remote Internet of Things device or IoT device, wherein the IoT device is configured to retrieve both (a) at least one IoT device command from an IoT device command database and (b) at least one actuator ID of one or more IoT actuator of the IoT device, in response to the transmitted one or more action command and the transmitted unique wearable device ID.Iadd., wherein the matching, selecting, analyzing, and transmitting are performed via at least the wearable device.Iaddend..

2. The method of claim 1, further comprising the step of receiving, via a user interface, input regarding which of the one or more wearable device applications stored in the wearable device application database to use to analyze the received sensor data.

3. The method of claim 1, wherein the action command comprises a command to control one or more of: a light, a lock, a thermostat, a food preparation device, a cleaning device, a first responder emergency call, an appliance, a reward item, exercise equipment, and a shower.

4. The method of claim 1, wherein the at least one sensor comprises a GPS, a camera, a pulse oximeter, a temperature sensor, an accelerometer, or a galvanic skin sweat sensor.

5. The method of claim 1, further comprising the step of downloading, via [.a.]. .Iadd.the wearable .Iaddend.device [.communication.]. .Iadd.communications .Iaddend.interface, a wearable device application from [.an.]. .Iadd.the .Iaddend.application network to the wearable device, and storing the downloaded wearable device application in the wearable device application database.

6. The method of claim 1, further comprising the step of downloading, via [.a.]. .Iadd.the .Iaddend.wearable device [.communication.]. .Iadd.communications .Iaddend.interface, a wearable device application from an application database of the Internet of Things device to the wearable device, and storing the downloaded wearable device application in the wearable device application database.

7. A system for controlling an Internet of Things device using a wearable device remote from the Internet of Things device or IoT device, the system comprising: an application network that comprises an application network database storing one or more wearable device applications, and a communications interface; an Internet of Things device that comprises an application database storing one or more wearable device applications, a communications interface, and one or more actuator; a wearable device, configured to be worn or carried, that comprises a unique wearable device ID, at least one sensor, a processor, a wearable device application database for storing one or more wearable device applications, and a communications interface, wherein the wearable device is configured to: (i) receive sensor data from the at least one sensor; (ii) determine a data type of the received sensor data; (iii) match the received sensor data with [.the.]. one or more [.of the.]. wearable device applications stored in the wearable device application database.Iadd., the application database of the application network, and the application database of the Internet of Things device .Iaddend.based on the determined data type of the received sensor data; (iv) select, based on at least one match, at least one of the one or more wearable device applications [.stored in the wearable device application database.]. to analyze the received sensor data; (v) analyze the received sensor data via the selected at least one of the one or more wearable device applications by comparing the received sensor data to a predetermined trigger of a respective wearable device application of the selected at least one of the one or more wearable device applications to determine whether or not the received sensor data comprises a triggering event; (vi) generate, if the received sensor data comprises a triggering event, one or more action command for the Internet of Things device; and (vii) transmit both (a) the one or more action command and (b) the unique wearable device ID to the Internet of Things device or IoT device, wherein the IoT device is configured to retrieve both (c) at least one IoT device command from an IoT device command database and (d) at least one actuator ID for one or more IoT actuator of the IoT device, in response to the transmitted one or more action command and the transmitted unique wearable device ID.Iadd., wherein the match, select, analyze, generate and transmit are performed via at least the wearable device.Iaddend..

8. The system of claim 7, wherein the wearable device is further configured to establish, via .[.a.]. .Iadd.the .Iaddend.wearable device .[.communication.]. .Iadd.communications .Iaddend.interface, communication with the application network, and to download a wearable device application from the application network database and store the downloaded wearable device application in the wearable device application database of the wearable device.

9. The system of claim 7, wherein the wearable device is further configured to establish, via .[.a.]. .Iadd.the .Iaddend.wearable device communications interface, communication with the application database of the Internet of Things device, and to download a wearable device application from the application database of the Internet of Things device and store the downloaded wearable device application in the wearable device application database of the wearable device.

10. The system of claim 7, wherein the Internet of Things device is configured to activate an actuator, identified via a retrieved actuator ID, of the one or more actuator, in response to receiving both (i) the one or more the action command and (ii) the unique wearable device ID from the wearable device.

11. The system of claim 7, wherein the Internet of Things device is configured to determine, based on the one or more action command and the unique wearable device ID transmitted by the wearable device, whether to activate an actuator, identified via a retrieved actuator ID, of the one or more actuator, in response to receiving both (i) the one or more action command and (ii) the unique wearable device ID from the wearable device.

12. A wearable device configured to be worn or carried and to control a remote Internet of Things device, the wearable device comprising: a unique wearable device ID; at least one sensor; a communications interface configured to transmit both (i) one or more action command and (ii) the unique wearable device ID to the remote Internet of Things device in response to a triggering event; a wearable device application database for storing one or more wearable device applications; and a processor, wherein the processor is configured to: (i) receive sensor data from the at least one sensor; (ii) determine a data type of the received sensor data; (iii) match the received sensor data with the one or more of the wearable device applications of stored in the wearable device application database based on the determined type of the received sensor data; (iv) select, based on at least one match, at least one of the one or more wearable device applications stored in the wearable device application database to analyze the received sensor data; (v) analyze the received sensor data via the selected at least one of the one or more wearable device applications by comparing the received sensor data to a predetermined trigger of a respective wearable application of the selected at least one of the one or more wearable device applications to determine whether or not the received sensor data comprises a triggering event; (vi) generate, if the received sensor data comprises a triggering event, the one or more action command for the Internet of Things device; and (vii) induce the communications interface to transmit both (a) the one or more action command and (b) the unique wearable device ID to the Internet of Things device or IoT device, wherein the IoT device is configured to retrieve both (c) at least one IoT device command from an IoT device command database and (d) at least one actuator ID for one or more IoT actuator of the IoT device, in response to the transmitted one or more action command and the transmitted unique wearable device ID.

13. The wearable device of claim 12, wherein the processor is further configured to download, from an application database of the Internet of Things device, a wearable device application and store the downloaded wearable device application in the wearable device application database.

14. The wearable device of claim 12, wherein the processor is further configured to download, from an application network, a wearable device application and store the downloaded wearable device application in the wearable device application database.

.Iadd.15. An Internet of Things device controllable via a wearable device remote from the Internet of Things device or IoT device, the IoT device comprising: an application database storing one or more wearable device applications; an IoT command database; a communications interface; and

one or more actuator, wherein the wearable device, configured to be worn or carried, comprises a unique wearable device ID, at least one sensor, a processor, a wearable device application database for storing one or more wearable device applications, and a communications interface, wherein the wearable device is configured to: (i) receive sensor data from the at least one sensor; (ii) determine a data type of the received sensor data; (iii) match the received sensor data with one or more of the wearable device applications stored in the wearable device application database. an application database of an application network. and the application database of the IoT device based on the determined data type of the received sensor data; (iv) select. based on at least one match. at least one of the one or more wearable device applications to analyze the received sensor data; (v) analyze the received sensor data via the selected at least one of the one or more wearable device applications by comparing the received sensor data to a predetermined trigger of a respective wearable device application of the selected at least one of the one or more wearable device applications to determine whether or not the received sensor data comprises a triggering event; (vi) generate. if the received sensor data comprises a triggering event. one or more action command for the Internet of Things device; and (vii) transmit both (a) the one or more action command and (b) the unique wearable device ID to the Internet of Things device or IoT device. and wherein the IoT device is configured to retrieve both (i) at least one IoT device command from the IoT device command database and (ii) at least one actuator ID for one or more IoT actuator of the IoT device. in response to receiving. via the communications interface. the transmitted one or more action command and the transmitted unique wearable device ID. wherein the match. select. analyze. generate and transmit are performed via at least the wearable device..Iaddend.

16. .Iadd.An application network for controlling an Internet of Things device using a wearable device remote from the Internet of Things device or IoT device. the application network comprising: an application database storing one or more wearable device applications; a communications interface; and a controller. wherein the controller is operatively coupled to the application database and the communications interface. wherein the Internet of Things device comprises an application database storing one or more wearable device applications. a communications interface. and one or more actuator, wherein the wearable device. configured to be worn or carried. comprises a unique wearable device ID. at least one sensor. a processor. a wearable device application database for storing one or more wearable device applications. and a communications interface. wherein the wearable device is configured to: (i) receive sensor data from the at least one sensor; (ii) determine a data type of the received sensor data; (iii) match the received sensor data with one or more of the wearable device applications stored in the wearable device application database. the application database of the application network. and the application database of the Internet of Things device based on the determined data type of the received sensor data; (iv) select. based on at least one match. at least one of the one or more wearable device applications to analyze the received sensor data; (v) analyze the received sensor data via the selected at least one of the one or more wearable device applications by comparing the received sensor data to a predetermined trigger of a respective wearable device application of the selected at least one of the one or more wearable device applications to determine whether or not the received sensor data comprises a triggering event; (vi) generate. if the received sensor data comprises a triggering event. one or more action command for the Internet of Things device; and (vii) transmit both (a) the one or more action command and (b) the unique wearable device ID to the Internet of Things device or IoT device. wherein the IoT device is configured to retrieve both (c) at least one IoT device command from an IoT device command database and (d) at least one actuator ID for one or more IoT actuator of the IoT device. in response to the transmitted one or more action command and the transmitted unique wearable device ID..Iaddend.

.Iadd.17. The application network of claim 16. wherein the wearable device is further configured to establish. via the wearable device communications interface. communication with the application network. and to download a wearable device application from the application database of the

application network and store the downloaded wearable device application in the wearable device application database of the wearable device..Iaddend.

.Iadd.18. The application network of claim 16, wherein the wearable device is further configured to establish, via the wearable device communications interface, communication with the application database of the Internet of Things device, and to download a wearable device application from the application database of the Internet of Things device and store the downloaded wearable device application in the wearable device application database of the wearable device..Iaddend.

.Iadd.19. The application network of claim 16, wherein the Internet of Things device is configured to activate an actuator, identified via a retrieved actuator ID, of the one or more actuator, in response to receiving both (i) the one or more the action command and (ii) the unique wearable device ID from the wearable device..Iaddend.

.Iadd.20. The application network of claim 16, wherein the Internet of Things device is configured to determine, based on the one or more action command and the unique wearable device ID transmitted by the wearable device, whether to activate an actuator, identified via a retrieved actuator ID, of the one or more actuator, in response to receiving both (i) the one or more action command and (ii) the unique wearable device ID from the wearable device..Iaddend.
