

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384703
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Gong; Yelin

Disinfection lamp with underwater light projection effect

Abstract

Disclosed is a disinfection lamp with an underwater light projection effect, comprising an upper lampshade, a lower lampshade, a lens lampshade and a tube for containing sustained release chlorine tablets, wherein a circuit board and a battery are arranged on the lens lampshade, a solar panel is mounted on the surface of the upper lampshade, a first light bead is arranged on the lower surface of the circuit board, a light diffuser is arranged at a position, corresponding to the first light bead, of a bottom of the lens lampshade, the first light bead is located in the light diffuser, and the lower lampshade is mounted at the bottom of the lens lampshade. The disinfection lamp can float on water, and the tube containing the sustained release chlorine tablets is immersed in water, such that a conventional water purification, sterilization and disinfection effect is realized.

Inventors: Gong; Yelin (Fuzhou, CN)

Applicant: SHEN ZHEN LAMHO PHOTOELECTRICITY & TECHNOLOGY CO., LTD
(Shenzhen, CN)

Family ID: 95822849

Assignee: SHEN ZHEN LAMHO PHOTOELECTRICITY & TECHNOLOGY CO., LTD
(Shenzhen, CN)

Appl. No.: 19/037298

Filed: January 27, 2025

Prior Publication Data

Document Identifier	Publication Date
US 20250171336 A1	May. 29, 2025

Publication Classification

Int. Cl.: C02F1/68 (20230101); C02F1/30 (20230101); C02F103/42 (20060101); G01K1/14 (20210101); G01K7/16 (20060101)

U.S. Cl.:

CPC C02F1/688 (20130101); C02F1/30 (20130101); G01K1/14 (20130101); G01K7/16 (20130101); C02F2103/42 (20130101); C02F2201/004 (20130101); C02F2201/009 (20130101); C02F2209/02 (20130101); C02F2303/04 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
429384	12/1889	Manwaring	206/0.5	C02F 1/42
2826484	12/1957	Buehler	206/0.5	B01F 21/22
2976129	12/1960	Buehler	206/0.5	C02F 1/688
3130124	12/1963	Ferris	210/764	C09D 5/16
3607103	12/1970	Kiefer	206/0.5	C02F 1/688
3677711	12/1971	Bond	239/57	C02F 1/688
3758276	12/1972	Bond et al.	422/310	E04H 4/1681
3792979	12/1973	Clinton	206/0.5	B01F 21/22
4217331	12/1979	Schaub	D23/207	B01D 11/00
4241025	12/1979	Grayson, IV	422/264	C02F 1/688
D261415	12/1980	Yates	D23/207	N/A
4337136	12/1981	Dahlgren	210/242.1	E04H 4/16
4350666	12/1981	Klutts	4/DIG.10	B01F 21/22
4374563	12/1982	Alexander	206/0.5	B65D 71/10
4416854	12/1982	Nielsen	210/764	C02F 1/46176
4473533	12/1983	Davey	D23/207	B01F 21/22
4503563	12/1984	Johnson	362/267	F21S 9/02
4630634	12/1985	Sasaki	D23/207	C02F 1/688
4670149	12/1986	Francis	210/615	B01D 17/04
4702270	12/1986	King, Sr.	137/268	B01F 33/25
4763685	12/1987	King, Sr.	137/268	B01F 21/22
D297857	12/1987	Alexander	D23/207	N/A
4798707	12/1988	Thomas	222/169	C02F 1/688
4810385	12/1988	Hater	210/615	C02F 3/348
4822571	12/1988	Nicholson	422/279	C02F 1/688
4825528	12/1988	Nicholson	29/463	C02F 1/688
4828803	12/1988	Nicholson	422/279	C02F 1/688
4828804	12/1988	Nicholson	441/24	B01F 21/22
4828805	12/1988	Connors	206/217	B01F 21/22
4876003	12/1988	Casberg	206/5	B01F 21/00
4880547	12/1988	Etani	210/764	C02F 1/688
4900432	12/1989	Arnold	210/91	E04H 4/1263

4917868	12/1989	Alexander	422/119	B01F 21/22
D309493	12/1989	Casberg	D23/208	N/A
5053205	12/1990	Taylor	210/205	C02F 1/688
5055183	12/1990	Buchan	210/85	C02F 1/688
5059296	12/1990	Sherman	204/DIG.5	C02F 1/46104
5059316	12/1990	Renton	210/242.1	B01F 21/22
5064624	12/1990	King	239/57	E04H 4/1281
5085753	12/1991	Sherman	210/220	C02F 1/4602
5106492	12/1991	Distinti	210/167.2	E04H 4/1263
5124032	12/1991	Newhard	210/206	C02F 1/688
D328333	12/1991	Casberg	D23/208	N/A
5128031	12/1991	Midkiff	210/167.2	B01D 35/05
5152610	12/1991	Hallett	374/208	E04H 4/14
5169236	12/1991	Iest	374/E1.008	G01K 13/00
5350509	12/1993	Nelson	210/232	E04H 4/1281
5407567	12/1994	Newhard	210/205	B01F 21/221
5433867	12/1994	Kisner	210/167.11	C02F 1/688
5476116	12/1994	Price	422/279	E04H 4/1281
D371824	12/1995	Price	D23/207	N/A
5681110	12/1996	Burzacchi	374/208	G01K 1/06
5702614	12/1996	Taylor	210/242.1	C02F 1/66
5795459	12/1997	Sweeney	205/742	C02F 1/4672
5879932	12/1998	Van Erdewyk	435/307.1	C12M 23/38
D412198	12/1998	Bonelli	D23/208	N/A
6162407	12/1999	Pihl	422/275	E04H 4/1281
6207048	12/2000	Bonelli	210/252	C02F 1/685
6221244	12/2000	Yassin	210/205	E04H 4/1281
6238553	12/2000	Lin	210/85	B01F 21/22
6309538	12/2000	Khan	210/85	G01N 33/1886
D451978	12/2000	Hood	D23/208	N/A
D451979	12/2000	VanErdewyk	D23/208	N/A
6340431	12/2001	Khan	210/85	G01N 33/1886
D461871	12/2001	Flowers	D21/597	N/A
6432371	12/2001	Oliver, Jr.	210/242.1	C02F 1/76
6500334	12/2001	King	422/243	B01F 25/312
6502953	12/2002	Hajianpour	362/186	F21S 4/20
6508929	12/2002	Mercer	205/742	C02F 1/46104
6562242	12/2002	King	210/764	B01F 25/316
6582668	12/2002	Green	4/227.1	C02F 1/688
6641787	12/2002	Siggins	210/242.1	E04H 4/1281
D486881	12/2003	Pecci	D23/207	N/A
6685827	12/2003	King	210/220	B01F 25/316
6730509	12/2003	VanErdewyk	435/297.1	C12M 23/20
6780293	12/2003	Munk	204/230.6	H10F 19/00
6792956	12/2003	Bredo	134/44	E04H 4/1654
6855300	12/2004	Cormier	441/24	C02F 1/688
6908551	12/2004	King	210/205	B01F 25/316
D510404	12/2004	Thompson	D23/207	N/A
D512481	12/2004	Thompson	D23/208	N/A
D517643	12/2005	Thompson	D23/208	N/A

D518142	12/2005	Thompson	D23/208	N/A
7014780	12/2005	King	210/205	B01F 25/312
D518554	12/2005	Thompson	D23/208	N/A
D518870	12/2005	Thompson	D23/208	N/A
7037038	12/2005	Haski	405/60	B60L 53/38
7059540	12/2005	King	239/34	B01F 21/22
7060190	12/2005	King	210/764	C02F 1/688
D526043	12/2005	Thompson	D23/208	N/A
D526382	12/2005	Thompson	D23/208	N/A
D528929	12/2005	Oliver, Jr.	D10/57	N/A
7101475	12/2005	Maaske	210/167.2	E04H 4/1263
7207701	12/2006	Kennedy	362/477	F21S 8/00
7309421	12/2006	Riley	210/167.2	C02F 1/001
D559943	12/2007	Mercer	D23/207	N/A
7329345	12/2007	King	222/129	B01F 21/22
7347935	12/2007	King	422/282	B01F 25/312
7409853	12/2007	Biberger	73/61.61	G01N 33/1886
7413319	12/2007	Longoria	362/267	G09F 13/24
7452461	12/2007	Riley	210/167.2	E04H 4/1636
7487790	12/2008	King	137/268	E04H 4/1281
7504025	12/2008	Burgassi	210/167.2	E04H 4/1654
7510651	12/2008	Auger	210/242.1	C02F 1/688
7704467	12/2009	Hodgetts	137/268	C02F 1/688
7841916	12/2009	Stetten	210/620	B01F 35/32055
7922982	12/2010	Brennan	210/242.1	B01F 21/22
D652374	12/2011	Mercer	D13/102	N/A
8728406	12/2013	Van Der Meijden	210/242.1	B01F 21/221
8827496	12/2013	VanderSchuit	362/184	F21S 10/007
8999259	12/2014	King	210/167.3	B01F 33/503
9174177	12/2014	King, Jr.	N/A	C02F 1/76
9175821	12/2014	Adair	N/A	F21S 9/037
D745947	12/2014	Finley	D23/208	N/A
9206952	12/2014	Gold	N/A	B01F 21/22
D747439	12/2015	Byers	D23/208	N/A
9227164	12/2015	Sherman	N/A	B01F 21/15
9273841	12/2015	Philhower	N/A	F21S 9/037
D757211	12/2015	Slocum	D11/160	N/A
9352236	12/2015	Fernandez	N/A	A63H 23/14
9557038	12/2016	Blair	N/A	F21V 15/04
9631388	12/2016	Hui	N/A	C02F 1/4606
D788878	12/2016	Smith, Jr.	D23/207	N/A
D794160	12/2016	Hui	D23/207	N/A
9815719	12/2016	Sayre	N/A	C02F 1/688
9847749	12/2016	Kiani	N/A	F24S 20/02
D806931	12/2017	Hui	D26/102	N/A
D806932	12/2017	Hui	D26/102	N/A
D806933	12/2017	Hui	D26/102	N/A
9858792	12/2017	Fernandes	N/A	E04H 4/14
9862626	12/2017	King	N/A	E04H 4/1281
9951940	12/2017	Hui	N/A	F21V 31/00

9975792	12/2017	Thorgersen	N/A	C02F 1/688
10017402	12/2017	King	N/A	C02F 1/76
10029932	12/2017	King	N/A	B01F 21/22
D826373	12/2017	Kisner	D23/208	N/A
10047535	12/2017	King	N/A	B01F 21/22
10079504	12/2017	Hui	N/A	H02S 40/38
10094129	12/2017	He	N/A	C02F 1/688
10118847	12/2017	Howe	N/A	C02F 3/305
10119287	12/2017	King	N/A	C02F 1/688
10259722	12/2018	Braunberger	N/A	C02F 1/004
10337200	12/2018	King	N/A	E04H 4/1281
10385582	12/2018	Smith, Jr.	N/A	C02F 1/001
10472264	12/2018	Simonsen	N/A	B01F 33/503
D882727	12/2019	Lee	D23/207	N/A
10665073	12/2019	Richerson, Jr.	N/A	G03B 29/00
D887658	12/2019	Smith, Jr.	D32/31	N/A
10704780	12/2019	Ko	N/A	F21S 9/037
10710912	12/2019	Gomez	N/A	C02F 1/688
10717055	12/2019	Huang	N/A	B01J 4/001
10737951	12/2019	Miller	N/A	C02F 1/66
10787831	12/2019	Smith, Jr.	N/A	C02F 1/001
10794075	12/2019	Smith, Jr.	N/A	C02F 1/008
10914091	12/2020	King	N/A	B01F 21/22
11008232	12/2020	Waldek	N/A	C02F 1/46104
11008235	12/2020	King	N/A	B01F 33/503
11097958	12/2020	Miller	N/A	C02F 1/685
11124436	12/2020	King	N/A	C02F 1/688
11408191	12/2021	King	N/A	C02F 1/688
11447406	12/2021	King	N/A	B01F 21/22
11453989	12/2021	Negron	N/A	E02B 15/10
D969269	12/2021	Tran	D23/208	N/A
11492276	12/2021	King	N/A	B01F 21/22
11493495	12/2021	Witelson	N/A	B63B 35/00
D972681	12/2021	Ren	D23/207	N/A
D980381	12/2022	Pike	D23/207	N/A
11739549	12/2022	Jensen	210/86	E04H 4/1263
D1001235	12/2022	Foglia	D23/207	N/A
11813379	12/2022	Ke	N/A	A61L 9/20
12049768	12/2023	Gong	N/A	E04H 4/14
12181348	12/2023	Li	N/A	G01K 1/14
2002/0020676	12/2001	King	210/753	B01F 25/312
2002/0078990	12/2001	Munk	136/291	C02F 1/4674
2002/0096198	12/2001	Bredo	210/167.25	E04H 4/1654
2002/0100733	12/2001	King	210/753	B01F 21/22
2002/0112742	12/2001	Bredo	134/10	A47K 3/001
2002/0197197	12/2001	Green	422/275	E04H 4/1281
2004/0069698	12/2003	King	210/205	B01F 25/312
2004/0144699	12/2003	Lin	210/85	G05D 21/02
2004/0168963	12/2003	King	210/198.1	B01F 21/22
2004/0173542	12/2003	Porat	210/192	E04H 4/1272

2004/0175311	12/2003	Cormier	422/40	A61L 2/23
2005/0063858	12/2004	Cormier	422/265	A61L 2/23
2005/0077374	12/2004	King	239/42	B01F 21/22
2005/0126977	12/2004	Carter	210/242.4	C02F 1/285
2005/0163684	12/2004	Sherr	422/265	B01F 21/22
2005/0194296	12/2004	Lin	210/85	G01N 27/4167
2005/0211613	12/2004	King	210/167.11	E04H 4/1272
2005/0220169	12/2004	McGowan-Scanlon	374/E1.018	G01N 33/1886
2005/0279677	12/2004	Lin	210/85	C02F 1/688
2006/0060513	12/2005	Craig	210/167.2	E04H 4/1263
2006/0092630	12/2005	Kennedy	362/157	F21S 8/00
2006/0096905	12/2005	Burgassi	210/242.1	E04H 4/1263
2006/0102532	12/2005	Cadotte	210/94	E04H 4/1654
2006/0104720	12/2005	Haski	405/60	G05D 1/247
2006/0254968	12/2005	King	210/198.1	C02F 1/688
2007/0039859	12/2006	King	210/97	E04H 4/1636
2007/0119761	12/2006	King	210/198.1	E04H 4/1281
2007/0235380	12/2006	Cawein	210/242.1	E04H 4/1263
2007/0272622	12/2006	Mercer	210/754	C02F 1/76
2008/0217258	12/2007	Buchan	210/167.11	B01F 21/22
2009/0075538	12/2008	Stetten	441/136	B01F 31/44
2010/0196228	12/2009	Efird	422/265	E04H 4/1281
2011/0089121	12/2010	Van Der Meijden	222/130	B01F 21/221
2011/0132848	12/2010	Diaz	210/764	B01F 21/22
2011/0168235	12/2010	Rosa Clot	136/246	H10F 77/68
2013/0092634	12/2012	King	210/749	C02F 1/766
2013/0092635	12/2012	King	210/749	E04H 4/1209
2013/0206660	12/2012	Hui	210/167.11	C02F 1/4606
2014/0027358	12/2013	Sayre	424/641	C02F 1/688
2014/0110352	12/2013	King	222/173	C02F 1/505
2014/0124456	12/2013	King	210/764	C02F 1/766
2014/0166076	12/2013	Kiani	136/246	F24S 20/02
2014/0170036	12/2013	Sherman	422/256	B01F 21/15
2014/0175022	12/2013	King	210/749	B01F 21/22
2014/0205512	12/2013	King	422/265	E04H 4/1281
2015/0021243	12/2014	Herrington	210/85	C02F 1/4672
2015/0116987	12/2014	VanderSchuit	362/101	F21V 23/02
2015/0152662	12/2014	King	422/265	C02F 1/76
2015/0152663	12/2014	King	210/747.1	C02F 1/766
2015/0240510	12/2014	King	210/85	E04H 4/1281
2015/0322683	12/2014	Edwards	210/86	E04H 4/1281
2015/0323389	12/2014	Dayan	374/156	G01K 13/00
2015/0368128	12/2014	King	422/119	C02F 1/76
2016/0025287	12/2015	Philhower	362/183	F21S 8/022
2016/0072429	12/2015	Kiani	136/246	H02S 40/22
2017/0092096	12/2016	Fernandes	N/A	E04H 4/00
2017/0159927	12/2016	Hui	N/A	F21V 31/00
2017/0205035	12/2016	Blair	N/A	F21V 3/00
2017/0356209	12/2016	He	N/A	C02F 1/688
2018/0029906	12/2017	King	N/A	C02F 1/766

2018/0041068	12/2017	Hui	N/A	F21L 4/08
2018/0130328	12/2017	Fernandes	N/A	G08B 21/084
2018/0209160	12/2017	King	N/A	C02F 1/76
2018/0229919	12/2017	King	N/A	C02F 1/688
2018/0327291	12/2017	Simonsen	N/A	B01F 33/503
2019/0017668	12/2018	Heaton	N/A	F21V 21/08
2019/0022603	12/2018	Huang	N/A	C02F 1/688
2019/0048608	12/2018	Smith, Jr.	N/A	B01D 29/014
2019/0136557	12/2018	Jensen	N/A	E04H 4/1272
2019/0218114	12/2018	Braunberger	N/A	E04H 4/1263
2019/0257102	12/2018	King	N/A	C02F 1/688
2019/0257807	12/2018	Witelson	N/A	B63B 35/00
2019/0301186	12/2018	Smith, Jr.	N/A	C02F 1/008
2019/0301187	12/2018	Smith, Jr.	N/A	C02F 1/001
2019/0301188	12/2018	Smith, Jr.	N/A	E04H 4/1263
2019/0309914	12/2018	Blair	N/A	F42B 12/42
2019/0322557	12/2018	King	N/A	C02F 1/76
2020/0095140	12/2019	Waldek	N/A	C02F 1/4674
2020/0135000	12/2019	Asiri	N/A	G08B 21/084
2020/0240626	12/2019	Ko	N/A	F21S 9/037
2020/0399153	12/2019	King	N/A	E04H 4/1281
2021/0071436	12/2020	King	N/A	E04H 4/1281
2021/0198130	12/2020	King	N/A	C02F 1/76
2021/0262638	12/2020	Zhao	N/A	F21V 11/08
2021/0340786	12/2020	Zhang	N/A	G01K 1/14
2021/0371309	12/2020	Gallant	N/A	F21L 4/08
2021/0402043	12/2020	Ke	N/A	A61L 9/20
2022/0002171	12/2021	Correa Salas	N/A	C02F 1/46109
2022/0023460	12/2021	Lin	N/A	A61L 2/10
2022/0136907	12/2021	Pike	374/100	G01K 1/08
2022/0251862	12/2021	Jensen	N/A	E04H 4/1263
2022/0259083	12/2021	Marchand	N/A	C02F 1/50
2022/0315458	12/2021	Buchan	N/A	C02F 1/50
2022/0332613	12/2021	Feniger	N/A	C02F 1/688
2022/0412113	12/2021	Zhang	N/A	C02F 1/687
2023/0101118	12/2022	Rowhani	210/198.1	C02F 1/76
2023/0184598	12/2022	Zhang	374/208	G01K 13/026
2024/0141666	12/2023	Gong	N/A	F21V 33/00
2024/0142099	12/2023	Longoria	N/A	F21S 8/00
2024/0165285	12/2023	Chen	N/A	F21K 9/23
2024/0262722	12/2023	Stevens	N/A	E04H 4/1281

Primary Examiner: Popovics; Robert J

Attorney, Agent or Firm: Hemisphere Law, PLLC

Background/Summary

BACKGROUND OF THE INVENTION

Technical Field

(1) The invention relates to the technical field of sterilization devices for swimming pools, in particular to a disinfection lamp with an underwater light projection effect.

Description of Related Art

(2) It is commonly known that swimming pools are special places where people swim. To guarantee cleanliness and sanitation, water in swimming pools needs to be purified, sterilized and disinfected regularly to be kept clean and sanitary. When water in swimming pools is purified, sterilizing agents such as sustained release chlorine tablets are generally thrown into water, and the sustained release chlorine tablets are dissolved in water slowly to fulfill a sterilization and disinfection effect.

(3) To improve the aesthetics and tidiness of swimming pools, the sustained release chlorine tablets, when used, are often contained in some devices such as a chlorine buoy and then placed in water rather than being directly thrown into swimming pools. However, existing such devices are only used for containing chlorine tablets and float on water. For the sake of aesthetics, light beads are installed on portions, floating on water, of some devices, and the sense of beauty is improved by means of light. However, such a sense of beauty is created above water and is limited, and particularly at night, the space under water in swimming pools is still completely dark. So existing products cannot provide better experience for users.

BRIEF SUMMARY OF THE INVENTION

(4) In view of the abovementioned defects in the prior art, the objective of the invention is to provide a disinfection lamp with an underwater light projection effect.

(5) To fulfill the above objective, the invention adopts the following technical solution:

(6) A disinfection lamp with an underwater light projection effect comprises an upper lampshade, a lower lampshade, a lens lampshade and a tube for containing sustained release chlorine tablets, wherein a circuit board and a battery electrically connected to the circuit board are arranged on the lens lampshade, a solar panel is mounted on a surface of the upper lampshade and electrically connected to the circuit board, the upper lampshade covers the lens lampshade and is in seal connection with the lens lampshade, a first light bead is arranged on a lower surface of the circuit board, a light diffuser is arranged at a position, corresponding to the first light bead, of a bottom of the lens lampshade, the first light bead is located in the light diffuser, the lower lampshade is mounted at the bottom of the lens lampshade and wraps around the light diffuser, an exhaust gap is reserved between the lower lampshade and the lens lampshade, the tube is detachably mounted at a bottom of the lower lampshade, and water holes are formed in the tube and the lower lampshade; water infiltrates into the lower lampshade by means of the water holes in the lower lampshade to remove part of air in the lower lampshade to greatly reduce the buoyancy, such that the situation where the whole disinfection lamp loses balance and skews in water because the center of gravity the disinfection lamp is instable is avoided; water comes in contact with the sustained release chlorine tablets by means of the water holes in the tube, such that chlorine water is released to purify water.

(7) Preferably, a reflection cup is arranged upside down in the lower lampshade and located below the light diffuser, and an outer end surface of the reflection cup is a reflecting surface, such that light refracted out of the light diffuser is reflected by the reflection cup to be diffused around.

(8) Preferably, second light beads are arranged on the circuit board and face the upper lampshade, the lower lampshade is a scutate light diffuser, the first light bead and the second light beads are colorful RGB light beads, and a diamond pattern is arranged on the surface of the upper lampshade.

(9) Preferably, foam is mounted around the lens lampshade.

(10) Preferably, the lower lampshade is detachably mounted at the bottom of the lens lampshade.

(11) Preferably, first lumps are arranged along an opening of the lower lampshade, a first socket

allowing the opening of the lower lampshade to be inserted therein is arranged at the bottom of the lens lampshade, L-shaped first slots are formed in a wall of the first socket, the opening of the lower lampshade is inserted into the first socket and is rotated to lock the first lumps in the first slots, and exhaust gaps are reserved between the first lumps and the first slots.

(12) Preferably, second lumps are arranged along an end opening of the tube, a second socket allowing the end opening of the tube to be inserted therein is arranged at the bottom of the lower lampshade, L-shaped second slots are formed in a wall of the second socket, and the end opening of the tube is inserted into the second socket and is rotated to lock the second lumps in the second slots.

(13) Preferably, the tube comprises two semi-cylinders, one ends of the semi-cylinders are connected by means of a bent portion, and the other ends of the semi-cylinders are connected by means of hasps.

(14) Preferably, lower ends of the semi-cylinders are sleeved with a cover, and receding holes are formed in positions, corresponding to the water holes, of the cover.

(15) Preferably, the disinfection lamp with an underwater light projection effect further comprises a water temperature probe, wherein the water temperature probe is mounted on the lens lampshade or detachably mounted on the lens lampshade or the lower lampshade, a display screen for displaying a temperature value is inlaid in the upper lampshade, the upper lampshade corresponding to the display screen is transparent, and the water temperature probe and the display screen are electrically connected to the circuit board.

(16) Preferably, in a case where the water temperature probe is fixedly mounted on the lens lampshade, a probe portion of the water temperature probe is arranged at the bottom of the lens lampshade and located in the lower lampshade.

(17) Preferably, in a case where the water temperature probe is detachably mounted on the lens lampshade, the water temperature probe is connected to a first connecting base mounted in the first socket; in a case where the water temperature probe is detachably mounted in the lower lampshade, the water temperature probe is connected to a second connecting base mounted in the second socket; third lumps are arranged on a periphery of the first connecting base and a periphery of the second connecting base, and by rotation, the third lumps on the first connecting base are respectively clamped in the first slots, and the third lumps on the second connecting base are clamped in the second slots.

(18) Preferably, a mounting rod is hinged to each of the first connecting base and the second connecting base, a mounting groove for fixing and mounting the water temperature probe is formed in the mounting rod, the water temperature probe is fixed and mounted in the mounting groove, and the probe portion of the water temperature probe is arranged outside the mounting groove.

(19) Preferably, a receiving groove is formed in a position, corresponding to the mounting rod, of each of the first connecting base and the second connecting base, the water temperature probe is rotated to be received in the receiving groove, and a grip portion to be held by users is arranged on an end surface of the mounting rod.

(20) By adopting the above technical solution, the disinfection lamp can float on water, and the tube containing the sustained release chlorine tablets is immersed in water, such that a conventional water purification, sterilization and disinfection effect is realized; the portion floating on water adopts an integrated design, such that the waterproofness is improved; and a sensory effect of underwater light projection and a solar power generation function are added, such that the functions of the disinfection lamp are diversified in many aspects, and a more gorgeous visual impression can be provided during water purification, thus bringing better product experience to users.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

- (1) FIG. 1 is a schematic structural view according to one embodiment of the invention.
- (2) FIG. 2 is an exploded structural view according to one embodiment of the invention.
- (3) FIG. 3 is a sectional view according to one embodiment of the invention.
- (4) FIG. 4 is a disassembled structural view according to one embodiment of the invention.
- (5) FIG. 5 is a schematic structural view of a tube according to one embodiment of the invention.
- (6) FIG. 6 is a schematic structural view in a case where a water temperature probe is mounted on a first connecting base according to one embodiment of the invention.
- (7) FIG. 7 is a schematic structural view in a case where the water temperature probe is mounted on a second connecting base according to one embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

(8) To gain a better understanding of the objectives, technical solutions and advantages of the invention, the invention is described in further detail below in conjunction with accompanying drawings and embodiments. It should be understood that the specific embodiments described below are merely used to explain the invention and are not used to limit the invention.

(9) In the description of the invention, it should be understood that terms such as “central”, “longitudinal”, “transverse”, “length”, “width”, “thickness”, “upper”, “lower”, “front”, “back”, “left”, “right”, “vertical”, “horizontal”, “top”, “bottom”, “inner”, “outer”, “clockwise” and “anticlockwise” are used to indicate directional or positional relations based on the accompanying drawings merely for the purpose of facilitating and simplifying the description of the invention, do not indicate or imply that devices or elements referred to must be in a specific direction or be configured and operated in a specific direction, and thus should not be construed as limitations of the invention. In addition, the terms “first” and “second” are merely for the purpose of description and should not be construed as indicating or implying relative importance or implicitly indicating the number of technical features referred to. Therefore, a feature defined by “first” or “second” may explicitly or implicitly indicate the inclusion of one or more said features. In the description of the invention, “multiple” refers to two or more, unless otherwise expressly and specifically defined.

(10) In the description of the invention, it should be noted that unless otherwise expressly stated and defined, terms such as “mount”, “link” and “connect” should be broadly understood. For example, “connect” may refer to fixed connection, detachable connection or integrated connection; or, mechanical connection or electrical connection; or, direct connection, indirect connection by means of an intermediate medium, or internal connection or interaction between two elements. Those ordinarily skilled in the art can appreciate the specific meanings of these terms in the invention as the case may be.

(11) As shown in FIGS. 1-7, this embodiment provides a disinfection lamp with an underwater light projection effect, comprising an upper lampshade 1, a lower lampshade 2, a lens lampshade 3 and a tube 4 for containing sustained release chlorine tablets, wherein a circuit board 5 and a battery 6 electrically connected to the circuit board 5 are arranged on the lens lampshade 3, a solar panel 7 is mounted on the surface of the upper lampshade 1 and electrically connected to the circuit board 5, the upper lampshade 1 covers the lens lampshade 3 and is in seal connection with the lens lampshade 3, a first light bead 8 is arranged on the lower surface of the circuit board 5, a light diffuser 9 is arranged at a position, corresponding to the first light bead 8, of the bottom of the lens lampshade 3, the first light bead 8 is located in the light diffuser 9, the lower lampshade 2 is mounted at the bottom of the lens lampshade 3 and wraps around the light diffuser 9, an exhaust gap is reserved between the lower lampshade 2 and the lens lampshade 3, the tube 4 is detachably mounted at the bottom of the lower lampshade 2, and water holes 10 are formed in the tube 4 and the lower lampshade 2; water infiltrates into the lower lampshade 2 by means of the water holes 10 in the lower lampshade 2 to remove part of air in the lower lampshade to greatly reduce the buoyancy, such that the situation where the whole disinfection lamp loses balance and skews in

water because the center of gravity the disinfection lamp is instable is avoided; water comes in contact with the sustained release chlorine tablets by means of the water holes **10** in the tube **4**, such that chlorine water is released to purify water.

(12) In this embodiment, the disinfection lamp can float on water, and the tube **4** containing the sustained release chlorine tablets is immersed in water, such that a conventional water purification, sterilization and disinfection effect is realized; the portion floating on water adopts an integrated design, such that the waterproofness is improved; and a sensory effect of underwater light projection and a solar power generation function are added, such that the functions of the disinfection lamp are diversified in many aspects, and a more gorgeous visual impression can be provided during water purification, thus bringing better product experience to users. Wherein, after the first light bead **8** is turned on, because the lower lampshade **2** is immersed in water under the action of water entering the lower lampshade **2**, light emitted by the first light bead **8** will be directly projected underwater, so corresponding light will be emitted underwater, and particularly, when water is purified at night, a gorgeous scene will be created for a swimming pool by means of the light, thus improving the sense of beauty of the atmosphere; when sunlight is available, the solar panel **7** can generate power to charge the battery **6** to ensure that the light bead can emit light normally, and manual charging is avoided, thus improving convenience.

(13) In specific use, first, the sustained release chlorine tablets are placed in the tube **4** one by one; next, the tube **4** is mounted on the lower lampshade **2** and then directly placed in water, and water is gradually guided into the tube **4** via the water holes **10** formed in the tube **4** and comes in contact with the sustained release chlorine tablets, such that water in a swimming pool is purified; at the same time, water gradually enters the lower lampshade **2** via the water holes **10** formed in the lower lampshade **2**, and air is discharged out of the lower lampshade **2** via the exhaust gap, so the lower lampshade **2** sinks into water; in the purification process, the first light bead **6** is turned on, and light emitted by the first light bead **8** is refracted out of the lower lampshade **2**, projected into the swimming pool and then reflected by the wall of the swimming pool, such that a more gorgeous lighting effect can be created. Internal power is provided mainly by the battery **6**, and the solar panel **7** arranged outside the upper lampshade **1** generates power by means of sunlight to charge the battery **6**, wherein because the solar panel **7** is directly arranged outside the upper lampshade **1**, sunlight will not be blocked by materials on the upper lampshade **1** and can be converted into electric energy to the maximum extent. When the sustained release chlorine tablets **200** in the tube **4** are used out, the tube **4** can be directly detached, and new sustained release chlorine tablets are placed in the tube **4** to be used again.

(14) Further, in this embodiment, a reflection cup **101** is arranged upside down in the lower lampshade **2** and located below the light diffuser, and an outer end surface of the reflection cup **101** is a reflecting surface, such that light refracted out of the light diffuser **9** is reflected by the reflection cup **101** to be diffused around, thus improving the underwater light diffusion effect.

(15) Further, to improve the lighting effect, in this embodiment, second light beads **11** are arranged on the circuit board **5** and face the upper lampshade **1**, and the second light beads **11** can project correspond light above water, such that corresponding light can be presented both underwater and above water, thus improving the sense of beauty.

(16) Further, in this embodiment, foam **100** is mounted around the lens lampshade **3**. By means of the foam **100**, the buoyancy can be improved to contain more sustained release chlorine tablets under the precondition of reducing the product size, the transportation cost and the material cost.

(17) Further, to guarantee the gorgeousness and diversity of light projection, in this embodiment, the lower lampshade **2** is a scutate light diffuser, a striped lens, or other lens light-diffusion lampshades with a lighting effect, the first light bead **8** and the second light beads **11** are colorful RGB light beads or light beads with the same effect, and a diamond pattern or other patterns are arranged on the surface of the upper lampshade **1**, such that light coming out of the upper lampshade **1** is more gorgeous and colorful.

(18) Further, as for the installation of the lower lampshade **2**, in this embodiment, the lower lampshade **2** is detachably mounted at the bottom of the lens lampshade **3**, such that various lower lampshades **2** can be used to satisfy the requirements of customers. As for the specific assembly structure of the lower lampshade **2**, first lumps **12** are arranged along an opening of the lower lampshade **2**, a first socket **13** allowing the opening of the lower lampshade **2** to be inserted therein is arranged at the bottom of the lens lampshade **3**, L-shaped first slots **14** are formed in the wall of the first socket **13**, the opening of the lower lampshade **2** is inserted into the first socket **13** and is rotated to lock the first lumps **12** in the first slots **14**, and exhaust gaps are reserved between the first lumps **12** and the first slots **14**. Of course, the lower lampshade **2** may be threadedly mounted at the bottom of the lens lampshade **3**.

(19) Further, as for the detachable assembly between the tube **4** and the lower lampshade **2**, second lumps **15** are arranged along an end opening of the tube **4**, a second socket **16** allowing the end opening of the tube **4** to be inserted therein is arranged at the bottom of the lower lampshade, L-shaped second slots **17** are formed in the wall of the second socket **16**, and the end opening of the tube **4** is inserted into the second socket **16** and is rotated to lock the second lumps **15** in the second slots **17**. Of course, the tube **4** and the lower lampshade **2** may be threadedly assembled.

(20) Further, as for the structure of the tube **4**, the tube **5** comprises two semi-cylinders **41**, one ends of the semi-cylinders **41** are connected by means of a bent portion **42**, the other ends of the semi-cylinders **41** are connected by means of hasps **43**, lower ends of the semi-cylinders **41** are sleeved with a cover **44**, receding holes **45** are formed in positions, corresponding to the water holes **10**, of the cover **44**, and the bent portion **42** may be formed directly by thinning a flexible material such as plastic.

(21) Further, the disinfection lamp in this embodiment may also function as an underwater temperature gauge, and in this case, the disinfection lamp further comprises a water temperature probe **102**, which may be mounted in various ways. Specifically, the water temperature probe **102** is mounted on the lens lampshade **3** or detachably mounted on the lens lampshade **3** or the lower lampshade **2**. A display screen **103** for displaying the temperature value is inlaid in the upper lampshade **1**, the upper lampshade corresponding to the display screen is transparent, and the water temperature probe **102** and the display screen **103** are electrically connected to the circuit board **5**. In this way, the temperature of water can be detected in real time by means of the water temperature probe **102** stretching into water and displayed by the display screen **103**. The principle of the water temperature probe **102** is based on the detection principle of an NTC temperature sensor, which is a conventional principle and will not be detailed in this embodiment.

(22) In specific use, there are the following cases for the water temperature probe:

(23) First, as shown in FIG. **3**, in a case where the water temperature probe **102** is fixedly mounted on the lens lampshade **3**, a probe portion of the water temperature probe **102** is arranged at the bottom of the lens lampshade **3** and located in the lower lampshade **2**.

(24) Second, in a case where the water temperature probe **102** is detachably mounted on the lens lampshade **3**, the water temperature probe **102** is connected to a first connecting base **104** mounted in the first socket **13**.

(25) Third, in a case where the water temperature probe **102** is detachably mounted in the lower lampshade **2**, the water temperature probe **102** is connected to a second connecting base **105** mounted in the second socket **16**.

(26) Wherein, third lumps **106** are arranged on the periphery of the first connecting base **104** and the periphery of the second connecting base **105**, and by rotation, the third lumps **106** on the first connecting base **104** are respectively clamped in the first slots **14**, and the third lumps **106** on the second connecting base **105** are clamped in the second slots **17**. Of course, in a case where the first connecting base **104** and the second connecting base **105** are respectively mounted in the first socket **13** and the second socket **16**, the lower lampshade **2** or the tube **4** that is originally mounted here should be detached, correspondingly. By means of detachable assembly, the water temperature

probe **102** may be electrically connected to the circuit board **5** by means of a waterproof plug. Of course, this is not the unique connection method, other connection methods may be adopted as long as pluggable and waterproof connection between the water temperature probe **102** and the circuit board **5** can be realized, and this embodiment has no limitation in this aspect. The first connecting base and the second connecting base may be detachably assembled by means of threads.

(27) Moreover, in this embodiment, a mounting rod **107** is hinged to each of the first connecting base **104** and the second connecting base **105**, a mounting groove (not shown) for fixing and mounting the water temperature probe **102** is formed in the mounting rod **107**, the water temperature probe **102** is fixed and mounted in the mounting groove, and the probe portion of the water temperature probe **102** is arranged outside the mounting groove. A receiving groove **108** is formed in a position, corresponding to the mounting rod **107**, of each of the first connecting base **104** and the second connecting base **105**, the water temperature probe **102** is rotated to be received in the receiving groove **108**, and a grip portion **109** to be held by users is arranged on the end surface of the mounting rod **107**. In this way, the water temperature probe **102** can be stored and protected; when rotated to be unfolded, the water temperature probe **102** can stretch deeper in water, such that the water temperature detected by the water temperature probe **102** is closer to the actual water temperature.

(28) In addition, the whole disinfection lamp may be controlled by keys or an infrared remote control, and this embodiment has no limitation in this aspect.

(29) The above embodiments are merely preferred ones of the invention and are not intended to limit the patent scope of the invention. All equivalent structures or flow transformations made according to the description and the accompanying drawings, or direct or indirect applications to other related technical fields should also fall within the patent protection scope of the invention.

Claims

1. A disinfection device for swimming pool water comprising: a disinfection lamp including: an upper lampshade (**1**); a lower lampshade (**2**); a lens lampshade (**3**); a tube (**4**) capable of holding sustained release chlorine tablets, detachably mounted to a bottom of the lower lampshade (**2**), water holes (**1**) are formed in the tube (**4**) and the lower lampshade (**3**), for placing swimming pool water in fluid communication with any sustained release chlorine tablets within the tube (**4**); a circuit board (**5**) and a battery (**6**) electrically connected to the circuit board (**5**) are mounted on the lens lampshade (**3**); a solar panel (**7**) is mounted on a top surface of the upper lampshade (**1**) and electrically connected to the circuit board (**5**); a light diffuser (**9**) is arranged at a bottom of the lens lampshade (**3**); a first light bead (**8**) is arranged on a lower surface of the circuit board (**5**) and within the light diffuser (**9**); an exhaust gap disposed between the lower lampshade (**2**) and the lens lampshade (**3**); wherein, the upper lampshade (**1**) covers the lens lampshade (**3**) and is sealingly connected to the lens lampshade (**3**); and wherein, the lower lampshade (**2**) is mounted at the bottom of the lens lampshade (**3**) and wraps around the light diffuser (**9**).
2. The disinfection device for swimming pool water of claim 1, further comprising: a reflection cup (**101**) is arranged upside down in the lower lampshade (**2**) and located below the light diffuser (**9**), and an outer end surface of the reflection cup (**101**) is a reflecting surface, such that light refracted out of the light diffuser is reflected by the reflection cup and diffused around.
3. The disinfection device for swimming pool water of claim 1, further comprising: a second light bead is arranged on the circuit board and faces the upper lampshade; the lower lampshade is a scutate light diffuser, and a diamond pattern is arranged on the surface of the upper lampshade; the first light bead and the second light bead includes colored RGB light beads.
4. The disinfection device for swimming pool water of claim 1, wherein, foam (**100**) is mounted around the lens lampshade (**3**) promoting buoyancy.
5. The disinfection device for swimming pool water of claim 1, wherein first lumps (**12**) are

arranged along an opening of the lower lampshade, a first socket (13) allowing the opening of the lower lampshade to be inserted therein, is arranged at the bottom of the lens lampshade, L-shaped first slots (14) are formed in a wall of the first socket, the opening of the lower lampshade is inserted into the first socket (13) and is rotated to lock the first lumps (12) in the first slots (14), and exhaust gaps are disposed between the first lumps and the first slots.

6. The disinfection device for swimming pool water of claim 1, wherein second lumps (15) are arranged along an end opening of the tube, a second socket (16) allowing the end opening of the tube to be inserted therein, is arranged at the bottom of the lower lampshade, L-shaped second slots (17) are formed in a wall of the second socket, and the end opening of the tube is inserted into the second socket and is rotated to lock the second lumps in the second slots.

7. The disinfection device for swimming pool water of claim 6, wherein the tube (4) comprises two semi-cylinders, one end of the semi-cylinders are connected by means of a bent portion, and the other end of the semi-cylinders are connected by means of hasps; lower ends of the semi-cylinders are sleeved with a cover, and receding holes are formed in positions, corresponding to the water holes, of the cover.

8. The disinfection device for swimming pool water of claim 7, further comprising: a water temperature probe (102), wherein the water temperature probe is mounted on the lens lampshade or detachably mounted on the lens lampshade or the lower lampshade, a display screen (103) for displaying a temperature value is inlaid in the upper lampshade, which is transparent, and the water temperature probe and the display screen are electrically connected to the circuit board.

9. The disinfection device for swimming pool water of claim 8, wherein: when the water temperature probe is fixedly mounted on the lens lampshade, a probe portion of the water temperature probe is arranged at the bottom of the lens lampshade and located in the lower lampshade; when the water temperature probe is detachably mounted on the lens lampshade, the water temperature probe is connected to a first connecting base mounted in the first socket; when the water temperature probe is detachably mounted in the lower lampshade, the water temperature probe is connected to a second connecting base mounted in the second socket.

10. The disinfection device for swimming pool water of claim 9, wherein, third lumps (106) are arranged on a periphery of the first connecting base and a periphery of the second connecting base, and by rotation, the third lumps on the first connecting base are respectively clamped in the first slots, and the third lumps on the second connecting base are clamped in the second slots.

11. The disinfection device for swimming pool water of claim 10, wherein a mounting rod is hinged to each of the first connecting base and the second connecting base, a mounting groove for fixing and mounting the water temperature probe is formed in the mounting rod, the water temperature probe is fixed and mounted in the mounting groove, and the probe portion of the water temperature probe is arranged outside the mounting groove; a receiving groove is formed in a position, corresponding to the mounting rod, of each of the first connecting base and the second connecting base, the water temperature probe is rotated to be received in the receiving groove, and a grip portion to be held by users is arranged on an end surface of the mounting rod.
