

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402911
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Pett; Daniel

Aspiration apparatus for intraosseous access system

Abstract

Embodiments disclosed herein are directed to an intraosseous access system configured to confirm access to a medullary cavity. The system includes a driver housing, an access system including a drive train, a needle assembly rotatably coupled to the access system, and an aspiration system. The needle assembly can include a needle defining a lumen and an obturator disposed therein. The aspiration system can include a syringe or a vacutainer, coupled to the obturator. Sliding one of a plunger or a vacutainer proximally can withdraw the obturator from the needle lumen and place a vacuum in fluid communication with the needle lumen to draw a fluid flow therethrough. A portion of the aspiration system can rotate along with the needle assembly. Withdrawing the obturator can place the obturator within the syringe or the vacutainer mitigating needle stick injuries. If the medullary cavity has not been accessed, the obturator can be replaced.

Inventors:	Pett; Daniel (Sandy, UT)
Applicant:	Bard Access Systems, Inc. (Salt Lake City, UT)
Family ID:	78078402
Assignee:	Bard Access Systems, Inc. (Salt Lake City, UT)
Appl. No.:	17/469613
Filed:	September 08, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220071659 A1	Mar. 10, 2022

Related U.S. Application Data

us-provisional-application US 63076189 20200909

Publication Classification

Int. Cl.: A61B17/34 (20060101); A61B17/00 (20060101); A61B17/16 (20060101)

U.S. Cl.:

CPC A61B17/3472 (20130101); A61B17/1628 (20130101); A61B17/164 (20130101); A61B2017/00477 (20130101); A61B2217/005 (20130101)

Field of Classification Search

CPC: A61B (17/3472); A61B (17/1628); A61B (17/164); A61N (2017/00477); A61N (2217/005)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2773501	12/1955	Young	N/A	N/A
3071135	12/1962	Baldwin et al.	N/A	N/A
3261594	12/1965	Michel	366/202	B01F 31/201
3734207	12/1972	Fishbein	173/217	A61B 17/1622
3753432	12/1972	Guerra	600/577	A61B 5/154
3804544	12/1973	Adams	N/A	N/A
3811442	12/1973	Maroth	604/188	A61M 5/20
3815605	12/1973	Schmidt et al.	N/A	N/A
3991765	12/1975	Cohen	N/A	N/A
4266555	12/1980	Jamshidi	N/A	N/A
4314565	12/1981	Lee	N/A	N/A
4342724	12/1981	Narra	422/918	B01L 3/5021
4381777	12/1982	Garnier	604/188	A61M 5/20
4383530	12/1982	Bruno	N/A	N/A
4562844	12/1985	Carpenter	604/220	A61B 5/150244
4736742	12/1987	Alexson et al.	N/A	N/A
4787893	12/1987	Villette	604/188	A61C 19/08
4889529	12/1988	Haindl	N/A	N/A
4952207	12/1989	Lemieux	N/A	N/A
4964854	12/1989	Luther	N/A	N/A
4969870	12/1989	Kramer et al.	N/A	N/A
5040542	12/1990	Gray	N/A	N/A
5042558	12/1990	Hussey et al.	N/A	N/A
5053017	12/1990	Chamuel	N/A	N/A
5122114	12/1991	Miller et al.	N/A	N/A
5207697	12/1992	Carusillo et al.	N/A	N/A
5263939	12/1992	Wortrich	N/A	N/A
5290267	12/1993	Zimmermann	N/A	N/A
5312364	12/1993	Jacobs	N/A	N/A

5332398	12/1993	Miller et al.	N/A	N/A
5364367	12/1993	Banks et al.	N/A	N/A
5372583	12/1993	Roberts et al.	N/A	N/A
5384103	12/1994	Miller	206/508	A61L 2/26
5406940	12/1994	Melzer et al.	N/A	N/A
5451210	12/1994	Kramer et al.	N/A	N/A
5554154	12/1995	Rosenberg	N/A	N/A
5573358	12/1995	Gobbers et al.	N/A	N/A
5575780	12/1995	Saito	N/A	N/A
5591188	12/1996	Waisman	N/A	N/A
5601559	12/1996	Melker et al.	N/A	N/A
5667509	12/1996	Westin	N/A	N/A
5688249	12/1996	Chang et al.	N/A	N/A
5694019	12/1996	Uchida et al.	N/A	N/A
5779708	12/1997	Wu	N/A	N/A
5817052	12/1997	Johnson et al.	N/A	N/A
5853393	12/1997	Bogert	N/A	N/A
5868711	12/1998	Kramer et al.	N/A	N/A
5885293	12/1998	McDevitt	N/A	N/A
5927976	12/1998	Wu	N/A	N/A
5960797	12/1998	Kramer et al.	N/A	N/A
5967143	12/1998	Klappenberger	N/A	N/A
6018227	12/1999	Kumar et al.	N/A	N/A
6056165	12/1999	Speranza	222/326	B05C 17/0103
6104162	12/1999	Sainsbury et al.	N/A	N/A
6117108	12/1999	Woehr et al.	N/A	N/A
6135769	12/1999	Kwan	N/A	N/A
6159161	12/1999	Hodosh	600/561	A61M 5/20
6199664	12/2000	Tkaczyk et al.	N/A	N/A
6210373	12/2000	Allmon	N/A	N/A
6228088	12/2000	Miller et al.	N/A	N/A
6247928	12/2000	Meller et al.	N/A	N/A
6270484	12/2000	Yoon	N/A	N/A
6273715	12/2000	Meller et al.	N/A	N/A
6419490	12/2001	Kitchings Weathers, Jr.	N/A	N/A
6458117	12/2001	Pollins, Sr.	N/A	N/A
6527778	12/2002	Athanasiou et al.	N/A	N/A
6547561	12/2002	Meller	433/80	A61C 1/081
6602214	12/2002	Heinz et al.	N/A	N/A
6626887	12/2002	Wu	N/A	N/A
6629959	12/2002	Kuracina et al.	N/A	N/A
6641395	12/2002	Kumar et al.	N/A	N/A
6652490	12/2002	Howell	N/A	N/A
6692471	12/2003	Boudreaux	N/A	N/A
6715969	12/2003	Eriksen	N/A	N/A
6761726	12/2003	Findlay et al.	N/A	N/A
6814734	12/2003	Chappuis et al.	N/A	N/A
6830562	12/2003	Mogensen et al.	N/A	N/A

6875219	12/2004	Arramon et al.	N/A	N/A
6905486	12/2004	Gibbs	N/A	N/A
6916292	12/2004	Morawski et al.	N/A	N/A
6984213	12/2005	Horner et al.	N/A	N/A
6997907	12/2005	Safabash et al.	N/A	N/A
7112191	12/2005	Daga	N/A	N/A
7135031	12/2005	Flint	N/A	N/A
7214208	12/2006	Vaillancourt et al.	N/A	N/A
7347838	12/2007	Kulli	N/A	N/A
7347840	12/2007	Findlay et al.	N/A	N/A
7407493	12/2007	Cane'	N/A	N/A
7458954	12/2007	Ferguson et al.	N/A	N/A
7513888	12/2008	Sircom et al.	N/A	N/A
7530965	12/2008	Villa et al.	N/A	N/A
7534227	12/2008	Kulli	N/A	N/A
7569033	12/2008	Greene et al.	N/A	N/A
7582102	12/2008	Heinz et al.	N/A	N/A
7588559	12/2008	Aravena et al.	N/A	N/A
7658725	12/2009	Bialecki et al.	N/A	N/A
7670328	12/2009	Miller	N/A	N/A
7699807	12/2009	Faust et al.	N/A	N/A
7699850	12/2009	Miller	N/A	N/A
7736332	12/2009	Carlyon et al.	N/A	N/A
7749225	12/2009	Chappuis et al.	N/A	N/A
7798994	12/2009	Brimhall	N/A	N/A
7811260	12/2009	Miller	604/188	A61M 5/1454
7815642	12/2009	Miller	N/A	N/A
7828774	12/2009	Harding et al.	N/A	N/A
7833204	12/2009	Picha	N/A	N/A
7842038	12/2009	Haddock et al.	N/A	N/A
7850620	12/2009	Miller	600/568	A61B 50/33
7850650	12/2009	Breitweiser	N/A	N/A
D633199	12/2010	MacKay et al.	N/A	N/A
7899528	12/2010	Miller et al.	N/A	N/A
7905857	12/2010	Swisher	N/A	N/A
7951089	12/2010	Miller	600/568	A61B 17/3476
7955297	12/2010	Radmer et al.	N/A	N/A
7972339	12/2010	Nassiri et al.	N/A	N/A
7976502	12/2010	Baid	N/A	N/A
8038038	12/2010	Hillhouse	185/39	B05B 11/1095
8038664	12/2010	Miller et al.	N/A	N/A
8043253	12/2010	Kraft et al.	N/A	N/A
8043265	12/2010	Abe et al.	N/A	N/A
8142365	12/2011	Miller	N/A	N/A
8152771	12/2011	Mogensen et al.	N/A	N/A
8162904	12/2011	Takano et al.	N/A	N/A
8167899	12/2011	Justis et al.	N/A	N/A
8221398	12/2011	Isobe et al.	N/A	N/A

8235945	12/2011	Baid	N/A	N/A
8246584	12/2011	Aravena et al.	N/A	N/A
8273053	12/2011	Saltzstein	N/A	N/A
8292891	12/2011	Browne et al.	N/A	N/A
8308693	12/2011	Miller et al.	N/A	N/A
8333769	12/2011	Browne et al.	N/A	N/A
8356598	12/2012	Rumsey	N/A	N/A
8357163	12/2012	Sidebotham et al.	N/A	N/A
8388541	12/2012	Messerly et al.	N/A	N/A
8388623	12/2012	Browne et al.	N/A	N/A
8414539	12/2012	Kuracina et al.	N/A	N/A
8419683	12/2012	Miller et al.	N/A	N/A
8480632	12/2012	Miller et al.	N/A	N/A
8480672	12/2012	Browne et al.	N/A	N/A
8486027	12/2012	Findlay et al.	N/A	N/A
8506568	12/2012	Miller	N/A	N/A
8535271	12/2012	Fuchs et al.	N/A	N/A
8562615	12/2012	Browne et al.	N/A	N/A
8641715	12/2013	Miller	N/A	N/A
8647257	12/2013	Jansen et al.	N/A	N/A
8656929	12/2013	Miller et al.	N/A	N/A
8657790	12/2013	Tal et al.	N/A	N/A
8663231	12/2013	Browne et al.	N/A	N/A
8668698	12/2013	Miller et al.	N/A	N/A
8684978	12/2013	Miller et al.	N/A	N/A
8690791	12/2013	Miller	N/A	N/A
8715287	12/2013	Miller	N/A	N/A
8771230	12/2013	White et al.	N/A	N/A
8781555	12/2013	Burnside et al.	N/A	N/A
8801663	12/2013	Woehr	N/A	N/A
8812101	12/2013	Miller et al.	N/A	N/A
8814835	12/2013	Baid	N/A	N/A
8821493	12/2013	Anderson	N/A	N/A
8828001	12/2013	Stearns et al.	N/A	N/A
8849382	12/2013	Cox et al.	N/A	N/A
8870872	12/2013	Miller	N/A	N/A
8894654	12/2013	Anderson	N/A	N/A
8936575	12/2014	Moulton	N/A	N/A
8944069	12/2014	Miller et al.	N/A	N/A
8974410	12/2014	Miller et al.	N/A	N/A
8998848	12/2014	Miller et al.	N/A	N/A
9072543	12/2014	Miller et al.	N/A	N/A
9078637	12/2014	Miller	N/A	N/A
9149625	12/2014	Woehr et al.	N/A	N/A
9173679	12/2014	Tzachar et al.	N/A	N/A
9226756	12/2015	Teisen et al.	N/A	N/A
9278195	12/2015	Erskine	N/A	N/A
9295487	12/2015	Miller et al.	N/A	N/A
9302077	12/2015	Domonkos et al.	N/A	N/A
9314232	12/2015	Stark	N/A	N/A

9314270	12/2015	Miller	N/A	N/A
9358348	12/2015	Weilbacher et al.	N/A	N/A
9393031	12/2015	Miller	N/A	N/A
9414815	12/2015	Miller et al.	N/A	N/A
9415192	12/2015	Kuracina et al.	N/A	N/A
9421345	12/2015	Woehr et al.	N/A	N/A
9427555	12/2015	Baid	N/A	N/A
9433400	12/2015	Miller	N/A	N/A
9439667	12/2015	Miller	N/A	N/A
9439702	12/2015	Arthur et al.	N/A	N/A
9445743	12/2015	Kassab	N/A	N/A
9451968	12/2015	Miller et al.	N/A	N/A
9451983	12/2015	Windolf	N/A	N/A
9456766	12/2015	Cox et al.	N/A	N/A
9480483	12/2015	Browne et al.	N/A	N/A
9492097	12/2015	Wilkes et al.	N/A	N/A
9504477	12/2015	Miller et al.	N/A	N/A
9521961	12/2015	Silverstein et al.	N/A	N/A
9545243	12/2016	Miller et al.	N/A	N/A
9554716	12/2016	Burnside et al.	N/A	N/A
9615816	12/2016	Woodard	N/A	N/A
9615838	12/2016	Nino et al.	N/A	N/A
9623210	12/2016	Woehr	N/A	N/A
9636031	12/2016	Cox	N/A	N/A
9636484	12/2016	Baid	N/A	N/A
9649048	12/2016	Cox et al.	N/A	N/A
9681889	12/2016	Greenhalgh et al.	N/A	N/A
9687633	12/2016	Teoh	N/A	N/A
9717564	12/2016	Miller et al.	N/A	N/A
9730729	12/2016	Kilcoin et al.	N/A	N/A
9782546	12/2016	Woehr	N/A	N/A
9839740	12/2016	Beamer et al.	N/A	N/A
9844646	12/2016	Knutsson	N/A	N/A
9844647	12/2016	Knutsson	N/A	N/A
9872703	12/2017	Miller et al.	N/A	N/A
9883853	12/2017	Woodard et al.	N/A	N/A
9895512	12/2017	Kraft et al.	N/A	N/A
9962211	12/2017	Csernaton	N/A	N/A
10052111	12/2017	Miller et al.	N/A	N/A
10092320	12/2017	Morgan et al.	N/A	N/A
10092706	12/2017	Denzer	N/A	A61M 5/50
10159531	12/2017	Misener et al.	N/A	N/A
10172538	12/2018	Kassab	N/A	N/A
10413211	12/2018	Kassab	N/A	N/A
10449330	12/2018	Newman et al.	N/A	N/A
D898908	12/2019	Denzer	D24/127	N/A
10893887	12/2020	Blanchard	N/A	N/A
10973532	12/2020	Miller	N/A	A61B 10/025
10973545	12/2020	Miller	N/A	A61B 17/3474

10980522	12/2020	Muse	N/A	N/A
11298202	12/2021	Miller	N/A	A61B 10/025
11446112	12/2021	Fink	N/A	A61M 5/427
11896264	12/2023	Lindekugel et al.	N/A	N/A
11925361	12/2023	Pett et al.	N/A	N/A
12274469	12/2024	Pett	N/A	A61B 17/3472
2003/0060781	12/2002	Mogensen et al.	N/A	N/A
2003/0225344	12/2002	Miller	N/A	N/A
2003/0225411	12/2002	Miller	N/A	N/A
2003/0229308	12/2002	Tsals et al.	N/A	N/A
2004/0010236	12/2003	Morawski	604/272	A61B 10/025
2004/0059317	12/2003	Hermann	N/A	N/A
2004/0220497	12/2003	Findlay et al.	N/A	N/A
2004/0243135	12/2003	Koseki	N/A	N/A
2005/0035014	12/2004	Cane	N/A	N/A
2005/0101912	12/2004	Faust et al.	N/A	N/A
2005/0113866	12/2004	Heinz et al.	N/A	N/A
2005/0131345	12/2004	Miller	N/A	N/A
2005/0165403	12/2004	Miller	N/A	N/A
2006/0015066	12/2005	Turieto et al.	N/A	N/A
2006/0020191	12/2005	Brister	600/345	A61B 5/14532
2006/0025723	12/2005	Ballarini	N/A	N/A
2006/0058826	12/2005	Evans et al.	N/A	N/A
2006/0147283	12/2005	Phillips	N/A	N/A
2007/0049945	12/2006	Miller	N/A	N/A
2007/0096690	12/2006	Casalena et al.	N/A	N/A
2007/0098507	12/2006	Whitehead	N/A	N/A
2007/0151116	12/2006	Malandain	33/512	A61B 17/0218
2007/0191772	12/2006	Wojcik	N/A	N/A
2007/0270775	12/2006	Miller et al.	N/A	N/A
2007/0276352	12/2006	Crocker et al.	N/A	N/A
2007/0282344	12/2006	Yedlicka et al.	N/A	N/A
2008/0015467	12/2007	Miller	600/568	A61B 17/3476
2008/0154304	12/2007	Crawford et al.	N/A	N/A
2008/0208136	12/2007	Findlay et al.	N/A	N/A
2008/0215056	12/2007	Miller et al.	N/A	N/A
2008/0221580	12/2007	Miller et al.	N/A	N/A
2008/0257359	12/2007	Rumsey	N/A	N/A
2009/0000292	12/2008	Schifferer	702/41	B66F 17/003
2009/0022557	12/2008	Whitehead	N/A	N/A
2009/0048575	12/2008	Waters	N/A	N/A
2009/0054808	12/2008	Miller	N/A	N/A
2009/0093830	12/2008	Miller	N/A	N/A
2009/0194446	12/2008	Miller et al.	N/A	N/A
2009/0204024	12/2008	Miller	N/A	N/A
2009/0306697	12/2008	Fischvogt	N/A	N/A

2010/0004606	12/2009	Hansen et al.	N/A	N/A
2010/0174243	12/2009	McKay	N/A	N/A
2010/0202842	12/2009	Whitehead et al.	N/A	N/A
2010/0204649	12/2009	Miller et al.	N/A	N/A
2010/0286607	12/2009	Saltzstein	N/A	N/A
2010/0298830	12/2009	Browne et al.	N/A	N/A
2010/0298831	12/2009	Browne et al.	N/A	N/A
2010/0312246	12/2009	Browne et al.	N/A	N/A
2011/0004163	12/2010	Vaidya	N/A	N/A
2011/0028976	12/2010	Miller	N/A	N/A
2011/0202065	12/2010	Takizawa et al.	N/A	N/A
2012/0116390	12/2011	Madan	606/41	A61B 50/30
2012/0116394	12/2011	Timm	606/41	G16H 20/40
2012/0202180	12/2011	Stock et al.	N/A	N/A
2012/0203154	12/2011	Tzachar	N/A	N/A
2012/0274280	12/2011	Yip et al.	N/A	N/A
2013/0030439	12/2012	Browne et al.	N/A	N/A
2013/0041345	12/2012	Kilcoin et al.	N/A	N/A
2013/0072938	12/2012	Browne et al.	N/A	N/A
2013/0102924	12/2012	Findlay et al.	N/A	N/A
2013/0158484	12/2012	Browne et al.	N/A	N/A
2013/0178807	12/2012	Baid	N/A	N/A
2014/0031674	12/2013	Newman et al.	N/A	N/A
2014/0031794	12/2013	Windolf	N/A	N/A
2014/0039400	12/2013	Browne et al.	N/A	N/A
2014/0081281	12/2013	Felder	N/A	N/A
2014/0142577	12/2013	Miller	N/A	N/A
2014/0171873	12/2013	Mark	N/A	N/A
2014/0188133	12/2013	Misener	N/A	N/A
2014/0221970	12/2013	Eaton	141/2	A61M 5/3202
2014/0262408	12/2013	Woodard	N/A	N/A
2014/0262880	12/2013	Yoon	N/A	N/A
2014/0276205	12/2013	Miller et al.	N/A	N/A
2014/0276206	12/2013	Woodward et al.	N/A	N/A
2014/0276471	12/2013	Emery et al.	N/A	N/A
2014/0276833	12/2013	Larsen et al.	N/A	N/A
2014/0276839	12/2013	Forman et al.	N/A	N/A
2014/0343454	12/2013	Miller et al.	N/A	N/A
2014/0343497	12/2013	Baid	N/A	N/A
2015/0011941	12/2014	Saeki	N/A	N/A
2015/0025311	12/2014	Kadan	600/104	A61B 17/3474
2015/0045732	12/2014	Murphy et al.	N/A	N/A
2015/0080762	12/2014	Kassab et al.	N/A	N/A
2015/0126931	12/2014	Holm et al.	N/A	N/A
2015/0196737	12/2014	Baid	N/A	N/A
2015/0223786	12/2014	Morgan et al.	N/A	N/A
2015/0230823	12/2014	Morgan et al.	N/A	N/A
2015/0238733	12/2014	bin Abdulla	N/A	N/A
2015/0342615	12/2014	Keinan et al.	N/A	N/A

2015/0342756	12/2014	Bays et al.	N/A	N/A
2015/0351797	12/2014	Miller et al.	N/A	N/A
2015/0366569	12/2014	Miller	N/A	N/A
2015/0367487	12/2014	Nino et al.	N/A	N/A
2016/0009812	12/2015	Satelli	424/1.49	A61P 35/00
2016/0022282	12/2015	Miller et al.	N/A	N/A
2016/0022284	12/2015	Lele et al.	N/A	N/A
2016/0039916	12/2015	Jiang	435/254.11	A61P 25/28
2016/0058432	12/2015	Miller	N/A	N/A
2016/0066954	12/2015	Miller et al.	N/A	N/A
2016/0136410	12/2015	Aklog et al.	N/A	N/A
2016/0183974	12/2015	Miller	N/A	N/A
2016/0184509	12/2015	Miller et al.	N/A	N/A
2016/0235949	12/2015	Baid	N/A	N/A
2016/0305497	12/2015	Victor et al.	N/A	N/A
2016/0354539	12/2015	Tan et al.	N/A	N/A
2016/0361519	12/2015	Teoh et al.	N/A	N/A
2017/0020533	12/2016	Browne	N/A	A61M 5/158
2017/0020560	12/2016	Van Citters et al.	N/A	N/A
2017/0021138	12/2016	Sokolski	N/A	N/A
2017/0043135	12/2016	Knutsson	N/A	N/A
2017/0105763	12/2016	Karve et al.	N/A	N/A
2017/0136217	12/2016	Riesenberger et al.	N/A	N/A
2017/0151419	12/2016	Sonksen	N/A	N/A
2017/0156740	12/2016	Stark	N/A	N/A
2017/0156751	12/2016	Csernaton	N/A	N/A
2017/0209129	12/2016	Fagundes et al.	N/A	N/A
2017/0231644	12/2016	Anderson	N/A	N/A
2017/0303962	12/2016	Browne et al.	N/A	N/A
2017/0303963	12/2016	Kilcoin et al.	N/A	N/A
2018/0049772	12/2017	Brockman et al.	N/A	N/A
2018/0092662	12/2017	Rioux et al.	N/A	N/A
2018/0116551	12/2017	Newman et al.	N/A	N/A
2018/0116642	12/2017	Woodard et al.	N/A	N/A
2018/0116693	12/2017	Blanchard et al.	N/A	N/A
2018/0117262	12/2017	Islam	N/A	N/A
2018/0125465	12/2017	Muse et al.	N/A	N/A
2018/0153474	12/2017	Aeschlimann et al.	N/A	N/A
2018/0154112	12/2017	Chan et al.	N/A	N/A
2018/0221003	12/2017	Hibner et al.	N/A	N/A
2018/0228509	12/2017	Fojtik	N/A	A61B 17/3472
2018/0242982	12/2017	Laughlin et al.	N/A	N/A
2019/0009398	12/2018	Zhong et al.	N/A	N/A
2019/0030701	12/2018	Duggan	N/A	N/A
2019/0059986	12/2018	Shelton, IV et al.	N/A	N/A
2019/0069812	12/2018	Isaacson et al.	N/A	N/A
2019/0083753	12/2018	Chu	N/A	N/A
2019/0150954	12/2018	Xie	N/A	N/A
2019/0175220	12/2018	Coppedge et al.	N/A	N/A

2019/0282244	12/2018	Muse	N/A	N/A
2020/0054347	12/2019	Coppedge	N/A	A61B 17/1628
2020/0054410	12/2019	Pfotenhauer et al.	N/A	N/A
2020/0113584	12/2019	McGinley	N/A	A61B 17/1622
2020/0129186	12/2019	Miller et al.	N/A	N/A
2020/0197121	12/2019	Morey et al.	N/A	N/A
2020/0297382	12/2019	Coppedge	N/A	A61B 17/3472
2020/0297452	12/2019	Coppedge	N/A	A61B 17/1622
2020/0337782	12/2019	Glassman et al.	N/A	N/A
2021/0015529	12/2020	Fenton, Jr.	N/A	A61B 17/8847
2021/0093357	12/2020	Pett et al.	N/A	N/A
2021/0093358	12/2020	Lindekugel et al.	N/A	N/A
2021/0113251	12/2020	Vogt	N/A	A61M 5/16881
2021/0282812	12/2020	Tierney et al.	N/A	N/A
2021/0322055	12/2020	Lindekugel et al.	N/A	N/A
2021/0375445	12/2020	Lindekugel	N/A	H04W 4/38
2021/0393337	12/2020	Zucker	N/A	G01L 5/26
2022/0240976	12/2021	Pett et al.	N/A	N/A
2022/0249104	12/2021	Pett et al.	N/A	N/A
2022/0273338	12/2021	Eisenthal	N/A	A61B 17/3403
2023/0106545	12/2022	Pett et al.	N/A	N/A
2023/0285049	12/2022	Howell	N/A	N/A
2023/0414251	12/2022	Pett	N/A	A61B 17/1624
2024/0058036	12/2023	Lindekugel	N/A	A61B 10/025
2024/0206887	12/2023	Pett	N/A	H02J 7/0042
2024/0261554	12/2023	Akerele-Ale	N/A	A61M 39/0247
2024/0277375	12/2023	Lindekugel	N/A	A61B 17/3472
2025/0120743	12/2024	Pett et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108742795	12/2017	CN	N/A
110547847	12/2018	CN	N/A
0923961	12/1998	EP	N/A
3687024	12/2019	EP	N/A
2390297	12/2011	ES	N/A
2581548	12/1985	FR	N/A
2018509969	12/2017	JP	N/A
20090006621	12/2008	KR	N/A

1997024151	12/1996	WO	N/A
1998052638	12/1998	WO	N/A
2005/046769	12/2004	WO	N/A
05041790	12/2004	WO	N/A
2005053506	12/2004	WO	N/A
2005072625	12/2004	WO	N/A
2007018809	12/2006	WO	N/A
2008002961	12/2007	WO	N/A
2008016757	12/2007	WO	N/A
2008033871	12/2007	WO	N/A
2008033872	12/2007	WO	N/A
2008033873	12/2007	WO	N/A
2008033874	12/2007	WO	N/A
2008054894	12/2007	WO	N/A
2008086258	12/2007	WO	N/A
2008124206	12/2007	WO	N/A
2008124463	12/2007	WO	N/A
2008130893	12/2007	WO	N/A
2008134355	12/2007	WO	N/A
2008144379	12/2007	WO	N/A
2009070896	12/2008	WO	N/A
2010043043	12/2009	WO	N/A
2011070593	12/2010	WO	N/A
2011097311	12/2010	WO	N/A
2011139294	12/2010	WO	N/A
2013003885	12/2012	WO	N/A
2013009901	12/2012	WO	N/A
2013173360	12/2012	WO	N/A
2014075165	12/2013	WO	N/A
2014142948	12/2013	WO	N/A
2014144239	12/2013	WO	N/A
2014144262	12/2013	WO	N/A
2014144489	12/2013	WO	N/A
2014144757	12/2013	WO	N/A
2014144797	12/2013	WO	N/A
2015061370	12/2014	WO	N/A
2015/177612	12/2014	WO	N/A
2016033016	12/2015	WO	N/A
16053834	12/2015	WO	N/A
2016/085973	12/2015	WO	N/A
2016163939	12/2015	WO	N/A
18006045	12/2017	WO	N/A
2018025094	12/2017	WO	N/A
2018058036	12/2017	WO	N/A
2018075694	12/2017	WO	N/A
18098086	12/2017	WO	N/A
2018165334	12/2017	WO	N/A
2018165339	12/2017	WO	N/A
2019051343	12/2018	WO	N/A
2019/164990	12/2018	WO	N/A

2021/011795	12/2020	WO	N/A
2021/016122	12/2020	WO	N/A
2021/062385	12/2020	WO	N/A
2021062038	12/2020	WO	N/A
2021062394	12/2020	WO	N/A
2022/165232	12/2021	WO	N/A
2022170269	12/2021	WO	N/A
2023177634	12/2022	WO	N/A
2024163884	12/2023	WO	N/A

OTHER PUBLICATIONS

Ekchian Gregory James et al: "Quantitative Methods for In Vitro and In Vivo Characterization of Cell and Tissue Metabolism", Jun. 11, 2018, XP055839281, retrieved from the internet on Sep. 8, 2021 : URL: <https://dspace.mit.edu/bitstream/handle/1721.1/117890/1051211749-MIT.pdf?sequence=1&isAllowed=y>. cited by applicant

PCT/US2019/ 018828 filed Feb. 20, 2019 International Preliminary Report on Patentability dated Aug. 27, 2020. cited by applicant

PCT/US2019/ 018828 filed Feb. 20, 2019 International Search Report and Written Opinion dated Jun. 13, 2019. cited by applicant

PCT/US2020/ 053119 filed Sep. 28, 2020 International Search Report and Written Opinion dated Jan. 5, 2021. cited by applicant

PCT/US2020/052558 filed Sep. 24, 2020 International Search Report and Written Opinion dated Feb. 11, 2021. cited by applicant

PCT/US2020/053135 filed Sep. 28, 2020 International Search Report and Written Opinion dated Dec. 18, 2020. cited by applicant

PCT/US2021/ 035232 filed Jun. 1, 2021 International Search Report and Written Opinion dated Oct. 19, 2021. cited by applicant

PCT/US2021/028114 filed Apr. 20, 2021 International Search Report and Written Opinion dated Jul. 12, 2021. cited by applicant

PCT/US2021/035475 filed Jun. 2, 2021 International Search Report and Written Opinion dated Sep. 17, 2021. cited by applicant

EP 20867024.0 filed Apr. 21, 2022 Extended European Search Report dated Aug. 8, 2023. cited by applicant

EP 20868351.6 filed Apr. 21, 2022 Extended European Search Report dated Aug. 10, 2023. cited by applicant

U.S. Appl. No. 17/235,134, filed Apr. 20, 2021 Notice of Allowance dated Sep. 20, 2023. cited by applicant

U.S. Appl. No. 17/335,870, filed Jun. 1, 2021 Non-Final Office Action dated Nov. 15, 2023. cited by applicant

U.S. Appl. No. 17/337,100, filed Jun. 2, 2021 Final Office Action dated Nov. 21, 2023. cited by applicant

U.S. Appl. No. 17/667,291, filed Feb. 8, 2022 Non-Final Office Action dated Aug. 31, 2023. cited by applicant

U.S. Appl. No. 17/863,898, filed Jul. 13, 2022 Final Office Action dated Nov. 22, 2023. cited by applicant

PCT/US2021/ 046573 filed Aug. 18, 2021 International Search Report and Written Opinion dated Nov. 30, 2021. cited by applicant

PCT/US2021/ 047378 filed Aug. 24, 2021 International Search Report and Written Opinion dated Nov. 17, 2021. cited by applicant

PCT/US2021/ 048542 filed Aug. 31, 2021 International Search Report and Written Opinion dated

Dec. 9, 2021. cited by applicant
PCT/US2021/ 049475 filed Sep. 8, 2021 International Search Report and Written Opinion dated Dec. 9, 2021. cited by applicant
U.S. Appl. No. 17/031,650, filed Sep. 24, 2020 Notice of Allowance dated Oct. 12, 2022. cited by applicant
U.S. Appl. No. 17/035,272, filed Sep. 28, 2020 Non-Final Office Action dated Mar. 9, 2023. cited by applicant
U.S. Appl. No. 17/035,272, filed Sep. 28, 2020 Restriction Requirement dated Dec. 9, 2022. cited by applicant
U.S. Appl. No. 17/035,336, filed Sep. 28, 2020 Notice of Allowance dated Jan. 11, 2023. cited by applicant
U.S. Appl. No. 17/235,134, filed Apr. 20, 2021 Restriction Requirement dated Mar. 7, 2023. cited by applicant
U.S. Appl. No. 17/031,650, filed Sep. 24, 2020 Non-Final Office Action dated Jan. 19, 2022. cited by applicant
PCT/US2022/014391 filed Jan. 28, 2022 International Search Report and Written Opinion dated Apr. 14, 2022. cited by applicant
PCT/US2022/015686 filed Feb. 8, 2022 International Search Report and Written Opinion dated May 25, 2022. cited by applicant
U.S. Appl. No. 17/031,650, filed Sep. 24, 2020 Final Office Action dated Jul. 20, 2022. cited by applicant
U.S. Appl. No. 17/035,336, filed Sep. 28, 2020 Restriction Requirement dated Jul. 26, 2022. cited by applicant
EP 19757657.1 filed Sep. 18, 2020 Extended European Search Report dated Oct. 22, 2021. cited by applicant
EP 23166984.7 filed Apr. 6, 2023 Extended European Search Report dated Jul. 5, 2023. cited by applicant
PCT/US2023/015127 filed Mar. 13, 2023 International Search Report and Written Opinion dated Jun. 26, 2023. cited by applicant
U.S. Appl. No. 17/035,272, filed Sep. 28, 2020 Notice of Allowance dated Jul. 7, 2023. cited by applicant
U.S. Appl. No. 17/235,134, filed Apr. 20, 2021 Non-Final Office Action dated Jun. 27, 2023. cited by applicant
U.S. Appl. No. 17/335,370, filed Jun. 1, 2021 Restriction Requirement dated Jul. 25, 2023. cited by applicant
U.S. Appl. No. 17/337,100, filed Jun. 2, 2021 Non-Final Office Action dated Jun. 2, 2023. cited by applicant
U.S. Appl. No. 17/667,291, filed Feb. 8, 2022 Restriction Requirement dated May 31, 2023. cited by applicant
U.S. Appl. No. 17/405,692, filed Aug. 18, 2021 Non-Final Office Action dated Sep. 6, 2024. cited by applicant
U.S. Appl. No. 17/410,863, filed Aug. 24, 2021 Non-Final Office Action dated Sep. 5, 2024. cited by applicant
U.S. Appl. No. 17/463,324, filed Aug. 31, 2021 Non-Final Office Action dated Oct. 30, 2024. cited by applicant
U.S. Appl. No. 17/463,324, filed Aug. 31, 2021 Restriction Requirement dated Aug. 8, 2024. cited by applicant
U.S. Appl. No. 18/075,269, filed Dec. 5, 2022 Notice of Allowance dated Sep. 11, 2024. cited by applicant
U.S. Appl. No. 18/244,730, filed Sep. 11, 2023 Final Office Action dated Aug. 8, 2024. cited by

applicant
U.S. Appl. No. 18/244,730, filed Sep. 11, 2023 Notice of Allowance dated Oct. 24, 2024. cited by applicant
U.S. Appl. No. 18/385,056, filed Oct. 30, 2023 Notice of Allowance dated Aug. 29, 2024. cited by applicant
U.S. Appl. No. 17/335,870, filed Jun. 1, 2021 Final Office Action dated Mar. 26, 2024. cited by applicant
U.S. Appl. No. 17/337,100, filed Jun. 2, 2021 Notice of Allowance dated Jan. 24, 2024. cited by applicant
PCT/US2024/014241 filed Feb. 2, 2024 International Search Report and Written Opinion dated May 8, 2024. cited by applicant
U.S. Appl. No. 17/405,692, filed Aug. 18, 2021 Restriction Requirement dated May 10, 2024. cited by applicant
U.S. Appl. No. 18/075,269, filed Dec. 5, 2022 Non-Final Office Action dated Jun. 24, 2024. cited by applicant
U.S. Appl. No. 18/244,730, filed Sep. 11, 2023 Non-Final Office Action dated May 3, 2024. cited by applicant
U.S. Appl. No. 18/385,056, filed Oct. 30, 2023 Non-Final Office Action dated May 9, 2024. cited by applicant
U.S. Appl. No. 17/405,692, filed Aug. 18, 2021 Final Office Action dated Dec. 4, 2024. cited by applicant
U.S. Appl. No. 17/410,863, filed Aug. 24, 2021 Notice of Allowance dated Dec. 13, 2024. cited by applicant
U.S. Appl. No. 17/587,900, filed Jan. 28, 2022 Non-Final Office Action dated Nov. 14, 2024. cited by applicant
U.S. Appl. No. 18/599,077, filed Mar. 7, 2024 Non-Final Office Action dated Feb. 3, 2025. cited by applicant
U.S. Appl. No. 17/405,692, filed Aug. 18, 2021 Advisory Action dated Feb. 14, 2025. cited by applicant
U.S. Appl. No. 17/405,692, filed Aug. 18, 2021 Non-Final Office Action dated Apr. 10, 2025. cited by applicant
U.S. Appl. No. 17/463,324, filed Aug. 31, 2021 Final Office Action dated Feb. 18, 2025. cited by applicant
U.S. Appl. No. 17/587,900, filed Jan. 28, 2022 Final Office Action dated Apr. 17, 2025. cited by applicant
U.S. Appl. No. 18/599,077, filed Mar. 7, 2024 Notice of Allowance dated Apr. 16, 2025. cited by applicant

Primary Examiner: Price; Nathan R

Assistant Examiner: Igel; Mark A

Attorney, Agent or Firm: Rutan & Tucker LLP

Background/Summary

PRIORITY (1) This application claims the benefit of priority to U.S. Patent Application No. 63/076,189, filed Sep. 9, 2020, which is incorporated by reference in its entirety into this application.

BACKGROUND

(1) Intraosseous (IO) access systems are configured to access a medullary cavity of a bone by drilling an access needle through the dense bone cortex and into the medullary cavity. Some IO access systems include a powered drill, or similar device, configured to rotate a needle assembly at high rotational speeds to drill an access needle through the bone cortex. Detecting when the needle has accessed the medullary cavity can be challenging. For example, to confirm access to the medullary cavity, a user must disengage the drill from the needle assembly, withdraw the obturator from a lumen of the needle, attach a syringe to the access needle and aspirate the needle lumen to observe the presence of bone marrow. Failure to aspirate bone marrow may mean that the access needle has not fully accessed the medullary cavity and further drilling is required. However, with the needle assembly disengaged from the drill, and the obturator withdrawn from the needle lumen, the needle cannot be reused and the clinician must withdraw the needle, couple a new needle assembly to the drill, and continue drilling. Further, patency of the original access site may be lost during needle exchange.

(2) Disclosed herein are systems, apparatus and methods directed to address the foregoing problems.

SUMMARY

(3) Disclosed herein is an intraosseous access system including, a housing, a needle assembly extending from a distal end of the housing and including an obturator extending along a longitudinal axis and disposed within a lumen of a needle, an aspiration system disposed within the housing and including one of a syringe or a vacutainer, the aspiration system configured to slide the obturator relative to the needle and selectively provide a vacuum in fluid communication with the needle lumen, and a drive train disposed within the housing and configured to rotate the needle assembly and one of a syringe barrel or a vacutainer canister about the longitudinal axis.

(4) In some embodiments, the drive train includes one of a biasing member, an electric motor, or a battery. In some embodiments, the syringe includes a plunger slidably engaged with the syringe barrel and the housing along a longitudinal axis, the syringe barrel rotatable about the longitudinal axis relative to the plunger. In some embodiments, the intraosseous access system further includes a piston rotatably coupled to one of the plunger, the syringe barrel, or the obturator. In some embodiments, the intraosseous access system further includes a handle coupled to the plunger, a portion of the handle extending through a wall of the housing.

(5) In some embodiments, the vacutainer includes a valve configured to selectively place a vacuum, disposed within the vacutainer canister, in fluid communication with the needle lumen. In some embodiments, the vacutainer further includes an actuator configured to slide the canister along a longitudinal axis or actuate the valve between an open and closed position. In some embodiments, the housing further includes an observation window configured to allow a user to observe one of the syringe barrel or vacutainer canister disposed therebelow. In some embodiments, one of the syringe barrel or vacutainer canister can include a transparent material. In some embodiments, the biasing member is one of a flat spring, a coiled spring, or a torsion spring. In some embodiments, a distal tip of the obturator is configured to be withdrawn into one of the syringe barrel or the housing **104** to mitigate accidental needle stick injuries.

(6) Also disclosed is a method for accessing a medullary cavity including, actuating a drive train disposed within a housing, rotating a needle assembly coupled to the drive train and including an obturator disposed within the a lumen of a needle, the needle extending along a longitudinal axis, rotating one of a syringe barrel or a vacutainer canister relative to the housing about the longitudinal axis, withdrawing an obturator from the needle lumen to provide a fluid communication between the needle lumen and one of the syringe barrel or the vacutainer canister, and replacing the obturator within the needle lumen.

(7) In some embodiments, the drive train includes one of a biasing member, a flat spring, a coiled

spring, a torsion spring, an electric motor, or a battery. In some embodiments, the method further includes sliding a handle coupled to one of a plunger or the vacutainer canister along a longitudinal axis relative to the housing, the handle remaining in a rotatably fixed position about the longitudinal axis, relative to the housing. In some embodiments, the handle extends through an aperture disposed in a wall of the housing. In some embodiments, the method further includes rotating a piston coupled to a distal end of the plunger, relative to one of the handle or the syringe barrel, the piston providing a fluid tight seal between a wall of the syringe barrel and the piston. (8) In some embodiments, the method further includes confirming access to the medullary cavity by observing a fluid flow into one of the syringe barrel or the vacutainer through one or more viewing windows disposed in the housing. In some embodiments, the method further includes detaching the needle from the needle assembly. In some embodiments, the method further includes disposing the obturator within one of the syringe barrel or the vacutainer canister to mitigate needle stick injuries. (9) These and other features of the concepts provided herein will become more apparent to those of skill in the art in view of the accompanying drawings and following description, which describe particular embodiments of such concepts in greater detail.

Description

DRAWINGS

- (1) A more particular description of the present disclosure will be rendered by reference to specific embodiments thereof that are illustrated in the appended drawings. It is appreciated that these drawings depict only typical embodiments of the invention and are therefore not to be considered limiting of its scope. Example embodiments of the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:
- (2) FIG. 1A illustrates a side view of an intraosseous access system including an aspiration system, in accordance with some embodiments.
- (3) FIG. 1B illustrates a perspective view of an intraosseous access system including an aspiration system, in accordance with some embodiments.
- (4) FIG. 2 illustrates a plan, cross-section view of an intraosseous access system including an aspiration system having a syringe, in accordance with some embodiments.
- (5) FIG. 3 illustrates a plan, cross-section view of an intraosseous access system including an aspiration system having a vacutainer, in accordance with some embodiments.
- (6) FIG. 4 illustrates a flow chart of an exemplary method of use for an intraosseous access system, in accordance with some embodiments.

DESCRIPTION

- (7) Before some particular embodiments are disclosed in greater detail, it should be understood that the particular embodiments disclosed herein do not limit the scope of the concepts provided herein. It should also be understood that a particular embodiment disclosed herein can have features that can be readily separated from the particular embodiment and optionally combined with or substituted for features of any of a number of other embodiments disclosed herein.
- (8) Regarding terms used herein, it should also be understood the terms are for the purpose of describing some particular embodiments, and the terms do not limit the scope of the concepts provided herein. Ordinal numbers (e.g., first, second, third, etc.) are generally used to distinguish or identify different features or steps in a group of features or steps, and do not supply a serial or numerical limitation. For example, “first,” “second,” and “third” features or steps need not necessarily appear in that order, and the particular embodiments including such features or steps need not necessarily be limited to the three features or steps. Labels such as “left,” “right,” “top,” “bottom,” “front,” “back,” and the like are used for convenience and are not intended to imply, for

example, any particular fixed location, orientation or direction. Instead, such labels are used to reflect, for example, relative location, orientation, or directions. Singular forms of “a,” “an,” and “the” include plural references unless the context clearly dictates otherwise.

(9) With respect to “proximal,” a “proximal portion” or a “proximal-end portion” of, for example, a needle disclosed herein includes a portion of the needle intended to be near a clinician when the needle is used on a patient. Likewise, a “proximal length” of, for example, the needle includes a length of the needle intended to be near the clinician when the needle is used on the patient. A “proximal end” of, for example, the needle includes an end of the needle intended to be near the clinician when the needle is used on the patient. The proximal portion, the proximal-end portion, or the proximal length of the needle can include the proximal end of the needle; however, the proximal portion, the proximal-end portion, or the proximal length of the needle need not include the proximal end of the needle. That is, unless context suggests otherwise, the proximal portion, the proximal-end portion, or the proximal length of the needle is not a terminal portion or terminal length of the needle.

(10) With respect to “distal,” a “distal portion” or a “distal-end portion” of, for example, a needle disclosed herein includes a portion of the needle intended to be near or in a patient when the needle is used on the patient. Likewise, a “distal length” of, for example, the needle includes a length of the needle intended to be near or in the patient when the needle is used on the patient. A “distal end” of, for example, the needle includes an end of the needle intended to be near or in the patient when the needle is used on the patient. The distal portion, the distal-end portion, or the distal length of the needle can include the distal end of the needle; however, the distal portion, the distal-end portion, or the distal length of the needle need not include the distal end of the needle. That is, unless context suggests otherwise, the distal portion, the distal-end portion, or the distal length of the needle is not a terminal portion or terminal length of the needle.

(11) Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by those of ordinary skill in the art.

(12) FIG. 1A illustrates a side view of an intraosseous (IO) access system (“system”) **100** including an aspiration system **110**, in accordance with some embodiments. FIG. 1B illustrates a perspective view of an intraosseous access system **100** with portions thereof shown in wire frame.

(13) The system **100** can generally include an access system **102** and an aspiration system **110**. The access system **102** can include a drive train **106** coupled to a needle assembly **160**. The drive train **106** can be configured to rotate the needle assembly **160** and drill a needle **162** through a bone cortex to access a medullary cavity. The aspiration system **110** can be in fluid communication with a needle **162** of the needle assembly **160** and can confirm access to the medullary cavity by aspirating bone marrow through a needle lumen **164**. Advantageously, the intraosseous access system **100** can be configured to determine when the medullary cavity has been accessed by aspirating the needle **162** without disengaging the needle assembly **160** from the system **100**.

(14) In an embodiment, the intraosseous access system **100** can include a housing **104** including one or more of the access system **102**, the aspiration system **110**, or portions thereof, disposed therein. The access system **102** can include a needle assembly **160** rotatably coupled to the drive train **106** and extending from a distal end of the housing **104**. Optionally, the housing **104** can include a grip, e.g. a pistol grip **108**, or similar structures, configured to facilitate grasping the housing **104** and urging the needle **162** distally into a bone.

(15) In an embodiment, the drive train **106** of the access system **102** can be configured to provide rotational movement to one or both of the aspiration system **110** and the needle assembly **160**, as described in more detail herein. In some embodiments, the access system **102** can be an automated driver (e.g. a drill that achieves high rotational speeds). In an embodiment, the access system **102** can be an automated driver that includes a drive train **106** having an electrical energy source (e.g. battery) to provide electrical power to a drilling mechanism, e.g. an electric motor, or the like. In an embodiment, the system **100** can include an actuator, e.g. button, switch, or the like, configured to

actuate the drive train **106**. In an embodiment, the drive train **106** can be actuated by an axial pressure applied to a distal tip of the needle **162**.

(16) In an embodiment, the drive train **106** can include a spring powered drilling mechanism, e.g. a coiled spring, flat spring, torsion spring, or similar biasing member, which may store potential mechanical energy and may be released upon actuation of the drive train **106**. In an embodiment, the drive train **106** can further include one or more gear mechanisms, biasing members, bearings, bushings, or the like, configured to facilitate rotating the needle assembly **160**. In an embodiment, the access system **102** can be a manual driver where a clinician can use a handle, pistol grip **108**, or similar structure to urge the needle assembly **160** through the bone cortex.

(17) In an embodiment, a portion of the housing **104** can include the aspiration system **110** disposed therein. The housing **104** can include one or more viewing windows **120** configured to allow a user to observe a portion of the aspiration system **110** disposed therein. In an embodiment, the viewing window **120** can define an aperture extending through a wall of the housing **104**. In an embodiment, the viewing window **120** can include a transparent or translucent portion of the housing **104**. In an embodiment, the entire housing **104** can be formed of a translucent or transparent material configured to allow a user to observe one or both of the aspiration system **110** and the access system **102**, or portions thereof, disposed therein.

(18) As shown in FIGS. 1A-2, in an embodiment, the aspiration system **110** can include a syringe **130** having a barrel **132**, and a plunger **134** slidably engaged therewith. The barrel **132** can be in fluid communication with a lumen **164** of the needle **162**. Sliding the plunger **134** relative to the barrel **132** can create a vacuum within the barrel **132** and can draw a fluid flow through the needle lumen **164** and into the barrel **132**. In an embodiment, a portion of the barrel **132** can be formed of a translucent or transparent material. In use, a user can observe the fluid flow within the syringe barrel **132** through one of the viewing windows **120**.

(19) In an embodiment, the aspiration system **102** can include a vacutainer, or similar structure configured to maintain a vacuum therein, as described in more detail herein. In use, a user can actuate a release mechanism, e.g. actuator, valve, etc., to place the vacutainer in fluid communication with the needle lumen **164** and draw a fluid flow into the vacutainer. A portion of the vacutainer can be formed of a transparent or translucent material, configured to allow a user to observe a fluid flow, as described herein.

(20) In an embodiment, the aspiration system **110** can be coupled to the access system **102**, or portions thereof. In an embodiment, the aspiration system **110** can be coupled to the needle assembly **160**, or portions thereof. In an embodiment, one or both of the aspiration system **110** and the needle assembly **160** can be rotatable relative to the housing **104**. In an embodiment, the drive train **106** can be configured to rotate the needle assembly **160** and aspiration system **102** assembly about a central longitudinal axis **10**.

(21) In an embodiment, a distal end of the syringe barrel **132** can be coupled with the access system **102**, or the needle assembly **160**, or both. In an embodiment, a distal end of the syringe barrel **132** can be integrally formed with the access system **102**. In an embodiment, a distal end of the syringe barrel **132** can be selectively coupled with the access system **102** using a threaded engagement system, an interference fit, press-fit, snap-fit engagement, luer lock, combinations thereof, or the like. In an embodiment, a distal end of the syringe barrel **132** can be coupled with the access system **102** using adhesive, bonding, welding, or the like.

(22) In an embodiment, the syringe barrel **132** can be coupled with the needle assembly **160** and the drive train **106** and can rotate both the barrel **132** and the needle assembly **160** about a central longitudinal axis **10** relative to the housing **104**. Further, the plunger **134** can remain substantially stationary relative to the housing **104** with regards to any rotational movement about the central longitudinal axis **10**. To note, the plunger **134** may still be slidably engaged with the syringe barrel **132** parallel to a longitudinal axis. Further, the plunger **134** can also be slidable along the longitudinal axis **10** relative to the housing **104**.

(23) In an embodiment, the needle assembly **160** can include an obturator **166** disposed within a needle lumen **164** and configured to prevent tissue and bone fragments from entering and occluding the needle lumen **164**. A proximal end of the obturator **166** can be coupled to the plunger **134**. In an embodiment, the obturator **166** can be rotatable relative to the plunger **134**. For example, the obturator **166** can be coupled to the plunger **134** using a bearing **150**. As used herein a bearing **150** can include a ball-bearing, bushing, or similar structure configured to facilitate rotational movement about an axis. As such, as the needle assembly **160**, including the needle **162** and the obturator **166**, is rotated by the drive train **106**, the obturator **166** can rotate relative to the plunger **134**. Further, sliding the plunger **134** longitudinally, relative to the housing **104**, can slide the obturator **166** relative to the needle **162**.

(24) In use, rotating the needle assembly **160** can drill a needle **162** through a bone cortex and access the medullary cavity. In an embodiment, once the user believes the medullary cavity has been accessed, the plunger **134** can be withdrawn proximally to both create a vacuum within the barrel **132** and remove the obturator **166** from the needle lumen **164** to place the barrel **134** in fluid communication with the needle lumen **164**. If access to the medullary cavity has been achieved, bone marrow can be aspirated through the needle lumen **164**. A user can visualize bone marrow in the syringe barrel **132** through the one or more viewing windows **120** to confirm access to the medullary cavity has been achieved. Advantageously, the aspiration system **110** allows for confirmation of access to the medullary cavity by bone marrow aspiration without the need to disassemble the needle assembly **160** from the intraosseous access system **100**. In the event that access to the medullary cavity has not been achieved, i.e. no bone marrow is observed, the user can advance the plunger **134** distally, replacing the obturator **166** within the needle lumen **164** and continue drilling the needle assembly **160** through the bone cortex.

(25) FIG. 2 illustrates a plan, cross-section view of an intraosseous access system **100**. In some embodiments, the one or more viewing windows **120** can be located on a distal portion of the housing body **112** and can be configured to allow a user to observe aspiration of fluids from the needle lumen **164**.

(26) In some embodiments, the plunger **132** can include a plunger shaft **146** extending longitudinally through a portion of the syringe barrel **134**. A proximal end of the plunger shaft **146** can be coupled to a plunger handle **142** extending perpendicular thereto. In an embodiment, the plunger handle **142** can be rotatably coupled to the plunger shaft **146** and can include a bearing **150**, disposed therebetween. As such, in an embodiment, the drive train **106** can rotate one or more of the needle assembly **160**, syringe barrel **132**, and plunger shaft **146** about the central longitudinal axis **10**, and the handle **142** can remain substantially stationary with regards to any rotational movement. In an embodiment, a portion of the plunger handle **142**, e.g. a first portion **142A** and a second portion **142B**, can extend from the plunger shaft **146** perpendicular to a longitudinal axis. In an embodiment, a portion of the plunger handle **142** can extend from the plunger shaft **146** perpendicular to a longitudinal axis to contact a wall of the housing **104**.

(27) In an embodiment, a portion of the plunger handle **142** can extend from the plunger shaft **146** perpendicular to a longitudinal axis and extend through a housing aperture **126** disposed in a wall of the housing **104**. In an embodiment, a portion of the plunger handle **142** can engage the housing aperture **126** and stabilize the plunger **134** relative to the housing **104**, e.g. prevent the handle **142** from rotating relative to the housing **104** about the longitudinal axis **10**. For example, a first portion **142A** can extend through a first housing aperture **126A** and a second portion **142B** can extend through a second housing aperture **126B**. In an embodiment, the housing aperture **126** can define an elongate shape extending longitudinally. In use a user can grasp a portion of the plunger handle **142**, extending through the housing aperture **126** and can urge the plunger **134** longitudinally relative to the housing **104**.

(28) In an embodiment, a distal end of the plunger shaft **146** can be coupled to a piston **148**. The piston **148** can be formed of a compliant material, e.g. rubber or the like, and can engage an inner

surface of the barrel **132** to provide a fluid tight seal therebetween. In use, withdrawing the plunger **134** proximally, along a longitudinal axis can create a vacuum between a proximal surface of the piston **148** and a distal end of the barrel **132**.

(29) In an embodiment, the piston **148** can be rotatably coupled to the plunger shaft **146** by way of a bearing **150**, bushing, or similar structure. In use, the drive train **106** can rotate the needle assembly **160**, the syringe barrel **132** and the piston **148** about the longitudinal axis **10** while the plunger shaft **146** and the housing **104** can remain rotationally stationary relative to the longitudinal axis **10**.

(30) In an embodiment, the piston **148** can be in a fixed relationship relative to the plunger shaft **146**. The piston **148** can then be rotatable relative to the syringe barrel **134** while maintaining a fluid tight seal therebetween. In use, the drive train **106** can rotate the needle assembly **160** and the syringe barrel **132** about the longitudinal axis **10** while the plunger shaft **146**, the piston **148**, and the housing **104** can remain rotationally stationary relative to the longitudinal axis **10**.

(31) In an embodiment, an obturator **166** can be disposed within the needle lumen **164**. A proximal end of the obturator **166** can be coupled to the piston **148** of the plunger **134**. In some embodiments, the obturator **166** can be coupled to the piston **148** by a snap-fit, press-fit, or interference fit engagement, or the like, or by adhesive, welding, bonding, combinations thereof, or the like. In an embodiment, the obturator **166** can be coupled in a fixed relationship relative to the plunger **134**. In an embodiment, the obturator **166** can be rotatably coupled to the plunger **134** by way of a bearing **150**, bushing, or similar structure. As such, the obturator can rotate independently of the piston **148**.

(32) In some embodiments, the obturator **166** can be removed from the needle lumen **164** to provide fluid communication, through the needle lumen **164** and into the syringe barrel **132**. In an embodiment, withdrawing the plunger **134** can simultaneously generate a vacuum within the syringe barrel **132** and remove the obturator **166** at least partially from the needle lumen **164**.

(33) In some embodiments, where no fluid flow is observed, the plunger **134** can be advanced distally and the obturator **166** can be replaced back into the needle lumen **164**. In an embodiment, the vacuum within the syringe barrel **132** can facilitate advancing the obturator **166** distally, replacing the obturator **166** back into the needle lumen **164**. The obturator **166** can then continue to prevent occlusion of the needle lumen **164** as the needle assembly **160** continues to penetrate the bone cortex. Advantageously, the obturator **166** can be withdrawn from the needle **162** and into the barrel **132** of the syringe **130**. As such the barrel **132** can prevent accidental needle stick injuries by the distal end of the obturator **166**.

(34) In an embodiment, the drive train **106** can provide rotational movement to the needle assembly **160** in a variety of ways. For example, with the aspiration system **110** being coupled to the needle assembly **160**, the drive train **106** can rotate both the aspiration system **110** and the needle assembly **160**. In some embodiments, the drive train **106** may rotate only the needle assembly **160**, i.e. without rotating the aspiration system **110**. In some embodiments, the drive train **106** may rotate one or more components of the aspiration system **110** and/or needle assembly **160** while maintaining other components stationary relative thereto.

(35) In an embodiment, the drive train **106** can rotate the barrel **132** of the syringe **130** while maintaining the plunger **134** stationary relative to any rotation about the longitudinal axis **10**. In an embodiment, the plunger handle **142** can engage the housing aperture **126** to prevent the plunger **134** from rotating about the longitudinal axis **10** as the barrel **132** rotates. In an embodiment, the plunger shaft **146** may be coupled to a bearing **150** bushing, or the like, disposed within the piston **148**. The bearing **150** is configured to allow rotational movement of piston **148** around the central axis **10** while allowing the plunger shaft **146** to remain substantially stationary. In some embodiments, the syringe **130** is configured to receive a volume of fluid therein. In some embodiments, the capacity of the syringe maybe between 1 ml and 10 ml. It will be appreciated that other volumes of capacity are also considered.

(36) FIG. 3 illustrates further details of an intraosseous access system **100** including an aspiration system **110** having a vacutainer **400**. The aspiration system **110** can be coupled to the access system **102**, as described herein. In an embodiment, the aspiration system **110** can include a vacutainer **400** configured to maintain a vacuum therein. The vacutainer **400** can include a canister **402** configured to maintain a vacuum therein, and a valve **404** configured to control fluid communication between the needle lumen **164** of the needle assembly **160** and the canister **402** vacutainer **400**.

(37) In an embodiment, the vacutainer **400** can further include a handle **442**. In an embodiment, a portion of the handle **442** can extend through a housing aperture **126**, as described herein. In user, a user can grasp the handle **442** and slide the vacutainer **400** longitudinally relative to the housing **104**. In an embodiment, the vacutainer **400** can include a bearing **150**, bushing, or the like, configured to allow the canister **402** to rotate relative to the handle **442**. In an embodiment, a proximal end of the obturator **166** can be coupled a distal end of the vacutainer **400**. In an embodiment, the vacutainer can further include a bearing **150** configured to allow the obturator **166** to rotate relative to the vacutainer **400**, or portions thereof, e.g. the canister **402** or valve **404**.

(38) In an embodiment, the drive train **106** can rotate the vacutainer **400** and the needle assembly **160** about the central axis **10**. When the user believes the medullary cavity has been accessed, a user can grasp the handle **442** and slide the vacutainer **400** proximally to at least partially withdraw the obturator **166** from the needle lumen **164** of the needle. With the obturator **166** withdrawn, a user can actuate the valve **404** and provide fluid communication between the needle lumen **164** and the canister **402** of the vacutainer **400**. The vacuum within the canister **402** can then draw a fluid flow through the needle lumen **164**. In an embodiment, a portion of the canister **402** can be formed of a transparent material and a fluid flow within the canister **402** can be observed through one or more observation windows **120**.

(39) If the medullary cavity has been accessed, the user can observe bone marrow within the canister **402**. If the medullary cavity has not been accessed, e.g. a distal tip of the needle **162** is still disposed within the bone cortex, no bone marrow will be observed. As such, a user can close the valve **404** and slide the handle **442** distally to replace the obturator **166** within the needle lumen **162** and continue drilling the needle assembly **160** through the bone cortex. Advantageously, withdrawing the vacutainer **400** and obturator **166** assembly proximally can maintain a tip of the obturator **166** within the housing **104** and mitigate accidental needle stick injuries. In an embodiment, the handle **442** can be configured to slide the vacutainer **400** along a longitudinal axis and actuate the valve **404**. In an embodiment, a separate actuator can be configured to actuate the valve **404** and transition the valve **404** between an open and a closed position.

(40) In some embodiments, portions of the aspiration system **110** may be configured to be selectively detachable from the access system **102**. For example, in an embodiment, in the aspiration system **110**, the syringe **130**, the vacutainer **400**, or combinations thereof may be configured to be detachable and interchangeable. In an embodiment, sliding the syringe **130** or the vacutainer **400** can be achieved by manually operating and handle, as described herein. In an embodiment, the system **100** can further include a second drive train configured to be actuated by a user and slide the aspiration system **110**, or portions thereof, along a longitudinal axis.

(41) FIG. 4 illustrates an exemplary method of use **500** for intraosseous access system **100**, including an aspiration system **110**. In an embodiment, the method **500** includes assembling the intraosseous access system **100** (block **502**). In some embodiments, assembling the intraosseous access system **100** includes coupling a needle assembly **106** with an access system **102** of the system **100**. The needle assembly **160** rotatably coupled to the system **100**. In some embodiments, assembling the intraosseous access system **100** includes coupling an aspiration system **110** having a syringe **130** or a vacutainer **400** with the system **100**.

(42) In an embodiment, the method **500** includes actuating the access system **102** to rotate the needle assembly **160**, the aspiration system **110**, or components thereof, to drill a needle **162**

through a bone cortex to access the medullary cavity (block 504). In an embodiment, when a user believes the medullary cavity has been accessed, the user can confirm access to the medullary cavity by withdrawing the obturator 166 from a needle lumen 164 (block 506). A fluid flow can be drawn through the needle lumen 164 by providing a vacuum in fluid communication with the needle lumen 164 (block 508). The vacuum can be provided either by withdrawing a plunger 134 from a syringe barrel 132, or by actuating a valve to place a vacutainer 400 in fluid communication with the needle lumen 164, or combinations thereof. (block 508).

(43) In an embodiment, the user can then determine if the medullary cavity has been accessed by observing a fluid flow (block 510). If medullary cavity access has been confirmed, the user can detach the system 100 from the needle 162 (block 512). If medullary cavity access is not confirmed, the user replace the obturator 166 within the needle lumen 164 (block 514) and continue drilling through the bone cortex (return to block 504).

(44) While some particular embodiments have been disclosed herein, and while the particular embodiments have been disclosed in some detail, it is not the intention for the particular embodiments to limit the scope of the concepts provided herein. Additional adaptations and/or modifications can appear to those of ordinary skill in the art, and, in broader aspects, these adaptations and/or modifications are encompassed as well. Accordingly, departures may be made from the particular embodiments disclosed herein without departing from the scope of the concepts provided herein.

Claims

1. An intraosseous access system, comprising: a housing; a needle assembly including a needle extending from a distal end of the housing along a longitudinal axis, and an obturator disposed within a lumen of the needle; an aspiration system disposed within the housing and including one of a syringe or a vacutainer, a proximal end of the obturator coupled to the aspiration system, the aspiration system configured to engage and slide the obturator relative to the needle, the aspiration system further configured to provide a vacuum to the lumen of the needle while remaining engaged with the obturator; and a drive train disposed within the housing and configured to rotate the needle assembly and one of a syringe barrel or a vacutainer canister about the longitudinal axis.
2. The intraosseous access system according to claim 1, wherein the drive train includes one of a biasing member, an electric motor, or a battery.
3. The intraosseous access system according to claim 1, wherein the syringe includes a plunger slidably engaged with the syringe barrel and the housing along the longitudinal axis, the syringe barrel rotatable about the longitudinal axis relative to the plunger.
4. The intraosseous access system according to claim 3, further including a piston rotatably coupled to one of the plunger, the syringe barrel, or the obturator.
5. The intraosseous access system according to claim 3, further including a handle coupled to the plunger, a portion of the handle extending through a wall of the housing.
6. The intraosseous access system according to claim 1, wherein the vacutainer includes a valve configured to control fluid communication between the vacutainer canister and the lumen of the needle to selectively apply the vacuum to the lumen of the needle.
7. The intraosseous access system according to claim 6, wherein the vacutainer further includes an actuator configured to slide the vacutainer canister along the longitudinal axis or to actuate the valve between an open and closed position.
8. The intraosseous access system according to claim 1, wherein the housing further includes an observation window configured to allow a user to observe one of the syringe barrel or the vacutainer canister disposed therebelow.
9. The intraosseous access system according to claim 1, wherein one of the syringe barrel or the vacutainer canister can include a transparent material.

10. The intraosseous access system according to claim 2, wherein the biasing member is one of a flat spring, a coiled spring, or a torsion spring.

11. The intraosseous access system according to claim 1, wherein a distal tip of the obturator is configured to be withdrawn into one of the syringe barrel or the housing to mitigate accidental needle stick injuries.
