

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405460
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	McManamon; Paul F. et al.

Decentered lens light beam steering

Abstract

An example system includes a first steering lens positioned between an EM source and a second steering lens, and the second steering lens positioned between the first steering lens and an emission lens. The example system includes the first and second steering lenses having a combined first effective focal length, and where the emission lens is a positive lens have a second focal length. The example system includes the first effective focal length being shorter than the second focal length. The example system includes a first steering actuator that move the first steering lens along a first movement course, and a second steering actuator that moves the second steering lens along a second movement course.

Inventors:	McManamon; Paul F. (Dayton, OH), Ataei; Abtin (Oakwood, OH)
Applicant:	Exciting Technology, LLC (Dayton, OH)
Family ID:	78084447
Assignee:	Exciting Technology LLC (Dayton, OH)
Appl. No.:	17/860834
Filed:	July 08, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220360037 A1	Nov. 10, 2022

Related U.S. Application Data

continuation parent-doc WO PCT/US2020/056253 20201019 PENDING child-doc US 17860834
us-provisional-application US 63040319 20200617
us-provisional-application US 63011706 20200417

Publication Classification

Int. Cl.: G02B26/08 (20060101); H01S5/00 (20060101); H01S5/02251 (20210101)

U.S. Cl.:

CPC G02B26/0875 (20130101); H01S5/0071 (20130101); H01S5/02251 (20210101)

Field of Classification Search

CPC: G02B (6/0875); H01S (5/0071); H01S (5/02251)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3822932	12/1973	Humphrey	N/A	N/A
5223971	12/1992	Magel	N/A	N/A
5249079	12/1992	Umeda	359/557	G02B 27/646
5392157	12/1994	Shih	359/623	G02B 26/0808
5444572	12/1994	Gal	359/620	G03F 7/70583
5598299	12/1996	Hayakawa	359/557	G02B 13/02
5703726	12/1996	Griffith	359/753	G02B 13/04
5923480	12/1998	Labeye	359/813	G02B 26/0875
5943159	12/1998	Zhu	359/254	G02F 1/292
5987041	12/1998	Taniguchi et al.	N/A	N/A
6169594	12/2000	Aye et al.	N/A	N/A
6295171	12/2000	Chao et al.	N/A	N/A
6317251	12/2000	Wang	N/A	N/A
6373620	12/2001	Wang	N/A	N/A
6384975	12/2001	Hayakawa	359/557	G02B 27/646
6400855	12/2001	Li et al.	N/A	N/A
6456419	12/2001	Winker et al.	N/A	N/A
6556260	12/2002	Itou et al.	N/A	N/A
6728033	12/2003	Hayakawa	359/557	G02B 27/646
6746618	12/2003	Li et al.	N/A	N/A
7057787	12/2005	Cicchiello et al.	N/A	N/A
7411724	12/2007	Cicchiello et al.	N/A	N/A
7544945	12/2008	Tan	250/353	G01S 17/87
8014050	12/2010	McGrew	N/A	N/A
8301027	12/2011	Shaw	398/118	H01S 5/423

8614743	12/2012	Winsor	348/145	H04N 23/60
8654292	12/2013	Kubota et al.	N/A	N/A
8699137	12/2013	McGrew	N/A	N/A
8941921	12/2014	Ito	359/557	G02B 27/646
9025230	12/2014	Sagan	359/558	G02B 27/4233
9075324	12/2014	Zimmerman et al.	N/A	N/A
9164206	12/2014	Valley et al.	N/A	N/A
9577327	12/2016	Driscoll	N/A	G02B 1/007
9709829	12/2016	McGrew	N/A	G02B 21/14
9915850	12/2017	Bitauld	N/A	G02F 1/29
10295671	12/2018	Gazit	N/A	G01S 17/931
10303037	12/2018	Spector	N/A	G01S 17/42
10386489	12/2018	Albelo et al.	N/A	N/A
10761195	12/2019	Donovan	N/A	G01S 17/931
10838043	12/2019	Hansson	N/A	G01S 7/4816
10845671	12/2019	McManamon et al.	N/A	N/A
10989982	12/2020	Ataei et al.	N/A	N/A
11221435	12/2021	Gopinath	N/A	G02B 26/0875
11762068	12/2022	Donovan	356/5.01	G01S 17/89
11822205	12/2022	Mcmanamon et al.	N/A	N/A
2002/0126383	12/2001	Hayakawa	359/557	G02B 27/646
2003/0021519	12/2002	Zalevsky et al.	N/A	N/A
2004/0067013	12/2003	Gu et al.	N/A	N/A
2004/0135965	12/2003	Holmes	N/A	N/A
2004/0264229	12/2003	Tsu	N/A	N/A
2005/0213964	12/2004	Kreger	396/544	G03B 17/565
2005/0265403	12/2004	Anderson et al.	N/A	N/A
2005/0271325	12/2004	Anderson	385/39	G02F 1/295
2006/0092499	12/2005	Cicchiello et al.	N/A	N/A
2006/0119928	12/2005	Cicchiello et al.	N/A	N/A
2007/0146910	12/2006	Duston et al.	N/A	N/A
2007/0181810	12/2006	Tan	250/341.1	G01S 7/4811
2007/0279365	12/2006	Kageyama	N/A	N/A
2008/0015553	12/2007	Zacharias	606/4	A61F 9/008
2008/0212007	12/2007	Meredith	N/A	N/A

2008/0239420	12/2007	McGrew	N/A	N/A
2008/0247031	12/2007	Wasilousky	N/A	N/A
2009/0073411	12/2008	Tanitsu	N/A	N/A
2009/0304328	12/2008	Presley et al.	N/A	N/A
2010/0046953	12/2009	Shaw	398/115	H01S 5/423
2010/0165322	12/2009	Kane	356/4.01	G01S 7/481
2011/0286063	12/2010	McGrew	N/A	N/A
2013/0128334	12/2012	Stephen	359/279	G02B 5/189
2013/0241761	12/2012	Cooper	342/54	G01S 7/4817
2014/0016051	12/2013	Kroll et al.	N/A	N/A
2015/0346495	12/2014	Welch	345/8	G02B 27/017
2015/0346521	12/2014	Williams	N/A	N/A
2015/0378241	12/2014	Eldada	N/A	N/A
2016/0170287	12/2015	Bitauld	385/4	G02F 1/2955
2016/0327636	12/2015	Gazit	N/A	G01S 7/4972
2017/0269453	12/2016	Galstian et al.	N/A	N/A
2017/0307736	12/2016	Donovan	N/A	G01S 7/484
2017/0357142	12/2016	Spector	N/A	G02B 27/30
2018/0038576	12/2017	Mao	N/A	N/A
2018/0101083	12/2017	Aflatouni	N/A	G02F 1/293
2018/0136538	12/2017	Khan	N/A	N/A
2018/0180256	12/2017	Mao et al.	N/A	N/A
2018/0275394	12/2017	Yeoh et al.	N/A	N/A
2018/0364463	12/2017	Yuan	N/A	G02B 17/008
2019/0129275	12/2018	McManamon et al.	N/A	N/A
2019/0146070	12/2018	Hansson	356/5.09	G01S 17/32
2019/0187482	12/2018	Lanman	N/A	N/A
2019/0285902	12/2018	Ouderkirk et al.	N/A	N/A
2020/0124864	12/2019	Rothberg et al.	N/A	N/A
2020/0183016	12/2019	Wang et al.	N/A	N/A
2020/0326606	12/2019	Ataei et al.	N/A	N/A
2020/0333679	12/2019	Ataei et al.	N/A	N/A
2020/0333680	12/2019	Ataei et al.	N/A	N/A
2020/0333682	12/2019	Ataei et al.	N/A	N/A
2021/0048723	12/2020	McManamon et al.	N/A	N/A
2021/0048725	12/2020	McManamon et al.	N/A	N/A
2021/0116778	12/2020	Zhang et al.	N/A	N/A
2021/0333443	12/2020	Gopinath	N/A	G02B 26/101

2022/0350135	12/2021	Mcmanamon et al.	N/A	N/A
2022/0350136	12/2021	Mcmanamon et al.	N/A	N/A
2023/0038746	12/2022	Mcmanamon et al.	N/A	N/A
2023/0039081	12/2022	Mcmanamon et al.	N/A	N/A
2023/0350192	12/2022	Mcmanamon et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102007004609	12/2006	DE	G01S 17/87
0903608	12/1998	EP	N/A
WO-2018097869	12/2017	WO	G02B 26/005
WO-2018097869	12/2017	WO	G02B 26/005
2020086111	12/2019	WO	N/A
2020086692	12/2019	WO	N/A
2020086111	12/2019	WO	N/A
2021211162	12/2020	WO	N/A
2021211163	12/2020	WO	N/A
2022266229	12/2021	WO	N/A

OTHER PUBLICATIONS

Bawart et al., Dynamic beam-steering by a pair of rotating diffractive elements, Optics Communications, vol. 460, 2020, 125071, ISSN 0030-4018, <https://doi.org/10.1016/j.optcom.2019.125071> (Year: 2020). cited by examiner

Duerr et al., Tracking integration in concentrating photovoltaics using laterally moving optics, Opt. Express 19, A207-A218 (2011) (Year: 2011). cited by examiner

Shi et al., Design considerations for high efficiency liquid crystal decentered microlens arrays for steering light, Appl. Opt. 49, 409-421 (2010) (Year: 2010). cited by examiner

Zohrabi et al., Wide-angle nonmechanical beam steering using liquid lenses, Opt. Express 24, 23798-23809 (2016) (Year: 2016). cited by examiner

Gibson, Jennifer L., et al., "Wide Angle Decentered Lens Beam Steering for Infrared Countermeasures", Opt'Eng; Publication [online]. Mar. 31, 2004 [retrieved Dec. 26, 2020]. Retrieved from the Internet; Mar. 31, 2004, 11 pages. cited by applicant

Glockner, Steffen , et al., "Micro-opto-mechanical beam deflectors", Opt Eng; Publication [online]. Jan. 12, 1997 [retrieved Dec. 31, 2020], Retrieved from the Internet; DOI: Jan. 12, 1997, 7 pages. cited by applicant

Hassanfirooz, Amir , et al., "Dual layer electrode liquid crystal lens for 2D/3D tunable endoscopy imaging system", Optics Express; vol. 24, No. 8, Apr. 18, 2016, 12 pages. cited by applicant

Hatcher, Burrell R., "Granularity of beam positions in digital phased arrays", Proceedings of the IEEE (vol. 56, Issue: 11, Nov. 1968), Nov. 1968, 1795-1800. cited by applicant

Lou, Yimin , et al., "Design and fabrication of tunable liquid crystal diffractive lens", Optical Engineering 091713-1, vol. 52(9), 2013, 6 pages. cited by applicant

Mcmanamon, Paul F., et al., "Broadband optical phased-array beam steering", Opt. Eng. 44, 128004, 2005, Dec. 2005, 1-5. cited by applicant

Mcmanamon, Paul F., et al., "Nonmechanical beam steering for active and passive sensors",

Downloaded From: <https://www.spiedigitallibrary.org/conference-proceedings-of-spie> on Aug. 22, 2019 Terms of Use: <https://www.spiedigitallibrary.org/terms-of-use>, 1993, 1-10. cited by applicant

Mcmanamon, Paul F., et al., ““Optical Phased Array Technology””, Proc. IEEE 84(2), 268-298,, Feb. 1996, 268-298. cited by applicant

Mcmanamon, Paul F., et al., “A Review of Phased Array Steering for Narrow-Band Electrooptical Systems”, Proceedings of the IEEE, vol. 97, No. 6,, Jun. 2009, 19 pages. cited by applicant

PCT/US19/57616 , “International Application Serial No. PCT/US19/57616, International Preliminary Report on Patentability mailed May 6, 2021”, Exciting Technology LLC, 9 pages. cited by applicant

PCT/US19/57616 , “International Application Serial No. PCT/US19/57616, International Search Report and Written Opinion mailed Jan. 13, 2020”, Exciting Technology LLC, 10 pages. cited by applicant

PCT/US2019/023915 , “International Application Serial No. PCT/US2019/023915, International Preliminary Report on Patentability mailed May 6, 2021”, Exciting Technology LLC, 12 pages. cited by applicant

PCT/US2019/023915 , “International Application Serial No. PCT/US2019/023915, International Search Report and Written Opinion mailed Jul. 18, 2019”, Exciting Technology LLC, 15 pages. cited by applicant

PCT/US2019/023915 , “International Application Serial No. PCT/US2019/023915, Invitation to Pay Additional Fees and, Where Applicable, Protest Fee mailed May 29, 2019”, Exciting Technology LLC, 2 pages. cited by applicant

PCT/US2020/056253 , “International Application Serial No. PCT/US2020/056253, International Search Report and Written Opinion mailed Feb. 3, 2021”, Exciting Technology LLC, 8 pages. cited by applicant

PCT/US2020/056254 , “International Application Serial No. PCT/US2020/056254, International Search Report and Written Opinion mailed Mar. 17, 2021”, Exciting Technology LLC, 11 pages. cited by applicant

PCT/US2020/056254 , “International Application Serial No. PCT/US2020/056254, Invitation to Pay Additional Fees and, Where Applicable, Protest Fee mailed Jan. 11, 2021”, Exciting Technology LLC, 2 pages. cited by applicant

PCT/US2020/064071 , “International Application Serial No. PCT/US2020/064071, International Search Report and Written Opinion mailed Apr. 16, 2021”, Exciting Technology LLC, 14 pages. cited by applicant

PCT/US2020/064071 , “International Application Serial No. PCT/US2020/064071, Invitation to Pay Additional Fees and, Where Applicable, Protest Fee mailed Feb. 19, 2021”, Exciting Technology LLC, 2 pages. cited by applicant

Rabinovich, William S., et al., “Two-dimensional beam steering using a thermo-optic silicon photonic optical-phased-array”, Opt. Eng. 55(11), 111603 (2016), doi: 10.1117/1.OE.55.11.111603, 2016, 8 pages. cited by applicant

Shang, Xiaobing , et al., “Tunable Optical Beam Deflection via Liquid Crystal Gradient Refractive Index Generated by Highly Resistive Polymer Film”, IEEE Photonics Journal, vol. 8, No. 3, 2016, pp. 1-11. cited by applicant

Thalhammer, Gregor , et al., ““Speeding up liquid crystal SLMs using overdrive with phase change reduction””, Jan. 28, 2013 / vol. 21, No. 2 / Optics Express p. 1779-1797, Jan. 2013, 1779-1797. cited by applicant

Wang, X. , et al., ““Spatial resolution limitation of liquid crystal spatial light modulator””, Liquid Crystal Conference, Great Lakes Photonics Symposium, Cleveland, OH Jun. 7-11, 2004, Oct. 2004, 45-57. cited by applicant

U.S. Appl. No. 17/860,813, filed Jul. 8, 2022, Pending, Paul F. McManamon, Abtin Ataei. cited by applicant

U.S. Appl. No. 17/860,846, filed Jul. 8, 2022, Pending, Paul F. McManamon, Abtin Ataei. cited by applicant
20931402.0, , “European Application Serial No. 20931402.0, Extended European Search Report mailed Mar. 4, 2024”, Exciting Technology LLC, 5 pages. cited by applicant
PCT/US2020/056253, , “International Application Serial No. PCT/US2020/056253, International Preliminary Report on Patentability mailed Oct. 13, 2022”, Exciting Technology LLC, 9 pages. cited by applicant
PCT/US2020/056254, , “International Application Serial No. PCT/US2020/056254, International Preliminary Report on Patentability mailed Oct. 27, 2022”, Exciting Technology LLC, 10 pages. cited by applicant
PCT/US2022/033640, , “International Application Serial No. PCT/US2022/033640, International Search Report and Written Opinion mailed Oct. 5, 2022”, Exciting Technology LLC, 12 pages. cited by applicant
PCT/US2022/033640, , “International Application Serial No. PCT/US2022/033640, International Preliminary Report on Patentability and Written Opinion mailed Dec. 28, 2023”, Exciting Technology LLC, 6 pages. cited by applicant

Primary Examiner: Radkowski; Peter

Attorney, Agent or Firm: GTC Law Group PC & Affiliates

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/US2020/056253, filed Oct. 19, 2020 entitled “DECENTERED LENS LIGHT BEAM STEERING (EXCT-0008-WO). (2) PCT/US2020/056253 (EXCT-0008-WO) claims priority to the following U.S. Provisional Patent Applications: Ser. No. 63/011,706, filed 17 Apr. 2020, and entitled “DECENTERED LENS LIGHT BEAM ELECTRO-MECHANICAL STEERING” (EXCT-0008-P01); and Ser. No. 63/040,319, filed 17 Jun. 2020, and entitled “DECENTERED LENS LIGHT BEAM ELECTRO-MECHANICAL STEERING” (EXCT-0008-P02). (3) Each of the foregoing patent applications is incorporated by reference herein in the entirety for all purposes.

BACKGROUND

- (1) A previously known decentered beam steering system consists of two identical thin lenses separated by two focal lengths, as seen in FIG. 1.
- (2) In the example previously known system, the first lens **112** is illuminated by an infinite uniform plane wave **102** (or incident beam). The first lens **112** and second lens **114** are arranged such that the back focal plane of the first lens coincides with the front focal plane of the second lens (at focal length **108** away from the second lens **114**). The incoming collimated wavefront is focused to a point on the shared focal plane. The second lens **114** is decentered (e.g., relative to an optical axis **120** of the incident beam **102**) by an offset **104** (defining steering angle A), and the decentered second lens **114** then collimates the exiting light **106**, but the beam **106** is directed to a nonzero steering angle (θ) as seen in FIG. 1, for example comparing beam boundary **116** with beam boundary **118**. The deflection angle θ can be calculated from the focal length **108** of the second lens (f) and the displacement **104** (defining Δ) as set forth in Eq. 1.
- (3) Deflection angle for previously known decentered beam steering system $= \tan^{-1}(\frac{\Delta}{f})$. Eq. 1
- (4) As the maximum possible lens displacement **104** (Δ) is half of the lens **114** diameter, it can be

seen that the maximum steering capability is ($f/\#$ is the f-number, or focal length over the beam diameter, in the context of the present disclosure):

(5) Maximum deflection angle for previously known decentered beam steering system

$$\theta_{\max} = \tan^{-1}\left(\frac{d}{2f}\right) = \tan^{-1}\left(\frac{1}{2f/\#}\right). \quad \text{Eq. 2}$$

(6) Displacing the lens up to half of its diameter is not always practical, straight forward, and/or may introduce limitations in the steering speed (or frequency—e.g., a sweep frequency for steering through a range of angles) capability. Further, steering to a large angle in previously known systems may prevent some rays from hitting the next lens and introduce vignetting, e.g., depicted as vignetting losses **110** in the example of FIG. **1**, where some of the initial beam **102** energy is directed to undesired locations, resulting in losses, heat generation, and/or direction of some beam energy to undesirable locations.

(7) Accordingly, the deflection angle **104** capability is determined by the diameter of the second lens **114**, which must be increased to increase steering capability, and the system must provide a corresponding increase in the displacement **104** to achieve that increased steering capability. The increased size of the lens **114** makes steering more difficult, with the requirement for a larger, more capable actuator, and the movement of a greater mass of the increased size of the lens **114**. Thus, in previously known systems, for a given focal length **108**, a large lens **114** must be moved a large distance **A** to provide for high angle steering capability, severely limiting the capability, increasing the cost, and/or increasing the footprint of the system to steer to large angles, especially if the final aperture is large (e.g., since the lens **114** must be at least twice the size of the final steered beam size).

(8) As depicted in FIG. **1**, a portion **110** of the steered beam is lost due to vignetting, where some of the light misses the second lens. A further previously known system includes the utilization of a field lens **202** as depicted in FIG. **2**. The field lens **202** does not increase the steering capability, but does reduce the vignette losses, and increases the fraction of the beam **102**, **106** that is successfully steered.

(9) The previously known system operates at a magnification of one (1), where the steered beam **106** must be incident on the second lens **114**, not counting the field lens **202**, and accordingly the second lens **114** must be at least the size of the desired steered beam. For example, to achieve a one (1) inch steered beam, a minimum of a one (1) inch second lens **114** must be utilized. The large size of the second lens **114** suffers similar drawbacks to the system depicted in FIG. **1**, for example requiring a large, highly capable, mechanical movement system for the second lens **114** to steer the beam **106**, increasing the cost, weight, and complexity of the steering system. Additionally, while the system of FIGS. **1** and **2** is depicted steering in a single direction (e.g., azimuth or elevation), the steering may be performed in a second direction as well, further increasing the cost and complexity of the steering system (e.g., adding additional lens layers, additional actuators, imposing a minimum lens size in both directions even where high capability is only required in one steering direction, etc.).

(10) Some previously known systems utilize a telescope (not shown) downstream of the second lens **114** to magnify the beam, reducing the required size of the second lens to achieve a desired steered beam size. However, the magnification proportionately reduces the effective steered angle θ by a fraction equal to the magnification, according to equation 3, where θ is the final steered angle, α is the deflected angle, and M is the magnification of the steered beam.

(11) Final deflection angle of a magnified beam $= M \cdot \alpha$. Eq. 3

(12) Accordingly, previously known decentered beam steering systems require large lenses with large deflections to achieve significant steering capability. Additionally, previously known systems suffer from high expense, low steering capability, a large footprint (e.g., weight, size, and/or power requirements), and generally more than one of these to meet some constraint for the others.

SUMMARY

(13) An example system includes a first steering lens interposed between an electromagnetic (EM) source and a second steering lens, the second steering lens interposed between the first steering lens and an emission lens, the first steering lens and the second steering lens having a combined first effective focal length, the emission lens comprising a positive lens having a second focal length, wherein the first effective focal length is shorter than the second focal length, a first steering actuator coupled to the first steering lens, the first steering actuator configured to move the first steering lens along a first movement course, and a second steering actuator coupled to the second steering lens, the second steering actuator configured to move the second steering lens along a second movement course, wherein the second movement course is distinct from the first movement course.

(14) Certain further aspects of the example system are described following, any one or more of which may be present in certain embodiments. An example system includes: wherein the first movement course corresponds to a first axis, and wherein the second movement course corresponds to a second axis; wherein the first axis comprises a first steering axis, and wherein the second axis comprises a second steering axis; wherein the first axis is perpendicular to the second axis; and/or wherein the first axis is radially separated from the second axis by at least 45 degrees. An example system includes: wherein the first steering lens comprises a negative lens; wherein the second steering lens comprises a negative lens; wherein the second steering lens comprises a positive lens, and wherein a power of the first steering lens comprises a distinct magnitude from the power of the second steering lens; wherein the first steering lens comprises a positive lens; wherein the second steering lens comprises a positive lens; and/or wherein the second steering lens comprises a negative lens, and wherein a power of the first steering lens comprises a distinct magnitude from the power of the second steering lens. An example system includes: wherein a ratio between the first effective focal length and the second focal length is selected in response to a beam steering angle capability value for a beam steering device comprising the first steering lens, the second steering lens, and the emission lens; wherein at least one of the first steering actuator or the second steering actuator comprises a piezoelectric actuator; wherein at least one of the first steering actuator or the second steering actuator comprises an electromagnetic actuator; wherein the first steering actuator comprises a configurable lens element having an active lens portion, wherein the first steering lens comprises the active lens portion, and wherein moving the first steering lens along the first movement course comprises changing a position of the active lens portion; wherein the second steering actuator comprises a configurable lens element having an active lens portion, wherein the second steering lens comprises the active lens portion, and wherein moving the second steering lens along the second movement course comprises changing a position of the active lens portion; and/or a source collimator lens interposed between the EM source and the first steering lens.

(15) An example system further includes a beam steering controller, including: a steering target circuit structured to interpret a beam steering target value; a steering lens control circuit structured to determine a first position of the first steering lens and a second position of the second steering lens in response to the beam steering target value; a steering actuation circuit structured to provide a first actuator command value in response to the first position, and a second actuator command value in response to the second position; and wherein the first actuator is responsive to the first actuator command value, and wherein the second actuator is responsive to the second actuator command value. An example system further includes one or more of: wherein the first position comprises a selected displacement along a first steering axis; wherein the second position comprises a selected displacement along a second steering axis; wherein the steering lens control circuit is further structured to determine the first position and the second position, such that the EM source is incident upon the emission lens at a selected position of the emission lens; wherein the beam steering target value comprises a steering azimuth value and a steering elevation value; wherein the steering lens control circuit is further structured to determine one of the first position or

the second position in response to the steering azimuth value, and to determine the other one of the first position or the second position in response to the steering elevation value; and/or wherein the steering lens control circuit is further structured to determine the first position and the second position such that the EM source incident upon the emission lens is at a selected position of the emission lens.

(16) An example system further includes one or more of: wherein a beam steering device comprising the first steering lens, the second steering lens, and the emission lens comprises a greater magnification in an azimuthal axis than in an elevation axis; wherein the beam steering device comprises an azimuthal steering capability aligned with the azimuthal axis, an elevation steering capability aligned with the elevation axis, and wherein the azimuthal steering capability is greater than the elevation steering capability; wherein the first movement course aligns with the azimuthal axis, and wherein the second actuator comprises a greater displacement range than the first actuator; wherein the second movement course aligns with the elevation axis, and wherein the first actuator comprise a greater displacement range than the second actuator; wherein a beam steering device comprising the first steering lens, the second steering lens, and the emission lens comprises a greater magnification in an elevation axis than in an azimuthal axis; wherein the beam steering device comprises an azimuthal steering capability aligned with the azimuthal axis, an elevation steering capability aligned with the elevation axis, and wherein the elevation steering capability is greater than the azimuthal steering capability; wherein the first movement course aligns with the elevation axis, and wherein the second actuator comprises a greater displacement range than the first actuator; and/or wherein the second movement course aligns with the azimuthal axis, and wherein the first actuator comprise a greater displacement range than the second actuator.

(17) An example system further includes one or more of: wherein a beam steering device comprising the first steering lens, the second steering lens, and the emission lens comprises a greater magnification in a first steering axis than in a second steering axis; wherein the beam steering device comprises a first steering capability aligned with the first steering axis, a second steering capability aligned with the second steering axis, and wherein the first steering capability is greater than the second steering capability; wherein the first movement course aligns with the first steering axis, and wherein the second actuator comprises a greater displacement range than the first actuator; wherein the second movement course aligns with the first axis, and wherein the first actuator comprise a greater displacement range than the second actuator; a field lens interposed between the second steering lens and the emission lens; and/or wherein the field lens is axially displaced by the first effective focal length from the second steering lens, and by the second focal length from the emission lens.

(18) Another example system includes: a steering lens interposed between an electromagnetic (EM) source and an emission lens, the steering lens having a first focal length; the emission lens comprising a positive lens having a second focal length; wherein the first focal length is shorter than the second focal length; and a steering actuator coupled to the steering lens, the steering actuator configured to move the first steering lens along a movement course.

(19) Certain further aspects of the example system are described following, any one or more of which may be present in certain embodiments. An example system further includes one or more of: wherein the movement course comprises selected movement along each of two axes; wherein a first one of the two axes comprises a first steering axis, and wherein a second one of the two axes comprises a second steering axis; wherein the two axes comprise perpendicular axes; wherein the steering actuator comprises a configurable lens element having an active lens portion, wherein the steering lens comprises the active lens portion, and wherein moving the steering lens along the movement course comprises changing a position of the active lens portion; wherein the steering lens comprises a positive lens, the system further comprising a field lens positioned between the steering lens and the emission lens; and/or further comprising a source collimator lens interposed between the EM source and the steering lens.

(20) Yet another example system includes: a fixed positive lens interposed between an electromagnetic (EM) source and a first steering layer; the first steering layer interposed between the fixed positive lens and a second steering layer, the first steering layer comprising a net negative effective focal power; the second steering layer comprising a net positive effective focal power; a first steering actuator coupled to the first steering layer, the first steering actuator configured to move the first steering layer along a first movement course; and a second steering actuator coupled to the second steering layer, the second steering actuator configured to move the second steering layer along a second movement course.

(21) Certain further aspects of the example system are described following, any one or more of which may be present in certain embodiments. An example system further includes one or more of: wherein the first steering layer comprises two lenses, and wherein the first steering actuator comprises a pair of actuators, each coupled to a corresponding one of the two lenses of the first steering layer; wherein the second steering layer comprises two lenses, and wherein the second steering actuator comprises a pair of actuators, each coupled to a corresponding one of the two lenses of the second steering layer; and/or a source collimator lens interposed between the EM source and the steering lens.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) FIG. 1 depicts an example previously known steering device.
- (2) FIG. 2 depicts another example previously known steering device.
- (3) FIG. 3 is a schematic depiction of an example type 3 steering device.
- (4) FIG. 4 is another schematic depiction of an example type 3 steering device.
- (5) FIG. 5 is another schematic depiction of an example type 3 steering device.
- (6) FIG. 6 is another schematic depiction of an example type 3 steering device.
- (7) FIG. 7 is an illustrative capability of a type 3 steering device.
- (8) FIG. 8 is another schematic depiction of an example type 3 steering device.
- (9) FIG. 9 is an illustrative capability of a type 3 steering device.
- (10) FIG. 10 is another schematic depiction of an example type 3 steering device.
- (11) FIG. 11 is an illustrative capability of a type 3 steering device.
- (12) FIG. 12 is a schematic depiction of an example type 1 steering device.
- (13) FIG. 13 is another schematic depiction of an example type 1 steering device.
- (14) FIG. 14 is an illustrative capability of a type 1 steering device.
- (15) FIG. 15 is a schematic depiction of an example type 2 steering device.
- (16) FIG. 16 is a schematic depiction of an example arrangement of individual beam steering devices.
- (17) FIG. 17 is a schematic depiction of an example arrangement of individual beam steering devices.
- (18) FIG. 18 is another schematic depiction of an example type 2 steering device.
- (19) FIG. 19 is an illustrative steering capability of an individual beam steering device.
- (20) FIG. 20 is an illustrative steering capability of an individual beam steering device.
- (21) FIG. 21 is an illustrative steering capability of an individual beam steering device.
- (22) FIG. 22 is an illustrative comparison of steering capability for a number of individual beam steering devices.
- (23) FIG. 23 is an illustrative comparison of steering capability for two individual beam steering devices, showing an overlap region.
- (24) FIG. 24 is a schematic depiction of an actuator coupled to steering layers of more than one individual beam steering device.

- (25) FIG. **25** is another schematic depiction of an example type 2 steering device.
- (26) FIGS. **26-28** provide example schematic depictions of an actuator for a beam steering device.
- (27) FIG. **29** is a schematic depiction of an actuator arrangement for a beam steering device.
- (28) FIG. **30** is a schematic depiction of movement directions for a beam steering device.
- (29) FIG. **31** is a schematic depiction of another embodiment of movement directions for a beam steering device.
- (30) FIGS. **32-35** are illustrative operating diagram(s) for a beam steering device.
- (31) FIG. **36** is a schematic depiction of a variaxial lens utilizable as a steering lens for embodiments of the present disclosure.
- (32) FIG. **37** is a schematic depiction of a write-able lens for embodiments of the present disclosure.
- (33) FIG. **38** is a schematic block diagram of a beam steering controller.
- (34) FIG. **39** is a schematic block diagram of a beam steering controller.
- (35) FIGS. **40-42** are schematic depictions of illustrative swapping operations for beam steering according to aspects of the present disclosure.
- (36) FIG. **43** is a schematic flow diagram of a procedure to command actuators of a beam steering device.
- (37) FIG. **44** is a schematic flow diagram of a procedure to command actuators, and swap optical paths, of a beam steering device.

DETAILED DESCRIPTION

- (38) Referencing FIG. **3**, an example beam steering device **300** is schematically depicted, having a number of aspects as set forth throughout the present disclosure. The example beam steering device **300** overcomes and/or mitigates a number of drawbacks of previously known steering systems, including at least small steering angles, small steering apertures, low steering speeds (and/or frequencies), and/or a requirement for high capability actuating elements for steering lenses.
- (39) The example system **300** includes an EM source **302**, for example a collimated light beam, laser, etc. In certain embodiments, the EM source **302** may be a fiber laser source or other fiber optic light source, and/or may be any other type of light source including a non-fiber light source. In certain embodiments, the EM source **302** may be provided as collimated light, and/or a converging and/or diverging light source, and/or combinations of these (e.g., in separate axes). In certain embodiments, the source light may be adjusted by a lens, a varifocal lens, and/or an aspherical collimating lens, before being provided to the negative lens(es). In certain embodiments, characteristics of the source light may be adjusted to the desired outlet characteristics, e.g., using net convergence and/or divergence, including in one or more axes, through the optical components of the steering system (e.g., the negative lens(es), field lens(es), and/or positive lens). Example, and non-limiting, light sources includes a laser diode, a fiber, and/or another laser component or collimated light source. As utilized herein, a light source, beam, or similar terms are understood to include electromagnetic (EM) radiation of any frequencies, including without limitation optical light, visible light, infrared radiation, ultraviolet radiation, microwaves, radio waves, and/or any selected frequency or range of frequencies relevant to the optical components of the steering system.
- (40) The example of FIG. **3**, and throughout the present disclosure, is generally described in terms of steering an emitted light beam (e.g., incident beam **102** emitted as steered beam **106**), for convenience of the present description. Additionally or alternatively, beam steering devices described throughout the present disclosure may be utilized to steer a received beam—for example a beam received from an object (e.g., emitted and/or reflected by the object), whereby the steering device directs the optical path of the beam steering device to the observed object, and steers the beam to final receiving optics or other observing components (e.g., a detection array or other device in FIG. **3** may replace the EM source **302**). It can be seen that a given beam steering device may steer for emission or observation, including utilizing separate steering components for each of

the emission and observation operations (e.g., reference FIGS. 15-18 and the related descriptions), utilizing the same steering components at distinct operating conditions (e.g., steering with the same components for emission at a first time, and for observation at a second time), and/or simultaneously (e.g., wherein the EM source **302** and/or observing components are configured to operate simultaneously, such as utilizing beam splitters or other optical components to separate the EM source **302** and observing components, and/or where the EM source **302** and observing components are configured to be aligned, such as with the EM source **302** directed through transparent observing components).

(41) In the example of FIG. 3, the system **300** includes an optional collimator lens **304**, for example to provide a selected divergence characteristic to the incident beam **302**. The collimator lens **304** may provide collimated light (e.g., correcting a divergence of the incident beam **302**, such as might be provided by a fiber laser), and/or light having a diverging or converging characteristic (e.g., to correct for net convergence or divergence in the remainder of the beam steering device **300**, and/or to provide a final emitted beam **106** having a selected converging and/or diverging character). The selected divergence characteristic of the collimator lens **304** can be designed based on the divergence characteristic of the incident beam **302**, the desired (and/or required) divergence characteristic of the emitted beam **106**, and/or according to the converging and/or diverging effect applied to the steered beam by other components of the beam steering device **300**.

(42) The example system **300** further includes at least one steering layer **306**, which may be a steering layer **306** according to any aspect of the present disclosure. The example steering layer **306** receives the collimated beam **312** (and/or the incident beam **102**), and provides steering operations by displacement of one or more lenses of the steering layer **306**, providing an initially steered beam **314**.

(43) An example steering layer **306** includes one or more steering lenses (typically a single lens, or two cooperating lenses), which are coupled to an actuator **318** that moves one (or more) associated steering lenses through a movement path. The steering layer **306** may include a negative lens, two cooperating negative lenses, a positive lens, two cooperating positive lenses, and/or a negative lens cooperating with a positive lens. The utilization of two lenses in a steering layer **306** allows for steering in two directions simultaneously (e.g., where one lens steers along a first axis and where the second lens steers along a second axis). For convenience of description, many examples throughout the present disclosure describe two steering lenses, where a first lens is moved in a first steering direction and a second lens is moved in a second steering direction. It will be understood that the movement directions of the lenses of a steering layer **306** may align with steering directions, or may be mis-aligned with the steering directions. For example, where steering is considered in two directions (e.g., an azimuthal direction and an elevation direction), a first example beam steering device **300** includes a first steering lens that moves in the azimuthal direction and a second steering lens that moves in the elevation direction. A second example beam steering device **300** includes the first steering lens that moves in a first direction, and a second steering lens that moves in a second direction, where the first and second direction are not aligned with the steering directions. In a further second example beam steering device **300**, the target steering directions and/or the target movement positions of the steering lenses may be transformed (e.g., using a rotation, look-up table, or the like) allowing for steering control in the target steering direction using the movement of both lenses in cooperation. In certain embodiments, the first movement direction and the second movement direction may be perpendicular (whether aligned with the steering axes or not), but the movement directions need not be perpendicular. It will be seen that, where the movement directions are not perpendicular, the overall steering capability of the beam steering device **300** may be lower (e.g., a reduced magnitude of steering capability for one or both steering directions) relative to an equivalent beam steering device **300** having perpendicular movement directions. However, the movement capability of a beam steering device **300** can be provided to have sufficient capability for target steering directions, for example using

one or more of (examples are not limiting): enhanced telescopic magnification (e.g., reference FIGS. 3-9); enhanced radial (and/or virtual) magnification (e.g., reference FIGS. 12-14); enhanced displacement of one or more steering lenses (e.g., a greater absolute displacement capability); and/or the utilization alternative steering components (e.g., where multiple steering layers are available, such as depicted in FIGS. 15-23). In certain embodiments, enhancement techniques may be differentiated by moving direction (e.g., a first steering lens having a greater displacement capability than a second steering lens); by steering direction (e.g., a greater capability for a first steering direction, such as azimuthal, relative to a second steering direction, such as elevation); by telescopic magnification capability (e.g., greater magnification in a selected movement direction and/or steering direction); by radial magnification capability (e.g., greater magnification in a selected movement direction and/or steering direction); and/or combinations of these. Lenses described and/or depicted throughout the present disclosure are generally set forth as spherical lenses for convenience of description, but it will be understood that lenses may have differential optical characteristics in a given direction (e.g., aspherical lens, anisotropic lens, negative power and/or positive power of the lens by direction, etc.), and/or may only have optical support for a given direction (e.g., a cylindrical lens).

(44) One of skill in the art, having the benefit of the present disclosure and information ordinarily available when contemplating a particular system, can readily select lens configurations and characteristics for a given embodiment. Without limitation to any other aspect of the present disclosure, certain considerations for determining lens configurations and characteristics include, without limitation: movement capability (displacement and/or speed) of available actuators; orientation of movement directions (to each other, and/or to steering axes); the target steering envelope (e.g., magnitude and/or direction of steering); the available axial footprint of the beam steering device (e.g., axial extent of the steering components and/or a housing defining the steering components); a beam size of the incident beam; a beam size of the steered beam; relative costs of lens components (e.g., spherical, aspherical, anisotropic, astigmatic, positive and/or negative lenses, cylindrical lenses, and/or write-able lenses—e.g. reference FIGS. 36, 37); power throughput of the incident beam and/or an observed beam; heat transfer characteristics and/or active cooling characteristics available for components of the beam steering device (e.g., capital costs, integration costs, footprint costs (e.g., size, weight, systems, interfaces, controls), operating costs, and/or performance effects or limitations); the focusing characteristic of the steered beam progressing through the beam steering device; the number and geometry of available steering paths relative to the number and geometry of steered beams (e.g., where switching of steering responsibility between paths can enhance steering capability, steering response time, heat generation, and/or component utilization—e.g., reference FIGS. 15-25, 39-42, and 44); and/or duty cycles of steering operations (e.g., steering angles and/or frequencies, and or power throughput; including a description of operating times corresponding to these; including consequent effects on steering actuators, component time-at-temperature, cooling system, and the like).

(45) The example beam steering device **300** further includes one or more steering actuator(s) **318** configured to move the steering lenses of the steering layer **306**. An example actuator **318** includes a piezoelectric actuator, for example a piezo responsive armature that displaces in response to an applied electric field, thereby moving an associated steering lens. In certain embodiments, a piezoelectric actuator has a modest displacement capability (e.g., a few millimeters), which may be preserved by separating actuators **318** into a first actuator **318** associated with a first steering lens, and a second actuator **318** associated with a second steering lens. Embodiments herein provide for significant steering capability, such that even with modest movement capabilities provided by piezoelectric actuators, highly capable steering (e.g., ± 10 degrees, ± 20 degrees, ± 30 degrees, ± 45 degrees, etc.) can nevertheless be achieved. An example actuator **318** includes an electromagnetic actuator, which may be of any type such as a linear actuator and/or a rotary-to-linear actuator of any type. An example actuator **318** includes an electromagnetic actuator (e.g.,

reference FIGS. 27-28) capable to steer a lens in one, or both, directions at the same time. Actuators described herein are capable to move a steering lens in a generally linear direction (e.g., along a movement axis and/or a steering axis), although a travelling path of a steering lens need not be linear (e.g., operating a transform between actuator position(s) and target steering directions). An example actuator **318** includes a write-able lens (e.g., reference FIGS. 36, 37, and the related descriptions), for example where movement operations of the steering lens are executed by adjusting a configuration of a write-able lens (e.g., providing a selected electric field to an electro-optical substrate). In certain embodiments, an actuator **318** may differ between a first steering lens and a second steering lens of a steering layer (e.g., a first type of actuator for the first steering lens, and a second type of actuator for the second steering lens), and/or for steering lenses between layers (e.g., a first type of actuator for a first steering layer, and a second type of actuator for a second steering layer). Different actuator types may be included for any reason, including at least providing differential steering capability to each movement direction and/or steering axis (e.g., differential displacement magnitude, steering speed, lifetime actuating cycles, and/or size/weight of steered lenses), and/or providing differential actuators dependent upon the available footprint for each (e.g., utilizing distinct input/output resources; utilizing distinct power resources; having differential sizes available at an actuating location within a system having the beam steering device; having differential integration requirements and/or interfaces to the system; etc.).

(46) The example beam steering device **300** includes a field lens **308**. The example field lens **308** is positioned at an intersection of a focal plane of an emission lens **310** and an effective focal plan of the steering layer **306** (e.g., the net focal position of lenses of the steering layer **306**. The field lens **308** ensures the steered beam **316** is fully incident on the emission lens **310** (e.g., reducing vignetting losses). The emission lens **310** is the final optical element of the beam steering device **300**, whereby the emitted beam **106** is the final steered beam. The emission lens **310** and the field lens **308** can be sized according to the desired steering capability, beam size, and axial length of the beam steering device **300**. The emission lens **310** can have a selected optical power to provide the selected convergence/divergence character (e.g., collimated) of the steered beam **106**, to provide the selected telescopic magnification (e.g., 1×, 1.5×, 2×, 3×, etc.), and/or selected axial length of the beam steering device **300**. The axial positioning of the components of the beam steering device **300**, the optical power of the components, and the size of the components, can be selected to provide the appropriate magnification for beam steering capability and steered beam size, and to ensure that the steered beam does not experience vignetting losses.

(47) It will be understood that a system including the beam steering device **300** may have further optics that the emitted beam **106** passes through before emission from the system. The example beam steering device **300** allows for significant steering capability (e.g., ± 8 deg., ± 10 deg., ± 15 deg., ± 20 deg., and/or ± 30 deg.) with an arbitrary aperture and/or emitted beam size. The example beam steering device **300** utilizes telescopic magnification to enhance the beam steering capability and the aperture size, allowing for a greater steering capability and/or steered beam size than available in previously known systems.

(48) Referencing FIG. 4, an example embodiment of a beam steering device **400** is schematically depicted. The example beam steering device **400** includes a steering layer **306** having two negative lenses **402**, **406** that steer an incident beam **102** in two directions, providing the steered beam **106** from an emission lens. The example beam steering device **400** includes a selected telescopic magnification (e.g., the ratios of the focal lengths between the emission lens and the effective lens equivalent of the steering lenses **402**, **404**), and/or steering capability (e.g., movement capability of the steering layer **306** combined with telescopic magnification). The movement directions of the steering lenses **402**, **404** may be perpendicular or offset from perpendicular, and/or may be aligned with steering directions (e.g., one lens **402**, **404** controls a first steering direction, and the other lens **404**, **402** controls a second steering direction) or offset from the steering directions (e.g., the lenses **402**, **404** move in cooperation to provide the selected steering angle(s)).

(49) The utilization of negative lenses **402**, **404**, as set forth herein, should be understood broadly. The negative lenses include a net effective concave aspect toward the incident light to be steered. While the negative lenses are depicted as concave lenses, it will be understood that the lenses may include any one or more of, without limitation: a concave lens, a net concave lens (e.g., having a concave and a convex portion, with a greater optical effect of the concave portion), a write-able lens (e.g., reference **36**, **37**, and the related description; also reference varifocal lens as described in PCT Patent Application PCT/US19/57616, entitled “SYSTEM, METHOD, AND APPARATUS FOR NON-MECHANICAL OPTICAL AND PHOTONIC BEAM STEERING” [EXCT-0004-WO], filed 23 Oct. 2019, which is incorporated herein by reference in the entirety for all purposes), and/or a Fresnel lens (e.g., having a net concave aspect).

(50) The example beam steering system includes two of the negative lenses **402**, **404** that steer in two directions that are referenced herein as an azimuthal direction (e.g., direction in a horizontal plane) and an elevation direction (e.g., direction in a vertical plane), although an example beam steering system may include only a single negative lens that steers in a selected direction (e.g., where steering in only a single axis is acceptable), a single negative lens that steers in two selected directions, or two of the negative lenses that steer in two selected directions. The two directions may be orthogonal, allowing for a continuous region of steering, or non-orthogonal, which will reduce the continuous region of steering, for example providing for gaps in the steering capability region, but may nevertheless provide for sufficient steering capability in certain embodiments. Additionally, or alternatively, the movement directions of the negative lenses may correspond to the steering directions (e.g., azimuthal and elevation movement corresponding to azimuthal and elevation steering), but they need not. For example, where the two negative lenses are capable to move orthogonally, then the lenses are capable of steering in a direction corresponding to azimuthal and elevation, but may have movement controlled in a transformed space to achieve the desired steering. It can be seen that the steering directions and the lens movement directions may correspond to any selected axes, including neither of the steering or lens movement occurring in a direction corresponding to “azimuthal” or “elevation,” although these terms are used herein for convenience and clarity of the description.

(51) In the example of FIG. **4**, the size and optical function (e.g., negative optical effect) may be the same or similar, providing for equivalent telescopic magnification and steering capability in each direction. However, the negative lenses need not be identical, for example, if differential telescopic magnification in a given direction is acceptable (or desirable), and/or if anisotropy in the steering direction capability is also acceptable (or desirable). Additionally, the negative lenses may be distinct lens types (e.g., one lens a concave lens, with the other lens corresponding to a variaxial lens or a Fresnel lens), whether the negative lenses **402**, **404** have the same functionality or distinct functionality.

(52) In the example of FIG. **4**, the negative lenses **402**, **404** cooperate in providing an effective, or virtual, focal plane of the negative lenses, that is aligned with a corresponding focal plane of the positive lens, providing for a steered beam, with steering controlled in a first direction by movement of one of the negative lenses, and in a second direction by movement of the other one of the negative lenses **402**, **404** (and/or controlled to a selected steering location in a transformed space relative to the movement directions, e.g., reference FIGS. **31-35** and the related descriptions).

(53) It can be seen that FIG. **4** and described variations provide for a number of advantages over previously known steering systems. Further description of some of the features are described following, as well as additional aspects of certain embodiments. However, it is informative to note certain advantageous aspects of the embodiments of FIG. **4** as set forth thus far. Embodiments of FIG. **4** provide for improved resulting effective aperture sizes, as the steered beam is magnified by the cooperative operation the negative lenses **402**, **404** and the positive lens **310**. Additionally, the telescopic magnification of the embodiment of FIG. **4** serves to enhance the effective steering capability, rather than reduce the effective steering capability as in previously known steering

systems. Accordingly, the net improvement in effective steering capability and aperture size is more than proportional to the magnification ratio of the corresponding systems. Further, as the negative lenses **402**, **404** can be sized proportionally smaller than the first lens of previously known systems, and the telescopic magnification supports an increasing steering angle, the positive lens **310** can be provided at a reasonable size and still avoid vignette losses. Additionally, as the positive lens (emission lens **310**) is not moved in the embodiment of FIG. **4**, even where a large positive lens is utilized, it results in fewer disadvantages relative to previously known systems. Further still, the virtual focal plane (e.g., focal plane provided by the effective equivalent lens of the negative lenses **402**, **404**), and resulting focal point at a given operating configuration, provided by the negative lenses **402**, **404** does not result in a physical focus, or concentration, of the steered beam. Instead, the beam experiences a smooth divergence throughout steering operations, with a net diffusion, but not convergence or divergence (i.e., the collimated light remains collimated if desired), after exiting the positive lens as a steered beam. Accordingly, the embodiment of FIG. **4** is capable of a higher power throughput than previously known systems, as there are no concentrations of the steered energy that may result in hot spots or other limitations due to the concentration of energy at a focal point. Additionally, the embodiment of FIG. **4** results in a reduced axial distance between the first and second lens portions (e.g., between the first lens and the second lens of previously known embodiments, or between the negative lenses and the positive lens of the embodiment of FIG. **4**), for a given steering capability.

(54) While the embodiment of FIG. **3** shows a compensating divergence of the negative lenses and convergence of the positive lens, it will be understood that net divergence or convergence of the steered beam **106** may be acceptable, or desirable, for certain systems and/or at certain operating conditions. Additionally or alternatively, the net convergence or divergence in each steered axis may be varied, if desired and/or acceptable, and/or may be eliminated for one axis but not the other.

(55) For the embodiments of FIGS. **3** and **4**, movement of the lenses of the steering layer **306** results in a steering amount as set forth in Equation 4:

(56) Steering angle for example embodiments
$$\theta_i = \tan^{-1} \left(\frac{M}{f_n} \Delta_{sub,i} \right) \quad \text{Eq. 4}$$

(57) Equation 4 sets forth the displacement for a given steering axis, and may be separated into a first component for the first negative lens **402**, and a second component for the second negative lens **404**. The value M is the net telescopic magnification for the steering system, the value $\Delta_{sub,i}$ is the component displacement (for the respective negative lens **402**, **404**), and $f_{sub,n}$ is the effective negative focal length, which is a composite of the individual focal lengths of the series negative lenses **402**, **404**.

(58) It can be seen from Equation 4 that telescopic magnification in the embodiments of FIGS. **3** and **4** increases the steering capability of embodiments of the steering device herein, in contrast to previously known systems where magnification > 1 reduces the steering capability.

(59) An example system includes two negative lenses each having an of -40 mm, and a radius of 7.5 mm, and a larger positive lens having a focal length of 50 mm and a radius of 18.867 mm. In the example arrangement, an axial distance between the positive lens and a closest negative lens may be about 24.876 mm, which may be readily determined by one of skill in the art contemplating a particular system, and having selected appropriate negative lenses and positive lenses, and aligning the effective focal plane of the negative lenses with the focal plan of the positive lens. In the example wherein one of the negative lenses provides a displacement of 1 mm, application of Eq. 4

(60)
$$\left(\tan^{-1} \left(\frac{18.67 * 1}{7.5 * 40} \right) \right)$$

of +/-0.063 radians, or 3.62° of steering. If the magnification is increased to 5, then 1.5 mm of displacement provides

(61)
$$\left(\tan^{-1} \left(\frac{5 * 1.5}{1 * 40} \right) \right) + / - 0.185$$

radians, or 10.62 degrees. Note that, in the example, the other negative lens may have a slightly

different configuration and resulting steering performance. For example, in one embodiment the first negative lens may have a radius of 7.5 mm, and the second negative lens may have a slightly larger radius (e.g., 7.596 mm, or ~7.6 mm), which may result in slightly different values for the component performance of Eq. 4 corresponding to the second steered axis. In certain embodiments, the positive lens may have an anisotropic characteristic (e.g., an elliptical shape, anisotropic focal length—e.g., utilizing an anisotropic optical material, a configured Fresnel lens, and/or a configured variaxial lens, or the like) to deliver equivalent performance in each steering direction, and/or a steering controller may utilize movement commands for each negative lens that compensate for variabilities in steering commands. In certain embodiments, for example when any of the parameters of Eq. 4 have a frequency dependency (e.g., a frequency of the electromagnetic radiation of the steered beam), a temperature dependency, a voltage dependency, or the like, a steering controller may compensate for those dependencies in the provision of steering commands.

(62) Referencing FIG. 5, an example beam steering device **500** includes one or more field lenses **502**, **504** may be provided, allowing for a reduction in the size of the positive lens **310**, and a minor reduction in the axial length of the steering system. The field lenses **502**, **504** are depicted as closely coupled to the negative lenses **402**, **404**, but the field lens(es) **502**, **504** may be positioned anywhere downstream of the negative lenses **402**, **404**, and/or individually downstream of the corresponding negative lens (e.g., field lens **502** downstream of negative lens **402**), but upstream of the emission lens **106**. The close coupling of the field lens(es) to the steering lenses may allow for a reduction in the size of the field lens(es). In certain embodiments, it may be desirable to tune the focal lengths of the lenses (e.g., steering lenses, negative lenses, field lens(es), and/or positive/emission lens) based on the presence of the field lens(es) relative to embodiments without the field lens(es), and/or based on the size and/or position of the field lens(es).

(63) Field lenses **502**, **504** may be positioned as shown in FIG. 5, with a single field lens (e.g., one of the depicted field lenses), and/or with an additional field lens upstream of the negative lenses. Example and non-limiting arrangements are described following, to illustrate some of the adjustments that may be made in certain embodiments having one or more field lenses. The examples illustrate some of the parameters that may be adjusted, but are not limiting descriptions.

(64) An example includes a single field lens positioned between the negative lenses, with the first negative lens having a radius of 7.5 mm and a focal length of -40 mm, the field lens having a radius of 7.547 mm and a focal length of 141.277 mm, the second negative lens having a radius of 7.58 mm and a focal length of -40 mm, and the positive lens having a radius of 16.714 mm and a focal length of 51.65 mm. In the example, an axial distance between the positive lens and a closest negative lens may be about 23.225 mm.

(65) Another example includes two field lenses, arranged as depicted in FIG. 4, with a first negative lens having a radius of 7.5 mm and a focal length of -40 mm, the first field lens having a radius of 7.547 mm and a focal length of 157.503 mm, the second negative lens having a radius of 7.582 mm and a focal length of -40 mm, the second field lens having a radius of 7.664 mm and a focal length of 107.865 mm, and the positive lens having a radius of 13.494 mm and a focal length of about 52.286 mm. In the example, an axial distance between the positive lens and a closest negative lens may be about 22.59 mm.

(66) It can be seen that the embodiments set forth in FIGS. 3-5 provide for high capability steering, with relatively small displacement of the negative lens(es). The example embodiments described magnification ranges between about 2.5 to 5, with steering capabilities between about 3 degrees per mm displacement to about 6 degrees per mm of displacement. Magnification ranges can be readily provided below about 2.5 (e.g., to increase steering accuracy where high steering capability is not required or desired) and/or to values of 10, 20, or greater, with corresponding increases in the steering capability and resulting effective aperture size. The magnification value may be selected based upon input light density, output light density targets, steering capability desired, aperture size desired, or the like. Additionally or alternatively, a number of steering assemblies such as those

depicted in FIGS. 3-5, or as described herein, may be provided (e.g., as a lenslet array). In certain embodiments, embodiments of a steering device can readily be provided having a steering capability of ± 5 degrees, ± 10 degrees, ± 15 degrees, ± 20 degrees, and/or ± 30 degrees. In certain embodiments, a steering device can be designed with greater than 30 degrees of capability, including up to about 60 degrees of steering capability.

(67) It will be understood, as described in further detail following, that certain steering capability values interact with frequency response values of mechanical steering components, providing for a reduced steering frequency capability at high steering capability angles (e.g., >20 degrees, >30 degrees, or more), and/or requiring a high degree of magnification at high steering capability angles. High magnification requirements can result in large components (e.g., of the positive lens), increased footprint of the beam steering device, and/or reduced steering precision. Accordingly, the steering capability, steering frequency capability, and magnification requirements are related in a multi-dimensional space, where any one of the capabilities (e.g., aperture size, steering capability, power throughput capability, and/or steering frequency capability) can be provided at almost any value, while at extreme capability values, one or more of the other capabilities and/or the telescopic magnification requirement become more constrained. In certain embodiments, steering capability values up to about ± 20 degrees can be provided with modest magnification requirements (e.g., $5\times$ to $20\times$, without limitation) and high frequency capability (e.g., up to at least several kHz), where extreme steering capabilities (e.g., greater than ± 30 degrees) are possible at more limited frequency capabilities (e.g., up to about 100 Hz) and/or with greater magnification (e.g., $20\times$ to $50\times$) and consequent increases in the beam steering system footprint and/or reduction in steering precision. One of skill in the art, having the benefit of the present disclosure, can readily design a steering system as set forth herein to meet desired capabilities within the multi-dimensional space, in accordance with Eq. 4 and other considerations set forth herein, and that will be understood to that person having knowledge of available optical components, mechanical steering components, and information about the contemplated system. Certain considerations for determining a particular configuration for a system include, without limitation, optical characteristics of available lenses, mechanical displacement capabilities and constraints, available footprint for the steering system (e.g., axial size; diameter; weight; power provision; cooling provision; and/or control capabilities including I/O, available sensors, and/or available actuators), capital cost considerations, operating cost considerations, and/or manufacturing constraints (e.g., tolerances of components, available materials, available operations such as machining, coating, finishing, etc.).

(68) It will be understood that the aperture size and final steered beam size can be configured according to the incident beam size **102**, the applied telescopic magnification (e.g., as described in relation to type 3 steering devices herein), and/or the lens sizes of steering components. Certain aspects that increase the emitted beam size relative to the aperture size (e.g., where aperture size corresponds to the emission lens **310**, where emitted beam size to aperture size may be referenced as aperture utilization) include aspects that increase a common area between steering lenses (e.g., determined according to a maximum displacement, size, and/or axial displacement of the steering lenses; and/or further determined according to an inclusion of field lens(es) between steering lenses). Accordingly, one or more design aspects can increase the aperture utilization include: increasing the size of one or both of the steering lenses; increasing a telescopic magnification (e.g., type 3) of the beam steering device (e.g., which reduces the required displacement to achieve a given steering capability, and increases the beam size through magnification); utilizing a field lens between the steering lenses (e.g., reference FIG. 5) which increases the effective common area between the steering lenses; and/or increasing a radial magnification (or virtual displacement; e.g., type 1) of the beam steering device (e.g., which reduces the required displacement to achieve a given steering capability).

(69) For convenient reference, embodiments of a beam steering device according to FIGS. 3-11 and the related descriptions may be referenced as a type 3 steering device. Any one or more aspects of

the following embodiments may be incorporated with or combined with any one or more of embodiments set forth throughout the present disclosure, including aspects of a type 3 steering device combined with aspects of another type of steering device (e.g., type 1 such as described in reference to FIGS. **12-14**, and/or type 2 such as described in reference to FIGS. **15-25**). The description utilizing types is provided for clear illustration of certain concepts of the present disclosure, and is not limiting to embodiments described herein. Accordingly, a beam steering device may include elements from one or more of the types, for example utilizing type 3 components for steering in a first direction, and type 1 components for steering in the second direction. Type 2 beam steering devices may include steering elements each configured according to a type 3 configuration, a type 1 configuration, combinations of these, and/or configurations of steering components using elements described herein regardless of the relationship of the steering components to a type 3 and/or type 1 configuration. In certain embodiments, a type 3 steering device utilizes telescopic magnification to enhance steering operations of the beam steering device. In certain embodiments, a type 1 steering device utilizes radial magnification (and/or displacement of a virtual image) to enhance steering operations of the beam steering device. Additionally, or alternatively, one or more aspects of the preceding embodiments may be incorporated with or combined with any one or more aspects of embodiments described throughout the present disclosure.

(70) FIG. **6** depicts an embodiment as an example type 3 beam steering device **400**, consistent with aspects of embodiments set forth in FIG. **4** and the related description. As seen in FIG. **6**, the steerer consists of three lenses; two small moving negative lenses **402**, **404** and one fixed larger positive lens **310**. Displacement of those two negative lenses **402**, **404** can be done by a variety of methods, such as small electromagnetic motors, piezoelectric actuators, and/or changing a position of a write-able lens as one or both of the negative lenses **402**, **404**. An example beam steering device **400** further includes a collimator lens **304**, having selected optical power to adjust the convergence/divergence characteristic of the incident beam **102**, including for example an aspherical lens to adjust a fiber laser EM source into a collimated beam.

(71) According to any aspect of the present disclosure, the steering lenses **402**, **404** can be estimated as an equivalent lens having effective optical activity equivalent to the steering lenses **402**, **404**. For example, a single negative lens with a moving focal point may be considered as an estimate for the two moving negative lenses **402**, **404**. The focal plane of the equivalent conceptual lens coincides with a focal plane of the emission lens **310**. An example performance of the example beam steering device of FIG. **6** is depicted in FIG. **7**, where the example steering is depicted in only a single direction (via displacement of negative lens **402**, in the example) for clarity of the present description.

(72) The angle of deflection in x and y axes (e.g., where the x axis aligns with a movement direction of a first steering lens, and where the y axis aligns with a movement direction of a second steering lens) are related to the displacement in those directions ($\Delta_{\text{sub.x}}$ and $\Delta_{\text{sub.y}}$), and the focal length ($f_{\text{sub.r}}$) of the recollimator lens **310** as follows in Equations 5 and 6:

$$(73) \quad \theta_x = \pm \tan^{-1} \left(\frac{\Delta_{\text{sub.x}}}{f_r} \right)$$

Eq. 5 Deflection angle of steered beam in the “x” direction

$$(74) \quad \theta_y = \pm \tan^{-1} \left(\frac{\Delta_{\text{sub.y}}}{f_r} \right)$$

Eq. 6 Deflection angle of steered beam in the “y” direction

(75) As set forth throughout the present disclosure, the x and y directions of the two steering lenses may be aligned with the logical steering axes of the beam steering device (e.g., the desired direction reference frame for steering nomenclature), and/or may be un-aligned with the logical steering axes. Additionally or alternatively, the x and y directions may be perpendicular, and/or may be mis-aligned. In certain embodiments, the mis-alignment of the x and y directions, and/or the perpendicularity of the x and y directions, may be due to design considerations (e.g.,

positioning of actuators in a confined space, ease of accommodation of movement, etc.), and/or due to manufacturing considerations (e.g., allowing for manufacturing tolerances of installation of actuators and/or lens movement direction; allowing for installation with lens movement within a range and/or at arbitrary directions—for example to simplify installation and/or integration; and/or allowing for a change of the logical steering axes after the installation and/or integration of the beam steering device into a system).

(76) Referencing FIG. 8, an example beam steering device **800** including a steering layer **306** having a first positive lens **602** and a second positive lens **604**. As seen in this FIG. 8, the beam steering device **800** includes four lenses, two small moving positive lenses **602**, **604**, one fixed positive field lens **308**, and one fixed positive recollimator/emission lens **310**. An actuator displaces each positive moving lens **602**, **604** in the respective movement direction (e.g., perpendicular or not, and aligned with logical steering axes, or not). In certain embodiments, a collimator lens **304** is provided to provide a selected convergence/divergence characteristic to the incident EM beam **102**.

(77) In the example of FIG. 8, the positive lenses **602**, **604** may be estimated as an equivalent positive lens, with a moving focal point equivalent to the two moving positive lenses **602**, **604**. The focal plane of that effective equivalent positive lens and the focal plane of the fixed positive recollimator/emission lens **310** coincide. The fixed positive field lens **308** is located at the focal plane of the fixed positive recollimator lens **310** (and, accordingly, at the focal plane of the effective equivalent positive lens). The example beam steering device **800**, having an equivalent steering capability and beam size for a corresponding beam steering device **400**, **500** (e.g., reference FIGS. 4-6), may have a greater axial footprint relative to the corresponding beam steering device **400**, **500**—for example the focal plane of the effective equivalent positive lens of FIG. 8 will be downstream of the steering layer **306**, compared to the focal plane of the effective equivalent negative lens of FIG. 4, which will be upstream of the steering layer **306**. The position of the focal plane of the effective equivalent lens (positive or negative) contributes to the axial footprint of the beam steering device **400**, **800**. An example performance of the example beam steering device of FIG. 8 is depicted in FIG. 9, where the example steering is depicted in only a single direction (via displacement of negative lens **602**, in the example) for clarity of the present description.

(78) With regard to the example of FIGS. 8 and 9, the angle of deflection in the x and y axes (e.g., corresponding to a movement direction of the first and second steering lens, respectively) is related to the displacement in each of the x and y directions, and the focal length of the recollimator lens as described in Equations 5 and 6. Referencing FIG. 10, an example beam steering device **1000** includes two steering layers **306**, each having one or more steering lenses coupled to respective actuators. The steering lenses and actuators may be of any type as set forth throughout the present disclosure. The example steering device **1000** includes the first steering layer **306** (e.g., left-most steering layer) including two negative steering lenses **1002**, **1004**, and the second steering layer **306** (e.g., right-most steering layer) including two positive steering lenses **1006**, **1008**). In the example of FIG. 10, one of the positive steering lenses **1008** further operates as an emission lens **310**, although an additional emission lens **310** may be provided if desired. The example beam steering device **1000** includes a fixed positive lens **1010** provided upstream of the two negative steering lenses **1002**, **1004**. The example beam steering device **1000** may further include an optional collimator lens **304**, for example to configure the incident EM beam **102**. The beam steering device **1000** displaces each negative steering lens and each positive steering lens, utilizing actuators (not shown) operatively coupled to each steering lens **1002**, **1004**, **1006**, **1008**. The movement of each pair of steering lenses may be aligned (e.g., with the logical steering axis, and/or with each other) or un-aligned, and additionally one or both steering layers **306** may include perpendicular movement of each steering lens (e.g., **1002** movement direction $\perp$ to **1004** movement direction, and/or **1006** movement direction $\perp$ to **1008** movement direction), or non-perpendicular movement for one or both steering layers.

(79) In the example of FIG. 10, the first steering layer 306 (e.g., left side negative lens pair in the example of FIG. 10) can be estimated with an equivalent effective negative lens having a moving focal point, and the second steering layer 306 (e.g., right side positive lens pair) can be estimated with an equivalent effective positive lens also having a moving focal point. The fixed positive lens 1010 sits at an axial displacement of $\frac{1}{2} F_{\text{sub.fp}}$ (the focal length of the fixed positive lens 1010) from the equivalent effective negative lens, and at an axial displacement of $F_{\text{sub.fp}}$ from the equivalent effective positive lens. In the example of FIG. 10, the focal length of the equivalent effective positive lens is equal to the focal length of the fixed positive lens 1010, and the focal length of the equivalent effective negative lens is equal to

$$(80) \frac{-F_{\text{fp}}}{4}.$$

Accordingly, the fixed positive lens 1010 is located at the focal plane of the equivalent effective positive lens. An example beam steering device 1010 includes the focal length of each moving negative lens 1002, 1004 as half of the focal length of the fixed positive lens 1010. An example beam steering device 1010 includes the focal length of each moving positive lens as twice the focal length of the fixed positive lens 1010. The example beam steering device 1000 is non-limiting, and each steering layer 306 may include positive lenses, negative lenses, or combinations thereof. In certain embodiments, the first beam steering layer 306 (the left layer) has a net negative optical power, and the second beam steering layer 306 (the right layer) has a net positive optical power. An example performance of the example beam steering device of FIG. 10 is depicted in FIG. 11, where the example steering is depicted in only a single direction (via displacement of negative lens 1002 and positive lens 1006, in the example) for clarity of the present description. The steering capability of the example beam steering device 1010 in each direction is a function of the telescopic magnification (e.g., determined according to the optical power of the lenses steering in the given direction) and the displacement. Accordingly, for equivalent steering capability in each direction and with equivalent displacement capability of steering lenses, the lens focal power in each direction should be equivalent. If steering capability is distinct (e.g., different in each direction) and/or if displacement capability is distinct, the lens power in each direction may likewise be distinct.

(81) In the example of FIG. 10, the moving negative and positive lenses are depicted moving in opposite directions to support steering in a given direction (e.g., lenses of the steering layers are moving cooperatively). In the example of FIG. 10, the steering layers 306 utilize corresponding steering lenses (e.g., first negative lens 1002 and first positive lens 1006) to cooperate and provide steering capability for a given direction. It will be understood that movement may be in the same or opposing directions (e.g., depending upon the positive/negative optical power of the corresponding lenses, and/or the control scheme selected that may utilize counter movement during at least certain operating conditions). It will be understood that movement between layers may be in the same direction (e.g., first negative lens 1002 and first positive lens 1006 aligned) and/or in distinct directions (e.g., a first steering target pursued by operations of the first steering layer, and a second steering target pursued by operations of the second steering layer, where the overall first steering target and second steering target provide steering to a selected position according to a final steering target for the beam steering device 1000). It will be understood that corresponding steering lenses may include similarly positioned steering lenses (e.g., first negative lens 1002 cooperates with first positive lens 1006 to provide steering for a given direction) and/or non-similarly positioned steering lenses (e.g., first negative lens 1002 cooperates with second positive lens 1008 to provide steering for a given direction). It will be understood that transformations between lens steering movement directions and/or a final steering target of the beam steering device 1000 may be performed according to each steering layer (e.g., the final steering target is transformed into a first steering target for the first layer, and a second steering target for the second layer), according to each cooperating lens pair (e.g., the final steering target is transformed into a first steering target for a lens pair such as 1002, 1006, and a second steering target for the other lens pair such as 1004,

1008), and/or according to any other operations set forth herein. Distribution of steering responsibility between cooperating lens pairs (e.g., burden of steering in a given direction shared between lens **1002** and cooperating lens **1006**) and/or between the steering layers (e.g., burden of steering shared between (left) first steering layer **306** and (right) second steering layer **306**) may be performed according to any operations set forth in the present disclosure, for example reference FIGS. **29-35** and the related description). Without limitation to any other aspect of the present disclosure, operations to distribute steering responsibility between available steering components (e.g., between cooperating lens pairs, between lens layers, and/or between actuators where more than one steering solution is available, such as when movement directions are not aligned with logical steering axes, and/or when movement directions are not fully perpendicular) include one or more operations such as: utilizing a first one of the components before utilizing the second one of the components (e.g., utilizing a faster one of the components during transient operations, utilizing one of the components until saturated and/or at a threshold actuation amount, then utilizing the other one of the components); utilizing a first one of the components alternated with the other one of the components (e.g., utilizing a piece-wise scheduling of the components, alternated through the steering range); utilizing both components simultaneously (e.g., according to a look-up table or other stored steering information, which may include target steering angles and corresponding actuator positions for each of the components, where both actuators are moved from a present position to the corresponding actuator position for the target steering angle); and/or combinations of these. Without limitation to any other aspect of the present disclosure, operations to distribute steering responsibility between available steering components include trimming the actuator positions after the target steering angle is achieved, and/or adjusting the actuator positions for the same target steering angle at a different time or operating condition. Example operations include utilizing a first distribution scheme to achieve a transient steering target, and utilizing a second distribution scheme to achieve the same steering target at a different time (e.g., with different starting conditions for the components when the same steering target is requested at the different time), and/or after a period of time where the steering target is held (e.g., changing the actuator positions as the steering target is held, for example to un-saturate a steering component, to adjust the conditions to allow for a more rapid exit from the steering target (e.g., utilizing a small lens to achieve the steering target, and sharing some of the steering burden to the larger lens as the steering target is held thereby extending the available range of the small lens for better response to future steering target changes).

(82) The available angle of deflection in the x and y axes are related to the displacements of the steering lenses of the steering layers **306**. Where the corresponding lenses in each layer have a same movement direction (e.g., lens **1002** and lens **1006** move in a same direction “x”), and where the (left) first steering layer **306** utilizes negative lenses and where the (right) second steering layer **306** utilizes positive lenses, the available angle of deflection in each of the x and y axes are set forth in Equations 7 and 8. Where the arrangement of beam steering device is different than the conditions described for Equations 7 and 8, adjustments to the equations may be readily made to determine the available angle of deflection in each direction. In Equations 7 and 8, $f_{\text{sub.r}}$ is the focal length of the effective equivalent positive lens, $\Delta_{\text{sub.1}}$ references movement of the steering lens from the (left) first steering layer **306**, and $\Delta_{\text{sub.2}}$ references movement of the steering lens from the (right) second steering layer **306**.

(83) 0Deflectionanglecapabilityofanexamplesteeringdeviceinaydirection

$$y = \pm \tan^{-1} \left(\frac{2 \Delta_{\text{sub.1}} + \Delta_{\text{sub.2}}}{f_r} \right). \quad \text{Eq. 7 Deflectionanglecapabilityofanexamplesteeringdevice}$$

inaydirection $y = \pm \tan^{-1} \left(\frac{2 \Delta_{\text{sub.1}} + \Delta_{\text{sub.2}}}{f_r} \right). \quad \text{Eq. 8}$

(84) It can be seen that the example beam steering device **1000** depicted in FIG. **10** can be utilized to create a beam steering device **1000** having a compact axial extent. For example, the axial extent

of the beam steering device **1000** between the fixed positive lens **1010** and the effective equivalent positive lens (e.g., between lenses **1006**, **1008**) is $f_{\text{sub.r}}$, a distance which might be $2f_{\text{sub.r}}$, in other embodiments. The example depicted in FIG. **10** additionally does not include focusing of the steered beam on any component (e.g., reference FIG. **13**, wherein focusing occurs on a field lens **308**), allowing for a greater range of power throughput, and/or a reduction in cooling or other heat transfer considerations. The example depicted in FIG. **10** includes four steering lenses and four corresponding actuators, with two of the actuators steering large, positive lenses (e.g., (right) second steering layer **306**). In certain embodiments, disadvantages associated with movement of large lenses and/or multiple actuators can be mitigated utilizing one or more of the following: 1) distributing a greater portion of steering responsibility onto smaller lenses of cooperating lens pairs; 2) distributing a greater portion of steering responsibility onto the (left) first steering layer **306** relative to the (right) second steering layer **306**; and/or reducing or eliminating steering capability in a selected direction (if applicable for the steering requirements of the given system).

(85) One of skill in the art, having the benefit of the present disclosure and information ordinarily available when contemplating a particular system, can readily determine an arrangement of steering layer(s), corresponding actuator(s), a distribution of steering responsibilities between components (e.g., steering layers and/or steering lenses), and/or a configuration of supporting steering components (e.g., collimating lenses, field lenses, etc.). Determined arrangements may be provided in accordance with any embodiments herein, including utilization of portions thereof, an including, without limitation, utilization of type 3 characteristics, type 1 characteristics, and/or combinations of these. Certain considerations to determine an arrangement of steering layer(s), corresponding actuator(s), distribution of steering responsibility between components, and/or configuration of supporting steering components include, without limitation: the cost and availability of lens types; the manufacturing tolerances of system aspects (e.g., lens characteristics; actuator position and alignment, including for the actuator during operation and/or installation); the available footprint for lenses and/or actuators (e.g., geometry, weight, and/or interfaces such as cooling, electrical power, communicative coupling, etc.); capital costs for a design (e.g., cost of components, cost of integration and/or engineering work, cost of tools to make a particular design, etc.); operating costs for a design (e.g., efficiency/power losses; wear and/or maintenance of components such as actuators; reliability and/or down-time considerations, etc.); and/or required and/or desired steering capability considerations (e.g., steering angle magnitudes, steering angle precision, steering speed, directional aspects of these; and/or steering duty cycle as expected or defined).

(86) Referencing FIG. **12**, an example beam steering device **1200** is schematically depicted, having a number of aspects as set forth throughout the present disclosure. The example beam steering device **1200** overcomes and/or mitigates a number of drawbacks of previously known steering systems, including at least small steering angles, small steering apertures, low steering speeds (and/or frequencies), and/or a requirement for high capability actuating elements for steering lenses.

(87) Aspects of the example beam steering device **1200** are similar to the beam steering device **300** depicted in reference to FIG. **3**, with certain changes as described following for certain embodiments, and adjustments to common features (e.g., actuator **318**) according to the capabilities and aspects of the example beam steering device **1200**. The example beam steering device **1200** may be referenced as a type 1 steering device herein for convenience of the description. A given beam steering device may include aspects of a type 3 steering device and/or a type 1 steering device, without limitation to examples set forth herein to illustrate certain principles of the present disclosure. An example type 1 steering device, as utilized herein, includes utilization of radial magnification (or virtual image displacement) to enhance the steering capability of the beam steering device **1200**. The enhancement of steering capability, as described herein and without limitation to any aspect of the present disclosure, and whether utilizing principles of a type 3 steering device, a type 1 steering device, other principles described herein, or combinations of

these, may reference any one or more of: enhancement of steering angle capability (e.g., steering to a greater angle than previously known systems), enhancement of steering speed and/or frequency (e.g., utilizing a reduced lens size and/or actuator displacement, thereby allowing for greater steering speed relative to previously known systems), reduction of steering device footprint (e.g., reduced weight, size, axial extent, power requirements, etc.), reduction in cost of components and/or fabrication (e.g., utilizing smaller lenses, reduced cost and/or capability of an actuator, and/or supporting aspects such as integration requirements, support requirements, active cooling requirements, etc.), enhanced aperture size/steered beam size, etc. Accordingly, in certain embodiments, a beam steering device of the present disclosure may have enhanced steering capability, while having the same or a lower steering angle capability relative to a previously known steering device.

(88) The example beam steering device **1200** includes the steering layer(s) **306** providing a steered beam **1204** to a magnifying lens **1202**, where the magnifying lens **1202** increases the steered angle (e.g., as depicted schematically with steered beam **1206**) of the beam **1206** incident on the field lens **308**. The magnifying lens **1202**, in coordination with lens(es) of the steering layer **306** provides for radial magnification, or displacement of a virtual image (or virtual object)—which is the displacement of a focal point of an equivalent lens of the lens(es) of the steering layer **306**. An example steering layer **306** includes one or more moving negative lenses, each of which may be aligned with a steering axis or offset from a steering axis (e.g., reference FIGS. **6**, **8**, **10**, **11**, **30-35**, and the related descriptions), and which may be arranged to move perpendicularly to each other, or offset from each other whether perpendicular or otherwise. An example steering layer **306** includes one or more positive lenses, and/or a combination of a negative lens with a positive lens. An example steering layer **306** includes the lenses of the steering layer **306** positioned in close proximity to each other, and positioned between one to two focal distances from the magnifying lens **1202**. The emission lens **310**, in an example, is a fixed positive lens, where the field lens **308** is positioned at a focal plane of the emission lens **310**. The emission lens **310** is positioned one focal distance away from the image plane of the magnifying lens **1202**.

(89) Referencing FIG. **13**, an example beam steering device **1300** utilizing aspects of a type 1 steering device as set forth herein is schematically depicted. The example beam steering device **1300** includes a steering layer **306** having two moving negative lenses and a magnifying lens **1202**. It will be understood that the steering layer **306** may utilize positive lenses (which may increase the axial extent of the beam steering device), and/or a combination of a positive steering lens and a negative steering lens (e.g., having distinct optical power). The steering layer **306** is positioned between one and two focal lengths away from the magnifying lens **1202**. The magnifying lens **1202** may be a spherical lens, or an aspherical lens (e.g., where the lenses of the steering layer **306** have different optical power). The utilization of negative lenses for the steering layer **306** provides for a moving virtual source point (e.g., upstream of the steering layer **306**), which can reduce the axial extent of the beam steering device **1300**, while the utilization of positive lenses for the steering layer **306** provides for a moving real source point (e.g., downstream of the steering layer **306**), which may increase the required axial extent of the beam steering device **1300**.

(90) An example beam steering device **1200**, **1300** does not require a field lens **308**, although the utilization of the field lens **308** allows for a more compact device (e.g., reduced size of the emission lens **310**) and/or reduces vignetting losses that may otherwise be present. The example type 1 beam steering device **1200**, **1300** creates a focus (concentration) of the beam energy on the field lens **308**. In certain embodiments, for example with a beam steering device **1200**, **1300** having a high power throughput, heat transfer from the field lens **308** may be considered in designing the beam steering device **1200**, **1300**. For example, the transparency of the field lens **308**, the material selection of the field lens **308**, the heat transfer environment of the field lens **308**, and/or active cooling thermally coupled to the field lens **308** may be provided to account for expected thermal performance of the field lens **308**. It can be seen that the field lens **308** is relatively large (in most embodiments)

relative to other lenses (e.g., lenses of the steering layer **306**), providing for a thermal sink that distributes heat throughout the field lens **308**. The focusing characteristic of the type 1 beam steering device can be managed to accommodate large power throughput devices (e.g., greater than 55 kW). Further, beam steering devices having high power throughput may generally have a larger field lens **308** (e.g., providing for a larger thermal sink and/or heat transfer area), and further have a greater surface area around the field lens **308** (e.g., allowing for the inclusion of passive and/or active heat transfer capabilities), therefore allowing for management of higher power throughput devices.

(91) An example type 1 steering device can be designed considering an equivalent lens with a moving focal point that is equivalent to the steering lens(es) of the steering layer **306** (e.g., with two steering lenses, an equivalent can be determined whether two negative lenses, two positive lenses, and/or one of each are present in the steering layer **306**). That moving focal point is the virtual object of the beam steering device **1200**, **1300**. The size of the virtual object is $A_{\text{sub}.x}$ in a first direction (according to actuator displacement of a steering lens in direction x) and $A_{\text{sub}.y}$ is a second direction (according to actuator displacement of a steering lens in direction y). As described throughout the present disclosure, x and y are in the movement direction(s) of the steering lens(es), which may be aligned or not with the steering directions, and which may be perpendicular or not. An example description provided for clarity of the present disclosure utilizes x as a first steering direction and y as a second steering direction. Magnification (e.g., radial magnification) of the virtual object is provided by positioning the moving focal point of the equivalent lens between $f_{\text{sub}.m}$ and $2f_{\text{sub}.m}$, where $f_{\text{sub}.m}$ is the focal distance of the magnifying lens **1202**. The magnification (M) provides for displacement of the virtual object as $M\Delta_{\text{sub}.x}$ in the x direction, and $M\Delta_{\text{sub}.y}$ in the y direction. The magnification M , which may be distinct in each direction (e.g., as $M_{\text{sub}.x}$ and $M_{\text{sub}.y}$, but is described herein as the same for clarity of the present description), is determined as $M=z'/z$, where z' is the distance between the image of the virtual object and the magnifying lens **1202**, and where z is the distance between the virtual object and the magnifying lens **1202**. The axial distance between the emission lens **310** and the magnifying lens **1202** is $z'+f_{\text{sub}.r}$ (or $Mz+f_{\text{sub}.r}$), where $f_{\text{sub}.r}$ is the focal length of the emission lens **310**. The field lens **308**, where present, is positioned at $f_{\text{sub}.r}$. The emission lens **310** has a selected optical power to recollimate the beam converged on the image plane of the magnifying lens **1202**, thereby providing a steered beam **106** having a selected collimation characteristic (e.g., collimated, and/or having a diverging and/or converging characteristic according to the requirements and/or application of the beam steering device **1200**, **1300**).

(92) In the present description, the virtual object may be understood as the focal point (e.g., of small negative steering lens(es)), and the image of the virtual object is a real image formed on another lens (e.g., a real image formed by a magnifying lens **1202** on a field lens **308**). Thus, the movement of the virtual object tracks movement of a focal point on a focal plane, and movement of the image of the virtual object tracks movement of the real image of the virtual object onto a lens of interest.

(93) The steering capability of a beam steering device **1200**, **1300** utilizing a type 1 configuration is set forth in equations 9 and 10. The example of equations 9 and 10 utilizes a single magnification M for both steering directions. It will be understood that the magnification M may vary between the steering directions, and/or transformations may be made where the steering directions and movement directions are not aligned, and/or where the movement directions are not linear (e.g., one or more actuator(s) **318** do not provide linear, or completely linear, motion of a steering lens).

(94) Deflectionanglecapabilityofanexamplesteeringdeviceinaxdirection

$$x = \pm \tan^{-1} \left(\frac{M}{f_r} x \right). \quad \text{Eq. 9 Deflectionanglecapabilityofanexamplesteeringdeviceinaydirection}$$

$$y = \pm \tan^{-1} \left(\frac{M}{f_r} y \right). \quad \text{Eq. 10 Referencing FIG. 14, an illustrative performance of a beam steering}$$

device **1300** is schematically depicted. Steering performance is illustrated in a single steering direction for clarity of the present description. Example embodiments herein utilizing a type 1 steering device to create a virtual displacement that is much larger than the real displacement (e.g., the angle of the final steered beam **106** is multiplied relative to the steered angle of the beam **1204** incident on the magnifying lens **1202**). An example beam steering device **1200** is readily capable to steer a beam **106** at large steering angles (e.g., $>+/-60$ degrees, $>+/-45$ degrees, and/or $>+/-30$ degrees) with modest displacement of the actuator **318**. Additionally, and without limitation to any other aspect of the present disclosure, the beam steering device **1200** enhances numerous aspects over previously known beam steering devices, for example reducing vignetting losses (e.g., reduced actuator displacement allows for reduction in moving lens sizes, field lens size, and/or greater ease in creating a common area between lenses of the steering layer **306**; thereby reducing moving lens sizes and/or field lens size that would otherwise be required to reduce vignetting losses for previously known beam steering devices), and/or enabling arbitrarily large apertures. For example, a beam steering device **1200** capable to produce a steered beam **106** having a size of 50 cm or greater can readily be constructed. The enhancements of the type 1 steering device can be utilized to increase capability of beam steering in other dimensions beyond a significant steering angle capability. For example, the type 1 steering device produces a high steering angle relative to the displacement amount of steering lens(es), allowing for reduced cost and/or capability of an actuator **318** moving the lens(es); an increased steering speed and/or frequency (e.g., putting a reduced mechanical strain on the system to move the steering lens(es)); increased common area of the steering lens(es) (e.g., increasing the supported beam size relative to aperture size of the emission lens **310**—resulting in a larger supported emission beam size relative to previously known systems); and/or a reduction in the steering lens size(s) (e.g., the smaller displacement reduces the required steering lens size(s) that preserve a given common area of the steering lens(es)).

(95) An example beam steering device **1300** includes a focal length of the equivalent negative lens (e.g., steering lenses of steering layer **306**) of 40 mm, a focal length of the magnifying lens **1202** of 20 mm, and a focal length of the emission lens **310** and field lens **308** of 12 mm. The example steering device is capable to provide the steered beam **106** deflected to $+/-15$ degrees at a speed of 0.2 KHz. The example steering device is based on modeling, simulation, and experience, and is believed to be representative of capabilities within the range (without limitation) of embodiments as set forth herein. The example steering device depicts steering in only a single axis for purposes of illustration.

(96) In certain embodiments, the optical components and configuration of a beam steering device (e.g., any type 3 steering device, type 1 steering device, and/or any other beam steering device as disclosed herein) are configurable to achieve a selected steered beam **106** size and/or convergence/divergence characteristic. An example configuration includes providing a type 3 steering device having a telescopic magnification selected to provide a steered beam **106** size, for example as a multiple of the incident beam **102** size according to the magnification of the optical components arranged within the beam steering device. Further configuration options for a type 3 steering device to accommodate a larger steered beam **106** size include one or more of: increasing a common area of steering lenses of the steering layer **306**; including and/or increasing a size of a field lens (e.g., as in FIG. 3 or 8); and/or including and/or increasing a size of additional field lens(es) (e.g., as in FIG. 5). An example configuration includes providing a type 1 steering device having a telescopic magnification selected to provide a steered beam **106** size, for example as a multiple of the incident beam **102** size according to the telescopic magnification (e.g., as opposed to a radial magnification) of the optical components arranged within the beam steering device. Further configuration options for a type 1 steering device to accommodate a larger steered beam **106** size include one or more of: reducing a size of the field lens (if present); positioning the field lens closer to the magnification lens; increasing an F # of the emission lens; increasing a common area between steering lenses of the steering layer **306** (e.g., adjusting lens size, displacement,

and/or utilizing field lens(es) associated with the steering lenses, such as in FIG. 5); and/or utilizing a positive/negative lens pair as the emission lens (e.g., which may reduce the steering capability, but increase the beam size). The convergent-divergent-collimated characteristic of the steered beam **106** depends upon the optical characteristic(s) of components throughout the optical path of a given beam steering device (e.g., each lens layer and/or optically active component layer), and the initial characteristics of the incident EM beam **102**.

(97) It can be seen that certain features of the optical arrangement of a beam steering device compete in certain arrangements. For example, telescopic magnification and steering angle capability compete for a type 1 beam steering device. In another example, steering lens common area competes with one or more of: steering lens size; steering angle capability (e.g., reduced steering lens displacement limits steering angle capability but improves steering lens common area); and/or axial extent of the beam steering device compete for either a type 3 beam steering device or a type 1 beam steering device. It can be seen that certain features of the optical arrangement of a beam steering device cooperate in certain arrangements. For example, telescopic magnification and steering angle capability cooperate for a type 3 beam steering device. In another example, steering lens common area cooperates with a low-displacement steering lens arrangement, which may be desirable in certain embodiments: reduced displacement benefits cost considerations of the actuator(s), power consumption of the beam steering device, and steering speed through the displacement range of the beam steering device. Embodiments herein provide for a greater maneuverability through the optical arrangement space of a beam steering device, allowing for improved outcomes, capability, cost, and/or performance of a resulting beam steering device relative to previously known beam steering devices.

(98) Without limitation to any other aspect of the present disclosure, embodiments herein provide for: high steering angle capabilities per unit of steering lens displacement; a high ratio of emitted beam size relative to the size of emitting optics (e.g., field lens(es), emission lens(es), etc.); a reduced and/or eliminated moving mass of actuated components (e.g., reduced size steering lens(es), and/or writeable lens(es) that eliminate physical movement); and/or a reduction in an axial extent of the beam steering device (e.g., utilizing negative steering lenses, and/or a net negative steering layer). Without limitation to any other aspect of the present disclosure, embodiments herein provide for numerous options to adjust the trade-off space of the arrangement of steering components, such as: utilization of telescopic magnification to enhance steering angle capability; dividing steering displacement burdens between multiple steering layers (e.g., compare arrangements of FIGS. 6, 8, 10, and 13); utilization of a focusing (e.g., type 1 beam steering device with a field lens) or non-focusing (e.g., type 3 beam steering device) arrangement; compensation for non-aligned steering lens movement with logical steering axes (e.g., allowing for trade-offs between actuator positioning options, actuator types, manufacturing and/or alignment tolerances, etc.); and/or utilization of standardized or customized components (e.g., lens type and power selections, reduction or increase in actuator capability allowing for a broader range of acceptable actuator components, etc.). One of skill in the art, having the benefit of the disclosure herein and information ordinarily available when contemplating a beam steering device, can readily determine a configuration to meet the desired capability for a given application, while balancing component cost, manufacturability, and footprint characteristics of the beam steering device. Certain considerations for configuring a beam steering device to meet a desired capability, and/or to adjust the trade-off space of the arrangement of steering components include, without limitation: movement capability (displacement and/or speed) of available actuators; orientation of movement directions (to each other, and/or to steering axes); the target steering envelope (e.g., magnitude and/or direction of steering); the available axial footprint of the beam steering device (e.g., axial extent of the steering components and/or a housing defining the steering components); a beam size of the incident beam; a beam size of the steered beam; optical characteristics and/or relative costs of lens components (e.g., spherical, aspherical, anisotropic, astigmatic, positive and/or negative

lenses, cylindrical lenses, and/or write-able lenses—e.g. reference FIGS. **36, 37**); power throughput of the incident beam and/or an observed beam; heat transfer characteristics and/or active cooling characteristics available for components of the beam steering device (e.g., capital costs, integration costs, footprint costs (e.g., size, weight, systems, interfaces, controls), operating costs, and/or performance effects or limitations); the focusing characteristic of the steered beam progressing through the beam steering device; the number and geometry of available steering paths relative to the number and geometry of steered beams (e.g., where switching of steering responsibility between paths can enhance steering capability, steering response time, heat generation, and/or component utilization—e.g., reference FIGS. **15-25, 39-42, and 44**); duty cycles of steering operations (e.g., steering angles and/or frequencies, and or power throughput; including a description of operating times corresponding to these; including consequent effects on steering actuators, component time-at-temperature, cooling system, and the like); mechanical displacement capabilities and constraints, available footprint for the steering system (e.g., axial size; diameter; weight; power provision; cooling provision; and/or control capabilities including I/O, available sensors, and/or available actuators), capital cost considerations, operating cost considerations, and/or manufacturing constraints (e.g., tolerances of components, available materials, available operations such as machining, coating, finishing, etc.).

(99) Referencing FIG. **15**, an example beam steering device **1500** that steers a number of EM beams **1502, 1504** simultaneously is depicted. For convenient reference herein, multiple beam steering arrangements such as those depicted in the examples of FIGS. **15-18, and 22**, are referenced as a type 2 beam steering device. In the example of FIG. **15**, the final steering optics include a shared field lens **1514** and a shared emission lens **1516**. The upstream steering components are consistent with a type 1 beam steering device for each EM beam **1502, 1504**, for example each including a steering layer and a magnifying lens. However, the upstream steering components for any one or all of the EM beams **1502, 1504**, which may be referenced as an individual steering device, may additionally or alternatively include an individual steering device consistent with a type 3 beam steering device (e.g., reference FIGS. **4, 5, 8, and 10**, and the related descriptions). The shared field lens **1514** may be in addition to any field lens (not shown) provided for an individual steering device, and/or may be provided as an additional steering component after the initial steering is performed by the given individual steering device. Additionally or alternatively, a given individual steering device may include an emission lens (not shown) that emits an individually steered beam from the individual steering device that is incident on the shared field lens **1514**, and/or may be omitted (e.g., as depicted in the example of FIG. **15**). Additionally or alternatively, an individual steering device may include a combination of type 3 beam steering device and type 1 beam steering device components.

(100) In the example of FIG. **15**, each individual beam steering device includes a nominal optical line that passes through approximately the center of the shared field lens **1514**, where steering of the individual beam (e.g., EM beam **1502**) move the incidence of the individual beam around the center of the shared field lens **1514**, which is then emitted from the shared emission lens **1502** as a final individual steered beam. It can be seen that, where one of the individual steering devices is provided at a centerline of the field lens **1514**— emission lens **1516** pair (e.g., the individual steering device that is steering EM beam **1504** in the example of FIG. **15**), all other individual steering devices will be offset by some angle. The amount of the offset will depend upon the size of the lenses (e.g., the magnifying lens(es) **1512, 1524**, where present, and/or lenses of the steering layers **1508, 1520**), the positioning and configuration of the actuator(s) **1510, 1522**, and/or any other components (not shown) such as housing or support structures, cooling interface(s), power connections, control connections, or the like. The example of FIG. **15** includes a centerline individual beam steering device (e.g., the individual steering device that is steering EM beam **1504** in the example of FIG. **15**), but a given beam steering device **1500** may not include a centerline individual beam steering device (e.g., where all individual beam steering devices are offset, for

example to provide a similar steering environment for each, and/or to reduce a total offset amount for all of the individual steering devices in the beam steering device **1500**). The example of FIG. **15** depicts an arrangement capable to steer two EM beams **1502**, **1504** as an illustration of certain features of the beam steering device **1500**, but a beam steering device **1500** may include a number of individual beam steering devices (e.g., reference FIGS. **16-18** and **22**, and the related description, for additional examples).

(101) In the example of FIG. **15**, a first individual steering device includes a first steering layer **1508** that receives an incident beam **1504** from a first EM source **1506**, and a first magnifying lens **1512** that receives the incident beam **1504** from the first steering layer **1508** and provides it to the shared field lens **1514**. Operations of the first steering layer **1508** move the EM beam **1504** about the field lens **1514**, resulting in a final steered beam **1504** emitted from the emission lens **1516**.

(102) In the example of FIG. **15**, a second individual steering device includes a second steering layer **1520** that receives an incident beam **1502** from a second EM source **1518**, and a second magnifying lens **1524** that receives the incident beam **1502** from the second steering layer **1520** and provides it to the shared field lens **1514**. Operations of the second steering layer **1520** move the EM beam **1502** about the field lens **1514**, resulting in a final steered beam **1502** emitted from the emission lens **1516**. Further to the example of FIG. **15**, the EM beams **1502**, **1504** may be steered independently and/or simultaneously.

(103) The example of FIG. **15** depicts the EM beams **1502**, **1504** received from EM sources **1506**, **1518** and selectively steered to a desired location (e.g., a steering value, which may include separate values for each EM beam **1502**, **1504**). However, the beam steering device **1500** may additionally or alternatively be targeted to a desired location to receive EM radiation from the target location back to a detector (e.g., in addition to or as a replacement for an EM source **1506**, **1518**) such as a photonic array. In certain embodiments, one or more individual steering devices may be dedicated to emitted beam steering, and other ones of the individual steering devices may be dedicated to received EM radiation. Additionally or alternatively, a same individual steering device may be utilized to steer an emitted beam at a first time, and to guide received EM radiation at a second time. In certain embodiments, further upstream optical components (e.g., a beam splitter, and/or further steering components—not shown) may manage the provision of the EM source **1506**, **1518** and/or final steering to a detector, allowing for the same individual steering device to perform steering operations without regard to whether the steering is performed for emission or receiving purposes, and/or allowing for simultaneous steering of emission and receiving (e.g., where a same target location is a target for both emissions and receiving of EM radiation at the same time).

(104) The components and/or type of each individual steering device may be the same or distinct, and/or the capability of each individual steering device may be the same or distinct. A device configured according to the example of FIG. **15** can steer more than one EM beam **1502**, **1504** simultaneously and in more than one dimension (e.g., azimuth and elevation). In certain embodiments, one or a number of the individual steering devices may be configured to steer in two dimensions, with other ones of the individual steering devices capable only to steer in one dimension.

(105) Referencing FIG. **16**, an example arrangement of a beam steering device is depicted, for example consistent with aspects of the beam steering device **1500** of FIG. **15**. In the example of FIG. **16**, one individual steering device steers a centerline beam **1502**, and a hexagonal arrangement of individual steering devices steer a number of beams **1504** on an offset steering path (e.g., consistent with the example of FIG. **15**, with multiple additions of the second individual steering devices). In the example of FIG. **16**, each offset steering path is offset from the centerline by a same amount (although this need not be the case), but each offset steering path has a distinct steering environment—for example a left-most one of the offset individual steering devices will have a different overall steering window relative to a right-most one of the offset individual

steering devices, in an embodiment where the left-most one and the right-most one otherwise have a sufficiently similar overall steering capability (e.g., ± 15 degrees, ± 20 degrees, etc.).

(106) The capabilities and arrangements (e.g., type 3, type 1, and/or combinations) of the individual steering devices may vary, providing the selected number of steering devices and capabilities according to the desired capability of the type 2 beam steering device and/or application. It can be seen that the offset beams **1504** are not on the centerline, and even with a same capability (e.g., nominal ± 45 degrees for each of the individual steering devices), there will be some loss in the available steered range. For example, reference FIGS. **19-22** for additional details. The amount of the offset from the centerline will depend upon the size of each individual steering device and other considerations (e.g., reference FIG. **15** and the related description), and will further depend upon the axial extent available for providing the type 2 steering device (e.g., a longer device with a fixed geometric offset results in a lower offset angle). The individual steering devices and/or the corresponding components (e.g., steering layers, magnifying lenses, etc.) may be arranged in any manner, such as on a plane, the frustum of a curved surface (e.g., a sphere, paraboloid, elliptical versions of these, hyperbolic versions of these, and/or may be positioned on a concave or a convex portion of such a surface, etc.), and/or may be arranged arbitrarily in three-dimensional space (e.g., to minimize collision of components such as actuators and/or magnifying lenses), with each of the individual steering devices having a selected optical line relative to the shared field lens **1514**. The description of a curved surface, a plane, or other arrangements are utilized to describe a general logical arrangement, and not positioning on the individual steering devices on an actual surface. However, depending upon the configuration, the individual steering devices may be positioned on an actual surface having the selected shape (or combination of shapes), for example a housing wall, structural support (e.g., a wall, bulkhead, and/or scaffold having the selected shape), or the like.

(107) The provided examples are non-limiting. In certain embodiments, the steering capability of the individual steering devices is sufficiently high such that non-steering considerations, such as ease of fabrication, integration of actuators, simplified geometry and/or footprint for the type 2 beam steering device, or the like, are utilized to determine the arrangement of the individual steering devices and components thereof. In certain embodiments, complex shapes and geometries of the individual steering devices are justified to preserve steering capability of the devices. In certain embodiments, a subset of the individual steering devices are maintained with high steering capability, such as: a selected number of individual steering devices, a related group of individual steering devices, and/or a distributed group of individual steering devices (e.g., to provide for distributed capability across the array of individual steering devices). The example of FIG. **16** includes a centerline individual steering device steering the EM beam **1502**, but a given embodiment need not include any centerline individual steering device.

(108) Referencing FIG. **17**, for example consistent with aspects of the beam steering device **1500** of FIG. **15**. In the example of FIG. **17**, one individual steering device steers a centerline beam **1502**, a hexagonal arrangement of individual steering devices steer a number of beams **1504** on an offset steering path (e.g., consistent with the example of FIG. **15**, with multiple additions of the second individual steering devices), and a further hexagonal arrangement of individual steering devices steer a number of beams **1702** on a second offset steering path. The individual steering devices for the number of beams **1702** are further offset from the centerline relative to the individual steering devices for the number of beams **1504**, but the considerations and description of FIG. **16** otherwise generally applies to the embodiment of FIG. **17**. It will be seen that the variance in the steering environment for the individual steering devices for the number of beams **1702** will be greater than the variance in the steering environment for the individual steering devices for the number of beams **1504**.

(109) An example tier arrangement includes a hex geometry of beams approaching the field lens, with the central beam being on axis, or near on axis, and a ring of 6 apertures around the central

ring to form a hex 7 arrangement, another ring of 12 around the hex 7 array to form a hex 19 array, and so on for larger hex arrangements.

(110) For convenience of description, each similarly positioned group of individual steering devices may be referenced as a tier of individual steering devices. For example, the centerline individual steering device (and/or a group of least offset individual steering devices) may be referenced as a first tier, the individual steering devices for the number of beams **1504** (and/or a group of next-least offset individual steering devices) may be referenced as a second tier, and the individual steering devices for the number of beams **1702** (and/or a group of next-least offset individual steering devices) may be referenced as a third tier. It can be seen that the difference in the overall steering environment for each tier will have a greater variance than a previous tier, at least for embodiments where the extent of a given tier is utilized. For example, an arrangement such as depicted in FIG. **17** includes a left-most member of the third tier and a right-most member of the third tier having a greater offset difference therebetween than a left-most member of the second tier and a right-most member of the second tier. However, an embodiment such as that depicted in FIG. **17**, but where the third tier is not fully utilized (e.g., where only two adjacent members of the third tier are present, but the entire second tier is present), there may be members of the second tier having a greater difference in the overall steering environment. In the example, while the two adjacent members of the third tier have a greater offset, the steering environment between the two adjacent members of the third tier will nevertheless have a similar environment relative to each other. The greater variance of steering environments within each subsequent tier, where present, may lead to operational gaps in the steering space of the type 2 beam steering device—for example a left-most member of the third tier may not be able to achieve steering to a portion of a target steering window (e.g., a left-most or right-most portion, depending upon the optical steering arrangement of the individual steering member, and/or the related actuator positioning and capability).

(111) An example type 2 beam steering device is configured to manage such operational gaps, for example utilizing target swapping (e.g., reference FIGS. **24**, **38-42**, and **44**, and the related description), and/or utilizing type selection and/or actuator arrangement of one or more individual beam steering devices (e.g., recognizing that a type 3 arrangement steers the beam in the direction of the steering lens movement, and that a type 1 arrangement steers the beam in the opposite direction of the steering lens movement). The example of FIG. **17** depicts three tiers of individual beam steering devices, but any number of tiers (e.g., four tiers, five tiers, etc.) and/or arrangement of individual beam steering devices is contemplated herein. The example of FIG. **17** depicts a hexagonal arrangement of individual beam steering devices, but any arrangement is contemplated herein, including a grid, a pattern of any type, and/or arbitrarily positioned individual beam steering devices. Provided tiers may include a full tier (e.g., all available positions occupied by individual beam steering devices), partial tiers (e.g., a number of individual beam steering devices provided for the tier with some positions unoccupied, for example where a count of individual beam steering devices are sufficient without all positions occupied, to provide space for a support structured, power coupling, cooling, control coupling, etc.).

(112) Referencing FIG. **18**, an example type 2 beam steering device **1800** is schematically depicted. The example of FIG. **18** includes a first tier individual beam steering device **1818**, a second tier individual beam steering device **1820**, and a third tier individual beam steering device **1822**. The example of FIG. **18** includes an example device **1818**, **1820**, **1822** from each tier for clarity of description for certain concepts of the present disclosure. However, a given tier may include any number of devices according to the selected arrangement. In certain embodiments, individual beam steering devices may have circular symmetry with regard to an optical axis **120** (e.g., devices within a tier have a same offset angle). In certain embodiments, individual beam steering devices may additionally or alternatively be distributed symmetrically about the optical axis **120** (e.g., where each individual beam steering device **1818** in a given tier has an opposing individual beam

steering device **1818** positioned in an opposite location mirrored across the optical axis **120**). It will be understood that alternate arrangements of each tier of a type 2 beam steering device are also contemplated here, for example with non-symmetrical and/or unbalanced arrangements of individual beam steering devices in a given tier. Additionally, it will be understood that a type 2 beam steering device **1800** may be provided without tiers—for example with a number of distributed individual beam steering devices each having an offset angle (and/or with a single one of these centered on the optical axis **120**), and/or combinations such as certain individual beam steering devices provided in one or more tiers, and additional individual beam steering device(s) provided at arbitrary values for the offset angle.

(113) The example beam steering device **1800** includes common optics **1824** (e.g., a field lens and an emission lens), where the first tier device **1818** steers a first EM beam **1801**, where the second tier device **1820** steers a second EM beam **1803**, and where the third tier device **1822** steers a third EM beam **1805**. The example beam steering device **1800** includes the first tier device **1818** as a centerline device (e.g., with the first EM beam **1801** provided in-line with an optical axis **120**). However, the beam steering device **1800** may not include a centerline device, and the devices **1818**, **1820**, **1822** may have distinct offsets from the optical axis **120** for any reason, regardless of whether the devices **1818**, **1820**, **1822** are provided as members of separate tiers. In the example of FIG. **18**, the first device **1818** steers the first EM beam **1801**, providing a steered EM beam **1802** to the common optics **1824**, which is then emitted as a first steered beam **1808**. The second device **1820** steers the second EM beam **1803**, providing a second steered EM beam **1804** to the common optics **1824**, which is then emitted as a second steered beam **1810**. The third device **1822** steers the third EM beam **1805**, providing a third steered EM beam **1806** to the common optics **1824**, which is then emitted as third steered beam **1812**.

(114) The steered beams **1808**, **1810**, **1812** are depicted schematically, and are provided to illustrate that, where the devices **1818**, **1820**, **1822** otherwise have similar steering capability, that devices **1818**, **1820**, **1822** having a further offset from the optical axis **120** have a reduced capability for maximum steering in at least one direction. For example, a nominal optical axis for the second device **1820** is offset by an angle **1814** from the optical axis **120**, and a nominal optical axis for the third device **1822** is offset by a larger angle **1816** from the optical axis **120**. The reduction in the maximum steering capability includes the offset angle **1814**, **1816** (e.g., steering “against” the offset angle requires that angle to be overcome in addition to the target steering value), but also includes a degradation of the overall capability of the offset device **1820**, **1822** due to the engagement angle of the steered beam (e.g., **1804**, **1806**) with the common optics **1824**. The degradation of the overall capability due to the engagement angle is not linear—for example, a mild offset of a few degrees may result in a capability loss of just a few degrees, but a larger offset (e.g., 20 degrees) will result in a more significant offset of the maximum capability. For example, where the first device **1818** includes a capability of ± 45 degrees, an otherwise similar second device **1820** having an offset angle **1814** of less than about 5 degrees may preserve an overall capability of ± 40 degrees, while an otherwise similar third device **1822** having an offset angle **1816** of less than about 10 degrees may preserve an overall capability of ± 30 degrees. The recited examples are non-limiting and illustrate the basic concept. The offset angles and capability degradation depend on a number of factors, which can be mitigated in the design details, for example utilizing axial distancing and/or arrangements of the individual beam steering devices **1818**, **1820**, **1822** to reduce offset angles, increased capability of the offset individual beam steering devices **1820**, **1822** (e.g., utilizing radial and/or telescopic magnification, intermediate field lenses, and/or enhanced displacement capability of the related actuator(s), etc.) to make up for lost capability due to the nominal geometric arrangement of the devices **1818**, **1820**, **1822**.

(115) Referencing FIG. **19**, an example steering capability **1902** of a first tier steering device (e.g., a centerline device) is schematically depicted. It can be seen that the steered beam **1808** includes a first range **1904**, which may be ± 30 degrees, ± 40 degrees, ± 45 degrees, etc. The example of

FIG. 19 is a schematic depiction for purposes of comparison with the other tiers of a type 2 beam steering device, such as that depicted in FIGS. 15-18. The comparison between FIGS. 19-21 is provided to illustrate performance of steering devices from distinct tiers (and/or otherwise having distinct offset angles) but otherwise having similar steering capability (e.g., magnification, displacement, etc.). In certain embodiments, one or more steering devices in higher tiers and/or having a greater offset may be provided having greater steering capability, thereby reducing the differences depicted in the comparison of FIGS. 19-21. In certain embodiments, one or more steering devices in higher tiers and/or having a greater offset may be provided having a reduced steering capability (e.g., where outer tier devices are sufficient to meet the desired steering targets and/or application mission regardless of the reduced capability), thereby increasing the differences depicted in the comparison of FIGS. 19-21.

(116) Referencing FIG. 20, an example steering capability **2002** of a second tier steering device (e.g., having an offset angle **1814**) is schematically depicted. It can be seen that the steered beam **1810** includes a second range **2004**. The second range **2004** is reduced in magnitude relative to the first range **1904**, and is additionally offset by angle **1814**. Accordingly, steering in one direction (e.g., above the optical axis **120** in the depiction of FIG. 20, or the disfavored direction) is greatly reduced in capability relative to the steering capability **1902**, while steering in the other direction (e.g., below the optical axis **120** in the depiction of FIG. 20, or the favored direction) is less degraded (and/or may be enhanced, depending upon the offset angle **1814** and the magnitude of the reduction of **2004** relative to **1904**).

(117) Referencing FIG. 21, an example steering capability **2102** of a third tier steering device (e.g., having an offset angle **1816**) is schematically depicted. It can be seen that the steered beam **1812** includes a third range **2104**. The third range **2104** is reduced in magnitude relative to the second range **2004**, and is additionally offset from the optical axis **120** by angle **1816**. Accordingly, steering in one direction (e.g., above the optical axis **120** in the depiction of FIG. 21) is greatly reduced in capability relative to either the steering capability **1902** or the steering capability **2002**, while steering in the other direction (e.g., below the optical axis **120** in the depiction of FIG. 21) is less degraded (and/or may be enhanced, depending upon the offset angle **1816** and the magnitude of the reduction of **2104** relative to **1904**, **2004**) relative to one or both of the steering capabilities **1902**, **2002**. In the example of FIG. 21, the upper range of the steering capability **2102** is above the optical axis **120**, and accordingly target swapping (e.g., reference FIGS. 24, 39-42, and 44, and the related description) may be utilized to provide full capability, or near-full capability (e.g., depending upon the extent of the steering capability **2102** in the favored direction) of steering from the third tier of steering device(s). It will be understood that target swapping may be utilized to preserve steering capability, but certain operating conditions may nevertheless result in loss of steering capability—for example when a large enough group of the third tier steering devices are instructed to steer in a disfavored direction, where not enough swappable third tier steering devices are available to achieve the desired steering targets for multiple steered beams. In certain embodiments, a target swap may extend through device tiers—for example where a second tier device is utilized to achieve a steering target that is nominally commanded for a third tier device.

(118) The examples of FIGS. 19-21 depict example capabilities for devices from multiple tiers (and/or for devices having selected offset values). One of skill in the art, having the benefit of the present disclosure, can readily design a multi-tiered (and/or multi-offset) type 2 beam steering device having a desired steering capability range with the desired number of steered beams. Certain considerations for designing a type 2 beam steering device having an arbitrary steering capability with an arbitrary number of steered beams include, without limitation: the available footprint for the type 2 beam steering device (e.g., axial extent, radial extent, volume, weight, etc.); the fungibility of EM sources (e.g., determining which devices from which tiers have an equivalent EM source, such as beam energy, diameter, frequency, phase, etc.); the availability of steering capability enhancements for devices in selected tiers; and/or the availability of multiple type 2

beam steering devices (e.g., having distinct optical axes **120**, tier arrangements, etc.).

(119) Referencing FIG. **22**, an example type 2 beam steering device **2200** includes a number of individual steering devices provided in a number of tiers—for example a first device **1818** in a first tier (which may be a centerline device), second devices **1820**, **2202** in a second tier, and third devices **1822**, **2204** in a third tier. In the example of FIG. **22**, each individual steering device includes an associated capability (e.g., device **1818** with capability **2226**, device **1820** with capability **2224**, device **1822** with capability **2222**, device **2202** with capability **2228**, and device **2204** with capability **2230**). It can be seen that devices **1822**, **2204**, in the example, have overlapping capabilities **2230**, **2222**, such that the devices **1822**, **2204** can cooperate (e.g., utilizing target swapping) to cover the entire range (e.g., from the top of **2230** to the bottom of **2222**, in the example of FIG. **22**). Additionally or alternatively, an out-of-range steering target for a given device (e.g., **1822**, **2204**) may be met by swapping to a device in another tier (e.g., **1820**, **2202**, or **1818**). The examples of FIGS. **19-22** are non-limiting, and are illustrative of the type of information, utilizable by one of skill in the art having the benefit of the present disclosure and information ordinarily available when contemplating a type 2 beam steering device **2200**, to ensure that the beam steering device **2200** will have sufficient capability to meet the application mission.

(120) Referencing FIG. **23**, an illustrative range overlap **2302** is depicted, for example consistent with the steering capabilities **2222**, **2230** depicted in FIG. **22**. For steering commands in the overlap range **2302**, either or both of the devices **1822**, **2204** can achieve the target steering, and steering operations can be performed by a default device **1822**, **2204** and/or by either or both devices **1822**, **2204**. For steering commands outside the overlap range **2302**, the appropriate one of the devices **1822**, **2204** may be utilized to achieve the target steering. In certain embodiments, for example when a steering command shifts from outside the overlap range **2302** into the overlap range **2302**, steering can be shifted from a swapped device (e.g., **1822** substituting for **2204**) to a default device, and/or management techniques such as application of a hysteresis may be applied (e.g., to prevent dithering or rapid swapping between devices **1822**, **2204** performing the steering operations). It can be further seen that swapping operations may be performed to improve steering response time (e.g., utilizing a device **1822**, **2204** that is already close to a target steering location), to reduce system power consumption (e.g., utilizing the overlap range **2302** to reduce aggregate actuator power consumption), or for any other purpose. It will be understood that the capabilities, swapping, and other operations described in relation to FIGS. **19-23** may be utilized for multiple steering directions (e.g., the description herein has been described in the context of a single steering axis for clarity of the description) and/or for swapping operations performed between tiers.

(121) Referencing FIG. **24**, an example actuator **2402** is depicted as coupled to more than one individual steering device, for example steering an EM beam **1504** associated with a given tier of the type 2 beam steering device. In certain embodiments, it may be desired to provide steering for more than one individual steering device to the same steering target (e.g., one device steering an emitted beam and the other device steering received EM radiation; one device steering a first emitted beam with a first characteristic and the other device steering a second emitted beam with a second characteristic, etc.). In the example of FIG. **24**, a single actuator can thereby steer more than one individual steering device, reducing the complexity of the overall type 2 beam steering device. In a further example, the first characteristic and the second characteristic may be any aspect of the EM beams, including a frequency difference, a phase difference, an energy difference, etc. In a further example, the first characteristic and the second characteristic may not have any differences—for example when the two (or more) beams are utilized to provide a selected amount of EM energy to the targeted location utilizing the combined steered EM beams **1504**.

(122) Referencing FIG. **25**, an example type 2 beam steering device **2500** is schematically depicted. The example beam steering device **2500** includes a first individual steering device **1818** performing steering operations for a first beam **1802**, and a second individual steering device **1820** performing steering operations for a second beam **1804**. The example beam steering device **2500**

includes a common field lens **1514** and emission lens **1516**. In certain embodiments, individual beam steering device(s) **1818, 1820** may have an individually associated field lens (not shown) and/or a subset of the individual beam steering device(s) may share a common field lens, while other individual beam steering device(s) have an individually associated field lens, and/or share a different common field lens. In certain embodiments, common shared optics between individual beam steering device(s) **1818, 1820** may be limited to the common emission lens **1516**.

(123) The example beam steering device **2500** further includes a first lens **2502** interposed between the first individual steering device **1818** and the common field lens **1514**, and a second lens **2504** interposed between the second individual steering device **1820** and the common field lens **1514**. The lenses **2502, 2504** may be magnifying lenses, for example to implement a type 1 beam steering device for steering one or more of the number of beams to be steered by the type 2 beam steering device **2500**. The lenses **2502, 2504** may additionally or alternatively include optical characteristics to apply selected adjustments to the steered beam, for example a lens **2502, 2504** may be an additional field lens (e.g., ensuring that the steered beams impinge on a common field lens **1514** and/or on a common emission lens **1516**), and/or convergence lenses configured to provide a selected convergence characteristic to the steered beams.

(124) In the examples of FIGS. **26-28**, a number and arrangement of electromagnetic actuators **318** including biasing members are depicted as examples. The steering layer **306** of the example embodiments includes a lens is surrounded by a metallic ring (e.g., a permanent magnet and/or a ferromagnetic material, and which may include and/or be replaced by features configured to respond to applied EM fields) responsive to EM fields produced by the actuators. The biasing members may be tension or compression biasing members, and may be formed from a non-magnetic material (or may be a magnetic material, for example where the magnetic response of the biasing member is negligible compared to the response of the lens, and/or where the magnetic response of the biasing member is accounted for in the actuation scheme). The number and arrangement of biasing members and actuating members is selectable. It will be understood that for steering in a single axis, at least a single actuating member having a force component, when activated, in the single steering axis (and/or associated movement direction) is provided. It will be understood that for steering in two axes, at least two actuating members are provided, with net force components in each of the steered axes. However, multiple actuating elements, such as those depicted, may be present. In certain embodiments, actuators **318** may operate in a pull arrangement on the lens, a push arrangement on the lens, or selectively in both arrangements (e.g., where an actuator on one side pushes and the opposing actuator, or a net composite of other actuators, also push on a second side). The selection of actuators, such as AC solenoids, DC solenoids, or other EM actuators, may be of any type, and may depend upon the characteristics desired for steering the given embodiment, such as desired response times, available actuating power, space available, or the like. In the embodiments of FIGS. **26-28**, a single steered lens is depicted. Additionally or alternatively, more than one steered lens for example to provide steered lenses having distinct steering characteristics (e.g., steering speed, steering precision, steering displacement capability, or the like), and/or due to other system characteristics making the presence of more than one steering lens desirable (e.g., cooperative steering to achieve an increased steering capability or response time, separating steering control for each axis, and/or due to constraints on a number or arrangement of actuators associated with one or more steering lenses, such as available space, EMI noise considerations, power delivery considerations, or the like).

(125) In certain embodiments, piezoelectric devices provide a number of advantages, such as rapid response times (e.g., allowing for rapid steering operations, scanning, or the like), low degradation over a high number of operating cycles, and convenient control through electronic commands. However, piezoelectric devices utilized in previously known systems have a number of drawbacks limiting their utility, such as a limited displacement capability and sensitivity to certain frequency. Embodiments herein provide enhanced displacement capabilities for the lens(es) using

piezoelectric devices, and/or enhanced steering capability mitigating a limited available displacement of the lens(es).

(126) Referencing FIG. 29, an example arrangement of steering lenses **2902**, **2904** with associated actuators **2402**, **2404** is depicted. An example embodiment includes the steering lenses **2902**, **2904** making up a steering layer for any beam steering device as described throughout the present disclosure. The example of FIG. 29 depicts the actuators **2902**, **2904** providing perpendicular motion to the steering lenses **2902**, **2904**, which may be aligned with the logical steering axes of the beam steering device, or not. The actuators **2402**, **2404** may be of any type as set forth throughout the present disclosure.

(127) Referencing FIG. 30, an example arrangement of actuators **2402**, **2404** moving respective steering lenses (not shown) in a first movement direction **3002** or a second movement direction **3004** are depicted. The example arrangement of FIG. 30 is consistent, for example, with the arrangement of steering lenses **2902**, **2904** depicted in FIG. 29. The movement directions **3002**, **3004** are depicted for purposes of illustration as both perpendicular and linear. However, the movement directions **3002**, **3004** may be non-perpendicular, including an offset of up to about 45 degrees. It will be understood, for example referencing FIGS. 32, 34, 35 and the related description, that utilizing non-perpendicular movement directions **3002**, **3004** reduces the overall steering envelope available for a given actuator movement amount. Nevertheless, the utilization of non-perpendicular movement directions **3002**, **3004** may be desirable for other reasons (e.g., to accommodate installation tolerances, blind installations of one or more components, to accommodate actuator position options within the beam steering device, etc.), and the utilization of non-perpendicular movement directions **3002**, **3004** can be accommodated. Further, the movement directions **3002**, **3004** may be non-linear, including a curve (e.g., imposed by motion of the actuator, to accommodate a housing curvature, to provide space for other components, etc.). The utilization of a curved motion trajectory for one or more movement directions **3002**, **3004** may result in multiple steering solutions—for example more than one actuator **2402**, **2404** position set to achieve a specified steering target value. The utilization of a curved motion trajectory for one or more movement directions **3002**, **3004** can be accommodated, for example as described in relation to FIGS. 32, 34, 35 and the related description. Additionally or alternatively, the movement directions **3002**, **3004** may align with the logical steering axes or not (e.g., reference FIGS. 32, 34 and the related description). The non-alignment of the movement directions **3002**, **3004** with the logical steering axes reduces the overall steering envelope available for a given actuator movement amount. Nevertheless, the utilization of non-aligned movement directions **3002**, **3004** with the logical steering axes may be desirable for other reasons (e.g., to accommodate installation tolerances, blind installations of one or more components, to accommodate actuator position options within the beam steering device, etc.), and the utilization of non-aligned movement directions **3002**, **3004** with the logical steering axes can be accommodated. In certain embodiments, enforcement of perpendicular movement directions **3002**, **3004** may be easier to accomplish (e.g., utilizing a steering layer assembly that is installed as a unit into the beam steering device) than alignment of the movement directions **3002**, **3004** with the logical steering axes.

(128) Referencing FIG. 31, an example arrangement of actuators **2402**, **2404** moving respective steering lenses (not shown) in a first movement direction **3002** or a second movement direction **3004** are depicted. The example movement directions **3002**, **3004** of the example in FIG. 31 are not perpendicular.

(129) Referencing FIG. 32, an example operating diagram **3202** for a beam steering device is depicted. The example operating diagram **3202** maps actuator positions (example horizontal lines **3204** corresponding to positions of a first actuator, and vertical/diagonal lines **3206** corresponding to positions of a second actuator) to logical steering axes values (e.g., elevation and azimuth, in the example). The diagonal nature of the lines **3206** in the example of FIG. 32 indicates that one of the actuators provides a movement direction that is not aligned with a steering axis, and the lack of

perpendicularity of the lines **3204**, **3206** indicates that the movement directions **3002**, **3004** are not perpendicular. Nevertheless, the operating diagram **3202** may be utilized to determine actuator positions to provide selected steering solutions. It can be seen in the example of FIG. **32** that the lack of alignment between the movement directions and the logical steering axes, and the lack of perpendicularity between the movement directions, provides for a reduced steering envelope (e.g., the unachievable steering solutions in the upper left and lower right of the operating diagram **3202**) relative to perfectly aligned and perpendicular movement directions. Nonetheless, the operating space can be sufficiently sized (e.g., utilizing actuators having sufficient movement, and/or increasing an appropriate magnification according to the beam steering device type) such that an arbitrary steering angle capability can be achieved. In certain embodiments, information such as the operating diagram **3202** may be stored on a computer readable medium, for example as an equation, look-up table, or the like, for reference and execution by a controller, circuit, processor, or other functional execution component as described herein. In certain embodiments, the line spacing (e.g., distance between horizontal lines **3204**) may indicate actuator position values to achieve the desired steering solution. In certain embodiments, operating lines (e.g., horizontal lines **3204**) may be curved—for example representing a non-linear motion of the corresponding actuator. It can be seen that if the lines are sufficiently curved, more than one actuator position solution may be available for a given target steering value. Where more than one actuator position solution is available, operations to determine an actuator position to achieve the target steering value may include, without limitation: progression to a closest actuator position (e.g., based on a current actuator position), progression to an actuator position that is furthest from saturation (e.g., keeping the actuators with operating room rather than saturating an actuator), and/or proceeding to a first actuator position and then adjusting to another actuator position (e.g., proceeding to a closest position first, and then adjusting to a different desired actuator position, such as to provide both high transient capability and operating margin for a later steering adjustment).

(130) Referencing FIG. **33**, an example operating diagram **3202** is provided, wherein the actuators provide for perpendicular movement directions, which are additionally aligned with the logical steering axes. It can be seen in the example of FIG. **33** that both alignment and perpendicularity maximize the steering capability envelope for a given actuator movement range. Referencing FIG. **34**, an example operating diagram **3202** is provided, wherein the actuators provide for perpendicular movement directions, which are significantly not aligned with the logical steering axes. It can be seen in the example of FIG. **34** that significant mis-alignment of the movement directions with the logical steering axes significantly reduces the steering capability envelope for a given actuator movement range. Nonetheless, the operating space can be sufficiently sized (e.g., utilizing actuators having sufficient movement, and/or increasing an appropriate magnification according to the beam steering device type) such that an arbitrary steering angle capability can be achieved. Referencing FIG. **35**, an example operating diagram **3202** is provided wherein the actuators do not provide perpendicular movement directions, and where neither of the movement directions are aligned with the logical steering axes.

(131) Referencing FIG. **36**, an example variaxial lens **3600** is schematically depicted. The example variaxial lens **3600** is depicted in an end view—for example where the EM beam to be steered passes vertically through the variaxial lens **3600** as depicted. The example variaxial lens **3600** includes a number of discrete high side electrodes **3602** that have controllable voltages, and a number of opposing discrete low side electrodes **3604** that may be a ground voltage, a low voltage (including a non-zero and/or a negative voltage). The variaxial lens **3600** includes an electro-optical substrate **3606**, for example having a refractive index (and/or birefringence) that changes in response to an applied electric field. An example variaxial lens **3600** may be provided as a steering lens—for example, the voltages of the high side electrodes **3602** (and/or the low side electrodes **3604**) are adjusted to “move” the lens to a selected location on the variaxial lens **3600**.

Accordingly, the variaxial lens **3600** is a writeable lens suitable as both a steering lens and actuator

as a part of a steering layer of a beam steering device. Typically, the maximum voltage is held constant (e.g., providing a same focal length of the variaxial lens **3600** during operations), with a voltage trajectory on either side of the maximum voltage position to provide the full writeable lens. In certain embodiments, the low side electrodes **3604** may be continuous. The utilization of a variaxial lens **3600** for one or more of the steering lenses provides for rapid response time and elimination of moving mechanical parts for at least a portion of the beam steering device.

(132) Referencing FIG. **37**, a writeable lens **3700** is schematically depicted. The example writeable lens **3700** includes a pixel grid **3708** of high side electrodes on a first side (the front side which is showing, in the example of FIG. **37**), and either a corresponding pixel grid or a continuous low side electrode on a second side (the back side which is not showing, in the example of FIG. **37**). The writeable lens **3700** includes an electro-optical substrate **3710** throughout at least an active area of the lens, for example having a refractive index (and/or birefringence) that changes in response to an applied electric field. The electrodes in the example are transparent electrodes, and the EM beam to be steered passes through the writeable lens **3700** into or out of the face of the writeable lens **3700** as depicted. Accordingly, the writeable lens **3700** is suitable as both a pair of steering lenses and actuator as a part of a steering layer of a beam steering device. Typically, the maximum voltage is held constant (e.g., providing a same focal length of the variaxial lens **3600** during operations), with a voltage trajectory surrounding the maximum voltage position to provide the full writeable lens, forming the lens portion **3706**. The utilization of a writeable lens **3700** such as that depicted provides for steering in both a first axis **3702** and a second axis **3704** (e.g., the position of the lens portion **3706** can be moved through voltage changes), that may be moved rapidly and without moving mechanical parts for at least a portion of the beam steering device.

(133) Referencing FIG. **38**, an example apparatus **3800** to control beam steering is schematically depicted. The example apparatus **3800** may be utilized with any beam steering device described throughout the present disclosure. The example apparatus **3800** may be included as a part of a beam steering device, as a part of a system including a beam steering device, and/or may be provided in communication with one or more aspects of a beam steering device, such as but not limited to actuator(s) **318**, active or write-able lenses (e.g., reference FIGS. **36**, **37**, and the related description), sensors (not shown, but including, for example, temperature determinations for various components, actuator feedback sensors, etc.), and/or active cooling components (not shown). The example apparatus **3800** may be communicatively coupled to any component of a beam steering device, and may be configured to receive steering command value(s) (e.g., provided by an operator, a controller (not shown), as a data file, etc.) and/or fault condition values (e.g., confirming operations of any actuator, steering device, active cooling device, etc.), and may further be configured to provide commands to any active component of the system (e.g., actuators **318**, active cooling devices, write-able lenses, etc.).

(134) The example apparatus **3800** includes a beam steering controller **3802** having a number of circuits configured to functionally execute operations of the controller **3802**. The example controller **3802** is depicted as a single device for clarity of description, but may be a distributed device, positioned on another device as a portion thereof (e.g., a system controller for a system including a beam steering device), or combinations of these. The example controller **3802** includes a steering target circuit **3803** that interprets a beam steering target value **3801** (e.g., a steering angle for a first beam, a steering target location for the first beam, a trajectory of these (e.g., relative to time, a scanning frequency, etc.), a steering lens control circuit **3804** that determines position(s) for steering lens(es) in response to the beam steering target value **3801**, and a steering actuation circuit **3806** that provides actuator command value(s) **3810** for actuators **318** of a beam steering device.

(135) An example steering target circuit **3803** makes the beam steering target value **3801** available to the steering lens control circuit **3804**, and may configure the beam steering target value **3801** according to a selected steering scheme. For example, the beam steering target value **3801** may be provided as a steering command according to an application view (e.g., 15 degrees azimuth, and -2

degrees elevation), and/or as a steering command according to a transformed view relative to the application view (e.g., making the steered beam incident on the emission lens at a selected location of the emission lens).

(136) The circuits **3803**, **3804**, **3806** are depicted as single devices for clarity of the present description. However, a given circuit **3803**, **3804**, **3806** may be: a distributed device; provided as a part of another device; provided, in whole or part, as computer readable instructions stored on a memory (not shown), wherein a processor (not shown) executing the instructions thereby performs at least a portion of the operations of the respective circuit **3803**, **3804**, **3806**; and/or provided, in whole or part, as a logic circuit and/or hardware component(s) configured to perform at least a portion of the operations of the respective circuit. A circuit, as utilized herein, may include one or more of any actuator, sensor, or other component of a beam steering device, and/or may be in communication with any actuator, sensor, or other component of the beam steering device.

(137) An example steering lens control circuit **3804** determines a first position of a first steering lens and a second position of a second steering lens (e.g., operating with a beam steering device including a steering layer having two steering lenses) in response to the beam steering target value **3801**. Example operations to determine the positions of the steering lenses include one or more of: determining a lens offset for each respective axis (e.g., where the lens movement for each steering lens is aligned with a steering axis); transforming the steering target value **3801** to respective lens positions **3808** (e.g., utilizing an operating diagram **3202**, transforming equation, or the like); and/or selecting positions consistent with the steering target value (e.g., where more than one available position set will achieve the steering, for example when an actuator has a curved movement path for a steering lens). An example steering lens control circuit **3804** can perform, without limitation, any operation as described herein to determine positions for a steering layer and/or for individual steering lenses, that provide steering according to the beam steering target value **3801**. An example steering lens control circuit **3804** accesses stored data **3812**, such as transformation parameters, operating diagrams **3202**, or the like. The lens positions **3808** correspond to a displacement of a steering lens (e.g., 3 mm in “x” direction, and 1 mm in “y” direction), and/or to a location of a steering lens on a writeable lens (e.g., a position of a variaxial lens, and/or a position on a pixelated writeable lens, and which may be an absolute position and/or a relative position) that provide beam steering according to the beam steering target value **3801**.

(138) An example steering actuation circuit **3806** provides actuator command value(s) **3810** in response to the lens position(s) **3808**, for example providing a first actuator command value in response to a first position, and a second actuator command value in response to a second position. The example of FIG. **38** is adaptable to steering multiple beams, for example with regard to a type 2 beam steering device, where multiple beam steering values **3801** are provided corresponding to each of a number of optical paths (e.g., each having an individual beam steering device, such as depicted in FIGS. **15-17** and **22**).

(139) Referencing FIG. **39**, another example apparatus **3900** to control beam steering is schematically depicted. The example apparatus **3900** includes a beam steering controller **3802** configured to steer a number of beams, which may be steered simultaneously (but need not be), with a number of beam steering target values **3801** each corresponding to one of a number of optical paths **3902** (e.g., each optical path having an individual beam steering device and/or devices, for example as depicted in FIGS. **15-17** and **22**). In the example of FIG. **39**, the steering target circuit **3803** is further capable to swap a beam steering target value **3801** from a first optical path **3902** to a second optical path **3902**, for example in response to steering capability(ies) of the associated individual beam steering device(s) for those optical paths, and the beam steering target values **3801**. In the example, the beam steering controller **3802** provides the swapped beam steering target value(s) **3906** to the steering lens control circuit **3804** as the beam steering target value **3801**. Without limitation to any other aspect of the present disclosure, the swapped beam steering target value(s) **3906** may be determined to ensure capability of a type 2 beam steering device to meet all

targeted steering operations, to reduce an aggregate amount of actuator movement across the individual beam steering devices (e.g., reducing power consumption, reducing a time to achieve the targeted steering operations, to preserve operating margin for one or more individual beam steering devices, and/or to reduce a maximum actuator movement from among the actuators being moved responsive to the steering commands). Operations to swap the beam steering target values may be performed during transient operations (e.g., rapid changes in steering angles), and/or during operations where one or more individual steering devices are commanded to steer to an angle that is not achievable by the nominal device (but a substitute individual steering device in the system is capable to steer to the commanded angle). Operations to swap the beam steering target values may be reversed (e.g., returning steering control for a specific steered beam to a nominal device) and/or changed (e.g., utilizing another substitute individual steering device) based on, without limitation, any one or more of: lack of capability of the initial substitute device to support updated steering commands (e.g., where another substitute device is capable to support the updated steering command); a change in the steering command where the nominal device is capable to support the steering command as changed; a change in steering operations from a highly transient operation to a lower transient operation (e.g., returning steering operation to a nominal device as operations approach steady state and/or a reduced transient); changes in operation to preserve operating margin (e.g., initially meeting steering operations with a first set of individual steering devices to respond to a first condition, such as the desired speed of steering operations; and updating steering operations with a second set of individual steering devices to respond to a second condition, such as preserving an operating margin of the entire system of individual steering devices, rotating utilization among individual steering devices, distributing heat generation throughout multiple individual steering devices, etc.).

(140) Referencing FIGS. **40-42**, example and non-limiting swapping operations are schematically depicted. Referencing FIG. **40**, an example system **4000** includes a type 2 steering device **4034** includes a number of optical paths, each having an individual steering device **4024**, **4026**, **4028**, **4030**, **4032**, and configured to selectively steer a beam from a corresponding EM source **4014**, **4016**, **4018**, **4020**, **4022**. In the example of FIG. **40**, three steering target values **4002**, **4004**, **4006** are provided, with corresponding steered beams **4008**, **4010**, **4012** that are to be steered to the steering target values **4002**, **4004**, **4006**. For purposes of illustration, steering target value **4002** is nominally commanded to an individual beam steering device **4024** provided in a second tier of individual beam steering devices, steering target value **4002** is nominally commanded to an individual beam steering device **4026** in a first tier of individual beam steering devices, and steering target value **4006** is nominally commanded to an individual beam steering device **4028** which is a centerline device in the example.

(141) Referencing FIG. **41**, operations of the beam steering controller **3802** have swapped the beam steering target values **4002**, **4004**, **4006**, for example to be serviced by individual beam steering devices **4026**, **4028**, **4030**, rather than nominal devices **4024**, **4026**, **4028** as depicted in FIG. **40**. The swapping may be a single swap (e.g., individual steering device **4030** services steering for the first target steering value **4002** in the place of individual steering device **4024**), a shift (e.g., device **4026** replaces device **4024**, device **4028** replaces device **4026**, and device **4030** replaces device **4028**), swapping within a tier (e.g., a tier 2 device replaces another tier 2 device), across tiers (e.g., a tier 1 device replaces a tier 2 device), and/or any other swapping operations as described throughout the present disclosure. It can be seen that swapping may occur among any individual beam steering devices, among related devices (e.g., according to tier, steering capability envelope coverage, etc.), and/or among devices having compatible EM sources **4014**, **4016**, **4018**, **4020**, **4022** associated therewith (e.g., between devices having a same or similar EM source, and/or having a configurable EM source capable to provide an acceptable EM beam during swapping operations). The EM sources **4014**, **4016**, **4018**, **4020**, **4022**, as described throughout the present disclosure, may additionally or alternatively include a detection array or the like, and swapping

operations may be available among devices according to the characteristics of the detection devices (e.g., similar pixel resolution, etc.).

(142) Referencing FIG. 42, operations of the beam steering controller **3802** have swapped the beam steering target values **4002**, **4004**, **4006**, for example to be serviced by individual beam steering devices **4026**, **4028**, **4032**, rather than nominal devices **4024**, **4026**, **4028** as depicted in FIG. 40. In the example of FIG. 42, the swapping is depicted as a swap from a nominal individual beam steering device **4024** to another individual beam steering device **4032** within the same tier. The illustration of FIG. 42 is a non-limiting example.

(143) Referencing FIG. 43, an example procedure **4300** to steer one or more EM beams is schematically depicted. The example procedure **4300** includes an operation **4302** to interpret a beam steering value (e.g., a location, steering angle, and/or other steering description) for steering an incident EM beam, and an operation **4304** to determine steering lens position(s) in response to the beam steering value. Example operations **4304** include transforming between logical steering axes and movement axes (and/or a movement trajectory, movement course, etc.) of an actuator configured to perform steering lens movement operations for associated steering layer(s).

(144) The example procedure **4300** further includes an operation **4306** to command an actuator to move steering lens(es) along movement courses (e.g., the movement trajectory of the lens enforced by the actuator) in response to the steering lens position(s). Operations of the example procedure **4300** may be performed to steer a single beam in a single axis, to steer the single beam along two axes (e.g., azimuth and elevation, or other steering nomenclature), and/or to steer more than one beam simultaneously, each having one or two steering axes. Example operations **4306** include providing an actuator command (e.g., a position, voltage, or other command), providing commands to a variaxial lens to move the lens to a selected portion of the EO active substrate, changing a position of an active lens portion of a configurable lens, and/or providing an actuator command to write a lens to a selected portion of a pixelated EO active substrate.

(145) Referencing FIG. 44, an example procedure **4400** includes an operation **4402** to determine a number of beam steering target values for a number of optical steering paths of a beam steering device — for example optical steering paths each having an individual beam steering device positioned therein. The example procedure **4400** includes an operation **4404** to determine whether to swap one or more beam steering target values between optical steering paths among the number of optical steering paths. In response to operation **4404** determining NO, the procedure **4400** includes an operation **4408** to determine steering lens position(s) for the individual beam steering devices in response to the beam steering target values, and an operation **4410** to command actuators to move steering lenses (e.g., along movement courses associated with each actuator) in response to the steering lens positions. In response to operation **4404** determining YES, the procedure **4400** includes an operation **4406** to determine steering lens position(s) for the individual beam steering devices in response to the swaps and the beam steering target values. Operations **4406** may additionally or alternatively include activating, de-activating, and/or configuring EM sources associated with the swapped individual beam steering devices such that the active steering devices receive an incident EM beam from the associated EM source, configured (e.g., frequency, phase, energy, trajectories of these, etc.) according to the intended steered beam characteristics. Without limitation to any other aspect of the present disclosure, operations **4406** to determine swaps among the individual beam steering devices include, without limitation, operations such as: providing an aggregate steering capability of the beam steering device to provide steered beams according to the beam steering target values; operations to reduce an aggregate movement amount of actuators of the beam steering device; operations to reduce an aggregate power consumption of the beam steering device; operations to reduce a time to achieve the beam steering target values; operations to reduce a maximum displacement of an actuator of the beam steering device (e.g., reducing a maximum displacement utilized to achieve a new steering target value); and/or operations to control reversion of steering operations to nominal individual beam steering devices (e.g., returning

to nominal steering after a transient event is serviced; adjusting the swapping to increase a capability margin of an individual beam steering device and/or an overall capability margin of the beam steering device; and/or utilizing hysteresis to control swapping adjustments, return to nominal operations, etc., for example to reduce dithering, cycling, or the like).

(146) An example system includes a first steering lens interposed between an electromagnetic (EM) source and a second steering lens; the second steering lens interposed between the first steering lens and a magnifying lens; the magnifying lens interposed between the second steering lens and a field lens; the field lens interposed between the magnifying lens and an emission lens; a first steering actuator coupled to the first steering lens, the first steering actuator configured to move the first steering lens along a first movement course; and a second steering actuator coupled to the second steering lens, the second steering actuator configured to move the second steering lens along a second movement course.

(147) Certain further aspects of the example system are described following, any one or more of which may be present in certain embodiments. The example system includes one or more of: wherein an optical configuration of the first steering lens, the second steering lens, and the magnifying lens is configured to position a virtual object of the steering lenses at a position between $f_{\text{sub.m}}$ and $2f_{\text{sub.m}}$, wherein the position $f_{\text{sub.m}}$ comprises a magnifying lens focal length displaced from the magnifying lens, and wherein the position $2f_{\text{sub.m}}$ comprises twice the distance $f_{\text{sub.m}}$; and/or wherein the optical configuration of the first steering lens, the second steering lens, and the magnifying lens comprises: an effective focal length of the combined first steering lens and second steering lens; the magnifying lens focal length; and an axial position of each of the first steering lens, second steering lens, and the magnifying lens.

(148) Another example system includes a steering lens interposed between an electromagnetic (EM) source and a magnifying lens; the magnifying lens interposed between the steering lens and a field lens; the field lens interposed between the magnifying lens and an emission lens; and a steering actuator coupled to the steering lens, the steering actuator configured to move the steering lens along a movement course.

(149) Certain further aspects of the example system are described following, any one or more of which are present in certain embodiments. An example system includes one or more of: wherein the movement course comprises selected movement along each of two axes; wherein a first one of the two axes comprises a first steering axis, and wherein a second one of the two axes comprises a second steering axis; wherein the two axes comprise perpendicular axes; wherein the steering actuator comprises a configurable lens element having an active lens portion, wherein the steering lens comprises the active lens portion, and wherein moving the steering lens along the movement course comprises changing a position of the active lens portion; wherein the steering lens comprises a positive lens, the system further comprising a second field lens positioned between the steering lens and the magnifying lens; and/or a source collimator lens interposed between the EM source and the steering lens.

(150) An example system includes: an emission lens defining an optical emission end of a beam steering device; a field lens interposed between the emission lens and a plurality of optical steering paths; a first optical steering path of the plurality of optical steering paths, the first optical steering path comprising a first magnifying lens interposed between the field lens and a first steering layer, wherein the first steering layer is interposed between the first magnifying lens and a first electromagnetic (EM) source, a first steering actuator coupled to the first steering layer, the first steering actuator configured to move the first steering layer along a first movement course; a second optical steering path of the plurality of optical steering paths, the second optical steering path comprising a second magnifying lens interposed between the field lens and a second steering layer, wherein the second steering layer is interposed between the second magnifying lens and a second EM source, and a second steering actuator coupled to the second steering layer, the second steering actuator configured to move the second steering layer along a second movement course.

(151) Certain further aspects of the example system are described following, any one or more of which may be present in certain embodiments. An example system includes wherein the first steering layer comprises a first steering lens interposed between the first EM source and a second steering lens, the second steering lens interposed between the first steering lens and the field lens, the first steering lens and the second steering lens having a combined first effective focal length, the field lens comprising a positive lens have a second focal length, wherein the first effective focal length is shorter than the second focal length, a first steering actuator coupled to the first steering lens, the first steering actuator configured to move the first steering lens along a first direction of the first movement course, and a second steering actuator coupled to the second steering lens, the second steering actuator configured to move the second steering lens along a second direction of the first movement course. An example system includes wherein the first steering layer comprises a steering lens interposed between the first EM source and the field lens, the steering lens having a first focal length, the field lens comprising a positive lens having a second focal length, wherein the first focal length is shorter than the second focal length, and a steering actuator coupled to the steering lens, the steering actuator configured to move the first steering lens along the first movement course. An example system includes wherein the first steering layer comprises, a first steering lens interposed between the first EM source and a second steering lens, the second steering lens interposed between the first steering lens and a magnifying lens, the magnifying lens interposed between the second steering lens and the field lens, a first steering actuator coupled to the first steering lens, the first steering actuator configured to move the first steering lens along a first direction of the first movement course, and a second steering actuator coupled to the second steering lens, the second steering actuator configured to move the second steering lens along a second direction of the first movement course. An example system includes wherein the first steering layer comprises a steering lens interposed between the first EM source and a magnifying lens, the magnifying lens interposed between the steering lens and the field lens, and a steering actuator coupled to the steering lens, the steering actuator configured to move the first steering lens along a first direction of the first movement course. An example system includes one or more of: wherein the first optical steering path comprises a centerline steering path, and wherein the second optical steering path comprises an offset steering path; wherein the first optical steering path comprises a centerline steering path, and wherein the second optical steering path comprises one of a plurality of offset steering paths; wherein the plurality of offset optical steering paths comprises six offset steering paths; wherein the first optical steering path comprises a centerline steering path, wherein the second optical steering path comprises one of a first plurality of offset steering paths surrounding the centerline steering path, the system further comprising a second plurality of offset steering paths surrounding the first plurality of offset steering paths; wherein the first plurality of offset steering paths comprises six offset steering paths; wherein the second plurality of offset steering paths comprises twelve offset steering paths; further comprising a third plurality of offset steering paths surrounding the second plurality of offset steering paths; wherein the first plurality of offset steering paths comprises six offset steering paths; wherein the second plurality of offset steering paths comprises twelve offset steering paths; and/or wherein the third plurality of offset steering paths comprises eighteen offset steering paths.

(152) An example system further includes a controller having a steering target circuit structured to interpret a beam steering target value for each of the plurality of optical steering paths, a steering lens control circuit structured to determine a steering lens position for each of the plurality of optical steering paths in response to a corresponding beam steering target value for each of the plurality of optical steering paths, a steering actuation circuit structured to provide an actuator command value for a corresponding actuator for each of the plurality of optical steering paths in response to the corresponding steering lens positions, and where an actuator for each of the plurality of optical steering paths are responsive to the corresponding actuator command values. An example system further includes wherein the steering target circuit is further structured to swap a

beam steering target value from a first one of the plurality of offset steering paths to a second one of the plurality of offset steering paths. An example system further includes one or more of: wherein the steering target circuit is further structured to swap a beam steering target value from a first one of the first plurality of offset steering paths to a second one of the first plurality of offset steering paths; wherein the steering target circuit is further structured to swap a beam steering target value from a first one of the first plurality of offset steering paths to a first one of the second plurality of offset steering paths; and/or wherein the steering target circuit is further structured to swap a beam steering target value from a first one of the second plurality of offset steering paths to a second one of the second plurality of offset steering paths.

(153) The methods and systems described herein may be deployed in part or in whole through a machine having a computer, computing device, processor, circuit, and/or server that executes computer readable instructions, program codes, instructions, and/or includes hardware configured to functionally execute one or more operations of the methods and systems disclosed herein. The terms computer, computing device, processor, circuit, and/or server, as utilized herein, should be understood broadly.

(154) Any one or more of the terms computer, computing device, processor, circuit, and/or server include a computer of any type, capable to access instructions stored in communication thereto such as upon a non-transient computer readable medium, whereupon the computer performs operations of systems or methods described herein upon executing the instructions. In certain embodiments, such instructions themselves comprise a computer, computing device, processor, circuit, and/or server. Additionally or alternatively, a computer, computing device, processor, circuit, and/or server may be a separate hardware device, one or more computing resources distributed across hardware devices, and/or may include such aspects as logical circuits, embedded circuits, sensors, actuators, input and/or output devices, network and/or communication resources, memory resources of any type, processing resources of any type, and/or hardware devices configured to be responsive to determined conditions to functionally execute one or more operations of systems and methods herein.

(155) Certain operations described herein include interpreting, receiving, and/or determining one or more values, parameters, inputs, data, or other information (“receiving data”). Operations to receive data include, without limitation: receiving data via a user input; receiving data over a network of any type; reading a data value from a memory location in communication with the receiving device; utilizing a default value as a received data value; estimating, calculating, or deriving a data value based on other information available to the receiving device; and/or updating any of these in response to a later received data value. In certain embodiments, a data value may be received by a first operation, and later updated by a second operation, as part of the receiving a data value. For example, when communications are down, intermittent, or interrupted, a first receiving operation may be performed, and when communications are restored an updated receiving operation may be performed.

(156) Certain logical groupings of operations herein, for example methods or procedures of the current disclosure, are provided to illustrate aspects of the present disclosure. Operations described herein are schematically described and/or depicted, and operations may be combined, divided, re-ordered, added, or removed in a manner consistent with the disclosure herein. It is understood that the context of an operational description may require an ordering for one or more operations, and/or an order for one or more operations may be explicitly disclosed, but the order of operations should be understood broadly, where any equivalent grouping of operations to provide an equivalent outcome of operations is specifically contemplated herein. For example, if a value is used in one operational step, the determining of the value may be required before that operational step in certain contexts (e.g. where the time delay of data for an operation to achieve a certain effect is important), but may not be required before that operation step in other contexts (e.g. where usage of the value from a previous execution cycle of the operations would be sufficient for those

purposes). Accordingly, in certain embodiments an order of operations and grouping of operations as described is explicitly contemplated herein, and in certain embodiments re-ordering, subdivision, and/or different grouping of operations is explicitly contemplated herein.

(157) The methods and systems described herein may transform physical and/or or intangible items from one state to another. The methods and systems described herein may also transform data representing physical and/or intangible items from one state to another.

(158) The methods and/or processes described above, and steps thereof, may be realized in hardware, program code, instructions, and/or programs or any combination of hardware and methods, program code, instructions, and/or programs suitable for a particular application. The hardware may include a dedicated computing device or specific computing device, a particular aspect or component of a specific computing device, and/or an arrangement of hardware components and/or logical circuits to perform one or more of the operations of a method and/or system. The processes may be realized in one or more microprocessors, microcontrollers, embedded microcontrollers, programmable digital signal processors or other programmable device, along with internal and/or external memory. The processes may also, or instead, be embodied in an application specific integrated circuit, a programmable gate array, programmable array logic, or any other device or combination of devices that may be configured to process electronic signals. It will further be appreciated that one or more of the processes may be realized as a computer executable code capable of being executed on a machine readable medium.

(159) While only a few embodiments of the present disclosure have been shown and described, it will be obvious to those skilled in the art that many changes and modifications may be made thereunto without departing from the spirit and scope of the present disclosure as described in the following claims. All patent applications and patents, both foreign and domestic, and all other publications referenced herein are incorporated herein in their entireties to the full extent permitted by law.

(160) While the disclosure has been disclosed in connection with the preferred embodiments shown and described in detail, various modifications and improvements thereon will become readily apparent to those skilled in the art. Accordingly, the spirit and scope of the present disclosure is not to be limited by the foregoing examples, but is to be understood in the broadest sense allowable by law.

(161) The use of the terms “a” and “an” and “the” and similar referents in the context of describing the disclosure (especially in the context of the following claims) is to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. The terms “comprising,” “having,” “including,” and “containing” are to be construed as open-ended terms (i.e., meaning “including, but not limited to,”) unless otherwise noted. Recitation of ranges of values herein are merely intended to serve as a shorthand method of referring individually to each separate value falling within the range, unless otherwise indicated herein, and each separate value is incorporated into the specification as if it were individually recited herein. All methods described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples, or exemplary language (e.g., “such as”) provided herein, is intended merely to better illuminate the disclosure, and does not pose a limitation on the scope of the disclosure unless otherwise claimed. No language in the specification should be construed as indicating any non-claimed element as essential to the practice of the disclosure.

(162) While the foregoing written description enables one skilled in the art to make and use what is considered presently to be the best mode thereof, those skilled in the art will understand and appreciate the existence of variations, combinations, and equivalents of the specific embodiment, method, and examples herein. The disclosure should therefore not be limited by the above described embodiment, method, and examples, but by all embodiments and methods within the scope and spirit of the disclosure.

(163) Any element in a claim that does not explicitly state “means for” performing a specified function, or “step for” performing a specified function, is not to be interpreted as a “means” or “step” clause as specified in 35 U.S.C. § 112(f). In particular, any use of “step of” in the claims is not intended to invoke the provision of 35 U.S.C. § 112(f).

(164) Persons skilled in the art may appreciate that numerous design configurations may be possible to enjoy the functional benefits of the inventive systems. Thus, given the wide variety of configurations and arrangements of embodiments of the present invention, the scope of the invention is reflected by the breadth of the claims below rather than narrowed by the embodiments described above.

Claims

1. A system, comprising: a steering layer including a first steering lens and a second steering lens each interposed between an electromagnetic (EM) source and an emission lens, the first steering lens and the second lens of the steering layer having a combined first effective focal length; the emission lens comprising a positive lens having a second focal length; wherein the first effective focal length is shorter than the second focal length; and a first steering actuator coupled to the first steering lens, the first steering actuator configured to move the first steering lens along a first axis; and a second steering actuator coupled to the second steering lens, the second steering actuator configured to move the second steering lens along a second axis, wherein the second axis is distinct from the first axis.
2. The system of claim 1, wherein the first and second axes are comprised in movement courses comprising selected movement along each of the first and second axes.
3. The system of claim 2, wherein the first axis comprises a first steering axis, and wherein the second axis comprises a second steering axis.
4. The system of claim 2, wherein the first and second axes are perpendicular to each other.
5. The system of claim 1, wherein: the first steering actuator comprises a configurable lens element having an active lens portion, wherein the first steering lens comprises the active lens portion, and wherein moving the first steering lens along the first axis comprises changing a position of the active lens portion; and the second steering actuator comprises a configurable lens element having an active lens portion, wherein the second steering lens comprises the active lens portion, and wherein moving the second steering lens along the second axis comprises changing a position of the active lens portion.
6. The system of claim 1, wherein the steering layer comprises a positive lens, the system further comprising a field lens positioned between the steering layer and the emission lens.
7. The system of claim 1, further comprising a source collimator lens interposed between the EM source and the steering layer.
8. A system, comprising: a fixed positive lens interposed between an electromagnetic (EM) source and a first steering layer; the first steering layer interposed between the fixed positive lens and a second steering layer, the first steering layer comprising a net negative effective focal power; the second steering layer comprising a net positive effective focal power, wherein the net negative effective focal power of the first steering layer comprises a distinct magnitude from the net positive effective focal power of the second steering layer; a first steering actuator coupled to the first steering layer, the first steering actuator configured to move the first steering layer along a first movement course; and a second steering actuator coupled to the second steering layer, the second steering actuator configured to move the second steering layer along a second movement course.
9. The system of claim 8, wherein the first steering layer comprises two lenses, and wherein the first steering actuator comprises a pair of actuators, each coupled to a corresponding one of the two lenses of the first steering layer.
10. The system of claim 8, wherein the second steering layer comprises two lenses, and wherein the

- second steering actuator comprises a pair of actuators, each coupled to a corresponding one of the two lenses of the second steering layer.
11. The system of claim 8, further comprising a source collimator lens interposed between the EM source and the steering lens.
12. The system of claim 1, wherein the system further comprises a field lens positioned at a focal plane of the emission lens.
13. The system of claim 1, wherein the emission lens is fixed in position.
14. The system of claim 8, further comprising an emission lens, wherein the first positive lens, the first steering layer, and the second steering layer are interposed between the EM source and the emission lens.
15. The system of claim 8, wherein at least one of a steering or a displacement capability of the first steering actuator is different from at least one of a steering or a displacement capability of the second steering actuator.
-