

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405600
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Mishra; Ajay et al.

Safety instrumented system interface

Abstract

Dual layer interface with a safety instrumented system (SIS) in an industrial plant. A diagnostic status aggregator having an established connection with the SIS collects and stores health and diagnostic status data from the SIS. An interface processing engine communicatively coupled to the diagnostic status aggregator and to a user device receives a new request for information relating to the SIS from the user device. A memory stores processor-executable instructions that, when executed, configure the interface processing engine for parsing the new request to identify one or more specific keywords therein associated with the requested information relating to the SIS, generating a query based on the identified keywords, retrieving, from the diagnostic status aggregator, the status data collected from the SIS responsive to the query, and providing, the status data retrieved from the diagnostic status aggregator to the user device.

Inventors: Mishra; Ajay (Irvine, CA), Ivanov; Diana (Rancho Santa Margarita, CA), Banchik; Erna (Rancho Santa Margarita, CA), Chockalingam; Karpagam (Mission Viejo, CA)

Applicant: Schneider Electric Systems USA, Inc. (Foxboro, MA)

Family ID: 78073787

Assignee: SCHNEIDER ELECTRIC SYSTEMS USA, INC. (Foxboro, MA)

Appl. No.: 17/032844

Filed: September 25, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20220100180 A1	Mar. 31, 2022

Publication Classification

Int. Cl.: G05B19/418 (20060101); G06F16/68 (20190101); G06F16/9032 (20190101);
G06F16/9035 (20190101); G06F16/9038 (20190101); G06F40/205 (20200101)

U.S. Cl.:

CPC G05B19/41865 (20130101); G05B19/4183 (20130101); G05B19/41885 (20130101);
G06F16/686 (20190101); G06F16/90332 (20190101); G06F16/9035 (20190101);
G06F16/9038 (20190101); G06F40/205 (20200101);

Field of Classification Search

CPC: G05B (19/4183); G05B (19/0428); G06F (16/90332); G06F (16/9035)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9582376	12/2016	Gabler et al.	N/A	N/A
12099935	12/2023	Okuno	N/A	G06N 5/02
2002/0112044	12/2001	Hessmer	709/223	H04L 69/329
2013/0110520	12/2012	Cheyet et al.	N/A	N/A
2015/0105887	12/2014	Troy	700/97	G05B 19/41865
2017/0068670	12/2016	Orr	N/A	H04N 21/41265
2017/0084167	12/2016	Bump	N/A	G06F 11/079
2017/0213155	12/2016	Hammond	N/A	G06F 8/31
2018/0357047	12/2017	Brown	N/A	G06F 18/2148
2018/0357334	12/2017	Chao	N/A	G05B 19/4185
2019/0026318	12/2018	Bertellotti	N/A	G06F 16/248
2019/0107827	12/2018	Dhakshinamoorthy	N/A	G05B 19/4183
2020/0117742	12/2019	Huang	N/A	G06F 16/24564
2020/0387147	12/2019	Nixon	N/A	G05B 19/4185
2021/0048798	12/2020	Bulanda	N/A	H04J 3/0661

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3451616	12/2018	EP	N/A
2018152053	12/2017	WO	N/A

OTHER PUBLICATIONS

European Search Report, European Application No. 21197400.1, dated Feb. 16, 2022, 12 pages.
cited by applicant

Primary Examiner: Mackes; Kris E

Attorney, Agent or Firm: Stinson LLP

Background/Summary

BACKGROUND

(1) In a process control system, fault tolerance enables continued operation in the event components within the system fail, or in the event the system experiences transient faults from various sources. One aspect common to fault tolerant systems involves the concept of redundancy, which can be simply defined as back up components that become operational when a failure occurs, allowing the system to continue to operate as intended. Safety instrumented systems (SIS), such as Triconex® safety controllers and the like available from Schneider Electric Systems USA, Inc., are known in the art for continuing operation in a “safe state” to avoid adverse safety and health consequences through the use of a fault tolerant controller. Such fault tolerant controllers are often used in hazard protection systems (i.e., systems that regulate nuclear plant operation, turbomachinery, fire and gas sensing systems, and the like).

(2) The safety demands on control systems vary by industry and application. While all must generally maintain operational parameters within desired ranges over time, control systems employed in industries such as oil & gas, chemical, and power additionally insure that controlled systems and subsystems avoid reaching states that might lead to hazard within the plant and/or its environs (e.g., fire, explosion, hazardous materials release, equipment destruction, human injury or loss of life, etc.). A typical SIS installed in the process is programmed to identify an impending highly critical unsafe event and respond immediately to drive the process to a safe condition. This is typically done independently from the process control system, but may at times be coordinated with the process control system. At the same time, these “safety systems” are expected to provide high availability while avoiding false trips that might lead system or subsystem shut-down (or operational down-regulation) in response to false sensor readings and/or when safety is not truly at risk. Field devices, controllers, workstations and other apparatus supporting preferred such safety systems are manufactured and sold by the assignee hereof under its Triconex® brand label, among others.

SUMMARY

(3) Briefly, aspects of the present disclosure provide efficient monitoring of safety systems by making information available to an end user from any location via a dual interface layer. The dual interface layer does not directly interact with the SIS, which ensures security and safety when processing information requests. In operation, the user uses a mobile device, such as a smartphone, to request access to the desired information by speech or text.

(4) Aspects of the present disclosure further provide enhanced interaction between the user and the safety system through remote maintenance capability, such as a handheld app, chat-bot, and voice-based interface with natural voice processing. For geo-location based requests, equipment can be identified externally by including a machine-readable code, which can be read by the mobile device). The statuses of the safety system are shared using a unidirectional interface for information flow such that the remote access components do not direct interact with the SIS. Instead there is dual layer for interaction.

(5) In an aspect, a method for interfacing with at least one SIS in an industrial plant comprises receiving, from a user device via an interface processing engine, a new request for information relating to the SIS. The user device is communicatively coupled to the interface processing engine and the interface processing engine is communicatively coupled to a diagnostic status aggregator. The diagnostic status aggregator has an established connection with the SIS and stores at least one of health and diagnostic status data collected from the SIS. The method further comprises parsing the new request to identify one or more specific keywords therein associated with the requested information relating to the SIS, generating a query based on the identified keywords, retrieving the

status data collected from the SIS responsive to the query, and providing the status data retrieved from the diagnostic status aggregator to the user device.

(6) In another aspect, a dual layer interface with a SIS includes a diagnostic status aggregator having an established connection with the SIS that collects and stores health and diagnostic status data from the SIS. An interface processing engine communicatively coupled to the diagnostic status aggregator and to a user device receives a new request for information relating to the SIS from the user device. A memory stores processor-executable instructions that, when executed, configure the interface processing engine for parsing the new request to identify one or more specific keywords therein associated with the requested information relating to the SIS, generating a query based on the identified keywords, retrieving, from the diagnostic status aggregator, the status data collected from the SIS responsive to the query, and providing, the status data retrieved from the diagnostic status aggregator to the user device.

(7) Other features will be in part apparent and in part pointed out hereinafter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a process control network architecture according to an embodiment.

(2) FIG. 2 is a block diagram of a safety instrumented system interface according to an embodiment.

(3) FIG. 3 is a block diagram of an interface processing engine of the interface of FIG. 2.

(4) Corresponding reference characters indicate corresponding parts throughout the drawings.

DETAILED DESCRIPTION

(5) FIG. 1 illustrates aspects of a plant network **100** in the form of an example process control network architecture. As shown, the plant network **100** is segmented into multiple zones, such as a business network **102**, a supervisory network **104**, and a control network **106**. In the illustrated embodiment, the control network **106** provides real time control to devices or equipment that communicate on either a safety network **110** or a non-safety network (e.g., a field device network **112**). One or more firewalls **114** separate each zone of plant network **100**.

(6) The control network **106** carries process control device communications to a basic process control system (BPCS) **118**. In turn, the BPCS **118**, which is coupled to the field device network **112**, interacts with field devices and other I/O devices, their controllers, and the like.

(7) The safety network **110** includes at least one safety system **120**, such as a safety instrumented system (SIS). As described above, the safety system **120** is configured to drive the process to a safe condition when unsafe.

(8) Referring now to FIG. 2, safety system **120** is a key protection layer to prevent industrial accidents in a plant. The safety system **120** comprises at least one safety programmable logic controller (PLC) main processor module **202** and at least one safety PLC input/output (IO) module **204**. As shown, the main processor module **202** may be housed in a main chassis and the IO module **204** may be housed in a separate, remote IO chassis. In an embodiment, components of safety system **120** may be located in a control room or distributed across a plant. The safety PLC main processor module **202** and safety PLC IO module **204** in the embodiment of FIG. 2 are distributed remotely (e.g., up to 70 kilometers) from each other.

(9) End users (e.g., asset owners, plant maintenance personnel) often operate and maintain safety systems **120** for many years during the operation of an industrial plant. A plant's maintenance personnel typically perform daily health monitoring and reporting of the health status of the plant's safety systems **120**. In addition, when a component of safety system **120** fails, the plant operator must alert the plant's maintenance personnel to perform repairs. The maintenance personnel typically use a maintenance software to perform a primary maintenance function by determining

which component of safety system **120** has failed in order to perform online repair by replacing the failed component. In some instances, the plant maintenance personnel require support and must first collect information relating to the failure for providing to the safety system vendor.

(10) Aspects of the present disclosure provide efficient monitoring of safety systems **120** by making information available to a user **206** from any location via a dual interface layer comprised of an interface processing engine **210** and a diagnostic status aggregator **212**. As shown in FIG. 2, the user **206** uses a mobile device **214**, such as a smartphone, to request access to the desired information by speech or text. For example, user **206** simply asks the mobile device **214** via traditional means, chats, or natural voice (e.g., "What is the overall status of the safety systems?"). The mobile device **214** executes a mobile application **216** that provides a speech/text interface by which user **206** can request information regarding safety system **120**. The speech/text interface of the mobile application **216** sends queries from text or natural voice to the interface processing engine **210** based on voice commands from user **206**.

(11) Referring further to FIG. 2, the diagnostic status aggregator **212**, embodied by cloud data storage, for example, collects live status information indicating the health of safety system **120**. The collected status information is preferably coupled with system metadata (e.g., area, equipment, safety instrumented function (SIF), predefined room/site location, etc.). This represents a one-way collection of data from safety system **120**. The statuses of safety system **120** are shared using a unidirectional interface for information flow such that the remote access components do not directly interact with safety system **120**. Instead there is a dual layer for interaction. The interface processing engine **210** is configured to send requests to and receive responses from diagnostic status aggregator **212**.

(12) For security reasons, there is no direct or indirect interaction between user **206** or interface processing engine **210** and safety system **120**. Moreover, coupling metadata with the status information for safety system **120** provides a higher level of confidence that the interaction is safe and secure and an improved natural workflow and productivity.

(13) As shown in FIG. 3, mobile application **216** provides a speech-to-text interface by which user **206** can request information regarding safety system **120**. The mobile application **216** sends a query converted from natural voice to text to interface processing engine **210**. In an embodiment, interface processing engine **210** uses artificial intelligence or machine learning to determine what information is to be retrieved and in what context based on the text query. The interface processing engine **210** accesses a database of questions/intents related to safety systems **120** referenced to specific keywords and executes machine learning or artificial intelligence to train for a given set of system configurations for user **206** and to parse user requests and to recognize a set of questions/intents related to safety system **120** of interest using the specific keywords and their variations. For example, the trained interface processing engine **210** determines if the new request corresponds to or is related to a previous request related to the safety system **120** by comparing the new request to previous requests using specific keywords and their variants. As a result, interface processing engine **210** can accurately formulate the proper contextual query and determine the correct command from user **206**. In an alternative embodiment, interface processing engine **210** additionally requests confirmation of the determined command from user **206**. The interface processing engine **210** then communicates the command to diagnostic status aggregator **212** for retrieving the requested information. In an embodiment, mobile application **216** converts the retrieved status information from text to natural voice for user **206**.

(14) Referring again to FIG. 2, aspects of the present disclosure further provide enhanced interaction between user **206** and safety system **120** through remote maintenance capability, such as a handheld app, chat-bot, and voice-based interface with natural voice processing executed on mobile device **214**. For geo-location based requests, equipment can be identified externally by including a machine-readable code **220**, which can be read by mobile device **214**. FIG. 2 illustrates a unique, individual, scannable machine-readable code **220** applied or affixed to the main chassis of

safety PLC main processor module **202** and/or the IO chassis of safety PLC IO module **204**. The machine-readable code **220** may be one or more of: a QR (quick response) 2-dimensional bar code; a data matrix 2-dimensional bar code; an RFID tag or code; a unique pattern or graphic that can be uniquely identified (e.g., a picture of a person identifiable by facial recognition software); an infrared code; a linear bar code; and/or other scannable identification markings, either visible or not visible within the visible light spectrum. In this manner, the dual interface layer does not directly interact with safety system **120**, which ensures security and safety when processing information requests.

(15) The mobile device **214** executes mobile application to **216** scan machine-readable code **220** from the chassis of a selected safety PLC module **202**, **204** of interest. In an embodiment, the scanned code **220** identifies the location and/or context of the selected safety PLC module **202**, **204**. In another embodiment, in addition to or instead of code scanning, mobile device **214** executes mobile application **216** to provide a speech/text interface by which user **206** can request information regarding safety system **120**. As described above, the speech/text interface sends queries from text or natural voice to interface processing engine **210** based on voice commands from user **206**.

(16) The following are example use cases in which diagnostic status aggregator **212** continuously collects health and diagnostic status information from safety systems **120**. The natural voice questions used in the examples are illustrative and it is contemplated that end users **206** will ask variations of these questions or different questions using natural language.

(17) Use Case #1: Finding Overall Status of Safety Systems **120** from a Remote Location.

(18) The user **206** asks in natural voice, “What is the overall status?” The application **216** executed on mobile device **214** translates the natural voice question to text and sends the text query to interface processing engine **210** for processing. The interface processing engine **210** determines the best match to the query and sends a data request to diagnostic data aggregator **212** to retrieve the requested information. The diagnostic data aggregator **212** sends the requested data back to interface processing engine **210**. In turn, interface processing engine **210** assembles the response in a correct contextual format and sends it back to mobile device **214**, which executes mobile application **216** to convert the response to natural voice for user **206**. In an alternative embodiment, mobile device **214** displays the information from interface processing engine **210** in a text format. The dual interface layer for processing the request eliminates direct interactions between user **206** and safety system **120** thus ensuring security and safety. Moreover, contextual notifications to user **206** upon failure will improve productivity.

(19) Use Case #2: Finding Status of Specific Component of Safety System **120**.

(20) Using mobile device **214**, user **206** scans machine-readable code **220** on the outside of a selected one of the main chassis of safety PLC main processor module **202** and the IO chassis of safety PLC IO module **204** of interest to obtain identification information. The user **206** then asks using natural voice via application **216** executing on mobile device **214**, “What has failed?” The mobile application **216** translates the natural voice request to text and sends the text query to interface processing engine **210** along with the machine-readable identification obtained from the specific safety system **120**. The interface processing engine **210** determines the best match to the voice request and sends a data request to diagnostic data aggregator **212** for the status information corresponding to the identified system component. The diagnostic data aggregator **212** sends back the requested data to interface processing engine **210**, which assembles the response in a correct contextual format and sends the response to mobile device **214**. In turn, interface processing engine **210** assembles the response in a correct contextual format and sends it back to mobile device **214**, which executes mobile application **216** to convert the response to natural voice for user **206**. In an alternative embodiment, mobile device **214** displays the information from interface processing engine **210** in a text format.

(21) Use Case #3: Contacting Customer Support.

(22) At the end of use case #2, above, user **206** may decide to seek help from a third party (e.g., a supplier of the safety system **120**). The user **206** instructs in natural voice, "Contact customer support." The application **216** executed on mobile device **214** translates the natural voice instruction to text and sends the specific user request/message to customer support along with the machine-readable identification **220** to interface processing engine **210**. The interface processing engine **210** collects the relevant information from diagnostic data aggregator **212**, compiles the collected information with the user request/message, and sends the information and request to customer support by email. Advantageously, aspects of the present disclosure improve the efficiency of maintenance requests to supplier customer support by facilitating the contact along with relevant failure information from safety system **120**.

(23) Commonly assigned U.S. Pat. No. 9,582,376, the entire contents of which are incorporated herein by reference, discloses a fault tolerant controller allowing for the flexible communication between safety instrumented systems that implement the aforementioned "safe state." Networked control devices, e.g., in addition to actuators and sensors, include one or more controllers that monitor and control respective aspects of the process, as modified in accord with the teachings hereof. The controllers can comprise mainframe computers, workstations, personal computers, special-purpose hardware, or other digital data processing apparatus capable of performing monitoring and control functions. Controllers may be operated in a manner known in the art, as modified by the teachings hereof. Preferred controllers are constructed and operated in the manner of the control processors ("CP") commercially available from the assignee hereof, such as Triconex® (a/k/a "Tricon") and Trident™ controllers.

(24) Embodiments of the present disclosure may comprise a special purpose computer including a variety of computer hardware, as described in greater detail below.

(25) For purposes of illustration, programs and other executable program components may be shown as discrete blocks. It is recognized, however, that such programs and components reside at various times in different storage components of a computing device, and are executed by a data processor(s) of the device.

(26) Although described in connection with an exemplary computing system environment, embodiments of the aspects of the invention are operational with other special purpose computing system environments or configurations. The computing system environment is not intended to suggest any limitation as to the scope of use or functionality of any aspect of the invention. Moreover, the computing system environment should not be interpreted as having any dependency or requirement relating to any one or combination of components illustrated in the exemplary operating environment. Examples of computing systems, environments, and/or configurations that may be suitable for use with aspects of the invention include, but are not limited to, personal computers, server computers, handheld or laptop devices, multiprocessor systems, microprocessor-based systems, set top boxes, programmable consumer electronics, mobile telephones, network PCs, minicomputers, mainframe computers, distributed computing environments that include any of the above systems or devices, and the like.

(27) Embodiments of the aspects of the invention may be described in the general context of data and/or processor-executable instructions, such as program modules, stored on one or more tangible, non-transitory storage media and executed by one or more processors or other devices. Generally, program modules include, but are not limited to, routines, programs, objects, components, and data structures that perform particular tasks or implement particular abstract data types. Aspects of the invention may also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules may be located in both local and remote storage media including memory storage devices.

(28) In operation, processors, computers and/or servers may execute the processor-executable instructions (e.g., software, firmware, and/or hardware) such as those illustrated herein to

implement aspects of the invention.

(29) Embodiments of the aspects of the invention may be implemented with processor-executable instructions. The processor-executable instructions may be organized into one or more processor-executable components or modules on a tangible processor readable storage medium. Aspects of the invention may be implemented with any number and organization of such components or modules. For example, aspects of the invention are not limited to the specific processor-executable instructions or the specific components or modules illustrated in the figures and described herein. Other embodiments of the aspects of the invention may include different processor-executable instructions or components having more or less functionality than illustrated and described herein.

(30) The order of execution or performance of the operations in embodiments of the aspects of the invention illustrated and described herein is not essential, unless otherwise specified. That is, the operations may be performed in any order, unless otherwise specified, and embodiments of the aspects of the invention may include additional or fewer operations than those disclosed herein. For example, it is contemplated that executing or performing a particular operation before, contemporaneously with, or after another operation is within the scope of aspects of the invention.

(31) When introducing elements of aspects of the invention or the embodiments thereof, the articles “a,” “an,” “the,” and “said” are intended to mean that there are one or more of the elements. The terms “comprising,” “including,” and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements.

(32) Not all of the depicted components illustrated or described may be required. In addition, some implementations and embodiments may include additional components. Variations in the arrangement and type of the components may be made without departing from the spirit or scope of the claims as set forth herein. Additional, different or fewer components may be provided and components may be combined. Alternatively or in addition, a component may be implemented by several components.

(33) The above description illustrates the aspects of the invention by way of example and not by way of limitation. This description enables one skilled in the art to make and use the aspects of the invention, and describes several embodiments, adaptations, variations, alternatives and uses of the aspects of the invention, including what is presently believed to be the best mode of carrying out the aspects of the invention. Additionally, it is to be understood that the aspects of the invention is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the drawings. The aspects of the invention are capable of other embodiments and of being practiced or carried out in various ways. Also, it will be understood that the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting.

(34) Having described aspects of the invention in detail, it will be apparent that modifications and variations are possible without departing from the scope of aspects of the invention as defined in the appended claims. It is contemplated that various changes could be made in the above constructions, products, and process without departing from the scope of aspects of the invention. In the preceding specification, various preferred embodiments have been described with reference to the accompanying drawings. It will, however, be evident that various modifications and changes may be made thereto, and additional embodiments may be implemented, without departing from the broader scope of the aspects of the invention as set forth in the claims that follow. The specification and drawings are accordingly to be regarded in an illustrative rather than restrictive sense.

(35) In view of the above, it will be seen that several advantages of the aspects of the invention are achieved and other advantageous results attained.

(36) The Abstract and Summary are provided to help the reader quickly ascertain the nature of the technical disclosure. They are submitted with the understanding that they will not be used to interpret or limit the scope or meaning of the claims. The Summary is provided to introduce a

selection of concepts in simplified form that are further described in the Detailed Description. The Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the claimed subject matter.

Claims

1. A method for interfacing with at least one safety instrumented system (SIS) in an industrial plant, the industrial plant comprising a plurality of equipment configured for communicating with the SIS, the method comprising: establishing a unidirectional connection from the SIS to a diagnostic status aggregator, the SIS configured for supplying at least one of health and diagnostic status data to the diagnostic status aggregator via the unidirectional connection, the diagnostic status aggregator storing the status data supplied by the SIS; communicatively coupling an interface processing engine to the diagnostic status aggregator, the interface processing engine configured for communicating with a remote user device configured to be located at a plurality of remote locations associated with the plurality of equipment of the industrial plant, the interface processing engine and the diagnostic status aggregator comprising a dual interface layer, wherein the unidirectional connection from the SIS to the diagnostic status aggregator of the dual interface layer prevents the user device from directly interacting with the SIS; receiving, via a mobile application of the user device, a new request for information relating to the SIS, wherein the user device is configured for generating the new request from the plurality of remote locations; receiving, by the interface processing engine, the new request from the user device, the user device communicatively coupled to the interface processing engine; executing at least one of an artificial intelligence system and a machine learning algorithm to train the interface processing engine to recognize one or more specific keywords associated with the requested information relating to the SIS; parsing, by the interface processing engine, the new request to identify one or more specific keywords therein associated with the requested information relating to the SIS, wherein identification of the one or more specific keywords is performed by the interface processing engine trained by the at least one of an artificial intelligence system and a machine learning algorithm; generating, by the interface processing engine, a query based on the identified keywords; retrieving, by the interface processing engine from the diagnostic status aggregator, the status data supplied by the SIS to the diagnostic aggregator responsive to the query; and providing, by the interface processing engine, the status data retrieved from the diagnostic status aggregator to the user device.

2. The method of claim 1, wherein the diagnostic status aggregator is configured to continuously collect the health and diagnostic status data from the SIS.

3. The method of claim 1, wherein parsing the new request comprises determining if the new request corresponds to one or more previous requests related to the SIS by comparing the new request to the one or more previous requests using the specific keywords and variants thereof.

4. The method of claim 3, wherein retrieving the status data the SIS comprises retrieving, in response to determining the new request corresponds to the one or more previous requests, the status data based, at least in part, on information learned from the one or more previous requests.

5. The method of claim 4, further comprising: in response to determining the new request does not correspond to the one or more previous requests, retrieving, by the interface processing engine from the diagnostic status aggregator, the status data supplied by the SIS responsive to the query; and using information relating to the new request and the status data retrieved from the diagnostic status aggregator to train the interface processing engine.

6. The method of claim 3, wherein determining if the new request corresponds to the one or more previous requests comprises training the interface processing engine.

7. The method of claim 1, wherein receiving the new request from the user device comprises executing a speech-to-text application to convert the new request in natural speech to a text-based

request.

8. The method of claim 1, wherein the status data is stored by the diagnostic status aggregator in connection with metadata relating to the SIS from which the status data is collected.

9. The method of claim 8, wherein the metadata comprises at least one of the following: a location of the SIS; an identifier of the SIS; and a safety instrumented function (SIF) associated with the SIS.

10. The method of claim 1, further comprising: receiving, from the mobile application of the user device by the interface processing engine, an identifier associated with the SIS, the identifier obtained by the user device by scanning a machine-readable code associated with the SIS.

11. A system comprising: at least one safety instrumented system (SIS) in an industrial plant, the industrial plant comprising a plurality of equipment configured for communicating with the SIS; a diagnostic status aggregator communicatively coupled to the SIS via a unidirectional connection established from the SIS to the diagnostic status aggregator, the diagnostic status aggregator configured to collect at least one of health and diagnostic status data from the SIS and to store the collected status data, wherein the SIS has the unidirectional established connection to the diagnostic status aggregator for supplying the status data thereto; a mobile application running on a remote user device, the remote user device configured to be located at a plurality of remote locations associated with the plurality of equipment of the industrial plant, the mobile application configured to generate a new request for information relating to the SIS from the plurality of remote locations; an interface processing engine communicatively coupled to the diagnostic status aggregator and to the remote user device, the interface processing engine configured to receive the new request from the user device, the interface processing engine and the diagnostic status aggregator comprising a dual interface layer, wherein the unidirectional connection from the SIS to the diagnostic status aggregator of the dual interface layer prevents the user device from directly interacting with the SIS; and a memory storage device storing processor-executable instructions that, when executed, further configure the interface processing engine for: executing at least one of an artificial intelligence system and a machine learning algorithm to train the interface processing engine to recognize one or more specific keywords associated with the requested information relating to the SIS; parsing the new request to identify the one or more specific keywords therein associated with the requested information relating to the SIS, wherein identification of the one or more specific keywords is performed by the interface processing engine trained by the at least one an artificial intelligence system and a machine learning algorithm; generating a query based on the identified keywords; retrieving, from the diagnostic status aggregator, the status data supplied by the SIS to the diagnostic aggregator responsive to the query; and providing, the status data retrieved from the diagnostic status aggregator to the user device.

12. The system of claim 11, wherein the diagnostic status aggregator is configured to continuously collect the health and diagnostic status data from the SIS.

13. The system of claim 11, wherein parsing the new request comprises determining if the new request corresponds to one or more previous requests related to the SIS by comparing the new request to the one or more previous requests using the specific keywords and variants thereof.

14. The system of claim 13, wherein retrieving the status data supplied by the SIS comprises retrieving, in response to determining the new request corresponds to the one or more previous requests, the status data based, at least in part, on information learned from the one or more previous requests.

15. The system of claim 14, wherein the memory storage device stores processor-executable instructions that, when executed, further configure the interface processing engine for: in response to determining the new request does not correspond to the one or more previous requests, retrieving, by the interface processing engine from the diagnostic status aggregator, the status data supplied by the SIS responsive to the query; and using information relating to the new request and the status data retrieved from the diagnostic status aggregator to train the interface processing

engine.

16. The system of claim 13, wherein determining if the new request corresponds to the one or more previous requests comprises training the interface processing engine.

17. The system of claim 11, wherein user devices is configured to execute a speech-to-text application to convert the new request in natural speech to a text-based request and wherein new request received by the interface processing engine is the text-based request.

18. The system of claim 11, wherein the status data is stored by the diagnostic status aggregator in connection with metadata relating to the SIS from which the status data is collected.

19. The system of claim 18, wherein the metadata comprises at least one of the following: a location of the SIS; an identifier of the SIS; and a safety instrumented function (SIF) associated with the SIS.

20. The system of claim 11, further comprising a machine-readable code associated with the SIS, wherein the interface processing engine is configured to receive, from the mobile application of the user device, an identifier associated with the SIS obtained by the user device by scanning the machine-readable code.
