

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12407269
B2
September 02, 2025
Kusukawa; Junpei et al.

Semiconductor device, busbar, and power converter

Abstract

Provided are a semiconductor device, a busbar, and a power converter that can suppress an increase in the size of the device and in inductance while ensuring insulation performance between terminals. For example, a semiconductor device **1** includes a first terminal **110** projecting from a sealing body **100** along a given direction, and a second terminal **120** adjacent to the first terminal **110** with a space formed between the second terminal **120** and the first terminal **110**, the second terminal **120** projecting from the sealing body **100** along a given direction in a direction of projection that is the same as a direction of projection of the first terminal **110**. The first terminal **110** has a first exposed part **112** exposed outside the sealing body **100**. The second terminal **120** has a second sheathed part **121** projecting from the sealing body **100**, the second sheathed part **121** being sheathed with an insulating material, and a second exposed part **122** projecting from the second sheathed part **121**, the second exposed part **122** being exposed outside the sealing body **100**. A distance D2 along a given direction from a front end **121a** of the second sheathed part **121** to the sealing body **100** is longer than a distance D1 along the given direction from a front end **112a** of the first exposed part **112** to the sealing body **100**.

Inventors:	Kusukawa; Junpei (Tokyo, JP), Mochizuki; Masahito (Tokyo, JP), Ide; Eiichi (Tokyo, JP)
Applicant:	Hitachi Astemo, Ltd. (Hitachinaka, JP)
Family ID:	78510384
Assignee:	Hitachi Astemo, Ltd. (Hitachinaka, JP)
Appl. No.:	17/924569
Filed (or PCT Filed):	January 22, 2021
PCT No.:	PCT/JP2021/002145
PCT Pub. No.:	WO2021/229859
PCT Pub. Date:	November 18, 2021

Prior Publication Data

Document Identifier

US 20230231487 A1

Publication Date

Jul. 20, 2023

Foreign Application Priority Data

JP

2020-084711

May. 13, 2020

Publication Classification

Int. Cl.: H02M7/00 (20060101); H01L23/00 (20060101); H01L23/049 (20060101); H01L25/07 (20060101)

U.S. Cl.:

CPC H02M7/003 (20130101); H01L23/049 (20130101); H01L24/48 (20130101); H01L25/072 (20130101); H01L2224/48137 (20130101); H01L2924/13055 (20130101); H01L2924/30107 (20130101)

Field of Classification Search

CPC: H02M (7/003); H01L (23/049); H01L (24/48); H01L (25/072); H01L (2224/48137); H01L (2924/13055); H01L (2924/30107)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5386342	12/1994	Rostoker	257/668	H01L 23/564
6560115	12/2002	Wakabayashi	361/728	H05K 5/0065
11029722	12/2020	Lee	N/A	G06F 1/183
2002/0109237	12/2001	Oka	257/777	H01L 24/86
2002/0190374	12/2001	Nakajima	257/713	H01L 21/565
2004/0099933	12/2003	Kimura	257/676	H01L 23/4334
2007/0252169	12/2006	Tokuyama et al.	N/A	N/A
2008/0017882	12/2007	Nakanishi	257/E25.031	H01L 24/40
2008/0174458	12/2007	Mundt	361/679.08	G06F 1/1616
2009/0302722	12/2008	Mihara	361/679.08	G06F 1/1656
2010/0149741	12/2009	Liu	361/679.08	G06F 1/1613
2013/0105961	12/2012	Jones et al.	N/A	N/A
2013/0277087	12/2012	Hayakawa	174/107	H01B 3/30
2014/0167241	12/2013	Matsuoka	257/690	H01L 23/24
2015/0221621	12/2014	Mochida	N/A	N/A
2016/0176369	12/2015	Ito	174/72A	H01B 9/006
2017/0040241	12/2016	Yoshida	N/A	H01L 23/473

2019/0096784	12/2018	Katayama	N/A	H01L 23/3737
2020/0124352	12/2019	Wakaoka	N/A	F28D 15/0233
2020/0176435	12/2019	Fukushima et al.	N/A	N/A
2020/0262364	12/2019	Eshima	N/A	H02G 3/0406
2021/0391236	12/2020	Tsuyuno	N/A	H01L 23/49531
2022/0082421	12/2021	Ogata	N/A	G01F 15/14
2022/0165712	12/2021	Matsuoka	N/A	H01L 23/49562

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2007-299781	12/2006	JP	N/A
2015-149363	12/2014	JP	N/A
2016-134492	12/2015	JP	N/A
2019-037048	12/2018	JP	N/A

OTHER PUBLICATIONS

International Search Report with English Translation and Written Opinion dated May 25, 2021 in corresponding International Application No. PCT/JP2021/002145. cited by applicant

Primary Examiner: Hayman; Imani N

Assistant Examiner: Morrison; Rashon E

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a semiconductor device, busbar, and a power converter.

BACKGROUND ART

(2) As a technique for ensuring insulation performance between terminals projecting from a resin package in which a semiconductor element is sealed, for example, a technique described in Patent Literature 1 is known.

(3) Patent Literature 1 describes a semiconductor device including a sealing part that seals a first lead terminal and a second lead terminal adjacent to each other, and a lead sheathed part with an insulation property that extends from an end of the sealing part and that sheathes an outer lead of the second lead terminal in such a way as to leave the front end of the outer lead exposed.

CITATION LIST

Patent Literature

(4) PTL 1: Japanese Patent No. 6345608

SUMMARY OF INVENTION

Technical Problem

(5) In the semiconductor device described in PTL 1, a creepage distance between the first lead terminal and the second lead terminal is secured by providing the second lead terminal with the lead sheathed part. In the semiconductor device described in Patent Literature 1, however, a space

distance between the first lead terminal and the second lead terminal is secured by merely increasing a space between the first lead terminal and the second lead terminal. Increasing the space between the first lead terminal and the second lead terminal leads to an increase in the size of the device and in inductance. Such a problem may arise also in a busbar having terminals connected to terminals of the semiconductor device or a power converter in which the terminals of the semiconductor device are connected to the terminals of the busbar to make up a main circuit. (6) The present invention has been conceived in view of the above problem, and it is therefore an object of the invention to provide a semiconductor device, a busbar, and a power converter that can suppress an increase in the size of a device and in inductance while ensuring insulation performance between terminals.

Solution to Problem

(7) In order to solve the above problem, a semiconductor device according to the present invention includes: a sealing body in which a semiconductor element is resin-sealed; a first terminal connected to the semiconductor element, the first terminal projecting from the sealing body along a given direction; and a second terminal connected to the semiconductor element, the second terminal being adjacent to the first terminal with a space formed between the second terminal and the first terminal and projecting from the sealing body along the given direction in a direction of projection that is the same as a direction of projection of the first terminal. The first terminal has a first exposed part that extends in the given direction and that is exposed outside the sealing body. The second terminal has a sheathed part projecting from the sealing body, the sheathed part extending in the given direction and being sheathed with an insulating material, and a second exposed part projecting from the sheathed part, the second exposed part extending in the given direction and being exposed outside the sealing body. A distance along the given direction from a front end of the sheathed part to the sealing body is longer than a distance along the given direction from a front end of the first exposed part to the sealing body.

Advantageous Effects of Invention

(8) According to the present invention, an increase in the size of a device and in inductance can be suppressed as insulation performance between terminals is ensured.

(9) Problems, configurations, and effects other than those described above will be made clear by the following description of embodiments.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is an external view of a semiconductor device according to a first embodiment.

(2) FIG. 2 is a cross-sectional view of the semiconductor device, the cross-sectional view being taken along a line A-A shown in FIG. 1.

(3) FIG. 3 depicts a comparative example of the semiconductor device shown in FIG. 1.

(4) FIG. 4 is an external view of a busbar according to the first embodiment.

(5) FIG. 5 is a cross-sectional view of the busbar, the cross-sectional view being taken along a line B-B shown in FIG. 4.

(6) FIG. 6 depicts a comparative example of the busbar shown in FIG. 4.

(7) FIG. 7 is an external view of a power converter according to the first embodiment.

(8) FIG. 8 depicts a comparative example of the power converter shown in FIG. 7.

(9) FIG. 9 is an external view of a semiconductor device according to a second embodiment.

(10) FIG. 10 is a cross-sectional view of the semiconductor device, the cross-sectional view being taken along a line C-C shown in FIG. 9.

(11) FIG. 11 is a top view of a busbar according to the second embodiment.

(12) FIG. 12 is a side view of the busbar, the side view being given when the busbar is seen in the

direction of an arrow E shown in FIG. 11.

(13) FIG. 13 is a cross-sectional view of the busbar, the cross-sectional view being taken along a line F-F shown in FIG. 11.

(14) FIG. 14 is a cross-sectional view of a power converter according to the second embodiment.

DESCRIPTION OF EMBODIMENTS

(15) Embodiments of the present invention will hereinafter be described with reference to the drawings. In each embodiment, constituent elements denoted by the same reference signs have the same functions unless otherwise specified, and therefore redundant description of such constituent elements is omitted. In addition, in drawings necessary for reference, orthogonal coordinate axes, i.e., an x-axis, a y-axis, and a z-axis are shown to make description of the positions of individual parts clear.

First Embodiment

(16) FIG. 1 is an external view of a semiconductor device 1 according to a first embodiment. FIG. 2 is a cross-sectional view of the semiconductor device 1, the cross-sectional view being taken along a line A-A shown in FIG. 1. FIG. 3 depicts a comparative example of the semiconductor device 1 shown in FIG. 1.

(17) The semiconductor device 1 is a power semiconductor module used in a power converter 3, such as an inverter. The semiconductor device 1 is a power semiconductor module widely used in fields of consumer goods, in-vehicle equipment, railway equipment, industrial products, and infrastructure constructions. The semiconductor device 1 shown in FIG. 1 is, for example, a power semiconductor module incorporated in power-operated vehicles, such as hybrid vehicles, electric vehicles, and fuel cell vehicles. The semiconductor device 1 converts an input DC voltage from a battery, into a pseudo AC voltage by switching operations of a semiconductor element, and outputs the AC voltage. To the semiconductor device 1, a busbar 2 shown in FIG. 4, which will be described later, is connected (see FIG. 7). The semiconductor device 1 and the busbar 2, plus a capacitor module (not illustrated), make up a main circuit of the power converter 3.

(18) As shown in FIG. 1, the semiconductor device 1 includes a sealing body 100, first terminals 110, second terminals 120, an output terminal 130, and control terminals 140.

(19) The sealing body 100 is a structure in which components of the semiconductor device 1, such as a first semiconductor element 151, are resin-sealed. The sealing body 100 is a structure in which the components of the semiconductor device 1 are sealed by transfer molding or the like, using a resin material 101, such as epoxy resin. The sealing body 100 is formed into a rectangular plate shape having a given plate thickness. The sealing body 100 makes up a resin package of the semiconductor device 1.

(20) As shown in FIG. 2, the sealing body 100 includes first semiconductor element 151, a second semiconductor element 152, a first circuit conductor 154, a second circuit conductor 155, a first insulating layer 156, a second insulating layer 157, a first heat-dissipating conductor 158, and second heat-dissipating conductor 159.

(21) The first semiconductor element 151 is composed of a power semiconductor element, such as an insulated gate bipolar transistor (IGBT) or an injection enhanced gate transistor (IEGT). The second semiconductor element 152 is composed of a diode, such as a free wheeling diode (FWD). The semiconductor device 1 shown in FIG. 1 includes the first semiconductor element 151 and the second semiconductor element 152 that make up an upper arm circuit, and the first semiconductor element 151 and the second semiconductor element 152 that make up a lower arm circuit. The semiconductor device 1 shown in FIG. 1 is a 2-in-1 power module.

(22) Each of the first semiconductor element 151 and the second semiconductor element 152 is of a rectangular chip shape. The first semiconductor element 151 has a pair of main surfaces 151a and 151b each having a large area and serving as an electrode surface. The second semiconductor element 152 has a pair of main surfaces 152a and 152b each having a large area and an electrode surface. One main surface 151a of the first semiconductor element 151 and one main surface 152a

of the second semiconductor element **152** are bonded to the first circuit conductor **154** via a bonding material **153**, such as solder. The other main surface **151b** of the first semiconductor element **151** and the other main surface **152b** of the second semiconductor element **152** are bonded to the second circuit conductor **155** via a bonding material **153**.

(23) The first circuit conductor **154** and the second circuit conductor **155** are made of a metal material with excellent electric conductivity and thermal conductivity, such as copper or aluminum, and are each formed into a plate shape. The first circuit conductor **154** and the second circuit conductor **155** each have a pattern of an electric circuit formed thereon by etching or the like. The first circuit conductor **154** and the second circuit conductor **155** are bonded to the first terminal **110**, the second terminal **120**, the output terminal **130**, and the control terminal **140** via the bonding material **153**. The first circuit conductor **154** is connected to a control electrode, which is formed on the other main surface **151b** of the first semiconductor element **151**, through a wire **160**. The first circuit conductor **154** has a surface bonded to the first insulating layer **156**, the surface being opposite to the other surface of first circuit conductor **154** that is bonded to the first semiconductor element **151** and the second semiconductor element **152**. The second circuit conductor **155** has a surface bonded to the second insulating layer **157**, the surface being opposite to the other surface of second circuit conductor **155** that is bonded to the first semiconductor element **151** and the second semiconductor element **152**.

(24) The first insulating layer **156** and the second insulating layer **157** are made of a ceramic material with excellent insulation, thermal conductivity, and toughness, such as silicon nitride or aluminum nitride, and are each formed into a plate shape. The first insulating layer **156** has a surface bonded to the first heat-dissipating conductor **158**, the surface being opposite to the other surface of first insulating layer **156** that is bonded to the first circuit conductor **154**. The second insulating layer **157** has a surface bonded to the second heat-dissipating conductor **159**, the surface being opposite to the other surface of second insulating layer **157** that is bonded to the second circuit conductor **155**.

(25) The first heat-dissipating conductor **158** and the second heat-dissipating conductor **159** are made of a metal material with excellent thermal conductivity and strength, such as copper or aluminum, and are each formed into a plate shape. The first heat-dissipating conductor **158** is molded such that a surface **158a** opposite to a surface bonded to the first insulating layer **156** is exposed from the resin material **101**. The second heat-dissipation conductor **159** is molded such that a surface **159a** opposite to a surface bonded to the second insulating layer **157** is exposed from the resin material **101**. The surface **158a** and the surface **159a** are set parallel to each other. The surface **158a** and the surface **159a** make up most of a main surface **100a** of the sealing body **100**.

(26) The first heat-dissipating conductor **158**, the first insulating layer **156**, and the first circuit conductor **154** may be configured as an insulating circuit board by bonded them together in advance by diffusion bonding or the like. The second heat-dissipating conductor **159**, the second insulating layer **157**, and the second circuit conductor **155** may be configured as an insulating circuit board by bonded them together in advance by diffusion bonding or the like.

(27) Each of the first terminal **110** and the second terminal **120** is made of a metal material with excellent electric conductivity, such as copper or aluminum, and is formed into a flat rod shape. Each of the first terminal **110** and the second terminal **120** is connected to the first semiconductor element **151** and the second semiconductor element **152**, via the first circuit conductor **154**, the second circuit conductor **155**, and the bonding material **153**. Each of the first terminal **110** and the second terminal **120** may be any one of a DC positive terminal, a DC negative terminal, an AC output terminal, or a control terminal. This embodiment will be explained on the assumption that the first terminal **110** is a DC negative terminal, the second terminal **120** is a DC positive terminal, the output terminal **130** is an AC output terminal, and the control terminal **140** is a control terminal.

(28) The first terminal **110** projects from the sealing body **100** along a given direction. The first terminal **110** projects from a side surface **100b** perpendicular to a shortish side of the sealing body

100, along a main surface **100a** of the sealing body **100**. In the example of FIG. **1**, a direction in which the first terminal **110** projects is a +x-axis direction. The first terminal **110** has a first sheathed part **111** projecting from the sealing body **100**, the first sheathed part **111** extending in the given direction and being sheathed with an insulating material, and a first exposed part **112** projecting from the first sheathed part **111**, the first exposed part **112** extending in the given direction and being exposed outside the sealing body **100**. The insulating material forming the first sheathed part **111** may be the same material as the resin material **101**, or may be a resin material different from the resin material **101**. A base end of the first sheathed part **111** is equivalent to a base end of the first terminal **110**, and is connected to the sealing body **100**. A front end **111a** of the first sheathed part **111** is connected to a base end of the first exposed part **112**. A front end **112a** of the first exposed part **112** is equivalent to a front end of the first terminal **110**.

(29) The second terminal **120** projects from the sealing body **100** along the given direction toward the same side to which the first terminal **110** projects. The second terminal **120** is adjacent to the first terminal **110** with a space formed between the second terminal **120** and the first terminal **110**.

(30) A direction along the space between the first terminal **110** and the second terminal **120** is a direction perpendicular to the given direction in which the first terminal **110** and the second terminal **120** project, and is a direction perpendicular to a direction along the main surface **100a** of the sealing body **100**. In the example of FIG. **1**, the direction along the space between the first terminal **110** and the second terminal **120** is a y-axis direction. The second terminal **120** has a second sheathed part **121** projecting from the sealing body **100**, the second sheathed part **121** extending in the given direction and being sheathed with an insulating material, and a second exposed part **122** projecting from the second sheathed part **121**, the second exposed part **122** extending in the given direction and being exposed outside the sealing body **100**.

(31) The insulating material forming the second sheathed part **121** may be the same material as the resin material **101**, or may be a resin material different from the resin material **101**. A base end of the second sheathed part **121** is equivalent to a base end of the second terminal **120**, and is connected to the sealing body **100**. A front end **121a** of the second sheathed part **121** is connected to a base end of the second exposed part **122**. A front end **122a** of the second exposed part **122** is equivalent to a front end of the second terminal **120**. The second sheathed part **121** is an example of a “sheathed part” described in the claims.

(32) In the semiconductor device **1**, the first terminals **110** and the second terminals **120** are arranged alternately from one end to the other end of the direction along the space between the first terminal **110** and the second terminal **120**. In the example of FIG. **1**, two sets of the first terminals **110** and the second terminals **120** are arranged alternately along a -y axis direction. Specifically, in the example of FIG. **1**, the first terminal **110** of the first set, the second terminal **120** of the first set, the first terminal **110** of the second set, and the second terminal **120** of the second set are arranged in this order along the -y axis direction.

(33) The output terminal **130** projects from a side surface **100b** opposite to the side surface **100b** of sealing body **100** that is provided with the first terminal **110** and the second terminal **120**, along the main surface **100a** of the sealing body **100** in the direction of projection that is opposite to the direction of projection of the first terminal **110** and the second terminal **120**. The output terminal **130** has a third sheathed part **131** projecting from the sealing body **100**, the third sheathed part **131** extending in the given direction and being sheathed with an insulating material, and a third exposed part **132** projecting from the third sheathed part **131**, the third exposed part **132** extending in the given direction and being exposed outside the sealing body **100**. The insulating material forming the third sheathed part **131** may be the same material as the resin material **101**, or may be a resin material different from the resin material **101**.

(34) The control terminal **140** is disposed on the side surface **100b** of sealing body **100** that is provided with the first terminal **110** and the second terminal **120** and on the side surface **100b** of sealing body **100** that is provided with the output terminal **130**. Specifically, one control terminal

140 projects from the side surface **100b** of sealing body **100** that is provided with the first terminal **110** and the second terminal **120**, along the main surface **100a** of the sealing body **100** in the direction of projection that is the same as the direction of projection of the first terminal **110** and the second terminal **120**. The one control terminal **140** is adjacent to the second terminal **120** with a space formed between the one control terminal **140** and the second terminal **120**. The length of projection of the one control terminal **140** from the sealing body **100** is shorter than the length of projection of the second sheathed part **121** of the second terminal **120** from the sealing body **100**. The other control terminal **140** projects from the side surface **100b** of sealing body **100** that is provided with the output terminal **130**, along the main surface **100a** of the sealing body **100** in the direction of projection that is opposite to the direction of projection of the first terminal **110** and the second terminal **120**. The other control terminal **140** is adjacent to the output terminal **130** with a space formed between the other control terminal **140** and the output terminal **130**.

(35) It is required, by the way, that the power converter **3** including the semiconductor device **1** and the busbar **2** increase power it can be handle. One conceivable method of increasing power that the power converter **3** can handle is to increase current flowing through the power converter **3**. Increasing current, however, increases an amount of heat generated by the power converter **3**. To reduce the amount of heat generated by the power converter **3**, a conductor volume in a current path may be increased. In such a case, however, the weight and volume of the power converter **3** increase, which is a problem. In particular, in a case where the power converter **3** is used in an electric vehicle, an increase in the weight and volume of the power converter **3** results in a drop in the traveling performance and electric consumption performance of the vehicle. As a method of increasing power that the power converter **3** can handle, increasing a voltage the power converter **3** can handle is found effective. For example, the power converter **3** incorporated in hybrid vehicles or electric vehicles currently in popular use can handle voltages ranging roughly from 200 V to 400 V. In near future, the power converter **3** is expected to become capable of handling voltages in a higher range of 600 V to 800 V. The power converter **3** capable of handling higher voltages allows handling of larger power without increasing the conductor volume, and is therefore an effective approach. This offers an additional advantage in reducing a time required for charging the battery of an electric vehicle. If a voltage that can be handled in ordinary quick charging facilities, which is currently 400 V, is increased to 800 V, a charging time would be the half of a charging time in the case of charging with 400 V, proving that a charge volume is the same.

(36) As described above, increasing voltage the power converter **3** handles is effective as a method of increasing power the power converter **3** handle. In this case, however, the power converter **3** needs to ensure its insulation performance that can deal with handling of higher voltage. One method of allowing the power converter **3** to ensure its insulation performance that can deal with handling of higher voltage is to secure an insulation distance. Such equipment as the semiconductor device **1**, the busbar **2**, and the power converter **3** need to meet requirements for a space distance P and a creepage distance Q that are defined by International Standard IEC 60664-1 (JIS C 60664-1 in Japanese Industrial Standards), as an insulation distance equipment needs. This standard defines the necessary space distance P and creepage distance Q, according to a voltage the semiconductor device **1** or the like handles or an environment (contamination level, etc.) under which the semiconductor device **1** or the like is used. The space distance P refers to a minimum distance in a space between two conductive parts. The creepage distance Q refers to a minimum distance along the surface of an insulating material between two conductive parts. As the space distance P and the creepage distance Q increase, an electrical short circuit (dielectric breakdown) between the two conductive parts is less likely to occur. As a result, ensuring the insulation performance of the equipment becomes easier and therefore ensuring the reliability of the equipment becomes easier as well.

(37) Now, as shown in FIGS. **1** and **3**, a distance along the given direction from the front end **112a** of the first exposed part **112** of the first terminal **110** to the sealing body **100** is defined as a

distance D1. A distance along the given direction from the front end **121a** of the second sheathed part **121** of the second terminal **120** to the sealing body **100** is defined as a distance D2. A distance along the given direction from the front end **122a** of the second exposed part **122** of the second terminal **120** to the sealing body **100** is defined as a distance D3. In the examples of FIGS. **1** and **3**, the distance D1 is equivalent to the length of projection of the first terminal **110** from the sealing body **100**. The distance D2 is equivalent to the length of projection of the second sheathed part **121** of the second terminal **120** from the sealing body **100**. The distance D3 is equivalent to the length of projection of the second terminal **120** from the sealing body **100**.

(38) In the comparative example shown in FIG. **3**, the length of projection of the second terminal **120** from the sealing body **100** is equal to the length of projection of the first terminal **110** from the sealing body **100**. In addition, the length of projection of the second sheathed part **121** of the second terminal **120** from the sealing body **100** is equal to the length of projection of the first sheathed part **111** of the first terminal **110** from the sealing body **100**. As a matter of course, the length of projection of the second exposed part **122** of the second terminal **120** from the sealing body **100** is equal to the length of projection of the first exposed part **112** of the first terminal **110** from the sealing body **100**. In other words, in the comparative example shown in FIG. **3**, the distance D3 and the distance D1 are equal, and the distance D2 is shorter than the distance D1.

(39) In the comparative example shown in FIG. **3**, the space distance P between the first terminal **110** and the second terminal **120** is the distance between the first exposed part **112** of the first terminal **110** and the second exposed part **122** of the second terminal **120**. The creepage distance Q between the first terminal **110** and the second terminal **120** is the distance to travel through a path starting from the front end **111a** of the first sheathed part **111** and extending along respective surfaces of the base end of the first sheathed part **111**, the sealing body **100**, and the base end of the second sheathed part **121** to reach the front end **121a** of the second sheathed part **121**. In the comparative example shown in FIG. **3**, a direction in which the space distance P between the first terminal **110** and the second terminal **120** extends is parallel to a direction along the space between the first terminal **110** and the second terminal **120** (y-axis direction). In the creepage distance Q between the first terminal **110** and the second terminal **120**, a part of creepage distance Q that extends along the surface of the second sheathed part **121** of the second terminal **120** and a part of creepage distance Q that extends along the surface of the first sheathed part **111** of the first terminal **110** may match in length.

(40) In contrast, in the semiconductor device **1** shown in FIG. **1**, the distance D2 is made longer than the distance D1. In other words, according to the semiconductor device **1** shown in FIG. **1**, in the direction along the space between the first terminal **110** and the second terminal **120**, the second sheathed part **121** is disposed on the second terminal **120** adjacent to the first exposed part **112** of the first terminal **110**. In the semiconductor device **1** shown in FIG. **1**, the distance D3 is made longer than the distance D1 so that the distance D2 is longer than the distance D1. Specifically, in the semiconductor device **1** shown in FIG. **1**, the length of projection of the second sheathed part **121** of the second terminal **120** from the sealing body **100** is longer than the length of projection of the first exposed part **112** of the first terminal **110** from the sealing body **100**. As a matter of course, the length of projection of the second terminal **120** from the sealing body **100** is longer than the length of projection of the first terminal **110** from the sealing body **100**.

(41) In the semiconductor device **1** shown in FIG. **1**, the space distance P between the first terminal **110** and the second terminal **120** is the distance between the front end **112a** of the first exposed part **112** of the first terminal **110** and the base end of the second exposed part **122**, which is connected to the front end **121a** of the second sheathed part **121** of the second terminal **120**. The creepage distance Q between the first terminal **110** and the second terminal **120** is the distance to travel through a path starting from the front end **111a** of the first sheathed part **111** of the first terminal **110** and extending along respective surfaces of the base end of the first sheathed part **111**, the sealing body **100**, and the base end of the second sheathed part **121** of the second terminal **120** to

reach the front end **121a** of the second sheathed part **121**. In the semiconductor device **1** shown in FIG. **1**, because the distance **D2** is longer than the distance **D1**, the direction of the space distance **P** may be tilted against the direction along the space between the first terminal **110** and the second terminal **120** (y-axis direction). In the semiconductor device **1** shown in FIG. **1**, therefore, even if the space between the first terminal **110** and the second terminal **120** is shorter than the space between the same in the comparative example shown in FIG. **3**, the necessary space distance **P** can be secured. In the semiconductor device **1** shown in FIG. **1**, because the distance **D2** is longer than the distance **D1**, the part of creepage distance **Q** that extends along the surface of the second sheathed part **121** of the second terminal **120**, the part making up the creepage distance **Q** between the first terminal **110** and the second terminal **120**, may be longer than the part of creepage distance **Q** that extends along the same in the comparative example shown in FIG. **3**. In the semiconductor device **1** shown in FIG. **1**, therefore, even if the space between the first terminal **110** and the second terminal **120** is shorter than the space between the same in the comparative example shown in FIG. **3**, the necessary creepage distance **Q** can be secured.

(42) According to the semiconductor device **1** of the first embodiment, because the distance **D2** is longer than the distance **D1**, the space between the first terminal **110** and the second terminal **120** can be shortened as the necessary space distance **P** and creepage distance **Q** are secured. In the semiconductor device **1**, dimensions in the direction along the space between the first terminal **110** and the second terminal **120** can be reduced, which allows a reduction in the size of the semiconductor device **1**. Reducing the size of the semiconductor device **1** allows a reduction in the size of the busbar **2** connected to the semiconductor device **1**, thus allowing a reduction in the size of the power converter **3** constructed by connecting the semiconductor device **1** to the busbar **2**.

(43) According to the semiconductor device **1** of the first embodiment, because the distance **D2** is longer than the distance **D1**, the second sheathed part **121** is disposed on the second terminal **120** adjacent to the first exposed part **112** of the first terminal **110**, in the direction along the space between the first terminal **110** and the second terminal **120**. This means that according to the semiconductor device **1**, on a portion where a shortest distance is formed between the first terminal **110** and the second terminal **120** adjacent to each other, the sheathed part sheathed with the insulating material is disposed. When overvoltage is generated between the first terminal **110** and the second terminal **120** as a result of turn-on/off operations or the like, therefore, the semiconductor device **1** can suppress the occurrence of an electrical short circuit (dielectric breakdown) between the first terminal **110** and the second terminal **120**. The semiconductor device **1** is thus able to improve its insulation performance and reliability. Because the reliability of the semiconductor device **1** is improved, the reliability of the power converter **3** constructed by connecting the semiconductor device **1** to the busbar **2** can be improved, too.

(44) Furthermore, according to the semiconductor device **1** of the first embodiment, by shortening the space between the first terminal **110** serving as the DC negative terminal and the second terminal **120** serving as the DC positive terminal, a mutual inductance between the first terminal **110** serving as the DC negative terminal and the second terminal **120** serving as the DC positive terminal can be increased. As a result, the semiconductor device **1** can reduce an overall combined inductance between the semiconductor device **1** and the busbar **2**, which make up the power converter **3**, thus being able to reduce overvoltage and noise resulting from turn on/off operations or the like.

(45) In the semiconductor device **1**, when the distance **D2** is longer than the distance **D1**, the space between the first terminal **110** and the second terminal **120** can be shortened as the necessary insulation distance is secured. In this case, the first terminal **110** having the first sheathed part **111** is not a prerequisite. However, in the semiconductor device **1**, the first terminal **110** having the first sheathed part **111** makes securing the necessary creepage distance **Q** easier than in a case of the first terminal **110** not having the first sheathed part **111**, and therefore allows a further shortening of the space between the first terminal **110** and the second terminal **120**. The first terminal **110** having

the first sheathed part **111** thus allows a reduction in the size of the device, an improvement in the insulation performance and the reliability, and a reduction in the combined inductance, and is therefore preferable.

(46) In the above embodiment, the case where the first terminal **110** serves as the DC negative terminal and the second terminal **120** serves as the DC positive terminal has been described. In the semiconductor device **1**, the first terminal **110** may serve as the DC positive terminal and the second terminal **120** may serve as the DC negative terminal, which case offers the same effect as offered by the above embodiment.

(47) FIG. **4** is an external view of the busbar **2** according to the first embodiment. FIG. **5** is a cross-sectional view of the busbar **2**, the cross-sectional view being taken along a line B-B shown in FIG. **4**. FIG. **6** depicts a comparative example of the busbar **2** shown in FIG. **4**.

(48) The busbar **2** is connected to the semiconductor device **1**, and makes up the main circuit of the power converter **3**. The busbar **2** is connected to the first terminal **110** and the second terminal **120** of the semiconductor device **1**. The busbar **2** is connected to respective first terminals **110** and second terminals **120** of a plurality of semiconductor devices **1**.

(49) The busbar **2** shown in FIG. **4** is the busbar **2** that connects three semiconductor devices **1**, which are 2-in-1 power modules, in parallel.

(50) As shown in FIG. **4**, the busbar **2** includes a molded body **200**, busbar first terminals **210**, and busbar second terminals **220**.

(51) The molded body **200** is a structure formed by molding components of the busbar **2** by a resin-molding method, such as injection molding using a resin material **201**, which is poly phenylene sulfide (PPS) resin or the like. The molded body **200** is formed into a rectangular plate shape with a given thickness. As shown in FIG. **5**, the molded body **200** includes a first conductor plate **251**, a second conductor plate **252**, and an insulating layer **253**.

(52) The first conductor plate **251** and the second conductor plate **252** are made of a metal material with excellent electric conductivity and thermal conductivity, such as copper or aluminum, and are each formed into a plate shape. The first conductor plate **251** and the second conductor plate **252** are connected to the busbar first terminal **210** and the busbar second terminal **220**, respectively. The insulating layer **253** is made of a resin material with excellent insulation properties, such as PPS resin, and is formed into a plate shape. The first conductor plate **251** and the second conductor plate **252** are disposed counter to each other across the insulating layer **253** interposed therebetween. The second conductor plate **252**, the insulating layer **253**, and the first conductor plate **251** are stacked in this order, and are resin-molded, using the resin material **201**. In the molded body **200** shown in FIG. **4**, the first conductor plate **251**, the second conductor plate **252**, and the insulating layer **253** are sealed with the resin material **201**. A main surface **200a** of the molded body **200** is a surface along the first conductor plate **251** and the second conductor plate **252**.

(53) The busbar first terminal **210** and the busbar second terminal **220** are made of a metal material with excellent electric conductivity, such as copper or aluminum, and are each formed into a flat rod shape. The busbar first terminal **210** is connected to the second terminal **120** of the semiconductor device **1**. The busbar second terminal **220** is connected to the first terminal **110** of the semiconductor device **1**.

(54) The busbar first terminal **210** project from the molded body **200** along a specific direction. The busbar first terminal **210** projects from a side surface **200b** perpendicular to a shortish side of the molded body **200**, along the main surface **200a** of the molded body **200**. In the example of FIG. **4**, the direction of projection of the busbar first terminal **210** is an $-x$ -axis direction. The busbar first terminal **210** includes a busbar first sheathed part **211** projecting from the molded body **200**, the busbar first sheathed part **211** extending in a specific direction and being sheathed with a sheathing material having an insulation property, and a busbar first exposed part **212** projecting from the busbar first sheathed part **211**, the busbar first exposed part **212** extending in the specific direction and being exposed outside the molded body **200**. The sheathing material forming the busbar first

sheathed part **211** may be the same material as the resin material **201**, or may be a resin material different from the resin material **201**. A base end of the busbar first sheathed part **211** is equivalent to a base end of the busbar first terminal **210**, and is connected to the molded body **200**. A front end **211a** of the busbar first sheathed part **211** is connected to a base end of the busbar first exposed part **212**. A front end **212a** of the busbar first exposed part **212** is equivalent to a front end of the busbar first terminal **210**.

(55) The busbar second terminal **220** projects from the molded body **200** along the specific direction in the direction of projection that is the same as the direction of projection of the busbar first terminal **210**. The busbar second terminal **220** is adjacent to the busbar first terminal **210** with a space formed between the busbar second terminal **220** and the busbar first terminal **210**. A direction along the space between the busbar first terminal **210** and the busbar second terminal **220** is a direction perpendicular to the specific direction in which the busbar first terminal **210** and the busbar second terminal **220** project, and is a direction perpendicular to a direction along the main surface **200a** of the molded body **200**. In the example of FIG. 4, the direction along the space between the busbar first terminal **210** and the busbar second terminal **220** is the y-axis direction. The direction along the space between the busbar first terminal **210** and the busbar second terminal **220** is parallel to the direction along the space between the first terminal **110** and the second terminal **120** of the semiconductor device **1**. The busbar second terminal **220** has a busbar second sheathed part **221** projecting from the molded body **200**, the busbar second sheathed part **221** extending in the specific direction and being sheathed with a sheathing material with an insulation property, and a busbar second exposed part **222** projecting from the second sheathed part **221**, the busbar second exposed part **222** extending in the specific direction and being exposed outside the molded body **200**. The sheathing material forming the busbar second sheathed part **221** may be the same material as the resin material **201**, or may be a resin material different from the resin material **201**. A base end of the busbar second sheathed part **221** is equivalent to a base end of the busbar second terminal **220**, and is connected to the molded body **200**. A front end **221a** of the busbar second sheathed part **221** is connected to a base end of the busbar second exposed part **222**. A front end **222a** of the busbar second exposed part **222** is equivalent to a front end of the busbar second terminal **220**. The busbar second sheathed part **221** is an example of a “busbar sheathed part” described in the claims.

(56) In the busbar **2**, the busbar first terminals **210** and the busbar second terminals **220** are arranged alternately from one end to the other end of the direction along the space between the busbar first terminal **210** and the busbar second terminal **220**. In the busbar **2**, the busbar first terminals **210** are connected respectively to the second terminals **120** of the semiconductor device **1**, and the busbar second terminals **220** are connected respectively to the first terminals **110** of the semiconductor device **1**. To allow this connection, the busbar **2** is configured such that the order of arrangement of the busbar first terminals **210** and the busbar second terminals **220** is reverse to the order of arrangement of the first terminals **110** and the second terminals **120** of the semiconductor device **1**. In the example of FIG. 4, because the busbar **2** is the busbar that connects three semiconductor devices **1**, which are the 2-in-1 power modules, in parallel, six sets of the busbar first terminals **210** and the busbar second terminals **220** are arranged alternately in the -y axis direction. Specifically, in the example of FIG. 4, the busbar second terminal **220** of the first set, the busbar first terminal **210** of the first set, the busbar second terminal **220** of the second set, the busbar first terminal **210** of the second set, the busbar second terminal **220** of the third set, the busbar first terminal **210** of the third set, the busbar second terminal **220** of the fourth set, the busbar first terminal **210** of the fourth set, the busbar second terminal **220** of the fifth set, the busbar first terminal **210** of the fifth set, the busbar second terminal **220** of the sixth set, and the busbar first terminal **210** of the sixth set are arranged in this order in the -y axis direction.

(57) Now, as shown in FIGS. 4 and 6, a distance along the specific direction from the front end **212a** of the busbar first exposed part **212** of the busbar first terminal **210** to the molded body **200** is

defined as a distance L1. A distance along the specific direction from the front end **221a** of the busbar second sheathed part **221** of the busbar second terminal **220** to the molded body **200** is defined as a distance L2. A distance along the given direction from the front end **222a** of the busbar second exposed part **222** of the busbar second terminal **220** to the molded body **200** is defined as a distance L3. In the examples of FIGS. **4** and **6**, the distance L1 is equivalent to the length of projection of the busbar first terminal **210** from the molded body **200**. The distance L2 is equivalent to the length of projection of the busbar second sheathed part **221** of the busbar second terminal **220** from the molded body **200**. The distance L3 is equivalent to the length of projection of the busbar second terminal **220** from the molded body **200**.

(58) In the comparative example shown in FIG. **6**, the length of projection of the busbar second terminal **220** from the molded body **200** is equal to the length of projection of the busbar first terminal **210** from the molded body **200**. In addition, the length of projection of the busbar second sheathed part **221** of the busbar second terminal **220** from the molded body **200** is equal to the length of projection of the busbar first sheathed part **211** of the busbar first terminal **210** from the molded body **200**. As a matter of course, the length of projection of the busbar second exposed part **222** of the busbar second terminal **220** from the molded body **200** is equal to the length of projection of the busbar first exposed part **212** of the busbar first terminal **210** from the molded body **200**. In other words, in the comparative example shown in FIG. **6**, the distance L3 and the distance L1 are equal, and the distance L2 is shorter than the distance L1.

(59) In the comparative example shown in FIG. **6**, the space distance P between the busbar first terminal **210** and the busbar second terminal **220** is the distance between the busbar first exposed part **212** of the busbar first terminal **210** and the busbar second exposed part **222** of the busbar second terminal **220**. The creepage distance Q between the busbar first terminal **210** and the busbar second terminal **220** is the distance to travel through a path starting from the front end **211a** of the busbar first sheathed part **211** and extending along respective surfaces of the base end of the busbar first sheathed part **211**, the molded body **200**, and the base end of the busbar second sheathed part **221** to reach the front end **221a** of the busbar second sheathed part **221**. In the comparative example shown in FIG. **6**, a direction in which the space distance P between the busbar first terminal **210** and the busbar second terminal **220** extends is parallel to the direction along the space between the busbar first terminal **210** and the busbar second terminal **220** (y-axis direction). In the creepage distance Q between the busbar first terminal **210** and the busbar second terminal **220**, a part of creepage distance Q that extends along the surface of the busbar second sheathed part **221** of the busbar second terminal **220** and a part of creepage distance Q that extends along the surface of the busbar first sheathed part **211** of the busbar first terminal **210** may match in length.

(60) In contrast, in the busbar **2** shown in FIG. **4**, the distance L2 is made longer than the distance L1. In other words, according to the busbar **2** shown in FIG. **4**, in the direction along the space between the busbar first terminal **210** and the busbar second terminal **220**, the busbar second sheathed part **221** is disposed on the busbar second terminal **220** adjacent to the busbar first exposed part **212** of the busbar first terminal **210**. In the busbar **2** shown in FIG. **4**, the distance L3 is made longer than the distance L1 so that the distance L2 is longer than the distance L1. Specifically, in the busbar **2** shown in FIG. **4**, the length of projection of the busbar second sheathed part **221** of the busbar second terminal **220** from the molded body **200** is longer than the length of projection of the busbar first exposed part **212** of the busbar first terminal **210** from the molded body **200**. As a matter of course, the length of projection of the busbar second terminal **220** from the molded body **200** is longer than the length of projection of the busbar first terminal **210** from the molded body **200**.

(61) In the busbar **2** shown in FIG. **4**, the space distance P between the busbar first terminal **210** and the busbar second terminal **220** is the distance between the front end **212a** of the busbar first exposed part **212** of the busbar first terminal **210** and the base end of the busbar second exposed part **222**, which is connected to the front end **221a** of the busbar second sheathed part **221** of the

busbar second terminal **220**. The creepage distance Q between the busbar first terminal **210** and the busbar second terminal **220** is the distance to travel through a path starting from the front end **211a** of the busbar first sheathed part **211** of the busbar first terminal **210** and extending along respective surfaces of the base end of the busbar first sheathed part **211**, the molded body **200**, and the base end of the busbar second sheathed part **221** of the busbar second terminal **220** to reach the front end **221a** of the busbar second sheathed part **221**. In the busbar **2** shown in FIG. **4**, because the distance L2 is longer than the distance L1, the direction of the space distance P may be tilted against the direction along the space between the busbar first terminal **210** and the busbar second terminal **220** (y-axis direction). In the busbar **2** shown in FIG. **4**, therefore, even if the space between the busbar first terminal **210** and the busbar second terminal **220** is shorter than the space between the same in the comparative example shown in FIG. **6**, the necessary space distance P can be secured. In the busbar **2** shown in FIG. **4**, because the distance L2 is longer than the distance L1, the part of creepage distance Q that extends along the surface of the busbar second sheathed part **221** of the busbar second terminal **220**, the part making up the creepage distance Q between the busbar first terminal **210** and the busbar second terminal **220**, may be longer than the part of creepage distance Q that extends along the same in the comparative example shown in FIG. **6**. In the busbar **2** shown in FIG. **4**, therefore, even if the space between the busbar first terminal **210** and the busbar second terminal **220** is shorter than the space between the same in the comparative example shown in FIG. **6**, the necessary creepage distance Q can be secured.

(62) According to the busbar **2** of the first embodiment, because the distance L2 is longer than the distance L1, the space between the busbar first terminal **210** and the busbar second terminal **220** can be shortened as the necessary space distance P and creepage distance Q are secured. In the busbar **2**, dimensions in the direction along the space between the busbar first terminal **210** and the busbar second terminal **220** can be reduced, which allows a reduction in the size of the busbar **2**. Reducing the size of the busbar **2** allows a reduction in the size of the semiconductor device **1** connected to the busbar **2**, thus allowing a reduction in the size of the power converter **3** constructed by connecting the busbar **2** to the semiconductor device **1**.

(63) According to the busbar **2** of the first embodiment, because the distance L2 is longer than the distance L1, the busbar second sheathed part **221** is disposed on the busbar second terminal **220** adjacent to the busbar first exposed part **212** of the busbar first terminal **210**, in the direction along the space between the busbar first terminal **210** and the busbar second terminal **220**. This means that according to the busbar **2**, on a portion where a shortest distance is formed between the busbar first terminal **210** and the busbar second terminal **220** adjacent to each other, the sheathed part sheathed with the sheathing material with the insulation property is disposed. When overvoltage is generated between the busbar first terminal **210** and the busbar second terminal **220** as a result of turn-on/off operations or the like, therefore, the busbar **2** can suppress the occurrence of an electrical short circuit between the busbar first terminal **210** and the busbar second terminal **220**. The busbar **2** is thus able to improve its insulation performance and reliability. Because the reliability of the busbar **2** is improved, the reliability of the power converter **3** constructed by connecting the busbar **2** to the semiconductor device **1** can be improved, too.

(64) Furthermore, according to the busbar **2** of the first embodiment, by shortening the space between the busbar first terminal **210** connected to the DC positive terminal and the busbar second terminal **220** connected to the DC negative terminal, a mutual inductance between the busbar first terminal **210** and the busbar second terminal **220** can be increased. As a result, the busbar **2** can reduce an overall combined inductance between the semiconductor device **1** and the busbar **2**, which make up the power converter **3**, thus being able to reduce overvoltage and noise resulting from turn on/off operations or the like.

(65) In the busbar **2**, when the distance L2 is longer than the distance L1, the space between the busbar first terminal **210** and the busbar second terminal **220** can be shortened as the necessary insulation distance is secured. In this case, the busbar first terminal **210** having the busbar first

sheathed part **211** is not a prerequisite. However, in the busbar **2**, the busbar first terminal **210** having the busbar first sheathed part **211** makes securing the necessary creepage distance Q easier than in a case of the busbar first terminal **210** not having the busbar first sheathed part **211**, and therefore allows further shortening of the space between the busbar first terminal **210** and the busbar second terminal **220**. The busbar first terminal **210** having the busbar first sheathed part **211** thus allows a reduction in the size of the device, an improvement in the insulation performance and the reliability, and a reduction in the combined inductance, and is therefore preferable.

(66) FIG. **7** is an external view of the power converter **3** according to the first embodiment. FIG. **8** depicts a comparative example of the power converter **3** shown in FIG. **7**.

(67) The power converter **3** includes the semiconductor devices **1** and the busbar **2** connected to the semiconductor devices **1**. In the power converter **3** shown in FIG. **7**, three semiconductor devices **1** of FIG. **1**, which are the 2-in-1 power modules, are connected in parallel to the busbar **2** shown in FIG. **4**. In the power converter **3** shown in FIG. **7**, a capacitor module (not illustrated) is connected to the busbar **2** shown in FIG. **4**.

(68) In the power converter **3**, as shown in FIG. **7**, each semiconductor device **1** and the busbar **2** are set in a position in which the given direction in which the first terminal **110** and the second terminal **120** project and the specific direction in which the busbar first terminal **210** and the busbar second terminal **220** project are the same direction. In the power converter **3**, the semiconductor device **1** and the busbar **2** are set in a position in which the first terminal **110** is counter to the busbar second terminal **220** and the second terminal **120** is counter to the busbar first terminal **210**. Furthermore, in the power converter **3**, the semiconductor device **1** and the busbar **2** are set in a position in which the direction of projection of the first terminal **110** and the second terminal **120** (+x-axis direction) is opposite to the direction of projection of the busbar first terminal **210** and the busbar second terminal **220** (-x-axis direction).

(69) In the power converter **3**, the semiconductor device **1** and the busbar **2** are connected by connecting the first exposed part **112** of the first terminal **110** to the busbar second exposed part **222** of the busbar second terminal **220** and connecting the second exposed part **122** of the second terminal **120** to the busbar first exposed part **212** of the busbar first terminal **210**. Specifically, in the power converter **3** shown in FIG. **7**, the first exposed part **112** and the busbar second exposed part **222** are set overlapping each other in the z-axis direction as the second exposed part **122** and the busbar first exposed part **212** are set overlapping each other in the z-axis direction, and their respective overlapping parts are connected by welding or the like. As a result, in the power converter **3**, the distance $D2$ is made longer than the distance $D1$ in the semiconductor device **1**, and the distance $L2$ is made longer than the distance $L1$ in the busbar **2**. In addition, in the power converter **3** shown in FIG. **7**, the sum of the distance $D1$ and the distance $L2$ is equal to the sum of the distance $D2$ and the distance $L1$ in the semiconductor device **1** and the busbar **2**.

(70) It is preferable that the first exposed part **112** be connected to the busbar second exposed part **222** and the second exposed part **122** be connected to the busbar first exposed part **212**, by tungsten inert gas (TIG) welding. These exposed parts, however, may be connected by a welding method different from TIG welding, such as laser welding or resistance welding, or by a mechanical connection method, such as ultrasonic welding or screw fastening.

(71) In the power converter **3** of the first embodiment, as mentioned in the above description of the semiconductor device **1** shown in FIG. **1** and the busbar **2** shown in FIG. **4**, the distance $D2$ is longer than the distance $D1$ and the distance $L2$ is longer than the distance $L1$. In the comparative example shown in FIG. **8**, in contrast, as mentioned in the above description of the semiconductor device **1** of the comparative example shown in FIG. **3** and the busbar **2** of the comparative example shown in FIG. **6**, the distance $D2$ is shorter than the distance $D1$ and the distance $L2$ is shorter than the distance $L1$.

(72) In the power converter **3** of the first embodiment, a space between a set of the first terminal **110** and the busbar second terminal **220** and a set of the second terminal **120** and the busbar first

terminal **210** can be shortened as the necessary space distance P and creepage distance Q of the space are secured. In the power converter **3**, dimensions of the semiconductor device **1** and the busbar **2** in the direction along the space can be reduced, which allows a reduction in the size of the power converter **3**.

(73) According to the power converter **3** of the first embodiment, on a portion where a shortest distance is formed between the set of the first terminal **110** and the busbar second terminal **220** and the set of the second terminal **120** and the busbar first terminal **210**, both sets being adjacent to each other, the sheathed parts with the insulation property are disposed. When overvoltage is generated in the space between the set of the first terminal **110** and the busbar second terminal **220** and the set of the second terminal **120** and the busbar first terminal **210**, as a result of turn-on/off operations or the like, therefore, the power converter **3** can suppress the occurrence of an electrical short circuit in the space. The power converter **3** is thus able to improve its insulation performance and reliability.

(74) Furthermore, the power converter **3** of the first embodiment can increase a mutual inductance between the set of the first terminal **110** and the busbar second terminal **220** and the set of the second terminal **120** and the busbar first terminal **210**. The power converter **3**, therefore, can reduce an overall combined inductance between the semiconductor device **1** and the busbar **2**, thus being able to reduce overvoltage and noise resulting from turn on/off operations or the like.

(75) In the power converter **3** of the first embodiment, the semiconductor device **1** and the busbar **2** are set in the position in which the first terminal **110** is counter to the busbar second terminal **220** and the second terminal **120** to the busbar first terminal **210**. Furthermore, the semiconductor device **1** and the busbar **2** are set in the position in which the side to which the first terminal **110** and the second terminal **120** project and the side to which the busbar first terminal **210** and the busbar second terminal **220** project are opposite to each other. As a result, in the power converter **3**, a connected part between the first terminal **110** and the busbar second terminal **220** and a connected part between the second terminal **120** and the busbar first terminal **210** are arranged such that the connected parts shift alternately to a side closer to the sealing body **100** and to a side closer to the molded body **200** with respect to a midline between the sealing body **100** and the molded body **200**. According to the power converter **3**, respective spaces between sets of the first terminals **110** and the busbar second terminals **220** and sets of the second terminals **120** and the busbar first terminals **210** can be further shortened all across the power converter **3** as the necessary space distance P and creepage distance Q are secured. Hence the power converter **3** allows a reduction in the size of the device, an improvement in the insulation performance and reliability, and a reduction in the combined inductance.

(76) According to the power converter **3** of the first embodiment, the sum of the distance D1 and the distance L3 is equal to the sum of the distance D3 and the distance L1 in the semiconductor device **1** and the busbar **2**. According to the power converter **3**, respective lengths of projection of groups of the terminals **110**, **120**, **210**, and **220**, which project between the sealing body **100** and the molded body **200**, are made equal as a whole in the power converter **3**. According to the power converter **3**, respective lengths of projection of the groups of the terminals **110**, **120**, **210**, and **220**, which project between the sealing body **100** and the molded body **200**, can be reduced as a whole in the power converter **3**. The power converter **3**, therefore, can reduce a self-inductance of the groups of the terminals **110**, **120**, **210**, and **220**, which project between the sealing body **100** and the molded body **200**, thus being able to further reduce an overall combined inductance of the power converter **3**. The power converter **3** can reduce dimensions in a direction along a space between the sealing body **100** and the molded body **200**, which allows a further reduction in the size of the power converter **3**.

Second Embodiment

(77) A semiconductor device **1**, a busbar **2**, and a power converter **3** according to a second embodiment will be described with reference to FIGS. **9** to **14**. In describing the second

embodiment, description of the same configurations and operations as those of the first embodiment will be omitted.

(78) As shown in FIG. 14, which will be described later, the semiconductor device **1** of the second embodiment is set in a position in which the given direction in which the first terminal **110** and the second terminal **120** project is along an upper-to-lower direction. In this embodiment, in the upper-to-lower direction, a side closer to a bottom **170b** of a case **170** of the semiconductor device **1** is referred to as “lower side”, and a side distant away from the bottom **170b** of the case **170** is referred to as “upper side”.

(79) FIG. 9 is an external view of the semiconductor device **1** according to the second embodiment. FIG. 10 is a cross-sectional view of the semiconductor device **1**, the cross-sectional view being taken along a line C-C shown in FIG. 9.

(80) The semiconductor device **1** of the second embodiment includes the case **170** in which the sealing body **100** is housed. The case **170** is made of a metal material with excellent thermal conductivity, such as copper or aluminum, and is formed into a flat cylindrical shape. The case **170** includes a pair of a first heat-dissipating board **171** and a second heat-dissipating board **172**, and a frame **173**. The first heat-dissipating board **171** and the second heat-dissipating board **172** are counter to each other across a space therebetween in a direction perpendicular to the main surface **100a** of the sealing body **100**, and are each disposed along the main surface **100a** of the sealing body **100**. Between the first heat-dissipating board **171** and the second heat-dissipating board **172**, an internal space of the case **170** is formed. Outer surfaces of the first heat-dissipating board **171** and the second heat-dissipating board **172** are provided respectively with a plurality of fins **174** extending outward. The frame **173** fixes the first heat-dissipating board **171** and the second heat-dissipating board **172**. The frame **173** is connected to the first heat-dissipating board **171** and the second heat-dissipating board **172** by laser welding or the like. The case **170** has an opening **170a** formed on one end, and the bottom **170b** disposed on the other end.

(81) On the sealing body **100** of the second embodiment, the first terminals **110**, the second terminals **120**, the output terminal **130**, and the control terminals **140** all project from one side surface **100b** of the sealing body **100** along the given direction in the same direction of projection. The sealing body **100** housed in the case **170** is disposed such that the terminals **110** to **140** extending along the given direction each project from the opening **170a** toward outside of the case **170**.

(82) In the sealing body **100** of the second embodiment, the first circuit conductor **154** and the second circuit conductor **155** each have a lead frame structure. The first circuit conductor **154** and the second circuit conductor **155** have a lead **154b** and a lead **155b**, respectively. The lead **154b** of the first circuit conductor **154** and the lead **155b** of the second circuit conductor **155** are formed integrally with the first terminal **110**, the second terminal **120**, and the output terminal **130**. According to the sealing body **100** of the second embodiment, because the first circuit conductor **154** and the second circuit conductor **155** are housed in the case **170** provided with the first heat-dissipating board **171** and the second heat-dissipating board **172**, the sealing body **100** dispenses with the first heat-dissipating conductor **158** and the second heat-dissipating conductor **159**. The first circuit conductor **154** and the second circuit conductor **155** are molded such that a surface **154a** and a surface **155a** are exposed from the resin material **101**, the surface **154a** and the surface **155a** being opposite respectively to surfaces bonded to the first semiconductor element **151** and the second semiconductor element **152**.

(83) In the sealing body **100** of the second embodiment, the first insulating layer **156** and the second insulating layer **157** are disposed respectively on the surface **154a** and the surface **155a** of the first circuit conductor **154** and the second circuit conductor **155**, the surface **154a** and the surface **155a** being exposed from the resin material **101**. The sealing body **100** is housed in the case **170** in a state in which the first insulating layer **156** and the second insulating layer **157** are disposed respectively on the surface **154a** and the surface **155a** of the first circuit conductor **154**

and the second circuit conductor **155**, the surface **154a** and the surface **155a** being exposed from the resin material **101**. In other words, the first insulating layer **156** and the second insulating layer **157** of the second embodiment are retrofitted to the sealing body **100**. To the sealing body **100**, the first insulating layer **156**, and the second insulating layer **157** that are housed in the case **170**, pressure is applied via the first heat-dissipating board **171** and the second heat-dissipating board **172** of the case **170**. As a result, the first insulating layer **156** and the second insulating layer **157** are bonded respectively to the surface **154a** and the surface **155a** of the sealing body **100**, the surface **154a** and the surface **155a** being exposed from the resin material **101**, respectively, and are bonded respectively to the first insulating layer **156** and the second insulating layer **157**. The case **170**, in which the sealing body **100**, the first insulating layer **156**, and the second insulating layer **157** are housed, is filled with a resin material **102** by potting.

(84) The control terminal **140** of the second embodiment has a fourth sheathed part **141** projecting from the sealing body **100**, the fourth sheathed part **141** extending in the given direction and being sheathed with an insulating material, and a fourth exposed part **142** projecting from the fourth sheathed part **141**, the fourth exposed part **142** extending in the given direction and being exposed outside the sealing body **100**. The insulating material forming the fourth sheathed part **141** may be the same material as the resin material **101**, or may be a resin material different from the resin material **101**. The control terminals **140** are disposed respectively on both ends of the side surface **100b** of sealing body **100** so that the control terminals **140** are separated from each other.

(85) In the semiconductor device **1** shown in FIG. **9**, one control terminal **140**, the first terminal **110** of the first set, the second terminal **120** of the first set, the first terminal **110** of the second set, and the second terminal **120** of the second set, the output terminal **130**, and the other control terminal **140** are arranged in this order along the $-y$ axis direction. According to the semiconductor device **1** of the second embodiment, in the direction along the space between the first terminal **110** and the second terminal **120**, the second sheathed part **121** is disposed on the second terminal **120** adjacent to the first exposed part **112** of the first terminal **110**, and the fourth sheathed part **141** is disposed on the control terminal **140** adjacent to the first exposed part **112** of the first terminal **110**. According to the semiconductor device **1** of the second embodiment, in the direction along the space between the first terminal **110** and the second terminal **120**, the second sheathed part **121** is disposed on the second terminal **120** adjacent to the output terminal **130**, and the fourth sheathed part **141** is disposed on the control terminal **140** adjacent to the output terminal **130**.

(86) In the semiconductor device **1** of the second embodiment, as shown in FIG. **9**, the distance **D2** is longer than the distance **D1** as is in the first embodiment. According to the semiconductor device **1** of the second embodiment, in the same manner as in the first embodiment, the second sheathed part **121** is disposed on the second terminal **120** adjacent to the first exposed part **112** of the first terminal **110**, in the direction along the space between the first terminal **110** and the second terminal **120**. The semiconductor device **1** of the second embodiment thus allows a reduction in the size of the device, an improvement in the insulation performance and reliability, and a reduction in the combined inductance, in the same manner as in the first embodiment.

(87) FIG. **11** is a top view of the busbar **2** according to the second embodiment. FIG. **12** is a side view of the busbar **2**, the side view being given when the busbar **2** is seen in the direction of an arrow **E** shown in FIG. **11**. FIG. **13** is a cross-sectional view of the busbar **2**, the cross-sectional view being taken along a line **F-F** shown in FIG. **11**.

(88) As shown in FIG. **13**, in the molded body **200** included in the busbar **2** of the second embodiment, a first conductor plate **251**, an insulating layer **253**, and a second conductor plate **252** are stacked in this order, and are resin-molded by injection molding or the like, using the resin material **201**. The molded body **200** has the main surface **200a** along the first conductor plate **251** and the second conductor plate **252**. The molded body **200** is set in a posture in which a direction along the main surface **200a** intersects the given direction and the specific direction.

(89) As shown in FIG. **11**, the molded body **200** is molded such that the second conductor plate **252**

is exposed from the resin material **201** on an upper surface **200c** that is one of the main surfaces **200a**. An upper surface **252a** of the second conductor plate **252** exposed from the resin material **201** is covered with a resin different from the resin material **201**, by potting or the like. The upper surface **200c** of the molded body **200** is the one main surface **200a** that is closer to the second conductor plate **252** connected to the busbar second terminal **220** than to the first conductor plate **251** connected to the busbar first terminal **210**. In other words, the upper surface **200c** of the molded body **200** is the one main surface **200a** that is separated farther from the first conductor plate **251** connected to the busbar first terminal **210** than from the second conductor plate **252** connected to the busbar second terminal **220**.

(90) As shown in FIGS. **12** and **13**, the busbar first terminal **210** of the second embodiment extends from the side surface **200b** of the molded body **200** along a direction perpendicular to a direction along the first conductor plate **251** and the second conductor plate **252**, and projects beyond the upper surface **200c** that is the one main surface **200a** of the molded body **200**. Specifically, the busbar first terminal **210** projects from the side surface **200b** of the molded body **200**, the side surface **200b** intersecting the direction along the upper surface **200c** that is the one main surface **200a** of the molded body **200**, to extend further beyond the upper surface **200c** that is the one main surface **200a** closer to the second conductor plate **252** than to the first conductor plate **251**. The specific direction along which the busbar first terminal **210** projects is the direction perpendicular to the upper surface **200c** extending along the first conductor plate **251** and the second conductor plate **252**. The direction of projection of the busbar first terminal **210** is the direction of heading from the first conductor plate **251** toward the second conductor plate **252**. In the example of FIG. **13**, the direction of projection of the busbar first terminal **210** is the +x-axis direction.

(91) The busbar first terminal **210** has the busbar first exposed part **212** extending in the specific direction and exposed outside the molded body **200**, but may not have the busbar first sheathed part **211**. In other words, the busbar first terminal **210** of the second embodiment may be composed of the busbar first exposed part **212** only. The front end **212a** of the busbar first exposed part **212** is equivalent to the front end of the busbar first terminal **210**, and projects beyond the upper surface **200c** that is the one main surface **200a** of the molded body **200**. The upper surface **200c**, which is the one main surface **200a** of the molded body **200**, is closer to the front end **212a** of the busbar first exposed part **212** than the other main surface **200a** is.

(92) As shown in FIGS. **12** and **13**, the busbar second terminal **220** of the second embodiment projects from the upper surface **200c** of the molded body **200**, the upper surface **200c** being located near the side surface **200b** provided with the busbar first terminal **210**, along the specific direction in the direction of projection that is the same as the direction of projection of the busbar first terminal **210**. The busbar second terminal **220** includes the busbar second sheathed part **221** projecting from the upper surface **200c** of the molded body **200**, the busbar second sheathed part **221** extending in the specific direction and being sheathed with the sheathing material with the insulation property, and the busbar second exposed part **222** projecting from the busbar second sheathed part **221**, the busbar second exposed part **222** extending in the specific direction and being exposed outside the molded body **200**.

(93) The busbar second sheathed part **221** projects from the upper surface **200c**, which is the main surface **200a** beyond which the busbar first exposed part **212** projects out, in the direction of going away from the upper surface **200c** in such a way as to project beyond the front end **212a** of the busbar first exposed part **212**. In the example of FIG. **13**, the busbar second sheathed part **221** projects from the upper surface **200c** along the specific direction, in which the busbar first exposed part **212** extends, in the direction of projection that is the same as the direction of projection of the busbar first exposed part **212** in such a way as to project beyond the front end **212a** of the busbar first exposed part **212**. In the example of FIG. **13**, the direction of projection of the busbar first exposed part **212** is the +x-axis direction.

(94) The busbar second exposed part **222** has a bent part **223** that is bent in the direction of heading

from the front end **221a** of the busbar second sheathed part **221** toward the side surface **200b** provided with the busbar first terminal **210** along the upper surface **200c**. In the example of FIG. **13**, the direction of heading toward the side surface **200b** is a $-z$ -axis direction. The busbar second exposed part **222** projects from the front end **223a** of the bent part **223** in the direction of going away from the front end **212a** of the busbar first exposed part **212**. In the example of FIG. **13**, the busbar second exposed part **222** projects from the front end **223a** of the bent part **223** along the specific direction, in which the busbar first exposed part **212** extends, in the direction of projection that is the same as the direction of projection of the busbar first exposed part **212**.

(95) In the busbar **2** of the second embodiment, as shown in FIGS. **12** and **13**, the distance **L2** is longer than the distance **L1** in the same manner as in the busbar **2** of the first embodiment.

According to the busbar **2** of the second embodiment, in the direction along the space between the busbar first terminal **210** and the busbar second terminal **220**, the busbar second sheathed part **221** is disposed on the busbar second terminal **220** adjacent to the busbar first exposed part **212** of the busbar first terminal **210**, in the same manner as in the first embodiment. As a result, the busbar **2** of the second embodiment allows a reduction in the size of the device, an improvement in the insulation performance and reliability, and a reduction in the combined inductance, as the busbar **2** of the first embodiment does.

(96) In the busbar **2** of the second embodiment, the busbar first exposed part **212** of the busbar first terminal **210** projects from the molded body **200** in such a way as to project beyond the upper surface **200c** that is the main surface **200a** closer to the second conductor plate **252** than to the first conductor plate **251**. The busbar second sheathed part **221** of the busbar second terminal **220** projects from the upper surface **200c**, beyond which the busbar first exposed part **212** projects out, in the direction of going away from the upper surface **200c** in such a way as to project beyond the front end **212a** of the busbar first exposed part **212**. The busbar second exposed part **222** of the busbar second terminal **220** has the bent part **223** that is bent in the direction of heading from the front end **221a** of the busbar second sheathed part **221** toward the side surface **200b**, and projects from the front end **223a** of the bent part **223** to the direction of going away from the front end **212a** of the busbar first exposed part **212**. As a result, in the busbar **2** of the second embodiment, the length of the busbar second sheathed part **221** can be reduced to be shorter than the length in a case where the busbar first exposed part **212** projects from the molded body **200** in such a way as to project beyond the main surface **200a** closer to the first conductor plate **251**. The busbar **2**, therefore, can secure the necessary space distance **P** and creepage distance **Q** without making the busbar second sheathed part **221** excessively long, and can reduce the self-inductance of the busbar second terminal **220**. Hence the busbar **2** can reduce the overall combined inductance between the semiconductor device **1** and the busbar **2** that make up the power converter **3**.

(97) FIG. **14** is a cross-sectional view of the power converter **3** according to the second embodiment. FIG. **14** shows a state in which the semiconductor device **1** of the second embodiment shown in FIG. **10** is connected to the busbar **2** of the second embodiment shown in FIG. **13**.

(98) In the power converter **3** of the second embodiment, as shown in FIG. **14**, the semiconductor device **1** and the busbar **2** are set in a position in which the given direction in which the first terminal **110** and the second terminal **120** project and the specific direction in which the busbar first terminal **210** and the busbar second terminal **220** project are the same. In the power converter **3**, the semiconductor device **1** and the busbar **2** are set in a position in which the first terminal **110** is counter to the busbar first terminal **210** and the second terminal **120** is counter to the busbar second terminal **220**. In addition, in the power converter **3**, the semiconductor device **1** and the busbar **2** are set in a position in which the direction of projection of the first terminal **110** and the second terminal **120** ($+x$ -axis direction) and the direction of projection of the busbar first terminal **210** and the busbar second terminal **220** ($+x$ -axis direction) are the same. In other words, in the power converter **3** of the second embodiment, the semiconductor device **1** and the busbar **2** are set in a position in which the direction along the main surface **200a** of the molded body **200**

intersects the given direction and the specific direction. In the power converter **3** shown in the example of FIG. **14**, the semiconductor device **1** and the busbar **2** are set in a position in which the direction along the main surface **200a** of the molded body **200** is perpendicular to the given direction and the specific direction. Further, in the power converter **3**, the semiconductor device **1** and the busbar **2** are set in a position in which the second conductor plate **252** is located above the first conductor plate **251**. In other words, the semiconductor device **1** and the busbar **2** are set in a position in which the second conductor plate **252** is separated farther from the sealing body **100** along the given direction and the specific direction than the first conductor plate **251** is.

(99) According to the power converter **3**, in the semiconductor device **1** and the busbar **2**, the first exposed part **112** of the first terminal **110** is connected to the busbar first exposed part **212** of the busbar first terminal **210**, and the second exposed part **122** of the second terminal **120** is connected to the busbar second exposed part **222** of the busbar second terminal **220**. Specifically, in the power converter **3** in the example of FIG. **14**, the first exposed part **112** and the busbar first exposed part **212** are set overlapping each other in the z-axis direction as the second exposed part **122** and the busbar second exposed part **222** are set overlapping each other in the z-axis direction, and their respective overlapping parts are connected by welding or the like.

(100) In the power converter **3** of the second embodiment, the distance D2 is longer than the distance D1 and the distance L2 is longer than the distance L1 in the same manner as in the first embodiment. According to the power converter **3** of the second embodiment, on a portion where a shortest distance is formed between a set of the first terminal **110** and the busbar first terminal **210** and a set of the second terminal **120** and the busbar second terminal **220**, both sets being adjacent to each other, the sheathed parts with the insulation property are disposed in the same manner as in the first embodiment. Hence the power converter **3** of the second embodiment allows a reduction in the size of the device, an improvement in the insulation performance and reliability, and a reduction in the combined inductance, as the power converter **3** of the first embodiment does.

(101) According to the power converter **3** of the second embodiment, the semiconductor device **1** and the busbar **2** are set in the position in which the first terminal **110** is counter to the busbar first terminal **210** and the second terminal **120** is counter to the busbar second terminal **220**. In addition, in the power converter **3**, the first terminal **110** and the second terminal **120** are arranged in the same orientation as the orientation of the busbar first terminal **210** and the busbar second terminal **220**. Because of this configuration, according to the power converter **3**, even when the direction along the main surface **200a** of the molded body **200** intersects the given direction and the specific direction, the semiconductor device **1** and the busbar **2** can be connected in such a way as to simultaneously achieve securing of the space distance P and creepage distance Q, a reduction in the size of the device, and a reduction in the combined inductance.

(102) In the power converter **3** of the second embodiment, the busbar first exposed part **212** of the busbar first terminal **210** projects from the molded body **200** in such a way as to project beyond the upper surface **200c** that is the main surface **200a** closer to the second conductor plate **252** than to the first conductor plate **251**. In the power converter **3**, the busbar second sheathed part **221** of the busbar second terminal **220** projects from the upper surface **200c**, beyond which the busbar first exposed part **212** projects out, in the direction of going away from the upper surface **200c** in such a way as to project beyond the front end **212a** of the busbar first exposed part **212**. In the power converter **3**, the busbar second exposed part **222** of the busbar second terminal **220** has the bent part **223** that is bent in the direction of heading from the front end **221a** of the busbar second sheathed part **221** toward the side surface **200b**, and projects from the front end **223a** of the bent part **223** to the direction of going away from the front end **212a** of the busbar first exposed part **212**.

(103) As a result, in the power converter **3** of the second embodiment, the length of the busbar second sheathed part **221** can be reduced to be shorter than the length in the case where the busbar first exposed part **212** projects from the molded body **200** in such a way as to project beyond the main surface **200a** closer to the first conductor plate **251**. The power converter **3**, therefore, can

reduce the self-inductance of the busbar second terminal **220**, thus being able to reduce the overall combined inductance of the power converter **3**. In the power converter **3**, the busbar first terminal **210** and the busbar second terminal **220** project to be above the upper surface **200c** of the molded body **200**. In other words, the busbar first terminal **210** and the busbar second terminal **220** project to the direction of being separated farther away from the sealing body **100** than the upper surface **200c** of the molded body **200** is. As a result, a connecting part where the first terminal **110** is connected to the busbar first terminal **210** and a connecting part where the second terminal **120** is connected to the busbar second terminal **220** are located on a side that is separated farther away from the sealing body **100** than the upper surface **200c** of the molded body **200** is. According to the power converter **3**, therefore, work of connecting the semiconductor device **1** to the busbar **2** can be done easily.

(104) [Others]

(105) It should be noted that the present invention is not limited to the above embodiments but includes various modifications.

(106) For example, the above embodiments have been described in detail for easy understanding of the present invention, and are not necessarily limited to an embodiment including all constituent elements described above. Some constituent elements of a certain embodiment may be replaced with constituent elements of another embodiment, and a constituent element of another embodiment may be added to a constituent element of a certain embodiment. In addition, some of constituent elements of each embodiment can be deleted therefrom or add to or replaced with constituent elements of another embodiment.

(107) Some or all of the above constituent elements, functions, processing units, processing means, and the like may be provided as hardware, such as properly designed integrated circuits. In addition, the above-described constituent elements, functions, and the like may be provided in the form of software-based programs by causing a processor to interpret and execute programs for implementing the constituent elements/functions. Information for implementing functions, such as programs, tables, and files, may be stored in a storage device, such as a memory, a hard disk, and a solid state drive (SSD), or in a recording medium, such as an IC card, an SD card, and a DVD.

(108) A group of control lines/information lines considered to be necessary for description are illustrated, and all control lines/information lines making up the product are not necessarily illustrated. It is safe to assume that, actually, almost the entire constituent elements are interconnected.

REFERENCE SIGNS LIST

(109) **1** semiconductor device **2** busbar **3** power converter **100** sealing body **110** first terminal **112** first exposed part **112a** front end **120** second terminal **121** second sheathed part (sheathed part) **121a** front end **122** second exposed part **122a** front end **151** first semiconductor element **152** second semiconductor element **200** molded body **200a** main surface **200b** side surface **200c** upper surface **210** busbar first terminal **212** busbar first exposed part **212a** front end **220** busbar second terminal **221** busbar second sheathed part (busbar sheathed part) **221a** front end **222** busbar second exposed part **222a** front end **223** bent part **223a** front end **251** first conductor plate **252** second conductor plate **253** insulating layer

Claims

1. A power converter comprising: a semiconductor device; and a busbar connected to the semiconductor device, wherein the semiconductor device includes: a sealing body in which a semiconductor element is resin-sealed; a first terminal connected to the semiconductor element, the first terminal projecting from the sealing body along a given direction; and a second terminal connected to the semiconductor element, the second terminal being adjacent to the first terminal with a space formed between the second terminal and the first terminal and projecting from the

sealing body along the given direction in a direction of projection that is the same as a direction of projection of the first terminal, wherein the first terminal has a first exposed part that extends in the given direction and that is exposed outside the sealing body, wherein the second terminal has a sheathed part projecting from the sealing body, the sheathed part extending in the given direction and being sheathed with an insulating material, and a second exposed part projecting from the sheathed part, the second exposed part extending in the given direction and being exposed outside the sealing body, wherein a distance along the given direction from a front end of the sheathed part to the sealing body is longer than a distance along the given direction from a front end of the first exposed part to the sealing body, wherein a busbar includes: a molded body in which a first conductor plate and a second conductor plate are resin-sealed; a busbar first terminal connected to the first conductor plate, the busbar first terminal projecting from the molded body along a specific direction; and a busbar second terminal connected to the second conductor plate, the busbar second terminal being adjacent to the busbar first terminal with a space formed between the busbar second terminal and the busbar first terminal and projecting from the molded body along the specific direction in a direction of projection that is the same as a direction of projection of the busbar first terminal, wherein the busbar first terminal has a busbar first exposed part that extends in the specific direction and that is exposed outside the molded body, wherein the busbar second terminal has a busbar sheathed part projecting from the molded body, the busbar sheathed part extending in the specific direction and being sheathed with a sheathing material with an insulation property, and a busbar second exposed part projecting from the busbar sheathed part, the busbar second exposed part extending in the specific direction and being exposed outside the molded body, and wherein a distance along the specific direction from a front end of the busbar sheathed part to the molded body is longer than a distance along the specific direction from a front end of the busbar first exposed part to the molded body.

2. The power converter according to claim 1, wherein the semiconductor device and the busbar are set in a position in which: the given direction and the specific direction are the same direction; and the first terminal is counter to the busbar second terminal, the second terminal is counter to the busbar first terminal, and a direction of the first terminal and the second terminal is opposite to a direction of the busbar first terminal and the busbar second terminal, and wherein the first exposed part is connected to the busbar second exposed part and the second exposed part is connected to the busbar first exposed part.

3. The power converter according to claim 1, wherein the semiconductor device and the busbar are set in a position in which: the given direction and the specific direction are the same direction; and the first terminal is counter to the busbar first terminal, the second terminal is counter to the busbar second terminal, and a direction of the first terminal and the second terminal is the same as a direction of the busbar first terminal and the busbar second terminal, and wherein the first exposed part is connected to the busbar first exposed part and the second exposed part is connected to the busbar second exposed part.

4. The power converter according to claim 2, wherein in the semiconductor device and the busbar, a sum of the distance along the given direction from the front end of the first exposed part to the sealing body and the distance along the specific direction from the front end of the busbar second exposed part to the molded body is equal to a sum of the distance along the given direction from the front end of the second exposed part to the sealing body and the distance along the specific direction from the front end of the busbar first exposed part to the molded body.

5. The power converter according to claim 3, wherein the molded body includes: the first conductor plate and the second conductor plate that are disposed counter to each other across an insulating layer interposed between the first conductor plate and the second conductor plate; and a main surface extending along the first conductor plate and the second conductor plate, wherein the molded body is set in a position in which a direction along the main surface intersects the given direction and the specific direction, wherein in the busbar first terminal, the busbar first exposed

part projects from a side surface of the molded body, the side surface intersecting the direction along the main surface, in such a way as to project beyond the main surface closer to the second conductor plate than to the first conductor plate, wherein in the busbar second terminal, the busbar sheathed part projects from the main surface beyond which the busbar first exposed part projects out, in such a way as to project beyond the front end of the busbar first exposed part in a direction of going away from the main surface, and wherein the busbar second exposed part has a bent part bent in a direction of heading from the front end of the busbar sheathed part toward the side surface along the main surface, and projects from a front end of the bent part in a direction of going away from the front end of the busbar first exposed part.
