

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408227
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Park; Sang Rae

Wireless microphone system comprising wireless microphone transmitter and receiver

Abstract

The present invention relates to a wireless microphone system with which a receiver user can transmit sound to a wireless microphone user and with which the sound of the receiver user can be recorded, without a separate communication means or recording means.

Inventors:	Park; Sang Rae (Seoul, KR)
Applicant:	Park; Sang Rae (Seoul, KR)
Family ID:	78150874
Appl. No.:	18/026762
Filed (or PCT Filed):	July 21, 2021
PCT No.:	PCT/KR2021/009393
PCT Pub. No.:	WO2022/059901
PCT Pub. Date:	March 24, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230345571 A1	Oct. 26, 2023

Foreign Application Priority Data

KR	10-2020-0120206	Sep. 18, 2020
----	-----------------	---------------

Publication Classification

Int. Cl.: H04W76/28 (20180101); H03M1/00 (20060101); H04R29/00 (20060101); H04W52/02 (20090101); H04W76/20 (20180101)

U.S. Cl.:

CPC H04W76/20 (20180201); H03M1/001 (20130101);

Field of Classification Search

CPC: H04B (10/50); H04B (10/2589); H04B (5/48); H04B (1/48); H04B (1/71635); H04J (14/0232); H04J (14/0235); H04R (2499/11); H04R (29/004); H04R (5/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11102814	12/2020	Bhorkar	N/A	H04L 5/005
2017/0339682	12/2016	Lee	N/A	H04L 1/188
2019/0058958	12/2018	Proctor, Jr.	N/A	H04N 21/4622
2020/0029276	12/2019	Kim	N/A	H04W 48/16
2020/0120607	12/2019	Kim	N/A	H04W 52/0235
2020/0260186	12/2019	Stachura	N/A	G10L 15/30
2022/0104260	12/2021	Wang	N/A	H04W 72/0446
2022/0346010	12/2021	Zhou	N/A	H04W 52/0229

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2012-124847	12/2011	JP	N/A
10-2008-0013652	12/2007	KR	N/A
10-1405331	12/2013	KR	N/A
10-1492736	12/2014	KR	N/A
10-1604678	12/2015	KR	N/A

OTHER PUBLICATIONS

International Search Report mailed Nov. 2, 2021, issued International Application No. PCT/KR2021/009393. cited by applicant

Primary Examiner: Aung; Sai

Attorney, Agent or Firm: Stein IP, LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is a national stage of International Application No. PCT/KR2021/009393, filed Jul. 21, 2021, which claims the benefit of Korean Application No. 10-2020-0120206, filed Sep. 18, 2020, in the Korean Intellectual Property Office, the disclosures of which are incorporated herein by reference.

TECHNICAL FIELD

(2) The present invention relates to a wireless microphone system comprising a wireless microphone transmitter and a receiver.

BACKGROUND ART

(3) A wireless microphone system used for performances, lectures, broadcasting, and the like is composed of a wireless microphone transmitter and a receiver. The wireless microphone transmitter transmits voice data input through a microphone to the receiver, and the receiver receives the voice data and records or output the voice data through a speaker.

(4) However, according to an existing wireless microphone system, when a user (e.g., a photographer) of a receiver needs to transmit voice, such as coating, questions, comments, etc., to a user (e.g., a person to be photographed) of a wireless microphone, or needs to record the transmitted voice, a separate communication means or recording means has to be used (e.g., by being connected to a camera). Therefore, it is impossible for the photographer to transmit voice to the person to be photographed or to record the voice of the photographer without additional equipment, and thus additional equipment is required in order to do so, which increases broadcasting production costs and complicated equipment operation.

(5) In addition, since the existing wireless microphone system has no choice but to configure wireless microphone transmitters and receivers in one-to-one or many-to-one correspondence, it is impossible to use the wireless microphone system in situations where multiple photographers need to photograph one person to be photographed or multiple photographers need to photograph multiple persons to be photographed.

DETAILED DESCRIPTION OF THE INVENTION

Technical Problems

(6) The present invention aims to provide a wireless microphone system with which a receiver user can transmit sound to a wireless microphone user and with which the sound of the receiver user can be recorded, without a separate communication means or recording means.

(7) Further, the present invention aims to provide a wireless microphone system that can be utilized even in a situation where multiple photographers photograph one person to be photographed or several photographers photograph several persons to be photographed.

Technical Solution

(8) In order to solve the aforementioned technical problems, a wireless microphone system according to the present invention includes a wireless microphone transmitter and a receiver, wherein the wireless microphone transmitter is configured to operate in one of a first mode for transmitting first data, which is input through an audio input unit of the wireless microphone transmitter, to the receiver and a second mode for receiving second data from the receiver, the receiver is configured to operate in one of a third mode for receiving the first data from the wireless microphone transmitter and a fourth mode for transmitting the second data, which is input through an audio input unit of the receiver, to the wireless microphone transmitter, the wireless microphone transmitter transmits the first data in a data transmission period when operating in the first mode in a time structure in which the data transmission period and a reception waiting period are alternately repeated, the receiver receives the first data in the data transmission period when operating in the third mode, transmits a first mode switch request message to the wireless microphone transmitter in the reception waiting period, switches to the fourth mode, and operates upon receiving a mode switch command in the third mode, and transmits the second data in the data transmission period

when operating in the fourth mode, the wireless microphone transmitter switches to the second mode and operates upon receiving the first mode switch request message and receives the second data in the data transmission period when operating in the second mode, the receiver transmits a second mode switch request message to the wireless microphone transmitter in the reception waiting period, switches to the third mode, and operates upon receiving a mode switch command in the fourth mode, and the wireless microphone transmitter switches to the first mode and operates upon receiving the second mode switch request message.

(9) The receiver may be provided with a mode switch button for receiving the mode switch command in the third mode and the mode switch command in the fourth mode from a user.

(10) The wireless microphone transmitter may operate in the first mode by default and the receiver may operate in the third mode by default.

(11) The wireless microphone transmitter may include an antenna; an audio input unit configured to receive an audio signal; an analog-to-digital (AD) converter configured to convert the audio signal into a digital signal and output the digital signal as the first data; a digital-to-analog (DA) converter configured to convert the second data into an analog signal and output the analog signal; an audio output unit configured to output a signal from the DA converter as an audio signal; and a control unit configured to transmit the first data through the antenna in the data transmission period in the first mode, receive the second data through the antenna in the data transmission period in the second mode, receive the first mode switch request message or the second mode switch request message in the reception waiting period, control switching from the first mode to the second mode in response to the first mode switch request message, and control switching from the second mode to the first mode in response to the second mode switch request message.

(12) The receiver may include an antenna; an audio input unit configured to receive an audio signal; an AD converter configured to convert the audio signal into a digital signal and output the digital signal as the second data; a DA converter configured to convert the first data into an analog signal and output the analog signal; an audio output unit configured to output a signal from the DA converter as an audio signal; a mode switch button configured to receive the mode switch command in the third mode and the mode switch command in the fourth mode; and a control unit configured to transmit the first data through the antenna in the data transmission period in the third mode, receive the second data through the antenna in the data transmission period in the fourth mode, transmit the first mode switch request message through the antenna in the reception waiting period upon receiving the mode switch command in the third mode, transmit the second mode switch request message through the antenna in the reception waiting period upon receiving the mode switch command in the fourth mode, control switching to the fourth mode in response to the mode switch command in the third mode, and control switching to the third mode in response to the mode switch command in the fourth mode.

(13) When a plurality of receivers are provided and any one of the receivers transmits the first mode switch request message in the reception waiting period, switches to the fourth mode, and transmits the second data in the data transmission period, the remaining receivers that have received the first mode request message may receive the second data in the data transmission period.

(14) When a plurality of wireless microphone transmitters are provided, a plurality of receivers are provided, and any one of the receivers transmits the first mode switch request message in the reception waiting period, switches to the fourth mode, and transmits the second data in the data transmission period, the plurality of wireless microphone transmitters that have received the first mode switch request message may switch to the second mode and operate and the remaining receivers that have received the first mode switch request message may receive the second data in the data transmission period.

Advantageous Effects

(15) The present invention described above may provide a wireless microphone system with which

a receiver user can transmit sound to a wireless microphone user and with which the sound of the receiver user can be recorded, without a separate communication means or recording means.

(16) The present invention described above may provide a wireless microphone system that can be used even in a situation where multiple photographers photograph one person to be photographed or multiple photographers photograph several persons to be photographed.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 illustrates the configuration of a wireless microphone system according to an embodiment of the present invention.

(2) FIGS. 2 to 4 illustrate a time structure in which a wireless microphone transmitter **100** and a receiver **200** exchange data.

(3) FIG. 5 is a flowchart illustrating an operation of the wireless microphone transmitter **100** according to an embodiment of the present invention.

(4) FIG. 6 is a flowchart illustrating an operation of the receiver **200** according to an embodiment of the present invention.

(5) FIG. 7 illustrates a configuration of the wireless microphone transmitter **100** according to an embodiment of the present invention.

(6) FIG. 8 illustrates a configuration of the receiver **200** according to an embodiment of the present invention.

(7) FIG. 9 illustrates a configuration of a wireless microphone system according to another embodiment of the present invention.

(8) FIG. 10 illustrates a configuration of a wireless microphone system according to still another embodiment of the present invention.

MODE FOR INVENTION

(9) Hereinafter, preferred embodiments of the present invention will be described in detail with reference to the accompanying drawings. Like reference numerals hereinafter refer to the like elements in descriptions and the accompanying drawings and thus the repetitive description thereof will be omitted. Further, in describing the present invention, detailed descriptions related to publicly known functions or configurations will be omitted in order not to obscure the gist of the present invention.

(10) FIG. 1 illustrates the configuration of a wireless microphone system according to an embodiment of the present invention. A wireless microphone system according to the present embodiment includes a wireless microphone transmitter **100** and a receiver **200**. When a photographer B photographs a person B to be photographed with a camera C, the person A may carry the wireless microphone transmitter **100** and the receiver **200** may be mounted on the camera C.

(11) The wireless microphone transmitter **100** may be provided with an audio input unit and an audio output unit. The audio input unit may be a built-in microphone or an input terminal of an external microphone. The audio output unit may be a built-in speaker or an input terminal of an external speaker (or earphones).

(12) The receiver **200** may be provided with an audio input unit and an audio output unit. The audio input unit may be a built-in microphone or an input terminal of an external microphone. The audio output unit may be a built-in speaker or an input terminal of an external speaker (or earphones). The audio output unit of the receiver **200** may be connected to the camera.

(13) The wireless microphone transmitter **100** and the receiver **200** may directly exchange data between each other using wireless communication. For example, the wireless microphone transmitter **100** and the receiver **200** may exchange data through an unlicensed frequency band of

900 MHz.

(14) FIGS. 2 to 4 illustrate a time structure in which a wireless microphone transmitter **100** and a receiver **200** exchange data. The time structure is a structure in which a data transmission period during which the wireless microphone transmitter **100** and the receiver **200** transmit and receive voice data to and from each other and a reception waiting period during which voice data is not transmitted and received are alternately repeated. The time length of the data transmission period is longer than the time length of the reception waiting period.

(15) The wireless microphone transmitter **100** is operable in one of a first mode for transmitting first data, which is input through its audio input unit, and a second mode for receiving second data from the receiver **200**. The wireless microphone transmitter **100** may operate in the first mode by default (i.e., when the power is turned on).

(16) The receiver **200** is operable in one of a third mode for receiving the first data from the wireless microphone transmitter **100** and a fourth mode for transmitting the second data, which is input through its audio input unit, to the wireless microphone transmitter **100**. The receiver **200** may operate in the third mode by default (i.e., when the power is turned on).

(17) Referring to FIG. 2 in conjunction with FIG. 1, the wireless microphone transmitter **100** transmits the first data to the receiver **200** in a data transmission period when operating in the first mode, and the receiver **200** receives the first data to the receiver **200** from the wireless microphone transmitter **100** in the data transmission period when operating in the third mode.

(18) Referring to FIG. 3 in conjunction with FIG. 1, when the receiver **200** receives a mode switch command from a user (e.g., the photographer B) while operating in the third mode, the receiver **200** transmits a first mode switch request message to the wireless microphone transmitter **100** in a reception waiting period. Then, the receiver **200** switches to the fourth mode and operates. When operating in the fourth mode, the receiver **200** transmits the second data to the wireless microphone transmitter **100** in a data transmission period.

(19) In response to receiving the first mode switch request message from the receiver **200**, the wireless microphone transmitter **100** switches to the second mode and operates. When operating in the second mode, the wireless microphone transmitter **100** receives the second data from the receiver **200** in a data transmission period.

(20) Referring to FIG. 4 in conjunction with FIG. 1, when the receiver **200** receives a mode switch command from a user (e.g., the photographer B) while operating in the fourth mode, the receiver **200** transmits a second mode switch request message to the wireless microphone transmitter **100** in a reception waiting period. Then, the receiver **200** switches back to the third mode and operates. That is, the receiver **200** receives the first data from the wireless microphone transmitter **100** in the data transmission period.

(21) In response to receiving the second mode switch request message from the receiver **200**, the wireless microphone transmitter **100** switches back to the first mode and operates. That is, the wireless microphone transmitter **100** transmits the first data to the receiver **200** in the data transmission period.

(22) When the wireless microphone transmitter **100** operates in the first mode and the receiver **200** operates in the third mode, voice of the person A to be photographed or the surrounding sound of the person A may be transmitted from the wireless microphone transmitter **100** to the receiver **200** and output through the audio output unit of the receiver **200** or recorded in the camera C.

(23) When the photographer B intends to transmit voice, such as coaching, questions, comments, etc., to the person A to be photographed or to record his/her own voice while the wireless microphone transmitter **100** is operating in the first mode and the receiver **200** is operating in the third mode, the photographer B inputs a mode switch command to the receiver **200**. Then, the wireless microphone transmitter **100** may operate in the second mode and the receiver **200** may operate in the fourth mode so that the voice of the person A to be photographed is transmitted to the wireless microphone transmitter **100** from the receiver **200** and thereby output through the audio

output unit of the wireless microphone transmitter **100** or recorded in the camera C.

(24) When the photographer B intends to finish transmitting the voice, the photographer B inputs a mode switch command again to the receiver **200**. Then, the wireless microphone transmitter **100** operates again in the first mode and the receiver **200** operates again in the third mode.

(25) FIG. 5 is a flowchart illustrating an operation of the wireless microphone transmitter **100** according to an embodiment of the present invention.

(26) When the power of the wireless microphone transmitter **100** is turned on (S210), the wireless microphone transmitter **100** operates in the first mode by default (S220). In the first mode, the wireless microphone transmitter **100** receives an audio signal through the audio input unit (S230) and transmits first data that corresponds to the input audio signal to the receiver **200** in a data transmission period (S240).

(27) When receiving a first mode switch request message while operating in the first mode (S250), the wireless microphone transmitter **100** switches to the second mode and operates (S260). In the second mode, the wireless microphone transmitter **100** receives second data from the receiver **200** in a data transmission period (S270) and outputs an audio signal that corresponds to the received second data through the audio output unit (S280).

(28) When receiving a second mode switch request message while operating in the second mode (S290), the wireless microphone transmitter **100** operates again in the first mode (S220).

(29) FIG. 6 is a flowchart illustrating an operation of the receiver **200** according to an embodiment of the present invention.

(30) When the power of the receiver **200** is turned on (S310), the receiver **200** operates in the third mode by default (S320). In the third mode, the receiver **200** receives the first data from the wireless microphone transmitter **100** in a data transmission period (S330) and outputs an audio signal that corresponds to the received first data through the audio output unit (S340).

(31) When receiving a mode switch command while operating in the third mode (S350), the receiver **200** transmits the first mode switch request message to the wireless microphone transmitter **100** in a reception waiting period (S355), switches to the fourth mode and operates (S360). In the fourth mode, the receiver **200** receives an audio signal through the audio input unit (S370) and transmits the second data that corresponds to the input audio signal to the wireless microphone transmitter **100** in a data transmission period (S380).

(32) When receiving a mode switch command while operating in the fourth mode (S390), the receiver **200** transmits the second mode switch request message to the wireless microphone transmitter **100** in a reception waiting period (S395) and operates again in the third mode (S320).

(33) FIG. 7 illustrates a configuration of the wireless microphone transmitter **100** according to an embodiment of the present invention.

(34) The wireless microphone transmitter **100** may include an audio input unit **110**, an analog-to-digital (AD) converter **120**, an audio output unit **130**, a digital-to-analog (DA) converter **140**, a control unit **150**, an antenna **160**, a user interface **170**, and a power supply unit **180**.

(35) The audio input unit **110** receives an audio signal. The audio input unit **110** may be a built-in microphone or an input terminal of an external microphone.

(36) The AD converter **120** converts the input audio signal into a digital signal and outputs the digital signal as first data.

(37) The DA converter **140** converts second data from the control unit **150** into an analog signal and outputs the analog signal.

(38) The audio output unit **130** outputs a signal from the DA converter **140** as an audio signal. The audio output unit **130** may be a built-in speaker or an input terminal of an external speaker (or earphones).

(39) The antenna **160** transmits and receives data to and from the receiver **200**.

(40) In the first mode, the control unit **150** transmits the first data from the AD converter **120** through the antenna **160** in a data transmission period. In the second mode, the control unit **150**

receives the second data from the receiver **200** through the antenna **160** in the data transmission period and provides the second data to the DA converter **140**. The control unit **150** receives a first mode switch request message or a second mode switch request message from the receiver **200** in a reception waiting period. The control unit **150** controls switching from the first mode to the second mode in response to the first mode switch request message, and controls switching from the second mode to the first mode in response to the second mode switch request message.

(41) The user interface **170** provides buttons for power on/off, volume control, etc., and displays an operating state.

(42) The power supply unit **180** provides power for the operation of the wireless microphone transmitter **100**.

(43) FIG. **8** illustrates a configuration of the receiver **200** according to an embodiment of the present invention.

(44) The receiver **200** may include an audio input unit **210**, an AD converter **220**, an audio output unit **230**, a DA converter **240**, a controller **250**, an antenna **260**, a user interface **270**, and a power supply unit **280**.

(45) The audio input unit **210** receives an audio signal. The audio input unit **210** may be a built-in microphone or an input terminal of an external microphone.

(46) The AD converter **220** converts the input audio signal into a digital signal and outputs the digital signal as second data.

(47) The DA converter **240** converts first data from the control unit **250** into an analog signal and outputs the analog signal.

(48) The audio output unit **230** outputs a signal from the DA converter **240** as an audio signal. The audio output unit **230** may be a built-in speaker or an input terminal of an external speaker (or earphones).

(49) The antenna **260** transmits and receives data to and from the wireless microphone transmitter **100**.

(50) In the third mode, the control unit **250** receives the first data from the wireless microphone transmitter **100** through the antenna **260** in a data transmission period and provides the first data to the DA converter **240**. In the fourth mode, the control unit **250** transmits the second data from the AD converter **220** through the antenna **260** in the data transmission period. Upon receiving a mode switch command in the third mode, the control unit **250** transmits a first mode switch request message through the antenna **260** in a reception waiting period, and upon receiving a mode switch command in the fourth mode, the control unit **250** transmits a second mode switch request message through the antenna **260** in the reception waiting period. The control unit **250** controls switching from the third mode to the fourth mode in response to the mode switch command in the third mode, and controls switching to the third mode in response to the mode switch command in the fourth mode.

(51) The user interface **270** provides buttons for power on/off, volume control, etc., and displays an operating state. The user interface **270** includes a mode switch button **272** for inputting a mode switch command from the user. The mode switch button **272** may be a toggle button or a push button. In the case of a toggle button, the mode may be switched (i.e., from the third mode to the fourth mode or from the fourth mode to the third mode) each time the button is pressed. In the case of a push button, the receiver **200** operates in the third mode when the button is not pressed, and operates in the fourth mode while the button is pressed.

(52) The power supply unit **280** provides power for the operation of the receiver **200**.

(53) In some embodiments, the wireless microphone transmitter **100** and the receiver **200** may be implemented in a single device, which may be selectively operable as one of the wireless microphone transmitter **100** and the receiver **200** according to the user setting. In this case, the function of the control unit **150** and the function of the control unit **250** may be implemented in a single control unit, which may be selectively operable according to the user setting, and the

function of the user interface **170** and the function of the user interface **270** may be implemented in a single user interface, which may be selectively operable according to the user setting.

(54) FIG. **9** illustrates a configuration of a wireless microphone system according to another embodiment of the present invention.

(55) A wireless microphone system according to the present embodiment includes a wireless microphone transmitter **100** and a plurality of receivers **200_1**, . . . , **200_n**, . . . , and **200_N** (where N is a natural number greater than or equal to 2 and n is a natural number ($1 \leq n \leq N$)). The plurality of receivers **200_1**, . . . , **200_n**, . . . , and **200_N** may be mounted in a plurality of cameras **C_1**, . . . , **C_n**, . . . , and **C_N** of a plurality of photographers **B_1**, . . . , **B_n**, . . . , and **B_N**, respectively.

(56) When operating in a first mode, the wireless microphone transmitter **100** transmits first data to the plurality of receivers **200_1**, . . . , **200_n**, . . . , and **200_N** in a data transmission period. When operating in a third mode, each of the receivers **200_1**, . . . , **200_n**, . . . , and **200_N** receives the first data from the wireless microphone transmitter **100** in the data transmission period.

Accordingly, the voice of a person **A** to be photographed can be transmitted to the plurality of photographers **B_1**, . . . , **B_n**, . . . , and **B_N**.

(57) When any one receiver **200_n** of the plurality of receivers **200_1**, . . . , **200_n**, . . . , and **200_N** receives a mode switch command from the photographer **B_n** in the third mode, the receiver **200_n** transmits a first mode switch request message in a reception waiting period, switches to a fourth mode, and transmits second data in a data transmission period. The remaining receivers **200_1**, . . . , **200_n-1**, **200_n+1**, . . . , and **200_N** that have received the first mode switch request message receive the second data from the receiver **200_n** in the data transmission period. Accordingly, the voice of the photographer **B_n** can be transmitted not only to the person **A** to be photographed but also to the other photographers **B_1**, . . . , **B_n-1**, **B_n+1**, . . . , and **B_N**.

(58) FIG. **10** illustrates a configuration of a wireless microphone system according to still another embodiment of the present invention.

(59) A wireless microphone system according to the present embodiment includes a plurality of wireless microphone transmitters **100_1**, . . . , **100_m**, . . . , and **100_M** (where M is a natural number greater than or equal to 2 and m is a natural number ($1 \leq m \leq M$)) and a plurality of receivers **200_1**, . . . , **200_n**, . . . , and **200_N** (where N is a natural number greater than or equal to 2 and n is a natural number ($1 \leq n \leq N$)). The plurality of wireless microphone transmitters **100_1**, . . . , **100_m**, . . . , and **100_M** may be carried by a plurality of persons **A_1**, . . . , **A_n**, . . . , and **A_M** to be photographed, respectively, and the plurality of receivers **200_1**, . . . , **200_n**, . . . , and **200_N** may be mounted in a plurality of cameras **C_1**, . . . , **C_n**, . . . , and **C_N** of a plurality of photographers **B_1**, . . . , **B_n**, . . . , and **B_N**, respectively.

(60) When operating in a first mode, the plurality of wireless microphone transmitters **100_1**, . . . , **100_m**, . . . , and **100_M** transmit first data to the plurality of receivers **200_1**, . . . , **200_n**, . . . , and **200_N**, respectively, in a data transmission period. When operating in a third mode, the plurality of receivers **200_1**, . . . , **200_n**, . . . , and **200_N** receive the first data from the plurality of wireless microphone transmitters **100_1**, . . . , **100_m**, . . . , and **100_M**, respectively, in the data transmission period. Accordingly, the voice of the plurality of persons **A_1**, . . . , **A_n**, . . . , and **A_M** to be photographed can be transmitted to the plurality of photographers **B_1**, . . . , **B_n**, . . . , and **B_N**.

(61) When any one receiver **200_n** of the plurality of receivers **200_1**, . . . , **200_n**, . . . , and **200_N** receives a mode switch command from the photographer **B_n** in the third mode, the receiver **200_n** transmits a first mode switch request message in a reception waiting period, switches to a fourth mode, and transmits second data in a data transmission period. The plurality of wireless microphone transmitters **100_1**, . . . , **100_m**, . . . , and **100_M** that have received the first mode switch request message switch to a second mode, and receive the second data from the receiver **200_n** in the data transmission period. The remaining receivers **200_1**, . . . , **200_n-1**, **200_n+1**, . . . , and **200_N** that have received the first mode switch request message receive the second data from

the receiver **200_n** in the data transmission period. Accordingly, the voice of the photographer **B_n** can be transmitted to the plurality of persons **A₁, . . . , A_n, . . . , and A_M** to be photographed and the other photographers **B₁, . . . , B_{n-1}, B_{n+1}, . . . , and B_N**.

(62) Meanwhile, one or more embodiments of the present invention can be written as computer programs and can be implemented in general-use digital computers that execute the programs using a computer readable recording medium. Examples of the computer readable recording medium include storage media such as magnetic storage media (e.g. ROM, floppy disks, hard disks, etc.) and optical recording media (e.g. CD-ROMs, or DVDs).

(63) One or more embodiments of the present invention may be described in terms of functional block components and various processing steps. Such functional blocks may be realized by any number of hardware and/or software components configured to perform the specified functions. For example, one or more embodiments may employ various integrated circuit (IC) components, e.g., memory elements, processing elements, logic elements, look-up tables, and the like, which may carry out a variety of functions under the control of one or more microprocessors or other control devices. Similarly, where the elements are implemented using software programming or software elements, the embodiments may be implemented with any programming or scripting language such as C, C++, Java, assembler language, or the like, with the various algorithms being implemented with any combination of data structures, processes, routines or other programming elements. Functional aspects may be implemented in algorithms that are executed on one or more processors. Furthermore, one or more embodiments could employ any number of techniques according to the related art for electronics configuration, signal processing and/or control, data processing and the like. The words “mechanism,” “element,” “means,” and “configuration” are used broadly and are not limited to mechanical or physical embodiments of the disclosure. The terms may include software routines in conjunction with processors, etc.

(64) The particular implementations shown and described herein are illustrative examples of the inventive concept and are not intended to otherwise limit the scope of the disclosure in any way. For the sake of brevity, electronics, control systems, software development and other functional aspects of the systems according to the related art may not be described in detail. Furthermore, the connecting lines, or connectors shown in the various figures presented are intended to represent exemplary functional relationships and/or physical or logical couplings between the various elements. It should be noted that many alternative or additional functional relationships, physical connections or logical connections may be present in a practical apparatus. Moreover, no item or component is essential to the practice of the inventive concept unless the element is specifically described as “essential” or “critical.”

(65) Various embodiments are described with reference to the accompanying drawings. However, the scope of the disclosure is not intended to be limited to the particular embodiments, and it is to be understood that the disclosure covers various modifications, equivalents, and/or alternatives falling within the scope and spirit of the disclosure. Therefore, the above-described embodiments should be understood from an illustrative perspective, not from a restrictive perspective. The scope of the disclosure is apparent from the claims, rather than from the detailed description of the disclosure, and the meaning and scope of the claims and all modifications or variations derived from their equivalent concept should be interpreted as falling within the scope of the disclosure.

Claims

1. A wireless microphone system comprising: a wireless microphone transmitter; and a receiver, wherein: the wireless microphone transmitter is configured to operate in one of a first mode for transmitting first data, which is input through an audio input unit of the wireless microphone transmitter, to the receiver and a second mode for receiving second data from the receiver, the receiver is configured to operate in one of a third mode for receiving the first data from the wireless

microphone transmitter and a fourth mode for transmitting the second data, which is input through an audio input unit of the receiver, to the wireless microphone transmitter, the wireless microphone transmitter transmits the first data in a data transmission period when operating in the first mode in a time structure in which the data transmission period and a reception waiting period are alternately repeated, the receiver receives the first data in the data transmission period when operating in the third mode, transmits a first mode switch request message to the wireless microphone transmitter in the reception waiting period, switches to the fourth mode, and operates upon receiving a mode switch command in the third mode, and transmits the second data in the data transmission period when operating in the fourth mode, the wireless microphone transmitter switches to the second mode and operates upon receiving the first mode switch request message and receives the second data in the data transmission period when operating in the second mode, the receiver transmits a second mode switch request message to the wireless microphone transmitter in the reception waiting period, switches to the third mode, and operates upon receiving a mode switch command in the fourth mode, and the wireless microphone transmitter switches to the first mode and operates upon receiving the second mode switch request message.

2. The wireless microphone system of claim 1, wherein the receiver is provided with a mode switch button for receiving the mode switch command in the third mode and the mode switch command in the fourth mode from a user.

3. The wireless microphone system of claim 1, wherein the wireless microphone transmitter is configured to operate in the first mode by default and the receiver is configured to operate in the third mode by default.

4. The wireless microphone system of claim 1, wherein the wireless microphone transmitter comprises: an antenna; an audio input unit configured to receive an audio signal; an analog-to-digital (AD) converter configured to convert the audio signal into a digital signal and output the digital signal as the first data; a digital-to-analog (DA) converter configured to convert the second data into an analog signal and output the analog signal; an audio output unit configured to output a signal from the DA converter as an audio signal; and a control unit configured to transmit the first data through the antenna in the data transmission period in the first mode, receive the second data through the antenna in the data transmission period in the second mode, receive the first mode switch request message or the second mode switch request message in the reception waiting period, control switching from the first mode to the second mode in response to the first mode switch request message, and control switching from the second mode to the first mode in response to the second mode switch request message.

5. The wireless microphone system of claim 1, wherein the receiver comprises: an antenna; an audio input unit configured to receive an audio signal; an AD converter configured to convert the audio signal into a digital signal and output the digital signal as the second data; a DA converter configured to convert the first data into an analog signal and output the analog signal; an audio output unit configured to output a signal from the DA converter as an audio signal; a mode switch button configured to receive the mode switch command in the third mode and the mode switch command in the fourth mode; and a control unit configured to transmit the first data through the antenna in the data transmission period in the third mode, receive the second data through the antenna in the data transmission period in the fourth mode, transmit the first mode switch request message through the antenna in the reception waiting period upon receiving the mode switch command in the third mode, transmit the second mode switch request message through the antenna in the reception waiting period upon receiving the mode switch command in the fourth mode, control switching to the fourth mode in response to the mode switch command in the third mode, and control switching to the third mode in response to the mode switch command in the fourth mode.

6. The wireless microphone system of claim 1, wherein, when a plurality of receivers are provided and any one of the receivers transmits the first mode switch request message in the reception

waiting period, switches to the fourth mode, and transmits the second data in the data transmission period, the remaining receivers that have received the first mode request message receives the second data in the data transmission period.

7. The wireless microphone system of claim 1, wherein, when a plurality of wireless microphone transmitters are provided, a plurality of receivers are provided, and any one of the receivers transmits the first mode switch request message in the reception waiting period, switches to the fourth mode, and transmits the second data in the data transmission period, the plurality of wireless microphone transmitters that have received the first mode switch request message switch to the second mode and operate and the remaining receivers that have received the first mode switch request message receive the second data in the data transmission period.
