

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408540
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Wu; Jiejie et al.

Display device and method for preparing same

Abstract

Embodiments of the present disclosure provide a display device and a method for preparing same. According to the display device provided in the embodiments of the present disclosure, a groove is provided in a second non-display area of a packaging cover plate, and a light-shielding layer is disposed in the groove. The light-shielding layer can shield metal traces in a first non-display area of a display panel. In this way, a problem of reflection of the metal traces in the first non-display area of the display panel is resolved, thereby enhancing visual perception and an all-black effect of the display panel.

Inventors:	Wu; Jiejie (Huizhou, CN), Jiang; Liuxi (Huizhou, CN)
Applicant:	HUIZHOU CHINA STAR OPTOELECTRONICS DISPLAY CO., LTD (Huizhou, CN); SHENZHEN CHINA STAR OPTOELECTRONICS SEMICONDUCTOR DISPLAY TECHNOLOGY CO., LTD. (Shenzhen, CN)
Family ID:	78164831
Appl. No.:	17/599574
Filed (or PCT Filed):	July 22, 2021
PCT No.:	PCT/CN2021/107948
PCT Pub. No.:	WO2023/283990
PCT Pub. Date:	January 19, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240032407 A1	Jan. 25, 2024

Foreign Application Priority Data

CN

202110795166.7

Jul. 14, 2021

Publication Classification

Int. Cl.: H10K59/80 (20230101); H10K59/12 (20230101); H10K102/00 (20230101)

U.S. Cl.:

CPC H10K59/8792 (20230201); H10K59/1201 (20230201); H10K59/872 (20230201);
H10K2102/351 (20230201)

Field of Classification Search

CPC: H01L (29/78633); H01L (27/3272); H10K (50/86); H10K (59/8792)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2002/0093284	12/2001	Adachi	313/506	H10K 59/8791
2004/0080267	12/2003	Cok	313/512	G06F 3/0412
2005/0019585	12/2004	Kashiwagi	428/917	H10K 50/844
2010/0033660	12/2009	Yamada	N/A	N/A
2021/0257583	12/2020	Park	N/A	H10K 50/87
2021/0408454	12/2020	He	N/A	H10K 59/88

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
204480220	12/2014	CN	N/A
208061170	12/2017	CN	N/A
107393907	12/2018	CN	H01L 23/60
111367117	12/2019	CN	N/A
111445790	12/2019	CN	N/A
111766977	12/2019	CN	N/A
112002223	12/2019	CN	N/A
212967755	12/2020	CN	N/A
112820839	12/2020	CN	N/A
2016224220	12/2015	JP	N/A

OTHER PUBLICATIONS

Sumerel, "Ink Jet Printing Adhesives", 2006 (Year: 2006). cited by examiner

Primary Examiner: Hanley; Britt D

Assistant Examiner: Boatman; Casey Paul

Background/Summary

FIELD OF INVENTION

(1) The present disclosure relates to the field of display technologies, and in particular, to a display device and a method for preparing same.

BACKGROUND OF INVENTION

(2) An organic light-emitting diode (OLED) display panel is a display panel made using an organic light-emitting diode. The OLED display panel is considered as an emerging application technology of a flat panel display of the next generation due to its excellent characteristics such as no need for backlight, high contrast, a small thickness, a wide viewing angle, a fast response speed, a wide range of application temperatures, a simple structure and process, and the like.

SUMMARY OF INVENTION

Technical Problem

(3) An OLED display panel includes a rigid OLED display panel and a flexible OLED display panel. At present, the rigid OLED display panel mostly adopts transparent glass to package a device layer to achieve an effect of blocking oxygen and water vapor. However, since the glass is transparent, metal traces on a bottom array base plate (that is, a thin film transistor **20** array base plate) can be obviously seen in a non-display area of the display panel. The metal traces are still visible to naked eyes even after a polarizer is attached, and especially light can be reflected in an environment with strong natural light, which seriously affects an appearance display effect and an all-black effect of the OLED display panel.

Technical Solution

(4) Embodiments of the present disclosure provide a display device and a method for preparing same. In this way, a problem of reflection of metal traces in a non-display area of a display panel can be resolved, thereby enhancing visual perception and an all-black effect of the display panel.

(5) The embodiment of the present disclosure provides a display device. The display device includes a display panel and a packaging cover plate that are disposed opposite to each other. The display panel includes a first display area and a first non-display area disposed on a periphery of the first display area. The packaging cover plate includes a second display area and a second non-display area disposed on a periphery of the second display area. The first display area corresponds to the second display area, and the first non-display area corresponds to the second non-display area. A groove is provided in the second non-display area, and a light-shielding layer is disposed in the groove.

Beneficial Effects

(6) According to the display device provided in the embodiments of the present disclosure, a groove is provided in a second non-display area of a packaging cover plate, and a light-shielding layer is disposed in the groove. The light-shielding layer can shield metal traces in a first non-display area of a display panel. In this way, a problem of reflection of the metal traces in the first non-display area of the display panel is resolved, thereby enhancing visual perception and an all-black effect of the display panel.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) To describe the technical solutions in the embodiments of the present disclosure more clearly, the following briefly describes the accompanying drawings required for describing the embodiments. Obviously, the accompanying drawings in the following descriptions are merely some embodiments of the present disclosure, and a person of ordinary skill in the art can further

obtain other accompanying drawings according to the accompanying drawings without creative efforts.

(2) For a more complete understanding of the present disclosure and beneficial effects thereof, the present disclosure is described below with reference to the accompanying drawings. In the following descriptions, same parts are denoted by same reference numerals.

(3) FIG. 1 is a schematic diagram of a first structure of a display device according to an embodiment of the present disclosure.

(4) FIG. 2 is a schematic top view of a packaging cover plate according to an embodiment of the present disclosure.

(5) FIG. 3 is a schematic diagram of a cross-sectional structure of a packaging cover plate taken along direction A-A of FIG. 2.

(6) FIG. 4 is a schematic diagram of a second structure of a display device according to an embodiment of the present disclosure.

(7) FIG. 5 is a flowchart of a method for preparing a display device according to an embodiment of the present disclosure.

(8) FIG. 6 is a schematic plan view of each process of the preparation method in FIG. 5.

(9) FIG. 7 is a schematic cross-sectional view of each process of the preparation method in FIG. 5.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

(10) The technical solutions of the embodiments of the present disclosure are clearly and completely described in the following with reference to the accompanying drawings of the embodiments of the present disclosure. Apparently, the described embodiments are merely some but not all of the embodiments of the present disclosure. All other embodiments obtained by a person skilled in the art based on the embodiments of the present disclosure without creative efforts shall fall within the protection scope of the present disclosure.

(11) An embodiment of the present disclosure provides a display device. Referring to FIGS. 1 to 3, FIG. 1 is a schematic diagram of a first structure of a display device according to an embodiment of the present disclosure, FIG. 2 is a schematic top view of a packaging cover plate according to an embodiment of the present disclosure, and FIG. 3 is a schematic cross-sectional view of the packaging cover plate according to an embodiment of the present disclosure. The display device **100** includes a display panel **120** and a packaging cover plate **110** that are disposed opposite to each other. The display panel **120** includes a first display area **21** and a first non-display area **22** disposed on a periphery of the first display area **21**. The packaging cover plate includes a second display area **11** and a second non-display area **12** disposed on a periphery of the second display area **11**. The first display area **21** corresponds to the second display area **11**, and the first non-display area **22** corresponds to the second non-display area **12**. A groove **121** is provided in the second non-display area, and a light-shielding layer **122** is disposed in the groove **121**.

(12) It can be understood that, the packaging cover plate **110** is configured to package the display panel **120** to isolate water, oxygen, and dust, thereby prolonging a service life of the display panel **120**.

(13) For example, the display device **100** can be a tablet computer, a notebook computer, a display, a television, and the like.

(14) The display panel **120** can be an OLED display panel. For example, the display panel **120** can be a rigid OLED display panel, and a substrate of the rigid OLED display panel is generally a glass base plate and is hard to bend. For example, the display panel **120** can also be a flexible OLED display panel. The flexible OLED display panel usually refers to a bendable and foldable display panel with good flexibility, and a substrate of the flexible OLED display panel is generally a plastic base plate.

(15) Metal traces are usually disposed in the first non-display area **22** of the display panel **120**. Therefore, there is a problem of reflection of the metal traces. According to the display device **100** provided in the embodiment of the present disclosure, the groove **121** is provided in the second

non-display area **12** of the packaging cover plate **110**, and the light-shielding layer **122** is disposed in the groove **121**, so that the light-shielding layer **122** in the packaging cover plate **110** can effectively shield the metal traces in the first non-display area **22** of the display panel **120**. In this way, the problem of the reflection of the metal traces in the first non-display area **22** can be resolved, thereby enhancing visual perception and an all-black effect of the display panel **120**.

(16) In the related art, in order to resolve the problem of the reflection of the metal traces on the periphery of the display area of the OLED display panel, a solution of a silk-screen printing or transfer printing black frame can be mostly adopted for a small-size OLED. That is, a circle of black ink is printed on a surface of the packaging cover plate using a silk-screen printing or transfer printing method, so as to cover the metal traces on the periphery of the display area. For a medium and large OLED, since a minimum size of the display panel is more than ten inches and a maximum size is more than a hundred inches, silk-screen printing has numerous disadvantages that a halftone of a corresponding size requires to be additionally designed and has a short lifespan, ink is mostly solvent-based ink, curing and ink layer thinning are realized by means of self-volatilization or volatilization of a solvent by baking, overall process efficiency is low, and the silk-screen printing is unfriendly to the environment. Therefore, it is necessary to adopt an ink-jet printing method to print a circle of black ink and perform curing by means of irradiation using ultraviolet light. However, the ink-jet printing method also has a plurality of problems, including the following. 1) An ultra-thin ink layer is required, otherwise a step can be formed between the ink layer and the packaging cover plate, which is bad for attachment of a polarizer, and easily causes problems of bubbles generated between the polarizer and the packaging cover plate. 2) The ink layer is required to have high adhesion, otherwise it can easily fall off the packaging cover plate. It can be seen that, the method of directly spraying and printing the black ink on the packaging cover plate has strict requirements for ink selection, devices, and processes, causing an increase in costs of materials, devices, and processes. According to the embodiment of the present disclosure, a groove **121** is provided on a packaging cover plate **110**, a light-shielding layer **122** is disposed in the groove **121**. As a result, technical effects can be achieved as follows. (1) A thickness of the light-shielding layer **122** can be controlled, so that the surface of the packaging cover plate **110** remains flat, which is conducive to attachment of a polarizer **40**, thereby avoiding bubbles generated between the polarizer **40** and the packaging cover plate **110** after attachment. (2) Since the light-shielding layer **122** is disposed in the groove **121** and has a relatively low requirement for adhesion of the light-shielding layer **122**, the light-shielding layer **122** is not easy to fall off the groove **121**. (3) Due to the presence of the groove **121**, the thickness of the light-shielding layer **122** can be properly increased to enhance light-shielding performance of the light-shielding layer **122**. In the prior art, the method of spraying and printing black ink is to maintain the flatness of the surface of the packaging cover plate **110**, and the thickness of an ink layer cannot be too thick. Therefore, the light-shield performance of the ink layer is relatively poor. (4) The solutions of the present disclosure have relatively low requirements for materials, devices, and accuracy of processes, so that process costs are relatively low. (5) A selection range of the light-shielding layer **122** (such as ink or glue) and devices is widened, so as to ensure the safety of supply chains of materials and devices.

(17) For example, a material of the packaging cover plate **110** is glass.

(18) For example, a color of the light-shielding layer **122** is black to achieve a better shielding effect, thereby enhancing an all-black effect of the display device **100**.

(19) Referring to FIG. 2, the groove **121** can be provided around the second display area **11** to form a closed-loop structure. For example, the groove **121** can be in a rectangular shape.

(20) For example, an absolute value of a height difference between a top surface of the light-shielding layer **122** and a surface of a side of the packaging cover plate **110** on which the groove **121** is provided is less than 5 μm . For example, an absolute value of a height difference between a top surface of the light-shielding layer **122** and a surface of a side of the packaging cover plate **110**

on which the groove **121** is provided can be 4 μm , 3 μm , 2 μm , 1 μm , or 0 μm . Preferably, the height difference between the top surface of the light-shielding layer **122** and a surface of a side of the packaging cover plate **110** on which the groove **121** is provided is 0. That is, the top surface of the light-shielding layer **122** is flush with the surface of the side of the packaging cover plate **110** on which the groove **121** is provided, which facilitates the attachment of the polarizer **40**.

According to the embodiment of the present disclosure, the groove **121** is provided on the packaging cover plate **110**, and the light-shielding layer **122** is disposed in the groove **121**, so as to improve the flatness of the surface of the packaging cover plate **110**, facilitate the attachment of the polarizer **40**, and improve an attachment effect. In this way, bubbles are not easily generated between the polarizer **40** and the packaging cover plate **110** after attachment.

(21) For example, a thickness (H) of the packaging cover plate **110** can be in a range of 100 μm to 1000 μm , and a ratio of a depth (h) of the groove **121** to the thickness (H) of the packaging cover plate **110** can be in a range of 0.01 to 0.1. That is, $0.01 H \leq h \leq 0.1 H$. However, in order to guarantee the strength of the packaging cover plate **110**, when the thickness (H) of the packaging cover plate **110** is in the range of 500 μm to 1000 μm , the depth (h) of the groove **121** is preferably in the range of 5 μm to 30 μm . When the thickness (H) of the packaging cover plate **110** is in the range of 100 μm to 500 μm , the depth (h) of the groove **121** is preferably in the range of 5 μm to 10 μm .

(22) For example, the distance between the groove **121** and the second display area **11** can be in a range of 100 μm to 400 μm , preferably 100 μm to 200 μm .

(23) For example, the distance between the groove **121** and the outer edge of the second non-display area **12** can be in a range of 100 μm to 200 μm , preferably 100 μm to 150 μm .

(24) For example, the width of the groove **121** can be in a range of 5 mm to 10 mm.

(25) It can be understood that, when the absolute value of the height difference between the top surface of the light-shielding layer **122** and the surface of the side of the packaging cover plate **110** on which the groove **121** is provided is not 0, the top surface of the light-shielding layer **122** can be higher than the surface of the side of the packaging cover plate **110** on which the groove **121** is provided, or can be lower than the surface of the side of the packaging cover plate **110** on which the groove **121** is provided.

(26) For example, the material of the light-shielding layer **122** can be ink or glue. Preferably, the ink is black, and the glue is black.

(27) With reference to FIG. 7, the first non-display area **22** of the display panel **120** can be sealingly connected to the second non-display area **12** of the packaging cover plate **110** using a frame sealing adhesive **30**, so as to form a sealed space, thereby preventing an OLED device **211** located in the first display area **21** from being corroded by water, oxygen, and the like.

(28) Referring to FIG. 1, the display device **100** further includes a polarizer **40**. The polarizer **40** is disposed on a side of the packaging cover plate **110** that is away from the display panel **120**. For example, the polarizer **40** is a circular polarizer.

(29) Referring to FIG. 4, FIG. 4 is a schematic diagram of a second structure of a display device according to an embodiment of the present disclosure. Compared with the display device **100** shown in FIG. 1, in the display device **100** shown in FIG. 4, a thin film encapsulation layer **51** can be further disposed on an outer surface of the OLED device **211** to further isolate water and oxygen. A desiccant **52** can further be disposed in an area formed by the frame sealing adhesive **30** on the display panel **120**. The desiccant **52** is disposed on a periphery of the OLED device **211**. In addition, filling glue **53** can be further disposed in a sealed space formed by the packaging cover plate **110**, the display panel **120**, and the frame sealing adhesive **30** in the display device **100**. The filling glue **53** covers the OLED device **211** encapsulated by the thin film encapsulation layer **51** and the desiccant **52** and fills the whole sealed space. In this way, the water and oxygen can be further isolated, and the service life of the OLED device **211** can be prolonged.

(30) An embodiment of the present disclosure further provides a method for preparing a display device. The display device can be the display device **100** described in any above embodiment.

Referring to FIGS. 5 to 7, FIG. 5 is a flowchart of the method for preparing the display device according to an embodiment of the present disclosure, FIG. 6 is a schematic plan view of each process of the preparation method in FIG. 5, and FIG. 7 is a schematic cross-sectional view of each process of the preparation method in FIG. 5. The method for preparing a display device can include steps as follows.

(31) **S100**: Provide a cover plate body **10**, wherein the cover plate body **10** has a second display area **11** and a second non-display area **12**.

(32) For example, a material of the cover plate body **10** is glass.

(33) **S200**: Form a groove **121** in the second non-display area **12** of the cover plate body **10**.

(34) When the material of the cover plate body **10** is glass, the forming a groove **121** in the second non-display area **12** of the cover plate body **10** can include in detail: etching the cover plate body **10**, so as to form a groove **121** in the second non-display area **12** of the cover plate body **10**.

(35) **S300**: Dispose a light-shielding layer **122** in the groove **121** to obtain a packaging cover plate **110**.

(36) In some embodiments, the disposing a light-shielding layer **122** in the groove **121** can include: applying glue in the groove **121** using a glue dispenser.

(37) For example, the glue dispenser can be a piezoelectric ceramic injection valve glue dispenser. A glue dispensing speed is in a range of 50 mm/s to 200 mm/s, and a viscosity of the glue is less than 10000 mPa·s (25° C.).

(38) The glue can be selected from either a single type of black glue or two or more types of glue. For example, the glue can be a combination of the black glue and the glue in other colors or a combination of the black glue and transparent glue. In some embodiments, the glue (can be colorless transparent glue, black glue, or glue in other colors) that can improve the surface property of the groove **121** can be first applied at the bottom of the groove **121**, so as to enhance the adhesion of the surface of the groove **121**, and then the black glue is applied in the groove **121** to achieve a light-shielding effect.

(39) In some embodiments, the material of the light-shielding layer **122** is glue. The light-shielding layer **122** is disposed in the groove **121**. A step of curing the light-shielding layer **122** is further provided. The method of curing is preferably curing by means of irradiation using ultraviolet light. A wave length of the ultraviolet light is in a range of 335 nm to 400 nm, and energy of the ultraviolet light is in a range of 1000 mJ/cm² to 10000 mJ/cm². The method of curing can further be moisture curing (20° C. to 25° C., 50% RH to 70% RH) or heat curing (40° C. to 100° C.). A height difference between a surface of a glue layer formed after glue curing and the surface of the cover plate body **10** is less than 5 μm. For example, the height difference between the surface of the glue layer and the surface of the cover plate body **10** is 4 μm, 3 μm, 2 μm, 1 μm, or 0 μm.

(40) In some other embodiments, the disposing a light-shielding layer **122** in the groove **121** can include in detail: spraying ink in the groove **121** using an ink-jet printer.

(41) For example, the ink-jet printer can be a piezoelectric ceramic ink-jet printer, and a viscosity of the ink can be in a range of 10 mPa·s to 20 mPa·s (25° C.).

(42) The ink can be selected from either a single type of black ink or two or more types of ink. For example, the ink can be a combination of the black ink and the ink in other colors or a combination of the black ink and transparent ink. In some embodiments, the ink (can be colorless transparent ink, black ink, or ink in other colors) that can improve the surface property of the groove **121** can be first sprayed at the bottom of the groove **121**, so as to enhance the adhesion of the surface of the groove **121**, and then the black ink is sprayed in the groove **121** to achieve the light-shielding effect.

(43) The disposing a light-shielding layer **122** in the groove **121** to obtain a packaging cover plate **110** can include in detail: disposing the light-shielding layer **122** in the groove **121**, wherein a material of the light-shielding layer **122** is ink, and curing the light-shielding layer **122** to obtain the packaging cover plate **110**. The method of curing is preferably curing by means of irradiation using

ultraviolet light. A wave length of the ultraviolet light is in a range of 335 nm to 400 nm, and energy of the ultraviolet light is in a range of 500 mJ/cm.sup.2 to 5000 mJ/cm.sup.2. The method of curing can further be performing curing while printing, or performing curing after the ink is levelled. After curing, post-processing can be further performed on the ink. That is, baking and heating are performed on the cured ink at a temperature in a range of 40° C. to 100° C., so as to increase the adhesion between an ink layer and the cover plate body **10** and surface hardness of the ink layer. A height difference between the surface of the ink layer formed after curing of the ink and the surface of the cover plate body **10** is less than 5 μm. For example, the height difference between the surface of the ink layer and the surface of the cover plate body **10** is 4 μm, 3 μm, 2 μm, 1 μm, or 0 μm.

(44) **S400**: Provide a display panel **120**, and combine the packaging cover plate **110** with the display panel **120** to obtain the display device **100**.

(45) The display device **100** prepared using the above preparation method is shown in FIGS. **1** to **4**. Details will not be described herein again.

(46) It should be noted that, in FIG. **1**, FIG. **2**, FIG. **3**, FIG. **4**, FIG. **6**, and FIG. **7**, dashed lines are merely used to represent a boundary between the first display area **21** and the first non-display area **22** or a boundary between the second display area **11** and the second non-display area **12**. The lines are not present in an actual product.

(47) The display device and the method for preparing same provided in the embodiments of the present disclosure are described in detail above. The principles and implementations of the present disclosure are described by using specific examples in this specification, and the descriptions of the foregoing embodiments are merely used for helping understand the present disclosure. Meanwhile, a person of ordinary skill in the art can make modifications to the specific implementations and application range according to the ideas of the present disclosure. In conclusion, the content of the specification is not to be construed as a limitation to the present disclosure.

Claims

1. A display device, comprising a display panel and a packaging cover plate that are disposed opposite to each other, wherein the display panel comprises a first display area and a first non-display area disposed on a periphery of the first display area, the packaging cover plate comprises a second display area and a second non-display area disposed on a periphery of the second display area, the first display area corresponds to the second display area, the first non-display area corresponds to the second non-display area, a groove is provided in the second non-display area and is defined in a top surface of the packaging cover plate away from the display panel, and a light-shielding layer is disposed in the groove; wherein a top surface of the light-shielding layer is flush with the top surface of the packaging cover plate in which the groove is defined; wherein a polarizer is disposed on the top surface of the packaging cover plate and covers the groove such that the light-shielding layer in the groove is sandwiched and disposed securely between the packaging cover plate and the polarizer; wherein the groove has two opposite inner sidewalls and an inner bottom wall formed between the sidewalls, and the inner sidewalls and the inner bottom wall of the groove contact and cooperatively encompass the light-shielding layer; wherein the inner sidewalls and the inner bottom wall of the groove form a U-shaped cross-section, each of the inner sidewalls is a closed-loop structure, and the inner bottom wall is a closed-loop structure.

2. The display device as claimed in claim 1, wherein the display panel is an organic light-emitting diode (OLED) display panel.

3. The display device as claimed in claim 1, wherein the groove is provided around the second display area to form a closed-loop structure.

4. The display device as claimed in claim 1, wherein an absolute value of a height difference between a top surface of the light-shielding layer and a surface of a side of the groove provided on

the packaging cover plate is less than 5 μm .

5. The display device as claimed in claim 1, wherein a thickness of the packaging cover plate is in a range of 100 μm to 1000 μm , and a ratio of a depth of the groove to the thickness of the packaging cover plate is in a range of 0.01 to 0.1.

6. The display device as claimed in claim 1, wherein a distance between the groove and the second display area is in a range of 100 μm to 400 μm , and a distance between the groove and an outer edge of the second non-display area is in a range of 100 μm to 200 μm .

7. The display device as claimed in claim 1, wherein a thickness of the packaging cover plate is in a range of 500 μm to 1000 μm , and a depth of the groove is in a range of 5 μm to 30 μm .

8. The display device as claimed in claim 1, wherein a thickness of the packaging cover plate is in a range of 100 μm to 500 μm , and a depth of the groove is in a range of 5 μm to 10 μm .

9. The display device as claimed in claim 1, wherein a material of the light-shielding layer is ink or glue.

10. A method for preparing a display device, the display device being the display device as claimed in claim 1, wherein the preparation method comprises: providing a cover plate body, wherein the cover plate body has a second display area and a second non-display area; forming a groove in the second non-display area of the cover plate body, wherein the groove is defined in a top surface of the packaging cover plate away from the display panel; disposing a light-shielding layer in the groove to obtain a packaging cover plate, wherein a top surface of the light-shielding layer is flush with the top surface of the packaging cover plate in which the groove is defined; and providing a display panel, and combining the packaging cover plate with the display panel to obtain a display device; providing a polarizer, wherein the polarizer is disposed on the top surface of the packaging cover plate and covers the groove such that the light-shielding layer in the groove is sandwiched and disposed securely between the packaging cover plate and the polarizer, the groove has two opposite inner sidewalls and an inner bottom wall formed between the sidewalls, and the inner sidewalls and the inner bottom wall of the groove contact and cooperatively encompass the light-shielding layer; wherein the inner sidewalls and the inner bottom wall of the groove form a U-shaped cross-section, each of the inner sidewalls is a closed-loop structure, and the inner bottom wall is a closed-loop structure.

11. The method for preparing a display device as claimed in claim 10, wherein the step of disposing the light-shielding layer in the groove comprises: applying glue in the groove using a glue dispenser.

12. The method for preparing a display device as claimed in claim 10, wherein the step of disposing the light-shielding layer in the groove comprises: spraying ink in the groove using an ink-jet printer.

13. The method for preparing a display device as claimed in claim 10, wherein a material of the light-shielding layer is ink or glue, and after the light-shielding layer is disposed in the groove, the method further comprises: curing the light-shielding layer.

14. The method for preparing a display device as claimed in claim 10, wherein the display panel is an OLED display panel.

15. The method for preparing a display device as claimed in claim 10, wherein the groove is provided around the second display area to form a closed-loop structure.

16. The method for preparing a display device as claimed in claim 10, wherein an absolute value of a height difference between a top surface of the light-shielding layer and a surface of a side of the groove provided on the packaging cover plate is less than 5 μm .

17. The method for preparing a display device as claimed in claim 10, wherein a thickness of the packaging cover plate is in a range of 100 μm to 1000 μm , and a ratio of a depth of the groove to the thickness of the packaging cover plate is in a range of 0.01 to 0.1.

18. The method for preparing a display device as claimed in claim 10, wherein a distance between the groove and the second display area is in a range of 100 μm to 400 μm , and a distance between

the groove and an outer edge of the second non-display area is in a range of 100 μm to 200 μm .

19. The method for preparing a display device as claimed in claim 10, wherein a thickness of the packaging cover plate is in a range of 500 μm to 1000 μm , and a depth of the groove is in a range of 5 μm to 30 μm ; or a thickness of the packaging cover plate is in a range of 100 μm to 500 μm , and a depth of the groove is in a range of 5 μm to 10 μm .

20. The method for preparing a display device as claimed in claim 10, wherein a material of the light-shielding layer is ink or glue.
