

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384570
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Grasberger; Christopher Brian et al.

Base stations for unmanned aerial vehicles (UAVs)

Abstract

A base station is disclosed for an unmanned aerial vehicle (UAV). The base station includes: a metallic enclosure; a first electronics module; a second electronics module; and a third electronics module, wherein the first electronics module, the second electronics module, and the third electronics module are each configured for individual removal from the metallic enclosure. The metallic enclosure is configured to receive the UAV and includes a front end having a front door and a rear end having a rear door. The rear door is located adjacent to the first electronics module and includes a metallic panel that is positioned in correspondence with the first electronics module so as to create a Faraday cage for the first electronics module and thereby reduce electromagnetic emissions from the base station.

Inventors: Grasberger; Christopher Brian (Burlingame, CA), O'Leary; Kevin Patrick Smith (San Francisco, CA), Woo; Yee Shan (Campbell, CA), Callaway; Dylan Matthew (San Francisco, CA), Robbins-Rothman; Asher Mendel (Redwood City, CA), Berthelet; Christopher C. (Sunnyvale, CA), Lowe; Patrick Allen (Palo Alto, CA)

Applicant: Skydio, Inc. (Redwood City, CA)

Family ID: 84982017

Assignee: Skydio, Inc. (San Mateo, CA)

Appl. No.: 17/900028

Filed: August 31, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230348105 A1	Nov. 02, 2023

Related U.S. Application Data

us-provisional-application US 63356595 20220629
us-provisional-application US 63356596 20220629
us-provisional-application US 63335686 20220427

Publication Classification

Int. Cl.: **B64U80/25** (20230101); **B60L53/10** (20190101); **B60L53/30** (20190101); **B60L53/302** (20190101); **B64F1/22** (20060101); **B64F1/36** (20170101); **B64U70/92** (20230101); **B64U80/70** (20230101); **H01Q1/22** (20060101); **H05K7/20** (20060101); B60L53/16 (20190101); B64C39/02 (20230101); B64D43/00 (20060101); B64D47/00 (20060101); B64U70/00 (20230101); H05B1/02 (20060101); H05K1/02 (20060101); H10N10/13 (20230101); H10N10/17 (20230101)

U.S. Cl.:

CPC **B60L53/30** (20190201); **B60L53/10** (20190201); **B60L53/302** (20190201); **B64F1/22** (20130101); **B64F1/362** (20130101); **B64U70/92** (20230101); **B64U80/25** (20230101); **B64U80/70** (20230101); **H01Q1/22** (20130101); **H05K7/20145** (20130101); **H05K7/20154** (20130101); **H05K7/20209** (20130101); **H05K7/20436** (20130101); B60L53/16 (20190201); B60L2200/10 (20130101); B64C39/024 (20130101); B64D43/00 (20130101); B64D47/00 (20130101); B64U70/00 (20230101); H01Q1/2291 (20130101); H05B1/0227 (20130101); H05K1/0215 (20130101); H10N10/13 (20230201); H10N10/17 (20230201)

Field of Classification Search

CPC: B64U (80/10); B64U (80/25); B64U (80/70); B64F (1/222); B64F (1/35); B64F (1/352); H05K (1/0201); H05K (1/0203); H05K (1/0209); H05K (1/021); H05K (1/0215); H05K (7/20145); H05K (7/20163)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2834573	12/1957	Stalker	N/A	N/A
4123020	12/1977	Korsak	N/A	N/A
5727754	12/1997	Carter, Jr.	N/A	N/A
5950373	12/1998	von Hoff et al.	N/A	N/A
6233003	12/2000	Ono	N/A	N/A
6352411	12/2001	Bucher et al.	N/A	N/A
6435453	12/2001	Carter, Jr.	N/A	N/A
6487779	12/2001	Underthun	N/A	N/A
6802694	12/2003	Bucher et al.	N/A	N/A
7448571	12/2007	Carter, Jr. et al.	N/A	N/A
8511606	12/2012	Lutke et al.	N/A	N/A
8588210	12/2012	Newberg et al.	N/A	N/A
9139310	12/2014	Wang	N/A	N/A
9457901	12/2015	Bertrand et al.	N/A	N/A

9469394	12/2015	Vaughn et al.	N/A	N/A
9567076	12/2016	Zhang	N/A	N/A
9678506	12/2016	Bachrach et al.	N/A	N/A
9718564	12/2016	Beckman et al.	N/A	N/A
9764829	12/2016	Beckman et al.	N/A	N/A
9764836	12/2016	Elzinga et al.	N/A	N/A
9777502	12/2016	Curlander et al.	N/A	N/A
9783075	12/2016	Henry et al.	N/A	N/A
9798322	12/2016	Bachrach et al.	N/A	N/A
9834305	12/2016	Taylor et al.	N/A	N/A
9840339	12/2016	O'Brien et al.	N/A	N/A
9891621	12/2017	Bachrach et al.	N/A	N/A
9972212	12/2017	Sperindeo et al.	N/A	N/A
10011352	12/2017	Dahlstrom	N/A	N/A
10011354	12/2017	Goldstein	N/A	N/A
10104289	12/2017	Enriquez et al.	N/A	N/A
10137983	12/2017	Horn	N/A	N/A
10207820	12/2018	Sullivan et al.	N/A	N/A
10386188	12/2018	Tian et al.	N/A	N/A
10435176	12/2018	McClure et al.	N/A	N/A
10453348	12/2018	Speasl et al.	N/A	N/A
10455155	12/2018	Kalinowski et al.	N/A	N/A
10467685	12/2018	Brisson et al.	N/A	N/A
10494094	12/2018	Foley	N/A	N/A
10520943	12/2018	Martirosyan et al.	N/A	N/A
10549850	12/2019	Ryan et al.	N/A	N/A
10575448	12/2019	Lewis	N/A	H05K 9/0081
10612523	12/2019	Srinivasan	N/A	N/A
10618650	12/2019	Hasinski et al.	N/A	N/A
10647404	12/2019	Sugaki et al.	N/A	N/A
10717524	12/2019	Boyes et al.	N/A	N/A
10793270	12/2019	Chen et al.	N/A	N/A
10816967	12/2019	Bachrach et al.	N/A	N/A
10831186	12/2019	Van Niekerk et al.	N/A	N/A
D906170	12/2019	Thompson et al.	N/A	N/A
10913546	12/2020	Krauss et al.	N/A	N/A
10946959	12/2020	Nwosu	N/A	N/A
10981661	12/2020	Oldroyd et al.	N/A	N/A
10992865	12/2020	Kalinowski et al.	N/A	N/A
11007290	12/2020	Kreitenberg et al.	N/A	N/A
11065976	12/2020	Venturelli et al.	N/A	N/A
11111033	12/2020	Burks	N/A	B64F 1/222
11124298	12/2020	Chen et al.	N/A	N/A
11148805	12/2020	Cooper et al.	N/A	N/A
11292598	12/2021	Foley	N/A	N/A
11308815	12/2021	Speasl et al.	N/A	N/A
11407526	12/2021	Wang	N/A	N/A
11453513	12/2021	Thompson et al.	N/A	N/A
11530028	12/2021	Wiegman	N/A	N/A
11530052	12/2021	Alsbaugh	N/A	B64U 70/90

11597515	12/2022	Passley	N/A	N/A
11636771	12/2022	Barker et al.	N/A	N/A
2001/0046442	12/2000	Bucher et al.	N/A	N/A
2005/0224874	12/2004	Chakravarthi et al.	N/A	N/A
2006/0249622	12/2005	Steele	N/A	N/A
2006/0251522	12/2005	Matheny et al.	N/A	N/A
2008/0251308	12/2007	Molnar et al.	N/A	N/A
2009/0283629	12/2008	Kroetsch et al.	N/A	N/A
2011/0139665	12/2010	Madsen	N/A	N/A
2011/0268194	12/2010	Nagano	N/A	N/A
2012/0162913	12/2011	Lai	165/96	H05K 7/20727
2012/0162917	12/2011	Chen	165/96	H05K 7/20145
2012/0232718	12/2011	Rischmuller et al.	N/A	N/A
2012/0287274	12/2011	Bevirt	N/A	N/A
2013/0051778	12/2012	Dimotakis	N/A	N/A
2013/0099063	12/2012	Grip et al.	N/A	N/A
2013/0175390	12/2012	Woodworth et al.	N/A	N/A
2013/0176423	12/2012	Rischmuller et al.	N/A	N/A
2013/0280084	12/2012	Nagle et al.	N/A	N/A
2014/0333074	12/2013	Wollacott	292/202	E05B 5/00
2014/0356174	12/2013	Wang et al.	N/A	N/A
2015/0137424	12/2014	Lyons et al.	N/A	N/A
2015/0149000	12/2014	Rischmuller et al.	N/A	N/A
2015/0321758	12/2014	Sarna, II	N/A	N/A
2015/0370250	12/2014	Bachrach et al.	N/A	N/A
2016/0009413	12/2015	Lee et al.	N/A	N/A
2016/0011592	12/2015	Zhang et al.	N/A	N/A
2016/0129998	12/2015	Welsh et al.	N/A	N/A
2016/0185466	12/2015	Dreano, Jr.	N/A	N/A
2016/0214713	12/2015	Cragg	N/A	N/A
2016/0214715	12/2015	Meffert	N/A	N/A
2016/0257426	12/2015	Mozer	N/A	N/A
2016/0286128	12/2015	Zhou	N/A	N/A
2016/0327950	12/2015	Bachrach et al.	N/A	N/A
2016/0340028	12/2015	Datta	N/A	N/A
2016/0364989	12/2015	Speasl et al.	N/A	N/A
2016/0376000	12/2015	Kohstall	N/A	N/A
2016/0376004	12/2015	Claridge et al.	N/A	N/A
2017/0023949	12/2016	Fisher et al.	N/A	N/A
2017/0036771	12/2016	Woodman et al.	N/A	N/A
2017/0050749	12/2016	Pilskalns	N/A	N/A
2017/0057630	12/2016	Schwaiger	N/A	N/A
2017/0073085	12/2016	Tremblay et al.	N/A	N/A
2017/0075351	12/2016	Liu	N/A	N/A
2017/0113793	12/2016	Toulmay	N/A	N/A
2017/0113800	12/2016	Freeman	N/A	N/A
2017/0117676	12/2016	James et al.	N/A	N/A
2017/0126935	12/2016	Tai et al.	N/A	N/A

2017/0129464	12/2016	Wang et al.	N/A	N/A
2017/0144776	12/2016	Fisher et al.	N/A	N/A
2017/0158328	12/2016	Foley	N/A	N/A
2017/0158352	12/2016	von Flotow et al.	N/A	N/A
2017/0217585	12/2016	Hulsman et al.	N/A	N/A
2017/0225802	12/2016	Lussier et al.	N/A	N/A
2017/0233069	12/2016	Apkarian	N/A	N/A
2017/0240061	12/2016	Waters	N/A	N/A
2017/0244270	12/2016	Waters	N/A	N/A
2017/0297681	12/2016	Yamada et al.	N/A	N/A
2017/0297738	12/2016	von Flotow et al.	N/A	N/A
2017/0301111	12/2016	Zhao et al.	N/A	N/A
2017/0327218	12/2016	Morin et al.	N/A	N/A
2018/0024570	12/2017	Hutson	N/A	N/A
2018/0032042	12/2017	Turpin et al.	N/A	N/A
2018/0046187	12/2017	Martirosyan et al.	N/A	N/A
2018/0093171	12/2017	Mallinson	N/A	N/A
2018/0093781	12/2017	Mallinson	N/A	N/A
2018/0181119	12/2017	Lee et al.	N/A	N/A
2018/0194463	12/2017	Hasinski et al.	N/A	N/A
2018/0208301	12/2017	Ye	N/A	N/A
2018/0208311	12/2017	Zhang et al.	N/A	N/A
2018/0284575	12/2017	Sugaki et al.	N/A	N/A
2018/0312253	12/2017	Zhao et al.	N/A	N/A
2018/0312254	12/2017	Ni	N/A	N/A
2018/0326255	12/2017	Schranz	N/A	N/A
2018/0327091	12/2017	Burks et al.	N/A	N/A
2019/0002124	12/2018	Garvin	N/A	N/A
2019/0002127	12/2018	Straus et al.	N/A	N/A
2019/0023395	12/2018	Lee et al.	N/A	N/A
2019/0023416	12/2018	Borko et al.	N/A	N/A
2019/0061976	12/2018	Schweighart et al.	N/A	N/A
2019/0068953	12/2018	Choi et al.	N/A	N/A
2019/0084673	12/2018	Chen et al.	N/A	N/A
2019/0100313	12/2018	Campbell	N/A	N/A
2019/0102874	12/2018	Goja	N/A	N/A
2019/0118944	12/2018	Kimchi et al.	N/A	N/A
2019/0135403	12/2018	Perry et al.	N/A	N/A
2019/0144100	12/2018	Samir	N/A	N/A
2019/0168872	12/2018	Grubb et al.	N/A	N/A
2019/0217971	12/2018	Comerford	N/A	N/A
2019/0230801	12/2018	Neuman	N/A	H05K 7/2039
2019/0248487	12/2018	Holtz et al.	N/A	N/A
2019/0270526	12/2018	Hehn et al.	N/A	N/A
2019/0289193	12/2018	Bevirt	N/A	N/A
2019/0329903	12/2018	Thompson et al.	N/A	N/A
2019/0367185	12/2018	Zambelli	N/A	N/A
2019/0377345	12/2018	Bachrach et al.	N/A	N/A
2019/0378423	12/2018	Bachrach et al.	N/A	N/A
2019/0379268	12/2018	Adams et al.	N/A	N/A

2020/0001990	12/2019	Jiang et al.	N/A	N/A
2020/0023995	12/2019	Song et al.	N/A	N/A
2020/0036896	12/2019	Kalinowski et al.	N/A	N/A
2020/0041996	12/2019	Bachrach et al.	N/A	N/A
2020/0064135	12/2019	Lai et al.	N/A	N/A
2020/0072283	12/2019	Roberts et al.	N/A	N/A
2020/0073385	12/2019	Jobanputra et al.	N/A	N/A
2020/0107154	12/2019	Kam et al.	N/A	N/A
2020/0108930	12/2019	Foley	N/A	N/A
2020/0156749	12/2019	Scacchi	N/A	N/A
2020/0164966	12/2019	Suzuki	N/A	N/A
2020/0165007	12/2019	Augugliaro et al.	N/A	N/A
2020/0391864	12/2019	Lee et al.	N/A	N/A
2020/0398999	12/2019	Ortiz	N/A	G07C 9/00309
2021/0009269	12/2020	Chen et al.	N/A	N/A
2021/0061482	12/2020	Ulrich et al.	N/A	N/A
2021/0070468	12/2020	Svirsky et al.	N/A	N/A
2021/0074170	12/2020	Barker	N/A	B64U 70/90
2021/0107682	12/2020	Kozlenko et al.	N/A	N/A
2021/0107684	12/2020	Le Lann	N/A	N/A
2021/0109312	12/2020	Honjo et al.	N/A	N/A
2021/0114729	12/2020	Ragan et al.	N/A	N/A
2021/0197983	12/2020	Wang et al.	N/A	N/A
2021/0214067	12/2020	West et al.	N/A	N/A
2021/0214068	12/2020	Bry et al.	N/A	N/A
2021/0245860	12/2020	Bry et al.	N/A	N/A
2021/0261252	12/2020	Dayan	N/A	N/A
2021/0269174	12/2020	Shuff	N/A	N/A
2021/0276733	12/2020	Kozlenko et al.	N/A	N/A
2021/0276734	12/2020	Kozlenko et al.	N/A	N/A
2021/0284335	12/2020	McLaughlin et al.	N/A	N/A
2021/0309388	12/2020	Ratajczak et al.	N/A	N/A
2021/0314490	12/2020	Kalinowski et al.	N/A	N/A
2021/0403177	12/2020	Thompson et al.	N/A	N/A
2022/0001982	12/2021	Chen et al.	N/A	N/A
2022/0019247	12/2021	Dayan et al.	N/A	N/A
2022/0185475	12/2021	Foley	N/A	N/A
2022/0326705	12/2021	Thompson et al.	N/A	N/A
2022/0355952	12/2021	Thompson et al.	N/A	N/A
2022/0411102	12/2021	Thompson et al.	N/A	N/A
2022/0411103	12/2021	Thompson et al.	N/A	N/A
2022/0412023	12/2021	Palombini	N/A	N/A
2023/0002074	12/2022	Thompson et al.	N/A	N/A
2023/0017530	12/2022	Lowe et al.	N/A	N/A
2023/0023246	12/2022	McLaughlin et al.	N/A	N/A
2023/0136701	12/2022	Wiegman	N/A	N/A
2023/0144408	12/2022	Thompson et al.	N/A	N/A
2023/0166862	12/2022	Thompson et al.	N/A	N/A
2023/0287675	12/2022	Stahl et al.	N/A	N/A

2024/0132238 12/2023 Qiu et al. N/A N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019213466	12/2019	AU	N/A
1278288	12/1989	CA	N/A
107235145	12/2016	CN	N/A
109455307	12/2018	CN	N/A
109622461	12/2018	CN	N/A
113148211	12/2020	CN	N/A
113247289	12/2020	CN	N/A
113562189	12/2020	CN	N/A
113716062	12/2020	CN	N/A
114475946	12/2021	CN	N/A
114537691	12/2021	CN	N/A
114572413	12/2021	CN	N/A
114655056	12/2021	CN	N/A
115626281	12/2022	CN	N/A
102018203290	12/2018	DE	N/A
112017007148	12/2018	DE	N/A
3418201	12/2017	EP	N/A
3050981	12/2016	FR	N/A
2021082794	12/2020	WO	N/A
2022045459	12/2021	WO	N/A
2023017027	12/2022	WO	N/A
2023056516	12/2022	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion mailed on Mar. 13, 2023 in corresponding PCT Application No. PCT/US2022/050705. cited by applicant

Primary Examiner: Michener; Joshua J

Assistant Examiner: Zohoori; Colin

Attorney, Agent or Firm: Young Basile Hanlon & MacFarlane, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims the benefit of and priority to U.S. Provisional Application No. 63/335,686, filed Apr. 27, 2022, U.S. Provisional Application No. 63/356,595, filed Jun. 29, 2022, and U.S. Provisional Application No. 63/356,596, filed Jun. 29, 2022, the disclosures of which are hereby incorporated by reference in their entirety.

TECHNICAL FIELD

(1) The present disclosure relates to a base station (dock) for an unmanned aerial vehicle (UAV) (e.g., a drone). More specifically, the present disclosure relates to a base station that includes a series of integrated systems, which allow for automated servicing (e.g., docking, storage, charging, operation, etc.) and accommodation of a UAV.

BACKGROUND

(2) Known base stations for UAVs are often large, mechanically complex, and expensive. The present disclosure addresses these deficiencies, among others, and provides a base station that offers improved servicing of UAVs and significant size reductions that allow for more efficient operation and substantial cost savings.

SUMMARY

(3) In one aspect of the present disclosure, a base station is disclosed that is configured for use with an unmanned aerial vehicle (UAV). The base station includes: an enclosure; a cradle that is configured to receive the UAV during docking to facilitate charging of a power source of the UAV; and a temperature control system that is connected to the cradle and which is configured to vary temperature of the power source of the UAV. The cradle is movable between a retracted position, in which the cradle is positioned within the enclosure, and an extended position, in which the cradle is positioned externally of the enclosure to facilitate docking with the UAV. The temperature control system includes: a thermoelectric conditioner (TEC) having a first end and a second end; a first air circuit that is thermally connected to the TEC and which is configured to regulate temperature of the TEC; and a second air circuit that is thermally connected to the TEC such that the TEC is located between the first air circuit and the second air circuit. The second air circuit is configured to direct air across the cradle to thereby heat or cool the power source of the UAV when docked with the base station.

(4) In various embodiments, the temperature control system may be configured to cool the power source of the UAV (e.g., when the base station and the UAV are used in hot environments) or to heat the power source of the UAV (e.g., when the base station and the UAV are used in cold environments).

(5) In certain embodiments, the first air circuit may be configured as an open system and the second air circuit may be configured as a closed system.

(6) In certain embodiments, the TEC may be configured as a Peltier system.

(7) In certain embodiments, the first air circuit may include: a first plenum; a first heat sink that is connected to the first plenum and the first end of the TEC; and a first air circulator that is configured to direct air through the first plenum and across the first heat sink to vary air temperature within the first air circuit and thereby regulate the temperature of the TEC.

(8) In certain embodiments, the second air circuit may include: a second plenum; a second heat sink that is connected to the second plenum and the second end of the TEC; and a second air circulator that is configured to direct air through the second plenum and across the second heat sink to vary air temperature within the second air circuit and thereby heat or cool the power source of the UAV when docked with the base station.

(9) In certain embodiments, the temperature control system may be configured to cool the power source of the UAV when docked with the base station.

(10) In certain embodiments, the second plenum may define an air inlet and an air outlet.

(11) In certain embodiments, the air inlet may be configured to direct air into the cradle and across the power source of the UAV and the air outlet may be configured to receive the air directed across the power source of the UAV and redirect the air across the second heat sink.

(12) In certain embodiments, the second plenum may include a first section and a second section that is movable in relation to the first section.

(13) In certain embodiments, the first section may be connected to the TEC and the second section may be connected to the cradle.

(14) In certain embodiments, the first section and the second section may be configured for mating engagement upon movement of the cradle into the retracted position.

(15) In another aspect of the present disclosure, a base station is disclosed that is configured for use with a UAV. The base station includes a temperature control system that is configured to vary temperature of the UAV. The temperature control system includes: a thermoelectric conditioner (TEC); an open air circuit that is thermally connected to the TEC and which is configured to

regulate temperature of the TEC; and a closed air circuit that is thermally connected to the TEC such that the TEC is located between the open air circuit and the closed air circuit. The closed air circuit is configured to direct air across the UAV when docked with the base station.

(16) In certain embodiments, the temperature control system may be configured to heat or cool the UAV subject to environmental conditions.

(17) In certain embodiments, the closed air circuit may include a first section and a second section that is movable in relation to the first section.

(18) In certain embodiments, the base station may further include a cradle that is configured to receive the UAV during docking to facilitate charging of the UAV.

(19) In certain embodiments, the cradle may be extendable from and retractable into the base station.

(20) In certain embodiments, the first section of the closed air circuit may be connected to the TEC and the second section of the closed air circuit may be connected to the cradle.

(21) In certain embodiments, the first section and the second section may be configured for mating engagement upon retraction of the cradle into the base station.

(22) In another aspect of the present disclosure, a method is disclosed for regulating the temperature of a power source in a UAV. The method includes: docking the UAV within a cradle of a base station; retracting the cradle into the base station; and directing thermally conditioned air across the power source of the UAV via an air circuit that is connected to the cradle.

(23) In certain embodiments, the method may further include directing air across a heat sink that is thermally connected to a thermoelectric conditioner (TEC) to treat the air prior to direction across the power source of the UAV.

(24) In certain embodiments, directing air across the heat sink may include circulating the air through a plenum that is connected to the heat sink.

(25) In certain embodiments, retracting the cradle into the base station may include closing the air circuit.

(26) In certain embodiments, closing the air circuit may include mating a first section of the plenum with a second section of the plenum.

(27) In certain embodiments, the first section of the plenum may be connected to the TEC and the second section of the plenum may be connected to the cradle.

(28) In another aspect of the present disclosure, a base station is disclosed that is configured for use with a UAV. The base station includes: an enclosure with an outer housing that defines a roof section and an inner housing that is connected to the outer housing; one or more heating elements that are supported by the enclosure and which are configured to heat the roof section; one or more fiducials that are supported by the enclosure; an illumination system that is supported by the enclosure and which is configured to illuminate the one or more fiducials; and a visualization system that is supported by the enclosure.

(29) In certain embodiments, the enclosure (e.g., the outer housing) may define one or more channels that are configured to direct water in a manner that inhibits entry into the base station.

(30) In certain embodiments, the base station may further include one or more temperature sensors that are in communication with the one or more heating elements such that the one or more heating elements are activated upon receiving a signal relayed by the one or more temperature sensors indicating that temperature has crossed a threshold.

(31) In certain embodiments, the one or more fiducials may include a first fiducial and a second fiducial, each of which is supported by the roof section.

(32) In certain embodiments, the second fiducial may be removably connected to the roof section.

(33) In certain embodiments, the first fiducial may define a first surface area, and the second fiducial may define a second surface area that is less than the first surface area.

(34) In certain embodiments, the first surface area may lie substantially within the range of (approximately) 40 percent to (approximately) 80 percent of a surface area defined by the roof

section.

(35) In certain embodiments, the second surface area may lie substantially within the range of (approximately) 10 percent to (approximately) 50 percent of the first surface area.

(36) In certain embodiments, the illumination system may include one or more light sources that are connected (secured) to the roof section and which are configured to light the first fiducial and the second fiducial.

(37) In certain embodiments, the illumination system may be configured to strobe the one or more light sources according to a pattern that is recognizable by the UAV during approach to thereby identify the base station.

(38) In certain embodiments, the visualization system may include a digital image capturing device that is configured to identify precipitation and actuate the one or more heating elements.

(39) In certain embodiments, the base station may further include one or more status indicators that are supported by the enclosure (e.g., the outer housing).

(40) In certain embodiments, the base station may further include one or more internal fans to regulate temperature and/or humidity within the base station.

(41) In certain embodiments, the internal fan(s) may be supported by at least one of the outer housing and the inner housing.

(42) In another aspect of the present disclosure, a base station is disclosed that is configured for use with a UAV. The base station includes: an enclosure; a (front) door that is movably connected to the enclosure such that the door is repositionable between a closed position and an open position; and one or more actuators that extend between the door and the enclosure. The enclosure includes an outer housing and an inner housing that is connected to the outer housing and which defines an internal cavity that is configured receive the UAV. Each actuator includes a motor assembly and a linkage assembly that extends between the motor assembly and the door. The motor assembly is connected (secured) to the inner housing such that the motor assembly is located between the outer housing and the inner housing, and the linkage assembly extends through the inner housing.

(43) In certain embodiments, the linkage assembly may include: a drive screw that is operatively connected to the motor assembly such that actuation of the motor assembly causes rotation of the drive screw; a carrier that is threadably engaged to the drive screw such that rotation of the drive screw causes axial translation of the carrier; a first arm; and a second arm.

(44) In certain embodiments, the first arm may have a first end that is pivotably connected to the carrier and a second end, and the second arm may have a first end that is pivotably connected to the second end of the first arm and a second end that is pivotably connected to the door.

(45) In certain embodiments, the base station may further include a bracket that is fixedly connected to the door.

(46) In certain embodiments, the bracket may be pivotably connected to the second end of the second arm.

(47) In certain embodiments, the drive screw may be configured such that rotation of the drive screw in a first direction causes advancement of the carrier towards the door and rotation of the drive screw in a second direction causes advancement of the carrier away from the door.

(48) In certain embodiments, the drive screw may include threading defining a pitch that is configured to inhibit force transmission from the door to the carrier to thereby maintain the door in the closed position.

(49) In another aspect of the present disclosure, a base station is disclosed that is configured for use with an unmanned aerial vehicle (UAV). The base station includes: an enclosure defining an internal cavity that is configured to receive the UAV; a first fiducial that is supported by a roof section of the enclosure and which defines a first surface area; a second fiducial that is supported by the roof section of the enclosure and which defines a second surface area that is less than the first surface area; and an illumination system that is supported by roof section and which is configured to illuminate the first fiducial and the second fiducial.

(50) In certain embodiments, the second fiducial may be configured for removable connection to the roof section.

(51) In certain embodiments, the first surface area may lie substantially within the range of (approximately) 40 percent to (approximately) 80 percent of a surface area defined by the roof section.

(52) In certain embodiments, the second surface area may lie substantially within the range of (approximately) 10 percent to (approximately) 50 percent of the first surface area.

(53) In certain embodiments, the illumination system may be configured to strobe according to a pattern recognizable by the UAV during approach to thereby identify the base station.

(54) In another aspect of the present disclosure, a UAV is disclosed that includes a power source. The power source includes: one or more power cells; one or more thermal transfer members that are thermally connected to the one or more power cells; and a heat exchanger that is thermally connected to the one or more thermal transfer members such that the one or more thermal transfer members and the heat exchanger facilitate a transfer of thermal energy between the power source and ambient air to decrease or increase temperature of the power source.

(55) In certain embodiments, the one or more thermal transfer members may extend between the one or more power cells and the heat exchanger.

(56) In certain embodiments, the one or more thermal transfer members may include graphite.

(57) In certain embodiments, the one or more thermal transfer members may be unitary in construction.

(58) In certain embodiments, the one or more power cells and the one or more thermal transfer members may correspond in number.

(59) In certain embodiments, the one or more power cells may include a plurality of individual power cells and the one or more thermal transfer members may include a plurality of individual thermal transfer members.

(60) In certain embodiments, the heat exchanger may include one or more diffusers to increase surface area of the heat exchanger and thermal energy distribution towards or away from the power source.

(61) In certain embodiments, the one or more diffusers may extend axially and/or laterally along an outer surface of the heat exchanger.

(62) In certain embodiments, the one or more diffusers may include a plurality of diffusers.

(63) In certain embodiments, the plurality of diffusers may be configured as fins that define one or more channels therebetween.

(64) In certain embodiments, the one or more channels may be configured to direct air flow along the heat exchanger to increase thermal energy distribution towards or away from the power source.

(65) In another aspect of the present disclosure, a UAV is disclosed that includes a power source. The power source includes a heat exchanger that is configured to transfer thermal energy between the power source and ambient air to decrease or increase temperature of the power source. The heat exchanger includes one or more diffusers to increase surface area of the heat exchanger and thermal energy distribution towards or away from the power source.

(66) In certain embodiments, the one or more diffusers may extend axially and/or laterally along an outer surface of the heat exchanger.

(67) In certain embodiments, the one or more diffusers may include a plurality of diffusers.

(68) In certain embodiments, the plurality of diffusers may be configured as fins that define one or more channels therebetween.

(69) In certain embodiments, the one or more channels may be configured to direct air flow along the heat exchanger to increase thermal energy distribution towards or away from the power source.

(70) In another aspect of the present disclosure, a UAV is disclosed that includes: a body; one or more antennas that extend from the body; and a power source that is connected to the body. The one or more antennas are reconfigurable between an active configuration, in which the one or more

antennas extend outwardly from the body, and a passive configuration, in which the one or more antennas are positioned adjacent to the body. The power source includes one or more diffusers that extend axially and/or laterally along an outer surface of the power source to transfer thermal energy between the power source and ambient air to decrease or increase temperature of the power source.

(71) In certain embodiments, the one or more antennas may be biased towards the active configuration.

(72) In certain embodiments, the one or more diffusers may include a plurality of diffusers.

(73) In certain embodiments, the plurality of diffusers may be configured as fins that define one or more channels therebetween.

(74) In certain embodiments, the one or more channels may be configured to direct air flow along the power source to increase thermal energy distribution towards or away from the power source.

(75) In certain embodiments, the power source may further include one or more power cells and one or more thermal transfer members that are thermally connected to the one or more power cells and to the one or more diffusers.

(76) In certain embodiments, the one or more thermal transfer members may include graphite.

(77) In certain embodiments, the one or more thermal transfer members may be unitary in construction.

(78) In another aspect of the present disclosure, a base station for an unmanned aerial vehicle (UAV) is disclosed that includes: an enclosure; a slide mechanism that includes openings; and a cradle.

(79) The slide mechanism is repositionable between a retracted position and an extended position and is secured in relation (connected) to the enclosure via first mounts and second mounts. The first mounts and the second mounts are located between the slide mechanism and the enclosure so as to separate the slide mechanism from the enclosure and thereby reduce vibration of the slide mechanism during repositioning between the retracted position and the extended position (extension and retraction).

(80) The cradle is connected to the slide mechanism and is configured for docking with the UAV such that the UAV is movable into and out of the enclosure during repositioning of the slide mechanism between the retracted position and the extended position.

(81) In certain embodiments, the enclosure may include a plurality of studs that extend towards the slide mechanism.

(82) In certain embodiments, each of the first mounts and the second mounts may be configured to receive one of the plurality of studs.

(83) In certain embodiments, the first mounts may include: a first bushing; a shank extending from the first bushing that is configured for insertion into one of the openings in the slide mechanism; and a fastener that is configured for releasable connection to the shank such that the slide mechanism is secured between the first bushing and the fastener.

(84) In certain embodiments, the first bushing may define an aperture to facilitate connection of the first bushing to the enclosure.

(85) In certain embodiments, the shank and the fastener may be configured for threaded engagement.

(86) In certain embodiments, the first bushing may include a compliant material to facilitate force absorption by the first mounts and thereby reduce vibration of the slide mechanism during repositioning between the retracted position and the extended position.

(87) In certain embodiments, the second mounts may include a second bushing having a non-uniform transverse cross-sectional configuration.

(88) In certain embodiments, the second bushing may include a base portion and a stem that extends from the base portion.

(89) In certain embodiments, the base portion may define a first transverse cross-sectional dimension and the stem may define a second transverse cross-sectional dimension that is less than

the first transverse cross-sectional dimension.

(90) In certain embodiments, the stem may be configured for insertion into one of the openings in the slide mechanism.

(91) In certain embodiments, the openings in the slide mechanism may define a third transverse cross-sectional dimension that is less than the first transverse cross-sectional dimension and greater than the second transverse cross-sectional dimension, whereby the stem is receivable by the slide mechanism such that the slide mechanism is movable in relation to the second mounts in two degrees-of-freedom that are oriented in generally orthogonal relation.

(92) In certain embodiments, the second mounts may further include a fastener that is configured to secure the second bushing in relation to the enclosure.

(93) In another aspect of the present disclosure, a base station for an unmanned aerial vehicle (UAV) is disclosed that includes: an enclosure having a plurality of studs that extend upwardly therefrom; a slide mechanism that includes openings; and a cradle.

(94) The slide mechanism is repositionable between a retracted position and an extended position and is indirectly connected to the enclosure via first mounts and second mounts. The first mounts include a first threaded interface that is configured for connection to one of the plurality of studs and a second threaded interface that is separated from the first threaded interface by a compliant material. The second mounts include: a base portion that defines a first transverse cross-sectional dimension; a stem that extends from the base portion and which defines a second transverse cross-sectional dimension that is less than the first transverse cross-sectional dimension; and a channel that extends through the base portion and the stem and which is configured to receive one of the plurality of studs.

(95) The cradle is connected to the slide mechanism and is configured for docking with the UAV such that the UAV is movable into and out of the enclosure via the slide mechanism.

(96) In certain embodiments, the first mounts and the second mounts may be located between the enclosure and the slide mechanism such that the enclosure and the slide mechanism are physically separated by the first mounts and the second mounts.

(97) In certain embodiments, the second threaded interface may include a shank that is configured for insertion into one of the openings in the slide mechanism and which is configured for connection to a fastener to thereby secure the first mounts and the slide mechanism to the enclosure.

(98) In certain embodiments, the stem may be configured for insertion into one of the openings in the slide mechanism, which defines a third transverse cross-sectional dimension that is less than the first transverse cross-sectional dimension and greater than the second transverse cross-sectional dimension such that a lateral gap is defined between the stem and the opening in the slide mechanism to allow for predetermined lateral movement of the slide mechanism within the enclosure to inhibit lateral over-travel of the slide mechanism.

(99) In certain embodiments, the second mounts may further include a fastener that is configured for releasable connection to the stud received by the channel such that an axial gap is defined between the fastener and the base portion to allow for predetermined axial movement of the slide mechanism within the enclosure to inhibit axial over-travel of the slide mechanism.

(100) In another aspect of the present disclosure, a base station for an unmanned aerial vehicle (UAV) is disclosed that includes: an enclosure; a slide mechanism that includes openings and which is retractable and extendable in relation to the housing to facilitate movement of the UAV into and out of the enclosure; first mounts that are configured for insertion into the slide mechanism such that the first mounts are located between the slide mechanism and the enclosure; and second mounts that are configured for insertion into the slide mechanism such that the second mounts are located between the slide mechanism and the enclosure, wherein the first mounts and the second mounts include non-identical configurations.

(101) In certain embodiments, the first mounts may be fixed in relation to the slide mechanism.

(102) In certain embodiments, the second mounts may be configured to facilitate relative movement between the second mounts and the slide mechanism.

(103) In certain embodiments, the second mounts may include a stepped configuration.

(104) In certain embodiments, the second mounts may include a base portion defining a first transverse cross-sectional dimension and a stem that extends from the base portion and which defines a second transverse cross-sectional dimension that is less than the first transverse cross-sectional dimension.

(105) In certain embodiments, the stem may be configured for insertion into one of the openings in the slide mechanism so as to define lateral and axial gaps allowing for predetermined lateral and axial movement of the slide mechanism within the enclosure in two degrees-of-freedom to inhibit over-travel of the slide mechanism and unintended contact between the slide mechanism and internal components of the base station.

(106) In another aspect of the present disclosure, a method of assembling a base station for an unmanned aerial vehicle (UAV) is disclosed. The method includes: connecting first mounts to an enclosure of the base station; connecting second mounts to the enclosure, wherein the first mounts include a first configuration, and the second mounts include a second, different configuration; connecting a slide mechanism to the first mounts and the second mounts such that the first mounts and the second mounts are located between the slide mechanism and the enclosure to thereby separate the slide mechanism from the enclosure and reduce vibration of the slide mechanism during extension and retraction; and connecting a cradle configured for docking with the UAV to the slide mechanism such that the UAV is movable into and out of the enclosure during extension and retraction of the slide mechanism.

(107) In certain embodiments, connecting the first mounts to the enclosure may include inserting first studs extending from the enclosure into apertures defined by the first mounts.

(108) In certain embodiments, inserting the first studs into the apertures defined by the first mounts may include threadably connecting the first studs to first bushings of the first mounts such that the first studs extend partially into the first bushings.

(109) In certain embodiments, connecting the second mounts to the enclosure may include inserting second studs extending from the enclosure into channels defined by second bushings of the second mounts such that the second studs extend through the second mounts.

(110) In certain embodiments, connecting the slide mechanism to the first mounts may include inserting shanks extending from the first bushings into openings in the slide mechanism.

(111) In certain embodiments, connecting the slide mechanism to the second mounts may include inserting the second bushings into openings in the slide mechanism.

(112) In certain embodiments, inserting the second bushings into the openings in the slide mechanism may include positioning base portions of the second bushings between the enclosure and the slide mechanism and inserting stems extending from the base portions into the openings in the slide mechanism such that the slide mechanism is movable in relation to the second mounts in two degrees-of-freedom oriented in generally orthogonal relation.

(113) In certain embodiments, connecting the slide mechanism to the first mounts may include threadably connecting first fasteners to the shanks extending from the first bushings.

(114) In certain embodiments, connecting the slide mechanism to the second mounts may include threadably connecting second fasteners to the second studs extending through the second bushings.

(115) In certain embodiments, connecting the slide mechanism to the second mounts may include forming radial gaps between the stems and the openings in the slide mechanism and forming axial gaps between the base portions and the second fasteners.

(116) In another aspect of the present disclosure, a base station for an unmanned aerial vehicle (UAV) is disclosed that includes: an enclosure defining an internal cavity that is configured to receive the UAV; a (front) door that is movably connected to the enclosure; actuators that extend between the door and the enclosure to facilitate opening and closure of the door; a cradle that is

configured to receive the UAV; and engagement members that are connected (secured) to the actuators and which are configured for contact with propeller assemblies on the UAV to facilitate folding of the propeller assemblies during movement of the UAV into the enclosure.

(117) The cradle is movable in relation to the enclosure such that the cradle is repositionable between a retracted position and an extended position to facilitate movement of the UAV into and out of the enclosure.

(118) In certain embodiments, the engagement members may include a compliant material to inhibit unseating of the UAV from the cradle upon contact between the engagement members and the propeller assemblies.

(119) In certain embodiments, the engagement members may include mounting brackets that are configured for connection to the actuators.

(120) In certain embodiments, the actuators may include a first actuator and a second actuator that is spaced laterally from the first actuator along a width of the enclosure.

(121) In certain embodiments, the engagement members may include a first engagement member that is connected to the first actuator and a second engagement member that is connected to the second actuator such that the second engagement member is spaced laterally from the first engagement member along the width of the enclosure.

(122) In another aspect of the present disclosure, a method of docking an unmanned aerial vehicle (UAV) within a base station is disclosed that includes: opening a (front) door of the base station; performing a first stage retraction of the UAV into the base station; partially folding rear propeller assemblies on the UAV via rotation of the rear propeller assemblies into contact with engagement members on the base station; performing a second stage retraction of the UAV into the base station; completely folding the rear propeller assemblies via rotation of the rear propeller assemblies into contact with the engagement members; performing a third stage retraction of the UAV into the base station; partially folding front propeller assemblies on the UAV via rotation of the front propeller assemblies into contact with the engagement members; and completely folding the front propeller assemblies.

(123) In certain embodiments, performing the second stage retraction of the UAV may include folding an antenna on the UAV via contact with the door.

(124) In certain embodiments, partially folding the rear propeller assemblies may include rotating a first rear propeller assembly in a first direction and rotating a second rear propeller assembly in a second direction, which is opposite to the first direction.

(125) In certain embodiments, completely folding the rear propeller assemblies may include rotating the first rear propeller assembly in the second direction and rotating the second rear propeller assembly in the first direction.

(126) In certain embodiments, completely folding the rear propeller assemblies may include positioning the rear propeller assemblies such that they are oriented towards the front propeller assemblies.

(127) In certain embodiments, the method may further include partially closing the door to facilitate contact between the engagement members and the front propeller assemblies.

(128) In certain embodiments, partially folding the front propeller assemblies may include actively rotating a first front propeller assembly in the second direction and actively rotating a second front propeller assembly in the first direction.

(129) In certain embodiments, partially folding the front propeller assemblies may further include passively rotating the first front propeller assembly in the first direction and passively rotating the second front propeller assembly in the second direction.

(130) In certain embodiments, passively rotating the first front propeller assembly and passively rotating the second front propeller assembly may include performing a fourth stage retraction of the UAV into the base station.

(131) In certain embodiments, partially folding the front propeller assemblies may include

positioning the front propeller assemblies such that they are oriented away from the rear propeller assemblies.

(132) In certain embodiments, completely folding the front propeller assemblies may include rotating the first front propeller assembly in the first direction and rotating the second front propeller assembly in the second direction.

(133) In certain embodiments, completely folding the front propeller assemblies may include actively rotating the front propeller assemblies such that they are oriented towards the rear propeller assemblies.

(134) In another aspect of the present disclosure, a method of docking an unmanned aerial vehicle (UAV) within a base station is disclosed that includes: folding rear propeller assemblies on the UAV via rotation of the rear propeller assemblies into contact with engagement members on the base station; retracting the UAV into the base station; and folding front propeller assemblies on the UAV via rotation of the front propeller assemblies into contact with the engagement members.

(135) In certain embodiments, the method may further include adjusting a position of a (front) door of the base station to facilitate contact between the engagement members and the rear propeller assemblies and contact between the engagement members and the front propeller assemblies.

(136) In certain embodiments, folding the rear propeller assemblies and folding the front propeller assemblies may include rotating the rear propeller assemblies and rotating the front propeller assemblies into bumpers supported by actuators connected to the door of the base station, the actuators being configured to facilitate opening and closure of the door.

(137) In certain embodiments, folding the rear propeller assemblies and folding the front propeller assemblies may include rotating the rear propeller assemblies and rotating the front propeller assemblies into bumpers supported by the door.

(138) In another aspect of the present disclosure, a base station for an unmanned aerial vehicle (UAV) is disclosed. The base station includes: an enclosure; a slide mechanism that is connected to the enclosure and which is repositionable between a retracted position and an extended position; a cradle that is connected to the slide mechanism and which is configured for docking with the UAV such that the UAV is movable into and out of the enclosure during repositioning of the slide mechanism between the retracted position and the extended position; and a charging hub that is connected to the slide mechanism and which is configured for electrical connection to a power source of the UAV to charge the power source.

(139) In certain embodiments, the slide mechanism may include a stationary slide member that is fixedly connected to the enclosure and a movable slide member that is slidable in relation to the stationary slide member.

(140) In certain embodiments, the charging hub may be connected to the stationary slide member.

(141) In certain embodiments, the charging hub may extend into the cradle when the slide mechanism is in the retracted position.

(142) In certain embodiments, the charging hub may include a charging member that is configured for electrical connection to the power source of the UAV.

(143) In certain embodiments, the cradle may define an opening that is configured to receive the charging member such that the charging member moves into and out of the cradle during repositioning of the slide mechanism between the retracted position and the extended position.

(144) In certain embodiments, the charging hub may include: a base that is connected to the slide mechanism; an alignment bracket that is (movably) supported by the base; and a charging member that is connected to the alignment bracket and which is configured for electrical connection to the power source.

(145) In certain embodiments, the charging member may be connected to the alignment bracket such that the charging member and the alignment bracket are movable in unison along an axis of movement.

(146) In certain embodiments, the alignment bracket may include an anchor that extends into a

corresponding opening in the charging member to inhibit relative movement between the alignment bracket and the charging member.

(147) In certain embodiments, the base may be fixedly connected to the slide mechanism.

(148) In certain embodiments, the base may define a cavity that is configured to receive the alignment bracket such that the alignment bracket is movable through the cavity during repositioning between a normal position and a deflected position.

(149) In certain embodiments, the base may include a base wall defining the cavity.

(150) In certain embodiments, the base wall may define an opening that is configured to receive the alignment bracket to facilitate assembly of the charging hub.

(151) In certain embodiments, the base wall may be configured to support the alignment bracket during repositioning between the normal position and the deflected position.

(152) In certain embodiments, the base wall may define a chamfered surface that is configured for engagement with the alignment bracket to facilitate repositioning of the alignment bracket between the normal position and the deflected position.

(153) In certain embodiments, the charging hub may further include a biasing member that is located within the cavity.

(154) In certain embodiments, the biasing member may be configured to bias the alignment bracket towards the normal position.

(155) In certain embodiments, the biasing member may include a first end that is in engagement with the base and a second end that is in engagement with the alignment bracket.

(156) In certain embodiments, the alignment bracket may include an alignment member that is configured for insertion into a receptacle defined by the power source of the UAV.

(157) In certain embodiments, the alignment member may extend axially forward of the charging member along the axis of movement.

(158) In certain embodiments, the alignment member may be vertically offset from the biasing member.

(159) In certain embodiments, the charging hub may further include a cap that is removably connected to the base.

(160) In certain embodiments, the cap may overlie the charging member to inhibit rotation of the charging member and the alignment bracket in relation to the base.

(161) In another aspect of the present disclosure, a charging hub is disclosed for a base station that is configured for use with an unmanned aerial vehicle (UAV). The charging hub includes: a base; an alignment bracket that is movably supported by the base such that the alignment bracket is repositionable between a normal position and a deflected position; a biasing member that is positioned between the base and the alignment bracket and which is configured to bias the alignment bracket towards the normal position; a charging member that is connected to the alignment bracket such that the charging member moves contemporaneously with the alignment bracket during repositioning of the alignment bracket between the normal position and the deflected position; and a cap that is removably connected to the base such that the cap overlies the charging member to inhibit rotation of the charging member and the alignment bracket in relation to the base.

(162) In certain embodiments, the biasing member may include a first end that is in engagement with the base and a second end that is in engagement with the alignment bracket.

(163) In certain embodiments, the alignment bracket may include an anchor that extends into a corresponding opening in the charging member to inhibit relative movement between the alignment bracket and the charging member.

(164) In certain embodiments, the base may define a cavity that is configured to receive the alignment bracket such that the alignment bracket is movable through the cavity during repositioning between the normal position and the deflected position.

(165) In certain embodiments, the base may define an opening that is configured to receive the

alignment bracket to facilitate assembly of the charging hub.

(166) In certain embodiments, the base may include a base wall defining the cavity.

(167) In certain embodiments, the base wall may be configured to support the alignment bracket during repositioning between the normal position and the deflected position.

(168) In certain embodiments, the base wall may define a chamfered surface that is configured for engagement with the alignment bracket to facilitate repositioning of the alignment bracket between the normal position and the deflected position.

(169) In certain embodiments, the alignment bracket may include an alignment member that is configured for insertion into a receptacle defined by a power source of the UAV.

(170) In certain embodiments, the alignment member may extend axially forward of the charging member and may be vertically offset from the biasing member.

(171) In another aspect of the present disclosure, a method of using a base station to charge an unmanned aerial vehicle (UAV) is disclosed. The method includes: docking the UAV with a cradle of the base station; retracting the cradle into an enclosure of the base station via a slide mechanism; and electrically connecting a power source of the UAV to a charging hub connected to the slide mechanism to thereby charge the power source.

(172) In certain embodiments, docking the UAV with the cradle may include guiding the power source into a chamber defined by the cradle via contact between the UAV and tapered sidewalls of the cradle.

(173) In certain embodiments, retracting the cradle may include repositioning the slide mechanism from an extended position into a retracted position.

(174) In certain embodiments, repositioning the slide mechanism from the extended position into the retracted position may include telescopically repositioning a movable slide member in relation to a stationary slide member.

(175) In certain embodiments, the charging hub may be connected to the stationary slide member.

(176) In certain embodiments, electrically connecting the power source of the UAV to the charging hub may include inserting a charging member into the power source.

(177) In certain embodiments, retracting the cradle may include aligning a first electrical connector on the charging hub with an opening on the power source to thereby facilitate engagement of the first electrical connector with a second electrical connector on the power source.

(178) In certain embodiments, aligning the first electrical connector with the opening on the power source may include inserting an alignment bracket on the charging hub into a receptacle defined by the power source.

(179) In certain embodiments, retracting the cradle may include inserting the alignment bracket into the receptacle.

(180) In certain embodiments, inserting the alignment bracket into the receptacle may include repositioning the alignment bracket from a normal position into a deflected position via movement of the alignment bracket in relation to a base of the charging hub along an axis of movement.

(181) In certain embodiments, the method may further include repositioning the alignment bracket from the normal position into the deflected position, wherein the charging member is connected to the alignment bracket such that the charging member and the alignment bracket move in unison.

(182) In certain embodiments, repositioning the alignment bracket from the normal position into the deflected position may include compressing a biasing member that is located between the alignment bracket and a base of the charging hub, wherein the biasing member is configured to bias the alignment bracket towards the normal position.

(183) In certain embodiments, repositioning the alignment bracket from the normal position into the deflected position may include increasing a preloaded force (e.g., a biasing force) applied to the alignment bracket.

(184) In certain embodiments, inserting the alignment bracket into the receptacle may include inserting an alignment member on the alignment bracket into the receptacle.

(185) In certain embodiments, the alignment member may extend axially forward of the first electrical connector along the axis of movement.

(186) In certain embodiments, repositioning the alignment bracket from the normal position into the deflected position may include inhibiting rotation of the alignment bracket and the first electrical connector in relation to the base via a cap that is removably connected to the base.

(187) In another aspect of the present disclosure, a method of using a base station to charge an unmanned aerial vehicle (UAV) is disclosed. The method includes: docking the UAV with the base station; retracting the UAV towards a charging hub of the base station; inserting an alignment member carried by an alignment bracket on the charging hub into a receptacle on a power source of the UAV; inserting a charging member on the charging hub into an opening on the power source; increasing a preloaded force applied to the alignment bracket by a biasing member positioned within a base of the charging hub, wherein the biasing member is vertically offset from the alignment member; and inhibiting rotation of the alignment bracket in relation to the base via a cap overlying the charging member.

(188) In certain embodiments, increasing the preloaded force may include displacing the alignment bracket and the charging member.

(189) In certain embodiments, displacing the alignment bracket and the charging member may include compressing the biasing member between the alignment bracket and the base.

(190) In certain embodiments, displacing the alignment bracket and the charging member may include moving the alignment bracket and the charging member in unison.

(191) In certain embodiments, displacing the alignment bracket and the charging member may include moving the charging member axially within a channel defined by the cap.

(192) In another aspect of the present disclosure, a method of using a base station to charge an unmanned aerial vehicle (UAV) is disclosed. The method includes: docking the UAV with the base station; retracting the UAV towards a charging hub of the base station so as to insert an alignment bracket on the charging hub into a receptacle defined by a power source of the UAV and thereby align a first electrical connector on the charging hub with a second electrical connector on the power source; and engaging the first electrical connector and the second electrical connector to thereby establish an electrical connection between the base station and the UAV and charge the power source.

(193) In certain embodiments, retracting the UAV towards the charging hub may include compressing a biasing member positioned between the alignment bracket and a base of the charging hub supporting the alignment bracket.

(194) In certain embodiments, compressing the biasing member may include compressing the biasing member within a cavity defined by the base.

(195) In certain embodiments, retracting the UAV towards the charging hub may include displacing the alignment bracket to thereby compress the biasing member.

(196) In certain embodiments, displacing the alignment bracket may include causing corresponding displacement of a charging member supporting the first electrical connector and connected to the alignment bracket such that the alignment bracket and the charging member move in unison.

(197) In another aspect of the present disclosure, a base station is disclosed for an unmanned aerial vehicle (UAV). The base station includes: an enclosure that is configured to receive the UAV and which includes a front end having a front door and a rear end having a rear door; a slide mechanism that is connected to the enclosure; a cradle that is configured for docking with the UAV and which is connected to the slide mechanism such that the UAV is movable into and out of the enclosure during repositioning of the cradle between a retracted position and an extended position; a first electronics module that is removably connected to the enclosure adjacent to the rear door; a second electronics module that is removably connected to a roof section of the enclosure; and a third electronics module that is removably connected to the slide mechanism, whereby the first electronics module, the second electronics module, and the third electronics module are

individually removable from the base station.

(198) In certain embodiments, the first electronics module may include a main heat sink and an auxiliary heat sink.

(199) In certain embodiments, the auxiliary heat sink may be connected to the main heat sink such that the main heat sink defines a plurality of side walls collectively describing a perimeter of the first electronics module and the auxiliary heat sink defines an end wall of the first electronics module.

(200) In certain embodiments, the auxiliary heat sink may include one or more diffusers that are configured to increase thermal energy distribution (e.g., of the auxiliary heat sink).

(201) In certain embodiments, the first electronics module may further include: a logic board that is supported by the main heat sink such that the logic board is located between the main heat sink and the auxiliary heat sink; a first printed circuit board assembly (PCBA) that is supported by the main heat sink; and an interface member that is located between the main heat sink and the first PCBA.

(202) In certain embodiments, the first electronics module may be configured to facilitate data processing and control of the base station. For example, in certain embodiments, the first PCBA may include a processor that is configured to facilitate data processing and control of the base station.

(203) In certain embodiments, the main heat sink may define a cavity that is configured to receive the logic board.

(204) In certain embodiments, the interface member may include at least one thermally conductive section that is configured to facilitate thermal energy transfer between the first PCBA and the main heat sink and at least one electrically conductive section that is configured to electrically ground the first PCBA.

(205) In certain embodiments, the at least one electrically conductive section may include an adhesive to connect the first PCBA to the main heat sink.

(206) In certain embodiments, the base station may further include an air circulation module that is connected to the enclosure adjacent to the rear door.

(207) In certain embodiments, the air circulation module may be positioned about the first electronics module to facilitate cooling thereof.

(208) In certain embodiments, the enclosure may include a frame that defines an outer surface and an inner surface.

(209) In certain embodiments, the first electronics module may be connected to the outer surface of the frame and the air circulation module may be connected to the inner surface of the frame such that the frame is located between the first electronics module and the air circulation module, whereby the first electronics module is removable from the base station separately from the air circulation module.

(210) In certain embodiments, the air circulation module may include ducting that is configured to direct air across the first electronics module and a fan that is supported by the ducting.

(211) In certain embodiments, the rear door may include a non-metallic frame and a metallic panel that is connected to the non-metallic frame.

(212) In certain embodiments, the metallic panel may be positioned in correspondence with the first electronics module so as to create a Faraday cage for the first electronics module and thereby reduce electromagnetic emissions from the base station.

(213) In certain embodiments, the rear door may further include a sealing member that extends about the metallic panel and which is configured for engagement with the enclosure.

(214) In certain embodiments, the second electronics module may be configured to control opening and closure of the front door.

(215) In certain embodiments, the second electronics module may include: an access panel that is removably connected to the roof section of the enclosure; a second PCBA that is connected to the access panel; and a fan that is connected to the access panel.

(216) In certain embodiments, the access panel may be removably connected to an inner surface of the roof section via a plurality of mechanical fasteners such that the second electronics module is accessible from within the enclosure.

(217) In certain embodiments, the plurality of mechanical fasteners may be configured as thumb screws to allow for toolless connection and disconnection of the access panel.

(218) In certain embodiments, the third electronics module may be configured to facilitate and control repositioning of the cradle between the retracted position and the extended position. For example, in certain embodiments, the third electronics module may be configured to control the slide mechanism.

(219) In certain embodiments, the third electronics module may include a third PCBA that is removably connected to the slide mechanism via a plurality of mechanical fasteners such that the third electronics module is accessible from within the enclosure upon removal of the UAV.

(220) In certain embodiments, the slide mechanism may include a stationary slide member that is connected to the enclosure and a movable slide member that is slidable in relation to the stationary slide member.

(221) In certain embodiments, the third PCBA may be removably connected to the stationary slide member.

(222) In another aspect of the present disclosure, a base station is disclosed for an unmanned aerial vehicle (UAV). The base station includes: an enclosure defining a window that is configured to receive the UAV to allow for entry of the UAV into the base station and exit of the UAV from the base station; a door that is movably connected to the enclosure such that the door is repositionable between a closed position and an open position; a sealing member that extends about the window and which is configured for engagement with the door so as to form a seal therewith when the door is in the closed position; and a heating system that is supported by the enclosure and which is configured to heat the door and/or the sealing member to support operation (e.g., opening and closure) of the door in a cold environment.

(223) In certain embodiments, the heating system may include at least one light source and at least one heating element.

(224) In certain embodiments, the at least one light source may be configured to identify a status of the base station.

(225) In certain embodiments, the at least one light source may be supported on an outer surface of the enclosure and the at least one heating element may be supported on an inner surface of the enclosure.

(226) In certain embodiments, the base station may further include a thermal interface material that is located between the enclosure and the at least one heating element.

(227) In certain embodiments, the heating system may further include at least one temperature sensor that is supported by the enclosure.

(228) In certain embodiments, the door may include a thermally conductive member to further facilitate heating of the door.

(229) In certain embodiments, the thermally conductive member may be embedded within the door.

(230) In certain embodiments, the sealing member may include a thermally conductive member to further facilitate heating of the sealing member.

(231) In certain embodiments, the thermally conductive member may be embedded within the sealing member.

(232) In certain embodiments, the base station may further include at least one additional heating element that is supported by a roof section of the enclosure.

(233) In another aspect of the present disclosure, a docking system is disclosed for an unmanned aerial vehicle (UAV). The docking system includes a base station that is configured to receive the UAV and a pedestal that is configured to support the base station in an elevated position. The pedestal defines an interior space that is configured in correspondence with an outer contour of the

base station such that the base station is positionable within the pedestal to protect the base station during nonuse.

(234) In certain embodiments, the pedestal may be unitary in construction.

(235) In certain embodiments, the pedestal may include: an upper wall having a non-linear configuration; first and second side walls extending from the upper wall, wherein each of the first and second side walls have a generally linear configuration; and first and second base walls extending laterally inward from the first and second side walls, respectively, wherein each of the first and second base walls have a generally linear configuration.

(236) In certain embodiments, the upper wall may include: a first segment that extends laterally inward from the first side wall; a second segment that extends laterally inward from the second side wall; a third segment that extends in generally parallel relation to the first segment and the second segment; a fourth segment that extends between the first segment and the third segment; and a fifth segment that extends between the second segment and the third segment.

(237) In certain embodiments, the first segment and the second segment may be vertically aligned.

(238) In certain embodiments, the third segment may be vertically offset from the first segment and the second segment so as to define a well.

(239) In certain embodiments, the first side wall may be configured so as to define a first acute angle with a first reference axis oriented in generally orthogonal relation to the first base wall and the second side wall may be configured so as to define a second acute angle with a second reference axis oriented in generally orthogonal relation to the second base wall.

(240) In certain embodiments, the well may be configured in correspondence with at least one antenna on the base station to create vertical clearance for the at least one antenna when the base station is positioned within the pedestal.

(241) In certain embodiments, the base station may include a pair of antennas.

(242) In certain embodiments, the fourth segment and the fifth segment may respectively subtend generally identical obtuse angles with the first segment and the second segment such that the well extends into a space defined between the pair of antennas when the base station is positioned within the pedestal.

(243) In another aspect of the present disclosure, a base station is disclosed for an unmanned aerial vehicle (UAV). The base station includes: an enclosure; a slide mechanism that is connected to the enclosure and which is repositionable between a retracted position and an extended position; and a cradle that is connected to the slide mechanism and which defines a chamber that is configured to receive the UAV such that the UAV is movable into and out of the enclosure during repositioning of the slide mechanism between the retracted position and the extended position. The cradle includes: an upper shell; a lower shell that is connected to the upper shell; and at least one thermal insulator that is located between the upper shell and the lower shell.

(244) In certain embodiments, the cradle may define an airflow channel that extends about the chamber and which is configured to facilitate air circulation within the cradle.

(245) In certain embodiments, the cradle may further define an air inlet (vent) and an air outlet (vent) that are in communication with the airflow channel and which are configured to direct air flow across the chamber to thereby heat or cool a power source of the UAV when the UAV is docked within the cradle.

(246) In certain embodiments, the cradle may include a rear end that defines lead-ins which are configured for engagement with the enclosure during retraction of the cradle to facilitate entry of the cradle into the enclosure.

(247) In certain embodiments, the upper shell may define an angled guide surface that is configured for engagement with the UAV to thereby direct the UAV into the chamber and facilitate proper docking of the UAV within the cradle.

(248) In certain embodiments, the upper shell and the lower shell may each include a non-metallic material.

(249) In certain embodiments, the at least one thermal insulator may include an insulative foam.

(250) In certain embodiments, the airflow channel may be defined by the at least one thermal insulator.

(251) In certain embodiments, the airflow channel may include a discontinuous configuration.

(252) In certain embodiments, the airflow channel may include a first channel portion and a second channel portion.

(253) In certain embodiments, the first channel portion and the second channel portion may be separated by a nose section of the cradle.

(254) In certain embodiments, the first channel portion may be in communication with the air inlet and the second channel portion may be in communication with the air outlet.

(255) In another aspect of the present disclosure, a base station is disclosed for an unmanned aerial vehicle (UAV). The base station includes: an enclosure that is configured to receive the UAV; a door that is movably connected to the enclosure such that the door is repositionable between a closed position and an open position; a primary heating system that is associated with a roof section of the enclosure; and a secondary heating system that is associated with the door.

(256) In certain embodiments, the secondary heating system may include an exterior light source and an interior heating element.

(257) In certain embodiments, the primary heating system and/or the secondary heating system may be configured for automatic activation upon receiving an activation signal.

(258) In certain embodiments, the base station may further include a temperature sensor that is configured to relay the activation signal to the primary heating system and/or the secondary heating system upon detecting a threshold temperature.

(259) In certain embodiments, the base station may further include a visualization system that is supported by the enclosure and which is configured to visually inspect environmental conditions.

(260) In certain embodiments, the visualization system may be configured to relay the activation signal to the primary heating system and/or the secondary heating system.

(261) In another aspect of the present disclosure, a method is disclosed for heating a base station for an unmanned aerial vehicle (UAV). The method includes activating a primary heating system that is associated with a roof section of the base station to expose at least one fiducial that is supported by the roof section and thereby facilitate visual identification of the base station by the UAV and/or guidance of the UAV during landing and docking with the base station.

(262) In certain embodiments, the method may further include activating a secondary heating system that is associated with a door of the base station to facilitate opening and closure thereof.

(263) In certain embodiments, activating the secondary heating system may include activating at least one thermally conductive member, wherein the at least one thermally conductive member is connected to the door and/or a sealing member that is configured for engagement with the door.

(264) In certain embodiments, activating the secondary heating system may include activating an exterior light source and activating an interior heating element.

(265) In certain embodiments, activating the primary heating system and activating the secondary heating system may include automatically activating the primary heating system and automatically activating the secondary heating system upon receiving an activation signal from at least one of: a temperature sensor on the base station that is configured to detect a threshold temperature; a visualization system on the base station that is configured to visually inspect environmental conditions; and a weather station that is wirelessly connected to the base station.

(266) In another aspect of the present disclosure, a docking system is disclosed for an unmanned aerial vehicle (UAV). The docking system includes a base station that is configured to receive the UAV and a pedestal that is configured to receive and support the base station such that the docking system is reconfigurable between a nested configuration, in which the base station is positioned within an interior space defined by the pedestal, and a stacked configuration, in which the base station is supported by the pedestal in an elevated position.

(267) In certain embodiments, the pedestal may be configured to create clearance with the base station about an entire periphery thereof so as to inhibit contact between the pedestal and the base station in the nested configuration.

(268) In certain embodiments, the interior space may be configured in correspondence with an outer contour of the base station.

(269) In certain embodiments, the base station may include a pair of antennas.

(270) In certain embodiments, the pedestal may define a well that is configured for positioning between the pair of antennas when the docking system is in the nested configuration.

(271) In certain embodiments, the pedestal may include a plurality of adjustable footings that are configured for removable connection thereto.

(272) In another aspect of the present disclosure, a method of using a docking system for an unmanned aerial vehicle (UAV) is disclosed. The method includes: storing a base station for the UAV within an interior space defined by a pedestal during nonuse of the base station; removing the base station from the interior space defined by the pedestal; and supporting the base station on the pedestal in an elevated position.

(273) In certain embodiments, the method may further include adjusting at least one footing on the pedestal to thereby stabilize the pedestal and the base station when the base station is in the elevated position.

(274) In certain embodiments, supporting the base station on the pedestal may include releasably connecting the base station to the pedestal to inhibit unintended separation thereof.

(275) In certain embodiments, the method may further include: facilitating takeoff of the UAV from the base station; docking the UAV with the base station after flight; and nesting the base station within the pedestal following docking of the UAV by returning the base station to the interior space.

(276) In certain embodiments, nesting the base station within the pedestal may include positioning a well defined by the pedestal between antennas on the base station.

(277) In another aspect of the present disclosure, a base station is disclosed for an unmanned aerial vehicle (UAV). The base station includes: an enclosure; a slide mechanism that is connected to the enclosure and which is repositionable between a retracted position and an extended position; and a cradle that is connected to the slide mechanism and which defines a chamber that is configured to receive the UAV such that the UAV is movable into and out of the enclosure during repositioning of the slide mechanism between the retracted position and the extended position. The cradle includes: an upper shell that defines an air inlet and an air outlet; a lower shell that is connected to the upper shell; and at least one thermal insulator that is positioned between the upper shell and the lower shell. The lower shell defines a first airflow opening that is in communication with the air inlet and a second airflow opening in communication with the air outlet. The at least one thermal insulator defines an airflow channel that is in communication with the first airflow opening and the second airflow opening and which extends about the chamber to facilitate air circulation within the cradle.

(278) In certain embodiments, the at least one thermal insulator may include an upper thermal insulator and a lower thermal insulator.

(279) In certain embodiments, the airflow channel may extend between the upper thermal insulator and the lower thermal insulator.

(280) In certain embodiments, the airflow channel may include a discontinuous configuration.

(281) In certain embodiments, the airflow channel may include a first channel portion and a second channel portion.

(282) In certain embodiments, the first channel portion may be in communication with the air inlet and the first airflow opening, and the second channel portion may be in communication with the air outlet and the second airflow opening.

(283) In certain embodiments, the first channel portion and the second channel portion may be

separated by a nose section of the cradle such that the nose section inhibits airflow between the first channel portion and the second channel portion to thereby direct airflow from the air inlet, across the chamber, and into the air outlet.

(284) In another aspect of the present disclosure, a base station is disclosed for an unmanned aerial vehicle (UAV). The base station includes: an enclosure; a slide mechanism that is connected to the enclosure and which is repositionable between a retracted position and an extended position; a charging hub that is connected to the slide mechanism and which is configured for electrical connection to a power source of the UAV; and a cradle that is connected to the slide mechanism and which defines a chamber that is configured to receive the UAV such that the UAV is movable into and out of the enclosure during repositioning of the slide mechanism between the retracted position and the extended position. The cradle includes: a housing and at least one thermal insulator. The at least one thermal insulator is located within the housing and defines an airflow channel that extends discontinuously about the chamber.

(285) In certain embodiments, the housing may define a charging window that is configured to receive the charging hub such that the charging hub is extendable into the cradle during repositioning of the slide mechanism between the retracted position and the extended position.

(286) In certain embodiments, the housing may define an air inlet and an air outlet that are positioned on opposite sides of the chamber.

(287) In certain embodiments, the airflow channel may include a first channel portion that is in communication with the air inlet and a second channel portion that is in communication with the air outlet.

(288) In certain embodiments, the first channel portion and the second channel portion may be separated by a nose section of the cradle such that the nose section inhibits airflow therebetween to thereby direct airflow from the air inlet, across the chamber, and into the air outlet.

(289) In another aspect of the present disclosure, a base station is disclosed for an unmanned aerial vehicle (UAV). The base station includes: an enclosure that is configured to receive the UAV and a charging hub that is operatively connected to the enclosure and which is configured to charge the UAV. The charging hub includes: a base; an alignment bracket that is movably supported by the base such that the alignment bracket is repositionable between a normal position and a deflected position; and a charging member that is configured for electrical connection to the UAV. The charging member is connected to the alignment bracket such that the charging member and the alignment bracket are movable in unison along an axis of movement during repositioning of the alignment bracket between the normal position and the deflected position.

(290) In certain embodiments, the charging hub may further include a biasing member that is positioned between the base and the alignment bracket and which is configured to bias the alignment bracket towards the normal position.

(291) In certain embodiments, the alignment bracket may include an alignment member that is configured for insertion into a receptacle defined by the UAV to facilitate proper positioning of the charging member and electrical connection of the charging hub to the UAV.

(292) In certain embodiments, the alignment member may extend axially forward of the charging member along the axis of movement.

(293) In certain embodiments, the alignment member may be vertically offset from the biasing member.

(294) In another aspect of the present disclosure, a base station is disclosed for an unmanned aerial vehicle (UAV). The base station includes: an enclosure having a front end that is configured to receive the UAV and a rear end; a cradle that is configured for docking with the UAV and which is movable in relation to the enclosure via a slide mechanism; a first electronics module that is removably connected to the rear end of the enclosure and which is configured to facilitate data processing and control of the base station; and an air circulation module that is connected to the rear end of the enclosure and which is positioned about the first electronics module to facilitate

cooling thereof.

(295) In certain embodiments, the base station may further include a second electronics module and a third electronics module.

(296) In certain embodiments, the second electronics module may be removably connected to a roof section of the enclosure and may be configured to facilitate opening and closure of the enclosure, and the third electronics module may be removably connected to the slide mechanism and may be configured to facilitate repositioning of the cradle, whereby the first electronics module, the second electronics module, and the third electronics module may be individually removable from the base station.

(297) In certain embodiments, the first electronics module may include a heat sink.

(298) In certain embodiments, the ducting may define a chamber having an inner contour that corresponds to an outer contour of the heat sink.

(299) In another aspect of the present disclosure, a base station is disclosed for an unmanned aerial vehicle (UAV). The base station includes: a metallic enclosure; a first electronics module; a second electronics module; and a third electronics module, wherein the first electronics module, the second electronics module, and the third electronics module are each configured for individual removal from the metallic enclosure. The metallic enclosure is configured to receive the UAV and includes a front end having a front door and a rear end having a rear door. The rear door is located adjacent to the first electronics module and includes a metallic panel that is positioned in correspondence with the first electronics module so as to create a Faraday cage for the first electronics module and thereby reduce electromagnetic emissions from the base station.

(300) In certain embodiments, the rear door may further include a non-metallic frame.

(301) In certain embodiments, the metallic panel may be connected to the non-metallic frame.

(302) In certain embodiments, the second electronics module may include an access panel that is removably connected to a roof section of the metallic enclosure.

(303) In certain embodiments, the access panel may be removably connected to an inner surface of the roof section via a plurality of mechanical fasteners such that the second electronics module is accessible from within the metallic enclosure.

(304) In certain embodiments, the mechanical fasteners may be configured to allow for toolless connection of the access panel to the roof section and toolless disconnection of the access panel from the roof section.

(305) In certain embodiments, the base station may further include a slide mechanism and a cradle that is connected to the slide mechanism.

(306) In certain embodiments, the slide mechanism may be connected to the metallic enclosure.

(307) In certain embodiments, the slide mechanism may be repositionable between a retracted position and an extended position.

(308) In certain embodiments, the cradle may be configured for docking with the UAV such that the UAV is movable into and out of the metallic enclosure during repositioning of the slide mechanism between the retracted position and the extended position.

(309) In certain embodiments, the third electronics module may be removably connected to the slide mechanism such that the third electronics module is accessible from within the metallic enclosure upon removal of the UAV.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present disclosure is best understood from the following detailed description when read in conjunction with the accompanying drawings. It is emphasized that, according to common practice, the various features of the drawings are not to-scale. On the contrary, the dimensions of the various

features are arbitrarily expanded or reduced for clarity.

(2) FIG. 1 is a front, perspective view of a base station (dock) according to the principles of the present disclosure.

(3) FIG. 2 is a partial, side view of the base station shown with one embodiment of a UAV docked within a cradle of the base station, which includes a plurality of propulsion mechanisms (e.g., propeller assemblies), each of which includes a hub and a plurality of propeller blades connected thereto.

(4) FIG. 3 is a partial, side view of the base station shown with an alternate embodiment of the UAV seen in FIG. 2.

(5) FIG. 4 is a bottom, perspective view of a power source of the UAV.

(6) FIG. 5 is a partial, side, perspective view of the power source of the UAV.

(7) FIG. 6 is a side, schematic view of the base station.

(8) FIG. 7 is a partial, rear, perspective view of the base station.

(9) FIG. 8 is a partial, side, perspective view of the base station illustrating a plurality of actuators that are configured to open and close a (front) door of the base station.

(10) FIGS. 9 and 10 are partial, top, perspective views of the base station illustrating the plurality of actuators.

(11) FIG. 11 is a partial, front, perspective view of the base station illustrating a cap that is supported on a slide mechanism, which facilitates movement of the cradle between a retracted position and an extended position.

(12) FIG. 12 is a partial, rear, perspective view of the cap shown overlayed by the door of the base station upon closure.

(13) FIG. 13 is a partial, side, perspective view of the base station with the cradle shown in the extended position.

(14) FIG. 14 is top, perspective view of the slide mechanism according to one embodiment of the disclosure, in which the slide mechanism is connected (secured) to an enclosure of the base station via a plurality of first mounts and a plurality of second mounts.

(15) FIG. 15 is a top, perspective view of the slide mechanism, the first mounts, and the second mounts.

(16) FIG. 16 is a bottom, plan view of the slide mechanism, the first mounts, and the second mounts.

(17) FIG. 17 is a partial, side, perspective view of the slide mechanism, one of the first mounts, and one of the second mounts during assembly.

(18) FIG. 18 is a partial, side, perspective view of the slide mechanism, the first mount, and the second mount seen in FIG. 17 upon assembly.

(19) FIG. 19 is bottom, perspective view of one of the first mounts.

(20) FIG. 20 is transverse (horizontal), cross-sectional view of one of the first mounts.

(21) FIG. 21 is an axial (vertical), cross-sectional view of one of the first mounts.

(22) FIG. 22 is an axial (vertical), cross-sectional view illustrating connection of the slide mechanism to the enclosure via one of the first mounts.

(23) FIG. 23 is a side, perspective view of one of the second mounts.

(24) FIG. 24 is an axial (vertical), cross-sectional view illustrating assembly of the enclosure, the slide mechanism, and one of the second mounts.

(25) FIG. 25 is a partial, top, perspective view of the slide mechanism, one of the first mounts, and one of the second mounts during assembly and illustrating a lateral (radial, horizontal) gap between the slide mechanism and the second mount.

(26) FIG. 26 is a side, plan view of the slide mechanism, the first mount, and the second mount seen in FIG. 25 upon assembly and illustrating an axial (vertical) gap between the slide mechanism and the second mount.

(27) FIG. 27 is a partial, top, perspective view of the base station illustrating one or more

connection antennas and one or more fiducials that are supported on a roof section thereof.

(28) FIG. **28** is a partial, top, perspective view of the base station according to an embodiment of the disclosure that includes a plurality of fiducials on the roof section.

(29) FIG. **29** is a partial, front, perspective view of the base station illustrating a status indicator.

(30) FIG. **30** is a partial, top, perspective view of the base station according to an embodiment of the disclosure that includes an illumination system on the roof section.

(31) FIG. **31A** is a partial, front, perspective view of the base station during movement of the cradle into the retracted position after docking of the UAV.

(32) FIG. **31B** is a partial, front, perspective view of the base station during movement of the cradle into the retracted position after docking of the UAV illustrating one embodiment of a contact member that is configured to facilitate reconfiguration (e.g., folding) of one or more antennas on the UAV

(33) FIG. **32** is partial, top, plan view of the base station and the UAV shown in a flight configuration.

(34) FIG. **33** is top, plan view of the UAV shown separated from the base station.

(35) FIGS. **34A-34C** are top, plan views of the UAV shown in the storage configuration with the propeller assemblies shown in a variety of orientations.

(36) FIG. **34D** is a partial, front, perspective view of the base station and the UAV during retraction of the UAV into the base station according to one embodiment of the disclosure.

(37) FIG. **35** is a partial, top, plan view of the UAV illustrating desired positional ranges for the propeller assemblies of the UAV in the storage configuration.

(38) FIG. **36** is a partial, end view of the base station shown with the door shown in an open position according to one embodiment of the disclosure, which includes engagement members (e.g., bumpers) that are supported by the actuators and configured to for contact with the propeller assemblies to facilitate reconfiguration of the UAV into the storage configuration.

(39) FIG. **37** is a partial, side, plan view of the base station and one of the engagement members.

(40) FIG. **38** is an end view of one of the engagement members shown separated from the base station.

(41) FIG. **39** is a partial, side, plan view of the base station illustrating an (angular) range of motion for the door.

(42) FIG. **40** is a partial, side, plan view of the base station illustrating an (angular) range of motion for the actuators and the engagement members.

(43) FIG. **41** illustrates a method of reconfiguring (e.g., folding) the propeller assemblies of the UAV

(44) FIG. **42** is a top, plan view of one of the propeller assemblies illustrating contact with one of the engagement members.

(45) FIG. **43** is a top, plan view of the propeller assembly and the engagement member seen in FIG. **42** during folding of the propeller assembly.

(46) FIG. **44** is an enlargement of the area of detail identified in FIG. **43**.

(47) FIG. **45** is side, plan view of an alternate embodiment of the base station, in which the engagement members are supported by the door.

(48) FIG. **46** is an end, plan view of the base station seen in FIG. **45**.

(49) FIGS. **47** and **48** are opposite side, schematic views of a temperature control system of the base station, which includes a first air circuit; a second air circuit; and a thermoelectric conditioner (TEC).

(50) FIG. **49** is a partial, side, schematic view of the cradle and the second air circuit.

(51) FIG. **50** is partial, side, schematic view of the temperature control system.

(52) FIG. **51** is a partial, side, schematic view of the temperature control system illustrating a first heat sink and a second heat sink.

(53) FIG. **52** is a partial, side, schematic view of the first heat sink and the second heat sink, which

is shown located within a plenum of the second air circuit.

(54) FIG. 53A is a partial, top, schematic view of the base station according to an embodiment of the disclosure that includes one or more heating elements on the roof section.

(55) FIG. 53B is a partial, bottom, schematic view of the base station illustrating the heating element(s) on the roof section seen in FIG. 53A.

(56) FIG. 54 is a front, plan view of the base station shown nested within a pedestal.

(57) FIG. 55 is a side, perspective view of the base station and the pedestal seen in FIG. 54 with the base station shown in an elevated position.

(58) FIG. 56 is a rear, perspective view of an insulated cradle according to one embodiment of the disclosure;

(59) FIG. 57 is a rear, perspective view of the insulated cradle seen in FIG. 56 with parts separated.

(60) FIG. 58 is a side, perspective view illustrating mating of the insulated cradle and the plenum of the second air circuit.

(61) FIG. 59 is a partial, rear, perspective view of the base station according to one embodiment of the disclosure, which includes a plurality of heating elements secured to an inner surface of the enclosure.

(62) FIG. 60 is a partial, front, perspective view of the base station with the (front) door shown in the open position.

(63) FIG. 61 is a partial, rear, perspective view of the base station according to one embodiment of the disclosure, which includes a thermal interface material located between the enclosure and the heating elements.

(64) FIG. 62 is a front, perspective view of the base station according to one embodiment of the disclosure in which the status indicator(s) are configured to heat the door and/or a sealing member that is supported by the enclosure and which is configured for engagement with the door.

(65) FIG. 63 is a partial, front, perspective view of an alternate embodiment of the base station, which includes thermally conductive members that are embedded within the door and/or the sealing member.

(66) FIG. 64 is a partial, top, schematic view of the base station illustrating an internal fan.

(67) FIG. 65 is a partial, rear, perspective view of the base station illustrating one or more channels that collect and direct water.

(68) FIG. 66 is a top, perspective view of the UAV shown connected to a charging hub of the base station, which includes: a base; an alignment bracket; one or more biasing members; a charging member; and a cap.

(69) FIG. 67 is a partial, top, plan view of the UAV and the charging hub shown with the cap removed.

(70) FIG. 68 is a top, perspective view of the charging hub shown separated from the UAV.

(71) FIG. 69 is a front, plan view of the charging hub.

(72) FIG. 70 is a rear, plan view of the charging hub

(73) FIG. 71A is a longitudinal, cross-sectional view of the UAV and the charging hub taken along line 71A-71A in FIG. 66 with the alignment bracket shown in a normal position.

(74) FIG. 71B is a longitudinal, cross-sectional view of the UAV and the charging hub with the alignment bracket shown in a deflected position.

(75) FIG. 72 is a partial, longitudinal, cross-sectional view of the charging hub.

(76) FIG. 73 is a partial, longitudinal, cross-sectional view of the charging hub shown with the charging member removed.

(77) FIG. 74 is a top, plan view of the charging hub shown with the cap removed.

(78) FIG. 75 is a top, plan view of the charging hub according to one embodiment of the disclosure, which includes a pair of biasing members.

(79) FIG. 76 is a rear, plan view of the base station.

(80) FIG. 77 is a front, perspective view of a (first) electronics module included in the base station.

- (81) FIG. **78** is a front, perspective view of the electronics module seen in FIG. **77** with parts separated.
- (82) FIG. **79** is a front, perspective view of the electronics module seen in FIG. **77** shown with an air circulation module.
- (83) FIG. **80** is a rear, perspective view illustrating connection of the electronics module seen in FIG. **77**.
- (84) FIG. **81** is a rear, plan view of the base station upon connection of the electronics module seen in FIG. **77**.
- (85) FIG. **82** is a front, perspective view of the base station shown with the air circulation module connected.
- (86) FIG. **83** is a rear, perspective view of the base station with a rear door thereof shown in an open position.
- (87) FIG. **84** is a front, perspective view of the rear door of the base station.
- (88) FIG. **85** is a partial, top, perspective view of the base station illustrating a (second) electronics module.
- (89) FIG. **86** is a partial, side, perspective view of the base station illustrating the electronics module seen in FIG. **85**.
- (90) FIG. **87** is a front, perspective view of the base station illustrating the electronics module seen in FIG. **85**.
- (91) FIG. **88** is a partial, front, perspective view of the base station illustrating a (third) electronics module.

DETAILED DESCRIPTION

Overview

- (92) The present disclosure relates to a base station for use with a UAV that is configured to not only charge the power source of the UAV, but regulate the temperature of the power source of the UAV. In various embodiments of the disclosure, depending upon the environmental conditions, the base station may be configured to cool the power source of the UAV (e.g., when the base station and the UAV are used in hot environments) or heat the power source of the UAV (e.g., when the base station and the UAV are used in cold environments).
- (93) To facilitate cooling and/or heating of the power source of the UAV, the base station includes a temperature control system. The temperature control system includes: a thermoelectric conditioner (TEC); a first air circuit that is thermally connected to the TEC and which is configured to regulate (e.g., increase or decrease) temperature of the TEC; and a second air circuit that is thermally connected to the TEC such that the TEC is located between the first air circuit and the second air circuit. The second air circuit is configured to direct treated air (e.g., air that has been either cooled or heated) across the power source of the UAV to thereby heat or cool the power source (subject to environmental conditions).
- (94) To increase functionality and improve operation of the base station, the base station includes a plurality of additional (ancillary) systems that are configured to address environmental concerns (e.g., humidity, precipitation, etc.), security concerns (e.g., anti-theft systems and mechanisms), etc. For example, the base station may include: a heating element that is supported by a roof section to reduce the presence of snow and/or ice; one or more fiducials that facilitate visual identification of the base station by the UAV; an illumination system that improves visibility of the one or more fiducials (e.g., during nighttime operation); and a visualization system (e.g., a digital image capturing device) that supports observation and visual analysis of the environment in which the base station and the UAV are located.
- (95) The base station includes a cradle that is configured to receive the UAV during docking and which is extendable from and retractable into the base station via a slide mechanism. In certain embodiments of the disclosure, the slide mechanism is (indirectly) connected (secured) to the base station (e.g., to a sheet metal base) via first and second mounts, which separate the slide mechanism

from the base station in order to reduce vibration (and other such movement) of the slide mechanism during extension and retraction.

(96) In certain embodiments of the disclosure, upon docking of the UAV with the base station, propeller assemblies on the UAV may be reconfigured (e.g., folded) from an extended configuration into a collapsed configuration, which not only allows for a reduction in the overall size of the base station, but inhibits (if not entirely prevents) undesirable contact with the propeller assemblies. To facilitate such reconfiguration, the base station includes engagement members, which may be supported by (connected to) the (front) door of the base station, actuators for the door, or any other suitable structure, and are configured for contact with the propeller assemblies to facilitate folding thereof. More specifically, during retraction of the cradle and the UAV into the base station, the propeller assemblies are folded via bidirectional rotation into contact with the engagement members.

(97) Referring now to the drawings, FIGS. 1 and 2 illustrate an unmanned aerial vehicle (UAV) 10 and a base (docking) station 100 that is configured for automated servicing (e.g., docking, storage, charging, operation, etc.) and accommodation of the UAV 10. While a single UAV 10 and a single base station 100 are shown and described herein, in certain embodiments of the disclosure, it is envisioned that a plurality of UAVs 10 and a plurality of base stations 100 may be utilized depending, for example, upon the particular intended use of the UAVs 10. The UAV

(98) The UAV 10 includes one or more propulsion mechanisms (systems) 12 and a power source 14 (e.g., a battery 16). To support autonomous landing and docking of the UAV 10 with the base station 100, it is envisioned that the UAV 10 may follow any suitable process or procedure and may include any suitable electrical and/or logic components, as described in U.S. application Ser. No. 16/991,122 ("the '122 application"), the entire contents of which are hereby incorporated by reference.

(99) The propulsion mechanism(s) 12 may include any components and/or structures suitable for the intended purpose of supporting flight of the UAV 10. For example, in the particular embodiment of the UAV 10 seen in FIGS. 2 and 32, the propulsion mechanism(s) 12 are configured as propeller assemblies 18 that include: propeller arms 38; (rotatable) hubs 40 that are supported by the propeller arms 38; and a plurality of propeller blades 42 that are connected (secured) to the hubs 40, either directly or indirectly (operatively). More specifically, the hubs 40 each include: a motor 44 (or other such drive mechanism); a rotatable drive shaft 46, which is connected to the motor 44; and a plurality of supports 48, which are connected to (and extend between) the drive shaft 46 and the propeller blades 42 such that rotation of the drive shaft 46 causes corresponding rotation of the propeller blades 42. It should be appreciated, however, that the particular configuration and/or components of the propulsion mechanism(s) 12 may be varied without departing from the scope of the present disclosure. FIG. 3, for example, illustrates an alternate configuration for the UAV 10.

(100) In the particular embodiment of the UAV 10 illustrated, the UAV 10 includes four propeller assemblies 18. More specifically, the UAV 10 includes: a (first) rear propeller assembly 18_{ri}; a (second) rear propeller assembly 18_{rii}; a (first) front propeller assembly 18_{fi}; and a (second) front propeller assembly 18_{fii}. As seen in FIG. 2, the rear propeller assemblies 18_{ri}, 18_{rii} and the front propeller assemblies 18_{fi}, 18_{fii} are oriented in (vertically) opposite directions (e.g., the rear propeller assemblies 18_{ri}, 18_{rii} are oriented (vertically) upwards and the front propeller assemblies 18_{fi}, 18_{fii} are oriented (vertically) downwards), whereby the rear propeller assemblies 18_{ri}, 18_{rii} are positioned in a first vertical location (e.g., height) and the front propeller assemblies 18_{fi}, 18_{fii} are positioned in a second, lower vertical location (e.g., height). It should be appreciated, however, that the particular number of propeller assemblies 18, the configuration of the propeller assemblies 18, the location of the propeller assemblies 18, and/or the orientation of the propeller assemblies 18 may be varied in alternate embodiments without departing from the scope of the present disclosure. As such, embodiments of the UAV 10 including both fewer and greater numbers of propeller

assemblies **18** are also envisioned herein and would not be beyond the scope of the present disclosure.

(101) It is envisioned that the propeller assemblies **18** may include either a fixed configuration or a variable configuration. For example, it is envisioned that the propeller assemblies **18** may be reconfigurable between an extended (first) configuration and a collapsed (folded, second) configuration to allow for a reduction in the overall size of the UAV **10** (e.g., during entry into the base station **100**) and, thus, a reduction in the overall size of the base station **100**, as described in further detail below. To facilitate reconfiguration of the propeller assemblies **18** between the extended configuration and the collapsed configuration, in certain embodiments, it is envisioned that the propeller blades **42** may be pivotably connected to the supports **48** via pivot members **50** (FIGS. **32**, **42-44**) (e.g., pins, posts, or the like) so as to facilitate folding of the propeller assemblies **18**, further details of which are provided below.

(102) The power source **14** is located (e.g., attached to or otherwise supported on) a lower (bottom) surface of the UAV **10** and includes one or more conducting (electrical) contacts (not shown) that are configured for engagement (contact) with one or more corresponding conducting (electrical) contacts on the base station **100** to enable charging of the power source **14**, as described in further detail below.

(103) Heat Exchange

(104) As seen in FIGS. **4** and **5**, the power source **14** includes one or more power cells **20**; one or more thermal transfer members **22**; and a heat exchanger **24**, which defines a lower (bottom) surface of the power source **14** and acts as a cover for the power cell(s) **20** and the thermal transfer member(s) **22**. The thermal transfer member(s) **22** and the heat exchanger **24** are configured to facilitate the transfer of thermal energy between the power source **14** and the ambient (air) to decrease or increase temperature of the power source **14**. For example, depending upon the particular environment in which the UAV **10** and the base station **100** are employed, the thermal transfer member(s) **22** and the heat exchanger **24** may be utilized to dissipate heat generated by the power source **14** during use and/or charging of the UAV **10** (e.g., in hot environments) or to transfer heat to the power source **14** (e.g., in cold environments) to thereby improve efficiency, operation, and/or the usable life of the UAV **10** and/or the power source **14**.

(105) In the particular embodiment illustrated, the power source **14** includes a plurality of individual (e.g., discrete) power cells **20**. It should be appreciated, however, that the particular number and/or configuration of the power cells **20** may be varied in alternate embodiments without departing from the scope of the present disclosure. For example, embodiments of the power source **14** including a single power cell **20** are also envisioned herein.

(106) The thermal transfer member(s) **22** are thermally connected to, and extend between, the power cell(s) **20** and the heat exchanger **24**. In the particular embodiment of the disclosure illustrated, the power source **14** includes a plurality of individual (e.g., discrete) thermal transfer members **22**, each of which is associated with (e.g., thermally connected to) a corresponding power cell **20** (e.g., such that the power source **14** includes a corresponding (equal) number of power cells **20** and thermal transfer members **22**). It should be appreciated, however, that the particular number of the thermal transfer members **22** may be varied in alternate embodiments without departing from the scope of the present disclosure and that embodiments of the power source **14** including an unequal number of power cells **20** and thermal transfer members **22** are also envisioned herein. For example, the present disclosure contemplates embodiments in which the number of power cells **20** may exceed the number of thermal transfer members **22** are also envisioned herein (e.g., embodiments in which the power source **14** includes a single thermal transfer member **22** that extends between the collection of power cells **20** and the heat exchanger **24**) as well as embodiments in which the number of thermal transfer members **22** may exceed the number of power cells **20**.

(107) The thermal transfer member(s) **22** may include (e.g., may be formed partially or entirely

from) any material or combination of materials that is suitable for the intended purpose of transferring heat between, and thermally connecting, the power cell(s) **20** and the heat exchanger **24**. For example, in one particular embodiment, it is envisioned that the thermal transfer member(s) **22** may include (e.g., may be formed partially or entirely from) graphite. It should be appreciated, however, that the use of other materials would not be beyond the scope of the present disclosure. Additionally, although each thermal transfer member **22** is shown as being unitary in construction (i.e., as being formed from a single piece of material), in alternate embodiments of the disclosure, it is envisioned that each thermal transfer member **22** may include a series of individual segments that are connected to each other during manufacture, assembly of the power source **14**, or at any other suitable point in time.

(108) The heat exchanger **24** is thermally connected to the thermal transfer member(s) **22** and is configured to communicate and distribute thermal energy between the power source **14** and the ambient (air), either away from the power source **14** (e.g., when utilized in hot environments) or towards the power source **14** (e.g., when utilized in cold environments), and may include (e.g., may be formed partially or entirely from) any material or combination of materials suitable for that intended purpose. For example, it is envisioned that the heat exchanger **24** may include (e.g., may be formed partially or entirely from) aluminum, magnesium, copper, etc.

(109) To increase the available surface area and, thus, the distribution of thermal energy (either towards or away from the power source **14**), in certain embodiments, such as that illustrated throughout the figures, the heat exchanger **24** may include one or more diffusers **26**, which may be configured in any manner suitable for that intended purpose. For example, it is envisioned that the diffuser(s) **26** may be configured as pins, protrusions, ribs, or other such surface irregularities and may extend axially (e.g., along a longitudinal axis Y) and/or laterally (e.g., along a transverse axis X) along an outer (bottom) surface **28** of the heat exchanger **24**. In the particular embodiment of the heat exchanger **24** illustrated throughout the figures, for example, the diffusers **26** are configured as fins **30** that define a plurality of channels **32** therebetween, which collectively direct air flow along the heat exchanger **24** to further increase the distribution of thermal energy.

(110) Although shown as including a plurality of diffusers **26** and channels **32** in the particular embodiment of the disclosure illustrated, it should be appreciated that the particular number of the diffusers **26** and/or channels **32** may be varied in alternate embodiments without departing from the scope of the present disclosure. For example, embodiments of the heat exchanger **24** including a single diffuser **26** are also envisioned herein.

(111) Base Station Construction

(112) With reference now to FIGS. **4-26** as well, the base station **100** includes: an enclosure (body) **102** having a front end **102a** and a rear end **102b**; a (front) door **104** that is movably connected to the enclosure **102** (at the front end **102a**); and a cradle **106** that is configured to receive (accommodate) the UAV **10**.

(113) The enclosure **102** includes an inner housing (shell) **108** and an outer housing (cover) **110**. The respective inner and outer housings **108**, **110** are configured as separate, discrete structures that may be connected together in any suitable manner, whether fixedly or removably (e.g., to allow for repeated assembly and disassembly of the base station **100** during maintenance, repair, etc.). For example, it is envisioned that the respective inner and outer housings **108**, **110** may be connected via a plurality of mechanical fasteners (e.g., screws, pins, bolts, clips, etc.), which may be hidden (or otherwise obscured) to inhibit theft and/or unauthorized disassembly of the base station **100**.

(114) The inner housing **108** defines an internal cavity **112** and a window **113**, each of which is configured to receive and accommodate the UAV **10** to allow for entry of the UAV **10** into the base station **100** and exit of the UAV **10** from the base station **100**. Additionally, the inner housing **108** provides a mounting surface for various components of the base station **100** including, for example, electrical components, actuators, and the like, which are connected (secured, mounted) to the inner housing **108** and support operation of the base station **100**.

(115) As described in detail below, the outer housing **110** protects the inner housing **108** and the various components that are connected (secured, mounted) thereto (e.g., from dust, debris, the ingress of moisture and/or water, etc.), supports various external components of the base station **100**, and provides structural support to the base station **100**. For example, in the particular embodiment shown, the outer housing **110** includes a sheet metal construction. It should be appreciated, however, that embodiments of the base station **110** in which the outer housing **110** may include one or more alternative materials are also envisioned herein.

(116) To facilitate access to the various components accommodated within the outer housing **110** (and/or the inner housing **108**), in certain embodiments, it is envisioned that the outer housing **110** may include an access panel **114** (FIG. 7) to support maintenance, repair, etc., which may be incorporated in any suitable location. For example, in the particular embodiment illustrated, the access panel **114** is located at the rear end **102b** of the enclosure **102** (e.g., the outer housing **110**). It should be appreciated, however, that the particular location of the access panel **114** may be varied in alternate embodiments without departing from the scope of the present disclosure (e.g., the access panel **114** may be located on a side of the base station **100**, rather than the rear end **102b**).

(117) In certain embodiments of the disclosure, it is envisioned that the outer housing **110** may include exterior coloration that not only reduces solar loading (heating), but promotes contrast to facilitate visualization and/or identification of the base station **100** by the UAV **10** during docking, as described in further detail below.

(118) The door **104** is movably connected to the outer housing **110** such that the door **104** is repositionable between a (fully) closed position (FIG. 1), in which the door **104** conceals the internal cavity **112** and the window **113**, and an open position (FIG. 6), in which the internal cavity **112** and the window **113** are exposed. More specifically, the door **104** is movably connected to a forward frame **116** of the outer housing **110**. Although illustrated as being pivotably connected to the forward frame **116** in the particular embodiment illustrated throughout the figures, it is also envisioned that the door **104** may be slidably repositionable between the closed position and the open position in alternate embodiments of the disclosure.

(119) As discussed below, due to the metallic (e.g., sheet metal) construction of the outer housing **110** and, thus, the forward frame **116**, the forward frame **116** conducts and facilitates the transfer of thermal energy in both hot and cold environments. More specifically, in hot environments, the forward frame **116** is operable as a heat sink that draws thermal energy (heat) away from thermally-sensitive components of the base station **100**, and in cold environments, the forward frame **116** is operable as a thermal conduit that directs thermal energy (heat) towards certain components of the base station **100** to facilitate heating thereof.

(120) To facilitate movement of the door **104** between the closed position and the open position, the base station **100** includes one or more actuators **118** (FIGS. 8-10) that extend between the door **104** and the enclosure **102**. Although shown as including respective first and second actuators **118i**, **118ii** in the particular embodiment illustrated, which are connected (secured) to opposing lateral ends of the door **104** such that the actuators **118i**, **118ii** are spaced laterally from each other along a width **W** of the enclosure **102**, it should be appreciated that the present disclosure also contemplates embodiments in which a single actuator **118** may be utilized to control the position of the door **104** (e.g., to reduce the overall cost and complexity of the base station **100**).

(121) Each actuator **118** includes a motor assembly **120** (e.g., a stepper motor) and a linkage assembly **122** that extends between the motor assembly **120** and the door **104**. More specifically, each motor assembly **120** is connected (secured) to the inner housing **108** such that the motor assembly(ies) **120** are located between the inner housing **108** and the outer housing **110**, which protects the motor assembly(ies) **120** and inhibits the collection of any dust, debris, etc. The linkage assembly **122** extends from the motor assembly **120**, through the inner housing **108**, and pivotably engages the door **104** such that, upon actuation of the motor assembly **120**, the linkage assembly **122** applies a force to the door **104** to thereby facilitate movement of the door **104** between the

closed position and the open position.

(122) Each linkage assembly **122** includes: a (threaded) drive screw **124**; a carrier **126**; a first arm **128**; and a second arm **130**. The drive screw **124** is (operatively) connected to the motor assembly **120** such that actuation of the motor assembly **120** causes rotation of the drive screw **124**. The carrier **126** is threadably engaged to the drive screw **124** such that rotation of the drive screw **124** causes axial translation of the carrier **126**. More specifically, rotation of the drive screw in a first direction (e.g., clockwise) causes forward advancement of the carrier **126** (e.g., movement of the carrier **126** towards the door **104**) and rotation of the drive screw in a second direction (e.g., counterclockwise) causes rearward advancement of the carrier **126** (e.g., movement of the carrier **126** away from the door **104**). The first arm **128** includes a first end **132** that is connected to the carrier **126** (either fixedly or pivotably) and a second end **134** that is pivotably connected to the second arm **130**. The second arm **130** includes a first end **136** that is pivotably connected to the second end **134** of the first arm **128** and a second end **138** that is pivotably connected to a bracket **140**. The bracket **140** is fixedly connected to the door **104** which allows for the transmission of force from the carrier **126** to the door **104** via the arms **128**, **130**.

(123) The cradle **106** defines respective (first and second) front and rear ends **106a**, **106b** (FIGS. 2, 10, 13) and a chamber **142** (FIG. 10) that is configured to receive the UAV **10** during docking so as to facilitate (support) charging of the power source **14**. More specifically, the base station **100** includes a charging hub (assembly) **143** (FIGS. 10, 66-75) that is configured for engagement with, and electrical connection to, the power source **14** upon receipt of the UAV **10** within the chamber **142** to thereby charge the power source **14**, as described in further detail below. To facilitate proper docking of the UAV **10** and a proper electrical interface between the power source **14** and the charging hub **143**, the cradle **106** defines sidewalls **146** that taper inwardly towards the chamber **142** so as to define an angled guide surface **148** (FIG. 10). The angled guide surface **148** is configured for engagement (contact) with the UAV **10** to direct the UAV **10** into the chamber **142** so as to facilitate seating of the UAV **10** within the cradle **106**.

(124) The cradle **106** is movable between a (fully) retracted position (FIGS. 2, 10), in which the cradle **106** (and the UAV **10**) are positioned within the enclosure **102** (e.g., within the internal cavity **112**), a plurality of partially retracted positions, as described in further detail below, and an extended position (FIG. 13), in which the cradle **106** (and the UAV **10**) are positioned externally of the enclosure **102** to facilitate docking with the UAV **10**, whereby the UAV **10** is movable into and out of the enclosure **102**. To support movement between the extended and retracted positions (extension and retraction), the cradle **106** is connected to a telescoping slide mechanism **150**, which is also movable between extended and retracted positions corresponding to those of the cradle **106**. The slide mechanism **150** extends through a window **152** (FIG. 1) defined by a bezel portion **154** of the forward frame **116** and supports a cap (hatch, cover) **156** (FIGS. 1, 8, 11, 12) that is configured in correspondence with the window **152**. The cap **156** is movably (e.g., pivotably) connected to (supported by) the enclosure **102** (e.g., the forward frame **116** of the outer housing **110**) such that the cap **156** is movable between a closed position (FIGS. 6, 11, 12) and an open position (FIGS. 1, 8) as the cradle **106** (and the slide mechanism **150**) move between the retracted position and the extended position, respectively. More specifically, the cap **156** moves from the closed position into the open position as the cradle **106** (and the slide mechanism **150**) move from the retracted position into the extended position and such that the cap **156** moves from the open position into the closed position as the cradle **106** (and the slide mechanism **150**) move from the extended position into the retracted position, whereby the cap **156** engages the bezel portion **154** and is received within the window **152**.

(125) In certain embodiments of the disclosure, such as that illustrated throughout the figures, the cap **156** may include an upstanding tab **158** (FIG. 11) that is configured for receipt within a corresponding recess **160** (FIGS. 8, 12) defined in an inner surface **162** of the door **104**. Receipt of the tab **158** within the recess **160** not only allows for proper closure of the door **104**, but allows for

overlayment of the cap **156** by the door **104** upon closure to facilitate sealing of the enclosure **102** and inhibit (if not entirely prevent) the entry of dust, debris, etc., through the door **104** and/or the bezel portion **154**. Additionally, the engagement between the bezel portion **154**, the slide mechanism **150**, and the door **104** (e.g., reception of the tab **158** by the recess **160**) improves the security of the base station **100** by inhibiting access to the cradle **106** and, thus, the UAV **10**.

(126) The slide mechanism **150** includes a stationary slide member **151a** (FIG. **13**), which is supported by the enclosure **102**, and a movable slide member **151b**, which is slidably supported by the stationary slide member **151a** so as to allow for telescopic movement of the slide mechanism **150** between an extended and retracted positions (which correspond to the extended and retracted positions of the cradle **106**). It is envisioned that the stationary slide member **151a** may be positioned about the movable slide member **151b** such that that movable slide member **151b** is received by the stationary slide member **151a**, as seen in FIG. **13**, or that the movable stationary slide member **151b** may be positioned about the stationary slide member **151a** such that that stationary slide member **151a** is received by the movable slide member **151b**.

(127) In alternate embodiments of the disclosure, it is envisioned that the slide mechanism **150** may be either directly or indirectly (operatively) connected (secured) to the enclosure **102**. For example, in certain embodiments, it is envisioned that the slide mechanism **150** (e.g., the stationary slide member **151a**) may be directly and fixedly (e.g., non-movably) connected (secured) to a plurality of studs **262** (FIGS. **14**, **17**, **21**) that extend (vertically) upward from a sheet metal base **264** of the enclosure **102** (e.g., towards the slide mechanism **150**) and which are configured for insertion into openings (apertures) **266** (FIGS. **17**, **24**, **25**) in the slide mechanism **150**. Alternatively, it is envisioned that the slide mechanism **150** (e.g., the stationary slide member **151a**) may be indirectly (operatively) connected (secured) to the enclosure **102** via a plurality of mounts **268** (FIGS. **14-26**), that are located between the enclosure **102** (e.g., the sheet metal base **264**) and the slide mechanism **150**. As described in detail below, positioning of the mounts **268** between the enclosure **102** and the slide mechanism **150** physically separates the slide mechanism **150** from the enclosure **102**, which reduces the rigidity of the interface therebetween. Physically separating the slide mechanism **150** from the enclosure **102** also increases the tolerance for relative movement (deflection) between the enclosure **102** and the slide mechanism **150** during extension and retraction and reduces (resonant) vibration of the slide mechanism **150** and, thus, undesirable movement (e.g., shaking, jittering, etc.). In the particular embodiment of the base station **100** illustrated in FIGS. **14-26**, the slide mechanism **150** is connected (secured) to the enclosure **102** via a plurality of first mounts **268i** and a plurality of second mounts **268ii**. The mounts **268i**, **268ii** are each configured to receive one of the studs **262** extending from the base **264** of the enclosure **102** and include dissimilar (e.g., non-identical configurations), as described in further detail below (e.g., the mounts **268i** include a first configuration and the mounts **268ii** include a second, different configuration). More specifically, the mounts **268i** are each configured to receive first studs **262i** (FIG. **22**), which define a first length LSi, and the mounts **268ii** are each configured to receive second studs **262ii** (FIGS. **17**, **18**, **24**), which define a second length LSii (FIG. **24**).

(128) The mounts **268i** define opposing (first and second) ends **270**, **272** (FIGS. **19**, **21**) having (first and second) female and male interfaces **274**, **276**, respectively, and each include: a (first) bushing (body, body portion) **278**; a shank **280**; and a (first) fastener **282** (FIGS. **18**, **22**, **25**). In the particular embodiment illustrated in FIGS. **14-26**, the base station **100** includes six mounts **268ia-268if**. More specifically, the mounts **268ia-268id** are located in corner sections (regions) **284i-284iv** of the slide mechanism **150**, respectively, one mount **268ie** that is located between the corner sections **284i**, **284ii** (e.g., such that the corner sections **284i**, **284ii** are spaced equidistant (or approximately equidistant) from the mount **268ie**), and one mount **268if** that is located between the corner sections **284iii**, **284iv** (e.g., such that the corner sections **284iii**, **284iv** are spaced equidistant (or approximately equidistant) from the mount **268if**). It should be appreciated, however, that the particular number of mounts **268i** may be varied in alternate embodiments without departing from

the scope of the present disclosure (e.g., depending upon the particular configuration of the base station **100**, the slide mechanism **150**, etc.). As such, embodiments including both greater and fewer numbers of mounts **268i** are envisioned herein and would not be beyond the scope of the present disclosure.

(129) The bushing **278** includes (e.g., is formed partially or entirely from) a compliant material, which (axially) separates the interfaces **274**, **276** along a longitudinal axis **Y1** of the mount **268i** and absorbs forces created during extension and retraction of the slide mechanism **150** so as to reduce vibration, shaking, jittering, etc. At the end **270**, the bushing **278** defines an aperture **286**, which defines the female interface **274** and is configured to receive one of the studs **262i** to facilitate connection of the bushing **278** to the enclosure **102** (e.g., via the studs **262i**). More specifically, as seen in FIG. **22**, the aperture **286** extends into, but not through, the bushing **278**, whereby the stud **262ii** extends partially into the bushing **278**.

(130) In the particular embodiment illustrated, the aperture **286** includes threading **288**, which is configured for engagement with corresponding threading **290** (FIG. **22**) on the studs **262i** such that the bushing **278** threadably engages (contacts) the sheet metal base **264** of the enclosure **102** (via the studs **262i**). It is envisioned, however, that the mounts **268i** and the enclosure **102** may be configured for engagement in any suitable manner. For example, in alternate embodiments of the disclosure, it is envisioned that the threading **288**, **290** may be omitted and that the mounts **268i** and the studs **262i** may be configured for engagement in a press-fit (interference fit) arrangement.

(131) The shank **280** defines the male interface **276** and extends (vertically) upward from the bushing **278** (e.g., away from the sheet metal base **264**) such that the shank **280** is insertable into one of the openings **266** (FIGS. **17**, **24**, **25**) in the slide mechanism **150**. The shank **280** is configured for (releasable) connection to (engagement with) the fastener **282** (FIGS. **18**, **22**, **25**) such that the slide mechanism **150** is secured between the bushing **278** and the fastener **282**. More specifically, in the particular embodiment illustrated, the shank **280** and the fastener **282** include corresponding threading **292**, **294**. It is envisioned, however, that the shank **280** and the fastener **282** may be configured for engagement in any manner suitable for the intended purpose of fixing the mounts **268i** and the slide mechanism **150** in relation to each other (e.g., so as to inhibit (if not entirely prevent) relative movement therebetween). For example, in alternate embodiments, it is envisioned that the threading **292**, **294** may be omitted and that the shank **280** and the fastener **282** may be configured for engagement in a press-fit (interference fit) arrangement.

(132) In the particular embodiment illustrated in FIGS. **16-22**, the mounts **268i** are configured such that the bushing **278** is in direct contact with the enclosure **102** (e.g., the sheet metal base **264**) and the slide mechanism **150**. Alternatively, however, it is envisioned that the mounts **268i** may be configured such that the bushing **278** is separated from the enclosure **102** (e.g., the sheet metal base **264**) and/or the slide mechanism **150**. For example, FIG. **26** illustrates an embodiment in which the mounts **268i** include an intermediate member **296** (e.g., a washer **298**, an O-ring, etc.) that is located between the bushing **278** and the slide mechanism **150**.

(133) Due to the compliant construction of the bushing **278**, during repositioning of the slide mechanism **150** between the retracted position and the extended position, the mounts **268i** undergo deformation (e.g., expansion and contraction) in the lateral (radial) directions identified by the arrows **1** (FIGS. **18**, **21**) and/or the axial (vertical) directions identified by the arrows **2**. The lateral and/or axial deformation tolerated by the mounts **268i** allows for relative movement between the slide mechanism **150** and the enclosure **102** (e.g., the sheet metal base **264**), which not only eliminates a direct, rigid connection therebetween, but dampens (absorbs) vibration during repositioning of the slide mechanism **150** so as to increase predictability, consistency, and/or uniformity in movement of the slide mechanism **150**.

(134) The mounts **268ii** define opposing (first and second) ends **300**, **302** and include: a (second) bushing (body, body portion) **304** with a base portion **306** and a stem **308** extending therefrom; a channel **310**; and a (second) fastener **312**. In the particular embodiment illustrated in FIGS. **14-26**,

the base station **100** includes four mounts **268ii**. More specifically, the base station **100** includes four mounts **268iia-268iid** that are located adjacent (or generally adjacent) to the mounts **268ia-268id** in the corner sections **284i-284iv** of the slide mechanism **150**, respectively. It should be appreciated, however, that the particular number of mounts **268ii** may be varied in alternate embodiments without departing from the scope of the present disclosure (e.g., depending upon the particular configuration of the base station **100**, the slide mechanism **150**, etc.). As such, embodiments including both greater and fewer numbers of mounts **268ii** are envisioned herein and would not be beyond the scope of the present disclosure.

(135) In the particular embodiment illustrated, the bushing **304** includes (e.g., is formed partially or entirely from) a compliant material to further facilitate force absorption by the mounts **268ii** and further reduce vibration of the slide mechanism **150** during extension and retraction. Embodiments of the base station **100** in which the bushing **304** may include a non-compliant material, however, are also envisioned herein and would not be beyond the scope of present disclosure.

(136) The base portion **306** defines a first transverse cross-sectional dimension (e.g., a diameter) **D1** (FIG. **24**) and the stem **308** defines a second transverse cross-sectional dimension (e.g., a diameter) **D2** that is less than the first transverse cross-sectional dimension **D1**, whereby the bushing **304** includes (defines) a non-uniform, stepped transverse cross-sectional configuration that varies along a longitudinal axis **Y2** of the mount **268ii**. More specifically, the stem **308** is configured for insertion into one of the openings **266** (FIGS. **17, 24, 25**) in the slide mechanism **150**, which defines a third transverse cross-sectional dimension (e.g., a diameter) **D3** (FIG. **25**) that is less than the first transverse cross-sectional dimension **D1** and greater than the second transverse cross-sectional dimension **D2**, such that the base portion **306** is positioned (located) between the enclosure **102** (e.g., the sheet metal base **264**) and the slide mechanism **150**. The differential between the transverse cross-sectional dimensions **D2, D3** respectively defined by the stem **308** and the opening **266** results in the formation (definition) of a lateral (radial, horizontal) gap **G1** (FIG. **25**) therebetween. For example, in the particular embodiment illustrated, the gap **G1** lies (substantially) within the range of (approximately) 0.5 mm to (approximately) 1.5 mm (e.g., (approximately) 1 mm). A gap **G1** outside of this range, however, is also envisioned herein and would not be beyond the scope of present disclosure.

(137) The channel **310** extends through the bushing **304** is configured to receive one of the studs **262ii** such that the stud **262ii** extends through the mount **268ii**, which facilitates (releasable) connection of (engagement between) the stud **262ii** and the fastener **312** such that the slide mechanism **150** is secured between the bushing **304** and the fastener **312** so as to inhibit (if not entirely prevent) relative movement between the mounts **268ii** and the enclosure **102** (e.g., the studs **262ii**) while allowing for relative movement between the mounts **268ii** and the slide mechanism **150**, as described in further detail below. For example, it is envisioned that the bushing **304** may be compressible retained between the fastener **312** and the sheet metal base **264** so as to secure the mount **268i** in relation to the enclosure **102**.

(138) In the particular embodiment illustrated, the fastener **312** includes threading **314** (FIG. **24**) that is configured for engagement with the threading **290** on the stud **262ii** extending through the mount **268ii** (via the channel **310**). It is envisioned, however, that the studs **262ii** and the fasteners **312** may be configured for engagement in any manner suitable for the intended purpose(s) discussed above. For example, in alternate embodiments, it is envisioned that the threading **290, 314** may be omitted and that the stud **262ii** and the fastener **312** may be configured for engagement in a press-fit (interference fit) arrangement.

(139) As seen in FIG. **26**, upon connection of the fastener **312** to the stud **262ii**, an axial (vertical) gap **G2** is defined between the fastener **312** and the base portion **306**, which is equivalent to a (vertical) height **HS** defined by the stem **308** of the bushing **304**. For example, in the particular embodiment illustrated, the gap **G2** lies (substantially) within the range of (approximately) 1 mm to (approximately) 2 mm (e.g., (approximately) 1.5 mm). A gap **G2** outside of this range, however, is

also envisioned herein and would not be beyond the scope of present disclosure.

(140) The gaps **G1**, **G2** allow for reception of the stem **308** by the opening **266** in the slide mechanism **150** in a manner that inhibits (if not entirely prevents) contact between (engagement of) the mounts **268ii** and the slide mechanism **150** when the slide mechanism **150** is in a normal state (condition) (e.g., when the slide mechanism **150** is stationary between periods of extension and retraction). The gaps **G1**, **G2** also allow for movement of the slide mechanism **150** in relation to the enclosure **102** and the second mounts **268ii**, which is further facilitated by the compliant material comprising the bushings **278** of the first mounts **268i**, in two degrees-of-freedom **DOF1** (FIGS. **18**, **25**), **DOF2** (FIGS. **18**, **26**), which are oriented in orthogonal (or generally orthogonal) relation. More specifically, the gaps **G1** (FIG. **25**), **G2** (FIG. **26**) respectively allow for predetermined lateral (radial) and axial (vertical) movement of the slide mechanism **150** (in relation to the enclosure **102** and the second mounts **268ii**) so as to limit (restrict) deformation of the mounts **268i** and movement of the slide mechanism **150** during extension and retraction, which inhibits (if not entirely prevents) lateral over-travel (e.g., in the degree-of-freedom **DOF1**) and axial over-travel (e.g., in the degree-of-freedom **DOF2**). Limiting deformation of the mounts **268i** and movement of the slide mechanism **150** (in relation to the enclosure **102** and the second mounts **268ii**) inhibits (if not entirely prevents) damage to (e.g., shearing of) the mounts **268i** and over-travel of the slide mechanism **150** within the enclosure **102**, which reduces (if not entirely eliminates) any likelihood of undesirable contact between the slide mechanism **150** and the various internal components of the base station **100**. For example, during docking of the UAV **10**, the slide mechanism **150** may experience (vertical) deflection under the weight of the UAV **10** and/or as a result of the force applied to the cradle **106** during landing. Any such (vertical) deflection (e.g., movement of the slide mechanism **150** in the degree-of-freedom **DOF2**), however, is restricted by the mounts **268ii** via contact between the slide mechanism **150** and the fastener **312**, which also restricts axial (vertical) deformation of the mounts **268i**, thus inhibiting (if not entirely preventing) damage to the mounts **268i** (e.g., overstretching, tearing) that may otherwise occur.

(141) In the particular embodiment of the base station **100** illustrated in FIGS. **14-26**, the mounts **268i** and the mounts **268ii** include non-identical (dissimilar) configurations, as described above. It should be appreciated, however, that embodiments of the base station **100** including a single variety of mount **268** are also envisioned herein and would not be beyond the scope of the present disclosure. For example, the present disclosure contemplates an embodiment of the base station **100** that is devoid of the mounts **268ii** and which exclusively includes the mounts **268i**.

(142) In certain embodiments of the disclosure, it is envisioned that the door **104** and the cradle **106** may be automatically actuated upon the receipt of an incoming/docking signal from the UAV **10**. For example, it is envisioned that the incoming/docking signal may automatically engage the actuator(s) **118** to thereby open the door **104**. Thereafter, when it is determined that the door **104** is fully opened, which may be achieved through the employ of Hall sensors (or any other such suitable detection mechanism), the cradle **106** may be extended via (telescopic) movement of the slide mechanism **150**.

(143) Anti-Theft and Security Measures

(144) To further improve the security of the base station **100**, in certain embodiments of the disclosure, it is envisioned that the door **104** may include a locking mechanism. For example, it is envisioned that the door **104** may include a magnetic lock to maintain closure of the door **104** in the absence of power to prevent inadvertent and/or unauthorized opening of the door **104** and, thus, access to the UAV **10**.

(145) Additionally, or alternatively, it is envisioned that the actuator(s) **118** (FIGS. **8-10**) may be configured to resist the application of (manual) force to the door **104**, and thereby maintain closure of the door **104**, by inhibit (if not entirely preventing) the transmission of force from the door **104** to the motor assembly(ies) **120**. For example, it is envisioned that the threading defined by the drive screw **124** may include a fine pitch, which would inhibit (if not entirely prevent) the

transmission of force applied to the door **104** to the carrier(s) **126**, thereby maintaining closure of the door **104**. Additionally, or alternatively, it is envisioned that the actuator(s) **118** may include a solenoid (or other such mechanism) that is configured to engage a locking pin (or other such member).

(146) Pedestal

(147) With reference to FIG. **1**, in certain embodiments, the base station **100** may be configured for use with a pedestal **164** (or other such free-standing platform) that is configured to support the base station **100** and the UAV **10** in an elevated position (e.g., above the ground). Together, the base station **100** and the pedestal **164** describe a docking system **165** for the UAV **10** that creates free air space to not only reduce turbulence (e.g., propeller wash) during takeoff and landing of the UAV **10**, but mitigate the entry of debris (e.g., dust, particulate, etc.) into the base station **100**.

(148) In certain embodiments of the docking system **165**, it is envisioned that the pedestal **164** and the base station **100** may include corresponding engagement structures (e.g., pins and holes, detents and recesses, ribs and slots, a footing and a channel, etc.) that are configured for releasable engagement (connection) to promote proper alignment of the pedestal **164** and the base station **100** and inhibit (if not entirely prevent) unintended separation of the base station **100** from the pedestal **164**, such as, for example, in the event that the base station **100** and/or the pedestal **164** is subjected to an applied force (e.g., a wind gust, impact with an external object, etc.). In one particular embodiment, it is envisioned that the corresponding engagement structures may include one or more openings and corresponding mechanical fasteners (e.g., bolts, screws, pins, etc.) that are configured for insertion into the opening(s) to allow for fixed, releasably connection of the pedestal **164** and the base station **100**.

(149) To inhibit (if not entirely prevent) unauthorized separation of the base station **100** from the pedestal **164** (e.g., to guard against theft of the base station **100** and/or the pedestal **164**), it is envisioned that the pedestal **164** and the base station **100** may include corresponding eyelets (or other such openings) that are configured to receive a lockable tether, chain, cable, bar, etc.

(150) With reference to FIGS. **54** and **55** as well, the pedestal **164** defines an interior space **334** having an inner contour **336** that is configured in correspondence with an outer contour **338** of the base station **100** (e.g. such that a vertical transverse cross-sectional configuration of the pedestal **164** approximates a vertical transverse cross-sectional configuration of the base station **100**). The corresponding contours **336**, **338** respectively defined by the interior space **334** and the base station **100** allows for positioning of the base station **100** within the pedestal **164** during nonuse (e.g., such that the base station **100** can be stored within the interior space **334** to protect the base station **100** during transport, in inclement weather, etc.) such that the docking system **165** is reconfigurable between a nested (inactive) configuration (arrangement), as seen in FIG. **54**, in which the base station **100** received by the pedestal **164**, and a stacked (active) configuration (arrangement), as seen in FIG. **55**, in which the base station **100** (and the UAV **10**) are supported by the pedestal **164** in the elevated position. As seen in FIG. **54**, the pedestal **164** is configured and dimensioned to create clearance with the base station **100** about an entire periphery **340** (e.g., an exterior envelope) of the base station **100**), which inhibits (if not entirely prevents) contact between the pedestal **164** and the base station **100**.

(151) In the particular embodiment illustrated, the pedestal **164** is unitary (e.g., monolithic) in construction and is formed from a single piece of (rigid or semi-rigid) material, which may be either metallic (e.g., aluminum, sheet metal, steel, etc.) or non-metallic (e.g., plastic, polymeric carbon fiber, etc.). In alternate embodiments of the disclosure, however, it is envisioned that the pedestal **164** may include a series of individual components that are connected together in any suitable manner (e.g., via one or more mechanical fasteners, in an interference fit, etc.).

(152) The pedestal **164** includes a trapezoidal (or generally trapezoidal) vertical cross-sectional configuration that defines: an upper wall **342** having a non-linear configuration; first and second side walls **344**, **346**, respectively, that extend vertically from the upper wall **342** and which each

include a linear (or generally linear) configuration; and first and second base walls **348**, **350** that extend laterally inward from the first and second side walls **344**, **346**, respectively, and which each include a linear (or generally linear) configuration.

(153) The upper wall **342** includes: a first segment **352i** that extends laterally inward from the first side wall **344**; a second segment **352ii** that extends laterally inward from the second side wall **346**; a third segment **352iii** that extends in parallel (or generally parallel) relation to the segments **352i**, **352ii**; a fourth segment **352iv** that extends between the segments **352i**, **352iii**; and a fifth segment **352v** that extends between the segments **352ii**, **352iii**. Whereas the segments **352i**, **352ii** are vertically aligned (e.g., such that the segments **352i**, **352ii** are positioned in the same (or substantially the same) vertical location), the segments **352iii** is vertically offset from the segments **352i**, **352ii** (e.g., such that the segment **352iii** is positioned in a different vertical location than the segments **352i**, **352ii**) so as to define a well **354**. Inclusion of the well **354** increases the strength and/or rigidity of the upper wall **342** and creates (vertical) clearance with the base station **100** (e.g., the antenna(s) **166**). Additionally, the well **354** is configured to receive a power cable **356** (FIG. 7) of the base station **100** so as to inhibit (if not entirely prevent) bending, kinking, and/or damage to the power cable **356**.

(154) In the particular embodiment illustrated, the segments **352iv**, **352v** subtend identical (or generally identical) obtuse angles α_i , α_{ii} with the segments **352i**, **352ii**, respectively, whereby the well **354** extends into a space (gap) **358** defined between the antennas **166**. It should be appreciated, however, that the particular configuration of the upper wall **342** and the arrangement of the segments **352** may be varied in alternate embodiments without departing from the scope of the present disclosure. For example, embodiments are envisioned in which the upper wall **342** may be configured such that the angles α_i , α_{ii} are equal (or approximately equal) to 90° , as are embodiments in which the angles α_i , α_{ii} may be unequal as well as embodiments in which the segment **352iii** may be vertically aligned with the segments **352i**, **352ii** so as to eliminate the well **354** such that the upper wall **342** includes a linear (or generally linear) configuration.

(155) To increase stability of the pedestal **164** (e.g., in windy conditions), the sidewalls **344**, **346** are angled in relation to the upper wall **342** and the base walls **348**, **350**, respectively, whereby the base walls **348**, **350** extend laterally outward of (beyond) the upper wall **342**. More specifically, the sidewalls **344**, **346** are configured so as to respectively define first and second (acute) angles β_i , β_{ii} with first and second reference axes R_i , R_{ii} , which are oriented in orthogonal (or generally orthogonal) relation to the base walls **348**, **350**.

(156) To further increase stability (e.g., on uneven terrain), it is envisioned that the pedestal **164** may include a plurality of adjustable footings **360**. The footings **360** are configured for removable connection to (engagement with) the base walls **348**, **350** and are reconfigurable to level the pedestal **164** and, thus, the base station **100** (e.g., by shortening and lengthening the footings **360**).

(157) Takeoff, Landing, and Docking

(158) With reference now to FIGS. 27-31B as well, the base station **100** includes a plurality of systems, components, and features that support takeoff of the UAV **10**, landing of the UAV **10**, and docking of the UAV **10** with the base station **100** after flight. For example, as described below, the base station **100** may include: one or more connection antennas **166**; one or more fiducials **168** that are supported by the enclosure **102**; an illumination system **170** that is supported by the enclosure **102**; one or more status indicators **172** that are supported by the enclosure **102**; and a visualization system **174** that is supported by the enclosure **102**.

(159) Connection Antennas

(160) The base station **100** includes primary connection antenna(s) **166** that facilitate wireless communication between the base station **100** and the UAV **10**, either directly or indirectly. For example, it is envisioned that the primary connection antenna(s) **166** may be utilized to facilitate communication between the base station **100** and an intervening communication point, such as a hangar, a warehouse, etc. In such embodiments, the primary connection antenna(s) **166** on

the base station **100** support direct communication with the hangar (or the like), which would communicate directly with the UAV **10**.

(161) In the particular embodiment seen in FIG. **27**, for example, the base station **100** includes a pair of primary connection antennas **166** that are connected (secured) to (or otherwise engaged with) a roof section **176** of the outer housing **110**. It should be appreciated, however, that the particular number of primary connection antennas **166** and/or the location of the primary connection antennas **166** may be varied in alternate embodiments without departing from the scope of the present disclosure. For example, embodiments including a single primary connection antenna **166** are also envisioned herein, as are embodiments in which the base station **100** may include one or more primary connection antennas **166** that are located on sidewalls of the outer housing **110**.

(162) In certain embodiments of the disclosure, it is envisioned that the base station **100** may include one more secondary communication antennas that facilitate communication over cellular and/or WiFi networks and/or support GPS functionality. In such embodiments, it is envisioned that the primary connection antenna(s) **166** and the secondary communication antenna(s) may operate in tandem. For example, embodiments are envisioned in which the primary communication antenna(s) **166** may facilitate docking of the UAV **10** with the base station **100** (and communication therebetween) while the secondary communication antenna(s) may facilitate communication between the base station **100** and the hangar (or vice versa).

(163) Fiducials

(164) The fiducials **168** facilitate not only visual identification of the base station **100** by the UAV **10**, but guidance of the UAV **10** during landing and docking with the base station **100**. To promote or otherwise enhance visualization and/or recognition of the fiducials **168**, it is envisioned that the outer housing **110** may include contrasting coloration.

(165) In the particular embodiment of the disclosure seen in FIGS. **13**, **27**, and **28**, for example, the base station **100** includes (first and second) fiducials **168i**, **168ii** that are located on (supported by) the roof section **176** of the outer housing **110** (e.g., between the primary connection antennas **166**) and a (third) fiducial **168iii** that is associated with (e.g., located on or adjacent to) the cradle **106**. It should be appreciated, however, that the particular number of fiducials **168** and/or the location(s) thereof, may be varied in alternate embodiments without departing from the scope of the present disclosure.

(166) The fiducial **168i** is initially recognized by the UAV **10** to guide the UAV **10** during approach. The fiducial **168i** defines a (first) surface area, which is sufficiently large to allow for visual recognition by the UAV **10** from a desired distance. For example, in certain embodiments, it is envisioned that the (first) surface area defined by the fiducial **168i** may lie substantially within the range of (approximately) 40 percent to (approximately) 80 percent of the surface area defined by the roof section **176**. Surface areas for the fiducial **168i** that lie outside the disclosed range, however, would not be beyond the scope of the present disclosure (e.g., to account for advancements in visualization technology utilized in the UAV **10**).

(167) The fiducial **168ii** is configured as an identification member **178** that is recognized by the UAV **10** during approach to the base station **100** (e.g., after recognition of the fiducial **168i**), which allows the UAV **10** to distinguish amongst a plurality of base stations **100** to facilitate proper pairing (e.g., docking of the UAV **10** to a specific base station **100**). In certain embodiments of the disclosure, it is envisioned that the fiducial **168i** may be fixedly connected to the base station **100** (e.g., the roof section **176**) and that the fiducial **168ii** may be configured for removable connection to the base station **100** (e.g., the roof section **176**). Removable connection of the fiducial **168ii** allows for the uniform manufacture of a fleet of base stations **100** and the subsequent attachment of the fiducials **168ii** thereto. Embodiments in which the fiducial **168ii** may be integrally (e.g., monolithically) formed with the base station **100**, however, would not be beyond the present disclosure.

(168) In the particular embodiment illustrated, the fiducial **168ii** defines a (second) surface area,

which is less than the (first) surface area defined by the fiducial **168i**. For example, it is envisioned that the (second) surface area defined by the fiducial **168ii** may lie substantially within the range of (approximately) 10 percent to (approximately) 50 percent of the (first) surface area defined by the fiducial **168i**. Surface areas for the fiducial **168ii** that lie outside the disclosed range, however, would not be beyond the scope of the present disclosure (e.g., to account for advancements in visualization technology utilized in the UAV **10**).

(169) The fiducial **168iii** is configured as an April tag **180** and is recognized by the UAV **10** after recognition of the fiducial **168ii**. In the particular embodiment of the disclosure illustrated, the fiducial **168iii** is located on the slide mechanism **150**, which inhibits (if not entirely prevents) any interference with air flow across the cradle **106** during cooling and/or heating of the power source **14** of the UAV **10**, which is discussed in further detail below. Embodiments in which the fiducial **168iii** may be located on the cradle **106** itself, however, are also envisioned herein and would not be beyond the scope of the present disclosure.

(170) Illumination System

(171) The illumination system **170** is configured to improve visibility of the fiducials **168** during nighttime operation. In the particular embodiment of the disclosure illustrated, the illumination system **170** includes one or more light sources **182** (FIG. **28**) (e.g., LEDs **184**) that are secured (connected, mounted) to, or otherwise supported by, the roof section **176** of the outer housing **110** to support lighting (illumination) of the fiducials **168i**, **168ii**. It is envisioned that the illumination system **170** may be connected to any suitable power source, whether internal to the base station **100** (e.g., to the power supply controlled by the main board/processor) or external (e.g., to a separate power supply, battery, or the like).

(172) In certain embodiments of the disclosure, it is envisioned that the illumination system **170** may be controlled by the main board/processor and configured to flash or strobe the light source(s) **182** according to a particular pattern, which can be recognized by the UAV **10** during approach to thereby identify the base station **100**. In such embodiments, it is envisioned that the illumination system **170** may either supplement or replace the fiducial **168ii** as a means of identifying the base station **100**.

(173) Status Indicators

(174) The status indicator(s) **172** (FIG. **29**) identify the status of the base station **100** (e.g., that the base station **100** is ready, requires service, is undergoing the docking procedure with the UAV **10**, etc.). Each status indicator **172** includes an (exterior) light source **173** (e.g., one or more LEDs **186**) that is supported by an outer (exterior, external) surface **116a** of the forward frame **116**, which not only supports status indication, but illumination of the fiducial **168iii** (FIG. **13**) and/or the cradle **106** (e.g., to facilitate docking of the UAV **10**). For example, in one particular embodiment, it is envisioned that one or more of the LEDs **186** may be configured to emit a colored light (e.g., red, blue, yellow, etc.) and that one or more of the LEDs **186** may be configured to emit a white light to illuminate the fiducial **168iii** and/or the cradle **106**.

(175) In the particular embodiment of the disclosure illustrated in FIG. **29**, the status indicator(s) **172** are secured (connected, mounted) to, or otherwise supported by, the forward frame **116** of the outer housing **110**. It should be appreciated, however, that the particular location of the status indicator(s) **172** may be varied in alternate embodiments without departing from the scope of the present disclosure. It is envisioned that the status indicator(s) **172** may be connected to any suitable power source, whether internal to the base station **100** (e.g., to the power supply controlled by the main board/processor) or external (e.g., to a separate power supply, battery, or the like).

(176) UAV Storage

(177) In certain embodiments of the disclosure, it is envisioned that the UAV **10** may be reconfigurable between a flight (unfolded) configuration (FIG. **32**), in which the propeller assemblies **18** are in the extended configuration, and a storage (folded) configuration (FIGS. **33** and **34A-34C**), in which each of the propeller assemblies **18** is in the collapsed configuration and

oriented within the positional range identified by the reference character R in FIG. 35.

Reconfiguration of the UAV **10** into the storage configuration not only allows for a reduction in the overall size of the base station **100**, but inhibits (if not entirely prevents) undesirable contact between the propeller assemblies **18** and the enclosure **102** (FIG. 32) that may otherwise result in unseating of the UAV **10** from the cradle **106**, interference with operation of the door **104**, damage to the various internal components of the base station **100**, etc.

(178) To support movement from the flight configuration into the storage configuration, it is envisioned that the base station **100** may be configured for engagement with the propeller assemblies **18** (e.g., during retraction of the cradle **106**). For example, it is envisioned that the base station **100** may include one or more engagement members that are configured to physically interface with (contact) the propeller assemblies **18** to fold the propeller assemblies **18** and move the propeller assemblies **18** into the collapsed configuration during retraction of the cradle **106** and movement of the UAV **10** into the enclosure **102**, as described in further detail below. It is envisioned that the engagement member(s) may be integrated into (or defined by) one or more surface(s) of the enclosure **102** (e.g., the forward frame **116** of the outer housing **110**). For example, the engagement member(s) may be configured as rollers, brushes, (spring-biased) stoppers, or the like.

(179) In certain embodiments of the disclosure, it is envisioned that the engagement member(s) may be configured for passive interaction with the propeller assemblies **18**, whereby the propeller assemblies **18** are brought into contact with the engagement member(s) by virtue of the retraction of the cradle **106**. Alternatively, it is envisioned that the engagement member(s) may be configured for active engagement (interaction) with the propeller assemblies **18**. For example, it is envisioned that the engagement member(s) may be repositionable (reconfigurable) between a first position (configuration), in which the engagement member(s) are positioned (configured) to avoid contact with the propeller assemblies **18** (e.g., such that the engagement member(s) are located outside the path followed by the propeller assemblies **18** during retraction of the cradle **106**), and a second position (configuration), in which the engagement member(s) are positioned (configured) for contact with the propeller assemblies **18** (e.g., such that the engagement member(s) are located within the path followed by the propeller assemblies **18** during retraction of the cradle **106**).

(180) To allow for additional reductions in the overall size of the base station **100**, it is envisioned that the base station **100** may include one or more contact members **188** that are configured for engagement (contact) with one or more antennas **34** on the UAV **10** to facilitate reconfiguration (repositioning, folding) thereof between an active (use, unfolded, deployed) configuration (FIG. 2), in which the antenna(s) **34** extend outwardly (away) from a body **36** of the UAV **10**, which supports (is connected to) the power source **14**, and a passive (storage, folded, undeployed) configuration, in which the antenna(s) **34** are positioned adjacent to (e.g., in contact (engagement) with the body **36** of the UAV **10**). Reconfiguration of the antenna(s) **34** from the active configuration into the passive configuration creates clearance with the various internal components of the base station **100** to inhibit (if not entirely prevent) unintended contact between the UAV **10** and the base station **100** during movement of the cradle **106** (and the UAV **10**) between the extended position (FIG. 13) and the retracted position (FIGS. 2, 10). In the particular embodiment of the UAV **10** illustrated throughout the figures, the antenna(s) **34** are biased towards the active configuration via one or more biasing members (e.g., springs or the like) such that the antenna(s) **34** are automatically reconfigured from the passive configuration into the active configuration as the UAV **10** exits the base station **100** (e.g., via movement of the cradle **106** from the retracted position (FIGS. 2, 10) into the extended position (FIG. 13)).

(181) In the embodiment illustrated in FIG. 31A, the contact member **188** defines a groove (channel) **189** that is configured to receive the antenna(s) **34** during retraction of the cradle **106** as the UAV **10** is withdrawn into the enclosure **102**. FIG. 31B illustrates another embodiment of the contact member **188** that includes a leading (forward) edge **190** and a trailing (rear) edge **192** and

defines a (vertical) height **H** that varies between the edges **190**, **192** so as to defined an angled (chamfered, beveled, ramped) surface **194** that is configured for engagement (contact) with the antenna(s) **34** on the UAV **10**. In the particular embodiment of the disclosure seen in FIG. **31B**, each contact member **188** tapers such that the height **H** decreases from the leading edge **190** towards the trailing edge **192**. Embodiments in which each contact member **188** may taper such that the height **H** increases from the leading edge **190** towards the trailing edge **192** are also envisioned herein and would not be beyond the scope of the present disclosure (e.g., depending upon the particular configuration and/or location of the antenna(s) **34** on the UAV **10**, spatial constraints of the enclosure **102**, etc.).

(182) In the embodiments illustrated in FIGS. **31A** and **31B**, the base station **100** includes a single contact member **188** that is secured (connected) to (or otherwise engaged with) an inner (e.g., upper) surface **196** of the inner housing **108**. It should be appreciated, however, that the particular number of contact members **188** and/or the location of the contact member(s) **188** may be varied in alternate embodiments without departing from the scope of the present disclosure (e.g., depending upon the number of antennas **34** on the UAV **10** and/or the location thereof). For example, embodiments including multiple contact members **188** are also envisioned herein, as are embodiments in which the base station **100** may include one or more contact members **188** that are located on sidewalls **198** of the inner housing **108**.

(183) It is envisioned that the contact member(s) **188** may be secured (connected) to the inner housing **108** in any suitable manner. For example, it is envisioned that the contact member(s) **188** may be integrally (e.g., monolithically) formed with the inner housing **108** or that the contact member(s) **188** and the inner housing **108** may be formed as separate, discrete structures, which may be secured (connected) together via one or more mechanical fasteners, an adhesive, etc.

(184) Folding of the Propeller Assemblies

(185) In certain embodiments of the disclosure, as indicated above, it is envisioned that the base station **100** may include one or more engagement members, which are identified by the reference character **316** (FIGS. **34D**, **36-40**), that are configured to facilitate movement of the propeller assemblies **18** into the collapsed configuration during retraction of the cradle **106** and the UAV **10** into the enclosure **102**. The engagement members **316** each include a mounting bracket **318** and a bumper **320** that is supported by (secured, connected to) the mounting bracket **318** such that the bumpers **320** contact (engage) the propeller assemblies **18** during retraction of the UAV into the enclosure **102**, which results in repeated, consistent positioning of the propeller assemblies **18** within the positional ranges **R** (FIG. **35**), as described in further detail below.

(186) In the particular embodiment of the disclosure illustrated, the base station **100** includes first and second engagement members **316i**, **316ii** that are (non-movably) supported by the actuators **118i**, **118ii**, respectively, such that the engagement members **316i**, **316ii** are spaced laterally from each other along the width **W** of the enclosure **102**. More specifically, the engagement members **316i**, **316ii** are fixedly connected to outer (lateral) faces **322** of the linkage assemblies **122** and are positioned outside (laterally outward of) the hubs **40** of the propeller assemblies **18** (e.g., in line with the propeller arms **38**), which allows the UAV **10** to pass between the engagement members **316i**, **316ii** during retraction of the cradle **106** into the enclosure **102**. It should be appreciated, however, that the particular location of the engagement members **316** may be altered in various embodiments without departing from the scope of the present disclosure (e.g., depending upon the particular configuration of the UAV **10**, the desired positions of the propeller assemblies **18** in the collapsed configuration, etc.). For example, the present disclosure envisions an embodiment in which the engagement members **316** may be (non-movably) supported by (e.g., secured, connected to) the door **104**, as described in further detail below.

(187) The mounting brackets **318** may be connected to the actuators **118** (e.g., the linkage assemblies **122**) in any suitable manner. For example, in the particular embodiment seen in FIGS. **36-38**, the mounting brackets **318** are configured for (releasable) connection to the actuators **118**

via one or more mechanical fasteners **324** (e.g., screws, pins, bolts, clips, etc.), which simplifies assembly and disassembly and facilitates repair, replacement, etc. Alternatively, however, it is envisioned that the mounting brackets **318** and the actuators **118** may be configured for connection in a press-fit (interference fit) arrangement, or that the mounting brackets **318** and the actuators **118** may be fixedly (non-removably) connected. For example, in certain embodiments, it is envisioned that the mounting brackets **318** and the actuators **118** may be integrally (e.g., monolithically) formed.

(188) Mounting of the engagement members **316** to the actuators **118** allows the vertical positions thereof to be adjusted with opening and closure of the door **104** so as to facilitate proper contact with the propeller assemblies **18**, as described in further detail below, while inhibiting (if not entirely preventing) interference with operation of the door **104** and unintended contact between the engagement members **316** and the various internal components of the base station **100**.

Additionally, with reference to FIGS. **39** and **40**, mounting the engagement members **316** to the actuators **118** allows for a reduction in the angular range of motion (path) **A1** followed by the actuators **118** and, thus, the engagement members **316**, during opening and closure of the door **104** when compared to the angular range of motion (path) **A2** followed by the door **104** itself. The reduced angular path **A1** allows the vertical positions of the engagement members **316** to be adjusted with less angular variation and allows for a reduction in a height (length) **HE** (FIG. **38**) of the engagement members **316**, which further reduces any likelihood of unintended contact between the engagement members **316** and the various internal components of the base station **100**, the enclosure **102** (e.g., the forward frame **116** (FIG. **36**)), etc.

(189) In the particular embodiment of the disclosure seen in FIGS. **36-38**, the bumpers **320** include (e.g., are formed partially or entirely from) one or more compliant (flexible) materials, the stiffness of which may be altered by varying one or more parameters of the bumpers **320**. For example, the stiffness of the bumpers **320** may be altered by varying the height **HE** (FIG. **38**), a (lateral) thickness **T** of the bumpers **320**, the configuration (e.g., the shape, profile) of the bumpers **320**, the durometer of the material(s) selected, etc. The use of compliant material(s) facilitates folding of the propeller assemblies **18** while allowing for resilient deflection (e.g., bending) of the bumpers **320**, which inhibits (if not entirely prevents) spearing of the bumpers **320** by the propeller blades **42** and unseating of the UAV **10** from the cradle **106** that might otherwise occur. The use of compliant material(s) also allows the bumpers **320** to return to their normal (undeflected) positions upon sufficient retraction of the UAV **10** to facilitate subsequent contact with the propeller assemblies **18**.

(190) While the bumpers **320** are illustrated as including a rubberized, weather-resistant, and abrasion-resistant material in the particular embodiment of the disclosure seen in FIGS. **36-38**, it is envisioned that the bumpers **320** may include any material(s) that support the operation and functionality described herein.

(191) The bumpers **320** include a first (upper) end portion **326** that extends from (is connected to) the corresponding mounting bracket **318** and a second (lower) end portion **328**. In the particular embodiment seen in FIGS. **36-38**, the second end portion **328** defines an angled (chamfered, beveled, ramped) surface **330**. It is envisioned that the angled surface **330** may guide the bumpers **320** over the propeller assemblies **18** during retraction of the UAV **10** (e.g., to reduce the force applied to the UAV **10** by the engagement members **316**). Embodiments devoid of the angled surface **330**, however, are also envisioned herein and would not be beyond the scope of the present disclosure.

(192) With reference now to FIGS. **2**, **32**, and **35-41**, upon docking of the UAV **10** with the base station **100**, the door **104** is moved from the closed position (FIG. **1**) into the open position (FIGS. **1**, **36**), and the cradle **106** begins to retract into the UAV **10** (e.g., during a first stage of retraction), which brings the rear propeller assemblies **18ri**, **18rii** into alignment (or general alignment) with the engagement members **316**. With the cradle **106** in a first partially retracted position, the door

104 is lowered (e.g., moved into a first partially closed position) and the rear propeller assemblies **18ri**, **18rii** are actively rotated (e.g., via actuation of the corresponding motors **44** (FIG. 2)). Lowering of the door **104** facilitates contact (engagement) with the antenna(s) **34** (FIG. 2) and reconfiguration thereof between the active configuration and the passive configuration as well as adjustment in the vertical positions of the engagement members **316** (FIGS. 39, 40), and active rotation of the rear propeller assemblies **18ri**, **18rii** causes the propeller blades **42** to contact (engage) the engagement members **316** (throughout the following discussion, rotation of the propeller assemblies **18** is described from a point-of-view located vertically above the UAV **10**). More specifically, the rear propeller assembly **18ri** is rotated in a first direction (e.g., clockwise) and the rear propeller assembly **18rii** is rotated in a second, opposite direction (e.g., counterclockwise). Upon contact with the engagement members **316**, continued rotation of the rear propeller assemblies **18ri**, **18rii** causes the propeller blades **42** to pivot about the pivot members **50** (FIG. 32), which results in partial folding of the rear propeller assemblies **18ri**, **18rii** and movement of the rear propeller assemblies **18ri**, **18rii** from the extended configuration towards the collapsed configuration.

(193) Following partial folding of the rear propeller assemblies **18ri**, **18rii**, retraction of the cradle **106** continues (e.g., during a second stage of retraction), which moves the cradle **106** into a second partially retracted position and reconfigures (folds) the antenna(s) **34** from the active configuration into the passive configuration (e.g., via contact (engagement) with the door **104**). The rear propeller assemblies **18ri**, **18rii** are then actively rotated (e.g., via actuation of the corresponding motors **44**) such that the propeller blades **42** are again brought into contact (engagement) with the engagement members **316**. More specifically, the rear propeller assembly **18ri** is rotated in the second direction (e.g., counterclockwise) and the rear propeller assembly **18rii** is rotated in the first direction (e.g., clockwise), which completes folding of the rear propeller assemblies **18ri**, **18rii** such that rear propeller assemblies **18ri**, **18rii** are oriented within the desired positional ranges R (FIG. 35). Folding of the rear propeller assemblies **18ri**, **18rii** is thus performed in two stages (e.g., a first stage, in which the rear propeller assemblies **18ri**, **18rii** are partially folded, and a second stage, in which the rear propeller assemblies **18ri**, **18rii** are completely folded).

(194) In certain embodiments of the disclosure, it is envisioned that the rear propeller assemblies **18ri**, **18rii** may be oriented forwardly (e.g., towards the front propeller assemblies **18fi**, **18fii** and the door **104**) upon complete folding, as seen in FIG. 34C (for example).

(195) Following complete folding of the rear propeller assemblies **18ri**, **18rii**, retraction of the cradle **106** continues (e.g., during a third stage of retraction) as the cradle **106** moves into a third partially retracted position, and the door **104** is lowered (e.g., into a second partially closed position). Retraction of the cradle **106** brings the front propeller assemblies **18fi**, **18fii** into alignment (or general alignment) with the engagement members **316**, and lowering of the door **104** adjusts the vertical positions of the engagement members **316** (FIGS. 39, 40) to facilitate contact (engagement) with the front propeller assemblies **18fi**, **18fii**, which accommodates (compensates for) the difference in the vertical locations (heights) between the rear propeller assemblies **18ri**, **18rii** and the front propeller assemblies **18fi**, **18fii**.

(196) The front propeller assemblies **18fi**, **18fii** are then actively rotated (e.g., via actuation of the corresponding motors **44**) such that the propeller blades **42** are brought into contact (engagement) with the engagement members **316**. More specifically, the front propeller assembly **18fi** is rotated in the second direction and the front propeller assembly **18fii** is rotated in the first direction. Upon contact with the engagement members **316**, continued rotation of the front propeller assemblies **18fi**, **18fii** causes the propeller blades **42** to pivot about the pivot members **50** (FIG. 32), which results in partial folding of the front propeller assemblies **18fi**, **18fii** and movement of the front propeller assemblies **18fi**, **18fii** from the extended configuration towards the collapsed configuration.

(197) Thereafter, retraction of the cradle **106** continues (e.g., during a fourth stage of retraction)

until the cradle **106** is moved into the fully retracted position. As the cradle **106** is moved into the fully retracted position, the cap **156** (FIGS. **1**, **8**, **11**, **12**) moves into the closed position so as to engage the bezel portion **154**, and the front propeller assemblies **18fi**, **18fii** are subjected to additional, passive rotation, during which, the corresponding motors **44** are inactive. More specifically, retraction of the cradle **106** causes the front propeller assembly **18fi** to rotate in the first direction via contact with the engagement members **316i** and the front propeller assembly **18fii** to rotate in the second direction via contact with the engagement member **316ii**, which results in forward orientation of the front propeller assemblies **18fi**, **18fii** (e.g., such that the front propeller assemblies **18fi**, **18fii** are oriented away from the rear propeller assemblies **18ri**, **18rii** and towards the door **104**), as seen in FIG. **34D**.

(198) The door **104** is then lowered further (e.g., into a third partially closed position) and the orientation of the front propeller assemblies **18fi**, **18fii** is altered so as to inhibit (if not entirely prevent) contact between the front propeller assemblies **18fi**, **18fii** and the door **104** during (final) closure. More specifically, the orientation of the front propeller assemblies **18fi**, **18fii** is reversed such that the front propeller assemblies **18fi**, **18fii** are oriented rearwardly (e.g., towards the rear propeller assemblies **18ri**, **18rii** and away from the door **104**), as seen in FIG. **34C** (for example), which completes folding of the front propeller assemblies **18fi**, **18fii** such that the front propeller assemblies **18fi**, **18fii** are oriented within the desired positional ranges R (FIG. **35**). To reverse the orientation of the front propeller assemblies **18fi**, **18fii**, in the particular embodiment illustrated, the front propeller assemblies **18fi**, **18fii** are actively rotated (e.g., via actuation of the corresponding motors **44**) in the first and second directions, respectively. Folding of the front propeller assemblies **18fi**, **18fii** is, thus, performed in three stages (e.g., a first stage, in which the front propeller assemblies **18fi**, **18fii** are partially folded via active rotation, a second stage, in which the front propeller assemblies **18fi**, **18fii** are partially folded via passive rotation, and a third stage, in which the orientations of the front propeller assemblies **18fi**, **18fii** are reversed).

(199) Following complete retraction of the cradle **106** and the UAV **10** into the enclosure **102**, the door **104** is lowered into the (fully) closed position.

(200) In certain embodiments of the disclosure, it is envisioned that the propeller assemblies **18** may undergo a final stage rotation (e.g., a third stage of rotation for the rear propeller assemblies **18ri**, **18rii** and a fourth stage of rotation for the front propeller assemblies **18fi**, **18fii**). In the final stage of rotation, the orientations of the propeller assemblies **18** are altered in order to avoid contact with the various internal components of the docking station **100** (e.g., during subsequent extension of the cradle **106** and the UAV **10**). It is envisioned that particular orientations of the propeller assemblies **18** achieved during the final stage of rotation may be varied depending upon the particular locations and/or configurations of the various internal components of the docking station **100**. For example, embodiments are envisioned in which the front propeller assemblies **18fi**, **18fii** and the rear propeller assemblies **18ri**, **18rii** may be oriented in the same direction, as are embodiments in which the front propeller assemblies **18fi**, **18fii** and the rear propeller assemblies **18ri**, **18rii** may be oriented in different directions and embodiments in which each of the propeller assemblies **18fi**, **18fii**, **18ri**, **18rii** may be oriented differently. The present disclosure also contemplates embodiments in which the final stage rotation may only be performed on certain propeller assemblies **18**. For example, it is envisioned that the final stage of rotation may only be performed on the front propeller assemblies **18fi**, **18fii**, the rear propeller assemblies **18ri**, **18rii**, the front propeller assembly **18fi** and the rear propeller assembly **18rii**, etc.

(201) During the aforescribed sequence, educated (informed) positioning of the door **104** (e.g., the ability of the docking station **100** to control and vary the position (height) of the door **104** and, thus, the engagement members **316**) reduces any likelihood of unintended contact between the engagement members **316** and the UAV **10**. More specifically, allowing the engagement members **316** to remain in an elevated vertical position during retraction of the cradle **106** reduces any likelihood of spearing of the engagement members **316** by the propeller assemblies **18** and

unseating of the UAV **10** from the cradle **106** that may otherwise occur. Educated positioning of the door **104** also allows for adjustments in the flexibility of the engagement members **316**. More specifically, lowering the vertical positions of the engagement members **316** and reducing spacing with the propeller assemblies **18** effectively increases the stiffness of the engagement members **316**, which facilitates and supports reconfiguration of the propeller assemblies **18** in the manner discussed above.

(202) Additionally, the bidirectional rotation of the propeller assemblies **18** discussed in connection with the aforescribed sequence (e.g., rotation of the propeller assemblies **18** in the first and second directions) is dictated by the specific configuration of the propeller assemblies **18** included in the particular embodiment of the UAV **10** illustrated. For example, with reference to FIGS. **42-44**, the propeller assemblies **18** included on the UAV **10** define hard stops **52**, which are configured for contact with an adjacent propeller blade **42** to limit continued rotation thereof. The bidirectional rotation of the propeller assemblies **18** discussed above accounts for (accommodates) the hard stops **52**, however, and allows for reconfiguration of the propeller assemblies **18** in the aforescribed manner. More specifically, rotation of the propeller assemblies **18** in the first direction (e.g., clockwise), which is identified by the arrow **3** (FIG. **42**), causes engagement (contact) between the propeller blades **42** and the corresponding hard stops **52**, as seen in FIGS. **43** and **44**, which results in partial folding of the propeller assemblies **18**. Thereafter, the propeller assemblies **18** are rotated in the opposite, second direction (e.g., counterclockwise), which is identified by the arrow **4**, to complete folding of the propeller assemblies **18**. Embodiments of the UAV **10** are also envisioned, however, in which the propeller assemblies **18** (e.g., the propeller blades **42** and/or the hard stops **52**) may be reconfigured (altered) so as to allow for unidirectional rotation during reconfiguration from the extended configuration into the collapsed configuration and would not be beyond the scope of the present disclosure.

(203) During reconfiguration of the propeller assemblies **18**, active rotation of the propeller assemblies **18** can be precisely controlled by varying the speed, the duration, and the direction of rotation (e.g., via embedded programming in the UAV **10** and/or the docking station **100**). Additionally, feedback from the motors **44** (FIGS. **2**, **42-44**) can be utilized to detect contact between the propeller blades **42** and the hard stops **52**. For example, upon contact between a propeller blade **42** and the corresponding hard stop **52**, a current spike may be detected in the motor **44**. In such embodiments, upon exceeding a threshold current, the motor **44** may be caused to rotate the propeller assembly **18** in the opposite direction or to halt rotation altogether.

(204) In an alternate embodiment of the disclosure, during a different sequence, it is envisioned that the motors **44** remain inactive and that folding of the propeller assemblies **18** may be accomplished solely via contact (engagement) with the engagement members **316**. In such embodiments, the engagement members **316** (e.g., the bumper **320**) act as guides that inhibit (if not entirely prevent) unintended contact between the propeller assemblies **18** and the enclosure **102** (e.g., spearing of the enclosure **102** by the propeller assemblies **18**) during retraction of the cradle **106**. More specifically, the engagement members **316** deflect the propeller blades **42** inwardly so as to inhibit (if not entirely prevent) contact with the forward frame **116** (FIG. **36**) (e.g., adjacent to the door **104**), which allows for folding of the propeller assemblies **18** during retraction of the cradle **106** via contact with the sidewalls **198** (FIGS. **31A**, **36**) of the inner housing **108**. In order to facilitate folding of the propeller assemblies **18**, it is envisioned that the visualization system **174** (FIG. **31B**) may be utilized to verify that the propeller assemblies **18** are positioned properly (e.g., that the propeller blades **42** have been successfully deflected so as to avoid contact with the forward frame **116**) prior to continued retraction of the cradle **106**.

(205) With reference now to FIGS. **45** and **46**, in an alternate embodiment of the base station **100**, it is envisioned that the engagement members **316** may be (non-movably) supported by (e.g., secured, connected to) the door **104**, as mentioned above. In the particular embodiment illustrated, the engagement members **316** are configured as bumpers **332** that each include a cylindrical (or

generally cylindrical) configuration. It should be appreciated, however, that the configuration of the bumpers **332** may be varied without departing from the scope of the present disclosure. For example, it is envisioned that the bumpers **332** may be replaced by the aforescribed bumpers **320**.

(206) The bumpers **332** are positioned inside (laterally inward of) the hubs **40** (FIGS. **32**, **33**, **35**) of the propeller assemblies **18** (e.g., in line with the propeller arms **38**), which allows the propeller assemblies **18** to be oriented in alignment (or general alignment) with the propeller arms **38** in the collapsed configuration, as seen in FIG. **34B**.

(207) Temperature Control System

(208) With reference now to FIGS. **47-52**, the base station **100** includes a temperature control (e.g., heating and cooling) system **200** that is connected to the cradle **106** and which is configured to thermally condition (e.g., cool and heat) the power source **14** (FIGS. **2**, **4**, **5**) of the UAV **10** when the UAV **10** is docked in the base station **100** (subject to environmental conditions). In the particular embodiment of the disclosure illustrated throughout the figures, the temperature control system **200** is configured to cool the power source **14** of the UAV **10** (e.g., when the UAV **10** and the base station **100** are operated in hot environments). It should be appreciated, however, that embodiments in which the temperature control system **200** may be configured to heat the power source **14** of the UAV **10** (e.g., when the UAV **10** and the base station **100** are operated in cold environments) are also envisioned herein and would not be beyond the scope of the present disclosure, as described in further detail below.

(209) The temperature control system **200** includes: an upper air circuit **202**; a lower air circuit **204**; and a thermoelectric conditioner (TEC) **206** that is thermally connected to, and located between, the respective upper and lower air circuits **202**, **204**.

(210) The upper air circuit **202** is an open system that receives and circulates ambient air, which may be sourced from within the base station **100** or externally of the base station **100** (e.g., via an air intake) to vary (regulate) the temperature of the TEC **206**. The upper air circuit **202** includes: an upper (first) plenum **208**; an upper (first) air circulator **210**; and an upper (first) heat sink **212**.

(211) The upper plenum **208** includes an (upper) ducting system **214** that receives and circulates the ambient air. The ducting system **214** may include any suitable material (or combination of materials) and may include either a unitary configuration, in which the upper plenum **208** is formed from a single piece of material, or a segmented configuration, in which the upper plenum **208** is formed from a plurality of segments that are connected together (e.g., via one or more mechanical fasteners, an adhesive, in an interference fit, etc.). In certain embodiments, it is envisioned that the upper plenum **208** may also include one or more sensors that are configured to detect and monitor temperature, humidity, etc. within the upper plenum **208**.

(212) The upper air circulator **210** supports and directs air flow through the upper plenum **208** and across the upper heat sink **212** to vary air temperature within the upper air **202** and thereby regulate the temperature of the TEC **206**, as described in further detail below. The upper air circulator **210** may include any structure or mechanism suitable for that intended purpose and may be positioned in any location suitable. For example, in the illustrated embodiment, the upper air circulator **210** is configured as a fan **216** (e.g., an axial fan) that is located within the upper plenum **208** (e.g., within the ducting system **214**). It is also envisioned, however, that the upper air circulator **210** may be located externally of the upper plenum **208**. For example, the upper air circulator **210** may be connected to (or otherwise supported on) an outer surface **218** of the ducting system **214**.

(213) The upper heat sink **212** (FIGS. **51**, **52**) is connected to (e.g., located within) the upper plenum **208** and is configured to alter the temperature of the air circulated through the upper air circuit **202**. For example, when the temperature control system **200** is utilized to cool the power source **14** (FIGS. **2**, **4**, **5**) of the UAV **10**, the upper heat sink **212** absorbs and distributes thermal energy (heat) generated by the TEC **206** to lower the temperature of the air flowing through the upper plenum **208**, as described in further detail below. To increase the absorption and distribution

of thermal energy by the upper heat sink **212**, air flow through the upper plenum **208** and, thus, air flow across the upper heat sink **212**, may be increased by increasing the speed of the upper air circulator **210** (e.g., by increasing power to the fan **216**).

(214) The lower air circuit **204** includes a lower (second) plenum **220**; a lower (second) air circulator **222**; and a lower (second) heat sink **224** and is configured as a closed system. As such, in contrast to the upper air circuit **202**, rather than drawing in additional ambient air, the lower air circuit **204** continuously circulates the air that is naturally present within the lower plenum **220**.

(215) The lower plenum **220** includes a (lower) ducting system **226** that directs air flow across the cradle **106** and the power source **14** of the UAV **10** when the UAV **10** is docked within the base station **100** and may include any suitable material (or combination of materials). The lower plenum **220** (e.g., the ducting system **226**) includes a segmented (non-unitary) configuration that defines a rear (first, fixed) section **228** and a forward (second, movable) section **230** that is movable in relation to the rear section **228**. In various embodiments of the disclosure, it is envisioned that the sections **228**, **230** may include either a unitary configuration, in which the sections **228**, **230** are each formed from a single piece of material, or a segmented configuration, in which the sections **228**, **230** are formed from a plurality of segments that are connected together (e.g., via one or more mechanical fasteners, an adhesive, in an interference fit, etc.). In certain embodiments, it is envisioned that the lower plenum **220** may also include one or more sensors that are configured to detect and monitor temperature, humidity, etc. within the upper plenum **208**.

(216) The rear section **228** of the lower plenum **220** is fixedly secured (connected) to the TEC **206** and, as such, is fixed in relation to the upper air circuit **202**. The forward section **230** of the lower plenum **220** is secured (connected) to the cradle **106** and is movable therewith during repositioning of the cradle **106** between the retracted position (FIGS. 2, 10) and the extended position (FIG. 13). As such, throughout the following disclosure, any references to the cradle **106** should be understood as referring to the assembly of the cradle **106** and the forward section **230** of the lower plenum **220**.

(217) The forward section **230** of the lower plenum **220** receives air from the rear section **228** and defines an air inlet **232** and an air outlet **234**, which are provided in (defined by) the cradle **106** and are located on opposite sides **142a**, **142b** of the chamber **142**). The air inlet **232** and the air outlet **234** each include one or more vents **235** (e.g., slits, apertures, or other such openings) that extend through the cradle **106** (e.g., the sidewalls **146**) and into the chamber **142**. The vents **235** facilitate air flow into and across the chamber **142** by directing air conditioned by the lower air circuit **204** into the cradle **106** and across the power source **14** of the UAV **10** when the UAV **10** is docked in the base station **100**. More specifically, the air inlet **232** is configured to direct air into the cradle **106** and across the power source **14** of the UAV **10** and the air outlet **234** is configured to receive the air directed across the power source **14** and redirect the air through the lower plenum **220** and across the lower heat sink **224**, as described in further detail below.

(218) Although shown as extending entirely about the cradle **106** in the particular embodiment illustrated throughout the figures, embodiments are also envisioned in which the forward section **230** of the lower plenum **220** may only partially circumscribe the cradle **106**. For example, embodiments are envisioned in which the forward section **230** of the lower plenum **220** may include opposite terminal ends that respectively define the air inlet **232** and the air outlet **234**.

(219) Additionally, while the forward section **230** of the lower plenum **220** and the cradle **106** are illustrated as being integrally (e.g., monolithically) formed in the illustrated embodiment, it is also envisioned that the lower plenum **220** and the cradle **106** may be configured for releasable (detachable) engagement to allow for repeated connection and disconnection of the lower plenum **220** and the cradle **106** (e.g., via corresponding engagement structures such as detents, clips, fasteners, or the like).

(220) The lower air circulator **222** supports and directs air flow through the lower plenum **220** and across the lower heat sink **224** to thermally condition the air within the lower air circuit **204** (e.g.,

vary the temperature thereof) and thereby heat or cool the power source **14** of the UAV **10**, as described in further detail below. The lower air circulator **222** may include any structure or mechanism suitable for that intended purpose and may be positioned in any location suitable. For example, in the illustrated embodiment, the lower air circulator **222** is configured as a fan **236** (e.g., a blower fan) that is located within the lower plenum **220** (e.g., within the ducting system **226**). It is also envisioned, however, that the lower air circulator **222** may be located externally of the lower plenum **220**. For example, the lower air circulator **222** may be connected to (or otherwise supported on) an outer surface **238** of the ducting system **226**.

(221) The lower heat sink **224** is connected to (e.g., located within) the lower plenum **220** and is configured to treat the air circulated therethrough (e.g., alter the temperature of the air within the lower plenum **220** via cooling or heating) prior to direction across the power source **14** of the UAV **10**. For example, when the temperature control system **200** is utilized to cool the power source **14** of the UAV **10**, the lower heat sink **224** absorbs and distributes thermal energy (heat) from the air flowing through the lower plenum **220** to lower the temperature thereof and, thus, the power source **14** of the UAV **10**. To increase the absorption and distribution of thermal energy by the lower heat sink **224** and, thus, enhance cooling of the power source **14** of the UAV **10**, air flow through the lower plenum **220** and, thus, air flow across the lower heat sink **224**, may be increased by increasing the speed of the lower air circulator **222** (e.g., by increasing power to the fan **236**).

(222) The TEC **206** is configured as a Peltier system and includes a dedicated/integrated power source/control as well as a first (upper, “hot”) end **240** (FIG. 51) and a second (lower, “cold”) end **242**, each of which includes a thermal member (e.g., a ceramic plate). The first end **240** is thermally and/or physically connected to the upper heat sink **212** and the second end **242** is thermally and/or physically connected to the lower heat sink **224**. Upon activation, as current flows through the TEC **206**, the temperature of the first end **240** increases (to an upper temperature threshold) while the temperature of the second end **242** decreases (to a lower temperature threshold) until a predetermined, fixed temperature differential is realized. For example, it is envisioned that the differential between the respective upper and lower ends **240**, **242** of the TEC **206** may lie substantially within the range of (approximately) 30° C. to (approximately) 70° C. (e.g., (approximately) 50° C.). Embodiments in which the temperature differential may lie outside the disclosed range, however, are also envisioned herein and would not be beyond the scope of the present disclosure. Consequently, reducing the upper temperature threshold allows for a corresponding reduction in the lower temperature threshold.

(223) During operation of the temperature control system **200**, in the particular embodiment of the disclosure illustrated, thermal energy (heat) generated by the TEC **206** is absorbed and dissipated by the upper heat sink **212** and the ambient air flowing through the upper plenum **208**. The upper air circuit **202** thus cools the first (“hot”) end **240** of the TEC **206**, which results in corresponding cooling of the second (“cold”) end **242** of the TEC **206** and, thus, increased cooling of the air flowing through the lower plenum **220** and the power source **14** of the UAV **10** when the UAV **10** is docked in the base station **100**.

(224) Although illustrated as including a single TEC **206** in the particular embodiment shown throughout the figures, embodiments are also envisioned in which the temperature control system **200** may include multiple TECs **206**. In such embodiments, it is envisioned that the TECs **206** may be identical or non-identical in configuration (e.g., it is envisioned that the temperature control system **200** may include TECs **206** that vary in size) and/or that the TECs **206** may be arranged in series or in parallel (e.g., in a stacked configuration).

(225) As indicated above, embodiments of the disclosure are envisioned herein in which the temperature control system **200** may be configured to heat, rather than cool, the power source **14** of the UAV **10** when the UAV **10** is docked in the base station **100**. In such embodiments, current flow through the TEC **206** can be reversed (e.g., via electronic control) such that the first end **240** of the TEC **206** functions as the “cold” end and the second end **242** of the TEC **206** functions as the “hot”

end.

(226) During use of the temperature control system **200**, the upper air circuit **202** draws air in from the ambient, either from within the base station **100** or externally of the base station **100**, which is directed across the upper heat sink **212** via the upper air circulator **210**. As the air flows across the upper heat sink **212**, heat is withdrawn, thereby cooling the upper heat sink **212** and, thus, the first (“hot”) end **240** of the TEC **206**, and heating the air. The heated air is then discharged from the upper air circuit **202**, being expelled either into the base station **100** or externally thereof (e.g., through a vent), and is replaced by cooler ambient air that is drawing into the upper air circuit **202** by the upper air circulator **210**.

(227) Upon docking of the UAV **10**, as the cradle **106** moves from the extended position (FIG. **13**) into the retracted position (FIGS. **2**, **10**), the forward section **230** of the lower plenum **220** mates with (engages) the rear section **228**, which closes the lower air circuit **204** and allows for the continuous circulation of air therethrough. To facilitate mating engagement between the forward section **230** and the rear section **228**, it is envisioned that the forward section **230** and the rear section **228** may include one or more seals (e.g., O-rings) or corresponding engagement structures (e.g., collars, flanges, or the like) at the interface therebetween.

(228) Air flowing through the lower air circuit **204** is directed across the lower heat sink **224** via the lower air circulator **222**, which withdraws heat from the air to cool the air prior to entering the chamber **142** of the cradle **106** via the air inlet **232**. As the cooled air flows through across the cradle **106** and through the chamber **142**, heat is withdrawn from the power source **14** (FIGS. **2**, **4**, **5**) of the docked UAV **10**, which is facilitated by the heat exchanger **24**. More specifically, in the illustrated embodiment, the cooled air flows through the channels **32** (FIG. **4**) defined by the diffusers **26** (e.g., the fins **30**), which increases the distribution of thermal energy from the power source **14** of the UAV **10** to enhance cooling, and increases the temperature of the air. After flowing across the power source **14**, the (heated) air exits the chamber **142** via the air outlet **234** and is redirected across the lower heat sink **224** (e.g., via the lower air circulator **222**) to again cool the air prior to recirculation through the cradle **106** and across the power source **14**.

(229) Cradle Insulation

(230) With reference to FIGS. **56-58**, in certain embodiments of the disclosure, it is envisioned that the cradle **106** may include an insulated construction to allow for increased control over, and regulation of, the temperature of the power source **14** of the UAV **10** when the UAV **10** is docked within the base station **100**. More specifically, insulation of the cradle **106** promotes and facilitates cooling and heating of the power source **14** and maintains the temperature of the power source **14** for increased periods of time.

(231) The (insulated) cradle **106** includes: an upper (first) shell **362**; a lower (second) shell **364**; and one or more thermal insulators **366**, wherein the shells **362**, **364** collectively define a housing **365** of the cradle **106**. It is envisioned that the shells **362**, **364** and the thermal insulator(s) **366** may be formed from any suitable materials. For example, in the particular embodiment illustrated, the shells **362**, **364** each include (e.g., are formed partially or entirely from) one or more non-metallic (e.g., plastic) materials and the thermal insulator(s) **366** include (e.g., are formed partially or entirely from) an insulative foam. Embodiments in which the shells **362**, **364** and/or the thermal insulator(s) **366** may include one or more alternate materials, however, would not be beyond the scope of the present disclosure. For example, embodiments in which the shell **362** and/or the shell **364** may include a composite material (e.g., carbon fiber) are also envisioned herein (e.g., to increase the overall strength and/or rigidity of the cradle **106**).

(232) The upper shell **362** is configured to receive the UAV **10** during docking and defines the chamber **142**, the sidewalls **146**, the air inlet **232** (FIGS. **47-49**), the air outlet **234**, and the angled guide surface **148** mentioned above, which collectively facilitate proper seating of the UAV **10** within the cradle **106**.

(233) The lower shell **364** is connected to the upper shell **362** and provides structural rigidity to the

cradle **106**. The lower shell **364** defines a charging window **368**, which is located in the rear end **106b** of the cradle **106**, as well as a pair of airflow openings **370**, **372** that are in respective communication with the air inlet **232** and the air outlet **234** so as to facilitate the circulation of cooled and heated air through the cradle **106** following conditioning by the TEC **206**. As described in further detail below, the charging window **368** is configured to receive the charging hub **143** (FIG. **10**) such that the charging hub **143** is extendable into and through the cradle **106** during retraction of the UAV **10** into the base station **100** to thereby facilitate connection of the charging hub **143** to the power source **14** of the UAV **10**. The airflow openings **370**, **372** are in communication with the air inlet **232** and the air outlet **234**, respectively, and allow cooled and heated air to enter the cradle **106** following condition by the TEC **206**.

(234) With reference to FIG. **58** in particular, the cradle **106** (e.g., the assembly of the cradle **106** and the forward section **230** of the lower plenum **220**) includes lead-ins **374**, which are positioned adjacent to (e.g., about) the airflow openings **370**, **372** and each define a chamfered (beveled, angled) end walls **376** that facilitates entry of the cradle **106** into the base station **100** during retraction. For example, in the event of misalignment with the window **113** (FIG. **2**) and contact with the enclosure **102** (e.g., the forward frame **116**), the lead-ins **374** redirect the cradle **106** (and the forward section **230** of the lower plenum **220**) laterally inward, thereby inhibiting (if not entirely preventing) jamming, damage to the cradle **106** and/or the forward section **230** of the lower plenum **220**, damage to the enclosure **102**, etc. The chamfered end walls **376** also facilitate proper registration of the cradle **106** (and the forward section **230** of the lower plenum **220**) and are configured for (mating) engagement (contact) with corresponding chamfered (beveled, angled) end walls **378** (FIG. **58**) on the rear section **228** of the lower plenum **220** such that, upon retraction of the cradle **106**, the cradle **106** (and the forward section **230** of the lower plenum **220**) mates with the rear section **228** of the lower plenum **220**, thereby facilitating proper air flow through the temperature control system **200** and the cradle **106** to support thermal conditioning (e.g., heating and cooling) of the power source **14** of the UAV **10**. The end walls **376**, **378** thus define corresponding mating surfaces on the cradle **106** and the rear section **228** of the lower plenum **220**, respectively.

(235) It is envisioned that the shells **362**, **364** may be connected together in any suitable manner. For example, in the particular embodiment of the cradle **106** illustrated, the shells **362**, **364** are connected via one or more mechanical fasteners (e.g., screws, pins, bolts, clips, etc.), which extend through openings **380** in the shells **362**, **364**. It is envisioned, however, that the shells **362**, **364** may be configured for connection in any suitable manner. For example, embodiments are also envisioned in which the shells **362**, **364** may be configured for engagement in a press-fit (interference fit) arrangement. Mechanically connecting the shells **362**, **364** simplifies assembly and disassembly of the cradle **106** so as to facilitate repair of the cradle **106**, replacement of any of the components thereof, etc.

(236) The thermal insulator(s) **366** are located and secured between the shells **362**, **364** (e.g., such that the thermal insulator(s) **366** are located within the housing **365**) and collectively define an airflow channel **382** that extends about the chamber **142** and, thus, the power source **14** when the UAV **10** is docked within the cradle **106**. In the particular embodiment of the disclosure illustrated, the cradle **106** is shown as including a pair of thermal insulators **366** (e.g., an upper thermal insulator **366i** and a lower thermal insulator **366ii**), which facilitates and simplifies the manufacture and assembly of the cradle **106**. Embodiments are also envisioned, however, in which the cradle **106** may include a single thermal insulator **366** that is unitary in construction (e.g., a monolithic thermal insulator **366** that is formed from a single piece of (insulative) material).

(237) The thermal insulator(s) **366** define an internal compartment **367** that is configured to receive (accommodate) the upper shell **362** such that the upper shell **362** (e.g., the chamber **142**) extends into the thermal insulator(s) **366**. More specifically, in the particular embodiment illustrated, the thermal insulators **366i**, **366ii** respectively include an opening **367a** and a recess **367b** that

collectively define the internal compartment **367** such that, upon assembly of the cradle **106**, the chamber **142** extends through the opening **367a** and is received by (positioned within) the recess **367b**.

(238) The airflow channel **382** is configured to receive, direct, and circulate thermally-conditioned air within (e.g., through, across) the cradle **106**. In the particular embodiment illustrated, the airflow channel **382** extends between thermal insulators **366i**, **366ii** and includes a (first) channel portion **384** with respective rear and front ends **386**, **388** that is in communication with the airflow opening **370** and the air inlet **232** and a (second) channel portion **390** with respective rear and front ends **392**, **394** that is in communication with the airflow opening **370** and the air outlet **234**. As seen in FIG. 57, the respective front ends **388**, **392** of the channel portions **384**, **390** are separated by a nose section **396** of the cradle **106**. The airflow channel **382** thus includes a discontinuous configuration that partially circumscribes the cradle **106** and the chamber **142** and inhibits (if not entirely prevents) air flow from the front end **388** of the channel portion **384** into the front end **394** of the channel portion **390**, thereby directing air from the air inlet **232**, across the chamber **142**, and into the air outlet **234**. Embodiments in which the airflow channel **382** may include a continuous (uninterrupted) configuration that entirely circumscribes the cradle **106** and the chamber **142** would not be beyond the scope of the present disclosure, however.

(239) Weather and Climate Management

(240) To allow for operation in various weather conditions, the base station **100** includes a plurality of components and systems that are configured to regulate temperature, moisture, humidity, and the like in order to maximize operability in a variety of environments.

(241) Snow and Ice

(242) As seen in FIGS. 53A and 53B, in certain embodiments of the disclosure, the base station **100** includes a (primary) heating system **244** that includes one or more heating elements **244a** (e.g., resistive heaters **244b**) that are thermally and/or physically connected to (supported by) the enclosure **102** (e.g., via an adhesive). Although shown as being associated with (supported by) the roof section **176** of the outer housing **110** in the particular embodiment illustrated, it is envisioned that the heating element(s) **244a** may be thermally and/or physically connected to any section(s) of the outer housing **110** that may benefit from heating. Upon activation, the heating element(s) **244a** increase the temperature of (heat) the outer housing **110** (e.g., to reduce the presence of snow and/or ice on the roof section **176** and thereby expose (reveal) the fiducial(s) **168** to facilitate visual identification of the base station **100** and/or guidance of the UAV **10** during landing and docking with the base station **100**). To further assist with the management of precipitation (e.g., snow, ice, sleet, rain, etc.), it is envisioned that the roof section **176** may be pitched (e.g., at 3°-5°) to encourage runoff and inhibit (if not entirely prevent) pooling on the roof section **176**.

(243) It is envisioned that the heating element(s) **244a** may be connected to any suitable power source, whether internal to the base station **100** (e.g., to the power supply controlled by the main board/processor) or external (e.g., to a separate power supply, battery, or the like), and that the heating system **244** (e.g., the heating element(s) **244a**) may be either manually or automatically activated. For example, it is envisioned that the heating system **244** may be activated via a signal that is relayed by one or more temperature sensors **246** that are in communication with the heating element(s) **244a** and which are configured to detect a threshold (environmental) temperature such that the heating system **244** is automatically activated when the temperature falls below or exceeds a predetermined value (e.g., 32° F.). Additionally, or alternatively, it is envisioned that the heating system **244** may be activated upon receiving an activation signal from a weather station (e.g., via a cloud-based or other such wireless connection) and/or from the visualization system **174**, which may be configured to visually inspect environmental conditions (e.g., to detect the presence of snow and/or ice) and relay the activation signal to the heating system **244**.

(244) With reference to FIGS. 59-62, to further support operation of the base station **100** in cold environments and/or conditions, it is envisioned that the base station **100** may include a

(secondary) heating system **245** that is supported by the enclosure **102**. More specifically, the heating system **245** includes one or more additional (interior) heating elements **244a** that are supported by (connected to) an inner (internal) surface **116b** of the forward frame **116** to facilitate opening and closure of the door **104**. The heating system **245** is located (positioned) adjacent (or generally adjacent) to a sealing member **398**, which is configured for engagement (contact) with the door **104** to form a seal therewith so as to inhibit (if not entirely prevent) the entry of dust, debris, moisture, water, etc., into the base station **100**. More specifically, the sealing member **398** is supported by the enclosure **102** (e.g., the forward frame **116**) and extends about the window **113**. To augment the distribution of thermal energy from the heating elements **244a**, in certain embodiments, it is envisioned that a thermal interface material **400** may be provided (located) between the forward frame **116** and the heating element(s) **244a**, as seen in FIG. **61**.

(245) As discussed above in connection with FIGS. **53a**, **53b** and heating of the roof section **176**, the heating system **245** may be connected to any suitable power source, whether internal or external to the base station **100** and may be either manually or automatically activated (e.g., via a signal that is relayed by one or more temperature sensors **246**, upon receiving an activation signal from a weather station and/or from the visualization system **174**, etc.). Upon activation of the heating element(s) **244a**, thermal energy is communicated to the sealing member **398** and/or the door **104** to heat the sealing member **398** and/or the door **104**. Heating of the sealing member **398** and/or the door **104** melts snow, ice, etc., and thereby facilitates proper opening and closure of the door **104**.

(246) In certain embodiments of the disclosure, it is envisioned that the heating system **245** may also include the status indicator(s) **172**. In such embodiments, the light source(s) **173** (e.g., the LED(s) **186**) may serve to augment the thermal effects of the heating element(s) **244a** by utilizing the thermal conductivity of the sheet metal used comprising the outer housing **110** (e.g., the forward frame **116**) to communicate heat generated via operation of the status indicator(s) **172** to the sealing member **398** and/or the door **104**. In such embodiments of the disclosure, the status indicator(s) **172** thus offer dual functionality (e.g., illumination and heating of the sealing member **398** and/or the door **104**).

(247) With reference to FIG. **63**, in certain embodiments of the disclosure, additionally or alternatively, it is envisioned that the sealing member **398** and/or the door **104** may include one or more thermally conductive members **402** (e.g., strip heaters, wires, coils, plates, etc.), which may be connected to any suitable power source, whether internal or external to the base station **100**. For example, in the particular embodiment illustrated, the base station **100** includes a (first) thermally conductive member **402i** that is embedded within the sealing member **398** and a (second) thermally conductive member **402ii** that is embedded within the door **104**. In such embodiments, upon activation of the thermally conductive members **402**, electrical energy is communicated (transferred) to the sealing member **398** and/or the door **104** to thereby heat the sealing member **398** and/or the door **104** and effectuate the necessary or desired temperature change.

(248) Internal Temperature and Humidity Regulation

(249) To regulate (control) the temperature and/or humidity within the base station **100**, it is envisioned that the base station **100** may include one or more internal fans **248** (FIG. **64**), which may be supported in any suitable location on the inner housing **108** and/or the outer housing **110**. The internal fan(s) **248** regulate (e.g., vary, control) temperature and/or humidity within the base station **100** and may be configured to either cool the base station **100** or heat the base station **100** (e.g., via thermal connection to one or more heating elements or components).

(250) The internal fan(s) **248** are controllable (e.g., via the main board/processor) to draw air in and exhaust air through one or more ports/vents in the outer housing **110** and/or the inner housing **108**, the location(s) of which may be varied to direct air flow in a particular direction (e.g., across the UAV **10**). For example, it is envisioned that the port(s)/vent(s) may be located and/or configured to create air flow through the base station **100** in any effective (or otherwise desired) pattern.

(251) In certain embodiments of the disclosure, it is envisioned that the internal fan(s) **248** may be

automatically activated via a signal that is relayed by one or more sensors **250** that are configured to detect temperature, humidity, etc. Additionally, or alternatively, it is envisioned that the internal fan(s) **248** may be connected to a timer such that the internal fan(s) **248** are automatically activated at a particular time of day.

(252) In the context of humidity regulation, upon the detection of moisture, the sensor(s) **250** may generate an activation signal that can be utilized to initiate one or more mitigation processes. For example, it is envisioned that the sensor(s) may be in communication with the internal fan(s) **248** such that the internal fan(s) **248** are engaged upon receipt of the activation signal from the sensor(s) **250** to remove (or otherwise mitigate) excess humidity within the base station **100**, thereby inhibiting (if not entirely preventing) condensation that might otherwise compromise the functionality of one or more components of the UAV **10** or the base station **100**. For example, the presence of condensation may result in malfunction and/or damage to the electronics modules (e.g., the main board/processor) and/or “fogging” of the visualization system **174**. To further inhibit (if not entirely prevent) the presence of humidity, condensation, moisture, etc., in certain embodiments of the disclosure, it is envisioned that the electronics modules may be sealed within the base station **100**. For example, the electronics module, or the various components thereof (e.g., motor drivers, interface boards, lighting boards, etc.), may be sealed, either collectively (via hermetic sealing) or individually (e.g., via dip coating).

(253) Drainage

(254) In certain embodiments of the disclosure, the enclosure **102** (e.g., the outer housing **110**) may include one or more channels **252** (FIG. **65**) that are configured to collect and direct water away from any entry points into the enclosure **102** in a manner that inhibits (if not entirely prevents) entry into the base station **100** and/or away from any components, whether electronic, mechanical, or otherwise, that may be compromised by the presence of moisture. For example, it is envisioned that the channel(s) **252** may be configured to collect and direct water away from the interface with any power cables, any locking members/mechanisms, the door **104** (FIG. **1**), etc. While the enclosure **102** is shown as including a single channel **252** that extends about a rear periphery **254** of the outer housing **110** in the particular embodiment illustrated, it should be appreciated that the number of channels **252** and/or the location of the channels **252** may be varied without departing from the present disclosure. For example, embodiments including one or more additional channels **252** are also envisioned herein, as are embodiments in which the enclosure **102** may include one or more channels **252** that extend about a front periphery **256** (FIG. **1**) of the outer housing **110**, the roof section **176**, etc.

(255) In the particular embodiment of the base station **100** illustrated in FIG. **65**, the channel **252** is defined by an (molded) insert **258** that is incorporated into the outer housing **110**. It is envisioned, however, that the channel(s) **252** may be configured in any manner suitable for the intended purpose of collecting and/or directing water in the manner described herein. For example, embodiments are also envisioned in which the channel(s) **252** may be integrally (e.g., monolithically) formed with the outer housing **110**.

(256) In certain embodiments of the disclosure, to further inhibit (if not entirely prevent) water penetration, it is envisioned that the enclosure **102** may include one or more seals, gaskets, etc., that are associated with the channel(s) **252**. For example, it is envisioned that such seals, gaskets, etc., may be positioned about the insert **258** and supported by the inner housing **108** and/or the outer housing **110**.

(257) It should be appreciated that any of the aforementioned components and/or systems may be omitted in order to reduce the overall cost and complexity of the base station **100**. For example, in hot (e.g., desert) climates, it is envisioned that the heating element(s) **244a** may be eliminated.

(258) Visualization System

(259) With reference now to FIG. **1**, the visualization system **174** includes a digital image capturing device **260** (e.g., a digital camera) or the like. It is envisioned that the visualization system **174** may

be connected to any suitable power source, whether internal to the base station **100** (e.g., to the power supply controlled by the main board/processor) or external (e.g., to a separate power supply, battery, or the like).

(260) In the particular embodiment of the disclosure illustrated, the visualization system **174** includes a single digital image capturing device **260** that is secured (connected, mounted) to, or otherwise supported by, the forward frame **116** of the outer housing **110**, which supports observation and visual analysis of the environment in which the base station **100** is located as well as observation and visual analysis of the UAV **10** (FIG. 2) prior to takeoff, during takeoff, and during landing. It should be appreciated, however, that the number of digital image capturing devices **260** and/or the location of the digital image capturing device(s) **260** may be varied in alternate embodiments without departing from the present disclosure. For example, embodiments including one or more additional digital image capturing devices **260** are also envisioned herein.

(261) During operation of the base station **100**, the visualization system **174** supports visual inspection of the environment, which not only improves safety of the base station **100** and the UAV **10** by confirming the absence of people, animals, etc., prior to takeoff, during takeoff, and during landing of the UAV **10**, but functionality of the base station **100** as well. For example, it is envisioned that the visualization system **174** may be configured to identify precipitation (e.g., snow, ice, rain, etc.) and actuate (trigger) operation of the heating element(s) **244a** (FIGS. 53A, 53B), the internal fan(s) **248** (FIG. 64), or other such systems. It is also envisioned that the visualization system **174** may be utilized to inspect the UAV **10** (e.g., prior to takeoff and/or during docking) and identify any damage that may result in subsequent suboptimal performance.

(262) Charging of the UAV

(263) With reference now to FIGS. 66-75, charging of the UAV **10** will be discussed. As indicated above, upon docking with the base station **100**, the UAV **10** and the power source **14** are received by the cradle **106**, which facilitates alignment and engagement with the charging hub **143**. The charging hub **143** is configured for electrical connection to any suitable power source, whether internal to the base station **100** or external, and includes: a base **404**; an alignment bracket **406** that is movably (slidably) supported by the base **404**; one or more biasing members **408**; a charging member **410** including a PCB **412** and a (male) electrical connector **414**; and a cap (cover, lid) **416** that overlies the charging member **410**.

(264) The base **404** is fixedly (non-movably) connected to the enclosure **102** and supports the remaining components of the charging hub **143**. More specifically, in the particular embodiment illustrated, the base **404** is fixedly (non-movably) connected to the slide mechanism **150** (e.g., the stationary slide member **151a**), as seen in FIGS. 10 and 64, for example, by a plurality of mechanical fasteners **417** (FIG. 67) (e.g., screws, pins, bolts, clips, etc.), which fixes the charging hub **143** in relation to not only the enclosure **102**, but the cradle **106** and the UAV **10**. It should be appreciated, however, that the particular location of the base **404** may be varied in alternate embodiments without departing from the scope of the present disclosure. For example, embodiments are also envisioned in which the base **404** may be connected to the sheet metal base **264** (FIG. 14) of the enclosure **102**.

(265) The base **404** defines a cavity (receptacle) **418** (FIG. 71A) that is configured to receive the alignment bracket **406** (and the biasing member(s) **408**) such that the alignment bracket **406** is movable within the cavity **418** and in relation to the base **404** during repositioning between a normal (initial, extended) position (FIG. 71A) and a deflected (subsequent, retracted) position (FIG. 71B), as described in further detail below. More specifically, the base **404** includes: a rear end wall **420**, which includes a boss (support) **422**; a front end wall **424**; sidewalls **426**, **428**; and a base wall **430**, which collectively define the cavity **418**.

(266) The base wall **430** is configured to support the alignment bracket **406** during repositioning between the normal and deflected positions. The base wall **430** extends between the side walls **426**, **428** and includes opposing (rear and front) ends **434**, **436** that are spaced from the end walls **420**,

424, respectively. More specifically, the ends **434**, **436** of the base wall **430** are spaced (axially) from the end walls **420**, **424** such that the base **404** defines (first, rear and second, front) openings **438**, **440**, respectively. The opening **438** is configured to provide access to the cavity **418** during manufacture and assembly of the charging hub **143** (e.g., to facilitate fabrication of the base **404** and the alignment bracket **406**) and the opening **440** is configured to receive the alignment bracket **406** such that the alignment bracket **406** is insertable into the base **404** during assembly of the charging hub **143**.

(267) The base wall **430** defines a guide surface **442** (FIG. 73) that is configured for contact (engagement) with the alignment bracket **406** during extension and retraction within the cavity **418**. In order to facilitate and support proper movement and repositioning of the alignment bracket **406**, the (front) end **436** of the base wall **430** includes a chamfered (beveled) surface **444** that is configured for engagement (contact) with the alignment bracket **406** so as to direct the alignment bracket **406** into contact (engagement) with the guide surface **442** and thereby inhibit jamming.

(268) The alignment bracket **406** supports (and is connected to) the charging member **410** and facilitates proper alignment between the UAV **10** and the charging hub **143** during retraction of the cradle **106** and, thus, electrical connection of the charging member **410** and the power source **14** of the UAV **10**. In the particular embodiment illustrated, the alignment bracket **406** is unitary (e.g., monolithic) in construction and is formed from a single piece of material. In alternate embodiments of the disclosure, however, it is envisioned that the alignment bracket **406** may include a series of individual components that are connected together in any suitable manner (e.g., via one or more mechanical fasteners, in an interference fit, etc.). As described in detail below, the alignment bracket **406** includes: a head section **448**; a body **450** that extends from the head section **448**; and a leg **452** that extends from the body **450**.

(269) The head section **448** defines (first and second) platforms **454**, **456** that are configured to support the PCB **412** and the electrical connector **414**, respectively, and includes one or more alignment members **458**. The platform **454** defines an aperture **460** that is configured to receive a mechanical fastener **462** (FIG. 72) (e.g., a screw, a pin, a bolt, a clip, etc.), which releasably and fixedly (non-movably) connects the charging member **410** and the alignment bracket **406** such that the charging member **410** and the alignment bracket **406** are movable in unison (contemporaneously), along an axis of movement M, during repositioning of the alignment bracket **406** between the normal and deflected positions.

(270) The alignment member(s) **458** extends axially forward of the charging member **410** (e.g., the electrical connector **414**) along the axis of movement M and are configured for insertion into a receptacle **464** defined by the power source **14** of the UAV **10** so as to facilitate proper positioning of the charging member **410** and electrical connection to the UAV **10**, as described in further detail below. In the particular embodiment illustrated, the alignment bracket **406** includes a pair of alignment members **458i**, **458ii** that are each configured as a pin **466**. It should be appreciated, however, that the particular number and/or configuration of the alignment members **458** may be altered in various embodiments without departing from the scope of the present disclosure. For example, an embodiment of the alignment bracket **406** including a single alignment member **458** is also envisioned herein.

(271) In order to improve tolerances, the alignment member **458** includes a tapered (conical) end **468** and the receptacle **464** includes chamfered (beveled) mouth **470**. The tapered end **468** of the alignment member **458** and the chamfered mouth **470** of the receptacle **464** allow and account for any offset (misalignment) therebetween and thereby facilitate proper insertion of the alignment member **458** into the receptacle **464**.

(272) The body **450** of the alignment bracket **406** extends rearwardly from the head section **448** and defines a recess **472** (FIG. 71A), which extends between the head section **448** and the leg **452**. The recess **472** is configured to receive the end wall **424** (defining the cavity **418** in the base **404**) such that the end wall **424** spaced an axial distance D from the head section **448** of the alignment

member **458**, which extends in parallel (or generally parallel) relation to the axis of movement M. During retraction of the alignment bracket **406** (e.g., as the UAV **10** is connected to charging hub **143**), the end wall **424** moves forwardly through the recess **472** (e.g., towards the head section **448** of the alignment member **458**), and during extension of the alignment bracket **406** (e.g., as the UAV **10** is disconnected from charging hub **143**), the end wall **424** moves rearwardly through the recess **472** (e.g., towards the leg **452**). The range of (maximum) relative motion between the alignment bracket **406** and the base **404** is thus equivalent to (defined by) the distance D between the end wall **424** of the base **404** and the head section **448** of the alignment member **458**.

(273) The leg **452** extends vertically upward from the body **450** of the alignment bracket **406** in parallel (or generally parallel) relation to the head section **448** and includes a boss (support) **474** and an anchor (foot) **476**. The boss **474** extends rearwardly from the leg **452** (e.g., away from the head section **448**) and is (vertically) aligned (or generally aligned) with the boss **422** so as to facilitate engagement of (contact between) the bosses **422**, **474** upon movement of the alignment member **458** into the deflected position (FIG. 71B), whereby the bosses **422**, **474** collectively define a hard stop **477** that prevents overtravel of the alignment bracket **406** and, thus, the charging member **410** and the electrical connector **414**. In certain embodiments of the disclosure, it is also envisioned that bosses **422**, **474** may be formed and accessed through the opening **438** in the base **404** (e.g., during injection molding) and that the bosses **422**, **474** may provide location features (reference points) to facilitate proper assembly of the charging hub **143**.

(274) As seen in FIG. 72, the anchor **476** is configured for insertion into a corresponding opening **478** in the charging member **410** (e.g., the PCB **412**). Positioning of the anchor **476** within the opening **478** further facilitates connection of the charging member **410** to the alignment bracket **406** and inhibits (if not entirely prevents) relative movement therebetween such that the charging member **410** moves concomitantly with the alignment bracket **406** during retraction and extension.

(275) In the particular embodiment illustrated in FIGS. 66-74, the charging hub **143** includes a single biasing member **408** that is configured as a coil spring **480**. It should be appreciated, however, that the particular number and/or configuration of the biasing member(s) **408** may be varied in alternate embodiments without departing from the scope of the present disclosure. For example, FIG. 75 illustrates an embodiment of the charging hub **143** that includes a pair of biasing members **408**.

(276) The biasing member **408** is located within the cavity **418** and is captured between the alignment bracket **406** and the base **404**. More specifically, the biasing member **408** includes a first (rear) end **482** that engages (contacts) the base **404** and a second (front) end **484** that engages (contacts) the alignment bracket **406**. More specifically, the first end **482** of the biasing member **408** is supported by (connected to) the boss **422** and the second end **484** of the biasing member **408** is supported by (connected to) the boss **474**, whereby the biasing member **408** is (vertically) offset from the alignment member(s) **458** along a (vertical) axis V that extends in orthogonal (or generally orthogonal) relation to the axis of movement M.

(277) The charging hub **143** (e.g., the base **404** and the alignment bracket **406**) is configured such that the biasing member **408** carries a preloaded force, whereby the biasing member **408** sits in compression between the alignment bracket **406** and the base **404** (e.g., between the bosses **422**, **474**). The preload carried by the biasing member **408** biases (urges) the alignment bracket **406** towards the normal position and increases alignment between the charging member **410** and the power source **14** of the UAV **10** to facilitate proper electrical connection thereof.

(278) The charging member **410** includes the PCB **412** and the electrical connector **414** mentioned above and is configured for electrical connection to the power source **14** of the UAV **10**. The electrical connector **414** is fixedly connected (e.g., soldered) to the PCB **412** so as to inhibit (if not entirely prevent) relative movement therebetween, whereby the electrical connector **414** moves concomitantly (simultaneously) with the PCB **412** and the alignment bracket **406** during repositioning of the alignment bracket **406** between the normal and deflected positions. To allow

for axial displacement (movement) of the PCB **412** and the electrical connector **414** during repositioning of the alignment bracket **406**, the charging hub **143** includes an opening **486** (FIGS. **67**, **70**, **71A**) defined in a rear end **488** thereof. The opening **486** is configured to receive the PCB **412** and the electrical connector **414** and allows the PCB **412** and the electrical connector **414** to exit and re-enter the charging hub **143** (e.g., the base **404**) during retraction and extension of the alignment bracket **406**. As seen in FIG. **71A**, for example, the PCB **412** and the electrical connector **414** are configured and positioned such that they are concealed by the charging hub **143** when the alignment bracket **406** is in the normal position.

(279) Together, the PCB **412** and the electrical connector **414** establish and control (regulate) electrical connection and communication between the charging hub **143** and the power source **14** of the UAV **10**. More specifically, the PCB **412** and the electrical connector **414** allow for the transmission of data between the UAV **10** and the base station **100** (via the charging hub **143**) including, for example, the temperature of the power source **14**, the voltage in each of the power cell(s) **20** (FIG. **5**), the occurrence of an undervoltage event, the number charge cycles, information pertaining to the general health and status of the power source **14**, etc.

(280) The electrical connector **414** is configured for insertion into an opening **490** on the power source **14** of the UAV **10** through the charging window **368** (FIGS. **66**, **67**, **71A**) defined in the rear end **106b** of the cradle **106**. The charging window **368** is configured to receive the charging member **410** such that the charging member **410** moves into and out of the cradle **106** during repositioning of the slide mechanism **150** and the cradle **106** between the extended and retracted positions. Upon insertion of the charging member **410** through the charging window **368**, the electrical connector **414** engages a corresponding (female) electrical connector **492** on the power source **14** so as to establish an electrical connection between the base station **100** (e.g., the charging hub **143**) and the UAV **10** that facilitates charging of the power source **14**.

(281) In certain embodiments of the disclosure, it is envisioned that the charging window **368** may be reconfigurable between an open position, in which the charging member **410** is receivable by the charging window **368**, and a closed position, in which the charging window **368** is concealed, so as to inhibit (if not entirely prevent) unintended contact between the UAV **10** and the cradle **106** (e.g., abutment of the charging member **410** with the walls defining the charging window **368**). For example, it is envisioned that the cradle **106** may include a movable door that is configured to expose the charging window **368** in the open position and conceal the charging window **368** in the closed position.

(282) The cap **416** defines a channel **494** (FIGS. **67**, **74**) that is configured to receive the charging member **410**, which allows for movement of the charging member **410** in relation to the cap **416** (and the base **404**), as described in further detail below. The cap is releasably connected to the base **404** by a plurality of mechanical fasteners **496** (e.g., screws, pins, bolts, clips, etc.) (FIGS. **68**, **74**, **75**). The cap **416** thus inhibits (if not entirely prevents) rotation (twisting) of the alignment bracket **406** and the charging member **410** in relation to the base **404** that may otherwise occur during insertion of the alignment member(s) **458** into the receptacle **464** (e.g., during repositioning the alignment bracket from the normal position into the deflected position) as a result of the vertical offset between the alignment member(s) **458** and the biasing member **408**.

(283) During connection of the UAV **10** to the charging hub **143**, it is envisioned that misalignment may occur between the charging member **410** and the power source **14** of the UAV **10**. For example, misalignment may occur as a result of variability in seating of the UAV **10** within the cradle **106**, exchange (replacement) of the power source **14**, which may result in seating of the UAV **10** in a different position within the cradle **106**, etc. Any such misalignment, however, is accommodated by axial, vertical, and horizontal tolerances (gapping), which allows for movement of the alignment bracket **406** and the charging member **410** in relation to the base **404** and the cap **416** in three degrees of freedom. More specifically, axial movement (floating, displacement) of the charging member **410** along the axis of movement **M** (FIG. **71A**) is tolerated via repositioning of

the alignment bracket **406** (and the charging member **410**) between the normal position (FIG. 71A) and the deflected position (FIG. 71B), which is facilitated by the cavity **418** in the base **404** and the axial separation between the end wall **424** and the head section **448** of the alignment bracket **406**. Additionally, the charging hub **143** is configured so as to define vertical gaps G1, G2 (FIG. 71A) between the base **404**, the charging member **410**, and the cap **416**, which allow for movement (floating, displacement) of the charging member **410** along the vertical axis V as well as (lateral) horizontal gaps G3, G4 (FIG. 67) between the charging member **410** and the cap **416**, which is facilitated by the relative dimensioning of the charging member **410** and the channel **494**. The gaps G3, G4 allow for movement (floating, displacement) of the charging member **410** within the channel **494** along a horizontal axis H, which extends in orthogonal (or generally orthogonal) relation to the axis of movement M and the vertical axis V (FIG. 71A).

(284) The axial, vertical, and horizontal tolerances described above not only facilitate more robust, consistent connection of the UAV **10** and the charging hub **143**, but protects the UAV **10**, the charging hub **143**, and the base station **100** during retraction of the cradle **106** and the UAV **10**. For example, in instances of gross misalignment (e.g., when connection of the charging member **410** to the power source **14** is physically impossible), retraction of the alignment bracket **406** and the charging member **410** inhibits (if not entirely prevents) damage to the UAV **10**, the charging member **410**, etc. (e.g., puncturing of the UAV **10**, unseating of the UAV **10** from the cradle **106**, etc.).

(285) With continued reference to FIGS. 66-74, a method of using the base station **100** to charge the UAV **10** (e.g., the power source **14**) will be discussed. Initially, the UAV **10** is docked within the cradle **106**, during which, the power source **14** is guided into the chamber **142** (FIG. 67) by the sidewalls **146** and the angled guide surface **148**. After docking with the cradle **106**, the cradle **106** is retracted into the enclosure **102** via repositioning of the slide mechanism **150** from the extended position into the retracted position, during which, the charging hub **143** is inserted into the cradle **106**. More specifically, as the slide mechanism **150** (and the cradle **106**) moves into the retracted position, the alignment bracket **406** is inserted into the receptacle **464** defined by the power source **14** of the UAV **10**, as seen in FIG. 71A, which facilitates proper positioning of the charging member **410** and alignment of the electrical connector **414** with the opening **490** on the power source **14**. Continued retraction of the cradle **106** causes insertion of the charging member **410** into the power source **14** (via the opening **490**) and, thus, engagement (contact) between the electrical connectors **414**, **492** so as to establish an electrical connection between the power source **14** and the charging hub **143**.

(286) During retraction of the cradle **106**, biasing of the alignment bracket **406** towards the normal position (FIG. 71A) supports a proper electrical interface between the electrical connectors **414**, **492**. Additionally, the axial tolerance created by the configuration of the base **404** and the alignment bracket **406** and the inclusion of the biasing member **408** allows for repositioning of the alignment bracket **406** between the normal position (FIG. 71A) and the deflected position (FIG. 71B) as necessary so as to accommodate misalignment between the UAV **10** and the charging hub **143**, during which, the biasing member **408** is compressed, which increases the preloaded force carried by the biasing member **408**.

(287) Serviceability of Electronic Modules

(288) With reference now to FIGS. 76-88, the base station **100** includes a plurality of electronic modules that are configured to control certain functional aspects of the base station **100**. More specifically, in the particular embodiment of the disclosure illustrated, the base station **100** includes a (first) electronics module **500**; a (second) electronics module **502**; and a third electronics module **504**. As described in further detail below, each of the electronics modules **500**, **502**, **504** is specifically configured and positioned for individual connection to and disconnection from the base station **100**, which allows each of the electronics modules **500**, **502**, **504** to be removed separately (e.g., for repair, service, replacement, etc.), thereby reducing downtime of the base station **100**.

(289) The electronics module **500** is supported by the enclosure **102** and is housed behind (inwardly of) a rear door **115** of the base station **100**, which represents an alternate embodiment of the aforementioned access panel **114** (FIG. 7) and is hingedly connected to the rear end **102b** of the enclosure **102** such that the rear door **115** is repositionable between a closed position (FIG. 76) and an open position (FIG. 83). More specifically, the electronics module **500** is removably connected to a rear frame **506** of the outer housing **110** and is positioned adjacent to the (rear) door **115** within an access window **508** defined by the rear frame **506**. In the particular embodiment illustrated, the electronics module **500** is secured (connected) to the rear frame **506** by a plurality of mechanical fasteners **510** (FIG. 78) (e.g., screws, pins, bolts, clips, etc.) and is positioned in a (rear) upper corner section **512** of the base station **100** (e.g., to increase ease of access to the electronics module **500** during connection and disconnection). It should be appreciated, however, that the particular location of the electronics module **500** may be altered in various embodiments without departing from the scope of the present disclosure, so long as access to the electronics module **500** in the manner described herein is maintained. For example, embodiments are envisioned in which the electronics module **500** may be connected to the rear frame **506** in a lower corner section **514** of the base station **100**. With reference to FIG. 78 in particular, the electronics module **500** includes: a main (first) heat sink **516**; an auxiliary (second, supplemental, ancillary) heat sink **518**; a logic board **520**; a (first) PCBA **522**; an interface member **524**; and an SD card **526**, as described in detail below.

(290) The main heat sink **516** includes (e.g., is formed partially or entirely from) a thermally conductive material (e.g., aluminum) and facilitates the distribution of thermal energy, either away from the electronics module **500** (e.g., in hot environments and/or conditions) or towards the electronics module **500** (e.g., in cold environments and/or conditions). The main heat sink **516** includes a body **528** with a block-style configuration, which provides structural integrity to the electronics module **500** to increase the stability (e.g., rigidity) thereof. The main heat sink **516** thus acts as (and provides) a (first) housing component **530** of the electronics module **500**.

(291) The body **528** of the main heat sink **516** defines a cavity (pocket) **532** that includes one or more recesses **534** and one or more standoffs (bosses) **536**. The cavity **532** is configured to receive (accommodate, house) the logic board **520** such that the logic board **520** is positioned in engagement (contact) with the standoff(s) **536**.

(292) The auxiliary heat sink **518** is connected to the main heat sink **516** and acts as (and provides) a (second) housing component **538** of the electronics module **500** that supplements the distribution of thermal energy performed by the main heat sink **516**. More specifically, in the particular embodiment illustrated, the heat sinks **516**, **518** are connected by a plurality of mechanical fasteners **540** (e.g., screws, pins, bolts, clips, etc.), which allows for assembly and disassembly of the electronics module **500** during repair, service, replacement, etc. As seen in FIG. 77, upon connection of the heat sinks **516**, **518**, the main heat sink **516** defines a plurality of side walls **542** that collectively describe a perimeter **544** of the electronics module **500** and the auxiliary heat sink **518** defines a (first, front) end wall **546** of the electronics module **500**.

(293) Like the main heat sink **516**, the auxiliary heat sink **518** includes (e.g., is formed partially or entirely from) a thermally conductive material (e.g., aluminum) and facilitates the distribution of thermal energy, either away from the electronics module **500** (e.g., in hot environments and/or conditions) or towards the electronics module **500** (e.g., in cold environments and/or conditions). While the heat sinks **516**, **518** are illustrated as including identical materials of construction in the particular embodiment shown, the present disclosure also envisions embodiments in which the heat sinks **516**, **518** may include different materials of construction. For example, it is envisioned that the main heat sink **516** may include (e.g., may be formed partially or entirely from) a first material with a first thermal conductivity and that the auxiliary heat sink **518** may include (e.g., may be formed partially or entirely from) a second, different material with a second, different thermal conductivity, which may be greater than or less than the first thermal conductivity.

(294) To increase the available surface area and, thus, the ability of the auxiliary heat sink **518** to distribute thermal energy, in certain embodiments, such as that which is illustrated, the auxiliary heat sink **518** includes one or more diffusers **548**, which may be configured in any manner suitable for that intended purpose. For example, in the particular embodiment illustrated, the diffusers **548** are configured as fins **550** that define a plurality of channels **552** therebetween, which collectively direct air flow along the auxiliary heat sink **518** to further increase the distribution of thermal energy. It should be appreciated, however, is envisioned that the diffuser(s) **548** may include any suitable configuration (e.g., pins, protrusions, ribs, or other such surface irregularities) without departing from the scope of the present disclosure.

(295) The logic board **520** supports operation and certain functional aspects of the base station **100** including, for example, temperature control of the power source **14**, powering of the heating elements(s) **244a**, powering of the light source(s) **173**, **182**, opening and closure of the (front) door **104**, extension and retraction of the slide mechanism **150** and the cradle **106**, communication between the base station **100**, the UAV **10**, and/or an external network, etc. As indicated above, the logic board **520** is supported by the main heat sink **516** (e.g., within the cavity **532**), whereby the logic board **520** is located between, and is protected by, the heat sinks **516**, **518**. In certain embodiments of the disclosure, it is envisioned that the cavity **532** (e.g., the recess(es) **534**) may include a thermal interface material (e.g., to augment the distribution of thermal energy from the logic board **520** to the main heat sink **516**).

(296) The (first) PCBA **522** is supported by (connected to) the main heat sink **516** so as to define a (second, rear) end wall **553** of the electronics module **500**. The PCBA **522** is configured to further support operation and certain functional aspects of the base station **100** including, for example, temperature control of the power source **14**, powering of the heating elements(s) **244a**, powering of the light source(s) **173**, **182**, opening and closure of the (front) door **104**, extension and retraction of the slide mechanism **150** and the cradle **106**, etc. To support such operation and functionality, the PCBA **522** includes a processor **554** that is configured to facilitate data processing and control of the base station **100**.

(297) In certain embodiments, it is envisioned that the PCBA **522** may also be connected to one or more of the antennas on the base station **100** (e.g., the antenna(s) **166**) via one or more antenna ports **556** (FIG. **78**). It is envisioned that connection of the PCBA **522** to the antenna(s) **166** may allow for communication over WiFi, LTE, over various frequencies, etc. Although shown as including two antenna ports **556** in the particular embodiment illustrated, it should be appreciated that the particular number of antenna ports **556** may be varied without departing from the scope of the present disclosure.

(298) The interface member **524** physically, thermally, and electrically connects the PCBA **522** and the heat sink **516** and is located therebetween. As seen in FIG. **78**, the interface member includes at least one thermally conductive section **558** and at least one electrically conductive section **560**. The thermally conductive section(s) **558** include a thermal interface material **562** and physically and thermally connects the PCBA **522** to the main heat sink **516** to facilitate the transfer of thermal energy therebetween. The electrically conductive section(s) **560** include an electrically conductive pressure-sensitive adhesive **564** (e.g., to facilitate connection of the PCBA **522** to the main heat sink **516**) and are configured to electrically ground the various components of the PCBA **522** so as to facilitate and increase shielding from electromagnetic interference (EMI) and/or radiofrequency interference (RFI).

(299) The SD card **526** is configured to further support operation and certain functional aspects of the base station **100** by facilitating high-capacity memory and the reading and writing of a data to support processing (e.g., by the PCBA **522**). Although illustrated as being supported by (connected to) the logic board **520** in the particular embodiment illustrated, it should be appreciated that the particular location of the SD card **526** may be varied in alternate embodiments without departing from the scope of the present disclosure. For example, embodiments in which the SD card **526** may

be supported by (connected to) the PCBA 522 are also envisioned herein.

(300) With reference now to FIGS. 79 and 82, in certain embodiments, the base station 100 may further include an air circulation module 566 to further facilitate the transfer of thermal energy away from, and thereby cool, the electronics module 500. As seen in FIG. 79, the air circulation module 566 is positioned about the electronics module 500 and includes ducting 568, which is configured to direct air flow across the electronics module 500, and a (first) fan 570, which is supported by (connected to) the ducting 568 and is configured to draw air therethrough.

(301) The air circulation module 566 is removably supported by the enclosure 102 adjacent to the (rear) door 115. More specifically, the air circulation module 566 is connected to the rear frame 506 by a plurality of mechanical fasteners 572 (FIG. 82) (e.g., screws, pins, bolts, clips, etc.), which allows for removal of the electronics module 500 and the air circulation module 566 from the base station 100 independently of (separately from) each other to facilitate repair, service, replacement, etc., thereby further reducing downtime of the base station 100. Whereas the electronics module 500 is supported by (connected to) an outer (rear) surface 574 of the rear frame 506, the air circulation module 566 is supported by (connected to) an inner (front) surface 576 of the rear frame 506, whereby the rear frame 506 is located between the electronics module 500 and the air circulation module 566.

(302) As seen in FIG. 79, the ducting 568 is configured to cover (overlie) the electronics module 500 and is configured in correspondence with the auxiliary heat sink 518. More specifically, the ducting 568 defines a chamber 578 with an inner contour 580 that mirrors (e.g., substantially matches) an outer contour 582 defined by the diffuser(s) 548. The corresponding configurations of the ducting 568 and the diffuser(s) 548 not only facilitates reception of the diffuser(s) 548 by the chamber 578, but proper mating of the ducting 568 and the auxiliary heat sink 518 as well as proper relative orientation of the air circulation module 566 and the electronics module 500.

(303) As indicated above, the electronics module 500 is positioned behind the (rear) door 115 within the access window 508 defined by the rear frame 506 (e.g., such that the door 115 is positioned adjacent (or generally adjacent) to the electronics module 500). The door 115 acts not only to protect the electronics module 500, but reduce (if not entirely eliminate) emissions from the base station 100. More specifically, together with the enclosure 102, the door 115 defines a Faraday cage for the electronics module 500 that reduces (if not entirely eliminates) EMI and/or RFI. The door 115 also conceals and protects an air filter housing 584 (FIG. 80) for one or more of the internal fans (e.g., the fan 248 (FIG. 64)) located within the base station 100.

(304) With reference to FIGS. 83 and 84, the door 115 includes: a (non-metallic) frame 586; a (metallic) panel 588 that is supported by (connected to) the frame 586; a sealing member 590 that extends about the panel 588 and which is configured for engagement (contact) with the enclosure 102 (e.g., the rear frame 506) to inhibit (if not entirely prevent) the entry of dust, debris, moisture, water, etc., into the base station 100; a plurality of hinges 592, which pivotably connect the door 115 to the rear frame 506; and a locking mechanism 594, which inhibits theft and/or unauthorized access to the internal components of the base station 100 through the door 115. The multi-material construction of the door 115 (e.g., the use of both metallic and non-metallic materials) not only reduces the overall weight of the door 115 and, thus, the base station 100, but the overall cost of the base station 100.

(305) The panel 588 is fixedly connected to the frame 586 by a plurality of mechanical fasteners 596 (e.g., screws, pins, bolts, clips, etc.) such that the panel 588 is positioned in correspondence with the electronics assembly 500 and covers (overlies) the electronics assembly 500 upon closure of the door 115. The metallic construction of the panel 588 results in the creation of an enclosed, metallic environment for the electronics assembly 500 when the door 115 is closed and establishment of the aforementioned Faraday cage upon grounding of the enclosure 102 (e.g., the rear frame 506).

(306) While the frame 586 and the panel 588 are respectively illustrated as including (e.g., as being

formed partially or entirely from) plastic and sheet metal in the particular embodiment shown in the figures, it should be appreciated that the particular material(s) used in construction of the frame **586** and the panel **588** may be varied without departing from the scope of the present disclosure.

(307) With reference now to FIGS. **85-87**, the (second) electronics module **502** will be discussed. The electronics module **502** is configured to facilitate and control operation of the actuator(s) **118** and, thus, opening and closure of the (front) door **104**. The electronics module **502** is removably connected to a roof section **598** of the inner housing **108** and includes: an access panel **600**, which is removably supported by (connected to) the roof section **598**; a (second) PCBA **602**; and a (second) fan **604**, each of which is secured (connected) to the access panel **600**.

(308) As seen in FIG. **87**, the access panel **600** is removably connected to an inner surface **606** of the roof section **598** via a plurality of mechanical fasteners **608**, whereby the electronics module **502** can be accessed and/or removed from within the enclosure **102**. Alternatively, the electronics module **502** (e.g., the PCBA **602** or the fan **604**) can be accessed (e.g., serviced) externally upon removal of the outer housing **110** (FIG. **1**). In the particular embodiment illustrated, the mechanical fasteners **608** are configured as thumb screws **610**, which allow for toolless (e.g., manual) connection and disconnection of the access panel **600**.

(309) With reference now to FIG. **88**, the (third) electronics module **504** will be discussed. The electronics module **504** is supported by (connected to) the slide mechanism **150** and is configured to facilitate and control the operation thereof and, thus, repositioning of the cradle **106** between the retracted and extended positions. More specifically, the electronics module **504** includes a (third) PCBA **612** that is removably connected to the stationary slide member **151b** via a plurality of mechanical fasteners **614**, which allows the electronics module **504** to be accessed and removed from within the internal cavity **112** of the enclosure **102** (via the front end **102a**) upon opening of the door **104** and removal of the UAV **10**.

(310) While the present disclosure has been described in connection with certain embodiments, it is to be understood that the present disclosure is not to be limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the scope of the appended claims, which scope is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures as is permitted under the law.

(311) Persons skilled in the art will understand that the various embodiments of the present disclosure and shown in the accompanying figures constitute non-limiting examples, and that additional components and features may be added to any of the embodiments discussed hereinabove without departing from the scope of the present disclosure. Additionally, persons skilled in the art will understand that the elements and features shown or described in connection with one embodiment may be combined with those of another embodiment without departing from the scope of the present disclosure to achieve any desired result and will appreciate further features and advantages of the presently disclosed subject matter based on the description provided.

Variations, combinations, and/or modifications to any of the embodiments and/or features of the embodiments described herein that are within the abilities of a person having ordinary skill in the art are also within the scope of the present disclosure, as are alternative embodiments that may result from combining, integrating, and/or omitting features from any of the disclosed embodiments.

(312) Use of the term “optionally” with respect to any element of a claim means that the element may be included or omitted, with both alternatives being within the scope of the claim.

Additionally, use of broader terms such as “comprises,” “includes,” and “having” should be understood to provide support for narrower terms such as “consisting of,” “consisting essentially of,” and “comprised substantially of.” Accordingly, the scope of protection is not limited by the description set out above, but is defined by the claims that follow, and includes all equivalents of the subject matter of the claims.

(313) In the preceding description, reference may be made to the spatial relationship between the

various structures illustrated in the accompanying drawings, and to the spatial orientation of the structures. However, as will be recognized by those skilled in the art after a complete reading of this disclosure, the structures described herein may be positioned and oriented in any manner suitable for their intended purpose. Thus, the use of terms such as “above,” “below,” “upper,” “lower,” “inner,” “outer,” “left,” “right,” “upward,” “downward,” “inward,” “outward,” “horizontal,” “vertical,” etc., should be understood to describe a relative relationship between the structures and/or a spatial orientation of the structures. Those skilled in the art will also recognize that the use of such terms may be provided in the context of the illustrations provided by the corresponding figure(s).

(314) Additionally, terms such as “approximately,” “generally,” “substantially,” and the like should be understood to allow for variations in any numerical range or concept with which they are associated and encompass variations on the order of 25% (e.g., to allow for manufacturing tolerances and/or deviations in design). For example, the term “generally parallel” should be understood as referring to configurations in which the pertinent components are oriented so as to define an angle therebetween that is equal to $180^{\circ} \pm 25\%$ (e.g., an angle that lies within the range of (approximately) 135° to (approximately) 225°). The term “generally parallel” should thus be understood as referring to encompass configurations in which the pertinent components are arranged in parallel relation.

(315) Although terms such as “first,” “second,” “third,” etc., may be used herein to describe various operations, elements, components, regions, and/or sections, these operations, elements, components, regions, and/or sections should not be limited by the use of these terms in that these terms are used to distinguish one operation, element, component, region, or section from another. Thus, unless expressly stated otherwise, a first operation, element, component, region, or section could be termed a second operation, element, component, region, or section without departing from the scope of the present disclosure.

(316) Each and every claim is incorporated as further disclosure into the specification and represents embodiments of the present disclosure. Also, the phrases “at least one of A, B, and C” and “A and/or B and/or C” should each be interpreted to include only A, only B, only C, or any combination of A, B, and C.

Claims

1. A base station for an unmanned aerial vehicle (UAV), the base station comprising: an enclosure configured to receive the UAV, wherein the enclosure includes: a front end having a front door and a rear end having a rear door; an inner housing; and an outer housing receiving the inner housing, wherein the inner housing and the outer housing are configured as discrete components to facilitate assembly and disassembly of the base station; a slide mechanism connected to the enclosure, wherein the slide mechanism includes: a stationary slide member supported by the enclosure; and a movable slide member slidably supported by the stationary slide member; a cradle configured for docking with the UAV and connected to the slide mechanism such that the UAV is movable into and out of the enclosure during repositioning of the cradle between a retracted position and an extended position; a first electronics module removably connected to the outer housing adjacent to the rear door; a second electronics module removably connected to a roof section of the inner housing such that the second electronics module is positioned between the inner housing and the outer housing; and a third electronics module including a first printed circuit board assembly (PCBA) removably and directly connected to the stationary slide member, whereby the first electronics module, the second electronics module, and the third electronics module are individually removable from the base station.

2. The base station of claim 1, wherein the first electronics module is configured to facilitate data processing and control of the base station.

3. The base station of claim 2, wherein the second electronics module is configured to facilitate opening and closure of the front door.
4. The base station of claim 3, wherein the third electronics module is configured to facilitate and control repositioning of the cradle between the retracted position and the extended position.
5. The base station of claim 1, wherein the first electronics module includes: a main heat sink; and an auxiliary heat sink connected to the main heat sink such that the main heat sink defines a plurality of side walls collectively describing a perimeter of the first electronics module and the auxiliary heat sink defines an end wall of the first electronics module.
6. The base station of claim 5, wherein the auxiliary heat sink includes one or more diffusers configured to increase thermal energy distribution.
7. The base station of claim 5, wherein the first electronics module further includes: a logic board supported by the main heat sink such that the logic board is located between the main heat sink and the auxiliary heat sink; a second PCBA supported by the main heat sink; and an interface member located between the main heat sink and the second PCBA.
8. The base station of claim 7, wherein the main heat sink defines a cavity configured to receive the logic board.
9. The base station of claim 7, wherein the interface member includes: at least one thermally conductive section configured to facilitate thermal energy transfer between the second PCBA and the main heat sink; and at least one electrically conductive section configured to electrically ground the second PCBA.
10. The base station of claim 9, wherein the at least one electrically conductive section includes an adhesive to connect the second PCBA to the main heat sink.
11. A base station for an unmanned aerial vehicle (UAV), the base station comprising: an enclosure including: a front end configured to receive the UAV; a rear end opposite the front end; an inner housing; and an outer housing receiving the inner housing, wherein the inner housing and the outer housing are configured as discrete components to facilitate assembly and disassembly of the base station; a cradle configured for docking with the UAV and movable in relation to the enclosure via a slide mechanism; a first electronics module removably connected to the outer housing at the rear end of the enclosure, wherein the first electronics module is positioned within a window defined by the outer housing to facilitate access thereto and is configured to facilitate data processing and control of the base station, wherein the first electronics module includes: a main heat sink providing a first housing component; an auxiliary heat sink directly connected to the main heat sink and providing a second housing component; and a printed circuit board assembly (PCBA) supported by the main heat sink such that the PCBA is positioned between the main heat sink and the auxiliary heat sink; and an air circulation module connected to the rear end of the enclosure and positioned about the first electronics module to facilitate cooling thereof, wherein the air circulation module includes: ducting configured to direct air across the first electronics module, wherein the ducting defines a chamber with an inner contour mirroring an outer contour defined by the auxiliary heat sink such that the auxiliary heat sink is positioned within the chamber; and a fan connected to the ducting and configured to draw air therethrough.
12. The base station of claim 11, further comprising: a second electronics module removably connected to a roof section of the inner housing and configured to facilitate opening and closure of the enclosure; and a third electronics module removably connected to the slide mechanism and configured to facilitate repositioning of the cradle, wherein the first electronics module, the second electronics module, and the third electronics module are individually removable from the base station.
13. The base station of claim 11, wherein the enclosure includes a frame defining an outer surface and an inner surface, the first electronics module being connected to the outer surface of the frame and the air circulation module being connected to the inner surface of the frame such that the frame is located between the first electronics module and the air circulation module, whereby the first

electronics module and the air circulation module are separately removable from the base station.

14. The base station of claim 11, wherein the first electronics module and the air circulation module are configured such that the main heat sink is exposed from the ducting.

15. A base station for an unmanned aerial vehicle (UAV), the base station comprising: a metallic enclosure configured to receive the UAV, the metallic enclosure including: a front end having a front door; a rear end having a rear door; an inner housing; and an outer housing receiving the inner housing, wherein the inner housing and the outer housing are configured as discrete components to facilitate assembly and disassembly of the base station; at least one actuator extending between the metallic enclosure and the front door, wherein the at least one actuator includes: a motor assembly; and a linkage assembly extending between the motor assembly and the front door; a cradle movable in relation to the metallic enclosure and configured for docking with the UAV; and a first electronics module removably connected to the outer housing adjacent to the rear door, a second electronics module controlling operation of the at least one actuator and removably connected to a roof section of the inner housing, and a third electronics module, wherein the first electronics module, the second electronics module, and the third electronics module are each configured for individual removal from the metallic enclosure, the rear door being located adjacent to the first electronics module and including a metallic panel positioned in correspondence with the first electronics module so as to create a Faraday cage for the first electronics module and thereby reduce electromagnetic emissions from the base station.

16. The base station of claim 15, wherein the rear door further includes a non-metallic frame, the metallic panel being connected to the non-metallic frame.

17. The base station of claim 15, wherein the second electronics module includes an access panel removably connected to the roof section of the inner housing.

18. The base station of claim 17, wherein the access panel is removably connected to an inner surface of the roof section via a plurality of mechanical fasteners such that the second electronics module is accessible from within the metallic enclosure, the mechanical fasteners being configured to allow for toolless connection of the access panel to the roof section and toolless disconnection of the access panel from the roof section.

19. The base station of claim 17, wherein the base station further includes: a slide mechanism connected to the metallic enclosure and repositionable between a retracted position and an extended position; and a cradle connected to the slide mechanism and configured for docking with the UAV such that the UAV is movable into and out of the metallic enclosure during repositioning of the slide mechanism between the retracted position and the extended position, the third electronics module being removably connected to the slide mechanism such that the third electronics module is accessible from within the metallic enclosure upon removal of the UAV.

20. The base station of claim 15, wherein the second electronics module and the at least one actuator are configured as discrete components of the base station.
