

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280879

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Alston; William W. et al.

Vaporizer Device With More Than One Heating Element

Abstract

Various embodiments of a vaporization device are described that include one or more features, such as for generating a combined inhalable aerosol. In some embodiments, the vaporization device can include one or more heaters that are configured to heat one or more vaporizable materials. Various embodiments of heating elements and heating systems for use in vaporization devices are also described.

Inventors: Alston; William W. (Lincoln, CA), Bowen; Adam (San Mateo, CA), Davis; Jacob R. (San Francisco, CA), Garcia-Doty; Ian (Oakland, CA), Ingebrethsen; Bradley J. (Saugerties, NY), Kurzman; Joshua A. (San Francisco, CA), Monsees; James (San Francisco, CA), Pappas; Andrew J. (San Francisco, CA), Vieira; Paul R. (Oakland, CA), Watson; Timothy J. (San Francisco, CA), Wilinski, JR.; Joseph S. (San Francisco, CA)

Applicant: JUUL Labs, Inc. (Washington, DC)

Family ID: 70550354

Appl. No.: 19/058921

Filed: February 20, 2025

Related U.S. Application Data

parent US continuation 17736707 20220504 parent-grant-document US 12232530 child US 19058921

parent US division 16679057 20191108 parent-grant-document US 11350664 child US 17736707

us-provisional-application US 62757689 20181108

us-provisional-application US 62791709 20190111

us-provisional-application US 62816452 20190311

us-provisional-application US 62821305 20190320

Publication Classification

Int. Cl.: **A24F40/46** (20200101); **A24F40/10** (20200101); **A24F40/30** (20200101); **A24F40/42** (20200101)

U.S. Cl.:

CPC **A24F40/46** (20200101); **A24F40/10** (20200101); **A24F40/42** (20200101); A24F40/30 (20200101)

Background/Summary

CROSS REFERENCE [0001] The present application claims priority to U.S. Provisional Patent Application No. 62/757,689 entitled “Vaporizer Device With More Than One Heating Element” filed Nov. 8, 2018, U.S. Provisional Patent Application No. 62/821,305 entitled “Vaporizer Device With More Than One Heating Element” filed Mar. 20, 2019, U.S. Provisional Patent Application No. 62/930,542 entitled “Vaporizer Device With More Than One Heating Element” filed Nov. 4, 2019, U.S. Provisional Patent Application No. 62/791,709 entitled “Vaporizer Including Positive Temperature Coefficient of Resistivity Heater” filed Jan. 11, 2019, U.S. Provisional Patent Application No. 62/816,452 entitled “Vaporizer Including Positive Temperature Coefficient of Resistivity Heater” filed Mar. 11, 2019, and U.S. Provisional Patent Application No. 62/898,522 entitled “Vaporizer Including Positive Temperature Coefficient of Resistivity Heater” filed Sep. 10, 2019, which are hereby incorporated by reference in their entirety.

TECHNICAL FIELD

[0002] The subject matter described herein relates to vaporizer devices configured to heat vaporizable material.

BACKGROUND

[0003] Vaporizer devices, which can also be referred to as vaporizers, electronic vaporizer devices, or e-vaporizer devices, can be used for delivery of an aerosol (for example, a vapor-phase and/or condensed-phase material suspended in a stationary or moving mass of air or some other gas carrier) containing one or more active ingredients by inhalation of the aerosol by a user of the vaporizing device. For example, electronic nicotine delivery systems (ENDS) include a class of vaporizer devices that are battery powered and that can be used to simulate the experience of smoking, but without burning of tobacco or other substances. Vaporizers are gaining increasing popularity both for prescriptive medical use, in delivering medicaments, and for consumption of tobacco, nicotine, and other plant-based materials. Vaporizer devices can be portable, self-contained, and/or convenient for use.

[0004] In use of a vaporizer device, the user inhales an aerosol, colloquially referred to as “vapor,” which can be generated by a heating element that vaporizes (e.g., causes a liquid or solid to at least partially transition to the gas phase) a vaporizable material, which can be liquid, a solution, a solid, a paste, a wax, and/or any other form compatible for use with a specific vaporizer device. The vaporizable material used with a vaporizer can be provided within a cartridge for example, a separable part of the vaporizer device that contains vaporizable material) that includes an outlet (for example, a mouthpiece) for inhalation of the aerosol by a user.

[0005] To receive the inhalable aerosol generated by a vaporizer device, a user may, in certain

examples, activate the vaporizer device by taking a puff, by pressing a button, and/or by some other approach. A puff as used herein can refer to inhalation by the user in a manner that causes a volume of air to be drawn into the vaporizer device such that the inhalable aerosol is generated by a combination of the vaporized vaporizable material with the volume of air.

[0006] An approach by which a vaporizer device generates an inhalable aerosol from a vaporizable material involves heating the vaporizable material in a vaporization chamber (e.g., a heater chamber) to cause the vaporizable material to be converted to the gas (or vapor) phase. A vaporization chamber can refer to an area or volume in the vaporizer device within which a heat source (for example, a conductive, convective, and/or radiative heat source) causes heating of a vaporizable material to produce a mixture of air and vaporized material to form a vapor for inhalation of the vaporizable material by a user of the vaporization device.

[0007] In some implementations, a liquid vaporizable material can be drawn out of a reservoir and into the vaporization chamber via a wicking element (e.g., a wick). Drawing of the liquid vaporizable material into the vaporization chamber can be at least partially due to capillary action provided by the wicking element as the wicking element pulls the liquid vaporizable material along the wick in the direction of the vaporization chamber.

[0008] Vaporizer devices can be controlled by one or more controllers, electronic circuits (for example, sensors, heating elements), and/or the like on the vaporizer. Vaporizer devices can also wirelessly communicate with an external controller for example, a computing device such as a smartphone).

SUMMARY

[0009] In certain aspects of the current subject matter, challenges associated with efficiently and effectively heating one or more types of vaporizable material can be addressed by inclusion of one or more of the features described herein or comparable/equivalent approaches as would be understood by one of ordinary skill in the art. Aspects of the current subject matter relate to embodiments of vaporizer devices including various heating elements and heating systems for heating one or more types of vaporizable material. In one aspect consistent with the current disclosure, a vaporizer device for generating a combined inhalable aerosol may include a body including an airflow pathway extending therethrough. The vaporizer device may include a first cartridge receptacle configured to receive a first cartridge. The first cartridge may be configured to contain a first vaporizable material. The vaporizer device may include a second cartridge receptacle configured to receive a second cartridge. The second cartridge may be configured to contain a second vaporizable material. The vaporizer device may include a first heater in communication with the first cartridge receptacle for heating the first vaporizable material and forming a first inhalable aerosol. The vaporizer device may include a second heater in communication with the second cartridge receptacle for heating the second vaporizable material and forming a second inhalable aerosol. The airflow pathway may extend adjacent the first heater and the second heater and may be configured to allow the first inhalable aerosol and the second inhalable aerosol to combine to form the combined inhalable aerosol for inhalation by a user from an end of the airflow pathway.

[0010] The vaporizer device may include a third heater positioned adjacent the airflow pathway at a position upstream from at least one of the first heater and the second heater. The first vaporizable material may be a liquid. The second vaporizable material may be a non-liquid. The first vaporizable material and the second vaporizable material may be a liquid. The first vaporizable material and the second vaporizable material may be a non-liquid. The first vaporizable material may be a first liquid and the second vaporizable material may be a second liquid that is different from the first liquid. The first vaporizable material may be a first non-liquid and the second vaporizable material may be a second non-liquid, which is different from the first non-liquid. The first heater and/or the second heater may include a nonlinear positive temperature coefficient of resistance material.

[0011] In an interrelated aspect, a method of a vaporizer device for generating a combined inhalable aerosol may include heating a first vaporizable material and forming a first inhalable aerosol. The heating may be performed by a first heater of the vaporizer device. The vaporizer device may include a body including an airflow pathway extending therethrough. The vaporizer device may include a first cartridge receptacle configured to receive a first cartridge. The first cartridge may be configured to contain the first vaporizable material. The first heater may be in communication with the first cartridge receptacle for heating the first vaporizable material. The vaporizer device may include a second cartridge receptacle configured to receive a second cartridge. The second cartridge may be configured to contain a second vaporizable material. The vaporizer device may include a second heater in communication with the second cartridge receptacle for heating the second vaporizable material and forming a second inhalable aerosol. The airflow pathway may extend adjacent the first heater and the second heater and may be configured to allow the first inhalable aerosol and the second inhalable aerosol to combine to form the combined inhalable aerosol for inhalation by a user from an end of the airflow pathway. The method may include heating the second vaporizable material and forming the second inhalable aerosol. The method may include combining the first inhalable aerosol with the second inhalable aerosol to form the combined inhalable aerosol for inhalation by the user.

[0012] In an interrelated aspect, a vaporizer device may include a housing including an air inlet. The vaporizer device may include a heating element within the housing and arranged to receive airflow from the air inlet. The heating element may include a nonlinear positive temperature coefficient of resistance material. The vaporizer device may include a heat exchanger thermally coupled to the heating element and may be configured to transfer heat between the heating element and the airflow to heat air in the airflow. The vaporizer device may be capable of providing the heated air to a vaporizable material for vaporization of the vaporizable material.

[0013] The heat exchanger may include a first heat exchanger thermally coupled to a first side of the heating element. The heat exchanger may include a second heat exchanger thermally coupled to a second side of the heating element. The heat exchanger may include a plurality of fin features. The vaporizer device may include a flow diverter located in a path of the airflow and may be configured to divert a portion of the airflow through the heat exchanger. The housing may include a cover containing the heat exchanger. The vaporizer device may include a power source configured to provide electrical energy to heat the heating element. The vaporizer device may include a cartridge located downstream of the heating element and oriented to receive the heated air, wherein downstream may be with respect to the airflow. The vaporizer device may include a cartridge configured to contain the vaporizable material. The housing may include a connector configured to couple the housing to the cartridge. The cartridge may include a solid vaporizable material. The cartridge may include a reservoir, liquid vaporizable material within the reservoir, and a wick in fluidic communication with the liquid vaporizable material. The cartridge may be configured to receive the heated air and direct the heated air over the wick. The cartridge may include a mouthpiece, and the wick may be located in a path of the airflow between the heating element and the mouthpiece. The cartridge may include a second air inlet configured to draw a second airflow into the cartridge for mixing with the heated air and within a reservoir located in a path of the airflow downstream from the heat exchanger and the vaporizable material. The cartridge may include a reservoir. The cartridge may include a liquid vaporizable material within the reservoir. The cartridge may include a wick in fluidic communication with the liquid vaporizable material. The wick may be arranged to receive the heated air from the heat exchanger to produce vaporized vaporizable material in the form of an inhalable aerosol. The cartridge may include a solid vaporizable material arranged to receive the vaporized vaporizable material from the wick. The cartridge may include a mouthpiece configured to receive the vaporized vaporizable material after the vaporized vaporizable material passes through the solid vaporizable material.

[0014] The vaporizer device may include a first cartridge including a reservoir, liquid vaporizable

material within the reservoir, and a wick in fluidic communication with the liquid vaporizable material. The wick may be arranged to receive the heated air from the heat exchanger to produce vaporized vaporizable material in the form of an inhalable aerosol. The vaporizer device may include a second cartridge including a solid vaporizable material and a mouthpiece. The solid vaporizable material arranged to receive the vaporized vaporizable material from the wick. The mouthpiece may be configured to receive the vaporized vaporizable material after the vaporized vaporizable material passes through the solid vaporizable material. The first cartridge may be removably coupled to the housing. The second cartridge may be removably coupled to the housing and/or the first cartridge.

[0015] The first cartridge and the second cartridge may be disposable cartridges. The second cartridge includes a second air inlet for mixing ambient temperature air with the vaporized vaporizable material after the vaporized vaporizable material passes through the solid vaporizable material. The vaporizer device may include a fibrous body arranged to receive and cool the vaporized vaporizable material after the vaporized vaporizable material passes through the solid vaporizable material. The nonlinear positive temperature coefficient of resistance material may include an electrical resistivity transition zone characterized by an increase in electrical resistivity over a temperature range such that, when the heating element is heated to a first temperature within the electrical resistivity transition zone, current flow from a power source is reduced to a level that limits further temperature increases of the heating element from current flow. The electrical resistivity transition zone may begin at a starting temperature of between 150° C. and 350° C. The electrical resistivity transition zone may begin at a starting temperature of between 220° C. and 300° C. The electrical resistivity transition zone may begin at a starting temperature between 240° C. and 280° C.

[0016] The increase in electrical resistivity over a temperature range of an electrical resistivity transition zone may include an increase factor of at least 10. The increase factor may characterize a relative change in electrical resistivity between electrical resistivity at a first temperature associated with a start of the electrical resistivity transition zone and electrical resistivity at a second temperature associated with an end of the electrical resistivity transition zone. An electrical resistivity transition zone may begin at a first temperature and electrical resistivity of the heating element at temperatures below the first temperature is between 0.2 ohm-cm and 200 ohm-cm. The vaporizer device may include a power source configured to provide a voltage between 3 Volts and 50 Volts to the heating element. The vaporizer device may include a pressure sensor. The vaporizer device may include a controller coupled to the pressure sensor and may be configured to detect inhalation and in response electrically connect the power source to the heating element. The housing may be cylindrical. The heating element may be cylindrical. The heat exchanger may be cylindrical.

[0017] In an interrelated aspect, a method may include receiving, by a vaporizer device, user input. The method may include heating, using the vaporizer device, a vaporizable material. The method may include forming inhalable aerosol.

[0018] In an interrelated aspect, a vaporizable material insert for use with a vaporizer device having a heating element may include an elongated body including an inner chamber defined by sidewalls and a first end. The elongated body may include an opening at a second end opposing the first end. The sidewalls may include a plurality of perforations. The inner chamber may be defined by the sidewalls and the first end. The inner chamber may be in fluid communication with the plurality of perforations. At least a part of the sidewalls may include a vaporizable material. The vaporizer device may include a receptacle for receiving the vaporizable material insert, as well as a sealed airflow pathway that extends along the side walls of the vaporizable material insert when the vaporizable material insert is inserted in the receptacle. The vaporizer device may be configured to flow heated air through the sealed airflow pathway to thereby allow the heated air to pass through the plurality of perforations and heat the vaporizable material to form an inhalable aerosol in the

inner chamber.

[0019] The details of one or more variations of the subject matter described herein are set forth in the accompanying drawings and the description below. Other features and advantages of the subject matter described herein will be apparent from the description and drawings, and from the claims. The claims that follow this disclosure are intended to define the scope of the protected subject matter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] The accompanying drawings, which are incorporated into and constitute a part of this specification, show certain aspects of the subject matter disclosed herein and, together with the description, help explain some of the principles associated with the disclosed implementations. In the drawings:

[0021] FIG. 1 illustrates a block diagram of a vaporizer consistent with implementations of the current subject matter;

[0022] FIG. 2A illustrates a block diagram of an embodiment of a heating and airflow system consistent with implementations of the current subject matter;

[0023] FIG. 2B illustrates a block diagram of another embodiment of a heating and airflow system consistent with implementations of the current subject matter;

[0024] FIG. 3 illustrates a top view of an embodiment of a vaporizer including the heating and airflow system of FIG. 2B;

[0025] FIG. 4A illustrates a top perspective view of another embodiment of a vaporizer including a liquid vaporizable material cartridge inserted at a first end of the vaporizer and a non-liquid tobacco cartridge inserted at a second end of the vaporizer;

[0026] FIG. 4B illustrates a top perspective exploded view of the vaporizer of FIG. 4A showing the liquid vaporizable material cartridge and the non-liquid tobacco cartridge removed from the first and second ends, respectively, of the vaporizer;

[0027] FIG. 4C illustrates a top perspective view of a distal end of the vaporizer of FIG. 4A showing a cartridge receptacle for inserting the tobacco cartridge therein;

[0028] FIG. 4D illustrates a block diagram of another embodiment of a heating and airflow system consistent with implementations of the current subject matter;

[0029] FIG. 5A illustrates a perspective cross-section view of an embodiment of a vaporizer cartridge with a tobacco consumable that is configured for use with any of the vaporizers described herein;

[0030] FIG. 5B illustrates a perspective side view of the tobacco consumable of FIG. 5A;

[0031] FIG. 5C illustrates a perspective cross-section view of the tobacco consumable of FIG. 5B, displaying a tobacco interior section;

[0032] FIG. 6 illustrates example properties associated with thermal power generation within an isotropic PTCR material;

[0033] FIG. 7 is a block diagram illustrating an example vaporizer device according to some implementations of the current subject matter that can provide for uniform heating of vaporizable material utilizing convective heating;

[0034] FIG. 8 is a block diagram of an example vaporizer device and cartridge with liquid vaporizable material that can provide for uniform heating of vaporizable material utilizing convective heating;

[0035] FIG. 9 is a cross-sectional view of an example vaporizer device with liquid vaporizable material;

[0036] FIG. 10 is a cross-sectional view of an example vaporizer device with solid vaporizable

material (e.g., heat-not-burn product);

[0037] FIG. **11** is a block diagram of an example vaporizer device and cartridge with liquid vaporizable material and solid vaporizable material that can provide for uniform heating of vaporizable material utilizing convective heating;

[0038] FIG. **12** is a block diagram of an example vaporizer device with multiple cartridges;

[0039] FIG. **13** is a cross-sectional view of an example vaporizer device with both liquid vaporizable material and solid vaporizable material;

[0040] FIG. **14** graphically illustrates an example resistivity vs. temperature curve for a nonlinear positive temperature coefficient of resistivity (PTCR) material;

[0041] FIG. **15** presents an example table of resistivity vs. temperature curve data for the nonlinear PTCR semiconducting material illustrated in FIG. **14**;

[0042] FIG. **16** graphically illustrates an example resistivity vs. temperature curve for a nonlinear positive temperature coefficient of resistivity (PTCR) material;

[0043] FIG. **17A** illustrates an embodiment of a PTCR heating element that can enable improved vaporizer heating;

[0044] FIG. **17B** illustrates a cross-sectional view of the PTCR heating element FIG. **17A**;

[0045] FIG. **18A**-FIG. **18E** illustrate modeled temperatures of an example PTCR heating element;

[0046] FIG. **19A**-FIG. **19F** illustrate modeled temperatures of an example PTCR heating element;

[0047] FIG. **20** illustrates modeled temperatures of an example heating element 6.0 seconds after application of a voltage in a free convective state;

[0048] FIG. **21A** graphically illustrates a modeled surface temperature as a function of time for an example PTCR heating element;

[0049] FIG. **21B** graphically illustrates a modeled and measured maximum surface temperatures as a function of time of an example PTCR heating element;

[0050] FIG. **21C** graphically illustrates a modeled and measured average surface temperatures as a function of time of an example PTCR heating element;

[0051] FIG. **22** graphically illustrates a transient current response as a function of time for an example PTCR heating element;

[0052] FIG. **23** is a perspective view of an example PTCR heater with heat exchanger assembly that can enable convective heating and improved uniform heating of vaporizable materials;

[0053] FIG. **24** is an exploded view of a rectangular embodiment of a PTCR insert for a vaporizer device;

[0054] FIG. **25** is a perspective view of an assembled embodiment of a rectangular embodiment of a PTCR insert for a vaporizer device;

[0055] FIG. **26** is a perspective view of an example PTCR heating element with cylindrical geometry;

[0056] FIG. **27** is an exploded view illustrating an example cylindrical PTCR heater with heat exchanger assembly;

[0057] FIG. **28** is a perspective view of the example assembled cylindrical PTCR heater with heat exchanger assembly;

[0058] FIG. **29** is a perspective view of a cylindrical embodiment of the PTCR insert for a vaporizer device;

[0059] FIG. **30** is a perspective view of the example cylindrical PTCR heater with heat exchanger assembly;

[0060] FIG. **31** illustrates an example graphical illustration showing a logarithm of resistivity of a cylindrical vaporization device with PTCR heater as a function of temperature;

[0061] FIG. **32** is a cross-sectional graphical illustration showing temperature simulations of the example implementation of the cylindrical vaporization device with PTCR heater; and

[0062] FIGS. **33A**-**33G** illustrate example cross-sectional graphical illustrations showing transient response of temperature for an example implementation of the cylindrical vaporization device with

PTCR heater.

[0063] When practical, similar reference numbers denote similar structures, features, or elements.

DETAILED DESCRIPTION

[0064] Implementations of the current subject matter include methods, apparatuses, articles of manufacture, and systems relating to vaporization of one or more materials for inhalation by a user. Example implementations include vaporizer devices and systems including vaporizer devices. The term “vaporizer device” as used in the following description and claims refers to any of a self-contained apparatus, an apparatus that includes two or more separable parts (for example, a vaporizer body that includes a battery and other hardware, and a cartridge that includes a vaporizable material), and/or the like. A “vaporizer system,” as used herein, can include one or more components, such as a vaporizer device. Examples of vaporizer devices consistent with implementations of the current subject matter include electronic vaporizers, electronic nicotine delivery systems (ENDS), and/or the like. In general, such vaporizer devices are hand-held devices that heat (such as by convection, conduction, radiation, and/or some combination thereof) a vaporizable material to provide an inhalable dose of the material.

[0065] Vaporizers described herein may be a cartridge-using vaporizer, a cartridge-less vaporizer, or a multi-use vaporizer capable of use with or without a cartridge. For example, some vaporizer embodiments may include a reusable vaporizer body that is configured to releasably couple a disposable or refillable cartridge containing at least one vaporizable material. As such, features described herein related to a vaporizer may be contained within the vaporizer body and/or the cartridge of the vaporizer. Furthermore, although some features described herein are described as being contained in the cartridge, such features may be contained within the vaporizer body without departing from the scope of this disclosure.

[0066] In some embodiments disclosed herein, vaporizers may produce aerosol on-demand (e.g., when a user puffs on the vaporizer) for inhalation. Additionally, the aerosol produced may include a combination of vaporized liquid material, vaporized non-liquid material, and/or inhalable elements from heating non-liquid vaporizable material. Such a combined aerosol may provide an enhanced user experience that is the same as or similar to inhaling smoke from a traditional cigarette.

[0067] Some vaporizer embodiments disclosed herein include a heating and airflow system having a first heating element that heats a first chamber and a second heating element that heats a second chamber. The first chamber may be configured to contain a liquid vaporizable material and the first heating element may be configured to heat and/or vaporize the liquid vaporizable material. Additionally, the second chamber may be configured to contain a non-liquid vaporizable material and the second heating element may be configured to heat and/or vaporize the non-liquid vaporizable material. The contents emitted from the first and second chambers as a result of being heated by the first and second heating elements, respectively, may be combined to form a combined aerosol for inhalation by a user, as will be described in greater detail below. This combined aerosol can be provided on-demand and include inhalable elements from both liquid and non-liquid vaporizable material, which can provide an experience that is similar to smoking a traditional cigarette. Various heating and airflow systems and associated features for achieving the above on-demand combined aerosol are described in greater detail below.

[0068] Various heater element embodiments are also described herein that can improve the efficiency and quality of heating of the vaporizable material, such as by heating the vaporizable material to a temperature that is hot enough to vaporize the vaporizable material into an aerosol for inhalation, but below a temperature that produces harmful byproducts and/or that results in combustion of the vaporizable material. In some embodiments, the heating element may be configured to heat the vaporizable material (e.g., non-liquid vaporizable material) to a temperature that is hot enough to produce a byproduct of the vaporizable material but does not vaporize or cause burning of the vaporizable material. In some embodiments, the heating elements described herein can achieve an optimal heating range at a rate that allows a user to have an enjoyable user

experience (e.g., not being required to wait a long time for the heating element to reach a temperature in the optimal heating range, etc.). In some embodiments, the heating element may be at least partially constructed of a material having a nonlinear positive temperature coefficient of resistance. In some embodiments, vaporizer cartridges including such heating elements can be cost effectively manufactured, thereby making them economically feasible as single-use disposable cartridges. Various vaporizers, including cartridges, and heating elements including one or more of the above features are described in greater detail below.

[0069] As mentioned above, a vaporizer device can be a cartridge-using vaporizer device, a cartridge-less vaporizer device, or a multi-use vaporizer device capable of use with or without a cartridge. For example, a vaporizer device can include at least one heating chamber (for example, an oven or other region in which material is heated by a heating element) configured to receive a vaporizable material directly into each heating chamber, and/or a reservoir or the like for containing the vaporizable material.

[0070] In some implementations, a vaporizer device can be configured for use with a liquid vaporizable material (for example, a carrier solution in which an active and/or inactive ingredient(s) are suspended or held in solution, or a liquid form of the vaporizable material itself), a paste, a wax, and/or a non-liquid or solid vaporizable material. A solid vaporizable material can include a plant material that emits some part of the plant material as the vaporizable material (for example, some part of the plant material remains as waste after the material is vaporized for inhalation by a user) or optionally can be a solid form of the vaporizable material itself, such that all of the solid material can eventually be vaporized for inhalation. A liquid vaporizable material can likewise be capable of being completely vaporized, or can include some portion of the liquid material that remains after all of the material suitable for inhalation has been vaporized. As noted above, vaporizable material used with a vaporizer may optionally be provided within a cartridge (e.g., a part of the vaporizer that contains the vaporizable material or a source substance that includes the vaporizable material in a reservoir or other container and that can be refillable when empty or disposable in favor of a new cartridge containing additional vaporizable material of a same or different type).

[0071] Referring to the block diagram of FIG. 1, a vaporizer device **100** can include a power source **112** (for example, a battery, which can be a rechargeable battery), and a controller **104** (for example, a processor, circuitry, etc. capable of executing logic) for controlling delivery of heat to cause at least one vaporizable material **102** to be converted from a condensed form to the gas phase. The controller **104** can be part of one or more printed circuit boards (PCBs) consistent with certain implementations of the current subject matter. After conversion of the vaporizable material **102** to the gas phase, at least some of the vaporizable material **102** in the gas phase can condense to form particulate matter in at least a partial local equilibrium with the gas phase as part of an aerosol, which can form some or all of an inhalable dose provided by the vaporizer device **100** during a user's puff or draw on the vaporizer device **100**. It should be appreciated that the interplay between gas and condensed phases in an aerosol generated by a vaporizer device **100** can be complex and dynamic, due to factors such as ambient temperature, relative humidity, chemistry, flow conditions in airflow paths (both inside the vaporizer and in the airways of a human or other animal), and/or mixing of the vaporizable material **102** in the gas phase or in the aerosol phase with other air streams, which can affect one or more physical parameters of an aerosol. In some vaporizer devices, and particularly for vaporizer devices configured for delivery of volatile vaporizable materials, the inhalable dose can exist predominantly in the gas phase (for example, formation of condensed phase particles can be very limited).

[0072] The atomizer (e.g., heating element **150**) in the vaporizer device **100** can be configured to vaporize a vaporizable material **102**. The vaporizable material **102** can be a liquid. Examples of the vaporizable material **102** include neat liquids, suspensions, solutions, mixtures, and/or the like. The atomizer can include a wicking element (i.e., a wick) configured to convey an amount of the

vaporizable material **102** to a part of the atomizer that includes a heating element **150**.

[0073] For example, the wicking element can be configured to draw the vaporizable material **102** from a reservoir **140** configured to contain the vaporizable material **102**, such that the vaporizable material **102** can be vaporized by heat delivered from a heating element. The wicking element can also optionally allow air to enter the reservoir **140** and replace the volume of vaporizable material **102** removed. In some implementations of the current subject matter, capillary action can pull the vaporizable material **102** into the wick for vaporization by the heating element, and air can return to the reservoir **140** through the wick to at least partially equalize pressure in the reservoir **140**. Other methods of allowing air back into the reservoir **140** to equalize pressure are also possible. As used herein, the terms “wick” or “wicking element” include any material capable of causing fluid motion via capillary pressure.

[0074] Various embodiments of the heating element **150**, as well as various configurations of one or more heating elements **150** of a heating system, are described herein. For example, in some embodiments the heating element **150** can include the heating element including a nonlinear positive temperature coefficient of resistance material. In some embodiments, the vaporizer can include a heating system including one or more heating elements, such as two or three heating elements that are configured to heat one or more types of vaporizable materials, as will be described in greater detail below.

[0075] As noted above, vaporizers consistent with implementations of the current subject matter may also or alternatively be configured to create an inhalable dose of gas-phase and/or aerosol-phase vaporizable material via heating of a non-liquid source substance containing or including a vaporizable material, such as for example a solid-phase vaporizable material or plant material (e.g., tobacco leaves and/or parts of tobacco leaves) containing the vaporizable material. In such vaporizers, a heating element may be part of or otherwise incorporated into or in thermal contact with the walls of an oven or other heating chamber into which the non-liquid source substance that contains or includes a vaporizable material is placed. Alternatively, a heating element or elements may be used to heat air passing through or past the non-liquid source substance to cause convective heating of the non-liquid vaporizable material. In still other examples, a heating element or elements may be disposed in intimate contact with plant material such that direct thermal conduction heating of the source substance occurs from within a mass of the source substance (e.g., as opposed to only by conduction inward from walls of an oven). Such non-liquid vaporizable materials may be used with cartridge using or cartridge less vaporizers.

[0076] The heating element can include one or more of a conductive heater, a radiative heater, and/or a convective heater. One type of heating element is a resistive heating element, which can include a material (such as a metal or alloy, for example a nickel-chromium alloy, or a non-metallic resistor) configured to dissipate electrical power in the form of heat when electrical current is passed through one or more resistive segments of the heating element. In some implementations of the current subject matter, a heating element which includes a resistive coil or other heating element wrapped around, positioned within, integrated into a bulk shape of, pressed into thermal contact with, or otherwise arranged to deliver heat to a mass of a source substance (e.g., plant based-substance such as tobacco) that contains the vaporizable material. Throughout the current disclosure, “source substance” generally refers to the part of a plant-based material (or other condensed form of a plant material or other material that may release vaporizable material without being burned) that contains vaporizable materials that are converted to vapor and/or aerosol for inhalation. Other heating elements, and/or atomizer assembly configurations are also possible.

[0077] For example, a resistive heating element can be activated in association with a user puffing (i.e., drawing, inhaling, etc.) on a mouthpiece **130** of the vaporizer device **100** to cause air to flow from an air inlet, along an airflow path that passes the heating element and an associated mass of the source substance. Optionally, air can flow from an air inlet through one or more condensation areas or chambers, to an air outlet in the mouthpiece **130**. Incoming air moving along the airflow

path moves over or through the heating element **150** and the source substance, where vaporizable material **102** in the gas phase is entrained into the air. The heating element can be activated via the controller **104**, which can optionally be a part of a vaporizer body **110** as discussed herein, causing current to pass from the power source **112** through a circuit including the resistive heating element, which is optionally part of a vaporizer cartridge **120** as discussed herein. As noted herein, the entrained vaporizable material in the gas phase can condense as it passes through the remainder of the airflow path such that an inhalable dose of the vaporizable material **102** in an aerosol form can be delivered from the air outlet (for example, the mouthpiece **130**) for inhalation by a user. Other airflow pathways and collection of aerosols and/or source substances of one or more vaporizable materials is described in greater detail below.

[0078] Activation of one or more heating elements can be caused by automatic detection of a puff based on one or more signals generated by one or more of a sensor **113**. The sensor **113** and the signals generated by the sensor **113** can include one or more of: a pressure sensor or sensors disposed to detect pressure along the airflow path relative to ambient pressure (or optionally to measure changes in absolute pressure), a motion sensor or sensors (for example, an accelerometer) of the vaporizer device **100**, a flow sensor or sensors of the vaporizer device **100**, a capacitive lip sensor of the vaporizer device **100**, detection of interaction of a user with the vaporizer device **100** via one or more input devices **116** (for example, buttons or other tactile control devices of the vaporizer device **100**), receipt of signals from a computing device in communication with the vaporizer device **100**, and/or via other approaches for determining that a puff is occurring or imminent.

[0079] As discussed herein, the vaporizer device **100** consistent with implementations of the current subject matter can be configured to connect (such as, for example, wirelessly or via a wired connection) to a computing device (or optionally two or more devices) in communication with the vaporizer device **100**. To this end, the controller **104** can include communication hardware **105**. The controller **104** can also include a memory **108**. The communication hardware **105** can include firmware and/or can be controlled by software for executing one or more cryptographic protocols for the communication.

[0080] A computing device can be a component of a vaporizer system that also includes the vaporizer device **100**, and can include its own hardware for communication, which can establish a wireless communication channel with the communication hardware **105** of the vaporizer device **100**. For example, a computing device used as part of a vaporizer system can include a general-purpose computing device (such as a smartphone, a tablet, a personal computer, some other portable device such as a smartwatch, or the like) that executes software to produce a user interface for enabling a user to interact with the vaporizer device **100**. In other implementations of the current subject matter, such a device used as part of a vaporizer system can be a dedicated piece of hardware such as a remote control or other wireless or wired device having one or more physical or soft (i.e., configurable on a screen or other display device and selectable via user interaction with a touch-sensitive screen or some other input device like a mouse, pointer, trackball, cursor buttons, or the like) interface controls. The vaporizer device **100** can also include one or more outputs **117** or devices for providing information to the user. For example, the outputs **117** can include one or more light emitting diodes (LEDs) configured to provide feedback to a user based on a status and/or mode of operation of the vaporizer device **100**.

[0081] In the example in which a computing device provides signals related to activation of the resistive heating element, or in other examples of coupling of a computing device with the vaporizer device **100** for implementation of various control or other functions, the computing device executes one or more computer instruction sets to provide a user interface and underlying data handling. In one example, detection by the computing device of user interaction with one or more user interface elements can cause the computing device to signal the vaporizer device **100** to activate the heating element to reach an operating temperature for creation of an inhalable dose of

vapor/aerosol. Other functions of the vaporizer device **100** can be controlled by interaction of a user with a user interface on a computing device in communication with the vaporizer device **100**. [0082] The temperature of a resistive heating element of the vaporizer device **100** can depend on a number of factors, including an amount of electrical power delivered to the resistive heating element and/or a duty cycle at which the electrical power is delivered, conductive heat transfer to other parts of the electronic vaporizer device and/or to the environment, latent heat losses due to vaporization of the vaporizable material **102** from the wicking element and/or the atomizer as a whole, and convective heat losses due to airflow (i.e., air moving across the heating element or the atomizer as a whole when a user inhales on the vaporizer device **100**). As noted herein, to reliably activate the heating element or heat the heating element to a desired temperature, the vaporizer device **100** may, in some implementations of the current subject matter, make use of signals from the sensor **113** (for example, a pressure sensor) to determine when a user is inhaling. The sensor **113** can be positioned in the airflow path and/or can be connected (for example, by a passageway or other path) to an airflow path containing an inlet for air to enter the vaporizer device **100** and an outlet via which the user inhales the resulting vapor and/or aerosol such that the sensor **113** experiences changes (for example, pressure changes) concurrently with air passing through the vaporizer device **100** from the air inlet to the air outlet. In some implementations of the current subject matter, the heating element can be activated in association with a user's puff, for example by automatic detection of the puff, or by the sensor **113** detecting a change (such as a pressure change) in the airflow path.

[0083] The sensor **113** can be positioned on or coupled to (i.e., electrically or electronically connected, either physically or via a wireless connection) the controller **104** (for example, a printed circuit board assembly or other type of circuit board). To take measurements accurately and maintain durability of the vaporizer device **100**, it can be beneficial to provide a seal **127** resilient enough to separate an airflow path from other parts of the vaporizer device **100**. The seal **127**, which can be a gasket, can be configured to at least partially surround the sensor **113** such that connections of the sensor **113** to the internal circuitry of the vaporizer device **100** are separated from a part of the sensor **113** exposed to the airflow path.

[0084] In some implementations, the vaporizer body **110** includes the controller **104**, the power source **112** (for example, a battery), one more of the sensor **113**, charging contacts (such as those for charging the power source **112**), the seal **127**, and a cartridge receptacle **118** configured to receive the vaporizer cartridge **120** for coupling with the vaporizer body **110** through one or more of a variety of attachment structures. In some examples, the vaporizer cartridge **120** includes the reservoir **140** for containing the vaporizable material **102**, and the mouthpiece **130** has an aerosol outlet for delivering an inhalable dose to a user. In these examples, the vaporizer cartridge **120** can include the atomizer having a wicking element and a heating element. Alternatively, one or both of the wicking element and the heating element can be part of the vaporizer body **110**. In implementations in which any part of the atomizer (i.e., heating element and/or wicking element) is part of the vaporizer body **110**, the vaporizer device **100** can be configured to supply the vaporizable material **102** from the reservoir **140** in the vaporizer cartridge **120** to the part(s) of the atomizer included in the vaporizer body **110**.

[0085] Various embodiments of a vaporizer cartridge are described herein that are configured for containing and vaporizing one or more non-liquid source substances, such as loose-leaf tobacco. Furthermore, such embodiments of vaporizer cartridges may be single-use such that they are not refillable after the vaporizable material has been used up. Such single-use vaporizer cartridges may thus require inexpensive material and manufacturing in order to be economically feasible. Furthermore, although it may be desirable to make and manufacture single-use vaporizer cartridges for vaporizing non-liquid source substances, it is also desirable to efficiently and effectively vaporize the vaporizable material. For example, a user inhaling on a vaporizer device typically prefers inhaling aerosol created by the vaporizer device shortly after engaging with the vaporizer

device (e.g., placing lips on mouthpiece, pushing an activation button, etc.). As such, the embodiments of the vaporizer cartridges disclosed herein may beneficially achieve efficient vaporization of vaporizable material from a source substance to achieve a desired user experience. Furthermore, embodiments of the vaporizer cartridge disclosed herein may advantageously provide sufficient heat energy to the source substance to cause release of the vaporizable material such to create an aerosol form of the vaporizable material for inhalation, while also limiting heating sufficiently to at least reduce creation of at least one harmful by-product that is not desired for a user to inhale. To achieve the above, various embodiments of heating elements are disclosed and described in greater detail below.

[0086] For example, various embodiments of heating elements are described herein that are configured to heat within a desired temperature range, such as at or below approximately 250 degrees Celsius. Such a temperature range may advantageously vaporize a source substance such as processed tobacco and allow nicotine and volatile flavor compounds to be aerosolized and delivered to a user puffing on the associated vaporization device. Such a temperature within the temperature range may also prevent the creation of at least one harmful or potentially harmful by-product. As such, at least one benefit of the heating assemblies described herein include the improved quality of aerosol for inhalation by a user.

[0087] In addition, various embodiments of the heating elements described herein may efficiently heat up to a temperature within the desired temperature range. This can allow the associated vaporizer device to achieve a desired user experience for the user inhaling on the vaporizer device. Such efficient heat-up time can result in efficient power usage, such as battery power from the vaporizer device. Furthermore, the various embodiments of the heating elements described herein can achieve such benefits while not requiring an increase in vaporizer device size. In some embodiments, the heating element can allow for a more compact vaporizer device than what is currently available. In addition, embodiments of the heating element can be made and manufactured at a cost that may allow the vaporizer cartridge to be single-use and economically feasible.

[0088] Embodiments of the heating elements described below can include at least one thermally conductive material, such as carbon, carbon foam, metal, metal foil, aluminum foam, or a biodegradable polymer. The thermally conductive material can allow energy provided by a vaporizer device to be transmitted to the thermally conductive feature (e.g., via the cartridge and vaporizer device contacts) to thereby cause an increase in temperature along at least a part of the thermally conductive feature, such as for vaporizing the vaporizable material from the source substance. The vaporizer body can include a controller that can control the amount of energy provided to the thermally conductive material, thereby assisting the heating element with reaching a temperature that is within the desired temperature range. For example, in some embodiments the heating element **150** can include the heating element including a nonlinear positive temperature coefficient of resistance material.

[0089] Further to and in addition to the above disclosure, various embodiments of a vaporizer are described herein that may heat more than one vaporizable material using more than one heating element.

[0090] FIGS. 2A and 2B illustrate first and second embodiments of a heating and airflow system **250** of a vaporizer device consistent with implementations of the current subject matter. For example, all or part of the heating and airflow systems **250** shown in FIGS. 2A and 2B may be contained in a vaporizer body and/or in a vaporizer cartridge configured to releasably couple to the vaporizer body. As shown in FIGS. 2A and 2B, the heating and airflow systems **250** include a first heating element **251** that is configured to heat a first chamber **254** configured to hold a first vaporizable material. Additionally, the heating and airflow systems **250** include a second heating element **252** that is configured to heat a second chamber **256** configured to hold a second vaporizable material. As such, the heating and airflow systems **250** of FIGS. 2A and 2B may

produce a combined aerosol that includes inhalable extracts from both the first and second vaporizable material. The first heating element **251** and the second heating element **252** may include the same or different configurations and type of heating element, and may be independently controlled. For example, the first heating element **251** and the second heating element **252** may be controlled to reach different temperatures and/or heat for different amounts of time.

[0091] For example, the first chamber **254** may be configured for containing a liquid vaporizable material and the first heating element **251** may be configured to heat or vaporize the liquid vaporizable material. Additionally, the second chamber **256** may be configured to contain a non-liquid vaporizable material and the second heating element **252** may be configured to heat and/or vaporize the non-liquid vaporizable material. As will be described in greater detail below, inhalable extracts from both the liquid and non-liquid vaporizable material may be combined for inhalation by a user.

[0092] For example, FIG. 2A shows an airflow pathway **260** that includes an inlet **262**, an outlet **264**, and a first pathway **266** and a second pathway **268** that extend between the inlet **262** and outlet **264**. The first pathway **266** may pass through or adjacent the first heating element **251** and/or first chamber **254** to allow inhalable extracts (e.g., within an aerosol) created from heating and/or vaporizing the liquid vaporizable material to mix with the airflow passing through the vaporizer device. Additionally, the second pathway **268** may pass through or adjacent the second heating element **252** and/or second chamber **256** to allow inhalable extracts created from heating and/or vaporizing the non-liquid vaporizable material to mix with the airflow passing through the vaporizer device.

[0093] As shown in FIG. 2A, when a user inhales on the vaporizer device (such as on the mouthpiece), airflow may be drawn into the inlet **262** and along the airflow pathway **260**. For example, a first part of the airflow may travel along the first pathway **266** thereby collecting the inhalable extracts of the liquid vaporizable material. Additionally, a second part of the airflow may travel along the second pathway **268** thereby collecting inhalable extracts of the non-liquid vaporizable material. The first part and second part of the airflow may converge prior to passing through the outlet **264** (e.g., a port along the mouthpiece). For example, the first pathway **266** and the second pathway **268** may converge at a mixing chamber that allows the inhalable extracts from the liquid and non-liquid vaporizable material to be combined prior to traveling out the outlet **264** for inhalation by a user.

[0094] Various airflow pathways may be implemented in the heating and airflow system **250** and are within the scope of this disclosure. For example, as shown in FIG. 2B, the airflow pathway **260** may include a single pathway that travels through and/or adjacent to the first heating element **251** and the second heating element **252** and the first chamber **254** and the second chamber **256** sequentially. As such, the airflow passing through and/or adjacent to the second heating element **252** and second chamber **256** may include inhalable extracts from the heated and/or vaporized first vaporizable material. Inhalable extracts from the heated and/or vaporized second vaporizable material may be added to the airflow such that the airflow exiting the outlet **264** includes the combined aerosol.

[0095] FIG. 3 illustrates an example embodiment of a vaporizer device **300** including a removable vaporizer cartridge **320** coupled to a vaporizer body **310** and a heating and airflow system consistent with this disclosure, such as the heating and airflow system **250** shown in FIG. 2B. As shown in FIG. 3, the vaporizer cartridge **320** includes an atomizer chamber **354** including humectants that may be vaporized by a first heating element **351**. Additionally, the vaporizer cartridge **320** includes a tobacco chamber **356** including tobacco blends that may be heated and/or vaporized by a second heating element **352**. The airflow pathway **360** of the vaporizer device **300** shown in FIG. 3 may travel linearly through and/or adjacent the first heating element **351** and the second heating element **352** to collect and combine inhalable extracts from the humectants and tobacco for inhalation by a user.

[0096] In some embodiments, other inhalable extracts and/or other aerosol flavorants may be optionally provided in a flavor filter **358**. The flavor filter **358** may be positioned between the tobacco chamber **356** and an outlet **364**.

[0097] FIGS. **4A-4D** illustrate another embodiment of a vaporizer device **400** configured to releasably couple two separate cartridges, such as a first cartridge **420** configured to contain a liquid vaporizable material and a second cartridge **470** configured to contain a non-liquid tobacco material. As shown in FIGS. **4A** and **4B**, the vaporizer device **400** can include a first cartridge receptacle **418** at a first end **472** of a vaporizer body **410** that is configured to releasably couple the first cartridge **420**, as well as a second cartridge receptacle **474** at a second end **476** of the vaporizer body **410** that is configured to releasably couple the second cartridge **470**. For example, the first cartridge **420** and first cartridge receptacle **418** can include features that allow for vaporization of the liquid vaporizable material contained within the first cartridge **420**, such as any of such features described herein. Additionally, the second cartridge **470** and the second cartridge receptacle **474** can include features that allow for vaporization of the non-liquid tobacco material contained within the second cartridge **470**, such as any of such features described herein.

[0098] Either the first end **472** or the second end **476** of the vaporizer body **410**, as well as either the first cartridge **420** or the second cartridge **470**, can be configured to allow airflow to pass along and/or through. For example, airflow can travel along and/or through either the first cartridge **420** or the second cartridge **470** to allow inhalable extracts from the vaporized liquid vaporizable material and vaporized non-liquid tobacco material to be inhaled by a user puffing on the vaporizer device **400**. The vaporizer device **400** can be configured such that the user can puff on either the first end **472** or the second end **476** of the vaporizer device **400** to thereby inhale aerosol containing inhalable extracts from the first cartridge **420** and the second cartridge **470**.

[0099] FIG. **4C** illustrates an example second cartridge **470** containing a non-liquid tobacco material that can be inserted and releasably coupled to the second cartridge receptacle **474**. Both the first cartridge **420** and the second cartridge **470** can be refillable and/or replaceable thereby allowing the vaporizer device **400** to be used with various cartridges containing various materials.

[0100] In some embodiments, the first cartridge **420** and the second cartridge **470** can contain the same or similar materials, such as two different liquid vaporizable materials.

[0101] In some embodiments, the first cartridge receptacle **418** can be configured to only allow cartridges containing a liquid material or a non-liquid material. Similarly, the second cartridge receptacle **474** can be configured to only allow cartridges containing a liquid material or a non-liquid material.

[0102] In some embodiments, the vaporizer device **400** can be configured to form an aerosol for inhalation by a user only when both the first cartridge **420** and the second cartridge **470** are coupled to the vaporizer device **400**. In some embodiments, only one of the first cartridge **420** and the second cartridge **470** need to be coupled to the vaporizer device **400** to allow the vaporizer device **400** to function to form an aerosol for inhalation by a user.

[0103] FIG. **4D** illustrates a third embodiment of a heating and airflow system **450** consistent with implementations of the current subject matter. For example, the heating and airflow system **450** illustrated in FIG. **4D** can be included in the vaporizer device **400** and/or first cartridge **420** and the second cartridge **470** of FIGS. **4A-4C**.

[0104] As shown in FIG. **4D** the heating and airflow system **450** can include a first heating element **451** that is configured to heat a first chamber **454** configured to hold a first vaporizable material, such as the liquid vaporizable material contained within the first cartridge **420**. Additionally, the heating and airflow system **450** can include a second heating element **452** that is configured to heat a second chamber **456** configured to hold a second vaporizable material, such as the non-liquid tobacco material contained within the second cartridge **470**. As such, the heating and airflow system **450** of FIG. **4D** may produce a combined aerosol that includes inhalable extracts from both the liquid and non-liquid vaporizable materials. The first heating element **451** and second heating

element **452** may include the same or different configurations and type of heating element, and may be independently controlled. For example, the first heating element **451** and second heating element **452** may be controlled to reach different temperatures and/or heat for different amounts of time. For example, in some embodiments the heating element **150** can include the heating element including a nonlinear positive temperature coefficient of resistance material.

[0105] For example, the first chamber **454** may be configured for containing a liquid vaporizable material and the first heating element **451** may be configured to heat or vaporize the liquid vaporizable material. Additionally, the second chamber **456** may be configured to contain a non-liquid vaporizable material and the second heating element **452** may be configured to heat and/or vaporize the non-liquid vaporizable material. The first heating element **451** can be integrated with the vaporizer device **400** or first cartridge **420** and the second heating element **452** can be integrated with the vaporizer device **400** or the second cartridge **470**.

[0106] Furthermore, as shown in FIG. **4D**, the heating and airflow system **450** can include a third heating element **453** positioned along the airflow pathway **460** and configured to assist with heating airflow traveling along the airflow pathway **460**, such as upstream or downstream from another heater (e.g., a heater for vaporizing vaporizable material). For example, the third heating element **453** can be integrated with the vaporizer device **400** and positioned along the airflow pathway **460** upstream from the second chamber **456** and second heating element **452**. As such, the third heating element **453** can increase the temperature of the airflow along the airflow pathway **460** leading up to the second chamber **456** and second heating element **452**. For example, such heating of the airflow can allow the second chamber **456** to achieve a smaller temperature gradient along the second chamber **456**, which can allow for efficient and effective vaporization of the vaporizable material (e.g., non-liquid tobacco material) contained therein. Furthermore, with the warmer airflow entering the second chamber **456** (compared to heating and airflow systems that do not heat airflow prior to entering a chamber containing vaporizing material), the non-liquid vaporizable material contained in the second chamber **456** can be heated by the second heating element **452** at a lower, more optimal temperatures. Such temperatures can at least reduce the formation of undesirable byproducts when vaporizing the non-liquid vaporizable material, as well as allow for effective start-and-stop vaporizing of the non-liquid vaporizable material. Such start-and-stop vaporizing can accommodate a user that wants to enjoy more than one session of puffing on the vaporizer device **400** using a single cartridge containing the non-liquid vaporizable material.

[0107] FIGS. **5A-5C** illustrate embodiments of a vaporizer cartridge **520** and a vaporizable material insert **580** that can be compatible for use with at least the vaporizer devices described herein. For example, FIG. **5A** illustrate the vaporizer cartridge **520** with the vaporizable material insert **580** inserted in a chamber **554** of the vaporizer cartridge **520**, which can include a heating element **550**. As shown in FIGS. **5B** and **5C**, the vaporizable material insert **580** can include a hollow core **582** that is enclosed within the vaporizable material insert **580** except for an open end **584** of the vaporizable material insert **580** that can be positioned outside of the chamber **554** of the vaporizer cartridge **520**, as shown in FIG. **5A**.

[0108] As shown in FIG. **5A**, the vaporizer cartridge **520** can include a seal **586** that forces heated air generated in the vaporizer cartridge **520** to pass through the walls of the vaporizable material insert **580** (which can contain the vaporizable material, such as tobacco) such that vapor or aerosol passes through the vaporizable material and into the hollow core **582** of the vaporizable material insert **580**. Such vapor or aerosol can then pass from the hollow core **582** of the vaporizable material insert **580** and out the open end **584** of the vaporizable material insert **580**, such as for allowing the aerosol to be inhaled by a user.

[0109] In some embodiments, the vaporizable material insert **580** can include an exterior shell made of one or more of a paper material and a plastic (low COG) material. In some embodiments, the vaporizable material insert **580** can include various hole pattern configurations, such as along one or more of an end and a side of the vaporizable material insert **580**. For example, the holes or

perforations **588** can allow air to pass therethrough for assisting in forming the inhalable aerosol that forms and/or collects in the hollow core **582** of the vaporizable material insert **580** for inhalation by a user. In some embodiments, the vaporizable material insert **580** can include a mouthpiece **530** that can assist a user with inhaling the inhalable aerosol.

[0110] At least one benefit of the vaporizable material insert **580** and vaporizer cartridge **520** of FIGS. 5A-5C includes that aerosol can be produced in the vaporizable material insert **580**, including collecting in the hollow core **582**. The airflow containing the aerosol can have a clean and direct exit path out of the vaporizer cartridge **520** and mouthpiece **530**, such as without contacting or contaminating a part of the durable portion of the vaporizer device.

[0111] In some embodiments, the vaporizable material insert **580** can be configured for use with a vaporizer device having a heating element, and the vaporizable material insert **580** may include an elongated body including the hollow core **582** (or inner chamber) that is defined by sidewalls and a first end. The elongated body may include the open end **584** at a second end opposing the first end. The sidewalls may include a plurality of perforations **588**, as shown in FIG. 5B. The hollow core **582** may be defined by the sidewalls and the first end, and the hollow core **582** may be in fluid communication with the plurality of perforations **588**. Additionally, at least a part of the sidewalls of the vaporizable material insert may include a vaporizable material. Some embodiments of a vaporizer device may include a receptacle for receiving the vaporizable material insert **580**, as well as a sealed airflow pathway that extends along the side walls of the vaporizable material insert **580** when the vaporizable material insert is inserted in the receptacle, as shown in FIG. 5A. The vaporizer device may be configured to flow heated air through the sealed airflow pathway to thereby allow the heated air to pass through the plurality of perforations and heat a vaporizable material to form and/or collect an inhalable aerosol in the hollow core **582**. The inhalable aerosol in the hollow core **582** can then be inhaled by a user.

[0112] Various airflow pathways may be implemented in the heating and airflow system and are within the scope of this disclosure, including the heating and airflow systems described with regards to FIGS. 2A and 2B. For example, as shown in FIG. 4D, the airflow pathway **460** may include a single pathway that travels through the first chamber **454** and the second chamber **456** sequentially. For example, the airflow pathway **460** can sequentially travel adjacent to the first heating element **451**, the third heating element **453**, and the second heating element **452**. As such, the airflow passing through and/or adjacent to the second heating element **452** and the second chamber **456** may include inhalable extracts from the heated and/or vaporized first heating element **451** and the first chamber **454**. Furthermore, such airflow including inhalable extracts from the heated and/or vaporized first cartridge **420** can be heated along the airflow pathway **460** by the third heating element **453** before passing through the second heating element **452** and the second chamber **456**. Inhalable extracts from the heated and/or vaporized second vaporizable material may be added to the airflow such that the airflow exiting the outlet **464** includes the combined aerosol. Various other airflow pathway configurations and heating and airflow systems are within the scope of this disclosure. For example, in some embodiments the heating element **150** can include the heating element including a nonlinear positive temperature coefficient of resistance material.

[0113] Vaporizers that include the heating and airflow systems described herein (e.g., heating and airflow systems shown in FIGS. 2A-3) may provide one or more of a variety of benefits over currently available vaporizer devices. For example, the heating and airflow systems described herein may provide a combined aerosol (e.g., inhalable elements from liquid and non-liquid vaporizable material). Other benefits may include the ability to provide the combined aerosol on-demand thereby not requiring a user to have to wait for a heating element to reach a required temperature. Such heat-up time may typically be required for drawing inhalable extracts from non-liquid vaporizable material. In the heating and airflow systems described herein, the inhalable extracts are drawn from both non-liquid and liquid vaporizable materials where the liquid vaporizable materials may be vaporized more efficiently and effectively on-demand. Furthermore,

the heating element configured to heat and/or vaporize the non-liquid vaporizable material may heat to a temperature (e.g., less than 150 degrees Celcius) that eliminates the potential for charring (e.g., reduce or eliminate amount of harmful and potentially harmful constituents produced) combined with the ability to start and stop a session at will, including multiple times with the same cartridge and/or heating and airflow systems. As such, a user may be able to enjoy multiple sessions with a single cartridge and not have to consume or use the entire non-liquid vaporizable material contained in the cartridge and/or heating and airflow systems in a single session. For example, since the non-liquid vaporizable material (e.g., tobacco) may be refreshed by vapor produced in the atomizer chamber, the user experience may be consistent throughout the session and subsequent sessions. Other benefits of the vaporizers and heating and airflow systems described herein are within the scope of this disclosure.

[0114] In an embodiment of the vaporizer device **100** in which the power source **112** is part of the vaporizer body **110**, and a heating element is disposed in the vaporizer cartridge **120** and configured to couple with the vaporizer body **110**, the vaporizer device **100** can include electrical connection features (for example, means for completing a circuit) for completing a circuit that includes the controller **104** (for example, a printed circuit board, a microcontroller, or the like), the power source **112**, and the heating element (for example, a heating element within the atomizer). These features can include one or more contacts (referred to herein as cartridge contacts **124a** and **124b**) on one or more outer surfaces of the vaporizer cartridge **120** and at least two contacts (referred to herein as receptacle contacts **125a** and **125b**) disposed on the vaporizer body, optionally in a cartridge receptacle **118** of the vaporizer device **100** such that the cartridge contacts **124a** and **124b** and the receptacle contacts **125a** and **125b** make electrical connections when the vaporizer cartridge **120** is inserted into and coupled with the cartridge receptacle **118**. The circuit completed by these electrical connections can allow delivery of electrical current to a heating element and can further be used for additional functions, such as measuring a resistance of the heating element for use in determining and/or controlling a temperature of the heating element based on a thermal coefficient of resistivity of the heating element.

[0115] Other configurations in which a vaporizer cartridge **120** is coupled to a vaporizer body **110** without being inserted into a cartridge receptacle **118** are also within the scope of the current subject matter. It will be understood that the references herein to “receptacle contacts” can more generally refer to contacts on a vaporizer body **110** that are not contained within the cartridge receptacle **118** but are nonetheless configured to make electrical connections with the cartridge contacts **124a** and **124b** of a vaporizer cartridge **120** when the vaporizer cartridge **120** and the vaporizer body **110** are coupled. The circuit completed by these electrical connections can allow delivery of electrical current to the resistive heating element and may further be used for additional functions, such as for example for measuring a resistance of the resistive heating element for use in determining and/or controlling a temperature of the resistive heating element based on a thermal coefficient of resistivity of the resistive heating element, for identifying a cartridge based on one or more electrical characteristics of a resistive heating element or the other circuitry of the vaporizer cartridge, etc. The vaporizer device **100** (and other features described herein in accordance with one or more implementations) may include circuitry having a heating element comprising a nonlinear positive temperature coefficient of resistance material, or features thereof, for example heating elements consistent with the as example implementations described in further detail below.

[0116] In some implementations of the current subject matter, the cartridge contacts **124a** and **124b** and the receptacle contacts **125a** and **125b** can be configured to electrically connect in either of at least two orientations. In other words, one or more circuits necessary for operation of the vaporizer device **100** can be completed by insertion of the vaporizer cartridge **120** into the cartridge receptacle **118** in a first rotational orientation (around an axis along which the vaporizer cartridge **120** is inserted into the cartridge receptacle **118** of the vaporizer body **110**) such that the cartridge contact **124a** is electrically connected to the receptacle contact **125a** and the cartridge contact **124b**

is electrically connected to the receptacle contact **125b**. Furthermore, the one or more circuits necessary for operation of the vaporizer device **100** can be completed by insertion of the vaporizer cartridge **120** in the cartridge receptacle **118** in a second rotational orientation such cartridge contact **124a** is electrically connected to the receptacle contact **125b** and cartridge contact **124b** is electrically connected to the receptacle contact **125a**.

[0117] In one example of an attachment structure for coupling the vaporizer cartridge **120** to the vaporizer body **110**, the vaporizer body **110** includes one or more detents (for example, dimples, protrusions, etc.) protruding inwardly from an inner surface of the cartridge receptacle **118**, additional material (such as metal, plastic, etc.) formed to include a portion protruding into the cartridge receptacle **118**, and/or the like. One or more exterior surfaces of the vaporizer cartridge **120** can include corresponding recesses (not shown in FIG. 1A) that can fit and/or otherwise snap over such detents or protruding portions when the vaporizer cartridge **120** is inserted into the cartridge receptacle **118** on the vaporizer body **110**. When the vaporizer cartridge **120** and the vaporizer body **110** are coupled (e.g., by insertion of the vaporizer cartridge **120** into the cartridge receptacle **118** of the vaporizer body **110**), the detents or protrusions of the vaporizer body **110** can fit within and/or otherwise be held within the recesses of the vaporizer cartridge **120**, to hold the vaporizer cartridge **120** in place when assembled. Such an assembly can provide enough support to hold the vaporizer cartridge **120** in place to ensure good contact between the cartridge contacts **124a** and **124b** and the receptacle contacts **125a** and **125b**, while allowing release of the vaporizer cartridge **120** from the vaporizer body **110** when a user pulls with reasonable force on the vaporizer cartridge **120** to disengage the vaporizer cartridge **120** from the cartridge receptacle **118**. It will be understood that other configurations for coupling of a vaporizer cartridge **120** and a vaporizer body **110** are within the scope of the current subject matter, for example as discussed in more detail herein.

[0118] In some implementations, the vaporizer cartridge **120**, or at least an insertable end of the vaporizer cartridge **120** configured for insertion in the cartridge receptacle **118**, can have a non-circular cross section transverse to the axis along which the vaporizer cartridge **120** is inserted into the cartridge receptacle **118**. For example, the non-circular cross section can be approximately rectangular, approximately elliptical (i.e., have an approximately oval shape), non-rectangular but with two sets of parallel or approximately parallel opposing sides (i.e., having a parallelogram-like shape), or other shapes having rotational symmetry of at least order two. In this context, approximate shape indicates that a basic likeness to the described shape is apparent, but that sides of the shape in question need not be completely linear and vertices need not be completely sharp. Rounding of both or either of the edges or the vertices of the cross-sectional shape is contemplated in the description of any non-circular cross section referred to herein.

[0119] The cartridge contacts **124a** and **124b** and the receptacle contacts **125a** and **125b** can take various forms. For example, one or both sets of contacts can include conductive pins, tabs, posts, receiving holes for pins or posts, or the like. Some types of contacts can include springs or other features to facilitate better physical and electrical contact between the contacts on the vaporizer cartridge **120** and the vaporizer body **110**. The electrical contacts can optionally be gold-plated, and/or include other materials.

[0120] Further to the discussion above regarding the electrical connections between the vaporizer cartridge **120** and the vaporizer body **110** being reversible such that at least two rotational orientations of the vaporizer cartridge **120** in the cartridge receptacle **118** are possible, in some embodiments of the vaporizer device **100**, the shape of the vaporizer cartridge **120**, or at least a shape of the insertable end of the vaporizer cartridge **120** that is configured for insertion into the cartridge receptacle **118**, can have rotational symmetry of at least order two. In other words, the vaporizer cartridge **120** or at least the insertable end of the vaporizer cartridge **120** can be symmetrical upon a rotation of 180° around an axis along which the vaporizer cartridge **120** is inserted into the cartridge receptacle **118**. In such a configuration, the circuitry of the vaporizer

device **100** can support identical operation regardless of which symmetrical orientation of the vaporizer cartridge **120** occurs.

[0121] Some aspects of the current subject matter relate to a vaporizer heater that utilizes a nonlinear positive temperature coefficient of resistivity (PTCR) heating element, also referred to as a PTCR heater, for use as a convective heater, such as in any of the vaporizer embodiments described herein. In such a convective heater for a vaporizer, air is heated by the heating element and passed over or through a vaporizable material to form a vapor and/or aerosol for inhalation. In some implementations, the vaporizable material may include a solid vaporizable material (e.g., loose-leaf materials commonly utilized in heat-not-burn (HNB) vaporizers) and/or a liquid vaporizable material (e.g., pre-filled cartridges, pods, and the like). A PTCR heating element (or alternatively, other heating elements consistent with the current disclosure) used for convective heating can enable more uniform heating of the vaporizable material. Improved uniformity in heating can provide a number of advantages, including avoiding differential temperature within vaporizable materials that act as an insulator, prevention of contamination of the heating element, and the like. And because the heating element can be formed from PTCR material, the heating element can be temperature self-limiting and, given a known range of applied voltages, will not heat beyond a specific temperature, thereby avoiding formation of unwanted, and potentially dangerous, chemical byproducts. A PTCR heating element may also optionally be implemented without the need for a temperature control circuit provided that the transition temperature of the PTCR material is selected to be capable of delivering heated air at a desired target operating temperature for the vaporizable material.

[0122] The thermal power generation within an isotropic PTCR material can be characterized such that, for every control volume $\partial x, \partial y, \partial z$ within an isotropic PTCR material subject to a voltage gradient ∇V , the control volume $\partial x, \partial y, \partial z$ will heat to a temperature within the PTCR transition zone and hold that temperature within a wide range of ∇V as illustrated in FIG. 6. Thermal power generation can be expressed as: $P = f \cdot \text{sub.vol}(\nabla V) \cdot \text{sup.2} / \rho \cdot d\text{vol}$, where P is thermal power generation, vol is the control volume (e.g., $\partial x, \partial y, \partial z$), and ρ is resistivity.

[0123] By utilizing a PTCR heating element some implementations can enable temperature to be controlled over a range of applied voltages and without the need for temperature sensors, electronic circuitry, microprocessors, and/or algorithms providing power control to the heating element.

[0124] As used herein, the term solid vaporizable material generally refers to vaporizable material that includes solid materials. For example, some vaporizer devices heat materials having origins as plant leaves or other plant components in order to extract plant specific flavor aromatics and other products as aerosol. These plant materials may be chopped and blended into a homogenized construct with a variety of plant products that may include tobacco, in which case nicotine and/or nicotine compounds may be produced and delivered in aerosol form to the user of such a vaporizer device. The homogenized construct may also include vaporizable liquids such as propylene glycol and glycerol in order to enhance the vapor density and aerosol produced when heated. In order to avoid production of unwanted harmful or potentially harmful constituents (HPHCs) vaporizer devices of this type benefit from heaters having temperature control means. Such vaporizer devices that heat plant leaves or homogenized construct as described above such that temperatures are kept below combustion levels are generally referred to as heat not burn (HNB) devices.

[0125] As used herein, the term liquid vaporizable material generally refers to vaporizable material without solid materials. The liquid vaporizable material can include, for example, a liquid, a solution, a wax, or any other form as may be compatible with use of a specific vaporizer device. In some implementations, a liquid vaporizable material can include any form suitable to utilize a wick or wicking element to draw the vaporizable material into a vaporization chamber.

[0126] Vaporizer devices operate by heating the vaporizable material to an appropriate temperature to create an aerosol but without burning or charring of the vaporizable material. One class vaporizer device is more sophisticated in that it utilizes relatively tight temperature control in order

to prevent overheating and the related formation of HPHCs. Such sophistication, typically requiring electronic circuitry including a microprocessor, is typically difficult in HNB devices because of the inherent non-uniformity and related spatially inconsistent thermal properties of the vaporizable materials to be heated. This results in over temperature regions and potential HPHC production. And some existing solution fail to control local temperatures within vaporizer devices, resulting in a high probability of producing vaporizable material over temperature regions and HPHCs.

[0127] Another class of vaporizer device is simpler in that no means of temperature control is provided, such that the construction of the vaporizer device may be less expensive but includes a danger of overheating and thereby causing unwanted chemical byproducts.

[0128] In HNB vaporizer devices (e.g., where the vaporizable material is solid), some existing methods lack the ability to impose uniform temperatures for one or more of the following reasons. For example, to-be-heated solid vaporizable materials have low thermal diffusivity such that diffusion of high temperatures from a heating element into the solid vaporizable materials can be both slow and result in high thermal gradients. As a result, non-uniform heating can be an unavoidable consequence. As another example, if heating element temperature control is employed, the heating element temperature control typically addresses an average temperature such that heating of non-uniform solid vaporizable material via high temperatures within the heating element can result in high temperatures within the solid vaporizable materials. As yet another example, in order to allow for heating of the insulative materials, some existing HNB devices require preheating times that may equal or exceed 30 seconds with accompanying cost in both energy consumption, battery drain, and user inconvenience.

[0129] In vaporizer devices where fluids are vaporized by causing a heating element to come into contact with the fluids to be vaporized, contamination of the heating element can occur leading to potential for compromising performance. A solution to this problem can be to incorporate the heating element into a disposable part of the vaporizer such that the heating element is replaced with each new disposable part and thereby limiting, but not eliminating, heating element contamination.

[0130] To overcome the difficulty of uniform heating of vaporizable materials, some implementations of the current subject matter can provide for the preheating of air using one or a plurality of PTCR heating elements in conjunction with a heat exchanger. As a user draws air into a vaporizer device, the incoming air is heated to a controlled temperature as it passes over the heat exchanger and then passes through or over the to-be-heated vaporizable material. The vaporizable material can be a solid material (e.g., as in a HNB material) or a liquid (e.g., fluid with a porous wick). In some implementations, the air can pass over the heat exchanger and then pass over and/or through a porous wick saturated with liquid vaporizable material, then through a solid vaporizable material (e.g., a HNB material), and then to the user. In some implementations, geometry for influx of cooling air may be included between the wick and the user, for example, a balanced air inlet. In addition, the current subject matter can provide for a PTCR heater having intrinsic temperature control such, for a given range of supply voltage (which can be variable by a factor of ten or more in some implementations), a designed peak temperature will not be exceeded. Such an approach can result in improved uniform heating of vaporizable material as compared to some conventional approaches.

[0131] In addition, using this convective heating approach, the PTCR heating element (or some other, conventional heating element) can be placed upstream of the wick, fluid container, and/or vaporizable material, such that the PTCR heating element is completely removed from any disposable part of the mechanism. By including the PTCR heating element in a non-disposable portion of the vaporizer device, unnecessary waste can be avoided. It will be understood that while the description of the particular convective heating embodiment refers to use of a heating element formed from or including a PTCR material to thereby optionally be temperature self-limiting, other

heating elements (configured for convective, conductive, and/or radiative heating) are also within the scope of the current disclosure. One of ordinary skill in the art will understand that a PTCR element as described herein could be replaced by a conventional resistive heating element used in conjunction with electrical and/or electronic circuitry capable of providing some control over a temperature to which the heating element and/or air moving across it and/or vaporizable material heated by it is elevated.

[0132] FIG. 7 illustrates a block diagram of an embodiment of a vaporizer device **700**, according to some implementations of the current subject matter, which can provide for uniform heating of a vaporizable material **702** utilizing convective heating. The example system as shown in FIG. 7 includes an air inlet **706**, a PTCR heater with heat exchanger **742**, and a power source **712**, such as a battery, capacitor, and/or the like. The vaporizer device **700** can include a housing **732**, which can couple to one or more of the PTCR heater with heat exchanger **742** and the power source **712**. In some implementations, the vaporizer device **700** can optionally include a controller **704** and a pressure sensor **713**. In some implementations, the housing **732** can define the air inlet **706**.

[0133] The heater with heat exchanger may be a conventional heating element or may include a heating element formed of PTCR material, which is described in more detail below. A PTCR heater with heat exchanger **742** can be thermally coupled to the heating element and can be configured to transfer heat between the heating element and airflow that passes over and/or through the PTCR heater with heat exchanger **742**. The PTCR heater with heat exchanger **742** can include multiple heat exchangers, for example, coupled to different sides of the heating element, and can include a flow diverter for diverting the airflow through and/or over fins of the heat exchanger to improve heat transfer. A more detailed discussion of example PTCR heaters with heat exchanger **742** is found below with reference to FIGS. 14-33G.

[0134] The vaporizer device **700** can include a connector **715** (shown in FIGS. 9, 10, and 13) for coupling the housing **732** to one or more cartridges **720** that include a vaporizable material **702**. In some implementations, the cartridge **720** can include a mouthpiece **730**. In some implementations, the coupling is removable such that the cartridge **720** can be coupled and decoupled from the vaporizer device **700** via the connector **715** easily and by a user.

[0135] When the vaporizer device **700** is coupled to the cartridge **720**, the vaporizer device **700** and cartridge **720** can be arranged to define an airflow path from the air inlet **706**, though and/or over the PTCR heater with heat exchanger **742**, through the vaporizable material **702**, and out the mouthpiece **730**.

[0136] The controller **704** (e.g., a processor, circuitry, etc., capable of executing logic) may be configured for controlling delivery of heat to cause a vaporizable material **702** to be converted from a condensed form (e.g., a solid, a liquid, a solution, a suspension, a part of an at least partially unprocessed plant material, etc.) to the gas phase. The controller **704** may be part of one or more printed circuit boards (PCBs) consistent with certain implementations of the current subject matter.

[0137] The power source **712** can include any source suitable for applying electrical power to the PTCR heater with heat exchanger **742**. For example, the power source **712** can include a battery, a capacitor (even with resistor-capacitor (RC) decay), and/or the like. In some implementations, the power source **712** can provide a voltage, which can be chosen from a wide range of voltages. For example, in some implementations, the power source **712** can provide a voltage between 3 volts and 50 volts or more. In some implementations, voltage supplied to the PTCR heater with heat exchanger **742** can vary by an order of magnitude with little effect on the PTCR heater with heat exchanger **742** performance. In some implementations, the power source **712** can include multiple power sources, which can be selected based on operating conditions and/or desired vaporizer device performance.

[0138] In operation, a user can draw air through the mouthpiece **730** (e.g., puff), which can be detected by the controller **704** using the pressure sensor **713**. In response to detecting a puff, the controller **704** can cause application of current from the power source **712** to the PTCR heater with

heat exchanger **742**, thereby causing the PTCR heater with heat exchanger **742** to warm. Because the PTCR heater with heat exchanger **742** is formed of PTCR material, heating will be self-limiting and the heating element will not overheat.

[0139] The airflow passes through the air inlet **706** and over and/or through the PTCR heater with heat exchanger **742**, causing air in the airflow to uniformly heat. The uniformly heated air passes to the vaporizable material **702** causing the vaporizable material **702** to also heat uniformly and to form a vapor (gas). The vaporizable material **702** can include a liquid, a solution, a solid, a wax, or any other form. In some implementations, incoming air passing along the airflow path passes over, through, and the like, a region or chamber (e.g., an atomizer), where gas phase vaporizable material is entrained into the air.

[0140] The entrained gas-phase vaporizable material may condense as it passes through the remainder of the airflow path such that an inhalable dose of the vaporizable material in an aerosol form can be delivered to the mouthpiece **730** for inhalation by the user in the form of a vapor and/or aerosol. In some implementations, the cartridge **720** includes a balanced air inlet **762** that can serve to provide ambient temperature air for mixing with the heated air after the heated air passes through the vaporizable material (e.g., downstream from the PTCR heater with heat exchanger **742** and the vaporizable material **702**), thereby cooling the airflow prior to inhalation by the user. In some implementations, the balanced air inlet **762** is integrated with mouthpiece **730**.

[0141] Activation of the PTCR heater with heat exchanger **742** may be caused by one or more events. Such events may include an automatic detection of the puff based on one or more of signals generated by one or more sensors, such as the pressure sensor **713** or sensors disposed to detect pressure along the airflow path relative to ambient pressure (or optionally to measure changes in absolute pressure), one or more motion sensors of the vaporizer device, one or more flow sensors of the vaporizer device, or a capacitive lip sensor of the vaporizer device. Other events may include a response to detection of interaction of a user with one or more input devices (e.g., buttons or other tactile control devices of the vaporizer such as a manual toggle switch, pushbutton switch, pressure switch, and the like), receipt of signals from a computing device in communication with the vaporizer and/or via other approaches for determining that a puff is occurring or imminent.

[0142] As alluded to in the previous paragraph, a vaporizer device consistent with implementations of the current subject matter may be configured to connect (e.g., wirelessly or via a wired connection) to a computing device (or optionally two or more devices) in communication with the vaporizer. To this end, the controller **704** may include communication hardware. The controller **704** may also include a memory. A computing device can be a component of a vaporizer system that also includes the vaporizer device, and can include its own communication hardware, which can establish a wireless communication channel with the communication hardware of the vaporizer device. For example, a computing device used as part of a vaporizer system may include a general-purpose computing device (e.g., a smartphone, a tablet, a personal computer, some other portable device such as a smartwatch, or the like) that executes software to produce a user interface for enabling a user of the device to interact with a vaporizer. In other implementations of the current subject matter, such a device used as part of a vaporizer system can be a dedicated piece of hardware such as a remote control or other wireless or wired device having one or more physical or soft (e.g., configurable on a screen or other display device and selectable via user interaction with a touch-sensitive screen or some other input device like a mouse, pointer, trackball, cursor buttons, or the like) interface controls. The vaporizer device can also include one or more output features or devices for providing information to the user.

[0143] A computing device that is part of a vaporizer system as defined above can be used for any of one or more functions, such as controlling dosing (e.g., dose monitoring, dose setting, dose limiting, user tracking, etc.), controlling sessioning (e.g., session monitoring, session setting, session limiting, user tracking, and the like), controlling nicotine delivery (e.g., switching between nicotine and non-nicotine vaporizable material, adjusting an amount of nicotine delivered, and the

like), obtaining locational information (e.g., location of other users, retailer/commercial venue locations, vaping locations, relative or absolute location of the vaporizer itself, and the like), vaporizer personalization (e.g., naming the vaporizer, locking/password protecting the vaporizer, adjusting one or more parental controls, associating the vaporizer with a user group, registering the vaporizer with a manufacturer or warranty maintenance organization, and the like), engaging in social activities (e.g., games, social media communications, interacting with one or more groups, and the like) with other users, or the like. The terms “sessioning”, “session”, “vaporizer session,” or “vapor session,” are used generically to refer to a period devoted to the use of the vaporizer. The period can include a time period, a number of doses, an amount of vaporizable material, and/or the like.

[0144] In the example in which a computing device provides signals related to activation of the PTCR heater with heat exchanger **742**, or in other examples of coupling of a computing device with a vaporizer for implementation of various control or other functions, the computing device executes one or more computer instructions sets to provide a user interface and underlying data handling. In one example, detection by the computing device of user interaction with one or more user interface elements can cause the computing device to signal the vaporizer to activate the PTCR heater with heat exchanger **742** to a full operating temperature for creation of an inhalable dose of vapor/aerosol. Other functions of the vaporizer may be controlled by interaction of a user with a user interface on a computing device in communication with the vaporizer.

[0145] The temperature of a PTCR heater with heat exchanger **742** of a vaporizer may depend on a number of factors, including conductive heat transfer to other parts of the electronic vaporizer and/or to the environment, latent heat losses due to vaporization of a vaporizable material from the wicking element and/or the atomizer as a whole, and convective heat losses due to airflow (e.g., air moving across the heating element or the atomizer as a whole when a user inhales on the electronic vaporizer). As noted above, to reliably activate the PTCR heater with heat exchanger **742** or heat the PTCR heater with heat exchanger **742** to a desired temperature, a vaporizer may, in some implementations of the current subject matter, make use of signals from the pressure sensor **713** to determine when a user is inhaling. The pressure sensor **713** can be positioned in the airflow path and/or can be connected (e.g., by a passageway or other path) to an airflow path connecting the air inlet **706** for air to enter the vaporizer device and an outlet (e.g., in the mouthpiece **730**) via which the user inhales the resulting vapor and/or aerosol such that the pressure sensor **713** experiences pressure changes concurrently with air passing through the vaporizer device from the air inlet **706** to the air outlet. In some implementations of the current subject matter, the PTCR heater with heat exchanger **742** may be optionally activated in association with a user's puff, for example by automatic detection of the puff, for example by the pressure sensor **713** detecting a pressure change in the airflow path. In some implementations, a switch is an input device that may be used to electrically complete a circuit between the power source **712** and the PTCR heater with heat exchanger **742**. In some implementations, an input device that includes a relay, a solenoid, and/or a solid-state device that may be used to electrically complete a circuit between the power source and the PTCR heater with heat exchanger **742** to activate the vaporizer device.

[0146] Typically, the pressure sensor **713** (as well as any other sensors) can be positioned on or coupled (e.g., electrically or electronically connected, either physically or via a wireless connection) to the controller **704** (e.g., a printed circuit board assembly or other type of circuit board). To take measurements accurately and maintain durability of the vaporizer, it can be beneficial to provide a resilient seal to separate an airflow path from other parts of the vaporizer. The seal, which can be a gasket, may be configured to at least partially surround the pressure sensor **713** such that connections of the pressure sensor **713** to internal circuitry of the vaporizer are separated from a part of the pressure sensor **713** exposed to the airflow path. In an example of a cartridge-based vaporizer device, the seal or gasket may also separate parts of one or more electrical connections between a vaporizer body and a vaporizer cartridge. Such arrangements of a

gasket or seal in a vaporizer can be helpful in mitigating against potentially disruptive impacts on vaporizer components resulting from interactions with environmental factors such as water in the vapor or liquid phases, other fluids such as the vaporizable material, etc., and/or to reduce escape of air from the designed airflow path in the vaporizer. Unwanted air, liquid or other fluid passing and/or contacting circuitry of the vaporizer can cause various unwanted effects, such as alter pressure readings, and/or can result in the buildup of unwanted material, such as moisture, the vaporizable material, etc., in parts of the vaporizer where they may result in poor pressure signal, degradation of the optional pressure sensor or other components, and/or a shorter life of the vaporizer. Leaks in the seal or gasket can also result in a user inhaling air that has passed over parts of the vaporizer device containing or constructed of materials that may not be desirable to be inhaled.

[0147] In some implementations, the cartridge **720** can include a fibrous body for cooling the heated air after it passes through the vaporizable material **702**. As noted above, the vaporizable material **702** can include solid vaporizable material (e.g., HNB materials) and/or liquid vaporizable material (e.g., a liquid, a solution, and the like).

[0148] FIG. **8** illustrates a block diagram of an embodiment of a vaporizer device **700** and cartridge **720** with a liquid vaporizable material that can provide for uniform heating of the vaporizable material **702** utilizing convective heating. The vaporizable material **702** includes an atomizer including a porous wick **744** in fluidic communication with a fluid tank or fluid reservoir **740**. The porous wick **744** is located within the path of the airflow between the PTCR heater with heat exchanger **742** and the mouthpiece **730**. The porous wick **744** is located such that, in operation, heated air passes over and/or through the porous wick **744**, which is saturated with the vaporizable material **702**, causing vaporization of the liquid vaporizable material saturating the porous wick **744** thereby forming a vapor and/or aerosol. In some implementations, the porous wick **744** may allow air to enter the fluid reservoir **740** to replace the volume of liquid removed. In other words, capillary action pulls liquid vaporizable material into the porous wick **744** for vaporization by the heated air, and air may, in some implementations of the current subject matter, return to the fluid reservoir **740** through the wick to at least partially equalize pressure in the fluid reservoir **740**. Other approaches to allowing air back into the fluid reservoir **740** to equalize pressure are also within the scope of the current subject matter.

[0149] FIG. **9** illustrates a cross-sectional view of an example vaporizer device with liquid vaporizable material and FIG. **10** illustrates a cross-sectional view of an example vaporizer device with solid vaporizable material (e.g., HNB product).

[0150] In some implementations, the vaporizable material **702** can include both a liquid vaporizable material and a solid vaporizable material. For example, FIG. **11** illustrates a block diagram of an embodiment of a vaporizer device **700** and cartridge **720** with a liquid vaporizable material **702a** and a solid vaporizable material **702b** that can provide for uniform heating of the vaporizable material **702** utilizing convective heating. The cartridge **720** may include a fluid reservoir **740** containing the liquid vaporizable material **702a** within the fluid reservoir **740**, a porous wick **744** in fluidic communication with the liquid vaporizable material **702a**, and a solid vaporizable material **702b** located downstream (with respect to airflow) of the porous wick **744**. The porous wick **744** is arranged to receive the heated air from the PTCR heater with heat exchanger **742** to produce vaporized vaporizable material in the form of a vapor and/or an aerosol. The solid vaporizable material **702b** is arranged to receive the vaporized vaporizable material from the wick. The mouthpiece **730** is configured to receive the vaporized vaporizable material after the vaporized vaporizable material passes through the solid vaporizable material **702b**. By combining both the liquid vaporizable material **702a** and the solid vaporizable material **702b**, improved flavoring can be achieved. In addition, by utilizing convective heating via the PTCR heater with heat exchanger **742** for vaporizing both the liquid vaporizable material **702a** and the solid vaporizable material **702b**, only a single heater is required to heat both materials.

[0151] In some implementations, the liquid vaporizable material **702a** and the solid vaporizable material **702b** can be included in different cartridges. For example, FIG. **12** illustrates a block diagram of an embodiment of a vaporizer device **700** with multiple cartridges. A first cartridge **721** includes the liquid vaporizable material **702a** (including fluid reservoir **740** and porous wick **744**) and a second cartridge **722** includes the solid vaporizable material **702b** that can provide for uniform heating of the vaporizable material **702** utilizing convective heating. The first cartridge **721** can removably couple to the vaporizer device **700** and the second cartridge **722** can removably couple to the first cartridge **721**. As illustrated, the first cartridge **721** includes the fluid reservoir **740** (e.g., tank), the liquid vaporizable material **702a** within the fluid reservoir **740**, and the porous wick **744** in fluidic communication with the liquid vaporizable material **702a**. When the first cartridge **721** is coupled to the vaporizer device **700**, the porous wick **744** is arranged to receive the heated air from the PTCR heater with heat exchanger **742** to produce vaporized vaporizable material in the form of a vapor and/or an aerosol. The second cartridge **722** includes the solid vaporizable material **702b**, the balanced air inlet **762**, and the mouthpiece **730**. When the second cartridge **722** is coupled to the first cartridge **721**, the solid vaporizable material **702b** is arranged to receive the vaporized vaporizable material from the porous wick **744**, and the mouthpiece **730** is configured to receive the vaporized vaporizable material after the vaporized vaporizable material passes through the solid vaporizable material **702b**. In some implementations, the balanced air inlet **762** can provide ambient temperature air for cooling the heated air having passed through the solid vaporizable material **702b**. FIG. **13** illustrates a cross-sectional view of another embodiment of a vaporizer device **700** with both of a liquid vaporizable material **702a** and a solid vaporizable material **702b**.

[0152] This convective heating approach can provide several advantages for vaporizing solid materials (e.g., HNB materials), as compared to conventional conductive heating approaches. For example, instead of poor conduction into insulative material (e.g., solid vaporizable material) in a direction normal to airflow, producing volatiles and differential porosity of the to-be-heated vaporizable material, some implementations of the current subject matter can provide incoming preheated air that enters the vaporizable material uniformly as a wave uniformly covering the cross-section of the vaporizable material. Volatiles are then released, coincident with increase in porosity, in a direction parallel to the flow of heated air. As another example, because of the cross-sectional uniform release of volatiles and coincident increase of porosity, the problem of differential flow path can be eliminated in some implementations. As yet another example, the problem of deteriorating conductive heat transfer through the product can be removed in some implementations of the current subject matter. As yet another example, some implementations of the current subject matter can eliminate a previously required preheating period, such that the current subject matter may provide aerosol on-demand from heated vaporizable material.

[0153] Similarly, this convective heating approach can provide several advantages for vaporizing liquid vaporizable materials. For example, instead of applying heat directly to the liquid vaporizable material using a heater element in direct contact with the liquid vaporizable material, some implementations of the current subject matter can provide incoming preheated air as a wave uniformly covering the cross-section of the porous wick saturated with the fluid to be vaporized, thereby avoiding differential temperatures and potential for heating element contamination.

[0154] As another example, by placing the wick in close proximity and upstream (with respect to the airflow) to the solid vaporizable material (e.g., loose-leaf tobacco), unwanted aerosol condensation within the device can be minimized.

[0155] In addition, intrinsic temperature control behavior of the PTCR heater with heat exchanger can simplify the electrical power delivery circuitry in that no specific thermal feedback is required. Electrical power delivery circuitry to PTCR heater with heat exchanger can be further simplified by eliminating the need, typical of electrical power delivery systems, for the power source to provide relatively constant voltage. In some implementations, applied voltage may vary by more than an

order of magnitude with potentially significantly affecting resulting heater element temperatures.

[0156] An example PTCR heater with heat exchanger will now be described in more detail. PTCR includes semiconducting materials that possess an electrical resistivity that changes nonlinearly with increasing temperature. Typical PTCR material resistivity is relatively low while temperature remains below a temperature transition zone. Above the temperature transition zone, the PTCR material resistivity is higher than the resistivity of the same PTCR material at temperatures below the temperature transition zone. The resistivity change can be orders of magnitude increase over a temperature transition zone of 50 degrees Celsius or less.

[0157] A heating element can utilize nonlinear PTCR material to enable intrinsic temperature control. For example, a heating element at an ambient temperature can be connected to a power source providing a voltage gradient and resulting current flow. Because the resistivity of the heating element is relatively low at ambient temperature (e.g., ambient temperature is below the transition zone), current will flow through the heating element. As current flows through the nonlinear PTCR material, heat is generated by resistance (e.g., dissipation of electrical power). The generated heat raises the temperature of the heating element, thereby causing the resistivity of the heating element to change. When the temperature of the heating element reaches the transition zone, the resistivity increases significantly over a small temperature range. The change in resistivity can be caused by the physical properties of the material. For example, a phase transition may occur in the material. Such an increase in resistivity (resulting in an overall increase in resistance) reduces current flow such that heat generation is reduced. The transition zone includes a temperature at which there is an inflection point such that heat generation will be insufficient to further raise the temperature of the heating element, thereby limiting the temperature of the heating element. So long as the power source remains connected and supplying current, the heating element will maintain a uniform temperature with minimal temperature variance. In this instance the applied power to the PTCR heating element can be represented by the equation

$P_{sub.I} = V_{sup.2} / \text{Resistance}$. The heat loss of the PTCR heating element can be represented by $P_{sub.L}$, and includes any combination of conductive, convective, radiative, and latent heat. During steady-state operation $P_{sub.I} = P_{sub.L}$. As $P_{sub.L}$ increases, the temperature of the PTCR heating element drops thereby reducing the resistance thereby increasing the current flow through the PTCR heating element. As $P_{sub.L}$ decreases, the temperature of the PTCR heating element increases thereby increasing the resistance thereby decreasing the current flow through the PTCR heating element. As $P_{sub.L}$ approaches 0, the resistance of the PTCR heating element increase logarithmically. The operating temperature at which a PTCR heating element is limited can be affected by the element materials, element geometry, element resistivity as a function of temperature characteristics, power source, circuit characteristics (e.g., voltage gradient, current, time-variance properties), and the like.

[0158] FIG. 14 is an example graphical illustration showing an example resistivity vs. temperature curve for a nonlinear PTCR material. The vertical axis is logarithmic. A heating element constructed (e.g., formed) of a nonlinear PTCR material (referred to as a PTCR heater) can include advantageous characteristics. For example, with application of sufficient voltage gradient (e.g., ∇V), a PTCR heater will generate heat and increase in temperature until the transition zone is reached. In the curve illustrated in FIG. 14, the transition zone spans between temperatures $T_{sub.1}$ and $T_{sub.2}$. In the curve illustrated in FIG. 14, the resistivity versus temperature curve appears nonlinear between $T_{sub.1}$ and $T_{sub.2}$, but in other embodiments, the resistivity versus temperature curve may be near linear or linear or other shapes. At some temperature above $T_{sub.1}$ the resistivity of the nonlinear PTCR material will have increased to the point where further temperature increase will cease because the overall resistance will increase to a point such that current flow is limited. In other words, implementations of a PTCR heater can be considered to be temperature self-limiting and, given a known range of applied voltages, will not heat beyond a temperature just above the low point $T_{sub.1}$ of the temperature transition zone.

[0159] Performance of a PTCR heater can depend on PTCR behavior as in FIG. 14 and on heater geometry. A PTCR heater having relatively long and narrow geometry and with electrical contacts for applying differential voltage at each end of the longer dimension of the PTCR heater can be ineffective in that resistivity of nonlinear PTCR materials is typically too high at temperatures below $T_{sub.1}$. Nonlinear PTCR materials having steep transition zones where the temperature difference between $T_{sub.1}$ and $T_{sub.2}$ is less than 10° C. may cause all voltage drop to be within a small fraction of the length of said long and narrow geometry and given inevitable spatial nonuniformities within any material. Therefore, some implementations of a PTCR heater include an electrode construct for a PTCR heater such that a nonlinear PTCR material is provided within a parallel circuit. In some implementations that can provide improved uniformity in heating, the PTCR heater geometry can include a thin section of nonlinear PTCR material sandwiched between electrical conductors or electrically conductive coatings to which differential voltages may be applied.

[0160] FIG. 15 presents a table of resistivity vs. temperature curve data for the nonlinear PTCR semiconducting material illustrated in FIG. 14. In some implementations, the PTCR heating element has a resistivity of between 10 ohm-cm and 100 ohm-cm at 100° C. and a resistivity of between 50000 ohm-cm and 150000 ohm-cm at 260° C. In some implementations, the PTCR heating element has a resistivity of between 20 ohm-cm and 200 ohm-cm at 100° C. and a resistivity of between 100000 ohm-cm and 200000 ohm-cm at 265° C. In some implementations, the PTCR heating element has a resistivity of less than 100 ohm-cm at 100° C. and a resistivity greater than 100000 ohm-cm at 260° C. In some implementations, the PTCR heating element has a resistivity of less than 100 ohm-cm at 100° C. and a resistivity greater than 250000 ohm-cm at 275° C. In some implementations, the PTCR heating element has a resistivity of less than 100 ohm-cm at 100° C. and a resistivity greater than 300000 ohm-cm at 295° C. In some implementations, the PTCR heating element has a resistivity of between 10 ohm-cm and 110 ohm-cm at 25° C. and a resistivity of between 10 ohm-cm and 110 ohm-cm at 100° C. and a resistivity of between 100000 ohm-cm and 325000 ohm-cm at 280° C. In some implementations, the PTCR heating element has a resistivity of between 10 ohm-cm and 150 ohm-cm at 25° C. and a resistivity of between 10 ohm-cm and 150 ohm-cm at 100° C. and a resistivity of between 100000 ohm-cm and 350000 ohm-cm at 280° C. In some implementations, the PTCR heating element has a resistivity of between 10 ohm-cm and 200 ohm-cm at 25° C. and a resistivity of between 10 ohm-cm and 200 ohm-cm at 100° C. and a resistivity of between 100000 ohm-cm and 375000 ohm-cm at 280° C. In some implementations, the PTCR heating element has a resistivity of between 10 ohm-cm and 300 ohm-cm at 25° C. and a resistivity of between 10 ohm-cm and 300 ohm-cm at 100° C. and a resistivity of between 100000 ohm-cm and 400000 ohm-cm at 280° C. In some implementations, the PTCR heating element has a resistivity of between 10 ohm-cm and 400 ohm-cm at 25° C. and a resistivity of between 10 ohm-cm and 400 ohm-cm at 100° C. and a resistivity of between 100000 ohm-cm and 450000 ohm-cm at 280° C. In some implementations, the PTCR heating element has a resistivity of between 10 ohm-cm and 500 ohm-cm at 25° C. and a resistivity of between 10 ohm-cm and 500 ohm-cm at 100° C. and a resistivity of between 100000 ohm-cm and 500000 ohm-cm at 280° C. In some implementations, the PTCR heating element has a resistivity of between 50 ohm-cm and 110 ohm-cm at 25° C. and a resistivity of between 50 ohm-cm and 110 ohm-cm at 100° C. and a resistivity of between 150000 ohm-cm and 325000 ohm-cm at 280° C. In some implementations, the PTCR heating element has a resistivity of between 50 ohm-cm and 150 ohm-cm at 25° C. and a resistivity of between 50 ohm-cm and 150 ohm-cm at 100° C. and a resistivity of between 150000 ohm-cm and 350000 ohm-cm at 280° C. In some implementations, the PTCR heating element has a resistivity of between 50 ohm-cm and 200 ohm-cm at 25° C. and a resistivity of between 50 ohm-cm and 200 ohm-cm at 100° C. and a resistivity of between 150000 ohm-cm and 375000 ohm-cm at 280° C. In some implementations, the PTCR heating element has a resistivity of between 50 ohm-cm and 300 ohm-cm at 25° C. and a resistivity of between 50 ohm-

[illegible]

[illegible]

[illegible]

of between 50 ohm-cm and 400 ohm-cm at 100° C. and a resistivity of between 75000 ohm-cm and 250000 ohm-cm at 260° C. In some implementations, the PTCR heating element has a resistivity of between 50 ohm-cm and 500 ohm-cm at 50° C. and a resistivity of between 50 ohm-cm and 500 ohm-cm at 100° C. and a resistivity of between 75000 ohm-cm and 300000 ohm-cm at 260° C. In some implementations, the PTCR heating element has a resistivity of between 75 ohm-cm and 110 ohm-cm at 50° C. and a resistivity of between 90 ohm-cm and 110 ohm-cm at 100° C. and a resistivity of between 100000 ohm-cm and 125000 ohm-cm at 260° C. In some implementations, the PTCR heating element has a resistivity of between 75 ohm-cm and 150 ohm-cm at 50° C. and a resistivity of between 90 ohm-cm and 150 ohm-cm at 100° C. and a resistivity of between 100000 ohm-cm and 150000 ohm-cm at 260° C. In some implementations, the PTCR heating element has a resistivity of between 75 ohm-cm and 200 ohm-cm at 50° C. and a resistivity of between 90 ohm-cm and 200 ohm-cm at 100° C. and a resistivity of between 100000 ohm-cm and 175000 ohm-cm at 260° C. In some implementations, the PTCR heating element has a resistivity of between 75 ohm-cm and 300 ohm-cm at 50° C. and a resistivity of between 90 ohm-cm and 300 ohm-cm at 100° C. and a resistivity of between 100000 ohm-cm and 200000 ohm-cm at 260° C. In some implementations, the PTCR heating element has a resistivity of between 75 ohm-cm and 400 ohm-cm at 50° C. and a resistivity of between 90 ohm-cm and 400 ohm-cm at 100° C. and a resistivity of between 100000 ohm-cm and 250000 ohm-cm at 260° C. In some implementations, the PTCR heating element has a resistivity of between 75 ohm-cm and 500 ohm-cm at 50° C. and a resistivity of between 90 ohm-cm and 500 ohm-cm at 100° C. and a resistivity of between 100000 ohm-cm and 300000 ohm-cm at 260° C.

[0161] FIG. 16 illustrates another example PTCR resistivity versus temperature curve. In this example, the PTCR material has a density of 5700 kg/m³, a heat capacity of 520 J/kg K, and a thermal conductivity of 2.1 W/m K. The coefficient of resistivity begins to initially increase at a temperature after about 440 K and then sharply increases between 503 K and 518 K. At 298 K, the resistivity of the PTCR material forming the PTCR heating element is 0.168 ohm-m, and at 373 K the resistivity of the PTCR material forming the PTCR heating element is 0.105 ohm-m, and at 518 K the resistivity of the PTCR material forming the PTCR heating element is 3.669 ohm-m. In some example implementations, the PTCR material has a density between 5000 kg/m³ and 7000 kg/m³, a heat capacity between 450 J/kg K and 600 J/kg K, and a thermal conductivity between 1.5 W/m K and 3.0 W/m K.

[0162] FIG. 17A illustrates an example PTCR heating element 850 that can enable improved vaporizer heating. A thin section of nonlinear PTCR material 890 is shown in FIG. 17A, where nonlinear PTCR material 890 is sandwiched between electrically conductive layers 892, which in turn are attached to conductive leads 894 such that conductive leads 894 may have differential voltage applied. FIG. 17B illustrates a cross-sectional view of the PTCR heating element 850 of FIG. 17A.

[0163] In some example implementations, which can be effective in a vaporizer device using, for example, a fluid combination including propylene glycol and glycerol, a PTCR heating element 850 includes the geometry illustrated in FIG. 17A with nonlinear PTCR material thickness of 0.5 mm (height) and 5.0 mm (length and width) in the other dimensions. The nonlinear PTCR material electrical characteristics includes these values: T_{sub.1} value between 150° C. and 300° C., such as between 220° C. and 280° C.; resistivity at temperatures below T_{sub.1} between 0.01 Ohm-m and 100 Ohm-m, such as between 0.1 Ohm-m and 1 Ohm-m; resistivity change between T_{sub.1} and T_{sub.2} having an increase of a factor exceeding 10 such as exceeding 100; and temperature difference between T_{sub.1} and T_{sub.2} less than 200° C. such as less than 50° C.

[0164] FIG. 18A-FIG. 18E illustrate modeled temperatures of an embodiment of the PTCR heating element 850. In the illustrated example, the nonlinear PTCR material 890 includes a plate geometry with dimensions of 5 mm×5 mm×0.5 mm; the conductive layers 892 may be formed of silver (Ag) with dimensions of 5 mm×5 mm×0.025 mm; and the conductive leads 894 may be formed of

copper (CU) with dimensions of 12 mm×2 mm×0.2 mm. The nonlinear PTCR material **890** may include a PTCR resistivity versus temperature curve as illustrated in FIG. **31**, with a nonlinear transition zone of about 240° C. to about 300° C. A voltage of 3 to 6 volts was applied across the conductive leads **894** of the example PTCR heating element **850**. Under these circumstances, the example PTCR heating element **850** in open air with free convective airflow will increase in temperature as shown in the modeled sequence of FIG. **18A**-FIG. **18E**, which illustrate respectively 0.0, 0.2, 0.5, 1.0, and 2.0 seconds after application of the voltage differential. As illustrated, the temperature beyond 1.0 second is relatively uniform and the peak temperatures at the surface of conductive layers **892** is less than 270° C.

[0165] FIG. **19A**-FIG. **19F** illustrate modeled temperatures of another example of a PTCR heating element **850**. A gradient temperature scale is shown on the left side of each figure with red representing the hottest temperature of about 255° C. and continues through the colors of the visible light spectrum in order (e.g., red, orange, yellow, green, blue, and violet) to the coolest temperature of about 23° C. In each of the illustrated examples, the nonlinear PTCR material **890** includes a plate geometry with dimensions of about 5 mm×5 mm×0.5 mm; the conductive layers **892** were formed of silver (Ag) with dimensions of about 5 mm×5 mm×0.025 mm; and the conductive leads **894** were formed of copper (CU) with dimensions of about 12 mm×2 mm×0.2 mm. The plate geometry can include two parallel sides including conductive layers **892** with conductive leads **894** attached thereto. The conductive leads **894** are centrally attached to conductive layers **892** on each side of the PTCR heating element **850** with a connection **896**. In some implementations, the connection **896** is a clamp, a clip, a conductive paste, a high-temperature, lead-free solder, and/or combinations thereof.

[0166] FIG. **19A** illustrates the temperature 1.0 second after activation by applying a current to the PTCR heating element **850**. The conductive leads **894** (e.g., violet colored) are still about 25° C. The majority of the nonlinear PTCR material **890** and conductive layers **892** has increased in temperature to about 120° C., with the area including connection **896** in the center being slightly cooler at a temperature around 80° C.

[0167] FIG. **19B** illustrates the temperature 2.0 seconds after activation by applying a current to the PTCR heating element **850**. The conductive leads **894** (e.g., blue/green colored) have increased in temperature to about 90° C. The majority of the nonlinear PTCR material **890** and conductive layers **892** has increased in temperature to about 210° C., with the area including connection **896** in the center being cooler at a temperature around 160° C.

[0168] FIG. **19C** illustrates the temperature 3.0 seconds after activation by applying a current to the PTCR heating element **850**. The conductive leads **894** (e.g., green colored) have increased in temperature to about 140° C. The majority of the nonlinear PTCR material **890** and conductive layers **892** has increased in temperature to about 250° C., with the area including connection **896** in the center being cooler at a temperature around 200° C.

[0169] FIG. **19D** illustrates the temperature 4.0 seconds after activation by applying a current to the PTCR heating element **850**. The conductive leads **894** (e.g., green colored) have increased in temperature to about 160° C. The majority of the nonlinear PTCR material **890** and conductive layers **892** remains at temperature to about 250° C., with the area including connection **896** in the center being cooler at a temperature around 215° C.

[0170] FIG. **19E** illustrates the temperature 5.0 seconds after activation by applying a current to the PTCR heating element **850**. The conductive leads **894** (e.g., green/yellow colored) have increased in temperature to about 180° C. The majority of the nonlinear PTCR material **890** and conductive layers **892** remains at temperature to about 250° C., with the area including connection **896** in the center being slightly cooler at a temperature around 225° C.

[0171] FIG. **19F** illustrates the temperature 6.0 seconds after activation by applying a current to the PTCR heating element **850**. The conductive leads **894** (e.g., yellow colored) have increased in temperature to about 200° C. The majority of the nonlinear PTCR material **890** and conductive

layers **892** remains at temperature to about 250°C ., with the area including connection **896** in the center being just slightly cooler at a temperature around 235°C . FIG. **20** illustrates modeled temperatures of an example heater 6.0 seconds after application of a voltage in a free convective state.

[0172] FIG. **21A** illustrates a modeled surface temperature as a function of time for an example PTCR heating element. In the model, the surface temperature of the PTCR heating element starts at 25°C . (i.e. room temperature) at time zero. After an electrical current is applied, the surface temperature increases linearly for about 2 seconds to a temperature of about 225°C . After about 2 seconds, the rate of the temperature increase tapers off to a steady-state operating temperature of about 250°C . that is achieve about 3 seconds after activation. In the model, it was assumed that the nonlinear PTCR material is in a non-contact, free convective state, and the emitted radiation was measured from a distance. In some implementations, the PTCR heating element is heated to an operating temperature between 240°C . and 280°C . In some implementations, the PTCR heating element is heated to an operating temperature between 245°C . and 255°C . In some implementations, the PTCR heating element is heated to an operating temperature about 250°C .

[0173] FIG. **21B** illustrates a modeled and measured maximum surface temperatures as a function of time for an example PTCR heating element. Four measurements were repeated using an infrared camera to measure the maximum surface temperatures of the PTCR heating element as a function of time, which were then plotted against the model of the maximum surface temperature. In the model, it was assumed that the nonlinear PTCR material is in a non-contact, free convective state and the emitted radiation was measured from a distance. In each case, the maximum surface temperature of the PTCR heating element starts at about 25°C . (i.e. room temperature) at time zero. After an electrical current is applied, the maximum surface temperature increases linearly for about 2 seconds to a temperature of about 225°C . After about 2 seconds, the rate of the temperature increase tapers off to a steady-state operating temperature of about 250°C . that is achieve about 3 seconds after activation. In some implementations, the PTCR heating element is heated to an operating temperature between 240°C . and 280°C . In some implementations, the PTCR heating element is heated to an operating temperature between 245°C . and 255°C . In some implementations, the PTCR heating element is heated to an operating temperature about 250°C .

[0174] FIG. **21C** illustrates a modeled and measured average surface temperatures as a function of time for an example PTCR heating element. Four measurements were repeated using an infrared camera to measure the average surface temperatures of the PTCR heating element as a function of time, which were then plotted against the model of the average surface temperature. In the model, it was assumed that the nonlinear PTCR material is in a non-contact, free convective state and the emitted radiation was measured from a distance. In each case, the average surface temperature of the PTCR heating element starts at about 25°C . (i.e. room temperature) at time zero. After an electrical current is applied, the maximum surface temperature increases linearly for about 2 seconds to a temperature of about 225°C . After about 2 seconds, the rate of the temperature increase tapers off to a steady-state operating temperature of about 250°C . that is achieve about 3 seconds after activation. In some implementations, the PTCR heating element is heated to an operating temperature between 240°C . and 280°C . In some implementations, the PTCR heating element is heated to an operating temperature between 245°C . and 255°C . In some implementations, the PTCR heating element is heated to an operating temperature about 250°C .

[0175] FIG. **22** illustrates a transient current response as a function of time of an example PTCR heating element, consistent with implementations of the current subject matter. In the graph, the current is measured in amps, which increases at a near linear rate, and reaches a peak draw after about 1.5 seconds from activation. Thereafter, the resistance quickly increases to reduce the current draw as the PTCR heating element achieves a self-regulating operating temperature.

[0176] Uniform temperature can be a desirable performance attribute of PTCR heaters, providing a distinct advantage over series coil heaters, including series heaters having power input controlled

by temperature sensors, electronic circuits with microprocessors, and sophisticated algorithms dedicated to the purpose of temperature control. These existing series heaters can have overall power modulated in response to temperature measurement at a point or by average temperature estimated by overall electrical resistivity in combination with TCR (temperature coefficient of resistivity) of the typical series heating element. However, in some series heaters, temperatures within the series heater can vary by 40° C. or more because local differences in the thermal mass of the surrounding medium, and local differences in losses to the surrounding medium, lead to variations in the local resistivity along the series heater.

[0177] In some implantations, a PTCR heating element **850** constructed with material having a nonlinear PTCR resistivity vs. temperature curve the same or similar to that shown in FIG. **14**, with parallel geometry such as that shown in FIG. **17A-17B**, and with an adequate (e.g., 3V to 6V) differential voltage applied to conductive leads **894**, each of a given control volume within such a PTCR heater will have a temperature within a narrow range, typically less than 10° C. This can be achieved even with differential thermal loading. The less than 10° C. range can be tailored for vaporization by controlling the materials and geometric arrangement of the PTCR heating element. [0178] Alternative PTCR heater designs and geometries are possible.

[0179] In some implementations, the PTCR heater can include a heat exchanger for the purpose of preheating air entering and passing through vaporizable materials. FIG. **23** is a perspective view of an example PTCR heater with heat exchanger assembly **942**. The PTCR heater with heat exchanger assembly **942** may include a PTCR heating element **950** including a PTCR material **934**, and a heat exchanger including heat exchanger elements **936** that can enable convective heating and improved uniform heating of vaporizable materials.

[0180] The PTCR heater with heat exchanger assembly **942** (also referred to as a rectangular PTCR air heater) includes the PTCR material **934** sandwiched between electrically conductive layers **992**. In contact with the PTCR material **934** are the heat exchanger elements **936**, which can be made of aluminum or other conductive material extrusion. Surrounding the heat exchanger elements **936** is a heater cover **946**.

[0181] FIG. **24** is an exploded view of a rectangular embodiment of a PTCR insert **980**.

[0182] The PTCR insert **980** includes the PTCR heater with heat exchanger assembly **942**, a disposable rectangular vaporizable material product **902** with a rectangular product cover **938**. In some implementations, the vaporizable material product **902** and the product cover **938** can include a disposable containing a solid vaporizable material. In some implementations, the vaporizable material product **902** and the product cover **938** can include a disposable liquid cartridge (e.g., pod) containing a liquid vaporizable material and wick. FIG. **25** illustrates a perspective view of an assembled embodiment of the PTCR insert **980**.

[0183] The current subject matter is not limited to rectangular geometries. For example, alternative designs of a PTCR heater with heat exchanger assembly **942** and/or PTCR insert **980** may depart from planar geometry in many possible configurations produced by extrusion or injection molding. For example, FIG. **26** is a perspective view of an example PTCR heating element **950** with cylindrical geometry. The example PTCR heating element **950** includes a cylindrical embodiment of the PTCR heating element **950** with cylindrical surface conductive layers **992**.

[0184] FIG. **27** is an exploded view illustrating an example cylindrical PTCR heater with heat exchanger assembly **942**, which includes the PTCR heating element **950**, external cylindrical heat exchanger **937**, internal cylindrical heat exchanger **935**, cylindrical flow diverter **998**, and a heater cover **946**. FIG. **28** is a perspective view of the example assembled cylindrical PTCR heater with heat exchanger assembly **942**. FIG. **29** is a perspective view of a cylindrical embodiment of the PTCR insert **980** with the external covers and cylindrical flow diverter removed, thereby showing orientation of the cylindrical PTCR heater with heat exchanger assembly **942**, external cylindrical heat exchanger **937**, and internal cylindrical heat exchanger **935** aligned with a cylindrical embodiment of the vaporizable material product **902**.

[0185] FIG. 30 is a perspective view of the example cylindrical PTCR heater with heat exchanger assembly 942 including the PTCR heating element 950, external cylindrical heat exchanger 937, internal cylindrical heat exchanger 935, cylindrical flow diverter 998, heater cover 946, and a cylindrical product cover 938 (which, in FIG. 23, obscures the vaporizable material product 902). [0186] FIG. 31 illustrates an example graphical illustration of the logarithm of resistivity of an example cylindrical vaporization device with PTCR heater as a function of temperature. The performance illustrated in FIG. 31 is according to example calculations characterizing a performance of an example implementation of a cylindrical PTCR heater with heat exchanger assembly 942. The example cylindrical PTCR heater with heat exchanger assembly 942 is a HNB device, with HNB product, treated in the calculation as a porous medium, with specific area by mass $S_{\text{sub.m}} \cong 10000 \text{ cm}^2/\text{g}$, density $\rho \cong 300 \text{ kg/m}^3$. Convective heat transfer constant $h = 2.0 \text{ W/m}^2\text{K}$. Surface area by volume can be calculated as $S_{\text{vol}} = S_{\text{sub.m}} \times \rho = 10000 \text{ cm}^2/\text{g} \times 1000 \text{ g/kg} \times \text{m}^3/1000 \text{ cm}^3$, and $S_{\text{vol}} = 1000 \text{ m}^2/\text{kg}$ from which volumetric heat exchange coefficient $v = hp (S_{\text{vol}}) = 6.0 \text{ E5 W/m}^3\text{K}$.

[0187] For the calculations, ambient conditions were 20.05° C. at standard pressure of 1 atmosphere. Input airflow rate was constant at 1.4 l/m, applied voltage was constant 3.7 volts across opposing electrically conductive layers 992. No electric current restrictions were applied beyond PTCR behavior shown in FIG. 26.

[0188] The calculated cylindrical vaporization device with PTCR heater included electrically conductive layers 992 that were silver, external cylindrical heat exchanger 937 and internal cylindrical heat exchanger 935 that were aluminum extrusions, cylindrical flow diverter 998 and heater cover 946 were polytetrafluoroethylene (PTFE), and product cover 938 was paper.

[0189] FIG. 32 is a cross-sectional graphical illustration showing temperature simulations of the example implementation of the cylindrical vaporization device with PTCR heater described above with respect to FIG. 33. FIGS. 33A-33G illustrate example cross-sectional graphical illustrations showing transient response of temperature as color for the example implementation of the cylindrical vaporization device with PTCR heater. FIGS. 33A-33G demonstrate that temperatures everywhere never exceed 280° C., well below combustion temperatures. It can also be seen in FIGS. 33A-33G that heating of solid vaporizable material proceeds in a wave from upstream to downstream such that cross-sectional hot spots and resulting differential porosity voids are eliminated.

Terminology

[0190] When a feature or element is herein referred to as being “on” another feature or element, it can be directly on the other feature or element or intervening features and/or elements can also be present. In contrast, when a feature or element is referred to as being “directly on” another feature or element, there are no intervening features or elements present. It will also be understood that, when a feature or element is referred to as being “connected”, “attached” or “coupled” to another feature or element, it can be directly connected, attached or coupled to the other feature or element or intervening features or elements can be present. In contrast, when a feature or element is referred to as being “directly connected”, “directly attached” or “directly coupled” to another feature or element, there are no intervening features or elements present.

[0191] Although described or shown with respect to one embodiment, the features and elements so described or shown can apply to other embodiments. It will also be appreciated by those of skill in the art that references to a structure or feature that is disposed “adjacent” another feature can have portions that overlap or underlie the adjacent feature.

[0192] Terminology used herein is for the purpose of describing particular embodiments and implementations only and is not intended to be limiting. For example, as used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise.

[0193] In the descriptions above and in the claims, phrases such as “at least one of” or “one or

more of may occur followed by a conjunctive list of elements or features. The term “and/or” may also occur in a list of two or more elements or features. Unless otherwise implicitly or explicitly contradicted by the context in which it is used, such a phrase is intended to mean any of the listed elements or features individually or any of the recited elements or features in combination with any of the other recited elements or features. For example, the phrases “at least one of A and B;” “one or more of A and B;” and “A and/or B” are each intended to mean “A alone, B alone, or A and B together.” A similar interpretation is also intended for lists including three or more items. For example, the phrases “at least one of A, B, and C;” “one or more of A, B, and C;” and “A, B, and/or C” are each intended to mean “A alone, B alone, C alone, A and B together, A and C together, B and C together, or A and B and C together.” Use of the term “based on,” above and in the claims is intended to mean, “based at least in part on,” such that an unrecited feature or element is also permissible.

[0194] Spatially relative terms, such as “forward”, “rearward”, “under”, “below”, “lower”, “over”, “upper” and the like, may be used herein for case of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if a device in the figures is inverted, elements described as “under” or “beneath” other elements or features would then be oriented “over” the other elements or features. Thus, the exemplary term “under” can encompass both an orientation of over and under. The device can be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly. Similarly, the terms “upwardly”, “downwardly”, “vertical”, “horizontal” and the like are used herein for the purpose of explanation only unless specifically indicated otherwise.

[0195] Although the terms “first” and “second” may be used herein to describe various features/elements (including steps), these features/elements should not be limited by these terms, unless the context indicates otherwise. These terms may be used to distinguish one feature/element from another feature/element. Thus, a first feature/element discussed below could be termed a second feature/element, and similarly, a second feature/element discussed below could be termed a first feature/element without departing from the teachings provided herein.

[0196] As used herein in the specification and claims, including as used in the examples and unless otherwise expressly specified, all numbers can be read as if prefaced by the word “about” or “approximately,” even if the term does not expressly appear. The phrase “about” or “approximately” may be used when describing magnitude and/or position to indicate that the value and/or position described is within a reasonable expected range of values and/or positions. For example, a numeric value can have a value that is $\pm 0.1\%$ of the stated value (or range of values), $\pm 1\%$ of the stated value (or range of values), $\pm 2\%$ of the stated value (or range of values), $\pm 5\%$ of the stated value (or range of values), $\pm 10\%$ of the stated value (or range of values), etc. Any numerical values given herein should also be understood to include about or approximately that value, unless the context indicates otherwise. For example, if the value “10” is disclosed, then “about 10” is also disclosed. Any numerical range recited herein is intended to include all sub-ranges subsumed therein. It is also understood that when a value is disclosed that “less than or equal to” the value, “greater than or equal to the value” and possible ranges between values are also disclosed, as appropriately understood by the skilled artisan. For example, if the value “X” is disclosed the “less than or equal to X” as well as “greater than or equal to X” (e.g., where X is a numerical value) is also disclosed. It is also understood that the throughout the application, data is provided in a number of different formats, and that this data, represents endpoints and starting points, and ranges for any combination of the data points. For example, if a particular data point “10” and a particular data point “15” are disclosed, it is understood that greater than, greater than or equal to, less than, less than or equal to, and equal to 10 and 15 are considered disclosed as well as between 10 and 15. It is also understood that each unit between two particular units are also

disclosed. For example, if 10 and 15 are disclosed, then 11, 12, 13, and 14 are also disclosed.

[0197] Although various illustrative embodiments are described above, any of a number of changes can be made to various embodiments without departing from the teachings herein. For example, the order in which various described method steps are performed may often be changed in alternative embodiments, and in other alternative embodiments, one or more method steps may be skipped altogether. Optional features of various device and system embodiments may be included in some embodiments and not in others. Therefore, the foregoing description is provided primarily for exemplary purposes and should not be interpreted to limit the scope of the claims.

[0198] One or more aspects or features of the subject matter described herein can be realized in digital electronic circuitry, integrated circuitry, specially designed application specific integrated circuits (ASICs), field programmable gate arrays (FPGAs) computer hardware, firmware, software, and/or combinations thereof. These various aspects or features can include implementation in one or more computer programs that are executable and/or interpretable on a programmable system including at least one programmable processor, which can be special or general purpose, coupled to receive data and instructions from, and to transmit data and instructions to, a storage system, at least one input device, and at least one output device. The programmable system or computing system can include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

[0199] These computer programs, which can also be referred to programs, software, software applications, applications, components, or code, include machine instructions for a programmable processor, and can be implemented in a high-level procedural language, an object-oriented programming language, a functional programming language, a logical programming language, and/or in assembly/machine language. As used herein, the term “machine-readable medium” refers to any computer program product, apparatus and/or device, such as for example magnetic discs, optical disks, memory, and Programmable Logic Devices (PLDs), used to provide machine instructions and/or data to a programmable processor, including a machine-readable medium that receives machine instructions as a machine-readable signal. The term “machine-readable signal” refers to any signal used to provide machine instructions and/or data to a programmable processor. The machine-readable medium can store such machine instructions non-transitorily, such as for example as would a non-transient solid-state memory or a magnetic hard drive or any equivalent storage medium. The machine-readable medium can alternatively or additionally store such machine instructions in a transient manner, such as for example, as would a processor cache or other random access memory associated with one or more physical processor cores.

[0200] The examples and illustrations included herein show, by way of illustration and not of limitation, specific embodiments in which the subject matter may be practiced. As mentioned, other embodiments may be utilized and derived there from, such that structural and logical substitutions and changes may be made without departing from the scope of this disclosure. Such embodiments of the inventive subject matter may be referred to herein individually or collectively by the term “invention” merely for convenience and without intending to voluntarily limit the scope of this application to any single invention or inventive concept, if more than one is, in fact, disclosed. Thus, although specific embodiments have been illustrated and described herein, any arrangement calculated to achieve the same purpose may be substituted for the specific embodiments shown. This disclosure is intended to cover any and all adaptations or variations of various embodiments. Combinations of the above embodiments, and other embodiments not specifically described herein, will be apparent to those of skill in the art upon reviewing the above description. Use of the term “based on,” herein and in the claims is intended to mean, “based at least in part on,” such that an unrecited feature or element is also permissible.

[0201] The subject matter described herein can be embodied in systems, apparatus, methods, and/or

articles depending on the desired configuration. The implementations set forth in the foregoing description do not represent all implementations consistent with the subject matter described herein. Instead, they are merely some examples consistent with aspects related to the described subject matter. Although a few variations have been described in detail herein, other modifications or additions are possible. In particular, further features and/or variations can be provided in addition to those set forth herein. For example, the implementations described herein can be directed to various combinations and subcombinations of the disclosed features and/or combinations and subcombinations of several further features disclosed herein. In addition, the logic flows depicted in the accompanying figures and/or described herein do not necessarily require the particular order shown, or sequential order, to achieve desirable results. Other implementations may be within the scope of the following claims.

Claims

1. A vaporizer device for generating a combined inhalable aerosol, the vaporizer device comprising: a body including an airflow pathway extending therethrough; a first cartridge receptacle configured to receive a first cartridge, the first cartridge being configured to contain a first vaporizable material; a second cartridge receptacle configured to receive a second cartridge, the second cartridge configured to contain a second vaporizable material; a first heater in communication with the first cartridge receptacle for heating the first vaporizable material and forming a first inhalable aerosol; and a second heater in communication with the second cartridge receptacle for heating the second vaporizable material and forming a second inhalable aerosol, wherein the airflow pathway extends adjacent the first heater and the second heater and is configured to allow the first inhalable aerosol and the second inhalable aerosol to combine to form the combined inhalable aerosol for inhalation by a user from an outlet of the airflow pathway.
2. The vaporizer device of claim 1, further comprising a third heater positioned adjacent the airflow pathway at a position upstream from at least one of the first heater and the second heater.
3. The vaporizer device of claim 1, wherein the first vaporizable material, the second vaporizable material, or both comprises a liquid.
4. The vaporizer device of claim 1, wherein the first vaporizable material, the second vaporizable material, or both comprises a non-liquid.
- 5.-6. (canceled)
7. The vaporizer device of claim 3, wherein the first vaporizable material comprises a first liquid and the second vaporizable material comprises a second liquid that is different from the first liquid.
8. The vaporizer device of claim 4, wherein the first vaporizable material comprises a first non-liquid and the second vaporizable material comprises a second non-liquid, which is different from the first non-liquid.
9. The vaporizer device of claim 1, wherein the first heater, the second heater, or both includes a nonlinear positive temperature coefficient of resistance material.
10. A method of operating a vaporizer device for generating a combined inhalable aerosol, the method comprising: heating a first vaporizable material and forming a first inhalable aerosol, the heating performed by a first heater of the vaporizer device, the vaporizer device comprising: a body including an airflow pathway extending therethrough; a first cartridge receptacle configured to receive a first cartridge, the first cartridge being configured to contain the first vaporizable material, the first heater being in communication with the first cartridge receptacle for heating the first vaporizable material; a second cartridge receptacle configured to receive a second cartridge, the second cartridge configured to contain a second vaporizable material; and a second heater in communication with the second cartridge receptacle for heating the second vaporizable material and forming a second inhalable aerosol, wherein the airflow pathway extends adjacent the first heater and the second heater and is configured to allow the first inhalable aerosol and the second

inhalable aerosol to combine to form the combined inhalable aerosol for inhalation by a user from an outlet of the airflow pathway; heating the second vaporizable material and forming the second inhalable aerosol; and combining the first inhalable aerosol with the second inhalable aerosol to form the combined inhalable aerosol for inhalation by the user.

11.-40. (canceled)

41. The method of claim 10, further comprising heating an airflow traveling within the airflow pathway with a third heater positioned adjacent the airflow pathway.

42. The vaporizer device of claim 1, wherein the first heater is a first heater type and the second heater is a second heater type, and wherein the first heater type is different than the second heater type.

43. The vaporizer device of claim 1, wherein the first heater and the second heater are independently controlled in temperature, amount of time, or both.

44. The vaporizer device of claim 1, wherein the airflow pathway comprises a first pathway extending adjacent the first heater and a second pathway extending adjacent the second heater, wherein the first pathway and the second pathway converge to combine the first inhalable aerosol and the second inhalable aerosol.

45. The vaporizer device of claim 1, wherein the airflow pathway extends sequentially from the first heater to the second heater.

46. The vaporizer device of claim 1, further comprising a filter positioned within the airflow pathway, wherein the filter contains an inhalable extract.

47. The vaporizer device of claim 46, wherein the filter is downstream of at least the first heater.

48. The vaporizer device of claim 1, wherein the first cartridge is releasably coupled to the first cartridge receptacle and the second cartridge is releasably coupled to the second cartridge receptacle.

49. The vaporizer device of claim 2, wherein the third heater is positioned upstream from the first heater, the second heater, or both.

50. The vaporizer device of claim 1, further comprising a mouthpiece comprising the outlet of the airflow pathway, wherein the airflow pathway extends between an inlet and the outlet.

51. A vaporizer device for generating a combined inhalable aerosol, the vaporizer device comprising: at least one cartridge receptacle configured to receive at least one cartridge, the at least one cartridge being configured to contain a vaporizable material; a first heater in communication with the at least one cartridge receptacle for heating the vaporizable material and forming a first inhalable aerosol; a second heater in communication with the at least one cartridge receptacle for heating the vaporizable material and forming a second inhalable aerosol, and an airflow pathway extending adjacent to the first heater and the second heater and through the at least one cartridge receptacle, the airflow path configured to allow the first inhalable aerosol and the second inhalable aerosol to combine to form the combined inhalable aerosol for inhalation by a user from an outlet of the airflow pathway.

52. The vaporizer device of claim 51, wherein the vaporizable material comprises a first vaporizable material and a second vaporizable material, wherein the first heater is configured to heat the first vaporizable material, and the second heater is configured to heat the second vaporizable material.
