

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250285394

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Edwards; Warren Keith

SYSTEMS AND METHODS FOR MANAGING NETWORK DEVICES USING AUGMENTED REALITY

Abstract

Systems and methods are described herein for controlling network devices in an augmented reality environment. A user may point a second network device at a first network device to determine a network activity the first network device. The second network device may display a user control interface to enable the user to control the network activity of the first network device (e.g., a pinch gesture control). In response to receiving the user input, the second network device causes the modification of the network activity based on the user input.

Inventors: Edwards; Warren Keith (Atlanta, GA)

Applicant: Adeia Guides Inc. (San Jose, CA)

Family ID: 90060771

Appl. No.: 19/219285

Filed: May 27, 2025

Related U.S. Application Data

parent US continuation 17902590 20220902 parent-grant-document US 12340472 child US 19219285

Publication Classification

Int. Cl.: G06T19/00 (20110101); H04W4/02 (20180101); H04W4/20 (20180101); H04W4/33 (20180101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 17/902,590, filed on Sep. 2, 2022. The disclosures of the referenced application are hereby incorporated by reference herein in its entirety.

BACKGROUND

[0002] This disclosure is generally directed to systems and method for managing network devices using augmented reality. In particular, systems and methods are provided herein that allow for the detection of network devices using wireless communications and indicating a position of the network device in an augmented reality environment. Additionally, systems and methods provided herein allow for the controlling of such detected network devices using user input provided within the augmented reality environment.

SUMMARY

[0003] With the proliferation of internet of things (“IoT”) devices in the home, the challenge of managing these devices has increased. Not only are there more devices within a home, but oftentimes each of the devices require their own specialized app or interface for controlling the device, rather than a centralized management interface. For example, a smart speaker by one manufacturer may have a different control interface from a smart speaker made by a second manufacturer. Oftentimes, a household may contain multiples of a same device (such as a smart speaker in each room)—making it difficult for a user to locate and control a desired one of the multiple devices. Furthermore, many of the specialized applications and interfaces focus primarily at the application layer rather than lower layers of the network. For example, an application on a smart speaker may allow a user to control a streaming audio quality, but does not allow for network layer control of a network activity.

[0004] Additionally, troubleshooting the network devices is difficult as the applications oftentimes do not have capabilities for diagnosing network issues which may prevent the network device from functioning properly. For example, the control application of a network device may not provide an indication of a Wi-Fi signal strength, thereby making it difficult for a user to diagnose whether reduced bandwidth at a network device is due to a location of the network device within a home (e.g., low signal strength) or due to network congestion (e.g., other devices consuming network bandwidth). Accordingly, the specialized applications and interfaces fail to address problems around bandwidth allocation, wireless signal strength, management of data caps, etc. While some router management interfaces may allow for controlling lower layers of the network stack, these interfaces are difficult for a typical household user and do not allow for the easy identification and control of devices within the home. For example, it may be difficult for a user to identify which devices are consuming network traffic and to where the network traffic is going. Furthermore, many of these applications produce abstract interfaces which do not correspond well with a user's intuitive physical and spatial model of home networking.

[0005] To address the aforementioned problems, systems and methods are described herein for identifying, managing, and controlling network devices in an augmented reality environment. In one embodiment, the systems and methods described herein identify one or more network devices using augmented reality. The systems and methods described herein utilize the wireless radios (e.g., ultra-wide band (“UWB”) radios) of network devices to determine a position of a first network device relative to a position of a second network device.

[0006] The second network device may generate an image from the camera on a display of the

second device and indicates a position of the first network device within the image. In some instances, the second network device includes an optical see-through (OST) display that is at least partially transmissive of light and that enables a user to view objects in their environment, as though looking through a window. If desired, the first network device may be viewed through such an OST device. Alternatively, the display of the first network device may be a video see-through (VST) device that generates and displays a digital image that has been captured via a camera. In any event, the image may be generated, displayed, or provided in or near real-time, enabling the user to view his or her environment via a screen of a phone, for example. For example, the first network device may be a smart speaker located in a living room and the second network device may be a smartphone. When a user points the smartphone camera to the living room, the smartphone may display an image of the living room and may augment the image with a circle (or any other type of indication) at a location of the smart speaker within the image. The second network device (e.g., the smartphone) may additionally or alternatively display an overlay at the position of the first network device within the image that includes, for example, a network address (e.g., local area network address), a name of the smart speaker (e.g., a user assigned name of first network device), a network activity (e.g., a name of the network activity consuming the most bandwidth by the first network device), etc. In other embodiments, the second network device may determine whether the first network device is visible via a display of the second network device. For example, when the display is an OST, the second network device may determine, based on a UWB signal, whether the first network device is visible via the display of the second network device by determining a position of the first network device relative to the second network device and determining whether the position would be visible via the display of the second network device.

[0007] By using the UWB signal from the first network device to detect a relative position of first network device to the second network device and generating for display an indicator and/or an overlay at the relative position within the image and/or display, the systems and methods described herein enable a user to easily identify a desired network device using an augmented reality environment. Additionally, the systems and methods provided herein may enable a user to diagnose network issues. For example, the overlay may include an indication of the bandwidth being consumed by the device, and/or by an application running on the device.

[0008] A user may utilize the information depicted in the overlay to determine whether to control and/or modify a network parameter the network device. For example, a user may wish to limit an amount of bandwidth available to the smart speaker so that they user can consume more bandwidth on a laptop. The systems and methods provided herein may provide a graphical interface for a user to control a parameter of a network activity. For example, the second network device may display a graphical dial. When the second network device detects that the user is decreasing a value on the graphical dial, the second network device may cause the bandwidth allocated to the first network device to decrease (e.g., the second network device may decrease a bandwidth cap for the first network device or may decrease a quality of service (QOS) prioritization for the network activity).

[0009] In some embodiments, the systems and methods described herein relate to an augmented reality environment for controlling and managing a network activity of the network devices. For example, when the second network device detects that the first network device is within a visual field of the camera of the second network device (e.g., based on a UWB signal from the first network device), the second network device retrieves a network address of the first network device (e.g., a local area network address of the first network device). In some embodiments, based on the first network address, the second network device determines a network activity of the first network device. For example, the second network device may query a router for the network activity of the first network device based on the network address. In another example, the second network device may transmit a query to the first network device requesting information about the network activity. In response to the query, the router and/or first network device may provide the second network

device with an identification of the network activity (e.g., the response may include an indication of a bandwidth consumed by the first network device and an indication of what application is using the most bandwidth, and an indication of the source/destination of the network activity). The second network device may generate for display a status of a parameter of the network activity. For example, the second network device may generate for display the bandwidth that is currently being consumed by the second network device for the given application.

[0010] The second network device may generate for display a graphical interface for controlling the parameter of the network activity. For example, the second network device may generate for display a slider bar where the user can increase or decrease the bandwidth for the first network device based on the position of the slider. In response to receiving a user input via the graphical interface, the second network device may adjust the parameter of the network activity based on the user input. For example, the second network device may transmit a command to the router to throttle the bandwidth of the first network device in response to receiving an input via the bandwidth slider as described above. In another embodiment, the second network device may transmit the request to the application running on the first network device. For example, the second network device may transmit a request to adjust the bandwidth to a music streaming application running on the smart speaker.

[0011] In some aspects, the overlay is displayed in response to selecting the first network device within the image and/or display. For example, in response to selecting the first network device, the systems described herein may display information about the network activity of the first network device. The overlay may include an indication of the bandwidth used by the first network device, an application associated with the bandwidth consumption, and a line pointing to the first network device within an image and/or display, etc.

[0012] In some aspects, the first network device and the second network device comprise one or more wireless radios. The one or more wireless radios may include a UWB radio and a WIFI radio. The second network device may determine an approximate position of the first network device (e.g., a distance) relative to the second network device based on time of flight of a UWB signal from the first wireless radio of the first network device detected by the UWB radio of the second network device. In some embodiments, the UWB radio of the second network device may comprise one or more antennas for determining a position of the first network device relative to the second network device based on an angle of arrival of the signal. For example, when the second network device detects a UWB signal at the wireless radio of the second network device, the second network device may determine both the angle of arrival (e.g., to approximate direction) and the time of flight (e.g., to approximate distance) to calculate a relative position of a transmitting device (e.g., the first network device). In some embodiments, when an angle of arrival is used to approximate the direction of the first network device, the second network device may be able to determine the location of the first network device without the use of additional devices and/or servers.

[0013] In some embodiments, the second network device may determine the position of the first network device relative to the second network device using one or more peer devices by using, for example a two way ranging protocol. For example, a first peer device and a second peer device may compute a time of flight between a first signal sent from the first network device to the first peer device and a second signal sent from the first network device to the second peer device. Based on the different times of flights for the various signals from the first network device, the second network device may use the times of flights to triangulate the location of the first network device. In some embodiments, the peer devices may provide approximate distances to the first network device instead of the times of flight to triangulate the location of the first network device. For example, the first peer device and the second peer device may calculate respective distances to the first network device based on the computed times of flight and may provide the respective distances to the second network device.

[0014] In some embodiments, the second network device may determine the position of the first network device using, for example, a time difference of arrival protocol. For example, a first peer device and a second peer device may comprise synchronized clock signals. The first network device may transmit messages over the UWB radio at regular intervals. The first peer device and the second peer device may both receive the message at different times (e.g., because the first peer device and the second peer device are located at different distances to the first network device). The first peer device may compute a first timestamp indicating an arrival time of the message at the first peer device and the second peer device may compute a second timestamp indicating a second arrival time of the message at the second peer device. Both of the timestamps may be generated based on the synchronized clock. The timestamps may be transmitted to a server (e.g., over a Wi-Fi connection of the peer devices) that aggregates the timestamps from the peer devices having the synchronized clocks. Based on the timestamps, the server may compute an approximate location for the first network device (e.g., by triangulating the location of the first network device based on difference in time for the timestamps). In such embodiments, the second network device may retrieve the approximate position for the first network device from the server (e.g., by requesting the position over a Wi-Fi connection of the second network device).

[0015] In some aspects, the second network device may store the relative position of the first network device, the network address, and/or an identifier of the first network device in a database. The database may be stored locally (e.g., on the second network device or may be stored remote to the second network device, such as on a server). In such instances, other devices may access and/or update information about the first network device and/or add information about additional devices within the network. For example, a router may also comprise a UWB radio and may determine when a position of the first network device moves based on a UWB signal from the first network device received by the router. The router may update the database based on a detected location of the first network device.

[0016] In some aspects, the second network device may display indications of multiple devices detected within a visual range of the camera of the second device. For example, the second network device may detect a third network device (e.g., based on detecting a UWB signal from the third network device) and may determine a position of the third network device relative to the second network device. When the second network device determines that the third network device is within a visual field of the camera of the second network device (e.g., based on the determined position of the third network device relative to the second network device), the second network device may generate for display an indication of the third network device within the image and/or display. The indication may include, for example, a name of the second network device and a network address of the third network device (e.g., a network address of a WIFI connection of the third network device). In some embodiments, the indication for the third network device is displayed simultaneously with the indication for the first network device within a same virtual environment.

[0017] In some aspects, the second network device may display an indication of a network activity of the third network device. For example, the second network device may determine a network activity of the third network device (e.g., determine that the third network device is streaming a movie) and may generate for display an indication of the network activity. For example, the second network device may generate for display an icon corresponding to the streaming application and a bandwidth associated with the stream. The second network device may display the icon and indication of the bandwidth in proximity to the third network device within the image and/or display (e.g., next to the device as it appears within the image and/or display).

[0018] In some aspects, the second network device may determine that the network activity is between the first network device and the third network device and may generate for display an indication of the activity between the two devices. For example, the second network device may determine, based on network address of the network activity, that the first network device is casting

a video to the third network device. Based on determining that the first network device is communicating with the third network device, the second network device may, for example, display a connection between the first network device and the third network device. In some aspects, the second network device may select a speed of the animation proportional to the a bandwidth of the network traffic between the first network device and the third network device (e.g., a higher animation speed may indicate a greater bandwidth than a slower animation speed). In another example, the second network device may generate for display the connection at a certain width based on the bandwidth of the connection (e.g., a wider connection size may indicate a larger amount of bandwidth).

[0019] In some aspects, the second network device may receive a user interface interaction to modify the parameter of the network activity (e.g., a user interface interaction to change a bandwidth or to terminate communication between devices). For example, a user may input a pinch gesture to the displayed connection to modify the bandwidth. In response to receiving the pinch gesture, the second network device may modify the bandwidth of the network activity. Subsequent to modifying the parameter of the network activity, the second network device may display an updated status of the network activity (e.g., a display the modified bandwidth in the overlay).

[0020] In some aspects, the second network device may detect that the third network device comprises a wide area network (“WAN”) connection. For example, the second network device may determine that a network connection of the third network device is associated with a public IP address (e.g., that the third network device is a router with a WAN port). In response to determining that the third network device comprises a WAN connection, the second network device may visually distinguish the third network device from the first network device. For example, the third network device may be indicated as a router and may comprise a display of the network activity with devices outside of the household. For example, when a device is communicating outside of the network (e.g., via the WAN) the network address of the remote device may be visually distinguished from an address of a device within the LAN. In some embodiments, the second network device may display all of the network activities involving devices outside of the home in a panel as to not crowd the space around the third network device (e.g., the device with the WAN port).

[0021] In some aspects, a network device (e.g., the third network device) comprises storage circuitry configured to store, in a database, at least one of a source address, a destination address, a device name, a bandwidth, a priority, a duration, an access time, a network cap, and a service characterization of the network activity. In some aspects, the second device, when determining the network activity of the first network device, retrieves, from the database, the at least one of the source address, the device name, the destination address, the bandwidth, the priority, the duration, the access time, the network cap, and the service characterization of the network activity from the storage circuitry of the third network device. The second network device may include any of the information indicated above in an overlay and may allow a user to control any of such aspects via a user interface generated on a display of the second network device.

[0022] In some aspects, in response to detecting movement of the second network device (e.g., using an accelerometer or detecting a change in an image received from the camera), the second network device may determine an updated position of the first network device relative to the second network device. For example, the second network device may identify a second UWB signal from the first network device and may utilize the second UWB signal to determine an updated position of the first network device (e.g., based on the time of flights and angle of arrival of the signal).

Description

BRIEF DESCRIPTION OF DRAWINGS

[0023] The present disclosure, in accordance with one or more various embodiments, is described in detail with reference to the following figures. The drawings are provided for purposes of illustration only and merely depict typical or example embodiments. These drawings are provided to facilitate an understanding of the concepts disclosed herein and shall not be considered limiting of the breadth, scope, or applicability of these concepts. It should be noted that for clarity and ease of illustration these drawings are not necessarily made to scale.

[0024] The above and other objects and advantages of the disclosure may be apparent upon consideration of the following detailed description, taken in conjunction with the accompanying drawings, in which:

[0025] FIG. 1A and FIG. 1B shows exemplary embodiments of a network device in accordance with some embodiments of the present disclosure;

[0026] FIG. 2 shows an exemplary embodiment of an augmented reality environment for managing network devices, in an accordance with some embodiments of the present disclosure;

[0027] FIG. 3a shows an exemplary database for storing information about a device, in accordance with some embodiments of the present disclosure;

[0028] FIG. 3b shows an exemplary database for storing information about a network traffic in accordance with some embodiments of the present disclosure;

[0029] FIG. 4 shows an exemplary embodiment of a detailed view of information about a network device, in an accordance with some embodiments of the present disclosure;

[0030] FIG. 5A shows an exemplary embodiment of a user interface (UI) element representing a connection between multiple network devices, in an accordance with some embodiments of the present disclosure;

[0031] FIG. 5b shows an exemplary embodiment of an UI element indicating a network activity between devices, in accordance with some embodiments of the present disclosure;

[0032] FIG. 6 shows an exemplary embodiment of a detailed view of network activities of multiple devices, in an accordance with some embodiments of the present disclosure;

[0033] FIG. 7 shows an exemplary embodiment of controlling a network device using a gesture, in an accordance with some embodiments of the present disclosure;

[0034] FIG. 8 shows an exemplary embodiment of a network device, in accordance with some embodiments of the present disclosure;

[0035] FIG. 9 shows an exemplary network configuration, in accordance with some embodiments of the present disclosure;

[0036] FIG. 10 shows an exemplary process for discovering devices, in an accordance with some embodiments of the present disclosure;

[0037] FIG. 11 shows an exemplary process for indicating a location of a device, in an accordance with some embodiments of the present disclosure;

[0038] FIG. 12 shows an exemplary process for identifying a network activity, in an accordance with some embodiments of the present disclosure;

[0039] FIG. 13 shows an exemplary process for controlling a network device based on a user input, in an accordance with some embodiments of the present disclosure;

[0040] FIG. 14 shows an exemplary process for identifying network devices in an augmented reality environment, in an accordance with some embodiments of the present disclosure; and

[0041] FIG. 15 shows an exemplary process for controlling network devices in an augmented reality environment, in an accordance with some embodiments of the present disclosure.

DETAILED DESCRIPTION

[0042] Systems and methods are described herein for identifying, managing, and controlling network devices in an augmented reality environment. Generally speaking, a network device is any device capable of wired or wireless communication with other devices. For example, a user may

point a camera of an augmented reality (AR) device, such as a smartphone, smart glasses, an augmented reality headset, etc., at an environment. The AR device may be any device configured to display or provide an AR interface. The systems and methods described herein may identify network devices within the environment (e.g., a smart speaker and a smart TV) and may display an overlay at the position of the identified devices within an AR environment depicted on the AR device. For example, the AR device may comprise a UWB radio for detecting other devices with UWB radios (e.g., a smart speaker) within an environment. When the AR device detects another device having a UWB radio, the AR device may utilize a signal from the UWB radio of the other device to determine a position of the other device (e.g., the smart speaker) relative to the AR device (e.g., the smartphone). Upon determining the relative position of the identified device to the AR device, the AR device may determine a position of the identified device within the AR environment (e.g., determine where within an image and/or display the identified device is located). Upon determining where the identified device is located within the AR environment, the AR device may display an overlay at the position of the identified device within the AR environment. For example, the AR device may display an overlay near a position of the smart speaker within the AR environment. The overlay may indicate a name and/or network address of the smart speaker, a network activity of the smart speaker (e.g., indicate that the smart speaker is streaming music), a parameter of the network activity (e.g., a bandwidth), etc. In some embodiments, the overlay may include information about the network activity such that the user can diagnose network issues and/or control network devices. For example, the overlay may comprise information about a Wi-Fi signal strength at the smart speaker or an amount of bandwidth being consumed by the smart speaker for the music streaming network activity and/or other network activities of the smart speaker.

[0043] Generally speaking, UWB refers to a set of technologies utilizing low energy for short-range, high-bandwidth communications over a large portion of the radio spectrum (e.g., utilizing channels at least 500 MHz wide at the around the 3-6 GHz range). A radio transmission may be considered a UWB transmission when the emitted signal bandwidth of the transmission exceeds the lesser of 500 MHz or 20% of the arithmetic center frequency. UWB may be utilized by the disclosed systems to enable ranging or position finding.

[0044] In an embodiment, described systems implement a two-way ranging (TWR) technique, wherein multiple messages and timestamps (e.g., provided by both transmitter and receiver) are used to determine a distance between the two devices (e.g., the first and second network devices) based on time-of-flight (ToF). If multiple receivers receive and respond to the signal(s) from the transmitter, the ToFs and corresponding distances can be calculated. From there, a position of the sender (e.g., the first network device) may be triangulated relative to the other devices.

[0045] In an embodiment, time difference of arrival (TDOA) techniques are utilized. For example, the transmitter (e.g., the first network device) may transmit messages (e.g., blink messages) in regular intervals. These messages may be received by multiple clock-synced peer devices, and each may generate a time-of-arrival timestamp that the peer devices then upload to a server. The server may then analyze the differences in time-stamps to calculate a position of the transmitter (e.g., the first or second network devices).

[0046] In an embodiment, angle of arrival (AoA) techniques are utilized. For example, an estimated AoA may be calculated via measurement of the phase difference of arrival at multiple receiver antennas. The disclosed systems may utilize any desired combination of TWR, TDOA, and AoA techniques to determine (i) a relative distance between two devices and (ii) a relative direction from one device to the other. In some embodiments, the AR device may compute the position of the identified device (e.g., the smart speaker) using the AoA technique without the use of other peer devices (e.g., the AR device may be able to determine the position based on computing the angle of arrival and the time of flight).

[0047] In some embodiments, the user may select and/or control the one or more identified devices

the devices within the AR environment. For example, when the AR device (e.g., the smartphone) detects a user selection of the smart speaker (e.g., an identified device) within the AR environment, the smartphone may cause the display of an interface for controlling a network parameter of the smart speaker. In some embodiments, the displayed interface for controlling the network device may be selected (by the AR device) based on the network activity and/or a parameter of the network device. For example, when the smart phone determines that a smart speaker that is streaming music, the smartphone may cause the display of a graphical slider to adjust a bandwidth of the music stream. When the AR device (e.g., smartphone) detects an interaction with the user interface, the AR device may modify the parameter of the network activity based on the interaction. For example, when the interaction moves the slider closer to a minimum value, the AR device may transmit a request to decrease a bandwidth of the network activity. In some embodiments, the AR device may communicate with the identified device (e.g., smart speaker) to cause the change in the parameter of the network activity, or may communicate with a third network device (e.g., a router or a server associated with the network activity) to cause the change. The third wireless device may comprise one or more wireless radios (e.g., a Wi-Fi radio and a UWB radio) and may communicate with the AR device and other devices using the one or more radios. For example, the AR device may transmit a request to a router to reduce a QoS prioritization of the music stream or may communicate with an application on the smart speaker to throttle the bandwidth of the music stream. In some embodiments, AR device may detect one or more gestures to perform control functions on the identified device. For example, when the AR device detects a pinch gesture, the AR device may automatically increase or decrease the bandwidth (e.g., based a finger position of the pinch gesture) and a swipe gesture may automatically terminate the network activity.

[0048] In some embodiments, changing or reducing an amount of bandwidth available for a first device may automatically modify an amount of bandwidth available for an additional device. For example, when a user decreases an amount of bandwidth available to the smart speaker, the AR device may automatically cause a bandwidth for a streaming activity of a smart TV to increase. In some embodiments, the positions and names of devices and/or parameters of the network activities of such devices may be stored on a database (e.g., one local to the AR device or remote to the AR device) such that the names, positions and/or parameters may be queried and updated by various other devices. The AR device, by identifying devices, displaying the status of devices, and enabling the control of devices within an AR environment, enables even the least tech savvy of users to both diagnose and control network activities previously only accessible to the most tech savvy.

[0049] FIG. 1A and FIG. 1B shows exemplary embodiments of a network device in accordance with some embodiments of the present disclosure (e.g., an AR device). An exemplary configuration of circuitry corresponding to network device **102** is discussed further in detail in FIG. 8.

Orientation **100** depicts a front of network device **102** having display **104**. Network device **102** is depicted within an exemplary Cartesian coordinate system with an origin at a center of the network device **102**. However, any origin for the coordinate axis system may be selected (e.g., a center originating at from a camera of network device **102** or a center originating at an antenna of a UWB radio of network device **102**) and any coordinate system may be selected (e.g., a polar coordinate system). Although network device **102** is depicted as a smartphone, any device may be used without departing from the scope of the present disclosure. For example, network device **102** may be an AR headset or smart glasses. In some embodiments, display **104** may be a transparent or semi-transparent display.

[0050] The exemplary Cartesian coordinate axis system is showing having a positive Y direction to a top of network device **102**, a positive X direction to a right of network device **102** and negative Z direction to a back of network device **102**. In some embodiments, the coordinate system depicted orientation **100** is utilized by network device **102** to determine and store a position of another network device (e.g., a first network device, such as the smart speaker described above) relative to the second network device (e.g., network device **102**). For example, when network device **102**

determines a position of the first network device relative to network device **102**, network device **102** may store the position of coordinates based on the coordinate system depicted in orientation **100**. For example, when the position of the first network device, relative to network device **102** is below, to the right of, and behind network device **102**, network device **102** may determine that the value for the Y position is negative, the value for the X position is positive, and the value for the Z position is negative. In some embodiments, network device **102** stores the relative position in storage of network device **102** (e.g., storage **808**) and/or storage of a remote device (e.g., storage **808** of a server or of a router). An exemplary database for storing the relative position is described further below with respect to FIG. **3a**.

[0051] In FIG. **1B**, orientation **150** depicts a rear of network device **102** having camera **106**. While camera **106** is depicted having two lenses, any number of lenses may be used. In some embodiments, each lens corresponds to a different image sensor and each lens may have different optical properties. In some embodiments, the distance between the lenses of camera **106**, and/or the optical properties of the lenses, is known by network device **102** and may be utilized by network device **102** to compute one or more dimensions within the coordinate system for an object captured by camera **106**. In some embodiments, network device **102** may additionally use values computed from one or more sensors to obtain an orientation for the lenses of camera **106** (e.g., from a gyroscope or an accelerometer). In some embodiments, network device **102** may capture a photo (or multiple photos in a sequence to form a video) and may compare a pixel disparity between objects detected in a first photo taken from the first lens and a second photo taken from the second lens. Based on the parameters known to network device **102** (e.g., the distance between the lenses, the optical properties, a resolution of the image sensor, the orientation of network device **102**, etc.), network device **102** may compute a relative position of the detected object based on a disparity between the pixels for an image captured of the object. In some embodiments, where display **102** is a transparent or semi-transparent display, network device **102** may determine whether a network device is visible via a display of network device **102** based on a wireless signal, such as a UWB signal emitted from a device.

[0052] In some embodiments, network device **102** may utilize an image processing algorithm to detect an object. For example, control circuitry **804** may detect a television within a visual range of camera **106** based on applying an image processing algorithm to one or more images captured by camera **106**. Network device **102** may identify pixels corresponding to the television and may compute a pixel disparity between pixels corresponding to the television from a first image captured from a first lens of camera **106** pixels corresponding to the television from a second image captured from a second lens of camera **106**. For example, network device **102** may detect the television in the first image and the second image and may determine a position of the television based on the disparity between the pixels corresponding to the television in each of the images.

[0053] In some embodiments, network device **102** utilizes an image captured from cameras **106** to generate an augmented reality environment (e.g., the environment depicted and described in relation to FIGS. **2-7**). For example, an environment located in the negative Z direction of network device **102** may be captured by camera **106** and displayed on display **104**. In some embodiments, network device **102** generates the augmented reality environment based on a sequential capture of one or more images from camera **106** (e.g., to form a video). The image captured by camera **106** and displayed on display **104** may be automatically update based on a specified refresh rate or based on detecting a change in the orientation of network device **102** (e.g., based on detecting a changed gyroscope measurement). In some embodiments, a user may pause the capture of the video by performing an action within the augmented reality environment (e.g., selecting an object within the augmented reality environment or pressing a pause button). In such instances, the user may re-orient the network device **102** without changing the image depicted on display **104**. In other instances, network device **102** may automatically update the displayed image as network device **102** is re-oriented. In some embodiments, the network device **102** generates an AR environment by

generating an overlay for display over an OST display. In such embodiments, network device **102** may identify the location of objects visible via the OST display based on a wireless signal from such objects or based on a position of such objects stored in, for example, a database.

[0054] FIG. 2 depicts shows an exemplary embodiment of an augmented reality environment for managing network devices, in accordance with some embodiments of the present disclosure. Augmented reality system **200** depicts network device **102** displaying an image of an environment on display **104** (e.g., an image of environment **250** captured from camera **106**). In some embodiments, the image of environment **250** is simply environment **250** as seen via a transparent or semi-transparent display (e.g., via a pair of smart glasses having a semi-transparent display). As referred to herein, the “image” may correspond to an environment as viewed through or via a transparent or semi-transparent display device. Augmented reality environment **275** is depicted augmenting environment **250** with identifiers (e.g., the boxes or circles) around devices identified by network device **102** within the environment. For example, as depicted in augmented reality environment **275**, network device **102** may detect sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214** and tablet **216** within the image captured of environment **250** and may display one or more indicators (e.g., a circle around the device and/or a device name) that indicate the position of an identified device. The devices depicted in environment **250** and augmented reality environment **275** are merely exemplary and any number and any type of device may be present without departing from the scope of the present disclosure. In some embodiments, the devices may comprise at least a portion of the circuitry depicted in exemplary network device in FIG. 8.

[0055] In some embodiments, network device **102** may detect the position of the one or more devices within environment **250** using a stereoscopic camera configuration as described above with respect to FIG. 1. For example, control circuitry **804** may detect a position of smart TV **204** relative to network device **102** by determining a disparity between pixels captured of smart TV **204** by two or more lenses of camera **106**. In another example, network device **102** may determine the relative position of smart TV **204** using a LiDAR scanner of network device **102**. For example, network device **102** may transmit a sequence of laser pulses and may measure a round trip time of the laser pulse. In some embodiments, network device **102** may utilize one or more combinations approaches to approximate a location of devices within environment **250**, such as using a UWB radio as described below.

[0056] In some embodiments, network device **102** and/or each of the devices depicted in environment **250** (e.g., sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214** and tablet **216**) comprises one more wireless radios. For example, network device **102** and each of the devices depicted in environment **250** (e.g., sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214** and tablet **216**) may comprise one or more of a Wi-Fi radio, an UWB radio, a Bluetooth radio, a cellular radio, etc. For example, a first network device (e.g., any of the devices depicted in augmented reality environment **275**, such as tablet **216**) may comprise a first wireless radio (e.g., a UWB radio) and a second wireless radio (e.g., a Wi-Fi radio). In some embodiments, the second wireless radio (e.g., the Wi-Fi radio) of the first network device (e.g., tablet **216**) may be used by the first network device to connect the first network device to a local area network (LAN) and/or a wide area network (WAN). In some embodiments, the connection to the LAN and/or WAN by the first network device may be made via one or more interstitial devices. For example, the first network device may connect to the LAN via a Wi-Fi access point, the Wi-Fi access point may be connected to one or more network switches, which may be connected to a network router that is connected to a WAN. An exemplary network configuration of devices is discussed further with respect to FIG. 9.

[0057] The first wireless radio (e.g., the UWB radio of tablet **216**, such as UWB radio **818**) may be used by the first network device (e.g., tablet **216**) to transmit information about the first network device to other devices. For example, the first network device may utilize the first wireless radio

for location discovery, device ranging, and/or for communication with other UWB enabled devices. In some embodiments, network device **102** (e.g., the second network device) comprises a UWB radio (e.g., the third wireless radio). When network device **102** enters a UWB range of tablet **216** (e.g., the first network device), the third wireless radio (i.e., the UWB radio of network device **102**) may detect a signal from the first wireless radio (e.g., the UWB radio of tablet **216**).

[0058] In response to detecting the signal, the second network device (e.g., network device **102**) may determine, via the third wireless radio (e.g., the UWB radio of network device **102**), a position of the first network device (e.g., tablet **216**) relative to the second network device (e.g., network device **102**). For example, when the first network device and the second network device come within range of one another, the two devices may begin a UWB ranging process to determine their relative locations and distances. In some instances, the second network device (e.g., network device **102**) initiates the ranging process and in other instances the first network device (e.g., tablet **216**) initiates the ranging process.

[0059] In some instances, the second network device (e.g., network device **102**) may utilize two-way ranging to determine the relative position of the first network device. The second network device may utilize the timing of various signals sent between the first network device and the second network device to determine a position of the first network device relative to the second network device. For example, the first network device may transmit a signal (e.g., from the first wireless radio) comprising a poll message. The first network device may record a time of sending the poll message (TSP). When the second network device (e.g., network device **102**) detects the signal, the second network device may record a time of receiving the poll message (TRP) and may transmit a response (e.g., via the third wireless radio) to the first network device (e.g., tablet **216**). The second network device may record a time of sending the response message (TSR). When the first network device (e.g., tablet **216**) receives the response message (e.g., at the first wireless radio), the first network device may record the time of receiving the response (TRR) and may transmit (e.g., via the first wireless radio) a final message. In some embodiments, the final message transmitted by the first network device may comprise a UWB identifier for the first network device, the TSP, the TRR, and a time of sending the final message (TSF). The second network device may receive the final message from the first network device at the third wireless radio (e.g., the UWB radio of network device **102**).

[0060] After receiving the final message, the second network device will have timing information (e.g., TSP, TRP, TSR, TRR, and TSF) for the various messages (e.g., the poll message, the response message, and the final message). Using the timing information, the second network device may compute a time of flight for the signal between the first network device and the second network device. The second network device may determine the position of the first network device relative to the second network device at least partially based on the time of flight, in particular the second network device may determine a distance of the first network device relative to the second network device based on the time of flight.

[0061] In some embodiments, the third wireless radio of the second network device (e.g., the UWB radio of the network device **102**) comprises one or more wireless antennas. By detecting the signal from the first network device (e.g., tablet **216**) at each of the one or more wireless antennas, and computing a phase difference in the signal across the one or more wireless antennas, the second network device may compute an angle of arrival of the signal. Using the computed angle of arrival of the signal, the second network device may identify a direction of the first network device relative to the second network device. The second network device may utilize the information about the time of flight of the signal and the angle of arrival of the signal to approximate a position of the first network device relative to the second network device. In some embodiments, subsequent to identifying the position of the network device, the second network device may determine additional information about the network device, such as a name of the device, a network address, etc. as discussed further in detail below.

[0062] Although the exemplary two-way ranging process described above commences with the first network device transmitting a poll signal, the poll signal may be transmitted by the second network device without departing from the scope of the present disclosure. Additionally, other methods for computing a position of the devices may be used. For example, instead of or in addition to computing an angle of arrival for the signal, the second network device may work in conjunction with other UWB capable devices. For example, a router may also complete the two-way ranging protocol with the first network device and may share (e.g., by transmitting the results of the ranging via the UWB radio of the router) the results of the ranging with the second network device. Based on the combined results of the ranging by both devices, the second network device may approximate a more precise location for the first network device.

[0063] In some embodiments, the second network device may utilize other UWB ranging protocols, such as time difference of arrival (TDOA). Using such a protocol, multiple network devices may work in conjunction to each identify the location of a target device. For example, a third network device, such as a router, may compute a second time of flight of the signal between the first network device and the third network device and may share the second time of flight with a server and/or the second network device. Based on the first time of flight and the second time of flight, the second network device and or a server may determine a location for the first network device. In some embodiments, the third network device is an anchor device (e.g., a device having a fixed and/or know location) that works in conjunction with other anchor devices to compute and/or determine the locations of other devices. For example, a first anchor device (e.g., a router), a second anchor device (e.g., a thermostat) and a third anchor device (e.g., a sensor) may each have a fixed location and may share a time clock. Each of the anchor devices may detect a signal from the first network device and may share a time of flight (e.g., based on the synchronized time clock) and may determine the location of the first network device by triangulating the location of the first network device using a difference in the time of flight between the signals detected by each of the anchor devices. While the example herein is described with respect to determining the position of devices based on a UWB signal, any type of signal or other method or steps may be used. For example, a Bluetooth or Wi-Fi signal may be used to approximate the location of a device or a camera may be used to detect and approximate a location of a device.

[0064] In some instances, a wireless radio of the second network device may be used to identify a location of a device that lacks a wireless radio. For example, smart TV **204** may comprise a Wi-Fi radio but may not comprise a UWB radio. The user may move the second network device (e.g., network device **102**) to a location of smart TV **204** and may perform a ranging routine with other network devices having fixed or know locations. For example, network device **102**, while next to the location of smart TV **204**, may complete a UWB ranging protocol with sensor **202**, camera **206**, thermostat **208**, and/or router **214**. Based on the position of network device **102** relative to signals transmitted by sensor **202**, camera **206**, thermostat **208**, and/or router **214**, network device **102** may compute and store a location for smart TV **204**. Therefore, when the user returns to a different location within environment **250**, network device **102** may approximate a location of smart TV **204**.

[0065] In some embodiments, network device **102** may detect multiple devices within environment **250**. For example, network device **102** may use an image processing algorithm as described above and may detect the presence and position of one or more devices within environment **250**. In other instances, or in combination with the camera-based device detection as described above, network device **102** may detect the presence of multiple devices based on detecting one or more wireless signals. For example, environment **250** may comprise a third network device, such as router **214**. The third network device may comprise a fourth wireless radio (e.g., a UWB radio) and a fifth wireless radio (e.g., a Wi-Fi radio). The third network device (e.g., router **214**) may transmit a poll signal, as described above. When the second network device (e.g., network device **102**) detects the signal from the UWB radio of the third network device (e.g., router **214**), the second network

device may determine a position of the third network device relative to the second network device by completing a UWB ranging protocol as described above. This example is intended to be exemplary and any number or combination of approaches (e.g., using a camera, using LiDAR, using a UWB radio, using a Bluetooth radio, etc.) may be used to detect a device and determine a position of the device within a user's environment (e.g., environment **250**).

[0066] In some instances, the relative direction and the relative distance of a device may be stored by the second network device (e.g., network device **102**). For example, network device **102** may store information about the position of the detected one or more devices within a database, such as the exemplary database **300** described further below with respect to FIG. **3A**. In some embodiments, network device **102** may determine and store at least an identifier for a detected device (e.g., a UWB identifier for an identified device), a relative direction of the identified device (e.g., a normalized vector pointing in the direction of the detected device, where network device **102** is the origin) and a relative distance (e.g., a distance between network device **102** and tablet **216**). In some embodiments, where the second network device determines additional information about the detected network device (e.g., a name of the network device or a network address of the network device), the second network device may additionally store such information in the database. The database may be stored locally (e.g., in storage of network device **102**) or may be stored remote to network device **102** (e.g., on storage of router **214** or on a server located on a wide area network).

[0067] In some embodiments, the second network device may utilize the determined position of the one or more detected devices to display an indicator of the detected device within augmented reality environment **275**, such as a circle around a detected device. For example, network device **102** may retrieve an image of environment **250** from camera **106** and may overlay the image with an indicator at the position within the image that corresponds to the relative position of the device (e.g., a circle around tablet **216**). For example, using the vector representing the relative position of tablet **216** (e.g., within the Cartesian system depicted in FIG. **1A** and FIG. **1B**) and/or the distance of tablet **216** to network device **102**, network device **102** may approximate a position of tablet **216** in the two-dimensional plane of the image (e.g., the image of environment **250**). In another example, network device **102** may overlay an environment as seen via a transparent or semi-transparent display by identifying a position within the display that corresponds to the relative position of the device and may display the indicator at the relative position within the display (e.g., such that the overlay appears to circle the device within the transparent or semi-transparent display).

[0068] In some embodiments, network device **102** may select a number of indicators to display based on an amount of available free space within the image of environment **250** and/or within an available amount of space on the transparent or semi-transparent display viewing environment **250**. For example, network device **102** may limit the number of indicators that are displayed when one or more indicators may overlap. In another example, network device **102** may limit the number of indicators displayed when the user is too far away from a network device. For example, when a smartwatch is in a background of an image, network device **102** may refrain from displaying the indicator for the smartwatch until network device **102** is closer to the smartwatch (e.g., until the smartwatch is more visible within the image). In another example, network device **102** may modify the appearance or style of the indicator based on the distance. For example, when a device is less than a threshold distance to network device **102** (or appears at least a threshold size within the image) network device **102** may display a first type of indicator (e.g., a circle around the device). When a device is greater than a threshold distance to network device **102** (or appears smaller than the threshold size within the image) network device **102** may display a second type of indicator (e.g., a line or arrow pointing to the device) or may display information about the device in a panel (e.g., one of the panels depicted in FIG. **4** or FIG. **6**).

[0069] In some embodiments, as network device **102** moves around environment **250**, augmented

reality environment **275** is continually updated to continue displaying the indicators at their appropriate positions. For example, network device **102** may detect movement via an accelerometer, gyroscope, changed image from the camera, etc. In response to detecting the movement of the second device, the second network device may determine an updated position of the first network device relative to the second network device. For example, network device **102** may perform the UWB ranging protocol to identify an updated position for tablet **216**. The second network device may modify a database entry based on the updated position. For example, the second network device may transmit the updated relative position to router **214** to store in database **300**.

[0070] In some embodiments, subsequent to determining the updated position, network device **102** may update a position of the overlays, indicators, text, etc. within augmented reality environment **275**. For example, as a user network device **102** closer to tablet **216**, the indicator around tablet **216** may enlarge as tablet **216** takes up additional screen space (e.g., as depicted in FIG. 4). In some embodiments, network device **102** may provide the user with an opportunity to pause augmented reality environment **275** such that when the user moves network device **102** augmented reality environment **275** is not updated (e.g., so that a user can select an object on screen or enlarge the display of augmented reality environment **275**).

[0071] In FIG. 2, sensor **202**, camera **206**, speaker **210**, stream box **212**, router **214**, and tablet **216** are each depicted by network device **102** in augmented reality environment **275** having a circular indicator. However, any indicator may be used. For example, thermostat **208** is depicted having a rectangular indicator. In some embodiments, the indicator may be an arrow pointing to a device, in other embodiments the indicator may be information placed proximate to the device (e.g., a device name and/or network address that is placed in the AR environment by network device **102** proximate to the device). Network device **102** may use edge detection to identify the outer limits of a detected device and may draw the indicator based on the detected edges. For example, the circle around tablet **216** in augmented reality environment **275** is selected such that it is slightly larger than tablet **216** as it appears in augmented reality environment **275**. Likewise, the additional information about the device may be placed such that it overlays the device, or is placed outside of the perimeter of the device as it appears within augmented reality environment **275**.

[0072] In some embodiments, network device **102** may graphically accentuate the detected device. For example, network device **102** may highlight the device within augmented reality environment **275** by applying a coloring (e.g., highlight) to the detected device or a border around the detected device. For example, network device **102** may use an edge detection algorithm to detect the perimeter of tablet **216** as it appears in augmented reality environment **275** and may display a highlighting around the border of tablet **216**. The aforementioned methods for identifying a detected device within augmented reality environment **275** are merely exemplary and multiple different methods may be implemented without departing from the scope of the present disclosure.

[0073] In some aspects, the second network device may determine additional information about a detected device so that the second network device (e.g., network device **102**) may display information about the device within augmented reality environment **275**. For example, network device **102** may determine a name of sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214**, and/or tablet **216** and a network address of the devices so that network device **102** can display a name and/or the network address of each device proximate to its location within augmented reality environment **275**. For example, the name for smart TV **204** (e.g., smart TV) and the network address (e.g., 192.168.1.102) may be displayed above smart TV **204** within augmented reality environment **275**. In another example, a name for camera **206** (e.g., camera_1) and a network address (e.g., 192.168.1.11) may be displayed in a box below camera **206** within augmented reality environment **275**. In some embodiments, network device **102** may determine the style to present the information based on objects that appear within the image. For example, network device **102** may present the information for router **214** in an opaque box when

the objects behind the text would obscure the clarity of the text. In contrast, network device **102** may display the information for smart TV **204** in a transparent overlay when the background of the text will not obscure the clarity of the text.

[0074] In some embodiments, the second network device receives, from the first network device the name of the first network device (e.g., a name for tablet **216**, Sam's Tablet) and a network address (e.g., 192.168.1.15) corresponding to the second wireless radio (e.g., the Wi-Fi radio of tablet **216**, such as Wi-Fi radio **816**). In some embodiments, the name and the network address are provided by the first network device subsequent to detecting the position of the first network device relative to the second network device (e.g., subsequent to completing the UWB ranging protocol). For example, in response to completing the UWB ranging protocol, the second network device (e.g., network device **102**) may initiate a UWB communication session with the second network device (e.g., tablet **216**). For example, the first network device may communicate via the first wireless radio (e.g., the UWB radio) with the third wireless radio (e.g., the UWB radio, such as UWB radio **818**) of the second network device.

[0075] During the communication session, the first network device and the second network device may exchange unique tokens that identify each of the devices via the UWB physical layer data transport protocol. For example, the first network device (e.g., tablet **216**) and the second network device (e.g., network device **102**) may exchange UWB identifiers/addresses corresponding to each of the devices such that each device can communicate directly with each other over a UWB communications channel. By establishing the session, the first network device (e.g., tablet **216**) and the second network device (e.g., network device **102**) may transmit additional information about each of the devices and, in some embodiments, may bootstrap an additional connection via a different communication protocol. For example, over the UWB connection (or any other connection used to perform the ranging, such as Bluetooth) the first network device and the second network device may transmit information about an IP address and a MAC address used for a Wi-Fi or ethernet connection. For example, subsequent to exchanging IP addresses, the first network device may communicate with the second network device via the second wireless radio (e.g., the Wi-Fi radio) of the first network device over a Wi-Fi connection.

[0076] In some embodiments, during the session the first network device and the second network device may exchange some of the following information: a device identity (e.g., name, serial number, etc.), a network identity (e.g., an IP address, a MAC address, etc.), a device type (e.g., TV, tablet, PC, etc.), a device icon, a device descriptor (e.g., an XML file or CSV file comprising any information about the device, such as an OS version, hardware version, etc.), an identifier of services and capabilities of the device, physical attributes of the device (e.g., a screen size, device size, etc., which may be used to assist the AR rendering). In some embodiments, the second network device stores the received information in a database, such as database **300**, further in relation to FIG. 3A. When multiple devices are detected by the second network device (e.g., network device **102**), network device **102** may retrieve device information for each of the detected devices. For example, when network device **102** detects sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214**, and/or tablet **216** in environment **250**, network device **102** may retrieve information corresponding to each of sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214**, and/or tablet **216** and may store such information in database **300**.

[0077] Although the abovementioned process for determining device attributes is described in relation to using a UWB radio, any protocol, method or process may be used without departing from the scope of the present disclosure. For example, the first network device and the second network device may use a Bluetooth connection to exchange device information.

[0078] In some embodiments, such a where a camera is used to detect the position of a device, network device **102** may determine the device information, by, for example scanning a QR code displayed on a device. For example, smart TV **204** may display a QR code to exchange the

information or may have a QR code affixed to an exterior of Smart TV **204** (or any visual depiction comprising encoded information about smart TV **204**, such as a barcode, machine readable text, etc.).

[0079] In some embodiments, network device **102** may use image processing techniques to determine that smart TV **204** is a television. In such embodiments, network device **102** may scan a local area network for televisions located on the local area network. When only one television is located on the local area network, network device **102** may determine that the network address for the device (e.g., smart TV **204**) is the address of the sole television located on the local area network. In response to detecting the network address, network device **102** may determine the name of the identified television by communicating using the network address (e.g., via Wi-Fi).

[0080] When multiple televisions are present, the multiple candidate network addresses (e.g., the network addresses corresponding to televisions) and/or candidate television names may be displayed. In some embodiments, when network device **102** cannot determine with certainty the identity of the device, network device **102** may display a prompt to request further user input in identifying the device. For example, control circuitry **804** may display a series of prompts to assist the user in selecting the correct network address from multiple candidate network addresses. For example, network device **102** may display a manufacturer and model of the television corresponding to each network address and may ask the user to confirm which TV appears in environment **250** based on the identified manufacturers and models of televisions on the local area network. Any methods or combination of methods may be used to identify information about the detected devices without departing from the scope of the present disclosure.

[0081] In some embodiments, the second network device may generate for display an overlay at a position of a detected device. For example, network device **102** may generate for display an overlay in augmented reality environment **275** comprising the identifier (as discussed above) and any of the information retrieved from the first network device, such as the name of the first network device (e.g., Sam's Tablet) and a network address corresponding to the second wireless radio (e.g., the Wi-Fi radio of tablet **216**). By displaying a name of a detected device (e.g., Sam's iPad), and a network address (e.g., the IP address on the Wi-Fi network), a user may more easily identify and troubleshoot network issues. The overlays depicted in augmented reality environment **275** are merely exemplary and any information may be included in the overlay, including various information about the device (e.g., a device type and OS) and/or various network information corresponding to the device (e.g., a bandwidth being consumed by the device or a Wi-Fi signal strength). In some embodiments, the information displayed in the overlay is retrieved from a local and/or remote database (e.g., from database **300** or database **350**), may be retrieved from the device itself (e.g., information about tablet **216** may be retrieved over a UWB connection with tablet **216**), and/or may be retrieved from a third device (e.g., information about tablet **216** may be retrieved from router **214**).

[0082] The overlay may take various forms. For example, network device **102** may generate for display the overlay so that it is centered over the position of the first network device within augmented reality environment **275**. In another example, the overlay may be positioned proximate to the detected device (e.g., around a perimeter of the device without obscuring the device). In yet another example, the information may be displayed in response to a user action. For example, the information may be displayed in response to receiving a user selection of an identified device within augmented reality environment **275**. For example, the user may select tablet **216** from augmented reality environment **275** displayed on network device **102** to cause network device **102** to display the information about tablet **216**.

[0083] In some embodiments, network device **102** may limit a number of displayed overlays as to prevent the overlays from obscuring more than a threshold percentage of the augmented reality environment **275**. For example, network device **102** may determine a number of overlays to display based on the number of detected devices within environment **250**. For example, when five devices

are detected, network device **102** may display five overlays each corresponding to a different device when the overlays will not obscure more than a threshold percentage of augmented reality environment **275**. In some embodiments, network device **102** may select which overlays to display based on prominence of the devices within environment **250**. For example, network device **102** may display an overlay for the two most prominent devices within environment **250** (e.g., for smart TV **204** and tablet **216** because those devices occupy the largest number of pixels within augmented reality environment **275**).

[0084] In some aspects, the second network device may visually distinguish a network device based on a capability or characteristic of the network device. For example, the second network device (network device **102**) may detect that the third network device (e.g., router **214**) comprises a wide area network (“WAN”) connection. For example, the second network device may determine that a network connection of the third network device is associated with a public IP address (e.g., that router **214** has a WAN port that is assigned a public IP address). In response to determining that the third network device comprises a WAN connection, the second network device may visually distinguish the third network device (e.g., router **214**) from the first network device (e.g., tablet **216**). For example, the second network device may highlight router **214** in a different color than tablet **216** and may place an icon next to router **214** to indicate that router **214** routes connections to the Internet.

[0085] FIGS. **3A** and **3B** depict exemplary databases in accordance with some embodiments of the present disclosure. Database **300** is an exemplary database that may be used by network device **102** for storing the relative location of devices within an environment (e.g., environment **250**) and/or information about each of the detected devices (e.g., each of sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214**, and/or tablet **216**). In some embodiments, network device **102** may create a new entry in database **300** for each device within environment **250** (e.g., eight entries). In some embodiments, database **300** is stored locally to network device **102** (e.g., on storage of network device **102**) and/or remote to network device **102** (e.g., on router **216** or on a server accessed over a WAN connection). In some embodiments, network device **102** may select one of multiple storage locations based on a latency of accessing a particular storage. For example, network device **102** may store information in a local database when network device **102** expects to need quick access to such information and may store the information in a remote database when quick access is not needed. For example, network device **102** may store the position of tablet **216** within augmented reality environment **275** (e.g., an X and Y coordinate corresponding to pixels on display **104**) on local storage so that network device **102** may quickly render information at the position of tablet **216** within augmented reality environment **275**. In contrast, network device **102** may store the OS version of tablet **216** on remote storage (e.g., storage of router **214**) because the OS version of tablet **216** may be accessed less frequently.

[0086] In some embodiments, database **300** may comprise a plurality of fields. A first field may store an identifier for a device. In exemplary database **300**, the identifier is a UWB identifier such as a hardware address for the UWB radio of a device. For example, when the second network device (e.g., network device **102**) detects the first network device (e.g., tablet **216**), the second network device may store a hardware identifier of the first wireless radio (e.g., the hardware address of the UWB radio of tablet **216**). Any identifier for the device may be used without departing from the scope of the present disclosure, such as a randomized identifier, a device serial number, a device name, a hash value of device characteristics, etc.

[0087] In some embodiments, the second network device may store a relative position of the first network device. For example, network device **102** may store the relative position of tablet **216** by storing a vector having the relative direction of tablet **216** and by storing a relative distance of tablet **216**. While database **300** depicts the relative position as occupying two fields, any number of fields may be used and may vary based on the relative position representation. For example, when using a Cartesian coordinate system, the relative position may occupy four fields of the database-

one field for each of the X, Y, and Z vector components and one field for the distance. When using a spherical coordinate system three fields may be used, one for the radial distance, one field for the polar angle, one field for the azimuthal angle.

[0088] In some embodiments, the second network device may store information about additional wireless radios of the first network device. For example, the second network device may store information about the second wireless radio (e.g., the Wi-Fi radio) of the first network device, such as a LAN IP address, a MAC address, a Wi-Fi frequency, a Wi-Fi standard, etc. To prevent overcomplicating the drawing, only the LAN IP address for the second wireless radio is depicted in database **300**.

[0089] In some embodiments, the second network device may receive additional information about the first network device and may store such information in a database (e.g., database **300**) in one or more fields. For example, the second network device may receive a device identity (e.g., name, serial number, etc.), a device type (e.g., TV, tablet, PC, etc.), a device icon, a device descriptor (e.g., an XML file or CSV file comprising any information about the device, such as an OS version, hardware version, etc.), an identifier of services and capabilities of the device, physical attributes of the device (e.g., a screen size, device size, etc.). In some embodiments, when the second network device (e.g., network device **102**) is rendering augmented reality environment **275**, the second network device may access database **300** to retrieve relative position information and/or information about a detected device (e.g., tablet **216**) to display in an overlay.

[0090] In some embodiments, the second network device may add additional information to database **300** to store tracking or other information related to the devices. For example, when the first network device is assigned a data cap or a bandwidth limit (discussed further below), network device **102** may store the data cap or bandwidth limit in database **300**. In another example, network device **102** may maintain and update bandwidth usage of the first network device by storing and updating a bandwidth usage field of database **300** corresponding to tablet **216**.

[0091] In some embodiments, the systems and methods presented herein track and/or monitor network activities of the devices. Parameters of the tracked network activities, such as a source address, destination address, service characterization, bandwidth, etc., may be stored in a database, such as database **350**. For example, database **350** may store information about network traffic originating from or destined for network device **102**, sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214**, and/or tablet **216**. In some embodiments, database **350** stores information about network traffic exceeding a certain data threshold (e.g., network traffic exceeding 0.5 MB/S), such as a video stream, a download, a VOIP call, etc. but does not store information about smaller or intermittent network traffic (e.g., a call to a network time protocol “NTP” server).

[0092] In some embodiments, a router, such as router **214** manages and maintains database **350**. In such instances, database **350** may be stored locally to router **214** (e.g., on storage circuitry **808** of router **214**), a server remote to router **214** (e.g., on storage circuitry **808** of a server accessed via the Internet), or storage of another device (e.g., a computer located on the LAN). For example, as router **214** routes traffic within the LAN and to the WAN, router **214** may monitor the network traffic to identify parameters of the network activity such as a source address, a destination address, a service characterization, an application corresponding to the network activity, a network usage, a priority, a duration, an access time, a network cap, etc. Upon detecting the network characteristics, router **214** may update database **350** to include the characteristics. For example, router **214** may store the metrics corresponding to the parameters locally or may transit the metrics to the remote server.

[0093] In some embodiments, network device **102** maintains database **350** based on information received and/or detected by network device **102** about the network traffic. For example, the second network device (e.g., network device **102**) may query the first network device (e.g., tablet **216**) for information about current or past network activities of the first network device. In response to

receiving the information about the network activities, network device **102** may store the information in database **350**. In some aspects, the applications installed on the first network device may report the network activity to a remote server (e.g., server accessed over the Internet). In such instances, the remote server may maintain database **350** and network device **102** may retrieve information about the network activity by transmitting queries to database **350** on the remote server.

[0094] In some embodiments, the information stored in database **350** is used by network device **102** and/or router **214** in conjunction with information stored in database **300**. For example, when the first network device is assigned a data cap, network device **102** and/or router **214** may utilize the information network traffic information of database **350** to update a bandwidth usage of tablet **216** stored in database **300**.

[0095] In some embodiments, the second network device may retrieve information from database **300** and/or database **350** to present information in augmented reality environment **275**. FIGS. **4-7** depict exemplary embodiments of displaying information about devices (e.g., sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214**, and/or tablet **216**) and about network activities corresponding to each of the devices. The depictions in such figures are meant to be exemplary and not limiting. Any type of data, characteristic, and/or parameter of a network activity, status of a parameter of a network activity may be captured and/or stored and displayed within an augmented reality environment (e.g., by using or including such status, data, characteristic and/or parameter in a user interface (UI) element mapped to and displayed within the augmented reality environment). In some embodiments, user actions may be performed prior to displaying information about the devices and/or the data, characteristic, and/or parameters. In some embodiments, the UI elements allow for the user to control various parameters of devices and/or of network activities.

[0096] FIG. **4** depicts exemplary embodiment of a detailed view of information (e.g., detailed information view **400**) about a network device (e.g., tablet **216**), in an accordance with some embodiments of the present disclosure. For example, as a user moves network device **102** closer to tablet **216** within environment **250**, network device **102** may determine an updated relative position of tablet **216** and, based on the updated position, may enlarge indicator **404** around tablet **216**. In some embodiments, the enlarging of the indicator **404** is based on an image processing algorithm that tracks the edges of tablet **216** within the image such that indicator **404** encompasses an entirety of tablet **216** may enlarge as tablet **216** takes up additional screen space (e.g., as depicted in FIG. **4**). In some embodiments, indicator **404** is scaled and sized based on a relative distance from network device **102** to tablet **216** and a known size of tablet **216**.

[0097] In some embodiments, the second network device may cause the display of a detailed information view in response to detecting that a distance between the second network device and the first network device is less than a threshold distance. For example, when network device **102** is less than one foot away from tablet **216**, network device **102** generates the display of detailed information view **402** on display **104**.

[0098] In some aspects, the second network device causes to be displayed detailed information view **402** in response to detecting that the first network device is centered within display **104** and/or occupies a threshold percentage of display **104**. For example, when tablet **216** is located approximately centered within display **104** and occupies at least 10% of the pixels corresponding to display **104**, network device **102** may cause to be displayed detailed information view **402**.

[0099] The second network device may cause to be displayed detailed information view **402** in response to determining that the first network device is the only device within a field of view of camera **106**. In another embodiment, the second network device causes to be displayed detailed information view **402** in response to detecting a user interaction with the first network device, such as a selection of an overlay or other identifier corresponding to the first network device within augmented reality environment **275** (e.g., selection of a highlighted region over tablet **216** or

selection of the text "Sam's Tablet"). The aforementioned ways that the second network device may initiate the display of detailed information view **402** are merely exemplary and any other ways of triggering the detailed information view may be used without departing from the scope of the present disclosure.

[0100] In some embodiments, a position of detailed information view **402** within the augmented reality environment is selected based on a position of the device within the augmented reality environment. For example, network device **102** may choose to render the display of the detailed information view **402** to the right of tablet **216** so that tablet **216** is not obscured by detailed information view **402**. In other embodiments, the position of detailed information view **402** may be selected such that it overlays the network device (e.g., tablet **216**).

[0101] Detailed information view **402** is depicted having detailed information about tablet **216** and information about network activities of tablet **216**. In some embodiments, prior to causing the display of detailed information view **402**, network device **102** retrieves information about network device **102** from database **300** and/or database **350**. For example, network device **102** may retrieve a name of tablet **216** (e.g., Sam's Tablet), model information (e.g., Tablet Pro 12" (2018 Model), an icon for the device, device characteristic (e.g., 256 GB of storage and Wi-Fi), current network usage (e.g., 2.5 MB/s up and 8.2 MB/s down), a listing of applications using the network (e.g., Media Streaming App, Messages App), a total bandwidth usage this month (e.g., 927 MB), a bandwidth cap (e.g., 2 GB), etc.

[0102] Subsequent to receiving the information, network device **102** may generate additional information about the device or may augment the information with additional data received from other devices. For example, network device **102** may augment the data by generating a pi chart based on the received total bandwidth usage and the bandwidth cap. In another example, network device **102** may retrieve additional information to display in detailed information view **402** from the Internet. For example, network device **102** may utilize the model information and/or device characteristics of tablet **216** to retrieve an icon for tablet **216** and may display the icon in detailed information view **402**. In another embodiment, network device **102** may infer the application corresponding to a network activity by, for example examining the network activity to see whether an application is indicated within the network activity and or by identifying a server corresponding to an origin or destination address of the network activity and identifying an application corresponding to the serve.

[0103] Detailed information view **402** is intended to be exemplary of a detailed view of information that the second network device may display in an augmented reality environment (e.g., augmented reality environment **275**) and is not intended to be limiting. For example, detailed information view may comprise additional information not depicted in detailed information view **402**, may be scrollable, may comprise buttons or other actionable interface items, etc. For example, detailed information view may comprise buttons to modify the bandwidth and/or data cap of tablet **216**.

[0104] FIG. 5A shows an exemplary embodiment of a UI element representing a connection between multiple network devices, in an accordance with some embodiments of the present disclosure. As discussed above, a device (e.g., router **214** or network device **102**) may monitor the network activity of devices on a network and may store information about the network activity in database **300** and/or database **350**. In some embodiments, the second network device may display a UI element representing a connection between devices in the augmented reality environment (e.g., augmented reality environment **275**) to indicate when two devices are communicating with each other, as depicted in exemplary connection view **500**. For example, when the second network device determines that the streaming box (e.g., stream box **212**) and the tablet (e.g., tablet **216**) are communicating with each other, network device **102** may display a UI element representing a connection (e.g., connection **504**) between stream box **212** and tablet **216** within augmented reality environment **275**. When the second network device (e.g., network device **102**) determines that

camera **206** is communicating with speaker **210**, the second network device may display connection **502** between camera **206** and speaker **210**.

[0105] For example, network device **102** may access database **350** and may identify network traffic that is both originating from and destined to devices within environment **250**. For example, network device **102** may identify the network addresses (e.g., IP addresses) of all devices within environment **250** and may filter database entries in database **350** based on the network addresses. When network device **102** determines that two devices are communicating with each other (e.g., a network activity has an origin IP address corresponding to tablet **216** and a destination of the network activity has a destination IP address corresponding to stream box **212**), network device **102** may generate within augmented reality environment **275** a connection between the two devices (e.g., connection **504**).

[0106] In some embodiments, a size of the UI element representing the connection is based on a parameter of the network activity, such as a bandwidth. The bandwidth of the network activity may be retrieved by network device **102** from database **350**. For example, connection **504** may be displayed wider than connection **502** when a bandwidth of a network activity between stream box **212** and tablet **216** is larger than a bandwidth of a network activity between camera **206** and speaker **210**. Network device **102** may adjust the width dynamically as the bandwidth of the network activity changes. For example, when a bandwidth of the network activity between stream box **212** and tablet **216**, network device **102** may automatically decrease the width of connection **504**.

[0107] In some embodiments, network device **102** may modify a display characteristic of the UI element representing the connection between the devices based on a parameter of the network activity. For example, network device **102** may display an arrowhead on connection **504** near stream box **212** when tablet **216** is uploading more data to stream box **212** than it is receiving. In some embodiments, the displayed connection (e.g., connection **502** or connection **504**) may have multiple additional connections. For example, connection **502** may comprise a first connection to depict an upload network activity and may comprise a second connection to depict a download network activity.

[0108] In some embodiments, network device **102** may animate the UI element representing the connection between the devices based on a parameter of the network activity. For example, network device **102** may display a flowing animation (e.g., using dots, bars, colors, etc.) from tablet **216** to stream box **212** to depict a flow of data from tablet **216** to stream box **212**. The direction of the flow may be based on a determination, by network device **102**, that more data is being transferred to stream box **212** by tablet **216** than stream box **212** to tablet **216** (e.g., by accessing the data stored in database **350**). In some embodiments, the system may pulse the UI element (e.g., connection **504**) based on a network parameter. For example, connection **504** may pulse based on a bandwidth corresponding to the network activity between stream box **212** and tablet **216**. In another example, network device **102** may display static or noise around the connection to indicate that the signal is experiencing poor connectivity.

[0109] In some embodiments, network device **102** may indicate a parameter of the network activity based on a color of the UI element. For example, when a signal strength between tablet **216** and stream box **212** is weak, network device **102** may display the UI element (e.g., connection **504**) in a red color, whereas the connection may be displayed in a green color when the signal strength is excellent. In some embodiments, the color may be based on other network parameters, such as an error/retransmit rate.

[0110] In some embodiments, the UI element is displayed such that it appears as if it exists in a three-dimensional augmented reality environment. For example, when stream box **212** is located farther away from tablet **216**, relative to network device **102**, the connection may taper such that a terminal end of connection **504** that is closer to stream box **212** appears smaller than a terminal end of connection **504** to tablet **216**. In some embodiments, drop shadows may be used to enhance the

effect that connection **504** exists in augmented reality environment **275**.

[0111] In some embodiments, the UI element may be user selectable so that the user may view additional information about the network activity corresponding to the connection. For example, network device **102** may detect a user touch input on connection **504** and in response to detecting the user touch input may display details about the network activity between stream box **212** and tablet **216**, as discussed further below.

[0112] FIG. **5b** shows an exemplary embodiment (e.g., exemplary detailed connection view **550**) of a UI element (e.g., UI element **552** indicating details of a network activity) indicating details of a network activity between devices, in accordance with some embodiments of the present disclosure. In some embodiments, network device **102** may automatically display UI element **552** in response to detecting the user approaching the devices that are involved in the network activity. For example, when the network activity is between stream box **212** and tablet **216**, network device **102** may automatically generate the display of network activity overlay **522** in response to detecting that a distance between network device **102** and stream box **212** and/or tablet **216** has decreased (e.g., by using the UWB ranging protocol and/or accessing information in database **300**). In another example, network device **102** may display UI element **552** in response to receiving a selection of any of the devices corresponding to a network activity (e.g., stream box **212** or tablet **216**). In some embodiments, network device **102** pauses the updated rendering of augmented reality environment **275** while displaying UI element **552**.

[0113] UI element **552** may comprise any information about the network activity and or about the devices engaging in the network activity. For example, UI element **552** may comprise information indicating a service corresponding to the network activity (e.g., “Streaming Service”), a connection being used to perform the network activity (e.g., Wi-Fi), a bandwidth of the network activity (e.g., 13.2 Mb/s), and quality of the wireless signal strength between the devices.

[0114] In some embodiments, network device **102** may generate information for including in UI element **552** and/or any other UI element, overlay, display, etc. to help a user diagnose network issues. For example, network device **102** may receive an indication of Wi-Fi signal strength as measured in dBm. However, many users may not be familiar with the measure of dBm so network device **102** may generate a user accessible indication of the signal strength by translating the dBm measure into something that is more easily understandable by the user (e.g., an indication of Excellent, Good, Bad, etc.).

[0115] The information depicted in UI element **552** is intended to be exemplary and not limiting, and any information may be included without departing from the scope of the present disclosure, such as any information stored in database **300** and/or **350**, information from a server on the Internet, or any information retrieved from any network device (sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214**, and/or tablet **216**).

[0116] FIG. **6** shows an exemplary embodiment of a detailed view of network activities of multiple devices (e.g., multi device view **600**), in an accordance with some embodiments of the present disclosure. Multi device view **600** is depicted having two UI elements depicting devices and/or services that are not detected within environment **250**, one for devices that are located within the home but are not within environment **250** (e.g., UI element **608**), and one for devices that are located outside of the user's home (e.g., UI element **604**) and or devices that are located in environment **250** but may not have a UWB radio and/or whose position was not detected using the camera or another method. Any number of UI elements and categorizations may be used without departing from the scope off the present disclosure. For example, one UI element may correspond to wired devices and/or services accessed via a wireless network.

[0117] UI element **604** is depicted having services that are located outside of the user's home. In some embodiments, network device **102** causes the display of UI element **604** in response to detecting that one or more devices detected within environment **250** are communicating with devices and/or services located outside of a user's home.

[0118] For example, network device **102** may detect that tablet **216** is communicating with a service or device outside of the home based on inspecting the network traffic of tablet **216** and determining that a destination IP address of the network activity is for a public IP address. Using the public IP address, network device **102** may determine a service to which tablet **216** is communicating. In other embodiments, network device **102** may receive an indication of the service and/or device from a database (e.g., database **300** and/or database **350**) or from the device itself (e.g., an application running on tablet **216**). In response to detecting the service and/or device, network device **102** may display a logo for the service and a name for the service in UI element **604** (e.g., because the service is located outside of the user's home). In some embodiments, network device **102** may display parameters of the network activity between tablet **216** and the service, such as an application corresponding to the network activity, a connection type (e.g., Wi-Fi), a bandwidth, etc.

[0119] Network device **102** may display a UI element, such as a connection, between tablet **216** and an identifier for the service (e.g., logo **610**) to indicate in the augmented reality environment (e.g., augmented reality environment **275**) that tablet **216** is communicating with an Internet based service (e.g., the service corresponding to logo **610**). In some embodiments, network device **102** may animate, color, or otherwise modify connection **602** (as indicated above with respect to FIG. 5) to indicate information about the network activity between tablet **216** and the service corresponding to logo **610**.

[0120] UI element **608** is depicted having devices that are located within the user's home, but are not detected (e.g., by network device **102**) within environment **250**. In some embodiments, network device **102** causes the display of UI element **608** in response to detecting that one or more devices detected within environment **250** (e.g., sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214**, and/or tablet **216**) are communicating with devices and/or services located on a LAN, but are not detected in environment **250** (e.g., because the devices do not have a UWB radio and/or were not added to database **300**).

[0121] For example, network device **102** may detect that stream box **212** is communicating with a service or device inside of the home (e.g., the corresponding to the logo of tablet **612**) based on inspecting the network traffic of tablet **216** and determining that a destination IP address of the network activity is for a local IP address. Using the IP address, network device **102** may search database **300** to determine whether information about the device (e.g., tablet **612**) is stored in database **300**. For example, information about the device (e.g., tablet **612**) may be stored in database **300** when network device **102** once detected the device but it is no longer present in environment **250** (e.g., because the device moved). In such embodiments, network device **102** may retrieve the information about the device from database **300** and may retrieve information about the network activity between the devices from database **350** and/or from the devices themselves (e.g., an application running on stream box **212** or tablet **612**). In response to detecting the service and/or device, network device **102** may display a logo for the device and a name for the device in UI element **608** (e.g., because the device is located inside of the user's home but is not detected in environment **250**). In some embodiments, network device **102** may display parameters of the network activity such as an application corresponding to the network activity, a connection type (e.g., Wi-Fi), a bandwidth, etc.

[0122] Network device **102** may display a UI element, such as a connection, between stream box **212** and the identifier of the tablet **612** to indicate in the augmented reality environment (e.g., augmented reality environment **275**) that stream box **212** is communicating with another device on the local network that is not in environment **250** (e.g., "Mom's Tablet"). In some embodiments, network device **102** may animate, color, or otherwise modify connection **602** (as indicated above with respect to FIG. 5) to indicate information about the network activity between stream box **212** and tablet **612**.

[0123] The information depicted in multi device view **600** is meant to be exemplary and not

limiting. Any type of information about devices, network activities, etc. may be displayed using a variety of methods, examples of which are described herein, without departing from the scope of the present disclosure.

[0124] FIG. 7 shows an exemplary embodiment of controlling a network device using a UI element, in an accordance with some embodiments of the present disclosure. In some embodiments, exemplary control interface **700** is depicted showing a user controlling an UI element in accordance to some embodiments of the present disclosure. The exemplary embodiment of controlling a device using an UI element is merely exemplary and other method of controlling various parameters of devices and/or parameters of network activities may be used without departing from the scope of the present disclosure.

[0125] In some embodiments, network device **102** may display a UI element (e.g., connection **504**) between two devices that are communicating over a LAN. For example, network device **102** may allow a user to decrease a bandwidth of the network activity between tablet **216** and stream box **212** based on receiving a pinch in gesture on connection **504** and may allow a user to increase a bandwidth of the network activity based on receiving a pinch outward gesture on connection **504**. For example, response to detecting a one or more touch points above connection **504** on display **104**, network device **102** may track the location of the touch points. As network device **102** determines that the touch points are getting closer, network device **102** may determine that the user is decreasing the bandwidth of connection **504**. When network device **102** determines that the touch points are getting farther away, network device **102** may determine that the user is increasing a bandwidth for the network activity.

[0126] In response to receiving the user input, the network device **102** may modify the parameter (e.g., bandwidth) of the network activity. For example, a device (e.g., router **214**) may comprise control circuitry (e.g., control circuitry **804**) configured control parameters of network activities. Network device **102** may transmit a request to router **214** comprising the request to control a parameter of a network activity between tablet **216** and stream box **212**. For example, network device **102** may transmit a packet to router **214** comprising an identifier for tablet **216** and stream box **212** (e.g., an IP address, MAC address, or other device ID), a parameter to control (e.g., a bandwidth) and a value corresponding to the parameter (e.g., a maximum bandwidth of 8 Mb/s. In response to receiving the packet, the device (e.g., router **214**) may update the parameter of the network activity. For example, in response to receiving the packet, router **214** may update a database entry corresponding to the network activity and/or tablet **216** and stream box **212** to reflect the bandwidth limit. Router **214** may enforce the bandwidth limit by throttling communication that occurs between the two devices that is routed through router **214**. In some embodiments, the request by network device **102** may be routed through one or more intermediary devices, such as a network switch, over the Internet, over any of the devices depicted in environment **250**, etc.

[0127] In some embodiments, changing the parameter of a first network activity (e.g., changing the bandwidth of a video stream) may come at an expense of a same parameter of a second network activity. For example, when network device **102** increases an amount of available bandwidth to tablet **216** and stream box **212** for the streaming activity, an amount of bandwidth for a streaming activity of smart TV **204** may be automatically decreased (e.g., by network device **102** requesting a decrease in the bandwidth or by router **214** automatically managing the bandwidth via, for example, quality of service settings.

[0128] In another example, the control of the network parameter may be handled by an application on one of the communicating devices (e.g., tablet **216** and stream box **212**) and/or AR device (e.g., network device **102**). For example, when the application is running on stream box **212**, network device **102** may transmit the packet to stream box **212** and may control application layer parameters, such as a stream quality to cause the change of the parameter of the network activity.

[0129] In some embodiments, network device **102** may display a confirmation in response to

updating the parameter of the network activity. For example, network device **102** may display overlay **702** confirming the new bandwidth of the network activity between stream box **212** and tablet **216**. Overlay **702** may comprise an updated status of the parameter of the network activity (e.g., an updated value for the bandwidth). In some embodiments, overlay **702** is displayed while the user is modifying the bandwidth (e.g., performing the pinch) so that the user can more precisely set a desired bandwidth. In some embodiments, the size and/or color of the UI element (e.g., connection **504**) while the user is performing the pinch action to more clearly indicate to the user the effect of the change in the parameter. In some embodiments, while network device **102** is attempting to change the parameter of the network activity the UI elements are displayed in a first manner and after confirming the change, the UI elements are displayed in a second manner. For example, while network device **102** is awaiting confirmation of the change in the parameter of the network activity (e.g., bandwidth), the UI element may flash. Once network device **102** confirms the change in the parameter of the network activity (e.g., the change in the bandwidth) the UI element may be displayed without flashing.

[0130] The user input with a UI element depicted in FIG. 7 is merely exemplary and not intended to be limiting. Other interactions with other UI elements may cause the modification of parameters of network activities or control devices, without departing from the scope of the present disclosure. For example, network device **102** may detect a swipe gesture corresponding to the UI element depicting the connection (e.g., connection **504**) between tablet **216** and stream box **212**. Based on receiving the swipe gesture, network device **102** may terminate the network activity between the two devices. For example, network device **102** may transmit a request to one or more applications running on tablet **216** or stream box **212** to terminate the network activity or network device **102** may transmit a request to router **214** to terminate the network activity. For example, in response to receiving the request, router **214** may block communications between tablet **216** and stream box **212** by dropping packets.

[0131] In some embodiments, network device **102** may detect a long press on a UI element (e.g., connection **504**) to reveal more information about a network activity corresponding to the UI element. For example, when network device **102** detects a long press on connection **602**, network device **102** may display a list of websites being access by tablet **216**. A user may swipe or select another UI element to block access to the website, change a parameter of the network activity corresponding to the service/website, etc.

[0132] In some embodiments, network device **102** may display parent control setting for a device based on a detecting a user selection of the device and or UI element corresponding to the device (e.g., connection **602** or an indicator corresponding to tablet **216**). Network device **102** may display parental control settings that allow a user to limit the bandwidth of a device, set allowed or denied websites (a user may select websites from a list of websites previously accessed by the device, retrieved from database **350**), set time limits for when a device can access a LAN or WAN, set a bandwidth limit, set a network usage cap, block or allow specific applications, etc.

[0133] In some embodiments, network device **102** may allow a user to block a device from accessing a network by receiving a user input via a UI element. For example, a user can flick an indicator for a device downward to block the device from accessing the network. For example, when network device **102** detects that user flicking up a UI element corresponding to tablet **216**, network device **102** may transmit to router **214** a request to remove tablet **216** from a RADIUS access control list of router **214**. The request sent by network device **102** to router **214** may include, for example, a hardware address of the second wireless radio of the first device (e.g., MAC address for the Wi-Fi radio). In some embodiments, in response to blocking a device, network device **102** may display a UI element listing the blocked device(s) and or may display an icon over the device within augmented reality environment **275**. For example, network device **102** may display a UI element such as UI element **608** and/or UI element **604** that is designated for blocked devices.

[0134] In some embodiments, network device **102** may allow a user to reset a network connection

of a device by receiving a user input via a UI element. For example, a user can flick upwards an indicator for a device to reset a network connection for the device. For example, a user can flick an indicator for a device upward (e.g., a UI element corresponding to tablet **216**) to reset a connection corresponding to the second wireless radio (e.g., the Wi-Fi radio of tablet **216**). Network device **102** may transmit to router **214** a request to reset the network connection corresponding to the second wireless radio of tablet **216** by, for example, including a hardware address of the second wireless radio of the first device (e.g., MAC address for the Wi-Fi radio) and a request to drop the device's network address translation table (NAT) lease, thereby resetting the IP address of the device.

[0135] By enabling a user to identify devices within an augmented reality environment (e.g., augmented reality environment **275**) network device **102** can limit the displayed available control options such that only options that correspond to a detected device are displayed. For example, only options corresponding to tablet **216** are displayed when the user selects tablet **216** in augmented reality environment **275**. Accordingly, a user can easily identify and control devices within a network.

[0136] In some embodiments, network device **102** may display the status of a network activity involving itself. For example, network device **102** may display a UI element to indicate a parameter of a network activity, such as a signal strength between network device **102** and router **214**. The indicator may be placed, for example, in a top bar of augmented reality environment **275** or may be displayed in full screen. For example, while a user is walking around environment **250**, display **104** may fill with static as the signal strength parameter of the network activity between network device **102** and router **214** decreases and become clear as the signal strength parameter of the network activity between network device **102** and router **214** increases.

[0137] FIG. **8** shows an illustrative, generalized embodiment of illustrative device **800**. Device **800** is depicted having components that are internal and external to device **800**, for example, processing circuitry **806**, storage **808**, and communications circuitry, such as Wi-Fi radio **816** and UWB radio **818**, which may each include one or more wireless antennas, input/output (hereinafter "I/O") interface **810**, display **812**, and communications path **802**. In some embodiments, each of the devices described herein (e.g., network device **102**, sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214**, and/or tablet **216**) may comprise some or all of the components of device **800**.

[0138] I/O interface **810** may provide content and data to control circuitry **804** and control circuitry **804** may be used to send and receive commands, requests, and other suitable data using I/O interface **810**. I/O interface **810** may connect control circuitry **804** (and specifically processing circuitry **806**) to one or more communications paths (e.g., Wi-Fi radio **816**, UWB radio **818**, path **802**). I/O functions may be provided by one or more of these communications paths, that may be shown as a single path in FIG. **8** to avoid overcomplicating the drawing.

[0139] Control circuitry **804** may be based on any suitable processing circuitry such as processing circuitry **806**. As referred to herein, processing circuitry should be understood to mean circuitry based on one or more microprocessors, microcontrollers, digital signal processors, programmable logic devices, field-programmable gate arrays (FPGAs), application-specific integrated circuits (ASICs), GPUs, etc., and may include a multiple parallel processing cores or redundant hardware. In some embodiments, processing circuitry **806** may be distributed across multiple separate processors or processing units, for example, multiple of the same type of processors or multiple different processors. In some embodiments, control circuitry **804** executes instructions stored in memory (i.e., storage **808**). Specifically, control circuitry **804** may be instructed to perform the functions discussed above and below. For example, network device **102** may provide instructions to control circuitry **804** to generate augmented reality environment **275** and control devices on a network (e.g., network device **102**, sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214**, and/or tablet **216**).

[0140] In some embodiments, control circuitry **804** may include communications circuitry (e.g., Wi-Fi radio **816** and/or UWB radio **818**) suitable for communicating with other networks (e.g., a LAN or a WAN), servers (e.g., a server accessed via the Internet or databases **300**, **350** and **910**), or devices (e.g., network device **102**, sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214**, and/or tablet **216**). The instructions for carrying out the above-mentioned functionality may be stored on database **910**. The communications circuitry may include a modem, a fiber optic communications device, an Ethernet card, or a wireless communications device for communicating with other devices. Such communications may involve the Internet or any other suitable communications networks or paths. In addition, communications circuitry may include circuitry that enables peer-to-peer communication between devices (e.g., using UWB radio **818**).

[0141] Memory may be an electronic storage device provided as storage **808** that is part of control circuitry **804**. As referred to herein, the phrase “electronic storage device” or “storage device” should be understood to mean any device for storing electronic data, computer software, or firmware, such as random-access memory, read-only memory, hard drives, optical drives, solid state devices, quantum storage devices, or any other suitable fixed or removable storage devices, and/or any combination of the same. Storage **808** may be used to store various types of data herein, such as instructions for performing the methods described herein, database **300**, database **350** any statuses of parameters of network activities, and/or information about devices. Nonvolatile memory may also be used (e.g., to launch a boot-up routine and other instructions). Cloud-based storage (e.g., storage accessed via the Internet) may be used to supplement storage **808** or instead of storage **808**.

[0142] A user may send instructions to control circuitry **804** using I/O interface **810** using an external device such as a remote control, mouse, keyboard, touch screen, etc. In some embodiments, control circuitry **804** correlates a user input with a location of a user interface element and performs an action based on the selected user interface element. Display **812** may be provided as a stand-alone device or integrated with other elements of device **800**. For example, display **812** may be a touchscreen or touch-sensitive display and may be combined with I/O interface **810**.

[0143] The system and methods described herein may be implemented using any suitable architecture. For example, it may be a stand-alone application wholly implemented on device **800**. In such an approach, instructions of the application are stored locally (e.g., in storage **808**). In some embodiments, the systems and methods described herein may be a client-server-based application. Data for use by a thick or thin client implemented on device **800** is retrieved on-demand by issuing requests to a server remote to the device **800**. In some embodiments, the systems and methods provided herein are downloaded and interpreted or otherwise run by an interpreter or virtual machine (run by control circuitry **804**). In some embodiments, some functions are executed and stored on one device and some are executed and stored on a second device. For example, network device **102** may display augmented reality environment **275** while router **214** controls a QoS and monitors and logs network activities.

[0144] FIG. **9** shows an exemplary network configuration, in accordance with some embodiments of the present disclosure. Network configuration **900** is showing depicting a plurality of devices, stream box **212**, tablet **216**, router **214**, speaker **210**, network device **102** and database **910**. In some embodiments, database **910** comprises database **300** and/or database **350**. As depicted in network configuration **900**, network device **102** may utilize UWB radio **818** of network device **102** to discovery a plurality of devices. For example, network device **102** may perform a ranging and discovery protocol with between UWB radio **818** of network device **102** and UWB radio **818** of tablet **216**, UWB radio **818** of speaker **210**, and UWB radio **818** of stream box **212**. In some embodiments, network device **102** may transmit the results of the ranging and discovery protocol to database **910**. For example, network device **102** may transmit, over Wi-Fi radio **816**, the device

names, identifiers (e.g., IP addresses), name etc. for storage on database **910** (e.g., which may comprise database **300** and/or database **350**).

[0145] FIG. **10** shows an exemplary process for discovering devices, in an accordance with some embodiments of the present disclosure. Process **1000** begins at **1002** where network device **102**, using control circuitry, such as control circuitry **804**, discovers UWB peer devices and begins ranging. For example, control circuitry **804** may discover UWB peer devices by listing, via UWB radio **818**, for other signals on the UWB frequency spectrum. For example, control circuitry **804** of network device **102** may detect via UWB radio **818** a signal from UWB radio **818** of tablet **216**. In response to detecting the signal, control circuitry **804** of network device **102** may begin the ranging process as described above. For example, control circuitry **804** may receive a network address for the UWB radio **818** of tablet **216** and may compute a time of flight and an angle of arrival of the signal from UWB radio **818** of tablet **216**. Subsequent to performing the ranging, control circuitry **804** may store the results of the ranging in database **910**. For example, control circuitry **804** may transmit the results of the ranging (e.g., UWB identifier, relative position, and relative distance) over Wi-Fi radio **816** to be stored in database **910**. In other embodiments, control circuitry **804** may store the results of the ranging in a local database such as on storage **808**. Control circuitry **804** may repeat this process in parallel for each of the other detected devices (e.g., streaming device **212**). It should be noted that process **1000**, or any step thereof, could be performed on, or provided by, any of the devices shown in FIGS. **1-9**.

[0146] At **1004**, control circuitry **804** of network device **102** initiates a session with each peer device. For example, control circuitry **804** may initiate a UWB communications session with tablet **216** via the respective UWB radios **818** of each device and may transmit additional information about each of the devices during the session.

[0147] At **1006**, control circuitry **804** acquires an IP address and other info for each peer device. For example, control circuitry **804** may request during the session via UWB radio **818** information about other radios of the peer devices (e.g., about Wi-Fi radio **816** of tablet **216**, such as an IP address), information about the device itself (e.g., a device name, OS, device capabilities, installed applications, etc.), and/or information about a network activity of the device (e.g., whether the device streaming content).

[0148] At **1008**, control circuitry **804** of network device **102** stores the acquired information in a database that is keyed based on the UWB identifier. For example, control circuitry **804** of network device **102** may store the acquired information in a database **910**. Database **910** may be organized such that a primary key for the database is represented by the UWB identifier of the network device as depicted in database **300** of FIG. **3A**. Control circuitry **804** may repeat **1004**, **1006**, and **1008** until control circuitry **804** acquires IP addresses and other information from each of the detected devices (e.g., sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214**, and/or tablet **216**).

[0149] It is contemplated that the steps or descriptions of FIG. **10** may be used with any other embodiment of this disclosure. In addition, the descriptions described in relation to the algorithm of FIG. **10** may be done in alternative orders or in parallel to further the purposes of this disclosure.

[0150] FIG. **11** shows an exemplary process for indicating a location of a device within an image, in an accordance with some embodiments of the present disclosure. In some embodiments, the process **1100** is performed by control circuitry **804** to generate augmented reality environment **275**. Process **1100** begins at **1102** where network device **102**, using control circuitry, such as control circuitry **804**, activates a device camera and displays a current field of view. For example, control circuitry **804** may activate a device camera (e.g., camera **106** of network device **102** via I/O interface **810** or path **802**. For example, control circuitry **804** may receive an image from camera **106** and may generate the received image on a display (e.g., display **812** and/or display **104**). In some embodiments, control circuitry **804** may continually receive new pictures from camera **106** (e.g., at a rate of 24 Hz images as to generate a video on display **812** and/or **104**). It should be noted

that process **1100**, or any step thereof, could be performed on, or provided by, any of the devices shown in FIGS. **1-9**.

[0151] At **1104**, control circuitry **804** of network device **102** queries the database for all known UWB devices within range. For example, control circuitry **804** may query database **910** or database **300** to receive information stored in the database about all known devices (e.g., sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214**, and/or tablet **216**). In some embodiments, control circuitry **804** may transmit the request over Wi-Fi radio **816** or may transmit the request to a local database stored on storage **808**.

[0152] At **1106**, control circuitry **804** identifies a peer device location for devices within the image (e.g., sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214**, and/or tablet **216**). For example, control circuitry **804** may determine a position of each device within the image based on correlating the relative location and the distance stored in the database with pixels of the image. In some embodiments, control circuitry **804** may determine that the peer devices are visible via a transparent or semi-transparent display.

[0153] At **1108**, control circuitry **804** renders a visual identifier of the device. For example, control circuitry **804** may generate a display of a circle (or any other visual indicator) around the detected device (e.g., tablet **216**) as depicted in augmented reality environment **275**. Control circuitry **804** may utilize the detected position of the device within the image to determine the position for the visual indicator. For example, the indicator may be centered at the position within the image or may be placed proximate to the position.

[0154] At **1110**, control circuitry **804** renders a name of the device. For example, control circuitry **804** may retrieve the name of tablet **216** at **1104** and may display the retrieved name proximate to the location of the device (e.g., overlaying the device or next to the device).

[0155] At **1112**, control circuitry **804** response to user input on the display. For example, control circuitry **804** may monitor (e.g., poll or receive interrupts from) I/O interface **810** that is connected to a touchscreen of display **812**. In response to detecting user input, control circuitry **804** may correlate the user input on the touch screen with a displayed object or UI element displayed on display **812**. In response to identifying the UI element that which the user is interacting, control circuitry **804** may determine an action to perform based on the user input. For example, control circuitry **804** may detect a swipe up on tablet **216** and based on the swipe up, may reset a network connection of tablet **216**.

[0156] At **1114** control circuitry **804** updates the display based on the user input. For example, control circuitry **804** may cause the display of an icon on display **812** to indicate that the network connection of tablet **216** is being reset and may clear the IP address and other network information from database **300**.

[0157] At **1116**, control circuitry **804** updates display of peer devices as locations are updated. For example, when control circuitry **804** detects that one of the devices has moved (e.g., based on detecting and performing the UWB ranging protocol or based on determining that a database entry for the device comprises a new relative position and/or distance, control circuitry **804** may cause the display of an updated augmented reality environment **275** where the position of the visual identifiers and/or names are updated to reflect the current positions.

[0158] It is contemplated that the steps or descriptions of FIG. **11** may be used with any other embodiment of this disclosure. In addition, the descriptions described in relation to the algorithm of FIG. **11** may be done in alternative orders or in parallel to further the purposes of this disclosure.

[0159] FIG. **12** shows an exemplary process for identifying a network activity, in an accordance with some embodiments of the present disclosure. Process **1200** begins at **1202** where control circuitry **804** (e.g., control circuitry **804** of network device **102** and/or control circuitry **804** of router **214**) begins packet capture and analysis. For example, control circuitry **804** may monitor network traffic between devices (e.g., network device **102**, sensor **202**, smart TV **204**, camera **206**, thermostat **208**, speaker **210**, stream box **212**, router **214**, and/or tablet **216**) by analyzing packets

sent by each of the devices. In some embodiments, this process is performed locally (e.g., the processing is done by the device performing the packet capture, or remotely, the processing is done by a second device).

[0160] At **1204**, control circuitry **804** extracts source and destination address information. For example, control circuitry **804** may examine a packet header to extract the source and destination information (e.g., IP addresses) from the packet header. Control circuitry **804** may store the information about the network activity such as the source and destination information, a size of a payload, a speed of transmission, etc. in database **910** and/or database **350**. For example, control circuitry **804** may extract from the header of the packet an IP address for tablet **216** as the source and an IP address for stream box **212** as the destination.

[0161] At **1206**, control circuitry **804** scans a database for an associated UWB identifier associated with each network address. For example, control circuitry **804** may determine that the packet header comprises a local IP address for both the source and destination addresses (e.g., IP addresses assigned to Wi-Fi radio **816** corresponding to each device). Control circuitry **804** may search database **300** to identify a UWB identifier corresponding to the local IP address. For example, control circuitry **804** may identify a UWB identifier for tablet **216** when control circuitry **804** detects the source IP address for tablet **216** in the packet header and may identify a UWB identifier for stream box **212** when control circuitry **804** detects the destination IP address for stream box **212** in the packet header.

[0162] At **1208**, control circuitry **804** retrieves position information for each UWB identifier. For example, control circuitry **804** may search database **300** based on the UWB identifier to identify a relative position of tablet **216** and stream box **212** by searching database **300** using the UWB identifier for each respective device.

[0163] At **1210**, control circuitry **804**, activates a camera (e.g., camera **106** of network device **102** via I/O interface **810** or path **802**) and displays the current field of view from the camera. For example, control circuitry **804** may display environment **250** as detected by camera **106** on display **812** and/or display **104**.

[0164] At **1212**, for network activity with a source and destination within a current field of view, control circuitry **804** renders a UI element over the video. For example, control circuitry **804** may render the traffic flow on an augmented reality display (e.g., augmented reality environment **275**). For example, based on the position of tablet **216** and stream box **212** within augmented reality environment **275**, control circuitry **804** may cause the display of a UI element (e.g., connection **504** between tablet **216** and stream box **212**).

[0165] At **1214**, for network activity over the Internet, control circuitry **804** renders a UI element on a first area of the screen. For example, control circuitry **804** may render UI element **604** comprising a listing of devices and/or services that are accessed over the Internet. Control circuitry **804** may display a UI element connecting the devices and services within UI element **604** to devices in environment **250**. For example, control circuitry **804** may generate the display of connection **602** between tablet **216** and a service in UI element **604** based on determining that a network activity is between tablet **216** and a service on the Internet (e.g., by inspecting the source and destination addresses in the destination and source fields of a packet header).

[0166] At **1216**, for network activity that occurs outside of a field of view, control circuitry **804** renders a UI element to a second area of the screen. For example, control circuitry **804** may display UI element **608** which may comprise a listing of devices to which a device within the field of view is communicating, such as tablet **616**. For example, when stream box **212** is communicating with tablet **616**, and tablet **616** is not within the field of view, control circuitry **804** may display a UI element, such as connection **606** which connects stream box **212** to indicate that both devices are communicating over a network connection (e.g., a connection via their respective Wi-Fi radios **816**).

[0167] At **1218**, control circuitry **804** maps traffic characteristics to on-screen visual characteristics. For example, control circuitry **804** may animate or color connections **504**, **602** and **606** based on

statuses of parameters of the network activities to which the connections correspond. For example, when an available bandwidth for the network activity between stream box **212** and tablet **616** is low, connection **606** may be displayed in red. Other examples of depicting such connections based on characteristics of the network activity are described above with respect to FIG. 5.

[0168] At **1220**, control circuitry **804** updates the display based on user input. For example, when control circuitry **804** determines that the device (e.g., network device **102**) rendering augmented reality environment **275** has moved (e.g., based on receiving input from an accelerometer via I/O interface **810** or path **802**), control circuitry **804** may update the display to include new locations of each of the devices. In another example, when control circuitry **804** determines that a user has selected a UI element (e.g., based on receiving the user input via a touch screen connected to I/O interface **810** or path **802**), control circuitry **804** may update the display to include an action corresponding to the user input (e.g., control circuitry **804** may display detailed information view **402** and/or UI element **552** comprising detailed network and/or device information).

[0169] It is contemplated that the steps or descriptions of FIG. **12** may be used with any other embodiment of this disclosure. In addition, the descriptions described in relation to the algorithm of FIG. **12** may be done in alternative orders or in parallel to further the purposes of this disclosure.

[0170] FIG. **13** shows an exemplary process for controlling a network device based on a user input, in an accordance with some embodiments of the present disclosure. Process **1300** begins at **1302** where network device **102**, using control circuitry, such as control circuitry **804**, receives user input on discovering device display. For example, control circuitry **804** may receive input via I/O path **810** from a touchscreen corresponding to display **812**.

[0171] At **1304**, control circuitry **804** identifies an underlying UI element or device at the location of the input. For example, control circuitry **804** correlates the location of the touch input with the location of a device (e.g., tablet **216**) or UI element (e.g., connection **504**, detailed information view **402**, etc.)

[0172] At **1306**, control circuitry **804** determines an input gesture. For example, control circuitry **804** may determine, based on information received from I/O interface **810** or path **802**, whether the user input is a swipe, a long press, a short press, a pinch, etc.

[0173] At **1308**, control circuitry **804** maps the gesture interface object to a management action. For example, long pressing on a device (e.g., tablet **216**) may cause the display of detailed information about the device (e.g., detailed information view **402**) while long pressing on a connection (e.g., connection **504**) may cause a display of detailed information about a network activity (e.g., UI element **552**) corresponding to the connection. In another example, a swipe over connection **504** may terminate a network activity between stream box **212** and tablet **216**. Additional types of gestures and management actions are described above with respect to FIG. **7**.

[0174] At **1310**, control circuitry **804** transmits the management action to the device. For example, when the management action is to terminate the network activity between tablet **216** and stream box **212**, control circuitry **804** may transmit the management action to router **214** via Wi-Fi radio **816** (e.g., so router **214** can drop packets with an origin and/or source for either device) or may transmit the management action to either of the devices (e.g., tablet **216** or stream box **212**). For example, control circuitry **804** may transmit over Wi-Fi radio **816** the management action to Wi-Fi radio **816** of tablet **216** or Wi-Fi radio **816** of stream box **212**.

[0175] At **1312**, control circuitry **804** updates the display based on the management action. For example, control circuitry **804** may receive (via Wi-Fi radio **816**) a confirmation that the network activity between tablet **216** and stream box **212** has been terminated. In response to receiving the confirmation, control circuitry **804** may cease displaying connection **504** or may display an animation indicating that the network activity has terminated.

[0176] It is contemplated that the steps or descriptions of FIG. **13** may be used with any other embodiment of this disclosure. In addition, the descriptions described in relation to the algorithm of FIG. **13** may be done in alternative orders or in parallel to further the purposes of this disclosure.

[0177] FIG. 14 shows an exemplary process for identifying network devices in an augmented reality environment, in an accordance with some embodiments of the present disclosure. Process 1400 begins at 1402 where network device 102, using control circuitry, such as control circuitry 804, detects, at a second network device, a signal from a first wireless radio of a first wireless device. For example, control circuitry 804 of network device 102 may detect a UWB signal from UWB radio 818 of tablet 216.

[0178] At 1404, control circuitry 804 determines, based on the signal, a position of the first network device relative to the second network device. For example, control circuitry 804 may use a UWB ranging protocol to detect a position and distance of tablet 216 to network device 102 (e.g., based on computing a time of flight for the UWB signal from UWB radio 818 of tablet 216 and angle of arrival of a signal as received by UWB radio 818 of network device 102).

[0179] At 1406, control circuitry 804 receives a name of the first network device and a network address corresponding to a second wireless radio of the first network device. For example, control circuitry 804 of network device 102 may receive a name of tablet 216 via UWB session between both devices. Tablet 216 may additionally transmit an indication of a network address (e.g., an IP address and/or a MAC address) corresponding to a second wireless radio of tablet 216 (e.g., Wi-Fi radio 816 of tablet 216).

[0180] At 1408, control circuitry 804 generates for display an image from the camera. For example, control circuitry 804 may generate for display on display 104 and/or display 812 an image from camera 106 received by control circuitry 804 via I/O interface 810. In some embodiments, control circuitry 804 may continually (e.g., at 30 Hz) receive images from camera 106 as to generate the display of a video on display 104 and/or display 812. In an embodiment, the control circuitry 804 does not generate for display the image. For example, the display may be an OST display that “displays” a scene by allowing light to pass through the display. In some embodiments, control circuitry 804 may determine that the first network device is visible via the display of the second network device.

[0181] At 1410, control circuitry 804 determines a position of the first network device within the image and/or display provided at the display 812. For example, control circuitry 804 may correlate the relative position of tablet 216 relative to network device 102 to a position within the image. For example, control circuitry 804 may identify a pixel and/or pixels corresponding to the first network device based on the relative position. In some embodiments, control circuitry 804 may determine the position within a transparent or semi-transparent display and may identify a pixel and/or pixels corresponding to the first network device within the transparent or semi-transparent display.

[0182] At 412, control circuitry 804 generates for display an overlay at the position comprising the network address and the name of the first network device. For example, control circuitry 804 may generate an overlay comprising the network address (e.g., the IP address of Wi-Fi radio 816 of tablet 216) and a name of tablet 216 (e.g., Tablet). In some embodiments, control circuitry 804 may display additional information about the device and/or a network activity. For example, control circuitry 804 may display, an indicator, such as a circle, centered at the position as depicted in augmented reality environment 275 of FIG. 2. In some aspects, control circuitry 804 may display any of the UI elements overlays, indicators, etc. depicted in FIGS. 1-7.

[0183] It is contemplated that the steps or descriptions of FIG. 13 may be used with any other embodiment of this disclosure. In addition, the descriptions described in relation to the algorithm of FIG. 13 may be done in alternative orders or in parallel to further the purposes of this disclosure.

[0184] FIG. 15 shows an exemplary process for controlling network devices in an augmented reality environment, in an accordance with some embodiments of the present disclosure. Process 1500 begins at 1502 where network device 102, using control circuitry, such as control circuitry 804, detects the first network device within a visual field of a camera of the second network device. For example, network device 102 may detect, via camera 106 of network device 102 that tablet 216 is within a visual field of the camera. For example, control circuitry 804 may utilize an image

processing algorithm to determine that network device **102** is within a visual field of camera **106**, or control circuitry **804** may utilize known characteristics of camera **106** to determine an approximate perimeter of the field of view. Based on the approximate perimeter of the field of view, control circuitry **804** may analyze database **300** and/or database **910** to detect devices that are within the field of view of camera **106** of network device **102**.

[0185] At **1504**, control circuitry **804** retrieves a network address of the first network device. For example, control circuitry **804** may identify the first network device within database **300** and may retrieve a network address corresponding to the first network device from database **300**. For example, control circuitry **804** may identify tablet **216** within database **300** and may retrieve a network identifier (e.g., IP address and/or MAC address) for Wi-Fi radio **816** of tablet **216**.

[0186] At **1506**, control circuitry **804** determines a network activity of the first network device based on the retrieved network address. For example, control circuitry **804** may retrieve, from database **350** and/or database **910** an indication of the network activity of tablet **216**. For example, control circuitry **804** may transmit a request to either database comprising the network identifier (e.g., IP address or MAC address) of tablet **216** and may search for network activities having a source or destination address matching the identifier.

[0187] At **1508**, control circuitry **804** generates for display a status of the network activity and a graphical interface or controlling a parameter of the network activity. For example, control circuitry **804** may generate the display of any of the UI elements described above and depicted in FIGS. **1-7** for controlling a network device. For example, control circuitry **804** may generate a display of connection **504** and enable a user to apply inputs to connection **504** to control a network activity corresponding to the connection. For example, control circuitry **804** may generate the display of connection **504** and allow a user to swipe across connection **504** to cease the network activity between tablet **216** and stream box **212**.

[0188] At **1510**, control circuitry **804** receives a user input that indicates a requested adjustment of the parameter of the network activity via the graphical interface. For example, control circuitry **804** may detect touch input on a touchscreen corresponding to display **104** and/or display **812**. Control circuitry **804** may track the position of the touch inputs to determine that a user pinching in on connection **504**. In response to determining that the user is pinching in on connection **504** (e.g., via the input received via I/O interface **810**), control circuitry **804** may determine that the user requests to decrease a bandwidth of the network activity (e.g., the streaming activity between tablet **216** and stream box **212**).

[0189] At **1512**, control circuitry **804** causes to be adjusted the parameter of the network activity based on the user input. For example, control circuitry **804** may transmit a request to router **214** to limit, throttle and/or deprioritize packets originating and/or destined between tablet **216** and stream box **212**. In another example, control circuitry **804** may transmit a request to tablet **216** or stream box **212** to reduce the bandwidth. For example, control circuitry **804** may transmit the request to an application running on stream box **212** which reduces a quality of the stream in response to receiving the request.

[0190] It is contemplated that the steps or descriptions of FIG. **15** may be used with any other embodiment of this disclosure. In addition, the descriptions described in relation to the algorithm of FIG. **15** may be done in alternative orders or in parallel to further the purposes of this disclosure.

[0191] The systems and processes discussed above are intended to be illustrative and not limiting. One skilled in the art would appreciate that the actions of the processes discussed herein may be omitted, modified, combined, and/or rearranged, and any additional actions may be performed without departing from the scope of the invention. More generally, the above disclosure is meant to be exemplary and not limiting. Only the claims that follow are meant to set bounds as to what the present disclosure includes. Furthermore, it should be noted that the features and limitations described in any one embodiment may be applied to any other embodiment herein, and flowcharts or examples relating to one embodiment may be combined with any other embodiment in a suitable

manner, done in different orders, or done in parallel. In addition, the systems and methods described herein may be performed in real time. It should also be noted that the systems and/or methods described above may be applied to, or used in accordance with, other systems and/or methods.

Claims

1. A system for an augmented reality environment, the system comprising: a first network device; a second network device; and a third network device, wherein the third network device comprises a camera, a display, and control circuitry configured to: capture, via the camera, an image; causing the captured image to be displayed on the display; detect a first signal from the first network device a second signal from the second network device; determine a first relative position of the first network device based on the first signal and a second relative position of the second network device based on the second signal; determine, at least in part on the first relative position and the second relative position, that the first network device and the second network device are visible via the image; identify network traffic between the first network device and the second network device; and causing an overlay to be displayed over the displayed image, wherein the overlay comprises an indication of the network traffic and controllable interface input to modify the network traffic between the first network device and the second network device.
