

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication	20250287751
Kind Code	A1
Publication Date	September 11, 2025
Inventor(s)	Kuo; Shu-Ming

LIGHT EMITTING DEVICE

Abstract

A light emitting device includes a first substrate, a light-emitting unit, a pixel define layer, an adhesive layer and a plurality of scattering particles. The light-emitting unit is disposed on the first substrate. The pixel define layer is disposed on the first substrate and includes an opening. At least one portion of the light-emitting unit is disposed in the opening. The plurality of scattering particles are disposed on the first substrate. At least one portion of the plurality of scattering particles are overlapped with the at least one portion of the light-emitting unit.

Inventors:	Kuo; Shu-Ming (Miaoli County, TW)
Applicant:	Innolux Corporation (Miaoli County, TW)
Family ID:	1000008626542
Assignee:	Innolux Corporation (Miaoli County, TW)
Appl. No.:	19/218563
Filed:	May 26, 2025

Foreign Application Priority Data

CN	202110391116.2	Apr. 12, 2021
----	----------------	---------------

Related U.S. Application Data

parent US continuation 17694693 20220315 parent-grant-document US 12336356 child US 19218563

Publication Classification

Int. Cl.: H10H20/858 (20250101); H01L25/075 (20060101); H10H20/80 (20250101); H10H20/851 (20250101); H10H20/855 (20250101)

U.S. Cl.:

CPC **H10H20/8583** (20250101); **H01L25/0753** (20130101); **H10H20/855** (20250101);
H10H20/8515 (20250101); H10H20/8581 (20250101); H10H20/882 (20250101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a continuation application of and claims the priority benefit of a prior U.S. application Ser. No. 17/694,693, filed on Mar. 15, 2022. The prior U.S. application Ser. No. 17/694,693 claims the priority benefits of China application serial no. 202110391116.2, filed on Apr. 12, 2021. The entirety of each of the above-mentioned patent applications is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND

Technical Field

[0002] The disclosure relates to a light emitting device, particularly to a light emitting device that improves heat dissipation or the service life.

Description of Related Art

[0003] Electronic devices (e.g., display panels) have been widely used in our daily lives. With the vigorous development of electronic devices, the higher the requirements for display quality, electronic devices continue to improve their display effects with larger or higher resolution.

SUMMARY

[0004] According to an embodiment of the present disclosure, the light emitting device includes a first substrate, a light-emitting unit, a pixel define layer, an adhesive layer and a plurality of scattering particles. The light-emitting unit is disposed on the first substrate. The pixel define layer is disposed on the first substrate and includes an opening. At least one portion of the light-emitting unit is disposed in the opening. The plurality of scattering particles are disposed on the first substrate. At least one portion of the plurality of scattering particles are overlapped with the at least one portion of the light-emitting unit.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] The drawings are included for further understanding of the present disclosure, and the drawings are incorporated into this specification and constitute a part of this specification. The drawings illustrate the embodiments of the present disclosure, and together with the description are used to explain the principles of the present disclosure.

[0006] FIG. 1A is a schematic partial top view of a display panel according to an embodiment of the disclosure.

[0007] FIG. 1B is a schematic partial cross-sectional view of the display panel of FIG. 1A along the section line I-I'.

[0008] FIG. 2 is a schematic partial cross-sectional view of a display panel according to another embodiment of the disclosure.

[0009] FIG. 3 is a schematic partial cross-sectional view of a display panel according to another embodiment of the disclosure.

[0010] FIG. 4 is a schematic partial cross-sectional view of a display panel according to another embodiment of the disclosure.

[0011] FIG. 5 is a schematic partial cross-sectional view of a display panel according to another

embodiment of the disclosure.

[0012] FIG. 6 is a schematic partial cross-sectional view of a display panel according to another embodiment of the disclosure.

[0013] FIG. 7 is a schematic partial cross-sectional view of a display panel according to another embodiment of the disclosure.

DESCRIPTION OF THE EMBODIMENTS

[0014] The present disclosure may be understood by referring to the following detailed description in conjunction with the drawings. For readers' understanding and the brevity of the drawings, the drawings of this disclosure only depict part of a light-emitting device, and the specific elements in the drawings are not drawn according to actual scale. In addition, the number and size of each element in the drawings are only for schematic purposes and do not limit the scope of the disclosure.

[0015] Throughout the disclosure and the claims, certain words are used to refer to specific elements. Those skilled in the art should understand that electronic device manufacturers may refer to the same components by different names. This article does not intend to distinguish those elements with the same function but different names. In the following description and claims, the words “having” and “including” are open-ended words, so they should be interpreted as meaning “including but the disclosure is not limited to.” Therefore, when the terms “including,” “containing” and/or “having” are used in the description of the present disclosure, they specify the existence of corresponding features, regions, steps, operations, and/or components, but do not exclude one or more existence of corresponding features, regions, steps, operations, and/or components.

[0016] When an element or a film layer is referred to as being “on” or “connected” to another element or film layer, it may be directly on or directly connected to the other element or film layer. Or, there may be an element or film layer intervening between the two (in the case of indirect contact). Conversely, when an element is referred to as being “directly” on or “directly connected” to another element or film layer, there is no element or film layer intervening between the two. In addition, when an element is referred to as “on another element,” the two are above or below each other in the top view direction, and this element may be above or below the other element, and this above-or-below relationship depends on the orientation of the device.

[0017] Although the terms “first,” “second,” “third,” and the likes may be used to describe various constituent elements, the constituent elements are not limited to these terms. This term is only used to distinguish a single constituent element from other constituent elements in the specification. The same terms may not be used in the claims, and the elements in the claims may be replaced with first, second, third and the likes according to the order declared by the elements in the claims. Therefore, in the following description, the first constituent element may be the second constituent element in the claims.

[0018] In the text, the terms “about,” “approximately,” “substantially,” and “substantially” usually mean it is within 10%, 5%, 3%, or 2%, 1%, or 0.5% of a given value or range. The quantity given here is an approximate quantity. In other words, in the absence of a specific description for the terms “about,” “approximately,” “substantially” or “approximately,” “about,” and “approximately,” the meaning of “substantially” and “substantially” is still implied. In addition, the descriptions “ranging from the first value to the second value” and “between the first value and the second value” imply that the range includes the first value, the second value, and other values in between.

[0019] In some embodiments of the present disclosure, terms related to bonding and connection, such as “connected,” “interconnected,” unless specifically defined, it mean that two structures are in direct contact, or that two structures are not in direct contact and there are other structures located between these two structures. And the terms about joining and connecting can also include the case where both structures are movable or both structures are fixed. In addition, the term “coupled” includes any direct and indirect electrical connection means.

[0020] In this disclosure, the thickness, length, and width may be measured by using an optical microscope, and the thickness may be measured by a cross-sectional image in an electron microscope, but it is not limited thereto. In addition, there may be a certain margin in any two values or directions used for comparison. If the first value is equal to the second value, it implies that there may be a margin of about 10% between the first value and the second value; if the first direction is perpendicular to the second direction, the angle between the first direction and the second direction may be between 80 degrees and 100 degrees; if the first direction is parallel to the second direction, the angle between the first direction and the second direction may be between 0 degrees and 10 degrees. Without further definitions, all terms (technical and scientific terms included) used herein have the same meanings as commonly understood by those skilled in the art to which this disclosure belongs. It is understandable that these terms, such as those defined in commonly used dictionaries, should be interpreted as having meaning consistent with the relevant technology and the background or context of this disclosure, and should not be interpreted in an idealized or excessively formal way, unless a specific definition is provided in the embodiment of the present disclosure.

[0021] The display panel of the present disclosure may be applied to electronic devices such as display devices, antenna devices (e.g., liquid crystal antennas), sensing devices, light-emitting devices, touch devices, splicing devices, or any combination of the foregoing, but the disclosure is not limited thereto. The electronic device may include a bendable and flexible electronic device. The appearance of the electronic device may include a rectangle, a circle, a polygon, a shape with a curved edge, or other suitable shapes. The display device may, for example, include light-emitting diodes (LEDs), liquid crystal (fluorescence), phosphor (phosphor), quantum dot (QD), other suitable materials, or a combination of the foregoing, but the disclosure is not limited thereto. Light-emitting diodes may include, for example, organic light-emitting diodes (OLED), inorganic light-emitting diodes, sub-millimeter light-emitting diodes (mini LEDs), micro LEDs, or quantum dot light-emitting diodes (QLED or QDLED), other suitable materials, or any combination of the above, but the disclosure is not limited thereto. The appearance of the electronic device may have rectangular, circular, polygonal shape, a shape with curved edges, or other suitable shapes. The electronic device may have peripheral systems such as a driving system, a control system, a light source system, a shelf system, to support a display device, an antenna device, or a splicing device. Hereinafter, the display panel will be adapted to illustrate the content of the disclosure, but the disclosure is not limited thereto.

[0022] It should be understood that the following embodiments may be substituted, reorganized, and mixed to complete other embodiments without departing from the spirit of the present disclosure. The features between the embodiments may be mixed and matched arbitrarily as long as they do not violate or in conflict with the spirit of the disclosure.

[0023] Reference will now be made in detail to the exemplary embodiments of the present disclosure, and examples of the exemplary embodiments are illustrated in the drawings. The same reference symbols may be used to denote the same or similar parts in the drawings and the description.

[0024] FIG. 1A is a schematic partial top view of a display panel according to an embodiment of the disclosure. FIG. 1B is a schematic partial cross-sectional view of the display panel of FIG. 1A along the section line I-I'. For clarity of the drawings and convenience of description, FIG. 1A omits several elements in the display panel.

[0025] The display panel **100** of this embodiment has a plurality of light-exit areas **101** and a non-light-exit area **102**. The display panel **100** may include a first substrate **110**, a pixel define layer **120**, a light-emitting unit **130**, an adhesive layer **140**, a second substrate **150**, an optical layer **160**, a separation layer **170**, and/or a light-converting unit **180**, but the disclosure is not limited thereto.

[0026] In some embodiments, a pixel define layer (PDL) **120** may be disposed on the first substrate **110** (e.g., a surface **111** of the first substrate **110**, and the surface **111** is, for example, adjacent to a

surface of the second substrate **150**). The pixel define layer **120** may include a plurality of openings **121**, and the openings **121** may be adapted to respectively accommodate the light-emitting units **130**. In some embodiments, the material of the pixel define layer **120** may include organic materials or inorganic materials, but it is not limited thereto.

[0027] In some embodiments, the light-emitting unit **130** may be disposed on the first substrate **110** (e.g., the surface **111** of the first substrate **110**), and the light-emitting unit **130** may be disposed in the opening **121** of the pixel define layer **120**. The aforementioned description “light-emitting unit **130** may be disposed in the opening **121** of the pixel define layer **120**” does not restrict an upper surface **TS1** of the pixel define layer **120** to protrude from an upper surface **TS2** of the light-emitting unit **130**. The upper surface **TS1** of the pixel define layer **120** may be selectively cut to be aligned with or lower than the upper surface **TS2** of the light-emitting unit **130**.

[0028] In some embodiments, the light-emitting unit **130** may be disposed corresponding to the light-exit area **101**, that is, in the normal direction of the first substrate **110**, and the light-emitting unit **130** may overlap the light-exit area **101**. In some embodiments, the light-emitting unit **130** may include, for example, red, green, blue, white light-emitting diodes, ultraviolet light-emitting diodes (UV LEDs), and/or light-emitting diodes of other suitable colors, but it is not limited thereto.

[0029] In some embodiments, the adhesive layer **140** may be disposed on the first substrate **110** (e.g., the surface **111** of a substrate **110**), and at least part of the adhesive layer **140** may be disposed in the opening **121** of the pixel define layer **120**. In some embodiments, the adhesive layer **140** may cover the pixel define layer **120** and/or cover the light-emitting unit **130**. In some embodiments, the material of the adhesive layer **140** may include optically clear adhesive (OCA), optical clear resin (OCR), other suitable materials, or a combination of the above, but the disclosure is not limited thereto. In some embodiments, the adhesive layer **140** may contact the pixel define layer **120** and/or the light-emitting unit **130**, but the disclosure is not limited thereto.

[0030] In some embodiments, the second substrate **150** is disposed relative to the first substrate **110**. In some embodiments, the first substrate **110** and the second substrate **150** may be attached to each other through an adhesive layer **140**. In some embodiments, the first substrate **110** and the second substrate **150** may be respectively located on opposite sides of the adhesive layer **140**. The second substrate **150** may have a surface **151** adjacent to the first substrate **110**, and the surface **111** of the first substrate **110** may face the surface **151** of the second substrate **150**. In some embodiments, the first substrate **110** and/or the second substrate **150** may include a rigid substrate, a flexible substrate, or a combination of the foregoing. For example, the material of the first substrate **110** may include glass, quartz, sapphire, ceramic, polycarbonate (PC), polyimide (PI), polyethylene terephthalate (PET), other suitable materials, or a combination of the foregoing, but the disclosure is not limited thereto.

[0031] In some embodiments, the optical layer **160** may be disposed on the second substrate **150** (e.g., the surface **151** of the second substrate **150**), and the optical layer **160** may be disposed between the second substrate **150** and the adhesive layer **140**. In some embodiments, the optical layer **160** may include a color filter layer **161**, a black matrix (BM) **162**, and/or other suitable optical layers, but the disclosure is not limited thereto. In some embodiments, the color filter layer **161** may be disposed corresponding to the light-exit area **101** or the light-converting unit **180**, and the black matrix layer **162** may be disposed corresponding to the non-light-exit area **102** or the separation layer **170**. In other words, in the normal direction of the first substrate **110**, the color filter layer **161** may overlap the light-exit area **101**, and the black matrix layer **162** may overlap the non-light-exit area **102**. In some embodiments, the color filter layer **161** may include red, green, blue filter layers or other suitable color filter layers, but the disclosure is not limited thereto.

[0032] In some embodiments, the material of the black matrix layer **162** includes a light-absorbing material, such as a black matrix (BM), but the disclosure is not limited thereto.

[0033] In some embodiments, the separation layer **170** may be disposed on the second substrate **150** (e.g., the surface **151** of the second substrate **150**), and has a plurality of openings **171**. In some

embodiments, the separation layer **170** substantially overlaps the black matrix layer **162**, and the black matrix layer **162** is located between the second substrate **150** and the separation layer **170**. In some embodiments, the separation layer **170** is located between the optical layer **160** (e.g., the black matrix layer **162**) and the adhesive layer **140**. In some embodiments, the separation layer **170** includes a plurality of openings **171**, and the openings **171** may be adapted to respectively accommodate the light-converting unit **180**. In some embodiments, the separation layer **170** is disposed substantially corresponding to the non-light-exit area **102**, and the opening **171** is disposed substantially corresponding to the light-exit area **101**. In other words, in the normal direction of the first substrate **110**, the separation layer **170** may overlap the non-light-exit area **102**, and the opening **171** may overlap the light-exit area **101**. In some embodiments, the material of the separation layer **170** includes light-absorbing materials and/or reflective materials, such as photoresist materials, black matrix (BM), metal materials, other suitable materials, or a combination of the above, but it is not limited thereto.

[0034] In some embodiments, the light-converting unit **180** is disposed on the second substrate **150** (e.g., the surface **151** of the second substrate **150**), and the light-converting unit **180** may be disposed, for example, in the opening **171** of the separation layer **170**. The light-converting unit **180** may be disposed, for example, in the opening **171** of the separation layer **170**, and the upper surface TS3 of the separation layer **170** is not limited to protrude from an upper surface TS4 of the light-converting unit **180**. The upper surface TS3 of the separation layer **170** may be selectively cut to be aligned with or lower than the upper surface TS4 of the light-converting unit **180**.

[0035] In some embodiments, the optical layer **160** (e.g., the color filter layer **161**) is located between the second substrate **150** and the light-converting unit **180**. In some embodiments, the light-converting unit **180** is located between the optical layer **160** and the adhesive layer **140**. In some embodiments, the light-converting unit **180** may substantially correspond to the light-exit area **101**, that is, in the normal direction of the first substrate **110**, and the light-converting unit **180** may overlap the light-exit area **101**. In some embodiments, the light-converting unit **180** is adapted to convert the first light provided by the light-emitting unit **130** into the second light, where the first light has a first peak wavelength, the second light has a second peak wavelength, and the first peak wavelength is smaller than the second peak wavelength.

[0036] In some embodiments, the light-converting unit **180** includes a polymer **181**, a plurality of light conversion particles **182**, a plurality of first heat dissipation particles **183**, and/or a plurality of scattering particles **184**, but the disclosure is not limited thereto. In some embodiments, the light conversion particles **182** include quantum dots, fluorescence, phosphorescence, other suitable materials, or a combination of the foregoing, but the disclosure is not limited thereto. In some embodiments, the scattering particles **184** include titanium oxide (TiO₂), other suitable scattering materials, or a combination of the foregoing, but the disclosure is not limited thereto.

[0037] In some embodiments, the particle size of the first heat dissipation particles **183** is, for example, between 10 nanometers and 10 micrometers ($10\text{ nanometers} \leq \text{particle diameter} \leq 10\text{ micrometers}$). For example, it is between 50 nanometers and 8 micrometers ($50\text{ nanometers} \leq \text{particle diameter} \leq 8\text{ micrometers}$), and between 100 nanometers and 5 micrometers ($100\text{ nanometers} \leq \text{particle diameter} \leq 5\text{ micrometers}$), but the disclosure is not limited thereto. In some embodiments, the first heat dissipation particles **183** may include boron nitride (BN), aluminum nitride (AlN), silicon carbide (SiC), silicon nitride (Si₃N₄), beryllium oxide (BeO), aluminum oxide (Al₂O₃), and other suitable heat dissipation materials, but the disclosure is not limited thereto. In some embodiments, the thermal conductivity of the first heat dissipation particles **183** may be, for example, greater than 50 W.Math.m.sup.-1.Math.K.sup.-1. For example, it is between 50 W.Math.m.sup.-1.Math.K.sup.-1 and 1000 W.Math.m.sup.-1.Math.K.sup.-1 ($50\text{ W.Math.m.sup.-1.Math.K.sup.-1} \leq \text{thermal conductivity} \leq 1000\text{ W.Math.m.sup.-1.Math.K.sup.-1}$), but the disclosure is not limited thereto. The first heat-dissipating particles help the light-converting unit **180** or the light-emitting unit **130** to dissipate heat, but it is not limited thereto. For example,

the coefficient of thermal conductivity of boron nitride is approximately 185 to 300 W.Math.m.sup.-1.Math.K.sup.-1, the coefficient of thermal conductivity of aluminum nitride is approximately 150 to 220 W.Math.m.sup.-1.Math.K.sup.-1, the coefficient of thermal conductivity of silicon carbide is about 340 W.Math.m.sup.-1.Math.K.sup.-1, and the coefficient of thermal conductivity of beryllium oxide is about 260 to 300 W.Math.m.sup.-1.Math.K.sup.-1, but it is not limited thereto. The given range of the thermal conductivity for each material mentioned above is only an example.

[0038] Since the first heat dissipation particles **183** disposed in the light-converting unit **180** help the light-converting unit **180** or the light-emitting unit **130** dissipate heat, the heat generated by the light-converting unit **180** or the light-emitting unit **130** may be reduced, and the service life of the light-converting unit **180** or the light-emitting unit **130** may be increased, thereby increasing the service life of the display panel **100**.

[0039] In some embodiments, based on the total weight of the light-converting unit **180**, the content of the light conversion particles **182** accounts for, for example, 15% to 40% by weight of the light-converting unit **180** ($15\% \leq \text{the content of the light conversion particles } 182 \leq 40\%$); for example, it is between 20% and 35% ($20\% \leq \text{the content of light conversion particles } 182 \leq 35\%$), or between 22% and 38% ($22\% \leq \text{the content of light conversion particles } 182 \leq 38\%$), but the disclosure is not limited thereto. In some embodiments, the content of the first heat dissipation particles **183** accounts for, for example, 1% to 25% by weight of the light-converting unit **180** ($1\% \leq \text{the content of the first heat dissipation particles } 183 \leq 25\%$); for example, it is between 5% and 20% ($5\% \leq \text{the content of the first heat dissipation particles } 183 \leq 20\%$), or between 8% and 17% ($8\% \leq \text{the content of the first heat dissipation particles } 183 \leq 17\%$), but the disclosure is not limited thereto. In some embodiments, when the content of the first heat dissipation particles **183** accounts for more than 25% by weight of the light-converting unit **180**, the content of the light conversion particles **182** may be insufficient, resulting in poor light conversion efficiency. In this way, the content of the polymer **181** may be insufficient and the structure of the light-converting unit **180** becomes fragile. In some embodiments, the light-converting unit **180** further includes a plurality of scattering particles **184**. The total content of the first heat dissipation particles **183** and the scattering particles **184** accounts for, for example, 5% to 50% by weight of the light-converting unit **180** ($5\% \leq \text{the total content of the first heat dissipation particles } 183 \text{ and the scattering particles } 184 \leq 50\%$); for example, it is between 10% and 40% ($10\% \leq \text{the total content of the first heat dissipation particles } 183 \text{ and the scattering particles } 184 \leq 40\%$), or between 15% and 35% ($15\% \leq \text{the total content of the first heat dissipation particles } 183 \text{ and the scattering particles } 184 \leq 35\%$), but the disclosure is not limited thereto.

[0040] In some embodiments, the light-converting unit **180** in the light-emitting unit **130** corresponding to different colors may be used in combination with a plurality of first heat dissipation particles **183** of different content or the same content, but it is not limited thereto. For example, the content of the first heat dissipation particles **183** in the light-converting unit **180** corresponding to the green LED may be greater than the content of the first heat dissipation particles **183** in the light-converting unit **180** corresponding to the red LED, or the content of the first heat dissipation particles **183** in the light-converting unit **180** corresponding to the red LED may be greater than the content of the first heat dissipation particles **183** in the light-converting unit **180** corresponding to the blue LED, but the disclosure is not limited thereto.

[0041] Other embodiments are listed below for description. It must be noted here that the following embodiments adopt the element numbers and part of the content of the foregoing embodiments, where the same numbers are used to represent the same or similar elements whose description is omitted hereinafter. Please refer to the foregoing embodiments for the description of the omitted parts, as they are not repeated in the following embodiments.

[0042] FIG. 2 is a schematic partial cross-sectional view of a display panel according to another embodiment of the disclosure. Please refer to FIG. 1B and FIG. 2 at the same time. The display

panel **100a** of this embodiment is substantially similar to the display panel **100** of FIG. **1B**. The descriptions of the same or similar components in the two embodiments are not repeated here. In this embodiment, its main difference from the display panel **100** is that the pixel defining layer **120a** of the display panel **100a** includes a plurality of second heat dissipation particles **122** and/or a plurality of first light-absorbing particles **123**.

[0043] In some embodiments, the thermal conductivity of the second heat-dissipating particles **122** is similar to that of the first heat-dissipating particles **183** to help the light-converting unit **180** or the light-emitting unit **130** to dissipate heat, and its description is not repeated here and the disclosure is not limited thereto.

[0044] In some embodiments, the first light-absorbing particles **123** may include carbon, dyes, other suitable light absorbing materials, or a combination of the foregoing, but the disclosure is not limited thereto. In some embodiments, the pixel define layer **120a** may further include scattering particles, or the first light-absorbing particles **123** in the pixel define layer **120a** may be replaced by scattering particles, but the disclosure is not limited thereto.

[0045] FIG. **3** is a schematic partial cross-sectional view of a display panel according to another embodiment of the disclosure. Please refer to FIG. **1B** and FIG. **3** at the same time. The display panel **100b** of this embodiment is substantially similar to the display panel **100** of FIG. **1B**.

Therefore, the description of the same or similar components in the two embodiments is not repeated here. In this embodiment, its main difference from the display panel **100** is that the separation layer **170a** of the display panel **100b** includes a plurality of third heat dissipation particles **172** and/or a plurality of second light absorption particles **173**.

[0046] In some embodiments, the first light-absorbing particles **123** and/or the second light-absorbing particles **173** include carbon, dyes, other suitable light absorbing materials, or a combination of the foregoing, but the disclosure is not limited thereto. In some embodiments, the separation layer **170a** includes scattering particles, or the second light-absorbing particles **173** in the separation layer **170a** may be replaced by scattering particles, but it is not limited thereto.

[0047] FIG. **4** is a schematic partial cross-sectional view of a display panel according to another embodiment of the disclosure. Please refer to FIG. **1B** and FIG. **4** at the same time. The display panel **100c** of this embodiment is substantially similar to the display panel **100** of FIG. **1B**. The descriptions of the same and similar components in the two embodiments are not repeated here. In this embodiment, its main difference from the display panel **100** is that the adhesive layer **140a** of the display panel **100c** includes a plurality of fourth heat dissipation particles **141**.

[0048] Note that the particle size, material, and/or thermal conductivity of the first heat dissipation particles **183**, the second heat dissipation particles **122**, the third heat dissipation particles **172**, and/or the fourth heat dissipation particles **141** of the present disclosure may be the same or different, and the description of these features are not repeated herein. The heat dissipation particles help dissipate the heat for the display panel **100c**.

[0049] FIG. **5** is a schematic partial cross-sectional view of a display panel according to another embodiment of the disclosure. Please refer to FIG. **2** and FIG. **5** at the same time. The display panel **100d** of this embodiment is substantially similar to the display panel **100a** of FIG. **2**, so the description of the same or similar components in the two embodiments is not repeated here. In this embodiment, its main difference from the display panel **100** is that that the display panel **100d** does not include the separation layer **170** and/or the light-converting unit **180** in the display panel **100a**.

[0050] Please refer to FIG. **5** for more details. The display panel **100d** of this embodiment has a light-exit area **101** and a non-light-exit area **102**. The display panel **100d** includes a first substrate **110**, a pixel define layer **120d**, a light-emitting unit **130**, an adhesive layer **140**, a second substrate **150**, and/or an optical layer **160**, but the disclosure is not limited thereto. The pixel define layer **120d** may be disposed, for example, on the first substrate **110** (e.g., a surface **111** of the first substrate **110**). The pixel define layer **120d** may include an opening **121** for accommodating the light-emitting unit **130**. The pixel define layer **120d** may further include a plurality of first light

absorption particles **123** and/or a plurality of heat dissipation particles **124**, but the disclosure is not limited thereto. Please refer to, for example, the first heat dissipation particle **183** above for the particle size, material, or thermal conductivity of the heat dissipation particles **124** of some embodiments, which is not repeated here. In some embodiments, the pixel define layer **120d** includes scattering particles; alternatively, the first light-absorbing particles **123** in the pixel define layer **120d** may be replaced by the scattering particles, but it is not limited thereto.

[0051] In some embodiments, the optical layer **160** includes a color filter layer **161** and a black matrix layer **162**. The black matrix layer **162** may have a plurality of openings **1620**, and the openings **1620** may respectively accommodate the color filter layer **161**. In some embodiments, the black matrix layer **162** substantially correspond to the non-light-exit area **102**, and the opening **1620** substantially corresponds to the light-exit area **101**. In other words, in the normal direction of the first substrate **110**, the black matrix layer **162** overlaps the non-light-exit area **102**, and the openings **1620** overlap the light-exit area **101**.

[0052] In some embodiments, the optical layer **160** is disposed between the second substrate **150** and the adhesive layer **140**. In some embodiments, the optical layer **160** contacts the adhesive layer **140**.

[0053] FIG. **6** is a schematic partial cross-sectional view of a display panel according to another embodiment of the disclosure. Please refer to FIG. **5** and FIG. **6** at the same time. The display panel **100e** of this embodiment is substantially similar to the display panel **100d** in FIG. **5**, so the description of same and similar components of the two embodiments is not repeated here. In this embodiment, its main difference from the display panel **100** is that the adhesive layer **140e** of the display panel **100e** includes a plurality of heat dissipation particles **142**. In some embodiments, the pixel define layer **120d** includes a plurality of first light-absorbing particles **123** and/or a plurality of heat dissipation particles **124**. In some embodiments, at least one of the pixel define layer **120d** and the adhesive layer **140e** optionally includes a plurality of heat-dissipating particles, which helps the light-emitting unit **130** to dissipate heat.

[0054] FIG. **7** is a schematic partial cross-sectional view of a display panel according to another embodiment of the disclosure. Please refer to FIG. **6** and FIG. **7** at the same time. The display panel **100f** of this embodiment is substantially similar to the display panel **100e** of FIG. **6**, so the description of same and similar components of the two embodiments is not repeated here. In this embodiment, its main difference from the display panel **100e** is that the display panel **100f** does not include the pixel define layer **120d**, the adhesive layer **140f** includes a plurality of heat dissipation particles **142**, and that the adhesive layer **140f** surrounds the light-emitting unit **130**. In some embodiments, the light-emitting unit **130** includes, for example, red, green, blue, white light-emitting diodes, ultraviolet light-emitting diodes (UV LEDs), and/or light-emitting diodes of other suitable colors, but it is not limited thereto.

[0055] In summary, in a display panel of an embodiment of the disclosure, since the light-converting unit includes a plurality of heat dissipation particles (e.g., the first heat dissipation particles), the thermal conductivity of the first heat dissipation particles is greater than $50 \text{ W} \cdot \text{m} \cdot \text{sup}^{-1} \cdot \text{K} \cdot \text{sup}^{-1}$, which helps the light-converting unit or the light-emitting unit in the display panel to dissipate heat, thereby increasing the service life of the display panel. In addition to the light-converting unit that includes a plurality of heat dissipation particles (e.g., the first heat dissipation particles), the pixel defining layer may also include a plurality of heat dissipation particles (e.g., the second heat dissipation particles), the separation layer may include a plurality of heat dissipation particles (e.g., the third heat dissipation particles), and/or the adhesive layer may include a plurality of heat dissipation particles (e.g., the fourth heat dissipation particles), or other suitable layers can include heat-dissipating particles, such that the heat generated by the light-converting unit or the light-emitting unit may be reduced, thereby increasing the service life of the display panel. In addition, in another display panel of the embodiment of the disclosure, since at least one of the pixel define layer and the adhesive layer includes a plurality of heat dissipation

particles, and the thermal conductivity of the heat dissipation particles is greater than 50 W.Math.m.sup.-1.Math.K.sup.-1, it help the heat to dissipate in the light-emitting unit in the display panel and increase the service life of the display panel.

[0056] Note that the range of the weight percentage of an A material or particles in a certain element (or layer) mentioned in the embodiment of the present disclosure may be detected, for example, by energy-dispersive X-ray spectroscopy (EDS), but the disclosure is not limited thereto. As mentioned above, the weight percentage of the first heat dissipation particles in the light-converting unit **180** is between 1% and 25%, and the element ratio of the first heat dissipation particles **183** in the light-converting unit **180** may be detected by EDS. For example, when the first heat-dissipating particles **183** are boron nitride (BN), the weight percentage may be substantially calculated by calculating the ratio of the elements of boron and nitrogen in the light-converting unit **180** to the overall elements of the light-converting unit **180**, but the disclosure is not limited thereto. In addition, since the A material or particles may be substantially distributed uniformly in a certain element or layer, the measurement is performed on, for example, part of the element (or layer) for detection, and it is not limited to perform the measurement on the whole element (or layer).

[0057] Finally, note that the above embodiments are only used to illustrate the technical solutions of the present disclosure, but not to limit them. Although the present disclosure has been described in detail with reference to the foregoing embodiments, those of ordinary skill in the art should understand that it is possible to combine and modify the technical solutions described in the foregoing embodiments, or to replace some or all of the equivalent technical features. However, these combinations, modifications, or replacements do not deviate the essence of the corresponding technical solutions from the scope of the technical solutions of the embodiments of the present disclosure.

Claims

1. A light emitting device, comprising: a first substrate; a light-emitting unit, disposed on the first substrate; a pixel define layer, disposed on the first substrate and comprising an opening, wherein at least one portion of the light-emitting unit is disposed in the opening; an adhesive layer, disposed on the pixel define layer and the light-emitting unit; and a plurality of scattering particles, disposed on the first substrate, wherein at least one portion of the plurality of scattering particles are overlapped with the at least one portion of the light-emitting unit.
2. The light emitting device according to claim 1, further comprising: a first light exit region, wherein the at least one portion of the light-emitting unit is disposed in the first light exit region.
3. The light emitting device according to claim 2, further comprising: a second light exit region and a non-light exit region, wherein the non-light exit region is disposed adjacently between the first light exit region and the second light exit region.
4. The light emitting device according to claim 3, further comprising: a plurality of light conversion particles, disposed on the first substrate and in the second light exit region.
5. The light emitting device according to claim 4, wherein the light emitting device emits a first color in the first light exit region and emits a second color in the second light exit region, and the first color and the second color are different.
6. The light emitting device according to claim 4, further comprising: a second substrate; and a first color filter unit, disposed in the first light exit region, wherein the first color filter unit is disposed between the second substrate and the plurality of scattering particles.
7. The light emitting device according to claim 6, further comprising: a second color filter unit, disposed in the second light exit region, wherein the second color filter unit is disposed between the second substrate and the plurality of light conversion particles.
8. The light emitting device according to claim 1, wherein the light-emitting unit is an organic light

emitting diode.

9. The light emitting device according to claim 1, wherein the light-emitting unit is an inorganic light emitting diode.
