

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414574
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Sumner; Robert

Device and method for imparting smoked flavors to beverages and foodstuffs

Abstract

Disclosed is a smoker device for imparting smoked flavors to beverages and foodstuffs can include a base having at least a wall defining a first end and a floor with an opening defining a second end, a cover capable of being positioned over the base first end, thereby defining an enclosed cavity, and a conduit portion defining an open channel at a first end and closed at a second end, the first end connecting to a perimeter of the base floor opening, creating a passageway from the enclosed cavity to the channel. Also disclosed is a method for using the smoker device to impart smoked flavors to beverages and foodstuffs.

Inventors:	Sumner; Robert (Sandbach, GB)
Applicant:	Soak Limited (Sandbach, GB)
Family ID:	1000008819261
Assignee:	Soak Limited (Sanbach, GB)
Appl. No.:	18/222037
Filed:	July 14, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230354834 A1	Nov. 09, 2023

Related U.S. Application Data

continuation parent-doc US 17100797 20201120 US 11744256 child-doc US 18222037

Publication Classification

Int. Cl.:	A23B4/052 (20060101); A23B4/044 (20060101)
U.S. Cl.:	
CPC	A23B4/052 (20130101); A23B4/044 (20130101)

Field of Classification Search

CPC:	A23B (4/044); A23B (4/052); A23B (4/0523); A47J (37/0786); A47J (31/18); A47J (31/20)
USPC:	99/482; 426/314; 426/315

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2246804	12/1940	Lipschutz	N/A	N/A
2967023	12/1960	Huckabee	N/A	N/A
3788301	12/1973	Terry	N/A	N/A
4779525	12/1987	Gaines	N/A	N/A
5048406	12/1990	Cofer	N/A	N/A
5193445	12/1992	Ferguson	N/A	N/A
6481344	12/2001	Green	N/A	N/A
6779438	12/2003	Citrynell	N/A	N/A
6971305	12/2004	Thomas	N/A	N/A
7694626	12/2009	Davis	N/A	N/A
8651018	12/2013	Loud, III	N/A	N/A
D721539	12/2014	Johnson	N/A	N/A

9433241	12/2015	Jalloul	N/A	N/A
9603372	12/2016	Bader	N/A	N/A
10420351	12/2018	Vinett	N/A	N/A
2004/0025714	12/2003	Neal	N/A	N/A
2006/0042641	12/2005	Young	N/A	N/A
2014/0216268	12/2013	Burch	N/A	N/A
2014/0261015	12/2013	Nelson	N/A	N/A
2014/0261016	12/2013	Kaderil	N/A	N/A
2018/0371387	12/2017	Hall et al.	N/A	N/A
2020/0305450	12/2019	Halasinski	N/A	A23B 4/044

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
202020100707	12/2019	DE	A23B 4/044
2020032912	12/2019	WO	N/A

OTHER PUBLICATIONS

Mokey Top cocktail smoker by Middleton Mixology <https://middletonmixology.com/collections/all/products/smoketop-1>. cited by applicant

Crafthouse Smoking Cloche https://www.potterybarn.com/products/crafthouse-smoking-cloche/?pkey=cdrink-accessories&sku=cm_src=drink-accessories[[N

Crafthouse Smoking Box [https://www.williams-sonoma.com/products/crafthouse-cocktail-smoking-box/?](https://www.williams-sonoma.com/products/crafthouse-cocktail-smoking-box/?catalogId=79&sku=4203118&cm_ven=PLA&cm_cat=Google&cm_pla=Tabletop%20%26%20Bar%20%3E%20Bar%20Tools&adclid=e161db514f3e1c7543)

catalogId=79&sku=4203118&cm_ven=PLA&cm_cat=Google&cm_pla=Tabletop%20%26%20Bar%20%3E%20Bar%20Tools&adclid=e161db514f3e1c7543

cited by applicant

Non-final Office Action, U.S. Appl. No. 17/100,797, mailed Jan. 31, 2023. cited by applicant

Primary Examiner: Alexander; Reginald

Attorney, Agent or Firm: Sheets Law

Background/Summary

BACKGROUND

(1) Alcoholic beverages such as cocktails are traditionally either served neat, over ice, or blended with juice or other mixing agents. For many spirits such as whiskey, flavors are traditionally added by introducing the distilled spirit into American Oak or other types of barrels, where color, sweetness, wood flavors, and smoke flavors from charcoal are infused from the wood into the spirit.

(2) Prior devices have been commercialized that attempt to impart smoky and spicy flavors into individually-served beverages in order to replicate the flavors of “aging” a spirit in a barrel. For example, hand-held or “bartop” smokers consist of a glass box in which a drinking glass can be enclosed. Wood chips are placed in a screen within a torch device and a hose connects the torch device securely into the glass box. As the torch is lit, it burns wood fuel and smoke pours through the hose into the box, thereby filling the box with smoke and adhering smoke to the drinking glass and infusing smokey flavors into the beverage. This device has many limitations, however, such as having to clean the glass box after each use and adhering smokey residue (and flavors) to the outside of the drinking glass as well the inside of the glass.

(3) Another device that has been commercialized uses a cut a piece of a wood stave from a whiskey barrel, having a circular groove carved into wood that will accept a glass rim. A portion of the stave piece is then lit on fire, and an empty glass is then turned upside down and placed onto the stave. Smoke can fill the glass, which is then removed after smoking completes. This device cannot infuse smokey flavors into a beverage, however, since an empty glass must be used.

(4) The disclosed systems and methods are directed to overcoming one or more of the shortcomings set forth above and/or other shortcomings of the prior art.

SUMMARY

(5) There is a need for a device to impart smokey and other flavors through a flow of smoke into an alcoholic beverages and foodstuffs that overcomes the problems of the prior art.

(6) In one aspect of the disclosure, a device for imparting smoked flavors to beverages and foodstuffs can include a base having at least a wall defining a first end and a floor with an opening defining a second end, a cover capable of being positioned over the base first end, thereby defining an enclosed cavity, and a conduit portion defining an open channel at a first end and closed at a second end, the first end connecting to a perimeter of the base floor opening, creating a passageway from the enclosed cavity to the channel. In another aspect, the conduit portion can include at least one aperture that extends from the channel through an outer wall of the conduit portion. In another aspect, the base, conduit, and lid are circumferential in shape. In yet another aspect, the conduit portion further comprises a plurality of apertures. In still another aspect, the plurality of apertures are positioned between a top end and a bottom end of the conduit portion. Other aspects include the aperture extends from the conduit portion at a rising angle towards the base floor opening. In one aspect, the base floor extends at a rising angle away from the lowermost floor opening. Another aspect includes a screen capable of being received by the base floor. In another aspect, the conduit portion is capable of receiving a portion of the screen into the channel.

(7) In other aspects of the embodiments, method can be used for imparting smoked flavors to beverages and foodstuffs that includes providing a device for imparting smoked flavors to beverages and foodstuffs, which includes providing a base having at least a wall defining a first end and a floor with an opening defining a second end, and a conduit portion defining an open channel at a first end and closed at a second end, the first end connecting to a perimeter of the base floor opening, creating a passageway from the enclosed cavity to the channel, wherein the conduit portion includes at least one aperture that extends from the channel through an outer wall of the conduit portion, positioning a screen into the passageway, positioning fuel onto the screen, igniting the fuel on the screen, and positioning a cover over the base first end, thereby defining an enclosed cavity above the base floor. In other aspects, the method can include positioning the device over an opening of a container such that the conduit portion is disposed into the container and the at least one aperture is positioned below a top of the container. In an aspect, the method can include smoke that streams from the at least one aperture into the container. In another aspect, the at least one aperture comprises a plurality of apertures positioned around the conduit portion. In other aspects, the at least one aperture extends from the conduit portion at a rising angle towards the base floor opening. In another aspect, the base floor extends at a rising angle away from the floor opening.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The disclosed subject matter of the present application will now be described in more detail with reference to exemplary embodiments of the apparatus and method, given by way of example, and with reference to the accompanying drawings, in which:
- (2) FIG. 1 illustrates a perspective view of an embodiment for a smoker device;
- (3) FIG. 2 illustrates a top view of an embodiment for a smoker device of FIG. 1;
- (4) FIG. 3 illustrates a side view of an embodiment for a smoker device of FIG. 1;
- (5) FIG. 4 illustrates a bottom view of an embodiment for a smoker device of FIG. 1;
- (6) FIG. 5A illustrates a side view of an embodiment for a smoker device of FIG. 1;
- (7) FIG. 5B illustrates a cross-sectional view of the embodiment for a smoker device of FIG. 5A;
- (8) FIG. 5C illustrates a cross-sectional view of the embodiment for a smoker device of FIG. 5A with a screen;
- (9) FIG. 6 illustrates an exploded view of an embodiment for a smoker device of FIG. 1;
- (10) FIG. 7 illustrates an embodiment for a smoker device of FIG. 1 positioned over a drinking glass;
- (11) FIG. 8 illustrates an embodiment for a smoker device of FIG. 1 positioned over a glass cover; and
- (12) FIG. 9 depicts a flowchart of an embodiment for a method for adding smoke flavor to food and beverages.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

- (13) A few inventive aspects of the disclosed embodiments are explained in detail below with reference to the various figures. Exemplary embodiments are described to illustrate the disclosed subject matter, not to limit its scope, which is defined by the claims. Those of ordinary skill in the art will recognize a number of equivalent variations of the various features provided in the description that follows.
- (14) FIG. 1 illustrates a perspective view of an embodiment for a smoker device. FIGS. 2, 3, and 4 illustrate top, side, and bottom views of the exemplary smoker device, respectively. In an embodiment, the smoker device **100** may comprise a cylindrically shaped base **102** and a cylindrically shaped cover **104**. In other embodiments, it is understood that the smoker device **100** may be generally formed in square, rectangle, elliptic, customized such as lettering or company logos, or any other shapes that can fall within the claims or their equivalents. Embodiments of the smoker device **100** can be manufactured of wood, resin, plastic, metal, stone, clay, or any material that can function according to the disclosure provided herein.
- (15) In the embodiments, the base **102** can be formed with a cylindrical hollow fuel chamber portion **106** at its uppermost or first end and a hollow, cylindrical conduit portion **108** at its lowermost end. The fuel chamber portion **106** can comprise at least an upper wall portion **110** defining a perimeter edge and first end. The fuel chamber portion **106** can also include a floor **112** defining a second, or bottom, end. The fuel chamber portion **106** can be operable to carry fuel, such as wood chips, for smoking food or beverages. The cover **104** can be capable of being positioned over the base uppermost or first end. By positioning the cover **104** in such a manner over the base uppermost or first end, an enclosed cavity can be defined within the base **102**. The cover **104** may seal, or partially seal, with the fuel chamber portion **106**. In an embodiment, the cover **104** loosely seats onto the uppermost portion of the fuel chamber portion **106** so as to provide ease of removal after a smoking procedure has completed. In some embodiments, the cover **104** may be unattached to the fuel chamber portion **106**. In other embodiments, the cover **104** may be removably attached to the fuel chamber portion **106**.
- (16) FIG. 2 illustrates a top view of an embodiment for the smoker device **100** of FIG. 1. Cover **104** is shown disposed over the fuel chamber portion **106** (not shown). An effect of cover **104** is to create an enclosed cavity within base **102** such that air trapped in such cavity can be utilized by a fuel for ignition and burning, and such cavity can prevent or substantially prevent smoke from rising up and out of the fuel chamber portion **106**. In an embodiment, cover **104** may be a larger size, such as a larger diameter, than the outermost size or diameter of the fuel chamber portion **106**. In other embodiments, cover **104** may be the same size or slightly smaller than the outermost size or diameter of the fuel chamber portion **106**. In the embodiments, any size of the cover **104** that can function to prevent or substantially prevent smoke from rising up and out of fuel chamber portion **106** may be appropriate.
- (17) FIG. 3 illustrates a side view of an embodiment for the smoker device **100** of FIG. 1. FIG. 4 illustrates a bottom view of an embodiment for the smoker device **100** of FIG. 1. In the embodiment, conduit portion can be sealably attached to floor **112**. In other embodiments, conduit portion **108** and fuel chamber portion **106** can be constructed as a single unit. For example, conduit portion **108** and fuel chamber portion **106** can be formed either out of one piece of wood or manufactured from a continuous plastic or resin mold. Conduit portion **108** may be open to fuel chamber portion **106** at its uppermost top end and sealably closed at its bottom terminal end. In an embodiment, conduit portion **108** is a hollow cylindrical structure centrally disposed on a longitudinal axis with the fuel chamber portion **106**. In other embodiments, conduit portion **108** may be disposed in any position below the floor **112** so as to facilitate a channel space for a flow of smoke from the fuel chamber portion **106** and the conduit portion **108** into and through one or more apertures **114**.
- (18) Each aperture **114** is an open hole through an outer wall of the conduit portion **108** that can extend a vent for smoke from the channel space to the exterior of the conduit portion **108**. In some embodiments, apertures **114** may be distally disposed around conduit portion **108** in an evenly-spaced manner. In another embodiment, apertures **114** may be positioned between an uppermost top end a bottom terminal end of the conduit portion **108** in any configuration or orientation that can operate as channels to facilitate the passage of smoke from the conduit portion **108**. In the embodiments, apertures **114** may be formed as cylindrical, elliptical, or irregular shaped channels. In an embodiment, apertures **114** are positioned approximately mid-way between an uppermost top end and bottom terminal end of the conduit portion **108**. In other embodiments, positions of the apertures **114** may vary. However, apertures **114** should be disposed on conduit portion **108** in such positions that apertures **114** will be disposed below a top rim of a drinking glass or glass enclosure after the smoker device **100** is placed upon such glass or enclosure, which is described below in relation to FIGS. 7 and 8.
- (19) FIG. 5A illustrates a side view of an embodiment for the smoker device **100** and FIG. 5B illustrates a cross-sectional view of the embodiment for a smoker device of FIG. 5A. In the embodiments, the lowermost end of cover **104** is formed with a protrusion **126**. The protrusion **126** can be disposed such that, when cover **104** is positioned over base **100**, protrusion **126** will rest inside of an innermost wall of upper wall portion **110**, thereby preventing lateral movement of cover **104** once seated. The inner base floor **112'** can be disposed at a rising angle, beginning at an uppermost terminal end of the conduit portion **108** and terminating at a shelf **116**. The shelf **116** can be formed abutting the innermost wall of upper wall portion **110** with a planar distance of the shelf **116** sized to facilitate seating of a screen **118**.
- (20) FIG. 5C illustrates a cross-sectional view of the embodiment for a smoker device of FIG. 5A with a screen **118**, and FIG. 6 illustrates an exploded view of an embodiment for the smoker device **100**. In the embodiments, the screen **118** can be disposed to seat within fuel chamber portion **106** and in some embodiments, also be partially disposed within conduit portion **108**. The screen **118** can be formed of metal grating, metal sheets with holes, or any other appropriate substance or perforations known in the art. In the embodiments, the screen **118** can be sized with multiplicity of holes that can permit heat and air to pass through the grating, while contemporaneously holding fuel such as wood chips, thereby preventing most or all of the fuel from falling through the screen **118**. In an embodiment, the screen **118** can be formed with a first upper portion **122** and second lower portion **124**. The upper screen portion **122** can be formed at a same or similar angle rise as the floor **112** with a flat ring **120** securely disposed at its outer terminal perimeter. Ring **120** can be formed at a same width as shelf **116**. In operation, ring **120** can seat onto shelf **116**, providing support to hold the screen **118** within base **102**.
- (21) The angle of the floor **112** rise and screen upper portion **122** rise can be selected at any angle to advantageously support screen **118** as well as to facilitate fuel pieces falling towards the center of screen **118** when loading the fuel onto the screen **112**. In other embodiments, floor **112** rise and

screen upper portion **122** may be flat without a rise or other compromising the operation of the smoker device **100**. Screen lower portion **124** can be formed in a cylindrical manner with a closed lowermost terminal end to hold fuel and open uppermost end to provide access to ignite the fuel. When seated into base **102**, the screen lower portion **124** can be disposed into the conduit portion **108**. Screen lower portion **124** can be elongated at any distance such that its lowermost terminal end preferable does not reach or touch the lowermost terminal end of the conduit portion **108**.

(22) In an embodiment, apertures **114** may be oriented as horizontal channels through conduit portion **118**. In other embodiments, apertures **114** may be oriented with rising angles of the channels towards the floor **112** opening in fuel chamber portion **106**. Such a rising angle for aperture **114** channels can enhance the flow of smoke from screen **118** out of the conduit portion **118**.

(23) FIG. 7 illustrates an embodiment for the smoker device **100** positioned over a drinking glass **128**. In the embodiments, conduit portion **108** is sized to be disposed within common drinking glasses used by bartenders to serve cocktails. Floor **112** can be sized to rest upon an uppermost rim of the drinking glass **128** so as to suspend conduit portion **108** within the glass **128**. Apertures **114** should preferably be oriented so as to be disposed below the uppermost rim of glass **128**. FIG. 8 illustrates an embodiment for the smoker device **100** positioned over a glass cover **130**. To facilitate operation of the smoker device **100** for foodstuffs, in the embodiments, conduit portion **108** is sized to be disposed within an uppermost opening in the glass cover **130**, which can be used to cover a plate, platter, or any flat space holding food. Floor **112** can be sized to rest upon an uppermost portion of glass cover **130** so as to suspend conduit portion **108** within the glass cover **130**. Apertures **114** should preferably be oriented so as to be disposed below the opening of glass cover **130**.

(24) FIG. 9 depicts a flowchart of an embodiment for a method for adding smoke flavor to food and beverages using an embodiment of the smoker device **100**. In operation, in step **132**, a device for imparting smoked flavors to beverages and foodstuffs can be provided. In the embodiments, the smoker device **100** can be provided for the operation. At step **134**, the cover **104** may be removed from the smoker device **100** and a screen **118** can be positioned into the smoker device **100**. At step **136**, fuel, such as wood chips, may be placed onto the screen **118**. In other embodiments, fuel may be placed onto the screen **118** prior to positioning the screen **118** within smoker device **100**. At step **138**, the fuel can be ignited using a chef's torch, lighter, or any appropriate ignition device. At step **140**, the cover **104** can be positioned and seated onto the fuel chamber portion **106**. At step **142**, the device can be positioned over an opening of a container such that the conduit portion is disposed into the container and the at least one aperture is positioned below a top of the container.

(25) After the fuel is ignited, the design of the smoker device will unexpectedly facilitate smoke to flow downward from the screen **118**, through at least one aperture **114** and preferably all apertures **114**, and out of the smoker device **100**. When the smoker device is positioned above a glass **128**, the smoke can flow into any empty space within the glass. The smoke flow can then infuse a smoke flavor into or onto a beverage and/or upon inner walls of the glass **128**. When the smoker device is positioned above a glass cover **130**, the smoke can flow into any empty space within the cover. The smoke flow can then infuse a smoke flavor into or onto foodstuffs within the glass cover **130** and/or upon inner walls of the glass cover **130**.

(26) It will be apparent to those skilled in the art that various modifications and variations can be made to the disclosed IoT data compression system and method. Other embodiments will be apparent to those skilled in the art from consideration of the specification and practice of the disclosure. It should be appreciated that different embodiments and different features of embodiments can be used with other embodiments. It is intended that the specification and examples be considered as exemplary only, with a true scope being indicated by the following claims and their equivalents.

Claims

1. A method for flowing smoke through a device, comprising: providing a base having a fuel chamber portion at its upper end and a conduit portion at its lower end, the fuel chamber portion comprising an upper wall portion defining a perimeter edge of the fuel chamber portion and a floor defining a bottom end, the floor extending from the upper wall portion to an opening in the floor; orienting the fuel chamber portion to hold fuel; disposing the conduit portion below the floor wherein the conduit portion comprises a channel through the conduit portion, wherein, when the fuel in the fuel chamber portion is ignited, the channel facilitates flow of smoke downward from the fuel chamber portion through at least one aperture that extends from the channel space through a wall of the conduit portion.
2. The method of claim 1, further comprising providing a cover to sit upon the upper wall portion.
3. The method of claim 1, further comprising forming a plurality of apertures in the conduit portion.
4. The method of claim 3, further comprising positioning the plurality of apertures between a top end and a bottom end of the conduit portion.
5. The method of claim 1, further comprising extending the aperture through the wall of the conduit portion at any position on the conduit portion.
6. The method of claim 1, further comprising extending the floor at a rising angle away from the opening in the floor to the upper wall portion.
7. The method of claim 1, further comprising providing a screen capable of being received by the base floor.
8. The method of claim 7, further comprising forming the conduit portion smaller in size than the fuel chamber portion.
9. A method for flowing smoke through a device, comprising: providing a fuel chamber portion having at least a wall defining a first end and a floor with an opening defining a second end; orienting fuel chamber portion to hold fuel; and providing a conduit portion, connected to the floor of the fuel chamber portion, defining an open channel at a first end, the first end connecting to a perimeter of the floor opening, creating a passageway from the enclosed cavity to the channel, wherein the conduit portion includes at least one aperture that extends from the channel through an outer wall of the conduit portion so that, when the fuel in the fuel chamber portion is ignited, the channel facilitates flow of smoke downward from the fuel chamber portion through the aperture.
10. A method for flowing smoke through a device, comprising: providing a fuel chamber portion comprising an upper wall portion defining a perimeter edge of the fuel chamber portion and a floor defining a bottom end, the floor extending from the upper wall portion to an opening in the floor; orienting the fuel chamber portion to hold fuel; and providing a conduit portion, disposed below the floor, comprising a channel space through the conduit portion so as to facilitate passage of smoke from the fuel chamber portion through at least one aperture that extends from the channel space through a wall of the conduit portion so that, when the fuel in the fuel chamber portion is ignited, the channel facilitates flow of smoke downward from the fuel chamber portion through the aperture.
11. The method of claim 10, further comprising forming the floor at a rising angle from the opening to the upper wall portion.
12. The method of claim 10, further comprising forming the floor flat between the upper wall portion and the opening.
13. The method of claim 10, further comprising providing a cover that is formed to seat upon the upper wall portion.
14. The method of claim 10, further comprising sealably attaching the conduit portion to the floor portion.
15. The method of claim 10 further comprising forming the conduit portion and the fuel chamber portion from a single unit of material.
16. The method of claim 10, further comprising providing a screen that is formed to partially fit within the opening in the floor portion of the upper fuel portion.
17. The method of claim 10, further comprising forming the conduit portion at a smaller size than the fuel chamber portion.
18. The method of claim 10, further comprising forming the conduit portion such that the conduit portion will insert into a drinking glass.
19. The method of claim 10, further comprising forming the floor to rest on the edge of a top of a drinking glass.