

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414656
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Runius; Christian

Lockable receptacle holder

Abstract

A receptacle holder may include a holder base portion configured to support the bottom of a receptacle, a holder upper portion and an elongated holder back portion extending between the holder base portion and the holder upper portion. A confining member may be provided to pivot relative the holder upper portion between a closed position (A) for confining the neck and/or the shoulder of the receptacle, and a release position to allow removal of the receptacle from the receptacle holder. A locking member may be provided to prevent movement of the confining member. The locking member may be brought out of engagement with a trough hole by application of a force (F) thereby allowing the confining member to be pivoted relative the holder upper portion.

Inventors:	Runius; Christian (Solna, SE)
Applicant:	RUNIUS DESIGN AB (Solna, SE)
Family ID:	1000008819152
Assignee:	RUNIUS DESIGN AB (Solna, SE)
Appl. No.:	18/773199
Filed:	July 15, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240366037 A1	Nov. 07, 2024

Foreign Application Priority Data

SE	1951172-4	Oct. 16, 2019
----	-----------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: A47K1/08 (20060101); A47K5/12 (20060101); F16M13/02 (20060101)

U.S. Cl.:

CPC A47K5/1205 (20130101); F16M13/02 (20130101); A47K2201/025 (20130101)

Field of Classification Search

CPC: A47K (5/1205); A47K (2201/025); F16M (13/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4213592	12/1979	Lingenfelser	N/A	N/A
5971335	12/1998	Perrin	248/311.2	A47K 5/12
6820770	12/2003	Makino et al.	N/A	N/A
9146003	12/2014	Carson	N/A	G01N 1/18
9988211	12/2017	Just et al.	N/A	N/A
10342391	12/2018	Beckerman	N/A	N/A
2011/0101196	12/2010	Schmidt et al.	N/A	N/A
2011/0132930	12/2010	Haworth	N/A	N/A
2016/0288151	12/2015	Schultz et al.	N/A	N/A
2018/0153354	12/2017	Beckerman	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
105534360	12/2015	CN	N/A
0915222	12/1998	EP	N/A
2019058426	12/2018	JP	N/A
540307	12/2017	SE	N/A
2014209636	12/2013	WO	N/A

Primary Examiner: Sterling; Amy J.

Attorney, Agent or Firm: Capitol City TechLaw

Background/Summary

(1) This application is a continuation application of U.S. patent application Ser. No. 17/768,787 filed Apr. 13, 2022, which is a US National Phase Application of International Application No. PCT/SE2020050982 filed Oct. 15, 2020, the entire contents of both of which are incorporated herein by reference. (2) This application claims priority under 35 USC 119 (a)-(d) to SE patent

application No. 1951172-4, which was filed on Oct. 16, 2019, the entire contents of which are incorporated herein by reference.

BACKGROUND

1. Field

(1) The present disclosure relates to a receptacle holder. In detail a lockable receptacle holder for a dispensing receptacle for dispensing liquid or creamy hygiene products such as soap, shampoo or lotion hand sanitizer

2. Related Art

(2) For environmental reasons, disposable hygiene products such as soap or shampoo in hotel rooms are increasingly being substituted with large volume dispensers. However, a general problem with refillable containers for hygiene products is that they may be subjected to theft or tampering.

(3) To address this problem there are provided holders for hygiene product dispensers with locking mechanisms. One example is US2011/0101196 which shows a holder for a dispensing bottle that is provided with a collar plate that is provided with an opening for receiving the throat of a soap dispenser. The collar plate is guided in two rods that extend from a wall support so that the collar plate may be brought from an inward position in which the collar plate may be locked to an outward position in which the throat of a dispenser bottle may be inserted into the opening of the collar plate.

(4) One drawback with the dispensing bottle holder of US2011/0101196 is that the throat of the dispenser bottle has to be moved in a slanted manner in direction from below in order to insert the throat of the dispensing bottle into the opening of the collar plate. This makes it awkward and time consuming for housekeeping personal to replace or refill the dispenser bottle. A further drawback resides in the locking of the dispenser bottle holder. To lock the dispensing bottle holder, the dispensing bottle and the collar plate has to be pushed rearwards until a notch in the floating locking pin coincides with a corresponding notch in the guide pin. Thereafter the locking pin is turned by the user. This is a time consuming locking process which involves several steps.

(5) A further holder for a dispenser bottle is shown in SE 540307 C2. In this holder the collar plate is attached to the bottle support by screws. Replacement of the dispenser bottle requires removal of the screws and is therefore time consuming.

(6) Thus, it is an object of the present disclosure to provide a receptacle holder which solves at least one of the problems of the prior art.

(7) In particular, it is an object of the present disclosure to provide a lockable receptacle holder which allows for fast and easy removal and replacement of a receptacle in few working steps.

(8) A further object is to provide a receptacle holder which provides a lockable receptacle holder which provides high resistance to unauthorized removal of a receptacle.

(9) A further object of the present disclosure is to provide a lockable receptacle holder which may be manufactured at low cost.

SUMMARY

(10) At least one of these objects are met by a lockable receptacle holder **10** comprising a holder base portion **20** configured to support the bottom **5** of a receptacle **1**; a holder upper portion **30** and an elongated holder back portion **40** extending between the holder base portion **20** and the holder upper portion **30** characterized in: a confining member **50** having a hook-shaped front portion **51** and pivotally attached to the holder upper portion **30** so that the confining member **50** may pivot relative the holder upper portion **30** between a closed position A in which the hook-shaped front portion **51** and the holder upper portion **30** form an at least partially closed space C for confining the neck **2** and/or the shoulder **30** of a receptacle **1**, and a release position B in which the hook-shaped front portion **51** and the holder upper portion **30** are spaced apart to allow removal of a receptacle **1** from the receptacle holder **10**; a locking member **60** attached to one of the holder upper portion **30** and the confining member **50** and having a locking portion **61** configured to be

received into one opening **33,34** of a through hole **32** in the other of the holder upper portion **30** and the confining member **50** when the confining member **50** is in the closed position A, thereby preventing movement of the confining member **50** wherein, the locking portion **61** is resilient so that it may be brought out of engagement with the trough hole **32** by application of a force F, optionally onto the locking portion **61** optionally through the other opening **33, 34** of the through hole **32**, thereby allowing the confining member **50** to be pivoted relative the holder upper portion **30**.

(11) The lockable receptacle holder is tamper resistant and allows for secure holding of receptacle. In practice, the hook-shaped confining member may easily be unlocked by inserting a purposely dimensioned tool, optionally into the through hole, to apply a force F unto the locking portion. Subsequently the confining member is pivoted to the side thereby allowing house-keeping personnel to easily remove the receptacle for exchange or refilling. Removal and replacement of the receptacle is easy, demands no tricky handling of the receptacle and may be performed in little time.

(12) The receptacle holder comprises few parts and is easy to assemble. It is also easy to clean and durable. Cyclic tests have shown that the components of the receptacle holder maintain structural integrity over 7000 cycles at 9 kg pressure.

(13) The holder upper portion **30** of the receptacle holder **10** may comprises an arcuate front portion **31** for receiving a portion of a neck **2** or shoulder **3** of a receptacle **1**. The arcuate front portion provides a secure support for the receptacle during operation of the confining member. Preferably, the hook-shaped front portion **51** of the confining member **50** may be rounded to form an at least partially closed circular space C with the front end **31** of the holder upper portion **30**.

(14) The through hole **32** may be configured to receive an end portion **8** of a tool **7** wherein the cross-sectional shape of the through hole **32** and the end portion **8** of the tool **7** may be configured such that end portion **8** of the tool **7** may pass through the through hole **32**. This provides the possibility to customize the through hole so that the locking portion only may be accessed by special tools. Thus, unauthorized opening of the receptacle holder may be prevented or made difficult.

(15) The one of the holder upper portion **30** and the confining member **50** to which the locking member **60** is attached may comprise a receiving opening **53** for receiving the locking portion **61** of the locking member **60** when the locking portion **61** is brought out of the through hole **32**. This allows for usage of a flat and thin locking portion, which in turn provides for a compact and tamper resistant receptacle holder **9**. The locking portion **61** may thereby be elongate, flat and provided with an upright edge **62** to be received in the through hole **32**. For example, the locking portion is a part of a locking member **60** in the form of an integral piece of resilient steel strip.

(16) A particularly compact and tamper resistant the receptacle holder **10** is provided when the confining member **50** and the locking member **60** and the holder upper portion **30** are superimposed and the through hole **32** and the locking portion **61** and the receiving opening **53** are aligned so that the locking portion **61** of the locking member **60** may be pushed into the receiving opening **53** by an end portion **8** of a tool **7** that is inserted through the other opening **33, 34** of the through hole **32**. Such a receptacle holder may be realized in that the locking member **60** is arranged underneath the holder upper portion **30** and the confining member **50** is arranged underneath the locking member **60** and wherein through hole **32** extends between an upper opening **33** on an upper side **35** and a lower opening **34** on a lower side **36** of the of the holder upper portion **30**.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Non-limiting embodiments will become more fully understood from the detailed description below and the accompanying drawings, wherein like elements are represented by like reference numerals, which are given by way of illustration only and thus are not limiting of the present invention.
- (2) FIG. 1 is a schematic drawing showing an exploded view of a receptacle holder according to the present disclosure.
- (3) FIGS. 2a, 2b, 3a, 3b, 4a, and 4b are schematic drawings illustrating the function of the receptacle holder according to the present disclosure.
- (4) FIG. 5 is a sectional view of a portion of the receptacle holder according to the present disclosure.
- (5) FIG. 6 is a schematic drawing showing a receptacle holder according to the present disclosure and a receptacle.
- (6) FIGS. 7a and 7b are schematic drawings showing receptacle holders according to alternatives of the present disclosure.
- (7) FIGS. 8a, 8b, and 8c are schematic drawings showing alternative base portions of the receptacle holder according to the present disclosure.
- (8) FIG. 9 is a schematic drawing of a receptacle holder according to an alternative of the present disclosure.
- (9) FIGS. 10a, 10b, and 10c are schematic drawings of alternative locking member and confining member of the present disclosure.

DESCRIPTION OF NON-LIMITING EMBODIMENTS

- (10) The receptacle holder according to the present disclosure will now be described more fully hereinafter. The receptacle holder according to the present disclosure may however be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided by way of example so that this disclosure will be thorough and complete, and will fully convey the scope of the present disclosure to those persons skilled in the art. Same reference numbers refer to same elements throughout the description.
- (11) A “receptacle” or “container” is configured to hold liquid, semi-liquid, creamy or paste-formed substances. Typically a receptacle is a bottle or a jar and has a neck, with a mouth, a shoulder, a body and a bottom. The receptacle may comprise a dispenser which is inserted into the mouth of the receptacle. The dispenser allows a user to pump out the content of the dispenser. The receptacle may in such case be denominated “dispenser receptacle”. FIG. 6 shows a receptacle 1 in the form of a bottle with a dispenser 6. The receptacle has a neck 2, a shoulder 3, a body 4 and bottom 5.
- (12) In the following description of the receptacle holder according to the present disclosure it is appreciated that the receptacle holder may be realized in different sizes and dimensions to fit receptacles of varying shape, size and dimension. Thus, when the receptacle holder, in the following is described with reference to a receptacle or parts thereof, it is appreciated that the receptacle holder is dimensioned in view of that receptacle.
- (13) Further in the following description, any references to directions such as “upright”, “upwards”, “downwards” or “lateral” are in relation to a vertical orientation of the receptacle holder in which the holder base is below the holder upper portion.
- (14) FIG. 1 shows an exploded view of a lockable receptacle holder 10 according to the present disclosure. The receptacle holder 10 comprises an elongated holder back portion 40 which may be configured to be attached to a structure such as a wall (not shown). Attachment of the holder back portion 40 to the structure may for example be achieved by double sided adhesive tape or by screws (not shown) through the openings 41. The holder back portion 40 extends between a holder base portion 20 and a holder upper portion 30. Thus, the holder base portion 20 may extend from one end of the holder back portion 20. The holder upper portion 30 extends opposite to the holder

base portion **20**. The holder base portion **20** is configured to support the bottom **5** of a receptacle (not shown). In FIG. **1** the holder base portion **20** therefore extends approximately perpendicular from the holder back portion **40** and has a width and a length sufficient to support the bottom **5** of a receptacle **1**.

(15) The holder upper portion **30** may extend from a second end of the holder back portion **40**. The holder upper portion **30** may thereby extend approximately parallel with the holder base portion **20**. The front portion **31** of the holder upper portion **30** points away from the holder back portion **40**. The distance between the holder upper portion **30** and the holder base portion **20** may be selected such that the front end **31** of the holder upper portion faces the neck or shoulder of a receptacle that is supported on the holder base portion **20**. The front end **31** of the holder upper portion **30** may be configured to receive a portion of the neck or shoulder of a receptacle that is supported on the holder base portion **20**. In FIG. **1**, the front end **31** of the holder upper portion **30** is arcuate, i.e. has an arc-shaped recess. However, the front end **31** of the holder upper portion **30** may have a square or triangular recess. In the embodiment shown in FIG. **1**, the holder upper portion **30** comprises a through hole **32** that extends between an upper opening **33** on the upper side **35** of the holder upper portion **30** and a lower opening **34** on the lower side **36** of the holder upper portion. The through hole **32** is dimensioned such that a locking portion **61** of a locking member **60** may be received through the lower opening **34** and such that at least the end portion **8** of a tool **7** may be inserted through the upper opening **33**. The cross-section of the end portion **8** of the tool **7** may thereby have the same or smaller dimensions as the cross-section of the through hole **32**. The cross-sectional shape of the end portion **8** of the tool **7** and/or the tip **8** of the cross-sectional shape of the through hole may be same or similar. For example, as shown in FIG. **1**, the through-hole **32** may be of rectangular cross-section and the end portion of the tool **7** may also be of rectangular cross-section. The length of the end portion **8** of the tool **7** is selected such that the end portion **8** extends through or flush with the lower opening **34** of the through hole.

(16) A shaft opening **38** for a pivot shaft **70** is provided in the rear portion **37** of the holder upper portion **30**. The rear portion **37** is located between the through hole **32** in the holder upper portion **30** and the holder back portion **40**.

(17) The receptacle holder **10** further comprises a confining member **50** which has a hook-shaped front portion **51** and a rear portion **52** which may be rectangular. The hook-shaped front portion **51** has a front end **57**, i.e. a free front end **57**. In FIG. **1**, the hook-shaped front portion **51** is rounded, however it may also have other configuration such as triangular—or rectangular hook-shape. The confining member **50** is pivotally attached to the holder upper portion **30**. The confining member may thereby pivot relative the holder upper portion **30** in a plane that is parallel to the width and length extension of the holder upper portion **30**. The confining member **50** may thereby be pivotally attached to a pivot shaft **70** that extends through a shaft opening **54** in the rear portion **52** of the confining member **50** and the shaft opening **38** in the holder upper portion **30**. In the described embodiment, the confining member **50** comprises a receiving opening **53** that is provided in the rear portion **52** of the confining member **50**. For example, the receiving opening **53** is provided between the shaft opening **54** and the hook-shaped front portion **51** of the confining member **50**. The receiving opening **53** may be a through-hole or a recess, and is configured to receive a locking portion **61** of a locking member **60**.

(18) The locking member **60** comprises a locking portion **61** and a rear portion **66** from which the locking portion **61** may extend. The locking portion **61** is configured to extend into the through hole **32** in the holder upper portion **30**. The locking portion **61** may therefore be elongated and have an upright edge **62**. That is, directed in direction away from the upper surface of the locking member **60**. In the shown embodiment, the locking portion **61** is a flat. However, the locking portion **61** may have other configuration, for example rod-shaped. It is also possible to divide the locking portion **61** in to two locking portion halves (not shown). In the shown embodiment, the locking member **60** is configured to be attached to the rear end of the confining member **50**. The

rear portion **66** of the locking member **60** may therefore have attachment means **63** in the form of parallel flanges that may be inserted into corresponding openings **58**, such as grooves in the confining member **50**. Alternatively, the locking member **60** may be glued or welded to the confining member **50**. The locking portion is resilient. For example, the locking member **60** or at least the locking portion **61** is manufactured from resilient material such as resilient steel strip such as spring steel. Alternatively, plastic material such as polypropylene may be used, for example.

(19) The locking member **60** may be arranged such that the locking portion **61** extends over the receiving opening **53** in the confining member **50**.

(20) The rear portion **66** of the locking member **60** may comprise an opening **65** for the pivot shaft **70**. The pivot shaft may be a press pin that is riveted into the holder upper portion **30**. The end of the pivot shaft may be secured by a rivet locking collar or by a nut and washer (not shown).

(21) In assembled state, the confining member **50** and the locking member **60** and the holder upper portion are superimposed and the through hole **32** and the locking portion **61** and the receiving opening **53** are aligned so that the locking portion **61** of the locking member **60** may be pushed into the receiving opening **53** by a tool **7** inserted through the upper opening **33** of the through hole **32**. As shown in FIG. **1**, the locking member **60** is arranged underneath the holder upper portion **30** and the confining member **50** is arranged underneath the locking member.

(22) The function of the receptacle holder **10** according to the present disclosure will in the following be described with reference to FIGS. **2a**, **2b-4a**, **4b** and **5**.

(23) FIG. **2a** shows the assembled receptacle holder **10** in a position A in which the front portion **31** of the holder upper portion **30** and the hook-shaped front portion **51** of the confining member **50** limits a partially closed space C which is configured to confine the neck or shoulder of a receptacle (not shown in FIG. **2**). By “confine” is meant that any opening between the front portion **31** of the holder upper portion **30** and the end **57** of the hook-shaped front portion **51** of the confining member **50** is too small to allow passage of a neck or shoulder of a receptacle. FIG. **5** shows a cross-sectional view taken along line X-X in FIG. **2a**. Thus, when the confining member **50** is in position A, the upright edge **62** of the locking portion **61** of the locking member **60** extends into the lower opening **33** of the through hole **32**. The locking portion **61** therefore locks the confining member **50** and prevents any pivotal movement thereof. FIG. **2b** shows the locking portion **61** extending over, but not beyond, the receiving opening **53** in the confining member **50**.

(24) FIG. **3a** shows the tool **7** inserted into the upper opening **33** of the through opening **32**. The tip **8** of the tool **7** thereby exerts a force F onto the upright edge **62** of the locking portion **61** and presses the locking portion **61** downwards into the receiving opening **53** (see FIG. **3b**). When the upright edge **62** has been pushed out of the through hole **32**, the confining member **50** is released to pivot relative to the holder upper portion **30**. In the described embodiment, as shown in FIG. **5**, the holder upper portion **30**, the locking member **60** and the confining member **50** are superimposed with essentially no gap between them. The tool **7** may therefore be configured such that the end portion **8** thereof merely extend through the through hole **32**. This will suffice to force the upright edge **62** of the locking portion **60** into the receiving opening **53** so that the upright edge **62** is flush with the upper surface **55** of the confining member. The confining member **50** will thereby be released to pivot.

(25) However, it is possible to arrange the holder upper portion **30** and the confining member **50** superimposed with a gap between them (not shown). In this case, the tip **7** of the tool **6** may be elongated to extend through the through hole **32** and through the gap between the holder upper portion **30** and the confining member **50** in order to force the edge **62** of the locking portion **61** out of the through hole and into the receiving opening **53**.

(26) It is further possible to arrange the holder upper portion **30** and the confining member **50** superimposed with a gap that is wide enough to accommodate the edge **62** of the locking portion. In that case the receiving opening **53** in the confining member **50** may be omitted (not shown).

(27) FIG. **4a** shows the receptacle holder **10** in a situation where the confining member **50** is

pivoted relative to the holder upper portion **30** to a release position B. In this position, the end **57** of the hook-shaped front portion **51** is spaced apart from the front portion **31** of the holder upper portion **30** such that an opening D is formed between the end **57** of the hook-shaped front portion **51** and the front portion **31** of the holder upper portion **30**. The opening D is sufficiently large to allow removal of a receptacle (not shown) from the receptacle holder. Thus, the opening D is sufficiently large to allow passage of the neck or shoulder of the receptacle. The upright edge **62** of the locking portion is in sliding contact with the lower surface **36** of the holder upper portion **30** during pivoting from the locked position A to the release position B. The rear portion **52** of the confining member **50** may be arranged such that it hits the holder back portion **40** when the confining member **50** is in the release position B which prevents further pivoting of the confining member **50**. This is favorable because the locking portion **61** may be kept in contact with the lower side of the holder upper portion which in turn may prevent damage of the locking portion when the confining member is pivoted towards the closed position A.

(28) A receptacle **1** may be inserted and locked into the receptacle holder **10** by performing the steps described above in reversed order.

(29) Although a particular embodiment has been disclosed in detail this has been done for purpose of illustration only, and is not intended to be limiting. In particular, it is contemplated that various substitutions, alterations and modifications may be made within the scope of the appended claims.

(30) For example, the receptacle holder **10** according to the present disclosure has hereinabove been described in an embodiment in which the holder upper portion **30** comprises the through hole **32** and the confining member **50** comprises the receiving opening **53** and wherein the locking member **60** is attached to the confining member **50**. In the described embodiment, the confining member **50** is arranged underneath the holder upper portion **30**.

(31) However, it is possible that the confining member **50** is arranged above the holder upper portion **30**.

(32) FIG. **9** shows an alternative in which the confining member **50** is arranged above the holder upper portion **30** and the locking member **60** is arranged between. For comparison it is referred to FIG. **1**. FIG. **9** is partly exploded in order to show the position and orientation of the locking member **60**.

(33) According to the alternative, the confining member **50** may thereby comprise the through hole **32** for accessing the upright edge **62** of the locking member **60**. The holder upper portion **30** may comprise the receiving opening **53** for receiving the locking portion **61** of the locking member **60** and openings **58** for receiving the attachment means **63** of the locking member **60**, i.e. the flanges. The described openings in the holder upper portion **30** are indicated by dashed lines since they are partly obscured by the confining member **50**. Thus in assembled state, the locking member **60** is attached to the upper holder portion **30** by engagement of the attachment means **63** with the openings **58** in the holder upper portion **30**. As shown in FIG. **1**, a pivot shaft (not shown) may extend through the confining member **50**, the locking member **60** and the holder upper portion **30**.

(34) In FIG. **1**, the locking member is attached to the confining member **50** by engagement between the attachment means **63** of the locking member **60** and the openings **58** in the confining member **50**. In FIG. **9**, the locking member **60** is attached to the upper holder portion **30** by engagement of the attachment means **63** of the locking member with the openings **58** in the holder upper portion **30**. Thus, the locking member **60** may be attached to one of the holder upper portion **30** and confining member **50**.

(35) The confining member **50** may be mirror-inverted and arranged to pivot in opposite direction than shown FIG. **4a**.

(36) Also alternatives for the confining member **50** and the locking member **60** are feasible. In the following alternatives for confining member **50** and locking member **60** are described relative the receptacle support shown in FIG. **1**.

(37) FIG. **10a** shows a locking member **60** according to an alternative of the present disclosure.

According to this alternative, the attachment means **63** is provided as a flange at the rear end of the locking member **60** opposite to the locking means **62**. The locking member **60** may further be provided with two support legs **67** that extend from the locking portion **61**. The attachment means **63** and the support legs **67** protrude vertically in the same direction from the flat surface of the locking member **60**. The locking means **62** protrudes in the opposite direction.

(38) FIG. **10b** shows the locking member **60** and an alternative confining member **50** in assembled state. The rear portion of the alternative confining member **50** is rounded, which results in a tight abutment with the holder back portion (not shown) during pivoting of the confining member **50**. In particular, this makes it difficult pivot beyond the locking member. FIG. **10c** shows the support legs **67** extending through the opening **53** in the confining member **50**. The support legs **67** engages with the sides of the opening **53** and prevents thereby side movement of the locking portion **61**.

(39) It is further possible to arrange the holder upper portion **30** such that the arcuate front portion **31** is oriented 90° to the facing direction of the holder back portion (not shown). The receptacle may thereby be introduced from the side of the receptacle holder.

(40) Also further alternatives or modifications of the receptacle holder **10** according to the present disclosure are feasible. For example:

(41) FIG. **7a** shows a configuration in which the hook-shaped front portion **51** extends partially around the neck **2** of a receptacle **1**. FIG. **7b** shows a configuration in which the hook-shaped front portion **51** extends partially around the shoulder **3** of a receptacle **1**. In FIGS. **7a** and **7b**, the arcuate front portion **31** of the holder upper portion **30** is configured to receive a portion of the neck **2** of the receptacle **1**. However, the front portion **31** of the holder upper portion **30** may be configured to receive a portion of the shoulder **3** of a receptacle **1** (not shown).

(42) The holder receptacle **10** may comprise retainer elements for holding the body or the bottom of a receptacle in order to further prevent lateral movement of a receptacle in the receptacle holder. For example, as shown in FIG. **8a**, the holder base portion **20** may comprise an arcuate lateral extension **22** having upright retainer pins **23** in each end. In use, the retainer pins **23** engage the bottom of a receptacle. FIG. **8b** shows a retainer element **21** in the form of a ring, which extends from the holder back portion **40** above the holder base portion **20**. The ring shaped retainer element is configured to hold the body of a receptacle.

(43) The present disclosure also relates to a receptacle holder unit **100** comprising two or more receptacle holder **10** that are joined together. FIG. **8c** shows a receptacle holder unit **100** comprising three receptacle holder **10**. In FIG. **8c**, the receptacle holder unit is integrally formed. However, it is possible to join two or more receptacle holder **10** to each other (by e.g. welding) to achieve a receptacle holder unit. FIG. **8c** also shows a further alternative of a retainer element **21**. The holder base portion comprises a first arcuate lateral extension **22** that extends in a concave manner from the holder base portion **20** and that has upright pins **23** in each end. A retainer element **21** in the form of a ring segment extends convexly between the upright pins and may thereby engage the body of a receptacle.

(44) Moreover, although specific terms may be employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation. Furthermore, as used herein, the terms “comprise/comprises” or “include/includes” do not exclude the presence of other elements. Finally, reference signs in the claims are provided merely as a clarifying example and should not be construed as limiting the scope of the claims in any way.

Claims

1. A receptacle holder comprising: a holder base portion configured to support a bottom of a receptacle; a holder upper portion; an elongated holder back portion extending between the holder base portion and the holder upper portion; a confining member having a hook-shaped front portion and pivotally attached to the holder upper portion, such that the confining member is pivotable

relative the holder upper portion between a closed position in which the hook-shaped front portion and the holder upper portion form an at least partially closed space for confining a neck and/or a shoulder of the receptacle, and a release position in which the hook-shaped front portion and the holder upper portion are spaced apart to allow removal of the receptacle from the receptacle holder; and a locking member attached to one of the holder upper portion and the confining member, the locking member having a locking portion configured to be received into a first opening of a through hole in the other of the holder upper portion and the confining member when the confining member is in the closed position, thereby preventing movement of the confining member; wherein the locking portion is resilient, such that it is disengageable from the through hole by application of a force, thereby allowing the confining member to pivot relative to the holder upper portion.

2. The receptacle holder according to claim 1, wherein the holder upper portion comprises an arcuate front portion for receiving a portion of the neck or the shoulder of the receptacle.

3. The receptacle holder according to claim 2, wherein the hook-shaped front portion of the confining member is rounded to form a partially closed circular space with a front end of the holder upper portion.

4. The receptacle holder according to claim 1, wherein the through hole is configured to receive an end portion of a tool; and wherein the through hole and the end portion of the tool are configured such that at least the end portion of the tool is passable through the through hole to apply the force onto the locking portion.

5. The receptacle holder according to claim 1, wherein the one of the holder upper portion and the confining member to which the locking member is attached comprises a receiving opening for receiving the locking portion of the locking member when the locking portion disengages from the through hole.

6. The receptacle holder according to claim 5, wherein the confining member and the locking member and the holder upper portion are superimposed and the through hole and the locking portion and the receiving opening are aligned so that the locking portion of the locking member may be pushed into the receiving opening by an end portion of a tool that is inserted through a second opening of the through hole.

7. The receptacle holder according to claim 6, wherein the locking member is arranged underneath the holder upper portion and the confining member is arranged underneath the locking member; and wherein the through hole extends between an upper opening on an upper side and a lower opening on a lower side of the of the holder upper portion.

8. The receptacle holder according to claim 1, wherein the confining member is pivotally attached to the holder upper portion by a pivot shaft extending through a rear portion of the holder upper portion and a rear portion of the confining member.

9. The receptacle holder according to claim 1, wherein the locking member is an integral piece of resilient steel strip.

10. The receptacle holder according to claim 1, wherein the locking portion is elongate, flat and has an upright edge to be received in the through hole.

11. The receptacle holder according to claim 1, wherein the locking portion comprises two locking portion halves.

12. The receptacle holder according to claim 1, wherein the locking member is configured to be attached to a rear end of the confining member.

13. The receptacle holder according to claim 8, wherein a rear portion of the locking member comprises an opening for the pivot shaft.

14. The receptacle holder according to claim 1, wherein the holder base portion comprises retainer pins that are configured to engage the bottom of the receptacle, or wherein the receptacle holder comprises a retainer element in the form of a ring that is configured to hold a body of the receptacle.

15. The receptacle holder according to claim 1, wherein the locking portion is disengageable from

the through hole by application of a force onto the locking portion.

16. The receptacle holder according to claim 15, wherein the locking portion is disengageable from the through hole by application of a force onto the locking portion through a second opening of the through hole.

17. A receptacle holder unit comprising two or more receptacle holders according to claim 1 that are joined together.
