

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415112
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Gwon; Yu Hong

Portable breathing measurement and breathing exercise device

Abstract

A portable breathing measurement and breathing exercise device includes a body part; a mouthpiece part coupled to one side of the body part; a sensor unit which is provided inside the body part and measures the pressure of a user's breathing via the mouthpiece part; a control unit which receives measurement values from the sensor part and stores the measurement values in real time, analyzes the user's breathing on the basis of the measurement values, and provides an exercise schedule; and a display unit for outputting the analysis results and exercise schedule of the control unit. The mouthpiece part includes a load adjustment unit for regulating the flow rate of air that flows in and out of the mouthpiece part and the body part due to the user's breathing.

Inventors:	Gwon; Yu Hong (Busan, KR)
Applicant:	GHINNOTEK CO., LTD. (Busan, KR)
Family ID:	1000008819119
Assignee:	GHINNOTEK CO., LTD. (Busan, KR)
Appl. No.:	18/564402
Filed (or PCT Filed):	October 28, 2021
PCT No.:	PCT/KR2021/015324
PCT Pub. No.:	WO2023/003088
PCT Pub. Date:	January 26, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240245953 A1	Jul. 25, 2024

Foreign Application Priority Data

KR

10-2021-0096821

Jul. 23, 2021

Publication Classification

Int. Cl.: **A63B23/18** (20060101); **A63B21/00** (20060101); **A63B24/00** (20060101); **A63B71/06** (20060101)

U.S. Cl.:

CPC **A63B23/18** (20130101); **A63B21/00069** (20130101); **A63B24/0062** (20130101); **A63B24/0075** (20130101); **A63B71/0622** (20130101); A63B2071/0658 (20130101); A63B2220/56 (20130101); A63B2225/20 (20130101)

Field of Classification Search

CPC: A63B (23/18); A63B (21/00069); A63B (24/0062); A63B (24/0075); A63B (71/0622); A63B (2071/0658); A63B (2220/56); A63B (2225/20); A63B (2024/0093); A63B (2230/405); A63B (21/0085); A63B (23/185); A63B (2225/50); A63B (24/0087); A61B (5/00); A61B (5/087); A61B (5/091); G16H (20/30)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3674910	12/1971	McKenzie	984/137	G10D 7/14
4196650	12/1979	Fricke	84/718	G10H 1/0558
5042467	12/1990	Foley	128/200.14	A61M 15/0086
5899832	12/1998	Hougen	482/13	A63B 23/18
6058932	12/1999	Hughes	482/13	A61M 16/0006
6083141	12/1999	Hougen	128/202.16	A61M 16/0006
6176235	12/2000	Benarrouch	128/205.12	A61M 16/20
6326532	12/2000	Antaki	84/377	G10D 7/14
6702769	12/2003	Fowler-Hawkins	482/13	A61M 16/08
6984214	12/2005	Fowler-Hawkins	482/13	A61M 16/0006
8653346	12/2013	Schaman	84/377	G10D 7/14
10369408	12/2018	Keller	N/A	A61M 16/0006
2004/0158178	12/2003	Fowler-Hawkins	601/41	A61M 16/08
2006/0223675	12/2005	Lew	482/13	A63D 3/00
2013/0036893	12/2012	Schaman	84/377	G10D 7/14

2015/0133810	12/2014	Osaki	600/538	A61B 5/486
2015/0314090	12/2014	Wu	128/202.22	A61M 16/0003
2018/0330702	12/2017	Schille	N/A	G10H 1/386

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2012-187292	12/2011	JP	N/A
2015-093039	12/2014	JP	N/A
10-2018-0095753	12/2017	KR	N/A
10-2019-0081588	12/2018	KR	N/A
10-2113999	12/2019	KR	N/A

OTHER PUBLICATIONS

International Search Report for PCT/KR2021/015324 mailed Apr. 19, 2022 from Korean Intellectual Property Office. cited by applicant

Korean Office Action for related KR Application No. 10-2021-0096821 mailed Sep. 27, 2021 from Korean Intellectual Property Office. cited by applicant

Primary Examiner: Atkinson; Garrett K

Attorney, Agent or Firm: Paratus Law Group, PLLC

Background/Summary

CROSS-REFERENCE TO PRIOR APPLICATIONS

(1) This Application is a National Stage Application of PCT International Application No. PCT/KR2021/015324 (filed on Oct. 28, 2021), which claims priority to Korean Patent Application No. 10-2021-0096821 (filed on Jul. 23, 2021), which are all hereby incorporated by reference in their entirety.

BACKGROUND

(2) The present invention relates to a portable breathing measurement and breathing exercise device, and more specifically, to a portable breathing measurement and breathing exercise device, which enables breathing measurement through self-diagnosis to allow safe breathing measurements in pandemic situations such as COVID-19, includes a load control unit to allow customized breathing training for a user, measures the user's breathing capacity or respiratory muscle pressure (MIP, or MEP) in real-time to acquire data by applying information communication technology, guides breathing training according to calculated values considering the user's gender and age based on the acquired data, enables breathing information to be digitized through applications and world wide web to utilize the data in monitoring and diagnosis, and sends alerts to medical personnel in real-time in emergency situations when the user's breathing falls below a predetermined lower limit of normal (LLN) so that the medical personnel can take measures.

(3) Due to the pandemic situation caused by COVID-19 and others, there is a tendency to avoid breathing measurements in hospitals. Accordingly, there is a demand for self-diagnostic breathing measurement devices.

(4) Meanwhile, breathing training is to train patients, who have respiratory difficulties, proper breathing methods in order to alleviate symptoms, such as difficulty in breathing, improve the quality of life, and enhance physical and emotional participation in daily life. Particularly, for

patients after lung surgery or patients with chronic obstructive pulmonary disease, breathing training is essential for treatment and recovery.

(5) Moreover, continuous breathing training is essential for respiratory muscle and diaphragm strengthening, lung expansion and stable oxygen supply through inhalation and exhalation training, development of lung capacity and cardiopulmonary function through consistent breathing training, vibrant metabolism through smooth oxygen supply, and participation in leisure/sports activities through cardiopulmonary strengthening.

(6) As an example of conventional breathing measurement devices, Korean Utility Model Registration No. 20-0484020 discloses a precise breathing test device, which can precisely and accurately measure a subject's lung volume to prevent an artificial change and an eddy current phenomenon caused by the Bernoulli effect from occurring on the air exhaled by the subject.

(7) However, such a conventional device cannot guide customized breathing training to each user while measuring the user's breathing capacity, and cannot be continuously used as a portable device.

SUMMARY

(8) Accordingly, the present invention has been made in view of the above-mentioned problems occurring in the related art, and it is an objective of the present invention to provide a portable breathing measurement and breathing exercise device, which enables breathing measurement through self-diagnosis to allow safe breathing measurements in pandemic situations such as COVID-19, includes a load control unit to allow customized breathing training for a user, measures the user's breathing capacity in real-time to acquire data by applying information communication technology, guides breathing training based on the acquired data, enables breathing information to be digitized through applications and world wide web to utilize the data in diagnosis, and sends alerts to medical personnel in real-time in emergency situations when the user's breathing falls below a predetermined lower limit of normal (LLN) so that the medical personnel can take measures.

(9) The aspects of the present invention are not limited to those mentioned above, and other aspects not mentioned herein will be clearly understood by those skilled in the art from the following description.

(10) To accomplish the above-mentioned objects, according to the present invention, there is provided a portable breathing measurement and breathing exercise device including: a body part; a mouthpiece part which is coupled to one side of the main body part; a sensor unit which is provided inside the main body part and measures the pressure of a user's breath through the mouthpiece part; a control unit which receives the measurement values from the sensor unit, stores the measurement value in real-time, analyzes the user's breath based on the measurement value, and provides an exercise schedule; and a display unit which outputs the analysis results and exercise schedule from the control unit, wherein the mouthpiece part includes a load adjusting part which controls the flow of air moving in and out of the mouthpiece part and the main body part due to the user's breath.

(11) Moreover, the mouthpiece part includes: an inlet which is inserted into the user's mouth; a mouthpiece body which is provided at the bottom of the inlet and formed in a cylindrical shape; a filter part which is provided inside the mouthpiece body; and a flexible part which extends from the bottom of the mouthpiece body, and the load adjusting part is provided at the lower portion of the flexible part and is coupled to the upper portion of the main body part.

(12) Furthermore, the main body part includes: a cylindrical part which protrudes upwards from the top of the main body part and has an empty space formed inside; a plurality of slit parts which are provided along the lower outer circumference of the cylindrical part; and a main hole which is formed at least partially through the cylindrical part, and the load adjusting part includes: a coupling part which is formed to surround around the outer circumference of the cylindrical part; a protrusion which is formed on the end of the coupling part to have a shape corresponding to the

shape of the plurality of slit parts; and an adjustment hole which is formed at least partially through the coupling part, such that the main body part and the load adjusting part are coupled with each other when the protrusion is inserted into any one of the plurality of slit parts.

(13) Additionally, the control unit includes: a personal web program which receives and stores the measurement values from the sensor unit in real-time; a web server which is linked to the personal web program and receives and stores the measurement values from the sensor unit in real-time; and an administrator web program which is linked to the web server and receives and stores the measurement values from the sensor unit in real-time. The display unit includes: a personal display which outputs the measurement values of the sensor unit; and an administrator display which is located remotely from the personal display and outputs the measurement values of the sensor unit, thereby allowing an administrator to monitor the measurement values of the sensor unit remotely. If the measurement values of the sensor unit fall below a preset threshold or are not transmitted for a preset duration, the control unit sends an alarm signal to the administrator web program and controls the output of the alarm signal to the administrator display.

(14) In addition, each of the personal display and the administrator display includes: an application which receives and stores measurement values from the sensor unit in real-time, analyzes the user's breath based on the measurement values of the sensor unit, and supports breathing exercise. The sensor units are provided in plural, and are respectively linked to the personal web program, the administrator web program, and the application. Each of the personal web program, the administrator web program, and the application stores information data of at least one reference sensor unit, and corrects the measurement values of the sensor units according to the state of the load adjusting part corresponding to each of the plurality of sensor units, thereby minimizing a measurement error between the different sensor units.

(15) The portable breathing measurement and breathing exercise device according to the present invention enables breathing measurement through self-diagnosis to allow safe breathing measurements in pandemic situations such as COVID-19, includes a load control unit to allow customized breathing training for a user, and can measure the user's breathing capacity in real-time to acquire data by applying information communication technology, and guide breathing training based on the acquired data.

(16) Moreover, the portable breathing measurement and breathing exercise device according to the present invention can adjust the intensity of breathing exercise by setting the main hole and the adjustment hole to communicate or not to communicate with each other as the protrusion is inserted into any one of the plurality of slit parts.

(17) Furthermore, the portable breathing measurement and breathing exercise device according to the present invention can enhance inspiratory muscle strength and endurance, increase diaphragmatic thickness, increase cardiac output, increase maximum oxygen consumption, prolong the time to exhaustion, and improve lactate decomposition ability.

(18) Additionally, the portable breathing and measurement breathing exercise device according to the present invention can monitor the state of breathing exercise in real-time.

(19) In addition, the portable breathing measurement and breathing exercise device according to the present invention allows users to continue breathing exercises and measurements without being bored through applications, and enables children to be interested and actively participate in breathing exercises and measurements.

(20) The advantages of the present invention are not limited to the above-mentioned advantages, and other advantages, which are not specifically mentioned herein, will be clearly understood by those skilled in the art from the following description.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a configuration diagram of a portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (2) FIG. 2 is a view illustrating a main body and a mouthpiece part of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (3) FIG. 3 is an exploded view illustrating the configuration of the main body part of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (4) FIG. 4, (a) is a front view of the main body part of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (5) FIG. 4, (b) is a side view of the main body part of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (6) FIG. 5, (a) is a view illustrating a state in which a main hole and an adjustment hole of the portable breathing measurement and breathing exercise device are coupled so as not to communicate with each other according to an embodiment of the present invention.
- (7) FIG. 5, (b) is a view illustrating the state in which the main hole and the adjustment hole of the portable breathing measurement and breathing exercise device are coupled to communicate with each other according to an embodiment of the present invention.
- (8) FIG. 6 is a side perspective view illustrating the configuration of the main body part of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (9) FIG. 7 is a view illustrating a plurality of adjustment holes of a portable breathing measurement and breathing exercise device according to another embodiment of the present invention.
- (10) FIG. 8 is a sectional view illustrating a plurality of adjustment holes of a portable breathing measurement and breathing exercise device according to another embodiment of the present invention.
- (11) FIG. 9 is a view illustrating a control configuration of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (12) FIGS. 10 and 11 are views illustrating a screen of a display part or an application of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (13) FIG. 12 is a flow chart showing an MIP and MEP diagnostic process of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (14) FIG. 13 is a view illustrating a screen of a display part or an application of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (15) FIG. 14 is an enlarged view illustrating the mouthpiece part and a pressure unit of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (16) FIG. 15 is a view illustrating the pressure unit of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (17) FIG. 16 is a view illustrating a frame part of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (18) FIG. 17 is a view illustrating an adjustment cover of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (19) FIG. 18 is a view illustrating a main filler of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (20) FIG. 19 is a view illustrating a sub-filler of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.

- (21) FIG. **20** is a view illustrating a regulator of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (22) FIG. **21** is a view illustrating a spring of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (23) FIG. **22** is a view illustrating a barrier of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (24) FIG. **23** is a view illustrating a sealing member of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (25) FIG. **24** is a side view illustrating a pressure unit of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (26) FIG. **25** is a sectional view illustrating the pressure unit of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (27) FIG. **26** is a sectional view illustrating the action of the pressure unit during inhalation of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (28) FIG. **27** is a sectional view illustrating the action of the pressure unit during exhalation of the portable breathing measurement and breathing exercise device according to an embodiment of the present invention.
- (29) FIG. **28** is a view illustrating two pressure units of the portable breathing measurement and breathing exercise device according to another embodiment of the present invention.

DETAILED DESCRIPTION

- (30) The terms used in the present specification will be explained in brief, and the present invention will be described in detail.
- (31) The terms used in the present invention have been chosen to be the general terms currently widely used, while considering the functions in the present invention. However, the terms may be changed depending on the intent of technicians in the field, precedents, or the emergence of new technologies. Therefore, the terms used in the present invention should be defined not just by the name of the term, but based on the meanings of the terms and the contents of the present invention as a whole.
- (32) In the entire specification of the present invention, when any portion “includes” any component, this does not exclude other components but means that any other component can be further included, unless stated otherwise.
- (33) Hereinafter, the embodiments of the present invention will be described in detail with reference to accompanying drawings so that the embodiments may be easily implemented by those skilled in the art. However, the present invention may be implemented in various ways without being limited to the embodiments.
- (34) Specific details including the technical problem, the technical solution, and the advantageous effects are included in the embodiments and drawings described below. The advantages and features of the present invention and the methods of achieving them will become clear with reference to the embodiments described in detail with the accompanying drawings.
- (35) Hereinafter, the present invention will be described in more detail with reference to the attached drawings.
- (36) Referring to FIGS. **1** through **9**, a portable breathing measurement and breathing exercise device according to a preferable embodiment of the present invention includes: a main body part **100**; a mouthpiece part **200** which is coupled to one side of the main body part **100**; a sensor unit **300** which is provided inside the main body part **100** and measures the pressure of a user's breath through the mouthpiece part **200**; a control unit **400** which receives the measurement values from the sensor unit **300**, stores the measurement value in real-time, analyzes the user's breath based on the measurement value, and provides an exercise schedule; and a display unit **500** which outputs the analysis results and exercise schedule from the control unit **400**.

(37) First, the main body part **100** is provided. The main body part **100** has an empty space inside and is formed to have an overall elliptical cross-section. For example, referring to FIGS. 2 and 3, the main body part **100** includes a left case **101**, a right case **102** which has a shape corresponding to the left case **101** and is coupled to the left case **101**, and caps **103** which are respectively coupled to the upper and lower portions of the left case **101** and the right case **102**.

(38) Moreover, the main body part **100** has a board **104** provided therein, and a display part **150**, a power switch **161**, an operation switch **162**, and a charging terminal **170** can be provided on the board **104**. Here, the display part **150** is provided on the front surface of the left case **101** to display the measurement values of the sensor unit **300**, the power switch **161** turns on and off the supply of power to the display part **150** and the operation switch **162**, the operation switch **162** allows setting the start and the end of breathing measurement and breathing exercise, and the charging terminal **170** allows charging a battery (not illustrated) which supplies power to the display part **150**, the power switch **161**, and the operation switch **162**.

(39) Next, the mouthpiece part **200** is provided. The mouthpiece part **200** includes: an inlet **210** which is inserted into the user's mouth; a mouthpiece body **220** which is provided at the bottom of the inlet **210** and formed in a cylindrical shape; a filter part **230** which is provided inside the mouthpiece body **220**; and a flexible part **240** which extends from the bottom of the mouthpiece body **220**.

(40) More specifically, the inlet **210** is inserted into the user's mouth during breathing measurement and exercise and allows the user's inspiration or expiration to flow to the sensor unit **300**. At this time, the inlet **210** is formed of a material which is harmless to the human body, and is designed to be easily assembled and disassembled to prevent the user's body fluid from being transferred to another user. That is, the inlet **210** can be selectively inserted into and coupled with the mouthpiece body **220**.

(41) Furthermore, the mouthpiece body **220** has a tube therein to allow the flow of the user's inhalation or exhalation, and is made of a rigid material to prevent the inhalation or the exhalation from leaking outside or shaking during the inhalation or the exhalation. Moreover, inside the mouthpiece body **220**, there is a filter part **230** which prevents the user's saliva or external foreign substances from being transmitted to the sensor unit **300**. In this instance, the filter part **230** may be a bacterial filter to prevent the user's saliva or bacteria from being transmitted to other users. Additionally, the filter part **230** may be made of synthetic fibers, natural fibers, or other various materials. The filter part **230** filters out foreign substances and harmful materials contained in the air passing through the inlet **210**, thereby transmitting only clean air into the main body part **100**, and enabling hygienic use. The filter part **230** also filters the user's breath to enable more accurate measurement of the breath.

(42) Moreover, the flexible part **240** is made of an elastic material and is formed to be rotatable, thereby making it easily accessible to the user's mouth during use. In this instance, the mouthpiece body **220** is formed to be adjustable in length, thereby facilitating easy reach to the user's mouth during use. In other words, the inlet **210** can easily reach the user's mouth without movement of the main body part **100**, thereby facilitating smoother breathing exercises and breathing measurements.

(43) On the other hand, the mouthpiece part **200** includes a load adjusting part **250** which controls the flow of air moving in and out of the mouthpiece part **200** and the main body part **100** due to the user's breath. The load adjusting part **250** is provided at the lower portion of the flexible part **240** and is coupled to the upper portion of the main body part **100**.

(44) More specifically, referring to FIGS. 5 and 6, the main body part **100** includes: a cylindrical part **110** which protrudes upwards from the top of the main body part **100** and has an empty space formed inside; a plurality of slit parts **120** which are provided along the lower outer circumference of the cylindrical part **110**; and a main hole **130** which is formed at least partially through the cylindrical part **110**.

(45) First, the cylindrical part **110** is inserted into a coupling part **251**, which will be described later,

to communicate with the coupling part, such that the user's inhalation or exhalation flowing through the inlet **210** can move into the interior of the main body part **100** and reach the sensor unit **300**. In addition, the plurality of slit parts **120** are radially arranged around the center of the cylindrical part **110**, and are formed alternately with the main hole **130**. In this instance, a protrusion **252**, which will be described later, is inserted into the slit parts **120**, such that the load adjusting part **250** and the main body part **100** can be fixed. Furthermore, the main hole **130** is formed in the center of the cylindrical part **110**, and allows at least a portion of the user's inhalation or exhalation flowing through the inlet **210** to leak outside when communicating with the adjustment hole **253**. In other words, when the main hole **130** and the adjustment hole **253** communicate, more intense breathing training can be conducted.

(46) The load adjusting part **250** includes: a coupling part **251** which is formed to surround around the outer circumference of the cylindrical part **110**; a protrusion **252** which is formed on the end of the coupling part **251** to have a shape corresponding to the shape of the plurality of slit parts **120**; and an adjustment hole **253** which is formed at least partially through the coupling part **251**, such that the main body part **100** and the load adjusting part **250** are coupled with each other when the protrusion **252** is inserted into any one of the plurality of slit parts **120**.

(47) First, the coupling part **251** has an empty space formed inside, and has an inner circumference corresponding to the outer circumference of the cylindrical part **110**. The protrusion **252** protrudes downwards from the coupling part **251**, and is eccentrically formed from the center of the coupling part **251**. As the cylindrical part **110** is inserted into the coupling part **251** and the protrusion **252** is inserted into the slit part **120**, the load adjusting part **250** and the main body part **100** are coupled. In this instance, the cylindrical part **110** may further include a guide part **111** which protrudes upwards from the inner surface to facilitate the insertion into the coupling part **251**. The guide part **111** serves to guide the cylindrical part **110** into the coupling part **251** more easily. Additionally, the adjustment hole **253** is formed in the center of the coupling part **251**, and allows at least a portion of the user's inhalation or exhalation flowing through the inlet **210** to leak outside when communicating with the adjustment hole **253**. In other words, when the main hole **130** and the adjustment hole **253** communicate, more intense breathing training can be conducted.

(48) In other words, when the protrusion **252** is inserted into any one of the multiple slit parts **120**, the main hole **130** and the adjustment hole **253** can communicate with each other. Here, the longitudinal length of the cylindrical part **110** is formed to be equal to the longitudinal length of the coupling part **251**, and the main hole **130** and the adjustment hole **253** are formed to correspond to each other at the central portion of the cylindrical part **110** and at the central portion of the coupling part **251**, respectively. Additionally, the length ranging from the protrusion **252** to the adjustment hole **253** is formed to be the same and correspond to the length ranging from the slit part **120** to the main hole **130**. Therefore, as illustrated in FIG. 5, (a), when the cylindrical part **110** is inserted into the coupling part **251** in the state in which the adjustment hole **253** is positioned at the rear, the main hole **130** is closed so that the user's inhalation or exhalation does not leak outside.

Conversely, as illustrated in FIG. 5, (b), when the mouthpiece part **200** is rotated with the adjustment hole **253** positioned at the front and the cylindrical part **110** is inserted into the coupling part **251**, the main hole **130** and the adjustment hole **253** communicate with each other so that at least a portion of the user's inhalation or exhalation flowing through the inlet **210** leaks outside. As described above, when the protrusion **252** is inserted into any one of the plurality of slit parts **120**, the intensity of breathing exercises can be adjusted.

(49) Consequently, as illustrated in FIG. 5, (a), when the cylindrical part **110** is inserted into the coupling part **251** in the state in which the adjustment hole **253** is located at the rear, the main hole **130** is closed and the user's inhalation or exhalation does not leak outside, thereby achieving more accurate breathing measurement. Furthermore, as illustrated in FIG. 5, (b), when the mouthpiece part **200** is rotated in the state in which the adjustment hole **253** is positioned at the front and the cylindrical part **110** is inserted into the coupling part **251**, the main hole **130** and the adjustment

hole **253** communicate with each other such that at least a portion of the user's inhalation or exhalation flowing through the inlet **210** leaks outside, thereby facilitating more intense breathing exercises.

(50) Referring to FIG. **6**, the main body part **100** further includes a plurality of sub-holes **140** provided along the lower outer circumferential surface of the cylindrical part **110**, and the plurality of sub-holes **140** are provided alternately with the plurality of slit parts **120**. The plurality of sub-holes **140** are arranged radially around the center of the cylindrical part **110**. For example, the sub-holes **140** may be spaced at 90-degree angles around the center of the cylindrical part **110** relative to adjacent sub-holes. Here, the plurality of sub-holes **140** are provided on the same circumference of a virtual circle as the plurality of slit parts **120**, such that at least a portion of the user's inhalation and exhalation always leaks outside. That is, the plurality of sub-holes **140** function to prevent damage to the sensor unit **300** and other components from sudden pressure changes inside the main body part **100** and mouthpiece part **200** due to the user's breath.

(51) Next, referring to FIGS. **7** and **8**, the plurality of adjustment holes **253** are arranged radially based on the center of the coupling part **251**. For example, the adjustment holes **253** may be provided at 90-degree angles to each adjacent adjustment hole **253** centered on the coupling part **251**. Moreover, the plurality of adjustment holes **253** can be formed to have different diameters. For example, the plurality of adjustment holes **253** can be arranged in such a way that the diameter of the adjustment hole **253** located at the front surface gradually increases as the coupling part **251** rotates clockwise. In this instance, diameter of each of the plurality of adjustment holes **253** is formed to be equal to or less than the diameter of the main hole **130**.

(52) Moreover, the slit parts **120** can be formed at 90-degree intervals around the center of the cylindrical part **110** relative to adjacent slit parts. As a result, when the protrusion **252** is inserted into one of the plurality of slit parts **120**, one of the plurality of adjustment holes **253** communicates with the main hole **130**. For example, when the protrusion **252** is inserted into the second slit part **120-2**, the main hole **130** communicates with the second adjustment hole **253-2**, and when the protrusion **252** is inserted into the third slit part **120-3**, the main hole **130** communicates with the third adjustment hole **253-3**. As described above, when the protrusion **252** is inserted into any one of the multiple slit parts **120**, the intensity of breathing exercises can be adjusted more minutely in stages.

(53) Next, the control unit **400** receives measurement values from the sensor unit **300**, stores them in real-time, analyzes the user's breath based on the values, and provides an exercise schedule. For example, the control unit **400** may be a public institution server away from the sensor unit **300**, and if the measurement value from the sensor unit **300** falls below the minimum standard for respiratory muscles, may generate an alarm signal to prompt a visit to a hospital or a similar facility. Therefore, the control unit **400** allows for the safe performance of breathing measurements through self-diagnosis in pandemic situations like COVID-19. Furthermore, the sensor unit **300** has a GPS function to periodically transmit the location of the relevant sensor unit **300**, thereby allowing the public institution server to track the location of the sensor unit **300**. Additionally, the sensor unit **300** may be a pressure sensor, which measures the pressure of the flow of the user's inhalation or exhalation and transmits the measurement values to the control unit **400**. In addition, a display unit **500** serves to output the analysis results and exercise schedule from the control unit **400**.

(54) In more detail, the sensor unit **300** is attached to and detached from the board **104**, and serves to measure and transmit the user's breathing pattern. That is, the sensor unit **300** serves to measure the pressure and the flow rate of the user's inhalation or exhalation, and can have any form as long as it can measure the pressure and the flow rate of the user's inhalation or exhalation. For example, the sensor unit **300** may be a pressure sensor which measures the user's lung volume.

(55) In this instance, the sensor unit **300** includes a communication part (not illustrated) that transmits the measurement values of the sensor unit **300** to a terminal device, and the display unit

500 can include an application **510** that analyzes the user's breathing pattern measurement values received from the communication part. The communication part can perform wireless communication using Bluetooth, WiFi, NFC, etc. The application **510** analyzes the user's breath based on the measurement values, and provides an appropriate exercise schedule for the user. Additionally, the application **510** can display analysis results and exercise schedules.

(56) In addition, the sensor unit **300** can include: a light-emitting part (not illustrated) that indicates the charging status and the operational status of the sensor unit **300**; and a supply part (not illustrated) that supplies power to the sensor unit **300**.

(57) In more detail, the light-emitting part may be an LED lamp which emits light in different colors according to the charging status or the operational status of the sensor unit **300**, thereby allowing the user to easily check the status visually. For example, the light-emitting part does not emit light ordinarily but lights up in a predetermined color when the user measures inhalation or exhalation, to indicate that the breathing measurement is in progress.

(58) Additionally, the communication part is provided to transmit and receive wireless signals with one or more external devices, and can include at least one of a Bluetooth chip, a WiFi chip, an NFC chip, or a wireless communication chip (such as an LTE chip). According to an embodiment of the invention, the communication part may use a Bluetooth chip for near-field communication with an external terminal, but it is just an example, and long-distance communication methods could also be used for communication with the terminal.

(59) Moreover, the supply part may include one or more rechargeable batteries built-in for power supply or a power module that can receive external power through a wired connection.

(60) Furthermore, the control unit **400** includes: a personal web program **401** which receives and stores the measurement values from the sensor unit **300** in real-time; a web server (not illustrated) which is linked to the personal web program **401** and receives and stores the measurement values from the sensor unit **300** in real-time; and an administrator web program **402** which is linked to the web server and receives and stores the measurement values from the sensor unit **300** in real-time. In addition, the display unit **500** includes: a personal display **501** which outputs the measurement values of the sensor unit **300**; and an administrator display **502** which is located remotely from the personal display **501** and outputs the measurement values of the sensor unit **300**, thereby allowing an administrator to monitor the measurement values of the sensor unit **300** remotely. In this instance, if the measurement values of the sensor unit **300** fall below a preset threshold or are not transmitted for a preset duration, the control unit **400** sends an alarm signal to the administrator web program **402** and controls the output of the alarm signal to the administrator display **502**. As a result, it allows for remote monitoring of users, such as patients with pulmonary surgery and patients with respiratory diseases, and allows real-time monitoring, especially for socially vulnerable groups such as the elderly living alone. Moreover, if the measurement values from the sensor unit **300** fall below a preset threshold or are not transmitted for a preset duration, it can induce visit of medical personnel and caregivers, thereby allowing for immediate action to be taken. The data stored in the administrator web program can be used as reference material for the diagnosis and treatment of the respective user.

(61) Additionally, the application **510** is provided. The application **510** can analyze the user's breathing based on the measurement values from the sensor unit **300** and provide an appropriate exercise schedule for the user.

(62) Moreover, the application **510** enables the exercise schedule management, the exercise status feedback, the analysis of exercise results, and the calorie consumption by breathing exercises to be output to a terminal such as the user's smartphone, based on the user's breathing information transmitted from the communication part. In this instance, the application **510** can serve to output analysis results and exercise schedules. That is, the application **510** can digitally display the user's lung volume through the value calculated by the sensor unit **300**, and the exercise schedule management, the exercise status feedback, and the analysis of exercise results can be output to the

user's device, such as a smartphone, by the application **510**.

(63) In addition, the application **510** also allows the user to receive and verify the exercise schedule management, the exercise status feedback, and the analysis of exercise results in real-time. For instance, after the user logs in to the smart app, the user can perform breathing exercises, measure maximum inspiration pressure and maximum expiration pressure, and check the user's usage records.

(64) For example, through the screen of the application **510**, the user registers the user's information, pressure values, and exercise type. In this instance, the user information can be divided and stored in plural, and the exercise types could include, for example, fitness, jogging, and cycling. After registering the user information, the user proceeds with breathing exercises and measurements by executing tabs for GPS, calorie consumption, and breathing pattern. Here, the sensor unit **300** may include a GPS sensor for measuring the location of the sensor unit **300**.

(65) Furthermore, when the user executes the breathing pattern tab, the user can check information such as the best record, and the average record, and for example, the most recent five breathing exercises and measurement values can be output. The application generates a graph with time on the horizontal axis and pressure on the vertical axis to calculate an average value, thereby facilitating an overview of recent breathing exercises and measurements at a glance. The created graph can be automatically stored as a file, and can be transmitted and received. Finally, the application outputs the user's strengths and weaknesses, and proposes methods for reproducing the optimal breathing graph shape.

(66) Additionally, when the user executes the calorie consumption tab, the stored breathing exercise and measurement values are displayed in a time-sequenced manner. For example, when the user clicks on an exercise duration of 30 seconds, information, such as maximum inspiration pressure, average inspiration pressure, maximum expiration pressure, average expiration pressure, and total exercise time, can be displayed. In this instance, breathing exercises and measurements are automatically recorded if the user does exercise for longer than three seconds.

(67) Moreover, when the user executes the GPS tab, the user's travel distance and route, and the user's location at different times of workout can be displayed.

(68) Referring to FIGS. **10** through **13**, the application **510** may include a recent record window **511**, a detailed measurement result window **512**, a summary result window **513**, a result graph window **514**, a correction setting window **515**, a breathing exercise control window **516**, a real-time breathing exercise result window **517**, and a final breathing exercise result window **518**.

(69) In more detail, as illustrated in FIG. **10**, (a), the user can perform user registration and Bluetooth pairing through a REGISTRATION button, and perform settings, such as user manual, glossary, and language selection, through a sawtooth button. In addition, referring to FIG. **10**, (b), when proceeding as a pre-registered user, the user touches the list on the user selection screen, and when the user wants to change the information of the pre-registered user, the user touches the screen till a change button and a delete button are popped up. Moreover, the user can perform new user registration and new Bluetooth pairing through the REGISTRATION button. Referring to FIG. **10**, (c), the sections marked with a red star indicate mandatory fields that must be filled for saving. Lastly, referring to FIG. **10**, (d), the user can perform breathing exercises through an EXERCISE button, perform breathing measurements through an MIP/MEP button, and check stored data through a RECORD button. In this instance, the RECORD button is optional, and a window generated through the EXERCISE and RECORD buttons can include a RECORD button.

(70) Referring to FIG. **11**, (a), the application **510** can produce different sounds for the start, end, and during breathing measurement or exercise. At the top screen of the application **510**, a “ ” mark for entering a help window which explains the terms of MIP/MEP can be formed, and the terms on the window all have the “ ” mark for entering a help window which explains the relevant terms. In addition, for recent record window **511**, a test to be reflected in Report can be selected by pressing for more than one second, and the selected Test may be indicated in a specific color. Five records

can be saved and reviewed, and the currently reviewed test result is marked in orange. When returning from a TECORD button, reset is not executed, and a clear button having a reset function can be formed. Furthermore, the detailed measurement result window **512** can select and output only a desired test result when the user clicks any one among a plurality of MIP/MEP test results, and can be linked with a printer. Furthermore, when the user clicks any one among the plurality of MIP/MEP test results to select the desired test result, a graph corresponding to the selected test result is displayed at the lower portion like the result graph window **514**. Moreover, a CORRECT button allows for correction. A popup window inducing a hospital visit when respiratory muscle status is at risk may be displayed.

(71) Additionally, referring to FIG. **12**, the control unit **400** compares the user's maximum inspiration pressure (MIP) or maximum expiration pressure (MEP) with a reference value to determine whether the MIP or the MEP is above the reference value. In this instance, when the user's MIP or MEP is above the reference, the control unit **400** determines that the user is in a normal state. Conversely, when the user's MIP or MEP is below the reference value, the control unit **400** generates a warning signal suspecting weakened pulmonary muscles. In addition, when the user's MIP or MEP is below the reference value, the control unit **400** determines whether the user's MIP or MEP falls below the preset minimum lower limit of normal (LLN). In this instance, when the user's MIP or MEP is above the preset minimum lower limit of normal (LLN), the control unit **400** generates a caution signal. Moreover, when the user's MIP or MEP falls below the preset minimum lower limit of normal (LLN), the control unit **400** generates a warning signal suspecting a lung disease. Such warning signals are saved or output respectively to the personal web program **401**, the administrator web program **402**, the personal display **501**, the administrator display **502**, and the application **510**.

(72) In addition, referring to FIG. **13**, (a), the breathing exercise control window **516** includes a button to allow adjustment of level by 1 cm H₂O or 1% and a button to adjust the measurement time at 10-second intervals, wherein the level is set to average values according to gender and age by default, and the measurement time is set to one minute by default. Additionally, the pressure ranges from 10% to 100% and can be adjusted by 5%. Accordingly, the MIP and MEP values are automatically changed and displayed. In this instance, the time can also be adjustable by 30 seconds. The default setting for the pressure may be 40% of the MIP and MEP values according to gender and age.

(73) Furthermore, referring to FIG. **13**, (b), the personal display **501** displays the optimized respiratory guideline **517-1** determined by the user's gender and age, with both maximum and minimum values, and displays the user's actual respiratory line **517-2** in real-time, thereby allowing the user to conduct breathing exercises by comparing the respiratory guideline **517-1** and the user's actual respiratory line **517-2**. Moreover, the personal display **501** may display the match rate between the respiratory guideline **517-1** and the respiratory line **517-2** and display the duration of breathing exercise by comparing the respiratory guideline **517-1** and the user's actual respiratory line **517-2**. In this instance, the exhalation duration may be five seconds, and the inhalation duration may be three seconds. Additionally, referring to FIG. **13**, (c), the results of the breathing exercise, ratings according to match rate, and respiratory muscle age can be displayed. In addition, referring to FIG. **13**, (d), a daily breathing exercise result window **519** may be displayed.

(74) Each of the personal display **501** and the administrator display **502** may include an application **510** which receives and stores measurement values from the sensor unit **300** in real-time, analyzes the user's breath based on the measurement values of the sensor unit **300**, and supports breathing exercise. The sensor units **300** are provided in plural, and are respectively linked to the personal web program **401**, the administrator web program **402**, and the application **510**. Moreover, each of the personal web program **401**, the administrator web program **402**, and the application **510** stores information data of at least one reference sensor unit **300** and corrects the measurement values of the sensor units **300** according to the state of the load adjusting part **250** corresponding to each of

the plurality of sensor units **300**, thereby minimizing a measurement error between the different sensor units **300**. Here, the information data of the reference sensor unit **300** refers to the property values of a standard pressure sensor set among various types of pressure sensors. That is, the plurality of sensor units **300** may be different models with different methods or components for measuring pressure, and are to correct errors between measurement values. Furthermore, the state of the load adjusting part **250** may pertain to whether the adjustment hole **253** is opened or not. For example, the portable breathing measurement and breathing exercise device of the invention may include different types of the mouthpiece parts **200** or different types of sensor units **300**.

Accordingly, even if the same user performs breathing measurement, there may be different measurement values. Therefore, in order to solve the problem, the property values of the standard sensor unit **300** are stored in the personal web program **401**, the administrator web program **402**, and the application **510**. Upon linkage, the property values of the plurality of sensor units **300** are respectively stored in the personal web program **401**, the administrator web program **402**, and the application **510**. Based on the above, the personal web program **401**, the administrator web program **402**, and the application **510** compare the property values of the standard sensor unit **300** with those of the different sensor units **300** to correct the measurement values, thereby minimizing measurement errors. Additionally, one portable breathing measurement and breathing exercise device may include the plurality of sensor units **300**.

(75) As a result, the application **510** allows the user to continue breathing exercises and measurements without being bored, and can encourage children's interest and participation in breathing exercises and measurements.

(76) Next, the portable breathing measurement and breathing exercise device may further include a pressure unit **600** which is detachably provided between the inlet **210** and the mouthpiece body **220**. That is, one end of the pressure unit **600** is inserted into the inlet **210**, and the other end of the pressure unit **600** is inserted into the mouthpiece body **220**, such that the pressure unit **600** is coupled between the inlet **210** and the mouthpiece body **220**. In this instance, rings (not illustrated) which is inserted into grooves (not illustrated) formed on the inlet **210** and the mouthpiece body **220** may be provided at both ends of the pressure unit **600**, and the pressure unit **600** can be formed in any shape as long as it is detachable between the inlet **210** and mouthpiece body **220**.

(77) Here, the pressure unit **600** serves to adjust the flow load of the user's inhalation or exhalation passing through the inlet **210**. That is, the pressure unit **600** controls the amount of air flowing into the mouthpiece body **220** during the user's inhalation or exhalation. In other words, it means that when the pressure unit **600** is provided, the amount of air flowing into the mouthpiece body **220** due to the user's inhalation or exhalation is reduced compared to when the pressure unit **600** is not provided.

(78) In this instance, the pressure unit **600** allows air to flow when the inhalation or the exhalation is performed with a pressure exceeding a preset pressure value, and blocks the flow of air when the inhalation or the exhalation is performed with a pressure below the preset pressure value.

(79) In more detail, referring to FIGS. **14** and **15**, the pressure unit **600** includes: a cylindrical frame part **610** having an empty space formed inside, an adjustment cover **620** provided in a manner that wraps around one end side of the frame part **610**, a main filler **630** provided inside the frame part **610** and coupled to the inner surface of the adjustment cover **620**, a sub-filler **640** coupled to the end of the main filler **630**, a regulator **650** having a hollow formed inside into which the main filler **630** is inserted such that the regulator **630** is coupled with the main filler **630**, a spring **660** having one end interfered with the regulator **650** and the other end interfered with the sub-filler **640**, a barrier **670** pivotally coupled to one end side of the main filler **630** and provided parallel to the sub-filler **640**, and a sealing member **680** provided between the sub-filler **640** and the frame part **610**.

(80) Referring to FIG. **16**, the frame part **610** has a 'C'-shaped cross-section with a hollow formed inside, and the sub-filler **640** is inserted into the hollow. Additionally, the frame part **610** is inserted and fixed into the mouthpiece body **220**, and prevents foreign substances from infiltrating inside.

(81) Here, the frame part **610** includes: rail parts **611** which protrude from the inner circumferential surface of the frame part **610** to guide the linear movement of the regulator **650**; and a plurality of adjustment protrusions **612** provided to protrude from the outer circumferential surface of the frame part **610**. For example, the rail parts **611** respectively couple with rail grooves **651** to guide the linear movement of the regulator **650** in response to the user's inhalation and exhalation. Moreover, the plurality of adjustment protrusions **612** can be radially arranged at regular intervals along the outer circumferential surface of the frame part **610**. In this instance, the plurality of protrusions **612** interfere with an elastic protrusion **621**, which will be described later, thereby selectively fixing the adjustment cover **620**.

(82) Referring to FIG. **17**, the adjustment cover **620** has a 'C'-shaped cross-section and is provided to wrap around one end side of the frame part **610**. In this instance, the inner circumferential surface of the adjustment cover **620** may have a spiral groove (not illustrated) or a spiral protrusion (not illustrated). That is, the adjustment cover **620** can couple with the spiral protrusion (not illustrated) or the spiral groove (not illustrated) formed on the outer circumferential surface of one side of the frame part **610** while rotating in contact with the spiral protrusion or the spiral groove.

(83) Here, the adjustment cover **620** includes an elastic protrusion **621** which protrudes from an end of the adjustment cover **620**. For example, the elastic protrusion **621** is formed to protrude from the outer circumferential surface of the adjustment cover **620** in the direction of the adjustment protrusions **612**. Therefore, the elastic protrusion **621** is placed between the adjustment protrusions **612** to fix the adjustment cover **620**. When the adjustment cover **620** is rotated to fix the adjustment cover **620** to the frame part **610**, the elastic protrusion **621** is bent in the upward direction of the plurality of adjustment protrusions **612** by elasticity of the elastic protrusion. That is, the elastic protrusion **621** is formed of a deformable elastic material.

(84) Moreover, the adjustment cover **620** includes a plurality of fitting slots **622** arranged radially to fix the main filler **630**. In this instance, fitting protrusions **631**, which will be described later, are inserted into the plurality of fitting slots **622**, thereby fixing the adjustment cover **620** to the main filler **630**. The plurality of fitting slots **622** are longitudinally elongated to prevent the fitting protrusions **631** from being separated from the fitting slots **622** even when the main filler **630** is moved linearly.

(85) Moreover, the adjustment cover **620** includes a plurality of cover ribs **623** arranged radially around the center of the adjustment cover **620** to allow the flow of the user's inhalation or exhalation. That is, the cover ribs **623** are configured to form an empty space on the outer circumferential surface of the adjustment cover **620** to ensure the rigidity of the adjustment cover **620** and to allow the flow of the user's inhalation or exhalation.

(86) Referring to FIG. **18**, the main filler **630** is inserted into the frame part **610** and coupled to the adjustment cover **620**. In this instance, the main filler **630** includes a plurality of fitting protrusions **631** protruding from the outer circumferential surface of the main filler **630** and arranged radially. The plurality of fitting protrusions **631** have the shape corresponding to the plurality of fitting slots **622**, and are inserted into the fitting slots **622**, so that the main filler **630** is coupled to the adjustment cover **620**. Here, the main filler **630** moves linearly in a direction of contracting the spring **660** during the user's inhalation and moves in a direction of expanding the spring **660** during the user's exhalation.

(87) Additionally, the main filler **630** also includes a shaft **632** which is inserted into the through-hole **641** and rotationally coupled to a spiral thread formed on the inner circumferential surface of the through-hole **641**. The shaft **632** protrudes towards the sub-filler **640** from the center of the main filler **630**. In this instance, a spiral thread may be formed on the outer circumferential surface of the shaft **632** allowing for rotational coupling with the through-hole **641**.

(88) Additionally, the main filler **630** includes a plurality of main filler ribs **633** arranged radially around the center of the main filler **630** to allow the flow of the user's inhalation or exhalation. The plurality of main filler ribs **633** are configured to form an empty space in the main filler **630** to

ensure the rigidity of the main filler **630** and to allow the flow of the user's inhalation or exhalation.

(89) Moreover, the plurality of main filler ribs **633** are gradually inclined to gather towards the center of the shaft **632** as they approach the end of the shaft **632**. Accordingly, the barrier **670** is bent and comes into contact with the outer circumferential surface of the main filler ribs **633** during the user's exhalation.

(90) Referring to FIG. **19**, the sub-filler **640** is disc-shaped and moves linearly in the same direction as the main filler **630** during the linear movement of the main filler **630**. Furthermore, the sub-filler **640** includes: a through-hole **641** formed through the center of the sub-filler **640**; and a sealing groove **642** formed on the outer circumferential surface of the sub-filler **640** to prevent separation of the sealing member **680**. In this instance, at least a portion of the sub-filler **640** can be inserted into or drawn out of the hollow of the frame **210** due to the user's inhalation or exhalation.

(91) Moreover, the sub-filler **640** includes a plurality of sub-filler ribs **643** arranged radially around the center of the sub-filler **640** to allow the flow of the user's inhalation or exhalation. The plurality of sub-filler ribs **643** are configured to form an empty space in the sub-filler **640** to ensure the rigidity of the sub-filler **640** and to allow the flow of the user's inhalation or exhalation.

(92) Referring to FIG. **20**, the regulator **650** has a hollow formed therein, and the hollow of the regulator **650** is formed to correspond to the outer circumferential surface of the main filler **630**. That is, the main filler **630** is inserted and fixed into the hollow of the regulator **650**. In this instance, the regulator **650** includes a plurality of rail grooves **651** arranged radially along the outer circumferential surface thereof. That is, the rail part **611** is inserted into at least one of the plurality of rail grooves **651** to move linearly in the same direction as the linear movement of the main filler **630**.

(93) In addition, the regulator **650** includes an interference part **652** protruding from the inner circumferential surface of the regulator **650** toward the center thereof to accommodate the spring **660**.

(94) Referring to FIG. **21**, the spring **660** is provided between the sub-filler **640** and the regulator **650**. That is, one end of the spring **660** is placed on the interference part **652**, and the other end is placed on the side of the sub-filler **640**. Here, the spring **660** is compressed while the main filler **630** pushes the regulator **650** in one direction as the adjustment cover **620** is coupled to the frame part **610**.

(95) Referring to FIG. **22**, the barrier **670** is disc-shaped and provided between the sub-filler **640** and regulator **650**, and includes an insertion hole **671** formed at the center of the barrier **670**. The insertion hole **671** is inserted into the shaft **632** to fix the barrier **670**. Furthermore, the barrier **670** is provided in a manner that covers at least a portion of the sub-filler **640**. In other words, the barrier **670** serves to block the empty space between the sub-filler ribs **643**. In this instance, the barrier **670** can be formed from a thin, elastic plate material. Therefore, the barrier **670** is bent during the user's exhalation and returns to its original shape after the exhalation. The barrier **670** induces the user to exhale with a force stronger than the elastic force of the barrier **670**, thereby enabling the user to perform exhalation exercise during breathing training. Here, the barrier **670** is bent in a direction adjacent to the outer circumferential surface of the main filler ribs **633** during the user's exhalation. The barrier **670** can be made, for example, of silicone material.

(96) Referring to FIG. **23**, the sealing member **680** is made of rubber material and serves to block a gap between the sub-filler **640** and the frame part **610**. In this instance, the sealing member **680** is provided along the outer circumferential surface of the sub-filler **640**. That is, the sealing member **680** is provided in a state of being placed in the sealing groove **642**.

(97) Referring to FIG. **24**, the compressed state of the spring **660** can be adjusted according to the distance between the adjustment cover **620** and the frame part **610**. In other words, when the adjustment cover **620** is coupled to the frame part **610**, the distance between the adjustment cover **620** and the frame part **610** is adjusted according to the rotational turns of the adjustment cover **620**, thereby adjusting the compression degree of the spring **660**. For instance, when the adjustment

cover **620** is rotated in one direction in the state in which the adjustment cover **620** is coupled to the frame part **610**, the adjustment cover **620** pushes the main filler **630** in the direction of the frame part **610** such that the main filler **630** moves linearly. When the main filler **630** moves linearly toward the frame part **610**, the regulator **650** is also moved in the same direction. Accordingly, the spring **660** is compressed. That is, the user's inhalation becomes easier, so the volume of breathing exercise is reduced. Conversely, when the adjustment cover **620** is rotated in the opposite direction in the state in which the adjustment cover **620** is coupled to the frame part **610**, the adjustment cover **620** pulls the main filler **630** in the opposite direction of the frame part **610**, so the main filler **630** moves linearly. When the main filler **630** moves linearly in the opposite direction to the direction of the frame part **610**, the regulator **650** is also moved in the same direction. Accordingly, the spring **660** is expanded. That is, the user's exhalation becomes harder, so the volume of breathing exercise is increased. Consequently, the rotation of the adjustment cover **620** can change the state of the spring **660**, thereby regulating the user's breathing intensity.

(98) Through such a configuration, referring to FIGS. 25 to 27, the outside air can pass through the pressure unit **600** only when the user inhales with a force stronger than the elastic force of the spring **660**, thereby enabling the user to perform inhalation exercise during breathing training.

(99) In more detail, when the user inserts the inlet **210** into the mouth in the state in which the pressure unit **600** is coupled to the mouthpiece body **220**, the flow of air is regulated by the pressure unit **600**. First, during the user's inhalation, the outside air flows in, and then, is stopped by the barrier **670**. In this instance, when the user inhales with a pressure exceeding the elastic force of the spring **660**, the sub-filler **640** is drawn out of the hollow of the frame part **610**, and a flow path is formed between the sub-filler **640** and the frame part **610**. That is, only when the user inhales with a pressure that exceeds the elastic force of the spring **660**, at least a portion of the sub-filler **640** is drawn out of the hollow of the frame part **610** to form a flow path, such that outside air can flow inside. Thereafter, when the user stops inhalation, the sub-filler **640** is inserted into the hollow of the frame part **610** by the elasticity of the spring **660** to return to its original position.

(100) Referring to FIG. 22, during the user's exhalation, the inside air flows, and then, is stopped by the barrier **670**. In this instance, when the user exhales with pressure exceeding the elastic force of the barrier **670**, the barrier **670** is bent to form a flow path between the barrier **670** and the sub-filler **640**. That is, only when exhalation is performed with pressure exceeding the elastic force of the barrier **670**, the barrier **670** is bent toward the main filler **630**, and at least a portion of the sub-filler **640** is opened to form a flow path, such that the inside air can flow to the outside.

(101) TABLE-US-00001 TABLE 1 Male Twenties Thirties Forties Fifties Sixties MIP (cmH.sub.2O) 111.8 107.7 103.6 99.5 95.4 30% MIP 33.54 32.31 31.08 29.85 28.62

(102) TABLE-US-00002 TABLE 2 Female Twenties Thirties Forties Fifties Sixties MIP (cmH.sub.2O) 95.8 89.7 83.6 77.5 71.4 30% MIP 28.74 26.91 25.08 23.25 21.42

(103) TABLE-US-00003 TABLE 3 Runner Swimmer MIP (cmH.sub.2O) 134 115 80% MIP 107.2 92

(104) In addition, Table 1 and Table 2 show average respiratory pressure values by age group, and propose appropriate exercise numerical values. For the general population, a pressure value of 30% is appropriate, and for athletes, a pressure value of 80% is appropriate. The spring **660** allows adjustment of pressure values within the range of 20 to 100 cmH₂O.

(105) Consequently, breathing exercises can be performed by using the spring **660** and the barrier **670**, and the intensity of the exercises can be adjusted by replacing the spring **660** and the barrier **670**. Furthermore, the user can focus on any one of the inhalation and exhalation exercises when any one of the spring **660** and the barrier **670** is coupled. For example, when the barrier **670** is not coupled to the pressure unit **600** but only the spring **660** is coupled to the pressure unit **600**, the user can focus on inhalation exercises. Conversely, when the spring **660** is not coupled to the pressure unit **600** but only the barrier **670** is coupled to the pressure unit **600**, the user can focus on exhalation exercises.

(106) Next, referring to FIG. 28, the mouthpiece part **200** may further include a pressure unit connector **260** which at least partially surrounds around the outer circumferential surface of the pressure unit **600**. That is, one end of the pressure unit connector **260** is coupled with a first pressure unit **600-1**, and the other end is coupled with a second pressure unit **600-2**. Here, two pressure units **600** are coupled with the mouthpiece part **200** in opposing directions. That is, the two pressure units **600** are provided to be in line symmetry about the central axis in the length direction of the pressure unit connector **260**. In this instance, the pressure unit connector **260** is rotatably coupled, such that the adjustment cover **620** can adjust pressure by rotation of the pressure unit cap **260** when the pressure unit cap **260** rotates. Consequently, the mouthpiece part **200** and the two pressure units **600** are coupled for easy carrying, thereby allowing the user to perform exhalation and inhalation exercises.

(107) Those skilled in the art will understand that the present invention can be implemented as other concrete forms without changing the inventive concept or essential features.

(108) Therefore, these embodiments as described above are only proposed for illustrative purposes and do not limit the present invention. It will be apparent to those skilled in the art that a variety of modifications and variations may be made without departing the spirit and scope of the present invention as defined by the appended claims. Further, such modifications and variations should not be understood independently from the technical idea or perspective of the present invention.

EXPLANATION OF REFERENCE NUMERAL

(109) **100**: main body **101**: left case **102**: right case **103**: cap **104**: board **110**: cylindrical part **111**: guide part **120**: slit part **120-1**: first slit part **120-2**: second slit part **120-3**: third slit part **120-4**: fourth slit part **130**: main hole **140**: sub-hole **150**: display part **161**: power switch **162**: operation switch **170**: charging terminal **200**: mouthpiece part **210**: inlet **220**: mouthpiece body **230**: filter part **240**: flexible part **250**: load adjusting part **251**: coupling part **252**: protrusion **253**: adjustment hole **253-1**: first adjustment hole **253-2**: second adjustment hole **253-3**: third adjustment hole **253-4**: fourth adjustment hole **260**: connector **300**: sensor unit **400**: control unit **401**: personal web program **402**: administrator web program **500**: display unit **501**: personal display **502**: administrator display **510**: application **511**: recent record window **512**: detailed measurement result window **513**: summary result window **514**: result graph window **515**: correction setting window **516**: breathing exercise control window **517**: real-time breathing exercise result window **517-1**: respiratory guideline **517-2** user respiratory line **518**: final breathing exercise result window **519**: daily breathing exercise result window **600**: pressure unit **610**: frame part **611**: rail part **612**: adjustment protrusion **620**: adjustment cover **621**: elastic protrusion **622**: fitting slot **623**: cover rib **630**: main filler **631**: fitting protrusion **632**: shaft **633**: main filler rib **640**: sub-filler **641**: through-hole **642**: sealing groove **643**: sub-filler rib **650**: regulator **651**: rail groove **652**: interference part **660**: spring **670**: barrier **671**: insertion hole **680**: sealing member

Claims

1. A portable breathing measurement and exercise device comprises: a main body; a mouthpiece assembly which is coupled to one side of the main body; a sensor module provided inside the main body and configured to measure a pressure of a user's breath through the mouthpiece assembly; a controller configured to receive measurement values from the sensor module, store the measurement values in real-time, analyze the user's breath based on the measurement values, and provide an exercise schedule; and a display device configured to output analysis results and the exercise schedule from the controller, wherein the mouthpiece assembly includes a load regulator configured to control a flow of air moving in and out of the mouthpiece assembly and the main body part response to the user's breath, wherein the controller includes: a personal web program configured to receive and store the measurement values from the sensor module in real-time; a web server linked to the personal web program and configured to receive and store the measurement

values from the sensor module in real-time; and an administrator web program linked to the web server and configured to receive and store the measurement values from the sensor module in real-time, wherein the display device includes: a personal display configured to output the measurement values of the sensor module; and an administrator display located remotely from the personal display and configured to output the measurement values of the sensor module, thereby allowing an administrator to monitor the measurement values of the sensor module remotely, wherein if the measurement values of the sensor module fall below a preset threshold or are not transmitted for a preset duration, the controller sends an alarm signal to the administrator web program and controls an output of the alarm signal to the administrator display.

2. The portable breathing measurement and exercise device according to claim 1, wherein the mouthpiece assembly includes: an inlet configured to be inserted into the user's mouth; a mouthpiece body provided at a bottom of the inlet and formed in a cylindrical shape; a filter provided inside the mouthpiece body; and a flexible extension which extends from a bottom of the mouthpiece body, wherein the load regulator is provided at a lower portion of the flexible extension and is coupled to an upper portion of the main body.

3. The portable breathing measurement and exercise device according to claim 2, wherein the main body includes: a cylindrical piece which protrudes upwards from a top portion of the main body and has an empty space formed inside; a plurality of slits provided along a lower outer circumference of the cylindrical piece and a main hole formed at least partially through the cylindrical piece, wherein the load regulator includes: a coupling sleeve configured to surround an outer circumference of the cylindrical piece a protrusion formed at an end of the coupling sleeve and shaped to correspond to a shape of the plurality of slits; and an adjustment hole formed at least partially through the coupling sleeve, such that the main body and the load regulator are coupled with each other when the protrusion is inserted into any one of the plurality of slit parts slits.

4. The portable breathing measurement and exercise device according to claim 1, wherein each of the personal display and the administrator display includes: an application which receives and stores measurement values from the sensor module in real-time, analyzes the user's breath based on the measurement values of the sensor module, and supports breathing exercise, wherein a plurality of sensor modules including the sensor module are provided, and are respectively linked to the personal web program, the administrator web program, and the application, and wherein each of the personal web program, the administrator web program, and the application stores information data of at least one reference sensor module, and corrects measurement values of the plurality of sensor modules according to a state of the load regulator corresponding to each of the plurality of sensor modules, thereby minimizing a measurement error between different sensor modules.
