

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415328
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Wang; Jian

Four side seal packaging bag and preparation device and method thereof

Abstract

The provided are a four side seal packaging bag and a preparation device and method thereof. The preparation device includes at least: a film material conveying mechanism, configured to continuously convey a film material of a packaging bag along a length direction of the film material; a folding mechanism, configured to fold the film material conveyed by the film material conveying mechanism; a cutting mechanism, configured to cut the upper film material; punch-and-cut mechanisms, configured to form square punch-and-cut regions and separate the square punch-and-cut regions from the side accordion film materials; a side accordion forming mechanism, configured to perform a forming operation on the side accordion film materials; and a hot-sealing mechanism, configured to hot-seal the upper film material, the formed side accordion film materials, and the lower film material.

Inventors: Wang; Jian (Shanghai, CN)

Applicant: SHANGHAI ZHOUTAI LIGHT INDUSTRY MACHINERY
MANUFACTURING CO., LTD. (Shanghai, CN)

Family ID: 1000008819162

Assignee: SHANGHAI ZHOUTAI LIGHT INDUSTRY MACHINERY
MANUFACTURING CO., LTD. (Shanghai, CN)

Appl. No.: 18/889492

Filed: September 19, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250010568 A1	Jan. 09, 2025

Foreign Application Priority Data

Related U.S. Application Data

continuation parent-doc WO PCT/CN2023/091935 20230502 PENDING child-doc US 18889492

Publication Classification

Int. Cl.: **B31B70/14** (20170101); **B31B70/26** (20170101); **B31B70/64** (20170101); **B31B70/81** (20170101); **B31B155/00** (20170101); **B31B170/30** (20170101); **B65D33/25** (20060101)

U.S. Cl.:

CPC **B31B70/148** (20170801); **B31B70/266** (20170801); **B31B70/8133** (20170801); **B65D33/2508** (20130101); B31B70/645 (20170801); B31B2155/0012 (20170801); B31B2170/30 (20170801)

Field of Classification Search

CPC: B31B (70/148); B31B (70/266); B31B (70/8133); B31B (70/16); B31B (70/645); B31B (2170/30); B31B (2155/0012)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2090308	12/1936	Potdevin	493/232	B31B 70/00
2788720	12/1956	Browning	156/203	B31B 70/79
8414465	12/2012	Totani	493/243	B65D 31/10
2004/0092375	12/2003	Pansier et al.	N/A	N/A
2004/0258332	12/2003	Totani et al.	N/A	N/A
2010/0290722	12/2009	DeSmedt	493/264	B31B 70/00
2010/0310195	12/2009	Miller	493/267	B65D 33/2525
2011/0077139	12/2010	Kujat	493/267	B31B 70/8133
2012/0196731	12/2011	Sargin	493/227	B65D 33/22
2014/0187401	12/2013	Totani	493/196	B31B 50/64

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103909680	12/2013	CN	N/A
205238550	12/2015	CN	N/A
106494000	12/2016	CN	N/A
110435218	12/2020	CN	B31B 70/00
202210102401.2	12/2021	CN	N/A
202210120014.1	12/2021	CN	N/A
3408722	12/1984	DE	B65D 31/10
3703757	12/1987	DE	B31B 70/00
1795335	12/2006	EP	N/A
2868466	12/2014	EP	B65D 31/10

H1059387	12/1997	JP	N/A
H11300855	12/1998	JP	N/A
2003170510	12/2002	JP	N/A
WO-2008120062	12/2007	WO	B65B 61/188

Primary Examiner: Kotis; Joshua G

Attorney, Agent or Firm: Bayramoglu Law Offices LLC

Background/Summary

CROSS-REFERENCE TO THE RELATED APPLICATIONS (1) This application is a continuation application of International Application No. PCT/CN2023/091935, filed on May 2, 2023, which is based upon and claims priority to Chinese Patent Application No. 202211720824.7, filed on Dec. 30, 2022, the entire contents of which are incorporated herein by reference.

TECHNICAL FIELD

(1) The present disclosure relates to the field of packaging bag processing machinery, and in particular, to a four side seal packaging bag and a preparation device and method thereof.

BACKGROUND

(2) Packaging bags, which refer to bags for packaging various products, are widely used in daily life and industrial production to facilitate the conveyance and storage of items during production and circulation processes. A four side seal packaging bag mainly includes upper and lower film materials, and two side accordion film materials located between the upper and lower film materials.

(3) The applicant has been committed to research and development in the preparation of four side seal packaging bags. The applicant has submitted to the China National Intellectual Property Administration (CNIPA) on Jan. 27, 2022 the Chinese patent application 202210102401.2, titled “FOUR SIDE SEAL PACKAGING BAG AND PREPARATION DEVICE THEREOF”, and the Chinese patent application 202210120014.1, titled “PREPARATION METHOD OF FOUR SIDE SEAL PACKAGING BAG”. Through repeated experimentation and research, the applicant has made further optimization and improvement on these solutions.

SUMMARY

(4) A technical problem to be solved by a technical solution of the present disclosure is to provide a four side seal packaging bag and a preparation device and method thereof.

(5) The present disclosure provides a preparation device of a four side seal packaging bag, including at least: a film material conveying mechanism, configured to continuously convey a film material of a packaging bag along a length direction of the film material; a folding mechanism, configured to fold the film material conveyed by the film material conveying mechanism so as to form an upper film material, a lower film material, and two side accordion film materials of the packaging bag, thereby forming a basic structure of the four side seal packaging bag; a cutting mechanism, configured to cut the upper film material formed by folding by the folding mechanism, along creases, so as to separate the upper film material from the lower film material and the side accordion film materials; punch-and-cut mechanisms, configured to form square punch-and-cut regions on the side accordion film materials separated from the upper film material and separate the square punch-and-cut regions from the side accordion film materials; a side accordion forming mechanism, configured to perform a forming operation on the side accordion film materials after the square punch-and-cut regions are separated by the punch-and-cut mechanism; and a hot-sealing mechanism, configured to hot-seal the upper film material, the formed side accordion film

materials, and the lower film material to form the four side seal packaging bag.

(6) Further, the film material folded by the folding mechanism is a one-piece structure; and the folding mechanism is configured to: fold the film material at a side and a center line of the film material upwards along a conveying direction of the film material; fold the film material back to form two fold angles, thereby forming the side accordion film materials; and fold, after two fold angles are formed at the center line, the folded-back film material upwards to cover upper sides of the two side accordion film materials, thereby forming the upper film material, where an unfolded film material part at a bottom forms the lower film material.

(7) Further, there are at least two punch-and-cut mechanisms; and the two punch-and-cut mechanisms are symmetrically arranged at the side accordion film materials at two sides of the upper film material, to form the square punch-and-cut regions of the two side accordion film materials, respectively.

(8) Further, the punch-and-cut mechanisms each are provided with at least a punch-proof structure; the punch-proof structure is provided with at least a punch-proof pad and a punch-proof pad insertion structure; and the punch-proof pad is inserted between the side accordion film material and the lower film material through the punch-proof pad insertion structure, to prevent damage to the lower film material caused when the punch-and-cut mechanism punches and cuts off the square punch-and-cut region of the side accordion film material.

(9) Further, the punch-and-cut mechanisms each are provided with at least a roll-to-cut structure; the roll-to-cut structure is provided with at least rolling cutters and a rolling cutter drive component; the rolling cutter drive component is connected to the rolling cutters to control roll-to-cut operation of the rolling cutters; the rolling cutters are located above the side accordion film material; and the rolling cutters roll-to-cut the side accordion film material in a direction perpendicular to the conveying direction of the side accordion film material, so as to form punch-and-cut edges of the square punch-and-cut region.

(10) Further, the punch-and-cut mechanisms each are further provided with at least a punching structure; the punching structure is located downstream of the roll-to-cut structure and is provided with at least a punching head and a punching drive structure; and the punching head is configured to punch and cut off the square punch-and-cut region with the punch-and-cut edges through the punching drive structure, thereby forming the square punch-and-cut region independent of the side accordion film material.

(11) Further, the punching head is a straight punching head; a length of the punching head is equal to a distance between the two punch-and-cut edges of the square punch-and-cut region; and during a punching operation, the punching head is located at a connection between the side accordion film material and a side edge of the lower film material, as well as above the side accordion film material.

(12) Further, the punch-and-cut mechanisms each are further provided with at least a gripping structure; the gripping structure is located downstream of the punching structure and is provided with at least a gripping end and a gripping end drive structure; and the gripping end is driven by the gripping end drive structure to grip the square punch-and-cut region punched and cut by the punching head.

(13) Further, the side accordion forming mechanism includes an angle folding mechanism; and the angle folding mechanism is located at two sides of the conveying direction of the film material, and is configured to fold, after the square punch-and-cut region is separated, the side accordion film material along a 45° angle straight line of the punch-and-cut edge, such that the punch-and-cut edge coincides with a side in a length direction of the side accordion after being folded and a right-angled triangle is formed at the side accordion film material.

(14) Further, the side accordion forming mechanism includes at least a seal strip conveying mechanism and the hot-sealing mechanism; the seal strip conveying mechanism is configured to feed, after the square punch-and-cut region is separated, a seal strip to the side accordion film

material along a direction perpendicular to the conveying direction of the film material to cover the punch-and-cut edge; and the hot-sealing mechanism is configured to hot-press the seal strip against the side accordion film material.

(15) Further, the side accordion forming mechanism is provided with either of the angle folding mechanism and the seal strip conveying mechanism.

(16) Further, the preparation device further includes a zipper conveying mechanism for conveying a zipper to a position between the lower film material and the upper film material.

(17) Further, the zipper conveyed by the zipper conveying mechanism is located in a zone of the lower film material corresponding to the original square punch-and-cut region and above the triangle formed by the side accordion forming mechanism or the hot-pressed seal strip.

(18) Further, the preparation device further includes a guiding mechanism; the guiding mechanism is located downstream of the cutting mechanism, and is configured to guide the upper film material cut by the cutting mechanism into another film material conveying mechanism for continuous conveyance in a same direction as the lower film material, and guide the upper film material to merge with the lower film material during final forming of the packaging bag.

(19) The present disclosure provides a preparation method of a four side seal packaging bag, implemented by the preparation device of a four side seal packaging bag, and specifically including the following steps: step 1: continuously conveying, by the film material conveying mechanism, the film material of the packaging bag along the length direction of the film material; step 2: folding, by the folding mechanism, the film material conveyed by the film material conveying mechanism to form the upper film material, the lower film material, and the two side accordion film materials, thereby forming a basic structure of the four side seal packaging bag; step 3: cutting, by the cutting mechanism, the upper film material formed by folding by the folding mechanism along creases, such that the upper film material is separated from the lower film material and the side accordion film materials; step 4: guiding, by the guiding mechanism, the upper film material cut by the cutting mechanism into another film material conveying mechanism for continuous conveyance in the same direction as the lower film material; step 5: forming, by the punch-and-cut mechanisms, the square punch-and-cut regions on the side accordion film materials separated from the upper film material, and separating the square punch-and-cut regions from the side accordion film materials; step 6: performing, by the side accordion forming mechanism, a forming operation on the side accordion film materials after the square punch-and-cut regions are separated; step 7: guiding, by the guiding mechanism, the upper film material with an upper side of the lower film material; and step 8: hot-sealing, by the hot-sealing mechanism, the upper film material, the formed side accordion film materials, and the lower film material to form the four side seal packaging bag.

(20) Further, in the step 2, the film material folded by the folding mechanism is a one-piece structure; and the folding mechanism is configured to: fold the film material at a side and a center line of the film material upwards along a conveying direction of the film material; fold the film material back to form two fold angles, thereby forming the side accordion film materials; and fold, after two fold angles are formed at the center line, the folded-back film material upwards to cover upper sides of the two side accordion film materials, thereby forming the upper film material, where an unfolded film material part at a bottom forms the lower film material.

(21) Further, in the step 5, specifically, the square punch-and-cut region is formed by at least: step 5a: when the side accordion film material enters a station for forming the square punch-and-cut region: inserting, by the punch-proof pad insertion structure of the punch-proof structure, the punch-proof pad between the side accordion film material and the lower film material, so as to prevent damage to the lower film material when the square punch-and-cut region of the side accordion film material is punched and cut off; step 5b: after the placement of the punch-proof pad is finished in the step 5a: starting the rolling cutter drive component of the roll-to-cut structure, and driving the rolling cutters to process the side accordion film material above the punch-proof pad, thereby forming the punch-and-cut edges of the square punch-and-cut region; step 5c: after the

punch-and-cut edges are formed in the step 5b: conveying the side accordion film material to a punching station; driving, by the punching drive structure of the punching structure, the punching head to punch and cut off the square punch-and-cut region with the punch-and-cut edges, thereby forming the square punch-and-cut region independent of the side accordion film material; and step 5d: after the square punch-and-cut region is punched and cut off in the step 5c: conveying the side accordion film material to a gripping station; driving, by the gripping end drive structure of the gripping structure, the gripping end to grip the punched and cut square punch-and-cut region to a waste disposal site for centralized recycling and processing.

(22) Further, in the step 5b, the roll-to-cut structure is provided with at least rolling cutters; the rolling cutters are located above the side accordion film material; and the rolling cutters roll-to-cut the side accordion film material in a direction perpendicular to the conveying direction of the side accordion film material, so as to form punch-and-cut edges of the square punch-and-cut region.

(23) Further, in the step 5c, the punching head is a straight punching head; a length of the punching head is equal to a distance between the two punch-and-cut edges of the square punch-and-cut region; and during a punching operation, the punching head is located at a connection between the side accordion film material and a side edge of the lower film material, as well as above the side accordion film material.

(24) Further, in the step 6, the forming of the side accordion includes at least: folding, after the square punch-and-cut region is separated, the side accordion film material along the 45° angle straight line of the punch-and-cut edge, such that the punch-and-cut edge coincides with the side in the length direction of the side accordion after being folded and a triangle is formed at one end of the side accordion film material.

(25) Further, in the step 6, the forming of the side accordion includes at least: feeding, by the seal strip conveying mechanism after the square punch-and-cut region is separated, the seal strip to the side accordion film material along the direction perpendicular to the conveying direction of the film material to cover the punch-and-cut edge; and hot-pressing, by the hot-sealing mechanism, the seal strip against the side accordion film material.

(26) Further, in the step 6, the forming of the side accordion optionally includes either of the angle folding step and the seal strip conveying step.

(27) Further, before guiding the upper film material to merge with the lower film material in the step 7 after the forming of the side accordion film material in the step 6, the preparation method further includes a zipper mounting step: conveying, by the zipper conveying mechanism, the zipper to the lower film material.

(28) Further, the zipper is located in a zone of the lower film material corresponding to the original square punch-and-cut region and above a triangle formed after the forming of the side accordion or the hot-pressed seal strip.

(29) The present disclosure further provides a four side seal packaging bag, prepared by the above preparation device and method of a four side seal packaging bag, and including at least the upper film material, the lower film material, and the two side accordion film materials located between the upper film material and the lower film material; and the zipper is located above the side accordion film materials between the upper film material and the lower film material; the side accordion film materials include at least two structures; in one structure, a triangle structure is formed at a side of the side accordion film material located at an opening of the packaging bag; and in the other structure, the side accordion film material is a square structure provided with a seal strip structure formed by hot-pressing; and the zipper is located above the triangle structure or the seal strip structure of the side accordion film material.

(30) In the present disclosure, the four side seal packaging bag and the preparation device and method thereof have the following technical effects: (1) In the technical solution, the setting of first forming a punching zone on the original film of the packaging bag during the formation of the side accordion is changed. That is, the formation process of the punch-and-cut region is carried out after

the separation of the upper film material, effectively ensuring the accuracy of the formation position of the punch-and-cut region and avoiding problems such as easy flanging of the film material during conveyance after punching in the original design. (2) The preparation device is in a centralized form, effectively reducing the volume and occupied area of the device after mounting. (3) The operation can be completed easily and quickly by the same station or adjacent stations upstream and downstream. (4) The side accordion forming device effectively ensures the sealing of the side accordion. (5) The same preparation device can prepare two forms of four side seal packaging bags, effectively saving the preparation process. The technical solution features a high degree of mechanization, convenient operation, and a wide range of applications.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order to make the objectives, features, and effects of the present disclosure fully understood, the concepts, specific structures and technical effects of the present disclosure are clearly and completely described below in conjunction with the drawings.

(2) FIG. 1 is a schematic diagram of a film material conveying process according to an embodiment of the present disclosure;

(3) FIG. 2 is a schematic diagram of a process for forming four film materials of a packaging bag by folding a one-piece film material according to an embodiment of the present disclosure;

(4) FIG. 3 is a schematic diagram of preparing a four side seal packaging bag with triangle structure side accordions according to Embodiment 1 of the present disclosure;

(5) FIG. 4 is a structural diagram of a punch-and-cut station according to Embodiment 1 of the present disclosure;

(6) FIG. 5 is a structural diagram of a punching structure according to an embodiment of the present disclosure;

(7) FIG. 6 is a structural diagram of the four side seal packaging bag according to Embodiment 1;

(8) FIG. 7 is a schematic diagram of preparing a four side seal packaging bag with seal strip structure side accordions according to Embodiment 2 of the present disclosure; and

(9) FIG. 8 is a structural diagram of the four side seal packaging bag according to Embodiment 2.

REFERENCE NUMERALS

(10) **1**. film material; **10**. packaging bag; **11**. upper film material; **12**. lower film material; **13**. side accordion film material; **130**. triangle; **131**. seal strip; **132**. square punch-and-cut region; **1320**.

punch-and-cut edge A; **1321**. punch-and-cut edge B; and **14**. zipper; and **20**. film material

conveying mechanism; **21**. cutting mechanism; **22**. guiding mechanism; **23**. hot-sealing

mechanism; **24**. punch-and-cut mechanism; **240**. punch-proof pad; **241**. rolling cutter; **242**.

punching structure; **2420**. mounting seat; **2421**. punching drive structure; and **2422**. opening.

(11) In the figures, the arrow indicates a movement direction of the film material of the packaging bag.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(12) The following clearly and completely describes the technical solutions in the embodiments of the present disclosure with reference to the embodiments of the present disclosure. Apparently, the described embodiments are merely a part rather than all of the embodiments of the present disclosure. All other embodiments obtained by those of ordinary skill in the art based on the embodiments of the present disclosure without creative efforts shall fall within the protection scope of the present disclosure.

(13) The technical solutions of the present disclosure are described below with reference to the embodiments.

Embodiment 1

(14) As shown in FIGS. 1 to 6, the present disclosure provides a preparation process for a four side seal packaging bag with triangle structure side accordions. A preparation device of the packaging bag includes at least the following components.

(15) Film material conveying mechanism **20** is configured to continuously convey film material **1** of packaging bag **10** along a length direction of the film material **1**. The film material conveying mechanism **20** is the same as an existing film material conveying mechanism of a bag making machine, and includes at least conveying rubber rollers for continuous conveyance of the film material **1** of the packaging bag.

(16) A folding mechanism is configured to fold the film material **1** conveyed by the film material conveying mechanism **20** so as to form upper film material **11**, lower film material **12**, and two side accordion film materials **13** of the packaging bag **10**. The film material **1** folded by the folding mechanism is a one-piece structure. The folding mechanism folds the film material **1** at a side and a center line of the film material **1** upwards along the conveying direction of the film material, and folds the film material back to form two fold angles, thereby forming a side accordion film material **13** part. After the two fold angles are formed at the center line, the folding mechanism is further configured to fold the folded-back film material **1** upwards to cover upper sides of the two side accordion film materials **13**, thereby forming the upper film material **11**. An unfolded film material **1** part at a bottom forms the lower film material **12**. The specific structural form of the folding mechanism can refer to the folding mechanism provided by the applicant in the technical solution of the Chinese patent application CN110435218B, or other folding mechanisms can be used, as long as the film material can be folded to form upper film material, the lower film material, and the side accordion film materials.

(17) Cutting mechanism **21** is located at two sides of the film material **1** of the packaging bag, and is configured to cut the upper film material **11** formed by folding by the folding mechanism, along creases, so as to separate the upper film material **11** from the lower film material **12** and the side accordion film materials **13**. In terms of specific structure, the cutting mechanism **21** includes at least a cutting blade and a blade drive mechanism. The cutting blade can be a sheet-like blade or blades in other forms that can cut the film material. The blade drive mechanism can be an electric motor, a robotic arm, a cylinder, etc., which is intended to place the cutting blade between the upper film material **11** and the side accordion film materials **13**, maintain the stability of the cutting blade, and move the cutting blade out after the cutting is completed.

(18) Guiding mechanism **22** is configured to guide the upper film material **11** cut by the cutting mechanism **21** into another film material conveying mechanism for continuous conveyance in a same direction as the lower film material **12**, and guide the upper film material **11** to merge with the lower film material **12** to form the packaging bag **10**. In terms of structure, the guiding mechanism **22** includes at least conveying rubber rollers and a roller-to-roller guiding mechanism. The conveying rubber rollers can be existing rubber rollers, and the roller-to-roller guiding mechanism can be a guiding mechanism in an existing film material conveying or distribution and feeding structure.

(19) Punch-and-cut mechanisms **24** are configured to form square punch-and-cut regions **132** on the side accordion film materials **13** separated from the upper film material **11** and separate the square punch-and-cut regions **132** from the side accordion film materials **13**. More specifically, there are at least two punch-and-cut mechanisms **24**. For example, in this embodiment, there are two punch-and-cut mechanisms. In other embodiments, if the bag making machine is relatively long, multiple punch-and-cut mechanisms can be provided to improve bag making efficiency, and the number of the punch-and-cut mechanisms is a complex number. In this embodiment, the two punch-and-cut mechanisms **24** are symmetrically arranged at the side accordion film materials **13** at two sides of the upper film material **11**, to form the square punch-and-cut regions **132** of the two side accordion film materials **13**, respectively.

(20) For example, a single punch-and-cut mechanism is specifically described below.

(21) The punch-and-cut targets of the punch-and-cut mechanisms **24** are the side accordion film materials **13**, and the side accordion film materials **13** are superposed with the lower film material **12**. Therefore, the punch-and-cut mechanism **24** is provided with at least a punch-proof structure, and the punch-proof structure is provided with at least punch-proof pad **240** and a punch-proof pad insertion structure. The punch-proof pad **240** is inserted between the side accordion film material **13** and the lower film material **12** through the punch-proof pad insertion structure, to prevent damage to the lower film material **12** caused when the punch-and-cut mechanism **24** punches and cuts off region **130** of the side accordion film material **13**. In this embodiment, the punch-proof pad **240** is a square plate-shaped structure. However, in practical use, it can also be a trapezoidal, triangle structure, etc. Preferably, for the convenience of insertion and punch-proof purposes, at least one edge of the punch-proof pad **240** is aligned with the creases of the side accordion film materials **13** and the lower film material **12** to facilitate punch-proof calibration. In addition, if the punch-proof pad **240** is a non-square structure, it includes at least a square area not less than an area of the square punch-and-cut region **132**, such that the square punch-and-cut region **132** can fully cover the punch-proof pad **240** during the punch-and-cut process, ensuring that the punch-and-cut is smooth and does not damage the lower film material **12**. The punch-proof pad insertion mechanism is connected to the punch-proof pad **240** and can use a power device such as a robotic arm, a suction cup robotic arm, or a push rod.

(22) The punch-and-cut mechanism **24** is provided with at least a roll-to-cut structure. Each roll-to-cut structure is provided with at least rolling cutters **241** and a rolling cutter drive component. The rolling cutter drive component is connected to the rolling cutters **241** to control roll-to-cut operation of the rolling cutters **241**. The rolling cutter **241** is located above the side accordion film material **13**, and the rolling cutter **241** rolls to cut off the side accordion film material **13** in a direction perpendicular to the conveying direction of the side accordion film material **13**, so as to form punch-and-cut edge A **1320** and punch-and-cut edge B **1321** of the square punch-and-cut region **132**. It should be noted that in this solution, although the structures for forming the punch-and-cut edges are called “roll-to-cut structure” and “rolling cutter”, it does not mean that only roll-to-cut blade structures belong to the protection scope of this solution. In fact, other blade structures that enter the surface of the side accordion film material in a horizontal or vertical direction to form the punch-and-cut edge also belong to the protection scope of this solution.

(23) In this embodiment, the rolling cutters **241** are circular roll-to-cut blades. There are two rolling cutters configured to form the punch-and-cut edge A **1320** and the punch-and-cut edge B **1321**, respectively. In terms of arrangement form, two separate rolling cutters **241** or one integrated double-edged rolling cutter **241** can be used, as long as the two cutting edges are parallel to each other. The width between the two cutting edges depends on the size of the square punch-and-cut region **132** to be cut according to actual needs.

(24) The rolling cutter drive component of the rolling cutters **241** can be a motor, cylinder, etc. with uniform and stable force application.

(25) The punch-and-cut mechanism **24** is provided with at least punching structure **242**. The punching structure **242** is located downstream of the roll-to-cut structure and is provided with at least a punching head and punching drive structure **2421**. The punching head is connected to the punching drive structure **2421**. The punching head punches out and punches and cuts off region **132** with the punch-and-cut edge A **1320** and the punch-and-cut edge B **1321** through the punching drive structure **2421**, thereby forming the square punch-and-cut region **132** independent of the side accordion film material.

(26) The punching head is a straight punching head. A length of the punching head is equal to a distance between the punch-and-cut edge A **1320** and the punch-and-cut edge B **1321**. During a punching operation, the punching head is located at a connection between the side accordion film material **13** and a side edge of the lower film material **12**, as well as above the side accordion film material **13**.

(27) In this embodiment, the punching structure **242** is provided with mounting seat **2420**. An upper side of the mounting seat **2420** is provided with punching drive structure **2421**. The mounting seat **2420** is provided with opening **2422** facing a side of the film material. During the conveyance process, the side accordion film material **13** and the lower film material **12** enter the opening **2422** of the mounting seat **2420** for positioning. The punching head is located above the opening **2422**. After the square punch-and-cut region **132** of the side accordion film material **13** is positioned, the punching head above the opening **2422** is driven by the punching drive structure **2421** to punch, thereby completely separating the square punch-and-cut region **132** from the side accordion film material **13**.

(28) In this embodiment, the punching drive structure **2421** uses cylinder drive or motor drive.

(29) The punch-and-cut mechanism **24** is provided with at least a gripping structure. The gripping structure is located downstream of the punching structure **242** and is provided with at least a gripping end and a gripping end drive structure. The gripping end is driven by the gripping end drive structure to grip the square punch-and-cut region **132** punched and cut by the punching head. The gripping structure can be a suction cup, a robotic arm, or other gripping tools.

(30) A side accordion forming mechanism is configured to perform a forming operation on the side accordion film materials **13** after the square punch-and-cut region **132** is separated by the punch-and-cut mechanism **24**. In this embodiment, the side accordion forming mechanism includes an angle folding mechanism. The angle folding mechanism is located at two sides of the conveying direction of the film material **1**, and is configured to fold a side of the cut side accordion film material **13** where the punch-and-cut edge B **1321** is formed, along a 45° angle straight line, such that the punch-and-cut edge B **1321** coincides with a side in a length direction of the side accordion after being folded and right-angled triangle **130** is formed at one end of the cut side accordion film material **13**.

(31) Hot-sealing mechanism **23** is configured to hot-seal the upper film material **11**, the formed side accordion film materials **13**, and the lower film material **12** to form the four side seal packaging bag **10**. The hot-sealing mechanism **23** adopts a hot-sealing mechanism of the existing bag making machine. Therefore, the hot-sealing mechanism is a prior art, and will not be further elaborated herein.

(32) A zipper conveying mechanism is configured to convey zipper **14** to a position between the lower film material **12** and the upper film material **11**.

(33) In practical operation, based on the complex process of the bag making machine, other devices used for preparing the four side seal packaging bag, such as the control device and the motor drive device are routine devices for preparing packaging bags, and will not be elaborated herein.

(34) Based on the above preparation device, this embodiment further provides a preparation method of the four side seal packaging bag **10**. The preparation method is implemented by the preparation device of the four side seal packaging bag **10**, and specifically includes the following steps.

(35) Step 1. The film material **1** of the packaging bag is continuously conveyed by the film material conveying mechanism **20** along the length direction of the film material **1**.

(36) Step 2. The folding mechanism folds the film material **1** conveyed by the film material conveying mechanism **20**. The film material folded by the folding mechanism is a one-piece structure. The folding mechanism folds a side and a center line of the film material upwards along the conveying direction to form two fold angles, thereby forming the side accordion film material **13** part. After the two fold angles are formed at the center line, the folded film material is folded upwards to cover the upper sides of the two side accordion film **13**, thereby forming the upper film material **11**. An unfolded film material part at the bottom forms the lower film material **12**. In this way, a basic structure of the four side seal packaging bag **10** is formed.

(37) Step 3. The cutting mechanism **21** cuts the upper film material **11** formed by folding by the folding mechanism along creases, such that the upper film material **11** is separated from the lower

film material **12** and the side accordion film materials **13**.

(38) Step 4. The guiding mechanism **22** guides the upper film material **11** cut by the cutting mechanism **21** into another film material conveying mechanism for continuous conveyance in the same direction as the lower film material **12**.

(39) Step 5. The punch-and-cut mechanism **24** punches and cuts off region **132** on the side accordion film material **13** separated from the upper film material **11**, and separates the square punch-and-cut region **132** from the side accordion film material **13**. The specific punching steps are as follows.

(40) Step 5a. When the side accordion film material **13** enters a station for forming the square punch-and-cut region **132**, the punch-proof pad **240** insertion structure of the punch-proof structure inserts the punch-proof pad between the side accordion film material **13** and the lower film material **12**, so as to prevent damage to the lower film material **12** when the square punch-and-cut region **132** of the side accordion film material **13** is punched and cut off.

(41) Step 5b. After the placement of the punch-proof pad **240** is finished in the step 5a, the rolling cutter drive component of the roll-to-cut structure is started to drive the rolling cutter **241** to process the side accordion film material **13** above the punch-proof pad **240**, thereby forming the punch-and-cut edge A **1320** and the punch-and-cut edge B **1321** of the square punch-and-cut region **132**.

(42) Step 5c. After the punch-and-cut edge A **1320** and the punch-and-cut edge B **1321** are formed in the step 5b, the side accordion film material **13** is conveyed to a punching station. The punching drive structure of the punching structure **242** drives the punching head to punch and cut off the square punch-and-cut region **132** with punch-and-cut edges A **1320** and B **1321**, thereby forming the square punch-and-cut region **132** independent of the side accordion film material.

(43) Step 5d. After the square punch-and-cut region **132** is punched and cut off in the step 5c, the side accordion film material **13** is conveyed to a gripping station. The gripping end drive structure of the gripping structure drives the gripping end to grip the punched and cut square punch-and-cut region **132** to a waste disposal site for centralized recycling and processing.

(44) Step 6. The side accordion forming mechanism performs a forming operation on the side accordion film material **13** after the square punch-and-cut region **132** is separated. The side accordion film material **13** separated from the square punch-and-cut region **132** is folded along the 45° angle straight line of the punch-and-cut edge B **1321**, such that the punch-and-cut edge B **1321** coincides with side edge in the length direction of the side accordion after being folded, and a right-angled triangle is formed at one end of the side accordion film material **13**.

(45) Step 7. The zipper conveying device conveys the zipper to the lower film material **12** after the side accordion is formed. The zipper **14** is located in a zone of the lower film material corresponding to the original square punch-and-cut region **132** and above the triangle formed after the side accordion is formed.

(46) Step 8. The guiding mechanism **22** guides the upper film material **11** with an upper side of the lower film material **12**.

(47) Step 9. The hot-sealing mechanism **23** seals the upper film material **11**, the formed side accordion film materials **13**, and the lower film material **12** to form the four side seal packaging bag **10**.

(48) The four side seal packaging bag **10** prepared by the above preparation device and method includes at least the upper film material **11**, the lower film material **12**, and the two side accordion film materials **13** located between the upper film material **11** and the lower film material **12**. The zipper **14** is located above the side accordion film materials **13** between the upper film material **11** and the lower film material **12**. The triangle **130** structure is formed at a side of the side accordion film material **13** located at an opening of the packaging bag **10**. An overlap part between the triangle structure and an edge of the side accordion film material **13** is hot-pressed by spot heating, and the zipper **14** is located above the triangle **130** structure of the side accordion film material.

Embodiment 2

(49) FIGS. 1, 2, 4, 5, 7, and 8 illustrate another embodiment of the technical solution. The difference between this embodiment and Embodiment 1 is as follows.

(50) In terms of preparation device, the side accordion forming mechanism includes at least a seal strip 131 conveying mechanism and the hot-sealing mechanism 23. After the square punch-and-cut region 132 is separated, the seal strip 131 conveying mechanism feeds seal strip 131 to the side accordion film material 13 along a direction perpendicular to the conveying direction of the film material to cover the punch-and-cut edge B 1321. The hot-sealing mechanism 23 hot-presses the seal strip 131 against the side accordion film material 13.

(51) In terms of preparation method, the side accordion molding process in the step 6 includes at least the following steps. After the square punch-and-cut region 132 is separated, the seal strip 131 conveying mechanism feeds the seal strip 131 to the side accordion film material 13 along a direction perpendicular to the conveying direction of the film material to cover the punch-and-cut edge B 1321. The hot-sealing mechanism 23 hot-presses the seal strip 131 against the side accordion film material 13. The zipper 14 conveyed by the zipper 14 conveying mechanism is located in a zone of the lower film material 12 corresponding to the original square punch-and-cut region 132 and above the seal strip 131 hot-pressed by the side accordion forming mechanism.

(52) The four side seal packaging bag structure formed based on the above difference includes at least the upper film material 11, the lower film material 12, and the two side accordion film materials 13 located between the upper film material 11 and the lower film material 12. The zipper 14 is located above the side accordion film materials 13 between the upper film material 11 and the lower film material 12. The side accordion film material 13 is a square structure where the seal strip 131 structure is hot-pressed.

(53) It should be noted that unless otherwise defined, the technical and scientific terms used in the claims and the specification are as they are usually understood by those skilled in the art to which the present disclosure pertains. In the specification and claims of the present disclosure, terms such as “connected to” and “connected with” are not restricted to physical or mechanical connections, but may include direct and indirect electrical connections. Terms such as “upper”, “lower”, “end”, and “side”, are used only to indicate a relative positional relationship, and when the absolute position of the described object is changed, the relative positional relationship is also changed accordingly.

(54) Those skilled in the art may easily think of other implementation solutions of the present disclosure after considering the specification and practicing the content disclosed herein. The present application is intended to cover any variations, uses, or adaptive changes of the present disclosure. These variations, uses, or adaptive changes follow the general principles of the present disclosure and include common knowledge or conventional technical means in the technical field that are not disclosed by the present disclosure. The specification and the embodiments are to be regarded as examples only, and the true scope and spirit of the present disclosure are pointed out by the claims.

(55) It should be understood that the present disclosure is not limited to the precise structure that has been described above and shown in the accompanying drawings, and various modifications and changes can be made without departing from its scope. The scope of the present disclosure is defined only by the appended claims.

Claims

1. A preparation device of a four side seal packaging bag, comprising: a film material conveying mechanism, configured to continuously convey a film material of a packaging bag along a length direction of the film material; a folding mechanism, comprising folding guides, configured to fold the film material conveyed by the film material conveying mechanism to form an upper film

material, a lower film material, and two side accordion film materials of the packaging bag, wherein a structure of the four side seal packaging bag is formed; a cutting mechanism, configured to cut the upper film material formed by folding by the folding mechanism, along creases, to separate the upper film material from the lower film material and the side accordion film materials; punch-and-cut mechanisms, configured to form square punch-and-cut regions on the side accordion film materials separated from the upper film material and separate the square punch-and-cut regions from the side accordion film materials; a side accordion forming mechanism, configured to perform a further forming operation on the side accordion film materials after the square punch-and-cut regions are separated by the punch-and-cut mechanism; and a hot-sealing mechanism, configured to hot-seal the upper film material, the formed side accordion film materials, and the lower film material to form the four side seal packaging bag; wherein the punch-and-cut mechanisms each are provided with a punch-proof structure; the punch-proof structure is provided with a punch-proof pad and a punch-proof pad insertion structure; and the punch-proof pad is inserted between the side accordion film material and the lower film material through the punch-proof pad insertion structure, to prevent damage to the lower film material caused when the punch-and-cut mechanism punches and cuts off the square punch-and-cut region of the side accordion film material; the punch-and-cut mechanisms each are provided with a roll-to-cut structure; the roll-to-cut structure is provided with rolling cutters and a rolling cutter drive component; the rolling cutter drive component is connected to the rolling cutters to control roll-to-cut operation of the rolling cutters; the rolling cutters are located above the side accordion film material; and the rolling cutters roll-to-cut the side accordion film material in a direction perpendicular to a conveying direction of the side accordion film material to form punch-and-cut edges of the square punch-and-cut region; the punch-and-cut mechanisms each are provided with a punching structure; the punching structure is located downstream of the roll-to-cut structure and is provided with at least a punching head and a punching drive structure; and the punching head is configured to punch and cut off the square punch-and-cut region with the punch-and-cut edges through the punching drive structure, wherein the square punch-and-cut region is formed; and the punch-and-cut mechanisms each are provided with a gripping structure; the gripping structure is located downstream of the punching structure and is provided with a gripping end and a gripping end drive structure; and the gripping end is driven by the gripping end drive structure to grip the square punch-and-cut region punched and cut by the punching head.

2. The preparation device of the four side seal packaging bag according to claim 1, wherein the film material folded by the folding mechanism is a one-piece structure; and the folding mechanism is configured to: fold the film material at a side and a center line of the film material upwards along a conveying direction of the film material; fold the film material back to form two fold angles, wherein the side accordion film materials are formed; and fold, after two fold angles are formed at the center line, the folded-back film material upwards to cover upper sides of the two side accordion film materials, wherein the upper film material is formed, wherein an unfolded film material part at a bottom forms the lower film material.

3. The preparation device of the four side seal packaging bag according to claim 1, wherein there are at least two punch-and-cut mechanisms.

4. The preparation device of the four side seal packaging bag according to claim 1, wherein the punching head is a straight punching head; a length of the punching head is equal to a distance between the two punch-and-cut edges of the square punch-and-cut region; and during a punching operation, the punching head is located at a connection between the side accordion film material and a side edge of the lower film material, as well as above the side accordion film material.

5. The preparation device of the four side seal packaging bag according to claim 1, wherein the side accordion forming mechanism comprises an angle folding mechanism; and the angle folding mechanism is located at two sides of the conveying direction of the film material, and is configured to fold, after the square punch-and-cut region is separated, the side accordion film material along a

45° angle straight line of the punch-and-cut edge, wherein the punch-and-cut edge coincides with a side in a length direction of the side accordion after being folded and a right-angled triangle is formed at the side accordion film material; or the side accordion forming mechanism comprises at least a seal strip conveying mechanism and the hot-sealing mechanism; the seal strip conveying mechanism is configured to feed, after the square punch-and-cut region is separated, a seal strip to the side accordion film material along a direction perpendicular to the conveying direction of the film material to cover the punch-and-cut edge; and the hot-sealing mechanism is configured to hot-press the seal strip against the side accordion film material; and the side accordion forming mechanism is provided with either of the angle folding mechanism and the seal strip conveying mechanism.

6. The preparation device of the four side seal packaging bag according to claim 5, further comprising a zipper conveying mechanism for conveying a zipper to a position between the lower film material and the upper film material, wherein the zipper conveyed by the zipper conveying mechanism is located in a zone of the lower film material corresponding to the square punch-and-cut region and above the triangle formed by the side accordion forming mechanism or the hot-pressed seal strip.

7. The preparation device of the four side seal packaging bag according to claim 1, further comprising a guiding mechanism, wherein the guiding mechanism is located downstream of the cutting mechanism, and is configured to guide the upper film material cut by the cutting mechanism into another film material conveying mechanism for continuous conveyance in a same direction as the lower film material, and guide the upper film material to merge with the lower film material during final forming of the packaging bag.

8. A preparation method of a four side seal packaging bag, implemented by the preparation device of the four side seal packaging bag according to claim 1, and comprising the following steps: step 1: continuously conveying, by the film material conveying mechanism, the film material of the packaging bag along the length direction of the film material; step 2: folding, by the folding mechanism, the film material conveyed by the film material conveying mechanism to form the upper film material, the lower film material, and the two side accordion film materials, wherein the structure of the four side seal packaging bag is formed; step 3: cutting, by the cutting mechanism, the upper film material formed by folding by the folding mechanism along the creases, wherein the upper film material is separated from the lower film material and the side accordion film materials; step 4: guiding, by a guiding mechanism, the upper film material cut by the cutting mechanism into another film material conveying mechanism for continuous conveyance in the same direction as the lower film material; step 5: forming, by the punch-and-cut mechanisms, the square punch-and-cut regions on the side accordion film materials separated from the upper film material, and separating the square punch-and-cut regions from the side accordion film materials; step 6: performing, the further forming operation on the side accordion film materials after the square punch-and-cut regions are separated; step 7: guiding, by the guiding mechanism, the upper film material above the lower film material; and step 8: hot-sealing, by the hot-sealing mechanism, the upper film material, the formed side accordion film materials, and the lower film material to form the four side seal packaging bag.

9. The preparation method of the four side seal packaging bag according to claim 8, wherein in the step 5, the square punch-and-cut region is formed by at least: step 5a: when the side accordion film material enters a station for forming the square punch-and-cut region: inserting, by the punch-proof pad insertion structure of the punch-proof structure, the punch-proof pad between the side accordion film material and the lower film material to prevent the damage to the lower film material when the square punch-and-cut region of the side accordion film material is punched and cut off; step 5b: after the placement of the punch-proof pad is finished in the step 5a: starting the rolling cutter drive component of the roll-to-cut structure, and driving the rolling cutters to process the side accordion film material above the punch-proof pad, wherein the punch-and-cut edges of

the square punch-and-cut region are formed; step 5c: after the punch-and-cut edges are formed in the step 5b: conveying the side accordion film material to a punching station; driving, by the punching drive structure of the punching structure, the punching head to punch and cut off the square punch-and-cut region with the punch-and-cut edges, wherein the square punch-and-cut region is formed; and step 5d: after the square punch-and-cut region is punched and cut off in the step 5c: conveying the side accordion film material to a gripping station; driving, by the gripping end drive structure of the gripping structure, the gripping end to grip the punched and cut square punch-and-cut region to a waste disposal site for centralized recycling and processing.

10. The preparation method of the four side seal packaging bag according to claim 8, wherein in the step 6, the further forming of the side accordion comprises at least: folding, after the square punch-and-cut region is separated, the side accordion film material along a 45° angle straight line of the punch-and-cut edge, wherein the punch-and-cut edge coincides with a side in a length direction of the side accordion after being folded and a triangle is formed at one end of the side accordion film material; or in the step 6, the further forming of the side accordion comprises at least: feeding, by a seal strip conveying mechanism after the square punch-and-cut region is separated, a seal strip to the side accordion film material along a direction perpendicular to the conveying direction of the film material to cover the punch-and-cut edge; and hot-pressing, by the hot-sealing mechanism, the seal strip against the side accordion film material; wherein either of the angle folding step and the seal strip conveying step is performed.

11. The preparation method of the four side seal packaging bag according to claim 8, wherein before guiding the upper film material to merge with the lower film material in the step 7 after the forming of the side accordion film material in the step 6, the preparation method further comprises a zipper mounting step: conveying, by a zipper conveying mechanism, the zipper to the lower film material.

12. The preparation method according to claim 8, wherein in the preparation device, the film material folded by the folding mechanism is a one-piece structure; and the folding mechanism is configured to: fold the film material at a side and a center line of the film material upwards along a conveying direction of the film material; fold the film material back to form two fold angles, wherein the side accordion film materials are formed; and fold, after two fold angles are formed at the center line, the folded-back film material upwards to cover upper sides of the two side accordion film materials, wherein the upper film material is formed, wherein an unfolded film material part at a bottom forms the lower film material.

13. The preparation method according to claim 8, wherein in the preparation device, there are at least two punch-and-cut mechanisms.

14. The preparation method according to claim 8, wherein in the preparation device, the punching head is a straight punching head; a length of the punching head is equal to a distance between the two punch-and-cut edges of the square punch-and-cut region; and during a punching operation, the punching head is located at a connection between the side accordion film material and a side edge of the lower film material, as well as above the side accordion film material.

15. The preparation method according to claim 8, wherein in the preparation device, the side accordion forming mechanism comprises an angle folding mechanism; and the angle folding mechanism is located at two sides of the conveying direction of the film material, and is configured to fold, after the square punch-and-cut region is separated, the side accordion film material along a 45° angle straight line of the punch-and-cut edge, wherein the punch-and-cut edge coincides with a side in a length direction of the side accordion after being folded and a right-angled triangle is formed at the side accordion film material; or the side accordion forming mechanism comprises at least a seal strip conveying mechanism and the hot-sealing mechanism; the seal strip conveying mechanism is configured to feed, after the square punch-and-cut region is separated, a seal strip to the side accordion film material along a direction perpendicular to the conveying direction of the film material to cover the punch-and-cut edge; and the hot-sealing mechanism is configured to hot-

press the seal strip against the side accordion film material; and the side accordion forming mechanism is provided with either of the angle folding mechanism and the seal strip conveying mechanism.

16. The preparation method according to claim 15, wherein the preparation device further comprises a zipper conveying mechanism for conveying a zipper to a position between the lower film material and the upper film material, wherein the zipper conveyed by the zipper conveying mechanism is located in a zone of the lower film material corresponding to the original-square punch-and-cut region and above the triangle formed by the side accordion forming mechanism or the hot-pressed seal strip.

17. The preparation method according to claim 8, wherein the preparation device further comprises the guiding mechanism, wherein the guiding mechanism is located downstream of the cutting mechanism, and is configured to guide the upper film material cut by the cutting mechanism into another film material conveying mechanism for the continuous conveyance in the same direction as the lower film material, and guide the upper film material to merge with the lower film material during final forming of the packaging bag.
