

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416113
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Lee; Kilryong et al.

Lifter for laundry treating apparatus

Abstract

A lifter for a laundry treating apparatus includes a first member mounted at an inner side of a drum; and a second member mounted on the first member and protruded toward an inside of the drum, wherein the first member includes a hook protruded and formed along a circumference of the first member, at least part of which is disposed to cover an inner circumferential surface of the drum when inserted into a fastening hole of the drum and then slid in one direction; and a shield protruded and formed at an inner side of the first member and configured to completely cover the fastening hole when the hook is inserted into the fastening hole and then slid in one direction.

Inventors: Lee; Kilryong (Seoul, KR), Jeon; Byeongha (Seoul, KR), Ahn; Jinseok (Seoul, KR)

Applicant: LG ELECTRONICS INC. (Seoul, KR)

Family ID: 1000008819130

Assignee: LG ELECTRONICS INC. (Seoul, KR)

Appl. No.: 18/629108

Filed: April 08, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240254675 A1	Aug. 01, 2024

Foreign Application Priority Data

KR	10-2016-0001209	Jan. 05, 2016
----	-----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: D06F37/06 (20060101); D06F37/04 (20060101)

U.S. Cl.:

CPC D06F37/065 (20130101); D06F37/06 (20130101); D06F37/04 (20130101)

Field of Classification Search

CPC: D06F (37/06); D06F (37/065)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1389182	12/1920	Binder	N/A	N/A
7827830	12/2009	Kim	N/A	N/A
2004/0129036	12/2003	Ratfisch	N/A	N/A
2005/0022565	12/2004	Jung et al.	N/A	N/A
2005/0097927	12/2004	Kim et al.	N/A	N/A
2005/0252253	12/2004	Ahn	N/A	N/A
2007/0017259	12/2006	Cho et al.	N/A	N/A
2008/0282747	12/2007	Kim	N/A	N/A
2009/0071202	12/2008	Lee et al.	N/A	N/A
2009/0120139	12/2008	Bobed	N/A	N/A
2012/0180532	12/2011	Park	N/A	N/A
2013/0081432	12/2012	Choi et al.	N/A	N/A
2014/0137425	12/2013	Kim et al.	N/A	N/A
2014/0366587	12/2013	Kegler	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1414163	12/2002	CN	N/A
1779032	12/2005	CN	N/A
1906349	12/2006	CN	N/A
101161907	12/2007	CN	N/A
201065483	12/2007	CN	N/A
101316959	12/2007	CN	N/A
101451297	12/2008	CN	N/A
101668891	12/2009	CN	N/A
202509279	12/2011	CN	N/A
103031694	12/2012	CN	N/A
103114418	12/2012	CN	N/A
104131438	12/2013	CN	N/A
1 958 076	12/1970	DE	N/A

1585867	12/1970	DE	N/A
2 310 435	12/1973	DE	N/A
3317201	12/1983	DE	N/A
36 42 459	12/1987	DE	N/A
10 2008 018 044	12/2007	DE	N/A
0 351 671	12/1989	EP	N/A
1 306 479	12/2002	EP	N/A
2053152	12/2008	EP	N/A
1849904	12/2008	EP	N/A
S54-152333	12/1978	JP	N/A
H06-152174	12/1993	JP	N/A
2003-126595	12/2002	JP	N/A
2010-526637	12/2009	JP	N/A
2019-50100	12/2018	JP	N/A
20-0358903	12/2003	KR	N/A
10-2004-0093601	12/2003	KR	N/A
10-0465724	12/2004	KR	N/A
10-0627908	12/2005	KR	N/A
10-2006-0127370	12/2005	KR	N/A
10-2007-0002284	12/2006	KR	N/A
10-0713946	12/2006	KR	N/A
10-0802467	12/2007	KR	N/A
10-0808204	12/2007	KR	N/A
10-1041802	12/2010	KR	N/A
10-2011-0088352	12/2010	KR	N/A
10-1208494	12/2011	KR	N/A
10-2013-0034911	12/2012	KR	N/A
10-2014-0084947	12/2013	KR	N/A
10-2014-0084951	12/2013	KR	N/A
10-1520610	12/2014	KR	N/A
10-2018-0135831	12/2017	KR	N/A
WO 2007/124804	12/2006	WO	N/A
WO 2008/140169	12/2007	WO	N/A

OTHER PUBLICATIONS

International Search Report dated Jan. 12, 2017 issued in Application No. PCT/KR2016/012808.
cited by applicant

European Search Report Dated May 24, 2017 issued in Application No. 17150288.3. cited by
applicant

European Search Report dated Aug. 30, 2017 issued in Application No. 17150288.3. cited by
applicant

Chinese Office Action (with English translation) dated Aug. 28, 2018 issued in CN Application No.
201710006431.2. cited by applicant

Chinese Office Action (with English translation) dated Apr. 22, 2019 issued in CN Application No.
201710006431.2. cited by applicant

European Search Report dated Oct. 24, 2019 issued in EP Application No. 19185629.3. cited by
applicant

Japanese Office Action (with English translation) dated Nov. 24, 2020 issued in JP Application No.
2018-554292. cited by applicant

Korean Office Action (with English translation) dated Dec. 1, 2020 issued in KR Application No.

10-2018-0160269. cited by applicant
Korean Office Action (with English translation) dated Dec. 1, 2020 issued in KR Application No. 10-2018-0160270. cited by applicant
Korean Office Action (with English translation) dated Dec. 1, 2020 issued in KR Application No. 10-2018-0160273. cited by applicant
Korean Office Action (with English translation) dated Dec. 1, 2020 issued in KR Application No. 10-2019-0068830. cited by applicant
Japanese Office Action dated Feb. 2, 2021 issued in JP Application No. 2019-091911. cited by applicant
Japanese Office Action dated Feb. 2, 2021 issued in JP Application No. 2019-091915. cited by applicant
Japanese Office Action dated Feb. 2, 2021 issued in JP Application No. 2019-091916. cited by applicant
Japanese Office Action dated Mar. 30, 2021 issued in JP Application No. 2020-060118. cited by applicant
Chinese Office Action dated Apr. 6, 2021 issued in CN Application No. 201911258571.4. cited by applicant
Chinese Office Action dated Apr. 6, 2021 issued in CN Application No. 201911258542.8. cited by applicant
United States Office Action dated Jun. 24, 2021 issued in U.S. Appl. No. 16/422,573. cited by applicant
Chinese Office Action dated Jul. 28, 2021 issued in CN Application No. 201911267126.4. cited by applicant
Japanese Office Action dated Aug. 23, 2021 issued in JP Application No. 2018-554292. cited by applicant
Chinese Office Action dated Sep. 15, 2021 issued in CN Application No. 201911259744.4. cited by applicant
U.S. Final Office Action dated Oct. 7, 2021 issued in U.S. Appl. No. 16/422,724. cited by applicant
United States Office Action dated Dec. 15, 2021 issued in co-pending related U.S. Appl. No. 16/422,573. cited by applicant
Chinese Office Action dated Jan. 27, 2022 issued in CN Application No. 201911267126.4. cited by applicant
Chinese Office Action dated Jul. 20, 2022 issued in Application No. 201911267532.0. cited by applicant
Chinese Notice of Allowance dated Dec. 5, 2022 issued in Application No. 201911259744.4. cited by applicant
U.S. Office Action dated Mar. 31, 2022 issued in U.S. Appl. No. 16/811,486. cited by applicant
U.S. Office Action dated Mar. 3, 2023 issued in U.S. Appl. No. 16/811,486. cited by applicant
U.S. Office Action dated Sep. 6, 2023 issued in U.S. Appl. No. 16/811,486. cited by applicant
Machine translation of KR-100802467-B1, dated Feb. 2008. (Year: 2008). cited by applicant
Machine translation of DE 3642459 A1, dated Jun. 1988. (Year: 1988). cited by applicant

Primary Examiner: Barr; Michael E

Assistant Examiner: Lee; Kevin G

Attorney, Agent or Firm: KED & ASSOCIATES, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This is a Continuation Application of U.S. application Ser. No. 16/811,486, filed on Mar. 6, 2020, which is a Continuation Application of U.S. application Ser. No. 15/398,921, filed on Jan. 5, 2017, now U.S. Pat. No. 10,633,779, issued on Apr. 28, 2020, which, pursuant to 35 U.S.C. § 119(a), claims the benefit of the earlier filing date and the right of priority to Korean Application No. 10-2016-0001209, filed on Jan. 5, 2016, the contents of each of which is incorporated by reference herein in its entirety.

BACKGROUND

1. Field

(1) The present disclosure relates to a lifter used for a laundry treating apparatus.

2. Background

(2) A laundry treating apparatus may allow clothes, bedding, and the like (hereinafter, referred to as laundry) to be placed into a drum to remove contamination on laundry. The laundry treating apparatus may perform the processes of washing, rinsing, dehydration, drying and the like. The laundry treating apparatus may be divided into a top loading type and a front loading type based on the method by which laundry is placed into the drum. A front loading type washing machine may be referred to as a drum washing machine.

(3) The laundry treating apparatus may be typically configured to include a body that forms an external appearance, a tub accommodated into the body, a drum rotatably mounted within the tub to accept laundry thereinto, and a detergent supply apparatus configured to supply detergent into the drum. When the drum is rotated by a motor in a state that washing water is supplied to laundry accommodated into the drum, dirt on the laundry may be removed by a friction between the drum and the washing water.

(4) A lifter configured to help the washing of laundry by the rise and fall of the laundry during the rotation of the drum may be located on an inner circumferential surface of the washer drum. The lifter may help the washing of laundry while lifting up and then dropping the laundry as the drum rotates after putting detergent, washing water and laundry into the drum. The lifter may be located within the drum to prevent the damage of laundry, reduce water usage, and cause knocking, rubbing, and washing of the laundry. The lifter may be attached to an inner circumferential surface of the drum to accommodate water into an inner space of the lifter and then perform the role of spraying water to laundry within the drum.

(5) A lifter in the related art may be typically coupled to the drum through an additional fastening member, thereby causing a performance deterioration of the lifter due to a defect or failure of the fastening member. Furthermore, water introduced into the lifter may be distributed through a fastening portion between the drum and the lifter, thereby causing unnecessary discharge of washing water.

(6) Consequently, it may be required to have a lifter with a structure capable of preventing water accommodated into the lifter from being discharged through a coupling portion between the drum and the lifter as well as not causing the performance deterioration of the lifter due to a coupling between the drum and the lifter. The above references are incorporated by reference herein where appropriate for appropriate teachings of additional or alternative details, features and/or technical background.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The embodiments will be described in detail with reference to the following drawings in which

like reference numerals refer to like elements wherein:

- (2) FIG. 1 is a perspective view illustrating the entire structure of a laundry treating apparatus;
- (3) FIG. 2 is a perspective view illustrating a lifter attached to an inner circumferential surface of a drum;
- (4) FIG. 3 is an exploded view illustrating the internal structure of a drum including the drum and a lifter attached to the drum;
- (5) FIG. 4 is a perspective view in which the lifter is seen from an inside of the drum;
- (6) FIG. 5 is an exploded view illustrating the entire structure of the lifter;
- (7) FIG. 6 is a perspective view illustrating a first member constituting the lifter;
- (8) FIG. 7 shows views illustrating a shape in which a protruding portion of a second member is inserted into a mounting hole of the first member (shown on top with label (a)); a shape in which a protruding portion of a second member is inserted and coupled to a mounting hole of the first member (shown in the middle with label (b)); and a shape in which a protruding portion of a second member is inserted into a mounting hole of the first member and then bent (shown on bottom with label (c));
- (9) FIG. 8 illustrates a shape in which the lifter is coupled to the drum;
- (10) FIG. 9 shows views illustrating a shape in which a hook portion of the first member is inserted into a fastening hole of the drum (shown on top left with label (a)); a shape in which the hook portion is slid (shown on top right with label (b)); a shape in which the hook portion is slid and then coupled to the drum (shown in the middle with label (c)); and a shape in which the lifter is coupled to an inner circumferential surface of the drum is seen from an outside of the drum (shown on bottom with label (d));
- (11) FIG. 10 illustrates a shape in which the lifter is coupled to an inner circumferential surface of the drum and its enlarged shape;
- (12) FIG. 11 is a view in which the drum is seen from a front side of the body; and
- (13) FIG. 12 illustrates a shape in which washing water is introduced into the lifter and then discharged into the drum through a washing water discharge hole.

DETAILED DESCRIPTION

- (14) Referring to FIG. 1, the laundry treating apparatus may include a laundry treating apparatus body **11** configured to form an appearance, a drum **20** rotatably mounted within the body **11** to put laundry therein, a lifter **100** provided within the drum **20**, a door **12** provided on a front surface of the body **11**, and a detergent inlet cover **13** covering a detergent inlet for adding detergent located at a lower portion of the body **11**. Furthermore, the laundry treating apparatus may include a duct, a heat exchanger, and the like therein to circulate air to dry laundry within the drum.
- (15) The lifter **100** may be provided on an inner circumferential surface **22** of the drum **20** to help the washing of laundry due to the rise and fall of the laundry during the rotation of the drum **20**. The lifter **100** may help the washing of laundry while lifting up and then dropping the laundry as the drum **20** rotates after putting detergent, washing water, and laundry into the drum **20**. The lifter **100** may prevent laundry within the drum **20** from getting tangled to prevent the damage of laundry, reduce water usage, and cause knocking, rubbing, and washing of the laundry.
- (16) Referring to FIG. 2, the lifter **100** may extend along a direction parallel to a rotational axis of the drum, and may be provided along an inner circumferential surface **22** of a drum body **21**. A plurality of lifters **100** may be typically provided on the inner circumferential surface **22** of the drum, but when the lifters **100** are asymmetrically provided based on a rotational axis of the drum, vibration and noise may occur as the drum rotates, and thus the plurality of lifters **100** may be preferably provided at predetermined angles around the rotational axis of the drum.
- (17) Referring to FIG. 3, the drum may include a front drum member **26**, the drum body **21**, the lifter **100**, a rear drum member **27**, a balancer **25a**, **25b**, and a spider **28**, and when those members are sequentially coupled as illustrated in FIG. 3, they have a shape of drum in FIG. 2. Considering the role of each member constituting the drum disclosed in FIG. 3, the balancer **25a**, **25b** may

suppress vibration as the drum rotates, and the spider **28** may provide a rotational force of the drum. The lifter **100** may lift up and then drop laundry within the drum as disclosed above, thereby enhancing washing performance through a fall head.

(18) As illustrated in FIG. 4, the lifter **100** may be formed by coupling a first member (or lifter base or base) **110** to a second member (or lifter top or cover) **120**, and the second member **120** may be located on the first member **110**. The lifter **100** may have a streamlined or S-shape, and have a nonlinear structure twisted by a predetermined angle. Through this, washing water within the drum may more efficiently flow by the lifter **100** as the drum rotates.

(19) First, the first member **110** will be considered through a lower end portion of FIG. 5 and FIG. 6. An upper surface of the first member **110** is illustrated at a lower portion of FIG. 5, and a lower surface of the first member **110** is illustrated in FIG. 6.

(20) The first member **110** may include a body **111**, a hook portion (or hook) **112**, a shielding portion (or shield) **113**, a mounting hole (or hole) **117**, a washing water inlet hole (or inlet) **115a**, and a screw insertion hole (or boss) **119**.

(21) The body **111** of the first member may form an entire structure of the first member **110**, and may extend in a direction in parallel to a rotational axis of the drum. The body **111** may also be provided on an inner circumferential surface **22** of the drum in parallel to the rotational axis of the drum.

(22) The first member **110** may include a washing water inlet portion (or washing water inlet) **115**. The washing water inlet portion **115** may include a hole through the first member **110** to introduce washing water into the lifter **100**. The washing water inlet portion **115** may overlap with part of a hole formed on the drum.

(23) The washing water inlet portion **115** may include a plurality of washing water inlet holes **115a**. As illustrated in FIG. 5, the washing water inlet holes **115a** may be separated from one another in a direction in parallel to a rotational axis of the washer drum, and may pass through the first member **110**. Washing water may be introduced into the drum from a tub as the drum rotates during the washing process of the laundry treating apparatus, and the washing water introduced through holes formed on the drum may be introduced into the lifter **100** through the washing water inlet holes **115a**, respectively, overlapping with the holes formed on the drum.

(24) The screw insertion hole (or boss) **119** may be formed at one side of the first member **110** to be affixed to the drum. The first member **110** may be fixed to an inner surface of the drum through the screw insertion hole **119** by screw fastening. The screw insertion holes **119** may be formed at both ends of the first member **110** as illustrated in FIG. 5, and the plurality of screw insertion holes **119** may be located between the washing water inlet holes **115a** of the first member **110**. The screw insertion hole **119** may have a typical shape into which a screw may be inserted.

(25) Looking at a rear surface of the first member **110**, the first member **110** may include a mounting hole **117**, a hook portion **112** and a shielding portion **113**. The mounting hole **117** may couple the first member **110** to the second member **120**, and a protruding portion (or tab) **123** of the second member **120** may be inserted into the mounting hole **117**, thereby coupling the first member **110** to the second member **120**.

(26) Referring to FIG. 7, the mounting hole **117** may be formed along a circumference of the first member **110**, and may have a corresponding shape to allow the protruding portion **123** of the second member **120** to be inserted therein. The mounting holes **117** may be located at a plurality of positions along a circumference of the first member **110**.

(27) The hook portion **112** may protrude and be formed along a circumference of a lower surface of the first member **110** to fix the first member **110** to the drum. The hook portion **112** may have a shape of a ring portion to support one side of the drum when inserted and then may be slid as illustrated in FIG. 6.

(28) The hook portion **112** may be inserted into a fastening hole located on the drum, and then slid and fixed to the drum to support one side of the drum. A plurality of hook portions **112** may be

located along a circumference of the first member **110** as illustrated in FIG. 6, and located to face each other. The hook portion **112** may be bent toward a central portion of the first member **110**. The hook portion **112** may be inserted into a fastening hole **24** of the drum and then slid in one direction, and at least part of the hook portion **112** may cover the inner circumferential surface **22** of the drum.

(29) The shielding portion **113** may protrude from and be formed at an inner side of the first member **110** to cover a portion of the fastening hole. The shielding portion **113** may completely cover the fastening hole when the hook portion **112** is inserted into the fastening hole and then slid in one direction. The shielding portion **113** may be formed at a first lateral side of the first member **110** to correspond to a rotational direction of the drum to prevent washing water from being discharged through the fastening hole **24** of the drum. A plurality of shielding portions **113** may be separated from one another along the first lateral side circumference portion of the first member **110** in a direction of extending the first member **110**.

(30) A centrifugal force may be generated as the drum rotates, and the shielding portion **113** covering the fastening hole may be located relatively far away based on a rotational direction of the drum. Thus, washing water accommodated in the lifter **100** may not be discharged despite rotation of the drum. In other words, as illustrated in FIG. 6, the shielding portion **113** may be formed only in one direction based on a major axis passing through a center of the first member **110** having an elliptical shape.

(31) The hook portion **112** protruding from and formed at an inner side of the first member **110** inserted into the fastening hole and slid in one direction to cover only part of the fastening hole **24** of the drum may be formed at a second lateral side of the first member **110** at which the shielding portion **113** is not located. As illustrated in FIG. 6, the shielding portion **113** may not be formed at the second lateral side based on the major axis of the first member **110**. Accordingly, part of washing water may be introduced into the lifter **100** through a portion of the fastening hole **24** of the drum. The first member **110** may be formed of synthetic resin, and for example, the first member **110** may be formed of injected plastic. However, the present disclosure may not be necessarily limited to that material.

(32) Considering the second member **120** through FIG. 5, the second member **120** may include a body **121**, the protruding portion **123** and a washing water discharge hole **125**. The body **121** of the second member **120** may protrude from and be formed at an inside of the drum to accommodate washing water in an inner space. The body **121** of the second member **120** may have a nonlinear shape.

(33) A plurality of protruding portions **123** may be formed along a lower circumference of the body **121**. The protruding portion **123** of the second member **120** may be inserted into the mounting hole **117** formed along a circumference of the first member **110**, and thus the first member **110** may be coupled to the second member **120**. As illustrated in FIG. 5, the protruding portion **123** may be formed at a lower portion of the body **121** of the second member **120**, and extend toward a lower portion from an upper portion.

(34) The washing water discharge hole **125** may be located at an upper portion of the body **121** to discharge washing water accommodated in the body **121** of the second member **120** from an outside of the drum, and formed in one direction. Specifically, an upper surface **122** of the second member body **121** extended along one direction may be located at an upper portion of the body **121** of the second member **120**, and a plurality of washing water discharge holes **125** are formed on the upper surface **122** of the body **121** of the second member **120**. Washing water accommodated in the lifter **100** may be discharged toward the drum through the washing water discharge holes **125** to help wash the laundry accommodated within the drum. Furthermore, water usage during the washing process may be reduced by supplying water into the drum through the lifter **100**.

(35) As illustrated in FIG. 7, part (a), the protruding portion **123** of the second member **120** may be inserted into the mounting hole **117** of the first member **110**, and a plurality of protruding portions

123 formed on the second member **120** may be inserted into a plurality of mounting holes **117** formed on the first member **110** at the corresponding positions, thereby coupling the first member **110** to the second member **120**. As illustrated in FIG. 7, part (b), the protruding portion **123** of the second member **120** may be inserted into the mounting hole **117** of the first member **110** such that the first member **110** is located at an upper portion of the lifter and the second member **120** is located at a lower portion of the lifter. Moreover, the protruding portion **123** of the second member **120** may be inserted into the mounting hole **117** of the first member **110** and protruded upward. (36) As illustrated in FIG. 7, part (c), the protruding portion **123** of the second member **120** inserted into the mounting hole **117** of the first member **110** may be bent to be fixed. The protruding portion **123** of the second member **120** inserted into the mounting hole **117** of the first member **110** and protruded upward may be bent to be coupled between the first member **110** and the second member **120**. The protruding portion **123** may be bent in an inward direction of the first member **110**. In other words, the protruding portion **123** of the second member **120** may be inserted and then bent to the mounting hole **117** of the first member **110**, thereby coupling the first member **110** to the second member **120**.

(37) As illustrated in FIG. 8, a plurality of fastening holes (or coupling holes) **24** to fix the lifter **100** may be located on the drum, and the hook portion **112** of the first member **110** of the lifter **100** may be inserted into the fastening hole **24** of the drum and then slid. A screw may then be fastened to the screw insertion hole **119** located at upper and lower portions of the first member of the lifter **100**, thereby fixing the lifter **100** to the drum.

(38) Referring to FIG. 9, part (a), the hook portion **112** of the first member **110** may be inserted into the fastening hole **24** of the drum. The hook portion **112** of the first member **110** may be inserted into the fastening hole **24** of the drum to fix the lifter **100** to the drum.

(39) Referring to FIG. 9, part (b), the hook portion **112** may be slid. The hook portion **112** of the first member **110** may be inserted into the fastening hole **24** of the drum, and then slid along an arrow direction on the drawing. The hook portion **112** may have a shape of a ring portion to support one side of the drum, and the hook portion **112** may be slid to support one side of the drum and thus be more closely fixed to the drum.

(40) Referring to FIG. 9, part (c), the hook portion **112** may be slid and then coupled to the drum. As illustrated in the drawing, the hook portion **112** may support the drum body **21**. Specifically, the hook portion **112** of the first member **110** may cover at least part of outer and inner circumferential surfaces of the drum.

(41) Referring to FIG. 9, part (d), a shape in which the lifter **100** is coupled to an inner circumferential surface **22** of the drum is seen from an outside of the drum. As illustrated in the drawing, part of the drum body **21** may be supported by each hook portion **112** located on the first member **110**, and the shielding portion **113** of the first member **110** is may cover on a fastening hole on the left. The drum body **21** may be fixed to the screw insertion hole **119** located on the first member **110** by screw fastening, thereby locating the lifter **100** on an inner circumferential surface of the drum.

(42) Referring to FIG. 10, the lifter **100** and the drum may be coupled to each other via the hook portion **112** of the first member **110** and screw fastening. The hook portion **112** of the first member **110** may support part of the inner circumferential surface **22** and outer circumferential surface of the drum, and may be coupled to the drum by inserting a screw into the screw insertion hole **119** of the first member **110**.

(43) When each hook portion **112** of the first member **110** is inserted into each fastening hole of the drum and then slid, the shielding portion **113** of the first member **110** may cover the fastening hole **24** of the drum. The shielding portion **113** may completely cover the fastening hole when the hook portion **112** is inserted into the fastening hole and then slid in one direction, thereby preventing washing water from being discharged. The first member **110** having an elliptical shape has a major axis, and the fastening hole may be completely covered through the shielding portion **113** of the

first member **110** on the left based on the major axis.

(44) Looking at an enlarged view on the left in FIG. **10**, the shielding portion **113** may be located at a lower end of the hook portion **112** to cover the fastening hole **24** of the drum. The shielding portion **113** may protrude from and be formed toward an inner side of the first member **110** along one side circumference of the first member **110**, and the shielding portion **113** may completely cover a corresponding fastening hole **24** of the drum to thereby prevent washing water introduced into the lifter **100** through an opposing fastening hole **24** of the drum from being discharged to an outside of the lifter **100**.

(45) Looking at an enlarged view on the right in FIG. **10**, part of the fastening hole **24** of the drum may be exposed on the right based on the major axis of the first member **110**. The shielding portion **113** may not be formed on the right based on the major axis passing through a center of the first member **110**, and thus a portion of the fastening hole may be exposed to an outside at a side on which the shielding portion **113** is not formed, thereby introducing part of washing water into the lifter **100** through that portion. For washing water flowing along an arrow direction of FIG. **10**, the washing water inlet hole **115a** and the shielding portion **113**, formed to overlap with the fastening hole **24** of the drum, may not be located, and thus part of the washing water may be introduced into the lifter **100** through part of the fastening hole exposed to an outside of the lifter **100**.

(46) Referring to FIG. **11**, when the drum rotates, washing water may be introduced into the drum from a tub surrounding the drum. The washing water may be partly accommodated even in the lifter **100** attached to the inner circumferential surface **22** of the drum, and may pass through a hole of the drum and be discharged into the drum through the washing water discharge hole **125** of the second member **120** through the washing water inlet hole **115a** of the first member **110** overlapping with the hole of the drum. Alternatively, part of the washing water may be introduced into the lifter **100** even through the fastening hole on which the shielding portion **113** is not located. An arrow in FIG. **11** indicates a moving direction of washing water.

(47) Referring to FIG. **12**, a plurality of lifters **100** may be provided along the inner circumferential surface **22** of the drum. Unless the lifters **100** are not symmetrically arranged based on a rotational axis of the drum, there is a concern that noise and vibration may occur as the drum rotates, and laundry may not be uniformly lifted up and thus washing may not be uniformly carried out on the entire laundry. Accordingly, a plurality of lifters **100** may be symmetrically located based on the rotational axis of the drum as illustrated in FIG. **12**. Laundry within the drum may be caught in the lifters **100** to be effectively lifted up to a predetermined height, and washing water within the drum may more efficiently flow to enhance a washing effect.

(48) The configurations and methods according to the above-described embodiments will not be limited to the foregoing lifter **100** for a laundry treating apparatus, and configured to make various modifications thereto. An object of the present disclosure is to propose a lifter having a structure capable of being attached to an inner surface of a drum.

(49) Another object of the present disclosure is to propose a lifter having a structure capable of being firmly coupled to an inner surface of a drum. Still another object of the present disclosure is to propose a lifter having a structure capable of reducing washing water accommodated therein from being discharged through a fastening portion between a drum and a lifter.

(50) A lifter for a laundry treating apparatus according to an embodiment of the present disclosure may include a first member mounted at an inner side of a drum; and a second member mounted on the first member and protruded toward an inside of the drum, wherein the first member includes a hook portion protruded and formed along a circumference of the first member, at least part of which is disposed to cover an inner circumferential surface of the drum when inserted into a fastening hole of the drum and then slid in one direction; and a shielding portion protruded and formed at an inner side of the first member and configured to completely cover the fastening hole when the hook portion is inserted into the fastening hole and then slid in one direction. The shielding portion may be formed at one side of the first member to correspond to a rotational

direction of the drum to prevent washing water from being discharged through the fastening hole.

(51) A plurality of shielding portions may be disposed to be separated from one another along one side circumference of the first member. The other side of the first member may protrude from and be formed at an inner side of the first member and configured to cover only part of the fastening hole when the hook portion is inserted into the fastening hole and then slid in one direction so as to allow the introduction of washing water.

(52) The first member may include a washing water inlet portion formed to overlap with part of a hole formed on the drum to introduce washing water. The washing water inlet portion may include a plurality of washing water inlet holes disposed to be separated from one another along a direction in parallel to a rotational axis of the washer drum.

(53) A lifter for a laundry treating apparatus according to an example associated with the present disclosure may include a first member mounted at an inner side of a drum; and a second member mounted on the first member and protruded toward an inside of the drum, wherein the second member includes a body protruded toward an inside of the drum to accommodate washing water therein; and a plurality of protrusion portions located along a lower circumference of the body. Furthermore, a plurality of mounting holes into which protrusion portions of the second member are inserted to be coupled to the second member may be formed on the first member along a lower circumference.

(54) A protruding portion of the second member may be inserted into a mounting hole of the first member and the protruding portion may be bent to couple the first member to the second member. The second member may include a plurality of washing water discharge holes located at an upper portion of the body and formed along one direction to discharge washing water accommodated in the body from an outside of the drum.

(55) A screw insertion hole may be formed at one side of the first member to fix the first member to an inner surface of the drum with screw fastening. The first member may be formed of stainless steel, and the second member may be formed of plastic.

(56) A laundry treating apparatus according to the present disclosure may be inserted into a fastening hole of the drum through a hook portion to support an inner circumferential surface of the drum to be coupled to the drum, thereby preventing performance deterioration due to coupling to the drum. A laundry treating apparatus according to the present disclosure may prevent washing water accommodated within the lifter from being discharged to an outside by the shielding portion formed on the first member even when the drum rotates during the washing process, and thus prevent the unnecessary discharge of washing water and discharge the washing water through the washing water discharge hole, thereby maintaining the performance of the lifter.

(57) Hereinafter, a lifter for a laundry treating apparatus associated with the present disclosure will be described in more detail with reference to the accompanying drawings. Even in different embodiments according to the present disclosure, the same or similar reference numerals are designated to the same or similar configurations, and the description thereof will be substituted by the earlier description. Unless clearly used otherwise, expressions in the singular number used in the present disclosure may include a plural meaning.

(58) Any reference in this specification to “one embodiment,” “an embodiment,” “example embodiment,” etc., means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. The appearances of such phrases in various places in the specification are not necessarily all referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with any embodiment, it is submitted that it is within the purview of one skilled in the art to effect such feature, structure, or characteristic in connection with other ones of the embodiments.

(59) Although embodiments have been described with reference to a number of illustrative embodiments thereof, it should be understood that numerous other modifications and embodiments

can be devised by those skilled in the art that will fall within the spirit and scope of the principles of this disclosure. More particularly, various variations and modifications are possible in the component parts and/or arrangements of the subject combination arrangement within the scope of the disclosure, the drawings and the appended claims. In addition to variations and modifications in the component parts and/or arrangements, alternative uses will also be apparent to those skilled in the art.

Claims

1. A laundry treating apparatus including a lifter comprising: a base including a first side which is configured to be coupled to an inner circumferential surface of a drum, and a second side with an inner portion and an outer portion protruding to an inside of the drum from the first side; and a cover coupled to the second side of the base and configured to protrude away to the inside of the drum, and including an inner space to receive the inner portion of the second side of the base; wherein the inner portion and the outer portion of the second side are spaced apart from each other to form a coupling groove there between along an entire circumference of the second side, and a circumference of a lower portion of the cover is configured to fit into the coupling groove; wherein the cover includes a plurality of tabs protruded along the circumference of the lower portion, and wherein each of the plurality of tabs is configured to be inserted into a corresponding one of the plurality of holes and then bent to couple the base to the cover.
 2. The laundry treating apparatus of claim 1, wherein the base includes a hook at the first side of the base and that protrudes toward the inner circumferential surface of the drum, and wherein the hook is configured to be inserted into a hole provided in the inner circumferential surface of the drum to mount the base to the inner circumferential surface of the drum.
 3. The laundry treating apparatus of claim 1, wherein the base includes a first opening through the first side and the second side such that water is configured to pass through the opening and get into the inner space.
 4. The laundry treating apparatus of claim 3, wherein the cover includes a second opening formed on an upper surface of the cover.
 5. The laundry treating apparatus of claim 1, wherein a part of the inner portion of the second side of the base extends along an interior side surface of the circumference of the lower portion of the cover.
 6. The laundry treating apparatus of claim 5, wherein the inner portion of the second side extends into the inner space of the cover and contacts to the interior side surface of the circumference of the lower portion of the cover.
 7. The laundry treating apparatus of claim 1, wherein the outer portion of the second side of the base is positioned between the inner circumferential surface of the drum and an upper portion of the cover such that an entirety of the outer portion of the second side of the base is exposed below the upper portion of the cover.
-