

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416185
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Guma; Jarrett et al.

Multifunction hub core for mortise lock and method of assembly

Abstract

A multifunction hub core for a mortise lock comprises a mortise lock body having a deadbolt operable by a first control member on the outside of a door and a second control member on the inside of the door, and a deadbolt arm with slots for receiving a hub core. The deadbolt arm is rotatable inside the mortise lock body to move the deadbolt between retracted and projected positions. The hub core disposed in the deadbolt arm comprises projections allowing it to fit in the deadbolt arm slots in one of two positions. The first position allows the second control member to move the deadbolt between retracted and projected positions and is known as the standard function. The second position allows the second control member to retract the deadbolt from a projected position, but cannot project the deadbolt from a retracted position, and is known as the classroom function.

Inventors:	Guma; Jarrett (Newington, CT), Palmieri; Eric (Rocky Hill, CT)
Applicant:	ASSA ABLOY Access and Egress Hardware Group, Inc. (New Haven, CT)
Family ID:	1000008819271
Assignee:	ASSA ABLOY Access and Egress Hardware Group, Inc. (New Haven, CT)
Appl. No.:	17/488037
Filed:	September 28, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220018161 A1	Jan. 20, 2022

Related U.S. Application Data

continuation parent-doc US 15787872 20171019 US 11156021 child-doc US 17488037
us-provisional-application US 62411098 20161021

Publication Classification

Int. Cl.: E05B63/00 (20060101); E05B9/02 (20060101); E05B59/00 (20060101); E05B63/08 (20060101)

U.S. Cl.:

CPC E05B63/0065 (20130101); E05B9/02 (20130101); E05B59/00 (20130101); E05B63/08 (20130101);

Field of Classification Search

CPC: E05B (63/0065); E05B (9/02); E05B (59/00); E05B (63/08); E05B (63/16); E05B (13/005); E05B (15/004); E05B (2063/0082); Y10T (292/1097); Y10T (70/5805); Y10T (70/5416); Y10T (70/5496)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1611940	12/1925	Ohmer	251/297	G07B 13/005
2426141	12/1946	Kell	70/129	E05B 63/0017
3672714	12/1971	Schultz	N/A	N/A
4047408	12/1976	Johns et al.	N/A	N/A
4313320	12/1981	Best et al.	N/A	N/A
5040652	12/1990	Fish	70/472	E05C 1/163
5113675	12/1991	Uyeda	70/279.1	E05B 13/10
6581423	12/2002	Lin	70/486	E05B 55/06
6598909	12/2002	Lu	292/144	E05B 47/0012
7188870	12/2006	Huang	N/A	N/A
8234892	12/2011	Laverty et al.	N/A	N/A
10626634	12/2019	Verderaime	N/A	E05B 1/0007
10890019	12/2020	Lien	N/A	E05B 63/14
11156021	12/2020	Guma	N/A	E05B 63/0065
11834863	12/2022	Lin	N/A	E05B 59/00
2002/0139156	12/2001	Aramburu	70/218	E05B 47/0692
2003/0019256	12/2002	Frolov	70/222	E05B 47/0688
2016/0017638	12/2015	Dore Vasudevan	292/137	E05B 55/12
2017/0275920	12/2016	Chen	N/A	E05B 17/22
2018/0112438	12/2017	Guma et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2 471 656	12/2010	GB	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion in International Application No. PCT/US2017/057578, mailed Jan. 26, 2018. cited by applicant

Primary Examiner: Mills; Christine M

Assistant Examiner: Ahmad; Faria F

Attorney, Agent or Firm: Wolf, Greenfield & Sacks, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 15/787,872, filed Oct. 19, 2017, which claims priority to U.S. Application Ser. No. 62/411,098, filed Oct. 21, 2016. The entire contents of these applications are incorporated herein by reference in their entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) The present invention is related to mortise locks, and in particular to a hub core for a deadbolt mechanism with the ability to change between standard and classroom functions based on assembly orientation.

2. Description of Related Art

(2) Conventional mortise locks employ both a latchbolt and a deadbolt. Both can be configured for different functions. A deadbolt operates by rotation of a deadbolt arm which mates securely around a hub core, which hub core is typically rotatable by a thumbturn or throw lever on the inside of the door, and a lock cylinder on the outside of the door. A “standard” function of a deadbolt is to permit the deadbolt to be operated in both directions, i.e., projected or extended to lock and retracted to unlock, by rotation of either the thumbturn inside the door or the lock cylinder (via a key) outside the door. Rotation of the thumbturn or key in one direction rotates the hub core and deadbolt arm and will cause the deadbolt to retract. Rotation of the thumbturn or key in the opposite direction rotates the hub core and deadbolt arm and will cause the deadbolt to project.

(3) In a “classroom” function, a key in the lock cylinder outside the door will operate both to project and retract the deadbolt. However, using the thumbturn will only cause the deadbolt arm to retract, while rotation in the opposite direction will not permit the deadbolt to project.

(4) Currently the only way to switch between standard and classroom functions is to swap between two completely different hub cores that mate in different configurations with the deadbolt arm.

SUMMARY OF THE INVENTION

(5) Bearing in mind the problems and deficiencies of the prior art, it is therefore an object of the present invention to provide an improved hub core for a mortise lock.

(6) It is another object of the present invention to provide a single hub core that may be used to set deadbolt operation in a mortise lock for both standard and classroom operation functions.

(7) A further object of the invention is to provide a deadbolt arm hub core that may be alternately switched between two different orientations during assembly of the mortise lock to provide either a standard or a classroom function for operation of the deadbolt.

(8) Still other objects and advantages of the invention will in part be obvious and will in part be apparent from the specification.

(9) The above and other objects, which will be apparent to those skilled in the art, are achieved in the present invention which is directed to a mortise lock for locking and unlocking a door. The mortise lock comprises a mortise lock body, a deadbolt arm, and a hub core. The mortise lock body

has a deadbolt operable by a first control member on the outside of the door and a second control member on the inside of the door. The deadbolt is selectably moveable between a projected position to lock the door and a retracted position to unlock the door. The deadbolt arm in the mortise lock body is rotatable to move the deadbolt between the projected and retracted positions. The hub core is disposed in the deadbolt arm and is operable by the second control member, the hub core being positionable in the deadbolt arm in two different positions. In a first position, the hub core is operable by the second control member to move the deadbolt between the projected and retracted positions. In a second position, the hub core is operable by the second control member to move the deadbolt from the projected position to the retracted position, the hub core not being operable by the second control member to move the deadbolt from the retracted position to the projected position.

(10) In an embodiment, the mortise lock first control member may be operable to move the deadbolt between the projected and retracted positions while in either of the first or second positions. The hub core may have a plurality of projections with arc lengths that fit into a plurality of slots with arc lengths in an opening in the deadbolt arm, wherein in the first position the hub core causes movement of the deadbolt in a standard function and in the second position the hub core causes movement of the deadbolt in a classroom function. The arc lengths of the hub core projections and deadbolt arm slots may be configured to permit the deadbolt arm to rotate and move the deadbolt in both the standard and classroom functions. The arc lengths of the hub core projections and deadbolt arm slots may also allow for a loss motion connection between the hub core and deadbolt arm slots when the hub core is in the second position. The hub core may also have a pair of projections with arc lengths that fit into a pair of slots with arc lengths in an opening in the deadbolt arm, wherein one hub core projection may fit rotationally tightly into one slot in the deadbolt arm opening when the hub core is in the first position in the deadbolt arm, and wherein both hub core projections fit rotationally loosely into both slots in the deadbolt arm opening when the hub core is in the second position in the deadbolt arm. The hub core may also have a first projection having an arc length of about 90° and a second projection having an arc length of about 45°, the deadbolt arm having an opening with a first slot having an arc length of about 90° and a second slot having an arc length of 135°, wherein in the first hub core position the first projection is disposed in the first slot and the second projection is disposed in the second slot, and in the second hub core position the first projection is disposed in the second slot and the second projection is disposed in the first slot. The hub core projections may have different thicknesses in an axial direction, with the thickness of the first projection being less than the thickness of the second projection.

(11) The present invention further provides a method of assembling a mortise lock for locking and unlocking a door. The method provides a mortise lock body, a deadbolt arm, and a hub core. The mortise lock body has a deadbolt operable by a first control member on the outside of the door and a second control member on the inside of the door. The deadbolt is selectably moveable between a projected position to lock the door and a retracted position to unlock the door. The deadbolt arm in the mortise lock body is rotatable to move the deadbolt between the projected and retracted positions. The hub core is operable by the second control member, the hub core being positionable in the deadbolt arm in two different positions. In a first position, the hub core is operable by the second control member to move the deadbolt between the projected and retracted positions. In a second position, the hub core is operable by the second control member to move the deadbolt from the projected position to the retracted position, the hub core not being operable by the second control member to move the deadbolt from the retracted position to the projected position.

(12) In an embodiment of the method, the first control member is operable to move the deadbolt between the projected and retracted positions while in either of the first or second positions. The hub core may have a plurality of projections with arc lengths that fit into a plurality of slots with arc lengths in an opening in the deadbolt arm, wherein in the first position the hub core causes

movement of the deadbolt in a standard function and in the second position the hub core causes movement of the deadbolt in a classroom function. The arc lengths of the hub core projections and deadbolt arm slots may be configured to permit the deadbolt arm to rotate and move the deadbolt in both the standard and classroom functions. The arc lengths of the hub core projections and deadbolt arm slots may also allow for a loss motion connection between the hub core and deadbolt arm slots when the hub core is in the second position. The hub core may also have a pair of projections with arc lengths that fit into a pair of slots with arc lengths in an opening in the deadbolt arm, wherein one hub core projection may fit rotationally tightly into one slot in the deadbolt arm opening when the hub core is in the first position in the deadbolt arm, and wherein both hub core projections fit rotationally loosely into both slots in the deadbolt arm opening when the hub core is in the second position in the deadbolt arm. The hub core may also have a first projection having an arc length of about 90° and a second projection having an arc length of about 45°, the deadbolt arm having an opening with a first slot having an arc length of about 90° and a second slot having an arc length of 135°, wherein in the first hub core position the first projection is disposed in the first slot and the second projection is disposed in the second slot, and in the second hub core position the first projection is disposed in the second slot and the second projection is disposed in the first slot. The hub core projections may have different thicknesses in an axial direction, with the thickness of the first projection being less than the thickness of the second projection.

(13) The present invention may still further provide a method of changing function of operation of a deadbolt in a mortise lock. The method provides a mortise lock body having a deadbolt operable by a first control member on the outside of the door and a second control member on the inside of the door. The deadbolt is selectably moveable between a projected position to lock the door and a retracted position to unlock the door. the mortise lock has a deadbolt arm rotatable to move the deadbolt between the projected and retracted positions, and a hub core disposed in the deadbolt arm that is operable by the second control member. The hub core is positionable in the deadbolt arm in one of a first or second position. In a first position, the hub core is operable by the second control member to move the deadbolt between the projected and retracted positions. In a second position, the hub core is operable by the second control member to move the deadbolt from the projected position to the retracted position, the hub core not being operable by the second control member to move the deadbolt from the retracted position to the projected position. The method includes removing the hub core from the deadbolt arm, then reinserting the hub core into the deadbolt arm in the other of the first and second position to change operation of the hub core by the second control member.

(14) In an embodiment, the method further includes the mortise lock body comprising sidewalls, and removing one sidewall from the mortise lock body prior to removing the hub core from the deadbolt arm. The method may also include the hub core and deadbolt arm being rotatable about an axis, and rotating the hub core after removing the hub core from the deadbolt arm prior to reinserting the hub core into the deadbolt arm. More specifically, the hub core may be rotated 180° after removal from the deadbolt arm and prior to reinsertion into the deadbolt arm.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The features of the invention believed to be novel and the elements characteristic of the invention are set forth with particularity in the appended claims. The figures are for illustration purposes only and are not drawn to scale. The invention itself, however, both as to organization and method of operation, may best be understood by reference to the detailed description which follows taken in conjunction with the accompanying drawings in which:

(2) FIG. 1 is a perspective, partially exploded view of a mortise lock incorporating the hub core and

the deadbolt arm of the present invention, switchable between standard and classroom functions.

(3) FIG. 2 is a side elevational view, with the side panel removed, of the mortise lock of FIG. 1.

(4) FIG. 3 is a side elevational view of a portion of the mortise lock of FIG. 1 showing the deadbolt arm and deadbolt in the projected or extended position, to lock the door.

(5) FIG. 4 is a side elevational view of a portion of the mortise lock of FIG. 1 showing the deadbolt arm and deadbolt in the retracted position, to unlock the door.

(6) FIG. 5 is a cross-sectional view of the switchable hub core within the central opening of deadbolt arm of the present invention, showing an elevational view of the fingers, elongated portions and tabs of the deadbolt arm in phantom lines, as employed the mortise lock of FIG. 1.

(7) FIG. 6 is a cross-sectional view of the switchable hub core within the central opening of deadbolt arm of FIG. 5, showing the hub core positioned within the opening of the deadbolt arm for the classroom function of operation of the deadbolt.

(8) FIG. 7 is a cross-sectional view of the switchable hub core within the central opening of deadbolt arm of FIG. 5, showing the hub core positioned within the opening of the deadbolt arm for the standard function of operation of the deadbolt.

(9) FIG. 8 shows various views of the deadbolt arm of FIG. 5.

(10) FIGS. 9-15 are various perspective views of the switchable hub core and/or deadbolt arm of the present invention.

(11) FIG. 16 is a perspective view of an auxiliary mortise lock incorporating the hub core and the deadbolt arm of the present invention, switchable between standard and classroom functions.

(12) FIG. 17 is a perspective, partially exploded view of the auxiliary mortise lock of FIG. 16.

(13) FIG. 18 is a side elevational view, with the side panel removed, of the auxiliary mortise lock of FIG. 16.

(14) FIG. 19 is a bottom view of the auxiliary mortise lock of FIG. 16.

(15) FIGS. 20 and 21 are opposite side elevational views of the hub core positioned within the opening of the deadbolt arm for the standard function of operation of the deadbolt,

(16) FIGS. 22 and 23 are opposite side elevational views of the hub core and deadbolt arm, positioned in the standard function of operation, retracting the deadbolt bracket,

(17) FIGS. 24 and 25 are opposite side elevational views of the hub core and deadbolt arm, positioned in the standard function of operation, projecting the deadbolt bracket.

(18) FIGS. 26 and 27 are opposite side elevational views of the hub core positioned within the opening of the deadbolt arm for the classroom function of operation of the deadbolt, after the inside thumbscrew control member has rotated the hub core to retract the deadbolt.

(19) FIGS. 28 and 29 are opposite side elevational views of the hub core and deadbolt arm, positioned in the classroom function of operation, retracting the deadbolt bracket.

(20) FIGS. 30 and 31 are opposite side elevational views of the hub core positioned within the opening of the deadbolt arm for the classroom function of operation of the deadbolt, after the inside thumbscrew control member has rotated the hub core to attempt to project the deadbolt.

(21) FIGS. 32 and 33 are opposite side elevational views of the hub core and deadbolt arm, positioned in the classroom function of operation, with the deadbolt bracket still retracted after the inside thumbscrew control member has rotated the hub core to attempt to project the deadbolt.

(22) FIGS. 34 and 35 are opposite side elevational views of the hub core and deadbolt arm, positioned in the classroom function of operation, projecting the deadbolt bracket after the outside lock cylinder control member has rotated the deadbolt arm to project the deadbolt.

DESCRIPTION OF THE EMBODIMENT(S)

(23) In describing the embodiment(s) of the present invention, reference will be made herein to FIGS. 1-35 of the drawings in which like numerals refer to like features of the invention. The invention may be utilized in both auxiliary and full mortise locks to configure them for either standard or classroom function operation of the deadbolt.

(24) In FIGS. 1 and 2 there is shown a full mortise-type lockset 10 incorporating the switchable-

function hub core and the deadbolt arm of the present invention. Mortise lock **10** has casing **12**, including top and bottom walls **18**, **20** and sidewalls **16a**, **16b**. Mortise lock **10** fits within a mortise opening in the door, and includes on the outside a lock cylinder **13** and on the inside a thumbturn **88** which operates deadbolt **26**. Mortise lock **10** has an outer lever handle **60a**, and an inner lever handle **60b**, which are connected via shafts to square opening **84** in spindle hub **80**. Rotation of spindle hub **80** moves latchbolt rod **62** and causes latchbolt **54** to retract and withdraw into casing **12**. Latchbolt **54** and rod **67** are normally held in the extended position by spring **104**. The operation of latchbolt **54** by handles **60a**, **60b** is conventional, and discussion below will be directed to assembly, construction and operation of the deadbolt and associated deadbolt arm and hub core of the present invention, which utilizes a different configuration and different assembly options compared to the prior art.

(25) The lock cylinder **13** extends through an opening in the door and lock cylinder opening **11** in mortise lock sidewall **16a**. The lock cylinder **13** acts as a control member to operate deadbolt **26** in the manner of the prior art. Rotation of key **17** turns the cylinder plug in lock cylinder **13** which operates a tail cam or arm **15** that engages fingers of a deadbolt arm within the mortise lock **10**. Rotation of the key **17** in one direction causes the deadbolt **26** to be extended and locks the mortise lock **10**. Rotation in the opposite direction retracts deadbolt **26** and unlocks the mortise lock mechanism.

(26) On the inside of the door, thumbturn throw lever **88** operates as a control member to rotate and turn thumbturn blade shaft **64** which extends into a slot **34** in a hub core **36** controlling rotation and operation of the deadbolt arm. When the deadbolt thumbturn on the inside is turned in one direction, it retracts deadbolt **26**. When turned in the opposite direction, the thumbturn **88** may or may not extend the deadbolt **26**, depending on whether the lock is set to the standard or classroom function.

(27) Referring to FIG. 2, lock **10** incorporates a deadbolt operation mechanism, which includes deadbolt **26**, deadbolt bracket **28** and deadbolt arm **30**. Deadbolt **26** is movable within opening **32** in front plate **14** and between a locked position and an unlocked position. When deadbolt **26** is in the locked position (FIGS. 2 and 3), deadbolt **26** projects from casing **12** through opening **32** in front plate **14**. When deadbolt **26** is in the unlocked position (FIG. 4), deadbolt **26** is substantially completely withdrawn into casing **12**.

(28) Deadbolt arm **30** pivots around hub core **36**, whose opposite ends extend through and are rotatably captured in circular openings in opposing sidewalls **16a** and **16b**. Deadbolt arm **30** comprises elongate portion **38** and hub portion **39**, from which extends a finger **46**. Elongated portion **38** has a tab **40** attached at the distal end thereof and is slideable within slot **52** of deadbolt bracket **28**. Slot **52** has an angle approximately midway between vertical and horizontal, so that when tab **40** is moved up and down by rotation of elongated portion **38**, it bears upon the walls of slot **52** to move deadbolt bracket **28** and consequently deadbolt **26** inward into lock **10** in a retracted position, to unlock the deadbolt, and outward from the lock **10** to a projected or extended position, to lock the deadbolt. FIGS. 2 and 3 illustrate deadbolt mechanism **24** configured with deadbolt **26** in the projected or locking position. When deadbolt **26** is in the locking position, portion **48a** of spring **48** contacts and applies a force to finger **46** of hub portion **39** to maintain deadbolt **26** in the locking position. When deadbolt arm **30** is pivoted by the key **17** or thumbturn **88** to retract and move deadbolt **26** to the unlocked position, as shown in FIG. 4, such pivoting action creates a force sufficient to push finger **46** downward beyond spring **48** and position portion **48a** of spring **48** to indented area **49** (FIG. 2) of hub portion **39**. Spring **48** then contacts and applies a force to area **49** of hub portion **39** to maintain deadbolt **26** in the unlocked position.

(29) Referring to FIG. 5, deadbolt arm **30** pivots and rotates about the axis **50** of hub core **36**, which extends through an opening **41** in deadbolt arm hub portion **39**. During operation by thumbturn **88**, deadbolt arm **30** is pivoted by thumbturn blade shaft **64** which is inserted into slot **34** of hub core **36** (FIGS. 1-2). Hub core **36** will then rotate the deadbolt arm **30** clockwise or

counterclockwise, depending on the direction of thumbturn **88** movement and the function configuration. Hub portion **39** also includes a V-configuration of fingers **42** and **44**. During operation by key **17** in lock cylinder **13**, downwardly extending arm **15** (FIG. **1**) cooperates with fingers **42** and **44** (FIG. **2**) to rotate the deadbolt arm **30** clockwise or counterclockwise. Such movement of elongated portion **38** down and up will retract and project the deadbolt **26**, as described above.

(30) Identification of the remaining features in FIGS. **1-4**, and operation of the deadbolt and latchbolt, are described in U.S. Pat. Nos. 5,678,870, 6,282,929, and 6,938,445, the disclosures of which are hereby incorporated by reference.

(31) The deadbolt arm **30** and switchable hub core **36** of the present invention are shown in more detail in FIGS. **5** and **8-15**. In FIGS. **5** and **9-15**, deadbolt arm **30** is shown from the side opposite to that shown in FIGS. **2-4**, so that elongate portion **38** extends out from hub portion **39** to the right and terminates in tab **40** which is configured to slide in and engage with slot **52** of deadbolt bracket **28** (FIGS. **2-4**). Finger **46** extends leftward from hub portion **39** (FIG. **5**), with indentation **49** between fingers **44** and **46**, which operate with spring **48** as explained previously (FIG. **2**). Fingers **42** and **44** extend upward in a V-configuration and terminate in tabs **43** and **45**, respectively, and these fingers and/or tabs are contacted by arm **15** extending down from the lock cylinder **13** (FIG. **1**) to rotate the deadbolt arm **30** clockwise or counterclockwise, and move elongated portion **38** down and up, to retract and project the deadbolt **26**, as described above. In both the standard and classroom functions of operation, operation of lock cylinder **13** via key **17** will always operate to retract and project the deadbolt.

(32) Hub core **36** has a generally cylindrical body with a central slot **34**, and is disposed in and extends through central opening **41** in hub portion **39** of deadbolt arm **30**. In the embodiment shown, the thickness of hub core **36** in the axial direction is greater than that of deadbolt arm hub portion **39** (FIGS. **11** and **13**). Hub core arm **33** extends radially outward from the hub core **36**. As described previously, hub core slot **34** is engaged by blade shaft **64** of the thumbturn **88** on the inner side of the door to rotate the hub slot core and cause the desired movement, or lack of movement, in the deadbolt arm **30** to effect the desired movement or lack of movement in the deadbolt **26**, depending on the selected function of operation.

(33) Hub core **36** employs a selective “keying” feature within deadbolt arm opening **41** to determine function of operation of the deadbolt **26**. Hub core **36** has a pair of arcuate segments or projections **35a**, **35b** extending radially outward around its periphery, the segments or projections **35a**, **35b** which extend into arcuate indentations or slots **47a**, **47b** formed in the inner wall of deadbolt arm hub portion **39**. As shown in FIGS. **6** and **7**, the hub core projections **35a**, **35b** and deadbolt arm slots **47a**, **47b** have dimensions that may be described by angles α and β , respectively, extending about axis **50**. Hub core first projection **35a** has an angle or arc length of $\alpha_{\text{sub.1}}$ and hub core second projection **35b** has an angle or arc length of $\alpha_{\text{sub.2}}$. Deadbolt arm first slot **47a** has an angle or arc length of $\beta_{\text{sub.1}}$ and deadbolt arm second slot **47b** has an angle or arc length of $\beta_{\text{sub.2}}$. The angles or arc widths may vary from that shown. For example, the arc length of the hub core first projection **35a** may be about $45^\circ \pm 5^\circ - 15^\circ$ and the arc length of the hub core second projection **35b** may be about $90^\circ \pm 5^\circ - 15^\circ$, while the arc length of the deadbolt arm first slot **47a** may be about $90^\circ \pm 5^\circ - 15^\circ$ and the arc length of the deadbolt arm second slot **47b** may be about $135^\circ \pm 5^\circ - 15^\circ$. The first and second hub core projections **35a**, **35b** are generally opposite each other, and one edge or end of the first projection **35a** may be about 180° opposite one edge or end of the second projection **35b**. Similarly, the first and second deadbolt arm slots **47a**, **47b** are generally opposite each other, and one edge or end of the first slot **47a** may be about 180° opposite one edge or end of the second slot **47b**.

(34) Hub core projections **35a**, **35b** may also differ in their thickness and location on the hub core **36**, in an axial direction along the thickness of the hub core **36**. As shown in FIG. **9**, both projections **35a**, **35b** have thicknesses less than that of the body of hub core **36**, with projection **35b**

extending more than half of the hub core body thickness starting at the end closest to arm 33, and projection 35a extending less than half of the hub core body thickness starting at the end closest to arm 33. Slot 47a formed in deadbolt arm inner wall 41 extends completely through the thickness of hub portion 39 (FIG. 10). Slot 47b has a portion, with an arcuate length approximately equal to arcuate length $\alpha_{sub.2}$ of hub core projection 35b, that extends completely through the thickness of hub portion 39, and a portion that extends less than the hub portion thickness, leaving an arcuate lower lip or flange 47c of arcuate length approximately equal to $\beta_{sub.2} - \alpha_{sub.2}$, as shown in FIGS. 8, 9, and 10.

(35) The arc lengths and thicknesses of the hub core projections in the deadbolt arm slots are configured to permit the deadbolt arm to rotate in a manner of the standard function when the hub core is disposed in the deadbolt arm in one position, and to permit the deadbolt arm to rotate in a manner of the classroom function when the hub core is disposed in the deadbolt arm in another position.

(36) In the example shown in FIGS. 7, 11, and 12, hub core 36 is in a first position in deadbolt arm opening 41 for the standard function of deadbolt operation, with hub core projection 35a in deadbolt arm slot 47a, and hub core projection 35b in deadbolt arm slot 47b. The arc length $\alpha_{sub.1}$ of hub core projection 35a is comparable and approximately equal to the arc length of $\beta_{sub.1}$ of deadbolt arm slot 47a. Hub core projection 35b extends into the portion of deadbolt arm slot 47b that extends through the entire thickness of the deadbolt arm hub 39. Hub core projection 35a has a tight fit rotationally about the axis of the hub slot within and with respect to deadbolt arm slot 47a (filling the arcuate length of slot 47a), and hub core projection 35b has a tight fit rotationally about the axis of the hub slot within and with respect to a portion of deadbolt arm slot 47b (filling the arcuate length of slot 47b that extends completely through the thickness of deadbolt arm hub portion 39) so that hub core rotation in either direction causes deadbolt arm rotation. This close fit between the projection(s) and slot causes any rotation of hub 36 by thumbturn 88 in either the clockwise direction C or the counterclockwise direction CC (FIG. 7) to similarly rotate the hub portion 39 and deadbolt arm 30. Such rotation occurs despite the fact that the arc length $\alpha_{sub.2}$ of hub core projection 35b is considerably less than the arc length of $\beta_{sub.2}$ of deadbolt arm slot 47b.

(37) To provide the classroom function of operation of the deadbolt, hub core 36 is placed in a second position in the opposite manner of FIG. 7, and is shown in FIGS. 5, 6, 13, 14, and 15 with core projection 35b in deadbolt arm slot 47a, and hub core projection 35a in deadbolt arm slot 47b. In this second position, the arc lengths of hub core projections 35a, 35b are both considerably less than the arc lengths of deadbolt arm slots 47b, 47a into which they respectively project, thus creating a loss or lost motion connection between the projections 35a, 35b and the slots 47a, 47b wherein for a portion of the rotation of the hub core 36, there is no rotation of the deadbolt arm 30. Both hub core projections 35a, 35b have a loose fit rotationally about the axis of the hub slot within and with respect to deadbolt arm slots 47b, 47a, i.e., any hub rotation does not necessarily cause deadbolt arm rotation. However, in the initial positions shown in FIGS. 5, 6, 13, and 14, both hub core projections 35a, 35b have one edge or end in contact with one edge or end of slots 47b, 47a, respectively, so that upon counterclockwise rotation of hub core 36 in direction CC (FIG. 6) by thumbturn 88, deadbolt arm hub portion 39 and the deadbolt arm 30 will be caused to also rotate in the counterclockwise direction, and cause the deadbolt 26 to retract. However, upon rotation of the thumbturn 88 in the opposite, clockwise direction, because of the smaller angular lengths of the projections 35a, 35b in the slots 47a, 47b, the thickness of the projections, and the spacing between the other edges of ends of the projections and slots, the hub core 36 will rotate clockwise within deadbolt arm opening 41 and the projections 35a, 35b will slide within their respective slots 47a, 47b to the opposite ends of the slots without causing rotation or other movement to the deadbolt arm 30 (FIG. 15).

(38) As shown in FIGS. 6-7, the dimensions of the hub core 36 outer periphery, including those of the projections 35a, 35b, and the dimensions of the deadbolt arm hub portion 39 central opening,

including those of the slots **47a**, **47b**, should be configured to permit a snug sliding fit between the two as the hub core **36** is slid axially into the deadbolt arm **30** opening during assembly of the lock. The dimensions of the arc lengths of the hub core projections **35a**, **35b** and deadbolt arm opening slots **47a**, **47b** may be different from that shown, but should be selected so that they operate as described above in the standard and classroom function of operation of the deadbolt.

(39) The hub core and deadbolt arm of the present invention are shown in connection with an auxiliary mortise lock **110** in FIGS. **16-19**. The housing components of auxiliary mortise lock **110** are similar to those shown in the full mortise lock of FIGS. **1-4**, except that the numeral “1” has been added in front of the comparable number. Auxiliary mortise lock incorporates within casing **112** a deadbolt mechanism **124** comparable to deadbolt mechanism **24** in the full mortise lock of FIG. **2** and operable by the inside thumbturn and outside lock cylinder control members, but includes no latchbolt mechanism. Hub core **36** has ends **36a**, **36b** containing slot **34** rotatable within comparably sized openings in opposing sidewalls **116a** and **116b** (FIG. **19**). The construction and operation of deadbolt arm **30** around and with respect to switchable hub core **36** are the same in auxiliary mortise lock **110** as they are in full mortise lock **10**.

(40) The operation of the hub core **36** within the opening of the deadbolt arm **30** for the standard function of operation of the deadbolt **26** is shown in FIGS. **20-25**. Hub core projection **35a** is snugly positioned in deadbolt arm slot **47a**, and hub core projection **35b** is positioned into the portion of deadbolt arm slot **47b** that extends through the entire thickness of the deadbolt arm hub **39**. This close fit permits the inner thumbturn control member to rotate hub **36** and deadbolt arm **30** in one direction to the retracted position shown in FIGS. **22** and **23** to unlock the deadbolt, and then in the opposite direction back to the projected position of FIGS. **24** and **25** to lock the deadbolt.

(41) The operation of the hub core **36** within the opening of the deadbolt arm **30** for the classroom function of operation of the deadbolt is shown in FIGS. **26-35**. In FIGS. **26** and **27** the inside thumbscrew control member has rotated hub core **36** within deadbolt arm hub portion **39** in one direction to unlock the deadbolt, and deadbolt bracket **28** in the resulting retracted position is shown in FIGS. **28** and **29**. When the inside thumbscrew control member has rotated hub core **36** in the opposite direction to attempt to lock the deadbolt, as shown in FIGS. **30-33**, hub projections **35a**, **35b** slide to the opposite ends within deadbolt hub portion slots **47a**, **47b** as the hub core **36** rotates in loss or lost motion. This has no effect on the rotation or position of deadbolt arm **30**, so deadbolt bracket **28** remains in the retracted position as shown in FIGS. **32** and **33**. On the other hand, the outside lock cylinder control member may still operate to rotate and move deadbolt arm **30** via fingers **42**, **44** to lock the deadbolt **26**, as shown in FIGS. **34** and **35** where the deadbolt bracket **28** has been projected. Because deadbolt arm **30** has rotated while hub core **36** has not, projections **35a**, **35b** slide to the ends within deadbolt hub portion slots **47a**, **47b** as shown previously in FIGS. **26-29**, and are now in position to permit the inner thumbturn control member to rotate hub core **36** and cause the deadbolt to retract.

(42) To change the lock from one function to the other, hub core **36** is removed from deadbolt arm **30** by withdrawing it in the direction of axis **50**, rotating it 180° about the axis **50**, and then reinserting the hub core into the deadbolt arm opening **41**. Consequently, during assembly the hub core of the present invention can be oriented in one position before insertion in the deadbolt arm opening to operate as a standard function, or rotated or flipped to the opposite position and inserted to operate as a classroom function. Alternatively, after assembly, mortise lock sidewall **16a** or **16b** can be removed, and the hub core **36** which has been positioned to operate as one function can be removed and then rotated or flipped, and then reinserted to operate as the other function. These different configurations use the aforescribed keying feature in the mating parts which changes the function depending on the orientation.

(43) One advantage of the present invention is that both functions can be created by use of a single hub core piece, rather than having a separate standard function hub core and a classroom function hub core, as in the prior art. The ability to switch between functions can easily be completed during

assembly, while the side of the lock is open. If the function is needed to be switched at a later time, the lock can be opened, and the hub core flipped 180°. One needs to create and stock only one hub core component, rather than two individual pieces. There is also the ability to easily switch between functions if necessary during assembly.

(44) While the present invention has been particularly described, in conjunction with a specific preferred embodiment, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art in light of the foregoing description. It is therefore contemplated that the appended claims will embrace any such alternatives, modifications and variations as falling within the true scope and spirit of the present invention.

Claims

1. A mortise lock for locking and unlocking a door comprising: a mortise lock body having a deadbolt operable by a first control member on an outside of the door and a second control member on an inside of the door, the deadbolt being selectably moveable between a projected position to lock the door and a retracted position to unlock the door; a deadbolt arm in the mortise lock body rotatable to move the deadbolt between the projected position and the retracted position; and a hub core disposed in the deadbolt arm, said hub core connected to and operable by the second control member, the hub core being positionable in the deadbolt arm in two different positions: in a first position, the hub core being operable by the second control member to move the deadbolt between the projected position and the retracted position; and in a second position, the hub core being operable by the second control member to move the deadbolt from the projected position to the retracted position, the hub core not being operable by the second control member to move the deadbolt from the retracted position to the projected position.
2. The mortise lock of claim 1, wherein the first control member is operable to move the deadbolt between the projected position and the retracted position in either of the first position or the second position.
3. The mortise lock of claim 1, wherein the hub core has a plurality of projections with arc lengths that fit into a plurality of slots with arc lengths in an opening in the deadbolt arm, and wherein the hub core in the first position causes movement of the deadbolt in a standard function and the hub core in the second position causes movement of the deadbolt in a classroom function.
4. The mortise lock of claim 3, wherein the arc lengths of the plurality of projections and the plurality of slots are configured to permit the deadbolt arm to rotate and move the deadbolt in both the standard function and the classroom function.
5. The mortise lock of claim 3, wherein the arc lengths of the plurality of projections and the plurality of slots allow for a loss motion connection between the hub core and the plurality of slots when the hub core is in the second position.
6. The mortise lock of claim 1, wherein the hub core has a first projection having an arc length of about 90° and a second projection having an arc length of about 45° and the deadbolt arm has an opening with first slot having an arc length of about 90° and a second slot having an arc length of 135°, wherein in the first position the first projection is disposed in the first slot and the second projection is disposed in the second slot, and in the second position the first projection is disposed in the second slot and the second projection is disposed in the first slot.
7. The mortise lock of claim 6, wherein the first projection and the second projection have different thicknesses in an axial direction, with a thickness of the first projection being less than a thickness of the second projection.
8. A method of assembling a mortise lock for locking and unlocking a door comprising: providing a mortise lock body having a deadbolt operable by a first control member on an outside of the door and a second control member on an inside of the door, the deadbolt being selectably moveable between a projected position to lock the door and a retracted position to unlock the door; providing

a deadbolt arm in the mortise lock body rotatable to move the deadbolt between the projected position and the retracted position; providing a hub core operable by the second control member, the hub core being positionable in the deadbolt arm in two different positions; and assembling the hub core into the deadbolt arm in one of the two different positions: in a first position, the hub core being operable by the second control member to rotate the deadbolt arm to move the deadbolt between the projected position and the retracted position; and in a second position, the hub core being operable by the second control member to rotate the deadbolt arm to move the deadbolt from the projected position to the retracted position, the hub core not being operable by the second control member to move the deadbolt from the retracted position to the projected position.

9. The method of claim 8, wherein the first control member is operable to move the deadbolt between the projected position and the retracted position in either of the first position or the second position.

10. The method of claim 8, wherein the hub core has a plurality of projections with arc lengths that fit into a plurality of slots with arc lengths in an opening in the deadbolt arm, and wherein the hub core in the first position causes movement of the deadbolt in a standard function and the hub core in the second position causes movement of the deadbolt in a classroom function.

11. The method of claim 10, wherein the arc lengths of the plurality of projections and the plurality of slots are configured to permit the deadbolt arm to rotate and move the deadbolt in both the standard function and the classroom function.

12. The method of claim 10, wherein the arc lengths of the plurality of projections and the plurality of slots allow for a loss motion connection between the hub core and the plurality of slots when the hub core is in the second position.

13. The method of claim 8, wherein the hub core has a first projection having an arc length of about 90° and a second projection has an arc length of about 45° and the deadbolt arm has an opening with a first slot having an arc length of about 90° and a second slot has an arc length of about 135° , wherein in the first position the first projection is disposed in the first slot and the second projection is disposed in the second slot, and in the second position the first projection is disposed in the second slot and the second projection is disposed in the first slot.

14. The method of claim 13, wherein the first projection and the second projection have different thicknesses in an axial direction, with a thickness of the first projection being less than a thickness of the second projection.

15. A mortise lock for locking and unlocking a door comprising: a mortise lock body having a deadbolt operable by a first control member on an outside of the door and a second control member on an inside of the door, the deadbolt being selectably moveable between a projected position to lock the door and a retracted position to unlock the door; and a hub core disposed in the mortise lock body, the hub core operatively coupled to the deadbolt, the hub core being selectively rotatable by the second control member, said hub core operatively connected to the second control member, the hub core being positionable in the mortise lock body in two different positions: in a first position, the hub core being operable by the second control member to move the deadbolt between the projected position and the retracted position; and in a second position, the hub core being operable by the second control member to move the deadbolt from the projected position to the retracted position, the hub core not being operable by the second control member to move the deadbolt from the retracted position to the projected position; wherein the hub core is rotatable between the first position and the second position.

16. The mortise lock of claim 15, further comprising a deadbolt arm in the mortise lock body rotatable to move the deadbolt between the projected position and the retracted position, wherein the hub core is disposed in the deadbolt arm.

17. The mortise lock of claim 16, wherein the hub core has a plurality of projections with arc lengths that fit into a plurality of slots with arc lengths in an opening in the deadbolt arm, and wherein the hub core in the first position causes movement of the deadbolt in a standard function

and the hub core in the second position causes movement of the deadbolt in a classroom function.

18. The mortise lock of claim 17, wherein the arc lengths of the plurality of projections and the plurality of slots allow for a loss motion connection between the hub core and the plurality of slots when the hub core is in the second position.

19. A mortise lock for locking and unlocking a door comprising: a mortise lock body having a deadbolt operable by a first control member on an outside of the door and a second control member on an inside of the door, the deadbolt being selectably moveable between a projected position to lock the door and a retracted position to unlock the door; a deadbolt arm in the mortise lock body rotatable to move the deadbolt between the projected position and the retracted position; and a hub core disposed in the deadbolt arm, the hub core operatively coupled to the deadbolt, the hub core being selectively rotatable by the second control member, said hub core operatively connected to the second control member, the hub core being positionable in the deadbolt arm in two positions, the hub core having a pair of projections with arc lengths that fit into a pair of slots with arc lengths in an opening in the deadbolt arm, and wherein one hub core projection fits rotationally tightly into one slot in the opening in the deadbolt arm when the hub core is in a first position of the two positions, and wherein both hub core projections fit rotationally loosely into both slots in the opening in the deadbolt arm when the hub core is in a second position of the two positions.

20. The mortise lock of claim 19, wherein in the first position, the hub core is operable by the second control member to move the deadbolt between the projected position and the retracted position; and wherein in the second position, the hub core is operable by the second control member to move the deadbolt from the projected position to the retracted position, the hub core not being operable by the second control member to move the deadbolt from the retracted position to the projected position.

21. The mortise lock of claim 19, wherein the arc lengths of the pair of projections and the pair of slots allow for a loss motion connection between the hub core and the pair of slots when the hub core is in the second position.

22. The mortise lock of claim 1, wherein the hub core is disposed in an opening in the deadbolt arm.

23. The mortise lock of claim 22, wherein the opening in the deadbolt arm extends through the deadbolt arm.

24. The mortise lock of claim 22, wherein the deadbolt arm is configured to rotate about a lock axis to move the deadbolt between the projected position and the retracted position, and wherein the opening in the deadbolt arm extends along the lock axis.

25. The mortise lock of claim 1, wherein the deadbolt arm is fully disposed in the mortise lock body.
