

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416756
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Agemizu; Wahei et al.

Surface light-emitting device, display device, and illumination device

Abstract

A surface light-emitting device includes a plurality of light sources, a light guide that guides light emitted from the plurality of light sources, and a controller that controls turn-on operations of the plurality of light sources. The light guide includes a plurality of light controllers on which the light from the plurality of light sources are incident. The plurality of light controllers are disposed side by side in a first direction intersecting optical axes of the plurality of light controllers, the plurality of light sources include a first light source and a second light source, the first light source is disposed on one of the optical axes of the plurality of light controllers, the second light source is disposed at a position away from the optical axes of the plurality of light controllers, and the controller turns on at least one of the first light source and the second light source.

Inventors: Agemizu; Wahei (Osaka, JP), Takata; Kazumasa (Osaka, JP)

Applicant: Panasonic Intellectual Property Management Co., Ltd. (Osaka, JP)

Family ID: 1000008819163

Assignee: PANASONIC INTELLECTUAL PROPERTY MANAGEMENT CO., LTD.
(Osaka, JP)

Appl. No.: 18/905145

Filed: October 03, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250028108 A1	Jan. 23, 2025

Foreign Application Priority Data

JP	2022-066127	Apr. 13, 2022
----	-------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/JP2023/005267 20230215 PENDING child-doc US 18905145

Publication Classification

Int. Cl.: F21V8/00 (20060101)

U.S. Cl.:

CPC G02B6/0045 (20130101); G02B6/002 (20130101); G02B6/0068 (20130101);

Field of Classification Search

CPC: G02B (6/0045); G02B (6/002); G02B (6/0068)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2007/0058108	12/2006	Uehara et al.	N/A	N/A
2012/0155109	12/2011	Hayashi	362/613	G02B 6/0068
2016/0004005	12/2015	Namekata et al.	N/A	N/A
2018/0074247	12/2017	Asakawa	N/A	G02B 6/0068
2019/0351814	12/2018	Furubayashi	N/A	F21S 43/239
2022/0043262	12/2021	Agemizu et al.	N/A	N/A
2022/0128829	12/2021	Sakaguchi	N/A	G02B 27/0972
2023/0290915	12/2022	Yoshida	N/A	F21V 5/007
2024/0027759	12/2023	Agemizu et al.	N/A	N/A
2024/0045206	12/2023	Agemizu	N/A	G02B 27/0101
2024/0151891	12/2023	Okuda	N/A	G02B 6/0036

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2007-079093	12/2006	JP	N/A
2016-027546	12/2015	JP	N/A
2019-164386	12/2018	JP	N/A
2019-200928	12/2018	JP	N/A
2020-021640	12/2019	JP	N/A
2021-027005	12/2020	JP	N/A
201516492	12/2014	TW	N/A
2011/024960	12/2010	WO	N/A

OTHER PUBLICATIONS

International Search Report of PCT application No. PCT/JP2023/005267 dated Apr. 11, 2023. cited by applicant
Extended European Search Report dated Jul. 7, 2025 for the related European Patent Application No. 23788015.8. cited by applicant

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a surface light-emitting device, a display device, and an illumination device.

BACKGROUND ART

(2) PTL 1 discloses a liquid crystal display device including a liquid crystal panel, viewing angle control means, a prism sheet, and a light guide plate.

(3) The viewing angle control means includes an upper transparent electrode layer, a lower transparent electrode layer, and a transmission state variable layer, and adjusts a voltage applied between the upper transparent electrode layer and the lower transparent electrode layer to change an alignment state of liquid crystals in the transmission state variable layer and controls width and narrowness of a viewing angle.

CITATION LIST

Patent Literature

(4) PTL 1: Unexamined Japanese Patent Publication No. 2019-164386

SUMMARY OF THE INVENTION

(5) However, in the invention of PTL 1, it is necessary to dispose the viewing angle control means for switching light distribution by electrical control between the light guide plate and the liquid crystal panel, and there is a problem that transmittance of light decreases and cost of the entire device increases.

(6) The present invention has been made in view of such a point, and an object thereof is to provide a surface light-emitting device capable of switching between a narrow angle light distribution and a wide angle light distribution with a relatively simple configuration.

(7) A surface light-emitting device according to an aspect of the present disclosure includes a plurality of light sources, a light guide that guides light emitted from the plurality of light sources, and a controller that controls turn-on operations of the plurality of light sources. The light guide includes a plurality of light controllers on which the light from the plurality of light sources are incident, a prism that reflects the light having passed through the plurality of light controllers, a light guide surface on which the prism is provided, and an emission surface that is disposed opposite to the light guide surface and emits the light reflected by the prism. The plurality of light controllers are disposed side by side in a first direction intersecting optical axes of the plurality of light controllers, the plurality of light sources include a first light source and a second light source, the first light source is disposed on one of the optical axes of the plurality of light controllers, the second light source is disposed at a position away from the optical axes of the plurality of light controllers, and the controller turns on at least one of the first light source and the second light source.

(8) As described above, at least one of the first light source and the second light source is turned on, and thus, the incident angle of the light incident on the light controller is changed. As a result, it is possible to switch between the narrow angle light distribution and the wide angle light distribution.

(9) According to the aspect of the present disclosure, it is possible to provide the surface light-emitting device capable of switching between the narrow angle light distribution and the wide angle light distribution with a relatively simple configuration.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view illustrating a configuration of a surface light-emitting device according to the present exemplary embodiment.
- (2) FIG. 2 is a plan view illustrating a configuration of the surface light-emitting device.
- (3) FIG. 3 is a side view illustrating a configuration of the surface light-emitting device.
- (4) FIG. 4 is a plan view illustrating a configuration of a display device including the surface light-emitting device.
- (5) FIG. 5 is a side view illustrating a configuration of the display device including the surface light-emitting device.
- (6) FIG. 6 is a schematic view for explaining light forming a narrow angle light distribution.
- (7) FIG. 7 is a schematic view for explaining light for forming a wide angle light distribution.
- (8) FIG. 8 is a diagram illustrating the light intensity angle distribution in a case where only a first light source for the narrow angle light distribution is turned on.
- (9) FIG. 9 is a diagram illustrating the light intensity angle distribution in a case where only a second light source for the wide angle light distribution is turned on.
- (10) FIG. 10 is a diagram illustrating a light intensity angle distribution in a case where the first light source and the second light source are simultaneously turned on.
- (11) FIG. 11 is a diagram illustrating a light intensity angle distribution in a case where a light amount of the second light source for the wide angle light distribution is reduced with respect to a light amount of the first light source for the narrow angle light distribution in the present first modified example.
- (12) FIG. 12 is a perspective view illustrating a configuration of a surface light-emitting device according to the present second modified example.
- (13) FIG. 13 is a side view illustrating a configuration of the surface light-emitting device.
- (14) FIG. 14 is a side view illustrating a configuration of a surface light-emitting device according to the present third modified example.
- (15) FIG. 15 is a perspective view illustrating a configuration of a surface light-emitting device according to the present fourth modified example.
- (16) FIG. 16 is a side view illustrating a configuration of the surface light-emitting device.
- (17) FIG. 17 is a side view illustrating a configuration of an illumination device including a surface light-emitting device according to another exemplary embodiment.

DESCRIPTION OF EMBODIMENT

- (18) Hereinafter, exemplary embodiments of the present invention will be described with reference to the drawings. Note that, the following descriptions of the preferable exemplary embodiments are merely examples in essence, and are not intended to limit the present invention, or application or usage of the present invention.
- (19) As illustrated in FIGS. 1 and 2, surface light-emitting device 10 includes light guide 1, first light sources 2, second light sources 3, and controller 5. First light sources 2 and second light sources 3 are implemented on control board 4. Control board 4 is connected to controller 5.
- (20) Light guide 1 guides light emitted from at least one of first light sources 2 and second light sources 3. Light guide 1 is made of a material transparent to visible light. Light guide 1 is made of, for example, polymethyl methacrylate (PMMA), polycarbonate, or the like.
- (21) Light guide 1 includes a plurality of light controllers 11, emission surface 12, light guide surface 13, and side surface 14. Note that, in the following description, in a case where an orthogonal coordinate system of an X-axis, a Y-axis, and a Z-axis is used, a right-handed XYZ orthogonal coordinate system in which a normal direction of emission surface 12 is a Z-axis plus direction and a normal direction of side surface 14 is an X-axis plus direction is used.

(22) The plurality of light controllers **11** are disposed side by side in a first direction intersecting optical axis **16** of light controller **11**. In the example illustrated in FIGS. **1** and **2**, the first direction is an X-axis direction. First light sources **2** and second light sources **3** are alternately disposed along the X-axis direction. Light emitted from at least one of first light sources **2** and second light sources **3** is incident on light controller **11**. Note that, a specific configuration of light controller **11** will be described later.

(23) As illustrated in FIG. **3**, prism **15** is provided on light guide surface **13**. Prism **15** reflects light passing through light controller **11** and passing through an inside of light guide **1** toward emission surface **12**.

(24) Emission surface **12** is disposed opposite to light guide surface **13**. Emission surface **12** emits light reflected by prism **15**.

(25) As illustrated in FIG. **2**, first light source **2** is disposed on one optical axis **16** of optical axes **16** of the plurality of light controllers **11**. Second light source **3** is disposed at a position away from optical axis **16** of light controller **11**. That is, second light source **3** is not disposed on optical axis **16** of light controller **11**.

(26) Here, second light source **3** is disposed within a range of +20% from an intermediate position between two adjacent first light sources **2** with respect to the intermediate position. More specifically, second light source **3** is disposed within a range of 20% of distance D between first light source **2** and second light source **3** with respect to the intermediate position between two adjacent first light sources **2**.

(27) In the present exemplary embodiment, second light source **3** includes the same type of light source as first light source **2**. Specifically, first light source **2** and second light source **3** are white LEDs. Note that, second light source **3** may be a light source different from first light source **2**. For example, second light source **3** may include an LED having a color different from that of first light source **2** or an LED having a spreading angle different from that of first light source **2**.

(28) As illustrated in FIG. **3**, in surface light-emitting device **10**, light is emitted from at least one of first light source **2** and second light source **3** toward light controller **11**. Light having passed through light controller **11** is totally reflected by emission surface **12** and light guide surface **13**, and propagates in light guide **1**.

(29) As illustrated in FIGS. **4** and **5**, surface light-emitting device **10** is used as a backlight of display device **20**. Display device **20** includes surface light-emitting device **10**, housing **21**, and liquid crystal panel **25**.

(30) Housing **21** houses surface light-emitting device **10** and liquid crystal panel **25**. Housing **21** is supported by support base **22**. Note that, display device **20** may not include support base **22**. Liquid crystal panel **25** is disposed on emission surface **12** side of light guide **1** in surface light-emitting device **10**. Liquid crystal panel **25** is disposed toward a user.

(31) As illustrated in FIG. **2**, controller **5** is connected to control board **4** on which first light source **2** and second light source **3** are implemented. Controller **5** controls turn-on operations of first light source **2** and second light source **3**. Controller **5** switches between a narrow angle light distribution and a wide angle light distribution by turning on at least one of first light source **2** and second light source **3**. An example of controller **5** is a processor that controls the turn-on operations of first light source **2** and second light source **3**.

(32) (About Narrow Angle Light Distribution)

(33) Hereinafter, means for forming the narrow angle light distribution will be described.

(34) As illustrated in FIG. **6**, light controller **11** constitutes an incident lens. Light controller **11** includes primary incident surface **111**, secondary incident surface **112**, and secondary incident surface **113**.

(35) First light source **2** is disposed on optical axis **16** of light controller **11**. Second light source **3** is not disposed on optical axis **16** of light controller **11**.

(36) Primary incident surface **111** is disposed opposite to first light source **2**. Secondary incident

surface **112** and secondary incident surface **113** are directed to a normal line of primary incident surface **111**. Secondary incident surface **112** and secondary incident surface **113** are positioned in at least a part around primary incident surface **111**.

(37) Here, for example, in a case where primary incident surface **111** has a dome shape, the normal line of primary incident surface **111** is the normal line of primary incident surface **111** at a distal end (vertex of the dome). In the example illustrated in FIG. **6**, the normal line of primary incident surface **111** coincides with optical axis **16** of light controller **11**.

(38) Primary incident surface **111** converts light emitted from optical axis **16** of first light source **2** into light substantially parallel to the Y-axis on an XY plane.

(39) Light controller **11** further includes outer peripheral surface **114** and outer peripheral surface **115**.

(40) Outer peripheral surface **114** is positioned on a side opposite to the normal line of primary incident surface **111** as viewed from secondary incident surface **112**. Outer peripheral surface **114** totally reflects light emitted from on optical axis **16** of first light source **2** and incident on light controller **11** from secondary incident surface **112** to convert the light into light substantially parallel to the Y-axis on the XY plane.

(41) Outer peripheral surface **115** is positioned on a side opposite to the normal line of primary incident surface **111** as viewed from secondary incident surface **113**. Outer peripheral surface **115** totally reflects light emitted from on optical axis **16** of first light source **2** and incident on light controller **11** from secondary incident surface **113** to convert the light into light substantially parallel to the Y-axis on the XY plane.

(42) Note that, the term “substantially parallel” in the present exemplary embodiment means that an angle falls within a range of about several degrees (for example, less than 10 degrees).

(43) The light emitted from first light source **2** is converted into substantially parallel light with respect to the Y-axis on the XY plane by light controller **11**, and is incident on the inside of light guide **1**. Thus, the light reflected from prism **15** toward emission surface **12** is also substantially parallel to the Z-axis on the XZ plane.

(44) As described above, the light emitted from light guide **1** can form the narrow angle light distribution substantially parallel to the Z-axis on the XZ plane.

(45) (About Wide Angle Light Distribution)

(46) Hereinafter, means for forming the wide angle light distribution will be described.

(47) As illustrated in FIG. **7**, the light emitted from second light source **3** not disposed on optical axis **16** of light controller **11** enters light guide **1** from primary incident surface **111**, secondary incident surface **112**, secondary incident surface **113**, outer peripheral surface **114**, and outer peripheral surface **115**.

(48) Primary incident surface **111**, secondary incident surface **112**, secondary incident surface **113**, outer peripheral surface **114**, and outer peripheral surface **115** have shapes that convert light on optical axis **16** of light controller **11** into substantially parallel light. Thus, most of the light from second light source **3** disposed outside optical axis **16** of light controller **11** is not converted into substantially parallel, and spreads inside light guide **1** on the XY plane. As a result, the light reflected from prism **15** toward emission surface **12** also becomes light spreading with respect to the Z-axis on the XZ plane.

(49) The turn-on operations of first light source **2** for the narrow angle light distribution and second light source **3** for the wide angle light distribution are combined, and thus, the light emitted from light guide **1** can form a wide angle light distribution having a certain range of spread with respect to the Z-axis on the XZ plane.

(50) (About Combination of Narrow Angle Light Distribution and Wide Angle Light Distribution)

(51) Next, the combination of the turn-on operations of first light source **2** for the narrow angle light distribution and second light source **3** for the wide angle light distribution will be described. In the following FIGS. **8** to **10**, a light intensity angle distribution when light guide **1** is viewed

from emission surface **12** side is illustrated.

(52) FIG. **8** is a diagram illustrating a light intensity angle distribution in a case where only first light source **2** for the narrow angle light distribution is turned on. A horizontal axis indicates the spread of the light emitted from light guide **1** in an XZ plane, and a vertical axis indicates the spread of the light emitted from light guide **1** in a YZ plane.

(53) As illustrated in FIG. **8**, when the spread of the light is defined as a half width that is 50% of a peak value, the light distribution has a spread of ± 15 degrees.

(54) Note that, although light controller **11** is designed to convert light emitted from optical axis **16** into substantially parallel light, since actual first light source **2** has a certain size of the light-emitting surface, light emitted from other than optical axis **16** cannot be converted into substantially parallel light, and the spread of the emitted light increases in accordance with the size of the light-emitting surface of the light source.

(55) FIG. **9** is a diagram illustrating the light intensity angle distribution in a case where only second light source **3** for the wide angle light distribution is turned on. A horizontal axis indicates the spread of the light emitted from light guide **1** in an XZ plane, and a vertical axis indicates the spread of the light emitted from light guide **1** in a YZ plane.

(56) As illustrated in FIG. **9**, when the spread of the light is defined as a half width that is 50% of a peak value, the light distribution has a spread of ± 60 degrees.

(57) FIG. **10** is a diagram illustrating the light intensity angle distribution in a case where first light source **2** and second light source **3** are simultaneously turned on. A horizontal axis indicates the spread of the light emitted from light guide **1** in an XZ plane, and a vertical axis indicates the spread of the light emitted from light guide **1** in a YZ plane.

(58) As illustrated in FIG. **10**, when the spread of the light is defined as a half width that is 50% of a peak value, the light distribution has a spread of ± 45 degrees.

(59) As described above, the narrow angle light distribution and the wide angle light distribution of light guide **1** can be switched by switching between a case where only first light source **2** is turned on and a case where first light source **2** and second light source **3** are simultaneously turned on.

First Modified Example of Exemplary Embodiment

(60) As illustrated in FIG. **11**, the spread of the light distribution may be changed by adjusting light amounts of first light source **2** for the narrow angle light distribution and second light source **3** for the wide angle light distribution.

(61) FIG. **11** is a diagram illustrating the light intensity angle distribution in a case where the light amount of second light source **3** for the wide angle light distribution is smaller than the light amount of first light source **2** for the narrow angle light distribution.

(62) Here, as illustrated in FIG. **10** described above, in a case where the light amount of second light source **3** with respect to the light amount of first light source **2** is not adjusted, in a case where light intensity at 0 degrees in a horizontal direction is 100%, light intensity at 30 degrees in the horizontal direction is about 50%.

(63) On the other hand, as illustrated in FIG. **11**, in a case where the light amount of second light source **3** is adjusted to be smaller than the light amount of first light source **2**, in a case where light intensity at 0 degrees in a horizontal direction is set to 100%, light intensity at 30 degrees in the horizontal direction can be about 30%.

Second Modified Example of Exemplary Embodiment

(64) As illustrated in FIGS. **12** and **13**, a shape of light controller **11** may be changed.

(65) Light controller **11** includes primary incident surface **111**, secondary incident surface **112**, secondary incident surface **113**, outer peripheral surface **114**, and outer peripheral surface **115**.

(66) Primary incident surface **111** is formed to have a curvature in a Z-axis direction. Specifically, primary incident surface **111** is formed in a convex lens shape curved to protrude toward first light source **2**.

(67) Secondary incident surface **112** and secondary incident surface **113** are formed to have

curvature in the Z-axis direction. Specifically, secondary incident surface **112** and secondary incident surface **113** are formed in a shape curved to protrude toward first light source **2**.

(68) outer peripheral surface **114** and outer peripheral surface **115** are formed to have curvature in the Z-axis direction. Specifically, outer peripheral surface **114** and outer peripheral surface **115** are formed in a shape curved to protrude toward second light source **3**.

(69) With such a configuration, the light emitted from first light source **2** and second light source **3** is condensed by light controller **11**, and the spread of the light on the YZ plane in light guide **1** can be controlled.

Third Modified Example of Exemplary Embodiment

(70) As illustrated in FIG. **14**, the shape of light controller **11** may be changed.

(71) Light controller **11** includes primary incident surface **111**, secondary incident surface **112**, secondary incident surface **113**, outer peripheral surface **114**, and outer peripheral surface **115**. Note that, in the example illustrated in FIG. **14**, only primary incident surface **111** will be described.

(72) Primary incident surface **111** is formed to have a curvature in a Z-axis direction. Specifically, primary incident surface **111** is formed in a concave lens shape that is curved and recessed with respect to first light source **2**.

(73) With such a configuration, the light emitted from first light source **2** and second light source **3** is diverged in light controller **11**, and the spread of the light on the YZ plane in light guide **1** can be controlled.

(74) Note that, secondary incident surface **112**, secondary incident surface **113**, outer peripheral surface **114**, and outer peripheral surface **115** may be similarly formed in concave lens shapes.

Fourth Modified Example of Exemplary Embodiment

(75) As illustrated in FIGS. **15** and **16**, light guide **1** may include direct optical path L in which the light incident from light controller **11** is directly reflected by prism **15** and is emitted from emission surface **12**.

(76) As illustrated in FIG. **15**, a multi-lens including a group of a plurality of small lenses **18** is provided on emission surface **12** of light guide **1**. In the present exemplary embodiment, each of the plurality of small lenses **18** is formed in a semi-cylindrical shape. The plurality of small lenses **18** are disposed side by side in the X-axis direction. Small lens **18** controls light distribution by refracting and diverging or converging emitted light extracted from emission surface **12**. Note that, small lens **18** may not be provided on emission surface **12**.

(77) As illustrated in FIG. **16**, the light radially spreading from first light source **2** passes through light controller **11** to become parallel light. Light controller **11** causes the light emitted from first light source **2** to be incident on incident surface **17** of light guide **1**.

(78) Emission surface **12** is a plane parallel to the XY plane. The XY plane is a plane including the X-axis and the Y-axis and is a plane orthogonal to the Z-axis. Incident surface **17** is a plane parallel to the XZ plane. The XZ plane is a plane including the X-axis and the Z-axis and is orthogonal to the Y-axis.

(79) Light guide surface **13** is not parallel to the XY plane but is a plane inclined with respect to the XY plane. Specifically, light guide surface **13** is inclined with respect to the XY plane, and becomes closer to emission surface **12** as the light guide surface **13** becomes distant from incident surface **17**. That is, emission surface **12** and light guide surface **13** are inclined to each other.

(80) A plurality of prisms **15** are provided on light guide surface **13**. Prisms **15** reflect light passing through the inside of light guide **1** toward emission surface **12**. In light guide **1**, most of the light having passed through incident surface **17** is emitted from emission surface **12** by being reflected by prism **15** without being reflected by light guide surface **13** or a portion of emission surface **12** excluding prism **15**.

(81) That is, light guide **1** includes direct optical path L along which light incident from light controller **11** is directly reflected by prisms **15** and the light is emitted as the emitted light from emission surface **12**. Accordingly, light taking efficiency can be improved.

Other Exemplary Embodiments

(82) The exemplary embodiment may have the following configuration.

(83) In the present exemplary embodiment, although the configuration in which surface light-emitting device **10** is used as the backlight of display device **20** has been described, the present invention is not limited to this mode. For example, as illustrated in FIG. **17**, surface light-emitting device **10** may be used as illumination device **30**.

(84) Illumination device **30** includes surface light-emitting device **10** and housing **31**. Surface light-emitting device **10** is accommodated in housing **31**. Illumination device **30** is embedded in ceiling **35**, for example. Emission surface **12** of light guide **1** in surface light-emitting device **10** is disposed on an indoor space side. Accordingly, illumination device **30** including surface light-emitting device **10** can be used as a downlight. Note that, illumination device **30** is not limited to be disposed in the indoor space, and may be disposed in an outdoor space.

INDUSTRIAL APPLICABILITY

(85) As described above, the present disclosure is useful for a surface light-emitting device capable of switching between narrow angle light distribution and wide angle light distribution.

REFERENCE MARKS IN THE DRAWINGS

(86) **1** light guide **2** first light source **3** second light source **5** controller **10** surface light-emitting device **11** light controller **12** emission surface **13** light guide surface **15** prism **16** optical axis **20** display device **30** illumination device **L** direct optical path

Claims

1. A surface light-emitting device comprising: a plurality of light sources; a light guide that guides light emitted from the plurality of light sources; and a controller that controls turn-on operations of the plurality of light sources, wherein the light guide includes a plurality of light controllers on which the light from the plurality of light sources are incident, a prism that reflects the light having passed through the plurality of light controllers, a light guide surface on which the prism is provided, and an emission surface that is disposed opposite to the light guide surface and emits the light reflected by the prism, when a normal direction of the emission surface is a Z-axis direction, a normal direction of a side surface of the light guide is an X-axis direction, and a direction perpendicular to the X-axis direction and the Z-axis direction is a Y-axis direction, the plurality of light controllers are arranged in a line along the X-axis direction so that an optical axis of each of the plurality of light controllers is parallel to the Y-axis direction, each of the plurality of light controllers comprises: a dome-shaped primary incident surface, a normal to a vertex of the dome-shaped primary incident surface coinciding with the optical axis; a first secondary incident surface and a second secondary incident surface provided on opposite sides of the dome-shaped primary incident surface in the X-axis direction, and the first secondary incident surface and the second secondary incident surface being directed to the normal to the vertex of the dome-shaped primary incident surface; a first outer peripheral surface provided on an opposite side of the dome-shaped primary incident surface from the first secondary incident surface in the X-axis direction; and a second outer peripheral surface provided on an opposite side of the dome-shaped primary incident surface from the second secondary incident surface in the X-axis direction, the plurality of light sources include a plurality of first light sources and a plurality of second light sources, the first light sources and the second light sources being alternately disposed along the X-axis direction, the optical axis of each of the plurality of first light sources passes through the vertex of a respective one of the dome-shaped primary incident surfaces, each of the plurality of second light sources faces one of the first outer peripheral surfaces and/or one of the second outer peripheral surfaces, and the controller is configured to turn on at least one of the first light sources or the second light sources.

2. The surface light-emitting device according to claim 1, wherein the second light sources include

a same type of light source as the first light sources.

3. The surface light-emitting device according to claim 1, wherein the light guide includes a direct optical path that directly reflects the light incident from the plurality of light controllers by the prism and emits the light from the emission surface.

4. A display device comprising the surface light-emitting device according to claim 1.

5. An illumination device comprising the surface light-emitting device according to claim 1.

6. The surface light-emitting device according to claim 1, wherein the control unit is configured to select one of: turning on only the first light sources; turning on only the second light sources; and turning on the first light sources and the second light sources simultaneously, so that a light intensity angle distribution when the light guide is viewed from a side of the emission surface can be changed between three levels.

7. The surface light emitting device according to claim 1, wherein the first outer peripheral surfaces and the second outer peripheral surfaces are each formed in a shape curved to protrude toward one of the second light sources.
