

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416929
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Rysdyk; Rolf et al.

Landing a vertical landing vehicle

Abstract

A method, apparatus, system, and computer program product for controlling landing of a vertical landing vehicle. In one illustrative example, a method controls landing of a vertical landing vehicle. A landing profile for landing the vertical landing vehicle is determined by the computer system using a third derivative of a position equation, an initial position, an initial speed, a final speed, and a touchdown point for the vertical landing vehicle. Landing of the vertical landing vehicle is controlled using the landing profile.

Inventors: Rysdyk; Rolf (Hood River, OR), Jackson; Joseph (White Salmon, WA), Decker; Jeffrey (Snowden, WA)

Applicant: Insitu, Inc. (Bingen, WA)

Family ID: 1000008819266

Assignee: The Boeing Company (Chicago, IL)

Appl. No.: 17/456834

Filed: November 29, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220197307 A1	Jun. 23, 2022

Related U.S. Application Data

us-provisional-application US 63127937 20201218

Publication Classification

Int. Cl.: G05D1/485 (20240101); G05D1/654 (20240101); G05D109/25 (20240101)

U.S. Cl.:

CPC G05D1/485 (20240101); G05D1/6545 (20240101); G05D2109/25 (20240101)

Field of Classification Search

CPC: G05D (1/485); G05D (1/6545); G05D (1/00); G08G (5/00); B64U (70/40)

USPC: 701/2-18

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
------------	-------------	---------------	----------	-----

11029709	12/2020	Stepanyan	N/A	G05D 1/1062
2009/0214080	12/2008	Hamza	382/103	G06T 7/11
2012/0265374	12/2011	Yochum	701/5	G05D 1/0607
2015/0291277	12/2014	Kubik	701/3	G05D 1/0858
2017/0212529	12/2016	Kumar	N/A	G01S 19/48
2017/0308099	12/2016	Kim	N/A	G01S 7/521
2017/0322069	12/2016	Mastrianni	N/A	B64C 25/001
2019/0061940	12/2018	Tai	N/A	B64U 50/38
2019/0215495	12/2018	Smolyanskiy	N/A	G05D 1/0094
2019/0250640	12/2018	OFlaherty et al.	N/A	N/A
2020/0012296	12/2019	Gurdan	N/A	G05D 1/0676

OTHER PUBLICATIONS

T. Rakgowa, E. K. Wong, K. S. Sim and M. E. Nia, “Minimal jerk trajectory for quadrotor VTOL procedure,” 2015 IEEE International Symposium on Robotics and Intelligent Sensors (IRIS), Langkawi, Malaysia, 2015, pp. 284-287, doi: 10.1109/IRIS.2015.7451626. (Year: 2015). cited by examiner

E. Tal and S. Karaman, “Accurate Tracking of Aggressive Quadrotor Trajectories Using Incremental Nonlinear Dynamic Inversion and Differential Flatness,” Jun. 2020, arXiv:1809.04048v2 (Year: 2020). cited by examiner

Fourth, fifth, and sixth derivatives of position—Wikipedia; captured via archive.org, Nov. 1, 2020 (Year: 2020). cited by examiner

A. Paris, B. T. Lopez and J. P. How, “Dynamic Landing of an Autonomous Quadrotor on a Moving Platform in Turbulent Wind Conditions,” 2020 IEEE International Conference on Robotics and Automation (ICRA), Paris, France, 2020, pp. 9577-9583, doi: 10.1109/ICRA40945.2020.9197081. (Year: 2020). cited by examiner

Kyriakopoulos et al., Minimum jerk for trajectory planning and control, *Robotica*, vol. 12, No. 2, Mar. 1994, pp. 109-113. cited by applicant

Mellinger et al., “Minimum snap trajectory generation and control for quadrotors,” 2011 IEEE International Conference on Robotics and Automation, May 2011, pp. 2520-2525. cited by applicant

Mueller et al., “A Computationally Efficient Motion Primitive for Quadcopter Trajectory Generation,” *IEEE Transactions on Robotics*, vol. 31, No. 6, Dec. 2015, pp. 1294-1310. cited by applicant

Extended European Search Report (EESR) dated May 6, 2022, regarding Application No. EP 21214306, 9 pages. cited by applicant

Primary Examiner: Piateski; Erin M

Assistant Examiner: Allen; Paul

Attorney, Agent or Firm: Yee & Associates, P.C.

Background/Summary

(1) This application is related to and claims the benefit of priority of provisional U.S. Patent Application Ser. No. 63/127,937 entitled “LANDING A VERTICAL LANDING VEHICLE”, filed on Dec. 18, 2020, which is hereby incorporated by reference.

BACKGROUND INFORMATION

1. Field

(1) The present disclosure relates generally to aircraft and, in particular, to vertical landing vehicles, such as vertical take-off and landing (VTOL) vehicles. Still more particularly, the present disclosure relates to a method, apparatus, and system for managing a vertical landing vehicle.

2. Background

(2) Vertical take-off and landing (VTOL) vehicles are vehicles that can take-off and land vertically. VTOL vehicles can also hover. Vertical take-off and landing vehicles can include various types of aircraft. For example, vertical take-off and landing vehicles can include fixed wing aircraft, helicopters, tiltrotors, and cyclocopters.

(3) Hybrid vertical take-off and landing vehicles can operate in multiple modes. For example, a hybrid vertical take-off and landing vehicle may also have a fixed wing enabling the hybrid vertical take-off and landing vehicle to fly for longer periods of time and cover more ground as compared to more traditional multi-rotor unmanned aerial vehicles.

(4) Landing a vertical landing vehicle, such as a vertical take-off and landing (VTOL) vehicle, can be challenging. For example, if the propulsion units are turned off too quickly or the rotors are slowed down prior to the vertical take-off and landing vehicle has landed, the vertical take-off and landing vehicle may drop straight to the ground, tilt, or drift in an undesired manner. The incidence of tilting or drifting in these situations can increase when turbulence or aerodynamic ground effects are encountered during landing.

(5) Therefore, it would be desirable to have a method and apparatus that take into account at least some of the issues discussed above, as well as other possible issues. For example, it would be desirable to have a method and apparatus that

overcome a technical problem with landing a vertical take-off and landing vehicle.

SUMMARY

(6) An example of the present disclosure provides a vertical landing system. The vertical take-off and landing system comprises a sensor system, a computer system, and a landing manager. The sensor system is configured to generate a landing signal when landing of the vertical landing vehicle is detected by the sensor system. The landing manager is located in the computer system. The landing manager is configured to determine a landing profile for landing the vertical landing vehicle using a third derivative of a position equation, an initial position, an initial speed, a final speed, and a touchdown point for the vertical landing vehicle. A jerk is reduced in landing the vertical landing vehicle at the touchdown point. The landing manager is configured to perform a set of actions when the landing signal is received from the sensor system and when the vertical landing vehicle reaches the touchdown point.

(7) Another example of the present disclosure provides a vertical landing system comprising a computer system and a landing manager in the computer system. The landing manager is configured to determine a landing profile for landing a vertical landing vehicle using a third derivative of a position equation, an initial position, an initial speed, a final speed, and a touchdown point for the vertical landing vehicle, wherein landing of the vertical landing vehicle lands at the touchdown point using the landing profile.

(8) Yet another example of the present disclosure provides a method for controlling landing of a vertical landing vehicle. A landing profile for landing the vertical landing vehicle is determined by a computer system using a third derivative of a position equation, an initial position, an initial speed, a final speed, and a touchdown point for the vertical landing vehicle. Landing of the vertical landing vehicle is controlled using the landing profile.

(9) Still another example of the present disclosure provides a computer program product for controlling landing of a vertical landing vehicle. The computer program product comprises a computer-readable storage media with first program code and second program code stored on the computer-readable storage media. The first program code is executable by a computer system to cause the computer system to determine a landing profile for landing the vertical landing vehicle using a third derivative of a position equation, an initial position, an initial speed, a final speed, and a touchdown point for the vertical landing vehicle. The second first program code is executable by the computer system to cause the computer system to control landing of the vertical landing vehicle using the landing profile.

(10) The features and functions can be achieved independently in various examples of the present disclosure or may be combined in yet other examples in which further details can be seen with reference to the following description and drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The novel features believed characteristic of the illustrative examples are set forth in the appended claims. The illustrative examples, however, as well as a preferred mode of use, further objectives and features thereof, will best be understood by reference to the following detailed description of an illustrative example of the present disclosure when read in conjunction with the accompanying drawings, wherein:

(2) FIG. 1 is a pictorial representation of a network of data processing systems in which illustrative examples may be implemented;

(3) FIG. 2 is a block diagram of a landing environment in accordance with an illustrative example;

(4) FIG. 3 is an illustration of a control system for controlling landing of an aircraft in accordance with an illustrative example;

(5) FIG. 4 is an illustration of a block diagram of a control model in accordance with an illustrative example;

(6) FIG. 5 is an illustration of trajectories in a landing profile for a vertical take-off and landing vehicle in accordance with an illustrative example;

(7) FIG. 6 is an illustration of a flowchart of a process for controlling landing of a vertical take-off and landing vehicle in accordance with an illustrative example;

(8) FIG. 7 is another illustration of a flowchart of a process for controlling landing of a vertical take-off and landing vehicle in accordance with an illustrative example;

(9) FIG. 8 is yet another illustration of a flowchart of a process for controlling landing of a vertical take-off and landing vehicle in accordance with an illustrative example;

(10) FIG. 9 is an illustration of a process for determining a landing profile in accordance with an illustrative example;

(11) FIG. 10 is an illustration of a process for controlling landing of a vertical take-off and landing vehicle in accordance with an illustrative example;

(12) FIG. 11 is an illustration of a flowchart of a process for controlling landing of a vertical take-off and landing vehicle in accordance with an illustrative example;

(13) FIG. 12 is an illustration of a block diagram of a data processing system in accordance with an illustrative example;

(14) FIG. 13 is an illustration of an aircraft manufacturing and service method in accordance with an illustrative example; and

(15) FIG. 14 is an illustration of a block diagram of an aircraft in which an illustrative example may be implemented.

DETAILED DESCRIPTION

(16) The illustrative examples recognize and take into account one or more different considerations. The illustrative examples recognize and take into account that one solution involves using sensors to determine when a vertical take-off and landing vehicle has landed. For example, the illustrative examples recognize and take into account that a switch on a skid or landing gear of a vertical take-off and landing vehicle can be used to detect when the vertical take-off and landing vehicle has

contacted the ground. As another example, the illustrative examples recognize and take into account that an altimeter or global positioning system receiver can also be used to determine when the vertical take-off and landing vehicle has contacted the ground.

(17) The illustrative examples recognize and take into account that these and other types of sensors can be used to measure parameters such as distance from the ground, weight on wheels, the delta between a commanded movement and a detected movement, and other suitable parameters. The illustrative examples recognize and take into account that each of these parameters and other parameters can be detected using a number of different types of sensors.

(18) The illustrative examples recognize and take into account that measuring parameters from different types of sensors provides independent sources of information to detect a landing of a vertical take-off and landing vehicle. The illustrative examples also recognize and take into account that one or more of these sources of information detected by a sensor system can be used in conjunction with a control process.

(19) The illustrative examples recognize and take into account that the control process that implements a landing profile based on reducing jerk can be used in addition to or in place of information from the sensor system to determine when the vertical take-off and landing vehicle has landed.

(20) In the illustrative example, jerk is felt by an object as a change in force. The jerk can be felt as an increasing or decreasing force on the object. The jerk is also known as a jolt, surge, or lurch and is a rate of change in acceleration. This rate of change in acceleration is a third derivative of a position equation.

(21) Thus, a method, apparatus, system, and computer program product can control a landing of a vertical take-off and landing vehicle. In one illustrative example, the landing can be controlled to provide smooth motion for movement of the vertical take-off and landing vehicle to a touchdown point. The touchdown point is a location where the vertical take-off and landing vehicle is to land. In one illustrative example, the smooth motion can be provided using a minimum jerk profile. This profile can be developed through solving an optimal control problem in the illustrative example.

(22) With reference now to the figures and, in particular, with reference to FIG. 1, a pictorial representation of a network of data processing systems is depicted in which illustrative examples may be implemented. Network data processing system **100** is a network of computers in which the illustrative examples may be implemented. Network data processing system **100** contains network **102**, which is the medium used to provide communications links between various devices and computers connected together within network data processing system **100**. Network **102** may include connections, such as wire, wireless communication links, or fiber optic cables.

(23) In the depicted example, server computer **104** and server computer **106** connect to network **102** along with storage unit **108**. In addition, client devices **110** connect to network **102**. As depicted, client devices **110** include vertical take-off and landing (VTOL) vehicle **112**, vertical take-off and landing (VTOL) vehicle **114**, client computer **116**, and vertical take-off and landing (VTOL) vehicle **118**. Client devices **110** can be, for example, vehicles, cars, vertical take-off and landing vehicles, aircraft, spacecraft, computers, workstations, or network computers. In the depicted example, server computer **104** provides information, such as boot files, operating system images, and applications to client devices **110**. Further, client devices **110** can also include other types of client devices such as tablet computer **120** and smart glasses **122**. In this illustrative example, server computer **104**, server computer **106**, storage unit **108**, and client devices **110** are network devices that connect to network **102** in which network **102** is the communications media for these network devices. Some or all of client devices **110** may form an Internet-of-things (IoT) in which these physical devices can connect to network **102** and exchange information with each other over network **102**.

(24) Client devices **110** are clients to server computer **104** in this example. Network data processing system **100** may include additional server computers, client computers, and other devices not shown. Client devices **110** connect to network **102** utilizing at least one of wired, optical fiber, or wireless connections.

(25) Program code located in network data processing system **100** can be stored on a computer-recordable storage media and downloaded to a data processing system or other device for use. For example, program code can be stored on a computer-recordable storage media on server computer **104** and downloaded to client devices **110** over network **102** for use on client devices **110**.

(26) In the depicted example, network data processing system **100** is the Internet with network **102** representing a worldwide collection of networks and gateways that use the Transmission Control Protocol/Internet Protocol (TCP/IP) suite of protocols to communicate with one another. At the heart of the Internet is a backbone of high-speed data communication lines between major nodes or host computers consisting of thousands of commercial, governmental, educational, and other computer systems that route data and messages. Of course, network data processing system **100** also may be implemented using a number of different types of networks. For example, network **102** can be comprised of at least one of the Internet, an intranet, a local area network (LAN), a metropolitan area network (MAN), or a wide area network (WAN). FIG. 1 is intended as an example, and not as an architectural limitation for the different illustrative examples.

(27) In this illustrative example, vertical take-off and landing (VTOL) vehicle **112**, vertical take-off and landing (VTOL) vehicle **114**, and vertical take-off and landing (VTOL) vehicle **118** connect to network **102** using wireless communications links when moving or flying. Vertical take-off and landing (VTOL) vehicle **112**, vertical take-off and landing (VTOL) vehicle **114**, and vertical take-off and landing (VTOL) vehicle **118** can switch to using wired communications links to connect to network **102** after landing.

(28) As used herein, a “number of,” when used with reference to items, means one or more items. For example, a “number of different types of networks” is one or more different types of networks.

(29) Further, the phrase “at least one of,” when used with a list of items, means different combinations of one or more of the listed items can be used, and only one of each item in the list may be needed. In other words, “at least one of” means any

combination of items and number of items may be used from the list, but not all of the items in the list are required. The item can be a particular object, a thing, or a category.

(30) For example, without limitation, “at least one of item A, item B, or item C” may include item A, item A and item B, or item B. This example also may include item A, item B, and item C or item B and item C. Of course, any combinations of these items can be present. In some illustrative examples, “at least one of” can be, for example, without limitation, two of item A; one of item B; and ten of item C; four of item B and seven of item C; or other suitable combinations.

(31) In this illustrative example, vertical take-off and landing (VTOL) vehicle **112**, vertical take-off and landing (VTOL) vehicle **114**, and vertical take-off and landing (VTOL) vehicle **118** can take-off and land vertically. In one illustrative example, landing these vertical take-off and landing (VTOL) vehicles can be controlled in a manner that provides a desired landing even when at least one of turbulence or ground effects are encountered during landing.

(32) For example, actions such as reducing power to the propulsion system, turning off the propulsion system, or other landing actions may be performed when vertical take-off and landing (VTOL) vehicle **112** has landed. Performing these actions after landing can reduce issues such as tilting, a hard landing, or drifting.

(33) In this illustrative example, sensor system **130** in vertical take-off and landing (VTOL) vehicle **112** and landing profile **132** for vertical take-off and landing (VTOL) vehicle **112** can be used to determine when vertical take-off and landing (VTOL) vehicle **112** has landed. Sensor system **130** can generate a landing signal when sensor system **130** detects landing of vertical take-off and landing (VTOL) vehicle **112**.

(34) Additionally, vertical take-off and landing (VTOL) vehicle **112** reaching a touchdown position identified in a landing profile can also be an indication that vertical take-off and landing (VTOL) vehicle **112** has landed. Both sensor system **130** and landing profile **132** can be used as independent sources for determining when vertical take-off and landing (VTOL) vehicle **112** has landed.

(35) As depicted, sensor system **130** can be, for example, a switch on a landing gear or an accelerometer for vertical take-off and landing (VTOL) vehicle **112**. Landing profile **132** can be determined in a manner that reduces jerk when vertical take-off and landing (VTOL) vehicle **112** descends to a touchdown point.

(36) In this illustrative example, landing profile **132** is a profile comprising a set of trajectories that can be followed to land vertical take-off and landing (VTOL) vehicle **112**. For example, landing profile **132** can include a speed trajectory, an acceleration trajectory, or some other curve profile that can be used to operate vertical take-off and landing (VTOL) vehicle **112** to land at a touchdown point.

(37) Landing profile **132** can be determined using a third derivative of the position equation that reduces the jerk when vertical take-off and landing (VTOL) vehicle **112** reaches the touchdown point. In this illustrative example, the touchdown point is the position where vertical take-off and landing (VTOL) vehicle **112** has landed on a surface.

(38) In another illustrative example, vertical take-off and landing (VTOL) vehicle **114** does not calculate a landing profile. Instead, landing profile **134** for vertical take-off and landing (VTOL) vehicle **114** can be determined by server computer **104**. Server computer **104** can send landing profile **134** to vertical take-off and landing (VTOL) vehicle **114** over network **102**. In this example, vertical take-off and landing (VTOL) vehicle **114** has determined that vertical take-off and landing (VTOL) vehicle **114** has landed using both sensor system **136** and landing profile **134** received from server computer **104**.

(39) For example, vertical take-off and landing (VTOL) vehicle **114** can determine that it has landed when sensor system **136** generates a landing signal, and vertical take-off and landing (VTOL) vehicle **114** determines that it has reached the touchdown point in landing profile **134**.

(40) In another illustrative example, landing profile **138** for vertical take-off and landing (VTOL) vehicle **118** can be determined by client computer **116**. In this illustrative example, client computer **116** can send commands **140** to control movement of vertical take-off and landing (VTOL) vehicle **118** to move to the touchdown point in landing profile **138**.

(41) In this depicted example, landing profile **138** is not sent to vertical take-off and landing (VTOL) vehicle **118**. Instead, commands **140** are sent to vertical take-off and landing (VTOL) vehicle **118** to control movement of vertical take-off and landing (VTOL) vehicle **118**. Further, in this depicted example, a sensor system may not be used to determine when vertical take-off and landing (VTOL) vehicle **118** has landed. Instead, the determination of when vertical take-off and landing (VTOL) vehicle **118** has landed can be made when vertical take-off and landing (VTOL) vehicle **118** reaches the touchdown point in landing profile **138**.

(42) In all three examples, the movement of the vertical take-off and landing (VTOL) vehicles is controlled using the landing profiles, directly or indirectly. Further, the use of sensor systems to generate a landing signal provides an additional independent source of determining when a vertical take-off and landing (VTOL) vehicle has landed in addition to using a landing profile. As a result, sensor systems can enable verification or increased accuracy in determining when a vertical take-off and landing (VTOL) vehicle has landed. In other words, with multiple sources for determining when vertical take-off and landing (VTOL) vehicles have landed, the confidence when landing has occurred increases.

(43) With reference now to FIG. 2, a block diagram of a landing environment is depicted in accordance with an illustrative example. In this illustrative example, landing environment **200** includes components that can be implemented in hardware such as the hardware shown in network data processing system **100** in FIG. 1.

(44) In landing environment **200**, vertical take-off and landing system **202** can operate to manage the landing of vertical take-off and landing vehicle **204**. In this illustrative example, vertical take-off and landing vehicle **204** can take a number of different forms. For example, vertical take-off and landing vehicle **204** can be selected from one of a tiltrotor vehicle, a rotorcraft, a helicopter, a gyrodyne, a gyroplane, a tilt jet vertical take-off and landing aircraft, a direct-lift thrust vectoring aircraft, a tilt wing aircraft, and other aircraft that are capable of taking off and landing vertically.

(45) Further, vertical take-off and landing vehicle **204** can be piloted, remotely piloted, or an autonomous aircraft. When

piloted or remotely piloted, management of landing can be performed as part of an autopilot or other automatic landing system for vertical take-off and landing vehicle **204**.

(46) In this illustrative example, vertical take-off and landing system **202** includes a number of different components. As depicted, vertical take-off and landing system **202** comprises computer system **206** and landing manager **208**. In this illustrative example, landing manager **208** is located in computer system **206**.

(47) Landing manager **208** can be implemented in software, hardware, firmware, or a combination thereof. When software is used, the operations performed by landing manager **208** can be implemented in program code configured to run on hardware, such as a processor unit. When firmware is used, the operations performed by landing manager **208** can be implemented in program code and data and stored in persistent memory to run on a processor unit. When hardware is employed, the hardware can include circuits that operate to perform the operations in landing manager **208**.

(48) In the illustrative examples, the hardware can take a form selected from at least one of a circuit system, an integrated circuit, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware configured to perform a number of operations. With a programmable logic device, the device can be configured to perform the number of operations. The device can be reconfigured at a later time or can be permanently configured to perform the number of operations. Programmable logic devices include, for example, a programmable logic array, a programmable array logic, a field programmable logic array, a field programmable gate array, and other suitable hardware devices. Additionally, the processes can be implemented in organic components integrated with inorganic components and can be comprised entirely of organic components excluding a human being. For example, the processes can be implemented as circuits in organic semiconductors.

(49) Computer system **206** is a physical hardware system and includes one or more data processing systems. When more than one data processing system is present in computer system **206**, those data processing systems are in communication with each other using a communications medium. The communications medium can be a network. The data processing systems can be selected from at least one of a computer, a server computer, a tablet computer, or some other suitable data processing system.

(50) In this illustrative example, landing manager **208** in computer system **206** is configured to determine landing profile **210** for landing vertical take-off and landing vehicle **204** using third derivative **212** of position equation **214**, initial position **216**, initial speed **218**, final speed **220**, and touchdown point **222** for vertical take-off and landing vehicle **204**. In this illustrative example, landing profile **210** can also be referred to as a descend profile. In this illustrative example, landing profile **210** can define position, speed, acceleration, and jerk over time.

(51) In this example, landing profile **210** is determined in a manner that jerk **224** is reduced in landing vertical take-off and landing vehicle **204** at touchdown point **222**. In this illustrative example, the reduction of jerk **224** can be, for example, reducing jerk **224** to at least one of minimum jerk **226** or desired level **228** of jerk **224**.

(52) In this illustrative example, position equation **214** is an equation that describes the position of vertical take-off and landing vehicle **204** over time. In this illustrative example, position equation **214** can be a fifth order equation. A fifth order equation is also known as a fifth degree polynomial. The fifth order equation can also be referred to as a quintic polynomial in this example. In this illustrative example, the position of vertical take-off and landing vehicle **204** is described in three dimensions. For example, the position of vertical take-off and landing vehicle **204** can be described using latitude, longitude, and altitude.

(53) In this illustrative example, initial position **216** is the position of vertical take-off and landing vehicle **204** at the beginning of calculations to determine landing profile **210**. Touchdown point **222** is the position of vertical take-off and landing vehicle **204** when vertical take-off and landing vehicle **204** reaches the final position, which is when vertical take-off and landing vehicle **204** has landed in this illustrative example.

(54) Initial speed **218** can be the speed of vertical take-off and landing vehicle **204** at the time when landing profile **210** is determined. Final speed **220** is the speed of vertical take-off and landing vehicle **204** when touchdown point **222** is reached. In this illustrative example, speed is the magnitude in the change of the position of vertical take-off and landing vehicle **204**. Speed is a scalar quantity. In some illustrative examples, a direction such as a negative or positive sign can be associated with speed to form a velocity for vertical take-off and landing vehicle **204**. In other words, speed can be the magnitude component of velocity.

(55) Landing manager **208** is configured to perform a set of actions **230** when landing signal **234** is received from sensor system **232** and when vertical take-off and landing vehicle **204** reaches touchdown point **222**. In this illustrative example, the set of actions **230** can be selected from at least one of turning off a propulsion system for vertical take-off and landing vehicle **204**, indicating that vertical take-off and landing vehicle **204** has landed, or some other suitable action.

(56) As depicted, sensor system **232** can be a part of vertical take-off and landing system **202**. Vertical take-off and landing system **202** operates as a high integrity touchdown detection system in which landing of vertical take-off and landing vehicle **204** can be detected with a desired level of confidence.

(57) In this example, sensor system **232** is configured to detect a landing of vertical take-off and landing vehicle **204**. In this illustrative example, sensor system **232** generates landing signal **234** when the landing of vertical take-off and landing vehicle **204** is detected by sensor system **232**.

(58) In this illustrative example, sensor system **232** is a hardware system and can include software. As depicted, sensor system **232** is comprised of a set of sensors **233**. The set of sensors **233** can be selected from at least one of a switch on a skid or landing gear on vertical take-off and landing vehicle **204**, an altitude sensor, an altimeter, a global positioning system receiver, an accelerometer, a camera system, an electromechanical sensing device, an ultrasonic sensor, a light detection and ranging system, or some other suitable type of sensor.

(59) Further, sensor system **232** can be located inside of vertical take-off and landing vehicle **204**, at a remote location, or a

combination of the two. In this illustrative example, sensors **233** in sensor system **232** can include redundant sensors to increase the integrity or accuracy at which landing of vertical take-off and landing vehicle **204** can be detected.

(60) For example, sensor system **232** includes a light detection and ranging system which can be located in a vertiport or other type of landing pattern location. Another portion of sensor system **232** can be an accelerometer located in the landing gear of vertical take-off and landing vehicle **204**. In yet other illustrative examples, another accelerometer can be located on a landing pad in addition to or in place of using an accelerometer on the landing gear of vertical take-off and landing vehicle **204**.

(61) In this illustrative example, the detection of vertical take-off and landing vehicle **204** reaching touchdown point **222** can also be determined using a sensor. In this illustrative example, the sensor can be a different type of sensor from the sensor used in sensor system **232** to determine the landing of vertical take-off and landing vehicle **204**. For example, reaching touchdown point **222** can be made using a global positioning system receiver while determining the landing of vertical take-off and landing vehicle **204** can be determined using an altitude sensor or a switch.

(62) In this manner, independent or different sources of information can be used to increase the confidence in determining when vertical take-off and landing vehicle **204** has landed. In this example, landing signal **234** provides additional confirmation that vertical take-off and landing vehicle has landed in addition to determining that touchdown point **222** and landing profile **210** have been reached.

(63) In addition to performing the set of actions **230** when vertical take-off and landing vehicle **204** has landed, landing manager **208** can also control operation of vertical take-off and landing vehicle **204** as part of the landing process. For example, landing manager **208** can control the landing of vertical take-off and landing vehicle **204** using landing profile **210**.

(64) In controlling the landing, landing manager **208** can send a set of commands **236** to controller **238** for vertical take-off and landing vehicle **204**. As depicted, commands **236** can cause controller **238** to control vertical take-off and landing vehicle **204** to follow landing profile **210** to land vertical take-off and landing vehicle **204** at touchdown point **222**. Controller **238** can be located in vertical take-off and landing vehicle **204**. Controller **238** can be hardware, software, or combination of the two. Controller **238** can be, for example, an autopilot, an autonomous flight management system, or some other suitable component that controls the landing of vertical take-off and landing vehicle **204**.

(65) In this illustrative example, landing profile **210** can be compared to actual landing profile **240**. This comparison can be used to make adjustments in the landing of vertical take-off and landing vehicle **204**. For example, commands **236** can be sent to adjust the landing of vertical take-off and landing vehicle **204**.

(66) In one illustrative example, one or more technical solutions are present that overcome a technical problem with landing a vertical take-off and landing vehicle. As a result, one or more technical solutions can provide a technical effect of enabling landing of vertical take-off and landing vehicle **204** in a desired manner. In one illustrative example, one or more technical solutions are present that provide a technical effect of performing actions when vertical take-off and landing vehicle **204** has actually landed.

(67) Computer system **206** can be configured to perform at least one of the steps, operations, or actions described in the different illustrative examples using software, hardware, firmware, or a combination thereof. As a result, computer system **206** operates as a special purpose computer system in which landing manager **208** in computer system **206** enables determining a landing profile that can be used to land vertical take-off and landing vehicle **204**. Further, when receiving landing signal **234** from sensor system **232**, a further confirmation or verification of the landing of vertical take-off and landing vehicle **204** can be determined by computer system **206** with landing manager **208**. In particular, landing manager **208** transforms computer system **206** into a special purpose computer system as compared to currently available general computer systems that do not have landing manager **208**.

(68) Turning next to FIG. **3**, an illustration of a control system for controlling landing of an aircraft is depicted in accordance with an illustrative example. In the illustrative examples, the same reference numeral may be used in more than one figure. This reuse of a reference numeral in different figures represents the same element in the different figures.

(69) In this illustrative example, landing manager **208** and controller **238** form a control system with feedback loop **300**. As depicted, inputs **302** include final speed **304** and final position **306**. These inputs are the desired parameters for landing vertical take-off and landing vehicle **204** in FIG. **2**. Inputs **302** also include initial position **216**, initial speed **218**, and initial acceleration **312** in this example. These inputs are measured at the beginning of the process performed by landing manager **208** to determine commands **236**.

(70) With these inputs, landing manager **208** can output commands **236**. In this example, commands **236** are sent to controller **238**. In this example, commands **236** can include commanded position **314**, commanded speed **316**, and commanded acceleration **318**. Controller **238** can control vertical take-off and landing vehicle **204** using commands **236**.

(71) Further, controller **238** can measure position **320**, speed **322**, and acceleration **324** which form data in feedback loop **300**. These parameters are used as initial position **216** and initial speed **218** in FIG. **2**. In some illustrative examples, initial acceleration **312** may also be present. When initial acceleration **312** is present, acceleration **324** is also measured and returned in feedback loop **300**.

(72) Landing manager **208** can generate new commands for commands **236**. The recalculated form of commands **236** are current commands that are sent to controller **238** for controlling the landing of vertical landing take-off and landing vehicle **204** in FIG. **2** using the current commands.

(73) Turning now FIG. **4**, an illustration of a block diagram of a control model is depicted in accordance with an illustrative example. In this depicted example, control model **400** is an example of a model that can be used in landing manager **208** to generate at least one of landing profile **210** or commands **236** to control the landing of vertical take-off and landing vehicle **204** in FIG. **2**.

(74) As depicted, inputs **402** into control model **400** comprise $x_{sub.0}$, $V_{sub.0}$, $\{\text{umlaut over (x)}\}_{sub.0}$, $V_{sub.f}$, and $x_{sub.f}$.

Outputs **404** from control model **400** comprise x , $\{\dot{x}\}$, and $\{\ddot{x}\}$.

(75) In this illustrative example, $x_{\text{sub.f}}$ is the touchdown point, and $V_{\text{sub.f}}$ is the final velocity. The velocity is speed with a sign indicating direction. These two parameters can be set as a desired touchdown point and landing speed for vertical take-off and landing vehicle **204** in FIG. 2. In this illustrative example, $x_{\text{sub.0}}$ is the initial position, $V_{\text{sub.0}}$ is the initial speed, and $\{\ddot{x}\}_{\text{sub.0}}$ is the initial acceleration.

(76) In this illustrative example, in outputs **404**, x is position, $\{\dot{x}\}$ is the velocity, $\{\ddot{x}\}$ is acceleration, and $\{\dddot{x}\}$ is jerk. In this illustrative example, the values of these parameters can be commands used to control the landing of vertical take-off and landing vehicle **204** in FIG. 2.

(77) As depicted, control model **400** comprises logic functions adder **406**, adder **408**, constant $K_{\text{sub.V.sub.f}}$ **410**, constant $K_{\text{sub.x}}$ **412**, $K_{\text{sub.}\{\dot{x}\}}$ constant **414**, and constant $K_{\text{sub.}\{\ddot{x}\}}$ **416**. Control model **400** also includes constant $1/s$ **418**, constant $1/s$ **420**, and constant $1/s$ **422**.

(78) In this illustrative example, the output of adder **408** is $\{\ddot{x}\}$; the output of constant $1/s$ **418** is $\{\ddot{x}\}$; the output of constant $1/s$ **420** is $\{\dot{x}\}$, and the output of constant **422** is x .

(79) In this illustrative example, the initial conditions in inputs **402** can be updated periodically, in response to events, or continuously in real-time. In this manner, these conditions can be used as feedback for updating commands **404** as vertical take-off and landing vehicle **204** in FIG. 2 moves towards landing on touchdown point **222** in FIG. 2. Updates to the initial conditions resulting in updates being made to the constants K gains is a function of the time remaining until touchdown for vertical takeoff and landing vehicle **204**.

(80) The illustrations of the different components in landing environment **200** in FIGS. 2-4 are not meant to imply physical or architectural limitations to the manner in which an illustrative example may be implemented. Other components in addition to or in place of the ones illustrated may be used. Some components may be unnecessary. Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be combined, divided, or combined and divided into different blocks when implemented in an illustrative example.

(81) For example, computer system **206** with landing manager **208** can be located in vertical take-off and landing vehicle **204** or at any remote location in communication with vertical take-off and landing vehicle **204**. When computer system **206** is at a location remote to vertical take-off and landing vehicle **204**, vertical take-off and landing vehicle **204** includes one or more data processing systems. The data processing systems can include a computer system, a controller, or other suitable components that can be used to autonomously control the landing of vertical take-off and landing vehicle **204**.

(82) As another example, sensor system **232** can be a separate component located outside of vertical take-off and landing system **202**. In yet another illustrative example, landing manager **208** can determine and perform actions for one or more vertical take-off and landing vehicles in addition to or in place of vertical take-off and landing vehicle **204**.

(83) With reference next to FIG. 5, an illustration of trajectories in a landing profile for a vertical take-off and landing vehicle is depicted in accordance with an illustrative example. In this illustrative example, vertical take-off and landing vehicle **500** is an example of an implementation for vertical take-off and landing vehicle **204** shown in block form in FIG. 2.

(84) As depicted, vertical take-off and landing vehicle **500** moves in the direction of arrow **502** during landing. In this illustrative example, path and velocity control occur simultaneously during an approach to a touchdown point for vertical take-off and landing vehicle **500**. In this illustrative example, Descend Rate curve **504** represents the velocity, and Distance to TDP curve **506** represents the path in this illustrative example. The path can also be referred to as the position of vertical take-off and landing vehicle **500** over time. These values for velocity and position are relative to y-axis **510** and time on x-axis **512**. These curves are shown relative to the time needed to reach a touchdown point at time of touchdown **514**.

(85) In this illustrative example, the control of the velocity and the path of take-off and landing vehicle **500** can be controlled using landing profile **516**. In this illustrative example, landing profile **516** comprises three trajectories. As depicted, landing profile **516** includes position trajectory **518**, speed trajectory **520**, and acceleration trajectory **522**.

(86) As shown, line **517** represents a position of zero for position trajectory **518**. In this example, the position of zero means that vertical take-off and landing vehicle **500** has landed on the touchdown point. Line **519** is a speed of zero for speed trajectory **520**, and line **521** is an acceleration of zero for acceleration trajectory **522**. In some cases, acceleration trajectory **522** can be omitted in controlling landing of vertical take-off and landing vehicle **500**.

(87) Landing profile **516** can be generated in a manner that minimizes jerk during the descend and deceleration phase prior to touchdown of landing vertical take-off and landing vehicle **500**. The jerk is a third derivative of a position vector with respect to time.

(88) A landing profile, such as landing profile **516**, provides the trajectory, velocity, and associated force or torque required to achieve the trajectory. In case of maneuvering a vertical take-off and landing vehicle, such as vertical take-off and landing vehicle **500**, this landing profile can be used by controller **238** in FIG. 2 to provide an estimate of the required tilt angles to decelerate into a hover condition, given an initialization point and desired touchdown point.

(89) The trajectories in the landing profile can be optimized for time or energy, with consideration of system limitations. Examples of trajectory generation can include minimization of maximum values of a state and control input, or the minimization of input energy into the system. One approach in Optimal Control Theory is to formulate a cost-function $J(z)$, which captures the desired aspect of the system to be minimized. For example, the cost-function $J(z)$ can be minimized:

(90) $J(z) = \max_{t \in [t_0, t_f]} \text{Math. } z \text{ Math.}$ which would minimize the maximum magnitude of z , where z is the parameter to be minimized.

(91) Alternatively, the overall input energy can be minimized by minimizing:

$J(z) = \int_{t_{\text{sub.f}}}^{t_{\text{sub.0}}} f_{z,\text{sup.}} 2d\tau$ where z is a function of the control signals, $t_{\text{sub.f}}$ is the time when the touchdown point is reached, and $t_{\text{sub.0}}$ is initial time.

(92) The derivative of acceleration is related to limitations of system actuation. As a result, $\ddot{z}$ can be selected to represent jerk, which is the derivative of acceleration. A minimum jerk profile is desirable for smooth motion. By formulating this as an optimal control problem, the minimum jerk trajectory can be governed by a fifth order polynomial as follows:

$x(t) = \sum_{n=0}^5 a_n (t - t_0)^n$ where n is the order, t is time, t_0 is initial time, and a_n is a constant.

(93) Given this fifth order polynomial model, the desired position $x(t)$, velocity $\dot{x}(t)$, acceleration $\ddot{x}(t)$, and jerk $\dddot{x}(t)$ are as follows:

$$x(t) = a_0 + a_1 \Delta t + a_2 \Delta t^2 + a_3 \Delta t^3 + a_4 \Delta t^4 + a_5 \Delta t^5 \quad (1)$$

$$\dot{x}(t) = a_1 + 2a_2 \Delta t + 3a_3 \Delta t^2 + 4a_4 \Delta t^3 + 5a_5 \Delta t^4 \quad (2)$$

$$\ddot{x}(t) = 2a_2 + 6a_3 \Delta t + 12a_4 \Delta t^2 + 20a_5 \Delta t^3 \quad (3)$$

$$\dddot{x}(t) = 6a_3 + 24a_4 \Delta t + 60a_5 \Delta t^2 \quad (4) \text{ where } \Delta t = t - t_0$$

is the time span since the initial condition and where t is time, t_0 is initial time, a_0 is initial position, a_1 is initial velocity, a_2 is initial acceleration. In this example, a_3 , a_4 , and a_5 can be determined from final conditions and can be related to a combination of initial and final states and the duration of the path to touchdown.

(94) In order to formulate the desired landing profile, the initial and desired final conditions are considered. With respect to initial conditions, a landing phase can start at $t = t_0$ [s] with an established descend-rate at: $V_0 = -500$ [fpm] at an altitude of $x_0 = 10$ [m] AGL, and our desired end condition is $x_f = 0$, where V_0 is the initial velocity, x_0 is initial position, x_f is the final position such as the touchdown point, and AGL is above ground level. $V_f = -200$ [fpm], and in this example, this landing phase is desired to be completed in $\Delta t_f = t_f - t_0 = 6$ [s]. In this case, these conditions determine parameters as follows: $a_0 = x(t_0)$, sets the initial position at x_0 [m] AGL; $a_1 = \dot{x}(t_0)$, descend rate at start of final descend; and $2a_2 = \ddot{x}(t_0)$, acceleration at the start of final descend.

(95) The last three parameters, a_3 , a_4 , and a_5 , can be defined by the desired conditions at touchdown. For example, a_3 , a_4 , and a_5 can be initial jerk, initial snap, and initial crackle, respectively.

(96) Final conditions can be defined for landing at the touchdown point. In this illustrative example, at touchdown, $t = t_f$, the following final conditions can be selected as follows: $x(t_f) = 0$, defines the TDP position at 0 at ground level (AGL); $\dot{x}(t_f) = -200$ [fpm], sets 200 fpm descend rate at the touchdown point (TDP) and $\ddot{x}(t_f) = 0$, specifies no further deceleration while at TDP.

(97) These final conditions can be used to solve for the remaining parameters, a_3 , a_4 , and a_5 , found in Equations (1)-(4). The remaining parameters can be determined by substituting the specified conditions in Equations (1)-(4). The desired conditions at touchdown are as follows:

$$(98) \begin{aligned} x(t_f) &= x_f = x_0 + V_0 \Delta t_f + \frac{1}{2} a_2 \Delta t_f^2 + a_3 \Delta t_f^3 + a_4 \Delta t_f^4 + a_5 \Delta t_f^5 \\ \dot{x}(t_f) &= V_f = V_0 + a_1 \Delta t_f + 3a_2 \Delta t_f^2 + 4a_3 \Delta t_f^3 + 5a_4 \Delta t_f^4 \\ \ddot{x}(t_f) &= 0 = A_0 + 6a_2 \Delta t_f + 12a_3 \Delta t_f^2 + 20a_4 \Delta t_f^3 \end{aligned}$$

where $\Delta t_f = t_f - t_0$ is the duration of the trajectory to the touchdown point.

(99) These expressions can be rearranged to determine the parameters as function of the desired behavior for the landing, as follows:

$$(100) \begin{bmatrix} a_3 \\ a_4 \\ a_5 \end{bmatrix} = M^{-1} \begin{bmatrix} -x_0 - V_0 \Delta t_f - \frac{1}{2} A_0 \Delta t_f^2 \\ V_f - V_0 - A_0 \Delta t_f \\ -A_0 \end{bmatrix} \text{ where } M(\Delta t_f) = \begin{bmatrix} \Delta t_f^3 & \Delta t_f^4 & \Delta t_f^5 \\ 3 \Delta t_f^2 & 4 \Delta t_f^3 & 5 \Delta t_f^4 \\ 6 \Delta t_f & 12 \Delta t_f^2 & 20 \Delta t_f^3 \end{bmatrix} \quad (5)$$

(101) The determination of a_0 through a_6 can be made using these equations. In this depicted example, with these parameters, desired trajectory for velocity and deceleration to the touchdown point can be determined.

(102) In this depicted example, position trajectory **518**, speed trajectory **520**, and acceleration trajectory **522** for landing profile **516** can be interpreted as 'open loop' feedforward signals. Feedback tracking errors can be detected and modifications to landing profile **516** can be made. These modifications can be made by iteratively resetting the initial conditions and determining landing profile **516** towards the same final conditions.

(103) Considering a general point in time $t = t_0$, the jerk required at that time to get to the desired final condition is as follows:

$$x^{(3)}(t_0) = 6a_3$$

(104) The inverse of M in Equation 5 is:

$$(105) M^{-1} = \begin{bmatrix} \frac{10}{\Delta t_f^3} & -\frac{4}{\Delta t_f^2} & \frac{1}{\Delta t_f} \\ -\frac{15}{\Delta t_f^2} & \frac{7}{\Delta t_f} & -\frac{1}{\Delta t_f} \\ \frac{6}{\Delta t_f} & -\frac{3}{\Delta t_f} & \frac{1}{\Delta t_f} \end{bmatrix} \text{ thus, the value of } a_3 \text{ is obtained as:}$$

$$(106) a_3 = \frac{10}{\Delta t_f^3} (x_f - x_0) - \frac{4}{\Delta t_f^2} V_f - \frac{6}{\Delta t_f} V_0 - \frac{3}{\Delta t_f} A_0$$

(107) The desired expression for the jerk at t_0 is as follows:

$$(108) x_c^{(3)}(t_0) = \frac{60}{\Delta t_f^3} (x_f - x_0) - \frac{24}{\Delta t_f^2} V_f - \frac{36}{\Delta t_f} V_0 - \frac{9}{\Delta t_f} A_0 \quad (6)$$

(109) This is now expressed in terms of the current speed, acceleration, and distance remaining. Expression (6) can be used in a model following setup to provide a guidance law to hover recovery. Expression (6) can be rewritten as follows:

$$(110) \frac{dX}{dt} = \begin{pmatrix} 0 & 1 & 0 \\ 0 & 0 & 1 \\ -K_x & -K_{\dot{x}} & -K_{\ddot{x}} \end{pmatrix} X + \begin{pmatrix} 0 \\ 0 \\ 0 \end{pmatrix} x_f + \begin{pmatrix} 0 \\ 0 \\ 0 \end{pmatrix} V_f \text{ where each gain } K=K(\Delta, \text{sub.f}) \text{ and } X \text{ custom character}(x \{ \text{dot} \\ \text{over } (x) \} \{ \text{umlaut over } (x) \}). \text{sup.T, and}$$

over (x)} {umlaut over (x)}.sup.T, and

$$(111) K_x = \frac{60}{f}, K_{\dot{x}} = \frac{36}{f}, K_{\ddot{x}} = \frac{9}{f}, K_{V_f} = \frac{24}{f} \quad (7)$$

(112) These gains can be used for K.sub.V.sub.f **410**, K.sub.x **412**, K.sub.{dot over (x)} **414**, and K.sub.{umlaut over (x)} **416** in control model **400** in FIG. 4.

(113) To prevent the singularity in Equation (7) and keep finite gain values, the time-remaining can be lower bounded $\Delta, \text{sub.f} \geq \epsilon$, where $\epsilon > 0$ can be determined ad-hoc or analytically from signal noise levels.

(114) In the illustrative example, the landing profile can be constrained by limits other than initial and final conditions as described above. For example, staying above a maximum descend rate or a limit on maximum deceleration may be desired in some cases. These goals can be achieved in generating a landing profile by, for example, implicitly limiting the minimum time span and by explicitly computing the minimal possible time span associated with the limits. The implicit method is inherent to a real-time implementation. The explicit method is based on analytically determining the minimum possible time-span that meets the stated requirements.

(115) If flexibility is present to pick the final time, such as if $\Delta, \text{sub.f}$ may be varied, when vertical take-off and landing vehicle reaches the touchdown point, additional constraints can be considered. For example, for a vertical take-off and landing approach, maximum descend rate and deceleration can be limited by a vortex-ring state in which an undesired loss in lift can occur.

(116) Limiting descend rate and deceleration can be achieved through the selection of $\Delta, \text{sub.f}$. For example, with specifying a descend rate limit $R, \text{sub.max}$ and a deceleration limit $D, \text{sub.max}$, the optimal control problem statement can be formulated as minimizing the jerk but with the added constraint of a maximum descend rate and deceleration limited as follows:

$$(117) \min_{t \in [0, t_f - t_0]} \dot{x}(t) \geq -R_{\max} \quad \min_{t \in [0, t_f - t_0]} \ddot{x}(t) \geq -D_{\max}$$

(118) Equations (1)-(4) then provide a lower limit on what $\Delta, \text{sub.f}$ can be achieved.

(119) For example, when deceleration is constrained, the minimum possible time span $\Delta, \text{sub.f}$ that keeps the vehicle within a deceleration constraint can be determined. Parameters $a, \text{sub.0}$ - $a, \text{sub.6}$ can be determined from the initial conditions and the final state. These parameters can be expressed in terms of $\Delta, \text{sub.f}$.

(120) The maximum deceleration occurs at the point-in-time where $\text{custom character}(t)=0$, that is, find $\Delta^*, \text{sub.t} = (t^* - t, \text{sub.0})$ for which:

$$x(t^*) = 6a, \text{sub.3} + 24a, \text{sub.4}\Delta^*, \text{sub.t} + 60a, \text{sub.5}\Delta, \text{sub.t}^{\text{sup.2}} = 0$$

(121) The value for $\Delta^*, \text{sub.t}$ is substituted into the expression for $\{\text{umlaut over } (x)\}(t)$ to determine the maximum deceleration as function of $\Delta, \text{sub.f}$,

$$\{\text{umlaut over } (x)\}(t^*) \text{ custom character} - D^*(\Delta, \text{sub.f})$$

(122) $\Delta, \text{sub.f}$ is selected to be large enough such that the maximum deceleration or minimum acceleration remains within the limit $D, \text{sub.max}$, that is:

$$D^*(\Delta, \text{sub.f}) \text{ Math. } D, \text{sub.max. Math. } \Delta, \text{sub.f}$$

(123) When the descend rate is constrained, a minimum descend rate can be set by selecting a minimum time-span. This minimum descent rate can be achieved by obtaining parameters $a, \text{sub.0}$ - $a, \text{sub.6}$ from the initial conditions and the required final state, as indicated above. These will be expressed in terms of $\Delta, \text{sub.f}$.

(124) In this illustrative example, the maximum descend rate occurs at the point-in-time where $\{\text{umlaut over } (x)\}(t)=0$, that is, find $\Delta, \text{sub.t}^{\text{sup.†}} = (t, \text{sup.†} - t, \text{sub.0})$ for which:

$$x(t, \text{sup.†}) = 2a, \text{sub.2} + 6a, \text{sub.3}\Delta, \text{sub.t}^{\text{sup.†}} + 12a, \text{sub.4}\Delta, \text{sub.t}^{\text{sup.†}2} + 20a, \text{sub.5}\Delta, \text{sub.t}^{\text{sup.†}3} = 0$$

(125) The value for $\Delta, \text{sub.t}^{\text{sup.†}}$ is substituted into the expression for $\{\text{dot over } (x)\}(t)$ to determine the maximum descend rate as function of $\Delta, \text{sub.f}$,

$$\{\text{umlaut over } (x)\}(t, \text{sup.†}) \text{ custom character} - R, \text{sup.†}(\Delta, \text{sub.f}) \quad \Delta, \text{sub.f} \text{ is selected to be large enough such that the maximum descend rate remains less than the lower limit } R, \text{sub.max, that is:}$$

$$R, \text{sup.†}(\Delta, \text{sub.f}) < R, \text{sub.max. Math. } \Delta, \text{sub.f}$$

(126) Turning next to FIG. 6, an illustration of a flowchart of a process for controlling landing of a vertical take-off and landing vehicle is depicted in accordance with an illustrative example. The process in FIG. 6 can be implemented in hardware, software, or both. When implemented in software, the process can take the form of program code that is run by one or more processor units located in one or more hardware devices in one or more computer systems. For example, the process can be implemented in landing manager **208** in computer system **206** in FIG. 2. In the illustrative example, landing manager **208** can be located in the vertical take-off and landing vehicle or can be in another location on a computer system in a remote location that is in communication with the vertical take-off and landing vehicle.

(127) The process begins by determining a landing profile for landing a vertical take-off and landing vehicle using a third derivative of a position equation, an initial position, an initial speed, a final speed, and a touchdown point for the vertical take-off and landing vehicle (operation **600**). The process controls landing of the vertical take-off and landing vehicle using the landing profile (operation **602**). The process terminates thereafter.

(128) With reference to FIG. 7, another illustration of a flowchart of a process for controlling landing of a vertical take-off and landing vehicle is depicted in accordance with an illustrative example. The process in FIG. 7 is an example of one implementation for operation **602** in FIG. 6.

(129) The process sends a set of commands to a controller for a vertical take-off and landing vehicle such that the set of commands causes the controller to control the vertical take-off and landing vehicle to follow the landing profile to land the vertical take-off and landing vehicle at a touchdown point (operation **700**). The process terminates thereafter.

(130) In FIG. **8**, yet another illustration of a flowchart of a process for controlling landing of a vertical take-off and landing vehicle is depicted in accordance with an illustrative example. The process in FIG. **8** is an example of one implementation for operation **602** in FIG. **6**.

(131) The process sends a landing profile to a controller for a vertical take-off and landing vehicle such that the controller uses the landing profile to control the vertical take-off and landing vehicle to follow the landing profile to land the vertical take-off and landing vehicle at a touchdown point (operation **800**). The process terminates thereafter.

(132) Turning now to FIG. **9**, an illustration process for determining a landing profile is depicted in accordance with an illustrative example. This process is an example of one implementation for operation **600** in FIG. **6**.

(133) The process determines at least one of a position trajectory, a speed trajectory, or an acceleration trajectory using the following:

$$x(t)=a_{\text{sub}.0}+a_{\text{sub}.1}(t-t_{\text{sub}.0})+a_{\text{sub}.2}(t-t_{\text{sub}.0})^2+a_{\text{sub}.3}(t-t_{\text{sub}.0})^3+a_{\text{sub}.4}(t-t_{\text{sub}.0})^4+a_{\text{sub}.5}(t-t_{\text{sub}.0})^5$$

$$\dot{x}(t)=a_{\text{sub}.1}+2a_{\text{sub}.2}(t-t_{\text{sub}.0})+3a_{\text{sub}.3}(t-t_{\text{sub}.0})^2+4a_{\text{sub}.4}(t-t_{\text{sub}.0})^3+5a_{\text{sub}.5}(t-t_{\text{sub}.0})^4$$

$$\ddot{x}(t)=2a_{\text{sub}.2}+6a_{\text{sub}.3}(t-t_{\text{sub}.0})+12a_{\text{sub}.4}(t-t_{\text{sub}.0})^2+20a_{\text{sub}.5}(t-t_{\text{sub}.0})^3$$

$\ddot{\ddot{x}}(t)=6a_{\text{sub}.3}+24a_{\text{sub}.4}(t-t_{\text{sub}.0})+60a_{\text{sub}.5}(t-t_{\text{sub}.0})^2$ where $x(t)$ is position, $\dot{x}(t)$ is velocity, $\ddot{x}(t)$ is acceleration, $\ddot{\ddot{x}}(t)$ is jerk, t is time, $t_{\text{sub}.0}$ is initial time, $a_{\text{sub}.0}$ is initial position, $a_{\text{sub}.1}$ is initial velocity, $a_{\text{sub}.2}$ is initial acceleration times $\frac{1}{2}$, $a_{\text{sub}.3}$ is initial jerk times $\frac{1}{6}$, $a_{\text{sub}.4}$ is initial snap times $\frac{1}{24}$, and $a_{\text{sub}.5}$ is initial crackle times $\frac{1}{120}$ (operation **900**). The process terminates thereafter.

(134) With reference to FIG. **10**, an illustration of a process for controlling landing of a vertical take-off and landing vehicle is depicted in accordance with an illustrative example. The process in FIG. **10** can be implemented in hardware, software, or both. When implemented in software, the process can take the form of program code that is run by one or more processor units located in one or more hardware devices in one or more computer systems. For example, the process can be implemented in landing manager **208** computer system **206** in FIG. **2**. In the illustrative example, landing manager **208** can be located in the vertical take-off and landing vehicle or can be in another location in a computer system at a remote location that is in communication with a vertical take-off and landing vehicle.

(135) The process begins by determining a landing profile for landing a vertical take-off and landing vehicle using a third derivative of a position equation, an initial position, an initial speed, a final speed, and a touchdown point for the vertical take-off and landing vehicle (operation **1000**). The process controls landing of the vertical take-off and landing vehicle using the landing profile (operation **1002**).

(136) A determination is made as to whether the vertical take-off and landing vehicle has landed (operation **1004**). If the vertical take-off and landing vehicle has not landed, the process returns to operation **1000**). Otherwise, the process terminates thereafter. In this manner, the process can repeatedly determine the landing profile for landing the vertical take-off and landing vehicle using the third derivative of the position equation, the initial position, the initial speed, the final speed, and the touchdown point for the vertical take-off and landing vehicle. The initial position is a current position of the vertical take-off and landing vehicle, and the initial speed is a current speed of the vertical take-off and landing vehicle.

(137) Turning next to FIG. **11**, an illustration of a flowchart of a process for controlling landing of a vertical take-off and landing vehicle is depicted in accordance with an illustrative example. The process in FIG. **6** can be implemented in hardware, software, or both. When implemented in software, the process can take the form of program code that is run by one or more processor units located in one or more hardware devices in one or more computer systems. For example, the process can be implemented in landing manager **208** in computer system **206** in FIG. **2**. In the illustrative example, landing manager **208** can be located in the vertical take-off and landing vehicle or can be in another location on a computer system at a remote location that is in communication with a vertical take-off and landing vehicle.

(138) The process begins by determining a landing profile for landing a vertical take-off and landing vehicle using a third derivative of a position equation, an initial position, an initial speed, a final speed, and a touchdown point for the vertical take-off and landing vehicle (operation **1100**).

(139) The process performs a set of actions when a landing signal indicating that the vertical take-off and landing vehicle has landed is received from a sensor system and when the vertical take-off and landing vehicle reaches the touchdown point (operation **1102**). The process terminates thereafter.

(140) In the illustrative example, a landing profile with other landing detection mechanisms in a sensor system provides combining multiple sources that can be used to conclude that a vertical take-off and landing vehicle has touched down at a touchdown point, while also reducing or avoiding false touchdowns such as detecting a touchdown while the vertical take-off and landing vehicle is still in flight. The illustrative example enables a shut-down of the propulsion system or other actions when a touchdown is considered to have occurred.

(141) The flowcharts and block diagrams in the different depicted examples illustrate the architecture, functionality, and operation of some possible implementations of apparatuses and methods in an illustrative example. In this regard, each block in the flowcharts or block diagrams can represent at least one of a module, a segment, a function, or a portion of an operation or step. For example, one or more of the blocks can be implemented as program code, hardware, or a combination of the program code and hardware. When implemented in hardware, the hardware can, for example, take the form of integrated circuits that are manufactured or configured to perform one or more operations in the flowcharts or block diagrams. When implemented as a combination of program code and hardware, the implementation may take the form of firmware. Each block in the flowcharts or the block diagrams can be implemented using special purpose hardware systems that perform the

different operations or combinations of special purpose hardware and program code run by the special purpose hardware.

(142) In some alternative implementations of an illustrative example, the function or functions noted in the blocks may occur out of the order noted in the figures. For example, in some cases, two blocks shown in succession may be performed substantially concurrently, or the blocks may sometimes be performed in the reverse order, depending upon the functionality involved. Also, other blocks may be added in addition to the illustrated blocks in a flowchart or block diagram.

(143) Turning now to FIG. 12, an illustration of a block diagram of a data processing system is depicted in accordance with an illustrative example. Data processing system **1200** can be used to implement server computer **104**, server computer **106**, and client devices **110** in FIG. 1. Data processing system **1200** can also be used to implement computer system **206**, controller **238**, and data processing systems in vertical take-off and landing vehicle **204** in FIG. 2 and vertical take-off and landing vehicle **500** in FIG. 5. In this illustrative example, data processing system **1200** includes communications framework **1202**, which provides communications between processor unit **1204**, memory **1206**, persistent storage **1208**, communications unit **1210**, input/output (I/O) unit **1212**, and display **1214**. In this example, communications framework **1202** takes the form of a bus system.

(144) Processor unit **1204** serves to execute instructions for software that can be loaded into memory **1206**. Processor unit **1204** includes one or more processors. For example, processor unit **1204** can be selected from at least one of a multicore processor, a central processing unit (CPU), a graphics processing unit (GPU), a physics processing unit (PPU), a digital signal processor (DSP), a network processor, or some other suitable type of processor. Further, processor unit **1204** can may be implemented using one or more heterogeneous processor systems in which a main processor is present with secondary processors on a single chip. As another illustrative example, processor unit **1204** can be a symmetric multi-processor system containing multiple processors of the same type on a single chip.

(145) Memory **1206** and persistent storage **1208** are examples of storage devices **1216**. A storage device is any piece of hardware that is capable of storing information, such as, for example, without limitation, at least one of data, program code in functional form, or other suitable information either on a temporary basis, a permanent basis, or both on a temporary basis and a permanent basis. Storage devices **1216** may also be referred to as computer-readable storage devices in these illustrative examples. Memory **1206**, in these examples, can be, for example, a random-access memory or any other suitable volatile or non-volatile storage device. Persistent storage **1208** can take various forms, depending on the particular implementation.

(146) For example, persistent storage **1208** may contain one or more components or devices. For example, persistent storage **1208** can be a hard drive, a solid-state drive (SSD), a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by persistent storage **1208** also can be removable. For example, a removable hard drive can be used for persistent storage **1208**.

(147) Communications unit **1210**, in these illustrative examples, provides for communications with other data processing systems or devices. In these illustrative examples, communications unit **1210** is a network interface card.

(148) Input/output unit **1212** allows for input and output of data with other devices that can be connected to data processing system **1200**. For example, input/output unit **1212** can provide a connection for user input through at least one of a keyboard, a mouse, or some other suitable input device. Further, input/output unit **1212** can send output to a printer. Display **1214** provides a mechanism to display information to a user.

(149) Instructions for at least one of the operating system, applications, or programs can be located in storage devices **1216**, which are in communication with processor unit **1204** through communications framework **1202**. The processes of the different examples can be performed by processor unit **1204** using computer-implemented instructions, which can be located in a memory, such as memory **1206**.

(150) These instructions are referred to as program code, computer usable program code, or computer-readable program code that can be read and executed by a processor in processor unit **1204**. The program code in the different examples can be embodied on different physical or computer-readable storage medium, such as memory **1206** or persistent storage **1208**.

(151) Program code **1218** is located in a functional form on computer-readable media **1220** that is selectively removable and can be loaded onto or transferred to data processing system **1200** for execution by processor unit **1204**. Program code **1218** and computer-readable media **1220** form computer program product **1222** in these illustrative examples. In the illustrative example, computer-readable media **1220** is computer-readable storage media **1224**.

(152) In these illustrative examples, computer-readable storage media **1224** is a physical or tangible storage device used to store program code **1218** rather than a medium that propagates or transmits program code **1218**. Computer-readable storage media **1224**, as used herein, is not to be construed as being transitory signals per se, such as radio waves or other freely propagating electromagnetic waves, electromagnetic waves propagating through a waveguide or other transmission media (e.g., light pulses passing through a fiber-optic cable), or electrical signals transmitted through a wire, as used herein, is not to be construed as being transitory signals per se, such as radio waves or other freely propagating electromagnetic waves, electromagnetic waves propagating through a waveguide or other transmission media (e.g., light pulses passing through a fiber-optic cable), or electrical signals transmitted through a wire.

(153) Alternatively, program code **1218** can be transferred to data processing system **1200** using a computer-readable signal media. The computer-readable signal media are signals and can be, for example, a propagated data signal containing program code **1218**. For example, the computer-readable signal media can be at least one of an electromagnetic signal, an optical signal, or any other suitable type of signal. These signals can be transmitted over connections, such as wireless connections, optical fiber cable, coaxial cable, a wire, or any other suitable type of connection.

(154) Further, as used herein, “computer-readable media **1220**” can be singular or plural. For example, program code **1218** can be located in computer-readable media **1220** in the form of a single storage device or system. In another example, program code **1218** can be located in computer-readable media **1220** that is distributed in multiple data processing systems. In

other words, some instructions in program code **1218** can be located in one data processing system while other instructions in program code **1218** can be located in one data processing system. For example, a portion of program code **1218** can be located in computer-readable media **1220** in a server computer while another portion of program code **1218** can be located in computer-readable media **1220** located in a set of client computers.

(155) The different components illustrated for data processing system **1200** are not meant to provide architectural limitations to the manner in which different examples can be implemented. In some illustrative examples, one or more of the components may be incorporated in or otherwise form a portion of, another component. For example, memory **1206**, or portions thereof, can be incorporated in processor unit **1204** in some illustrative examples. The different illustrative examples can be implemented in a data processing system including components in addition to or in place of those illustrated for data processing system **1200**. Other components shown in FIG. **12** can be varied from the illustrative examples shown. The different examples can be implemented using any hardware device or system capable of running program code **1218**.

(156) Illustrative examples of the disclosure may be described in the context of aircraft manufacturing and service method **1300** as shown in FIG. **13** and aircraft **1400** as shown in FIG. **14**. Turning first to FIG. **13**, an illustration of an aircraft manufacturing and service method is depicted in accordance with an illustrative example. During pre-production, aircraft manufacturing and service method **1300** may include specification and design **1302** of aircraft **1400** in FIG. **14** and material procurement **1304**.

(157) During production, component and subassembly manufacturing **1306** and system integration **1308** of aircraft **1400** in FIG. **14** takes place. Thereafter, aircraft **1400** in FIG. **14** can go through certification and delivery **1310** in order to be placed in service **1312**. While in service **1312** by a customer, aircraft **1400** in FIG. **14** is scheduled for routine maintenance and service **1314**, which may include modification, reconfiguration, refurbishment, and other maintenance or service.

(158) Each of the processes of aircraft manufacturing and service method **1300** may be performed or carried out by a system integrator, a third party, an operator, or some combination thereof. In these examples, the operator may be a customer. For the purposes of this description, a system integrator may include, without limitation, any number of aircraft manufacturers and major-system subcontractors; a third party may include, without limitation, any number of vendors, subcontractors, and suppliers; and an operator may be an airline, a leasing company, a military entity, a service organization, and so on.

(159) With reference now to FIG. **14**, an illustration of an aircraft is depicted in which an illustrative example may be implemented. In this example, aircraft **1400** is produced by aircraft manufacturing and service method **1300** in FIG. **13** and may include airframe **1402** with plurality of systems **1404** and interior **1406**. Examples of systems **1404** include one or more of propulsion system **1408**, electrical system **1410**, hydraulic system **1412**, and environmental system **1414**. Any number of other systems may be included. Although an aerospace example is shown, different illustrative examples may be applied to other industries, such as the automotive industry.

(160) Apparatuses and methods embodied herein may be employed during at least one of the stages of aircraft manufacturing and service method **1300** in FIG. **13**.

(161) In one illustrative example, components or subassemblies produced in component and subassembly manufacturing **1306** in FIG. **13** can be fabricated or manufactured in a manner similar to components or subassemblies produced while aircraft **1400** is in service **1312** in FIG. **13**. As yet another example, one or more apparatus examples, method examples, or a combination thereof can be utilized during production stages, such as component and subassembly manufacturing **1306** and system integration **1308** in FIG. **13**. One or more apparatus examples, method examples, or a combination thereof may be utilized while aircraft **1400** is in service **1312**, during maintenance and service **1314** in FIG. **13**, or both. The use of a number of the different illustrative examples may substantially expedite the assembly of aircraft **1400**, reduce the cost of aircraft **1400**, or both expedite the assembly of aircraft **1400** and reduce the cost of aircraft **1400**.

(162) For example, one or more components of a vertical managing take-off system, such as a vertical take-off and landing system **202** in FIG. **2**, can be implemented in aircraft **1400** during various stages of aircraft manufacturing and service method **1300** in FIG. **13**. In one illustrative example, when aircraft **1400** is a vertical take-off and landing vehicle, and landing manager can be implemented in aircraft **1400** during at least one of system integration **1308**, maintenance and service **1314**, or in service **1312**. When implemented during maintenance and service **1314**, a landing manager can be added or installed during at least one of scheduled routine maintenance and service, modification, reconfiguration, refurbishment, and other maintenance or service.

(163) Thus, the illustrative examples provide a method, apparatus, system, and computer program product for controlling landing of a vertical take-off and landing vehicle. In one illustrative example, a method controls landing of a vertical take-off and landing vehicle. A landing profile for landing the vertical take-off and landing vehicle is determined by a computer system using a third derivative of a position equation, an initial position, an initial speed, a final speed, and a touchdown point for the vertical take-off and landing vehicle. Landing of the vertical take-off and landing vehicle is controlled using the landing profile.

(164) In the illustrative example, a landing manager can be used to determine when a vertical take-off and landing vehicle has landed and perform actions based on this determination. In one illustrative example, a landing profile is used in conjunction with receiving a landing signal indicating that the vertical take-off and landing vehicle has landed. This type of determination provides increased accuracy in performing the actions after landing in a manner that avoids issues with undesired environmental conditions such as turbulence and aerodynamic ground effects.

(165) Thus, when a vertical landing and take-off system includes a sensor system and a landing manager, increased integrity or accuracy occurs at which landing of a vertical take-off and landing vehicle can be detected. This increased accuracy in detecting landing can provide at least one of reducing the time at which a vertical landing and take-off vehicle hovers, reducing false positive detections which may result in damage to the vertical take-off and landing vehicle, or increasing the

ability for rapid recovery of the vertical landing and take-off vehicle.

(166) The description of the different illustrative examples has been presented for purposes of illustration and description and is not intended to be exhaustive or limited to the examples in the form disclosed. The different illustrative examples describe components that perform actions or operations. In an illustrative example, a component can be configured to perform the action or operation described. For example, the component can have a configuration or design for a structure that provides the component an ability to perform the action or operation that is described in the illustrative examples as being performed by the component. Further, to the extent that terms “includes”, “including”, “has”, “contains”, and variants thereof are used herein, such terms are intended to be inclusive in a manner similar to the term “comprises” as an open transition word without precluding any additional or other elements.

(167) Many modifications and variations will be apparent to those of ordinary skill in the art. Further, different illustrative examples may provide different features as compared to other desirable examples. The example or examples selected are chosen and described in order to best explain the principles of the examples, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various examples with various modifications as are suited to the particular use contemplated.

(168) Some features of the illustrative examples are described in the following clauses. These clauses are examples of features not intended to limit other illustrative examples.

(169) Clause 1: A vertical landing system comprising a sensor system configured to generate a landing signal when landing of the vertical landing vehicle is detected by the sensor system; a computer system; a landing manager in the computer system, wherein the landing manager is configured to: determine a landing profile for landing the vertical landing vehicle using a third derivative of a position equation, an initial position, an initial speed, a final speed, and a touchdown point for the vertical landing vehicle, wherein a jerk is reduced in landing the vertical landing vehicle at the touchdown point; and perform a set of actions when the landing signal is received from the sensor system and when the vertical landing vehicle reaches the touchdown point.

(170) Clause 2: The vertical landing system of Clause 1, wherein the landing manager is configured to control the landing of the vertical landing vehicle using the landing profile.

(171) Clause 3: The vertical landing system of Clause 2, wherein in controlling the landing of the vertical landing vehicle at the touchdown point using the landing profile, the landing manager is configured to: send a set of commands to a controller for the vertical landing vehicle such that the set of commands causes the controller to control the vertical landing vehicle to follow the landing profile to land the vertical landing vehicle at the touchdown point.

(172) Clause 4: The vertical landing system of any of Clauses 1-3, wherein in determining the landing profile for landing the vertical landing vehicle using the third derivative of the position equation, the initial position, the initial speed, the final speed, and the touchdown point for the vertical landing vehicle, the landing manager is configured to determine at least one of a position trajectory, a speed trajectory, or an acceleration trajectory using the following:

$$x(t)=a_{\text{sub}.0}+a_{\text{sub}.1}\Delta_{\text{sub}.t}+a_{\text{sub}.2}\Delta_{\text{sub}.t}^2+a_{\text{sub}.3}\Delta_{\text{sub}.t}^3+a_{\text{sub}.4}\Delta_{\text{sub}.t}^4+a_{\text{sub}.5}\Delta_{\text{sub}.t}^5$$

$$\dot{x}(t)=a_{\text{sub}.1}+2a_{\text{sub}.2}\Delta_{\text{sub}.t}+3a_{\text{sub}.3}\Delta_{\text{sub}.t}^2+4a_{\text{sub}.4}\Delta_{\text{sub}.t}^3+5a_{\text{sub}.5}\Delta_{\text{sub}.t}^4$$

$$\ddot{x}(t)=2a_{\text{sub}.2}+6a_{\text{sub}.3}\Delta_{\text{sub}.t}+12a_{\text{sub}.4}\Delta_{\text{sub}.t}^2+20a_{\text{sub}.5}\Delta_{\text{sub}.t}^3$$

$$\ddot{\ddot{x}}(t)=6a_{\text{sub}.3}+24a_{\text{sub}.4}\Delta_{\text{sub}.t}+60a_{\text{sub}.5}\Delta_{\text{sub}.t}^2$$

where $x(t)$ is position, $\Delta_{\text{sub}.t}$ is the time span since the initial condition and where t is time, $t_{\text{sub}.0}$ is initial time, $a_{\text{sub}.0}$ is initial position, $a_{\text{sub}.1}$ is initial velocity, $a_{\text{sub}.2}$ is initial acceleration times $\frac{1}{2}$, and $a_{\text{sub}.3}$, $a_{\text{sub}.4}$, and $a_{\text{sub}.5}$ are determined by final conditions at touchdown.

(173) Clause 5: The vertical landing system of any of Clauses 1-4, wherein in determining the landing profile for landing the vertical landing vehicle using third derivative of the position equation, the initial position, the initial speed, the final speed, and the touchdown point for the vertical landing vehicle, the landing manager is configured to repeatedly determine the landing profile for landing the vertical landing vehicle using the third derivative of the position equation, the initial position, the initial speed, the final speed, and the touchdown point for the vertical landing vehicle, wherein the initial position is a current position of the vertical landing vehicle and the initial speed is a current speed of the vertical take-off and landing vehicle.

(174) Clause 6: The vertical landing system of any of Clauses 1-5, wherein the jerk is reduced to at least one of a minimum jerk or a desired level of jerk.

(175) Clause 7: The vertical landing system of any of Clauses 1-6, wherein the set of actions is selected from at least one of turning off a propulsion system for the vertical landing vehicle or indicating that the vertical landing vehicle has landed.

(176) Clause 8: The vertical landing system of any of Clauses 1-7, wherein the vertical landing vehicle is selected from one of a tiltrotor vehicle, a rotorcraft, a helicopter, a gyrodyne, a gyroplane, a tilt jet vertical landing aircraft, a direct-lift thrust vectoring aircraft, and a tilt wing aircraft.

(177) Clause 9: A vertical landing system comprising a computer system; and a landing manager in the computer system, wherein the landing manager is configured to: determine a landing profile for landing a vertical landing vehicle using a third derivative of a position equation, an initial position, an initial speed, a final speed, and a touchdown point for the vertical landing vehicle, wherein landing of the vertical landing vehicle lands at the touchdown point using the landing profile.

(178) Clause 10: The vertical landing system of Clause 9 further comprising a sensor system is configured to detect a landing of the vertical and landing vehicle, wherein the sensor system generates a landing signal when the landing of the vertical landing vehicle is detected by the sensor system; wherein the landing manager is configured to: perform a set of actions when the landing signal is received from the sensor system and when the vertical landing vehicle reaches the touchdown point.

(179) Clause 11: The vertical landing system of Clause 9 or 10, wherein the landing manager is configured to control a

landing of the vertical landing vehicle at the touchdown point using the landing profile.

(180) Clause 12: The vertical landing system of Clause 11, wherein in controlling the landing of the vertical landing vehicle at the touchdown point using the landing profile, the landing manager is configured to send a set of commands to a controller for the vertical landing vehicle such that the set of commands cause the controller to control the vertical landing vehicle to follow the landing profile to land the vertical landing vehicle at the touchdown point.

(181) Clause 13: The vertical landing system of any of Clauses 9-12, wherein the landing manager is configured to perform a set of actions when a landing signal indicating that the vertical landing vehicle has landed is received from a sensor system and when the vertical landing vehicle reaches the touchdown point.

(182) Clause 14: The vertical landing system of any of Clauses 9-13, wherein in determining the landing profile for landing the vertical landing vehicle using the third derivative of the position equation, the initial position, the initial speed, the final speed, and the touchdown point for the vertical landing vehicle, the landing manager is configured to determine at least one of a position trajectory, a speed trajectory, or an acceleration trajectory using the following:

$$x(t)=a_{\text{sub}.0}+a_{\text{sub}.1}(t-t_{\text{sub}.0})+a_{\text{sub}.2}(t-t_{\text{sub}.0})^2+a_{\text{sub}.3}(t-t_{\text{sub}.0})^3+a_{\text{sub}.4}(t-t_{\text{sub}.0})^4+a_{\text{sub}.5}(t-t_{\text{sub}.0})^5$$

$$\dot{x}(t)=a_{\text{sub}.1}+2a_{\text{sub}.2}(t-t_{\text{sub}.0})+3a_{\text{sub}.3}(t-t_{\text{sub}.0})^2+4a_{\text{sub}.4}(t-t_{\text{sub}.0})^3+5a_{\text{sub}.5}(t-t_{\text{sub}.0})^4$$

$$\ddot{x}(t)=2a_{\text{sub}.2}+6a_{\text{sub}.3}(t-t_{\text{sub}.0})+12a_{\text{sub}.4}(t-t_{\text{sub}.0})^2+20a_{\text{sub}.5}(t-t_{\text{sub}.0})^3$$

$$\text{custom character}(t)=6a_{\text{sub}.3}+24a_{\text{sub}.4}(t-t_{\text{sub}.0})+60a_{\text{sub}.5}(t-t_{\text{sub}.0})^2$$

where $x(t)$ is position, $\dot{x}(t)$ is velocity, $\ddot{x}(t)$ is acceleration, $\text{custom character}(t)$ is jerk, t is time, $t_{\text{sub}.0}$ is initial time, $a_{\text{sub}.0}$ is initial position, $a_{\text{sub}.1}$ is initial velocity, and $a_{\text{sub}.2}$ is initial acceleration times $\frac{1}{2}$, and $a_{\text{sub}.3}$, $a_{\text{sub}.4}$, and $a_{\text{sub}.5}$ are determined by final conditions at touchdown.

(183) Clause 15: The vertical landing system of any of Clauses 9-14, wherein in determining the landing profile for landing the vertical landing vehicle using the third derivative of the position equation, the initial position, the initial speed, the final speed, and the touchdown point for the vertical landing vehicle, the landing manager is configured to repeatedly determine the landing profile for landing the vertical landing vehicle using the third derivative of the position equation, the initial position, the initial speed, the final speed, and the touchdown point for the vertical landing vehicle, wherein the initial position is a current position of the vertical landing vehicle and the initial speed is a current speed of the vertical landing vehicle.

(184) Clause 16: The vertical landing system of any of Clauses 9-15, wherein a jerk is reduced in landing the vertical landing vehicle at the touchdown point.

(185) Clause 17: The vertical landing system of Clause 16, wherein the jerk is reduced to at least one of a minimum jerk or a desired level of jerk.

(186) Clause 18: The vertical landing system of Clause 13, wherein the set of actions is selected from at least one of turning off a propulsion system for the vertical landing vehicle, or indicating that the vertical landing vehicle has landed.

(187) Clause 19: The vertical landing system of any of Clauses 9-18, wherein the vertical landing vehicle is selected from one of a tiltrotor vehicle, a rotorcraft, a helicopter, a gyrodyne, a gyroplane, a tilt jet vertical take-off and landing aircraft, a direct-lift thrust vectoring aircraft, and a tilt wing aircraft.

(188) Clause 20: A method for controlling landing of a vertical landing vehicle, the method comprising determining, by a computer system, a landing profile for landing the vertical landing vehicle using a third derivative of a position equation, an initial position, an initial speed, a final speed, and a touchdown point for the vertical landing vehicle; and controlling landing of the vertical landing vehicle using the landing profile.

(189) Clause 21: The method of Clause 20, wherein controlling of the vertical landing vehicle at the touchdown point using the landing profile comprises sending, by the computer system, a set of commands to a controller for the vertical landing vehicle such that the set of commands causes the controller to control the vertical landing vehicle to follow the landing profile to land the vertical landing vehicle at the touchdown point.

(190) Clause 22: The method of Clause 20 or 21, further comprising performing, by the computer system, a set of actions when a landing signal indicating that the vertical landing vehicle has landed is received from a sensor system and when the vertical landing vehicle reaches the touchdown point.

(191) Clause 23: The method of any of Clauses 20-22, wherein determining, by the computer system the landing profile for landing the vertical landing vehicle using the third derivative of the position equation, the initial position, the initial speed, the final speed, and the touchdown point for the vertical landing vehicle comprises determining, by the computer system, at least one of a position trajectory, a speed trajectory, or an acceleration trajectory using the following:

$$x(t)=a_{\text{sub}.0}+a_{\text{sub}.1}(t-t_{\text{sub}.0})+a_{\text{sub}.2}(t-t_{\text{sub}.0})^2+a_{\text{sub}.3}(t-t_{\text{sub}.0})^3+a_{\text{sub}.4}(t-t_{\text{sub}.0})^4+a_{\text{sub}.5}(t-t_{\text{sub}.0})^5$$

$$\dot{x}(t)=a_{\text{sub}.1}+2a_{\text{sub}.2}(t-t_{\text{sub}.0})+3a_{\text{sub}.3}(t-t_{\text{sub}.0})^2+4a_{\text{sub}.4}(t-t_{\text{sub}.0})^3+5a_{\text{sub}.5}(t-t_{\text{sub}.0})^4$$

$$\ddot{x}(t)=2a_{\text{sub}.2}+6a_{\text{sub}.3}(t-t_{\text{sub}.0})+12a_{\text{sub}.4}(t-t_{\text{sub}.0})^2+20a_{\text{sub}.5}(t-t_{\text{sub}.0})^3$$

$$\text{custom character}(t)=6a_{\text{sub}.3}+24a_{\text{sub}.4}(t-t_{\text{sub}.0})+60a_{\text{sub}.5}(t-t_{\text{sub}.0})^2$$

where $x(t)$ is position, $\dot{x}(t)$ is velocity, $\ddot{x}(t)$ is acceleration, $\text{custom character}(t)$ is jerk, t is time, $t_{\text{sub}.0}$ is initial time, $a_{\text{sub}.0}$ is initial position, $a_{\text{sub}.1}$ is initial velocity, and $a_{\text{sub}.2}$ is initial acceleration times $\frac{1}{2}$, and $a_{\text{sub}.3}$, $a_{\text{sub}.4}$, and $a_{\text{sub}.5}$ are determined by final conditions at touchdown.

(192) Clause 24: The method of any of Clauses 20-23, wherein determining, by the computer system, the landing profile for landing the vertical landing vehicle using the third derivative of the position equation, the initial position, the initial speed, the final speed, and the touchdown point for the vertical landing vehicle comprises repeatedly determining, by the computer system, the landing profile for landing the vertical landing vehicle using the third derivative of the position equation, the initial position, the initial speed, the final speed, and the touchdown point for the vertical landing vehicle, wherein the initial position is a current position of the vertical landing vehicle and the initial speed is a current speed of the vertical landing vehicle.

(193) Clause 25: The method of any of Claims 20-24, wherein a jerk is reduced in landing the vertical landing vehicle at the touchdown point.

(194) Clause 26: The method of Claim 25, wherein the jerk is reduced to at least one of a minimum jerk or a desired level of jerk.

(195) Clause 27: The method of Claim 22, wherein the set of actions is selected from at least one of turning off a propulsion system for the vertical landing vehicle or indicating that the vertical landing vehicle has landed.

(196) Clause 28: The method of any of Claims 20-27, wherein the vertical landing vehicle is selected from one of a tiltrotor vehicle, a rotorcraft, a helicopter, a gyrodyne, a gyroplane, a tilt jet vertical landing aircraft, a direct-lift thrust vectoring aircraft, and a tilt wing aircraft.

(197) Clause 29: A computer program product for controlling landing of a vertical landing vehicle, the computer program product comprising a computer-readable storage media; first program code, stored on the computer-readable storage media, executable by a computer system to cause the computer system to determine a landing profile for landing the vertical landing vehicle using a third derivative of a position equation, an initial position, an initial speed, a final speed, and a touchdown point for the vertical landing vehicle; and second first program code, stored on the computer-readable storage media, executable by the computer system to cause the computer system to control landing of the vertical landing vehicle using the landing profile.

Claims

1. A vertical landing system that comprises: a computer system that comprises a landing manager; and an electromechanical sensing device, an ultrasonic sensor, and an additional sensor, each configured to detect a landing of a vertical landing vehicle, and responsive thereto generate and send a landing signal to the computer system, wherein the landing manager is configured to: receive inputs that comprise: a desired final speed, a desired final position, an initial position, an initial speed, and an initial acceleration; determine, based upon periodic updates in real-time, a landing profile for the vertical landing vehicle that minimizes a jerk that acts on the vertical landing vehicle in a descend and deceleration phase prior to a touchdown point that is derived from a gain adjusted velocity and a gain adjusted acceleration in a real-time open-loop, wherein the landing profile is derived from: a third derivative of a position equation, the initial position, the initial speed, the desired final speed, and the desired final position for the vertical landing vehicle; determine that the vertical landing vehicle is located at the touchdown point of the landing profile; and responsive to a reception of the landing signal from all of: the electromechanical sensing device, the ultrasonic sensor, and the additional sensor, and the determination that the vertical landing vehicle is located at the touchdown point of the landing profile, indicate that the vertical landing vehicle has landed and turn off a propulsion system of the vertical landing vehicle.
2. The vertical landing system of claim 1, wherein: the additional sensor is not located on the vertical landing vehicle; and the landing manager is configured to control the landing of the vertical landing vehicle using the landing profile.
3. The vertical landing system of claim 2, wherein the landing manager is further configured to: send a set of commands based upon the landing profile to a controller for the vertical landing vehicle such that the set of commands causes the controller to control the vertical landing vehicle to follow the landing profile to land the vertical landing vehicle at the touchdown point.
4. The vertical landing system of claim 3, wherein the controller is further configured to provide an estimate, based upon the landing profile, of a tilt angle required to decelerate the vertical landing vehicle into a hover.
5. The vertical landing system of claim 1, wherein the landing manager is further configured to determine at least one of: a position trajectory, a speed trajectory, or an acceleration trajectory using at least one of the following:

$$\dot{x}(t) = a_{\text{sub}.0} + a_{\text{sub}.1}\Delta_{\text{sub}.t} + a_{\text{sub}.2}\Delta_{\text{sub}.t}^{\text{sup}.2} + a_{\text{sub}.3}\Delta_{\text{sub}.t}^{\text{sup}.3} + a_{\text{sub}.4}\Delta_{\text{sub}.t}^{\text{sup}.4} + a_{\text{sub}.5}\Delta_{\text{sub}.t}^{\text{sup}.5}$$

$$\ddot{x}(t) = a_{\text{sub}.1} + 2a_{\text{sub}.2}\Delta_{\text{sub}.t} + 3a_{\text{sub}.3}\Delta_{\text{sub}.t}^{\text{sup}.2} + 4a_{\text{sub}.4}\Delta_{\text{sub}.t}^{\text{sup}.3} + 5a_{\text{sub}.5}\Delta_{\text{sub}.t}^{\text{sup}.4}$$

$$\dddot{x}(t) = 2a_{\text{sub}.2} + 6a_{\text{sub}.3}\Delta_{\text{sub}.t} + 12a_{\text{sub}.4}\Delta_{\text{sub}.t}^{\text{sup}.2} + 20a_{\text{sub}.5}\Delta_{\text{sub}.t}^{\text{sup}.3}$$

$$\ddot{\ddot{x}}(t) = 6a_{\text{sub}.3} + 24a_{\text{sub}.4}\Delta_{\text{sub}.t} + 60a_{\text{sub}.5}\Delta_{\text{sub}.t}^{\text{sup}.2}$$
where $x(t)$ is position, $\Delta_{\text{sub}.t} \triangleq t - t_{\text{sub}.0}$ is a time span since an initial condition and where t is time, $t_{\text{sub}.0}$ is initial time, $a_{\text{sub}.0}$ is initial position, $a_{\text{sub}.1}$ is initial speed, $a_{\text{sub}.2}$ is initial acceleration times $\frac{1}{2}$, and $a_{\text{sub}.3}$, $a_{\text{sub}.4}$, and $a_{\text{sub}.5}$ are determined by final conditions at touchdown.
6. The vertical landing system of claim 1, wherein the landing manager is further configured to repeatedly determine the landing profile for landing the vertical landing vehicle using the third derivative of the position equation, the initial position, the initial speed, the desired final speed, and the touchdown point for the vertical landing vehicle, wherein the initial position is a current position of the vertical landing vehicle and the initial speed is a current speed of the vertical landing vehicle.
7. The vertical landing system of claim 1, further comprising a touchdown point sensor configured to sense when the vertical landing vehicle is at the touchdown point, wherein the vertical landing vehicle is selected from one of a tiltrotor vehicle, a rotorcraft, a helicopter, a gyrodyne, a gyroplane, a tilt jet vertical landing aircraft, a direct-lift thrust vectoring aircraft, and a tilt wing aircraft.
8. The vertical landing system of claim 1, wherein the additional sensor system comprises a light detection and ranging system.
9. A vertical landing system that comprises: a computer system that comprises a landing manager; and an electromechanical sensing device, an ultrasonic sensor, and an additional sensor, each configured to detect a landing of a vertical landing vehicle, and responsive thereto generate and send a landing signal to the computer system, wherein the landing manager is configured to: determine, based on periodic updates in real-time, a landing profile for landing a vertical landing vehicle that minimizes a jerk that acts on the vertical landing vehicle in a descend and deceleration phase prior to a touchdown point that

is derived from a gain adjusted velocity and a gain adjusted acceleration in a real-time open-loop, wherein the landing profile is based upon: a third derivative of a position equation, an initial position, an initial speed, a desired final speed, and a desired final position for the vertical landing vehicle; communicate with a controller to land the vertical landing vehicle at the touchdown point of the landing profile based upon the landing profile; and responsive to a reception of the landing signal from all of: the electromechanical sensing device, the ultrasonic sensor, and the additional sensor and a determination in the landing manager that the vertical landing vehicle is located at the touchdown point of the landing profile, indicate that the vertical landing vehicle has landed and turn off a propulsion system of the vertical landing vehicle.

10. The vertical landing system of claim 9, wherein the landing manager is configured to: control a landing of the vertical landing vehicle at the touchdown point based upon the landing profile.

11. The vertical landing system of claim 10, wherein the landing manager is configured to send a set of commands based upon the landing profile to the controller for the vertical landing vehicle such that the set of commands cause the controller to control the vertical landing vehicle to follow the landing profile to land the vertical landing vehicle at the touchdown point.

12. The vertical landing system of claim 9, wherein in determining the landing profile for landing the vertical landing vehicle using the third derivative of the position equation, the initial position, the initial speed, the desired final speed, and the touchdown point for the vertical landing vehicle, the landing manager is configured to determine at least one: of a position trajectory, a speed trajectory, or an acceleration trajectory using at least one of the following:

$$x(t)=a_{\text{sub}.0}+a_{\text{sub}.1}(t-t_{\text{sub}.0})+a_{\text{sub}.2}(t-t_{\text{sub}.0})^2+a_{\text{sub}.3}(t-t_{\text{sub}.0})^3+a_{\text{sub}.4}(t-t_{\text{sub}.0})^4+a_{\text{sub}.5}(t-t_{\text{sub}.0})^5$$
$$\{\dot{x}\}(t)=a_{\text{sub}.1}+2a_{\text{sub}.2}(t-t_{\text{sub}.0})+3a_{\text{sub}.3}(t-t_{\text{sub}.0})^2+4a_{\text{sub}.4}(t-t_{\text{sub}.0})^3+5a_{\text{sub}.5}(t-t_{\text{sub}.0})^4$$
$$\{\ddot{x}\}(t)=2a_{\text{sub}.2}+6a_{\text{sub}.3}(t-t_{\text{sub}.0})+12a_{\text{sub}.4}(t-t_{\text{sub}.0})^2+20a_{\text{sub}.5}(t-t_{\text{sub}.0})^3$$
$$\{\dddot{x}\}(t)=6a_{\text{sub}.3}+24a_{\text{sub}.4}(t-t_{\text{sub}.0})+60a_{\text{sub}.5}(t-t_{\text{sub}.0})^2$$
 where $x(t)$ is position, $\{\dot{x}\}(t)$ is velocity, $\{\ddot{x}\}(t)$ is acceleration, $\{\dddot{x}\}(t)$ is jerk, t is time, $t_{\text{sub}.0}$ is initial time, $a_{\text{sub}.0}$ is initial position, $a_{\text{sub}.1}$ is initial speed, and $a_{\text{sub}.2}$ is initial acceleration times $\frac{1}{2}$, and $a_{\text{sub}.3}$, $a_{\text{sub}.4}$, and $a_{\text{sub}.5}$ are determined by final conditions at touchdown.

13. The vertical landing system of claim 9, wherein the landing manager is further configured to: repeatedly determine the landing profile for landing the vertical landing vehicle using the third derivative of the position equation, the initial position, the initial speed, the desired final speed, and the touchdown point for the vertical landing vehicle, wherein the initial position is a current position of the vertical landing vehicle and the initial speed is a current speed of the vertical landing vehicle.

14. The vertical landing system of claim 9, wherein the controller is further configured to provide an estimate, based upon the landing profile, of a tilt angle required to decelerate the vertical landing vehicle into a hover.

15. A method for controlling landing of a vertical landing vehicle, the method comprising: receiving, in a landing manager in a computer system in the vertical landing vehicle: from an electromechanical sensing device, an ultrasonic sensor, and an additional sensor on the vertical landing vehicle, respectively, a landing signal; and inputs comprising: a desired final speed, a desired final position, an initial position, an initial speed, and an initial acceleration, for the vertical landing vehicle; deriving, in the landing manager using a gain adjusted velocity and a gain adjusted acceleration in a real-time open-loop and minimized in a descend and deceleration phase prior to a touchdown point, a jerk of the vertical landing vehicle; determining, based upon periodic updates in real time by the computer system using: a third derivative of a position equation, the initial position, the initial speed, the desired final speed, and the touchdown point for the vertical landing vehicle, a landing profile for landing the vertical landing vehicle; controlling landing of the vertical landing vehicle using the landing profile; determining, in the computer system, that the vertical landing vehicle is located at the touchdown point of the landing profile; and using the landing signal from all of: the electromechanical sensing device, the ultrasonic sensor, and the additional sensor, determining and indicating that the vertical landing vehicle landed at the touchdown point of the landing profile; and turning off a propulsion system of the vertical landing vehicle.

16. The method of claim 15, further comprising sending, by the computer system, a set of commands based upon the landing profile to a controller for the vertical landing vehicle such that the set of commands causes the controller to control the vertical landing vehicle to follow the landing profile to land the vertical landing vehicle at the touchdown point.

17. The method of claim 15, further comprising performing, by the computer system, a set of actions when the landing signal indicating that the vertical landing vehicle has landed is received and when the vertical landing vehicle reaches the touchdown point.

18. The method of claim 15, further comprising the controller using the landing profile and estimating a tilt angle required to decelerate the vertical landing vehicle into a hover.

19. A computer program product for controlling landing of a vertical landing vehicle, wherein the computer program product comprises: a computer-readable non-transitory storage media; first program code, stored on the computer-readable non-transitory storage media, executable by a computer system to cause the computer system to: receive a landing signal from: an electromechanical sensing device, an ultrasonic sensor, and an additional sensor, each configured to detect a landing of a vertical landing vehicle, and responsive thereto generate and send the landing signal; and determine, based upon periodic updates in real-time, a landing profile for landing the vertical landing vehicle based upon: a third derivative of a position equation, an initial position, an initial speed, a final speed, and a touchdown point for the vertical landing vehicle, wherein a jerk in a descend and deceleration phase prior to landing of the vertical landing vehicle is derived from a gain adjusted velocity and a gain adjusted acceleration in a real-time open-loop and minimized, and the vertical landing vehicle lands at the touchdown point based upon the landing profile; and second program code, stored on the computer-readable non-transitory storage media, executable by the computer system to cause the computer system to control landing of the vertical landing vehicle based upon the landing profile and responsive to a reception of the landing signal from all of: the electromechanical sensing device, the ultrasonic sensor, and the additional sensor and a determination that the vertical landing vehicle is located

at the touchdown point of the landing profile, indicate that the vertical landing vehicle has landed and turn off a propulsion system of the vertical landing vehicle.

20. The computer program product for controlling landing of a vertical landing vehicle of claim 19, further comprising the second program code configured to provide the landing profile to a controller configured to provide an estimate of a tilt angle required to decelerate the vertical landing vehicle into a hover.
