

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417322
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Kida; Luis et al.

Technologies for filtering memory access transactions received from one or more I/O devices

Abstract

Technologies for secure I/O include a compute device having a processor, a memory, an input/output (I/O) device, and a filter logic. The filter logic is configured to receive a first key identifier from the processor, wherein the first key identifier is indicative of a shared memory range includes a shared key identifier range to be used for untrusted I/O devices and receive a transaction from the I/O device, wherein the transaction includes a second key identifier and a trust device ID indicator associated with the I/O device. The filter logic is further configured to determine whether the transaction is asserted with the trust device ID indicator indicative of whether the I/O device is assigned to a trust domain and determine, in response to a determination that the transaction is not asserted with the trust device ID indicator, whether the second key identifier matches the first key identifier.

Inventors: Kida; Luis (Beaverton, OR), Zmudzinski; Krystof (Forest Grove, CA), Lal; Reshma (Portland, OR), Pappachan; Pradeep (Tualatin, OR), Basak; Abhishek (Bothell, WA), Trikalinou; Anna (Hillsboro, OR)

Applicant: Intel Corporation (Santa Clara, CA)

Family ID: 1000008819259

Assignee: Intel Corporation (Santa Clara, CA)

Appl. No.: 18/200543

Filed: May 22, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230297725 A1	Sep. 21, 2023

Related U.S. Application Data

Publication Classification

Int. Cl.: G06F21/78 (20130101); G06F21/44 (20130101); G06F21/85 (20130101)

U.S. Cl.:

CPC G06F21/78 (20130101); G06F21/44 (20130101); G06F21/85 (20130101);

Field of Classification Search

CPC: G06F (21/78); G06F (21/44); G06F (21/85)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7716389	12/2009	Bruce et al.	N/A	N/A
10073977	12/2017	Pappachan et al.	N/A	N/A
10181946	12/2018	Lal et al.	N/A	N/A
10404674	12/2018	Bshara et al.	N/A	N/A
2009/0222816	12/2008	Mansell et al.	N/A	N/A
2010/0094981	12/2009	Cordray et al.	N/A	N/A
2014/0201526	12/2013	Burgess	N/A	N/A
2016/0132345	12/2015	Bacher et al.	N/A	N/A
2017/0090800	12/2016	Alexandrovich et al.	N/A	N/A
2017/0132158	12/2016	Axnix et al.	N/A	N/A
2017/0277898	12/2016	Powell et al.	N/A	N/A
2017/0331627	12/2016	Harp	N/A	N/A
2018/0006820	12/2017	Arasu et al.	N/A	N/A
2018/0121125	12/2017	Zeng	N/A	G06F 3/0622
2019/0018800	12/2018	Jayasena et al.	N/A	N/A
2019/0130120	12/2018	Lal et al.	N/A	N/A
2020/0349265	12/2019	Lal et al.	N/A	N/A
2022/0035923	12/2021	Pappachan et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3326103	12/2018	EP	N/A

OTHER PUBLICATIONS

Final Office Action, U.S. Appl. No. 17/515,092, Feb. 21, 2023, 15 pages. cited by applicant
Non-Final Office Action, U.S. Appl. No. 16/234,871, Dec. 15, 2020, 9 pages. cited by applicant
Non-Final Office Action, U.S. Appl. No. 17/515,092, Sep. 30, 2022, 13 pages. cited by applicant
Notice of Allowance, U.S. Appl. No. 16/234,871, Dec. 13, 2021, 6 pages. cited by applicant
Notice of Allowance, U.S. Appl. No. 16/234,871, Feb. 22, 2022, 5 pages. cited by applicant

Primary Examiner: Tran; Ellen

Attorney, Agent or Firm: Nicholson De Vos Webster & Elliott LLP

Background/Summary

CLAIM TO PRIORITY (1) This application is a continuation of and claims the benefit of and priority to U.S. application Ser. No. 17/515,092, entitled TECHNOLOGIES FOR FILTERING MEMORY ACCESS TRANSACTIONS RECEIVED FROM ONE OR MORE I/O DEVICES, by Luis Kida, et al., filed Oct. 29, 2021, which is a continuation of and claims the benefit of and priority to U.S. application Ser. No. 16/234,871, entitled TECHNOLOGIES FOR FILTERING MEMORY ACCESS TRANSACTIONS RECEIVED FROM ONE OR MORE I/O DEVICES, by Luis Kida, et al., filed Dec. 28, 2018, which is now U.S. Pat. No. 11,373,013 issued on Jun. 8, 2022, the entire contents of which are incorporated herein by reference.

BACKGROUND

- (1) Trust domains provide isolation for virtual machines without including a virtual machine monitor (VMM) in a trusted code base (TCB) of the trust domain. Memory is protected using multi-key total memory encryption (MKTME). Each trust domain has its own Key ID used by MKTME to protect memory contents from other trust domains and the VMM.
 - (2) Hardware in a system-on-a-chip (SoC) enforces the protection. Generally, trust domain systems do not allow I/O devices to access trust domain-protected memory.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The concepts described herein are illustrated by way of example and not by way of limitation in the accompanying figures. For simplicity and clarity of illustration, elements illustrated in the figures are not necessarily drawn to scale. Where considered appropriate, reference labels have been repeated among the figures to indicate corresponding or analogous elements.
- (2) FIG. 1 is a simplified block diagram of at least one embodiment of a compute device having one or more filter logics for filtering direct memory access (DMA) transactions between one or more I/O devices and a trust domain;
- (3) FIG. 2 is a simplified block diagram of at least one embodiment of an environment of the filter logic of FIG. 1; and
- (4) FIGS. 3 and 4 are a simplified flow diagram of at least one embodiment of a method for filtering memory access transactions from an I/O device to establish a secure data transfer between an I/O device and a trust domain that may be executed by the filter logic of the compute device of FIGS. 1 and 2.

DETAILED DESCRIPTION OF THE DRAWINGS

- (5) While the concepts of the present disclosure are susceptible to various modifications and alternative forms, specific embodiments thereof have been shown by way of example in the drawings and will be described herein in detail. It should be understood, however, that there is no intent to limit the concepts of the present disclosure to the particular forms disclosed, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives consistent with the

present disclosure and the appended claims.

(6) References in the specification to “one embodiment,” “an embodiment,” “an illustrative embodiment,” etc., indicate that the embodiment described may include a particular feature, structure, or characteristic, but every embodiment may or may not necessarily include that particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, it is submitted that it is within the knowledge of one skilled in the art to effect such feature, structure, or characteristic in connection with other embodiments whether or not explicitly described. Additionally, it should be appreciated that items included in a list in the form of “at least one A, B, and C” can mean (A); (B); (C); (A and B); (A and C); (B and C); or (A, B, and C). Similarly, items listed in the form of “at least one of A, B, or C” can mean (A); (B); (C); (A and B); (A and C); (B and C); or (A, B, and C).

(7) The disclosed embodiments may be implemented, in some cases, in hardware, firmware, software, or any combination thereof. The disclosed embodiments may also be implemented as instructions carried by or stored on a transitory or non-transitory machine-readable (e.g., computer-readable) storage medium, which may be read and executed by one or more processors. A machine-readable storage medium may be embodied as any storage device, mechanism, or other physical structure for storing or transmitting information in a form readable by a machine (e.g., a volatile or non-volatile memory, a media disc, or other media device).

(8) In the drawings, some structural or method features may be shown in specific arrangements and/or orderings. However, it should be appreciated that such specific arrangements and/or orderings may not be required. Rather, in some embodiments, such features may be arranged in a different manner and/or order than shown in the illustrative figures. Additionally, the inclusion of a structural or method feature in a particular figure is not meant to imply that such feature is required in all embodiments and, in some embodiments, may not be included or may be combined with other features.

(9) Referring now to FIG. 1, an illustrative compute device **100** for filtering data transactions between a trust domain (TD) and an accelerator **150, 170** or other I/O devices **160, 180** is shown. In order to perform a secure I/O with the trust domain, the trust domain may authenticate an I/O device and determine a reliable device ID for the I/O device. The trust domain may program enforcement hardware (e.g., the IOMMU, root complex, or the device itself) with a binding between the trust domain and the device ID and memory access permissions for a trust domain memory. As such, when the I/O device generates direct memory access (DMA) transactions to access the trust domain memory, the enforcement hardware may enforce the binding between the trust domain and the device ID as well as the memory access permissions. If the transaction is allowed, the trust domain memory is accessed securely using multi-key total memory encryption (MKTME) support. It should be appreciated that a similar technique may be applied to other types of data transactions (e.g., memory-mapped I/O (MMIO) or cache access transactions) generated by the I/O device.

(10) In use, as described further below, a filter logic **122, 140, 172, 182** may filter direct memory access (DMA) transactions received from one or more associated I/O devices (e.g., an accelerator **150, 170** or an I/O device **160, 180**) to allow a transaction between a trust domain and an accelerator **150, 170** or other I/O devices **160, 180** or block any transaction that may be potentially malicious. To do so, the filter logic **122, 140, 172, 182** may be programmed by the trust domain with one or more private key identifiers (KIDs) of the trust domain for trusted I/O devices and a range of shared KIDs that may be used for untrusted I/O devices. Each DMA transaction generated by an I/O device may include a key identifier (KID) and a trust device ID (TID) indicator, which indicates whether the I/O device is assigned to the trust domain.

(11) For example, when an accelerator **150, 170** generates a DMA transaction to access trust domain memory, the DMA transaction includes a KID and a TID indicator. In response to receiving

the DMA transaction, the filter logic **122, 140, 172, 182** may determine whether the TID indicator (e.g., a TID flag) was asserted to determine whether the corresponding accelerator **150, 170** is a trusted I/O device to allow secure I/O with the trust domain. The TID indicator is a flag that may be asserted in the DMA transaction to indicate that the corresponding I/O device is assigned to the trust domain. In other words, the assertion of the TID indicator (i.e., the TID flag was set) indicates that the filter logic **122, 140, 172, 182** is programmed by the trust domain with one or more private key identifiers (KIDs) of the trust domain for trusted I/O devices. If the TID indicator was not asserted (i.e., the TID flag was not set), the filter logic **122, 140, 172, 182** may further determine whether the KID is within a shared KID range assigned by the trust domain to determine whether to allow I/O with a memory outside of the trust domain. Accordingly, the filter logic **122, 140, 172, 182** may filter data transactions generated by an accelerator or other I/O device to allow I/O with a trust domain memory, allow I/O with a memory outside of the trust domain, or block transactions as being potentially malicious, which may improve security and/or performance of the compute device **100**. It should be appreciated that, although the trust domain is described as being a single trust domain throughout the present application, the filter logic **122, 140, 172, 182** may monitor and filter data transaction between one or more trust domains and an I/O device (e.g., an accelerator **150, 170** or other I/O device **160, 180**). Additionally, it should be also appreciated that trusted devices may not be universally trusted by all trusted domains. In other words, one trusted device may be trusted by one trusted domain but not by another trusted domain. When multiple trust domains are involved, the filter logic **122, 140, 172, 182** may determine which trust domain's memory that a given I/O device is allowed to access based on an internal table, which may only be programmed by the trust domains.

(12) The compute device **100** may be embodied as any type of device capable of performing the functions described herein. For example, the compute device **100** may be embodied as, without limitation, a computer, a laptop computer, a tablet computer, a notebook computer, a mobile compute device, a smartphone, a wearable compute device, a multiprocessor system, a server, a workstation, a distributed compute device, a disaggregated compute device, and/or a consumer electronic device. As shown in FIG. 1, the illustrative compute device **100** includes a processor **110**, an I/O subsystem **120**, a memory **130**, a communication subsystem **190**, one or more accelerators **150, 170**, one or more I/O devices **160, 180**, and a filter logic **122, 140, 172, 182**. Additionally, in some embodiments, one or more of the illustrative components may be incorporated in, or otherwise form a portion of, another component. For example, the memory **130**, or portions thereof, may be incorporated in the processor **110** in some embodiments.

(13) The processor **110** may be embodied as any type of processor capable of performing the functions described herein. For example, the processor **110** may be embodied as a single or multi-core processor(s), digital signal processor, microcontroller, or other processor or processing/controlling circuit. As shown, the processor **110** illustratively includes multi-key total memory encryption (MKTME) support **112**. The MKTME **112** may encrypt data that is transmitted to the memory **130** for storage and decrypt encrypted data retrieved from the memory **130**.

(14) The MKTME support **112** allows the processor **110** to transparently encrypt the contents of the memory **130**. The MKTME support **112** maintains a table or other internal, protected structure with multiple encryption keys, which are used to encrypt and decrypt data as it is stored to and read from the memory **130**, respectively. The encryption keys are illustratively 128-bit AES XTS keys although may be embodied as any symmetric, asymmetric, or other encryption key. The encryption key may be selected by the MKTME support **112** on a per-page basis, for example based on a key identifier included in one or more otherwise unused upper bits of the physical memory page address for a particular memory access. In those embodiments, an operating system, virtual memory monitor, or other supervisory component of the compute device **100** may control access to particular memory pages by configuring one or more page tables and/or extended page tables with the appropriate key identifiers. MKTME keys may be generated by the MKTME support **112**, in

which case they are not disclosed outside of the processor **110**, or may be supplied by software. In some embodiments, the MKTME support **112** may include support for Intel Trusted Domain Extensions (TDX). With TDX, the MKTME support **112** may accept an external “domain” key, also called a “user” or “tenant” key. The processor **110** may also use a default key that is self-generated to protect memory used by MKTME and Intel SGX as well as Intel TDX.

(15) The memory **130** may be embodied as any type of volatile or non-volatile memory or data storage capable of performing the functions described herein. In operation, the memory **130** may store various data and software used during operation of the compute device **100** such as operating systems, applications, programs, libraries, and drivers. As described above, in some embodiments, part or all of the contents of the memory **130** may be encrypted or otherwise protected from unauthorized disclosure using the MKTME support **112** of the processor **110**. Illustratively, the memory **130** is communicatively coupled to the processor **110** via the I/O subsystem **120**, which may be embodied as circuitry and/or components to facilitate input/output operations with the processor **110**, the memory **130**, and other components of the compute device **100**.

(16) For example, the I/O subsystem **120** may be embodied as, or otherwise include, memory controller hubs, input/output control hubs, sensor hubs, host controllers, firmware devices, communication links (i.e., point-to-point links, bus links, wires, cables, light guides, printed circuit board traces, etc.) and/or other components and subsystems to facilitate the input/output operations. In some embodiments, the memory **130** may be directly coupled to the processor **110**, for example via an integrated memory controller hub or a data port. The I/O subsystem **120** may further include a sideband network, secure fabric, or other secure routing support. The secure routing support may include hardware support to ensure I/O data cannot be misrouted in the I/O subsystem **120** under the influence of rogue software. Additionally, in some embodiments, the I/O subsystem **120** may form a portion of a system-on-a-chip (SoC) and be incorporated, along with the processor **110**, the memory **130**, and other components of the compute device **100**, on a single integrated circuit chip. The compute device **100** may include a data storage device (not shown), which may be embodied as any type of device or devices configured for short-term or long-term storage of data such as, for example, memory devices and circuits, memory cards, hard disk drives, solid-state drives, non-volatile flash memory, or other data storage devices.

(17) The accelerator **150**, **170** may be embodied as any coprocessor, field-programmable gate array (FPGA), application-specific integrated circuit (ASIC), or other hardware- or software-based accelerator that is capable of performing accelerated processing for the compute device **100**. The accelerator **150**, **170** may access large amounts of memory stored in the memory **130** via the I/O subsystem **120**. In some embodiments, the accelerator **150**, **170** may include a cache or other local memory other than the main memory **130**. It should be appreciated that, although the compute device **100** depicted in FIG. 1 includes one accelerator **150** and one accelerator **170** with a filter logic, the compute device may include any given number of accelerator(s) **150** and **170**. For example, in some embodiments, the compute device **100** may include one or more accelerator **150** and/or one or more accelerator **170**.

(18) The I/O device **160**, **180** may be embodied as an accelerator **150**, **170**, a peripheral device (not shown), and/or or other I/O device of the compute device **100**. For example, in some embodiments, the peripheral devices may include a touch screen, graphics circuitry, a graphical processing unit (GPU) and/or processor graphics, an audio device, a microphone, a camera, a keyboard, a mouse, a network interface, and/or other input/output devices, interface devices, and/or peripheral devices. It should be appreciated that, although the compute device **100** depicted in FIG. 1 includes one I/O device **160** and one I/O device **180** with a filter logic, the compute device may include any given number of I/O device(s) **160** and **180**. For example, in some embodiments, the compute device **100** may include one or more I/O device **160** and/or one or more I/O device **180**.

(19) As shown, the compute device **100** further includes a filter logic **122**, **140**, **172**, **182**. The filter logic **122**, **140**, **172**, **182** may be embodied as any hardware controller(s), component(s), or other

circuitry capable of performing the functions described herein. In particular, the filter logic **122**, **140**, **172**, **182** may filter I/O transactions as described further below. It should be appreciated that the filter logic may be incorporated in an I/O device itself. For example, the filter logic **172** and the filter logic **182** are incorporated in the accelerator **170** and the I/O device **180**, respectively. In such embodiments, the I/O device **170**, **180** with the filter logic **172**, **182** may use an authentication scheme similar to the PCIe-Sig standard for Universal Serial Bus (USB) device authentication to attest itself as a trusted I/O device to the trust domain. It should be appreciated that the filter logic **172**, **182** is configured to filter data transactions generated by the associated I/O device (e.g., an accelerator **170** or an I/O device **180**). Additionally or alternatively, in some embodiments, the filter logic may be incorporated along the I/O path from the I/O device to a single integrated circuit chip. For example, as illustrated in FIG. 1, the filter logic **140** is incorporated along the I/O path to a single integrated circuit chip that may include the processor **110**, the I/O subsystem **120**, and the memory **130**. It should be appreciated that the filter logic **140** is configured to filter data transactions generated by one or more accelerators or I/O devices of the compute device **100**.

(20) Additionally or alternatively, in other embodiments, the filter logic may form a portion of a processor **110** or an integrated circuit chip (e.g., a root complex or other system-on-a-chip (SoC) component). For example, the filter logic **122** is incorporated in the I/O subsystem **120** as a portion of a SoC. In such embodiments, the root complex or other system-on-a-chip (SoC) component may include one or more ports, such as PCI express ports, IAL ports, or other ports. Each port may be coupled to one or more accelerators and/or other I/O devices, and the filter logic **122** may be incorporated in each ports to filter transactions generated by one or more accelerators or I/O devices coupled to that port. In some embodiments, filtering may be performed for Intel Accelerator Link (IAL) devices, including secure use of IAL.mem and IAL.cache. In such embodiments, the filter logic is included in a SoC's control module, MS2IAL, for cache accesses. This filter logic may be programmed statically by a trusted agent during boot. As described further below, the filter logic may drop all cache accesses where the KID of a DMA transaction falls within the private KID reserved for trust domains. Alternatively, the MS2IAL module may be programmed dynamically after boot. MS2IAL will allow only those trust domain memory accesses whose KIDs is programmed in the filter logic. It should be appreciated that, although the compute device depicted in FIG. 1 includes all of the filter logics **122**, **140**, **172**, and **182**, in some embodiments the compute device **100** may include any one or more of the filter logic **122**, the filter logic **140**, the filter logic **172**, and/or the filter logic **182**.

(21) The compute device **100** also includes the communication subsystem **190**, which may be embodied as any communication circuit, device, or collection thereof, capable of enabling communications between the compute device **100** and other remote devices over a computer network (not shown). The communication subsystem **190** may be embodied as any network interface card, network adapter, network controller, host fabric interface, network coprocessor, or other component that connects the compute device **100** to a computer network. The communication subsystem **190** may be configured to use any one or more communication technology (e.g., wired or wireless communications) and associated protocols (e.g., Ethernet, InfiniBand®, Bluetooth®, Wi-Fi®, WiMAX, 3G, 4G LTE, etc.) to effect such communication. In some embodiments, the communication subsystem **190** may form a portion of an SoC and be incorporated along with the processor **110**, the memory **130**, the I/O subsystem **120**, and/or other components of the compute device **100** on a single integrated circuit chip.

(22) Referring now to FIG. 2, in an illustrative embodiment, the filter logic **122**, **140**, **172**, **182** of the compute device **100** establishes an environment **200** during operation. The illustrative environment **200** includes a trust domain communicator **210**, an I/O communicator **220**, a transaction filter **230**, and a trusted device manager **240**. The various components of the environment **200** may be embodied as hardware, firmware, software, or a combination thereof. As such, in some embodiments, one or more of the components of the environment **200** may be

embodied as circuitry or collection of electrical devices (e.g., trust domain communicator circuitry **210**, I/O communicator circuitry **220**, transaction filter circuitry **230**, and/or trusted device manager circuitry **240**). It should be appreciated that, in such embodiments, one or more of the trust domain communicator circuitry **210**, the I/O communicator circuitry **220**, the transaction filter circuitry **230**, and/or the trusted device manager circuitry **240** may form a portion of the filter logic **122**, **140**, **172**, **182**. Additionally, in some embodiments, one or more of the illustrative components may form a portion of another component and/or one or more of the illustrative components may be independent of one another.

(23) The trust domain communicator **210** is configured to communicate with a trust domain to receive one or more private KIDs of the trust domain for trusted I/O devices, which is stored in a private KID database **204**. In some embodiments, the trust domain communicator **210** may also be configured to communicate with a trust domain to receive a range of shared KIDs that may be used for untrusted I/O devices. However, it should be appreciated that, in some embodiments, the range of shared KIDs may be received from the processor **110** of the compute device. The range of shared KIDs is stored in a shared KID database **202**. As discussed above and further below, the KID ranges are to be used by the transaction filter **230** to determine whether an I/O device (e.g., an accelerator or other I/O device) can establish a secure I/O communication with the trust domain (e.g., to access a trust domain memory).

(24) The I/O communicator **220** is configured to communicate with an I/O device (e.g., an accelerator or other I/O device) to receive a DMA transaction generated by the I/O device that requests to access a memory (e.g., the trust domain memory or the memory outside of the trust domain). As discussed above, the DMA transaction includes a key identifier (KID) and a trusted device identifier (TID) indicator.

(25) The transaction filter **230** is configured to filter DMA transactions received from an I/O device (e.g., an accelerator or other I/O device) based on the KID and the TID indicator associated with the DMA transaction. As discussed further below, the transaction filter **230** is configured to determine whether the DMA transaction is asserted with the TID indicator. If the TID indicator is asserted, the transaction filter **230** allows the I/O device to access the trust domain memory securely using the MKTME support. If the TID indicator was not asserted, the transaction filter **230** is further configured to determine whether the KID is within a shared KID range assigned by the trust domain. As discussed above and further below, if the KID is within a shared KID range, the transaction filter **230** allows the requesting I/O device to access the memory outside of the trust domain. However, if the KID of the data transaction received from the requesting I/O device is not within the shared KID range, the transaction filter **230** determines that the transaction is potentially malicious and blocks the data transaction. Accordingly, the transaction filter **230** is configured to monitor and filter the data transaction from the requesting I/O device (e.g., an accelerator or other I/O device) to allow access to the trust domain memory, allow access to the memory outside of the trust domain, or block the transaction as being potentially malicious.

(26) Once the transaction filter **230** allows the I/O device (e.g., an accelerator or other I/O device) to access the trust domain memory in response to a determination that the DMA transaction is asserted with the TID indicator, the trusted device manager **240** is configured to replace the KID received from the accelerator with a private KID of the trust domain. As discussed above, the TID indicator is a flag that is asserted in the DMA transaction to indicate that the corresponding I/O device is assigned to the trust domain. For example, in some embodiments, if the TID indicator or flag is set, the trusted device manager **240** replaces one or more most significant bits (MSBs) of an address of the transaction with the assigned private KID to allow secure I/O with the trust domain.

(27) Referring now to FIGS. **3** and **4**, in use, the compute device **100** may execute a method **300** for filtering memory access transactions from an I/O device to establish a secure data transfer between an I/O device and a trust domain. It should be appreciated that, in some embodiments, the operations of the method **300** may be performed by one or more components of the environment

200 of the filter logic **172** of the compute device **100** as shown in FIG. 2. The method **300** begins in block **302**, in which the filter logic **172** receives a key identifier (KID) ranges from a trust domain. For example, as indicated in block **304**, the filter logic **172** receives a shared KID range assigned by an operating system, trust domain, or other entity that may be used for untrusted I/O devices. In some embodiments, the filter logic **172** may also receive one or more private KIDs of the trust domain assigned to one or more trusted I/O devices as indicated in block **306**.

(28) In block **308**, the filter logic **172** receives a direct memory access (DMA) transaction that includes a KID and a trust device ID (TID) indicator or flag from an accelerator **170**. In block **310**, the filter logic **172** determines whether a transaction has been received. If the filter logic **172** determines that a transaction has not been received, the method **300** loops back to block **308** to continue waiting for a transaction from an accelerator. If, however, the filter logic **172** determines that a transaction has been received from an accelerator, the method **300** advances to block **312**.

(29) In block **312**, the filter logic **172** determines whether the transaction is asserted with the TID flag (e.g., whether the TID flag is set). As discussed above, the TID flag indicates whether the accelerator **170** is programmed to securely communicate with the processor **110**. In other words, if the TID is set, the filter logic **172** is programmed with one or more private KID of the trust domain for trusted I/O devices. If the filter logic **172** determines in block **314** that the TID flag has not been asserted (i.e., the TID flag is not set), the method **300** skips ahead to block **322** in FIG. 4, which is discussed in detail below. If, however, the filter logic **172** determines that the TID flag has been asserted, the method **300** advances to block **316**, in which the filter logic **172** allows the transaction to access the trust domain. To do so, in block **316**, the filter logic **172** replaces the KID received from the accelerator with a private KID of the trust domain. For example, the filter logic **172** may replace one or more most significant bits (MSBs) of an address of the transaction with the assigned private KID as indicated in block **318**. Subsequently, in block **320**, the filter logic **172** performs secure I/O with the trust domain to access a trust domain memory using MKTME support. After performing secure I/O, the method **300** loops back to block **308** to continue processing transactions received from the accelerator.

(30) Referring now back to block **314**, if the filter logic **172** determines that the TID flag is not set, the method **300** skips ahead to block **322** of FIG. 4 to determine whether the KID included in the DMA transaction from the accelerator **170** falls within the shared KID range. As discussed above, the shared KID range is assigned by an operating system, trust domain, or other entity to be used for untrusted I/O devices to allow the untrusted I/O devices to access memory outside of any trust domain memory. If the filter logic **172** determines that the KID asserted by the accelerator is within the shared KID range assigned by the trust domain, the method **300** advances to block **326**. In block **326**, the filter logic **172** allows the transaction to perform I/O with the memory outside of the trust domain. Subsequently, the method **300** loops back to block **308**, shown in FIG. 3, to continue waiting for a transaction from an I/O device.

(31) Referring back to block **324**, if the filter logic **172** determines that the KID asserted by the accelerator **170** is not within the shared KID range assigned by the trust domain, the method **300** advances to block **328**. In block **328**, the filter logic **172** blocks the DMA transaction as potentially malicious. Thus, the filter logic **172** may prevent unauthorized access to trust domain memory or other memory outside of the shared KID range. In some embodiments, as indicated in block **330**, the filter logic **172** may further transmit a warning notification to a trust domain owner of the KID asserted by the accelerator **170**. Subsequently, the method **300** loops back to block **308** to continue waiting for a transaction from an I/O device.

(32) The method **300** is described with reference to the filter logic **172** and the accelerator **170**. However, it should be understood that the method **300** could be additionally or alternatively performed using the filter logic **182** and the I/O device **180**. Additionally, it should be appreciated that the filter logic **122**, **140** may be used with an I/O device that does not have a filter logic incorporated in the I/O device itself (i.e., the accelerator **150** and the I/O device **160**). In such

embodiments, the filter logic **122, 140** is configured to receive all DMA transactions from any I/O devices **150, 160, 170, 180**.

(33) It should further be appreciated that, in some embodiments, the method **300** may be embodied as various instructions stored on a computer-readable media, which may be executed by the processor **110**, the I/O subsystem **120**, the filter logic **122, 140, 172, 182**, and/or other components of the compute device **100** to cause the compute device **100** to perform the respective method **300**. The computer-readable media may be embodied as any type of media capable of being read by the compute device **100** including, but not limited to, the memory **130**, the data storage device **128**, firmware devices, other memory or data storage devices of the compute device **100**, portable media readable by a peripheral device **136** of the compute device **100**, and/or other media.

EXAMPLES

(34) Illustrative examples of the technologies disclosed herein are provided below. An embodiment of the technologies may include any one or more, and any combination of, the examples described below.

(35) Example 1 includes a compute device for secure I/O, the compute device comprising a processor; a memory; an input/output (I/O) device; and a filter logic configured to receive a first key identifier from the processor, wherein the first key identifier is indicative of a shared memory range includes a shared key identifier range to be used for untrusted I/O devices; receive a transaction from the I/O device, wherein the transaction includes a second key identifier and a trust device ID indicator associated with the I/O device; determine whether the transaction is asserted with the trust device ID indicator indicative of whether the I/O device is assigned to a trust domain; and determine, in response to a determination that the transaction is not asserted with the trust device ID indicator, whether the second key identifier matches the first key identifier.

(36) Example 2 includes the subject matter of Example 1, and wherein the transaction is a direct memory access transaction.

(37) Example 3 includes the subject matter of any of Examples 1 and 2, and wherein the trust device ID indicator indicates whether the corresponding I/O device is assigned to the trust domain.

(38) Example 4 includes the subject matter of any of Examples 1-3, and wherein the filter logic is further configured to receive a third key identifier from the trust domain, wherein the third key identifier is indicative of a private key identifier of the trust domain, wherein to perform the secure I/O with the trust domain comprises to replace, in response to determining that the trust device ID indicator is asserted, the second key identifier with the third key identifier and to perform the secure I/O with the trust domain.

(39) Example 5 includes the subject matter of any of Examples 1-4, and wherein the filter logic is further configured to perform, in response to determining that the trust device ID indicator is asserted, a secure I/O with the trust domain.

(40) Example 6 includes the subject matter of any of Examples 1-5, and wherein to replace the second key identifier with the third key identifier of the trust domain comprises to replace one or more most significant bits of an address of the transaction with the private key identifier.

(41) Example 7 includes the subject matter of any of Examples 1-6, and wherein the filter logic is further configured to perform, in response to determining that the second key identifier falls within the shared key identifier range, I/O with a memory outside of the trust domain; and block, in response to determining that the second key identifier does not fall within the shared key identifier range, the transaction.

(42) Example 8 includes the subject matter of any of Examples 1-7, and wherein the filter logic is further configured to transmit, in response to determining that the second key identifier does not fall within the shared key identifier range, a warning notification to a trust domain owner of the second key identifier.

(43) Example 9 includes the subject matter of any of Examples 1-8, and wherein the filter logic is coupled between the processor and the I/O device.

- (44) Example 10 includes the subject matter of any of Examples 1-9, and wherein the filter logic is included in the I/O device.
- (45) Example 11 includes the subject matter of any of Examples 1-10, and wherein the filter logic is included in the processor.
- (46) Example 12 includes a method for secure I/O, the method comprising receiving, by a filter logic of a compute device, a first key identifier from a processor of the compute device, wherein the first key identifier indicative of a shared memory range includes a shared key identifier range to be used for untrusted input/output (I/O) devices; receiving, by the filter logic, a transaction from an input/output (I/O) device, wherein the transaction includes a second key identifier and a trust device ID indicator associated with the I/O device; determining, by the filter logic, whether the transaction is asserted with the trust device ID indicator indicative of whether the I/O device is assigned to a trust domain; and determining, in response to determining that the transaction is not asserted with the trust device ID indicator and by the filter logic, whether the second key identifier matches the first key identifier.
- (47) Example 13 includes the subject matter of Example 12, and wherein the transaction is a direct memory access transaction.
- (48) Example 14 includes the subject matter of any of Examples 12 and 13, and wherein the trust device ID indicator indicates whether the corresponding I/O device is assigned to the trust domain.
- (49) Example 15 includes the subject matter of any of Examples 12-14, and further including receiving, by the filter logic, a third key identifier from the trust domain, wherein the third key identifier is indicative of a private key identifier of the trust domain, wherein performing the secure I/O with the trust domain comprises replacing, in response to determining that the trust device ID indicator is asserted and by the filter logic, the second key identifier with the third key identifier and performing the secure I/O with the trust domain.
- (50) Example 16 includes the subject matter of any of Examples 12-15, and further including performing, in response to determining that the trust device ID indicator is asserted and by the filter logic, a secure I/O with the trust domain.
- (51) Example 17 includes the subject matter of any of Examples 12-16, and wherein replacing the second key identifier with the third key identifier of the trust domain comprises replacing, by the filter logic, one or more most significant bits of an address of the transaction with the third key identifier.
- (52) Example 18 includes the subject matter of any of Examples 12-17, and further including performing, in response to determining that the second key identifier falls within the shared key identifier range and by the filter logic, I/O with a memory outside of the trust domain; and blocking, in response to determining that the second key identifier does not fall within the shared key identifier range and by the filter logic, the transaction.
- (53) Example 19 includes the subject matter of any of Examples 12-18, and further including transmitting, in response to determining that the second key identifier does not fall within the shared key identifier range and by the filter logic, a warning notification to a trust domain owner of the second key identifier.
- (54) Example 20 includes one or more machine-readable storage media comprising a plurality of instructions stored thereon that, in response to being executed, cause a compute device to receive a first key identifier from the processor, wherein the first key identifier indicative of a shared memory range includes a shared key identifier range to be used for untrusted input/output (I/O) devices; receive a transaction from an I/O device, wherein the transaction includes a second key identifier and a trust device ID indicator associated with the I/O device; determine whether the transaction is asserted with the trust device ID indicator indicative of whether the I/O device is assigned to a trust domain; and determine, in response to a determination that the transaction is not asserted with the trust device ID indicator, whether the second key identifier matches the first key identifier.

Claims

1. An apparatus comprising: a processor; and a filter circuitry to: determine whether a transaction from an input/output (I/O) device is asserted with a trust device identifier indicator indicative that the I/O device is assigned to a trust domain; allow the I/O device to access memory within the trust domain when the transaction is asserted with the trust device identifier indicator, including to store a private key identifier of the trust domain in a plurality of upper bits of an address of the transaction, wherein the private key identifier is to identify a private key of the trust domain, wherein contents of the memory within the trust domain are to be encrypted with a key that is not accessible to a virtual machine monitor (VMM); and not allow the I/O device to access the memory within the trust domain when the transaction is not asserted with the trust device identifier indicator.
2. The apparatus of claim 1, wherein the filter circuitry, when the transaction is asserted with the trust device identifier indicator, is to replace a first key identifier with a in the plurality of upper bits with the private key identifier.
3. The apparatus of claim 2, wherein the filter circuitry is to receive the private key identifier from the trust domain.
4. The apparatus of claim 1, wherein, when the transaction is not asserted with the trust device identifier indicator, the filter circuitry is to determine whether a first key identifier asserted with the transaction matches a shared key identifier or is within a shared key identifier range, the shared key identifier or the shared key identifier range corresponding to shared memory to be used for untrusted I/O.
5. The apparatus of claim 4, wherein the filter circuitry, when the first key identifier matches the shared key identifier or is within the shared key identifier range, is to allow the I/O device to access memory outside of the trust domain.
6. The apparatus of claim 5, wherein the filter circuitry, when the first key identifier does not match the shared key identifier or is not within the shared key identifier range, is to block the transaction.
7. The apparatus of claim 6, wherein the filter circuitry, when the first key identifier does not match the shared key identifier or is not within the shared key identifier range, is to cause a warning to be provided.
8. The apparatus of claim 4, wherein the filter circuitry is to receive the shared key identifier or the shared key identifier range from the processor.
9. The apparatus of claim 1, wherein the transaction is a direct memory access (DMA) transaction.
10. The apparatus of claim 1, wherein the filter circuitry is coupled between the processor and the I/O device.
11. The apparatus of claim 1, wherein the filter circuitry is included in the I/O device.
12. A method comprising: receiving a transaction from an input/output (I/O) device at a filter circuitry within one of an IOMMU and a root complex; determining, by the filter circuitry, whether the transaction is asserted with a trust device identifier indicator indicative that the I/O device is assigned to a trust domain; allowing, by the filter circuitry, the I/O device to access memory within the trust domain when the transaction is asserted with the trust device identifier indicator, including replacing a first key identifier in a plurality of upper bits of an address of the transaction with a private key identifier that identifies a private key of the trust domain, wherein contents of the memory within the trust domain are encrypted with a key not known to a virtual machine monitor (VMM); and not allowing the I/O device to access the memory within the trust domain when the transaction is not asserted with the trust device identifier indicator.
13. The method of claim 12, further comprising replacing a first key identifier in the plurality of upper bits with the private key identifier when the transaction is asserted with the trust device identifier indicator.

14. The method of claim 12, further comprising determining whether a first key identifier asserted with the transaction matches a shared key identifier or is within a shared key identifier range when the transaction is not asserted with the trust device identifier indicator, the shared key identifier or the shared key identifier range corresponding to shared memory used for untrusted I/O.
15. The method of claim 14, further comprising: allowing the I/O device to access memory outside of the trust domain when the first key identifier matches the shared key identifier or is within the shared key identifier range; and blocking the transaction when the first key identifier does not match the shared key identifier or is not within the shared key identifier range.
16. A system comprising: a system memory; a processor coupled with the system memory; an input/output (I/O) device; and a filter circuitry coupled with the processor and coupled with the I/O device, the filter circuitry to: determine whether a transaction from the I/O device is asserted with a trust device identifier indicator indicative that the I/O device is assigned to a trust domain; allow the I/O device to access memory within the trust domain when the transaction is asserted with the trust device identifier indicator, including to store a private key identifier of the trust domain in a plurality of upper bits of an address of the transaction, wherein the private key identifier is to identify a private key of the trust domain, wherein contents of the memory within the trust domain are to be encrypted with a key that a virtual machine monitor (VMM) cannot access; and not allow the I/O device to access the memory within the trust domain when the transaction is not asserted with the trust device identifier indicator.
17. The system of claim 16, wherein the filter circuitry, when the transaction is asserted with the trust device identifier indicator, is to replace a first key identifier in the plurality of upper bits with the private key identifier.
18. The system of claim 16, wherein, when the transaction is not asserted with the trust device identifier indicator, the filter circuitry is to determine whether a first key identifier asserted with the transaction matches a shared key identifier or is within a shared key identifier range, the shared key identifier or the shared key identifier range corresponding to shared memory to be used for untrusted I/O, wherein the filter circuitry, when the first key identifier matches the shared key identifier or is within the shared key identifier range, is to allow the I/O device to access memory outside of the trust domain.
19. The system of claim 18, wherein the filter circuitry, when the first key identifier does not match the shared key identifier or is not within the shared key identifier range, is to block the transaction.
-