

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417588
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Evangelidis; Georgios et al.

Fast AR device pairing using depth predictions

Abstract

A method for aligning coordinate systems from separate augmented reality (AR) devices is described. In one aspect, the method includes generating predicted depths of a first point cloud by applying a pre-trained model to a first single image generated by a first monocular camera of a first augmented reality (AR) device, and first sparse 3D points generated by a first SLAM system at the first AR device, generating predicted depths of a second point cloud by applying the pre-trained model to a second single image generated by a second monocular camera of the second AR device, and second sparse 3D points generated by a second SLAM system at the second AR device, determining a relative pose between the first AR device and the second AR device by registering the first point cloud with the second point cloud.

Inventors: Evangelidis; Georgios (Vienna, AT), Micusik; Branislav (St.Andrae-Woerden, AT), Zillner; Jakob (Absdorf, AT), Litke; Nathan Jacob (Redondo Beach, CA)

Applicant: Snap Inc. (Santa Monica, CA)

Family ID: 1000008819217

Assignee: Snap Inc. (Santa Monica, CA)

Appl. No.: 17/893723

Filed: August 23, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230401796 A1	Dec. 14, 2023

Foreign Application Priority Data

GR	0220100478	Jun. 08, 2022
----	------------	---------------

Publication Classification

Int. Cl.: **G06T19/00** (20110101); **G06T7/55** (20170101); **G06T7/73** (20170101); **G06T19/20** (20110101); **G06V20/20** (20220101)

U.S. Cl.:

CPC **G06T19/006** (20130101); **G06T7/55** (20170101); **G06T7/74** (20170101); **G06T19/20** (20130101); **G06V20/20** (20220101); G06T2207/10028 (20130101); G06T2207/30244 (20130101); G06T2219/024 (20130101)

Field of Classification Search

CPC: G06T (19/006); G06T (7/74); G06T (19/20); G06T (2207/10028); G06T (2207/30244); G06T (2219/024); G06T (2207/10024); G06T (2207/20084); G06T (7/55); G06V (20/20); G06F (3/011); G06F (3/012)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10290049	12/2018	Xu	N/A	G06T 19/20
2019/0026948	12/2018	Kellogg	N/A	G06T 19/006
2019/0197788	12/2018	Forbes	N/A	G06T 15/005
2020/0242835	12/2019	Cherukuri	N/A	G06T 19/006
2020/0394012	12/2019	Wright, Jr.	N/A	G06F 3/005
2021/0142497	12/2020	Pugh	N/A	G06T 7/543
2021/0174570	12/2020	Bleyer	N/A	G02B 27/017
2021/0326584	12/2020	Kim	N/A	G06V 40/20
2021/0373336	12/2020	Price	N/A	G02B 27/0172
2023/0161418	12/2022	Gribetz	345/156	G06F 3/011

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
112581629	12/2020	CN	G06T 17/00
WO-2019174377	12/2018	WO	G06T 17/00
2023239776	12/2022	WO	N/A

OTHER PUBLICATIONS

Jae-Won Kam, Robust and Fast Collaborative Augmented Reality Framework Based on Monocular SLAM, Aug. 2020, IEIE Transactions on Smart Processing and Computing, vol. 9, No. 4, pp. 325-335 (Year: 2020). cited by examiner

Fangchang Ma, Sparse-to-Dense: Depth Prediction from Sparse Depth Samples and a Single Image, 2018, arXiv:1709.04749v2, pp. 1-8 (Year: 2018). cited by examiner
“International Application Serial No. PCT/US2023/024688, International Search Report mailed Sep. 21, 2023”, 4 pgs. cited by applicant
“International Application Serial No. PCT/US2023/024688, Written Opinion mailed Sep. 21, 2023”, 7 pgs. cited by applicant
Ran, Xukan Xran, “Multi-user augmented reality with communication efficient and spatially consistent virtual objects”, Proceedings of the IEEE ACM 42nd International Conference on Software Engineering Workshops, Acmpub27, New York, NY, USA,, (Nov. 23, 2020), 386-398. cited by applicant

Primary Examiner: LaPage; Michael P

Attorney, Agent or Firm: Schwegman Lundberg & Woessner, P.A.

Background/Summary

CLAIM OF PRIORITY

(1) This application claims the benefit of priority to Greece Application Serial No. 20220100478, filed Jun. 8, 2022, which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(2) The subject matter disclosed herein generally relates to an augmented reality (AR) device. Specifically, the present disclosure addresses systems and methods for pairing AR devices using depth predictions from monocular cameras.

BACKGROUND

(3) An augmented reality (AR) device enables a user to observe a scene while simultaneously seeing relevant virtual content that may be aligned to items, images, objects, or environments in the field of view of the device. A virtual reality (VR) device provides a more immersive experience than an AR device. The VR device blocks out the field of view of the user with virtual content that is displayed based on a position and orientation of the VR device.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

- (1) To easily identify the discussion of any particular element or act, the most significant digit or digits in a reference number refer to the figure number in which that element is first introduced.
- (2) FIG. 1 is a block diagram illustrating a network environment for a collaborative augmented reality experience in accordance with one example embodiment.
- (3) FIG. 2 is a block diagram illustrating a network environment for a collaborative augmented reality experience in accordance with another example embodiment.
- (4) FIG. 3 is a block diagram illustrating an AR device in accordance with one example embodiment.
- (5) FIG. 4 is a block diagram illustrating a process for reconstructing a dense point cloud in accordance with one example embodiment.
- (6) FIG. 5 illustrates training and use of a machine-learning program, according to some example embodiments.
- (7) FIG. 6 is a block diagram illustrating a shared device application in accordance with one

example embodiment.

(8) FIG. 7 is a block diagram illustrating a server in accordance with one example embodiment.

(9) FIG. 8 is an interaction diagram illustrating an alignment operation in accordance with one example embodiment.

(10) FIG. 9 is an interaction diagram illustrating a collaborative AR experience in accordance with one example embodiment.

(11) FIG. 10 is a flow diagram illustrating a method for aligning reference coordinate frames in accordance with one example embodiment.

(12) FIG. 11 is a flow diagram illustrating a method for sharing an AR experience in accordance with one example embodiment.

(13) FIG. 12 illustrates a routine in accordance with one example embodiment.

(14) FIG. 13 is a diagram illustrating aligning coordinate systems from two AR devices in accordance with one embodiment.

(15) FIG. 14 illustrates a network environment in which a head-wearable device can be implemented according to one example embodiment.

(16) FIG. 15 is block diagram showing a software architecture within which the present disclosure may be implemented, according to an example embodiment.

(17) FIG. 16 is a diagrammatic representation of a machine in the form of a computer system within which a set of instructions may be executed for causing the machine to perform any one or more of the methodologies discussed herein, according to one example embodiment.

DETAILED DESCRIPTION

(18) The description that follows describes systems, methods, techniques, instruction sequences, and computing machine program products that illustrate example embodiments of the present subject matter. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide an understanding of various embodiments of the present subject matter. It will be evident, however, to those skilled in the art, that embodiments of the present subject matter may be practiced without some or other of these specific details. Examples merely typify possible variations. Unless explicitly stated otherwise, structures (e.g., structural Components, such as modules) are optional and may be combined or subdivided, and operations (e.g., in a procedure, algorithm, or other function) may vary in sequence or be combined or subdivided.

(19) The term “augmented reality” (AR) is used herein to refer to an interactive experience of a real-world environment where physical objects that reside in the real-world are “augmented” or enhanced by computer-generated digital content (also referred to as virtual content or synthetic content). AR can also refer to a system that enables a combination of real and virtual worlds, real-time interaction, and 3D registration of virtual and real objects. A user of an AR system perceives virtual content that appears to be attached or interact with a real-world physical object.

(20) The term “virtual reality” (VR) is used herein to refer to a simulation experience of a virtual world environment that is completely distinct from the real-world environment. Computer-generated digital content is displayed in the virtual world environment. VR also refers to a system that enables a user of a VR system to be completely immersed in the virtual world environment and to interact with virtual objects presented in the virtual world environment.

(21) The term “AR application” is used herein to refer to a computer-operated application that enables an AR experience. The term “VR application” is used herein to refer to a computer-operated application that enables a VR experience. The term “AR/VR application” refers to a computer-operated application that enables a combination of an AR experience or a VR experience.

(22) The term “visual tracking system” is used herein to refer to a computer-operated application or system that enables a system to track visual features identified in images captured by one or more cameras of the visual tracking system. The visual tracking system builds a model of a real-world environment based on the tracked visual features. Non-limiting examples of the visual tracking

system include: a visual Simultaneous Localization and Mapping system (VSLAM), and Visual Inertial Odometry (VIO) system. VSLAM can be used to build a target from an environment, or a scene based on one or more cameras of the visual tracking system. A VIO system (also referred to as a visual-inertial tracking system) determines a latest pose (e.g., position and orientation) of a device based on data acquired from multiple sensors (e.g., optical sensors, inertial sensors) of the device.

(23) The term “Inertial Measurement Unit” (IMU) is used herein to refer to a device that can report on the inertial status of a moving body including the acceleration, velocity, orientation, and position of the moving body. An IMU enables tracking of movement of a body by integrating the acceleration and the angular velocity measured by the IMU. IMU can also refer to a combination of accelerometers and gyroscopes that can determine and quantify linear acceleration and angular velocity, respectively. The values obtained from the IMUs gyroscopes can be processed to obtain the pitch, roll, and heading of the IMU and, therefore, of the body with which the IMU is associated. Signals from the IMU's accelerometers also can be processed to obtain velocity and displacement of the IMU.

(24) The term “three-degrees of freedom tracking system” (3DOF tracking system) is used herein to refer to a device that tracks rotational movement. For example, the 3DOF tracking system can track whether a user of a head-wearable device is looking left or right, rotating their head up or down, and pivoting left or right. However, the head-wearable device cannot use the 3DOF tracking system to determine whether the user has moved around a scene by moving in the physical world. As such, 3DOF tracking system may not be accurate enough to be used for positional signals. The 3DOF tracking system may be part of an AR/VR display device that includes IMU sensors. For example, the 3DOF tracking system uses sensor data from sensors such as accelerometers, gyroscopes, and magnetometers.

(25) The term “six-degrees of freedom tracking system” (6DOF tracking system) is used herein to refer to a device that tracks rotational and translational motion. For example, the 6DOF tracking system can track whether the user has rotated their head and moved forward or backward, laterally or vertically and up or down. The 6DOF tracking system may include a Simultaneous Localization and Mapping (SLAM) system and/or a VIO system that relies on data acquired from multiple sensors (e.g., depth cameras, inertial sensors). The 6DOF tracking system analyzes data from the sensors to accurately determine the pose of the display device.

(26) Each AR device may include its own 6DOF tracking system that generates its own reference coordinate system/frame. As such, two or more AR devices may have two or more different reference coordinate systems that are to be aligned to express the pose of any of the AR devices in a common coordinate system. Each AR device generates a dense point cloud based on its corresponding reference coordinate system. However, using a conventional depth sensor (e.g., using stereo vision camera) to generate the dense point cloud can be time-consuming. High-resolution depth is computed by processing visual information, which is a computationally demanding process. Typically, the AR device estimates a depth map for the whole image area of every processed frame. However, depth estimation in portable AR device may not be performed for every frame due to limited computational resources and power constraints. Similarly, pre-building a map of an existing physical environment can be time consuming and may raise privacy issues. Other standard solutions include the use of a marker (e.g., a predefined 2D image) to synchronize the coordinate systems of each AR device.

(27) The present application describes a system that enables two or more AR devices to share an AR experience by using single-view depth predictions to align the different coordinate systems of each AR device. In order to share AR experiences, the coordinates systems are aligned, so that poses (e.g., 3D position+orientation) of any device are expressed in a common coordinate system. The system uses depth-from-SLAM (VI-SLAM) to predict depth and reconstruct dense point cloud(s) from a single image per AR device. Each AR device perceives a same scene but from

different viewpoints. The system determines a relative pose of the AR devices (e.g., relative pose between VIO reference frames) by aligning/registering the overlapping regions of the point clouds. The system uses the relative pose to align in 3D the VIO reference coordinate frames of the AR devices for shared AR experiences.

(28) In one example embodiment, a method for aligning coordinate systems from separate augmented reality (AR) devices is described. In one aspect, the method includes generating predicted depths of a first point cloud by applying a pre-trained model to a first single image generated by a first monocular camera of a first augmented reality (AR) device, and first sparse 3D points generated by a first SLAM system at the first AR device, generating predicted depths of a second point cloud by applying the pre-trained model to a second single image generated by a second monocular camera of the second AR device, and second sparse 3D points generated by a second SLAM system at the second AR device, determining a relative pose between a first reference coordinate frame of the first AR device and a second reference coordinate frame of the second AR device by registering the first point cloud with the second point cloud based on corresponding predicted depths, and providing the relative pose to at least one of the first AR device or the second AR device.

(29) As a result, one or more of the methodologies described herein facilitate solving the technical problem of resource management from aligning coordinate systems from separate augmented reality (AR) devices. The presently described method provides an improvement to an operation of the functioning of a computer by providing power consumption reduction. As such, one or more of the methodologies described herein may obviate a need for certain efforts or computing resources. Examples of such computing resources include processor cycles, network traffic, memory usage, data storage capacity, power consumption, network bandwidth, and cooling capacity.

(30) FIG. 1 is a network diagram illustrating a network environment **100** suitable for operating an AR device A **112**, an AR device B **114**, and a server **110**, according to some example embodiments. The network environment **100** includes the AR device A **112**, the AR device B **114**, and the server **110**, communicatively coupled to each other via a network **104**. The AR device A **112**, AR device B **114**, and the server **110** may each be implemented in a computer system, in whole or in part, as described below with respect to FIG. 16. The server **110** may be part of a network-based system. For example, the network-based system may be or include a cloud-based server system that provides additional information, such as reference frame alignment data of the AR device A **112** and the AR device B **114**.

(31) A user **106** operates the AR device A **112**. The user **106** may be a human user (e.g., a human being), a machine user (e.g., a computer configured by a software program to interact with the AR device A **112**), or any suitable combination thereof (e.g., a human assisted by a machine or a machine supervised by a human). The user **106** operates the AR device A **112** by pointing the AR device A **112** towards physical object(s) **108** in the real world environment **102**.

(32) A user **116** operates the AR device B **114**. The user **116** may be a human user (e.g., a human being), a machine user (e.g., a computer configured by a software program to interact with the AR device B **114**), or any suitable combination thereof (e.g., a human assisted by a machine or a machine supervised by a human). The user **116** operates the AR device B **114** by pointing the AR device B **114** towards physical object(s) **108** in the real world environment **102**.

(33) The AR device A **112** and the AR device B **114**, each may be a computing device with a display such as a smartphone, a tablet computer, or a wearable computing device (e.g., watch or glasses). The computing device may be hand-held or may be removable mounted to a head of a user (e.g., user **106**, user **116**). In one example, the display may be a screen that displays what is captured with a camera of the AR device A **112**/AR device B **114**. In another example, the display of the device may be transparent, such as in lenses of wearable computing glasses, that allow a user to view content presented on the display while simultaneously viewing real world object visible through the display.

(34) The user **106** operates an AR application at the AR device A **112**. The AR application may be configured to provide the user **106** with an AR experience triggered by a physical object(s) **108**, such as a two-dimensional physical object (e.g., a picture), a three-dimensional physical object (e.g., a statue), a location (e.g., at factory), or any references (e.g., perceived corners of walls or furniture) in the real world environment **102**. For example, the user **106** may point a camera of the AR device A **112** to capture an image of the physical object(s) **108**.

(35) The user **116** operates an AR application at the AR device B **114**. The AR application may be configured to provide the user **116** with an AR experience triggered by the physical object(s) **108**, such as a two-dimensional physical object (e.g., a picture), a three-dimensional physical object (e.g., a statue), a location (e.g., at factory), or any references (e.g., perceived corners of walls or furniture) in the real world environment **102**. For example, the AR device B **114** may point a camera of the AR device B **114** to capture an image of the physical object(s) **108** from a different viewpoint (relative to AR device A **112**). As such, the images captured by the AR device A **112** and the AR device B **114** include overlapping regions.

(36) The AR device A **112** includes a tracking system (not shown). The tracking system tracks the pose (e.g., position and orientation) of the AR device A **112** relative to the real world environment **102** using optical sensors (e.g., image camera), inertia sensors (e.g., gyroscope, accelerometer), wireless sensors (Bluetooth, Wi-Fi), GPS sensor, and audio sensor to determine the location of the AR device A **112** within the real world environment **102**. In one example, the tracking system of the AR device A **112** uses a single image from a monocular camera of the AR device A **112** and sparse 3D points to predict a dense depth map and reconstruct a corresponding dense point cloud.

(37) The AR device B **114** includes a tracking system (not shown). The tracking system tracks the pose (e.g., position and orientation) of the AR device B **114** relative to the real world environment **102** using optical sensors (e.g., image camera), inertia sensors (e.g., gyroscope, accelerometer), wireless sensors (Bluetooth, Wi-Fi), GPS sensor, and audio sensor to determine the location of the AR device B **114** within the real world environment **102**. In one example, the tracking system of the AR device B **114** uses a single image from a monocular camera of the AR device B **114** and sparse 3D points to predict depth and reconstruct a dense point cloud.

(38) In one example embodiment, the server **110** receives the dense cloud point from AR device A **112** and AR device B **114** and aligns the dense point cloud between the AR device A **112** and the AR device B **114** to obtain the relative pose between the VIO reference frames of the AR device A **112** and AR device B **114**. The server **110** provides the alignment data (e.g., relative pose data) to the AR device A **112** and the AR device B **114**. In another example, the alignment of the dense point clouds may be performed on either AR device A **112**, AR device B **114**, or the server **110**, or a combination between the AR device A **112**, AR device B **114**, and the server **110**.

(39) Any of the machines, databases, or devices shown in FIG. **1** may be implemented in a general-purpose computer modified (e.g., configured or programmed) by software to be a special-purpose computer to perform one or more of the functions described herein for that machine, database, or device. For example, a computer system able to implement any one or more of the methodologies described herein is discussed below with respect to FIG. **10**. As used herein, a “database” is a data storage resource and may store data structured as a text file, a table, a spreadsheet, a relational database (e.g., an object-relational database), a triple store, a hierarchical data store, or any suitable combination thereof. Moreover, any two or more of the machines, databases, or devices illustrated in FIG. **1** may be combined into a single machine, and the functions described herein for any single machine, database, or device may be subdivided among multiple machines, databases, or devices.

(40) The network **104** may be any network that enables communication between or among machines (e.g., server **110**), databases, and devices (e.g., AR device A **112**, AR device B **114**). Accordingly, the network **104** may be a wired network, a wireless network (e.g., a mobile or cellular network), or any suitable combination thereof. The network **104** may include one or more portions that constitute a private network, a public network (e.g., the Internet), or any suitable

combination thereof.

(41) FIG. 2 is a block diagram illustrating a network environment **200** for a collaborative augmented reality experience in accordance with another example embodiment. The network environment **200** includes the AR device A **112** and the AR device B **114**. One of the AR devices receives the dense point cloud from the other AR device and performs the alignment. For example, AR device B **114** provides the dense point cloud to AR device A **112**. The AR device A **112** aligns the dense point cloud from the AR device A **112** with the dense point cloud from AR device B **114** to obtain the relative pose between the VIO reference frames of the AR device A **112** and AR device B **114**. The AR device A **112** uses the relative pose to align in 3D the VIO reference coordinate frames of AR device A **112** with AR device B **114**. The AR device A **112** uses the aligned VIO reference coordinate frames to display a virtual object anchored to the physical object(s) **108** or the real world environment **102**.

(42) FIG. 3 is a block diagram illustrating modules (e.g., components) of the AR device A **112**, according to some example embodiments. The AR device A **112** includes sensors **302**, a display **304**, a processor **308**, a Graphical processing unit **318**, a display controller **320**, and a storage device **306**. Examples of the AR device A **112** include a wearable computing device, a tablet computer, or a smart phone.

(43) The sensors **302** include an optical sensor **314** and an inertial sensor **316**. The optical sensor **314** includes a monocular camera. The inertial sensor **316** includes a combination of gyroscope, accelerometer, magnetometer. Other examples of sensors **302** include a proximity or location sensor (e.g., near field communication, GPS, Bluetooth, Wifi), an audio sensor (e.g., a microphone), or any suitable combination thereof. It is noted that the sensors **302** described herein are for illustration purposes and the sensors **302** are thus not limited to the ones described above. In one example embodiment, the AR device A **112** does not include a depth sensor such as a structured-light sensor, a time-of-flight sensor, passive stereo sensor, and an ultrasound device, time-of-flight sensor.

(44) The display **304** includes a screen or monitor configured to display images generated by the processor **308**. In one example embodiment, the display **304** may be transparent or semi-transparent so that the user **106** can see through the display **304** (in AR use case). In another example, the display **304**, such as a LCOS display, presents each frame of virtual content in multiple presentations.

(45) The processor **308** includes an AR application **310**, a 6DOF tracker **312**, a depth system **324**, and a shared device application **328**. The AR application **310** detects and identifies a physical environment or the physical object(s) **108** using computer vision. The AR application **310** retrieves a virtual object (e.g., 3D object model) based on the identified physical object(s) **108** or physical environment. The display **304** displays the virtual object. The AR application **310** includes a local rendering engine that generates a visualization of a virtual object overlaid (e.g., superimposed upon, or otherwise displayed in tandem with) on an image of the physical object(s) **108** captured by the optical sensor **314**. A visualization of the virtual object may be manipulated by adjusting a position of the physical object(s) **108** (e.g., its physical location, orientation, or both) relative to the optical sensor **314**. Similarly, the visualization of the virtual object may be manipulated by adjusting a pose of the AR device A **112** relative to the physical object(s) **108**.

(46) The 6DOF tracker **312** estimates a pose of the AR device A **112**. For example, the 6DOF tracker **312** uses image data and corresponding inertial data from the optical sensor **314** and the inertial sensor **316** to track a location and pose of the AR device A **112** relative to a frame of reference (e.g., real world environment **102**). In one example, the 6DOF tracker **312** uses the sensor data to determine the three-dimensional pose of the AR device A **112**. The three-dimensional pose is a determined orientation and position of the AR device A **112** in relation to the user's real world environment **102**. For example, the AR device A **112** may use images of the user's real world environment **102**, as well as other sensor data to identify a relative position and orientation of the

AR device A **112** from physical objects in the real world environment **102** surrounding the AR device A **112**. The 6DOF tracker **312** continually gathers and uses updated sensor data describing movements of the AR device A **112** to determine updated three-dimensional poses of the AR device A **112** that indicate changes in the relative position and orientation of the AR device A **112** from the physical objects in the real world environment **102**. The 6DOF tracker **312** provides the three-dimensional pose of the AR device A **112** to the **324** and the shared device application **328**.

(47) The depth system **324** accesses a single image from the optical sensor **314** (e.g., monocular camera) and sparse 3D points from the 6DOF tracker **312** to predict depths and generate a dense point cloud. In one example embodiment, the AR device A **112** does not include a depth sensor or a stereo sensor. The depth system **324** uses a trained model based on the single image and sparse 3D points to predict depths and generate the dense point cloud. The depth system **324** is described in more detail below with respect to FIG. 4.

(48) The shared device application **328** accesses the dense point cloud from AR device A **112** and the dense point cloud from AR device B **114** and performs a registration of the dense point cloud based on the partial overlapped regions of the respective dense point clouds. The shared device application **328** identifies the relative pose between the AR device A **112** and the AR device B **114**. The AR application **310** uses the relative pose to enable sharing of AR experience between the two AR devices. For example, the correct location/perspective of a virtual object is accurately presented in both the AR device A **112** and the AR device B **114** (e.g., user **116** points to a country on a virtual globe, AR device A **112** displays the virtual globe so that user **106** can see the same country that user **116** is pointing to (as perceived from the perspective of user **106**). Example components of the shared device application **328** are described further below with respect to FIG. 6.

(49) The Graphical processing unit **318** includes a render engine (not shown) that is configured to render a frame of a 3D model of a virtual object based on the virtual content provided by the AR application **310** and the pose of the AR device A **112** (relative to AR device B **114**). In other words, the Graphical processing unit **318** uses the three-dimensional pose of the AR device A **112** to generate frames of virtual content to be presented on the display **304**. For example, the Graphical processing unit **318** uses the three-dimensional pose to render a frame of the virtual content such that the virtual content is presented at an orientation and position in the display **304** to properly augment the user's reality. As an example, the Graphical processing unit **318** may use the three-dimensional pose data to render a frame of virtual content such that, when presented on the display **304**, the virtual content overlaps with a physical object in the user's real world environment **102**. The Graphical processing unit **318** generates updated frames of virtual content based on updated three-dimensional poses of the AR device A **112**, which reflect changes in the position and orientation of the user in relation to physical objects in the user's real world environment **102**.

(50) The Graphical processing unit **318** transfers the rendered frame to the display controller **320**. The display controller **320** is positioned as an intermediary between the Graphical processing unit **318** and the display **304**, receives the image data (e.g., rendered frame) from the Graphical processing unit **318**, provides the rendered frame to display **304**.

(51) The storage device **306** stores virtual object content **322**, relative pose data **326** (e.g., relative pose between AR device A **112** and AR device B **114**), and a pre-trained model **330**. The virtual object content **322** includes, for example, a database of visual references (e.g., images, QR codes) and corresponding virtual content (e.g., three-dimensional model of virtual objects). The relative pose data **326** indicate relative pose between a first reference coordinate frame of the first AR device and a second reference coordinate frame of the second AR device by registering the first point cloud with the second point cloud based on corresponding predicted depths. The pre-trained model **330** includes a machine learning model that is trained with (monocular) images provided by a plurality of AR devices and corresponding pose data.

(52) Any one or more of the modules described herein may be implemented using hardware (e.g., a Processor of a machine) or a combination of hardware and software. For example, any module

described herein may configure a processor to perform the operations described herein for that module. Moreover, any two or more of these modules may be combined into a single module, and the functions described herein for a single module may be subdivided among multiple modules. Furthermore, according to various example embodiments, modules described herein as being implemented within a single machine, database, or device may be distributed across multiple machines, databases, or devices.

(53) FIG. 4 is a block diagram illustrating a process for reconstructing a dense point cloud in accordance with one example embodiment. The 6DOF tracker **312** includes a VI-SLAM **406**. The VI-SLAM **406** can be used to identify sparse 3D points from the real world environment **102**. The VI-SLAM **406** (also referred to as a visual-inertial tracking system) determines a latest pose (e.g., position and orientation) of the AR device A **112** based on data acquired from multiple sensors (e.g., optical sensors, inertial sensors) of the AR device A **112**. In one example, the 6DOF tracker **312** provides a single image from a monocular camera of the AR device A **112** and sparse 3D points to the depth system **324**. Sparse 3D points referred to as 3D points are tracked and 3D reconstructed by the VI-SLAM **406**.

(54) The depth system **324** receives the single image from the optical sensor **314** (e.g., monocular camera) and the sparse 3D points from the 6DOF tracker **312**. The depth system **324** generates a dense point cloud by predicting the depths in the single image using a trained machine learning model (e.g., pre-trained model **402**). In one example, the depth system **324** includes a deep neural network that provides depths from a single image.

(55) The depth system **324** includes a pre-trained model **402** and a depth prediction module **404**. The pre-trained model **402** is trained with images generated by AR devices and pose data corresponding to the images. As such, the AR device A **112** does not include a pre-mapping or pre-building of the real world environment **102**. In other words, the AR device A **112** does not build a detailed model of the real world environment **102**. An example of a machine learning training program is described in more detail below with respect to FIG. 5.

(56) The depth prediction module **404** applies the single image and sparse 3D points to the pre-trained model **402** to predict depths in the single image and to generate a dense 3D point cloud (e.g., point cloud data A **408**) based on the predicted depths. The depth system **324** provides the point cloud data A **408** to the shared device application **328** for aligning the VIO reference coordinate frames of the AR devices.

(57) FIG. 5 illustrates training and use of a machine-learning program **500**, according to some example embodiments. In some example embodiments, machine-learning programs (MLPs), also referred to as machine-learning algorithms or tools, are used to perform operations associated with dense point cloud depths prediction.

(58) Machine learning is a field of study that gives computers the ability to learn without being explicitly programmed. Machine learning explores the study and construction of algorithms, also referred to herein as tools, that may learn from existing data and make predictions about new data. Such machine-learning tools operate by building a model from example training data **504** in order to make data-driven predictions or decisions expressed as outputs or assessments (e.g., assessment **512**). Although example embodiments are presented with respect to a few machine-learning tools, the principles presented herein may be applied to other machine-learning tools.

(59) In some example embodiments, different machine-learning tools may be used. For example, Logistic Regression (LR), Naive-Bayes, Random Forest (RF), neural networks (NN), matrix factorization, and Support Vector Machines (SVM) tools may be used for classifying or scoring job postings.

(60) Two common types of problems in machine learning are classification problems and regression problems. Classification problems, also referred to as categorization problems, aim at classifying items into one of several category values (for example, is this object an apple or an orange?). Regression algorithms aim at quantifying some items (for example, by providing a value

that is a real number).

(61) The machine-learning algorithms use features **502** for analyzing the data to generate an assessment **512**. Each of the features **502** is an individual measurable property of a phenomenon being observed. The concept of a feature is related to that of an explanatory variable used in statistical techniques such as linear regression. Choosing informative, discriminating, and independent features is important for the effective operation of the MLP in pattern recognition, classification, and regression. Features may be of different types, such as numeric features, strings, and graphs.

(62) In one example embodiment, the features **502** may be of different types and may include one or more of content **514**, concepts **516**, attributes **518**, historical data **520** and/or user data **522**, merely for example.

(63) The machine-learning algorithms use the training data **504** to find correlations among the identified features **502** that affect the outcome or assessment **512**. In some example embodiments, the training data **504** includes labeled data, which is known data for one or more identified features **502** and one or more outcomes, such as detecting depths patterns.

(64) With the training data **504** and the identified features **502**, the machine-learning tool is trained at machine-learning program training **506**. The machine-learning tool appraises the value of the features **502** as they correlate to the training data **504**. The result of the training is the trained machine-learning program **510**.

(65) When the trained machine-learning program **510** is used to perform an assessment, new data **508** is provided as an input to the trained machine-learning program **510**, and the trained machine-learning program **510** generates the assessment **512** as output.

(66) FIG. **6** is a block diagram illustrating a shared device application **328** in accordance with one example embodiment. The shared device application **328** includes an AR device interface **602**, a point cloud alignment application **604**, a relative pose module **606**, and a coordinate frame alignment module **608**. The AR device interface **602** is configured to communicate with AR device B **114** (e.g., via Bluetooth, wireless network). In one example, the AR device interface **602** accesses the point cloud data B **610** from the AR device B **114**.

(67) The point cloud alignment application **604** accesses point cloud data A **408** from depth system **324** and point cloud data B **610** from AR device interface **602**. The point cloud alignment application **604** performs a joint alignment of both the point cloud data A **408** and point cloud data B **610**. In one example, the point cloud alignment application **604** performs a Joint Registration of Multiple Point Sets (JRMPC) algorithm on the point cloud data A **408** and point cloud data B **610**. In another example, the point cloud alignment application **604** performs an Iterative Closest Point (ICP) algorithm on the point cloud data A **408** and point cloud data B **610**. Those of ordinary skills in the art will recognize that the point cloud alignment application **604** can use other joint point cloud alignment algorithms.

(68) The relative pose module **606** determines the relative pose based on the aligned point cloud determined at point cloud alignment application **604**. In one example, the relative pose module **606** determines the relative pose between the VIO reference frames of each AR device based on the aligned point cloud.

(69) The coordinate frame alignment module **608** uses the relative pose to align in 3D the VIO reference coordinate frames of each AR device. It is noted that once the alignment of point cloud alignment application **604** is performed, connected AR devices (e.g., AR device A **112** and AR device B **114**) do not need to be time-synced again. As such, the relative pose computation is performed only when the AR device A **112** and AR device B **114** are connected during a joint collaborative AR session (e.g., each AR device view a “same” virtual object in the real world environment **102**). In another example, the coordinate frame alignment module **608** provides alignment data (e.g., relative pose of AR device A **112** relative to AR device B **114**) to the AR application **310**/graphical processing unit **318** for accurate placement/display of a virtual object.

(70) FIG. 7 is a block diagram illustrating a server **110** in accordance with one example embodiment. The server **110** includes an AR device interface **702**, a point cloud alignment application **704**, a relative pose module **706**, and a coordinate frame alignment module **708**. The AR device interface **702** is configured to communicate with both AR device A **112** and AR device B **114**. In one example, the AR device interface **702** accesses the point cloud data A **408** from AR device A **112** and point cloud data B **610** from the AR device B **114**.

(71) The point cloud alignment application **704** accesses point cloud data A **408** and point cloud data B **610** from AR device interface **702**. The point cloud alignment application **704** performs a joint alignment of both the point cloud data A **408** and point cloud data B **610**. In one example, the point cloud alignment application **704** performs a Joint Registration of Multiple Point Sets (JRMPC) algorithm on the point cloud data A **408** and point cloud data B **610**. In another example, the point cloud alignment application **704** performs an Iterative Closest Point (ICP) algorithm on the point cloud data A **408** and point cloud data B **610**. Those of ordinary skills in the art will recognize that the point cloud alignment application **704** can use other joint point cloud alignment algorithms.

(72) The relative pose module **706** determines the relative pose based on the aligned point cloud performed at point cloud alignment application **704**. In one example, the relative pose module **706** determines the relative pose between the VIO reference frames of each AR device based on the aligned point cloud.

(73) The coordinate frame alignment module **708** uses the relative pose to align in 3D the VIO reference coordinate frames of each AR device. In one example, the coordinate frame alignment module **608** provides coordinate frame alignment **710** (e.g., relative pose of AR device A **112** relative to AR device B **114**) to the AR device A **112** and AR device B **114** for accurate placement/display of a virtual object.

(74) FIG. 8 is an interaction diagram illustrating an alignment operation in accordance with one example embodiment. The AR device A **112** sends point cloud data A **408** to the server **110** (to align reference frame with AR device B **114**). The AR device B **114** sends point cloud data B **610** to the server **110** (to align reference frame with AR device A **112**). Server **110** performs a registration process (e.g., align point cloud data **802**, determine relative pose **804**, align coordinate system **806**) and provides coordinate frame alignment **808** to both AR device A **112** and AR device B **114**.

(75) FIG. 9 is an interaction diagram illustrating a collaborative AR experience in accordance with one example embodiment. The AR device A **112** identifies virtual object in reference coordinate frame B **902**. The AR device A **112** displays the virtual object based on the aligned reference frames by (access coordinate frame alignment between AR device A and AR device B **904**, and display virtual object in reference coordinate frame A based on the coordinate frame alignment **906**).

(76) FIG. 10 is a flow diagram illustrating a method **1000** for aligning reference coordinate frames in accordance with one example embodiment. Operations in the method **1000** may be performed by the AR device A **112**, using components (e.g., modules, engines) described above with respect to FIG. 6. Accordingly, the method **1000** is described by way of example with reference to the AR device A **112**. However, it shall be appreciated that at least some of the operations of the method **1000** may be deployed on various other hardware configurations or be performed by similar components residing elsewhere.

(77) In block **1002**, the shared device application **328** receives point cloud data from depth system **324** of AR device A **112** and AR device B **114**. In block **1004**, the point cloud alignment application **604** aligns point cloud data from AR device A **112** and AR device B **114**. In block **1006**, the relative pose module **606** determines relative pose of the AR device A **112** and AR device B **114**. In block **1008**, the coordinate frame alignment module **608** aligns reference coordinate frames based on the relative pose. In block **1010**, the coordinate frame alignment module **608** provides the aligned reference coordinate frame to AR application **310** of AR device A **112** and/or AR device B **114**.

(78) It is to be noted that other embodiments may use different sequencing, additional or fewer operations, and different nomenclature or terminology to accomplish similar functions. In some embodiments, various operations may be performed in parallel with other operations, either in a synchronous or asynchronous manner. The operations described herein were chosen to illustrate some principles of operations in a simplified form.

(79) FIG. **11** is a flow diagram illustrating a method **1100** for sharing an AR experience in accordance with one example embodiment. Operations in the method **1100** may be performed by the AR device A **112**, using components (e.g., modules, engines) described above with respect to FIG. **3**. Accordingly, the method **1100** is described by way of example with reference to the AR device A **112**. However, it shall be appreciated that at least some of the operations of the method **1100** may be deployed on various other hardware configurations or be performed by similar components residing elsewhere.

(80) In block **1102**, the shared device application **328** receives virtual object data in reference frame b (e.g., reference frame of AR device B **114**). In block **1104**, the shared device application **328** accesses coordinate frame alignment between AR device A **112** and AR device B **114**. In block **1106**, the AR application **310** displays virtual object in reference frame a (e.g., reference frame of AR device A **112**).

(81) It is to be noted that other embodiments may use different sequencing, additional or fewer operations, and different nomenclature or terminology to accomplish similar functions. In some embodiments, various operations may be performed in parallel with other operations, either in a synchronous or asynchronous manner. The operations described herein were chosen to illustrate some principles of operations in a simplified form.

(82) FIG. **12** illustrates a routine **1200** in accordance with one example embodiment. In block **1202**, routine **1200** generates predicted depths of a first point cloud by applying a pre-trained model to a first single image generated by a first monocular camera of a first augmented reality (AR) device, and first sparse 3D points generated by a first SLAM system at the first AR device. In block **1204**, routine **1200** generates predicted depths of a second point cloud by applying the pre-trained model to a second single image generated by a second monocular camera of the second AR device, and second sparse 3D points generated by a second SLAM system at the second AR device. In block **1206**, routine **1200** determines a relative pose between a first reference coordinate frame of the first AR device and a second reference coordinate frame of the second AR device by registering the first point cloud with the second point cloud based on corresponding predicted depths. In block **1208**, routine **1200** provides the relative pose to at least one of the first AR device or the second AR device.

(83) FIG. **13** is a diagram illustrating aligning coordinate systems from two AR devices in accordance with one embodiment. As shown, different images of a scene are captured by the different devices and sparse points are captured in each image. The depth of the sparse points are predicted using a pre-trained model and a point cloud is generated for each image. A partial overlap of the points clouds is used to align the two point clouds, which is then used to determine the relative pose of each device.

(84) A monocular camera of a first AR device generates monocular image A **1302**. A monocular camera of a second AR device generates monocular image B **1304**. The monocular image A **1302** and the sparse 3D points A **1310** are applied to a pre-trained model to predict predicted point cloud A **1306**. The monocular image B **1304** and the sparse 3D points A **1312** are applied to the same pre-trained model to predict predicted point cloud A **1308**. The predicted point cloud A **1306** and predicted point cloud A **1308** are registered/aligned. The relative pose of the AR devices is determined based on the registered point clouds **1314**.

(85) System with Head-Wearable Apparatus

(86) FIG. **14** illustrates a network environment **1400** in which the head-wearable apparatus **1402** can be implemented according to one example embodiment. FIG. **14** is a high-level functional

block diagram of an example head-wearable apparatus **1402** communicatively coupled a mobile client device **1438** and a server system **1432** via various network **1440**.

(87) head-wearable apparatus **1402** includes a camera, such as at least one of visible light camera **1412**, infrared emitter **1414** and infrared camera **1416**. The client device **1438** can be capable of connecting with head-wearable apparatus **1402** using both a communication **1434** and a communication **1436**. client device **1438** is connected to server system **1432** and network **1440**. The network **1440** may include any combination of wired and wireless connections.

(88) The head-wearable apparatus **1402** further includes two image displays of the image display of optical assembly **1404**. The two include one associated with the left lateral side and one associated with the right lateral side of the head-wearable apparatus **1402**. The head-wearable apparatus **1402** also includes image display driver **1408**, image processor **1410**, low-power low power circuitry **1426**, and high-speed circuitry **1418**. The image display of optical assembly **1404** are for presenting images and videos, including an image that can include a graphical user interface to a user of the head-wearable apparatus **1402**.

(89) The image display driver **1408** commands and controls the image display of the image display of optical assembly **1404**. The image display driver **1408** may deliver image data directly to the image display of the image display of optical assembly **1404** for presentation or may have to convert the image data into a signal or data format suitable for delivery to the image display device. For example, the image data may be video data formatted according to compression formats, such as H. 264 (MPEG-4 Part 10), HEVC, Theora, Dirac, RealVideo RV40, VP8, VP9, or the like, and still image data may be formatted according to compression formats such as Portable Network Group (PNG), Joint Photographic Experts Group (JPEG), Tagged Image File Format (TIFF) or exchangeable image file format (Exif) or the like.

(90) As noted above, head-wearable apparatus **1402** includes a frame and stems (or temples) extending from a lateral side of the frame. The head-wearable apparatus **1402** further includes a user input device **1406** (e.g., touch sensor or push button) including an input surface on the head-wearable apparatus **1402**. The user input device **1406** (e.g., touch sensor or push button) is to receive from the user an input selection to manipulate the graphical user interface of the presented image.

(91) The components shown in FIG. **14** for the head-wearable apparatus **1402** are located on one or more circuit boards, for example a PCB or flexible PCB, in the rims or temples. Alternatively, or additionally, the depicted components can be located in the chunks, frames, hinges, or bridge of the head-wearable apparatus **1402**. Left and right can include digital camera elements such as a complementary metal-oxide-semiconductor (CMOS) image sensor, charge coupled device, a camera lens, or any other respective visible or light capturing elements that may be used to capture data, including images of scenes with unknown objects.

(92) The head-wearable apparatus **1402** includes a memory **1422** which stores instructions to perform a subset or all of the functions described herein. memory **1422** can also include storage device.

(93) As shown in FIG. **14**, high-speed circuitry **1418** includes high-speed processor **1420**, memory **1422**, and high-speed wireless circuitry **1424**. In the example, the image display driver **1408** is coupled to the high-speed circuitry **1418** and operated by the high-speed processor **1420** in order to drive the left and right image displays of the image display of optical assembly **1404**. high-speed processor **1420** may be any processor capable of managing high-speed communications and operation of any general computing system needed for head-wearable apparatus **1402**. The high-speed processor **1420** includes processing resources needed for managing high-speed data transfers on communication **1436** to a wireless local area network (WLAN) using high-speed wireless circuitry **1424**. In certain examples, the high-speed processor **1420** executes an operating system such as a LINUX operating system or other such operating system of the head-wearable apparatus **1402** and the operating system is stored in memory **1422** for execution. In addition to any other

responsibilities, the high-speed processor **1420** executing a software architecture for the head-wearable apparatus **1402** is used to manage data transfers with high-speed wireless circuitry **1424**. In certain examples, high-speed wireless circuitry **1424** is configured to implement Institute of Electrical and Electronic Engineers (IEEE) 1402.11 communication standards, also referred to herein as Wi-Fi. In other examples, other high-speed communications standards may be implemented by high-speed wireless circuitry **1424**.

(94) The low power wireless circuitry **1430** and the high-speed wireless circuitry **1424** of the head-wearable apparatus **1402** can include short range transceivers (Bluetooth™) and wireless wide, local, or wide area network transceivers (e.g., cellular or WiFi). The client device **1438**, including the transceivers communicating via the communication **1434** and communication **1436**, may be implemented using details of the architecture of the head-wearable apparatus **1402**, as can other elements of network **1440**.

(95) The memory **1422** includes any storage device capable of storing various data and applications, including, among other things, camera data generated by the left and right, infrared camera **1416**, and the image processor **1410**, as well as images generated for display by the image display driver **1408** on the image displays of the image display of optical assembly **1404**. While memory **1422** is shown as integrated with high-speed circuitry **1418**, in other examples, memory **1422** may be an independent standalone element of the head-wearable apparatus **1402**. In certain such examples, electrical routing lines may provide a connection through a chip that includes the high-speed processor **1420** from the image processor **1410** or low power processor **1428** to the memory **1422**. In other examples, the high-speed processor **1420** may manage addressing of memory **1422** such that the low power processor **1428** will boot the high-speed processor **1420** any time that a read or write operation involving memory **1422** is needed.

(96) As shown in FIG. 14, the low power processor **1428** or high-speed processor **1420** of the head-wearable apparatus **1402** can be coupled to the camera (visible light camera **1412**; infrared emitter **1414**, or infrared camera **1416**), the image display driver **1408**, the user input device **1406** (e.g., touch sensor or push button), and the memory **1422**.

(97) The head-wearable apparatus **1402** is connected with a host computer. For example, the head-wearable apparatus **1402** is paired with the client device **1438** via the communication **1436** or connected to the server system **1432** via the network **1440**. server system **1432** may be one or more computing devices as part of a service or network computing system, for example, that include a processor, a memory, and network communication interface to communicate over the network **1440** with the client device **1438** and head-wearable apparatus **1402**.

(98) The client device **1438** includes a processor and a network communication interface coupled to the processor. The network communication interface allows for communication over the network **1440**, communication **1434** or communication **1436**. client device **1438** can further store at least portions of the instructions for generating a binaural audio content in the client device **1438**'s memory to implement the functionality described herein.

(99) Output components of the head-wearable apparatus **1402** include visual components, such as a display such as a liquid crystal display (LCD), a plasma display panel (PDP), a light emitting diode (LED) display, a projector, or a waveguide. The image displays of the optical assembly are driven by the image display driver **1408**. The output components of the head-wearable apparatus **1402** further include acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor), other signal generators, and so forth. The input components of the head-wearable apparatus **1402**, the client device **1438**, and server system **1432**, such as the user input device **1406**, may include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point-based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or other pointing instruments), tactile input components (e.g., a physical button, a touch screen that provides location and force of touches or touch gestures, or other tactile input components), audio

input components (e.g., a microphone), and the like.

(100) The head-wearable apparatus **1402** may optionally include additional peripheral device elements. Such peripheral device elements may include biometric sensors, additional sensors, or display elements integrated with head-wearable apparatus **1402**. For example, peripheral device elements may include any I/O components including output components, motion components, position components, or any other such elements described herein.

(101) For example, the biometric components include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram based identification), and the like. The motion components include acceleration sensor components (e.g., accelerometer), gravitation sensor components, rotation sensor components (e.g., gyroscope), and so forth. The position components include location sensor components to generate location coordinates (e.g., a Global Positioning System (GPS) receiver component), WiFi or Bluetooth™ transceivers to generate positioning system coordinates, altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like. Such positioning system coordinates can also be received over and communication **1436** from the client device **1438** via the low power wireless circuitry **1430** or high-speed wireless circuitry **1424**.

(102) Where a phrase similar to “at least one of A, B, or C,” “at least one of A, B, and C,” “one or more A, B, or C,” or “one or more of A, B, and C” is used, it is intended that the phrase be interpreted to mean that A alone may be present in an embodiment, B alone may be present in an embodiment, C alone may be present in an embodiment, or that any combination of the elements A, B and C may be present in a single embodiment; for example, A and B, A and C, B and C, or A and B and C.

(103) Changes and modifications may be made to the disclosed embodiments without departing from the scope of the present disclosure. These and other changes or modifications are intended to be included within the scope of the present disclosure, as expressed in the following claims.

(104) FIG. **15** is a block diagram **1500** illustrating a software architecture **1504**, which can be installed on any one or more of the devices described herein. The software architecture **1504** is supported by hardware such as a machine **1502** that includes Processors **1520**, memory **1526**, and I/O Components **1538**. In this example, the software architecture **1504** can be conceptualized as a stack of layers, where each layer provides a particular functionality. The software architecture **1504** includes layers such as an operating system **1512**, libraries **1510**, frameworks **1508**, and applications **1506**. Operationally, the applications **1506** invoke API calls **1550** through the software stack and receive messages **1552** in response to the API calls **1550**.

(105) The operating system **1512** manages hardware resources and provides common services. The operating system **1512** includes, for example, a kernel **1514**, services **1516**, and drivers **1522**. The kernel **1514** acts as an abstraction layer between the hardware and the other software layers. For example, the kernel **1514** provides memory management, Processor management (e.g., scheduling), Component management, networking, and security settings, among other functionality. The services **1516** can provide other common services for the other software layers. The drivers **1522** are responsible for controlling or interfacing with the underlying hardware. For instance, the drivers **1522** can include display drivers, camera drivers, BLUETOOTH® or BLUETOOTH® Low Energy drivers, flash memory drivers, serial communication drivers (e.g., Universal Serial Bus (USB) drivers), WI-FI® drivers, audio drivers, power management drivers, and so forth.

(106) The libraries **1510** provide a low-level common infrastructure used by the applications **1506**. The libraries **1510** can include system libraries **1518** (e.g., C standard library) that provide functions such as memory allocation functions, string manipulation functions, mathematic functions, and the like. In addition, the libraries **1510** can include API libraries **1524** such as media

libraries (e.g., libraries to support presentation and manipulation of various media formats such as Moving Picture Experts Group-4 (MPEG4), Advanced Video Coding (H.264 or AVC), Moving Picture Experts Group Layer-3 (MP3), Advanced Audio Coding (AAC), Adaptive Multi-Rate (AMR) audio codec, Joint Photographic Experts Group (JPEG or JPG), or Portable Network Graphics (PNG)), graphics libraries (e.g., an OpenGL framework used to render in two dimensions (2D) and three dimensions (3D) in a graphic content on a display), database libraries (e.g., SQLite to provide various relational database functions), web libraries (e.g., WebKit to provide web browsing functionality), and the like. The libraries **1510** can also include a wide variety of other libraries **1528** to provide many other APIs to the applications **1506**.

(107) The frameworks **1508** provide a high-level common infrastructure that is used by the applications **1506**. For example, the frameworks **1508** provide various graphical user interface (GUI) functions, high-level resource management, and high-level location services. The frameworks **1508** can provide a broad spectrum of other APIs that can be used by the applications **1506**, some of which may be specific to a particular operating system or platform.

(108) In an example embodiment, the applications **1506** may include a home application **1536**, a contacts application **1530**, a browser application **1532**, a book reader application **1534**, a location application **1542**, a media application **1544**, a messaging application **1546**, a game application **1548**, and a broad assortment of other applications such as a third-party application **1540**. The applications **1506** are programs that execute functions defined in the programs. Various programming languages can be employed to create one or more of the applications **1506**, structured in a variety of manners, such as object-oriented programming languages (e.g., Objective-C, Java, or C++) or procedural programming languages (e.g., C or assembly language). In a specific example, the third-party application **1540** (e.g., an application developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform) may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or another mobile operating system. In this example, the third-party application **1540** can invoke the API calls **1550** provided by the operating system **1512** to facilitate functionality described herein.

(109) FIG. **16** is a diagrammatic representation of the machine **1600** within which instructions **1608** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **1600** to perform any one or more of the methodologies discussed herein may be executed. For example, the instructions **1608** may cause the machine **1600** to execute any one or more of the methods described herein. The instructions **1608** transform the general, non-programmed machine **1600** into a particular machine **1600** programmed to carry out the described and illustrated functions in the manner described. The machine **1600** may operate as a standalone device or may be coupled (e.g., networked) to other machines. In a networked deployment, the machine **1600** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **1600** may comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a PDA, an entertainment media system, a cellular telephone, a smart phone, a mobile device, a wearable device (e.g., a smart watch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **1608**, sequentially or otherwise, that specify actions to be taken by the machine **1600**. Further, while only a single machine **1600** is illustrated, the term “machine” shall also be taken to include a collection of machines that individually or jointly execute the instructions **1608** to perform any one or more of the methodologies discussed herein.

(110) The machine **1600** may include Processors **1602**, memory **1604**, and I/O Components **1642**, which may be configured to communicate with each other via a bus **1644**. In an example embodiment, the Processors **1602** (e.g., a Central Processing Unit (CPU), a Reduced Instruction

Set Computing (RISC) Processor, a Complex Instruction Set Computing (CISC) Processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an ASIC, a Radio-Frequency Integrated Circuit (RFIC), another Processor, or any suitable combination thereof) may include, for example, a Processor **1606** and a Processor **1610** that execute the instructions **1608**. The term “Processor” is intended to include multi-core Processors that may comprise two or more independent Processors (sometimes referred to as “cores”) that may execute instructions contemporaneously. Although FIG. **16** shows multiple Processors **1602**, the machine **1600** may include a single Processor with a single core, a single Processor with multiple cores (e.g., a multi-core Processor), multiple Processors with a single core, multiple Processors with multiples cores, or any combination thereof.

(111) The memory **1604** includes a main memory **1612**, a static memory **1614**, and a storage unit **1616**, both accessible to the Processors **1602** via the bus **1644**. The main memory **1604**, the static memory **1614**, and storage unit **1616** store the instructions **1608** embodying any one or more of the methodologies or functions described herein. The instructions **1608** may also reside, completely or partially, within the main memory **1612**, within the static memory **1614**, within machine-readable medium **1618** within the storage unit **1616**, within at least one of the Processors **1602** (e.g., within the Processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **1600**.

(112) The I/O Components **1642** may include a wide variety of Components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O Components **1642** that are included in a particular machine will depend on the type of machine. For example, portable machines such as mobile phones may include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input device. It will be appreciated that the I/O Components **1642** may include many other Components that are not shown in FIG. **16**. In various example embodiments, the I/O Components **1642** may include output Components **1628** and input Components **1630**. The output Components **1628** may include visual Components (e.g., a display such as a plasma display panel (PDP), a light emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic Components (e.g., speakers), haptic Components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The input Components **1630** may include alphanumeric input Components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input Components), point-based input Components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or another pointing instrument), tactile input Components (e.g., a physical button, a touch screen that provides location and/or force of touches or touch gestures, or other tactile input Components), audio input Components (e.g., a microphone), and the like.

(113) In further example embodiments, the I/O Components **1642** may include biometric Components **1632**, motion Components **1634**, environmental Components **1636**, or position Components **1638**, among a wide array of other Components. For example, the biometric Components **1632** include Components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram-based identification), and the like. The motion Components **1634** include acceleration sensor Components (e.g., accelerometer), gravitation sensor Components, rotation sensor Components (e.g., gyroscope), and so forth. The environmental Components **1636** include, for example, illumination sensor Components (e.g., photometer), temperature sensor Components (e.g., one or more thermometers that detect ambient temperature), humidity sensor Components, pressure sensor Components (e.g., barometer), acoustic sensor Components (e.g., one or more

microphones that detect background noise), proximity sensor Components (e.g., infrared sensors that detect nearby objects), gas sensors (e.g., gas detection sensors to detection concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other Components that may provide indications, measurements, or signals corresponding to a surrounding physical environment. The position Components **1638** include location sensor Components (e.g., a GPS receiver Component), altitude sensor Components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor Components (e.g., magnetometers), and the like.

(114) Communication may be implemented using a wide variety of technologies. The I/O Components **1642** further include communication Components **1640** operable to couple the machine **1600** to a network **1620** or devices **1622** via a coupling **1624** and a coupling **1626**, respectively. For example, the communication Components **1640** may include a network interface Component or another suitable device to interface with the network **1620**. In further examples, the communication Components **1640** may include wired communication Components, wireless communication Components, cellular communication Components, Near Field Communication (NFC) Components, Bluetooth® Components (e.g., Bluetooth® Low Energy), WiFi® Components, and other communication Components to provide communication via other modalities. The devices **1622** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a USB).

(115) Moreover, the communication Components **1640** may detect identifiers or include Components operable to detect identifiers. For example, the communication Components **1640** may include Radio Frequency Identification (RFID) tag reader Components, NFC smart tag detection Components, optical reader Components (e.g., an optical sensor to detect one-dimensional bar codes such as Universal Product Code (UPC) bar code, multi-dimensional bar codes such as Quick Response (QR) code, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, UCC RSS-2D bar code, and other optical codes), or acoustic detection Components (e.g., microphones to identify tagged audio signals). In addition, a variety of information may be derived via the communication Components **1640**, such as location via Internet Protocol (IP) geolocation, location via Wi-Fi® signal triangulation, location via detecting an NFC beacon signal that may indicate a particular location, and so forth.

(116) The various memories (e.g., memory **1604**, main memory **1612**, static memory **1614**, and/or memory of the Processors **1602**) and/or storage unit **1616** may store one or more sets of instructions and data structures (e.g., software) embodying or used by any one or more of the methodologies or functions described herein. These instructions (e.g., the instructions **1608**), when executed by Processors **1602**, cause various operations to implement the disclosed embodiments.

(117) The instructions **1608** may be transmitted or received over the network **1620**, using a transmission medium, via a network interface device (e.g., a network interface Component included in the communication Components **1640**) and using any one of a number of well-known transfer protocols (e.g., hypertext transfer protocol (HTTP)). Similarly, the instructions **1608** may be transmitted or received using a transmission medium via the coupling **1626** (e.g., a peer-to-peer coupling) to the devices **1622**.

(118) As used herein, the terms “Machine-Storage Medium,” “device-storage medium,” and “computer-storage medium” mean the same thing and may be used interchangeably in this disclosure. The terms refer to a single or multiple storage devices and/or media (e.g., a centralized or distributed database, and/or associated caches and servers) that store executable instructions and/or data. The terms shall accordingly be taken to include, but not be limited to, solid-state memories, and optical and magnetic media, including memory internal or external to processors. Specific examples of Machine-Storage Media, computer-storage media, and/or device-storage media include non-volatile memory, including by way of example semiconductor memory devices, e.g., erasable programmable read-only memory (EPROM), electrically erasable programmable

read-only memory (EEPROM), field-programmable gate arrays (FPGAs), and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The terms “Machine-Storage Media,” “computer-storage media,” and “device-storage media” specifically exclude carrier waves, modulated data signals, and other such media, at least some of which are covered under the term “signal medium” discussed below.

(119) The terms “transmission medium” and “signal medium” mean the same thing and may be used interchangeably in this disclosure. The terms “transmission medium” and “signal medium” shall be taken to include any intangible medium that is capable of storing, encoding, or carrying the instructions **1416** for execution by the machine **1400**, and include digital or analog communications signals or other intangible media to facilitate communication of such software. Hence, the terms “transmission medium” and “signal medium” shall be taken to include any form of modulated data signal, carrier wave, and so forth. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal.

(120) The terms “machine-readable medium,” “Computer-Readable Medium,” and “device-readable medium” mean the same thing and may be used interchangeably in this disclosure. The terms are defined to include both Machine-Storage Media and transmission media. Thus, the terms include both storage devices/media and carrier waves/modulated data signals.

(121) Although an embodiment has been described with reference to specific example embodiments, it will be evident that various modifications and changes may be made to these embodiments without departing from the broader scope of the present disclosure. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense. The accompanying drawings that form a part hereof, show by way of illustration, and not of limitation, specific embodiments in which the subject matter may be practiced. The embodiments illustrated are described in sufficient detail to enable those skilled in the art to practice the teachings disclosed herein. Other embodiments may be utilized and derived therefrom, such that structural and logical substitutions and changes may be made without departing from the scope of this disclosure. This Detailed Description, therefore, is not to be taken in a limiting sense, and the scope of various embodiments is defined only by the appended claims, along with the full range of equivalents to which such claims are entitled.

(122) Such embodiments of the inventive subject matter may be referred to herein, individually and/or collectively, by the term “invention” merely for convenience and without intending to voluntarily limit the scope of this application to any single invention or inventive concept if more than one is in fact disclosed. Thus, although specific embodiments have been illustrated and described herein, it should be appreciated that any arrangement calculated to achieve the same purpose may be substituted for the specific embodiments shown. This disclosure is intended to cover any and all adaptations or variations of various embodiments. Combinations of the above embodiments, and other embodiments not specifically described herein, will be apparent to those of skill in the art upon reviewing the above description.

(123) The Abstract of the Disclosure is provided to allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. In addition, in the foregoing Detailed Description, it can be seen that various features are grouped together in a single embodiment for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claimed embodiments require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter lies in less than all features of a single disclosed embodiment. Thus the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separate embodiment.

EXAMPLES

(124) Example 1 is a method comprising: generating predicted depths of a first point cloud by applying a pre-trained model to a first single image generated by a first monocular camera of a first augmented reality (AR) device, and first sparse 3D points generated by a first SLAM system at the first AR device; generating predicted depths of a second point cloud by applying the pre-trained model to a second single image generated by a second monocular camera of the second AR device, and second sparse 3D points generated by a second SLAM system at the second AR device; determining a relative pose between a first reference coordinate frame of the first AR device and a second reference coordinate frame of the second AR device by registering the first point cloud with the second point cloud based on corresponding predicted depths; and providing the relative pose to at least one of the first AR device or the second AR device.

(125) Example 2 includes the method of example 1, further comprising: rendering a first virtual object in a first display of the first AR device based on the relative pose; and rendering a second virtual object in a second display of the second AR device based on the relative pose, wherein the second virtual object corresponds to the first virtual object.

(126) Example 3 includes the method of example 1, further comprising: accessing the first sparse 3D points from a six-degrees of freedom (6DOF) tracker of the first AR device.

(127) Example 4 includes the method of example 3, wherein the 6DOF tracker comprises a Visual Inertial-Simultaneous Localization and Mapping (VI-SLAM) system.

(128) Example 5 includes the method of example 1, wherein the pre-trained model is a machine learning model trained with images captured by a plurality of camera devices.

(129) Example 6 includes the method of example 1, wherein a server is configured to: communicate with the first AR device and the second AR device; determine the relative pose by registering overlapping regions of the first point cloud and the second point cloud; and provide the relative pose to at least one of the first AR device or the second AR device.

(130) Example 7 includes the method of example 1, wherein the first AR device communicates with the second AR device, wherein the first AR device is configured to receive the second point cloud from the second AR device, and to determine the relative pose.

(131) Example 8 includes the method of example 1, further comprising: generating predicted depths of a third point cloud by applying the pre-trained model to a third single image generated by a third monocular camera of a third AR device, and third sparse 3D points generated by a third SLAM system at the third AR device; determining a first relative pose between a first reference coordinate frame of the first AR device and a second reference coordinate frame of the second AR device by registering the first point cloud with the second point cloud; determining a second relative pose between the first reference coordinate frame of the first AR device and a third reference coordinate frame of the third AR device by registering the first point cloud with the third point cloud; providing the first relative pose to the second AR device; and providing the second relative pose to the third AR device.

(132) Example 9 includes the method of example 1, further comprising: generating predicted depths of a third point cloud by applying the pre-trained model to a third single image generated by a third monocular camera of a third AR device, and third sparse 3D points generated by a third SLAM system at the third AR device; and identifying, using a new reference coordinate frame common to the first AR device, the second AR device, and the third AR device, a first pose of the first AR device based on the depths of the first point cloud, a second pose of the second AR device based on the depths of the second point cloud, and a third pose of the third AR device based on the depths of the third point cloud by registering overlapping regions of the first point cloud, the second point cloud, and the third point cloud for the new reference coordinate frame.

(133) Example 10 includes the method of example 1, wherein the first AR device is configured to generate the first point cloud from the first single image and first sparse 3D points, the first point cloud being denser than the first sparse 3D points.

(134) Example 11 is a computing apparatus comprising: a processor; and a memory storing

instructions that, when executed by the processor, configure the apparatus to: generate predicted depths of a first point cloud by applying a pre-trained model to a first single image generated by a first monocular camera of a first augmented reality (AR) device, and first sparse 3D points generated by a first SLAM system at the first AR device; generate predicted depths of a second point cloud by applying the pre-trained model to a second single image generated by a second monocular camera of the second AR device, and second sparse 3D points generated by a second SLAM system at the second AR device; determine a relative pose between a first reference coordinate frame of the first AR device and a second reference coordinate frame of the second AR device by registering the first point cloud with the second point cloud based on corresponding predicted depths; and provide the relative pose to at least one of the first AR device or the second AR device.

(135) Example 12 is the computing apparatus of example 11, wherein the instructions further configure the apparatus to: render a first virtual object in a first display of the first AR device based on the relative pose; and render a second virtual object in a second display of the second AR device based on the relative pose, wherein the second virtual object corresponds to the first virtual object.

(136) Example 13 is the computing apparatus of example 11, wherein the instructions further configure the apparatus to: access the first sparse 3D points from a six-degrees of freedom (6DOF) tracker of the first AR device.

(137) Example 14 is the computing apparatus of example 13, wherein the 6DOF tracker comprises a Visual Inertial-Simultaneous Localization and Mapping (VI-SLAM) system.

(138) Example 15 is the computing apparatus of example 11, wherein the pre-trained model is a machine learn model trained with images captured by a plurality of camera devices.

(139) Example 16 is the computing apparatus of example 11, wherein a server is configured to: communicate with the first AR device and the second AR device; determine the relative pose by registering overlap regions of the first point cloud and the second point cloud; and provide the relative pose to at least one of the first AR device or the second AR device.

(140) Example 17 is the computing apparatus of example 11, wherein the first AR device communicates with the second AR device, wherein the first AR device is configured to receive the second point cloud from the second AR device, and to determine the relative pose.

(141) Example 18 is the computing apparatus of example 11, wherein the instructions further configure the apparatus to: generate predicted depths of a third point cloud by applying the pre-trained model to a third single image generated by a third monocular camera of a third AR device, and third sparse 3D points generated by a third SLAM system at the third AR device; determine a first relative pose between a first reference coordinate frame of the first AR device and a second reference coordinate frame of the second AR device by registering the first point cloud with the second point cloud; determine a second relative pose between the first reference coordinate frame of the first AR device and a third reference coordinate frame of the third AR device by registering the first point cloud with the third point cloud; provide the first relative pose to the second AR device; and provide the second relative pose to the third AR device.

(142) Example 19 is the computing apparatus of example 11, generate predicted depths of a third point cloud by applying the pre-trained model to a third single image generated by a third monocular camera of a third AR device, and third sparse 3D points generated by a third SLAM system at the third AR device; and identify, using a new reference coordinate frame common to the first AR device, the second AR device, and the third AR device, a first pose of the first AR device based on the depths of the first point cloud, a second pose of the second AR device based on the depths of the second point cloud, and a third pose of the third AR device based on the depths of the third point cloud by registering overlapping regions of the first point cloud, the second point cloud, and the third point cloud for the new reference coordinate frame.

(143) Example 20 is a non-transitory computer-readable storage medium, the computer-readable storage medium including instructions that when executed by a computer, cause the computer to:

generate predicted depths of a first point cloud by applying a pre-trained model to a first single image generated by a first monocular camera of a first augmented reality (AR) device, and first sparse 3D points generated by a first SLAM system at the first AR device; generate predicted depths of a second point cloud by applying the pre-trained model to a second single image generated by a second monocular camera of the second AR device, and second sparse 3D points generated by a second SLAM system at the second AR device; determine a relative pose between a first reference coordinate frame of the first AR device and a second reference coordinate frame of the second AR device by registering the first point cloud with the second point cloud based on corresponding predicted depths; and provide the relative pose to at least one of the first AR device or the second AR device.

(144) Described implementations of the subject matter can include one or more features, alone or in combination as illustrated below by way of example.

Claims

1. A method comprising: generating, at a first augmented reality (AR) device, predicted depths of a first point cloud by applying a pre-trained model to a first single image generated by a first monocular camera of the first AR device, and first sparse 3D points generated by a first SLAM (Simultaneous Localization and Mapping) system at the first AR device, wherein the pre-trained model is configured to combine the first single image data with the concurrently generated first sparse 3D points to yield the predicted depths in a single pass without requiring a separate environment map; receiving, at the first AR device, predicted depths of a second point cloud from a second AR device, the predicted depths of the second point cloud generated at the second AR device by applying the pre-trained model to a second single image generated by a second monocular camera of the second AR device, and second sparse 3D points generated by a second SLAM system at the second AR device; determining, at the first AR device, a relative pose between a first reference coordinate frame of the first AR device and a second reference coordinate frame of the second AR device by registering the first point cloud with the second point cloud based on corresponding predicted depths; and providing the relative pose to the second AR device.
2. The method of claim 1, further comprising: rendering a first virtual object in a first display of the first AR device based on the relative pose; and rendering a second virtual object in a second display of the second AR device based on the relative pose, wherein the second virtual object corresponds to the first virtual object.
3. The method of claim 1, further comprising: accessing the first sparse 3D points from a six-degrees of freedom (6DOF) tracker of the first AR device.
4. The method of claim 3, wherein the 6DOF tracker comprises a Visual Inertial-Simultaneous Localization and Mapping (VI-SLAM) system.
5. The method of claim 1, wherein the pre-trained model is a machine learning model trained with images captured by a plurality of camera devices.
6. The method of claim 1, wherein a server is configured to: communicate with the first AR device and the second AR device; determine the relative pose by registering overlapping regions of the first point cloud and the second point cloud; and provide the relative pose to at least one of the first AR device or the second AR device.
7. The method of claim 1, wherein the first AR device communicates with the second AR device, wherein the first AR device is configured to receive the second point cloud from the second AR device, and to determine the relative pose.
8. The method of claim 1, further comprising: generating predicted depths of a third point cloud by applying the pre-trained model to a third single image generated by a third monocular camera of a third AR device, and third sparse 3D points generated by a third SLAM system at the third AR device; determining a first relative pose between a first reference coordinate frame of the first AR

device and a second reference coordinate frame of the second AR device by registering the first point cloud with the second point cloud; determining a second relative pose between the first reference coordinate frame of the first AR device and a third reference coordinate frame of the third AR device by registering the first point cloud with the third point cloud; providing the first relative pose to the second AR device; and providing the second relative pose to the third AR device.

9. The method of claim 1, further comprising: generating predicted depths of a third point cloud by applying the pre-trained model to a third single image generated by a third monocular camera of a third AR device, and third sparse 3D points generated by a third SLAM system at the third AR device; and identifying, using a new reference coordinate frame common to the first AR device, the second AR device, and the third AR device, a first pose of the first AR device based on the depths of the first point cloud, a second pose of the second AR device based on the depths of the second point cloud, and a third pose of the third AR device based on the depths of the third point cloud by registering overlapping regions of the first point cloud, the second point cloud, and the third point cloud for the new reference coordinate frame.

10. The method of claim 1, wherein the first AR device is configured to generate the first point cloud from the first single image and first sparse 3D points, the first point cloud being denser than the first sparse 3D points, wherein the first AR device registers the first point cloud with the second point cloud by performing one of a Joint Registration of Multiple Point Sets (JRMPC) algorithm on the first point cloud and the second point cloud, or an Iterative Closest Point (ICP) algorithm on the first point cloud and the second point cloud.

11. A first augmented reality (AR) device comprising: a processor; and a memory storing instructions that, when executed by the processor, configure the first AR device to: generate predicted depths of a first point cloud by applying a pre-trained model to a first single image generated by a first monocular camera of the first AR device, and first sparse 3D points generated by a first SLAM (Simultaneous Localization and Mapping) system at the first AR device, wherein the pre-trained model is configured to combine the first single image data with the concurrently generated first sparse 3D points to yield the predicted depths in a single pass without requiring a separate environment map; receive predicted depths of a second point cloud from a second AR device, the predicted depths generated at the second AR device by applying the pre-trained model to a second single image generated by a second monocular camera of the second AR device, and second sparse 3D points generated by a second SLAM system at the second AR device; determine a relative pose between a first reference coordinate frame of the first AR device and a second reference coordinate frame of the second AR device by registering the first point cloud with the second point cloud based on corresponding predicted depths; and provide the relative pose to the second AR device.

12. The first AR device of claim 11, wherein the instructions further configure the first AR device to: render a first virtual object in a first display of the first AR device based on the relative pose; and render a second virtual object in a second display of the second AR device based on the relative pose, wherein the second virtual object corresponds to the first virtual object.

13. The first AR device of claim 11, wherein the instructions further configure the first AR device to: access the first sparse 3D points from a six-degrees of freedom (6DOF) tracker of the first AR device.

14. The first AR device of claim 13, wherein the 6DOF tracker comprises a Visual Inertial-Simultaneous Localization and Mapping (VI-SLAM) system.

15. The first AR device of claim 11, wherein the pre-trained model is a machine learning model trained with images captured by a plurality of camera devices.

16. The first AR device of claim 11, wherein a server is configured to: communicate with the first AR device and the second AR device; determine the relative pose by registering overlap regions of the first point cloud and the second point cloud; and provide the relative pose to at least one of the first AR device or the second AR device.

17. The first AR device of claim 11, wherein the first AR device communicates with the second AR device, wherein the first AR device is configured to receive the second point cloud from the second AR device, and to determine the relative pose.
18. The first AR device of claim 11, wherein the instructions further configure the first AR device to: generate predicted depths of a third point cloud by applying the pre-trained model to a third single image generated by a third monocular camera of a third AR device, and third sparse 3D points generated by a third SLAM system at the third AR device; determine a first relative pose between a first reference coordinate frame of the first AR device and a second reference coordinate frame of the second AR device by registering the first point cloud with the second point cloud; determine a second relative pose between the first reference coordinate frame of the first AR device and a third reference coordinate frame of the third AR device by registering the first point cloud with the third point cloud; provide the first relative pose to the second AR device; and provide the second relative pose to the third AR device.
19. The first AR device of claim 11, wherein the instructions further configure the first AR device to: generate predicted depths of a third point cloud by applying the pre-trained model to a third single image generated by a third monocular camera of a third AR device, and third sparse 3D points generated by a third SLAM system at the third AR device; and identify, using a new reference coordinate frame common to the first AR device, the second AR device, and the third AR device, a first pose of the first AR device based on the depths of the first point cloud, a second pose of the second AR device based on the depths of the second point cloud, and a third pose of the third AR device based on the depths of the third point cloud by registering overlapping regions of the first point cloud, the second point cloud, and the third point cloud for the new reference coordinate frame.
20. A non-transitory computer-readable storage medium, the computer-readable storage medium including instructions that when executed by a computer, cause the computer to: generate, at a first augmented reality (AR) device, predicted depths of a first point cloud by applying a pre-trained model to a first single image generated by a first monocular camera of the first AR device, and first sparse 3D points generated by a first SLAM (Simultaneous Localization and Mapping) system at the first AR device, wherein the pre-trained model is configured to combine the first single image data with the concurrently generated first sparse 3D points to yield the predicted depths in a single pass without requiring a separate environment map; receive, at the first AR device, predicted depths of a second point cloud from a second AR device, the predicted depths generated at the second AR device by applying the pre-trained model to a second single image generated by a second monocular camera of the second AR device, and second sparse 3D points generated by a second SLAM system at the second AR device; determine, at the first AR device, a relative pose between a first reference coordinate frame of the first AR device and a second reference coordinate frame of the second AR device by registering the first point cloud with the second point cloud based on corresponding predicted depths; and provide the relative pose to the second AR device.
-