

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12419144
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Kim; Seongmin et al.

Light emitting device for display and backlight unit including the same

Abstract

A light emitting device includes a first light emitter including a first light emitting chip emitting first blue light and at least one among a first phosphor and a second phosphor, the first light emitter being configured to emit second blue light, and a second light emitter including a second light emitting chip emitting third blue light and at least one among a third phosphor and a fourth phosphor, the second light emitter being configured to emit fourth blue light, wherein a ratio of an intensity of a peak wavelength of the fourth blue light to an intensity of a peak wavelength of the second blue light is greater than or equal to 0.6.

Inventors: Kim; Seongmin (Suwon-si, KR), Yun; Jeongeun (Suwon-si, KR), Oh; Jeongrok (Suwon-si, KR), Choi; Sungwoo (Suwon-si, KR), Yoon; Chulsoo (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 1000008819151

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 18/885155

Filed: September 13, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250006872 A1	Jan. 02, 2025

Foreign Application Priority Data

KR	10-2022-0111008	Sep. 01, 2022
----	-----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **H01L33/50** (20100101); **F21V8/00** (20060101); **H01L25/075** (20060101); **H10H20/851** (20250101)

U.S. Cl.:

CPC **H10H20/8513** (20250101); **G02B6/0073** (20130101); **H01L25/0753** (20130101); **H10H20/8514** (20250101);

Field of Classification Search

CPC: H01L (33/504); H01L (25/0753); H01L (33/505); G02B (6/0073); G02B (6/0046); G02B (6/0068); G02B (6/0001); G02F (1/133614); G02F (1/133514); G02F (1/133553); G02F (1/133615); G02F (2202/36); G02F (2203/055)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6372608	12/2001	Shimoda et al.	N/A	N/A
6645830	12/2002	Shimoda et al.	N/A	N/A
RE38466	12/2003	Inoue et al.	N/A	N/A
6818465	12/2003	Biwa et al.	N/A	N/A
6818530	12/2003	Shimoda et al.	N/A	N/A
6858081	12/2004	Biwa et al.	N/A	N/A
6967353	12/2004	Suzuki et al.	N/A	N/A
7002182	12/2005	Okuyama et al.	N/A	N/A
7084420	12/2005	Kim et al.	N/A	N/A
7087932	12/2005	Okuyama et al.	N/A	N/A
7154124	12/2005	Han et al.	N/A	N/A
7208725	12/2006	Sherrer et al.	N/A	N/A
7288758	12/2006	Sherrer et al.	N/A	N/A
7319044	12/2007	Han et al.	N/A	N/A
7501656	12/2008	Han et al.	N/A	N/A
7569987	12/2008	Naitou	N/A	N/A
7709857	12/2009	Kim et al.	N/A	N/A
7759140	12/2009	Lee et al.	N/A	N/A
7781727	12/2009	Sherrer et al.	N/A	N/A
7790482	12/2009	Han et al.	N/A	N/A
7940350	12/2010	Jeong	N/A	N/A
7959312	12/2010	Yoo et al.	N/A	N/A
7964881	12/2010	Choi et al.	N/A	N/A
7985976	12/2010	Choi et al.	N/A	N/A
7994525	12/2010	Lee et al.	N/A	N/A
8008683	12/2010	Choi et al.	N/A	N/A

8013352	12/2010	Lee et al.	N/A	N/A
8049161	12/2010	Sherrer et al.	N/A	N/A
8129711	12/2011	Kang et al.	N/A	N/A
8179938	12/2011	Kim	N/A	N/A
8263987	12/2011	Choi et al.	N/A	N/A
8324646	12/2011	Lee et al.	N/A	N/A
8399944	12/2012	Kwak et al.	N/A	N/A
8432511	12/2012	Jeong	N/A	N/A
8459832	12/2012	Kim	N/A	N/A
8502242	12/2012	Kim	N/A	N/A
8536604	12/2012	Kwak et al.	N/A	N/A
8723217	12/2013	Moon	N/A	N/A
8735931	12/2013	Han et al.	N/A	N/A
8766295	12/2013	Kim	N/A	N/A
9312246	12/2015	Roth et al.	N/A	N/A
10018776	12/2017	Itoh et al.	N/A	N/A
11251344	12/2021	Kim et al.	N/A	N/A
11287090	12/2021	Krames et al.	N/A	N/A
2014/0055982	12/2013	Tao	N/A	N/A
2014/0340890	12/2013	Hata	N/A	N/A
2019/0198724	12/2018	Amiya	N/A	N/A
2020/0006298	12/2019	Kim et al.	N/A	N/A
2020/0303358	12/2019	Zhang	N/A	N/A
2020/0303598	12/2019	Kim	N/A	N/A
2020/0313045	12/2019	Asai	N/A	N/A
2020/0381596	12/2019	Choi	N/A	N/A
2021/0296294	12/2020	Sun	N/A	N/A
2022/0020732	12/2021	Li et al.	N/A	N/A
2023/0288042	12/2022	Iwakura	N/A	N/A

OTHER PUBLICATIONS

Robert J. Lucas et al., “Measuring and using light in the melanopsin age”, Trends in Neurosciences, Jan. 2014, vol. 37, No. 1, pp. 1-9. cited by applicant

U.S. Appl. No. 18/236,105, filed Aug. 21, 2023. cited by applicant

Primary Examiner: Quarterman; Kevin

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation application of U.S. patent application Ser. No. 18/236,105, filed Aug. 21, 2023, in the US Patent and Trademark Office, which is based on and claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 10-2022-0111008, filed on Sep. 1, 2022, in the Korean Intellectual Property Office, the disclosure of which is incorporated by reference herein in its entirety.

BACKGROUND

(1) The present disclosure relates generally to a light emitting device for a display and a backlight

unit including the same.

(2) Semiconductor light emitting devices, such as light-emitting diodes (LEDs), have a long lifespan, low power consumption, a high response speed, and eco-friendliness and are used as light sources in various products, such as lighting fixtures and backlights of displays.

(3) Unlike LEDs used for lighting, LEDs used for backlights of displays are required to have an appropriate color gamut to implement color close to the original on a screen.

SUMMARY

(4) Example embodiments provide a light emitting device for a display, which may improve the circadian rhythm of the human body, and a backlight unit including the light emitting device.

(5) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

(6) According to an aspect of an example embodiment, a light emitting device includes: a first light emitter configured to emit second blue light, the first light emitter including: a first light emitting chip configured to emit first blue light having a peak wavelength in a range of about 430 nm to about 465 nm, at least one of a first phosphor configured to convert part of the first blue light into light having a peak wavelength in a range of about 530 nm to about 560 nm, and a second phosphor configured to convert part of the first blue light into light having a peak wavelength in a range of about 600 nm to about 650 nm; and a second light emitter configured to emit fourth blue light, the second light emitter including: a second light emitting chip configured to emit third blue light having a peak wavelength in a range of about 465 nm to about 500 nm, and at least one of a third phosphor configured to convert part of the third blue light into light having a peak wavelength in the range of about 530 nm to about 560 nm, and a fourth phosphor configured to convert part of the third blue light into light having a peak wavelength in the range of about 600 nm to about 650 nm, wherein a ratio of an intensity of a peak wavelength of the fourth blue light to an intensity of a peak wavelength of the second blue light is greater than or equal to 0.6.

(7) According to an aspect of an example embodiment, a light emitting device includes: a first light emitter configured to emit second blue light having a peak wavelength in the range of about 430 nm to about 465 nm, the first light emitter including: a first light emitting chip configured to emit first blue light having a peak wavelength in a range of about 430 nm to about 465 nm, a first wavelength conversion phosphor including at least one of a green phosphor and a red phosphor, and a first resinous body around the first light emitting chip and the first wavelength conversion phosphor; a second light emitter configured to emit fourth blue light having a peak wavelength in the range of about 465 nm to about 500 nm, the second light emitter including: a second light emitting chip configured to emit third blue light having a peak wavelength in a range of about 465 nm to about 500 nm, a second wavelength conversion phosphor including at least one of the green phosphor and the red phosphor, and a second resinous body around the second light emitting chip and the second wavelength conversion phosphor; a light emitting package around the first light emitter and the second light emitter, and exposing a top surface of the first light emitter and a top surface of the second light emitter; and a wavelength conversion film in a path of the second blue light and a path of the fourth blue light, the wavelength conversion film being configured to: convert at least part of the second blue light into first white light, and convert at least part of the fourth blue light into second white light, wherein a ratio of an intensity of the peak wavelength of the fourth blue light to an intensity of the peak wavelength of the second blue light is greater than or equal to 0.6.

(8) According to an aspect of an example embodiment, a backlight unit includes: a light guide plate; a reflector; and a light emitting module including a light emitting device and a substrate, wherein the light emitting device includes a first light emitter and a second light emitter, wherein the first light emitter is configured to emit second blue light having a peak wavelength in the range of about 430 nm to about 465 nm, and includes: a first light emitting chip configured to emit first blue light having a peak wavelength in a range of about 430 nm to about 465 nm, a first wavelength

conversion phosphor including at least one of a green phosphor and a red phosphor, and a first encapsulation material around the first light emitting chip and the first wavelength conversion phosphor; wherein the second light emitter is configured to emit fourth blue light having a peak wavelength in the range of about 465 nm to about 500 nm, and includes: a second light emitting chip configured to emit third blue light having a peak wavelength in a range of about 465 nm to about 500 nm, a second wavelength conversion phosphor including at least one of the green phosphor and the red phosphor, and a second encapsulation material around the second light emitting chip and the second wavelength conversion phosphor; a light emitting package around the first light emitter and the second light emitter, and exposing a top surface of the first light emitter and a top surface of the second light emitter; and a wavelength conversion film configured to convert at least part of the second blue light and at least part of the fourth blue light into white light, wherein the light emitting module is in an edge portion of the light guide plate, and wherein a ratio of an intensity of the peak wavelength of the fourth blue light to an intensity of the peak wavelength of the second blue light is greater than or equal to 0.6.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) The above and other aspects, features, and advantages of certain example embodiments of the present disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 is a cross-sectional view of a light emitting device for a display, according to one or more example embodiments;
- (3) FIG. 2 is a diagram of the emission spectra of second blue light and fourth blue light of the light emitting device of FIG. 1 according to one or more example embodiments;
- (4) FIG. 3 is a diagram of a CIE 1931 color coordinate system showing the color coordinates of second blue light, fourth blue light, first white light, and second white light of the light emitting device of FIG. 1 according to one or more example embodiments;
- (5) FIGS. 4 and 5 are diagrams of emission spectra with respect to the driving of a light emitting device for a display, according to one or more example embodiments;
- (6) FIG. 6 is a diagram of a CIE 1931 color coordinate system showing a color gamut of a light emitting device for a display, according to one or more example embodiments;
- (7) FIG. 7 is a diagram of a light emitting module including the light emitting device of FIG. 1 according to one or more example embodiments;
- (8) FIG. 8 is a cross-sectional view of a light emitting device for a display, according to one or more example embodiments;
- (9) FIG. 9 is a diagram of a light emitting module including the light emitting device of FIG. 8 according to one or more example embodiments;
- (10) FIG. 10 is a cross-sectional view of a backlight unit according to one or more example embodiments;
- (11) FIG. 11 is a cross-sectional view of a backlight unit according to one or more example embodiments; and
- (12) FIG. 12 is a cross-sectional view of a backlight unit according to one or more example embodiments.

DETAILED DESCRIPTION

(13) Hereinafter, example embodiments are described in detail with reference to the accompanying drawings. In the drawing, like reference characters denote like elements, and redundant descriptions thereof will be omitted.

(14) As used herein, expressions such as “at least one of,” when preceding a list of elements,

modify the entire list of elements and do not modify the individual elements of the list. For example, the expression, “at least one of a, b, and c,” should be understood as including only a, only b, only c, both a and b, both a and c, both b and c, or all of a, b, and c.

(15) In related art, the influence of blue light on the circadian rhythm is not considered. For example, light induced from a blue light having a peak wavelength in a range of 430 nm to 465 nm suppresses the release of melatonin that is a hormone closely involved in sleep and may thus cause a sleep disorder. Example embodiments of the disclosure may be directed to light emitting devices that are appropriate to the circadian rhythm and realizing the three primary colors for displays.

(16) FIG. 1 is a cross-sectional view of a light emitting device **100** for a display, according to one or more example embodiments. FIG. 2 is a diagram of the emission spectra of second blue light and fourth blue light of the light emitting device of FIG. 1 according to one or more example embodiments. FIG. 3 is a diagram of a CIE 1931 color coordinate system showing the color coordinates of second blue light, fourth blue light, first white light, and second white light of the light emitting device of FIG. 1 according to one or more example embodiments. In particular, FIG. 2 illustrates the emission spectra of second blue light B2 and fourth blue light B4 of the light emitting device **100** of FIG. 1. FIG. 3 illustrates a CIE 1931 color coordinate system showing the color coordinates of the second blue light B2, the fourth blue light B4, first white light W1, and second white light W2 of the light emitting device **100** of FIG. 1.

(17) The light emitting device **100** for a display may include a substrate **110**, a light emitting package **112**, a first light emitter **132**, and a second light emitter **134**.

(18) The first light emitter **132** and the second light emitter **134** may be on the substrate **110** and housed in the light emitting package **112**. The light emitting package **112** may have a recess **122**, which is defined by a top surface **110U** of the substrate **110** and an inner surface **1121** of the light emitting package **112**. The first light emitter **132** and the second light emitter **134** may be respectively accommodated in recesses **122**.

(19) The light emitting package **112** may surround the first light emitter **132** and the second light emitter **134** and expose the respective top surfaces of the first and second light emitters **132** and **134**. For example, the light emitting package **112** may include an outer wall **113** and a partition **114**. The first light emitter **132** may be separated from the second light emitter **134** by the partition **114**.

(20) Each of the recesses **122** may be configured to reflect light, which is emitted from the first or second light emitter **132** or **134**, to the exposed top surface of first or second light emitter **132** or **134**. For example, the inner surface **1121** of the light emitting package **112** may be oblique to the top surface **110U** of the substrate **110**, and the cross-sectional area of each recess **122** in a horizontal direction (the X direction and/or the Y direction) may increase away in a vertical direction (the Z direction) from the top surface **110U** of the substrate **110**.

(21) The substrate **110** may correspond to a printed circuit board (PCB) including a wiring structure. For example, the wiring structure may be electrically connected to a first light emitting chip **142** of the first light emitter **132** and a second light emitting chip **144** of the second light emitter **134**. The first light emitting chip **142** and the second light emitting chip **144** may be independently driven.

(22) The light emitting package **112** may include polymer resin. For example, the light emitting package **112** may include polymer resin including a reflective material.

(23) The first light emitter **132** may include the first light emitting chip **142**, first wavelength conversion phosphor **151a**, and a first encapsulation material **156** surrounding the first light emitting chip **142** and the first wavelength conversion phosphor **151a**.

(24) The first light emitting chip **142** may emit first blue light B1 having a peak wavelength in a range of about 430 nm to about 465 nm. The first blue light B1 may have a peak wavelength in a range of about 445 nm to about 455 nm and desirably have a peak wavelength at about 450 nm. A coordinate of the first blue light B1 is around the edge of the diagram in FIG. 3 called spectral

locus. For example, the first blue light B1 represents almost pure monochromatic light. A full width at half maximum of the first blue light B1, for example, may be less than 19 nm.

(25) The first wavelength conversion phosphor **151a** may include at least one of a first phosphor **152a** and a second phosphor **154a**. The first phosphor **152a** may convert part of the first blue light B1 into light having a peak wavelength in a range of about 530 nm to about 560 nm. The second phosphor **154a** may convert part of the first blue light B1 into light having a peak wavelength in a range of about 600 nm to about 650 nm.

(26) The first light emitter **132** may emit the second blue light B2 having a peak wavelength in a range of about 430 nm to about 465 nm. The second blue light B2 may be formed by the sum of the part of the first blue light B1 converted by the first phosphor **152a**, the part of the first blue light B1 converted by the second phosphor **154a**, and the majority of the first blue light B1 not converted by phosphors. In a range of first coordinates CB2 corresponding to the CIE 1931 coordinates of the second blue light B2, an x-coordinate may be about 0.1 to about 0.3 and a y-coordinate may be about 0.02 to about 0.2. For example, in the range of the first coordinates CB2 corresponding to the CIE 1931 coordinates of the second blue light B2, the x-coordinate may be about 0.18 to about 0.22 and the y-coordinate may be about 0.06 to about 0.12.

(27) The second light emitter **134** may include the second light emitting chip **144**, a second wavelength conversion phosphor **151b**, and a second encapsulation material **158** surrounding the second light emitting chip **144** and the second wavelength conversion phosphor **151b**.

(28) The second light emitting chip **144** may emit third blue light B3 having a peak wavelength in a range of about 465 nm to about 500 nm. The third blue light B3 may have a peak wavelength in a range of about 475 nm to about 485 nm and desirably have a peak wavelength at about 480 nm. A coordinate of the third blue light B3 is around the spectral locus of the diagram of FIG. 3. For example, the third blue light B3 represents almost pure monochromatic light. A full width at half maximum of the third blue light B3, for example, may be less than 19 nm.

(29) The second wavelength conversion phosphor **151b** may include at least one among a third phosphor **152b** and a fourth phosphor **154b**. The third phosphor **152b** may convert part of the third blue light B3 into light having a peak wavelength in a range of about 530 nm to about 560 nm. The fourth phosphor **154b** may convert part of the third blue light B3 into light having a peak wavelength in a range of about 600 nm to about 650 nm.

(30) The second light emitter **134** may emit the fourth blue light B4 having a peak wavelength in a range of about 465 nm to about 500 nm. The fourth blue light B4 may be formed by the part of the third blue light B3 converted by the third phosphor **152b**, the part of the third blue light B3 converted by the fourth phosphor **154b**, and the majority of the third blue light B3 not converted by phosphors. In a range of second coordinates CB4 corresponding to the CIE 1931 coordinates of the fourth blue light B4, an x-coordinate may be about 0.05 to about 0.3 and a y-coordinate may be about 0.05 to about 0.3. For example, in the range of the second coordinates CB4 corresponding to the CIE 1931 coordinates of the fourth blue light B4, the x-coordinate may be about 0.2 to about 0.24 and the y-coordinate may be about 0.16 to about 0.22.

(31) The light emitting device **100** for a display may include the first light emitter **132** emitting the second blue light B2 and the second light emitter **134** emitting the fourth blue light B4, thereby improving the circadian rhythm of the human body. For example, the second blue light B2 may not interfere with the release of melatonin, which is deeply involved in sleep, and the fourth blue light B4 may suppress the release of melatonin. For example, the second light emitting chip **144** may be driven more predominantly than the first light emitting chip **142** during the day, and the first light emitting chip **142** may be driven more predominantly than the second light emitting chip **144** during the night. For example, when the drive strengths of the first and second light emitting chips **142** and **144** are controlled based on time, the release of melatonin may be controlled, and accordingly, the circadian rhythm of the human body may be improved.

(32) A melanopic ratio (MR) may be used as an index quantifying the effect of light on the

circadian rhythm of the human body. The MR may also be referred to as a melanopic/photopic (M/P) ratio. For example, an MR may quantify the response of human eyes to light and may refer to a ratio of a melanopic (e.g., circadian) intensity to a photopic (e.g., visual) intensity. For example, an MR may indicate how much a light source stimulates the circadian system. An MR may be given by Equation (1) as follows.

$$(33) \quad MR = \frac{EML}{Im} \quad (1) \quad EML = 72983.25 * \int_{380}^{780} SPD(\lambda) * Melanopicsensitivity(\lambda) d\lambda$$
$$Im = 683 * \int_{380}^{780} SPD(\lambda) * Photopicsensitivity(\lambda) d\lambda$$

(34) In Equation (1), SPD(λ) is the color profile of light measured by equipment like a spectrometer, and each of Melanopic sensitivity(λ) and the Photopic sensitivity(λ) may refer to functions, such as functions proposed in “Measuring and Using Light in the Melanopsin Age” by Lucas et al., the contents of which are incorporated by reference herein. The EML may refer to an equivalent melanopic lux (EML).

(35) For example, when an EML is high, the release of melatonin may be suppressed and there may be a boost of alertness. The effects on hormone regulation may be compared based on the EML of light.

(36) A ratio of an intensity 14 of the peak wavelength of the fourth blue light B4 to an intensity 12 of the peak wavelength of the second blue light B2 may be greater than or equal to 0.6.

Accordingly, the first emitter **132** and the second emitter **134** may be driven together, and the melanopic sensitivity of the light emitting device **100** including a wavelength conversion film **160** may be improved. Accordingly, the circadian system control performance of the light emitting device **100** for a display according to embodiments may be increased within above range, and the color reproducibility of a backlight unit (**300** in FIG. **10**) including the light emitting device **100** for a display may also be increased.

(37) The first wavelength conversion phosphor **151a** of the first light emitter **132** may be provided in an amount of about 0.1 parts by weight to about 15 parts by weight per 100 parts by weight of the first encapsulation material **156**. In some embodiments, the first wavelength conversion phosphor **151a** of the first light emitter **132** may be provided in an amount of about 1 part by weight to about 10 parts by weight per 100 parts by weight of the first encapsulation material **156**. In the range described above, the effect of the light emitting device **100** on the improvement of the circadian rhythm by inducing the release of hormone may be increased, and a high color reproducibility may be realized.

(38) The second wavelength conversion phosphor **151b** of the second light emitter **134** may be provided in an amount of about 0.1 parts by weight to about 20 parts by weight per 100 parts by weight of the second encapsulation material **158**. In some embodiments, the second wavelength conversion phosphor **151b** of the second light emitter **134** may be provided in an amount of about 1 part by weight to about 12 parts by weight (e.g., about 4 parts by weight to about 8 parts by weight), per 100 parts by weight of the second encapsulation material **158**. In the range described above, the effect of the light emitting device **100** on the improvement of the circadian rhythm by suppressing the hormone may be increased, and a high color reproducibility may be realized.

(39) A ratio of a content of the first wavelength conversion phosphor **151a** to a content of the first encapsulation material **156** in the first light emitter **132** may be less than a ratio of a content of the second wavelength conversion phosphor **151b** to a content of the second encapsulation material **158** in the second light emitter **134**. Accordingly, the performance of the light emitting device **100** for a display may be increased.

(40) A ratio of a content of the first phosphor **152a** to a content of the second phosphor **154a** in the first light emitter **132** may be about 0.5 to about 0.7. A ratio of a content of the third phosphor **152b** to a content of the fourth phosphor **154b** in the second light emitter **134** may be about 0.01 to about 0.2. The second light emitter **134** may not include the third phosphor **152b**. In the content ranges described above with respect to the first to fourth phosphors **152a**, **154a**, **152b**, and **154b**, the

hormone regulation performance of the light emitting device **100** for a display may be increased, and the backlight unit **300** including the light emitting device **100** may have a high color reproducibility.

(41) Each of the first and third phosphors **152a** and **152b** may include at least one of β -SiAlON:Eu, (Ga,Gd,Y).sub.2Al.sub.5O.sub.12:Ce, La.sub.3Si.sub.6Ni:Ce, Eu-doped (Sr,Ca,Ba)Si.sub.2O.sub.2N.sub.2:Eu, (Ba,Sr)Al.sub.2O.sub.4:Eu, YBO.sub.3:Ce,Tb, BaMgAl.sub.10O.sub.17:Eu,Mn, (Sr,Ca,Ba)(Al,Ga).sub.2S.sub.4:Eu, ZnS:Cu,Al, Ca.sub.8Mg(SiO.sub.4).sub.4Cl.sub.2:Eu,Mn, Ba.sub.2SiO.sub.4:Eu, (Ba,Sr).sub.2SiO.sub.4:Eu, Ba.sub.2(Mg,Zn)Si.sub.2O.sub.7:Eu, Sr.sub.2Si.sub.3O.sub.8.2SrCl.sub.2:Eu, (Sr,Ca,Ba,Mg)P.sub.2O.sub.7N.sub.8:Eu,Mn, (Sr,Ca,Ba,Mg).sub.3P.sub.2O.sub.8:Eu,Mn, Ca.sub.3Sc.sub.2Si.sub.3O.sub.12:Ce, CaSc.sub.2O.sub.4:Ce, and Ln.sub.2Si.sub.3O.sub.3N.sub.4:Tb.

(42) Each of the second and fourth phosphors **154a** and **154b** may include at least one of (Sr,Ca).sub.2AlSiN.sub.3:Eu, CaAlSiN.sub.3:Eu, K.sub.xSiF.sub.y:Mn.sup.4+(2≤x≤3, 4≤y≤7), Y.sub.2O.sub.2S:Eu, YVO.sub.4:Eu,Bi, Y.sub.2O.sub.2S:Eu,Bi,SrS:Eu, (Ca,Sr)S:Eu, SrY.sub.2S.sub.4:Eu, CaLa.sub.2S.sub.4:Ce, (Sr,Ca,Ba).sub.3SiO.sub.5:Eu, and (Sr,Ca,Ba).sub.2Si.sub.5N.sub.8:Eu.

(43) Each of the first and second encapsulation materials **156** and **158** may include epoxy resin, silicon, urethane resin, oxetane resin, acrylic resin, polycarbonate, polyimide, or a combination thereof.

(44) The light emitting device **100** for a display may further include a wavelength conversion film **160** in a path of the second blue light B2 and a path of the fourth blue light B4. The wavelength conversion film **160** may include a wavelength conversion quantum dot **161** and a transparent encapsulation film **166** surrounding the wavelength conversion quantum dot **161**. In some embodiments, the wavelength conversion film **160** may be on the top surface of the first light emitter **132** and the top surface of the second light emitter **134**. Alternatively, the wavelength conversion film **160** may be separated from the top surface of the first light emitter **132** and the top surface of the second light emitter **134**.

(45) The wavelength conversion quantum dot **161** may refer to generally a semiconductor nanocrystal and have various shapes, such as an isotropic semiconductor nanocrystal, a quantum rod, and a quantum plate. For example, the aspect ratio of a quantum rod may be greater than 1 or greater than or equal to 2, 3, or 5. For example, the aspect ratio of a quantum rod may be less than or equal to 50, 30, or 20. The wavelength conversion quantum dot **161** may have a particle diameter of about 1 nm to about 100 nm. In some embodiments, the wavelength conversion quantum dot **161** may have a particle diameter of about 1 nm to about 80 nm. For example, the wavelength conversion quantum dot **161** may have a particle diameter of about 1 nm to about 50 nm or about 1 nm to about 20 nm. For example, when the wavelength conversion quantum dot **161** is not round, the particle diameter of the wavelength conversion quantum dot **161** may refer to the size of the longest portion thereof.

(46) The wavelength conversion quantum dot **161** may include a binary compound, a ternary compound, or a quaternary compound in a uniform concentration distribution or in a partially different concentration distribution. In some embodiments, the wavelength conversion quantum dot **161** may have a core-shell structure, in which a quantum dot is surrounded by another quantum dot. For example, the interface between the core and the shell of a quantum dot may have a concentration gradient, in which the concentration of elements in the shell decreases toward the center of the shell. For example, the composition of the shell of a quantum dot may have a higher energy band gap than the composition of the core of the quantum dot, and accordingly, the quantum confinement effect occurs. For example, a quantum dot may have a structure which includes a single core and multiple shell layers surrounding the core. In this case, the multi-layer shell structure may include at least two layers of shells, and each layer may have a single composition,

alloy, or concentration gradient. For example, among the multiple layers of shells, the energy band gap of each shell increases away from the core, and accordingly, the quantum confinement effect occurs.

(47) When the wavelength conversion quantum dot **161** has a core-shell structure, the diameter of a core may be about 1 nm to about 30 nm. In some embodiments, the diameter of a core may be about 3 nm to about 10 nm. The thickness of a shell may be about 0.1 nm to about 20 nm. In some embodiments, the thickness of a shell may be about 0.5 nm to about 10 nm, about 0.5 nm to about 5 nm, or about 0.5 nm to about 2 nm.

(48) The wavelength conversion quantum dot **161** may include at least one of a first quantum dot **162** and a second quantum dot **164**. The first quantum dot **162** may convert part of each of the second blue light **B2** and the fourth blue light **B4** into light having a peak wavelength in a range of about 510 nm to about 550 nm. The second quantum dot **164** may convert part of each of the second blue light **B2** and the fourth blue light **B4** into light having a peak wavelength in a range of about 610 nm to about 660 nm.

(49) The wavelength conversion film **160** may convert at least part of the second blue light **B2** into the first white light **W1**. In a range of third coordinates **CW1** corresponding to the CIE 1931 coordinates of the first white light **W1**, an x-coordinate may be about 0.28 to about 0.32 and a y-coordinate may be about 0.29 to about 0.33. Accordingly, within above range, the color reproducibility of a backlight unit (**300** in FIG. **10**) including the light emitting device **100** for a display may also be increased.

(50) The wavelength conversion film **160** may convert at least part of the fourth blue light **B4** into the second white light **W2**. In a range of fourth coordinates **CW2** corresponding to the CIE 1931 coordinates of the second white light **W2**, an x-coordinate may be about 0.28 to about 0.32 and a y-coordinate thereof may be about 0.29 to about 0.33. Accordingly, within above range, the color reproducibility of a backlight unit (**300** in FIG. **10**) including the light emitting device **100** for a display may also be increased.

(51) The EML of the second white light **W2** may be greater than the EML of the first white light **W1**. For example, a first ratio, which is the ratio of the EML of the second white light **W2** to the EML of the first white light **W1**, may be greater than 1. In this case, the effect of the EML of the second white light **W2** derived from second emitter **134** having high melanopic sensitivity may be increased, and when the first emitter **132** and the second emitter **134** are driven together, the effect of the light emitting device **100** on the improvement of the circadian rhythm may be increased.

(52) The wavelength conversion quantum dot **161** may be provided in an amount of about 5 parts by weight to about 30 parts by weight per 100 parts by weight of the transparent encapsulation film **166**. The first quantum dot **162** may be provided in an amount of about 2.5 parts by weight to about 15 parts by weight, and for example, about 5 parts by weight to about 10 parts by weight, per 100 parts by weight of the transparent encapsulation film **166**. The second quantum dot **164** may be provided in an amount of about 2.5 parts by weight to about 15 parts by weight, and for example, about 5 parts by weight to about 10 parts by weight, per 100 parts by weight of the transparent encapsulation film **166**. In the ranges described above, the first white light **W1** and the second white light **W2** may respectively satisfy the range of the third coordinates **CW1** and the range of the fourth coordinates **CW2**.

(53) For example, an emission wavelength may be adjusted by changing the size and/or composition of the wavelength conversion quantum dot **161**. The wavelength conversion quantum dot **161** may include a Group II-VI compound, a Group III-V compound, a Group IV-VI compound, a Group VI compound, or a combination thereof. For example, the Group II-VI compound may be a binary compound of CdSe, CdTe, ZnS, ZnSe, ZnTe, ZnO, HgS, HgSe, HgTe, MgSe, MgS, and a combination thereof, a ternary compound of CdSeS, CdSeTe, CdSTe, ZnSeS, ZnSeTe, ZnSTe, HgSeS, HgSeTe, HgSTe, CdZnS, CdZnSe, CdZnTe, CdHgS, CdHgSe, CdHgTe, HgZnS, HgZnSe, HgZnTe, MgZnSe, MgZnS, and a combination thereof, and a quaternary

compound of HgZnTeS, CdZnSeS, CdZnSeTe, CdZnSTe, CdHgSeS, CdHgSeTe, CdHgSTe, HgZnSeS, HgZnSeTe, HgZnSTe, and a combination thereof. For example, the Group III-V compound may be a binary compound of GaN, GaP, GaAs, GaSb, AlN, AlP, AlAs, AlSb, InN, InP, InAs, InSb, and a combination thereof, a ternary compound of GaNP, GaNAs, GaNSb, GaPAs, GaPSb, AlNP, AlNAs, AlNSb, AlPAs, AlPSb, InNP, InNAs, InNSb, InPAs, InPSb, GaAlNP, and a combination thereof, and a quaternary compound of GaAlNAs, GaAlNSb, GaAlPAs, GaAlPSb, GaInNP, GaInNAs, GaInNSb, GaInPAs, GaInPSb, InAlNP, InAlNAs, InAlNSb, InAlPAs, InAlPSb, and a combination thereof. For example, the Group IV-VI compound may be a binary compound of SnS, SnSe, SnTe, PbS, PbSe, PbTe, and a combination thereof, a ternary compound of SnSeS, SnSeTe, SnSTe, PbSeS, PbSeTe, PbSTe, SnPbS, SnPbSe, SnPbTe, and a combination thereof, and a quaternary compound of SnPbSSe, SnPbSeTe, SnPbSTe, and a combination thereof. For example, the Group IV compound may be a single-element compound of Si, Ge, and a mixture thereof and a binary compound of SiC, SiGe, and a mixture thereof. For example, each of the first quantum dot **162** and the second quantum dot **164** may include at least one of InP/ZnS, InP/ZnSe, CdSe/CdS, CdSe/ZnS, PbS/ZnS, and InP/GaP/ZnS.

(54) The quantum yield of the wavelength conversion quantum dot **161** may be greater than or equal to about 10% (e.g., about 30%, about 50%, about 60%, about 70%, or about 90%, but not limited thereto). For example, the wavelength conversion quantum dot **161** may have a relatively narrow spectrum. For example, the wavelength conversion quantum dot **161** may have a full width at half maximum (FWHM) of 45 nm or less. For example, the wavelength conversion quantum dot **161** may have an FWHM of 40 nm or less or 30 nm or less.

(55) The transparent encapsulation film **166** may include epoxy resin, silicon, urethane resin, oxetane resin, acrylic resin, polycarbonate, polyimide, or a combination thereof.

(56) FIGS. **4** and **5** are diagrams of emission spectra with respect to the driving of the light emitting device **100** for a display, according to one or more example embodiments.

(57) Referring to FIG. **4**, when the first light emitter **132** of the light emitting device **100** for a display is driven, the first white light W**1** may be emitted. The first white light W**1** may have a peak wavelength in a range of about 430 nm to about 465 nm, a peak wavelength in a range of about 530 nm to about 560 nm, and a peak wavelength in a range of about 600 nm to about 650 nm. A melanopic sensitivity curve MS marked with the dashed line in FIG. **4** may have a peak wavelength in a range of about 465 nm to about 500 nm. For example, the emission spectrum curve of the first white light W**1** may have a low value in the peak wavelength range of the melanopic sensitivity curve MS.

(58) Referring to FIG. **5**, when the second light emitter **134** of the light emitting device **100** for a display is driven, the second white light W**2** may be emitted. The second white light W**2** may have a peak wavelength in a range of about 465 nm to about 500 nm, a peak wavelength in a range of about 530 nm to about 560 nm, and a peak wavelength in a range of about 600 nm to about 650 nm. The emission spectrum curve of the second white light W**2** may have a peak wavelength in the peak wavelength range of the melanopic sensitivity curve MS. For example, when the backlight unit **300** including the second white light W**2** is used as a light source of a display, the release of melatonin of a person exposed to the display may be suppressed, and the person's circadian rhythm may be improved.

(59) FIG. **6** is a diagram of a CIE 1931 color coordinate system showing a color gamut of the light emitting device **100** for a display, according to one or more example embodiments. FIG. **6** illustrates a DCI color standard G**0**, a first gamut G**1** that is the gamut of the first white light W**1** emitted from the first light emitter **132**, and a second gamut G**2** that is the gamut of the second white light W**2** emitted from the second light emitter **134**.

(60) Referring to FIG. **6**, the first gamut G**1** may cover at least 90% of the area of the DCI color standard G**0**. For example, the first gamut G**1** may cover at least 95% of the area of the DCI color standard G**0**. The second gamut G**2** may cover at least 60% of the area of the DCI color standard

G0. For example, the second gamut G2 may cover at least 70% of the area of the DCI color standard G0. The light emitting device **100** for a display includes the first light emitter **132** and the second light emitter **134**, thereby improving the circadian rhythm and realizing a high color reproducibility.

(61) FIG. 7 is a diagram of a light emitting module **200** including the light emitting device **100** of FIG. 1 according to one or more example embodiments.

(62) Referring to FIG. 7, the light emitting module **200** may include the light emitting device **100** for a display. The light emitting module **200** may have a shape that is longer in a first horizontal direction (the X direction) than in a second horizontal direction (the Y direction) in a plan view. The substrate **110** may have a rectangular band shape extending in the first horizontal direction (the X direction) in a plan view, and a plurality of light emitting devices **100** for a display may be arranged on the substrate **110** in the first horizontal direction (the X direction). For example, the light emitting devices **100** for a display may share the substrate **110**.

(63) FIG. 8 is a cross-sectional view of a light emitting device **100a** for a display, according to one or more example embodiments. FIG. 8 differs from FIG. 1 in that the light emitting device **100a** for a display further includes a third light emitter **136**.

(64) The light emitting device **100a** for a display may further include the third light emitter **136**. The third light emitter **136** may include a third light emitting chip **146**, a third wavelength conversion phosphor **151c**, and a third encapsulation material **159** surrounding the third light emitting chip **146** and the third wavelength conversion phosphor **151c**. The third light emitting chip **146** may emit fifth blue light B5 having a peak wavelength in a range of about 430 nm to about 465 nm. In some embodiments, the fifth blue light B5 may have a peak wavelength in a range of about 445 nm to about 455 nm and desirably have a peak wavelength at about 450 nm. The third wavelength conversion phosphor **151c** may include at least one of a fifth phosphor **152c** and a sixth phosphor **154c**. The fifth phosphor **152c** may convert part of the fifth blue light B5 into light having a peak wavelength in a range of about 530 nm to about 560 nm. The sixth phosphor **154c** may convert part of the fifth blue light B5 into light having a peak wavelength in a range of about 600 nm to about 650 nm. The third light emitter **136** may emit a sixth blue light B6 having a peak wavelength in a range of about 430 nm to about 465 nm. The sixth blue light B6 may be produced based on the part of the fifth blue light B5 converted by the fifth phosphor **152c** and the part of the fifth blue light B5 converted by the sixth phosphor **154c**.

(65) The sixth blue light B6 may have the same coordinate range as the first coordinates CB2 corresponding to the CIE 1931 coordinates of the second blue light B2. For example, an x-coordinate in the CIE 1931 coordinates of the sixth blue light B6 may be about 0.1 to about 0.3, and a y-coordinate therein may be about 0.02 to about 0.2. For example, an x-coordinate in the CIE 1931 coordinates of the sixth blue light B6 may be about 0.18 to about 0.22, and a y-coordinate therein may be about 0.06 to about 0.12.

(66) The fifth phosphor **152c** may include at least one of the phosphors described above as being included in the first phosphor **152a**. The sixth phosphor **154c** may include at least one of the phosphors described above as being included in the second phosphor **154a**. The third encapsulation material **159** may include epoxy resin, silicon, urethane resin, oxetane resin, acrylic resin, polycarbonate, polyimide, or a combination thereof.

(67) A content of the fifth phosphor **152c** may be substantially the same as a content of the first phosphor **152a**, and a content of the sixth phosphor **154c** may be substantially the same as a content of the second phosphor **154a**,

(68) The third light emitter **136** may be substantially the same as the first light emitter **132**. The light emitting device **100a** for a display may include two first light emitters **132** and one second light emitter **134**. For example, the second light emitter **134** may be between the two first light emitters **132**.

(69) The wavelength conversion film **160** may be in a path of light emitted from the third light

emitter **136**. For example, the third light emitter **136** may share the wavelength conversion film **160** with the first and second light emitters **132** and **134**. The wavelength conversion film **160** may convert at least part of the sixth blue light **B6** into third white light **W3**. An x-coordinate in the CIE 1931 coordinates of the third white light **W3** may be about 0.28 to about 0.32, and a y-coordinate therein may be about 0.29 to about 0.33.

(70) FIG. **9** is a diagram of a light emitting module **200a** including the light emitting device **100a** of FIG. **8** according to one or more example embodiments. FIG. **9** differs from FIG. **7** in that the light emitting module **200a** includes the light emitting device **100a** including the third light emitter **136**.

(71) Referring to FIG. **9**, a plurality of light emitting devices **100a**, each of which includes the first to third light emitters **132**, **134**, and **136** in the first horizontal direction (the X direction), may be arranged in the first horizontal direction (the X direction). The second light emitter **134** may be between the first light emitter **132** and the third light emitter **136** in the first horizontal direction (the X direction).

(72) FIG. **10** is a cross-sectional view of a backlight unit **300** according to one or more example embodiments.

(73) Referring to FIG. **10**, the backlight unit **300** may include the light emitting module **200**, a light guide plate **312**, and a reflector **314**. The backlight unit **300** may be of an edge type, in which light is incident to a side surface **312S** of the light guide plate **312**.

(74) The light emitting module **200** may be beside the light guide plate **312** and emit light to the side surface **312S** of the light guide plate **312**. According to embodiments, light incident to the side surface **312S** of the light guide plate **312** may be reflected by the reflector **314** and emitted through a top surface **312U** of the light guide plate **312**. For example, a color filter may be on the top surface **312U** of the light guide plate **312**.

(75) The wavelength conversion film **160** may be on the top of the light emitting module **200**. The wavelength conversion film **160** may be directly on the respective top surfaces of the first and second light emitters **132** and **134**. The wavelength conversion film **160** may be separated from the light guide plate **312** in the vertical direction (the Z direction).

(76) FIG. **11** is a cross-sectional view of a backlight unit **300a** according to one or more example embodiments. FIG. **11** differs from FIG. **10** in that the wavelength conversion film **160** is on the side surface **312S** of the light guide plate **312**, which is near the light emitting module **200**.

(77) Referring to FIG. **11**, the wavelength conversion film **160** may be on the side surface **312S** of the light guide plate **312**. The wavelength conversion film **160** may be separated from the light emitting module **200** in the vertical direction (the Z direction).

(78) FIG. **12** is a cross-sectional view of a backlight unit **300b** according to one or more example embodiments. FIG. **12** differs from FIG. **10** in that the wavelength conversion film **160** is on the top surface **312U** of the light guide plate **312**.

(79) Referring to FIG. **12**, the wavelength conversion film **160** may be on the top surface **312U** of the light guide plate **312**. Blue light may be emitted from the light emitting module **200** and incident to the side surface **312S** of the light guide plate **312**. The blue light may be reflected by the reflector **314** to the top surface **312U** of the light guide plate **312** and converted into white light by the wavelength conversion film **160** on the top surface **312U** of the light guide plate **312**.

(80) Various experimental examples are described below with respect to Tables 1-5 to further demonstrate aspects of the disclosure. The values, aspects, and other components for producing the experimental results below are examples and not exclusive of the embodiments disclosed herein.

(81) The light emitting device **100** for a display was manufactured using the first light emitting chip **142** having a peak wavelength of about 450 nm and the second light emitting chip **144** having a peak wavelength of about 480 nm such that the second blue light **B2** of the first light emitter **132** and the fourth blue light **B4** of the second light emitter **134** have MRs of Table 1 below. In the experiments, emission spectra were measured using CAS140 from Instrument Systems.

(82) TABLE-US-00001 TABLE 1 Experimental examples MR(B2) MR(B4) MR(B4)/MR(B2)
Experimental example A 3.02 3.67 1.22 Experimental example B 1.64 3.12 1.91 Experimental
example C 1.66 3.94 2.37 Experimental example D 15.85 7.43 0.47

Experimental Example A

(83) The intensity of the peak wavelength of each of the second blue light B2 and the fourth blue light B4 of the light emitting device **100** for a display according to Experiment Example A in Table 1 was changed as shown in Table 2 below, and the EML of the first white light W1 and the EML of the second white light W2 were measured.

(84) TABLE-US-00002 TABLE 2 Experimental Peak intensity(B4)/ example A Peak intensity(B2)
EML(W2)/EML(W1) A-1 0.4 0.82 A-2 0.5 1.02 A-3 0.6 1.23 A-4 0.7 1.43 A-5 0.8 1.64

Experimental Example B

(85) The intensity of the peak wavelength of each of the second blue light B2 and the fourth blue light B4 of the light emitting device **100** for a display according to Experiment Example B in Table 1 was changed as shown in Table 3 below, and the EML of the first white light W1 and the EML of the second white light W2 were measured.

(86) TABLE-US-00003 TABLE 3 Experimental Peak intensity(B4)/ example B Peak intensity(B2)
EML(W2)/EML(W1) B-1 0.4 0.69 B-2 0.5 0.86 B-3 0.6 1.03 B-4 0.7 1.2 B-5 0.8 1.37

Experimental Example C

(87) The intensity of the peak wavelength of each of the second blue light B2 and the fourth blue light B4 of the light emitting device **100** for a display according to Experiment Example C in Table 1 was changed as shown in Table 4 below, and the EML of the first white light W1 and the EML of the second white light W2 were measured.

(88) TABLE-US-00004 TABLE 4 Experimental Peak intensity(B4)/ example C Peak intensity(B2)
EML(W2)/EML(W1) C-1 0.4 0.72 C-2 0.5 0.91 C-3 0.6 1.09 C-4 0.7 1.27 C-5 0.8 1.45

Experimental Example D

(89) The intensity of the peak wavelength of each of the second blue light B2 and the fourth blue light B4 of the light emitting device **100** for a display according to Experiment Example D in Table 1 was changed as shown in Table 5 below, and the EML of the first white light W1 and the EML of the second white light W2 were measured.

(90) TABLE-US-00005 TABLE 5 Experimental Peak intensity(B4)/ example D Peak intensity(B2)
EML(W2)/EML(W1) D-1 0.4 0.68 D-2 0.5 0.85 D-3 0.6 1.02 D-4 0.7 1.19 D-5 0.8 1.36

(91) Referring to Tables 2 to 5, when a ratio of the intensity of the peak wavelength of the fourth blue light B4 to the intensity of the peak wavelength of the second blue light B2 is greater than or equal to 0.6, it may be seen that a ratio of the EML of the second white light W2 to the EML of the first white light W1 is greater than or equal to 1. For example, when the EML of the second white light W2 is greater than the EML of the first white light W1, the circadian rhythm may be improved.

(92) According to example embodiments, a light emitting device for a display may include a first light emitting chip, which has a peak wavelength in a range of 430 nm to 465 nm, and a second light emitting chip, which has a peak wavelength in a range of 465 nm to 500 nm. A ratio of the intensity of the peak wavelength of light, which is emitted from a second light emitting unit including the second light emitting chip, to the intensity of the peak wavelength of light, which is emitted from a first light emitting unit including the first light emitting chip, may be greater than or equal to 0.6. Accordingly, the EML of the second white light W2 may be greater than the EML of the first white light W1. When the light emitting device is used as a light source of a display, the circadian rhythm and the color reproducibility may be improved.

(93) Each of the embodiments provided in the above description is not excluded from being associated with one or more features of another example or another embodiment also provided herein or not provided herein but consistent with the disclosure

(94) While the disclosure has been particularly shown and described with reference to example

embodiments thereof, it will be understood that various changes in form and details may be made therein without departing from the spirit and scope of the following claims.

Claims

1. A backlight unit comprising: a light guide plate; a reflector; and a light emitting module comprising a light emitting device and a substrate, wherein the light emitting device comprises a first light emitter and a second light emitter, wherein the first light emitter is configured to emit second blue light having a peak wavelength in a range of 430 nm to 465 nm, wherein the first light emitter comprises: a first light emitting chip configured to emit first blue light having a peak wavelength in a range of 430 nm to 465 nm, a first wavelength conversion phosphor comprising at least one of a green phosphor and a red phosphor, and a first encapsulation material around the first light emitting chip and the first wavelength conversion phosphor; wherein the second light emitter is configured to emit fourth blue light having a peak wavelength in a range of 465 nm to 500 nm, wherein the second light emitter comprises: a second light emitting chip configured to emit third blue light having a peak wavelength in a range of 465 nm to 500 nm, a second wavelength conversion phosphor comprising at least one of the green phosphor and the red phosphor, and a second encapsulation material around the second light emitting chip and the second wavelength conversion phosphor; wherein the backlight unit further comprises: a light emitting package around the first light emitter and the second light emitter, and exposing a top surface of the first light emitter and a top surface of the second light emitter; and a wavelength conversion film configured to convert at least part of the second blue light and at least part of the fourth blue light into white light, wherein the light emitting module is in an edge portion of the light guide plate, and wherein a ratio of an intensity of the peak wavelength of the fourth blue light to an intensity of the peak wavelength of the second blue light is greater than or equal to 0.6.
2. The backlight unit of claim 1, wherein, in a range of first coordinates corresponding to CIE 1931 coordinates of the second blue light, an x-coordinate is 0.18 to 0.22, and a y-coordinate is 0.06 to 0.12, and wherein, in a range of second coordinates corresponding to CIE 1931 coordinates of the fourth blue light, an x-coordinate is 0.2 to 0.24, and a y-coordinate is 0.16 to 0.22.
3. The backlight unit of claim 1, wherein the wavelength conversion film is on a top surface of the light emitting package.
4. The backlight unit of claim 1, wherein the wavelength conversion film is on a side surface of the light guide plate.
5. The backlight unit of claim 1, wherein the wavelength conversion film is on a top surface of the light guide plate.
6. The backlight unit of claim 1, wherein the wavelength conversion film is separated from the top surface of the first light emitter and the top surface of the second light emitter.
7. The backlight unit of claim 6, wherein the peak wavelength of the second blue light in a range of 430 nm to 465 nm, and wherein the peak wavelength of the fourth blue light in a range of 465 nm to 500 nm.
8. The backlight unit of claim 1, wherein the wavelength conversion film has an integral structure in a path of the second blue light and a path of the fourth blue light.
9. A backlight unit comprising: a light guide plate; a reflector; and a light emitting module comprising a light emitting device and a substrate, wherein the light emitting device comprises a first light emitter and a second light emitter, wherein the first light emitter is configured to emit second blue light, wherein the first light emitter comprises: a first light emitting chip configured to emit first blue light having a peak wavelength in a range of 430 nm to 465 nm, at least one of a first phosphor configured to convert part of the first blue light into light having a peak wavelength in a range of 530 nm to 560 nm, and a second phosphor configured to convert part of the first blue light into light having a peak wavelength in a range of 600 nm to 650 nm, wherein the second light

emitter is configured to emit fourth blue light, wherein the second light emitter comprises: a second light emitting chip configured to emit third blue light having a peak wavelength in a range of about 465 nm to about 500 nm, and at least one of a third phosphor configured to convert part of the third blue light into light having a peak wavelength in a range of 530 nm to 560 nm, and a fourth phosphor configured to convert part of the third blue light into light having a peak wavelength in a range of 600 nm to 650 nm, and wherein a ratio of an intensity of a peak wavelength of the fourth blue light to an intensity of a peak wavelength of the second blue light is greater than or equal to 0.6.

10. The backlight unit of claim 9, wherein the first light emitter further comprises the first phosphor, wherein the second light emitter further comprises the third phosphor, and wherein each of the first phosphor and the third phosphor comprises at least one of β -SiAlON:Eu, (Ga,Gd,Y) $2\text{Al}_5\text{O}_{12}$:Ce, $\text{La}_3\text{Si}_6\text{Ni}$:Ce, Eu-doped (Sr,Ca,Ba) $\text{Si}_2\text{O}_2\text{N}_2$:Eu, and (Sr,Ba) Si_2O_4 :Eu.

11. The backlight unit of claim 9, wherein the first light emitter further comprises the second phosphor, and wherein the second light emitter further comprises the fourth phosphor, and each of the second phosphor and the fourth phosphor comprises at least one of (Sr,Ca)AlSiN $_3$:Eu, CaAlSiN $_3$:Eu, and $\text{K}_x\text{SiF}_y\text{:Mn}^{4+}$ ($2 \leq x \leq 3$, $4 \leq y \leq 7$).

12. The backlight unit of claim 9, wherein the second light emitter does not comprise the third phosphor.

13. The backlight unit of claim 9, wherein, in a range of first coordinates corresponding to CIE 1931 coordinates of the second blue light, an x-coordinate is 0.18 to 0.22 and a y-coordinate is 0.06 to 0.12.

14. The backlight unit of claim 9, wherein, in a range of second coordinates corresponding to CIE 1931 coordinates of the fourth blue light, an x-coordinate is 0.2 to 0.24 and a y-coordinate is 0.16 to 0.22.

15. The backlight unit of claim 9, further comprising a wavelength conversion film in a path of the second blue light and a path of the fourth blue light, the wavelength conversion film being configured to: convert at least part of the second blue light into first white light, and convert at least part of the fourth blue light into second white light, wherein the wavelength conversion film comprises: a first quantum dot configured to convert part of each of the second blue light and the fourth blue light into light having a peak wavelength in a range of 510 nm to 550 nm; and a second quantum dot configured to convert part of each of the second blue light and the fourth blue light into light having a peak wavelength in a range of 610 nm to 660 nm.

16. The backlight unit of claim 15, wherein each of the first quantum dot and the second quantum dot comprises at least one of InP/ZnS, InP/ZnSe, CdSe/CdS, CdSe/ZnS, PbS/ZnS, and InP/GaP/ZnS.

17. The backlight unit of claim 15, wherein, in a range of third coordinates corresponding to CIE 1931 coordinates of the first white light, an x-coordinate is 0.28 to 0.32 and a y-coordinate is 0.29 to 0.33, and wherein in a range of fourth coordinates corresponding to CIE 1931 coordinates of the second white light, an x-coordinate is 0.28 to 0.32 and a y-coordinate is 0.29 to 0.33.

18. A backlight unit comprising: a light guide plate; a reflector; and a light emitting module comprising a light emitting device and a substrate, wherein the light emitting device comprises a first light emitter and a second light emitter, wherein the first light emitter is configured to emit second blue light, wherein the first light emitter comprises: a first light emitting chip configured to emit first blue light having a peak wavelength in a range of 430 nm to 465 nm, at least one of a first phosphor configured to convert part of the first blue light into light having a peak wavelength in a range of 530 nm to 560 nm, and a second phosphor configured to convert part of the first blue light into light having a peak wavelength in a range of 600 nm to 650 nm, wherein the second light emitter is configured to emit fourth blue light, wherein the second light emitter comprises: a second light emitting chip configured to emit third blue light having a peak wavelength in a range of about 465 nm to about 500 nm, and at least one of a third phosphor configured to convert part of the third

blue light into light having a peak wavelength in a range of about 530 nm to about 560 nm, and a fourth phosphor configured to convert part of the third blue light into light having a peak wavelength in a range of about 600 nm to about 650 nm, wherein the backlight unit further comprises: a light emitting package around the first light emitter and the second light emitter, and exposing a top surface of the first light emitter and a top surface of the second light emitter; and a wavelength conversion film in a path of the second blue light and a path of the fourth blue light, the wavelength conversion film being configured to: convert at least part of the second blue light into first white light, and convert at least part of the fourth blue light into second white light, wherein the light emitting module is in an edge portion of the light guide plate, and wherein a ratio of an intensity of the peak wavelength of the fourth blue light to an intensity of the peak wavelength of the second blue light is greater than or equal to 0.6.

19. The backlight unit of claim 18, further comprising a plurality of first light emitters, wherein the plurality of first light emitters comprise the first light emitter.

20. The backlight unit of claim 18, wherein an equivalent melanopic lux (EML) of the second white light is greater than an EML of the first white light.
