

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276561

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

KANG; In Keun

AUTOMOTIVE THERMAL MANAGEMENT FLUID MODULE

Abstract

One embodiment relates to an automotive thermal management fluid module using a circulating fluid, such as a refrigerant or coolant, the module comprising: a manifold plate having a plurality of fluid passages formed therein; and a thermal interference avoidance unit that is coupled to the manifold plate, wherein fluid passages having a relatively high or low temperature from among the fluid passages are formed separately other fluid passages.

Inventors:	KANG; In Keun (Daejeon, KR)
Applicant:	HANON SYSTEMS (Daejeon, KR)
Family ID:	91379613
Appl. No.:	18/858561
Filed (or PCT Filed):	September 13, 2023
PCT No.:	PCT/KR2023/013728

Foreign Application Priority Data

KR	10-2022-0170502	Dec. 08, 2022
----	-----------------	---------------

Publication Classification

Int. Cl.: B60H1/32 (20060101); F28D21/00 (20060101)

U.S. Cl.:

CPC B60H1/3229 (20130101); F28D21/00 (20130101); B60H2001/325 (20130101); B60H2001/3257 (20130101); F28D2021/0082 (20130101)

Background/Summary

TECHNICAL FIELD

[0001] The present invention relates to an automotive thermal management fluid module, and more specifically, to an automotive thermal management fluid module that modularizes a heat exchanger and valve components into one.

BACKGROUND ART

[0002] Under the trend of environmentally friendly industrial development and development of energy sources that replace fossil fuels, the most notable fields in the automobile industry recently are electric vehicles and hybrid electric vehicles. An electric vehicle and a hybrid electric vehicle are provided with a battery to provide a driving force, and the battery is used not only for traveling but also for cooling and heating.

[0003] In vehicles that provide the driving force using the battery, when the battery is used as a heat source for cooling and heating, it means that a traveling distance is reduced accordingly, and to overcome the above problem, methods of applying a thermal management system widely used in household heating and cooling devices to vehicles have been proposed.

[0004] For reference, the thermal management system refers to absorbing low-temperature heat and transferring the absorbed heat to high temperature. As an example, the thermal management system has a cycle in which a liquid fluid evaporates in an evaporator, takes heat from the surroundings to become a gas, and then discharges heat back to the surroundings by a condenser to be liquefied. When the thermal management system is applied to electric vehicles or hybrid electric vehicles, there is an advantage that it is possible to secure a heat source that is lack in conventional general air conditioners.

[0005] Currently, a modularization configuration of the thermal management system for an electric vehicle is a partial modularization method, and important parts (a valve, an accumulator, a chiller, a condenser, an internal heat exchanger, a sensor, etc.) are connected by pipes. In the process of modularizing the thermal management system for a vehicle, there is a problem that thermal management performance is degraded due to thermal interference between a high-temperature fluid and a low-temperature fluid.

DISCLOSURE

Technical Problem

[0006] One embodiment of the present invention is directed to providing an automotive management fluid module having a structure that can minimize thermal interference between a high-temperature fluid and a low-temperature fluid by arranging inlets and outlets of a heat exchanger through which a high-temperature fluid flows and a heat exchanger through which a low-temperature fluid flows to be maximally spaced apart, thereby preventing degradation of thermal management performance.

[0007] In addition, one embodiment of the present invention is directed to providing an automotive management fluid module having a structure that can minimize pressure loss so that a flow path through which a low-temperature and low-pressure fluid flows has a greater flow cross-sectional area than another flow path in a cooling mode.

[0008] In addition, one embodiment of the present invention is directed to providing an automotive management fluid module having a structure that can accurately sense a state of a fluid discharged from a chiller by arranging a PT sensor for measuring a temperature and pressure of the fluid (refrigerant) on a flow path at an outlet side of the chiller (second heat exchanger) among heat exchangers.

Technical Solution

[0009] An automotive thermal management fluid module according to one embodiment of the

present invention may include a manifold plate having a flow path through which refrigerant flows formed therein, and a heat exchanger which is coupled to one surface of the manifold plate, in which the refrigerant and coolant exchange heat while flowing, and which has a refrigerant inlet and a refrigerant outlet through which the refrigerant is introduced and discharged, and the refrigerant inlet and the refrigerant outlet of the heat exchanger are disposed at one end or the other end of the manifold plate, and the refrigerant inlet is disposed above the refrigerant outlet.

[0010] The heat exchanger may include a first heat exchanger which is coupled to one surface of the manifold plate, in which high-temperature refrigerant and coolant exchange heat while flowing, and which is provided with a first refrigerant inlet and a first refrigerant outlet through which the high-temperature refrigerant is introduced and discharged, and a second heat exchanger which is coupled to one surface of the manifold plate, in which low-temperature refrigerant and coolant exchange heat while flowing, and which is provided with a second refrigerant inlet and a second refrigerant outlet through which the refrigerant is introduced and discharged, and the first refrigerant inlet and the first refrigerant outlet may be disposed to be spaced apart from the second refrigerant inlet and the second refrigerant outlet.

[0011] The first refrigerant inlet and the first refrigerant outlet may be disposed at one end of the manifold plate, and the second refrigerant inlet and the second refrigerant outlet may be disposed at the other end of the manifold plate.

[0012] The first heat exchanger may be provided with a first coolant inlet and a first coolant outlet through which the coolant is introduced and discharged, and the second heat exchanger may be provided with a second coolant inlet and a second coolant outlet through which the coolant is introduced and discharged.

[0013] The first coolant inlet and the first coolant outlet may be disposed adjacent to the second coolant inlet and the second coolant outlet.

[0014] The first coolant inlet and the first coolant outlet, and the second coolant inlet and the second coolant outlet may be disposed between the first refrigerant inlet and the first refrigerant outlet, and the second refrigerant inlet and the second refrigerant outlet.

[0015] A distance between the first coolant inlet and the first coolant outlet, and the second coolant inlet and the second coolant outlet may be greater than a distance between the first refrigerant inlet and the first refrigerant outlet, and the second refrigerant inlet and the second refrigerant outlet.

[0016] The manifold plate at the locations at which the first coolant inlet, the first coolant outlet, the second coolant inlet, and the second coolant outlet are disposed may be formed to be open.

[0017] A flow path through which the refrigerant flows into the second heat exchanger and a flow path through which refrigerant discharged from the second heat exchanger may have a large flow cross-sectional area than other flow paths.

[0018] A sensor configured to measure a temperature and pressure of the refrigerant may be disposed on a flow path through which refrigerant discharged from the refrigerant outlet flows.

[0019] An inlet hole of the refrigerant inlet, an outlet hole of the refrigerant outlet, and a sensor insertion hole into which the sensor is inserted, which are formed in the manifold plate, may be disposed in a direction of gravity.

[0020] The sensor may be coupled to the same one surface of the manifold plate as the heat exchanger.

[0021] The heat exchanger may be coupled to the one surface of the manifold plate, and the sensor may be coupled to a side surface of the manifold plate.

[0022] The first heat exchanger may be a water-cooled condenser, and the second heat exchanger may be a chiller.

Advantageous Effects

[0023] According to one embodiment of the present invention, it is possible to minimize the thermal interference between the high-temperature fluid and the low-temperature fluid by arranging the inlets and outlets of the heat exchanger through which the high-temperature fluid flows and the

heat exchanger through which the low-temperature fluid flows to be maximally spaced apart, thereby preventing degradation of thermal management performance.

[0024] In addition, according to one embodiment of the present invention, it is possible to minimize pressure loss so that the flow path through which the low-temperature and low-pressure fluid flows has a greater flow cross-sectional area than another flow path in the cooling mode.

[0025] In addition, according to one embodiment of the present invention, it is possible to accurately sense the state of the fluid discharged from the chiller by arranging the sensor for measuring the temperature and pressure of the fluid (refrigerant) on the flow path at the outlet side of the chiller (second heat exchanger) among the heat exchangers.

Description

DESCRIPTION OF DRAWINGS

[0026] FIG. 1 is a perspective view showing a front surface of an automotive thermal management fluid module according to one embodiment of the present invention.

[0027] FIG. 2 is a view showing a rear surface of the automotive thermal management fluid module according to one embodiment of the present invention.

[0028] FIG. 3 is a view showing a high-temperature flow path and a low-temperature flow path of the automotive thermal management fluid module according to one embodiment of the present invention.

[0029] FIG. 4 is a view showing that a sensor of the automotive thermal management fluid module according to one embodiment of the present invention is installed on a manifold plate.

[0030] FIG. 5 is a view showing another installation example of the sensor shown in FIG. 4.

MODE FOR INVENTION

[0031] Since the present invention may have various changes and various embodiments, specific embodiments are shown in the accompanying drawings and described in detail. However, it should be understood that it is not intended to limit specific embodiments and includes all modifications, equivalents, and substitutes included in the spirit and technical scope of the present invention. In describing the present invention, when it is determined that the detailed description of a related known technology may unnecessarily obscure the gist of the present invention, detailed description thereof will be omitted.

[0032] Terms such as first and second may be used to describe various components, but the components should not be limited by the terms. The terms are used only for the purpose of distinguishing one component from another.

[0033] The terms used in the present application are only used to describe specific embodiments and are not intended to limit the present invention. The singular includes the plural unless the context clearly dictates otherwise. In the application, it should be understood that terms such as “comprise” or “have” are intended to specify that a feature, a number, a step, an operation, a component, a part, or a combination thereof described in the specification is present, but do not preclude the possibility of the presence or addition of one or more other features, numbers, steps, operations, components, parts, or combinations thereof.

[0034] In addition, throughout the specification, when a certain component is described as being “connected” to another, this does not just mean that two or more components are directly connected and may mean that two or more components are indirectly connected through another component, are physically connected, and electrically connected, or are referred to as different names depending on positions or functions thereof but are integrated.

[0035] Hereinafter, one embodiment of an automotive thermal management fluid module according to the present invention will be described in detail with reference to the accompanying drawings, and in describing the present invention with reference to the accompanying drawings, the same or

corresponding components are denoted by the same reference numeral, and overlapping descriptions thereof will be omitted.

[0036] FIG. 1 is a perspective view showing a front surface of an automotive thermal management fluid module according to one embodiment of the present invention, FIG. 2 is a view showing a rear surface of the automotive thermal management fluid module according to one embodiment of the present invention, FIG. 3 is a view showing a high-temperature flow path and a low-temperature flow path of the automotive thermal management fluid module according to one embodiment of the present invention, and FIG. 4 is a view showing that a sensor of the automotive thermal management fluid module according to one embodiment of the present invention is installed on a manifold plate.

[0037] Therefore, as shown, the automotive thermal management fluid module according to one embodiment of the present invention may include a manifold plate **10** having a flow path through which refrigerant flows formed therein, and heat exchangers **20** and **60** which are coupled to one surface of the manifold plate **10**, in which the refrigerant and coolant exchange heat while flowing, and which have refrigerant inlets **21** and **61** and refrigerant outlets **22** and **62** through which the refrigerant is introduced and discharged, in which the refrigerant inlets **21** and **61** and the refrigerant outlets **22** and **62** of the heat exchangers **20** and **60** may be disposed at an end of one side or the other side of the manifold plate **10**, and the refrigerant inlets **21** and **61** may be disposed above the refrigerant outlets **22** and **62**.

[0038] The manifold plate **10** has a substantially plate shape that has a fluid path formed therein and has a predetermined thickness. As described above, the manifold plate **10** may be modularized by coupling a first heat exchanger **20** and a second heat exchanger **60** that are heat exchange devices of the thermal management system, expansion valves **30** and **70**, and direction change valves **40** and **50**, thereby reducing the number of processes for manufacturing a product and reduce the number of processes in an assembly line of a vehicle. In addition, the manifold plate **10** may perform functions of piping, fitting, and housing at the same time, thereby saving cost and improving workability.

[0039] The manifold plate **10** may include an assembly composed of a bottom plate **11** and a top plate **12** and may be manufactured in a coupling manner using brazing, structural adhesives, gaskets, etc. In addition, a material of the manifold plate **10** may be applied variously according to a manufacturing method or purposes and functions, such as aluminum, thermoplastic, and stainless steel.

[0040] The bottom plate **11** is formed in a plate shape, and the top plate **12** is coupled to protrude a predetermined thickness from one surface of the bottom plate **11**, thereby forming a fluid flow path between the bottom plate **11** and the top plate **12**.

[0041] Referring to FIG. 2, a fluid introduction port **14** through which a high-temperature and high-pressure gaseous fluid discharged from a compressor or an internal condenser is provided on a rear surface of the manifold plate **10**. In addition, various fluid ports for the introduction and discharge of the fluid may be provided on the rear surface of the manifold plate **10**. In the present embodiment, an external heat exchanger discharge port **16** through which refrigerant is discharged to an external heat exchanger (not shown) is provided.

[0042] Referring back to FIG. 1, the manifold plate **10** is coupled to the first heat exchanger **20** and the second heat exchanger **60** as heat exchange devices. The refrigerant and the coolant may exchange heat while passing through the first heat exchanger **20** and the second heat exchanger **60**, respectively.

[0043] In the present embodiment, a water-cooled condenser may be used as the first heat exchanger **20**, and a chiller may be used as the second heat exchanger **60**. The water-cooled condenser serves to condense a high-temperature and high-pressure gaseous fluid (refrigerant) discharged from the compressor or the internal condenser into a high-pressure liquid by exchanging heat with an external heat source. The chiller is a device in which a low-temperature and low-

pressure fluid is supplied and exchanges heat with coolant flowing in a coolant circulation line (not shown), and the cold coolant exchanging heat in the chiller may exchange heat with a battery by circulating in the coolant circulation line.

[0044] The first heat exchanger **20** is provided with a refrigerant port through which refrigerant is introduced and discharged. The refrigerant port includes a first refrigerant inlet **21** and a first refrigerant outlet **22** provided at an upper end and lower end of the first heat exchanger **20**, respectively. The first refrigerant inlet **21** is a part through which the refrigerant passing through the first expansion valve **30** is introduced, and the first refrigerant outlet **22** is a part through which the refrigerant exchanging heat in the first heat exchanger **20** is discharged. The first refrigerant inlet **21** and the first refrigerant outlet **22** may be formed in the form of a hole at the upper and lower ends of the first heat exchanger **20**, respectively.

[0045] In this case, considering thermal interference, the first refrigerant inlet **21** may be formed at one side close to the first expansion valve **30**, and the first refrigerant outlet **22** may be formed at the other side far from the first expansion valve **30**. More specifically, the first refrigerant inlet **21** may be disposed closer to the first expansion valve **30** than the first refrigerant outlet **22** is. For example, a distance from the first expansion valve **30** to the first refrigerant inlet **21** may be smaller than a distance from the first expansion valve **30** to the first refrigerant outlet **22**.

[0046] In addition, the first heat exchanger **20** is provided with a coolant port through which coolant is introduced and discharged. The coolant port includes a first coolant inlet **23** and a first coolant outlet **24** provided at the lower end and upper end of the first heat exchanger **20**, respectively. The first coolant inlet **23** is a part through which coolant is introduced, and the first coolant outlet **24** is a part through which coolant exchanging heat with the refrigerant is discharged. The coolant exchanges heat with the refrigerant while flowing in a direction (bottom.fwdarw.top) opposite to the refrigerant.

[0047] Since the above-described refrigerant port and coolant port are disposed separately, it is possible to improve the assemblability of refrigerant pipes and coolant pipes.

[0048] The first expansion valve **30** serves to control whether to expand the refrigerant flowing into the first heat exchanger **20**. The first expansion valve **30** may be disposed above the first heat exchanger **20** and may expand or pass the refrigerant introduced through the fluid introduction port **14**. The refrigerant introduced through the first expansion valve **30** may exchange heat while passing through the first heat exchanger **20** or move to an external heat exchanger.

[0049] The refrigerant discharged through the first refrigerant outlet **22** of the first heat exchanger **20** flows into the first direction change valve **40**. The first direction change valve **40** serves to control a direction of the refrigerant discharged from the first heat exchanger **20**. The refrigerant flowing into the first direction change valve **40** may move to the external heat exchanger. In this case, the refrigerant may move to the external heat exchanger through the external heat exchanger discharge port **16**. In addition, the refrigerant flowing into the first expansion valve **30** may move to the second direction change valve **50** and then to an evaporator (not shown) in a dehumidification mode.

[0050] The second heat exchanger **60** receives the low-temperature and low-pressure refrigerant and exchanges heat with the coolant moving from the coolant circulation line (not shown). The cold coolant exchanging heat in the second heat exchanger **60** may exchange heat with the battery by circulating in the coolant circulation line. The refrigerant exchanging heat with the external heat exchanger flows into the second expansion valve **70**, and the refrigerant expanded in the second expansion valve **70** flows into the second heat exchanger **60**. The refrigerant exchanging heat in the second heat exchanger **60** is discharged through the lower end thereof and flows into an accumulator (not shown).

[0051] To this end, the second heat exchanger **60** is provided with a refrigerant port through which refrigerant is introduced and discharged. The refrigerant port includes a second refrigerant inlet **61** and a second refrigerant outlet **62** provided at an upper end and lower end of the second heat

exchanger **60**, respectively. The second refrigerant inlet **61** is a part through which the refrigerant is introduced, and the second refrigerant outlet **62** is a part through which the refrigerant exchanging heat in the second heat exchanger **60** is discharged. The second refrigerant inlet **61** and the second refrigerant outlet **62** may be formed in the form of a hole at the upper and lower ends of the second heat exchanger **60**, respectively.

[0052] In this case, considering thermal interference, the second refrigerant inlet **61** of the second heat exchanger **60** may be formed at one side close to the second expansion valve **70**, and the second refrigerant outlet **62** may be formed at the other side far from the second expansion valve **70**. More specifically, the second refrigerant inlet **61** may be disposed closer to the second expansion valve **70** than the second refrigerant outlet **62** is. For example, a distance from the second expansion valve **70** to the second refrigerant inlet **61** may be smaller than a distance from the second expansion valve **70** to the second refrigerant outlet **62**.

[0053] Among the fluid flow paths formed on the manifold plate **10** in FIG. **3**, a path marked by the dotted line may be a relatively high-temperature or low-temperature fluid flow path. A flow path through which the refrigerant discharged after exchanging heat in the first heat exchanger **20** flows into the first direction change valve **40** may be a high-temperature flow path **100**, and a flow path through which the refrigerant flows into the second heat exchanger **60** and a flow path through which the refrigerant exchanging heat in the second heat exchanger **60** is discharged may be a low-temperature flow path **102**.

[0054] Since the high-temperature flow path **100** and the low-temperature flow path **102** are fluid flow paths formed in one manifold plate **10**, when disposed adjacent to each other, thermal management performance may be degraded due to thermal interference therebetween. Therefore, in the present embodiment, to arrange the high-temperature flow path **100** and the low-temperature flow path **102** to be spaced apart, the refrigerant inlets **21** and **61** and the refrigerant outlets **22** and **62** of the first heat exchanger **20** and the second heat exchanger **60** are disposed to be maximally spaced apart.

[0055] More specifically, the refrigerant inlets **21** and **61** and the refrigerant outlets **22** and **62** are discharged in the first heat exchanger **20** and the second heat exchanger **60**, respectively, for heat exchange of refrigerant and disposed at locations as far away as possible to minimize thermal interference between the respective refrigerants flowing therethrough. As an example, the first refrigerant inlet **21** and the first refrigerant outlet **22** may be disposed at one end, that is, a right end of the manifold plate **10**, and the second refrigerant inlet **61** and the second refrigerant outlet **62** may be disposed at the other end, that is, a left end of the manifold plate **10**, thereby minimizing thermal interference.

[0056] In addition, the refrigerant inlets **21** and **61** may be disposed above the refrigerant outlets **22** and **62** so that the refrigerant may flow in a direction of gravity, that is, from the top to the bottom.

[0057] Meanwhile, the first heat exchanger **20** and the second heat exchanger **60** have a first coolant inlet **23** and a first coolant outlet **24**, and a second coolant inlet **63** and a second coolant outlet **64**, respectively, and the first coolant inlet **23** and the first coolant outlet **24**, and the second coolant inlet **63** and the second coolant outlet **64** may be disposed between the first refrigerant inlet **21** and the first refrigerant outlet **22**, and the second refrigerant inlet **61** and the second refrigerant outlet **62**. That is, as shown in the drawing, from the left, the second refrigerant inlet **61**, the second refrigerant outlet **62**, the second coolant inlet **63**, the second coolant outlet **64**, the first coolant inlet **23**, the first coolant outlet **24**, the first refrigerant inlet **21**, the first refrigerant outlet **22** may be disposed sequentially.

[0058] In the first heat exchanger **20** and the second heat exchanger **60**, the refrigerant flows along the fluid flow path formed in the manifold plate **10**, but the coolant flows through a separate pipe and thus is relatively unaffected by thermal interference. Therefore, the above pipe is configured to be disposed between the refrigerant inlets **21** and **61** and the refrigerant outlets **22** and **62** to minimize thermal interference.

[0059] The manifold plate **10** at the locations at which the first coolant inlet **23**, the first coolant outlet **24**, the second coolant inlet **63**, and the second coolant outlet **64** are disposed may be formed to be open to be connected to the pipe (not shown). That is, the first heat exchanger **20** and the second heat exchanger **60** may be coupled to a front surface of the manifold plate **10**, and the first coolant inlet **23** and the first coolant outlet **24**, and the second coolant inlet **63** and the second coolant outlet **64** may be provided on rear surfaces of the first heat exchanger **20** and the second heat exchanger **60**, respectively, and to avoid interference with the pipe connected at the rear of the manifold plate **10**, the manifold plate **10** may be formed to be open.

[0060] In addition, a distance **D1** between the first coolant inlet **23** and the first coolant outlet **24**, and the second coolant inlet **63** and the second coolant outlet **64** may be greater than a distance **D2** between the first refrigerant inlet **21** and the first refrigerant outlet **22**, and the second refrigerant inlet **61** and the second refrigerant outlet **62**. As described above, when the flow paths with a difference in fluid temperature is disposed to be spaced apart, it is possible to minimize thermal interference therebetween, thereby maximizing thermal management performance.

[0061] Meanwhile, the low-temperature flow path **102** through which the refrigerant flows into the second heat exchanger **60** and the low-temperature flow path **102** through which the refrigerant discharged from the second heat exchanger **60** flows may have a larger flow cross-sectional area than other flow paths (e.g., the high-temperature flow path **100**). This is intended to minimum low-pressure side pressure loss in the low-temperature flow path **102** by constituting the relatively low-temperature and low-pressure refrigerant, which has a relatively large flow cross-sectional area, because the above refrigerant is sensitive to flow resistance such as the size of the cross-sectional area.

[0062] Referring to FIG. **4**, a sensor **80** for measuring a temperature and pressure of the refrigerant may be disposed on the low-temperature flow path **102** through which the refrigerant discharged from the second heat exchanger **60** flows. This is intended to sense an accurate state (temperature, pressure) of the refrigerant discharged from the second heat exchanger **60** and improve the controllability of a chiller expansion valve (not shown).

[0063] The sensor **80** may be mounted on the top plate **12** of the manifold plate **10**, that is, on the same one surface as the second heat exchanger **60** to sense a refrigerant state.

[0064] FIG. **5** is a view showing another installation example of the sensor shown in FIG. **4**.

[0065] Referring to FIG. **5**, the second heat exchanger **60** may be coupled to the one surface of the manifold plate **10**, and the sensor **80** may be coupled to a side surface of the manifold plate **10**. That is, in the above-described embodiment, the sensor **80** has been described as being coupled to the same one surface as the second heat exchanger **60**, but as in the present embodiment, may also be coupled to a different one surface from the second heat exchanger **60**.

[0066] In addition, an inlet hole **84** of the second refrigerant inlet **61**, an outlet hole **86** of the second refrigerant outlet **62**, and a sensor insertion hole **82** into which the sensor **80** is inserted, which are formed in the manifold plate **10**, may be disposed in the direction of gravity. The inlet hole **84** and the outlet hole **86** are parts formed on the second refrigerant inlet **61** and the second refrigerant outlet **62**, and the sensor insertion hole **82** is a part formed on the manifold plate **10** to couple the sensor **80**.

[0067] In this drawing, although the inlet hole **84** and the outlet hole **86** are not formed to overlap the sensor **80** in a vertical direction, the inlet hole **84** and the outlet hole **86** may be formed to overlap the sensor **80** in the vertical direction.

[0068] Although the above description has been made with reference to specific embodiments of the present invention, those skilled in the art will be able to understand that the present invention may be variously modified and changed without departing from the spirit and scope of the present invention described in the appended claims.

TABLE-US-00001 [DESCRIPTION OF REFERENCE NUMERALS] 10: manifold plate 11: bottom plate 12: top plate 14: fluid introduction port 16: external heat exchanger discharge 20: first

heat exchanger port 21: first refrigerant inlet 22: first refrigerant outlet 23: first coolant inlet 24: first coolant outlet 30: first expansion valve 40: first direction change valve 50: second direction change valve 60: second heat exchanger 61: second refrigerant inlet 62: second refrigerant outlet 63: second coolant inlet 64: second coolant outlet 70: second expansion valve 80: sensor 82: sensor insertion hole 84: inlet hole 86: outlet hole 100: high-temperature flow path 102: low-temperature flow path

Claims

1. An automotive thermal management fluid module comprising: a manifold plate having a flow path through which refrigerant flows formed therein; and a heat exchanger which is coupled to one surface of the manifold plate, in which the refrigerant and coolant exchange heat while flowing, and which has a refrigerant inlet and a refrigerant outlet through which the refrigerant is introduced and discharged, and the refrigerant inlet and the refrigerant outlet of the heat exchanger are disposed at one end or the other end of the manifold plate, and the refrigerant inlet is disposed above the refrigerant outlet.
2. The automotive thermal management fluid module of claim 1, wherein the heat exchanger includes: a first heat exchanger which is coupled to one surface of the manifold plate, in which high-temperature refrigerant and coolant exchange heat while flowing, and which is provided with a first refrigerant inlet and a first refrigerant outlet through which the high-temperature refrigerant is introduced and discharged; and a second heat exchanger which is coupled to one surface of the manifold plate, in which low-temperature refrigerant and coolant exchange heat while flowing, and which is provided with a second refrigerant inlet and a second refrigerant outlet through which the refrigerant is introduced and discharged, and the first refrigerant inlet and the first refrigerant outlet are disposed to be spaced apart from the second refrigerant inlet and the second refrigerant outlet.
3. The automotive thermal management fluid module of claim 2, wherein the first refrigerant inlet and the first refrigerant outlet are disposed at one end of the manifold plate, and the second refrigerant inlet and the second refrigerant outlet are disposed at the other end of the manifold plate.
4. The automotive thermal management fluid module of claim 2, wherein the first heat exchanger is provided with a first coolant inlet and a first coolant outlet through which the coolant is introduced and discharged, and the second heat exchanger is provided with a second coolant inlet and a second coolant outlet through which the coolant is introduced and discharged.
5. The automotive thermal management fluid module of claim 4, wherein the first coolant inlet and the first coolant outlet are disposed adjacent to the second coolant inlet and the second coolant outlet.
6. The automotive thermal management fluid module of claim 4, wherein the first coolant inlet and the first coolant outlet, and the second coolant inlet and the second coolant outlet are disposed between the first refrigerant inlet and the first refrigerant outlet, and the second refrigerant inlet and the second refrigerant outlet.
7. The automotive thermal management fluid module of claim 4, wherein a distance between the first coolant inlet and the first coolant outlet, and the second coolant inlet and the second coolant outlet is greater than a distance between the first refrigerant inlet and the first refrigerant outlet, and the second refrigerant inlet and the second refrigerant outlet.
8. The automotive thermal management fluid module of claim 4, wherein the manifold plate at the locations at which the first coolant inlet, the first coolant outlet, the second coolant inlet, and the second coolant outlet are disposed is formed to be open.
9. The automotive thermal management fluid module of claim 2, wherein a flow path through which the refrigerant flows into the second heat exchanger and a flow path through which refrigerant discharged from the second heat exchanger have a large flow cross-sectional area than

other flow paths.

10. The automotive thermal management fluid module of claim 1, wherein a sensor configured to measure a temperature and pressure of the refrigerant is disposed on a flow path through which refrigerant discharged from the refrigerant outlet flows.

11. The automotive thermal management fluid module of claim 10, wherein an inlet hole of the refrigerant inlet, an outlet hole of the refrigerant outlet, and a sensor insertion hole into which the sensor is inserted, which are formed in the manifold plate, are disposed in a direction of gravity.

12. The automotive thermal management fluid module of claim 10, wherein the sensor is coupled to the same one surface of the manifold plate as the heat exchanger.

13. The automotive thermal management fluid module of claim 10, wherein the heat exchanger is coupled to the one surface of the manifold plate, and the sensor is coupled to a side surface of the manifold plate.

14. The automotive thermal management fluid module of claim 2, wherein the first heat exchanger is a water-cooled condenser, and the second heat exchanger is a chiller.
