

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280104

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

SEO; Gaewon

ELECTRONIC APPARATUS FOR TRANSMITTING IMAGE DATA AND CONTROLLING METHOD THEREOF

Abstract

An electronic apparatus includes: a first interface configured to be connected to a first small form-factor pluggable (SFP) module provided at an end of an optical cable; a second interface configured to be connected to a second SFP module provided at a second end of the optical cable; memory storing instructions; and one or more processors configured to execute the instructions to: identify a driving voltage corresponding to image data; change a level of the driving voltage of the image data to generate test data; and based on the test data transmitted through the first interface being received by the second interface, identify whether the first SFP module, the second SFP module, or the optical cable are progressively defective based on the received test data and the image data.

Inventors: SEO; Gaewon (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 91897236

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 19/212005

Filed: May 19, 2025

Foreign Application Priority Data

KR 10-2023-0005404

Jan. 13, 2023

Related U.S. Application Data

parent WO continuation PCT/KR2023/019364 20231128 PENDING child US 19212005

Publication Classification

Int. Cl.: H04N17/00 (20060101); G02B6/42 (20060101); H04N7/22 (20060101)

U.S. Cl.:

CPC H04N17/00 (20130101); H04N7/22 (20130101); G02B6/4278 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) [0001] This application is a continuation of International Application No. PCT/KR2023/019364, filed on Nov. 28, 2023, in the Korean Intellectual Property Receiving Office, which is based on and claims priority to Korean Patent Application No. 10-2023-0005404, filed on Jan. 13, 2023, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

1. Field

[0002] The disclosure relates to an electronic apparatus for transmitting image data and a controlling method thereof, and more particularly, to an electronic apparatus for transmitting image data to a display apparatus using an optical cable connected through an small form-factor pluggable (SFP) module and a controlling method thereof.

2. Description of Related Art

[0003] The development of display technology has diversified the screen sizes of display apparatuses. In the past, it was possible to produce display apparatuses with only a limited size, but in recent years, it has become possible to produce display apparatuses with large screens, freeing them from the limitations of display sizes. As a result, the use of large-screen display apparatuses is increasing. For example, a digital signage billboard may include a large-screen display apparatus that is installed in places with a lot of floating population, such as subway stations and bus stops, and then display advertisements through the display apparatus.

[0004] A large-screen display apparatus may receive image data from a separate source apparatus. In this case, the source apparatus and the display apparatus may be connected through an optical cable including an SFP module, and the source apparatus may transmit image data to the display apparatus through the optical cable. Accordingly, when the optical cable and the SFP module are defective, some data may be missing from the image data transmitted by the source apparatus, and furthermore, the image data itself may not be transmitted. Defects in such an optical cable and SFP module may be caused by long-term use of the optical cable and SFP module in the course of use.

SUMMARY

[0005] Aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

[0006] According to an aspect of the disclosure, an electronic apparatus may include: a first interface configured to be connected to a first small form-factor pluggable (SFP) module provided at an end of an optical cable; a second interface configured to be connected to a second SFP module provided at a second end of the optical cable; memory storing instructions; and one or more processors configured to execute the instructions to: identify a driving voltage corresponding to image data; change a level of the driving voltage of the image data to generate test data; and based on the test data transmitted through the first interface being received by the second interface, identify whether the first SFP module, the second SFP module, or the optical cable are progressively defective based on the received test data and the image data.

[0007] The one or more processors may be further configured to execute the instructions to: generate verification data based on the image data; generate the test data based on the verification data and the changed level of the driving voltage of the image data; and extract the verification data from the received test data, and identify whether the first SFP module, the second SFP module, or the optical cable are progressively defective based on the extracted verification data.

[0008] The one or more processors may be further configured to execute the instructions to change the level of the driving voltage of the image data based on a pre-emphasis method.

[0009] The one or more processors may be further configured to execute the instructions to change the level of the driving voltage of the image data based on a de-emphasis method.

[0010] The one or more processors may be further configured to: change a level of a driving voltage of the first SFP module and the second SFP module and apply the changed driving voltage to the first SFP module and the second SFP module, transmit the test data through the first interface, and receive the test data through the second interface in a state in which the changed driving voltage is being applied to the first SFP module and the second SFP module.

[0011] The one or more processors may be further configured to: transmit the image data through the first interface; based on the image data transmitted through the first interface being received by the second interface, identify whether the optical cable is defective based on the image data; and based on the optical cable being identified as normal, generate the test data.

[0012] The one or more processors may be further configured to generate the test data by reducing the level of the driving voltage of the image data to a preset voltage level.

[0013] The one or more processors may be further configured to generate the test data by changing the level of the driving voltage of the image data to a voltage level within a preset range.

[0014] According to an aspect of the disclosure, a controlling method of an electronic apparatus may include: identifying a driving voltage corresponding to image data; generating test data by changing a level of the driving voltage of the image data; transmitting the test data through a first interface connected to a first small form-factor pluggable (SFP) module provided at a first end of an optical cable; receiving the test data through a second interface connected to a second SFP module provided at a second end of the optical cable; and identifying whether the first SFP module, the second SFP module, or the optical cable are progressively defective based on the received test data and the image data.

[0015] The generating may further include: generating verification data based on the image data; and generating the test data based on the verification data and the changed level of the driving voltage of the image data, where the identifying whether the first SFP module, the second SFP module, or the optical cable are progressively defective is based on the verification data.

[0016] The generating may further include changing the level of the driving voltage of the image data based on a pre-emphasis method.

[0017] The generating may further include changing the level of the driving voltage of the image data based on a de-emphasis method.

[0018] The transmitting may include: changing a level of a driving voltage of the first SFP module and the second SFP module and applying the changed driving voltage to the first SFP module and the second SFP module, and transmitting the test data through the first interface, where the receiving includes receiving the test data through the second interface in a state in which the changed driving voltage is being applied to the first SFP module and the second SFP module.

[0019] The method may further include: transmitting the image data through the first interface; receiving the image data transmitted by the first interface through the second interface; and identifying whether the optical cable is defective based on the image data, where the generating includes, based on the optical cable being identified as normal, generating the test data.

[0020] According to an aspect of the disclosure, a non-transitory computer-readable recording medium storing a computer instruction that, when executed by one or more processors of an electronic apparatus, may cause the electronic apparatus to: identify driving voltage corresponding

to image data; change a level of the driving voltage of the image data to generate test data; transmit the test data through a first interface connected to a first small form-factor pluggable (SFP) module provided at a first end of an optical cable; receive the test data through a second interface connected to a second SFP module provided at a second end of the optical cable; and identify whether the first SFP module, the second SFP module, or the optical cable are progressively defective based on the received test data and the image data.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] The above and other aspects, features, and advantages of certain embodiments of the present disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

[0022] FIG. 1 is an example view illustrating an electronic apparatus and a display apparatus that receives image data from the electronic apparatus according to an embodiment;

[0023] FIG. 2 is a schematic view illustrating an electronic apparatus according to an embodiment;

[0024] FIG. 3 is an example view illustrating a connection state between an electronic apparatus and an optical cable according to an embodiment;

[0025] FIG. 4 is an example view illustrating test data according to an embodiment;

[0026] FIGS. 5A, 5B and 5C are example views illustrating test data according to one or more embodiments; and

[0027] FIG. 6 is an example view schematically illustrating a controlling method of an electronic apparatus according to an embodiment.

DETAILED DESCRIPTION

[0028] The embodiments of the present disclosure may be modified in various ways, and may have various embodiments, so specific embodiments are illustrated in the drawings and described in detail in the detailed description. However, it is to be understood that the disclosure is not limited to specific example embodiments, but include all modifications, equivalents, and/or alternatives according to example embodiments of the disclosure. Throughout the description of the accompanying drawings, similar components may be denoted by similar reference numerals.

[0029] In describing the disclosure, when it is decided that a detailed description for the known functions or configurations related to the disclosure may unnecessarily obscure the gist of the disclosure, the detailed description therefor will be omitted.

[0030] In addition, the following example embodiments may be modified in several different forms, and the scope of the technical spirit of the disclosure is not limited to the following example embodiments. Rather, these example embodiments make the disclosure thorough and complete, and are provided to completely transfer the spirit of the disclosure to those skilled in the art.

[0031] Terms used in the disclosure are used only to describe specific example embodiments rather than limiting the scope of the disclosure. Singular forms are intended to include plural forms unless the context clearly indicates otherwise.

[0032] In the disclosure, the expressions “comprise”, “may comprise”, “have”, “may have”, “include” or “may include” used herein indicate existence of corresponding features (e.g., elements such as numeric values, functions, operations, or components), but do not exclude presence of additional features.

[0033] As used herein, expressions such as “at least one of,” when preceding a list of elements, modify the entire list of elements and do not modify the individual elements of the list. For example, the expression, “at least one of a, b, and c,” should be understood as including only a, only b, only c, both a and b, both a and c, both b and c, or all of a, b, and c.

[0034] Expressions “first”, “second”, “1st”, “2nd,” or the like, used in the disclosure may indicate

various components regardless of sequence and/or importance of the components, will be used only in order to distinguish one component from the other components, and do not limit the corresponding components.

[0035] When it is described that an element (e.g., a first element) is referred to as being “(operatively or communicatively) coupled with/to” or “connected to” another element (e.g., a second element), it should be understood that it may be directly coupled with/to or connected to the other element, or they may be coupled with/to or connected to each other through an intervening element (e.g., a third element).

[0036] On the other hand, when an element (e.g., a first element) is referred to as being “directly coupled with/to” or “directly connected to” another element (e.g., a second element), it should be understood that there is no intervening element (e.g., a third element) in-between.

[0037] An expression “~configured (or set) to” used in the disclosure may be replaced by an expression, for example, “suitable for,” “having the capacity to,” “~designed to,” “~adapted to,” “~made to,” or “~capable of” depending on a situation. A term “~configured (or set) to” may not necessarily mean “specifically designed to” in hardware.

[0038] Instead, an expression “~an apparatus configured to” may mean that an apparatus “is capable of” together with other apparatuses or components. For example, a “processor configured (or set) to perform A, B, and C” may mean a dedicated processor (e.g., an embedded processor) for performing the corresponding operations or a generic-purpose processor (e.g., a central processing unit (CPU) or an application processor) that may perform the corresponding operations by executing one or more software programs stored in a memory apparatus.

[0039] In the disclosure, a ‘module’ or a ‘unit’ may perform at least one function or operation, and be implemented as hardware or software or be implemented as a combination of hardware and software. In addition, a plurality of ‘modules’ or a plurality of ‘units’ may be integrated into at least one module and be implemented as at least one processor except for a ‘module’ or a ‘unit’ that needs to be implemented as specific hardware.

[0040] Meanwhile, various elements and regions in the drawings are schematically drawn in the drawings. Therefore, the technical concept of the disclosure is not limited by a relative size or spacing drawn in the accompanying drawings.

[0041] Hereinafter, one or more embodiments according to the present disclosure will be described in detail with reference to the accompanying drawings so that a person with ordinary knowledge in the technical field to which the present disclosure belongs can easily implement the present disclosure.

[0042] FIG. 1 is an example view illustrating an electronic apparatus and a display apparatus that receives image data from the electronic apparatus according to an embodiment.

[0043] An electronic apparatus **100** of the present disclosure transmits image data to a display apparatus **300**. Upon receiving the image data from the electronic apparatus **100**, the display apparatus **300** may display a screen corresponding to the image data. According to an embodiment, the electronic apparatus **100** may be implemented as a source apparatus, a set-top box, or the like.

[0044] Referring to FIG. 1, the electronic apparatus **100** and the display apparatus **300** may be connected through an optical cable **220** to transmit and receive image data. Specifically, the electronic apparatus **100** may be connected to one end of the optical cable **220** through SFP modules **210**, **230**. In this case, the display apparatus **300** may be connected to the other end of the optical cable **220** through another SFP module. Accordingly, the electronic apparatus **100** and the display apparatus **300** may transmit and receive various data including image data through the optical cable **220**.

[0045] Meanwhile, since the electronic apparatus **100** and the display apparatus **300** are connected through the SFP modules **210**, **230** and the optical cable **220**, when the SFP modules **210**, **230** and the optical cable **220** are defective, data may not be normally transmitted or received between the electronic apparatus **100** and the display apparatus **300**. Specifically, a part of the image data may

be missing, and when the defect is severe, it may be impossible to transmit or receive image data between the electronic apparatus **100** and the display apparatus **300**.

[0046] Thus, when the display apparatus **300** and the electronic apparatus **100** are connected through the optical cable **220**, it entails a process of checking whether the optical cable **220** and the SFP modules **210**, **230** are defective. However, defects in the SFP modules **210**, **230** and the optical cable **220** may be discovered or may occur during the process of using the display apparatus **300**. In other words, defects in the SFP modules **210**, **230** and the optical cable **220** may not be detected at the time of initially connecting the display apparatus **300** and the electronic apparatus **100** through the optical cable **220**, the SFP modules **210**, **230** and the optical cable **220** were normal, but defects in the SFP modules **210**, **230** and the optical cable **220** may be discovered later or a defect may occur in the SFP modules **210**, **230** and the optical cable **220** that were normal. The above cases are due to various reasons such as high temperature or aging of the optical cable **220** caused by long-term use.

[0047] As a result, when the optical cable **220** or the SFP modules **210**, **230** become defective in the process of using the display apparatus **300**, the SFP modules **210**, **230** and the optical cable **220** must be replaced. Therefore, time and cost are required separately. In particular, in the case of the large display apparatus **300** installed outdoors, the distance between the electronic apparatus **100** and the large display apparatus **300** is often far apart, so the length of the optical cable **220** used to connect the electronic apparatus **100** and the large display apparatus **300** is also very long. Therefore, in the case of the large display apparatus **300**, it is costly and time-consuming to replace the optical cable **220**.

[0048] In order to solve the above-described problem, the electronic apparatus **100** according to an embodiment may proactively identify the possibility of a defect in the SFP modules **210**, **230** including the optical cable **220** before connecting the optical cable **220** between the electronic apparatus **100** and the display apparatus **300**. Here, the possibility of a defect refers to a defect in the optical cable **220** and the SFP module that may occur in the future. In other words, the electronic apparatus **100** predicts whether a defect may occur due to high temperature, long-term use of the optical cable **220**, and the like. Through this, the user may use the optical cable **220** and SFP modules **210**, **230** with higher stability. Hereinafter, an embodiment of the present disclosure in this regard will be described in detail.

[0049] FIG. 2 is a schematic view illustrating the electronic apparatus **100** according to an embodiment.

[0050] The electronic apparatus **100** includes a first interface **110**, a second interface **120**, and one or more processors **130**.

[0051] The first interface **110** is connected to a first small form-factor pluggable (SFP) module **210**. The electronic apparatus **100** is connected to an end of the optical cable **220** through the first SFP module **210**,

[0052] Referring to FIG. 3, the second interface **120** is connected to a second SFP module **230**. The electronic apparatus **100** is connected to the other end of the optical cable **220** through the second SFP module **230**. In other words, as one end of the optical cable **220** is connected to the first interface **110** (more specifically, one end of the optical cable **220** is connected through the first SFP module **210** connected to the first interface **110**) and the other end of the optical cable **220** is connected to the second interface **120** (more specifically, one end of the optical cable **220** is connected through the second SFP module **230** connected to the second interface **120**), the electronic apparatus **100** may form a closed-loop structure by the optical cable **220**.

[0053] The one or more processors **130** control the overall operations and functions of the electronic apparatus **100**. In particular, based on the closed loop structure of the electronic apparatus **100** and the optical cable **220**, the one or more processors **130** may transmit image data through the first interface **110** and receive the transmitted image data back through the second interface **120**.

[0054] Specifically, when the one or more processors **130** transmit a digital signal corresponding to the image data to the first SFP module **210** through the first interface **110**, the first SFP module **210** transmits an optical signal corresponding to the received digital signal to the second SFP module **230** through the optical cable **220**. The second SFP module **230** then converts the received optical signal into a digital signal and transmits the converted digital signal to the electronic apparatus **100** through the second interface **120**. The one or more processors **130** may restore the image data based on the digital signal received from the second SFP module **230** through the second interface **120**.

[0055] The one or more processors **130** may include one or more of a central processing unit (CPU), a graphics processing unit (GPU), an accelerated processing unit (APU), a many integrated core (MIC), a digital signal processor (DSP), a neural processing unit (NPU), a hardware accelerator, or a machine learning accelerator. The one or more processors **130** may control one or any combination of the other components of the electronic apparatus **100**, and may perform communication-related operations or data processing. The one or more processors **130** may execute at least one program or instruction stored in the memory. For example, the one or more processors **130** may perform a method according to an embodiment by executing at least one instruction stored in the memory.

[0056] When a method according to an embodiment includes a plurality of operations, the plurality of operations may be performed by one processor **130** or by a plurality of processors **130**. For example, when a first operation, a second operation, and a third operation are performed by the method according to an embodiment, all of the first operation, the second operation, and the third operation may be performed by the first processor **130**, or the first operation and the second operation may be performed by the first processor (e.g., a general-purpose processor) and the third operation may be performed by the second processor (e.g., an artificial intelligence-dedicated processor).

[0057] The one or more processors **130** may be implemented as a single core processor including a single core, or as one or more multicore processors including a plurality of cores (e.g., homogeneous multicore or heterogeneous multicore). When the one or more processors **130** are implemented as a multicore processor, each of the plurality of cores included in the multicore processor may include internal memory of the processor, such as cache memory and an on-chip memory, and a common cache shared by the plurality of cores may be included in the multicore processor. Each of the plurality of cores (or some of the plurality of cores) included in the multicore processor may independently read and perform program instructions to implement the method according to an embodiment, or all (or some) of the plurality of cores may be coupled to read and perform program instructions to implement the method according to an embodiment.

[0058] When a method according to an embodiment includes a plurality of operations, the plurality of operations may be performed by one core of a plurality of cores included in a multi-core processor, or may be performed by a plurality of cores. For example, when a first operation, a second operation, and a third operation are performed by a method according to an embodiment, all of the first operation, the second operation, and the third operation may be performed by the first core included in the multi-core processor, or the first operation and the second operation may be performed by the first core included in the multi-core processor and the third operation may be performed by the second core included in the multi-core processor.

[0059] In the embodiments of the present disclosure, the one or more processors **130** may mean a system-on-chip (SoC) in which one or more processors and other electronic components are integrated, a single-core processor, a multi-core processor, or a core included in a single-core processor or multi-core processor and here, the core may be implemented as CPU, GPU, APU, MIC, DSP, NPU, hardware accelerator, or machine learning accelerator, and the like, but the core is not limited to the embodiments of the present disclosure.

[0060] Hereinafter, the one or more processors **130** will be referred to as the processor **130** for

convenience of explanation.

[0061] FIG. 4 is an example view illustrating test data according to an embodiment.

[0062] According to an embodiment, the processor **130** changes the level of a voltage of image data to generate test data corresponding to the image data.

[0063] Here, the image data may be data corresponding to a pixel value for each pixel on a pixel array included in the display apparatus **300**. The pixel value may correspond to a voltage applied to the pixel. Specifically, the display apparatus **300** may identify a pixel value corresponding to each pixel based on the image data received from the electronic apparatus **100**, and may generate and provide to each pixel a voltage of the image data corresponding to the identified pixel value.

[0064] In particular, the display apparatus **300** (more specifically, the driver IC included in the display apparatus **300**) may provide a gate signal for driving each pixel based on the image data or a data signal for providing an image data voltage (e.g., a constant current source data voltage or a PWM data voltage) provided to each pixel.

[0065] FIG. 4 illustrates image data provided to the display apparatus **300**. According to an embodiment, when the pixel value for a specific pixel among a plurality of pixels included in the display apparatus **300** is '10', the image data corresponding to the specific pixel may be an analog signal corresponding to binary data corresponding to '10'. More specifically, when the pixel value is from 0 to 16, the binary data corresponding to the pixel value of '10', which is a pixel value corresponding to the specific pixel, is '1010'. In this case, the image data may represent the '1010' in the form of an analog signal.

[0066] In this case, the processor **130** adjusts the voltage level of the image data to generate test data corresponding to the image data. Here, the voltage level of the image data may be the size of the voltage of the image data. In other words, the processor **130** may generate the test data by adjusting the size of the voltage of the image data.

[0067] According to an embodiment, the processor **130** may generate the test data by decreasing the voltage level of the image data to a preset size. However, the present disclosure is not limited thereto, and the processor **130** may also generate the test data by increasing the voltage level of the image data to a preset size. However, hereinafter, for convenience of explanation, it is assumed that the test data is generated by decreasing the voltage level of the image data to a preset size.

[0068] For example, referring back to FIG. 4, the processor **130** may reduce the voltage level of the image data corresponding to the pixel value '10' by 10% to generate test data corresponding to the image data.

[0069] In this case, the voltage level applied to the image data voltage to generate the test data may be set according to the location and environment where the display apparatus **300** is installed. For example, the processor **130** may identify the temperature of the place where the display apparatus **300** is installed, and apply a voltage level corresponding to the identified temperature to the image data voltage. To this end, the memory of the electronic apparatus **100** may store a table including information on voltage levels applied according to temperature.

[0070] Alternatively, the processor **130** may apply different voltage levels depending on the expected usage period of the display apparatus **300**. For example, the processor **130** may generate test data by adjusting the image data voltage to a higher voltage level as the expected usage period of the display apparatus **300** is longer.

[0071] Further, the processor **130** according to an embodiment may generate test data by changing the voltage level of the image data within a preset range. Specifically, the processor **130** may change the voltage level of the image data within a range above a preset threshold voltage.

[0072] According to an embodiment, referring to FIG. 4, when a preset threshold voltage is $V_{sub.th}$, the processor **130** may adjust the voltage of the image data such that the level of the maximum voltage of the image data is equal to or greater than $V_{sub.th}$. Specifically, as the voltage level of the image data corresponding to a '1' among the binary data corresponding to the pixel value changes, when the level of the changed voltage falls below $V_{sub.th}$, the SFP module may

identify the corresponding data as a '0'. Thus, the processor **130** may adjust the voltage level of the image data within a range in which the pixel value of each pixel remains unchanged.

[0073] Meanwhile, according to an embodiment, the processor **130** may change the voltage of the image data based on a pre-emphasis method. Referring to FIG. 5A, the processor **130** may adjust the voltage of the image data corresponding to pixel value '8' according to the pre-emphasis method. Specifically, the processor **130** may adjust the initial voltage level of the voltage corresponding to the binary data '1' among the image data voltage. For example, the processor **130** may decrease the size of the initial voltage level of the voltage corresponding to the binary data '1' of the image data voltage by 10% to generate test data.

[0074] Further, according to an embodiment, the processor **130** may change the voltage of the image data based on a de-emphasis method. Referring to FIG. 5B, the processor **130** may adjust the voltage of the image data corresponding to pixel value '8' according to the de-emphasis method. Specifically, the processor **130** may adjust the terminal voltage level of the voltage corresponding to the binary data '1' among the image data voltage. For example, the processor **130** may reduce the size of the terminal voltage level of the voltage corresponding to the binary data '1' among the image data voltage by 10% to generate test data.

[0075] Meanwhile, according to an embodiment, the processor **130** may simultaneously apply a pre-emphasis method and a de-emphasis method to generate a test voltage. Referring to FIG. 5C, the processor **130** may adjust the initial voltage level and the terminal voltage level of the voltage corresponding to the binary data '1' among the image data voltage. Specifically, the processor **130** may reduce the size of each of the initial voltage level and the size of the late voltage level of the voltage corresponding to the binary data '1' among the image data voltage by 10% to generate test data.

[0076] When the test data transmitted through the first interface **110** is received through the second interface **120**, the processor **130** identifies whether the optical cable **220** is progressively defective based on the received test data and the image data.

[0077] Here, the progressive defect refers to a defect of the optical cable **220** and the SFP modules **210**, **230** that may occur in the future. In other words, the processor **130** may predict in advance a defect of the optical cable **220** and the SFP modules **210**, **230** that may occur in various situations in the future, such as high temperature, long-term use of the SFP modules **210**, **230** and the optical cable **220**, and the like.

[0078] In particular, the level of the image data voltage received by the SFP modules **210**, **230** may change due to high temperature, long-term use of the SFP modules **210**, **230** and the optical cable **220**, and the like. Therefore, the processor **130** may change the level of the image data voltage in advance to generate test data, and use the generated test data to predict a defect of the optical cable **220** and the SFP modules **210**, **230** that may occur in the future.

[0079] Meanwhile, the processor **130** may generate verification data corresponding to the image data based on the image data, and may generate test data based on the generated verification data and the image data in which the level of the voltage is changed. Subsequently, the processor **130** may extract verification data from the received test data, and predict whether the optical cable **220** is defective based on the extracted verification data.

[0080] According to an embodiment, the processor **130** may generate verification data based on a plurality of pixel values included in the image data. For example, the processor **130** may generate verification data by summing a plurality of pixel values, identifying binary data corresponding to the plurality of pixel values, and generating an analog signal corresponding to the identified binary data. Subsequently, the processor **130** may generate test data including the generated verification data (hereinafter, referred to as first verification data) and the image data in which the voltage level adjusted.

[0081] Subsequently, the processor **130** may transmit the generated test data to the first SFP module **210** through the first interface **110** and then receive the test data from the second SFP

module **230** through the second interface **120**. The processor **130** may then extract verification data (hereinafter, referred to as second verification data) included in the received test data from and compare it with the first verification data generated prior to transmission, and when it is identified that the extracted second verification data matches the first verification data, identify that the SFP modules (i.e., the first SFP module **210** and the second SFP module **230**) and the optical cable **220** are normal.

[0082] Alternatively, the processor **130** may store the generated first verification data in the memory of the electronic apparatus **100**, and may adjust the level of the image data voltage to generate the test data. In this case, upon receiving the test data transmitted to the first SFP module **210** through the first interface **110** from the second SFP module **230** through the second interface **120**, the processor **130** may generate the second verification data based on the received test data.

[0083] For example, when generating image data by summing a plurality of pixel values, the processor **130** may identify each pixel value based on the received test data, and generate the second verification data by summing the identified each pixel value. Subsequently, the processor **130** may identify whether the first verification data and the second verification data stored in the memory match, and when it is identified that the first verification data and the second verification data match, identify that the SFP modules (i.e., the first SFP module **210** and the second SFP module **230**) and the optical cable **220** are normal.

[0084] Further, according to an embodiment, the processor **130** may change the level of the driving voltage of the SFP modules **210**, **230**, apply the changed driving voltage to the SFP modules, transmit the test data through the first interface **110**, and receive the test data through the second interface **120** while the changed driving voltage is applied. Based on the received test data, the processor **130** may identify whether the SFP modules (i.e., the first SFP module **210** and the second SFP module **230**) and the optical cable **220** are progressively defective.

[0085] Specifically, when the SFP modules (i.e., the first SFP module **210** and the second SFP module **230**) are connected to each interface, the processor **130** may provide a driving voltage to the SFP modules **210**, **230**. In this case, the first SFP module **210** provided with the driving voltage from the electronic apparatus **100** may receive a digital signal corresponding to the image data from the electronic apparatus **100**, and may generate an optical signal corresponding to the received digital signal (i.e., convert the received digital signal into an optical signal). Subsequently, the first SFP module **210** may transmit the optical signal to the second SFP module **230** through the optical cable **220**. Meanwhile, the second SFP module **230** provided with the driving voltage from the electronic apparatus **100** may receive an optical signal from the first SFP module **210**, convert the received optical signal into a digital signal, and transmit the converted digital signal to the electronic apparatus **100** through the second interface **120**. In other words, the first and second SFP modules **210**, **230** may operate based on the driving voltage provided by the electronic apparatus **100** after being connected to the first and second interfaces **110**, **120** of the electronic apparatus **100**, respectively.

[0086] After generating a test signal, the processor **130** may change the driving voltage level applied to the first SFP module **210** before transmitting the test data to the first SFP module **210** through the first interface **110**. According to an embodiment, the processor **130** may reduce the driving voltage level applied to the first SFP module **210** by 10% before transmitting the test data to the first SFP module **210** through the first interface **110**. In this case, the processor **130** may reduce the driving voltage level applied to the second SFP module **230** by 10%, as it did to the first SFP module **210**. While the driving voltage level with the 10% reduced driving voltage level is being applied to the second SFP module **230**, the processor **130** may receive an optical signal corresponding to the test data transmitted to the first SFP module **210** from the second SFP module **230** through the second interface **120**. Subsequently, based on the received test data, the processor **130** may identify whether the SFP modules (i.e., the first SFP module **210** and the second SFP module **230**) and the optical cable **220** are progressively defective. The method of identifying

whether there is a progressive defect may be equally applicable as described above and thus, will not be described in detail.

[0087] As such, the processor **130** may adjust the level of driving voltage provided to the SFP modules **210**, **230** and then transmit and receive the test data to detect a possible defect in the SFP modules and optical cable **220** in advance. For example, when the voltage efficiency of the SFP module decreases due to long-term use, the driving voltage in the SFP module may decrease even if the same driving voltage is applied to the electronic apparatus **100**. Therefore, the processor **130** may adjust the level of driving voltage provided to the SFP module in advance to identify a defect that may occur in the case of long-term use of the SFP module.

[0088] Meanwhile, according to an embodiment, when the image data transmitted through the first interface **110** is received through the second interface **120**, the processor **130** may identify whether the optical cable **220** is defective based on the image data and, when it is identified that the optical cable **220** is normal, may generate test data.

[0089] Specifically, the processor **130** may identify whether the SFP modules and optical cable **220** are progressively defective based on the test data after identifying whether there is a defect that can be currently discovered in the SFP modules and the optical cable **220**, rather than a progressive defect that may occur in the future. To this end, the processor **130** may transmit the image data to the first SFP module **210** through the first interface **110**, receive the image data from the second SFP module **230** through the second interface **120**, and then identify whether there is a defect based on the received image data.

[0090] In other words, when it is identified that the transmitted image data and the received image data match, the processor **130** may identify that the SFP modules **210**, **230** and the optical cable **220** are normal. Specifically, the processor **130** may transmit data combining digital data corresponding to the image data and digital data generated based on pixel values of a plurality of pixels constituting an image based on the image data (for example, binary data corresponding to the sum of pixel values of the plurality of pixels) to the first SFP module **210** through the first interface **110**, and may receive data transmitted from the second SFP module **230** through the second interface **120** (i.e., data combining digital data corresponding to the image data and digital data generated based on pixel values of a plurality of pixels). In this case, the processor **130** may extract data corresponding to the digital data generated based on the pixel values of the plurality of pixels included in the received data and compare it with verification data included in the transmitted data (i.e., digital data generated based on the pixel values of the plurality of pixels). Subsequently, when the extracted data and the verification data match, the processor **130** may identify that the SFP modules **210**, **230** and the optical cable **220** are normal. On the other hand, when the extracted data and the verification data do not match, the processor **130** may identify that the SFP modules **210**, **230** and the optical cable **220** are defective.

[0091] Subsequently, when it is identified that the SFP modules **210**, **230** and optical cable **220** are normal, the processor **130** may adjust the level of the image data voltage to generate test data.

[0092] Meanwhile, according to an embodiment, the processor **130** may stepwise perform the process of identifying a defect using image data, the process of identifying a defect using test data, and the process of identifying a defect by adjusting a driving voltage level. For example, the processor **130** may first identify whether there is a defect using image data (step 1) and then, when it is identified that the SFP modules **210**, **230** and the optical cable **220** are normal based on the image data, adjust the voltage level of the image data to generate test data, and identify whether there is a defect using the test data (step 2). Subsequently, when it is identified that the SFP modules **210**, **230** and the optical cable **220** are normal based on the test data, the processor **130** may adjust the driving voltage level of the SFP modules **210**, **230** to identify whether there is a defect (step 3). Meanwhile, in the step 2, the processor may first generate a test voltage by reducing the voltage of the image data collectively to identify whether there is a defect (step 2-1), generate a test voltage by reducing the voltage of the image data based on the pre-emphasis method to identify

whether there is a defect (step 2-2), and then generate a test voltage by reducing the voltage of the image data based on the de-emphasis method to identify whether there is a defect (step 2-3).

[0093] FIG. 6 is an example view schematically illustrating a controlling method of an electronic apparatus according to an embodiment.

[0094] When the method of controlling the electronic apparatus **100** is performed by the processor **130** according to an embodiment, the processor **130** first changes the voltage level of the image data to generate test data corresponding to the image data (S610).

[0095] In this case, the processor **130** may change the voltage of the image data based on at least one of a pre-emphasis method and a de-emphasis method.

[0096] In addition, the processor **130** may generate test data by reducing the voltage level of the image data to a preset size.

[0097] Further, the processor **130** may generate test data by changing the voltage of the image data within a preset range.

[0098] Meanwhile, after generating the test data, the processor **130** transmits the test data through the first interface **110** connected to the first small form-factor pluggable (SFP) module included in one end of the optical cable **220** (S620).

[0099] Subsequently, the processor **130** receives the test data through the second interface **120** connected to the second SFP module **230** included in the other end of the optical cable **220** (S630).

[0100] Meanwhile, in step S620, the processor **130** may change the level of the driving voltage of the SFP module to apply the changed voltage to the first and second SFP modules **210**, **230**, and may transmit the test data through the first interface **110**. Subsequently, the processor **130** may receive the test data through the second interface **120** while the driving voltage changed in step S630 is applied to the first and second SFP modules **210**, **230**.

[0101] Meanwhile, the processor **130** identifies whether the optical cable **220** is progressively defective based on the received test data and the image data (S640).

[0102] Specifically, the processor **130** may generate verification data corresponding to the image data based on the image data. In this case, the test data may further include the verification data along with the image data with the changed level. Meanwhile, upon receiving the test data from the second SFP module **230** through the second interface **120**, the processor **130** may identify whether the optical cable **220** is defective based on the pre-generated verification data.

[0103] Meanwhile, prior to step S601, the processor **130** may receive the image data transmitted through the first interface **110** through the second interface **120**, and may identify whether the optical cable **220** is defective based on the image data. Subsequently, when it is identified that the optical cable **220** is normal the processor **130** may generate test data.

[0104] Meanwhile, the methods according to the various embodiments described above may be implemented in the form of an application that can be installed in an existing electronic apparatus. Alternatively, the methods according to the various embodiments described above may be performed using a deep learning-based artificial neural network (or deep artificial neural network), i.e., a learning network model. In addition, the methods according to the various embodiments of the present disclosure described above may be implemented only with a software upgrade or a hardware upgrade for an existing electronic apparatus. Further, the various embodiments of the present disclosure described above may also be performed through an embedded server provided in the electronic apparatus or an external server of the electronic apparatus.

[0105] Meanwhile, according to an embodiment, the above-described various embodiments may be implemented as software including instructions stored in machine-readable storage media, which can be read by machine (e.g.: computer). The machine refers to a apparatus that calls instructions stored in a storage medium, and can operate according to the called instructions, and the apparatus may include a display apparatus (e.g., display apparatus A) according to the aforementioned embodiments. In case an instruction is executed by a processor, the processor may perform a function corresponding to the instruction by itself, or by using other components under its control.

The instruction may include a code that is generated or executed by a compiler or an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Here, the term ‘non-transitory’ means that the storage medium is tangible without including a signal, and does not distinguish whether data are semi-permanently or temporarily stored in the storage medium.

[0106] In addition, according to an embodiment, the above-described methods according to the various embodiments may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a purchaser. The computer program product may be distributed in a form of a storage medium (e.g., a compact disc read only memory (CD-ROM)) that may be read by the machine or online through an application store (e.g., PlayStore™). In case of the online distribution, at least a portion of the computer program product may be at least temporarily stored in a storage medium such as a memory of a server of a manufacturer, a server of an application store, or a relay server or be temporarily generated.

[0107] Further, the components (e.g., modules or programs) according to various embodiments described above may include a single entity or a plurality of entities, and some of the corresponding sub-components described above may be omitted or other sub-components may be further included in the various embodiments. Alternatively or additionally, some components (e.g., modules or programs) may be integrated into one entity and perform the same or similar functions performed by each corresponding component prior to integration. Operations performed by the modules, the programs, or the other components according to the various embodiments may be executed in a sequential manner, a parallel manner, an iterative manner, or a heuristic manner, or at least some of the operations may be performed in a different order or be omitted, or other operations may be added.

[0108] Although example embodiments of the present disclosure have been shown and described above, the disclosure is not limited to the specific embodiments described above, and various modifications may be made by one of ordinary skill in the art without departing from the gist of the disclosure as claimed in the claims, and such modifications are not to be understood in isolation from the technical ideas or prospect of the disclosure.

Claims

1. An electronic apparatus comprising: a first interface configured to be connected to a first small form-factor pluggable (SFP) module provided at an end of an optical cable; a second interface configured to be connected to a second SFP module provided at a second end of the optical cable; memory storing instructions; and one or more processors configured to execute the instructions to: identify a driving voltage corresponding to image data; change a level of the driving voltage of the image data to generate test data; and based on the test data transmitted through the first interface being received by the second interface, identify whether the first SFP module, the second SFP module, and the optical cable are progressively defective based on the received test data and the image data.
2. The apparatus as claimed in claim 1, wherein the one or more processors are further configured to execute the instructions to: generate verification data based on the image data; generate the test data based on the verification data and the changed level of the driving voltage of the image data; and extract the verification data from the received test data, and identify whether the first SFP module, the second SFP module, or the optical cable are progressively defective based on the extracted verification data.
3. The apparatus as claimed in claim 1, wherein the one or more processors are further configured to execute the instructions to change the level of the driving voltage of the image data based on a pre-emphasis method.
4. The apparatus as claimed in claim 1, wherein the one or more processors are further configured

to execute the instructions to change the level of the driving voltage of the image data based on a de-emphasis method.

5. The apparatus as claimed in claim 1, wherein the one or more processors are further configured to: change a level of a driving voltage of the first SFP module and the second SFP module and apply the changed driving voltage to the first SFP module and the second SFP module, transmit the test data through the first interface, and receive the test data through the second interface in a state in which the changed driving voltage is being applied to the first SFP module and the second SFP module.

6. The apparatus as claimed in claim 1, wherein the one or more processors are further configured to: transmit the image data through the first interface; based on the image data transmitted through the first interface being received by the second interface, identify whether the optical cable is defective based on the image data; and based on the optical cable being identified as normal, generate the test data.

7. The apparatus as claimed in claim 1, wherein the one or more processors are further configured to generate the test data by reducing the level of the driving voltage of the image data to a preset voltage level.

8. The apparatus as claimed in claim 1, wherein the one or more processors are further configured to generate the test data by changing the level of the driving voltage of the image data to a voltage level within a preset range.

9. A controlling method of an electronic apparatus, the method comprising: identifying a driving voltage corresponding to image data; generating test data by changing a level of the driving voltage of the image data; transmitting the test data through a first interface connected to a first small form-factor pluggable (SFP) module provided at a first end of an optical cable; receiving the test data through a second interface connected to a second SFP module provided at a second end of the optical cable; and identifying whether the first SFP module, the second SFP module, and the optical cable are progressively defective based on the received test data and the image data.

10. The method as claimed in claim 9, wherein the generating further comprises: generating verification data based on the image data; and generating the test data based on the verification data and the changed level of the driving voltage of the image data, and wherein the identifying whether the first SFP module, the second SFP module, or the optical cable are progressively defective is based on the verification data.

11. The method as claimed in claim 9, wherein the generating further comprises changing the level of the driving voltage of the image data based on a pre-emphasis method.

12. The method as claimed in claim 9, wherein the generating further comprises changing the level of the driving voltage of the image data based on a de-emphasis method.

13. The method as claimed in claim 9, wherein the transmitting comprises: changing a level of a driving voltage of the first SFP module and the second SFP module and applying the changed driving voltage to the first SFP module and the second SFP module, and transmitting the test data through the first interface, and wherein the receiving comprises receiving the test data through the second interface in a state in which the changed driving voltage is being applied to the first SFP module and the second SFP module.

14. The method as claimed in claim 9, further comprising: transmitting the image data through the first interface; receiving the image data transmitted by the first interface through the second interface; and identifying whether the optical cable is defective based on the image data, wherein the generating comprises, based on the optical cable being identified as normal, generating the test data.

15. A non-transitory computer-readable recording medium storing a computer instruction that, when executed by one or more processors of an electronic apparatus, causes the electronic apparatus to: identify driving voltage corresponding to image data; change a level of the driving voltage of the image data to generate test data; transmit the test data through a first interface

connected to a first small form-factor pluggable (SFP) module provided at a first end of an optical cable; receive the test data through a second interface connected to a second SFP module provided at a second end of the optical cable; and identify whether the first SFP module, the second SFP module, and the optical cable are progressively defective based on the received test data and the image data.
